VS79L15 Three-terminal Negative Voltage Regulator

FEATURES

- Maximum output current
  I_{OM}: 0.1A
- Output voltage
  V_o: -15V
- Continuous total dissipation
  P_D:0.6 W (T_a= 25 ℃)

1.OUT
2.GND
3.IN

SOT-89

ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies unless otherwise specified)

Parameter	Symbol	Value	Unit
Input Voltage	V_i	-35	V
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	208.3	℃/W
Operating Junction Temperature Range	T_{OPR}	-40~+125	℃
Storage Temperature Range	T_{STG}	-65~+150	℃

ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JINCTION TEMPERATURE (Vi=-23V, Io=40mA,Ci=0.33μF,Co=0.1μF, unless otherwise specified)

Parameter	Symbol	Test condition	Min	Typ	Max	Unit
Output voltage	Vo	T_J=25℃	-14.55	-15	-15.45	V
		-17.5V≤V_i≤-30V, Io=1mA~40mA	-14.25	-15	-15.75	V
		Io=1mA~70mA	-14.25	-15	-15.75	V
Load Regulation	ΔVo	Io=1mA~100mA, V_i=-23V ,T_J=25℃		25	150	mV
		Io=1mA~40mA, V_i=-23V ,T_J=25℃		15	75	mV
Line regulation	ΔVo	-17.5V≤Vi≤-30V,Io=40mA,T_J=25℃		65	300	mV
		-20V≤Vi≤-30V,Io=40mA ,T_J=25℃		50	250	mV
Quiescent Current	Iq	T_J=25℃			6.5	mA
Quiescent Current Change	ΔIq	-20V≤Vi≤-30V, Io=40mA			1.5	mA
	ΔIq	1mA≤I_O≤40mA			0.1	mA
Output Noise Voltage	V_N	10Hz≤f≤100KHz ,T_J=25℃		90		μV/Vo
Ripple Rejection	RR	-18.5V≤Vi≤-28.5V,f=120Hz	34	39		dB
Dropout Voltage	Vd	T_J=25℃		1.7		V

* Pulse test.

TYPICAL APPLICATION



Note : Bypass capacitors are recommended for optimum stability and transient response and should be located as close as possible to the regulators.

Output Characteristics



Dropout Characteristics



Quiescent Current vs Input Voltage



Current Cut-off Grid Voltage



Output Voltage vs Junction Temperature



Power Derating Curve