

SBD20H200CT、SBDF20H200CT


MAIN CHARACTERISTICS

SCHOTTKY BARRIER RECTIFIER

I_O	20(10×2)A
V_{RRM}	200 V
T_j	175 °C
$V_{F(typ)}$	0.72V (@ $T_j=150^{\circ}C$)

FEATURES

- Low Power Loss,High Efficiency
- Guard Ring Die Construction for Transient Protection
- High Current Capability and Low Forward Voltage Drop






MAXIMUM RATINGS ($T_a=25^{\circ}C$ unless otherwise noted)

Symbol	Parameter	SBD		Unit
		20H200CT	F20H200CT	
V_{RRM}	Peak repetitive reverse voltage	200		V
V_{RWM}	Working peak reverse voltage			
V_R	DC blocking voltage			
$V_{R(RMS)}$	RMS reverse voltage	140		V
I_O	Average rectified output current	20		A
I_{FSM}	Non-Repetitive peak forward surge current (8.3ms half sine wave)	200		A
$R_{\theta Jc}$	Thermal resistance from junction to case , $T_c=25^{\circ}C$	2.0	3.0	$^{\circ}C/W$
$R_{\theta JA}$	Thermal resistance from junction to ambient	75		$^{\circ}C/W$
T_j	Junction temperature	175		$^{\circ}C$
T_{stg}	Storage temperature	-55~+175		$^{\circ}C$

ELECTRICAL CHARACTERISTICS ($T_a=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse voltage	$V_{(BR)}$	$I_R=0.1mA$	200			V
Reverse current	I_R	$V_R=200V$	$T_j=25^{\circ}C$	0.5	1.0	μA
			$T_j=150^{\circ}C$	0.5		mA
Forward voltage	V_F	$I_F=5A$	$T_j=25^{\circ}C$	0.80		V
			$T_j=150^{\circ}C$	0.64		V
		$I_F=10A$	$T_j=25^{\circ}C$	0.86	0.95	V
			$T_j=150^{\circ}C$	0.72		V

*Pulse test: pulse width $\leq 300\mu s$, duty cycles $\leq 2.0\%$.

FIG.1: FORWARD CURRENT DERATING CURVE

FIG.2: TYPICAL FORWARD CHARACTERISTICS

FIG.3: TOTAL CAPACITANCE DERATING CURVE

FIG.4: TYPICAL REVERSE CHARACTERISTICS
