DESCRIPTION:

The BTB16-600B SCR series with the parallel resistor between Gate and Cathode are especially recommended for use on straight hair, igniter, anion generator, etc.



MAIN FEATURES

Symbol	Value	Unit
$I_{T(RMS)}$	16	A
V_{DRM} /V_{RRM}	600/800/1200	V



ABSOLUTE MAXIMUM RATINGS

Parameter		Symbol	Value	Unit
Storage junction temperature range		T_{stg}	-40-150	℃
Operating junction temperature range		T_j	-40-125	℃
Repetitive peak off-state voltage (T_j=25℃)		V_{DRM}	600/800/1200	V
Repetitive peak reverse voltage (T_j=25℃)		V_{RRM}	600/800/1200	V
Non repetitive surge peak Off-state voltage		V_{DSM}	V_{DRM} +100	V
Non repetitive peak reverse voltage		V_{RSM}	V_{RRM} +100	V
RMS on-state current	TO-220A(Ins)/ TO-220F(Ins) (T_C=75℃)	$I_{T(RMS)}$	16	A
	TO-220A(Non-Ins)/ TO-220C (T_C=95℃)			
	TO-262 (T_C=70℃)			
Non repetitive surge peak on-state current (full cycle, F=50Hz)		I_{TSM}	160	A

I^2t value for fusing (tp=10ms)	I^2t	128	A^2s
Critical rate of rise of on-state current (I_G =2×I_{GT})	dI/dt	50	A/μs
Peak gate current	I_{GM}	4	A
Average gate power dissipation	$P_{G(AV)}$	1	W
Peak gate power	P_{GM}	5	W

ELECTRICAL CHARACTERISTICS (T_j=25℃ unless otherwise specified)

3 Quadrants

Symbol	Test Condition	Quadrant		Value				Unit
				BW	CW	SW	TW	
I_{GT}	V_D =12V R_L =33Ω	Ⅰ-Ⅱ-Ⅲ	MAX	50	35	10	5	mA
V_{GT}		Ⅰ-Ⅱ-Ⅲ	MAX	1.3				V
V_{GD}	V_D =V_{DRM} T_j =125℃ R_L =3.3KΩ	Ⅰ-Ⅱ-Ⅲ	MIN	0.2				V
I_L	I_G =1.2I_{GT}	Ⅰ-Ⅲ	MAX	70	50	30	15	mA
		Ⅱ		80	60	40	20	
I_H	I_T =100mA		MAX	60	40	25	15	mA
dV/dt	V_D=2/3V_{DRM} Gate Open T_j =125℃		MIN	1000	500	200	100	V/μs

4 Quadrants

Symbol	Test Condition	Quadrant		Value		Unit
				B	C	
I_{GT}	V_D =12V R_L =33Ω	Ⅰ-Ⅱ-Ⅲ	MAX	50	25	mA
		Ⅳ		70	50	
V_{GT}		ALL	MAX	1.5		V
V_{GD}	V_D =V_{DRM} T_j =125℃ R_L =3.3KΩ	ALL	MIN	0.2		V
I_L	I_G =1.2I_{GT}	Ⅰ-Ⅲ-Ⅳ	MAX	70	50	mA
		Ⅱ		100	80	
I_H	I_T =100mA		MAX	60	40	mA
dV/dt	V_D=2/3V_{DRM} Gate Open T_j=125℃		MIN	500	200	V/μs

STATIC CHARACTERISTICS

Symbol	Parameter		Value(MAX)			Unit
			-600V	-800V	-1200V	
V_{TM}	I_{TM} =22.5A tp=380μs	T_j=25℃	1.5			V
I_{DRM}	V_D =V_{DRM} V_R =V_{RRM}	T_j=25℃	5	5	10	μA
I_{RRM}		T_j=125℃	1	1	2	mA

THERMAL RESISTANCES

Symbol	Parameter		Value	Unit
$R_{th(j-c)}$	junction to case(AC)	TO-220A(Ins)	2.1	℃/W
		TO-220A(Non-Ins)/ TO-220C	1.2	
		TO-220F(Ins)	2.3	
		TO-262	2.5	

FIG.1 Maximum power dissipation versus RMS on-state current



FIG.2: RMS on-state current versus case temperature



FIG.3: Surge peak on-state current versus number of cycles



FIG.4: On-state characteristics (maximum values)



FIG.5: Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp<20ms, and corresponging value of I^2t (dI/dt < 50A/μs)



FIG.6: Relative variations of gate trigger current, holding current and latching current versus junction temperature