Description

Features

- V_{DS}= -50V, I_D= -0.13A
  $R_{DS(ON)}$ <3.6Ω @ V_{GS} = -10V
  $R_{DS(ON)}$ <5.4Ω @ V_{GS} = -4.5V
- Advanced Trench Technology
- Excellent $R_{DS(ON)}$ and Low Gate Charge
- Lead free product is acquired

Application

- PWM Applications
- Load Switch
- Power Management

SOT-23-3



Schematic Diagram

Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
VSM84A-S2	VSM84A	TAPING	SOT-23-3	7inch	3000	180000

Absolute Maximum Ratings (T_A=25℃ unless otherwise specified)

Symbol	Parameter		Max.	Units
V_{DSS}	Drain-Source Voltage		-50	V
V_{GSS}	Gate-Source Voltage		±20	V
I_D	Continuous Drain Current	T_A = 25℃	-0.13	A
		T_A = 100℃	-0.08	A
I_{DM}	Pulsed Drain Current note1		-0.52	A
P_D	Power Dissipation	T_A = 25℃	0.225	W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		556	℃/W
T_J, T_{STG}	Operating and Storage Temperature Range		-55 to +150	℃

Electrical Characteristics (T_J=25℃ unless otherwise specified)

Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	V_{GS}=0V, I_D= -250μA	-50	-	-	V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}= -50V, V_{GS}=0V,	-	-	-1	μA
I_{GSS}	Gate to Body Leakage Current	V_{DS}=0V, V_{GS}= ±20V	-	-	±100	nA
On Characteristics						
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}= V_{GS}, I_D= -250μA	-0.8	-1.5	-2.5	V
$R_{DS(on)}$	Static Drain-Source on-Resistance note2	V_{GS}= -10V, I_D= -0.13A	-	2.2	3.6	Ω
		V_{GS}= -4.5V, I_D= -0.1A	-	2.6	5.4	
Dynamic Characteristics						
C_{iss}	Input Capacitance	V_{DS}= -25V, V_{GS}=0V, f=1.0MHz	-	30	-	pF
C_{oss}	Output Capacitance		-	10	-	pF
C_{rss}	Reverse Transfer Capacitance		-	5	-	pF
Q_g	Total Gate Charge	V_{DS}= -25V, I_D= -0.13A, V_{GS}= -10V	-	4.5	-	nC
Q_{gs}	Gate-Source Charge		-	0.8	-	nC
Q_{gd}	Gate-Drain(“Miller”) Charge		-	1.2	-	nC
Switching Characteristics						
$t_{d(on)}$	Turn-on Delay Time	V_{DD}= -25V, I_D= -0.1A, V_{GS}= -10V, R_{GEN}=2.5Ω	-	2.5	-	ns
t_r	Turn-on Rise Time		-	1	-	ns
$t_{d(off)}$	Turn-off Delay Time		-	16	-	ns
t_f	Turn-off Fall Time		-	8	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I_S	Maximum Continuous Drain to Source Diode Forward Current		-	-	-0.13	A
I_{SM}	Maximum Pulsed Drain to Source Diode Forward Current		-	-	-0.52	A
V_{SD}	Drain to Source Diode Forward Voltage	V_{GS}=0V, I_S= -0.13A	-	-0.8	-1.2	V

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature

2. Pulse Test: Pulse Width≤300μs, Duty Cycle≤2%

Typical Performance Characteristics

Figure1: Output Characteristics



Figure 2: Typical Transfer Characteristics



Figure 3: On-resistance vs. Drain Current



Figure 4: Body Diode Characteristics



Figure 5: Gate Charge Characteristics



Figure 6: Capacitance Characteristics



Figure 7: Normalized Breakdown Voltage vs. Junction Temperature



Figure 8: Normalized on Resistance vs. Junction Temperature



Figure 9: Maximum Safe Operating Area



Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature



Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient



Test Circuit

Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms