



## Description

<b>Features</b> <ul style="list-style-type: none"> <li>● 30V, 15A</li> <li>● <math>R_{DS(ON)} &lt; 8m\Omega</math> @ <math>V_{GS} = 10V</math></li> <li>● <math>R_{DS(ON)} &lt; 14m\Omega</math> @ <math>V_{GS} = 4.5V</math></li> <li>● Advanced Trench Technology</li> <li>● Provide Excellent <math>R_{DS(ON)}</math> and Low Gate Charge</li> <li>● Lead free product is acquired</li> </ul>	<b>Application</b> <ul style="list-style-type: none"> <li>● Load Switch</li> <li>● PWM Application</li> <li>● Power management</li> </ul> <p>100% UIS 100% <math>\Delta V_d</math>s</p>
 <p>SOP-8</p>	 <p>Schematic Diagram</p>

## Package Marking and Ordering Information

Device Marking	Device	OUTLINE	Device Package	Reel Size	Reel (PCS)	Per Carton (PCS)
VSM15N03-S8	VSM15N03	TAPING	SOP-8	13inch	4000	48000

## Absolute Maximum Ratings (T<sub>A</sub>=25°C unless otherwise specified)

Symbol	Parameter	Max.	Units
V <sub>DSS</sub>	Drain-Source Voltage	30	V
V <sub>GSS</sub>	Gate-Source Voltage	±20	V
I <sub>D</sub>	Continuous Drain Current	T <sub>A</sub> = 25°C 15 T <sub>A</sub> = 100°C 10	A A
I <sub>DM</sub>	Pulsed Drain Current <sup>note1</sup>	60	A
E <sub>AS</sub>	Single Pulsed Avalanche Energy <sup>note2</sup>	39	mJ
P <sub>D</sub>	Power Dissipation	T <sub>A</sub> = 25°C 3	W
R <sub>θJA</sub>	Thermal Resistance, Junction to Ambient	41	°C/W
T <sub>J</sub> , T <sub>STG</sub>	Operating and Storage Temperature Range	-55 to +150	°C

**Electrical Characteristics** ( $T_J=25^{\circ}\text{C}$  unless otherwise specified)







Symbol	Parameter	Test Condition	Min.	Typ.	Max.	Units
Off Characteristic						
V <sub>(BR)DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	30	-	-	V
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>DS</sub> =30V, V <sub>GS</sub> =0V,	-	-	1.0	μA
I <sub>GSS</sub>	Gate to Body Leakage Current	V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V	-	-	±100	nA
On Characteristics						
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA	1.0	1.5	2.5	V
R <sub>DS(on)</sub>	Static Drain-Source on-Resistance <small>note3</small>	V <sub>GS</sub> =10V, I <sub>D</sub> =15A	-	6.2	8	mΩ
		V <sub>GS</sub> =4.5V, I <sub>D</sub> =10A	-	10	14	
Dynamic Characteristics						
C <sub>iss</sub>	Input Capacitance	V <sub>DS</sub> =15V, V <sub>GS</sub> =0V, f=1.0MHz	-	1116	-	pF
C <sub>oss</sub>	Output Capacitance		-	187	-	pF
C <sub>rss</sub>	Reverse Transfer Capacitance		-	152	-	pF
Q <sub>g</sub>	Total Gate Charge	V <sub>DS</sub> =15V, I <sub>D</sub> =8A, V <sub>GS</sub> =10V	-	13.3	-	nC
Q <sub>gs</sub>	Gate-Source Charge		-	3.1	-	nC
Q <sub>gd</sub>	Gate-Drain(“Miller”) Charge		-	5	-	nC
Switching Characteristics						
t <sub>d(on)</sub>	Turn-on Delay Time	V <sub>DS</sub> =15V, I <sub>D</sub> =15A, R <sub>GEN</sub> =3Ω, V <sub>GS</sub> =10V	-	15	-	ns
t <sub>r</sub>	Turn-on Rise Time		-	19	-	ns
t <sub>d(off)</sub>	Turn-off Delay Time		-	35	-	ns
t <sub>f</sub>	Turn-off Fall Time		-	21	-	ns
Drain-Source Diode Characteristics and Maximum Ratings						
I <sub>S</sub>	Maximum Continuous Drain to Source Diode Forward Current		-	-	15	A
I <sub>SM</sub>	Maximum Pulsed Drain to Source Diode Forward Current		-	-	60	A
V <sub>SD</sub>	Drain to Source Diode Forward Voltage	V <sub>GS</sub> =0V, I <sub>S</sub> =15A	-	-	1.2	V
t <sub>rr</sub>	Body Diode Reverse Recovery Time	I <sub>F</sub> =15A, dI/dt=100A/μs	-	14	-	ns
Q <sub>rr</sub>	Body Diode Reverse Recovery Charge		-	4.1	-	nC

Notes:1. Repetitive Rating: Pulse Width Limited by Maximum Junction Temperature


2. EAS condition:  $T_J=25^{\circ}\text{C}$ ,  $V_{GS}=15V$ ,  $R_G=25\Omega$ ,  $L=0.5mH$ ,  $I_{AS}=12.6A$ 

3. Pulse Test: Pulse Width $\leq 300\mu s$ , Duty Cycle $\leq 0.5\%$


## Typical Performance Characteristics

**Figure1: Output Characteristics**

**Figure 2: Typical Transfer Characteristics**

**Figure 3: On-resistance vs. Drain Current**

**Figure 4: Body Diode Characteristics**

**Figure 5: Gate Charge Characteristics**

**Figure 6: Capacitance Characteristics**



**Figure 7: Normalized Breakdown Voltage vs. Junction Temperature**




**Figure 8: Normalized on Resistance vs. Junction Temperature**




**Figure 9: Maximum Safe Operating Area**



**Figure 10: Maximum Continuous Drain Current vs. Ambient Temperature**



**Figure.11: Maximum Effective Transient Thermal Impedance, Junction-to-Ambient**



## Test Circuit




Figure1:Gate Charge Test Circuit & Waveform




Figure 2: Resistive Switching Test Circuit & Waveforms




Figure 3:Unclamped Inductive Switching Test Circuit & Waveforms