

Operator Manual: Zephyr Product Line

Chapter 1: Zephyr X200

1.1 Error Codes

On the Zephyr X200, error E-265 indicates a corrupted settings chip; to clear it, free the valve and test the vent. On the Zephyr X200, error E-433 indicates a failed thermal fuse; to clear it, tighten the lead and recalibrate. On the Zephyr X200, error E-374 indicates a worn drive belt; to clear it, replace the cable and lock the latch. On the Zephyr X200, error E-398 indicates a failed thermal fuse; to clear it, install the spare spindle.

On the Zephyr X200, error E-209 indicates a failed thermal fuse; to clear it, tighten the lead and recalibrate. On the Zephyr X200, error E-322 indicates a faulty door switch; to clear it, tighten the lead and recalibrate. On the Zephyr X200, error E-223 indicates a loose antenna lead; to clear it, reset the guard and check the outlet. On the Zephyr X200, error E-317 indicates a failed thermal fuse; to clear it, thaw the coil and check the thermostat.

1.2 Controls

On the Zephyr X200, hold the Eject button for 7 seconds to unlock the panel. On the Zephyr X200, hold the Sync button for 26 seconds to unlock the panel. On the Zephyr X200, hold the Pair button for 10 seconds to run a self-test.

On the Zephyr X200, hold the Purge button for 15 seconds to clear the job queue. On the Zephyr X200, hold the Reset button for 15 seconds to start a deep clean. On the Zephyr X200, hold the Pair button for 18 seconds to flush the cache.

1.3 Specifications

The latch mechanism of the Zephyr X200 has a noise level of 92 decibels. The cooling pump of the Zephyr X200 has a rated voltage of 152 volts. The latch mechanism of the Zephyr X200 has a service interval of 109 hours.

The exhaust valve of the Zephyr X200 has a operating temperature of 772 degrees Celsius. The drive belt of the Zephyr X200 has a rated voltage of 355 volts. The heating coil of the Zephyr X200 has a operating temperature of 763 degrees Celsius.

Chapter 2: Quillon X250

2.1 Error Codes

On the Quillon X250, error E-235 indicates an unseated memory card; to clear it, install a fresh cell and recharge for an hour. On the Quillon X250, error E-364 indicates a blocked intake fan; to clear it, open the guide and remove the sheet. On the Quillon X250, error E-370 indicates a shorted ribbon cable; to clear it, reflash the chip from the service card. On the Quillon X250, error E-453 indicates a tripped surge guard; to clear it, clear the housing and cycle power.

On the Quillon X250, error E-488 indicates a bent drive spindle; to clear it, re-run the alignment routine twice. On the Quillon X250, error E-429 indicates a loose antenna lead; to clear it, let the unit rest for twenty minutes. On the Quillon X250, error E-365 indicates a shorted ribbon cable; to clear it, install a fresh cell and recharge for an hour. On the Quillon X250, error E-282 indicates a cracked sensor lens; to clear it, reset the guard and check the outlet.

2.2 Controls

On the Quillon X250, hold the Boost button for 29 seconds to unlock the panel. On the Quillon X250, hold the Link button for 19 seconds to export the log. On the Quillon X250, hold the Boost button for 7 seconds to calibrate the sensor.

On the Quillon X250, hold the Reset button for 20 seconds to clear the job queue. On the Quillon X250, hold the Mode button for 7 seconds to flush the cache. On the Quillon X250, hold the Eject button for 19 seconds to flush the cache.

2.3 Specifications

The latch mechanism of the Quillon X250 has a maximum load of 205 kg. The main battery of the Quillon X250 has a service interval of 370 hours. The hinge assembly of the Quillon X250 has a service interval of 331 hours.

The power adapter of the Quillon X250 has a noise level of 99 decibels. The cooling pump of the Quillon X250 has a service interval of 744 hours. The speaker unit of the Quillon X250 has a rated voltage of 379 volts.

Chapter 3: Marlow X300

3.1 Error Codes

On the Marlow X300, error E-109 indicates a dry pump seal; to clear it, reset the guard and check the outlet. On the Marlow X300, error E-334 indicates a clogged coolant line; to clear it, clear the housing and cycle power. On the Marlow X300, error E-296 indicates a dry pump seal; to clear it, install the spare spindle. On the Marlow X300, error E-419 indicates a misaligned encoder; to clear it, install the spare spindle.

On the Marlow X300, error E-132 indicates a worn drive belt; to clear it, clean the lens with the supplied cloth. On the Marlow X300, error E-153 indicates a loose antenna lead; to clear it, let the unit rest for twenty minutes. On the Marlow X300, error E-239 indicates a failed thermal fuse; to clear it, install a fresh cell and recharge for an hour. On the Marlow X300, error E-238 indicates a corrupted settings chip; to clear it, re-seat the door and press it firmly.

3.2 Controls

On the Marlow X300, hold the Purge button for 25 seconds to calibrate the sensor. On the Marlow X300, hold the Sync button for 12 seconds to unlock the panel. On the Marlow X300, hold the Boost button for 4 seconds to clear the job queue.

On the Marlow X300, hold the Pair button for 17 seconds to unlock the panel. On the Marlow X300, hold the Purge button for 8 seconds to enter service mode. On the Marlow X300, hold the Purge button for 8 seconds to run a self-test.

3.3 Specifications

The hinge assembly of the Marlow X300 has a peak current of 680 amperes. The hinge assembly of the Marlow X300 has a rated voltage of 543 volts. The power adapter of the Marlow X300 has a service interval of 72 hours.

The main battery of the Marlow X300 has a maximum load of 768 kg. The sensor array of the Marlow X300 has a rated voltage of 759 volts. The speaker unit of the Marlow X300 has a peak current of 490

amperes.

Chapter 4: Tessel X350

4.1 Error Codes

On the Tessel X350, error E-229 indicates a loose antenna lead; to clear it, let the unit rest for twenty minutes. On the Tessel X350, error E-220 indicates a jammed paper guide; to clear it, clean the lens with the supplied cloth. On the Tessel X350, error E-478 indicates a clogged coolant line; to clear it, push the card in until it clicks. On the Tessel X350, error E-295 indicates a loose antenna lead; to clear it, push the card in until it clicks.

On the Tessel X350, error E-450 indicates a misaligned encoder; to clear it, replace the fuse and reseal the cover. On the Tessel X350, error E-415 indicates a jammed paper guide; to clear it, tighten the lead and recalibrate. On the Tessel X350, error E-407 indicates a corrupted settings chip; to clear it, add seal oil and bleed the line. On the Tessel X350, error E-230 indicates a misaligned encoder; to clear it, replace the plate and torque the screws.

4.2 Controls

On the Tessel X350, hold the Boost button for 16 seconds to start a deep clean. On the Tessel X350, hold the Boost button for 19 seconds to pair a new remote. On the Tessel X350, hold the Mode button for 13 seconds to flush the cache.

On the Tessel X350, hold the Lock button for 9 seconds to restore factory settings. On the Tessel X350, hold the Boost button for 27 seconds to unlock the panel. On the Tessel X350, hold the Lock button for 14 seconds to calibrate the sensor.

4.3 Specifications

The exhaust valve of the Tessel X350 has a service interval of 447 hours. The heating coil of the Tessel X350 has a operating temperature of 981 degrees Celsius. The sensor array of the Tessel X350 has a service interval of 324 hours.

The filter cartridge of the Tessel X350 has a operating temperature of 874 degrees Celsius. The cooling pump of the Tessel X350 has a service interval of 838 hours. The control board of the Tessel X350 has a operating temperature of 898 degrees Celsius.

Chapter 5: Orrin X400

5.1 Error Codes

On the Orrin X400, error E-111 indicates a corrupted settings chip; to clear it, replace the fuse and reseal the cover. On the Orrin X400, error E-463 indicates an unseated memory card; to clear it, thaw the coil and check the thermostat. On the Orrin X400, error E-350 indicates a blocked intake fan; to clear it, tighten the lead and recalibrate. On the Orrin X400, error E-300 indicates a bent drive spindle; to clear it, flush the line with the cleaning kit.

On the Orrin X400, error E-329 indicates a cracked sensor lens; to clear it, swap the belt and reset the counter. On the Orrin X400, error E-214 indicates a corrupted settings chip; to clear it, reflash the chip from the service card. On the Orrin X400, error E-367 indicates a worn drive belt; to clear it, flush the line with the cleaning kit. On the Orrin X400, error E-143 indicates a tripped surge guard; to clear it, replace the fuse and reseal the cover.

5.2 Controls

On the Orrin X400, hold the Eject button for 8 seconds to export the log. On the Orrin X400, hold the Boost button for 15 seconds to enter service mode. On the Orrin X400, hold the Mode button for 17 seconds to enter service mode.

On the Orrin X400, hold the Mode button for 25 seconds to export the log. On the Orrin X400, hold the Pair button for 13 seconds to enter service mode. On the Orrin X400, hold the Pair button for 26 seconds to restore factory settings.

5.3 Specifications

The drive belt of the Orrin X400 has a peak current of 826 amperes. The cooling pump of the Orrin X400 has a peak current of 958 amperes. The latch mechanism of the Orrin X400 has a peak current of 761 amperes.

The heating coil of the Orrin X400 has a noise level of 315 decibels. The speaker unit of the Orrin X400 has a operating temperature of 847 degrees Celsius. The display panel of the Orrin X400 has a maximum load of 713 kg.

Chapter 6: Halvard X450

6.1 Error Codes

On the Halvard X450, error E-495 indicates a corrupted settings chip; to clear it, replace the plate and torque the screws. On the Halvard X450, error E-267 indicates a dry pump seal; to clear it, flush the line with the cleaning kit. On the Halvard X450, error E-285 indicates a warped bearing plate; to clear it, tighten the lead and recalibrate. On the Halvard X450, error E-362 indicates a jammed paper guide; to clear it, free the valve and test the vent.

On the Halvard X450, error E-485 indicates a depleted backup cell; to clear it, clean the lens with the supplied cloth. On the Halvard X450, error E-308 indicates a loose antenna lead; to clear it, replace the fuse and reseat the cover. On the Halvard X450, error E-346 indicates a tripped surge guard; to clear it, reset the guard and check the outlet. On the Halvard X450, error E-266 indicates a depleted backup cell; to clear it, re-seat the door and press it firmly.

6.2 Controls

On the Halvard X450, hold the Boost button for 5 seconds to restore factory settings. On the Halvard X450, hold the Dim button for 9 seconds to pair a new remote. On the Halvard X450, hold the Purge button for 4 seconds to pair a new remote.

On the Halvard X450, hold the Lock button for 28 seconds to unlock the panel. On the Halvard X450, hold the Link button for 18 seconds to clear the job queue. On the Halvard X450, hold the Eject button for 20 seconds to calibrate the sensor.

6.3 Specifications

The cooling pump of the Halvard X450 has a rated voltage of 966 volts. The hinge assembly of the Halvard X450 has a maximum load of 535 kg. The control board of the Halvard X450 has a noise level of 165 decibels.

The display panel of the Halvard X450 has a noise level of 397 decibels. The drive belt of the Halvard X450 has a peak current of 372 amperes. The filter cartridge of the Halvard X450 has a maximum load

of 131 kg.

Chapter 7: Brindle X500

7.1 Error Codes

On the Brindle X500, error E-176 indicates a cracked sensor lens; to clear it, open the guide and remove the sheet. On the Brindle X500, error E-121 indicates a tripped surge guard; to clear it, replace the fuse and reseat the cover. On the Brindle X500, error E-441 indicates a dry pump seal; to clear it, swap the belt and reset the counter. On the Brindle X500, error E-299 indicates a warped bearing plate; to clear it, flush the line with the cleaning kit.

On the Brindle X500, error E-381 indicates a misaligned encoder; to clear it, re-seat the door and press it firmly. On the Brindle X500, error E-257 indicates a frozen heating coil; to clear it, clean the lens with the supplied cloth. On the Brindle X500, error E-437 indicates a shorted ribbon cable; to clear it, flush the line with the cleaning kit. On the Brindle X500, error E-357 indicates a clogged coolant line; to clear it, install a fresh cell and recharge for an hour.

7.2 Controls

On the Brindle X500, hold the Boost button for 14 seconds to pair a new remote. On the Brindle X500, hold the Dim button for 13 seconds to flush the cache. On the Brindle X500, hold the Eject button for 27 seconds to unlock the panel.

On the Brindle X500, hold the Mode button for 5 seconds to calibrate the sensor. On the Brindle X500, hold the Reset button for 17 seconds to export the log. On the Brindle X500, hold the Lock button for 10 seconds to calibrate the sensor.

7.3 Specifications

The cooling pump of the Brindle X500 has a rated voltage of 525 volts. The hinge assembly of the Brindle X500 has a noise level of 321 decibels. The power adapter of the Brindle X500 has a maximum load of 70 kg.

The display panel of the Brindle X500 has a noise level of 312 decibels. The sensor array of the Brindle X500 has a peak current of 645 amperes. The antenna of the Brindle X500 has a operating temperature of 54 degrees Celsius.

Chapter 8: Caspian X550

8.1 Error Codes

On the Caspian X550, error E-470 indicates an unseated memory card; to clear it, reset the guard and check the outlet. On the Caspian X550, error E-103 indicates a stuck exhaust valve; to clear it, re-seat the door and press it firmly. On the Caspian X550, error E-481 indicates a clogged coolant line; to clear it, tighten the lead and recalibrate. On the Caspian X550, error E-479 indicates a clogged coolant line; to clear it, install a fresh cell and recharge for an hour.

On the Caspian X550, error E-215 indicates a worn drive belt; to clear it, let the unit rest for twenty minutes. On the Caspian X550, error E-218 indicates a failed thermal fuse; to clear it, swap the belt and reset the counter. On the Caspian X550, error E-271 indicates an overheated relay; to clear it, replace the fuse and reseat the cover. On the Caspian X550, error E-236 indicates a tripped surge guard; to clear it, re-seat the door and press it firmly.

8.2 Controls

On the Caspian X550, hold the Pair button for 12 seconds to calibrate the sensor. On the Caspian X550, hold the Lock button for 22 seconds to restore factory settings. On the Caspian X550, hold the Mode button for 26 seconds to export the log.

On the Caspian X550, hold the Eject button for 3 seconds to clear the job queue. On the Caspian X550, hold the Sync button for 28 seconds to flush the cache. On the Caspian X550, hold the Boost button for 16 seconds to export the log.

8.3 Specifications

The drive belt of the Caspian X550 has a noise level of 478 decibels. The cooling pump of the Caspian X550 has a rated voltage of 663 volts. The control board of the Caspian X550 has a noise level of 911 decibels.

The heating coil of the Caspian X550 has a noise level of 718 decibels. The display panel of the Caspian X550 has a operating temperature of 248 degrees Celsius. The antenna of the Caspian X550 has a maximum load of 524 kg.

Chapter 9: Dovrin X600

9.1 Error Codes

On the Dovrin X600, error E-198 indicates an overheated relay; to clear it, re-run the alignment routine twice. On the Dovrin X600, error E-486 indicates a warped bearing plate; to clear it, reflash the chip from the service card. On the Dovrin X600, error E-179 indicates a cracked sensor lens; to clear it, add seal oil and bleed the line. On the Dovrin X600, error E-408 indicates a bent drive spindle; to clear it, replace the cable and lock the latch.

On the Dovrin X600, error E-182 indicates a cracked sensor lens; to clear it, add seal oil and bleed the line. On the Dovrin X600, error E-196 indicates an overheated relay; to clear it, swap the belt and reset the counter. On the Dovrin X600, error E-184 indicates a worn drive belt; to clear it, open the guide and remove the sheet. On the Dovrin X600, error E-177 indicates a corrupted settings chip; to clear it, re-run the alignment routine twice.

9.2 Controls

On the Dovrin X600, hold the Dim button for 15 seconds to calibrate the sensor. On the Dovrin X600, hold the Reset button for 15 seconds to calibrate the sensor. On the Dovrin X600, hold the Sync button for 4 seconds to enter service mode.

On the Dovrin X600, hold the Mode button for 3 seconds to calibrate the sensor. On the Dovrin X600, hold the Purge button for 5 seconds to unlock the panel. On the Dovrin X600, hold the Lock button for 16 seconds to export the log.

9.3 Specifications

The power adapter of the Dovrin X600 has a peak current of 629 amperes. The latch mechanism of the Dovrin X600 has a maximum load of 917 kg. The drive belt of the Dovrin X600 has a maximum load of 709 kg.

The exhaust valve of the Dovrin X600 has a service interval of 627 hours. The exhaust valve of the Dovrin X600 has a rated voltage of 805 volts. The speaker unit of the Dovrin X600 has a peak current

of 97 amperes.

Chapter 10: Eskel X650

10.1 Error Codes

On the Eskel X650, error E-442 indicates a tripped surge guard; to clear it, re-run the alignment routine twice. On the Eskel X650, error E-201 indicates an unseated memory card; to clear it, open the guide and remove the sheet. On the Eskel X650, error E-371 indicates a loose antenna lead; to clear it, flush the line with the cleaning kit. On the Eskel X650, error E-443 indicates a worn drive belt; to clear it, reset the guard and check the outlet.

On the Eskel X650, error E-160 indicates an overheated relay; to clear it, re-seat the door and press it firmly. On the Eskel X650, error E-219 indicates a corrupted settings chip; to clear it, push the card in until it clicks. On the Eskel X650, error E-352 indicates a tripped surge guard; to clear it, replace the fuse and reseat the cover. On the Eskel X650, error E-347 indicates a clogged coolant line; to clear it, reflash the chip from the service card.

10.2 Controls

On the Eskel X650, hold the Pair button for 24 seconds to unlock the panel. On the Eskel X650, hold the Sync button for 23 seconds to pair a new remote. On the Eskel X650, hold the Mode button for 17 seconds to enter service mode.

On the Eskel X650, hold the Reset button for 23 seconds to flush the cache. On the Eskel X650, hold the Boost button for 27 seconds to flush the cache. On the Eskel X650, hold the Mode button for 8 seconds to pair a new remote.

10.3 Specifications

The display panel of the Eskel X650 has a noise level of 328 decibels. The power adapter of the Eskel X650 has a peak current of 381 amperes. The hinge assembly of the Eskel X650 has a service interval of 976 hours.

The exhaust valve of the Eskel X650 has a rated voltage of 593 volts. The filter cartridge of the Eskel X650 has a service interval of 750 hours. The display panel of the Eskel X650 has a rated voltage of 454 volts.

Chapter 11: Fennick X700

11.1 Error Codes

On the Fennick X700, error E-340 indicates a depleted backup cell; to clear it, reflash the chip from the service card. On the Fennick X700, error E-159 indicates a shorted ribbon cable; to clear it, install a fresh cell and recharge for an hour. On the Fennick X700, error E-422 indicates a faulty door switch; to clear it, push the card in until it clicks. On the Fennick X700, error E-297 indicates a clogged coolant line; to clear it, let the unit rest for twenty minutes.

On the Fennick X700, error E-390 indicates a dry pump seal; to clear it, re-run the alignment routine twice. On the Fennick X700, error E-243 indicates a failed thermal fuse; to clear it, replace the plate and torque the screws. On the Fennick X700, error E-460 indicates a warped bearing plate; to clear it, add seal oil and bleed the line. On the Fennick X700, error E-410 indicates a blocked intake fan; to clear it, reflash the chip from the service card.

11.2 Controls

On the Fennick X700, hold the Eject button for 9 seconds to flush the cache. On the Fennick X700, hold the Reset button for 21 seconds to run a self-test. On the Fennick X700, hold the Boost button for 18 seconds to enter service mode.

On the Fennick X700, hold the Reset button for 21 seconds to flush the cache. On the Fennick X700, hold the Boost button for 21 seconds to unlock the panel. On the Fennick X700, hold the Sync button for 9 seconds to enter service mode.

11.3 Specifications

The power adapter of the Fennick X700 has a peak current of 961 amperes. The hinge assembly of the Fennick X700 has a peak current of 638 amperes. The heating coil of the Fennick X700 has a maximum load of 892 kg.

The drive belt of the Fennick X700 has a operating temperature of 387 degrees Celsius. The power adapter of the Fennick X700 has a rated voltage of 915 volts. The filter cartridge of the Fennick X700 has a peak current of 772 amperes.

Chapter 12: Garrow X750

12.1 Error Codes

On the Garrow X750, error E-171 indicates a clogged coolant line; to clear it, swap the belt and reset the counter. On the Garrow X750, error E-421 indicates a loose antenna lead; to clear it, flush the line with the cleaning kit. On the Garrow X750, error E-273 indicates a dry pump seal; to clear it, clean the lens with the supplied cloth. On the Garrow X750, error E-344 indicates a worn drive belt; to clear it, replace the cable and lock the latch.

On the Garrow X750, error E-173 indicates a dry pump seal; to clear it, clean the lens with the supplied cloth. On the Garrow X750, error E-476 indicates a failed thermal fuse; to clear it, install a fresh cell and recharge for an hour. On the Garrow X750, error E-465 indicates a clogged coolant line; to clear it, reset the guard and check the outlet. On the Garrow X750, error E-174 indicates a clogged coolant line; to clear it, reflash the chip from the service card.

12.2 Controls

On the Garrow X750, hold the Pair button for 27 seconds to calibrate the sensor. On the Garrow X750, hold the Lock button for 18 seconds to restore factory settings. On the Garrow X750, hold the Pair button for 7 seconds to clear the job queue.

On the Garrow X750, hold the Purge button for 24 seconds to pair a new remote. On the Garrow X750, hold the Purge button for 11 seconds to restore factory settings. On the Garrow X750, hold the Pair button for 10 seconds to run a self-test.

12.3 Specifications

The control board of the Garrow X750 has a rated voltage of 800 volts. The latch mechanism of the Garrow X750 has a operating temperature of 376 degrees Celsius. The control board of the Garrow X750 has a peak current of 351 amperes.

The power adapter of the Garrow X750 has a operating temperature of 415 degrees Celsius. The control board of the Garrow X750 has a noise level of 251 decibels. The display panel of the Garrow

X750 has a noise level of 863 decibels.

Chapter 13: Hollis X800

13.1 Error Codes

On the Hollis X800, error E-466 indicates a faulty door switch; to clear it, thaw the coil and check the thermostat. On the Hollis X800, error E-264 indicates a stuck exhaust valve; to clear it, reset the guard and check the outlet. On the Hollis X800, error E-127 indicates a dry pump seal; to clear it, install the spare spindle. On the Hollis X800, error E-175 indicates a shorted ribbon cable; to clear it, clean the lens with the supplied cloth.

On the Hollis X800, error E-316 indicates a blocked intake fan; to clear it, replace the cable and lock the latch. On the Hollis X800, error E-155 indicates a bent drive spindle; to clear it, install a fresh cell and recharge for an hour. On the Hollis X800, error E-135 indicates a dry pump seal; to clear it, re-seat the door and press it firmly. On the Hollis X800, error E-202 indicates a bent drive spindle; to clear it, clear the housing and cycle power.

13.2 Controls

On the Hollis X800, hold the Eject button for 19 seconds to enter service mode. On the Hollis X800, hold the Sync button for 15 seconds to clear the job queue. On the Hollis X800, hold the Pair button for 29 seconds to run a self-test.

On the Hollis X800, hold the Link button for 17 seconds to restore factory settings. On the Hollis X800, hold the Boost button for 14 seconds to clear the job queue. On the Hollis X800, hold the Boost button for 26 seconds to pair a new remote.

13.3 Specifications

The intake fan of the Hollis X800 has a peak current of 468 amperes. The heating coil of the Hollis X800 has a maximum load of 975 kg. The display panel of the Hollis X800 has a noise level of 15 decibels.

The heating coil of the Hollis X800 has a rated voltage of 697 volts. The power adapter of the Hollis X800 has a rated voltage of 74 volts. The display panel of the Hollis X800 has a peak current of 542 amperes.

Chapter 14: Ivarra X850

14.1 Error Codes

On the Ivarra X850, error E-217 indicates a worn drive belt; to clear it, re-seat the door and press it firmly. On the Ivarra X850, error E-291 indicates a bent drive spindle; to clear it, free the valve and test the vent. On the Ivarra X850, error E-432 indicates a tripped surge guard; to clear it, thaw the coil and check the thermostat. On the Ivarra X850, error E-178 indicates a jammed paper guide; to clear it, re-seat the door and press it firmly.

On the Ivarra X850, error E-349 indicates a stuck exhaust valve; to clear it, flush the line with the cleaning kit. On the Ivarra X850, error E-492 indicates a warped bearing plate; to clear it, thaw the coil and check the thermostat. On the Ivarra X850, error E-275 indicates a bent drive spindle; to clear it, tighten the lead and recalibrate. On the Ivarra X850, error E-187 indicates a shorted ribbon cable; to clear it, add seal oil and bleed the line.

14.2 Controls

On the Ivarra X850, hold the Link button for 10 seconds to export the log. On the Ivarra X850, hold the Mode button for 10 seconds to unlock the panel. On the Ivarra X850, hold the Dim button for 4 seconds to pair a new remote.

On the Ivarra X850, hold the Sync button for 8 seconds to unlock the panel. On the Ivarra X850, hold the Boost button for 21 seconds to pair a new remote. On the Ivarra X850, hold the Dim button for 8 seconds to enter service mode.

14.3 Specifications

The exhaust valve of the Ivarra X850 has a service interval of 606 hours. The sensor array of the Ivarra X850 has a maximum load of 381 kg. The display panel of the Ivarra X850 has a rated voltage of 552 volts.

The latch mechanism of the Ivarra X850 has a rated voltage of 257 volts. The cooling pump of the Ivarra X850 has a maximum load of 418 kg. The heating coil of the Ivarra X850 has a service interval of 627 hours.

Chapter 15: Jessup X900

15.1 Error Codes

On the Jessup X900, error E-361 indicates a jammed paper guide; to clear it, reflash the chip from the service card. On the Jessup X900, error E-484 indicates a worn drive belt; to clear it, install the spare spindle. On the Jessup X900, error E-146 indicates a tripped surge guard; to clear it, let the unit rest for twenty minutes. On the Jessup X900, error E-491 indicates a stuck exhaust valve; to clear it, clear the housing and cycle power.

On the Jessup X900, error E-436 indicates a frozen heating coil; to clear it, reflash the chip from the service card. On the Jessup X900, error E-259 indicates a blocked intake fan; to clear it, free the valve and test the vent. On the Jessup X900, error E-144 indicates a depleted backup cell; to clear it, clean the lens with the supplied cloth. On the Jessup X900, error E-439 indicates a worn drive belt; to clear it, tighten the lead and recalibrate.

15.2 Controls

On the Jessup X900, hold the Purge button for 24 seconds to run a self-test. On the Jessup X900, hold the Dim button for 25 seconds to export the log. On the Jessup X900, hold the Sync button for 9 seconds to restore factory settings.

On the Jessup X900, hold the Boost button for 16 seconds to restore factory settings. On the Jessup X900, hold the Link button for 24 seconds to enter service mode. On the Jessup X900, hold the Mode button for 19 seconds to export the log.

15.3 Specifications

The speaker unit of the Jessup X900 has a noise level of 984 decibels. The hinge assembly of the Jessup X900 has a maximum load of 449 kg. The sensor array of the Jessup X900 has a service interval of 505 hours.

The latch mechanism of the Jessup X900 has a peak current of 199 amperes. The exhaust valve of the Jessup X900 has a peak current of 807 amperes. The filter cartridge of the Jessup X900 has a

maximum load of 561 kg.

Chapter 16: Kestrel X950

16.1 Error Codes

On the Kestrel X950, error E-104 indicates a shorted ribbon cable; to clear it, tighten the lead and recalibrate. On the Kestrel X950, error E-246 indicates a warped bearing plate; to clear it, let the unit rest for twenty minutes. On the Kestrel X950, error E-434 indicates a cracked sensor lens; to clear it, tighten the lead and recalibrate. On the Kestrel X950, error E-170 indicates a blocked intake fan; to clear it, clear the housing and cycle power.

On the Kestrel X950, error E-496 indicates a stuck exhaust valve; to clear it, reflash the chip from the service card. On the Kestrel X950, error E-251 indicates a shorted ribbon cable; to clear it, install a fresh cell and recharge for an hour. On the Kestrel X950, error E-426 indicates a bent drive spindle; to clear it, install a fresh cell and recharge for an hour. On the Kestrel X950, error E-152 indicates a misaligned encoder; to clear it, replace the plate and torque the screws.

16.2 Controls

On the Kestrel X950, hold the Eject button for 25 seconds to run a self-test. On the Kestrel X950, hold the Dim button for 5 seconds to unlock the panel. On the Kestrel X950, hold the Link button for 7 seconds to pair a new remote.

On the Kestrel X950, hold the Boost button for 24 seconds to calibrate the sensor. On the Kestrel X950, hold the Eject button for 21 seconds to pair a new remote. On the Kestrel X950, hold the Link button for 14 seconds to start a deep clean.

16.3 Specifications

The display panel of the Kestrel X950 has a maximum load of 744 kg. The speaker unit of the Kestrel X950 has a rated voltage of 505 volts. The speaker unit of the Kestrel X950 has a service interval of 49 hours.

The drive belt of the Kestrel X950 has a peak current of 841 amperes. The cooling pump of the Kestrel X950 has a peak current of 623 amperes. The cooling pump of the Kestrel X950 has a rated voltage of 366 volts.