

AI-BASED PLANT STRESS DETECTION SYSTEM

Project Enhancement, Novelty & Research Plan

AI / Machine Learning / Embedded Systems / TinyML

Prepared for project planning and future reference

Name:	V Shailesh
Registration Number:	24MIS0301
Institution:	VIT Vellore
Team Members:	[Placeholder]
Faculty:	[Placeholder]
Academic Year:	[Placeholder]

Table of Contents

- 1. Project Context
- 2. Primary Research Direction
- 3. Proposed Core Classification
- 4. Novelty Enhancement 1 — Confidence-Aware / Uncertainty Detection
- 5. Novelty Enhancement 2 — Stress Severity Estimation
- 6. Novelty Enhancement 3 — Model Interpretability / Spectral Feature Analysis
- 7. Major Experimental Contribution — Generalization to Unseen Plants
- 8. Environmental Robustness Experiment
- 9. Recommended Final Project Architecture
- 10. Machine-Learning Development Strategy
- 11. Priority of Features
- 12. Features That Should Not Be Added Unless Necessary
- 13. Core + Enhancement Strategy
- 14. Final Proposed Novelty Statement
- 15. Recommended Final Scope
- 16. Development Philosophy
- 17. Key Project Principle
- 18. Final Research Direction

1. Project Context

The proposed project is a low-cost, portable plant stress detection system using a multispectral sensing unit connected to an ESP32 microcontroller.

The system is intended to capture the spectral characteristics of a plant leaf and use a lightweight machine-learning model to identify the physiological condition of the plant. The current proposed classification categories are:

- Healthy
- Nitrogen Stress
- Water Stress

The system is intended to perform the final inference at the edge using the ESP32 rather than depending entirely on a cloud-based system.

The existing reference work already demonstrates the feasibility of using an ESP32, multispectral sensing, a leaf-clip arrangement and TinyML for plant-stress-related classification. Therefore, simply reproducing the same hardware and TinyML pipeline would provide limited novelty.

The project should therefore focus on improving the diagnostic capability, reliability and experimental evaluation of the system rather than merely reproducing the previous hardware architecture.

2. Primary Research Direction

2.1 Core Research Question

RESEARCH QUESTION

Can a low-cost, ESP32-based multispectral sensing system distinguish between different physiological causes of plant stress, particularly nitrogen stress and water stress, rather than merely detecting whether a plant is stressed or healthy?

This changes the objective from simple "Stress Detection" to "**Stress Classification / Cause-Specific Stress Identification.**"

3. Proposed Core Classification

The initial machine-learning system will classify plant conditions into three categories:

- **CLASS 1 — HEALTHY:** Plant/leaf showing no intentionally induced stress condition.
- **CLASS 2 — NITROGEN STRESS:** Plant/leaf subjected to controlled nitrogen deficiency.
- **CLASS 3 — WATER STRESS:** Plant/leaf subjected to controlled water-deficit conditions.

The three-class system should remain the minimum viable project objective. Additional features should only be implemented after this core classification system works reliably.


4. Novelty Enhancement 1 — Confidence-Aware / Uncertainty Detection

4.1 Concept

A conventional classifier will normally be forced to select one of the available classes. (e.g., Prediction: Nitrogen Stress — 84%). However, real-world plant samples may not always clearly belong to one class.

Sensor noise, environmental variation, plant age, measurement positioning, intermediate stress conditions and overlapping physiological symptoms can cause uncertain predictions. Therefore, an additional confidence-aware decision mechanism can be introduced.

4.2 Proposed Operation



Example Outputs

- **High-confidence prediction:** Output: *NITROGEN STRESS (Confidence: 87%)*
- **Low-confidence prediction:** Output: *UNCERTAIN (PLEASE RESCAN)*

4.3 Purpose & Expected Contribution

A system that is forced to provide a diagnosis for every sample may produce a confident but incorrect result. An uncertainty mechanism allows the device to acknowledge that the current sensor measurement does not provide sufficient confidence for a reliable classification. This makes the system more realistic for practical diagnostic use.

EXPERIMENTAL QUESTION

"How does classification accuracy change when low-confidence predictions are rejected?"

5. Novelty Enhancement 2 — Stress Severity Estimation

OPTIONAL / ADVANCED FEATURE

This feature is marked as optional and should not be added unless reliable labels can be created. The project should first successfully achieve the core three-class classification.

5.1 Concept & Possible Output

A possible extension is to estimate the severity of the identified stress (e.g., Mild, Moderate, Severe). Instead of outputting just "Nitrogen Stress", the system could eventually provide "Nitrogen Stress — Moderate".


5.2 Requirement for Scientifically Reliable Labels

The team must establish a scientifically defensible method for defining Mild, Moderate, and Severe Stress. Experimental variables may include nutrient availability, water availability, and duration of stress exposure. The exact severity definition must be finalized after discussing the methodology with the faculty.

6. Novelty Enhancement 3 — Model Interpretability / Spectral Feature Analysis

6.1 Concept & Pipeline

The ML model should not be treated entirely as a black box. The project can investigate which spectral features contribute most strongly to distinguishing healthy, nitrogen-stressed, and water-stressed leaves.



6.2 Research Output & Value

PRELIMINARY CLAIM

The actual important spectral bands must be determined experimentally. They should not be predetermined or claimed without analyzing the collected dataset.

Instead of simply reporting an accuracy percentage, the project can investigate *why* the model distinguishes the different stress conditions, providing an additional scientific analysis component.

7. Major Experimental Contribution — Generalization to Unseen Plants

7.1 The Problem

A model can achieve very high accuracy if training and testing samples are too similar (e.g., training and testing on leaves from the exact same plant).

7.2 Proposed Experiment

Separate plants rather than simply randomly separating individual sensor measurements. For example, train on Plants 1–8 and test on Plants 9–10. The model therefore has to classify leaves from plants it has not previously seen during training.

RESEARCH QUESTION

"Can the trained model generalize to previously unseen plants?"

This provides a stronger evaluation of practical usefulness and is considered one of the most important experiments.

8. Environmental Robustness Experiment

The proposed system uses a leaf-clip arrangement to reduce the effect of external lighting conditions. The project can experimentally investigate whether this design improves measurement consistency under varying conditions:


- **Condition A:** Controlled indoor lighting.
- **Condition B:** Different indoor lighting.
- **Condition C:** Outdoor / shaded conditions (if feasible).


RESEARCH QUESTION

"How robust is the multispectral classification system to changes in measurement and environmental conditions?"

Compare classification accuracy, prediction confidence, sensor-value variation, and misclassification rate.

9. Recommended Final Project Architecture





10. Machine-Learning Development Strategy

- **Phase 1: Dataset Creation** – Collect labelled multispectral measurements for Healthy, Nitrogen Stress, and Water Stress.
- **Phase 2: Data Preprocessing** – Data cleaning, missing-value handling, normalization/scaling, feature preparation, label encoding.
- **Phase 3: Baseline Models** – Evaluate lightweight classifiers (e.g., Random Forest, SVM).
- **Phase 4: Model Evaluation** – Evaluate accuracy, precision, recall, F1-score, confusion matrix, model size, computational requirements, inference time.
- **Phase 5: Robustness Evaluation** – Test unseen plants, different measurement conditions, repeated measurements, noisy measurements.
- **Phase 6: Confidence Mechanism** – Add the confidence/uncertainty mechanism.
- **Phase 7: TinyML Deployment** – Convert Python model → Embedded-Compatible Representation → ESP32 → On-Device Inference.

11. Priority of Features

Feature	Priority	Reason
Three-Class Classification	Essential	This is the core project objective (Healthy vs Nitrogen Stress vs Water Stress).
Dataset Quality	Essential	Directly determines the scientific validity of the model.
Model Comparison	Essential	Provides justification for selecting the final lightweight model.
Unseen-Plant Testing	High	Tests whether the model generalizes to plants not used during training.
Confidence / Uncertainty	High	Improves practical reliability and prevents forced predictions on low confidence.
Spectral Feature Analysis	High	Provides scientific interpretation of contributing spectral features.
Environmental Robustness	High	Tests reliability under varying measurement conditions.
Stress Severity Estimation	Optional / Advanced	Requires scientifically reliable severity labels.
Mobile / Cloud Dashboard	Not Required	Adds complexity without directly strengthening the core research contribution.

12. Features That Should Not Be Added Unless Necessary

IMPORTANT

The project should avoid adding features merely to make the system appear more complex. These additions increase development complexity without necessarily improving the scientific contribution.

- Mobile application
- Cloud dashboard
- Chatbot
- GPS
- Blockchain
- Drone integration
- Camera-based CNN
- Excessive number of sensors
- Large deep-learning models

13. Core + Enhancement Strategy

CORE SYSTEM:

ESP32 + Multispectral Sensor + Leaf Clip + Dataset + Healthy/Nitrogen Stress/Water Stress + Lightweight ML + TinyML + OLED

ENHANCEMENTS:

- Confidence / Uncertainty
- Unseen Plant Generalization
- Spectral Feature Analysis
- Environmental Robustness

OPTIONAL:

Stress Severity Estimation

14. Final Proposed Novelty Statement

PRELIMINARY — TO BE VALIDATED

"The proposed system aims to develop a low-cost, edge-based multispectral plant stress detection device capable of distinguishing healthy, nitrogen-stressed and water-stressed plants using lightweight machine-learning models deployed on an ESP32. Beyond basic stress classification, the system will investigate confidence-aware prediction, model generalization to previously unseen plants, spectral feature importance and robustness under varying measurement conditions."

This is a working novelty statement and is NOT the final claim of novelty. It should be finalized only after reviewing literature, confirming implementation feasibility, discussing with faculty, and demonstrating experimentally.


15. Recommended Final Scope

The project should follow a CORE + ENHANCEMENT strategy.

- **CORE:** ESP32 + Multispectral Sensor + Leaf Clip + Healthy / Nitrogen Stress / Water Stress + Dataset + Lightweight ML + TinyML + OLED

- **PRIMARY ENHANCEMENTS:** (1) Confidence / Uncertainty Detection, (2) Generalization to Unseen Plants, (3) Spectral Feature Importance Analysis, (4) Environmental Robustness Evaluation
- **OPTIONAL ADVANCED ENHANCEMENT:** (5) Stress Severity Estimation

16. Development Philosophy



17. Key Project Principle

**DO NOT MAKE THE PROJECT COMPLICATED.
MAKE THE EXPERIMENT STRONGER.**

The strongest contribution is not necessarily adding more hardware or software. The project should demonstrate that the system can distinguish stress causes, provide reliable predictions, identify uncertainty, generalize to unseen plants, interpret spectral features, remain robust, and run lightweight locally.

18. Final Research Direction

The project should move beyond simply asking "*Can we detect plant stress?*" and instead investigate:

CENTRAL DIRECTION

"Can a low-cost multispectral edge device reliably distinguish different physiological causes of plant stress and provide a confidence-aware diagnosis that generalizes to previously unseen plants?"

The hardware should remain simple and practical. The ML model should remain lightweight. Main efforts should be invested in dataset quality, experimental design, model comparison, generalization, confidence analysis, spectral feature interpretation, robustness testing, and TinyML deployment.