Chapter 6 — State Management

Chapter 3 gave components memory with `useState` and showed **lifting state up**. As apps grow, update logic scatters across handlers and data needed far away must pass through every layer. This chapter covers React's two built-ins for that — **`useReducer`** (organise *how* state changes) and **Context** (deliver values *far down* the tree) — then the libraries in most codebases: **Redux Toolkit** and **Zustand** for client state, **TanStack Query** for server state. Every library example runs with the real packages.

Code: `code/` — React 19.3, Redux Toolkit 2.12 + React Redux 9.3, Zustand 5.0, TanStack Query 5.104, in jsdom.

6.1 Kinds of state — and where each belongs

What it is

Apps have several **kinds** of state with different needs; most state-management pain comes from putting one kind in the wrong home — especially treating **server data** as ordinary client state.

Kind	Examples	Needs	Natural home
Local UI state	Is this dropdown open? Current tab? Text in this input?	Nothing special	`useState` in the component (Chapter 3)
Complex local state	A form wizard, an editor with many actions	Clear update rules	`useReducer` (§6.2)
Shared / global client state	Current user, theme, cart, feature flags (switches enabling a feature for some users), a multi-step draft	Reachable from far away; efficient updates	Lift up → Context (§6.3) → Zustand / Redux (§6.7–6.8)
Server state (a cached copy of data a server owns)	Product list, user profile, search results	Fetching, caching, de-duplication (merging identical requests), refetching, staleness (how out of date the copy may be), retries	TanStack Query (§6.9), RTK Query, or framework loaders (router functions that fetch a page's data; Chapter 9)
URL state	Filters, page number, selected item ID	Shareable, survives reload, back button	Route params (the `42` in `/books/42`) and search params (`?genre=sf&page=2`) (Chapter 9)
Form state	Field values, errors, pending	Validation, submission	Form Actions / `useActionState`, or a form library (Chapter 4)
Derived state	Totals, filtered lists, "is valid"	Must never be out of sync	**Not state** — compute during render (§3.8)

Why server state is different

Server data is **owned by someone else** — other users can change it any time, so your copy is always potentially **stale**. It needs loading/error states, caching, de-duplication, background refetching and **invalidation** (marking cached data out of date so it is refetched) after you change it (System Design Fundamentals on caching). Hand-writing that with `useEffect` + `useState` (§5.7) or storing it in Redux is a major source of complexity; a server-state library usually removes most of an app's "global state".

TL;DR

Classify first: local, complex local, shared client, server, URL, form, derived. Keep state as local as possible; put server data in a query cache; never store what you can derive.

6.2 `useReducer` — consolidate update logic

What it is

With `useState` each handler decides the next state; as actions multiply (add, edit, delete, reorder, clear…) that logic spreads. `useReducer` moves it into **one function outside the component**:

```
const [state, dispatch] = useReducer(reducer, initialArg, init?);
// reducer(state, action) -> nextState     (pure: no side effects, no mutation)
// dispatch(action)                        (action = a plain object describing what happened, e.g. { type:
'added', text })
// init?: optional function; initial state = init(initialArg), computed once
```

An **action** is a plain object describing **what happened** (a `type` string like `'added'` plus data). **Dispatch** = send an action to the reducer. The **reducer** takes current state + action and returns the **next** state. Actions form a clear history of what happened.

How it works

The reducer (`code/tasks-reducer.js`) never mutates and throws on unknown actions:

```
export function tasksReducer(tasks, action) {
  switch (action.type) {
    case 'added':
      return [...tasks, { id: action.id, text: action.text, done: false }];
    case 'toggled':
      return tasks.map((t) => (t.id === action.id ? { ...t, done: !t.done } : t));
    case 'renamed':
      return tasks.map((t) => (t.id === action.id ? { ...t, text: action.text } : t));
    case 'deleted':
      return tasks.filter((t) => t.id !== action.id);
    case 'cleared_done':
      return tasks.filter((t) => !t.done);
    default:
      throw new Error(`Unknown action: ${action.type}`);   // catches typos early
  }
}
```

`code/01_use_reducer.jsx` :

```
// 1. Reducers are plain functions: test them without React.
const s0 = [{ id: 1, text: 'Visit Kafka Museum', done: true }];
const s1 = tasksReducer(s0, { type: 'added', id: 2, text: 'Watch a puppet show' });
const s2 = tasksReducer(s1, { type: 'toggled', id: 2 });
// ...
// 2. In a component: dispatch describes WHAT happened; the reducer decides HOW state changes.
function createInitialTasks(username) {                // lazy initialiser: runs once
  console.log(`  (init for ${username})`);
  return [{ id: 1, text: `${username}'s first task`, done: false }];
}
function TaskApp({ username }) {
  const [tasks, dispatch] = useReducer(tasksReducer, username, createInitialTasks);
  return (
    <>
      <button onClick={() => dispatch({ type: 'added', id: nextId++, text: 'Buy stamps' })}>add</button>
      <button onClick={() => dispatch({ type: 'cleared_done' })}>clear done</button>
      <ul>
        {tasks.map((t) => (
          <li key={t.id}>
            <label><input type="checkbox" checked={t.done} onChange={() => dispatch({ type: 'toggled', id: t.id
})} />{t.text}</label>
            <button onClick={() => dispatch({ type: 'deleted', id: t.id })}>delete {t.text}</button>
          </li>
        ))}
      </ul>
    </>
  );
}
```

Output:

```
pure reducer: ["[x] Visit Kafka Museum","[x] Watch a puppet show"] | s0 untouched: true
typo caught  : Unknown action: addded
  (init for Ada)
after 2 adds       : [ "[ ] Ada's first task", '[ ] Buy stamps', '[ ] Buy stamps' ]
toggle + clear done: [ '[ ] Buy stamps', '[ ] Buy stamps' ]
delete one         : [ '[ ] Buy stamps' ]
```

The reducer was **tested without rendering** and left the original array untouched (§3.6); a misspelt type failed loudly; the **lazy initialiser** ran once across several renders; handlers became one-liners saying *what happened*, with all the *how* in one place.

Rules for reducers

1. **Pure**: same state + action → same result. No requests, timers, random IDs or `Date.now()` inside — create those in the handler and put them in the action (`id: nextId++`). StrictMode calls reducers twice in development.
2. **Immutable**: return new objects/arrays. (Immer's `useImmerReducer` allows mutating-style code — the trick Redux Toolkit uses, §6.7.)
3. **Actions describe events, not setters**: `{ type: 'task_completed', id }` over `{ type: 'set_done', value: true }`. One user action = one dispatch, even if several fields change.
4. `dispatch` has a **stable identity** (same function every render) — safe to pass down or omit from Effect dependencies.
5. Like setters, `dispatch` affects only the **next** render; reading `state` right after gives the old snapshot (§3.3).

`useState` VS `useReducer`

	`useState`	`useReducer`
Code size	Small for simple values	More upfront (reducer + actions)
Many update types on one piece of state	Logic scattered in handlers	Centralised, readable
Testing	Needs a render	Test the reducer as a plain function
Debugging	Where did this change?	Log every action + state in one place
Next state depends on several fields	Several setters, risk of inconsistency	One transition computes everything

Start with `useState`; switch when several handlers modify the same state in related ways or updates get inconsistent. Mixing both is fine.

In the interview

> **30-second answer:** "`useReducer` takes a reducer — a pure function from state and action to the next state — and returns the state plus a stable `dispatch`. Handlers dispatch actions describing what happened, and all update logic lives in the reducer, which I can **unit-test** (test one small piece of code on its own) without React. I switch from `useState` when many handlers update the same state or the transitions get complex, and I combine it with context for app-wide state."

- *Can a reducer fetch data?* — No; it must be pure. Fetch in a handler or Effect and dispatch the result.
- *Third argument?* — An initialiser: initial state = `init(initialArg)`, computed once.
- *Why throw on unknown types?* — Typos fail immediately instead of being silently ignored.

TL;DR

`const [state, dispatch] = useReducer(reducer, initial)`. Reducer = pure `(state, action) => next`. Dispatch events, not setters. Test reducers without React.

6.3 Context — pass data deeply without props

The problem it solves

Prop drilling — passing a prop through many components that don't use it — becomes noise when a theme, current user or **locale** (language and regional formats) is needed in dozens of places, and **couples** every layer to data it doesn't care about. **Context** lets a parent make a value available to **every component below it**, however deep; components outside the provider get the default.

How it works

Three steps: **create**, **provide**, **use**.

`code/02_context_basics.jsx`:

```jsx
// 1. Create: the argument is the DEFAULT, used only when there is no provider above.
const ThemeContext = createContext('light');
const LevelContext = createContext(1);

// 2. Read: useContext(Ctx) — or use(Ctx), which (unlike Hooks) may be called conditionally.
function Button({ children }) {
  const theme = useContext(ThemeContext);
  return <button className={`btn-${theme}`}>{children}</button>;
}
function Heading({ children }) {
  if (!children) return null;                  // early return...
  const level = use(LevelContext);             // ...then read context: allowed with use(), not with useContext
  const Tag = `h${Math.min(level, 6)}`;
  return <Tag>{children}</Tag>;
}
// 3. A component can read the nearest value and provide a new one for its subtree.
function Section({ children }) {
  const level = useContext(LevelContext);
  return <section><LevelContext value={level + 1}>{children}</LevelContext></section>;   // React 19: <Ctx value>
}

function App() {
  const [theme, setTheme] = useState('light');
  return (
    <ThemeContext value={theme}>
      <Heading>Title</Heading>
      <Section>
        <Heading>Chapter</Heading>
        <Section>
          <Heading>Sub-section</Heading>
          <Heading />
          <Button>Save</Button>
          <ThemeContext.Provider value="high-contrast">   {/* older syntax, still works */}
            <Button>Nested override</Button>
          </ThemeContext.Provider>
        </Section>
      </Section>
      <button onClick={() => setTheme(theme === 'light' ? 'dark' : 'light')}>toggle theme</button>
    </ThemeContext>
  );
}
```

Output:

```
headings : H1:Title  H2:Chapter  H3:Sub-section
buttons  : Save -> btn-light | Nested override -> btn-high-contrast
toggled  : Save -> btn-dark | Nested override -> btn-high-contrast
no provider -> btn-light (the default from createContext)
```

1. Each `Section` read the level from the **nearest provider above** and provided `level + 1` — headings got the right tag with no `level` prop.
2. The inner `high-contrast` provider overrode the theme only for its **subtree**.
3. When the provided value changed, consumers **re-rendered automatically**.
4. With **no provider**, `useContext` returned the `createContext` **default**.

Syntax notes (React 19)

Topic	Detail
Providing	`<MyContext value={…}>` is the React 19 way; `<MyContext.Provider value={…}>` still works and is planned for deprecation
Reading	`useContext(MyContext)` (a Hook: top level only) or `use(MyContext)` (can be inside `if`/after early returns)
Default value	Used only when no provider is above — not when the provider's value is `undefined`
Scope	Context passes through any intermediate components, including library ones
Class components	`static contextType` (legacy)

Common uses: theme, locale/i18n (internationalisation — translating the UI), current user/auth, feature flags, a router's location, a form library's form state, design-system settings (density, direction), and **dependency injection** for tests (handing a component its services from outside, e.g. a fake API client).

Before you use context

- **Try props first** — explicit props through two or three levels are fine.
- **Try composition** — pass JSX as `children` so middle components never see the data (§2.4): `<Layout sidebar={<UserMenu user={user} />} />`.
- Context is a **delivery mechanism**, not a state manager: the value still lives in `useState`/`useReducer`/a store.

In the interview

> **30-second answer:** "Context lets a component provide a value to its entire subtree without prop drilling: `createContext(default)`, provide with `<Ctx value>` (or `.Provider` in older code), read with `useContext` or `use`. Consumers get the nearest provider's value and re-render when it changes. I use it for rarely-changing, widely-needed values like theme, locale or auth, and I try props or composition first."

- *No provider?* — The default from `createContext`.
- *`useContext` vs `use(Context)`?* — `use` can be called conditionally (after early returns, in loops); `useContext` follows Hook rules.

TL;DR

`createContext(default)` → `<Ctx value={v}>` → `useContext(Ctx)`/`use(Ctx)`. Nearest provider wins; consumers re-render on change. Props and composition first.

6.4 Context performance caveats

What it is

When a provider's `value` changes (`Object.is`), **every component reading that context re-renders** — even inside `memo` (skips re-render when props are unchanged — Chapter 10), and even if it uses one field. Fine for rarely-changing values (theme, locale); a problem for frequently-changing data or a new object created every render.

How it works — measuring renders

`code/03_context_performance.jsx`:

```jsx
const AuthContext = createContext(null);
const UserBadge = memo(function UserBadge() {           // reads the user
  count('UserBadge'); const { user } = useContext(AuthContext); return <span>{user}</span>;
});
const LogoutButton = memo(function LogoutButton() {     // only needs the function
  count('LogoutButton'); const { logout } = useContext(AuthContext); return <button onClick=
{logout}>logout</button>;
});
const Sidebar = memo(function Sidebar() { count('Sidebar(no context)'); return <nav>links</nav>; });

function App({ memoValue }) {
  const [user, setUser] = useState('ada');
  const [clock, setClock] = useState(0);                // unrelated state in the same component
  const logout = useCallback(() => setUser(null), []);
  const literal = { user, logout };                      // 🔴 new object every render
  const memoised = useMemo(() => ({ user, logout }), [user, logout]);   // ✅ same object until user changes
  return (
    <AuthContext value={memoValue ? memoised : literal}>
      <UserBadge /><LogoutButton /><Sidebar />
      <button onClick={() => setClock(clock + 1)}>tick</button>
    </AuthContext>
  );
}

// Split state and actions into two contexts: action-only consumers stop re-rendering.
function AuthProvider({ children }) {
  const [user, setUser] = useState('ada');
  const actions = useMemo(() => ({ logout: () => setUser(null), login: (u) => setUser(u) }), []);  // never
changes
  return <UserContext value={user}><AuthActionsContext value={actions}>{children}</AuthActionsContext>
</UserContext>;
}
// render(<AuthProvider><Badge2 /><Logout2 /><Sidebar /></AuthProvider>)
```

Output (renders per component for each step):

```
mount (literal value)                    {"UserBadge":1,"LogoutButton":1,"Sidebar(no context)":1}
  unrelated state change ->              {"UserBadge":1,"LogoutButton":1}
  user changed ->                        {"UserBadge":1,"LogoutButton":1}
mount (useMemo value)                    {"UserBadge":1,"LogoutButton":1,"Sidebar(no context)":1}
  unrelated state change ->              {}
  user changed ->                        {"UserBadge":1,"LogoutButton":1}
split contexts: mount                    {"Badge2":1,"Logout2":1,"Sidebar(no context)":1}
  user changed ->                        {"Badge2":1}
```

1. **Object literal as `value` → new object every provider render → all consumers re-render** on *unrelated* changes (the tick), defeating `memo`. `useMemo` for the value (returns the same cached value until inputs change) and `useCallback` for functions fixed it — the React Compiler does this automatically (Chapter 10).
2. **Consumers re-render when anything in the value changes**: `LogoutButton` needs only `logout` but re-rendered when `user` changed. **Splitting** state and actions contexts fixed it.
3. `memo` components that **don't read** the context (`Sidebar`) are unaffected; a provider receiving its subtree as `children` (like `AuthProvider`) doesn't re-render that subtree on its own state change — only the consumers.

Techniques summary

Problem	Fix
New object/function as `value` each render	`useMemo` for the value, `useCallback` for functions (or the React Compiler)
Some consumers only need actions/dispatch	Separate "state" and "dispatch/actions" contexts (§6.5)
One big context with unrelated values	Split per concern: `ThemeContext`, `AuthContext`, `CartContext`
High-frequency values (mouse position, typing, timers)	Keep local, or use a store with **selectors** (Zustand/Redux re-render only components whose selected slice changed)
Provider re-renders its whole subtree	Put state in a dedicated provider component that takes `children`

When not to use context: as a general global store for frequently changing data — it has no **selectors** ("re-render me only when `cart.count` changes"), which is exactly what external stores add.


TL;DR

All consumers re-render when the value's identity changes. Memoise the value, split state from actions, split by concern, and use a selector-based store for fast-changing shared data.

6.5 Reducer + context — a store with only React

What it is

A **reducer** owns the state and update rules; **two contexts** deliver the state and `dispatch` to any component; a provider component plus two custom Hooks wrap it — a tidy, dependency-free store for a feature-sized slice of state.



How it works

`code/04_reducer_plus_context.jsx`:

```jsx
// ---- TasksContext.jsx (in a real app: its own file exporting the provider + two Hooks)
const TasksContext = createContext(null);
const TasksDispatchContext = createContext(null);

export function TasksProvider({ initialTasks, children }) {
  const [tasks, dispatch] = useReducer(tasksReducer, initialTasks);
  return (
    <TasksContext value={tasks}>
      <TasksDispatchContext value={dispatch}>{children}</TasksDispatchContext>
    </TasksContext>
  );
}
export function useTasks() {
  const tasks = useContext(TasksContext);
  if (tasks === null) throw new Error('useTasks must be used inside <TasksProvider>');
  return tasks;
}
export function useTasksDispatch() {
  const dispatch = useContext(TasksDispatchContext);
  if (dispatch === null) throw new Error('useTasksDispatch must be used inside <TasksProvider>');
  return dispatch;                                    // stable identity: components using only this rarely re-render
}

// ---- Components deep in the tree: no tasks/onAdd/onToggle props passed through the middle.
function AddTask() {
  const dispatch = useTasksDispatch();
  const [text, setText] = useState('');
  return (
    <form onSubmit={(e) => { e.preventDefault(); dispatch({ type: 'added', id: nextId++, text }); setText(''); }}>
      <input aria-label="New task" value={text} onChange={(e) => setText(e.target.value)} /><button>Add</button>
    </form>
  );
}
function TaskList() { const tasks = useTasks(); const dispatch = useTasksDispatch(); /* ... checkboxes dispatch 'toggled' */ }
function Counter() { const tasks = useTasks(); return <p>{tasks.filter((t) => !t.done).length} left</p>; }
function Layout() { return <main><AddTask /><section><TaskList /></section><footer><Counter /></footer></main>; }
// passes nothing down
```

Output:

```
tasks  : [ '[x] Philosopher’s Path', '[ ] Visit the temple' ]
footer : 1 left
outside provider -> useTasks must be used inside <TasksProvider>
```

`Layout` passes **no props**. The **custom Hooks** hide the context objects and turn "forgot the provider" into a clear error (possible because the default is `null`). Since `dispatch` never changes, `AddTask` doesn't re-render when tasks change (§6.4 lesson 2).

Limits: every `useTasks()` consumer re-renders on every change; no selectors, no devtools/time travel (stepping back through previous states), no middleware; async flows are up to you. Fine for a feature or small app; large, frequently updated shared state is better in a library.

> **TL;DR**
>
> `useReducer` in a provider + separate state and dispatch contexts + `useX()` Hooks that throw outside the provider = a small, dependency-free store.

6.6 When to reach for a library

Built-ins (local state, lifting, `useReducer`, context) take most apps a long way. Signals a library pays off:

Signal	Likely answer
Lots of `useEffect` + `useState` for fetching; loading/error flags everywhere; duplicate requests; stale lists after edits	**TanStack Query** (or RTK Query / SWR / framework loaders) — this alone removes most "global state"
Shared client state that changes often and is read by many components (editor, canvas, dashboard filters, cart)	A store with selectors: **Zustand** (small) or **Redux Toolkit** (structured)
Large team, many features, strict conventions, action logs, time-travel debugging, middleware	**Redux Toolkit**
State updated from outside React (WebSocket messages, timers, non-React code)	A store usable outside React (Zustand's `getState/setState`, Redux `store.dispatch`)
Complex flows with explicit states and transitions (checkout, wizard, media player)	A reducer, or a **state-machine** library (fixed states + allowed transitions) such as XState
Fine-grained derived values (spreadsheet-like)	An **atom** library (state split into many tiny independent pieces) such as Jotai


You *don't* need one for a few rarely-changing shared values (theme, user — context is enough) or for "global state" that is really server data (use a query library).

6.7 Redux Toolkit

What it is

Redux keeps app-wide state in **one store**, changed only by **dispatching actions** to **reducers** (`useReducer`'s idea, global, with a big ecosystem). **Redux Toolkit (RTK)** is the official way to write Redux today, removing the old **boilerplate** (hand-written action types, switch statements, spread-heavy updates, store setup).

Term	Meaning
Store	Holds the whole state tree; `getState()`, `dispatch(action)`, `subscribe(listener)`
Slice	One feature's state + reducers + generated action creators (`createSlice`)
Action creator	Function returning an action object: `added('p1')` → `{ type: 'cart/added', payload: 'p1' }`
Selector	Function that reads (and maybe derives) data from state: `state => state.cart.lines`
Thunk	A function you dispatch for async logic; `createAsyncThunk` dispatches `pending` / `fulfilled` / `rejected` (a promise's waiting/succeeded/failed states) for you
Middleware	Code between `dispatch` and the reducer (logging, thunks, analytics)



How it works

`code/05_redux_toolkit.jsx`:

```
// ---- features/products/productsSlice.js : async data with createAsyncThunk
export const fetchProducts = createAsyncThunk('products/fetch', () => fakeApi.fetchProducts());
const productsSlice = createSlice({
  name: 'products',
  initialState: { items: [], status: 'idle', error: null },
  reducers: {},
  extraReducers: (builder) => {
    builder
      .addCase(fetchProducts.pending, (state) => { state.status = 'loading'; })
      .addCase(fetchProducts.fulfilled, (state, action) => { state.status = 'succeeded'; state.items =
action.payload; })
      .addCase(fetchProducts.rejected, (state, action) => { state.status = 'failed'; state.error =
action.error.message; });
  },
});

// ---- features/cart/cartSlice.js : "mutating" code is safe here — Immer produces a new immutable state
const cartSlice = createSlice({
  name: 'cart',
  initialState: { lines: {} },                        // { [productId]: quantity }
  reducers: {
    added(state, action) { const id = action.payload; state.lines[id] = (state.lines[id] ?? 0) + 1; },
    removed(state, action) { delete state.lines[action.payload]; },
    cleared() { return { lines: {} }; },              // or return a brand-new state
  },
});
export const { added, removed, cleared } = cartSlice.actions;   // action creators generated for you

// ---- selectors: read and derive; createSelector memoises derived data
const selectLines = (state) => state.cart.lines;
const selectProducts = (state) => state.products.items;
export const selectCartTotal = createSelector([selectLines, selectProducts], (lines, products) =>
  products.reduce((sum, p) => sum + (lines[p.id] ?? 0) * p.price, 0));

// ---- app/store.js
export const makeStore = () => configureStore({ reducer: { products: productsSlice.reducer, cart:
cartSlice.reducer } });

// ---- components
function ProductList() {
  const { items, status } = useSelector((s) => s.products);
  const dispatch = useDispatch();
  if (status === 'loading') return <p>Loading…</p>;
  return <ul>{items.map((p) => <li key={p.id}>{p.name} ${p.price} <button onClick={() =>
dispatch(added(p.id))}>add {p.name}</button></li>)}</ul>;
}
function CartTotal() {
  const total = useSelector(selectCartTotal);          // re-renders only when THIS value changes
  return <p>Total: ${total}</p>;
}
// render(<Provider store={store}><ProductList /><CartTotal /></Provider>); store.dispatch(fetchProducts()); click
"add" ×3
```

Output:

```
initial state : {"products":{"items":[],"status":"idle","error":null},"cart":{"lines":{}}}
after fetch   : Notebook, Pen | succeeded
cart lines    : {"p1":2,"p2":1} | Total: $10
renders       : {"CartTotal":3} (ProductList does not re-render: the products slice did not change)
memoised selector recomputed on repeat calls: 0 times
after cleared : Total: $0 | action object: {"type":"cart/added","payload":"p9"}
```

1. `createSlice` generated the reducer *and* action creators. Its reducers **look** mutating but run through **Immer**, producing new immutable state. (Mutate the draft *or* return a new value — not both.)
2. `createAsyncThunk` dispatched `pending` → `fulfilled`; `extraReducers` tracked `status`.
3. `configureStore` combined slices and by default added thunk middleware, Redux DevTools support, and dev checks warning about mutation outside reducers or non-serializable values (class instances, functions) in state.

4. `useSelector` subscribes to **just its selected value**: three cart adds re-rendered `CartTotal` three times, `ProductList` zero.
5. `createSelector` (Reselect, re-exported by RTK) **memoised** the derived total: repeat calls didn't recompute.

Rules and good practices

- One store per app; **slices per feature** (`features/cart/cartSlice.js`). Only put state there if other parts of the app care (form input text usually doesn't).
- Keep state **serializable** (plain objects/arrays/primitives) — needed for DevTools, persistence and SSR.
- **Selectors must not return new objects/arrays each call** (`useSelector(s => s.items.filter(...))`) — the component re-renders on every dispatch (React Redux warns in dev). Use `createSelector` or select primitives.
- Model actions as **events** (`cart/added`), not setters (`cart/setLines`).
- For server data prefer **RTK Query** (in RTK: `createApi`, generated hooks like `useGetProductsQuery`, caching and invalidation by tags — labels linking queries to the mutations that make them stale) over hand-written thunks — same ideas as §6.9.
- TypeScript: infer `RootState` and `AppDispatch` from the store and use pre-typed hooks (Chapter 11).

Trade-offs

Pros	Cons
Predictable one-way data flow; every change is a loggable action	More concepts and files than Zustand
Excellent DevTools: action log, state diff, time travel	Overkill for small apps
Conventions scale to large teams	Needs a `<Provider>`
Middleware ecosystem; RTK Query built in	Global by default — easy to over-centralise

In the interview

30-second answer: "Redux keeps app state in one store changed only by dispatching actions to pure reducers. Redux Toolkit is the modern way: `createSlice` generates reducers and action creators and uses Immer so I can write mutating-style updates; `configureStore` sets up thunks, DevTools and safety checks; `createAsyncThunk` or RTK Query handle async data. Components read with `useSelector`, which re-renders only when the selected value changes, and write with `useDispatch`. I'd pick it for large apps with lots of shared client state and a need for strict conventions and tooling."

- *Why can `state.count++` appear in an RTK reducer?* — Immer gives a draft and produces new immutable state from the changes.
- *Why might a component re-render on every dispatch?* — Its selector returns a new object/array each time; memoise with `createSelector`.
- *Redux vs Context?* — Context only delivers a value; Redux is a store with selectors, middleware and tooling, so consumers re-render selectively.

TL;DR

RTK: `createSlice` (reducers + actions, Immer), `configureStore`, `<Provider>`, `useSelector` (fine-grained), `useDispatch`, `createAsyncThunk`/RTK Query, `createSelector`. Structured and tool-rich; best for large apps.

6.8 Zustand

What it is

Zustand ("state" in German) is a small store library: one function returns the state *and* the actions, and `create` gives back a **Hook**. Components pass a **selector** and re-render only when that selection changes. No provider, action types or reducers required.

How it works

`code/06_zustand.jsx`:

```jsx
// ---- stores/useBearStore.js : state and the actions that change it live together
const useBearStore = create((set, get) => ({
  bears: 0,
  fish: 10,
  addBear: () => set((state) => ({ bears: state.bears + 1 })),     // set merges (shallowly) into the state
  eatFish: () => set((state) => ({ fish: Math.max(0, state.fish - get().bears) })),
  reset: () => set({ bears: 0, fish: 10 }),
}));

function BearCounter() { const bears = useBearStore((s) => s.bears); return <p>{bears} bears</p>; }
function FishCounter() { const fish = useBearStore((s) => s.fish); return <p>{fish} fish</p>; }
function Controls() {
  // several values at once: useShallow compares the picked object's fields, not its identity
  const { addBear, eatFish } = useBearStore(useShallow((s) => ({ addBear: s.addBear, eatFish: s.eatFish })));
  return <><button onClick={addBear}>add bear</button><button onClick={eatFish}>eat</button></>;
}
function Everything() { const s = useBearStore(); return <small>{s.bears}/{s.fish}</small>; }   // no selector

// Outside React: read, write, subscribe (tests, WebSocket handlers, other modules).
const unsub = useBearStore.subscribe((state, prev) => console.log(`  subscriber: bears ${prev.bears} ->
${state.bears}`));
useBearStore.getState().addBear();
useBearStore.setState({ fish: 99 });

// ---- Middleware: persist to localStorage.
const useSettings = create(persist(
  (set) => ({ theme: 'light', toggle: () => set((s) => ({ theme: s.theme === 'light' ? 'dark' : 'light' })) }),
  { name: 'settings', storage: createJSONStorage(() => localStorage) },
));

// ---- Common mistake: a selector that builds a NEW object each call, without useShallow.
function Broken() { const { bears, fish } = useBearStore((s) => ({ bears: s.bears, fish: s.fish })); return <p>
{bears}/{fish}</p>; }
```

Output:

```
after 2 bears: 2 bears | 10 fish | renders: {"BearCounter":2,"Everything(no selector)":2}
after eating : 8 fish | renders: {"FishCounter":1,"Everything(no selector)":1}
  subscriber: bears 2 -> 3
  subscriber: bears 3 -> 3
getState()   : {"bears":3,"fish":99} | screen: 99 fish
persisted    : {"state":{"theme":"dark"},"version":0}
new-object selector -> Maximum update depth exceeded. This can …  (fix: useShallow)
```

- **Selective re-renders**: bears → only `BearCounter`; fish → only `FishCounter`; `Controls` (stable action functions) never; `Everything` (**no selector**) subscribed to the whole store and re-rendered every time — avoid.
- `set` **merges** the returned object one level deep (like the old class `setState`); pass `true` as a second argument to replace. `get()` reads current state inside actions.
- **Outside React**: `getState`, `setState`, `subscribe` work anywhere (the subscriber fired for both changes, including fish-only).
- **Middleware**: `persist` saved to `localStorage` and **rehydrates** (loads it back) on load; `devtools` connects Redux DevTools; `immer` allows mutating-style `set`.

- **Classic Zustand 5 bug**: a selector returning a **new object** every call makes React see a change on every check → **infinite loop** ("Maximum update depth exceeded"). Select primitives separately, or wrap object/array selectors in `useShallow`.

Trade-offs

Pros	Cons
Tiny API; almost no boilerplate	Fewer conventions — large teams must agree on structure
No provider; usable outside React	Stores are module **singletons** (one shared instance per loaded file): SSR per-request state or tests may need a store-per-provider pattern (`createStore` + context)
Selector-based re-renders	Less tooling than Redux (DevTools via middleware)
Middleware for persist/devtools/immer	Easy to grow one giant store — split into slices/stores

In the interview

> **30-second answer:** "Zustand creates a store with `create((set, get) => ({ state…, actions… }))` and returns a Hook. Components select what they need — `useStore(s => s.count)` — and re-render only when that value changes; for multiple values I wrap the selector in `useShallow`. It needs no provider, works outside React via `getState/setState`, and has middleware like `persist` and `devtools`. I choose it for shared client state when Redux's structure would be overkill."

TL;DR

`const useStore = create((set, get) => ({ …state, …actions }))`; read with selectors; `useShallow` for objects; `getState/setState/subscribe` outside React; `persist` / `devtools` middleware.

6.9 TanStack Query — server state

What it is

TanStack Query (formerly React Query) is a **cache for server data**. Describe *what* data with a **query key** and *how* to fetch it with a **query function**; it handles loading/error states, caching, de-duplication, background refetching, retries, and staleness after changes.

Concept	Meaning	Default
`queryKey`	Array identifying the data, e.g. `['todos']`, `['user', id]`. Include every variable the fetch depends on	—
`queryFn`	Async function returning the data (or throwing)	—
`staleTime`	How long fetched data counts as **fresh** (no automatic refetch)	`0` (stale immediately)
`gcTime`	How long **unused** cached data is kept before garbage collection (freeing unused memory)	5 minutes
Retries	Failed queries retried with exponential backoff (waits 1 s, 2 s, 4 s…)	3 retries in the browser
Refetch triggers	While stale: component mount, window refocus (user returns to the tab), network reconnect	On
`status`	`'pending'` (no data yet), `'error'`, `'success'`	—
`fetchStatus`	`'fetching'`, `'paused'` (offline), `'idle'` — can be fetching while `success` (background refresh)	—

How it works

`code/07_tanstack_query.jsx`:

```
function useTodos() {                                   // wrap each query in a small custom Hook
  return useQuery({ queryKey: ['todos'], queryFn: api.getTodos, staleTime: 30_000 });
}
function TodoCount() { const { data } = useTodos(); return <p>count: {data?.length ?? '…'}</p>; }
function TodoList() {
  const { data, isPending, isError, error, isFetching } = useTodos();
  if (isPending) return <p>Loading…</p>;                  // no data yet
  if (isError) return <p role="alert">{error.message}</p>;
  return <ul aria-busy={isFetching}>{data.map((t) => <li key={t.id}>{t.title}</li>)}</ul>;
}
function AddTodo() {
  const queryClient = useQueryClient();
  const mutation = useMutation({
    mutationFn: api.addTodo,
    onSuccess: () => queryClient.invalidateQueries({ queryKey: ['todos'] }),   // mark stale + refetch
  });
  return <button disabled={mutation.isPending} onClick={() => mutation.mutate('Review chapter 6')}>
{mutation.isPending ? 'Adding…' : 'Add'}</button>;
}
function UserCard({ id }) {                              // the key includes the variable -> one cache entry per
id
  const { data, status, error } = useQuery({ queryKey: ['user', id], queryFn: () => api.getUser(id) });
  return <p>user {id}: {status === 'success' ? data.name : status === 'error' ? `error (${error.message})` :
'loading'}</p>;
}

// Test/script settings: no retries (default is 3) and no 5-minute garbage-collection timers keeping Node alive.
const queryClient = new QueryClient({ defaultOptions: { queries: { retry: false, gcTime: Infinity }, mutations: {
gcTime: Infinity } } });
const App = ({ children }) => <QueryClientProvider client={queryClient}>{children}</QueryClientProvider>;
```

Output:

```
first render  : Loading… | count: …
loaded        : [ 'Write chapter 6' ] | count: 1 | requests: [ 'GET /todos' ]
remount       : shows 1 item(s) instantly from cache | requests: []
mutating      : button = Adding…
after mutation: [ 'Write chapter 6', 'Review chapter 6' ] | requests: [ 'POST /todos', 'GET /todos' ]
user switch   : user 1: User 1 (from cache at once; refetched in the background because staleTime is 0)
missing user  : user 404: error (User not found) | requests: [ 'GET /users/1', 'GET /users/2', 'GET /users/1',
'GET /users/404' ]
cache keys    : ["todos"] ["user",1] ["user",2] ["user",404]
```

1. **De-duplication**: `TodoList` and `TodoCount` both asked for `['todos']` — **one** request.
2. **Caching**: remounting within `staleTime` (30 s) showed the list **instantly with zero requests**.
3. **Mutations + invalidation**: `useMutation` gave `isPending` for the button; `invalidateQueries(['todos'])` marked the list stale and refetched — no manual "push the item into state".
4. **Keys with variables**: one cache entry per user ID. Back to user 1: cached name at once, then a background refetch (default `staleTime` `0`) — **stale-while-revalidate**.
5. **Errors** are a state (`status === 'error'` , `error.message`), not a crash. A browser would first retry 3 times; retries are off here.

Compared with §5.7: no `useEffect` , `ignore` flag, loading/error `useState` s, cache or refetch-after-save code; races are handled because results are stored per key.

More features (brief)

- **Optimistic updates** with `onMutate` (update the cache, return a rollback) or by rendering `mutation.variables` while pending.
- `enabled: false` for dependent queries (fetch B only when A's result exists).
- `placeholderData: keepPreviousData` for **pagination** (one page of results at a time) without flashing a spinner.
- `useInfiniteQuery` for "load more"/infinite scroll; `useSuspenseQuery` for Suspense (Chapter 9).
- **Prefetching** (`queryClient.prefetchQuery` before data is needed) on hover or in route loaders; a **DevTools** panel.

Common mistakes

- A variable left out of the key (`['user']` for every id) — users overwrite each other's cache.
- Copying query `data` into `useState` /Redux — you lose updates; read from the query, derive filtered views in render.
- Creating `QueryClient` in a component body without `useState` — a new cache every render. Create once (module level or `useState(() => new QueryClient())`).
- Expecting `isPending` during background refetches — use `isFetching` .

In the interview

30-second answer: "Server state is a cache of data someone else owns, so it needs fetching, caching, de-duplication, refetching and invalidation — TanStack Query does that. `useQuery({ queryKey, queryFn })` returns status, data and error; the key identifies the cache entry and must include every variable. `staleTime` controls freshness, `gcTime` how long unused data stays. Writes go through `useMutation` , and on success I invalidate the affected keys so they refetch. With it, most 'global state' disappears from Redux or context."

- *`isPending` vs `isFetching` ?* — `isPending` : no data yet. `isFetching` : any request in flight, including background refetches.
- *`staleTime` vs `gcTime` ?* — Fresh vs stale (drives refetch triggers) vs how long unused data stays in memory.


TL;DR

TanStack Query = server-state cache. `useQuery({ queryKey: [...vars], queryFn })` , `useMutation` + `invalidateQueries` . Defaults: `staleTime` `0`, `gcTime` 5 min, 3 retries, refetch on focus/reconnect/mount.

6.10 Choosing — comparison and decision flow

	Context (+ reducer)	Redux Toolkit	Zustand	TanStack Query
For	Rarely-changing shared values; small feature stores	Large shared client state, strict conventions	Shared client state with little ceremony	**Server** state
Provider needed	Yes	Yes	No	Yes (`QueryClientProvider`)
Selective re-renders	No (all consumers)	Yes (`useSelector`)	Yes (selectors)	Per query/key
Async	Your code	Thunks, RTK Query	Plain async actions	Built in (it's the whole point)
DevTools	React DevTools only	Redux DevTools (time travel)	Via `devtools` middleware	TanStack Query DevTools
Outside React	No	`store.dispatch/getState`	`getState/setState`	`queryClient` methods
Extra bundle size	None	Moderate (RTK + React Redux)	Very small (about 1 kB gzipped)	Moderate

Other names: **Jotai** (atoms composed together), **MobX** (observable objects that notify listeners, with automatic tracking), **Valtio** (proxy-based mutable state), **XState** (state machines), **SWR** (Vercel's server-state library, similar to TanStack Query), **Recoil** (Meta's atom library — its repository was archived, i.e. made read-only and unmaintained, in January 2025; don't start new projects with it).



In the interview

30-second answer: "I start by classifying the state. Server data goes into a query cache like TanStack Query; shareable UI state like filters goes in the URL; local state stays in components with `useState` / `useReducer` ; rarely-changing app-wide values use context. Only frequently-changing shared client state needs a store — Zustand for simplicity, Redux Toolkit when the team benefits from its structure and tooling."

6.11 Putting it together — a bookshop

`code/shop.jsx` puts each kind of state in its natural home:

State	Home	Why
Book catalogue	TanStack Query (`['books']`)	Server data: cached, shared by `Catalog` and `Cart` with one request
Cart lines	Zustand store	Shared client state, updated often, needed in several places, cleared from outside React after checkout
Currency	Context	App-wide, changes rarely
Genre filter	`useState` in `Catalog`	Local UI state
Visible books, cart items, totals	Computed during render	Derived

Key parts (full file in `code/shop.jsx`):

```
// ---- Zustand: cart store (usable from any component, no provider)
export const useCart = create((set) => ({
  lines: {},                                                  // { [bookId]: qty }
  add: (id) => set((s) => ({ lines: { ...s.lines, [id]: (s.lines[id] ?? 0) + 1 } })),
  remove: (id) => set((s) => { const { [id]: _, ...rest } = s.lines; return { lines: rest }; }),
  clear: () => set({ lines: {} }),
}));

// ---- Context: currency formatter chosen once at the top
const CurrencyContext = createContext({ code: 'USD', locale: 'en-US' });
function useMoney() {
  const { code, locale } = useContext(CurrencyContext);
  return (n) => new Intl.NumberFormat(locale, { style: 'currency', currency: code }).format(n);
}

// ---- TanStack Query: the catalog
function useBooks(fetchBooks) {
  return useQuery({ queryKey: ['books'], queryFn: fetchBooks, staleTime: 60_000 });
}

function Catalog({ fetchBooks }) {
  const [genre, setGenre] = useState('all');                  // local UI state
  const { data: books, isPending, isError, error } = useBooks(fetchBooks);
  const add = useCart((s) => s.add);                          // select just the action -> never re-renders for
cart changes
  const money = useMoney();
  if (isPending) return <p className="muted">Loading catalog…</p>;
  if (isError) return <p role="alert">{error.message}</p>;
  const visible = genre === 'all' ? books : books.filter((b) => b.genre === genre);   // derived
  // ... genre buttons + list with "Add" buttons
}

function Cart({ fetchBooks }) {
  const { lines, remove, clear } = useCart(useShallow((s) => ({ lines: s.lines, remove: s.remove, clear: s.clear
})));
  const { data: books = [] } = useBooks(fetchBooks);          // same key -> same cache, no extra request
  const money = useMoney();
  const items = books.filter((b) => lines[b.id]).map((b) => ({ ...b, qty: lines[b.id] }));
  const total = items.reduce((sum, i) => sum + i.qty * i.price, 0);   // derived
  // ... list with remove buttons, total, "Empty cart"
}

// Shop = <QueryClientProvider client={queryClient}><CurrencyContext value={currency}> <Catalog/> <Cart/> …
```

(`Shop` takes `queryClient = new QueryClient()` as a default parameter — fine for an app root that renders once; in a re-rendering component use `useState(() => new QueryClient())` .)

`code/08_bookshop.jsx` drives it with a euro/German-locale currency from context:

```
start      : Loading catalog…
catalog    : 4 books | catalog requests: 1 (Catalog and Cart share one query)
fiction    : [ 'The Hobbit', 'Dune' ]
cart       : Cart (3) -> 1 × The Pragmatic Programmer; 2 × Dune | Total 72,00 €
store      : {"b4":2,"b1":1}
removed    : 1 × The Pragmatic Programmer | Total 42,00 €
cleared    : Your cart is empty.
```

One catalogue request served both panels; the filter was purely local; money formatting followed the context (`72,00 €`); the cart was cleared from outside React, as a checkout callback would.

In the browser (`code/shop.html` , styles in `shop.css` ; the entry seeds the cart store with two titles, default USD):




Figure 6.1 — The bookshop. The catalogue comes from the TanStack Query cache, the cart from a Zustand store seeded with `useCart.setState` before rendering, and the prices are formatted using the currency context.

Design notes: **no Redux, no Effects** (server data in the query cache; the store holds only client-owned data); **selectors keep renders narrow** (`Catalog` selects only `add`); **everything countable is derived**.

Chapter 6 TL;DR

Idea	Remember
Kinds of state	Local, complex local, shared client, server, URL, form, derived — each has a home
`useReducer`	Pure `(state, action) => next`; dispatch events; test without React
Context	`createContext(default)`, `<Ctx value>`, `useContext` / `use`; nearest provider wins
Context performance	All consumers re-render on value change; memoise value, split state/actions, split by concern
Reducer + context	Provider + two contexts + `useX()` Hooks that throw outside the provider
Redux Toolkit	`createSlice` (Immer), `configureStore`, `useSelector` / `useDispatch`, thunks, `createSelector`, RTK Query
Zustand	`create((set, get) => …)`; selectors; `useShallow`; no provider; `persist` / `devtools`
TanStack Query	`useQuery({ queryKey, queryFn })`, `useMutation` + `invalidateQueries`; `staleTime` vs `gcTime`
Choosing	Server → query cache; shareable → URL; local → `useState`; rare global → context; busy global → Zustand/RTK

Next: Chapter 7 — Custom Hooks and the Rules of Hooks.