Chapter 22 — Revision: Cheat Sheets & Glossary

> **What this chapter is.** One-page summaries of the whole handbook — the LLD (low-level design: the classes and code inside one program) answer framework (Ch 1), OOP and UML (Ch 2–3), SOLID, principles and clean code (Ch 4–6), the 24 smells (Ch 7), all 23 GoF patterns plus extras (Ch 8–11), the concurrency toolbox (Ch 12–13), a map of every case study (Ch 14–21), machine-coding and edge-case checklists, and a glossary of about 200 terms.
>
> Nothing here is new: every row summarises a section of Chapters 1–21, and the right-hand column says where to find the full explanation. No code.

How to read the references. "§12.17" means section 12.17. Chapters 5 and 6 number their sections from 1 inside the chapter, so "Ch 5 §13" means section 13 of Chapter 5 (Fail Fast). Chapters 16, 17 and 19 have unnumbered case studies, so they are referenced by name, for example "Ch 16 · Car Rental".

New to a term? Every technical word in the tables, from `API` and `JVM` to `TTL` and `SKU`, is defined once — in its cheat-sheet row or in the glossary (22.11). A **TL;DR** ("too long; didn't read") heading marks a short summary.

22.1 How to revise

In 15 minutes (the morning of the interview)

Minutes	Read	Why
0–3	22.2 (the framework)	You will use it in the first minute of the interview
3–6	22.4 (SOLID one-pager) and the relationship table in 22.3	The two things asked about most often by name
6–10	"Which pattern?" table in 22.7	Patterns should come from a signal, not from memory
10–13	Concurrency cheat sheet and deadlock checklist in 22.8	Every booking/inventory problem has a race
13–15	The row(s) of 22.9 for the problems you expect	One sentence per problem: entities, pattern, the atomic step

The night before (about 2 hours)

1. **Read 22.2–22.8 slowly** (45 min). For each table row, say out loud *one example from the handbook*. If you cannot, open the referenced section.
2. **Pick three case studies** from 22.9 you have not practised recently (45 min). For each: write requirements, list classes, draw the class diagram, and name the one hard method, without looking. Then compare with the chapter's TL;DR.
3. **Scan the glossary** (22.11) and mark any term you cannot explain in one sentence (20 min). Read those sections only.
4. **Stop.** Sleep matters more than one more pattern.

Common mistakes when revising

- Re-reading chapters instead of **recalling** first and then checking. Recall is what the interview tests.
- Memorising all 23 patterns equally. Six come up in almost every round (22.7): Strategy, Factory, Observer, State, Singleton, Builder.
- Skipping the "when *not* to use it" column. Interviewers ask "would you always do that?" (§4.13).

22.2 The LLD interview answer framework (one page)

Source: Chapter 1 (§1.2, §1.4–§1.10, §1.12, §1.14).

TL;DR

Clarify → requirements → use cases → entities → relationships → class diagram → key flows → patterns/SOLID → code → edge cases/concurrency → extensions. Say each step out loud as you enter it.

The eleven steps

#	Step	Ask yourself	Output
1	Clarify	Who uses it? Single site or many?	Shared understanding
2	Requirements	Functional? Non-functional (thread-safe, extensible, in-memory)? **Out of scope?**	8–12 numbered lines + out-of-scope list
3	Use cases	What can each actor do?	Actor → use-case list
4	Entities	Which nouns hold state or behaviour? Which are just values?	Classes, one sentence each
5	Relationships	Uses / knows / has / owns / is-a? How many?	Typed lines with multiplicity
6	Class diagram	Fields, key methods, interfaces, enums	UML class diagram
7	Key flows	Steps of the 2–3 main use cases; lifecycle of the core object	Sequence / activity / state diagram
8	Patterns & SOLID	A rule that varies? A lifecycle? Many listeners? Two reasons to change?	1–2 named patterns + one rejected
9	Code	Interfaces, enums, models, services, driver	Running code for the main flows
10	Edge cases & concurrency	Bad input? Full? Two users, one seat?	Validation, exceptions, locks
11	Extensions	"What if X is added?"	Short answers, maybe one class

Time budgets

45-minute OOD round		**90-minute machine-coding round (write runnable code)**	
Clarify requirements	5–8 min	Read, requirements, assumptions	5–10 min
Actors and use cases	3–5 min	Model: entities, enums, service interfaces	10–15 min
Find the classes	8–10 min	Core flow end to end	30–40 min
Connect the classes	8–10 min	Remaining features, validation, edge cases	15–20 min
Write the code	12–15 min	Polish, one extension point, demo	5–10 min
		Buffer	5 min (never zero)

Rule of thumb: roughly **a quarter of the hour goes before you name a class**, and in machine coding you **get something running by the halfway mark** (§1.2).

Finding classes (§1.6)

- **Nouns → candidate classes; verbs → methods.** A verb with no class to live on means a class is missing.
- Cut candidates with five tests: is it a **value**? the **same thing** under another name? does it have **changing state**? does anything **call** it? does it differ in **behaviour or only data**?
- **Different data → field or enum. Different behaviour → class.**
- One sentence per class, **no "and"**. Put each method where its data is (Information Expert).
- Beginners most often forget the **record-keeping class** (ticket, loan, booking) and the **rule class** (rate, strategy).

What the interviewer judges (§1.2)

1. Did you **bound** the problem? 2. Does each class have **one job** you can say in a sentence? 3. Are the **relationships** right? 4. Does the **code match the diagram**? 5. Can you explain a **trade-off** (the choice and the rejected option)?

Machine coding adds: does it **run**, is it **modular**, **readable**, does it **handle bad input**, and (senior roles) is shared state **thread-safe**.

Code habits interviewers notice (§1.10)

Habit	Instead of
Pass time in (`long nowMinute` , `Instant now` , injected `Clock`)	Reading the clock inside logic
Money as `BigDecimal` from strings, or whole cents in a `long`	`double` (0.1 + 0.2 ≠ 0.3)
`IllegalArgumentException` / `IllegalStateException` / a custom exception	Silent failure or error codes
`Optional` when "not found" is normal	Returning `null`
`private final` fields	Public mutable fields
Domain names (`ParkingTicket`)	`Manager` , `Helper` , `Data2`

Skeleton: **Models** → **Repositories** → **Strategies** → **Services** → **Driver** (§1.10). The driver is the `main` class that feeds sample commands to the services and prints the results.

In the interview

> **30-second answer** (from §1.14): "I clarify and write 8 to 12 requirements with an out-of-scope list, list actors and use cases, pick classes from the nouns and give each one responsibility, connect them and draw a class diagram, sketch the key flow, run a quick SOLID check and pick one or two patterns where the signal is clear, then code the two or three core flows, handle edge cases and concurrency, and finish with extensions and trade-offs."

Common mistakes (§1.14)

Mistake	Fix
Coding in minute two	8–13 minutes on requirements and actors first
No out-of-scope list	Write it down and agree it
One subclass per value (`CompactSpot` , `LargeSpot`)	Different data → field/enum
God class (`ParkingLotManager`)	One sentence per class; split on "and"
Inheritance for reuse ("Car extends Engine")	Composition
Pattern stuffing	One or two patterns, each with its signal
All twelve classes at equal depth	Two or three flows fully
Ignoring two users on one resource	Lock or atomic operation on the shared state
Non-running code in machine coding	Thin end-to-end path running by halfway

---

22.3 OOP & relationships cheat sheet

Source: Chapter 2 (OOP) and Chapter 3 (relationships and UML).

The four pillars (§2.3–§2.6)

Pillar	One line	Java tools	Smell when missing
Encapsulation (§2.3)	Data is private; only the owning class's methods change it, and they enforce the *invariants*	`private` fields, no setters, validation in constructors	Public fields; setters that break invariants
Abstraction (§2.4)	Expose only what callers need; hide how	Interfaces, abstract classes, small public API	Callers reach into internals
Inheritance (§2.5)	Child reuses and specialises parent — **only when "child is a parent" is truly correct**	`extends`, `super`, `@Override`	Subclass refuses or throws on parent methods
Polymorphism (§2.6)	One call, different behaviour per object; removes type switches	Overriding + dynamic dispatch	`switch` / `instanceof` chains on type

Encapsulation vs abstraction: hiding *data* behind rule-enforcing methods vs hiding *complexity* behind a minimal set of operations (Ch 2 self-check).

Other OOP facts worth one line each

Topic	Remember	Where
Overloading vs overriding	Compile time, by declared parameter types vs run time, by the actual object. Fields and `static` methods are not polymorphic (statics are hidden, not overridden)	§2.7
`this`, `static`, `final`	Current object; one per class; cannot be reassigned/overridden/extended	§2.2
Interfaces	Contracts; can have `default`, `static`, `private` methods; a functional interface has one abstract method (usable with lambdas)	§2.8
Enums	Fixed sets with fields and behaviour ("which spot types fit a truck" lives on `VehicleType`)	§2.10
Composition over inheritance	Avoids fragile base classes; allows run-time swapping	§2.11, Ch 5 §6
`equals` / `hashCode`	Equal objects must have equal hash codes; override both or hash collections break	§2.12
Immutability & records	Final class, private final fields, no setters, defensive copies. Records are only **shallowly** immutable — copy collections in the compact constructor	§2.13
Access modifiers	Who can see a member: `public`, `protected`, package-private (same package only), `private`; default to `private`	§2.14
Generics	Type parameters (`List<T>`) for type-safe reusable infrastructure; **PECS**: producer `extends`, consumer `super`	§2.15
Coupling & cohesion	Low coupling (between classes), high cohesion (inside a class)	§2.16
OOA → OOD → OOP	What the problem is → how, with objects → code. Connections that carry data become objects	§2.17

Abstract class vs interface (§2.9)

	Abstract class	Interface
Instantiable?	No	No
Instance fields (state)	Yes	No (only `public static final` constants)
Constructors	Yes	No
Method bodies	Any	`default`, `static`, `private` only
How many per class	**One** (`extends`)	**Many** (`implements`)
Relationship expressed	"is a" (shared identity and state)	"can do" (capability / role)
Typical use	Shared state + partial implementation for a close family (Template Method)	Contracts, roles, strategies, test seams

Rule of thumb: start with an interface; add an abstract class underneath when implementations share real state or a fixed algorithm (JDK: `List` + `AbstractList` + `ArrayList`).


The six relationships (§3.2–§3.8)

Weakest to strongest coupling: **dependency, association, aggregation, composition, realization, generalization** (§3.16).

Relationship	Phrase	UML line	Java shape	Lifetime	Example
Dependency (§3.5)	A *uses* B	dashed, open arrow → B	B as parameter / local / return / static call	none	`CheckoutService` uses `PaymentGateway`
Association (§3.2)	A *knows* B	solid line (arrow for one-way)	field of type B, created elsewhere	independent	`Order` → `Customer`
Aggregation (§3.3)	A *has* B, parts live on	solid, hollow ◇ at A (the whole)	field/collection, parts passed in	B outlives A	`Airline` ◇— `Aircraft`
Composition (§3.4)	A *owns* B	solid, filled ◆ at A (the whole)	A creates B, hides it, B not shared	B dies with A	`ParkingFloor` ◆— `ParkingSpot`
Realization (§3.7)	A *implements* B	dashed, hollow △ at B	`implements`	—	`EmailNotifier` ⇢ `Notifier`
Generalization (§3.6)	A *is a* B	solid, hollow △ at B	`extends`	—	`CardPayment` → `Payment`

Choosing, in order (§3.8): interface A promises to fulfil → realization. Substitutable with no refused methods → generalization. Not kept in a field → dependency. Part that dies with the whole → composition. Part that outlives it → aggregation. Otherwise → association.

UML arrow legend (Mermaid)



Mermaid	Meaning
`A ..> B`	A depends on B
`A --> B`	A associated with B, navigable A to B
`A -- B`	association (both ways / unspecified)
`A o-- B`	aggregation, A is the whole
`A *-- B`	composition, A is the whole
`B <|.. A`	A realizes interface B
`B <|-- A`	A extends B
`A "1" *-- "1..*" B`	with multiplicities

Multiplicity → code (§3.17): `1` required field; `0..1` `Optional`/nullable; `1..*` non-empty collection checked in the constructor; exact numbers checked in constructors. Visibility: `+` public, `-` private, `#` protected, `~` package.

UML diagrams in the interview (§3.9–§3.15)

Diagram	Use it for	Budget in 45 min
Use case (§3.10)	Scope: actors + what each does. «include» = always; «extend» = sometimes	Usually spoken, 3–5 min
Class (§3.11)	**The answer.** 10–15 boxes, every line typed, with multiplicity	Always drawn, 10–15 min
Sequence (§3.12)	Call order between objects (3–4 objects, 6–8 messages)	One behaviour diagram only
Activity (§3.13)	A flow that branches; fork/join for parallel steps	"
State machine (§3.14)	One object's lifecycle; transition label `event [guard] / action`	"

UML has 14 diagram types: 7 structural, 7 behavioural (§3.9).

Common mistakes

- Diamond at the wrong end (it goes at the **whole**); triangle at the wrong end (it goes at the **parent/interface**) (§3.8).
- Lines without type or multiplicity (§3.8).
- Inheritance used to share data; subclasses that only pass a constant to `super` → one class with an enum field (§3.16).

22.4 SOLID one-pager

Source: Chapter 4 (§4.2, §4.7–§4.10, §4.12–§4.15), smells from Chapter 7 (§7.4).

TL;DR

SOLID = five names for the ways code becomes painful to change. **Use them to diagnose, not as a checklist**, apply a fix when a real change asks for it, and always say what the fix costs.

Principle	One-line rule	Smell that signals a violation	Fix	Patterns that help
S — Single Responsibility (§4.2)	A class should have one reason to change (one actor asks for its changes)	The responsibility sentence needs an "and"; *Divergent Change*, *Large Class*	Split by actor (Extract Class); each new class needs a name that stands alone	Command, Proxy, Decorator (each concern in its own class)
O — Open/Closed (§4.7)	Add new behaviour by adding code, not by editing working code	A `switch` / `if` chain over a type; *Repeated Switches*, *Shotgun Surgery*	Put the part that *has* varied behind an interface; add variants as classes (Replace Conditional with Polymorphism)	Strategy, Template Method, Decorator, Factory Method, Observer, Command, Visitor
L — Liskov Substitution (§4.8)	A subtype must be usable anywhere its parent is expected	Subclass throws, does nothing, or refuses a parent method; *Refused Bequest*	Better parent, a narrower interface, or composition (Replace Subclass with Delegate)	Composite, Null Object
I — Interface Segregation (§4.9)	No client should depend on methods it does not use	Empty method bodies or `UnsupportedOperationException` in implementers; fat interfaces	Split into **role interfaces**, one per kind of caller	Adapter
D — Dependency Inversion (§4.10)	Depend on abstractions, not concrete details; the policy owns the abstraction	A high-level class does `new` of (or names) a low-level one; cannot test without the real database/provider	Inject an interface owned by the high-level class; `main` wires the details	Strategy, Factory Method / Abstract Factory, Adapter, Observer

LSP in detail (§4.8, TL;DR): a subclass must accept at least as much, promise at least as much, keep invariants and history, and throw nothing new. Square/Rectangle is worse than `Penguin.fly()` throwing because it fails **silently** (wrong area, no error).

Five-minute pass over your diagram (§4.13, §1.8)

Run S → O → L → I → D over the diagram you just drew. **Two findings is a good pass; five means rework; zero means you did not look.** S and O earn the most credit: O is what interviewers probe with a late requirement ("what if trucks are charged differently?" → "add a class").

Related ideas (§4.3–§4.6, §4.14)

Idea	Question it asks
SRP	How many actors can ask this class to change?
Cohesion	Do the parts of this class belong together?
Coupling	How much does A depend on B?
Separation of Concerns	Is each area of work in its own module?
SRP vs ISP	SRP splits **classes** (guards the worker); ISP splits **interfaces** (guards the caller)
DIP vs DI vs IoC	DIP = principle (depend on abstractions); DI = technique (pass dependencies in); IoC = the broader idea that a framework calls your code; IoC containers (e.g. Spring) perform DI

Common mistakes: over-engineering (§4.15)

Warning sign	Principle misapplied	Do instead
`XHelper`, `XUtils`, `XManager2` after a split	SRP	Split by actor; names must stand alone
Six small classes that always change in the same commit	SRP over-split	Merge them back
Interface + factory + registry for one implementation	OCP (*Speculative Generality*)	Write the `if`; refactor at the second or third case (rule of three)
A subclass that "works" by silently doing nothing	LSP	Better parent or composition
One interface per method	ISP over-split	Group by caller into role interfaces
An interface in front of stable `String`-like classes	DIP	Invert only volatile dependencies
A DI container for a 200-line program	DIP	Wire by hand in `main`

YAGNI is the counterweight: SOLID says *what* a good seam looks like; YAGNI says *when* to cut it.

In the interview

Say **observation → cost → fix → price of the fix**, and describe before you label: "`Reporting` implements nine methods but calls two — an interface segregation problem" (§4.13).

22.5 Other design principles and Clean Code rules

Other principles (Chapter 5)

Principle	One-line idea	Smell it fixes	Key Java tool	Where
DRY	Each piece of knowledge has one authoritative home	Duplicated rules drifting apart	Value objects, constants, methods	Ch 5 §1
KISS	Choose the simplest design that works	Over-engineering	Plain code, `switch` expressions	Ch 5 §2
YAGNI	Don't build features before they are needed	Speculative Generality	Delete unused code	Ch 5 §3
Law of Demeter	Only talk to your immediate friends	Train wrecks `a.getB().getC().do()`	Intent-revealing delegate methods	Ch 5 §4
Tell, Don't Ask	Tell objects what to do; don't pull their data out and decide for them	Anemic model, Feature Envy	Command methods on the owner	Ch 5 §5
Composition over inheritance	Prefer "has-a" to "is-a" for reuse	Fragile base class	Forwarding / decorators	Ch 5 §6
Program to an interface	Depend on supertypes, choose the concrete class once at the edge	Hard-wired concrete dependencies	Interfaces + DI	Ch 5 §7
Encapsulate what varies	Isolate the part that changes behind an interface	Growing type switches	Strategy, lambdas	Ch 5 §8
Loose coupling	Interacting objects know little about each other	God orchestrators	Observer, events, DI	Ch 5 §9
Hollywood Principle / IoC	"Don't call us, we'll call you" — the framework owns the flow	Duplicated skeletons	Template Method, callbacks, DI	Ch 5 §10
Separation of Concerns	Each part handles one concern	Spaghetti code	Layers, MVC	Ch 5 §11, §4.5
Least Astonishment	Do what the name promises and nothing more	Hidden side effects	Honest names, `Optional`	Ch 5 §12
Fail fast	Detect problems early and loudly	Distant `NullPointerException`s	Guard clauses, `requireNonNull`	Ch 5 §13
Immutability	Objects never change after creation	Aliasing, races	Records, `List.copyOf`	Ch 5 §14
Design by Contract	Preconditions (caller), postconditions (method), invariants (always)	Magic error values	Checks at method entry/exit	Ch 5 §15
GRASP	Larman's nine guidelines for "which class should do this?"	God classes	Expert, Creator, Controller…	Ch 5 §16
Domain-Driven Design	Model the business: bounded contexts, entities vs value objects, small aggregates, domain events, repositories per root	Anemic model, big ball of mud, primitive obsession	Records as value objects, aggregate roots, events + outbox	Ch 5 §17

GRASP in one line each (Ch 5 §16.1–§16.9):

Guideline	Rule
Information Expert	The class with the data does the work
Creator	The class that contains, records or has the initial data for A creates A
Controller	A thin non-UI object receives each system event and delegates
Low Coupling	Choose the design with fewer, more stable dependencies
High Cohesion	Each class does one related set of things
Polymorphism	Let each type implement the varying behaviour; don't switch on types
Pure Fabrication	Invent a helper class (e.g. a repository) when no domain class is a clean home
Indirection	Put a middleman between things that shouldn't know each other
Protected Variations	Wrap what's unstable behind a stable interface

Tensions to mention (Ch 5 summary): DRY vs loose coupling (sharing code couples its users); YAGNI vs encapsulate-what-varies (abstract only real or clearly predicted variation); Law of Demeter vs cohesion (too many delegates → Middle Man); Information Expert vs SoC (domain objects compute, fabrications persist).

Clean Code rules checklist (Chapter 6)

Area	Rule of thumb	Where
Names	Reveal intent; pronounceable; searchable; one word per concept; code reads like the requirement	Ch 6 §1
Functions	Small; do one thing; one level of abstraction; top-down (stepdown); ≤ 2–3 arguments; **no flag arguments**; no hidden side effects; commands *or* queries (CQS); exceptions, not error codes	Ch 6 §2
Comments	Say it in code; comment only the *why*, warnings, legal text, public contracts; delete commented-out code	Ch 6 §3
Formatting	Newspaper order (headline first); related things close; one automated team style	Ch 6 §4
Objects vs data structures	Objects hide data and expose behaviour; data structures expose data; no hybrids; no train wrecks	Ch 6 §5
Error handling	Unchecked exceptions with context; wrap vendor exceptions; empty collections / `Optional` / special case instead of `null`; never pass `null`; always clean up	Ch 6 §6
Boundaries	Keep third-party code behind your own interfaces; learn it with tests	Ch 6 §7
Unit tests	Three laws of TDD (Test-Driven Development: write a failing test first); one concept per test; Given–When–Then; **F.I.R.S.T.** (Fast, Independent, Repeatable, Self-validating, Timely)	Ch 6 §8
Classes	Small by responsibility; cohesive; open for extension; depend on abstractions	Ch 6 §9
Systems	Build objects in one place (composition root) and inject them; cross-cutting concerns in proxies/aspects	Ch 6 §10
Simple design	Beck: passes the tests → reveals intention → no duplication → fewest elements (*Clean Code* swaps the middle two)	Ch 6 §11
Concurrency	Separate concurrency code; share as little as possible; use the library; keep locks small; plan shutdown	Ch 6 §12
Smells	The C/E/F/G/J/N/T heuristics catalogue as a review vocabulary	Ch 6 §14
Code review	Correctness → design → readability → tests → security → performance → operability; automate style; small PRs (pull requests: proposed changes sent for review)	Ch 6 §15
Error strategy	Classify, translate at boundaries, retry only transient + idempotent with backoff, one global handler that logs once	Ch 6 §16
Testing strategy	Many unit, some integration, few E2E (end-to-end, whole-system); right test double; verify state over interactions; don't mock what you don't own	Ch 6 §17

Boy Scout Rule: leave the code a little cleaner than you found it (Ch 6 intro).

22.6 Code smells → refactorings (all 24)

Source: Chapter 7 (§7.2 smells, §7.3 catalogue, §7.4 lookup table). ***Bold*** *= the usual first move.*

#	Smell	Signal (one line)	Group	Refactorings that cure it
1	Mysterious Name (§7.2.1)	Name doesn't say what it does/holds (`data`, `proc()`, `Manager`)	2nd-ed extra	**Change Function Declaration**, Rename Variable, Rename Field
2	Duplicated Code (§7.2.2)	Same structure in more than one place	Dispensables	**Extract Function**, Slide Statements, Pull Up Method
3	Long Function (§7.2.3)	You want a comment to explain a block	Bloaters	**Extract Function**, Replace Temp with Query, Introduce Parameter Object, Preserve Whole Object, Replace Function with Command, Decompose Conditional, Replace Conditional with Polymorphism, Split Loop
4	Long Parameter List (§7.2.4)	Many parameters, same types, boolean flags	Bloaters	Replace Parameter with Query, **Preserve Whole Object**, **Introduce Parameter Object**, Remove Flag Argument, Combine Functions into Class
5	Global Data (§7.2.5)	Readable and writable from anywhere (incl. mutable singletons)	2nd-ed extra	**Encapsulate Variable** (then shrink its scope)
6	Mutable Data (§7.2.6)	Shared data changed after creation	2nd-ed extra	**Encapsulate Variable**, Split Variable, Slide Statements, Extract Function, Separate Query from Modifier, Remove Setting Method, Replace Derived Variable with Query, Combine Functions into Class/Transform, Change Reference to Value
7	Divergent Change (§7.2.7)	One class changed for many different reasons (SRP)	Change Preventers	**Split Phase**, Move Function, Extract Function, **Extract Class**
8	Shotgun Surgery (§7.2.8)	One change forces many small edits in many classes	Change Preventers	**Move Function**, **Move Field**, Combine Functions into Class/Transform, Split Phase, Inline Function, Inline Class
9	Feature Envy (§7.2.9)	Method uses another class's data more than its own	Couplers	**Move Function**, Extract Function
10	Data Clumps (§7.2.10)	Same group of values always travel together (`startDate, endDate`)	Bloaters	**Extract Class**, **Introduce Parameter Object**, Preserve Whole Object
11	Primitive Obsession (§7.2.11)	Money as `double`, status as `String`	Bloaters	**Replace Primitive with Object**, Replace Type Code with Subclasses, Replace Conditional with Polymorphism, Extract Class, Introduce Parameter Object
12	Repeated Switches (§7.2.12)	The *same* switch on a type code in several places	OO Abusers	**Replace Conditional with Polymorphism**
13	Loops (§7.2.13)	Classic loop that filters/maps/aggregates	2nd-ed extra	**Replace Loop with Pipeline**
14	Lazy Element (§7.2.14)	A class/function that doesn't pull its weight	Dispensables	**Inline Function**, **Inline Class**, Collapse Hierarchy

#	Smell	Signal (one line)	Group	Refactorings that cure it
15	Speculative Generality (§7.2.15)	Hooks "we might need someday"; abstract class with one subclass	Dispensables	Collapse Hierarchy, Inline Function, Inline Class, Change Function Declaration, Remove Dead Code
16	Temporary Field (§7.2.16)	Field set only in some situations, `null` otherwise	OO Abusers	**Extract Class**, Move Function, Introduce Special Case
17	Message Chains (§7.2.17)	`order.getCustomer().getAddress().getCity()`	Couplers	**Hide Delegate**, Extract Function, Move Function
18	Middle Man (§7.2.18)	Most methods just forward to another class	Couplers	**Remove Middle Man**, Inline Function, Replace Superclass/Subclass with Delegate
19	Insider Trading (§7.2.19)	Two modules poke at each other's internals	Couplers	**Move Function**, **Move Field**, Hide Delegate, Replace Subclass/Superclass with Delegate
20	Large Class (§7.2.20)	Too many fields/methods — a God Class	Bloaters	**Extract Class**, Extract Superclass, Replace Type Code with Subclasses
21	Alternative Classes with Different Interfaces (§7.2.21)	Same job, different method names (`sendMail` vs `dispatch`)	OO Abusers	**Change Function Declaration**, Move Function, Extract Superclass
22	Data Class (§7.2.22)	Only fields and getters/setters; others manipulate it	Dispensables	**Encapsulate Record**, Remove Setting Method, Move Function, Extract Function, Split Phase
23	Refused Bequest (§7.2.23)	Subclass doesn't want inherited methods, or throws on them (LSP)	OO Abusers	Push Down Method/Field, **Replace Subclass with Delegate**, **Replace Superclass with Delegate**
24	Comments (§7.2.24)	Comment used as deodorant for unclear code	Dispensables	**Extract Function**, Change Function Declaration, Introduce Assertion

Smell family → principle violated (§7.4)

Smell family	Principle
Divergent Change, Large Class	SRP
Repeated Switches, Shotgun Surgery	OCP
Refused Bequest	LSP
Long Parameter List with flags, fat interfaces	ISP / clean function design
Global Data, Mutable Data	Encapsulation
Hard-wired `new` of concrete dependencies	DIP
Duplicated Code	DRY
Speculative Generality	YAGNI
Message Chains, Insider Trading	Law of Demeter
Feature Envy, Data Class	Tell, Don't Ask

Refactoring toward patterns (§7.6)

Smell	Refactor toward
Switch/if-chain choosing an algorithm	Strategy
Methods that check and change a status field	State
`if (x == null)` at many call sites	Null Object / Special Case
Sibling subclasses with the same skeleton	Template Method
Many confusing constructors	Factory Method / creation methods
Complex object built by many ordered calls	Builder
Undo/queueing needed; huge function with shared locals	Command
Logging/caching mixed into a core class	Decorator
Objects polling for changes; hard-coded notification	Observer
Two classes, same job, different interfaces	Adapter
Subclass explosion from feature combinations	Strategy / Decorator / Bridge
A pattern that no longer earns its keep	Remove it (Inline Class, Collapse Hierarchy)

Refactoring = changing structure without changing behaviour, in small steps, with tests as the safety net. Wear one of **two hats** at a time: adding function or refactoring (§7.1.1).

22.7 Design patterns: all 23 GoF + extras

Source: Chapters 8–11. Catalogue in §8.3; comparisons in §8.15, §9.8, §10.7, §11.6, §11.8.

Count: 5 creational + 7 structural + 11 behavioral = **23**. **Class-scoped** (inheritance) patterns: Factory Method, class Adapter, Template Method, Interpreter; almost everything else is object-scoped (composition) (§8.3).

Creational (Chapter 8)

Pattern	Intent (one line)	Use when	Java / JDK example	Commonly confused with	Where
Singleton	Exactly one instance with a global access point	There really must be exactly one (config, pool, registry)	`Runtime.getRuntime()`; Spring singleton-scoped beans	A global variable; a DI singleton scope (preferred for testing)	§8.8
Factory Method	Subclasses decide which concrete class to create via an overridable method	Shared procedure, varying product; others will add types	`Collection.iterator()`	Simple Factory (one method with a switch)	§8.10
Abstract Factory	Create *families* of related objects without naming concrete classes	Products must match; swap a whole set at once	`DocumentBuilderFactory`; JDBC `Connection`	Factory Method (one product by inheritance vs a family by composition)	§8.11
Builder	Build a complex object step by step; one validating `build()`	Many optional fields, cross-field validation, immutable result	`StringBuilder`, `HttpClient.newBuilder()`	A plain constructor (fine for a handful of required fields); telescoping constructors	§8.12
Prototype	Create new objects by copying a configured instance	Setup is expensive, or only the interface is known	Copy constructors, `ArrayList.clone()`	Memento (a snapshot to restore, not a copy to use)	§8.13

Singleton notes (§8.8, §8.17): eager, holder-class or **`enum`** (most robust: blocks duplicates made through reflection, i.e. code calling private constructors by name, or through serialization, i.e. saving to bytes and reading back); double-checked locking needs a **`volatile`** field. It is global state that hurts testing — prefer injecting one shared instance. Many case studies reject it (Ch 14 self-check).

Structural (Chapter 9)

Pattern	Intent (one line)	Use when	Java / JDK example	Commonly confused with	Where
Adapter	Convert one interface into another that clients expect	"The vendor API doesn't match ours" (after the fact)	`Arrays.asList`, `InputStreamReader`	Bridge (same shape, but Bridge is designed up front); Facade	§9.1
Bridge	Split abstraction from implementation so both vary independently	Class names with two nouns; two dimensions multiplying classes	JDBC `Connection` + drivers	Adapter; Strategy (same shape)	§9.2
Composite	Treat single objects and trees uniformly	Part-whole trees (files, menus, UI)	`java.awt.Container` is a `Component` holding `Component`s	Decorator (also wraps a component, but adds behaviour to one)	§9.3
Decorator	Add responsibilities dynamically by wrapping; same interface, stackable	"Sometimes logging, sometimes caching, sometimes both"	`BufferedInputStream`, `Collections.synchronizedList`	Proxy (same shape; Proxy *controls access*); Chain of Responsibility (in CoR someone can stop the flow)	§9.4
Facade	One simple entry point to a complex subsystem	Every caller repeats the same multi-step sequence	SLF4J `LoggerFactory`, service layers	Adapter (converts one object's interface); Mediator	§9.5
Flyweight	Share intrinsic (immutable) state across huge numbers of objects	Millions of near-identical objects	`Integer.valueOf`, `String.intern()`	Object Pool (reuses objects one borrower at a time; flyweights are shared at once)	§9.6
Proxy	A stand-in that controls access (lazy, remote, protective, caching)	It's expensive, remote or restricted	`java.lang.reflect.Proxy`, Spring `@Transactional`, Hibernate lazy load	Decorator	§9.7

Memory hooks (§9.8): Adapter *make it fit* · Decorator *add to it* · Proxy *guard it* · Facade *simplify it* · Bridge *split it* · Composite *nest it* · Flyweight *share it*.

Behavioral (Chapters 10–11)

Pattern	Intent (one line)	Use when	Java / JDK example	Commonly confused with	Where
Chain of Responsibility	Pass a request along handlers until one handles (or stops) it	Several checks, any may reject; handler not known in advance	Servlet `Filter` chain; `java.util.logging` handlers	Decorator (every layer always runs)	§10.1
Command	Turn a request into an object: queue, log, retry, undo	Undo/redo, job queues, scheduling	`Runnable` / `Callable`; Swing `UndoManager`	Strategy (Strategy = *how*; Command = *what*)	§10.2
Iterator	Traverse a collection without exposing how it is stored	Walk a collection/tree/paged API	`Iterator`, `Spliterator`, JDBC `ResultSet`	Visitor (what to do at each node)	§10.3
Mediator	Centralise communication between peers in one coordinator	Many objects interact in tangled ways; order of reactions matters	Chat servers, UI controllers; `Executor` / `Timer` are a loose fit (§10.4)	Observer (broadcast, no coordination); Facade	§10.4
Memento	Capture and restore state without breaking encapsulation	Undo, checkpoints, rollback	A `record` snapshot; DB `ROLLBACK`, Git commits (real-world)	Command undo (store actions, not states); Prototype	§10.5
Interpreter	One class per grammar rule; evaluate sentences of a small language	User-written rules/expressions	`java.util.regex.Pattern`, SpEL (Spring's expression language)	Composite (same tree); Visitor (many operations over the AST)	§10.6
Observer	Notify many dependents automatically when one object changes	An open-ended set of independent listeners	`PropertyChangeListener`, `java.util.concurrent.Flow`, Spring `@EventListener`	Mediator; pub-sub (Observer through a broker, §20.6)	§11.1
State	Behaviour changes with internal state, as if the class changed	Many states/transitions; methods repeat a `switch` on status	TCP connection (GoF's example), order lifecycles. `Thread.State` is only an enum of states, not the pattern	Strategy (same diagram; states know each other and advance themselves)	§11.2
Strategy	Make a family of algorithms interchangeable behind one interface	Several ways to do one job, chosen at run time	`Comparator`; `RejectedExecutionHandler` policies	State; Template Method; Decorator (Strategy *replaces* a rule, Decorator *wraps* one)	§11.3
Template Method	Fixed algorithm skeleton in a base class; subclasses fill in steps	Long fixed flow, a few varying steps	`AbstractList`, `InputStream.read(byte[],…)`, `HttpServlet.service()`	Strategy (Template = inheritance, one step varies;	§11.4

Pattern	Intent (one line)	Use when	Java / JDK example	Commonly confused with	Where
				Strategy = composition, whole algorithm varies)	
Visitor	Add operations to a stable set of classes without changing them (double dispatch)	Many new operations over a fixed type set (ASTs)	`javax.lang.model.element.ElementVisitor`; `FileVisitor` is named after it but is really a tree-walk callback	Iterator; in Java 21, **sealed types + pattern-matching** `switch` usually replace it	§11.5

Beyond GoF: extras you will meet

Pattern	Intent (one line)	Use when	Java / real example	Commonly confused with	Where
Simple Factory (idiom)	One `create(type)` method maps a type value to a class	Small, stable set of types chosen by config	`Calendar.getInstance()`, `EnumSet.noneOf`	Factory Method	§8.9
Object Pool	Borrow and return a bounded set of expensive objects	DB connections, limited resources	HikariCP (a database connection pool), `ThreadPoolExecutor`	Flyweight	§8.14
Null Object	A do-nothing implementation instead of `null`	`null` checks everywhere for an optional collaborator	`Collections.emptyList()`, `OutputStream.nullOutputStream()`	`Optional` (for lookups)	§11.7.1
Dependency Injection	Receive collaborators (as interfaces) through the constructor	Classes create their own collaborators; hard to test	Spring constructor injection; a hand-wired `main`	Service Locator (anti-pattern)	§11.7.2
Repository	Collection-like interface over storage	Business logic mixed with storage code	Spring Data `CrudRepository`	DAO (table-oriented)	§11.7.3
Specification	A named, combinable business rule (`isSatisfiedBy`, and/or/not)	Same rule in queries and validation; finder-method explosion	`Predicate`; Spring Data JPA `Specification`	—	§11.7.4
MVC	Separate model, view and controller (Observer + Strategy + Composite)	UI, input handling and rules tangled	Spring MVC; Swing `JTable` + `TableModel`	MVP, MVVM (relatives)	§11.7.5
Event Sourcing (lite)	Store the events; derive current state by replaying them	Full history, audit, time travel	Append-only logs	Plain audit log	§11.7.6
Architectural styles (layered, client-server, modular monolith vs microservices, event-driven, pipe-and-filter, hexagonal/clean)	Fix the shape of the *whole system*: parts, dependency direction, communication	Deciding where classes live and answering "would you split this?"	Spring layered apps; Kafka consumers; Unix pipes; ports and adapters	Design patterns (a few classes inside one part); MVC (only the UI edge)	§11.9

"Which pattern?" by problem symptom

Combined from §8.5, §8.15, §9.8, §11.8 and §7.6. Look-alikes to rule out are in each pattern's "Commonly confused with" cell above.

If you see / need…	Use
One operation, several interchangeable rules chosen at run time (pricing, matching, routing)	**Strategy**
The class to create depends on a type value; caller shouldn't know the concrete class	**Factory** (Simple Factory / Factory Method)
Products must always match as a family	**Abstract Factory**
Constructor has ~6+ arguments, many optional	**Builder**
Another one of *this*, cheaply or without knowing its class	**Prototype**
Exactly one instance must exist	**Singleton** (or DI singleton scope)
Expensive objects created and destroyed repeatedly	**Object Pool**
Existing class has the wrong interface	**Adapter**
Two dimensions multiplying classes (`WindowsButton`, `MacButton`, …)	**Bridge**
Tree of part-whole objects treated the same	**Composite**
Add behaviour in combinations without editing the class	**Decorator**
Every caller repeats the same five steps into a subsystem	**Facade**
Millions of near-identical objects	**Flyweight**
Lazy load, access control, remote, caching (same interface)	**Proxy**
A request must pass several checks; any may reject it	**Chain of Responsibility**
Undo/redo, queue, schedule, retry or log *requested actions*	**Command**
Evaluate user-written rules in a small language	**Interpreter** (+ Specification)
Walk a collection/tree/paged API without exposing structure	**Iterator**
Many objects depend on each other and the **order** of reactions matters	**Mediator**
Roll back to an earlier state without exposing internals	**Memento**
One change must reach an open-ended set of listeners	**Observer** (or a broker)
Three or more methods repeat one `switch` over a status; legal actions depend on it	**State** (or enum + guarded method for 3–4 states)
Several classes share a long fixed flow, differ in a few steps	**Template Method**
Many new operations over a stable set of types	**Visitor**, or sealed types + pattern matching
`null` checks everywhere	**Null Object** / `Optional`
Classes create their own collaborators	**Dependency Injection**
Business logic mixed with storage	**Repository**
Same rule duplicated in queries and validation	**Specification**

Three questions for the famous look-alikes (§11.8):

1. Do the alternatives reference each other? Yes → **State**. No → **Strategy** (or Bridge if chosen once at wiring).
2. Can one participant stop the flow? Yes → **Chain of Responsibility**. Everyone always runs → **Decorator**. Everyone is told, nobody stops anyone → **Observer**.
3. Does a central object decide what happens next? Yes → **Mediator**. Each listener decides for itself → **Observer**.

The six that come up in almost every round (§1.9, §8.5)

Pattern	Signal	Do not use when
Strategy	One operation, several swappable rules	Only one rule exists and nothing hints at a second
Factory	Creation depends on a type value	Only one concrete class exists
Observer	Several listeners the source should not know	A single listener the source already references
State	Behaviour depends on status; many transitions	3–4 states handled by one guarded method
Singleton	Genuinely exactly one	You just want a global handle
Builder	Many optional fields; long constructor	A handful of required fields

Common mistakes (§8.6)

Anti-pattern	Fix
God Object (one class does everything)	Split by responsibility; push behaviour to the data owners
Golden Hammer (favourite pattern everywhere)	Start from the problem's signal
Pattern overuse ("patternitis") — factories for one class, single-implementation interfaces	YAGNI: add the pattern when the second variant arrives
Singletonitis (singletons as globals)	Dependency injection
Cargo-cult patterns (structure without intent)	Name the property the pattern gives you, or drop it

In the interview

Use **one or two** patterns in a 45-minute design, placed where their signal appears, and **name one you rejected** and why (§8.5, §8.16).

22.8 Concurrency cheat sheet

Source: Chapter 12 (concepts) and Chapter 13 (classic problems).

TL;DR (§12.28)

Races come from **shared mutable state**. Make the critical section atomic, or remove sharing/mutability. Visibility needs **happens-before** edges. Prevent deadlock with **lock ordering** or **tryLock + back-off**. In LLD: name the contended resource, keep **check + claim atomic**, lock fine-grained and in order, and say what changes with many servers.

Primitive | use for | gotcha

Primitive	Use for	Gotcha	Where
`synchronized`	Making a multi-step update atomic (mutex + visibility)	Don't lock on a changing reference, a boxed value or a string literal; no slow I/O while holding it; readers must use the same lock	§12.7
`ReentrantLock`	Same as `synchronized` plus try/timed/fair locking and `Condition` s	Call `lock()` **just before** `try` , `unlock()` in `finally` ; fairness is noticeably slower	§12.8
`tryLock(timeout)`	Give up if the lock is busy; deadlock prevention with back-off	Never `unlock()` when `tryLock` returned `false` ; don't retry in a tight loop (livelock)	§12.9
`ReentrantReadWriteLock`	Many readers, few writers	Cannot upgrade read → write (self-deadlock); don't modify under the read lock; writer starvation in non-fair mode	§12.10
`StampedLock`	Read-mostly data with optimistic reads	**Not reentrant**; `validate` the stamp before using values read optimistically	§12.10
`volatile`	Visibility of a flag or a published immutable snapshot	Gives visibility, **not** atomicity: `count++` is still a race	§12.6
`AtomicInteger` / `AtomicLong` / CAS	Lock-free counters and single-variable claims	Separate `get()` then `set()` is still a race — use `compareAndSet` / `updateAndGet` ; no side effects in the lambda (may run several times); ABA → `AtomicStampedReference`	§12.15
`LongAdder`	Very hot counters (metrics)	Use instead of `AtomicLong` when contention is high	§12.15
`Semaphore(N)`	Limit concurrent access to N; signalling between threads	Release in `finally` ; don't release when `acquire` never succeeded	§12.12
`wait/notifyAll` , `Condition`	Waiting for a condition on shared state	Always `while` , never `if` (spurious wakeups); hold the monitor; `notify()` can wake the wrong thread; state change without notify = lost wakeup	§12.13
`CountDownLatch`	Wait for N events once	One-shot; `countDown()` in `finally` , `await(timeout)`	§12.14
`CyclicBarrier` / `Phaser`	N threads meet at each phase (reusable)	Fewer threads than parties → everyone waits forever	§12.14
`ConcurrentHashMap`	Shared map	`containsKey` then `put` is a race — use `putIfAbsent` / `computeIfAbsent` / `merge` ; no slow work or recursive updates inside `compute` ; no `null` keys/values	§12.16
`CopyOnWriteArrayList`	Read-mostly lists (listener lists)	Every write copies the array	§12.16
`BlockingQueue` (bounded)	Handing work between threads (producer–consumer)	Unbounded queue → no back-pressure → memory blow-up; one poison pill per consumer	§12.22
`ExecutorService` / `ThreadPoolExecutor`	Running tasks on a bounded pool	Call `shutdown()` ; `newFixedThreadPool` has an **unbounded** queue; exceptions in `submit` ted tasks are lost unless	§12.4, §12.21

Primitive	Use for	Gotcha	Where
	(separates what to run from how)	you call `get()`; tasks waiting on tasks in the same pool → thread-starvation deadlock	
Virtual threads	Lightweight JVM-managed threads (Java 21) for many blocking I/O tasks	Pinning (Java 21–23: blocking inside `synchronized`); heavy `ThreadLocal`s waste memory	§12.4, §12.24
`ForkJoinPool` / parallel streams	Splitting CPU work	Use a threshold: tiny tasks cost more to schedule than to run; subtasks must touch disjoint data	§12.26, §13.10
`CompletableFuture`	Combining async results (`thenApply`, `thenCombine`, `allOf`)	Handle errors with `exceptionally` rather than calling `get()` at every step	§12.4
`ThreadLocal`	Per-thread state (thread confinement)	Clear it (`remove()`) in pooled threads, or values leak into the next task	§12.24
Immutability / confinement	Avoiding synchronization entirely	`final List` is not immutable if the list is mutable and exposed	§12.24

Which `java.util.concurrent` class for which job (§12.26)

Read the **Use for** column of the table above as the §12.26 "I need to… → use" lookup (`java.util.concurrent` is Java's standard package of thread-safety tools). Two entries not in that table: to **stop a loop from another thread**, use a `volatile boolean` flag or `interrupt()`; for **many readers, few writers**, an immutable snapshot published through a `volatile` field is often simpler than a read-write lock.

Deadlock checklist (§12.17–§12.19)

A deadlock needs **all four Coffman conditions**; break any one and it cannot happen.

#	Condition	How to break it
1	Mutual exclusion	Lock-free/immutable data, shareable resources (read locks)
2	Hold and wait	Acquire everything at once, or `tryLock` and release everything on failure
3	No preemption	Timeouts (`tryLock(timeout)`), leases that expire
4	Circular wait	**Global lock ordering** (always lock the lower id first)

- [ ] Do I ever hold two locks? If yes, is there **one global order** (account id, seat id), with a tie-breaker for equal keys?
- [ ] Do I call a **listener, callback or another object's synchronized method while holding my lock**? Move it outside the lock.
- [ ] Do tasks in a bounded pool **wait for other tasks in the same pool**? (thread-starvation deadlock)
- [ ] Are retries randomised (**jitter**) so two threads don't back off in lockstep? (livelock, §12.18)
- [ ] Could one thread wait forever while others progress? Consider fairness (§12.19).
- [ ] Detection: a thread dump (`jstack` / `jcmd`) prints "Found one Java-level deadlock"; `ThreadMXBean.findDeadlockedThreads()`.

Deadlock vs livelock vs starvation: nobody progresses and all wait / everybody runs but nobody progresses / some progress while one never does (§12.27).

The LLD concurrency recipe (§12.25)

1. **Name the shared mutable state** (free spots, seat → owner, stock).
2. **State the invariant** ("a seat has at most one booking", "stock ≥ 0").
3. **Find the critical operation** — usually a check-then-act (*find free → assign*).

4. **Pick the smallest tool that makes it atomic:** one item → `queue.poll()`, `putIfAbsent`, `compareAndSet`; several items all-or-nothing → per-item locks **in sorted order**; across servers → DB constraints/transactions, optimistic versioning, or a distributed lock.
5. **Choose granularity:** per floor / show / SKU, not one global lock.
6. **Handle time:** holds with expiry, timeouts, idempotent retries.

Classic problems (§13.12)

Problem	Key primitive	Invariant to state
FooBar (§13.1)	2 semaphores	Exactly one permit exists across both
Zero Even Odd (§13.2)	3 semaphores	Zero dispatches; one permit circulates
FizzBuzz (§13.3)	monitor + `notifyAll`	Predicates partition 1..n
H2O (§13.4)	2 semaphores + barrier	≤ 2 H and ≤ 1 O per round
Dining Philosophers (§13.5)	ordered locks / n−1 semaphore	No circular wait
TTL cache (§13.6)	`ConcurrentHashMap` + `compute` + conditional remove	Never return or keep expired data
Striped map (§13.7)	lock array	Each bucket belongs to exactly one stripe
Blocking queue (§13.8)	lock + 2 conditions	0 ≤ count ≤ capacity; wait in loops
Bloom filter (§13.9)	atomic OR	Bits only go 0 → 1; no false negatives
Merge sort (§13.10)	Fork/Join	Subtasks touch disjoint ranges
Token-bucket rate limiter (§13.11)	lock or CAS on immutable state	Refill + take is one atomic step

Common mistakes (§12.25 and throughout Chapter 12)

- A global `synchronized` on `ParkingLot.park()` — correct, but serialises every gate.
- Checking availability with one call and booking with another (check-then-act).
- Locking seats in the order the user clicked them (deadlock between two multi-seat bookings).
- Forgetting that in-memory locks don't work across multiple app servers.
- Swallowing `InterruptedException` — rethrow, or restore the flag with `Thread.currentThread().interrupt()` (§12.3).
- Calling `run()` instead of `start()` (§12.3).

22.9 Case-study map

Source: Chapters 14–21. "Concurrency concern" is the race each chapter guards against, and "atomic step" is how.

Everyday objects (Chapter 14)

Problem	Key entities	Patterns used	Concurrency concern	Where
Parking lot	`ParkingLot`, `ParkingFloor`, `ParkingSpot`, `Vehicle`, `Ticket`, `DisplayBoard`, `SpotType` / `VehicleType` enums	Strategy (pricing, spot-finding), Factory (electric spots), Observer (boards); Singleton rejected	Two gates take one spot → atomic `pollFirst` + CAS; per-ticket lock for payment; `putIfAbsent` for plates	§14.1
Vending machine	`VendingMachine`, `Slot`, `Inventory`, `CashBox`, `Denomination`, `VendingState` + 5 states	**State** (the whole design)	`synchronized` machine; change-making by bounded coin-change DP, not greedy	§14.2
Coffee machine	`CoffeeMachine`, `Recipe`, `RecipeBook`, `IngredientStore`, `OrderResult` (sealed)	Observer (low stock), recipes as data	Two orders take the last milk → one `ReentrantLock` around check + deduct; notify outside the lock	§14.3
ATM	`Atm`, `AtmState` + 4 states, `Transaction` (sealed), `NoteHandler`, `CashDispenser`, `BankService`, `Account`	State (session), Command (transactions), Chain of Responsibility (note cassettes)	Overdraw from two ATMs → per-account lock; transfers lock in id order	§14.4
Elevator	`Elevator`, `StopList` (two sorted sets), `Door`, `Dispatcher`, `DispatchStrategy`, `Building`	Strategy (dispatch) + modes; LOOK scheduling	Per-car lock, synchronized dispatcher; tick-driven `step()`	§14.5
Traffic signal	`Intersection`, `TrafficLight`, `Phase`, `SignalState` + 5 states, `TimingPolicy`, `SafetyMonitor`	State (timed), Strategy (timing), Observer (lights)	Synchronized tick; safe with a timer thread plus emergency threads	§14.6
Shipping locker (Amazon Locker)	`LockerStation`, `Compartment`, `Booking`, `CompartmentSelector`, `PickupResult` (sealed), `LockerListener`, `LockerNetwork`	Strategy (door choice), Observer (SMS text messages), enum state machines, sealed results	Two carriers, one door → station lock around choose-and-mark; lazy expiry of holds and pickup windows; hashed single-use pickup and return drop-off codes, keypad lockout	§14.7

Booking & inventory (Chapters 15–16)

Problem	Key entities	Patterns used	Concurrency concern	Where
Library	`Book` (title) vs `BookItem` (copy), `Member`, `BookLending`, `LendingService`, `Catalog`	Strategy (fines), notifier interface; FIFO reservation queue per title	Last copy lent twice → lock member then copy (fixed order)	§15.1
Movie tickets (BookMyShow)	`Show`, `ShowSeat`, `Booking`, `SeatLockProvider`, `BookingService`, `CancellationPolicy`	Strategy (refund rule), gateway behind an interface	Book `ShowSeat`s; all-or-nothing hold with TTL → pay → atomic commit; refund if hold lost	§15.2
Concert tickets	`SeatedInventory`, `GaPool`, `SeatState` (sealed), `Hold`, `VirtualWaitingRoom`, `PurchaseLimiter`	Sealed seat states, waitlist	Extreme contention → CAS per seat, CAS counter for GA, FIFO waiting room, per-user limits, TTL holds with a reaper	§15.3
Hotel	`Hotel`, `Room`, `RoomBooking`, `Invoice`, `RoomCharge`, `Payment` subclasses, `FrontDesk`	Template Method (`RoomCharge`)	Room × night reserved atomically in `synchronized Room.tryReserve`	§15.4
Car rental	`Vehicle`, `DateRange`, `Reservation`, `Bill` / `BillItem`, `ReservationAddOn`, `PricingStrategy`	Template Method (add-ons), Strategy + Decorator (pricing), state machine	Availability is about **dates** → `Vehicle.tryBook(range)` synchronized	Ch 16 · Car Rental
Restaurant	`Menu` / `MenuSection` / `MenuItem`, `Table`, `Reservation`, `Order`, `Meal` / `MealItem`, `Kitchen`, `Check`	Observer (order ready), Strategy (chef assignment, payment), state machine	Two receptionists, one table → `Table.tryHold(time)` synchronized; listeners after the lock	Ch 16 · Restaurant
Airline	`Flight` vs `FlightInstance`, `Seat` vs `FlightSeat`, `FlightReservation`, `Itinerary`, `FareStrategy`	Strategy + Decorator (fares), Facade	Selling one seat twice → `FlightInstance.holdSeats` all-or-nothing under the instance lock	Ch 16 · Airline
Course registration	`Course` vs `Section`, `Student`, `RegistrationRule`s, `Registrar`	Chain of rules / Specification	Overselling a section → section lock inside a student lock (fixed order)	Ch 16 · Course Registration
Meeting scheduler	`Interval` (half-open), `Room` (owns a `TreeMap` calendar), `Meeting`, `Invitation`, `RoomSelectionStrategy`, `MeetingObserver`, `Recurrence`	Strategy (room ranking), Observer (invites, RSVPs)	Two organizers, overlapping times → check (`lowerEntry`) and insert under the room lock; rank then try each room; lock order meeting → room	Ch 16 · Meeting Scheduler

Games (Chapter 17)

Problem	Key entities	Patterns used	Concurrency concern	Where
Blackjack + deck	`Card`, `Deck<T>`, `Shoe`, `Hand`, `BlackjackScoring`, `PlayerStrategy`, `DealerPolicy`	Strategy (player, dealer); injected randomness	One table = one thread; shared balances need an atomic wallet service	Ch 17 · Blackjack
Chess	`Piece` (sealed) + subclasses, `SlidingPiece`, `Board`, `Move`, `Rules`, `Game`	Polymorphic pieces, Factory Method, Command + Memento (undo)	`synchronized` game so a move and a resignation don't interleave	Ch 17 · Chess
Tic-tac-toe	`Board` (row/col/diagonal counters), `Game`, `Player`, `MoveStrategy`	Strategy (players)	Many games in a `ConcurrentHashMap`; per-game lock	Ch 17 · Tic-Tac-Toe
Snake & ladder	`Board`, `Jump`, `Dice`, `Rules`, `OverflowRule`, `WinStrategy`, `Game`	Strategy (dice, overflow, win)	Each game its own `Random` and its own thread of turns	Ch 17 · Snake and Ladder
2048	`LineMerger`, `Board`, `TileSpawner`, `Game`, `Direction`	Strategy (spawner); one pure merge function	Single-threaded; `synchronized move` if UI and input threads both call it	Ch 17 · 2048
Jigsaw puzzle	`Side` (FLAT/TAB/BLANK + shape code), `Piece` (immutable), `Board` + `Placement` (piece, rotation), `PuzzleValidator`, `SolverStrategy`	Strategy (brute force vs edge-first with a side index); one placement check for players and solvers	Co-op players → `synchronized` game; solvers carry an attempt budget	Ch 17 · Jigsaw

Platforms (Chapters 18–19)

Problem	Key entities	Patterns used	Concurrency concern	Where
Stack Overflow	`Post` (sealed) → `Question` / `Answer` / `Comment`, `Member`, `Tag`, `Bounty`, `QuestionIndex`	Strategy (reputation), Observer (badges), Facade; inverted index	Two votes at once → `synchronized` post; `AtomicInteger` reputation	§18.1
Cricinfo	`Match` → `Innings` → `Over` → `Ball`, `Team`, `Playing11`, `StatQuery`	Template Method (stat queries), Observer (live pages)	Two scorers → `synchronized` match; observers in `CopyOnWriteArrayList`	§18.2
LinkedIn	`Member`, `Profile`, `SocialContent`, `ConnectionInvitation`, `ConnectionService`, `SearchIndex`, `FeedService`	State (invitation), Strategy (feed ranking, notifications), Facade	Symmetric connections → all graph changes synchronized on the service	§18.3
Facebook	`Member`, `Audience` (sealed), `PrivacyList`, `FriendService`, `VisibilityService`, `NewsFeedService`	Strategy (feed ranker), Observer (notifications)	Accept can't leave a one-way friendship → synchronized service, concurrent adjacency sets	§18.4
Amazon	`Product`, `ShoppingCart`, `Order`, `OrderLog`, `Payment`, `Shipment`, `Customer` → `Guest` / `Member`	Strategy (payment), Observer (notifications), order state machine, Facade	Last unit, two buyers → `synchronized Product.reserve`; all-or-nothing multi-line reservation	Ch 19 · Amazon
Stock brokerage + exchange	`Order` → Market/Limit/StopLoss/StopLimit, `OrderPart`, `StockLot`, `OrderBook`, `MatchingEngine`	Observer (fills), Template Method (statements), trade-price policy	Over-spending → reserved funds; one lock per symbol; price-then-time matching	Ch 19 · Stock Brokerage
Auction	`AuctionListing`, `Bid`, `BidResult`, `AuctionService`, `AuctionListener`	Observer, Specification (search), status state machine	Concurrent bids → all bid rules in one per-listing critical section; notify after unlocking	Ch 19 · Auction
Music streaming (Spotify)	`Song` / `Album` / `Artist`, `MusicLibrary`, `Playlist`, `MusicPlayer`, `PlaybackOrder`, `Recommender`	Strategy (play order, recommendations), Observer (plays), plan rules in an enum	Two devices press "next" → `synchronized` player methods	Ch 19 · Music Streaming
Food delivery (Swiggy) + FoodKart	`Restaurant`, `Cart`, `Order`, `DeliveryAgent`, `DeliveryAssignmentStrategy`, `RestaurantSelectionStrategy`	Strategy (assignment, selection, payment), Observer, order state machine	Kitchen capacity reserved atomically; riders claimed with CAS	Ch 19 · Food Delivery
Grocery store (POS, point of sale)	`Register`, `Sale`, `LineItem`, `PricingEngine`, `ItemPromotion` / `BasketPromotion`, `TaxPolicy`, `Tender` (sealed), `Receipt`, `Inventory`	Strategy (offers, tax, payment gateway), Facade (register), Observer (stock), sale state machine	Registers share stock → atomic `merge`, may go negative, edge-triggered alerts; returns claimed with `compute`	Ch 19 · Grocery Store

Pattern-driven components (Chapter 20)

Problem	Key entities	Patterns used	Concurrency concern	Where
Splitwise	`Expense`, `SplitStrategy` (Equal/Exact/Percent), `Share`, `Ledger`, `DebtSimplifier`	Strategy (splits)	One signed number per pair, one mutator; `BigDecimal`, no lost cents	§20.1
Notification service	`NotificationChannel` (abstract), channels, `SendRule`, `ChannelFactory`, `DeliveryListener`	Template Method (channels), Strategy (send rules), Observer, Simple Factory, Adapter	Rate-limit check-then-act gap; idempotency	§20.2
In-memory cache / LRU	`Cache<K,V>`, `Node`, `DoublyLinkedList`, `EvictionPolicy`, `Cache.Builder`, `ShardedCache`	Strategy (eviction), Observer (removals), Builder	One lock (a `get` is a write in LRU); listeners outside the lock; shard to scale	§20.3
Ride sharing (Uber)	`Rider`, `Driver`, `Trip`, `MatchingStrategy`, `PricingStrategy`, `SurgePricing`	Strategy ×3, Decorator (surge), trip state machine	Double-booking a driver → atomic claim (`AtomicBoolean`)	§20.4
Logging framework	`Logger`, `LogManager`, `LogRecord`, `Appender`, `AsyncAppender`, `Formatter`	Chain of Responsibility (hierarchy), Singleton (`LogManager`), Strategy (formatters), Template Method (appender), Decorator (async)	Thread-safe sinks; never block on a full queue; never crash the app	§20.5
Pub-sub	`Broker`, `Topic`, `Subscription`, `Subscriber`, `Message`	Observer through a broker	One dispatcher per subscription; ack after processing (at-least-once) → idempotent subscribers	§20.6
Rate limiter	`Limiter` (TokenBucket, FixedWindow, SlidingWindowLog/Counter), `CompositeLimiter`, `LimiterFactory`	Strategy, Simple Factory, Composite, Facade	Atomic refill-check-take; one limiter per key via `computeIfAbsent`; Redis + Lua across servers	§20.7

Machine-coding problems (Chapter 21)

Problem	Key entities	Patterns used	Concurrency concern	Where
Task management	`Task`, `TaskStatus`, `TaskService`, `TaskRepository`, `TaskFilter`	Specification (filters), Strategy (sorts), Observer, enum state machine	Per-task `synchronized`	§21.1
Digital wallet	`Wallet`, `Transaction`, `Money`, `Offer`, `WalletService`	Strategy (offers), idempotency key	Lock both wallets in a global (id) order; debit before credit; total conserved	§21.2
Event calendar (Flipkart)	`TimeSlot` (half-open), `Event`, `EventStore`, `RepresentativeSelector`, `CalendarService`	Strategy (representative), plan-then-save	Atomic check-and-book	§21.3
Coding Blox (Flipkart)	`Contest`, `Level`, `User`, `Question`, `SolveSimulator`, `CommandProcessor`	Command map, Strategy (solver, scoring)	Atomic rating update; don't run a contest twice	§21.4
PropertyHunt (ClearTrip)	`Property`, `SearchCriteria` (+ Builder), `PropertyService`	Builder + predicate list, Strategy (sort)	Synchronized mark-sold	§21.5
Ledger Co (Navi)	`Loan`, `LumpSum`, `Balance`, `InterestPolicy`, `LedgerService`	Strategy (interest), derived state, command loop	Synchronized lump sums	§21.6
Inventory management	`Product`, `Warehouse`, `StockMovement`, `AllocationStrategy`, `ReorderListener`	Strategy (allocation), Observer (edge-triggered alerts)	Overselling → lock per SKU	§21.7
Unix file search (`find`)	`Node` → `FileNode` / `DirectoryNode`, `FileFilter`, `AndFilter` / `OrFilter` / `NotFilter`, `SearchCriteria` (+ Builder), `FileSearcher`, `FindCommandParser`	Specification + Composite (filters and file tree), Builder, recursive-descent parser	Weakly consistent children map; read-only fork/join walk	§21.8

TL;DR — what every case study teaches

- **Name the real unit of inventory** (copy, show seat, room-night, vehicle-day) (Ch 15 summary).
- **Every "if free then take" is one atomic step** — a monitor, a CAS, or a conditional `UPDATE` (Ch 15 summary).
- **Put rules on the object that owns the data**; the service only orders the steps (Ch 16, Ch 20 summaries).
- **Strategy** for the rule most likely to change; **Observer** for "tell someone when it happens"; **State** (or an enum state machine) for lifecycles.
- **Inject** time and randomness; money in `BigDecimal` or integer cents; call listeners **outside** locks.

22.10 Machine-coding and edge-case checklists

Source: §21.0 (and §1.10).

Machine-coding checklist

Before coding (0–20 min)

- [ ] Read the statement twice; mark **mandatory vs bonus**; ask clarifying questions.
- [ ] Put the statement's sample input into the driver as a `List<String>` of commands.
- [ ] Ask: "Where does it need to be thread-safe?" (wallets and inventory: always yes).

- [ ] Nouns → entities, verbs → service methods. Pick the 1–2 patterns the statement begs for ("can be sorted by X or Y" → Strategy).
- [ ] Create the six packages: **model, repository, service, strategy, exception, driver**.

While coding (20–75 min)

- [ ] Implement mandatory requirements **in the statement's order**; run the driver after each one (at least every 15 minutes).
- [ ] Entities guard their own invariants (e.g. `Task.changeStatus` rejects `TODO → DONE`).
- [ ] Services return data and throw domain exceptions; **no `System.out` in services**.
- [ ] Repository = interface + `ConcurrentHashMap` implementation; IDs from an `AtomicInteger`.
- [ ] Driver = `Map<String, Consumer<String[]>>` command processor; catch domain exceptions per command, **print and continue**.

Before you stop (75–90 min)

- [ ] Edge cases and validation done (see below); custom exceptions with readable messages.
- [ ] Thread-safety where money or stock is shared; say where the lock is and why.
- [ ] Bonus only after every mandatory feature runs.
- [ ] Clean names, delete dead code, run everything once more, prepare a 2-minute walkthrough.

Rubric the interviewer uses (§21.0)

#	Criterion	How to score well
1	Working, demo-able code	Thin end-to-end path in the first hour; never finish with code that doesn't compile
2	Functional completeness	Mandatory first, in order
3	Clean models	Enums for fixed sets, records for values, classes for things that change
4	Separation of concerns	Driver → Service → Repository
5	Extensibility	New rule = new class (Strategy, Specification)
6	Edge cases & failure handling	Custom exceptions; the driver keeps going
7	Readability	Names from the statement's nouns and verbs
8	Concurrency (when asked)	Say where the lock is; demo with a thread pool if time allows
9	Tests (bonus)	A tiny `assert`-style self-check in `main` is enough

Edge-case checklist (§1.10, §21.0, case studies)

Category	Questions to ask your code
Input	`null`, empty, negative, zero, duplicate IDs, unknown IDs, invalid numbers
Ownership	Wrong user acting on someone else's object; a player moving out of turn
Capacity	Full lot, zero seats left, empty playlist, max loans reached, party larger than any table
State	Paying twice, exiting without entering, cancelling a delivered order, moving after game over, running a contest twice
Time	Exit before entry, holds/bookings expiring, part hours (round up?), an event exactly at the end instant (half-open intervals), late returns
Money	`BigDecimal` scale and rounding; no lost cents in splits; compare with `compareTo`, not `equals` (Ch 4 money note)
Concurrency	Two threads booking the same seat/spot/rider; multi-item bookings locking in sorted order; retries that must be idempotent
Failure	Payment declined after a hold; hold lost before payment → compensating refund; listener throws
Randomness	Seeded `Random` or a scripted strategy so the demo is repeatable

Common mistakes (§21.0)

All covered by the checklist above and 22.2: a 20-minute "perfect" class diagram (type enums/records first — the diagram lives in the names), one `Manager` with 15 maps, printing inside services, `double` money, crashing on the first bad command, bonus before mandatory, unseeded `Random`, and `LocalDate.now()` in logic (inject a `java.time.Clock`).

22.11 Glossary

Alphabetical; "Where" is the section with the full explanation. Besides design vocabulary it covers the everyday Java, tooling and domain words the case studies take for granted (`JVM`, `Redis`, `SKU`, `UPI` …). Terms already defined in a cheat-sheet row above (principles, smells, patterns, concurrency tools) point there instead of being defined twice. System-design terms (latency, throughput, caching, brokers, eventual consistency) go deeper in System Design Fundamentals.

Term	Plain meaning	Where
ABA problem	A value changes A → B → A, so a compare-and-swap cannot notice the change; fix with a version stamp (`AtomicStampedReference`)	§12.15
Abstract class	OOP fact — see 22.3	§2.9
Abstract Factory	Creational pattern — see 22.7	§8.11
Abstraction	OOP pillar — see 22.3	§2.4
Access modifiers	OOP fact — see 22.3	§2.14
Activity diagram	UML flowchart of a process, with decisions, swimlanes and fork/join	§3.13
Actor	Someone or something that uses the system (customer, admin, the system itself)	§1.5
Adapter	Structural pattern — see 22.7	§9.1
Aggregate (DDD)	A cluster of objects changed as one unit; only its root is reachable from outside, and the root guards the invariants	Ch 5 §17
Aggregation	UML relationship — see 22.3	§3.3
Anemic domain model	Classes with data but no behaviour; the logic lives in services that pull the data out	Ch 5 §5
Anti-corruption layer	Translation layer at a bounded context's border that keeps a foreign or legacy model out of yours	Ch 5 §17
Anti-pattern	A common "solution" that reliably causes more problems than it solves	§8.6
AOP (aspect-oriented programming)	Adding cross-cutting behaviour (logging, transactions) around many methods without editing them, usually via generated proxies	Ch 5 §11, §9.7
API	Application Programming Interface: the set of public methods (or endpoints) other code is allowed to call	§2.6, §2.14
Appender / formatter	Logging roles: an appender writes a log record somewhere (console, file); a formatter turns it into text	§20.5
Append-only log	Messages are only ever added at the end; readers track their own offset	§20.6
Assertion	A check in code or a test that a condition is true, failing loudly if it is not	Ch 6 §8
Association	UML relationship — see 22.3	§3.2
Association class	A class that holds data about a link itself (e.g. `Enrollment{grade}`)	§3.11
AST (abstract syntax tree)	The tree a parser builds from an expression or program, one node per piece of grammar	§10.6
Asynchronous vs synchronous	The caller carries on and gets the result later vs the caller waits until the work finishes	§3.12, §20.5
At-least-once delivery	A message may be delivered more than once, never lost; consumers must be idempotent	§20.6
Atomic variable	`AtomicInteger` / `AtomicLong` / `AtomicReference` — concurrency tool, see 22.8	§12.15
Atomicity / atomic operation	An operation that happens completely or not at all, with no other thread able to see it half-done	§12.5
Audit log	An append-only record of who did what and when, kept for checking later	§10.2, Ch 21

Term	Plain meaning	Where
Authentication vs authorization	Proving who you are (login, PIN) vs checking what you are allowed to do	Ch 6 §10, §14.4
Back-pressure	Slowing producers when consumers can't keep up, e.g. with a bounded queue	§12.22
BFS / DFS	Breadth-first search (visit neighbours level by level) vs depth-first search (go deep down one path, then back up)	§18.3, §21.8
`BigDecimal`	Exact decimal type used for money; build from strings, compare with `compareTo`	§1.10, Ch 4 (money note)
Big-O notation	Shorthand for how running time or memory grows with input size: `O(1)` constant, `O(log n)`, `O(n)` linear	§20.3
Blocking call	A call that makes the thread wait (for I/O, a lock or a queue) before it can continue	§12.4
Bloom filter	Probabilistic set: may say "maybe present" wrongly, never says "absent" wrongly	§13.9
Boilerplate	Repetitive code that must be written but carries no real logic (getters, `equals`, `hashCode`)	§2.13
Bounded context	Boundary inside which one domain model and one vocabulary apply consistently (often one team or service)	Ch 5 §17
Bounded queue	A queue with a fixed capacity; producers wait or are refused when it is full	§12.22
Boy Scout Rule	Clean-code rule — see 22.5	Ch 6 (intro)
Bridge	Structural pattern — see 22.7	§9.2
Broker	A middleman service that receives messages from publishers and delivers them to subscribers	§20.6
Build tool	A program (Maven, Gradle) that downloads dependencies, compiles, tests and packages the code	§3.5
Builder	Creational pattern — see 22.7	§8.12
Busy waiting (spinning)	A thread repeatedly checking a condition in a loop instead of sleeping; wastes CPU	§12.6
Bytecode	The compact instruction format `javac` produces and the JVM runs	Ch 12
Callback	A function you hand to other code so it can call you back when something happens	Ch 5 §10
Caretaker / Originator	Memento roles: the originator makes and restores snapshots; the caretaker stores them without looking inside	§10.5
Carrier thread	The real OS thread that a virtual thread runs on while it is not blocked	§12.4
CAS (compare-and-swap)	Atomic "set to new value only if it still equals the expected value"	§12.15
Chain of Responsibility	Behavioral pattern — see 22.7	§10.1
Characterisation test	A test that records what existing code does now, before you refactor it	§7.8
Checked vs unchecked exception	Checked exceptions must be declared or caught (compiler-enforced); unchecked ones (`RuntimeException` subclasses) need not be	§2.5, Ch 6 §6
Check-then-act	Read a condition, then act on it, as two steps: a race unless made atomic	§12.5, §12.25

Term	Plain meaning	Where
Circuit breaker	Stops calling a failing dependency for a while after repeated errors, then tries again carefully	Ch 5 §13
Circular wait	T1 waits for T2's lock while T2 waits for T1's; one of the four deadlock conditions	§12.17
Class	A blueprint for objects: fields plus methods	§2.2
Class diagram	UML diagram of classes, fields, methods and relationships — "the answer" in an LLD round	§3.11
Class explosion	Subclasses multiplying across two dimensions (`WindowsButton`, `MacButton`, …)	§9.2
Classpath	The list of folders and JAR files where the JVM looks for classes	§1.3
Clean code	Code whose intent is obvious to the next reader and which is easy to change safely	Ch 6 (intro)
Coarse- vs fine-grained locking	One big lock for everything (simple, slow under load) vs many small locks per item (faster, harder to get right)	§12.11
Code review	A peer reads a change before merge: correctness first, then design, readability, tests, security, performance	Ch 6 §15
Code smell	A surface symptom that usually signals a deeper design problem; not a bug by itself	§7.2
Coffman conditions	Deadlock — see 22.8	§12.17
Cohesion	How closely the things inside one class belong together; high is good	§2.16, §4.3
Coin-change DP	Finding the fewest coins (or whether change is possible) by building answers for smaller amounts first	§14.2
Collections framework	Java's built-in data structures (`List`, `Set`, `Map`, `Queue`) and their implementations	Ch 2
Command	Behavioral pattern — see 22.7	§10.2
Command–Query Separation (CQS)	A method either changes state or returns a value, not both	Ch 6 §2
Commit / rollback	Make a transaction's changes permanent vs throw all of them away	§10.5, §15.2
`Comparator` / `Comparable`	An object that orders two values from outside vs a class's own natural order (`compareTo`)	§1.9, §11.3
Compensation	Undoing a completed step with a new action (e.g. a refund) because money can't be rolled back	§15.2
Compile time vs run time	When `javac` checks and translates the code vs when the program is actually executing	§2.7
`CompletableFuture`	Concurrency tool — see 22.8	§12.4
Composite	Structural pattern — see 22.7	§9.3
Composition	UML relationship — see 22.3	§3.4
Composition over inheritance	Principle — see 22.5	§2.11, Ch 5 §6
Composition root	The one place (usually `main`) where objects are created and wired together	Ch 6 §10
Compound interest	Interest charged on the principal plus interest already added	§21.6
Concurrency	Several tasks in progress at once, possibly sharing data	§12.1

Term	Plain meaning	Where
Concurrency vs parallelism	Many tasks in progress (structure) vs many executing at the same instant (hardware)	§12.1
`ConcurrentHashMap`	Concurrency tool — see 22.8	§12.16
Condition variable	Concurrency tool — see 22.8	§12.13
Constructor	Special method that runs when an object is created and sets up its fields	§2.2
Constructor chaining	One constructor calling another with `this(...)`	§2.2
Contention	Many threads competing for the same lock or variable at once, making them wait	§12.7, §12.11
Context switch	The OS pausing one thread and resuming another on a CPU core; costs time	§12.1
Controller (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.3
`CopyOnWriteArrayList`	Concurrency tool — see 22.8	§12.16
`CountDownLatch`	Concurrency tool — see 22.8	§12.14
Coupling	How much one class depends on another's details; low is good	§2.16, §4.4
CPU	The processor; each core runs one thread at a time	§12.1
CQRS	Command Query Responsibility Segregation: separate models for writing data and for reading it	Ch 5 §17
Creator (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.2
Critical section	Code that touches shared state and must run in one thread at a time	§12.5
Cron	A schedule format (minute, hour, day…) for running a job at fixed times	§10.6
Cross-cutting concern	Behaviour needed in many places (logging, security, transactions) that doesn't belong to one class	§4.5, Ch 6 §10
CRUD	Create, Read, Update, Delete: the four basic storage operations	Ch 5 §17
CSV	Comma-separated values: a plain-text table, one row per line	Ch 5 §3
`CyclicBarrier`	Concurrency tool — see 22.8	§12.14
Daemon thread	A background thread that does not keep the JVM alive once all normal threads end	§12.4
DAO (Data Access Object)	A class that wraps the SQL for one table; closer to the database than a Repository	§11.7.3
Data Class (smell)	Code smell — see 22.6	§7.2.22
Data Clumps (smell)	Code smell — see 22.6	§7.2.10
Database transaction	A group of database changes that succeed or fail together	§12.25, Ch 15
Dead code	Code that is never run or whose result is never used; delete it	Ch 6 §13, Ch 7
Dead-letter queue	Where messages go after retries are exhausted, for later inspection	§20.6
Deadlock	Concurrency hazard — see 22.8	§12.17
Debit / credit	Taking money out of an account vs putting money in	§14.4, §21.2
Decorator	Structural pattern — see 22.7	§9.4
Deep vs shallow copy	Copying nested objects too vs sharing them with the original	§8.13
Defensive copy	Copying a mutable object passed in or handed out so outsiders can't change your internals	§2.13

Term	Plain meaning	Where
Delegation	An object handing a job to another object it holds, instead of doing it itself	§2.11, Ch 5 §6
Dependency	UML relationship — see 22.3	§3.5
Dependency injection (DI)	Pattern — see 22.7	§4.10, §11.7.2
Dependency Inversion Principle	SOLID principle — see 22.4	§4.10
`Deque` / `ArrayDeque`	Double-ended queue: add and remove at both ends; the usual Java stack and queue	§7.7
Derive, don't store	Compute counts and totals from the underlying records so they can't drift	§18.5
Design by Contract	Principle — see 22.5	Ch 5 §15
Design pattern	A named, reusable solution to a recurring design problem	§8.1
Director	Optional Builder role that runs a fixed sequence of building steps	§8.12
Distributed lock	A lock shared by several servers, kept in an external store (database, Redis)	§12.25
Divergent Change (smell)	Code smell — see 22.6	§7.2.7
Domain event	Past-tense record of a business fact (`OrderPlaced`) that other parts of the system react to	Ch 5 §17
Domain exception	A custom exception named after a business rule (`InsufficientBalanceException`)	§21.0
Domain-Driven Design (DDD)	Principle — see 22.5	Ch 5 §17
Double dispatch	Choosing a method by both the element's and the visitor's type (Visitor's `accept`)	§11.5
Double-checked locking	Lazy singleton that checks, locks, checks again; the field must be `volatile`	§8.8
Driver (machine coding)	The `main` class that feeds commands to the services and prints results	§1.10, §21.0
DRY	Don't Repeat Yourself — principle, see 22.5	Ch 5 §1
DTO (Data Transfer Object)	A plain data holder used only to carry values across a boundary (API, layer)	§2.3
Dynamic dispatch	The JVM picks an overridden method from the object's actual class at run time	§2.6–§2.7
Dynamic programming (DP)	Solving a problem by combining saved answers to smaller sub-problems	§14.2
Edge-triggered alert	Fires once when a value crosses a threshold, not on every update while it stays past it	Ch 19 · Grocery Store, §21.7
EMI	Equated monthly instalment: the fixed amount repaid each month on a loan	§21.6
Encapsulate what varies	Principle — see 22.5	Ch 5 §8
Encapsulation	OOP pillar — see 22.3	§2.3
Entity (DDD)	Object defined by an identity that survives changes; two entities are equal when their ids are equal	Ch 5 §17
Enum (with behaviour)	A fixed set of named constants that can carry fields and methods	§2.10

Term	Plain meaning	Where
`EnumMap` / `EnumSet`	Very fast map and set implementations whose keys are the constants of one enum	§2.10
`equals` / `hashCode` contract	Equal objects must have equal hash codes	§2.12
Event Sourcing	Pattern — see 22.7	§11.7.6
Event-driven	Parts of the system react to published events instead of calling each other directly	Ch 5 §9
Eventual consistency	Copies of data may disagree for a short time but converge once updates stop	Ch 5 §17
Eviction	Removing entries from a cache to make room (LRU, LFU, FIFO)	§20.3
Exception	An object thrown to signal an error, which unwinds the call stack until something catches it	Ch 6 §6
`ExecutorService`	Concurrency tool — see 22.8	§12.4
Exponential backoff	Waiting longer after each failed retry (1 s, 2 s, 4 s…), usually with jitter	Ch 6 §16
Expression problem	Visitor makes adding operations cheap but adding types expensive (and the reverse for plain polymorphism)	§11.5
Facade	Structural pattern — see 22.7	§9.5
Factory Method	Creational pattern — see 22.7	§8.10
Fail fast	Principle — see 22.5	Ch 5 §13
Fairness	Serving waiting threads roughly in order so none starves; costs throughput	§12.19
Fan-out	One event or post copied to many receivers (followers' feeds, subscribers)	§18.4, §20.6
Feature Envy (smell)	Code smell — see 22.6	§7.2.9
Field	A variable that belongs to an object (instance field) or to the class (`static` field)	§2.2
FIFO / LIFO	First in, first out (a queue) vs last in, first out (a stack)	§12.8, Ch 15
F.I.R.S.T.	Clean-test rule — see 22.5	Ch 6 §8
Flag argument	A boolean parameter that makes a function do two things; split it instead	Ch 6 §2
Flyweight	Structural pattern — see 22.7	§9.6
Fork/Join	Split a task recursively into subtasks run in parallel, then combine results	§12.26, §13.10
Fragile base class	A change in a parent class silently breaks subclasses	Ch 5 §6
Framework	A library that owns the program's flow and calls your code at set points (Spring, JUnit)	Ch 5 §10
Functional interface	An interface with one abstract method, usable with lambdas	§2.8
Functional requirement	A behaviour the system must have ("a customer takes a ticket")	§1.5
GA (general admission)	Unnumbered standing or seating tickets sold as a count, not as named seats	§15.3
Garbage collection (GC)	The JVM automatically freeing memory of objects nothing refers to any more	Ch 12
Generalization	UML relationship — see 22.3	§3.6

Term	Plain meaning	Where
Generics	OOP fact — see 22.3	§2.15
Geohash	Encodes a latitude/longitude as a short string; nearby places share a prefix, so it works as a search key	§20.4
Getter / setter	Methods that read (`getX`) or change (`setX`) a field	§2.3
Git	The version-control tool that records every change to the code as commits	§4.2
Glob	Filename wildcard pattern: `*` any characters, `?` one character, `[0-9]` one character from a set	§21.8
Global Data (smell)	Code smell — see 22.6	§7.2.5
God class / God Object	Anti-pattern — see 22.7	§8.6, §7.2.20
GoF	"Gang of Four": the four authors of the 1994 book that catalogued the 23 classic design patterns	§8.2
Golden Hammer	Anti-pattern — see 22.7	§8.6
Graph	Nodes joined by edges (people and connections, stops and routes)	§18.3
GRASP	Principle — see 22.5	Ch 5 §16
Greedy algorithm	Always take the best-looking choice right now; fast, but not always correct (e.g. coin change)	§14.2
GST	Goods and Services Tax, India's sales tax	Ch 19 · Grocery Store
Guard clause	An early check-and-return/throw at the top of a method instead of nested `if`s	§7.3.5, Ch 5 §13
Half-open interval	A time range `[start, end)` that includes the start but not the end, so back-to-back bookings don't clash	§15.4, §21.3
Happens-before	Java Memory Model rule guaranteeing one action's effects are visible to another	§12.6
Hash function / hash code	Turns a value into a number used to pick a bucket; equal values must give equal hashes	§2.12
Hash table / `HashMap`	Key-value store that finds an entry in about constant time by hashing the key	§2.12
Heap vs stack (memory)	Where objects live (shared by all threads) vs each thread's own area for local variables and calls	§12.2
Heuristic	A rule of thumb that is usually right and cheap to apply, not a guarantee	Ch 6 §14
Hexagonal architecture	Ports and adapters: the domain core defines interfaces; databases, UIs and vendors plug in from outside	§20.4
High Cohesion (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.5
HLD vs LLD	Many services and machines vs classes inside one application	§1.2
Hold with TTL	A temporary claim (e.g. seats during payment) that expires automatically	§15.2
Holder-class idiom	Lazy singleton created inside a nested static class; the JVM's class loading makes it thread-safe	§8.8
Hollywood Principle	Principle — see 22.5	Ch 5 §10
HTTP	The request/response protocol browsers and web services use	§3.12

Term	Plain meaning	Where
IDE	Integrated development environment (IntelliJ, Eclipse): editor plus compiler, debugger and refactoring tools	Ch 7
Idempotency	Running an operation twice has the same effect as once; an idempotency key enforces it	§21.2, §20.6
Identity vs equality	Same object in memory (`==`) vs same value (`equals`)	§2.12
Immutability	Principle — see 22.5	§2.13, Ch 5 §14
Indirection (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.8
Information Expert (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.1
Inheritance	OOP pillar — see 22.3	§2.5
In-memory	Data kept only in the program's RAM, lost when it stops; the default in LLD rounds	§1.4
Insider Trading (smell)	Code smell — see 22.6	§7.2.19
Instance	One object created from a class	§2.2
Integration test	Tests several real parts together (e.g. service plus database), slower than a unit test	Ch 6 §17
Interface	A contract of methods; a class can implement many	§2.8
Interface Segregation Principle	SOLID principle — see 22.4	§4.9
Interning	Keeping one shared copy of each equal value (`String.intern()`)	§9.6
Interpreter	Behavioral pattern — see 22.7	§10.6
Interrupt	A polite request to a thread to stop what it is doing; blocking calls react by throwing `InterruptedException`	§12.3
Intrinsic vs extrinsic state	Flyweight's shared, immutable part vs the per-use part passed in by the caller	§9.6
Invariant	A fact about an object that must always be true ("balance is never negative")	Ch 5 (key terms), §15
Inversion of Control (IoC)	The framework controls the flow and calls your code; DI is one way to achieve it	Ch 5 §10, §4.14
Inverted index	A map from each word/tag to the list of items containing it, for search	§18.1
Invoker / Receiver	Command roles: the invoker triggers commands; the receiver does the real work	§10.2
I/O	Input/output: reading or writing files, network or database; slow compared with CPU work	§12.4
Iterator	Behavioral pattern — see 22.7	§10.3
JAR	Java archive: a zip file of compiled classes and resources	§4.7
Java Memory Model (JMM)	Rules for when one thread's writes become visible to another	§12.6
`java.time`	Java's date-time API: `Instant` (a moment), `Duration`, `LocalDate`, and `Clock` (injectable "now")	§1.10
JDBC	Java's standard API for talking to relational databases	§8.11
JDK	Java Development Kit: compiler, tools and the standard library	Ch 2
JIT compiler	Part of the JVM that turns hot bytecode into fast machine code while the program runs	Ch 12

Term	Plain meaning	Where
Jitter	Random extra delay added to retries so many clients don't retry at the same instant	Ch 6 §16, §12.18
JPA / Hibernate	Java's standard for mapping objects to database tables, and its most popular implementation	§9.7
JSON	A text format for structured data: objects in `{}`, lists in `[]`	§3.2
JUnit	The standard Java unit-testing framework	Ch 6 §8
JVM	Java Virtual Machine: runs compiled Java bytecode and manages memory and threads	Ch 2, Ch 12
Kafka	A distributed append-only log used as a durable message broker	§20.6
KISS	Keep It Simple — principle, see 22.5	Ch 5 §2
KYC	Know Your Customer: identity checks a financial app must do before allowing higher limits	§21.2
Lambda	A short anonymous function, e.g. `x -> x * 2`, usable wherever a functional interface is expected	§2.8
Large Class (smell)	Code smell — see 22.6	§7.2.20
Latency	How long one operation takes from start to finish	§1.4
Law of Demeter	Principle — see 22.5	Ch 5 §4
Lazy Element (smell)	Code smell — see 22.6	§7.2.14
Lazy expiry	Deleting an expired entry only when someone next touches it, instead of by a timer	§13.6, §14.7
Lazy initialization	Creating an object only when it is first needed	§8.8
Lease	A lock or hold that expires automatically after a set time unless renewed	§12.9
Least Astonishment	Principle — see 22.5	Ch 5 §12
Ledger	An append-only list of money movements from which balances are derived	§20.1, Ch 21
Legacy code	Existing code, often without tests, that is risky to change	§7.8
LFU / MRU	Cache eviction that removes the least frequently used vs the most recently used entry	§20.3
Linked list	A chain of nodes where each points to the next (doubly linked: also the previous)	§20.3
`LinkedHashMap`	A `HashMap` that also remembers insertion or access order; the shortcut for an LRU cache	§20.3
Linter / static analysis	Tools that read code without running it and flag likely bugs or style issues	Ch 6 §15
Liskov Substitution Principle	SOLID principle — see 22.4	§4.8
Listener	An object registered to be told when an event happens (the observer in Observer)	§11.1
Livelock	Concurrency hazard — see 22.8	§12.18
Lock ordering	Always acquire locks in one global order to prevent circular wait	§12.17
Lock striping	Guarding a map with an array of locks, each covering some buckets	§13.7
Lombok	A library that generates boilerplate (getters, builders) from annotations at compile time	§8.12

Term	Plain meaning	Where
Long Function (smell)	Code smell — see 22.6	§7.2.3
Long Parameter List (smell)	Code smell — see 22.6	§7.2.4
`LongAdder`	Concurrency tool — see 22.8	§12.15
LOOK scheduling	Elevator keeps moving in one direction while stops remain ahead, then reverses	§14.5
Loops (smell)	Code smell — see 22.6	§7.2.13
Loose coupling	Principle — see 22.5	Ch 5 §9
Lost wakeup	A signal sent before the waiter started waiting, so the waiter sleeps forever	§12.13
Low Coupling (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.4
LRU cache	Evicts the least recently used entry; hash map + doubly linked list gives O(1)	§20.3
Lua	A small scripting language; Redis runs a Lua script as one atomic step	§20.7
Machine-coding round	LLD round where working, runnable in-memory code is the answer (90–120 min)	§1.2, §21.0
Market vs limit order	Buy or sell now at the best available price vs only at a given price or better	Ch 19 · Stock Brokerage
Matching engine	Per-symbol order book matching buy and sell orders by best price, then oldest first	Ch 19 · Stock Brokerage
MDC	Mapped Diagnostic Context: per-thread key-values (request id, user) automatically added to log lines	§20.5
Mediator	Behavioral pattern — see 22.7	§10.4
Memento	Behavioral pattern — see 22.7	§10.5
Memory leak	Memory that is never freed because something still holds references to objects no longer needed	§11.1, §12.24
Message Chains (smell)	Code smell — see 22.6	§7.2.17
Message queue	A buffer service where producers leave messages for consumers to process later	§20.6
Method	A function that belongs to a class	§2.2
Method reference	Shorthand for a lambda that just calls a method, e.g. `String::length`	§2.8
Microservice vs monolith	Many small independently deployed services vs one deployable application	Ch 5 §17
Middle Man (smell)	Code smell — see 22.6	§7.2.18
Mixin	A small interface with `default` methods that adds a capability to many classes	§4.3
Mock / stub / fake	Test doubles: a mock checks calls were made, a stub returns canned answers, a fake is a simple working version	Ch 6 §17
Mockito	The most common Java library for creating mocks in tests	Ch 6 §8
Module / package	A group of related classes; in Java a package is a folder-level namespace	§2.14
Monitor	The lock built into every Java object, used by `synchronized` and `wait/notify`	§12.7

Term	Plain meaning	Where
Multiplicity	How many objects take part at each end of a relationship (`1`, `0..1`, `*`, `1..*`)	§3.2
Mutable Data (smell)	Code smell — see 22.6	§7.2.6
Mutation testing	Deliberately breaking the code in small ways to check the tests notice	Ch 6 §17
Mutex	A lock that lets only one thread into a critical section	§12.7
MVC	Model–View–Controller — pattern, see 22.7	§11.7.5
Mysterious Name (smell)	Code smell — see 22.6	§7.2.1
Non-functional requirement	A quality: thread safety, extensibility, in-memory storage, latency	§1.5
Null Object	Pattern — see 22.7	§11.7.1
`NullPointerException` (NPE)	Thrown when you call a method or read a field through a `null` reference	Ch 5 §13
Object	One instance of a class with real values	§2.2
Object Pool	Creational pattern — see 22.7	§8.14
Observer	Behavioral pattern — see 22.7	§11.1
Offset	A position number in a log or list; each reader remembers its own	§20.6
OOA / OOD / OOP	Object-oriented analysis / design / programming — see 22.3	§2.17
Open/Closed Principle	SOLID principle — see 22.4	§4.7
Optimistic locking	Read with a version; the write succeeds only if the version is unchanged	§12.10, §12.25
`Optional`	A container that may be empty; return it when "not found" is normal	§1.10
Order book	Per-stock lists of waiting buy and sell orders, sorted by price then time	Ch 19 · Stock Brokerage
OTP	One-time password: a short code valid for a single use, usually sent by SMS	Ch 5 §13, §20.2
Outbox (transactional)	Save events in a table in the same transaction as the data, and publish them afterwards, so neither is lost	Ch 5 §17
`OutOfMemoryError`	Thrown when the JVM cannot find memory for a new object	§12.2
Out-of-scope list	Written list of what you will not build; shrinks the problem	§1.5
Overloading	OOP fact — see 22.3	§2.7
Overriding	OOP fact — see 22.3	§2.7
Payment gateway	An external service that actually charges cards or UPI; hidden behind your own interface	§15.2, Ch 19
PECS	OOP fact — see 22.3	§2.15
Pessimistic locking	Lock a row before changing it (e.g. `SELECT … FOR UPDATE`) so nobody else can touch it meanwhile	§12.5, §15.2
Phaser	Concurrency tool — see 22.8	§12.14, §12.26
PII	Personally identifiable information (names, phone numbers) that must not leak into logs	Ch 6 §15
Pinning	A virtual thread stuck on its carrier thread while it blocks	§12.4
Pipeline	Data flowing through a sequence of steps, each feeding the next (streams, filters, middleware)	§7.2.13

Term	Plain meaning	Where
PLU code	Four-digit price look-up code for loose produce, keyed at the till together with the scale weight	Ch 19 · Grocery Store
Plugin	A piece of code added to a system through a known interface without editing the system	§4.7
PNR	Passenger name record: the booking reference for an airline reservation	Ch 16 · Airline
Poison pill	A special message telling a consumer to stop; one per consumer	§12.22
Polymorphism	OOP pillar — see 22.3	§2.6, Ch 5 §16.6
POS	Point of sale: the till where a sale is rung up and paid	Ch 19 · Grocery Store
Precondition / postcondition	What must be true before a call (caller's duty) / what the method promises after it	§4.8, Ch 5 §15
Primitive Obsession (smell)	Code smell — see 22.6	§7.2.11
`PriorityQueue`	A queue that always hands out the smallest (or highest-priority) element first; a binary heap inside	Ch 16 · Course Registration
Process	A running program with its own memory; it contains one or more threads	§12.2
Producer–consumer	Threads hand work through a (bounded) queue	§12.22
Program to an interface	Principle — see 22.5	Ch 5 §7
Protected Variations (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.9
Prototype	Creational pattern — see 22.7	§8.13
Proxy	Structural pattern — see 22.7	§9.7
Pub-sub	Observer through a broker: publishers and subscribers don't know each other	§20.6
Pure Fabrication (GRASP)	GRASP guideline — see 22.5	Ch 5 §16.7
Pure function	A function whose result depends only on its inputs and which changes nothing else	§11.7.6, Ch 17 · 2048
Qualified association	An association looked up by a key (`Library [isbn] → Book`, i.e. a `Map`)	§3.11
Race condition	The result depends on the timing of threads touching shared mutable state	§12.5
Rate limiter	Caps how many requests a key may make per time window (token bucket, windows)	§13.11, §20.7
Read-write lock	Many readers at once, or one writer	§12.10
Realization	UML relationship — see 22.3	§3.7
Record	OOP fact — see 22.3	§2.13
Recursion	A function that solves a problem by calling itself on a smaller part	§9.3
Recursive-descent parser	A parser with one method per grammar rule, each calling the others	§10.6, §21.8
Redis	A fast shared in-memory key-value store, often used for caches, counters and distributed locks	§20.7
Reentrancy	A thread may re-acquire a lock it already holds	§12.8
`ReentrantLock`	Concurrency tool — see 22.8	§12.8

Term	Plain meaning	Where
Refactoring	Refactoring — see 22.6	§7.1
Reflection	Code inspecting or calling classes, fields and methods at run time by name	§8.8
Refused Bequest (smell)	Code smell — see 22.6	§7.2.23
Regex	Regular expression: a pattern language for matching text	§10.6
Repeated Switches (smell)	Code smell — see 22.6	§7.2.12
Repository	Pattern — see 22.7	§11.7.3
Requirement	One thing the system must do, written so you can check it	§1.5
REST	A style of HTTP API built around resources (URLs) and verbs (GET, POST…)	Ch 5 §1
Retry	Trying a failed operation again; safe only if the operation is idempotent	Ch 6 §16
Role interface	A small interface serving one kind of caller (the ISP fix)	§4.9
Rule of three	Refactor to an abstraction at the second or third case, not the first	§4.15
`RuntimeException`	Base class of unchecked exceptions	§2.5
Saga	A long business process split into local steps, each with a compensating action if a later step fails	§3.12, Ch 15
Scalability	How well a system keeps working as users, data or load grow	§1.14
`ScheduledExecutorService`	Runs tasks after a delay or repeatedly at a fixed rate	§13.6
Schema	The defined structure of stored data (tables, columns, types)	§2.17
SDK	Software development kit: a vendor's ready-made library for calling its service	§9.1
Sealed type	A type whose permitted subtypes are fixed, enabling exhaustive `switch`	§11.5
Seam	A place where you can swap behaviour (e.g. an interface) without editing the code around it; used for testing	§2.9, §7.7
Seed	The starting number for a pseudo-random generator; the same seed gives the same sequence	Ch 17
Semaphore	Concurrency tool — see 22.8	§12.12
Separation of Concerns	Principle — see 22.5	§4.5, Ch 5 §11
Sequence diagram	UML diagram of messages between objects over time	§3.12
Serialization	Turning an object into bytes or text (and back) for storing or sending	§8.8
Service Locator	Anti-pattern where a class asks a registry for its dependencies, hiding them	§11.7.2
Sharding	Splitting data across independent parts (each with its own lock) to scale	§20.3
Shotgun Surgery (smell)	Code smell — see 22.6	§7.2.8
Side effect	Anything a function does besides returning a value (changing a field, writing a file)	Ch 5 §12, Ch 6 §2
Signaling	One thread tells another that something has happened (semaphore, latch)	§12.20

Term	Plain meaning	Where
Simple Factory	Creational pattern — see 22.7	§8.9
Single Responsibility Principle	SOLID principle — see 22.4	§4.2
Singleton	Creational pattern — see 22.7	§8.8
SKU	Stock-keeping unit: one sellable product variant tracked in inventory	§21.7
SLF4J	A logging facade: code logs through its API and any logging library can sit underneath	§9.5
Sliding window	Rate-limit algorithm counting requests in a moving time window (log or counter)	§20.7
SMS / SMTP	Text messages to phones / the protocol for sending email	§20.2
Snapshot	A copy of state at one moment, used to restore it or to read it safely	§10.5
SOLID	SRP, OCP, LSP, ISP, DIP — see 22.4	§4.1
Specification	Pattern — see 22.7	§11.7.4
Speculative Generality (smell)	Code smell — see 22.6	§7.2.15
Split tender	Paying one bill with several payment methods (e.g. part UPI, part cash)	Ch 19 · Grocery Store
Spring	The most widely used Java application framework; creates and wires objects (DI), web, data access	§4.14, §11.7.2
Spurious wakeup	A waiting thread wakes with no signal; why `wait()` sits in a `while` loop	§12.13
SQL	The language for querying and updating relational databases	§11.7.3
Stack trace	The list of method calls active when an exception was thrown; shows where it came from	Ch 6 §6
`StampedLock`	Concurrency tool — see 22.8	§12.10
Starvation	Concurrency hazard — see 22.8	§12.19
State (pattern)	Behavioral pattern — see 22.7	§11.2
State machine diagram	UML diagram of one object's states and transitions (`event [guard] / action`)	§3.14
Stateless vs stateful	Keeps no data between calls (safe to share) vs remembers data between calls	§1.6
`static`	Belongs to the class, one per class, not to each object	§2.2
Stop-loss / stop-limit	Orders that wake up when the price hits a trigger, then sell at market / at a limit price	Ch 19 · Stock Brokerage
Strategy	Behavioral pattern — see 22.7	§11.3
Stream (Java)	A pipeline over a collection (`filter` , `map` , `collect`) that states what, not how	§2.8, §7.2.13
Subclass / superclass	The child class that `extends` / the parent it extends	§2.5
`synchronized`	Concurrency tool — see 22.8	§12.7
TCP	The internet protocol that delivers a reliable, ordered byte stream between two machines	§11.2

Term	Plain meaning	Where
Technical debt	Shortcuts in code that make future changes slower until someone cleans them up	§7.1
Telescoping constructors	A ladder of constructors each adding one more parameter; Builder replaces it	§8.12
Tell, Don't Ask	Principle — see 22.5	Ch 5 §5
Template Method	Behavioral pattern — see 22.7	§11.4
Temporary Field (smell)	Code smell — see 22.6	§7.2.16
Test double	Anything standing in for a real dependency in a test: dummy, stub, spy, mock, fake	Ch 6 §17
Test-Driven Development (TDD)	Failing test → make it pass → refactor, in very short cycles	Ch 6 §8
Thread	An independent path of execution inside a process, sharing its memory	§12.2
Thread confinement	Keeping data inside one thread so it never needs locking	§12.24
Thread dump	A snapshot of every thread's state and call stack (`jstack`, `jcmd`) used to diagnose hangs	§12.3
Thread pool	A fixed set of reusable threads fed from a task queue	§12.21
Thread states	NEW, RUNNABLE, BLOCKED, WAITING, TIMED_WAITING, TERMINATED	§12.3
Thread-safe	Gives correct results even when many threads call it at the same time	§12.5
Thread-starvation deadlock	Tasks in a bounded pool wait for tasks queued behind them in the same pool	§12.17, §12.21
Throughput	How much work gets done per unit of time (requests per second)	§12.11
Timeout	A limit on how long to wait before giving up	§12.9
TL;DR	"Too long; didn't read": a short summary at the end of each section or chapter	Every chapter
Token bucket	Rate-limit algorithm: tokens refill at a fixed rate; each request takes one; allows bursts	§13.11
`toString`	Method returning a readable text form of an object, used in logs and printing	§2.12
`TreeMap` / `TreeSet`	Sorted map and set (red-black tree inside); support "next higher" and range queries	§14.5
`tryLock`	Concurrency tool — see 22.8	§12.9
TTL (time to live)	How long an entry or hold stays valid before it expires	§13.6, §15.2
Two hats	Refactoring — see 22.6	§7.1.1
Type erasure	Java removes generic type arguments after compiling, so `List<String>` and `List<Integer>` are the same class at run time	§2.15
Ubiquitous language	One vocabulary shared by domain experts and the code (`place()`, not `setStatus(2)`)	Ch 5 §17
UI	User interface: the screens or controls a person interacts with	§11.7.5
UML	Unified Modeling Language: 14 diagram types, 7 structural and 7 behavioural	§3.9
Unit test	A fast test of one small piece of code in isolation	Ch 6 §8

Term	Plain meaning	Where
UPI	Unified Payments Interface: India's instant bank-to-bank mobile payment system	Ch 19, §21.2
Use case	One thing an actor can do with the system	§1.5, §3.10
Use-case diagram	UML diagram of actors, use cases and the system boundary («include», «extend»)	§3.10
UTC	Coordinated Universal Time: the time-zone-free reference clock for storing timestamps	Ch 16 · Airline
Value object	A small immutable object defined by its values (money, date range), usually a record	§2.13, Ch 5 §1, Ch 5 §17
Virtual threads	Concurrency tool — see 22.8	§12.4
Virtual waiting room	FIFO queue that admits buyers gradually during a ticket rush	§15.3
Visibility (memory)	Whether a write by one thread can be seen by another; not guaranteed without `volatile`, locks or other happens-before edges	§12.6
Visitor	Behavioral pattern — see 22.7	§11.5
`volatile`	Concurrency tool — see 22.8	§12.6
Webhook	A URL a service calls to notify you that something happened (e.g. "payment succeeded")	§15.2
Wildcard (generics)	`?` in a generic type: `? extends T` (read from it), `? super T` (write to it)	§2.15
Work stealing	Idle threads in a fork/join pool take queued tasks from busy threads	§12.26
Wrapper	An object that holds another and adds or changes behaviour around it (decorators, adapters, boxed primitives)	§9.4
Write-through / write-back	Cache writes go to storage immediately vs later in batches	§20.3
YAGNI	You Aren't Gonna Need It — principle, see 22.5	Ch 5 §3

Self-check

- **Q:** Name the eleven framework steps in order. **A:** Clarify, requirements, use cases, entities, relationships, class diagram, key flows, patterns & SOLID, code, edge cases & concurrency, extensions.
- **Q:** Where does the diamond go, and what does filled mean? **A:** At the whole; filled = composition (the part dies with the whole).
- **Q:** A `switch (vehicleType)` computes fees. Which principle, smell and pattern? **A:** OCP; Repeated Switches (if it repeats); Strategy.
- **Q:** Decorator vs Proxy vs Chain of Responsibility? **A:** Decorator adds behaviour and every layer runs; Proxy controls access; in CoR one handler can stop the flow.
- **Q:** State vs Strategy? **A:** States know each other and advance themselves; strategies are chosen from outside.
- **Q:** Four Coffman conditions, and the usual fix? **A:** Mutual exclusion, hold and wait, no preemption, circular wait; global lock ordering.
- **Q:** Why is `volatile` not enough for `count++`? **A:** Visibility, not atomicity; use `AtomicInteger` or a lock.
- **Q:** The six machine-coding packages? **A:** model, repository, service, strategy, exception, driver.
- **Q:** What makes every booking problem safe? **A:** Naming the real unit of inventory and making "if free then take" one atomic step (plus holds that expire).

TL;DR

- **Framework:** clarify → requirements → use cases → entities → relationships → diagram → flows → patterns/SOLID → code → edge cases/concurrency → extensions.
- **Classes:** different data → field; different behaviour → class; one sentence per class; composition over inheritance.
- **SOLID** diagnoses change pain; always state the cost of the fix, and know when not to apply it.
- **Patterns** come from signals: Strategy (rules vary), Factory (type value → class), Observer (many listeners), State (lifecycle), Singleton (exactly one), Builder (many optional fields). Use one or two, name a rejected one.
- **Concurrency:** find the shared state, state the invariant, make check-then-act atomic with the smallest tool, lock in a fixed order, notify outside locks.
- **Machine coding:** run early and often, mandatory first, services return data, the driver prints and keeps going.