Chapter 1 — Getting Started with Python

This chapter takes you from "never run Python" to "I understand what happens when I press Enter". You will install Python, run code two different ways, see how the CPython interpreter turns your text into something a machine executes, and learn the small set of layout rules (indentation, lines, quotes, comments) that every later chapter relies on.

What you'll learn

#	Topic	You will be able to…
1.1	Who this book is for and how it is organised	pick the right path through the chapters
1.2	What Python is, its history and design traits	explain Python in one minute to anyone
1.3	Where Python is used	name real products built with it
1.4	Installing Python and virtual environments	set up a clean project on any OS
1.5–1.6	REPL vs scripts, IDEs	choose the right tool for experimenting vs building
1.7	Your first program	write, run and understand `print("Hello, World!")`
1.8	How CPython runs code	describe source → bytecode → virtual machine
1.9	Basic syntax	identifiers, indentation, line continuation, quotes, blank lines, `input()`, `;`
1.10	Comments and docstrings	document code the way Python tools expect
1.11	PEP 8 and PEP 20	write code that looks like professional Python

All code lives in `code/` and was run with CPython 3.14. Run any file with `python code/<file>.py`.

1.1 Who this book is for, and how it is organised

What it is


A single, self-contained path through core Python — from first program to intermediate topics — written so you never need a second source.

Who should read it

Reader	What you get
Complete beginners (students, career changers)	A first language taught from zero, with every term defined on first use
Developers from Java, C#, JavaScript, Go…	The "Python way" of doing things you already know, plus the traps that differ from your language
Data analysts and scientists	A solid language base before NumPy, pandas and scikit-learn
Teachers and trainers	Ready-made explanations, examples and self-check questions
Hobbyists and automators	Enough Python to script your own tasks and projects

Prerequisites: a computer (Windows, macOS or Linux), the ability to install software, curiosity, and willingness to type code yourself rather than only read it. No maths beyond arithmetic is needed in these early chapters.

How the book is organised



Each chapter builds on the previous one. Every topic follows the same rhythm: *what it is → why it matters → how it works → code with real output → trade-offs → common mistakes → real-world use → interview questions → self-check → TL;DR*. Skim the TL;DR boxes to review; do the self-checks to confirm you actually learned it.

1.2 What Python is

What it is

Python is a **high-level, general-purpose programming language**. *High-level* means you describe *what* to do (add these numbers, sort this list) without managing memory addresses or CPU registers. *General-purpose* means it is not tied to one domain: the same language builds websites, trains neural networks and renames files.

Think of it as a very capable assistant who speaks almost-English: you write `for name in guests: print(name)` and it does exactly that.

Python is **multi-paradigm**: you can write it as a list of steps (procedural), organise it into classes and objects (object-oriented), or compose small functions (functional). You do not have to pick one.

A short history

Year	Event
Dec 1989	Guido van Rossum starts Python at CWI (the Dutch national maths and computer science institute) as a successor to the ABC teaching language. The name comes from the comedy group *Monty Python*, not the snake.
1991	First public release, 0.9.0.
2000	Python 2.0: list comprehensions and a garbage collector that can reclaim reference cycles.
2008	Python 3.0: a deliberate clean-up that broke backward compatibility (e.g. `print` became a function, text became Unicode by default).
2018–19	Guido steps down as "Benevolent Dictator For Life" (July 2018); since 2019 a five-person **Steering Council**, elected by the core developers, governs the language.
2020	Python 2 reaches end of life (1 January 2020). Only Python 3 is maintained.
2020 → now	One feature release per year, every October (since 3.9; PEP 602) (3.10 added `match`; 3.11 made CPython markedly faster; 3.13 added a new interactive shell and experimental free-threading; 3.14 is current).

Language changes are proposed in **PEPs** – *Python Enhancement Proposals* – numbered design documents. You will meet PEP 8 (style) and PEP 20 (philosophy) in this chapter.

Why it matters — the design traits

Trait	What it means in practice	The honest caveat
Readable syntax	Indentation shows structure; keywords are English words (`and`, `not`, `in`).	Whitespace errors become syntax errors.
Dynamically typed	You never declare a variable's type; each *value* carries its type, checked while the program runs.	Type mistakes surface at run time unless you add type hints and a checker such as mypy.
Strongly typed	Python refuses to silently mix unrelated types: `"3" + 4` is an error, not `"34"` or `7`.	You convert explicitly (Chapter 2).
Automatic memory management	Objects are freed when nothing refers to them (reference counting plus a cycle collector). You never call `free()`.	Less control over memory layout than C.
"Interpreted"	You run source files directly — no separate compile step for you. Internally CPython *does* compile to bytecode first (see §1.8).	Pure-Python loops are slower than C/Java; heavy numeric work goes to libraries written in C.
Extensible	Hot spots can be written in C, C++ or Rust and imported like normal modules (this is how NumPy is fast).	Adds build complexity.
Embeddable	A C/C++ program can host the interpreter to give users a scripting language (Blender, GIMP, many games).	–
"Batteries included"	A large standard library: files, JSON, HTTP, dates, maths, testing, databases (SQLite). Plus 500 000+ third-party packages on PyPI.	Quality of third-party packages varies.

Common mistakes

- Believing "interpreted" means "reads one line, runs it, reads the next". The whole file is compiled first; a syntax error on line 200 stops line 1 from ever running (proved in §1.8).
- Confusing *dynamic* with *weak* typing. Python is dynamic **and** strong.
- Learning Python 2 material. Anything using `print "hi"` (no parentheses) is obsolete.

In the interview

> **30-second answer:** "Python is a high-level, dynamically but strongly typed, garbage-collected, multi-paradigm language. The reference implementation, CPython, compiles source to bytecode and runs it on a stack-based virtual machine. It trades raw speed for developer productivity and pushes heavy computation into C extensions like NumPy."

- *Is Python compiled or interpreted?* → Both: compiled to bytecode, then the bytecode is interpreted by a VM. "Interpreted" describes the user experience.
- *Why is Python slow, and how do people cope?* → Every operation goes through dynamic type checks in the VM. Teams vectorise with NumPy, use C/Rust extensions, use PyPy (a JIT-compiling implementation), or rely on CPython's own speed-ups since 3.11.
- *What is a PEP?* → A design document proposing a change or standard; e.g. PEP 8 is the style guide.

Self-check

1. Is `"3" + 4` allowed? → No, `TypeError`: Python is strongly typed.
2. Who governs Python today? → The elected five-member Steering Council.
3. What does "dynamically typed" mean? → Types belong to values and are checked at run time; names have no fixed type.
4. When did Python 2 stop being supported? → 1 January 2020.

TL;DR

Python = readable, dynamic-but-strong, garbage-collected, batteries-included. Created by Guido van Rossum (1989–91); Python 3 (2008) is the only live version; changes go through PEPs.

1.3 Where Python is used

What it is

Python's niche is "everywhere glue is needed plus everywhere a mature library exists". The table pairs each area with the key libraries and verified real-world users.

Area	Key tools	Real-world examples
Web back-ends	Django (batteries-included: ORM, admin, auth), Flask (minimal), FastAPI (async, type-hint driven)	Instagram runs one of the largest Django deployments; Reddit was rewritten in Python in 2005; Pinterest and Mozilla sites use Django/Flask
Data analysis	pandas (tables and time series), NumPy (fast arrays), Jupyter notebooks	Finance, analytics and research teams worldwide; Jupyter is the default notebook tool in data science
Machine learning & AI	scikit-learn, PyTorch, TensorFlow/Keras, Hugging Face Transformers	PyTorch (Meta) and TensorFlow (Google) expose Python as their main interface; most LLM tooling ships Python SDKs first
Scientific computing	SciPy, NumPy, Matplotlib, Astropy	NumPy was used in the first black-hole image (Event Horizon Telescope) and in LIGO's gravitational-wave detection
Automation & scripting	standard library (`pathlib`, `subprocess`, `shutil`), Ansible	Sysadmin scripts, CI pipelines, Ansible itself is written in Python
Networking	`socket`, `asyncio`, Twisted, `requests` / `httpx`	Network tooling, scrapers, async servers
Game development & scripting	Pygame (2-D games), embedded Python in engines	*EVE Online* uses Stackless Python on its servers; *Civilization IV* used Python for game logic; Blender and Maya expose Python scripting APIs
Desktop GUIs	Tkinter (ships with Python), PyQt/PySide, wxPython	Internal tools, utilities, the Python IDLE editor itself (Tkinter)
Education	IDLE, Thonny, turtle graphics	Widely used as a first language in schools and universities (e.g. MIT 6.100L teaches Python)
IoT & embedded	MicroPython, CircuitPython	Runs on microcontrollers such as the Raspberry Pi Pico and ESP32 to read sensors and talk to networks

Why it matters

Choosing a language is mostly choosing an ecosystem. Python wins where libraries matter more than raw speed: data, ML, scripting, web APIs.

When not to use it

Situation	Better fit	Why
Hard real-time or very latency-sensitive systems (trading engines, game engines' inner loops)	C, C++, Rust	Predictable performance, no interpreter overhead
Browser front-end code	JavaScript / TypeScript	Browsers run JavaScript natively (Python in the browser via WebAssembly exists but is niche)
Native mobile apps	Swift, Kotlin	Platform SDKs and tooling
CPU-bound multi-threaded code (on standard CPython)	Go, Rust, Java — or Python with multiprocessing / free-threaded builds	The Global Interpreter Lock (GIL) lets only one thread run Python bytecode at a time in the default build

Self-check

1. Name the two main Python web frameworks and their difference. → Django: full-featured with ORM/admin; Flask: minimal core, add what you need.
2. Why is Python fast enough for ML if Python itself is slow? → The heavy maths runs in C/C++/CUDA inside NumPy/PyTorch; Python only orchestrates.
3. Which Python variant runs on microcontrollers? → MicroPython (and its fork CircuitPython).

TL;DR

Python dominates data, ML, scripting and web back-ends because of its libraries; avoid it for hard real-time, browser front-ends and native mobile.

1.4 Installing Python and creating a project

What it is

To run Python you need an **interpreter** — the program that reads and executes Python code. The official one is **CPython** (written in C), downloaded from python.org. Other implementations exist (PyPy, MicroPython, GraalPy), but "Python" in this book means CPython.

How it works — install per OS

OS	Recommended	Check it worked
Windows	Installer from python.org (tick **"Add python.exe to PATH"**), or the Microsoft Store package. Windows also installs the `py` launcher, which picks a version: `py -3.14`.	`py --version` or `python --version`
macOS	Installer from python.org, or Homebrew: `brew install python`. Do not rely on any old system copy.	`python3 --version`
Linux	Your package manager, e.g. `sudo apt install python3 python3-venv`. **Never remove** the system Python — the OS uses it.	`python3 --version`

On macOS/Linux the command is usually `python3` (plain `python` may not exist or may point elsewhere). Inside an activated virtual environment, `python` always means that environment's interpreter.


Virtual environments (intro)

What it is: *a virtual environment* ("venv") is a private folder containing its own `python` executable link and its own `site-packages` directory for installed libraries. Analogy: each project gets its own toolbox, so upgrading a hammer for project A doesn't break project B.

The problem it solves: project A needs `Django 4`, project B needs `Django 5`. Installing both globally is impossible; installing into the system Python can break OS tools. Modern Linux distributions and Homebrew even refuse (`error: externally-managed-environment`, PEP 668) to let `pip` install globally.

How it works:

1. Create: `python3 -m venv .venv` (on Windows: `py -m venv .venv`).
2. Activate: `source .venv/bin/activate` (macOS/Linux) or `.venv\Scripts\activate` (Windows). Your prompt shows `(.venv)`.
3. Install packages: `python -m pip install requests`. They go into `.venv/…/site-packages`, nowhere else.
4. Record them: `python -m pip freeze > requirements.txt`; a teammate recreates with `python -m pip install -r requirements.txt`.
5. Leave: `deactivate`. Delete the environment by deleting the `.venv` folder.



`python -m pip` (rather than bare `pip`) guarantees you install into the interpreter you are actually running. Faster all-in-one tools such as **uv** and **Poetry** manage venvs and dependencies for you; they build on the same idea.

Common mistakes

- Forgetting to tick "Add to PATH" on Windows → `'python' is not recognized`.
- Installing packages globally with `sudo pip` → breaks OS tools. Use a venv.
- Committing `.venv/` to Git. Commit `requirements.txt` (or `pyproject.toml`) instead; add `.venv/` to `.gitignore`.
- Running `pip` from one Python and `python` from another → "I installed it but import fails". Use `python -m pip`.

In the interview

30-second answer: "I create one virtual environment per project with `python -m venv .venv`, activate it, install with `python -m pip`, and pin dependencies in `requirements.txt` or `pyproject.toml`. That isolates versions between projects and keeps the system interpreter clean."

- *Where do packages go in a venv?* → Its own `site-packages` directory; `sys.prefix` points to the venv.
- *Does a venv copy the whole interpreter?* → Typically it links to (or copies) the base interpreter binary and adds its own `site-packages`; the standard library is shared.

Self-check

1. Command to create a venv named `.venv`? → `python -m venv .venv`.
2. How do you know it is active? → Prompt shows `(.venv)`; `python -c "import sys; print(sys.prefix)"` points into it.
3. Why `python -m pip` instead of `pip`? → It runs pip for exactly the interpreter you call.

TL;DR

Install CPython from python.org (or your OS package manager), then give every project its own `.venv` and install with `python -m pip`.

1.5 Two ways to run code: the REPL and scripts

What it is

- **REPL** (*Read–Eval–Print Loop*): type `python3` with no arguments. You get a `>>>` prompt; each line you type is read, evaluated, and its result printed, then it loops. Continuation lines show `...`.
- **Script**: a text file ending in `.py` that you run with `python3 hello.py`. Nothing is echoed automatically — you must `print()`.

```
$ python3
>>> 2 + 3
5
>>> _ * 10          # _ holds the last printed result (REPL only)
50
>>> name = "Ada"
>>> name            # a bare expression is echoed in the REPL...
'Ada'
>>> exit()          # or Ctrl-D (macOS/Linux), Ctrl-Z then Enter (Windows)
```

Since Python 3.13 the default REPL supports colour, multi-line editing, and `exit` / `quit` without parentheses. Use `help(len)` inside the REPL for documentation and `help()` for an interactive help browser.

Ways to run Python

Command	What it does	Use it for
`python3`	Start the REPL	Quick experiments
`python3 script.py`	Run a file	Real programs
`python3 -i script.py`	Run a file, then drop into the REPL with its variables	Debugging / exploring results
`python3 -m module`	Run a module found on the import path	Tools: `-m venv`, `-m pip`, `-m http.server`, `-m pytest`
`python3 -c "print(1+1)"`	Run a one-line program	Shell one-liners
Jupyter notebook	Cells of code + output + text	Data exploration, teaching

On macOS/Linux a script can start with a **shebang** line `#!/usr/bin/env python3`; after `chmod +x script.py` you can run `./script.py` directly.

The `if __name__ == "__main__":` guard

Every module has a variable `__name__`. When a file is **run directly** it is `"__main__"`; when it is **imported** it is the module's name. Putting start-up code under the guard lets a file be both a runnable script and an importable library — every script in this book does it.

Trade-offs

	REPL	Script
Feedback	Instant	After each run
Keeps your work	No (history only)	Yes, in a file you can version
Auto-prints values	Yes	No – use `print()`
Best for	Trying one idea	Anything you'll run twice

Common mistakes

- Typing `python3 hello.py` *inside* the `>>>` prompt → `SyntaxError`. That is a shell command; exit the REPL first.
- Expecting a bare expression like `2 + 3` in a script to print something. Only the REPL echoes.
- Naming your file after a standard module (`random.py`, `email.py`) – `import random` then imports *your* file.

Self-check

1. What does `_` hold in the REPL? → The last echoed result.
2. How do you run a file and then inspect its variables? → `python3 -i file.py`.
3. What is `__name__` when a file is imported? → The module's name, not `"__main__"`.

TL;DR

REPL for trying, scripts for keeping. Guard start-up code with `if __name__ == "__main__":`.

1.6 IDEs and editors

What it is

An **IDE** (*Integrated Development Environment*) combines an editor with running, debugging, autocompletion and error checking. You can write Python in any text editor, but tooling catches mistakes before you run.

Tool	Best for	Notes
VS Code + Python extension	Most people	Free; Pylance gives autocompletion and type checking; integrated debugger and Jupyter
PyCharm	Large projects	Deep refactoring and inspections; core features are free, advanced ones need a paid Pro subscription
Jupyter / JupyterLab	Data analysis, teaching	Cells, inline charts; not ideal for large applications
IDLE	First hour	Ships with Python; simple REPL + editor
Thonny	Absolute beginners	Shows variables and step-by-step execution visually
Vim / Neovim / Emacs / Zed / Sublime	Keyboard-driven developers	Add a language server (Pyright, pylsp) for smart features

Add three tools to any editor: a **formatter** (Black or Ruff format – rewrites layout to PEP 8), a **linter** (Ruff or Flake8 – flags bugs and style issues), and optionally a **type checker** (mypy or Pyright).

Common mistakes

- The editor uses a different interpreter than your venv → imports "missing". Select the `.venv` interpreter in the IDE.
- Hand-formatting code. Let the formatter do it on save.

TL;DR

VS Code or PyCharm for projects, Jupyter for data, IDLE/Thonny to start; always pair with a formatter and linter.

1.7 Your first program

What it is

The traditional first program prints a greeting. It proves your installation works and introduces two ideas: a **function call** and a **string**.

```
# Print "Hello, World!" to the console
print("Hello, World!")
```

- `print` is a **built-in function** — always available, no import needed. Calling it means writing its name followed by parentheses containing **arguments**.
- `"Hello, World!"` is a **string** (type `str`): a sequence of characters between quotes.
- `print` writes the text to **standard output** (the console) and then a newline.
- The `# …` line is a **comment**; Python ignores it.

`print` has two handy keyword arguments: `sep` (what goes between arguments, default a space) and `end` (what goes after, default `"\n"`). From `code/first_program.py`:

```
print("Hello, World!")
print("Python", sys.version_info.major, sys.version_info.minor, sep=".", end="  <- running version\n")
```

Output:

```
Hello, World!
Python.3.14  <- running version
```

Common mistakes

- `Print("hi")` → `NameError`: Python is case-sensitive.
- `print "hi"` → `SyntaxError` (Python 2 syntax).
- Mismatched or curly quotes pasted from a word processor (`“hi”`) → `SyntaxError`.

Self-check

1. What type is `"Hello, World!"`? → `str`.
2. How do you print `a-b-c` from three arguments? → `print("a", "b", "c", sep="-")`.
3. How do you print without a trailing newline? → `print(x, end="")`.

TL;DR

`print(...)` sends text to the console; text in quotes is a `str`; everything is case-sensitive.


1.8 How CPython runs your code

What it is

When you type `python3 app.py`, CPython does **not** execute your text line by line. It first translates the *entire file* into **bytecode** — compact instructions for an imaginary, stack-based computer — and then its **virtual**

machine (VM) executes those instructions. Analogy: a translator first converts a whole speech into shorthand notes (bytecode), then reads the notes aloud (VM).

How it works



1. **Tokenize** – the text is split into tokens: names, numbers, operators, `INDENT` / `DEDENT` markers. Comments are discarded here.
2. **Parse** – tokens are arranged into an **Abstract Syntax Tree (AST)**, a tree describing the program's structure. Since 3.9 CPython uses a PEG parser (PEP 617). Syntax errors are found here – for the whole file, before anything runs.
3. **Compile** – the AST becomes a **code object**: bytecode plus tables of constants and names.
4. **Cache** – for *imported* modules, the code object is saved as a `.pyc` file in `__pycache__/` so the next import can skip steps 1–3 if the source hasn't changed. The main script you run directly is not cached.
5. **Execute** – the VM's evaluation loop reads each instruction, pushes and pops values on a stack, and calls C code to do the real work. Since 3.11 the VM *specialises* hot instructions for the types it actually sees (PEP 659), one reason 3.11+ is noticeably faster than 3.10.

From `code/how_cpython_runs.py`:

```
SOURCE = 'price = 20\nqty = 3\ntotal = price * qty\nprint("total =", total)\n'
code = compile(SOURCE, "<demo>", "exec")       # steps 1-3
dis.dis(code)                                  # show the bytecode
exec(code, {})                                 # step 5
```

Output (CPython 3.14 – instruction names change between versions):

```
implementation: cpython 3.14.7
code object: code | constants: (20, 'total =', None) | names: ('price', 'qty', 'total', 'print')
--- bytecode ---
  1           LOAD_SMALL_INT          20
              STORE_NAME               0 (price)
  2           LOAD_SMALL_INT           3
              STORE_NAME               1 (qty)
  3           LOAD_NAME                0 (price)
              LOAD_NAME                1 (qty)
              BINARY_OP                5 (*)
              STORE_NAME               2 (total)
  4           LOAD_NAME                3 (print)
              PUSH_NULL
              LOAD_CONST               1 ('total =')
              LOAD_NAME                2 (total)
              CALL                     2
              ...
--- run ---
total = 60
SyntaxError at line 2 - so line 1 never ran
cached bytecode file: __pycache__/shop.cpython-314.pyc
cache tag for this interpreter: cpython-314
```

Read line 3 of the bytecode: push `price`, push `qty`, `BINARY_OP *` pops both and pushes the product, `STORE_NAME` pops it into `total`. That is a stack machine.

Other implementations

Implementation	Runs on	Notable for
CPython	C	The reference; what python.org ships
PyPy	RPython, JIT-compiled	Often several times faster on long-running pure-Python code
MicroPython	Microcontrollers	Tiny memory footprint
GraalPy, Jython	JVM	Java interoperability

CPython itself added an experimental JIT compiler (3.13, off by default) and an optional **free-threaded** build without the GIL (experimental in 3.13, officially supported but still optional in 3.14).

Trade-offs

Bytecode + VM makes Python portable (the same `.py` runs on any OS) and quick to start, at the cost of per-instruction overhead versus native machine code.

Common mistakes

- Thinking `.pyc` files hide or protect source code — they are trivially decompiled and version-specific.
- Committing `__pycache__/` to Git. Ignore it.
- Expecting a syntax error late in the file to let earlier lines run.

In the interview

> **30-second answer:** "CPython tokenizes and parses the whole file into an AST, compiles it to bytecode in a code object, caches bytecode for imported modules in `__pycache__`, and then a stack-based virtual machine executes the bytecode. Since 3.11 it specialises instructions based on observed types."

- *What's in a `.pyc`?* → A header (magic number identifying the bytecode version, plus source timestamp/size or hash) followed by the serialised code object.
- *What is the GIL?* → A lock in the default CPython build that allows only one thread to execute bytecode at a time; it simplifies memory management but limits CPU-bound threading.
- *How can you see bytecode?* → The `dis` module: `dis.dis(func)`.

Self-check

1. Name the stages from source to execution. → Tokenize → parse (AST) → compile (bytecode/code object) → execute on the VM.
2. Is your main script cached as `.pyc`? → No, only imported modules.
3. Why can a syntax error on line 50 prevent line 1 from running? → The whole file is parsed and compiled before execution starts.

TL;DR

Source → tokens → AST → bytecode → VM. "Interpreted" really means "compiled to bytecode, then interpreted".

1.9 Basic syntax

Identifiers

An **identifier** is a name you give to a variable, function, class or module.

Rules (enforced — breaking them is a `SyntaxError`):

1. Starts with a letter or underscore `_`; then any letters, digits, underscores.
2. No spaces or symbols like `-`, `@`, `$`, `!`, `#`, `%`.
3. Case-sensitive: `total`, `Total`, `TOTAL` are three different names.

4. Any length.
5. Not a **keyword** (reserved word). Python 3.14 has 35 keywords (`if`, `for`, `class`, `True`, `None`, …) plus four **soft keywords** – `match`, `case`, `type`, `_` – that are special only in certain positions, so `match = 3` is still legal.
6. Unicode letters are allowed (`café = 1` works), but stick to ASCII for shared code.

From `code/first_program.py`, which tests names with `str.isidentifier()` and `keyword.iskeyword()`:

```
'total'      valid identifier? True
'_private'   valid identifier? True
'user2'      valid identifier? True
'2user'      valid identifier? False
'user-name'  valid identifier? False
'class'      valid identifier? False
'café'       valid identifier? True
```

Lines and indentation

What it is: Python marks a **block** (the body of an `if`, loop, function, class) by *indentation*, not braces `{}`. A line ending in `:` opens a block; every line in it must be indented by the same amount; the block ends when indentation returns to the outer level.

```
if temperature > 30:
    label = "hot"      # inside the if-block
else:
    label = "mild"     # inside the else-block
print(label)           # back at the outer level: always runs
```

Rules:

- PEP 8 says: **4 spaces per level**, never tabs. Configure your editor to insert spaces.
- Mixing tabs and spaces inconsistently is a `TabError` in Python 3.
- An unexpected indent is `IndentationError: unexpected indent`; a missing one after `:` is `IndentationError: expected an indented block`.
- An empty block is illegal – use `pass` as a placeholder (Chapter 3).

Why it matters: the layout you see *is* the structure the computer sees. In brace languages, misleading indentation can hide bugs (a famous example is Apple's 2014 "goto fail" SSL bug, where a duplicated, indented line looked like it belonged to an `if`). In Python that mismatch cannot exist.

Multi-line statements

A statement normally ends at the end of the line. To continue it:

Method	Example	Verdict
Implicit – inside `()`, `[]`, `{}`	`total = (1` ⏎ `+ 2` ⏎ `+ 3)`	Preferred by PEP 8
Explicit – backslash `\` at line end	`total = 1 + \` ⏎ `2 + \` ⏎ `3`	Works, but a stray space after `\` breaks it

Both produce `6` in `line_continuation_demo()`. PEP 8 also suggests breaking long expressions *before* binary operators (`+ 2` at the start of the next line), which lines operators up for the reader.

Quotation marks

Form	Use	Example
`'...'`	Strings containing `"`	`'It said "hi"'`
`"..."`	Strings containing `'`	`"It's sunny"`
`'''...'''` or `"""..."""`	Text spanning lines; docstrings	`"""Line one` ⏎ `Line two"""`

Single and double quotes are identical in meaning — pick one style and stay consistent (formatters like Black standardise on `"`). Output of `quotes_demo()`:

```
It said "hi" | It's sunny | ['Line one', 'Line two']
```

Blank lines

Blank lines are ignored by the interpreter (inside the REPL, a blank line ends a multi-line block). Use them to separate logical steps. PEP 8: **two** blank lines around top-level functions and classes, **one** between methods in a class.

Reading user input

`input(prompt)` prints the prompt, waits for the user to press Enter, and returns what they typed **as a `str`** — **always**, even if they typed digits.

```
user_name = input("Please enter your name: ")
print("Hello, " + user_name + "!")
```

The runnable script replaces `input()` with a stand-in so it runs unattended; the output is what a user typing `Ada` would see:

```
Please enter your name: Ada
Hello, Ada!
```

To do maths with input, convert it: `age = int(input("Age: "))` (Chapter 2 covers conversion and its errors).

Several statements on one line

A semicolon `;` separates statements on a single line:

```
import sys; x = "foo"; sys.stdout.write(x + "\n")      # prints: foo
```

It is legal, but PEP 8 discourages it: one statement per line is easier to read, diff and debug. (`sys.stdout.write` is the lower-level cousin of `print`: it writes exactly the string you give it, with no automatic newline.)

Common mistakes

- Forgetting the colon: `if x > 3` → `SyntaxError: expected ':'`.
- Copying code from the web that uses tabs into a file that uses spaces.
- Treating `input()` as a number: `input() + 1` → `TypeError`.
- Using `-` in names (`user-name` means "user minus name").

In the interview

> **30-second answer:** "Python uses indentation to define blocks — four spaces per PEP 8 — so visual structure equals logical structure. Statements end at the newline unless you're inside brackets, which is the preferred way to continue a line. Identifiers are case-sensitive and can't be keywords."

- *What's a soft keyword?* → A word that's only reserved in a specific context, like `match`/`case` in a match statement, so old code using `match` as a variable still works.
- *Why prefer brackets over backslashes?* → A backslash fails silently if followed by whitespace, and brackets let editors auto-indent.

Self-check

1. Is `my-var` a valid identifier? → No; `-` is subtraction.
2. What does `input()` return if the user types `42`? → The string `"42"`.

3. What error do you get for inconsistent tabs and spaces? → `TabError`.
4. How many spaces per indentation level does PEP 8 recommend? → 4.

TL;DR

Names: letters/digits/underscore, not starting with a digit, not keywords, case-sensitive. Blocks = `:` + 4-space indent. Continue lines inside brackets. `input()` returns `str`. Avoid `;`.

1.10 Comments and docstrings

What it is

- A **comment** starts with `#` and runs to the end of the line. The tokenizer throws it away; it never reaches the bytecode. It is a note for humans.
- A **docstring** is a string literal placed as the *first statement* of a module, function, class or method. Unlike a comment, it is kept at run time in the object's `__doc__` attribute, and tools (`help()`, IDE tooltips, Sphinx documentation generators) read it.

Single-line and inline comments

```
# A comment explains WHY; the code already says WHAT.
return width * height  # inline comment: two spaces before the '#'
```

PEP 8: start with `# ` (hash + space); for inline comments put at least two spaces before `#`; keep comments up to date — a wrong comment is worse than none.

"Multi-line comments"

Python has **no** dedicated multi-line comment syntax. Two options:

1. **Consecutive `#` lines** — the correct way; every editor can toggle them with one shortcut.
2. **A triple-quoted string not assigned to anything** — often called a "multi-line comment". Technically it is an *expression statement*: the string is a value that is created and immediately discarded (CPython usually optimises it away). It "works", but it is not a comment: if it happens to be the first statement in a function it silently becomes the docstring, and it must obey indentation rules like any other statement. Prefer `#` lines; reserve triple quotes for docstrings.

Docstrings

From `code/comments_docstrings.py`:

```
def area(width: float, height: float) -> float:
    """Return the area of a rectangle.

    Args:
        width: size along x, in metres.
        height: size along y, in metres.
    """
    return width * height
```

Output:

```
module doc first line: Chapter 1 - comments vs docstrings, PEP 20, and keywords.
function doc first line: Return the area of a rectangle.
area(3, 4) = 12
```

Conventions (PEP 257): triple double quotes; a one-line summary in the imperative ("Return…", not "Returns…"), ending with a period; for longer docstrings a blank line then details. Popular layouts for the details are

Google style (shown above), NumPy style and reStructuredText.

Comments vs docstrings

	`#` comment	Docstring
Kept at run time?	No	Yes, in `__doc__`
Audience	Maintainers reading the code	Users of the function/module (via `help()`, IDEs)
Content	*Why* a tricky line exists	*What* the object does, its arguments, return value, errors
Position	Anywhere	First statement of module/class/function

Common mistakes

- Comments that repeat the code (`x += 1 # add one to x`). Explain intent instead.
- Leaving commented-out code blocks around – that's what version control is for.
- Writing a docstring after the first statement (it's then just an ignored string).

In the interview

> **30-second answer:** "Comments start with `#` and are discarded by the tokenizer; they explain *why*. Docstrings are the first string literal in a module, class or function, stored in `__doc__`, and describe *what* the object does for its users. Python has no block-comment syntax; use several `#` lines."

- *Is a triple-quoted string a comment?* → No, it's a string expression that's evaluated and discarded – unless it's first in a body, then it's a docstring.
- *How do you read a docstring at runtime?* → `obj.__doc__` or `help(obj)`.

Self-check

1. Where must a docstring go? → First statement in the module/class/function body.
2. Do comments slow down your program? → No; they're removed during tokenizing.
3. Proper way to comment out five lines? → Put `#` at the start of each (editor shortcut).

TL;DR

`#` = note for maintainers, gone at run time. Docstring = first-statement string, kept in `__doc__`, read by `help()` and IDEs. No real multi-line comments – use several `#` lines.

1.11 PEP 8 and PEP 20 – writing Pythonic code

What it is

- **PEP 8** is the official **style guide**: how Python code should *look*. Consistency lets any Python developer read any codebase.
- **PEP 20**, *The Zen of Python* by Tim Peters, is the language's **philosophy** in 19 short aphorisms. Type `import this` to print it.

PEP 8 essentials

Rule	Example
4 spaces per indent, no tabs	`····return x`
Lines ≤ 79 characters (72 for comments/docstrings); many teams relax to 88–100	–
`snake_case` for variables, functions, modules	`user_age`, `load_data()`
`CapWords` (CamelCase) for classes	`UserProfile`
`UPPER_SNAKE_CASE` for constants	`MAX_RETRIES = 3`
Leading `_` for "internal" names	`_cache`
Spaces around `=` in assignments and around comparisons; none inside brackets	`x = f(a, b)` not `x=f( a,b )`
No spaces around `=` in keyword arguments	`print(x, end="")`
Imports at the top, one per line, grouped: standard library, third-party, local	`import os` ⏎ `import sys`
Two blank lines around top-level functions/classes	–
Compare to `None` with `is`, not `==`	`if x is None:`
Don't compare booleans to `True`	`if ready:` not `if ready == True:`

PEP 8 itself says consistency within a project beats rigid rule-following. Automate it: **Black** or **Ruff** formats code; **Ruff** or **Flake8** lints.

PEP 20 – the aphorisms that matter most

From `code/comments_docstrings.py`, which captures the output of `import this`:

```
Zen of Python has 19 aphorisms, e.g.:
   Beautiful is better than ugly.
   Explicit is better than implicit.
   Simple is better than complex.
   Readability counts.
35 hard keywords, e.g. ['False', 'None', 'True', 'and', 'as', 'assert']
soft keywords (only special in some places): ['_', 'case', 'match', 'type']
```

How they show up in daily decisions:

Aphorism	In practice
Explicit is better than implicit	`from math import sqrt` rather than `from math import *`
Readability counts	Descriptive names; one statement per line
Errors should never pass silently	Don't write `except: pass`
There should be one obvious way to do it	Use `for item in items`, not index juggling
Flat is better than nested	Early returns instead of deep `if` pyramids (Chapter 3)
In the face of ambiguity, refuse the temptation to guess	Why `"3" + 4` raises instead of guessing

"**Pythonic**" means code that follows these idioms.

Common mistakes

- Arguing about style in code review – let the formatter decide.
- Using `camelCase` for functions (a Java habit).

In the interview

> **30-second answer:** "PEP 8 is the style guide – 4-space indents, snake_case functions, CapWords classes, 79-char lines, grouped imports – and I enforce it with Ruff or Black. PEP 20 is the Zen of Python; the ideas I lean on most are 'explicit is better than implicit', 'readability counts' and 'errors should never pass silently'."

- *What does "Pythonic" mean?* → Using the language's idioms (iteration, context managers, comprehensions) instead of translating another language line by line.

Self-check

1. Name style for a class holding user settings? → `UserSettings`.
2. How do you print the Zen of Python? → `import this`.
3. Which is PEP 8-correct: `if x == None` or `if x is None`? → `if x is None`.

TL;DR

PEP 8 = how code looks (automate it). PEP 20 = why Python feels the way it does. Together they define "Pythonic".

Chapter 1 TL;DR

- Python is a high-level, dynamically and strongly typed, garbage-collected language; CPython is the reference implementation; Python 3 is the only supported line.
- It's used for web back-ends, data, ML, science, automation, games scripting, GUIs, education and IoT – mostly because of its libraries.
- Install from python.org or your OS; give each project a `.venv`; install with `python -m pip`.
- REPL (`>>>`) for experiments, `.py` scripts for real work, `if __name__ == "__main__":` for start-up code.
- CPython: source → tokens → AST → bytecode (cached as `.pyc` for imports) → stack-based VM. The whole file is compiled before any line runs.
- Syntax: blocks by `:` + 4-space indentation; case-sensitive identifiers; continue lines inside brackets; `'` / `"` / `"""` strings; `input()` returns `str`; avoid `;`.
- `#` comments vanish at compile time; docstrings live in `__doc__`.
- Follow PEP 8 (enforced by a formatter) and the spirit of PEP 20.