
Chapter 13 — Type Hints and Static Typing

What you will learn. Why a dynamic language added optional types, and how to write them: annotation syntax, built-in generics such as `list[int]`, `Optional` / `Union` / `X | None`, `Any`, generics with `TypeVar` and the new 3.12 bracket syntax, `Callable` and `ParamSpec`, structural typing with `Protocol`, and the special forms `TypedDict`, `Literal`, `Final` and `NewType`. Then how types meet `dataclasses`, how to name types with aliases and the 3.12 `type` statement, how to run **mypy** and **pyright** and read their errors, what types do (and do not do) at runtime, and how **pydantic** turns hints into runtime validation.

Prerequisites. Functions (Chapter 7), classes and dataclasses (Chapter 10), decorators (Chapter 12).

Code. Every script is in `chapters/13-type-hints/code/` and runs on Python 3.12+. Script `04_run_mypy.py` needs `pip install mypy`:

```
python chapters/13-type-hints/code/02_generics_protocols.py
mypy --strict chapters/13-type-hints/code/03_special_forms.py
```



13.1 Why typing?

What it is

A **type hint** (or *annotation*) is a note attached to a variable, parameter or return value saying what kind of value it should hold: `def area(w: float, h: float) -> float`. Python itself **does not enforce** these notes. Separate programs called **static type checkers** (mypy, pyright) read your source code *without running it* and report places where the notes are contradicted.

Two words you will see everywhere:

- **Dynamic typing** — types belong to *values*, and are checked while the program runs (`"a" + 1` fails only when that line executes). Python is dynamically typed.
- **Static typing** — types are checked *before* the program runs, from the source text. Java, Go and Rust do this in the compiler.

Python's type hints give you **gradual typing**: you can add types to as much or as little of the code as you like, and un-annotated code is treated leniently.

Analogy: hints are road signs. The car (the interpreter) does not stop you from ignoring them; the type checker is the driving instructor who reads the route beforehand and says "this turn is a dead end".

Why it matters

1. **Bugs found early.** Passing `None` where a `str` is expected, misspelled attribute names, wrong argument order — caught before tests, before production.
2. **Documentation that cannot go stale.** A signature like `def fetch(ids: list[int]) -> dict[int, User]` explains itself, and the checker complains if the code drifts from it.
3. **Editor power.** Autocomplete, go-to-definition and safe renames all work much better when the editor knows the types (VS Code's Pylance is built on pyright).
4. **Safer refactoring** in large codebases: change a function's signature and the checker lists every caller that must change.

How it works

1. Annotations were added in Python 3.0 (PEP 3107) as free-form metadata; PEP 484 (Python 3.5) gave them standard meaning and created the `typing` module.

2. At runtime, annotations are stored on the object (`func.__annotations__`) and otherwise ignored.
3. A checker parses your code, infers the type of every expression, and compares it with what each annotation promises.
4. Un-annotated code is treated as `Any` (see §13.5), which is why you can adopt typing one file at a time.

Trade-offs

Benefit	Cost
Catches whole classes of bugs before running	Extra syntax to learn and write
Self-documenting APIs, better IDE support	Some dynamic patterns are awkward to type
Refactoring confidence at scale	False sense of safety if `Any` leaks everywhere
Zero runtime cost (hints are not checked)	…which also means no runtime protection

When not to use it

Throw-away scripts, notebooks exploring data, and tiny programs gain little. Types pay off in code that lives long, is shared by several people, or is a library others call.

Real-world examples

Dropbox type-checked about 4 million lines of Python with mypy (Guido van Rossum worked on mypy there). Instagram and Meta built the Pyre checker; Microsoft built pyright. **FastAPI** and **pydantic** read type hints at runtime to validate requests and generate API docs. The standard library's type information lives in the **typeshed** project, which every checker uses.

In the interview

"Python is dynamically typed, but since PEP 484 we can add optional type hints. They're ignored at runtime; a static checker like mypy or pyright verifies them before the code runs. It's gradual, so you can type a codebase incrementally. I use them on anything long-lived because they catch `None` bugs and make refactors safe."

- *Do hints make code faster?* No. CPython ignores them. (Tools like mypyc can compile typed code to C extensions, but that is a separate compiler.)
- *Does `x: int = "a"` raise?* No, it runs fine. Only the checker complains.

Self-check

1. Are annotations enforced when the program runs? → No; they are metadata for tools.
2. What does "gradual typing" mean? → Typed and untyped code can coexist; un-annotated parts are treated as `Any`.
3. Name two static checkers. → mypy, pyright (also Pyre; newer Rust-based ones like Astral's ty and Meta's Pyrefly).

TL;DR

Hints are optional, unenforced notes. A static checker reads them to find bugs before runtime. Adopt gradually; the biggest wins are in long-lived, shared code.

13.2 Annotation syntax

What it is

The places you can write an annotation:

```python
def greet(name: str, times: int = 1) -> str:   # parameters and return
    return ", ".join([f"hi {name}"] * times)

port: int = 8080                               # variable with value
scores: dict[str, list[int]] = {"asha": [90]}  # nested types
total: int                                     # bare annotation: declares, creates nothing

class User:
    name: str            # class-level annotation (dataclasses use these as fields)
    def rename(self, new: str) -> None: ...     # self is not annotated
```

How it works

1. `param: Type` annotates a parameter; with a default it is `param: Type = default` (spaces around `=`, unlike the un-annotated `param=default` – PEP 8).
2. `-> Type` annotates the return. A function that returns nothing is `-> None`.
3. `name: Type = value` annotates a variable (PEP 526). A bare `name: Type` creates **no** variable – reading `total` above raises `NameError`.
4. Annotations are stored in `__annotations__`; `typing.get_type_hints(obj)` returns them fully resolved (turning string forward references into real classes).
5. **Forward references.** If a type is not defined yet (a class referring to itself), write it as a string: `def clone(self) -> "Node":`. Since 3.11 you can also use `typing.Self` for "the current class".
6. **When are annotations evaluated?** Up to 3.13, annotations are evaluated when the `def` runs (unless the module has `from __future__ import annotations`, which stores them as strings). **Python 3.14** (PEP 649/749) makes evaluation *lazy* by default: annotations are computed only when someone asks for them, so forward references usually work without quotes. The new `annotationlib` module exposes the details.

Script `01_annotations_basics.py`:

```python
print("greet annotations:", greet.__annotations__)
print("get_type_hints    :", get_type_hints(greet))
print("greet(123, 2)     :", greet(123, 2))   # int passed for str - runs fine
```

Output:

```
greet annotations: {'name': <class 'str'>, 'times': <class 'int'>, 'return': <class 'str'>}
get_type_hints    : {'name': <class 'str'>, 'times': <class 'int'>, 'return': <class 'str'>}
greet(123, 2)     : hi 123, hi 123
```

The last line proves the point: Python happily ran `greet(123, 2)`. Running mypy on the same file reports it:

```
01_annotations_basics.py:34: error: Argument 1 to "greet" has incompatible type "int"; expected "str"  [arg-type]
```

What to annotate

- **Always:** function parameters and return types of public functions. This is where types help most.
- **Rarely:** local variables. The checker **infers** `x = 5` as `int`. Annotate locals only when inference cannot work, e.g. an empty container: `seen: set[str] = set()`.

Common mistakes

- Forgetting `-> None`. Under mypy's default settings a function with *no* annotations at all is not checked inside – adding `-> None` opts it in.
- Writing `def f(x: int=5)` – works, but style is `x: int = 5`.
- Expecting `total: int` to create `total`.

TL;DR

`param: T`, `-> T`, `var: T = value`. Annotate signatures, let inference handle locals. Hints live in `__annotations__`; read them with `get_type_hints`.

13.3 Built-in generics and the abstract collection types

What it is

A **generic type** is a container type with a *parameter* saying what it holds: `list[int]` is "a list of ints". Since Python 3.9 (PEP 585) the built-in classes accept brackets directly — you no longer need `typing.List`, `typing.Dict`, etc. (they still work but are deprecated aliases).

Type	Meaning
`list[int]`	list of ints
`dict[str, float]`	keys `str`, values `float`
`set[str]`, `frozenset[str]`	set of strings
`tuple[int, str]`	**exactly** two items: an int then a str
`tuple[int, ...]`	any length, all ints
`tuple[()]`	the empty tuple
`type[User]`	the class `User` itself (or a subclass), not an instance

Accept abstract, return concrete

`collections.abc` defines *abstract* collection types you can also parameterise:

Abstract type	What it promises	Accepts
`Iterable[T]`	can be looped over	list, tuple, set, dict, generator, file…
`Sequence[T]`	indexable, has `len`, read-only	list, tuple, str, range
`Mapping[K, V]`	read-only dict-like	dict, `MappingProxyType`, custom
`MutableSequence[T]`, `MutableMapping[K, V]`	can be modified	list / dict
`Iterator[T]`, `Generator[Y, S, R]`	produced by generators	generator functions

The rule (from *Robust Python* and *Fluent Python* alike): **parameters should ask for the least they need; return values should say exactly what they give.**

```
from collections.abc import Iterable

def total(prices: Iterable[float]) -> float:   # works with list, tuple, generator
    return sum(prices)

def tokens(text: str) -> list[str]:            # caller knows they get a real list
    return text.split()
```

Variance in one paragraph

Is `list[int]` a `list[float]`? **No.** A function taking `list[float]` could append `2.5` to it, which would corrupt your `list[int]`. Mutable containers are **invariant** — the parameter must match exactly. Read-only ones like

`Sequence` are **covariant**: a `Sequence[int]` *is* accepted where `Sequence[float]` is expected, since nothing can be written into it. (Separately, the typing rules let a plain `int` be passed where a `float` is expected — a special "numeric promotion".) This is one more reason to prefer `Sequence` / `Iterable` for parameters.

Common mistakes

- `def f(xs: list)` — a bare `list` means `list[Any]`; you lose checking of the items.
- `tuple[int]` when you meant "tuple of ints" — that is a one-element tuple. Use `tuple[int, ...]`.
- Importing `List`, `Dict` from `typing` in new code (fine, just old style).

TL;DR

Use `list[int]`, `dict[str, int]`, `tuple[int, ...]` directly. For parameters prefer `Iterable` / `Sequence` / `Mapping` from `collections.abc`; mutable containers are invariant.

13.4 `Optional`, `Union` and `X | None`

What it is

- A **union** means "one of these types": `int | str` (3.10+, PEP 604) or `Union[int, str]` (older).
- `X | None` means "an `X` or `None`". `Optional[X]` is exactly the same type — the name is misleading: it does **not** mean "optional argument", it means "may be None".

```
def find_user(user_id: int) -> str | None:
    users = {1: "asha", 2: "ben"}
    return users.get(user_id)
```

Why it matters

`None` bugs (`'NoneType' object has no attribute 'upper'`) are among the most common production errors in Python. Tony Hoare called null references his "billion-dollar mistake". Marking the possibility in the type forces every caller to handle it.

How it works — narrowing

The checker tracks **narrowing**: after a check, it knows a more specific type in that branch.

```
def f(x: int | str | None) -> None:
    if x is None:
        return
    reveal_type(x)          # int | str
    if isinstance(x, int):
        reveal_type(x)      # int
    else:
        reveal_type(x)      # str
```

`reveal_type(...)` is a checker built-in (also importable from `typing` since 3.11) that makes mypy print the inferred type. Real mypy output for this snippet:

```
note: Revealed type is "int | str"
note: Revealed type is "int"
note: Revealed type is "str"
```

Things that narrow: `is None` / `is not None`, `isinstance`, truthiness (`if x:` — careful, it also removes `""` and `0`), `==` against a literal, `match` patterns, early `return` / `raise`, and your own functions returning `TypeGuard[T]` or (3.13+) `TypeIs[T]`.

Unions also work at runtime in `isinstance`: `isinstance(5, int | str)` → `True`.

Common mistakes

- `def f(x: str = None)` – the default is `None`, so the type must be `str | None`. mypy rejects the shorthand by default ("implicit Optional" is off since mypy 0.990).
- Using `if x:` to narrow when `0` or `""` are valid values – use `if x is not None:`.
- Returning `X | None` everywhere "just in case": every caller must then check. Raise an exception instead when absence is an error.

In the interview

"`Optional[X]` is just `X | None`. The checker forces callers to narrow with `is not None` before using it, which eliminates most `NoneType has no attribute` errors."

- *Is `Optional` about default arguments?* No – a parameter can have a default and not be Optional, and vice versa.

TL;DR

`A | B` = either. `X | None` = `Optional[X]` = may be None. Narrow with `is not None`, `isinstance`, or early return before use.

13.5 `Any` (and `object`)

What it is

`Any` is the escape hatch: a value of type `Any` is compatible with **every** type in both directions, and every operation on it is allowed. Checking is switched off for it. Un-annotated parameters are implicitly `Any`.

`object` is the opposite: it is the top of the class hierarchy. **Anything can be passed in**, but you can only do things every object supports (`print`, `==`, `hash`) until you narrow it.

	Accepts anything?	Can call any method on it?	Safety
`Any`	yes	yes	none
`object`	yes	no (must narrow with `isinstance`)	full

```python
def load(raw: Any) -> None:
    raw.whatever()        # checker says nothing - could crash at runtime

def show(x: object) -> None:
    x.upper()             # error: "object" has no attribute "upper"
    if isinstance(x, str):
        x.upper()         # fine after narrowing
```

When to use it

- Truly dynamic data at a boundary (a parsed JSON blob before validation), or a third-party library without types.
- Temporarily during migration.

Common mistakes

`Any` is **contagious**: `y = raw.field` is also `Any`, and so is everything computed from it. A few `Any`s at the edges can silently disable checking deep inside. Prefer `object` when you just mean "I accept anything"; validate and convert `Any` data into real types as early as possible (§13.14). `mypy --strict` includes flags that warn about `Any` leaking from untyped code.

TL;DR

`Any` turns checking off; `object` accepts everything but keeps checking. Contain `Any` at boundaries.

13.6 `TypeVar` and generics

What it is

A **type variable** is a placeholder that stands for "some type, the same one each time it appears". It lets you write one function that works for many types *without* losing precision.

The problem it solves: `def first(items: list[Any]) -> Any` works, but `first([1, 2]) + "x"` is not caught — the result is `Any`. With a type variable, the checker knows `first([1, 2])` is an `int`.

How it works

Old style (3.5–3.11), still common:

```
from typing import TypeVar
T = TypeVar("T")

def first_old(items: Sequence[T]) -> T:
    return items[0]
```

New style (3.12+, PEP 695) — declare type parameters in square brackets; no separate `TypeVar` line:

```
def first[T](items: Sequence[T]) -> T:
    return items[0]

def biggest[N: (int, float)](a: N, b: N) -> N:   # constrained: N is int or float
    return a if a > b else b

class Stack[T]:
    def __init__(self) -> None:
        self._items: list[T] = []
    def push(self, item: T) -> None:
        self._items.append(item)
    def pop(self) -> T:
        return self._items.pop()
```

1. At each call, the checker **solves** `T` from the arguments: `first("xyz")` → `T = str` → returns `str`.
2. **Bound**: `[T: Hashable]` (old: `TypeVar("T", bound=Hashable)`) means "T can be any subtype of Hashable".
3. **Constraints**: `[N: (int, float)]` means "`N` is solved to exactly `int` or exactly `float`, never a subclass or a mix". So `biggest(2, 7)` returns `int`, and `biggest(2, 7.0)` returns `float` (the `int` is accepted as a `float`, see *numeric promotion* in §13.3). The classic example is `AnyStr = (str, bytes)`: `concat("a", b"b")` is rejected because no single choice fits both.
4. **Generic class**: `Stack[int]()` or `s: Stack[int] = Stack()` fixes `T` for that instance; `s.push("a")` is then an error.
5. Old-style generic classes inherit `Generic[T]`: `class Stack(Generic[T]): ...`.
6. Since 3.13 (PEP 696), type parameters can have **defaults**: `class Box[T = int]: ...`.

Output of `02_generics_protocols.py` (generic part):

```
first_old([3,4]) : 3
first('xyz')     : x
biggest(2, 7)    : 7
Stack pop        : 2 | len 1
type params      : (T,) (T,)
```

The 3.12 syntax also records the parameters at runtime in `__type_params__`.

Trade-offs

	Old `TypeVar`	3.12 `[T]` syntax
Works on	3.5+	3.12+ only
Scope	module-global name, easy to misuse	scoped to the function/class
Variance	declared manually (`covariant=True`)	inferred automatically

Common mistakes

- Using a type variable only once in a signature (`def f(x: T) -> None`) – it adds nothing; use `object`.
- Reusing one old-style `T` across unrelated functions and being confused – each function solves it independently, which is fine, but the 3.12 syntax makes this clearer.

Real-world examples

`dict.get`, `list.__getitem__`, `max`, `sorted`, `functools.lru_cache` and `asyncio.Queue[T]` are all generic in typeshed. SQLAlchemy 2.0's `Mapped[int]` and Django-stubs use generics so ORM columns have precise types.

In the interview

"A TypeVar ties input and output types together, so `first(list_of_ints)` returns `int` instead of `Any`. Since 3.12 I write `def first[T](xs: Sequence[T]) -> T` and `class Stack[T]`."

- *Bound vs constrained?* Bound: any subtype of X. Constrained: exactly one of the listed types.
- *Why is `list[int]` not a `list[float]`?* Invariance – the callee could insert a float.

Self-check

1. What does `first([1, 2])` return to the checker with `-> T`? → `int`.
2. How do you declare a generic class in 3.12? → `class Stack[T]: ...`.
3. When is a TypeVar pointless? → When it appears only once in the signature.

TL;DR

Type variables connect types across a signature. Prefer `def f[T](...)` / `class C[T]` on 3.12+; use `bound=` or constraints to restrict them.

13.7 `Callable` and `ParamSpec`

What it is

`Callable[[Arg1, Arg2], Return]` is the type of "something you can call with these arguments that returns this". Import it from `collections.abc` (the `typing` version is a deprecated alias).

```
from collections.abc import Callable, Iterable

def apply_all(fn: Callable[[int], int], xs: Iterable[int]) -> list[int]:
    return [fn(x) for x in xs]
```

- `Callable[..., int]` – any arguments, returns int (loose).
- `Callable[[], None]` – no arguments, returns nothing (a callback).
- For keyword arguments, overloads or default values, `Callable` cannot express the signature; define a `Protocol` with a `__call__` method instead (§13.8).

ParamSpec – typing decorators (brief)

A decorator that wraps *any* function should keep that function's exact parameters. Before `ParamSpec` (3.10, PEP 612) people wrote `Callable[..., Any]` and lost all checking of the decorated function's arguments.

```
P = ParamSpec("P")
R = TypeVar("R")

def timed(fn: Callable[P, R]) -> Callable[P, R]:
    @wraps(fn)
    def wrapper(*args: P.args, **kwargs: P.kwargs) -> R:
        start = time.perf_counter()
        try:
            return fn(*args, **kwargs)
        finally:
            print(f"  {fn.__name__} took {time.perf_counter() - start:.4f}s")
    return wrapper

@timed
def add(a: int, b: int) -> int:
    return a + b
```

1. `P` captures the whole parameter list of `fn`; `R` captures its return type.
2. `*args: P.args, **kwargs: P.kwargs` says "the wrapper takes exactly what `fn` takes".
3. The result type `Callable[P, R]` means `add("x", 1)` is still flagged after decoration.
4. 3.12 syntax: `def timed[**P, R](fn: Callable[P, R]) -> Callable[P, R]:`.
5. `Concatenate[Request, P]` expresses decorators that add or remove a leading argument.

Output:

```
apply_all       : [1, 4, 9]
add(2, 3) ->
  add took 0.0000s
  result 5
```

TL;DR

`Callable[[args], ret]` types function values. `ParamSpec` lets decorators preserve the wrapped signature.

13.8 `Protocol` — structural typing

What it is

Nominal typing means "B is a subtype of A because B *inherits* from A". **Structural typing** means "B is compatible with A because it *has the right methods*", whatever its ancestry. A `Protocol` (PEP 544, 3.8) declares such a shape. It is duck typing — "if it walks like a duck…" — made checkable.

Why it matters

- You can type code against objects you do not control (a third-party class cannot be made to inherit your ABC, but it may already have a `close()` method).
- It decouples modules: the consumer defines the tiny interface it needs; producers need not import it.

How it works

```
from typing import Protocol, runtime_checkable

@runtime_checkable
class SupportsClose(Protocol):
    def close(self) -> None: ...

class DbConnection:              # does NOT inherit from SupportsClose
    def close(self) -> None:
        print("  db closed")

def close_all(things: Iterable[SupportsClose]) -> None:
    for t in things:
        t.close()
```

1. A class body that inherits `Protocol` lists the required methods/attributes with `...` bodies.
2. Any class whose members match (names **and** compatible signatures) satisfies it — checked statically.
3. `@runtime_checkable` additionally allows `isinstance(x, SupportsClose)`; at runtime this checks only that the **names exist**, not their signatures.
4. Protocols can be generic: `class SupportsLessThan[T](Protocol): def __lt__(self, other: T) -> bool: ...`.

Output:

```
close_all ->
  db closed
  temp file removed
isinstance(DbConnection(), SupportsClose): True
isinstance(42, SupportsClose)            : False
```

Trade-offs — Protocol vs ABC

	`Protocol`	`abc.ABC`
Relationship	structural (shape)	nominal (must inherit / register)
Checked	by the type checker	at instantiation (`TypeError` if abstract methods missing)
Shares implementation	not intended	yes, concrete helper methods
Works with third-party classes	yes	only with `register()`

Common mistakes

- Trusting `isinstance` with a runtime-checkable protocol to verify signatures — it doesn't.
- Big protocols. Keep them small (one to three methods), like the standard ones: `Iterable`, `Sized`, `Hashable`, `SupportsInt`, `SupportsAbs`.

Real-world examples

`typing.SupportsIndex`, `collections.abc.Iterable` and typeshed's `SupportsRead[str]` (used for "anything with a `.read()` method", e.g. in `json.load`) are all structural.

In the interview

"A Protocol is a statically checked duck type: any class with matching methods satisfies it, with no inheritance. I use it to define the minimal interface a function needs, for example `SupportsClose`, which also makes testing with fakes easy."

- *Protocol or ABC?* ABC when you want to share code and force subclasses to implement methods; Protocol when you only describe a shape.

TL;DR

`Protocol` = interface by shape. Keep it small; `@runtime_checkable` only checks method names.

13.9 `TypedDict`

What it is

A **TypedDict** describes a dict with a fixed set of string keys, each with its own value type – the typical shape of JSON objects and configuration.

```
from typing import NotRequired, TypedDict

class Movie(TypedDict):
    title: str
    year: int
    rating: NotRequired[float]      # key may be absent (3.11+)

m: Movie = {"title": "Arrival", "year": 2016}
```

How it works

1. The checker verifies keys and value types in literals and on access: `m["yeer"]` and `m["year"] = "2016"` are errors.
2. By default every key is required. Use `NotRequired[...]` per key, or `class Movie(TypedDict, total=False)` to make all optional (then `Required[...]` for exceptions). `ReadOnly[...]` (3.13) forbids writes.
3. **At runtime it is just a `dict`**: no validation, no class instance. `isinstance(x, Movie)` raises `TypeError`.

Output:

```
TypedDict value  : {'title': 'Arrival', 'year': 2016} | type at runtime: dict
Movie keys       : frozenset({'title', 'year'}) frozenset({'rating'})
```

TypedDict vs dataclass

	TypedDict	dataclass
Runtime object	plain `dict`	instance of your class
Access	`m["title"]`	`m.title`
Methods	none	yes
Best for	JSON in/out, `**kwargs` typing (`Unpack[Opts]`)	domain objects in your code

TL;DR

TypedDict types dict-shaped data (JSON). It's static only – a normal dict at runtime.

13.10 `Literal` , `Final` , `NewType`

`Literal` – only these exact values

```
Mode = Literal["r", "w", "a"]
def open_log(path: str, mode: Mode = "r") -> str: ...
open_log("app.log", "x")      # error: expected "Literal['r', 'w', 'a']"
```

Good for string/int "flags" when an `Enum` feels heavy. `typing.get_args(Mode)` returns `('r', 'w', 'a')` at runtime, which you can use for validation. `match` / `==` against a literal narrows it. Standard library example: `open()`'s `mode` is typed with literals in typeshed so the checker knows `open(p, "rb")` returns a binary file.

`Final` – must not be reassigned

```
MAX_RETRIES: Final = 3        # inferred as int, and constant
MAX_RETRIES = 4               # error: Cannot assign to final name "MAX_RETRIES"
```

Also `@final` on a method (no overriding) or class (no subclassing). Not enforced at runtime. Related: `@typing.override` (3.12) marks a method that must override a parent method, catching typos in method names.

`NewType` – a distinct name for the same runtime type

```
UserId = NewType("UserId", int)
OrderId = NewType("OrderId", int)

def get_user(uid: UserId) -> str: ...
get_user(UserId(7))   # OK
get_user(42)          # error: expected "UserId"
```

1. For the checker, `UserId` is a *subtype* of `int`: you can pass a `UserId` where an `int` is expected, but not the reverse.
2. At runtime `UserId(7)` just returns `7` – `type(UserId(7)) is int` is `True`. Zero cost.
3. Use it to stop mixing up IDs, units (`Meters` vs `Feet`) or sanitised vs raw strings (`SafeHtml`).

Output of `03_special_forms.py`:

```
Literal args     : ('r', 'w', 'a')
open app.log in 'a'
NewType          : user#7 | UserId(7) is int: True
```

Common mistakes

- `NewType` vs alias: `UserId = int` is an alias (interchangeable – no protection); `NewType` makes a distinct type.
- Expecting `Final` or `Literal` to raise at runtime.

Other special forms you will meet

Form	Meaning	Example
`Annotated[T, meta]` (3.9)	Type `T` plus extra metadata the checker ignores but libraries read	FastAPI/pydantic: `age: Annotated[int, Field(gt=0)]`
`Self` (3.11)	"An instance of the current class" – for fluent methods and alternative constructors	`def with_name(self, n: str) -> Self:`
`NoReturn` / `Never` (3.11)	The function never returns normally (always raises or exits)	`def fail(msg: str) -> NoReturn: raise SystemExit(msg)`
`ClassVar[T]`	A class-level attribute, not a per-instance field	`count: ClassVar[int] = 0`
`@overload`	Several signatures for one function, when the return type depends on the arguments	`open(p, "rb")` → binary file, `open(p, "r")` → text file
`TypeGuard[T]` / `TypeIs[T]` (3.10 / 3.13)	A user function that narrows its argument when it returns `True`	`def is_str_list(x: list[object]) -> TypeIs[list[str]]:`
`LiteralString` (3.11)	Only strings written in the source code, not user input	SQL query builders defending against injection
`Unpack[TD]` (3.11/3.12)	Type `**kwargs` with a `TypedDict`	`def f(**kw: Unpack[Opts]):`

TL;DR

`Literal` = fixed values; `Final` = no reassignment; `NewType` = type-safe wrapper with no runtime cost. `Annotated`, `Self`, `Never`, `@overload`, `TypeIs` cover the remaining common cases.

13.11 dataclasses and typing

What it is

`@dataclass` (Chapter 10) reads the **class-level annotations** to decide which fields exist and in what order, and generates `__init__`, `__repr__` and `__eq__`. It is the best-known place in the standard library where annotations change runtime behaviour (others: `typing.NamedTuple`, `TypedDict`, and `functools.singledispatch`'s `register`, which can dispatch on a parameter's annotation) – but it uses them only as *field declarations*; it does not validate types.

```
@dataclass(frozen=True, slots=True)
class Point:
    x: float
    y: float
    tags: tuple[str, ...] = ()

@dataclass
class Cart:
    owner: str
    items: list[str] = field(default_factory=list)
```

How it works

1. Each annotated class attribute becomes a field; the generated `__init__` has typed parameters, so checkers verify `Point("a", 2)`.
2. Attributes annotated `ClassVar[int]` are **not** fields; `InitVar[str]` is an `__init__`-only parameter passed to `__post_init__`.
3. Mutable defaults need `field(default_factory=list)` – a plain `= []` raises `ValueError` at class creation.

4. `frozen=True` makes instances immutable (checkers flag `p.x = 5`; at runtime it raises `FrozenInstanceError`).
5. `Point(x="oops", y=2)` **runs** — dataclasses do not check types.

Output:

```
dataclass        : Point(x=1.0, y=2.0, tags=()) | fields: ['x', 'y', 'tags']
default_factory  : ['pen'] []
frozen           : FrozenInstanceError
```

Related typed record types

Tool	Mutable	Validates types	Notes
`@dataclass`	yes (or `frozen`)	no	the default choice
`typing.NamedTuple`	no	no	a real tuple (unpacks, indexes)
`TypedDict`	yes	no	plain dict
`attrs` (third-party)	configurable	optional validators	dataclasses' ancestor
`pydantic.BaseModel`	yes	**yes**	for untrusted input (§13.14)

TL;DR

dataclasses turn annotations into fields but never validate. Use `field(default_factory=...)`, `ClassVar`, `frozen=True` as needed.

13.12 Type aliases and the `type` statement

What it is

A **type alias** is a short name for a long type, to make signatures readable.

```
Vector = list[float]                                  # implicit alias (any version)
from typing import TypeAlias
Headers: TypeAlias = dict[str, str]                   # explicit (3.10+, now deprecated style)
type JSON = dict[str, JSON] | list[JSON] | str | int | float | bool | None   # 3.12+
```

How it works

1. The `type` statement (3.12, PEP 695) creates a `TypeAliasType` object. Its value is evaluated **lazily**, so the alias can refer to itself (recursive types like `JSON`) or to names defined later, without quotes.
2. Aliases can be generic: `type Pair[T] = tuple[T, T]`, then `Pair[int]`.
3. An alias is interchangeable with what it names — unlike `NewType`, it gives no extra safety.
4. A `type` alias is **not** a class: `isinstance(x, JSON)` fails; you cannot call it. Use `JSON.__value__` to see the underlying type.

Output:

```
type alias       : JSON -> TypeAliasType
alias value      : dict[str, 'JSON'] | list['JSON'] | str | int | float | bool | None
scale            : [3.0, 6.0]
```

(The script quotes `"JSON"` inside the alias only for display; with the `type` statement quotes are optional.)

TL;DR

Name complicated types with `type Name = ...` (3.12+) or `Name = ...` (older). Aliases are for readability, not safety.

13.13 Running mypy and pyright; common errors

What it is

mypy is the original checker (reference implementation of PEP 484, written in Python and compiled with mypyc). **pyright** (Microsoft, written in TypeScript) is faster and powers VS Code's Pylance; it also infers more aggressively in un-annotated code. Both read the same annotations and typeshed stubs; they occasionally disagree on edge cases.

How it works — using mypy

```
pip install mypy
mypy src/                          # check a package
mypy --strict src/                 # turn on all optional strictness flags
```

Configure once in `pyproject.toml`:

```
[tool.mypy]
python_version = "3.12"
strict = true                      # new code: go strict
warn_unused_ignores = true

[[tool.mypy.overrides]]
module = ["legacy.*"]
ignore_errors = true               # old code: switch off per module while migrating
```

pyright equivalent: `pip install pyright` (or `npm i -g pyright`), then `pyright src/`, configured in `[tool.pyright]` with `typeCheckingMode = "strict"`.

Gradual adoption plan (what Dropbox and others describe):

1. Run the checker in CI with default settings on everything; fix or silence the first errors.
2. Annotate the most-used modules and public functions first.
3. Turn on `strict` per module as it becomes fully typed.
4. Forbid new untyped functions (`disallow_untyped_defs`).
5. Install stubs for third-party libraries: `pip install types-requests` etc. (mypy suggests the package name when missing).

Reading real errors

`bad_types.py` contains seven deliberate mistakes; `04_run_mypy.py` runs mypy through its Python API (`mypy.api.run`):

```
if __name__ == "__main__":
    area("3", 4)                   # 1 wrong argument type
    name = find(1)                 # returns str | None
    print(name.upper())            # 2 Optional not narrowed
    get_user(42)                   # 3 plain int is not a UserId
    mode("x")                      # 4 not an allowed literal
    LIMIT = 11                     # 5 reassigning a Final
    count: int = "three"           # 6 wrong assignment
    shout(name)                    # 7 str | None passed where str needed
```

Output (real mypy 2.x):

```
bad_types.py:29: error: Argument 1 to "area" has incompatible type "str"; expected "float"  [arg-type]
bad_types.py:31: error: Item "None" of "str | None" has no attribute "upper"  [union-attr]
bad_types.py:32: error: Argument 1 to "get_user" has incompatible type "int"; expected "UserId"  [arg-type]
bad_types.py:33: error: Argument 1 to "mode" has incompatible type "Literal['x']"; expected "Literal['r',
'w']"  [arg-type]
bad_types.py:34: error: Cannot assign to final name "LIMIT"  [misc]
bad_types.py:35: error: Incompatible types in assignment (expression has type "str", variable has type "int")
[assignment]
bad_types.py:36: error: Argument 1 to "shout" has incompatible type "str | None"; expected "str"  [arg-type]
exit status: 1
```

Each line is `file:line: error: message [error-code]`. The code in brackets is what you name in a targeted ignore.

Common errors and fixes

Error (code)	Usual cause	Fix
`Incompatible types in assignment` `[assignment]`	variable reused for a different type	new variable name, or a union type
`Argument 1 has incompatible type` `[arg-type]`	wrong type passed	convert (`float(s)`) or fix the signature
`Item "None" of "X | None" has no attribute` `[union-attr]`	Optional not narrowed	`if x is not None:` / early return / raise
`Need type annotation for "d"` `[var-annotated]`	empty container `d = {}`	`d: dict[str, int] = {}`
`Missing return statement` `[return]`	a branch falls off the end	return or raise in every branch
`Function is missing a type annotation` `[no-untyped-def]`	strict mode, un-annotated def	annotate it
`Library stubs not installed for "requests"` `[import-untyped]`	no type info for a package	`pip install types-requests`
`Returning Any from function declared to return "int"` `[no-any-return]`	value came from untyped code	`cast(int, ...)` after validating, or validate

Escape hatches (use sparingly)

- `# type: ignore[arg-type]` on one line – always include the code, so unrelated errors are not hidden; `warn_unused_ignores` finds stale ones.
- `typing.cast(T, value)` – tells the checker "trust me"; does nothing at runtime.
- `if TYPE_CHECKING:` – import only for the checker (avoids import cycles).
- `.pyi` **stub files** – type information kept separate from code (how typeshed works).
- `@overload` – several precise signatures for one function whose return type depends on arguments.

Common mistakes

- Blanket `# type: ignore` without a code.
- Assuming un-annotated functions are checked – mypy skips their bodies unless `check_untyped_defs = true` (included in `--strict`).
- Using `cast` instead of real validation on external data.

In the interview

"I run mypy or pyright in CI and pre-commit, strict for new code and per-module overrides for legacy code. Most errors are unhandled `None`, empty containers needing annotations, and missing stubs. I use `reveal_type` to debug inference and always put an error code on `type: ignore`."

Self-check

1. How do you see what mypy inferred? → `reveal_type(expr)`.
2. What does `cast` do at runtime? → Nothing; it returns the value unchanged.
3. `Library stubs not installed` – fix? → install the `types-…` stub package or the library's own typed version.
4. Why include the code in `# type: ignore[...]`? → To suppress only that error and let `warn_unused_ignores` catch stale ones.

TL;DR


`mypy --strict` / `pyright` in CI; configure in `pyproject.toml`; adopt gradually. Read `file:line: error: msg [code]`; fix the cause; ignore only with a code.

13.14 Runtime vs static – and pydantic

What it is

- **Static** checking (mypy/pyright) reasons about your **code** before it runs. It knows nothing about the actual data that arrives at runtime.
- **Runtime validation** checks the **data** while the program runs – essential for anything from outside: HTTP requests, files, environment variables, user input, LLM output.

A program fully typed with mypy can still crash if a JSON payload has `"age": "thirty"`, because `json.loads` returns `Any`.



What Python does at runtime with hints

Feature	Runtime effect
Parameter/variable annotations	stored only; never checked
`@dataclass`	fields from annotations; **no** type check
`NewType`, `cast`, `Final`, `Literal`, `TypedDict`	no checks (NewType returns its argument)
`isinstance(x, int | str)`	works
`isinstance(x, list[int])`	`TypeError` – parameterised generics can't be checked with isinstance
`@runtime_checkable` Protocol	`isinstance` checks method names only
`get_type_hints`, `get_origin`, `get_args`	let libraries read hints and act on them

How runtime validation works – a tiny version

`05_runtime_validation.py` builds a mini validator with `get_type_hints` + `get_origin` / `get_args`, which is the idea behind pydantic:

```python
def check(value: object, tp: object) -> bool:
    origin = get_origin(tp)
    if tp is NoneType or tp is None:
        return value is None
    if origin is UnionType:                      # X | Y
        return any(check(value, arg) for arg in get_args(tp))
    if origin is list:                           # list[T]
        (item_tp,) = get_args(tp)
        return isinstance(value, list) and all(check(v, item_tp) for v in value)
    if isinstance(tp, type):                     # plain class
        return isinstance(value, tp) and not (tp is int and isinstance(value, bool))
    raise TypeError(f"unsupported type {tp!r}")
```

Output:

```
Signup(email='a@x.io', age=30, referrer=None, tags=['beta'])
rejected: age='30' is not <class 'int'>
rejected: tags=['ok', 5] is not list[str] | None
```

(The `bool` special case exists because `bool` is a subclass of `int` – `isinstance(True, int)` is `True`.)

pydantic (brief, real-world)

pydantic is the most widely used runtime-validation library; version 2's core is written in Rust (`pydantic-core`). You declare a model with ordinary hints and it validates, converts and serialises data. (Needs `pip install pydantic` – not run here.)

```python
from pydantic import BaseModel, ValidationError

class Signup(BaseModel):
    email: str
    age: int
    referrer: str | None = None

s = Signup(email="a@x.io", age="30")      # "lax" mode converts "30" -> 30
print(s.age + 1)                          # 31
print(s.model_dump())                     # {'email': 'a@x.io', 'age': 30, 'referrer': None}

try:
    Signup(email="b@x.io", age="thirty")
except ValidationError as e:
    print(e.error_count(), "error")       # 1 error: age is not a valid integer

s2 = Signup.model_validate_json('{"email": "c@x.io", "age": 41}')
```

Key facts:

1. By default pydantic is **lax**: it converts compatible input (`"30"` → `30`). `strict=True` (per model or field) rejects such conversions.
2. Errors are collected together in one `ValidationError` with the location of each problem.
3. `model_dump()` / `model_dump_json()` serialise; `model_json_schema()` produces JSON Schema.
4. Where it is used: **FastAPI** validates request bodies and generates OpenAPI docs from pydantic models; `pydantic-settings` loads typed config from environment variables; LLM SDKs (including Anthropic's and OpenAI's Python SDKs) use pydantic models for responses, and "structured output" tools validate model output against pydantic schemas.
5. Alternatives: `attrs` + `cattrs`, `msgspec` (very fast), `marshmallow` (schema objects separate from classes), `typeguard` / `beartype` (check function hints at call time).

When not to use it

Don't validate internal data that has already been validated and is covered by static types – it wastes time. Validate **once, at the boundary**, then trust the types inside ("parse, don't validate").

In the interview

"Type hints are static; Python never enforces them. For untrusted data I validate at the boundary with pydantic, which uses the same annotations to parse JSON into typed objects, then mypy guarantees the rest of the code uses those objects correctly."

- *Would mypy catch a bad API payload?* No — it never sees runtime data.
- *Why is pydantic fast in v2?* Its validation core is written in Rust.

Self-check

1. Does `@dataclass` check that `x: int` got an int? → No.
2. Can you `isinstance(x, list[int])`? → No, `TypeError`.
3. Where should runtime validation happen? → At system boundaries, once.
4. pydantic lax vs strict? → Lax converts compatible values (`"30"` → `30`); strict rejects them.

TL;DR

Static checking verifies code; runtime validation verifies data. Use both: pydantic (or similar) at the edges, type hints everywhere else.

13.15 Chapter self-check

1. Does `def f(x: int)` stop `f("a")` from running? → No; only a checker flags it.
2. `Optional[str]` equals? → `str | None`.
3. Parameter type for "anything I can loop over once"? → `Iterable[T]`.
4. Why is `list[int]` not a subtype of `list[float]`? → Lists are mutable, so invariant.
5. `Any` vs `object`? → `Any` disables checks; `object` accepts all but allows only universal operations.
6. 3.12 syntax for a generic function? → `def first[T](xs: Sequence[T]) -> T:`.
7. How do you keep a decorated function's signature? → `ParamSpec` (`Callable[P, R]`).
8. Class with `close()` but no inheritance — matches `SupportsClose` Protocol? → Yes, structurally.
9. What is a TypedDict at runtime? → A plain dict.
10. `UserId = int` vs `NewType("UserId", int)`? → Alias = interchangeable; NewType = distinct for the checker.
11. How do you write a recursive JSON type in 3.12? → `type JSON = dict[str, JSON] | list[JSON] | str | int | float | bool | None`.
12. Mypy says `Need type annotation for "d"`. Fix? → `d: dict[str, int] = {}`.
13. Where do you validate data from an API? → At the boundary, e.g. with pydantic.

Chapter TL;DR

- **Hints are optional and unenforced.** Checkers (mypy, pyright) read them before runtime; typing is gradual.
- **Syntax:** `param: T`, `-> T`, `var: T = v`. Annotate signatures; let inference handle locals. 3.14 evaluates annotations lazily.
- **Generics:** `list[int]`, `dict[str, int]`, `tuple[int, ...]`; parameters take `Iterable` / `Sequence` / `Mapping`; mutable containers are invariant.
- **Unions:** `A | B`; `X | None` = `Optional[X]`; narrow with `is not None` / `isinstance`. `Any` switches checking off, `object` doesn't.
- **Type variables:** `def f[T](...)`, `class C[T]` (3.12), bounds and constraints. `Callable` for function values, `ParamSpec` for decorators.
- `Protocol` = structural interface. `TypedDict` = typed dict. `Literal` = fixed values. `Final` = constant. `NewType` = zero-cost distinct type.
- **dataclasses** use annotations as fields but never validate. **Aliases** via `type X = ...`.
- **Tooling:** `mypy --strict` / pyright in CI, config in `pyproject.toml`, `reveal_type`, `# type: ignore[code]`, stubs (`types-*`).

- **Runtime vs static:** validate untrusted data once at the boundary (pydantic), trust the types inside.