Chapter 8 — Exceptions

Programs fail: files go missing, users type "forty-two" for a number, networks time out, code has bugs. An **exception** is Java's way to report failure *without* every method returning an error code. This chapter covers the mechanism (how an exception travels up the call stack — the chain of in-progress method calls), the hierarchy (checked vs unchecked vs errors), the syntax (`try`/`catch`/`finally`, multi-catch, try-with-resources, `throw`, `throws`), custom exceptions, and the practices that keep failures visible.

Already met: `NumberFormatException` from `Integer.parseInt`, `ArithmeticException` from `Math.addExact` (Chapter 2), `ArrayIndexOutOfBoundsException` (Chapter 4), and overriding methods not throwing broader checked exceptions (§6.3).

Code: `code/` (package `ch08.*`), `javac --release 25`, run on JDK 26; outputs from real runs. Exam traps (unreachable catches, `finally` returns, resource scope, suppressed exceptions, overriding and `throws`): OCP Chapter 11 (sections 1–4). Service-level strategy (retries — see System Design Fundamentals — error codes at API boundaries, logging): LLD Clean Code §6 and §16.

8.1 What an exception is

What it is

An **exception** is an object describing an abnormal event, plus the act of **throwing** it: the JVM stops the current code and jumps to the nearest matching **handler** (`catch` block). If no method on the call stack handles it, the thread dies and the JVM prints a **stack trace** (the method calls active at the time, §8.9).

Versus C-style error codes, exceptions **separate** normal logic from error handling, **can't be silently ignored** by a forgotten check, **propagate automatically** to the level that knows what to do (a request handler, a UI, a retry loop), and **carry information** (type, message, cause, call path).

How it works

1. Something fails: the JVM detects it (division by zero, `null` dereference, bad index) or code runs `throw new SomeException(...)`.
2. The current block stops; remaining statements are skipped.
3. The JVM looks for an enclosing `try` whose `catch` type matches (the object is an instance of it). That catch runs, then execution continues **after the whole** `try` **statement** — not back at the throw point.
4. If none in this method, the method ends abruptly and the exception is rethrown at the call site in the **caller** — repeating up the stack (**stack unwinding**), running `finally` blocks on the way.
5. At the top of a thread, its *uncaught exception handler* prints the trace and the thread ends. If that was `main` and no non-daemon threads (daemon = background helpers that don't keep the JVM alive) remain, the program exits with status 1 (non-zero = failure).

`code/ch08/basics/FirstException.java` (key parts):

```
static int average(int[] values) {
    int sum = 0;
    for (int v : values) sum += v;
    return sum / values.length;            // length 0 -> ArithmeticException
}

try {
    System.out.println("before the call");
    int avg = average(new int[0]);         // throws; the rest of the try block is skipped
    System.out.println("never printed " + avg);
} catch (ArithmeticException e) {
    System.out.println("caught " + e.getClass().getName() + ": " + e.getMessage());
}
System.out.println("program continues normally");

static void setAge(int age) {
    if (age < 0) throw new IllegalArgumentException("age must be >= 0, was " + age);
    ...
}
```

Output:

```
average {4, 8} = 6
before the call
caught java.lang.ArithmeticException: / by zero
program continues normally
caught IllegalArgumentException: age must be >= 0, was -5
```

Propagation through the call stack


`code/ch08/basics/Propagation.java` calls `level1 → level2 → level3`; only `level1` catches:

```
static void level3(String s) {
    System.out.println("  level3 start");
    System.out.println("  length = " + s.length());   // NPE when s is null
    System.out.println("  level3 end");
}
static void level2(String s) { System.out.println(" level2 start"); level3(s); System.out.println(" level2 end");
}
static void level1(String s) {
    System.out.println("level1 start");
    try { level2(s); }
    catch (NullPointerException e) { System.out.println("level1 caught: " + e.getMessage()); }
    System.out.println("level1 end");
}
```

Output:

```
level1 start
 level2 start
  level3 start
  length = 2
  level3 end
 level2 end
level1 end
---
level1 start
 level2 start
  level3 start
level1 caught: Cannot invoke "String.length()" because "<parameter1>" is null
level1 end
```

With `null`, "level3 end" and "level2 end" never print — both methods were abandoned as the exception unwound.



`"<parameter1>"` appears because the runner compiles without debug info; with `javac -g` (IDEs and Maven/Gradle default) it reads `because "s" is null`. **`Helpful NullPointerException messages`**: Java 14 (JEP 358), on by default since 15.

8.2 The `Throwable` hierarchy: checked, unchecked and errors


What it is

Only `java.lang.Throwable` and subclasses can be thrown. Two branches:

- `Error` — serious JVM/environment problems applications shouldn't handle: `OutOfMemoryError`, `StackOverflowError`, `NoClassDefFoundError`, `ExceptionInInitializerError`.
- `Exception` — conditions a program may handle; its subclass `RuntimeException` is special.

The compiler sorts them into:

- **Checked**: `Exception` and subclasses *except* the `RuntimeException` branch. The compiler **forces** handle-or-declare (§8.3). They model recoverable external problems: I/O failures, network errors, "file not found", `InterruptedException` (a waiting thread asked to stop).
- **Unchecked**: `RuntimeException` and subclasses **plus** `Error` and subclasses. No enforcement. `RuntimeException`s usually signal **programming errors** — a violated precondition (a condition required before the call): `null` argument, bad index, illegal state.



(`NoSuchFileException`, in `java.nio.file`, actually extends `FileSystemException`, which extends `IOException`.)

`code/ch08/hierarchy/Hierarchy.java` walks `getSuperclass()` for common types (selected lines):

```
NumberFormatException [unchecked]
    extends IllegalArgumentException > RuntimeException > Exception > Throwable
ArrayIndexOutOfBoundsException [unchecked]
    extends IndexOutOfBoundsException > RuntimeException > Exception > Throwable
UncheckedIOException [unchecked]
    extends RuntimeException > Exception > Throwable
FileNotFoundException [CHECKED]
    extends IOException > Exception > Throwable
SQLException [CHECKED]
    extends Exception > Throwable
InterruptedException [CHECKED]
    extends Exception > Throwable
CloneNotSupportedException [CHECKED]
    extends Exception > Throwable
StackOverflowError [error, unchecked]
    extends VirtualMachineError > Error > Throwable
```

The exceptions you'll meet most

Exception	Kind	Typical cause
`NullPointerException`	unchecked	method/field on `null`, unboxing `null`
`IllegalArgumentException`	unchecked	a method rejects an argument value
`NumberFormatException`	unchecked (IAE subclass)	`Integer.parseInt("abc")`
`IllegalStateException`	unchecked	call at the wrong time (`iterator.remove()` twice, using a closed object)
`IndexOutOfBoundsException` (+ `Array…`, `String…`)	unchecked	bad index
`ClassCastException`	unchecked	invalid downcast
`ArithmeticException`	unchecked	integer `/ 0`, `*Exact` overflow, non-terminating `BigDecimal` division
`UnsupportedOperationException`	unchecked	modifying an immutable collection (`List.of(...).add(x)`)
`ConcurrentModificationException`	unchecked	changing a collection while iterating (Chapter 10)
`NoSuchElementException`	unchecked	`iterator.next()` past the end; `Optional.get()` / `orElseThrow()` on empty
`DateTimeException`, `DateTimeParseException`	unchecked	invalid date values/text (Chapter 7)
`IOException` (+ `FileNotFoundException`, `NoSuchFileException`…)	checked	file/network I/O
`InterruptedException`	checked	a blocked thread was interrupted (Chapter 14)
`SQLException`	checked	database errors (JDBC)
`ExecutionException`, `TimeoutException`	checked	a `Future` (handle to a background task's result) failed / waited too long
`ExceptionInInitializerError`	error	exception in a `static` initialiser
`StackOverflowError`, `OutOfMemoryError`	error	runaway recursion; heap exhausted

Trade-offs — checked vs unchecked

	Checked	Unchecked
Compiler enforcement	Catch or declare	None
Signals	Recoverable external condition	Programming error or unrecoverable state
API cost	Every caller must deal with it, even if it can't help	Callers may ignore it; `@throws` docs matter more
Lambdas/streams	Poor — `java.util.function` interfaces declare none (Chapter 11)	Fine
Examples	`IOException`, `SQLException`	`IllegalArgumentException`, `NullPointerException`

Java is unusual in having checked exceptions (C#, Kotlin, Python, JavaScript don't). *Effective Java* Items 70–71: checked for conditions the caller can **recover** from, runtime for programming errors, avoid checked when the caller can't do anything useful. Spring, JPA/Hibernate wrap checked exceptions in unchecked ones for this reason.

In the interview

> **30-second answer:** "Everything thrown is a `Throwable`. `Error`s are JVM-level problems you don't catch. `Exception`s are checked — compiler-enforced catch-or-declare, for recoverable external failures like `IOException` — or unchecked `RuntimeException`s for programming errors like `IllegalArgumentException`. I use unchecked for precondition violations and checked only when the caller can genuinely recover."

- *Is `Error` checked?* No — `Error` and `RuntimeException` (and subclasses) are unchecked.
- *Catch `Throwable`?* Only at the very top of a thread/request to log and fail cleanly — it also catches `OutOfMemoryError`, after which continuing may be unsafe.

TL;DR

`Throwable` → `Error` (don't catch) and `Exception`; `RuntimeException` + `Error` = unchecked; the rest of `Exception` = checked (handle or declare).

8.3 Handle or declare: checked exceptions and `throws`

What it is

The **handle-or-declare rule** ("catch or specify"): if code in a method can throw a **checked** exception, the method must **handle** it (`try` with a matching `catch`) or **declare** it in its `throws` **clause**, passing responsibility to callers. Otherwise: *"unreported exception IOException; must be caught or declared to be thrown"* (e.g. `void m() { Thread.sleep(10); }` doesn't compile).

`throw` is a statement throwing one object now (`throw new IOException("x")`); `throws` is part of the method declaration listing exception *types* (`void read() throws IOException, SQLException`).

How it works

`code/ch08/checked/CheckedDemo.java`:

```java
// "Declare": this method does not handle IOException, it passes it to the caller
static String readConfig(Path path) throws IOException {
    return Files.readString(path);
}

// "Handle": this method catches and decides what to do
static String readConfigOrDefault(Path path) {
    try {
        return readConfig(path);
    } catch (NoSuchFileException e) {           // more specific first
        System.out.println("no such file: " + e.getFile() + " -> using defaults");
        return "mode=default";
    } catch (IOException e) {                   // any other I/O problem
        System.out.println("I/O failure: " + e);
        return "mode=default";
    }
}

public static void main(String[] args) throws IOException {   // main may declare too
    Path tmp = Files.createTempFile("ch08-", ".properties");
    Files.writeString(tmp, "mode=fast");
    System.out.println("existing file: " + readConfigOrDefault(tmp));
    Files.delete(tmp);
    System.out.println("deleted file:  " + readConfigOrDefault(Path.of("missing-config.properties")));
    for (String in : new String[]{"42", "forty-two"}) {
        try { System.out.println("parsed " + Integer.parseInt(in)); }
        catch (NumberFormatException e) { System.out.println("bad number '" + in + "': " + e.getMessage()); }
    }
}
```

Output:

```
existing file: mode=fast
no such file: missing-config.properties -> using defaults
deleted file:  mode=default
parsed 42
bad number 'forty-two': For input string: "forty-two"
```

The rules in one table

Rule	Detail
Checked exceptions must be caught or declared	including those from methods you call
Unchecked *may* be declared	documentation only; the compiler ignores it — prefer Javadoc `@throws`
Can't catch a checked exception the `try` body can't throw	*"exception IOException is never thrown in body of corresponding try statement"* — except `Exception` / `Throwable`, which may hide unchecked ones (so `catch (Exception e)` after an empty `try` compiles)
Overrides may not throw **new or broader** checked exceptions	fewer, narrower or unchecked are fine (§6.3)
Lambdas	may throw a checked exception only if the functional interface method declares it; `Runnable`, `Function` don't (Chapter 11)
Initialiser blocks	`static` initialisers can't throw checked (unchecked are wrapped in `ExceptionInInitializerError`); instance initialisers can only if every constructor declares it

When to handle vs declare

- **Handle** where you can act: retry, fall back, re-ask the user, translate (§8.8).
- **Declare** when this layer can't fix it and the caller has more context. Low-level helpers declare; boundaries (request handler, `main`, UI handler) handle.

- Never "handle" by catching and doing nothing (§8.10).

8.4 `try` / `catch` / `finally` and control flow

What it is

`finally` runs after the `try` (and any `catch` that ran) **however** the `try` ended — normally, by exception (caught or not), or by `return`/`break`/`continue`. It is for cleanup that must always happen (release a lock, reset a flag; for resources §8.6 is better).

How it works — the syntax rules

1. A `try` needs at least one `catch` **or** a `finally` (or resources); `try { } finally { }` is legal.
2. Order: `try`, zero or more `catch`, at most one `finally`. Braces always required.
3. At most one `catch` runs — the **first** match.
4. `finally` runs after that `catch`, or right after `try` if nothing was thrown or nothing matched (then the exception keeps propagating **after** `finally`).


`code/ch08/finallyflow/FinallyDemo.java` (key parts):

```
static int returnInTry() {
    int x = 1;
    try {
        return x;             // the value 1 is saved here...
    } finally {
        x = 99;               // ...so changing x in finally does not change the returned value
        System.out.println("finally ran before the method returned");
    }
}

static int finallyOverrides() {
    try {
        throw new RuntimeException("lost!");
    } finally {
        return -1;            // BAD: discards the exception and any return value from try
    }
}
```

Output:

```
no failure: try try-end finally
failure:    try catch finally
finally ran before the method returned
returnInTry() = 1
finallyOverrides() = -1 (the RuntimeException vanished)
inner finally runs even though nobody here catches
outer caught: inner
```



The tricky cases

Situation	What happens
`return` in `try`, `finally` changes the variable	The return **value** was already evaluated: `try { return "a"; } finally { print("b"); }` prints `b`, returns `"a"` (a returned object's *contents* can still be mutated)
`return` in `finally`	Overrides the `try`'s return **and silently discards any exception** — never (javac `-Xlint:finally` warns)
`finally` throws	The new exception replaces and loses the original
`catch` throws	`finally` still runs, then the new exception propagates
`System.exit()` in `try`, JVM crash/halt, power loss, `try` never finishes	`finally` does **not** run

Common mistakes

- Returning or throwing from `finally`.
- Manual resource closing in `finally` with nested `try`s — use try-with-resources.
- Confusing `final` (no reassignment), `finally` (always-run block), `finalize()` (deprecated for removal since Java 18, JEP 421).

8.5 Multi-catch, catch order and rethrowing

What it is

- **Multi-catch** (Java 7): one `catch` for several unrelated types: `catch (NumberFormatException | IndexOutOfBoundsException e)`.
- **Catch order**: the first match wins, so a subclass must come **before** its superclass, else the subclass block is unreachable (compile error).
- **Precise rethrow** (Java 7): catch broadly and rethrow the same (effectively final) variable; the compiler knows it can only be the checked types the `try` really throws — so you can log broadly yet keep a narrow `throws`.
- **Unnamed variable** `_` (Java 22, JEP 456): `catch (NumberFormatException _)` when the object isn't used.

`code/ch08/multicatch/MultiCatch.java` (key parts):

```
try {
    risky(i);        // 0: parseInt("x")  1: List.of(1,2).get(5)  2: IOException  3: fine
} catch (NumberFormatException | IndexOutOfBoundsException e) {     // multi-catch
    System.out.println(i + ": bad input -> " + e.getClass().getSimpleName());
} catch (java.io.IOException e) {
    System.out.println(i + ": I/O -> " + e.getMessage());
} finally {
    System.out.println(i + ": finally");
}

try { Integer n = (Integer) (Object) "text"; }
catch (ClassCastException e) { System.out.println("ClassCastException first"); }   // specific first
catch (RuntimeException e)   { System.out.println("RuntimeException"); }           // then general

try { value = Integer.parseInt(input); }
catch (NumberFormatException _) { value = -1; }                                    // Java 22

static void rethrow(boolean io) throws java.io.IOException, java.util.concurrent.TimeoutException {
    try {
        if (io) throw new java.io.IOException("io failed");
        throw new java.util.concurrent.TimeoutException("too slow");
    } catch (Exception e) {
        System.out.println("log and rethrow: " + e);
        throw e;                    // compiler knows e is IOException | TimeoutException
    }
}
```

Output:

```
0: bad input -> NumberFormatException
0: finally
1: bad input -> IndexOutOfBoundsException
1: finally
2: I/O -> disk full
2: finally
  no problem
3: finally
ClassCastException first
value = -1
log and rethrow: java.util.concurrent.TimeoutException: too slow
caller got TimeoutException
```

Compiler rules (real `javac` messages)

You write	Result
`catch (RuntimeException e) {} catch (ClassCastException e) {}`	*exception ClassCastException has already been caught*
`catch (IllegalArgumentException | NumberFormatException e)` (or `IOException | FileNotFoundException`)	*Alternatives in a multi-catch statement cannot be related by subclassing* — catch the parent
`catch (IllegalStateException | ArithmeticException e) { e = null; }`	*multi-catch parameter e may not be assigned* (implicitly `final`)
`catch (java.io.IOException e)` around code that can't throw it	*exception IOException is never thrown in body of corresponding try statement*

A multi-catch variable's type is the alternatives' closest common supertype, so only shared methods (usually `Throwable`'s) are callable.

8.6 try-with-resources

What it is

A **resource** must be closed after use — files, sockets, DB connections, streams, closeable locks. **try-with-resources** (Java 7) declares them in parentheses after `try` and closes them automatically however the block ends.

Any `java.lang.AutoCloseable` (`void close() throws Exception`) qualifies. `java.io.Closeable` is the older I/O sub-interface whose `close()` throws `IOException` and must be idempotent (a second call has no further effect).

Before Java 7, correct cleanup needed `finally` with a null check and a nested `try` around `close()`, and a `close()` failure could *replace* the real error. *Effective Java* Item 9: "Prefer try-with-resources to try-finally."

How it works

1. Resources initialise left to right; each is implicitly `final` (reassigning: *"auto-closeable resource r may not be assigned"*).
2. The body runs.
3. Resources are **closed in reverse order** (`a, b, c` → `c, b, a`) — **before** any `catch`/`finally` of the same statement. `catch`/`finally` are optional.
4. If an initialisation fails, only already-opened resources are closed; `null` resources are skipped.
5. If the body throws *and* `close()` throws, the body's exception is **primary**; close failures are attached as **suppressed** (`getSuppressed()`; traces print them under "Suppressed:").
6. Java 9: an existing **effectively final** variable can be used directly: `try (reader) { ... }`.

`code/ch08/resources/TryWithResources.java` (key parts):

```java
static class Res implements AutoCloseable {
    Res(String name, boolean failOnClose) { ...; System.out.println("open " + name); }
    void use(boolean fail) { System.out.println("use " + name); if (fail) throw new IllegalStateException("use of
" + name + " failed"); }
    @Override public void close() {
        System.out.println("close " + name);
        if (failOnClose) throw new IllegalStateException("close of " + name + " failed");
    }
}

try (Res a = new Res("A", false); Res b = new Res("B", false)) { a.use(false); b.use(false); }

try (Res a = new Res("A", false)) { a.use(true); }
catch (IllegalStateException e) { System.out.println("catch: " + e.getMessage()); }
finally { System.out.println("finally"); }

try (Res a = new Res("A", true); Res b = new Res("B", true)) { b.use(true); }
catch (IllegalStateException e) {
    System.out.println("primary: " + e.getMessage());
    for (Throwable s : e.getSuppressed()) System.out.println("suppressed: " + s.getMessage());
}

BufferedReader reader = new BufferedReader(new StringReader("line one\nline two"));
try (reader) { System.out.println("first line: " + reader.readLine()); }     // Java 9
```

Output:

```
-- 1. normal: closed in reverse order
open A
open B
use A
use B
close B
close A
-- 2. body fails: resources closed BEFORE catch runs
open A
use A
close A
catch: use of A failed
finally
-- 3. body AND close fail: close exception is suppressed
open A
open B
use B
close B
close A
primary: use of B failed
suppressed: close of B failed
suppressed: close of A failed
-- 4. Java 9: effectively final variable as a resource
first line: line one
after close: Stream closed
```

Real-world use (not run — needs a database; JDBC in Chapter 18):

```java
try (Connection con = dataSource.getConnection();
     PreparedStatement ps = con.prepareStatement("SELECT name FROM users WHERE id = ?")) {
    ps.setLong(1, id);
    try (ResultSet rs = ps.executeQuery()) { ... }
}   // rs, ps, con closed in that order — even if the query throws
```

Common mistakes

- Opening a resource *outside* `try (...)` without passing it in — leaks if something fails in between.
- Returning a resource out of the `try` (e.g. a `Stream` from `Files.lines`) — closed before the caller uses it. `Files.lines`/`Files.walk` must themselves be in try-with-resources (Chapter 13).

- Wrapped streams: `try (var in = new BufferedReader(new FileReader(f)))` closes both, but if the *outer* constructor throws, the inner leaks. For strictness, declare each as its own resource.

In the interview

> **30-second answer:** "try-with-resources closes any `AutoCloseable` automatically, in reverse order, before catch and finally run. If both the body and `close` throw, the body's exception wins and close failures are attached as suppressed exceptions, so nothing is lost. It replaced error-prone `finally { if (x != null) x.close(); }`."

- *`AutoCloseable` vs `Closeable`?* `Closeable` (java.io) extends `AutoCloseable`, throws `IOException`, and should be idempotent.

TL;DR

Anything `AutoCloseable` goes in `try (...)`. Reverse-order close, before catch/finally; secondary failures are suppressed, not lost.

8.7 Throwing exceptions and writing custom ones

Reuse standard exceptions first

Effective Java Item 72: readers already know the standard ones.

Situation	Throw
Invalid argument value (`setAge(-5)`)	`IllegalArgumentException`
Required argument is `null`	`NullPointerException` — `Objects.requireNonNull(x, "x")`
Index out of range	`IndexOutOfBoundsException` — `Objects.checkIndex(i, size)` (Java 9)
Object in the wrong state (`start()` twice)	`IllegalStateException`
Operation not supported by this implementation	`UnsupportedOperationException`
Lookup found nothing and must return a value	`NoSuchElementException` (or return `Optional`, §8.10)
Concurrent modification detected	`ConcurrentModificationException`

Don't throw `Exception`, `RuntimeException`, `Throwable` or `Error` directly — callers can't distinguish your failure.

When to write your own

When callers must **distinguish** it or it should **carry data** (account ID, shortfall, error code):

1. Name it `…Exception`.
2. Extend `RuntimeException` for programming/state errors and most domain rule violations; extend `Exception` only if callers should recover and the compiler should remind them.
3. Provide `(String message)` and `(String message, Throwable cause)` — the cause constructor enables chaining (§8.8).
4. `final` fields with getters, so handlers act on data without parsing messages. Exceptions are `Serializable`; strict linting (`-Xlint:serial`) wants a `serialVersionUID`.
5. Messages carry failure-capture details (*Effective Java* Item 75) — the offending values, not "Error occurred"; never passwords or personal data.

`code/ch08/custom/CustomExceptions.java` (key parts):

```java
// Checked: the caller is expected to recover (e.g. show "insufficient funds" to the user)
static class InsufficientFundsException extends Exception {
    private final BigDecimal shortfall;
    InsufficientFundsException(BigDecimal shortfall) {
        super("insufficient funds: short by " + shortfall);
        this.shortfall = shortfall;
    }
    BigDecimal getShortfall() { return shortfall; }
}

// Unchecked: a programming/state error in our domain
static class AccountFrozenException extends RuntimeException {
    AccountFrozenException(String accountId) { super("account " + accountId + " is frozen"); }
}

void withdraw(BigDecimal amount) throws InsufficientFundsException {
    if (amount.signum() <= 0) throw new IllegalArgumentException("amount must be positive: " + amount);
    if (frozen) throw new AccountFrozenException(id);
    if (amount.compareTo(balance) > 0) throw new InsufficientFundsException(amount.subtract(balance));
    balance = balance.subtract(amount);
}
```


Output (first four lines):

```
withdrew 30.00, balance 70.00
insufficient funds: short by 430.00 (shortfall field = 430.00)
rejected: amount must be positive: -1
rejected: account ACC-1 is frozen
```

`withdraw` checks every condition **before** changing `balance` — **failure atomicity** (*Effective Java* Item 76): a failed call leaves the object as it was.

Custom exception hierarchies

A small hierarchy lets callers catch broadly or narrowly:



Keep it shallow — three or four types callers handle differently beat twenty nobody catches. A sealed interface or an error-code enum field also works.

8.8 Chaining and exception translation

What it is

Chaining stores the original exception as the **cause** of a new one: `new ReportException("could not build report", e)`. **Translation** (*Effective Java* Item 73): a higher layer (web → service → data access) catches low-level exceptions and throws ones meaningful at *its* abstraction — a `ReportService` shouldn't leak `SQLException`/`IOException`. The trace prints the high-level exception, then **"Caused by:"** with the original.

How it works

1. Catch the low-level exception.
2. Throw a new one with the original as `cause` (constructor, or `initCause` for old types without one).
3. Callers use `getCause()` (repeatedly, for the root); logs show the whole chain.
4. To pass a checked exception through code that can't declare it (lambdas, `Runnable`), wrap it in an unchecked one — **`UncheckedIOException`** for `IOException`.

```
static String buildReport(String name) throws ReportException {
    try {
        return loadTemplate(name);                        // throws IOException
    } catch (IOException e) {
        throw new ReportException("could not build report " + name, e);   // translate + chain
    }
}

java.util.List.of("a").forEach(n -> {
    try { loadTemplate(n); }
    catch (IOException e) { throw new UncheckedIOException(e); }         // lambda can't throw IOException
});
```

Output (last three lines of `CustomExceptions`):

```
error: could not build report monthly
cause: java.io.IOException: template 'monthly' not found on disk
unwrapped cause: template 'a' not found on disk
```

Common mistakes

- `throw new ReportException("failed: " + e.getMessage());` — loses the original type and trace. **Always pass `e` as the cause.**
- Log-and-rethrow at every layer — one failure, five log entries. Log once, where handled.
- Bare `RuntimeException` wrapping with no message — say what the operation was.

8.9 Reading stack traces

What it is

A **stack trace** lists the active method calls (**frames**) when the exception was *created*, most recent first, each as `class.method(File.java:line)` — Java's most useful debugging artefact.

`code/ch08/stacktrace/StackTraces.java`:

```java
static int parsePort(String text) { return Integer.parseInt(text); }

static int loadPort(String text) {
    try {
        return parsePort(text);
    } catch (NumberFormatException e) {
        throw new ServiceException("invalid port setting", e);
    }
}
// in main:
try { loadPort("80a"); }
catch (ServiceException e) { e.printStackTrace(System.out); ... }
```

Output (line numbers in `java.base` frames depend on the JDK build — these are JDK 26):

```
ch08.stacktrace.StackTraces$ServiceException: invalid port setting
    at ch08.stacktrace.StackTraces.loadPort(StackTraces.java:17)
    at ch08.stacktrace.StackTraces.main(StackTraces.java:23)
Caused by: java.lang.NumberFormatException: For input string: "80a"
    at java.base/java.lang.NumberFormatException.forInputString(NumberFormatException.java:67)
    at java.base/java.lang.Integer.parseInt(Integer.java:527)
    at java.base/java.lang.Integer.parseInt(Integer.java:624)
    at ch08.stacktrace.StackTraces.parsePort(StackTraces.java:10)
    at ch08.stacktrace.StackTraces.loadPort(StackTraces.java:15)
    ... 1 more
top frame: ch08.stacktrace.StackTraces.loadPort line 17
caught StackOverflowError (an Error: normally you do NOT catch these)
```

How to read one

1. **First line**: class + message — *what* happened.
2. **Frames**: *where*, most recent first; the first frame in **your** code is usually the place to look (`loadPort`, line 17).
3. **"Caused by:"**: the underlying exception. **Go to the last one** — the root cause (`"80a"` from `parsePort` line 10).
4. **`... 1 more`**: remaining frames identical to the enclosing trace's, elided.
5. **`java.base/`**: the module (Chapter 16); `$` marks a nested class.
6. **"Suppressed:"**: exceptions attached by try-with-resources (§8.6).

Tools

API	Use
`e.getMessage()`, `e.toString()`	message; class name + message
`e.printStackTrace()`	to `System.err` — fine for learning; applications use a logger (`log.error("msg", e)`), which records the trace
`e.getStackTrace()`	`StackTraceElement[]` for inspection
`e.getCause()`, `e.getSuppressed()`	navigate the chain
`StackWalker` (Java 9)	lazily inspect the *current* stack without an exception
`Thread.setDefaultUncaughtExceptionHandler`	last-chance logging for dying threads

The trace is captured at **construction**, costing time proportional to stack depth — one reason not to use exceptions for control flow (§8.10). Frameworks sometimes pre-allocate exceptions or disable capture via the protected `Throwable(String, Throwable, boolean enableSuppression, boolean writableStackTrace)` constructor — a niche optimisation.

8.10 Best practices and anti-patterns

The rules (with *Effective Java* item numbers)

#	Practice	Why
1	**Exceptions only for exceptional conditions** (Item 69), never normal control flow	Slower (stack capture), obscures logic, hides bugs
2	**Checked for recoverable, runtime for programming errors** (Item 70); avoid needless checked (Item 71)	Don't force callers to catch what they can't handle
3	**Prefer standard exceptions** (Item 72)	Familiar meaning
4	**Throw exceptions appropriate to the abstraction** (Item 73) — translate and chain	Decoupled layers, cause preserved
5	**Document every exception** with `@throws` (Item 74), including relevant unchecked ones	The compiler can't tell callers
6	**Failure details in the message** (Item 75)	Self-explanatory traces
7	**Failure atomicity** (Item 76): validate before mutating	No half-updated state
8	**Don't ignore exceptions** (Item 77)	Swallowed errors = silent corruption
9	**Fail fast**: validate at the start of public methods/constructors	Error surfaces near its cause
10	**Catch the most specific type you can handle**; broad only at boundaries	Don't catch bugs by accident
11	**Log or rethrow, not both**; log once with the exception object	No duplicates; trace kept
12	**try-with-resources** for anything closeable (Item 9)	Correct cleanup

`code/ch08/practices/BestPractices.java` (key parts):

```
record User(String name, String email) {
    User {
        Objects.requireNonNull(name, "name");                                   // fail fast
        if (email == null || !email.contains("@")) throw new IllegalArgumentException("bad email: " + email);
    }
}

static Optional<String> findUser(int id) { return Optional.ofNullable(USERS.get(id)); }   // absence is normal
static String getUser(int id) {                                                  // absence is a bug
    String u = USERS.get(id);
    if (u == null) throw new NoSuchElementException("no user with id " + id);
    return u;
}

System.out.println("bounds check instead of catching: " + (i < data.length ? data[i] : "out of range"));

try {
    Thread.sleep(1);
} catch (InterruptedException e) {
    Thread.currentThread().interrupt();        // restore the interrupt flag
    ...
}
```

The *interrupt flag* is a per-thread "please stop" marker; catching `InterruptedException` clears it, so set it again. Output:

```
findUser(3) -> guest
getUser(3) -> no user with id 3
requireNonNull -> NPE: name
validation -> bad email: not-an-email
helpful NPE: Cannot invoke "String.toUpperCase()" because "<local1>[1]" is null
bounds check instead of catching: out of range
done
```

(With `javac -g` the NPE names the variable: `because "names[1]" is null`.)

Exception or `Optional` or special value?

Situation	Return / throw
"Not found" is normal (search, cache lookup, a `findById` that often misses)	`Optional<T>` (Chapter 11) or an empty collection — never `null` for collections
Caller broke the contract (null argument, bad index)	Unchecked exception
External failure the caller can act on (file missing, remote service down)	Checked, or unchecked with clear docs
User-input validation with many possible errors	A result object listing all errors (throwing on the first is poor UX)

Anti-patterns

```java
// 1. Swallowing: the failure disappears
try { save(order); } catch (Exception e) { }

// 2. Pokemon catching ("gotta catch 'em all") deep inside business logic
catch (Throwable t) { ... }                // also catches OutOfMemoryError, StackOverflowError

// 3. Losing the cause
catch (IOException e) { throw new RuntimeException("failed"); }       // pass e!

// 4. Exceptions as control flow
try { int i = 0; while (true) arr[i++].process(); } catch (ArrayIndexOutOfBoundsException e) { }

// 5. Returning from finally (hides exceptions) — see 8.4

// 6. Swallowing InterruptedException without restoring the flag
catch (InterruptedException e) { }          // callers can no longer see the interrupt
```

If ignoring is genuinely right (closing during shutdown), name the variable `ignored` or `_` and comment why.

Assertions — a note

`assert condition : "message";` throws `AssertionError` when false — **only with** `-ea` (off by default). Use for internal invariants during development/testing; never for public-method argument validation or anything with side effects.

Real-world examples

- Spring's `@ControllerAdvice` maps exceptions at the request boundary to HTTP statuses (System Design Fundamentals): `IllegalArgumentException` → 400, custom `NotFoundException` → 404, anything else → 500 with a logged trace.
- Frameworks translate checked JDBC/file exceptions into unchecked hierarchies (Spring's `DataAccessException`) to keep business code clean.
- `Objects.requireNonNull` at the top of constructors throughout the JDK.

In the interview

> **30-second answer:** "I validate early and throw standard unchecked exceptions for contract violations, use checked exceptions only for recoverable external failures, translate low-level exceptions at layer boundaries while chaining the cause, never swallow exceptions or return from `finally`, use try-with-resources for anything closeable, and handle — log once, map to a response — at the boundary. For expected absence I return `Optional`."

- *What's wrong with `catch (Exception e) {}`?* It hides every failure, including bugs, leaving unknown state.
- *`final` vs `finally` vs `finalize`?* Modifier; always-run block; deprecated GC hook (JEP 421, Java 18) — use try-with-resources or `Cleaner`.
- *Why restore the interrupt flag?* So code further up sees cancellation was requested (Chapter 14).

TL;DR

Validate early, standard unchecked exceptions for bugs, checked only when recovery is realistic, translate with a cause at boundaries, never swallow, log once, `Optional` for normal absence.

Chapter TL;DR

Topic	Remember
Mechanism	`throw` stops the block; the stack unwinds to the first matching `catch`; uncaught → thread dies with a stack trace
Hierarchy	`Throwable` → `Error` (don't catch) / `Exception`; `RuntimeException` + `Error` unchecked; rest checked
Handle or declare	Checked exceptions caught or listed in `throws`; overriding can't widen checked exceptions
`finally`	Always runs (except `System.exit`/crash); return value already evaluated; never `return`/`throw` from it
Catch rules	First match wins; subclass first; multi-catch types unrelated, variable final; precise rethrow; `catch (X _)` (22)
try-with-resources	`AutoCloseable`; reverse-order close before catch/finally; close failures suppressed; `try (existingVar)` (9)
Custom exceptions	Standard ones first; custom when callers must distinguish or need data; detailed message; cause constructor
Chaining	Always pass the cause; translate to your layer's abstraction; `UncheckedIOException` for lambdas
Stack traces	Top line, first frame in your code, then the last "Caused by:"; `-g` for variable names in NPE messages
Practices	Exceptions for exceptional cases, fail fast, failure atomicity, don't swallow, log once, `Optional` for normal absence

Next: Chapter 9 — Generics. Checked exceptions in lambdas and `Optional`: Chapter 11. Exceptions in threads, `ExecutionException`: Chapter 15. Exam traps: OCP Chapter 11. Service-level error handling: LLD Clean Code §16.