Chapter 1 — Why React, and Setting Up

This chapter answers three questions before you write any serious React: *what problem does React solve*, *how does it update the screen*, and *how do I start a project*. By the end you will have read and run a first app, and you will know the handful of JSX rules that every later chapter assumes.

What you'll learn

#	Topic	You will be able to…
1.1	What React is	explain React in one minute, and say what it is *not*
1.2	Declarative UI	contrast "describe the result" with "list the DOM steps"
1.3	Rendering, the virtual DOM and reconciliation	describe render → commit and why React touches only changed nodes
1.4	SPA vs MPA vs SSR	pick a rendering strategy and name its costs
1.5	Setting up a project	create an app with a framework or with Vite, and know which to choose
1.6	Project structure	find your way around `index.html`, `main.jsx`, `App.jsx`, `package.json`
1.7	Your first component	write, export, import and nest components
1.8	JSX rules	one root, closed tags, `className`, `{expressions}`, fragments, `style` objects

All code lives in `code/`. It was run with **React 19.3** (current as of September 2026) on Node 24: `.jsx` files are compiled by esbuild and rendered into **jsdom** (a browser-like DOM that runs inside Node), and `@testing-library/react` is used to click buttons and read what a user would see. Run everything with `bash tools_run_js.sh react` from the repository root.

1.1 What React is

What it is

React is a JavaScript **library** for building **user interfaces** (UIs) out of **components**. A *component* is a JavaScript function that returns a description of a piece of screen — a button, a profile card, a whole page. You combine small components into bigger ones, the way you build a wall out of bricks.

Analogy: think of a restaurant. You (the developer) write the *menu* — for each situation, what the plate should look like. React is the kitchen: it works out how to get from the plate on the table now to the plate described on the menu, and does only the necessary work.

Key vocabulary used for the rest of the book:

Term	Meaning
DOM (Document Object Model)	The browser's live tree of objects for the page (`<div>`, `<button>` …). Changing it changes what you see.
Component	A function whose name starts with a capital letter and that returns JSX.
JSX	An HTML-like syntax inside JavaScript (`<h1>Hi</h1>`) that compiles to plain function calls (§1.8).
Props	Inputs passed to a component, like function arguments (Chapter 2).
State	Data a component remembers between renders, such as "how many likes" (Chapter 3).
Render	React calling your component to find out what the UI should look like.
Hook	A function starting with `use` (e.g. `useState`) that lets a component use React features.

Library, not framework

React itself handles only one job: turning components + data into UI and keeping it up to date. Routing (which page for which URL), data fetching, and build tooling come from other packages or from a **framework** built on React (Next.js, React Router, Expo – §1.5).

Package	What it does
`react`	Components, JSX runtime, Hooks – platform independent
`react-dom`	Renders React to a browser DOM (`react-dom/client`) or to HTML strings/streams on a server (`react-dom/server`)
`react-native`	Renders the same kind of components to native iOS/Android views (separate project)

A short history

Year	Event
2011–2012	Jordan Walke builds React at Facebook; it runs the Facebook News Feed and then Instagram.
May 2013	Open-sourced at JSConf US. JSX was controversial ("HTML in my JavaScript?").
2015	React Native brings the model to mobile apps.
Feb 2019	React 16.8 introduces **Hooks**; function components become the standard way to write React.
Mar 2022	React 18: concurrent rendering and automatic batching of state updates.
Dec 5, 2024	**React 19**: Actions, `useActionState`, `useOptimistic`, `use`, `ref` as a normal prop, Server Components stable.
Feb 14, 2025	Create React App (CRA) deprecated for new apps.
Oct 2025	React 19.2; React Compiler 1.0 (automatic memoization); Meta announces React will move to an independent React Foundation hosted by the Linux Foundation.
Sep 9, 2026	React 19.3 (`<ViewTransition>`, refs on `<Fragment>`) – the version used in this book.

Why it matters

- **Reusable pieces.** A `<Button>` written once is used in 200 places; fixing a bug in that one file repairs every place it is used.
- **Predictable updates.** You describe the UI for the current data; React keeps the screen in sync (§1.2).
- **Huge ecosystem.** Routers, form libraries, component kits, testing tools, and jobs. React is used by Meta (Facebook, Instagram, WhatsApp Web, Threads), Netflix, Airbnb, Discord, Shopify, and many others.

- **One mental model, many targets.** Browser (React DOM), server HTML (SSR), mobile (React Native), even terminals and PDFs via community renderers.

When not to use it

Situation	Better fit
A mostly static site (blog, docs, landing page) with little interactivity	Plain HTML/CSS, or a static-site generator; add a sprinkle of JS
A tiny widget on a server-rendered page	Vanilla JS or a very small library
Hard limits on JavaScript size (very slow devices/networks)	Server-rendered HTML with minimal JS

React's runtime (react + react-dom) adds roughly 60–70 KB of gzipped JavaScript (the Figure 1.1 bundle, React included, is 69 KB gzipped) – small for an app, large for a single dropdown.

Common mistakes

- Thinking React *is* the whole app. You still need routing, data fetching, and a build tool – which is why react.dev recommends starting with a framework (§1.5).
- Learning old tutorials: class components, `componentDidMount`, and CRA are legacy. This book uses function components and Hooks only.

TL;DR

React = a UI library: components (functions returning JSX) + React DOM to put them in the browser. Everything else (routing, data, build) comes from the ecosystem or a framework.

1.2 Declarative UI


What it is

There are two ways to tell a computer how the screen should change.

- **Imperative**: you give step-by-step commands. "Find the label. Set its text to 3 likes. Find the button. If likes ≥ 3 change its text to Popular!"
- **Declarative**: you describe the *result* for any given data. "The label says *N like(s)*; the button says *Popular!* when N ≥ 3." A system (React) figures out the steps.

Analogy: a taxi. Imperative = "left, then right, then straight 200 m". Declarative = "take me to the station". You say *where*, the driver works out *how*.

React's core idea is often written as **UI = f(state)**: the screen is a function of the current data. When the data changes, React calls your function again and updates the page to match.



The problem it solves

In an imperative UI every event handler must remember *every* piece of screen that depends on the changed data. With three labels, a badge and a disabled button all depending on `likes`, forgetting one line produces an inconsistent screen. Bugs grow with the number of (state × places-that-show-it) combinations. In the declarative version there is only one place – the JSX – that says what each piece looks like.

How it works – the same button both ways

`code/01_imperative_vs_declarative.jsx`

```
// ---- Imperative: YOU write every step that changes the page ----
let likes = 0;
const btn = document.createElement('button');
const label = document.createElement('span');
label.textContent = 'No likes yet';
btn.textContent = 'Like';
btn.addEventListener('click', () => {
  likes++;                                        // 1. change the data
  label.textContent = `${likes} like(s)`;         // 2. remember to update the label
  btn.textContent = likes >= 3 ? 'Popular!' : 'Like'; // 3. ...and the button
});

// ---- Declarative: you describe WHAT the UI looks like for a given state ----
function LikeButton() {
  const [likes, setLikes] = useState(0);
  return (
    <div>
      <button onClick={() => setLikes(likes + 1)}>{likes >= 3 ? 'Popular!' : 'Like'}</button>{' '}
      <span>{likes === 0 ? 'No likes yet' : `${likes} like(s)`}</span>
    </div>
  );
}
// ... both are clicked three times, then printed
```

Output:

```
imperative: <button>Popular!</button> <span>3 like(s)</span>
declarative: <div><button>Popular!</button> <span>3 like(s)</span></div>
```

Both give the same HTML. The difference is *where the knowledge lives*: in the imperative version the click handler knows about the label and the button; in React the click handler only changes data (`setLikes`), and the JSX alone decides what is shown. `useState` is explained fully in Chapter 3.

Trade-offs

	Imperative DOM code	Declarative React
Small widget	Shortest code, no dependency	Overhead of a library and build step
Growing UI	Handlers get tangled; easy to forget an update	Each piece described once; scales well
Performance	You can hand-optimise every step	React does diffing work; fast enough for almost all UIs, with tools for hot spots
Debugging	Trace which handler changed what	Inspect state and props in React DevTools

In the interview

30-second answer: "React is declarative: I describe what the UI should look like for the current state, and React works out the DOM operations. When state changes, React re-runs my component, compares the new output with the previous one, and applies only the differences. That removes a whole class of bugs where some part of the screen isn't updated."

- *Is React fully declarative?* – The UI description is. You still write imperative code in event handlers (e.g. "on click, set state") and escape hatches such as refs and Effects (Chapter 5).
- *What does UI = f(state) mean?* – Given the same state and props, a component should return the same JSX; the screen is derived from data rather than edited by hand.

TL;DR

Imperative = list the steps; declarative = describe the result. React components describe the result for the current state and React applies the steps.

1.3 Rendering, the virtual DOM and reconciliation (brief)

What it is

- A **React element** is a small, plain JavaScript object that describes one piece of UI: `{ type: 'h1', props: { children: 'Hi' } }`. JSX creates these objects (§1.8).
- The tree of elements your components return is often called the **virtual DOM**: a lightweight *description* of the page that lives in JavaScript memory, not the real DOM. (react.dev rarely uses the term; it talks about the *render tree* instead, but you will hear "virtual DOM" in interviews.)
- **Reconciliation** is React's process of comparing the new element tree with the previous one to work out the smallest set of real DOM changes.

Analogy: an architect's plan. When the client asks for a bigger window, the builder compares the new plan to the old one and replaces only the window – not the whole house.

How it works – three steps on every update

1. **Trigger** – something asks for a render: the initial `root.render(<App />)`, or a state update (`setLikes`).
2. **Render** – React *calls your components* to get a new element tree and compares (diffs) it with the previous tree to work out what changed. This is pure calculation; nothing on screen changes yet.
3. **Commit** – React applies only those differences to the real DOM. The browser then paints.



The diff uses two simple rules instead of an expensive general tree comparison (a general algorithm is roughly $O(n^3)$; React's heuristics make it about $O(n)$):

Rule	Consequence
Different type at the same position (`<div>` → `<section>`, or `<Profile>` → `<Settings>`)	React throws away the old subtree (DOM *and* component state) and builds a new one.
Same type at the same position	React keeps the DOM node and component state, and updates only changed attributes/text.
Lists	Items are matched by their `key` prop, so React can tell "moved" from "changed" (Chapter 2 §2.8).

Since React 16 the engine that performs this work is called **Fiber**; it can split rendering into small units, pause and resume (the basis of React 18+ *concurrent rendering*). You do not need its details to write React.

Code – watching what React actually changes

`code/04_reconciliation.jsx` renders a clock, records every DOM mutation with a `MutationObserver` (a browser API that reports DOM changes), then renders again with a new `time` prop.

```jsx
function Clock({ time }) {
  return (
    <div className="clock">
      <h1>Hello, world!</h1>
      <p>It is {time}.</p>
    </div>
  );
}
await act(() => root.render(<Clock time="10:00:00" />));
// ... start observing, then:
await act(() => root.render(<Clock time="10:00:01" />));
```

Output:

```
DOM changes made by React:
  characterData on <p>: "10:00:00" -> "10:00:01"
same <h1> node kept? true
same <p> node kept?  true
HTML now: <div class="clock"><h1>Hello, world!</h1><p>It is 10:00:01.</p></div>
```

Although the whole `Clock` function ran again, exactly **one** text node changed in the real DOM. (`act()` from `react` is a test helper that makes React finish all pending work before the next line runs; you only use it in tests and scripts like these.)

Common mistakes

- "React re-renders = React rewrites the DOM." No: *re-render* means your function is called again; the DOM changes only where output differs.
- "The virtual DOM makes React faster than hand-written DOM code." Not necessarily — perfectly hand-tuned DOM code does less work. The benefit is getting *good enough* performance automatically while writing declarative code.
- Defining a component *inside* another component: each render creates a new function = a new *type*, so rule 1 applies and state is reset every time (§1.7).

In the interview

> **30-second answer:** "When state changes, React re-renders: it calls the components to build a new tree of elements, diffs it against the previous tree, and commits only the differences to the DOM. The diff is O(n) thanks to two heuristics — elements of different types produce different trees, and keys identify list items across renders."

- *What is the difference between render and commit?* — Render = calling components to compute the new tree (pure, may be repeated or discarded); commit = mutating the DOM and running layout effects/refs.
- *Why can changing a wrapper from `<div>` to `<section>` lose input text?* — Different type at the same position → the subtree is destroyed and recreated, including its state.

Self-check

1. After `setState`, which of your functions run? → The component that owns the state and, by default, all its children (they re-render); only changed DOM nodes are updated.
2. What does a React element look like? → A plain object with `type` and `props` (plus internals such as `key`).
3. What happens to state when a component's type at a position changes? → It is destroyed; the new component starts fresh.

TL;DR

Trigger → render (call components, build element tree) → commit (apply minimal DOM diff). Same type at same position = keep and update; different type = replace; lists matched by key.

1.4 SPA vs MPA vs SSR (and SSG)

What it is

These are strategies for **where and when HTML is produced**.

Term	Full name	How the page is produced
MPA	Multi-Page Application	Every navigation asks the server for a new HTML page (classic PHP/Rails/Django sites).
SPA	Single-Page Application	The server sends one almost-empty HTML file plus a JavaScript bundle; JavaScript builds every screen in the browser and handles navigation without full reloads. Also called **CSR** – client-side rendering.
SSR	Server-Side Rendering	The server runs your React components per request and sends finished HTML; the browser then **hydrates** it (React attaches event handlers to existing HTML).
SSG	Static Site Generation	Like SSR, but done once at **build time**; the HTML files are served from a CDN (Content Delivery Network – servers around the world that cache files close to users).

How it works – see the difference in HTML

`code/05_csr_vs_ssr.jsx` renders one component both ways.


```
function App() {
  const [n, setN] = useState(0);
  return <main><h1>Shop</h1><button onClick={() => setN(n + 1)}>Cart: {n}</button></main>;
}
const html = renderToString(<App />);                  // SSR: component -> HTML string
document.getElementById('root').innerHTML = html;      // what the browser receives
button.click();                                        // before hydration
await act(() => { hydrateRoot(document.getElementById('root'), <App />); });
await act(() => button.click());                       // after hydration
```

Output:

```
CSR first HTML : <div id="root"></div>  (+ <script src="bundle.js">)
SSR first HTML : <div id="root"><main><h1>Shop</h1><button>Cart: <!-- -->0</button></main></div>
click before hydration -> Cart: 0 (nothing happens yet)
click after hydration  -> Cart: 1 | same DOM node reused: true
```

What the output teaches:

1. With **CSR**, the first HTML has no content – users and search-engine crawlers see nothing until JavaScript downloads and runs.
2. With **SSR**, the content is in the first HTML (the `<!-- -->` comment separates two adjacent text pieces so hydration can match them).
3. Server HTML is *not interactive* until **hydration** finishes; a click before that does nothing.
4. Hydration **reuses** the server's DOM nodes rather than recreating them.



Trade-offs

	MPA	SPA / CSR	SSR	SSG
First content shown	Fast	Slow (wait for JS)	Fast	Fastest (from CDN)
Navigation between pages	Full reload	Instant, app-like	App-like after hydration	App-like after hydration
SEO (search-engine optimisation) / link previews	Good	Weaker (crawlers must run JS)	Good	Good
Server needed	Yes	No – static hosting	Yes (Node or edge runtime)	No – static hosting
Fresh per-request data	Yes	Via API calls	Yes	Only at build (or revalidation)
Typical examples	Wikipedia, classic admin tools	Figma-style tools, dashboards behind login	E-commerce, news	Docs, blogs, marketing pages

Modern React frameworks mix these **per route**: a marketing page can be static, a product page server-rendered, a dashboard client-rendered. React 19's **Server Components** go one step further (components that run only on the server and send no JS) – covered in Chapter 13.

When not to use SSR

- An internal tool behind a login where SEO does not matter and users keep the tab open all day – a plain SPA is simpler and cheaper to host.
- When you cannot run a server (pure static hosting) – choose CSR or SSG.

Common mistakes

- Using browser-only APIs (`window`, `localStorage`) during render in an SSR app: the server has no `window`, so it crashes or the HTML differs from the client (a **hydration mismatch**).
- Assuming SSR makes the page interactive sooner. It makes content *visible* sooner; interactivity still waits for JS + hydration.

In the interview

> **30-second answer:** "An SPA ships an empty shell and renders everything in the browser – simple hosting, app-like navigation, but slow first paint and weaker SEO. SSR renders HTML on the server per request, so content appears immediately, then hydration attaches React to it. SSG does the same at build time for pages that rarely change. Frameworks like Next.js let you choose per route."

- *What is hydration?* – React running in the browser over server-generated HTML, reusing the existing DOM and attaching event handlers and state.
- *What causes a hydration mismatch?* – Rendering different output on server and client, e.g. `Date.now()`, `Math.random()`, or `window` checks during render.

TL;DR

MPA = server page per navigation; SPA/CSR = JS builds everything in the browser; SSR = server HTML + hydration; SSG = HTML at build time. Pick per route.

1.5 Setting up a React project

What you need first

Tool	Why	Check
Node.js (current LTS; Vite needs 20.19+ or 22.12+)	Runs the dev server and build tools on your computer – your React code still runs in the browser	`node -v`
npm (comes with Node), or pnpm / yarn / bun	Installs packages listed in `package.json`	`npm -v`
An editor – VS Code is the common choice	Syntax highlighting, JSX support, extensions (ESLint, Prettier)	–
React Developer Tools browser extension (Chrome, Firefox, Edge)	Inspect the component tree, props, and state; profile renders	Components tab in DevTools

Option A – start with a framework (react.dev's recommendation for new apps)

A **framework** bundles React with routing, data loading, server rendering and a build pipeline, so you do not assemble these yourself. The React docs currently recommend:

Framework	Command	Good for
Next.js (App Router)	`npx create-next-app@latest`	Full-stack web apps, SSR/SSG, Server Components; maintained by Vercel
React Router v8 (framework mode)	`npx create-react-router@latest`	Apps that grow from an SPA to full stack; built on Vite, maintained by Shopify
Expo	`npx create-expo-app@latest`	iOS, Android and web from one codebase (React Native)

react.dev also lists newer options such as TanStack Start and RedwoodSDK. `npx` downloads and runs a package's command once without installing it globally; `@latest` picks the newest version.

Option B — build from scratch with Vite

Use this when you want a plain client-side app (learning, dashboards, embedding in an existing site) and are happy to add routing and data fetching yourself. React docs list **Vite**, **Parcel** and **Rsbuild** as build tools; Vite is the most common.

```
# (not run here — needs network) create, install, start
npm create vite@latest my-react-app -- --template react   # or react-ts for TypeScript
cd my-react-app
npm install          # download react, react-dom, vite, plugins into node_modules/
npm run dev          # start the dev server -> http://localhost:5173
```

Command	What happens
`npm create vite@latest …`	Runs the `create-vite` scaffolder, which copies a template folder. The extra `--` passes `--template react` through npm to the scaffolder. Templates include `react`, `react-ts`, and `react-compiler` / `react-compiler-ts` (pre-configured React Compiler).
`npm install`	Reads `package.json`, installs dependencies into `node_modules/`, writes `package-lock.json` (exact versions).
`npm run dev`	Starts Vite's **dev server**: serves files as native ES modules, compiles JSX on the fly, and uses **HMR** (Hot Module Replacement — edits appear in the browser in milliseconds without losing component state).
`npm run build`	Produces an optimised production bundle in `dist/` (minified, tree-shaken, hashed file names for caching).
`npm run preview`	Serves `dist/` locally to test the production build.

Equivalent scaffolding commands: `pnpm create vite`, `yarn create vite`, `bun create vite`.


What about Create React App?

Create React App (CRA) was the standard starter from 2016. The React team deprecated it for new apps on **14 February 2025** (it still works in maintenance mode) because it had no active maintainers, was slow (webpack-based) and gave no path to routing, data fetching or SSR. Old tutorials using `npx create-react-app` are outdated — use a framework or Vite.

Adding React to an existing page

You do not need a new project to use React. On an existing server-rendered site you can mount React into one element: add a build step that bundles your component, put `<div id="cart-widget"></div>` in the HTML, and call `createRoot(document.getElementById('cart-widget')).render(<Cart />)`. You can have several roots on one page.

Choosing



How this book runs React without a browser

You cannot open a browser from a script, so each runnable example does what Vite does – compile JSX with **esbuild** (a fast compiler of the same kind Vite uses; Vite 8 uses Oxc, earlier versions esbuild) – and then renders into **jsdom**, a pure-JavaScript implementation of the DOM:

```
import '../../../../tools_dom.mjs';          // 1. create window/document globals (jsdom)
import { render, screen } from '@testing-library/react';
// 2. render components, click/type like a user, console.log what is on screen
```

For pictures of real pages, the same code is bundled for the browser and screenshotted in headless Chrome. That is exactly how React apps are tested in real projects (Vitest/Jest + jsdom + Testing Library – Chapter 12).

Common mistakes

- Running `npm run dev` outside the project folder (no `package.json` → "Missing script: dev").
- Opening `index.html` by double-clicking. Vite's `index.html` loads `/src/main.jsx`, which a browser cannot run directly; use the dev server or build first.
- Committing `node_modules/` to git; commit `package.json` and the lockfile instead.
- Mixing package managers (`npm` and `yarn` lockfiles in one repo).

In the interview

> **30-second answer:** "For a new production app, react.dev recommends a framework — Next.js, React Router, or Expo for native — because you get routing, data loading and SSR out of the box. For a pure client-side app or learning, I'd use Vite with the react or react-ts template. CRA is deprecated since February 2025."

- *Why Vite over CRA/webpack?* — The dev server serves native ES modules and compiles only the files the browser requests, so startup and HMR stay fast as the app grows; the production build is still fully bundled and optimised. CRA bundled everything with webpack before showing anything.
- *What is HMR?* — Hot Module Replacement: the dev server swaps the changed module in the running page, keeping state, instead of reloading.

TL;DR

Framework (Next.js / React Router / Expo) for real apps; `npm create vite@latest app -- --template react` for SPAs and learning; CRA is deprecated. `npm run dev` / `build` / `preview`.

1.6 Project structure

What it is

A new Vite React project looks like this (file list from the current `template-react`; the linter config file name varies by template version):

```
my-react-app/
├── index.html          ← the single HTML page; contains <div id="root"> and loads src/main.jsx
├── package.json        ← name, scripts (dev/build/preview/lint), dependencies
├── package-lock.json   ← exact installed versions (after npm install)
├── vite.config.js      ← Vite settings; registers @vitejs/plugin-react (JSX, Fast Refresh)
├── public/             ← files copied as-is (favicon, robots.txt), served from /
├── src/
|   ├── main.jsx        ← entry point: finds #root and renders <App />
|   ├── App.jsx         ← the top-level component you edit first
|   ├── App.css, index.css
|   └── assets/         ← images imported from code (get hashed file names on build)
└── node_modules/       ← installed packages (never edit, never commit)
```

How it works — from `index.html` to pixels

1. The browser loads `index.html`, which has an empty `<div id="root"></div>` and `<script type="module" src="/src/main.jsx">`.
2. `main.jsx` calls `createRoot(domNode)` — this creates a React `root`, React's handle on that DOM element.
3. `root.render(<App />)` renders your component tree into it. From now on React owns everything inside `#root`.
4. `<StrictMode>` wraps the app in development only: it calls each component twice per render and runs every Effect's setup → cleanup → setup once extra on mount, to expose impure code and missing cleanups early (Chapter 2 §2.5, Chapter 5). It has no effect in production builds.

`code/vite-app/src/main.jsx` (identical in shape to the template):

```
import { StrictMode } from 'react';
import { createRoot } from 'react-dom/client';
import './index.css';
import App from './App.jsx';

createRoot(document.getElementById('root')).render(
  <StrictMode>
    <App />
  </StrictMode>,
);
```

`code/vite-app/src/App.jsx`:

```
import { useState } from 'react';

function Welcome({ name }) {
  return <h1>Welcome to React, {name}!</h1>;
}

export default function App() {
  const [count, setCount] = useState(0);
  return (
    <div className="card">
      <Welcome name="Sam" />
      <p>This page was built from components.</p>
      <button onClick={() => setCount((c) => c + 1)}>count is {count}</button>
    </div>
  );
}
```

The runnable twin

Because the Vite dev server is not run here (no network), `code/06_first_app.jsx` mounts the **same** `App` into jsdom exactly as `main.jsx` does, then clicks twice:

```
import '../../../../tools_dom.mjs';
import { StrictMode, act } from 'react';
import { createRoot } from 'react-dom/client';
import App from './vite-app/src/App.jsx';

const root = createRoot(document.getElementById('root'));
await act(() => root.render(<StrictMode><App /></StrictMode>));
console.log('after first render :', document.getElementById('root').textContent);
const button = document.querySelector('button');
await act(() => button.click());
await act(() => button.click());
console.log('after two clicks   :', button.textContent);
```

Output:

```
after first render : Welcome to React, Sam!This page was built from components.count is 0
after two clicks   : count is 2
```

And the same `main.jsx` bundled with esbuild and opened in Chrome (`code/first-app.html`):




Figure 1.1 – `App` from `vite-app/src` running in a real browser.

`package.json` in brief

```
{
  "type": "module",
  "scripts": { "dev": "vite", "build": "vite build", "preview": "vite preview" },
  "dependencies": { "react": "^19.x", "react-dom": "^19.x" },
  "devDependencies": { "vite": "…", "@vitejs/plugin-react": "…" }
}
```

`dependencies` ship in your app; `devDependencies` are only needed to build it. `^19.x` means "any 19.* version" (semantic versioning – see the JavaScript book's modules chapter, `../../../javascript/chapters/10-modules-and-tooling/README.md`).

How to grow the structure

Start flat; add folders when a pattern appears. A common medium-size layout: `src/components/` (reusable UI), `src/features/<feature>/` (components + hooks + tests for one feature), `src/hooks/`, `src/lib/` (non-React helpers). Keep one component per file when it is exported. Architecture is covered in Chapter 14.

Common mistakes

- Calling `createRoot` twice on the same element (React warns); create the root once, call `render` as needed.
- Changing DOM inside `#root` by hand (`innerHTML = …`) – React will overwrite it or get confused.
- Removing `<StrictMode>` to "fix" doubled console logs; the doubles reveal real bugs.

Self-check

1. Which file does the browser load first? → `index.html`, which loads `src/main.jsx`.
2. What does `createRoot` need? → A DOM element (e.g. `#root`) that React will manage.
3. Does `StrictMode` slow down production? → No; its checks run only in development.

TL;DR

`index.html` (#root) → `main.jsx` (`createRoot(...).render(<StrictMode><App/></StrictMode>)`) → `App.jsx` (your components). `public/` is copied as-is; `node_modules/` is never committed.

1.7 Your first component

What it is

A component is a JavaScript function that:

1. has a name starting with a **capital letter** (`Profile`, not `profile`),
2. returns **JSX** (or `null` to render nothing).

```
function Profile() {
  return <img src="https://i.imgur.com/MK3eW3As.jpg" alt="Katherine Johnson" />;
}

export default function Gallery() {
  return (
    <section>
      <h1>Amazing scientists</h1>
      <Profile />
      <Profile />
      <Profile />
    </section>
  );
}
```

`Gallery` is a **parent** that renders three **child** `Profile` components. (A runnable version with its output is `01_function_components.jsx` in Chapter 2 §2.1.) The tree of components is the **component tree**; React DevTools shows it.

Why the capital letter?

JSX uses it to decide the `type`: lowercase `<section>` → the string `'section'` (an HTML tag); capitalised `<Profile />` → the variable `Profile` (your function). A lowercase component would be treated as an unknown HTML tag (Chapter 2 §2.1 shows the output).

Exporting and importing

Style	Export	Import
Default (one per file)	`export default function Button() {}`	`import Button from './Button.jsx'` (any name)
Named (many per file)	`export function Button() {}`	`import { Button } from './Button.jsx'` (exact name)

Teams often pick one style for consistency; named exports make renames and auto-imports more reliable.

Rules

- **Define components at the top level of a module, never inside another component.** A component defined inside a parent is a brand-new function every render, so React sees a *different type* each time (§1.3) and destroys its state and DOM — slow and buggy.
- **A component should be pure while rendering**: same inputs → same JSX, no changing outside variables (Chapter 2 §2.5).
- Keep components small: when a piece of JSX has its own meaning (a card, a row, a header) extract it.

Common mistakes

Mistake	Symptom	Fix
`function profile()` (lowercase)	Renders `<profile>` tag, nothing shown	Capitalise
Missing `return` or a line break after `return`	Component renders nothing (`return` alone returns `undefined`)	Wrap multi-line JSX in `( … )` starting on the `return` line
Nested component definitions	Inputs lose focus on every keystroke	Move the inner function to module level
Calling a component as a function `{Profile()}`	Hooks inside break rules, no own identity in the tree	Use `<Profile />`

TL;DR

Component = capitalised function returning JSX, defined at top level, exported default or named, used as `<Name />`.

1.8 JSX

What it is

JSX (JavaScript XML) is a syntax extension that lets you write markup inside JavaScript. It is *not* HTML and not a string: the compiler (esbuild, Babel, SWC, Oxc) turns each tag into a function call that returns a React element object. You can use React without JSX, but almost nobody does.

`code/02_jsx_is_javascript.jsx`:

```
import { createElement, isValidElement } from 'react';

const fromJsx = <h1 className="title">Hello, {'Ada'}!</h1>;
const byHand = createElement('h1', { className: 'title' }, 'Hello, ', 'Ada', '!');

const show = (el) => JSON.stringify({ type: el.type, props: el.props });
console.log('JSX         ->', show(fromJsx));
console.log('createElement->', show(byHand));
console.log('is a React element?', isValidElement(fromJsx));
console.log('typeof element:', typeof fromJsx, '| frozen (dev):', Object.isFrozen(fromJsx));
```

Output:

```
JSX         -> {"type":"h1","props":{"className":"title","children":["Hello, ","Ada","!"]}}
createElement-> {"type":"h1","props":{"className":"title","children":["Hello, ","Ada","!"]}}
is a React element? true
typeof element: object | frozen (dev): true
```

So JSX is just a nicer way to write `createElement(type, props, ...children)`. Since React 17 the compiler uses the **automatic JSX runtime** (`import { jsx } from 'react/jsx-runtime'` inserted for you), which is why modern files do not need `import React from 'react'`. Elements are **immutable** (frozen in development): to change the UI you render a new element, you never edit an old one.

The rules

`code/03_jsx_rules.jsx`:

```jsx
const user = { name: 'Grace Hopper', avatar: 'https://i.imgur.com/yXOvdOSs.jpg', online: true };
const size = 64;

function ProfileHeader() {
  // Rule 1: return ONE root element. A Fragment (<>...</>) groups without adding a DOM node.
  return (
    <>
      {/* Rule 2: attributes are camelCase; class -> className, for -> htmlFor */}
      <label htmlFor="bio" className="label">Bio</label>
      {/* Rule 3: every tag must be closed, even <img /> and <input /> */}
      <img src={user.avatar} alt={user.name} width={size} height={size} />
      <input id="bio" defaultValue="Wrote the first compiler" />
      {/* Rule 4: curly braces hold any JavaScript EXPRESSION */}
      <h2>{user.name.toUpperCase()} ({user.online ? 'online' : 'offline'})</h2>
      {/* Rule 5: style takes an object; property names are camelCase */}
      <p style={{ backgroundColor: 'black', color: 'pink', fontSize: 14 }}>{2 + 3} papers</p>
    </>
  );
}
```

Output (the HTML React produced):

```html
<label for="bio" class="label">Bio</label>
<img alt="Grace Hopper" width="64" height="64" src="https://i.imgur.com/yXOvdOSs.jpg">
<input id="bio" value="Wrote the first compiler">
<h2>GRACE HOPPER (online)</h2>
<p style="background-color: black; color: pink; font-size: 14px;">5 papers</p>
```

#	Rule	Why	Example
1	**One root element**	A function can return only one value; JSX becomes one object	Wrap in `<div>` or a **Fragment** `<>…</>` (no extra DOM node, as the output shows)
2	**Close every tag**	JSX is stricter than HTML	` `, `<img />`, `<li>…</li>`
3	**camelCase attributes**	Attributes become JS object keys; `class` and `for` are reserved words	`className`, `htmlFor`, `onClick`, `tabIndex`, `strokeWidth`. Exceptions: `aria-*` and `data-*` keep dashes
4	**`{}` for JavaScript expressions**	Anything that produces a value: variables, calls, ternaries, `&&`, `.map()`	`{user.name}`, `{count * 2}`, `{formatDate(d)}`
5	**`style` is an object**	`{{ … }}` = braces for JS + an object literal	`style={{ fontSize: 14 }}` – numbers get `px` automatically for most properties

Details that trip beginners:

- **Quotes vs braces for attributes:** `alt="text"` passes a string literal; `alt={name}` passes a JS value. Do not write `src="{avatar}"` – that is the literal text `{avatar}`.
- **Expressions, not statements:** `if`, `for`, and `const` cannot go inside `{}`. Use a ternary, `&&`, `.map()`, or compute a variable *above* the `return` (Chapter 2 §2.7).
- **Comments** inside JSX: `{/* like this */}`.
- **What renders nothing:** `null`, `undefined`, `true`, `false` render nothing; but `0` and `NaN` *do* render (the `&&` trap, Chapter 2 §2.7).
- **Objects cannot be rendered:** `{user}` throws "Objects are not valid as a React child" – render `{user.name}` instead. Arrays of elements are fine.
- **Keyed fragments:** the short `<>` cannot take props; when you need a `key` in a list use `<Fragment key={id}>` (import `Fragment` from `react`).
- **Safety:** text in `{}` is escaped automatically, so `{"<script>…"}` shows as text rather than running – protection against XSS (cross-site scripting). Inserting raw HTML requires the deliberately scary `dangerouslySetInnerHTML={{ __html: … }}`; only use it with sanitised content.

- `defaultValue` (seen above) sets an input's *initial* value without React controlling it; `value` makes it a **controlled input** (Chapter 3 §3.9).

Converting HTML to JSX by hand is error-prone; online "HTML to JSX" converters and editor extensions do it automatically.

Trade-offs

JSX	Alternatives (template languages in Vue/Angular/Svelte)
Full JavaScript inside markup – no new loop/if syntax to learn	Special directives (`v-for`, `@if`) are more restricted but easier for designers to read
Type-checked with TypeScript like any code	Needs dedicated tooling
Needs a compile step	Also needs a compile step (in practice)

In the interview

> **30-second answer:** "JSX is syntax sugar: the compiler turns `<h1 className='x'>Hi</h1>` into a `jsx('h1', {className:'x', children:'Hi'})` call that returns a plain, immutable element object. The rules come from that: one root because a function returns one value, `className` because `class` is reserved, braces for expressions only, and style as an object."

- *Why do you not need `import React` any more?* – The automatic JSX runtime (React 17+) imports `jsx` from `react/jsx-runtime` for you.
- *Is JSX safe from XSS?* – Values in braces are escaped before insertion; the risks are `dangerouslySetInnerHTML`, user-supplied URLs in `href` (React 19 replaces a `javascript:` URL with one that throws "React has blocked a javascript: URL as a security precaution"; still validate URLs yourself) and third-party HTML.
- *Fragment vs div?* – A fragment groups children without an extra DOM node, keeping CSS layouts (flex/grid/tables) and HTML validity intact.

Self-check

1. What does `<Card title="x" />` compile to? → A call like `jsx(Card, { title: 'x' })` returning `{ type: Card, props: { title: 'x' } }`.
2. Why is `<div class="box">` wrong in JSX? → `class` must be `className`; React still sets it but logs "Invalid DOM property `class`. Did you mean `className`?".
3. How do you return two sibling elements? → Wrap them in a Fragment `<>…</>`.
4. Which renders nothing: `false`, `0`, `null`, `''`? → `false`, `null` and `''` (empty text); `0` renders "0".

TL;DR

JSX = `createElement` calls → immutable element objects. One root (use `<>`), close all tags, camelCase attributes (`className`, `htmlFor`), `{expressions}`, `style={{…}}`, text is auto-escaped.

Chapter 1 TL;DR

Idea	Remember
React	Library for UIs built from components; `react-dom` renders to the browser
Declarative	Describe UI for the current state; React applies the DOM changes
Update cycle	Trigger → render (call components) → commit (minimal DOM diff)
Diff rules	Same type = keep + update; different type = replace; lists by key
Rendering strategies	CSR/SPA, SSR (+ hydration), SSG, MPA — frameworks mix them per route
Setup	Framework (Next.js / React Router / Expo) or Vite (`--template react`); CRA deprecated Feb 2025
Entry point	`createRoot(document.getElementById('root')).render(<StrictMode><App/></StrictMode>)`
Components	Capitalised functions returning JSX, defined at module top level
JSX	One root, closed tags, `className` , `{expression}` , `style={{}}` , fragments

Next: Chapter 2 — Components and Props.