Chapter 20 — Cheat Sheets and Glossary

This last chapter squeezes Chapters 1–19 into pages you can scan in a minute or two: one **cheat sheet** per topic, **decision tables** for "which algorithm / which metric for this problem?", the **50 interview questions** that come up most often with short answers, and an alphabetical **glossary** of 348 terms. Nothing here is new. Every line points back to where the idea is taught properly, written like **§6.3** (= Chapter 6, section 6.3); if a line doesn't make sense, follow the reference.

Every formula or number on a sheet that can be computed was recomputed by `code/cheatsheet_checks.py` (it also asserts the library defaults quoted here, for scikit-learn 1.9, PyTorch 2.x and NumPy 2.x):

```
OK  sheet_20_2_math
OK  sheet_20_3_api
OK  sheet_20_4_data_prep
OK  sheet_20_5_algorithms
OK  sheet_20_6_losses
OK  sheet_20_7_metrics
OK  sheet_20_8_validation
OK  sheet_20_9_deep_learning
OK  sheet_20_10_cnn_rnn_attention
OK  sheet_20_11_recommenders
OK  sheet_20_12_rl
OK  sheet_20_13_system_design
OK  sheet_20_14_production
OK  sheet_20_15_responsible
all 14 cheat-sheet checks passed
```


What's inside

#	Sheet	Built from
20.1	The ML workflow	Ch 1, 4, 6, 15, 16
20.2	Math essentials (key formulas)	Ch 2
20.3	NumPy, pandas and scikit-learn API	Ch 3, 4
20.4	Data preparation and feature engineering	Ch 4
20.5	Every algorithm in one table	Ch 5, 7–14
20.6	Loss functions	Ch 2, 5, 8, 10, 13, 14
20.7	Metrics: regression, classification, ranking and more	Ch 6, 9, 11, 13, 16
20.8	Validation and tuning	Ch 4, 6
20.9	Deep learning: layers, activations, optimizers, regularisation, debugging	Ch 10
20.10	CNN, RNN and attention: shapes and formulas	Ch 11, 12
20.11	Recommenders	Ch 13, 17
20.12	Reinforcement-learning update rules	Ch 14
20.13	ML system design: the 7-step framework and napkin math	Ch 15, 17, 18
20.14	Production and MLOps checklist	Ch 16
20.15	Responsible-ML checklist	Ch 19
20.16	Decision tables: which algorithm, which metric	all
20.17	Top 50 interview questions	all
20.18	Glossary (A–Z)	all

Chapter links: 1 · 2 · 3 · 4 · 5 · 6 · 7 · 8 · 9 · 10 · 11 · 12 · 13 · 14 · 15 · 16 · 17 · 18 · 19

Notation used throughout: x = feature vector, y = true label, ŷ = prediction, w = weights, b = bias, η = learning rate, σ = sigmoid, n = number of examples, d = number of features, k = number of neighbours / clusters / results (the context says which).

20.1 The ML workflow (§1.9, §4.10, §6.11, §15.3, §16.1)



Step	Do	Don't	Where
1. Frame	Name the decision the prediction drives, the task type (classification / regression / ranking / clustering), the metric tied to business value, and the **baseline** (current rule, human, "predict the mean")	Start by picking a model	§1.9, §15.3
2. Data	Find where labels come from and how late they arrive; set the test split aside **before** deep EDA; check legality and privacy	Explore the test set; assume labels "exist"	§4.1, §4.2
3. Prepare	Dedupe, impossible values → NaN, impute, encode, scale — all inside one `Pipeline`	Fit anything on the full dataset (leakage)	§4.3–4.6, §4.10
4. Train	Linear/logistic model first, then a random forest and gradient boosting; deep nets for images/text/audio	Jump to the fanciest model	§5.1, §8.4
5. Evaluate	Cross-validate on train, tune on validation folds, report the test score **once**, next to the baseline, per segment	Tune on the test set; quote accuracy on imbalanced data	§6.1, §6.6, §6.9
6. Deploy	Ship preprocessing + model as one artifact; offline gate → shadow → canary → ramp, with a fallback	Re-implement features in another language (skew)	§16.2, §16.6
7. Monitor	Health → inputs → predictions → outcomes; investigate alerts; retrain through the same gates	Auto-promote on a drift alert	§16.8, §16.10

Diagnosing a model from two numbers (§1.10, §6.7):

Train error	Validation error	Diagnosis	First fixes
High	High (close)	Underfitting (high bias)	More capacity, better features, less regularisation, train longer
Low	Much higher	Overfitting (high variance)	More data, more regularisation, simpler model, early stopping, bagging
Low	Low (close)	Good fit	Test once, ship
Suspiciously perfect	Suspiciously perfect	Probably **leakage**	Check feature timestamps, splits, duplicates, top importances (§4.8)

Supervision types (§1.4): supervised (labels) · unsupervised (no labels: clusters, dimensions, anomalies) · semi-supervised (few labels + many unlabelled) · self-supervised (labels made from the data, e.g. next token) · reinforcement (rewards from actions). **Classification** predicts a category, **regression** a number (§1.5). **Batch** learning retrains on everything periodically; **online** learning updates with `partial_fit` (§1.7). **Instance-based** (k-NN) keeps the data; **model-based** keeps parameters (§1.8).

20.2 Math essentials (Ch 2)

Linear algebra (§2.1–2.3)

Idea	Formula	Worked value
Dot product	$a \cdot b = \Sigma\, a_i b_i = \|a\|\|b\|\cos\theta$	$[1,2,3]\cdot[4,5,6] = \mathbf{32}$
L2 / L1 / L∞ norm	$\sqrt{\Sigma a_i^2}$ · $\Sigma\|a_i\|$ · $\max\|a_i\|$	$\|[1,2,3]\|_2 = \sqrt{14} \approx 3.74$
Cosine similarity	$a \cdot b \,/\, (\|a\|\|b\|)$	$32 / (3.74 \cdot 8.77) \approx \mathbf{0.975}$
Linear model	$\hat{y} = w \cdot x + b$; batch: $\hat{y} = Xw + b$	shapes $(n\times d)(d,) \to (n,)$
Matrix product	$(m\times n)(n\times p) \to m\times p$; entry = row·column; **AB ≠ BA**	$(100\times 20)(20\times 5) \to 100\times 5$
2×2 determinant / inverse	$\det = ad - bc$; $A^{-1} = (1/\det)[[d, -b], [-c, a]]$	$[[1,2],[3,4]]$: det −2, inverse $[[-2,1],[1.5,-0.5]]$
Solve Ax = c	`np.linalg.solve(A, c)` (never `inv`)	$x_1+2x_2=5$, $3x_1+4x_2=11 \to x = [1, 2]$
Eigenvector	$Av = \lambda v$	$[[2,1],[1,2]]$: $\lambda = 3$ on $[1,1]$, $\lambda = 1$ on $[1,-1]$
SVD	$M = U\Sigma V^T$ (rotate, stretch, rotate)	top-k singular values = best rank-k approximation
Normal equation	$\theta = (X^TX)^{-1}X^Ty$ (use `lstsq`)	Ridge: $(X^TX + \alpha I)^{-1}X^Ty$

Calculus and optimisation (§2.4–2.5)

Idea	Formula
Power / chain rule	$(x^n)' = nx^{n-1}$ · $(f(g(x)))' = f'(g(x))\cdot g'(x)$
Sigmoid and derivative	$\sigma(z) = 1/(1+e^{-z})$; $\sigma' = \sigma(1-\sigma)$; $\sigma(0) = 0.5$, $\sigma'(0) = 0.25$ (its maximum)
Gradient	∇f = vector of partial derivatives; points **uphill**
Gradient descent	$w \leftarrow w - \eta\nabla L(w)$. On $f = (w-3)^2$, $\eta = 0.1$: 0 → 0.6 → 1.08 (each step keeps 80% of the gap)
MSE gradient	$\nabla = (2/n)X^T(Xw - y)$
Log-loss gradient	$\nabla = (1/n)X^T(\sigma(Xw) - y)$ — "features × (prediction − truth)"
Numerical gradient check	$f'(x) \approx (f(x+h) - f(x-h)) / 2h$
Convergence (MSE)	GD converges if $\eta < 2/\lambda_{max}$ of the Hessian (§5.4)

Probability and statistics (§2.6–2.11)

Idea	Formula / rule	Worked value
Bernoulli / binomial / normal	mean p, var p(1−p) · mean np, var np(1−p) · mean μ, var σ^2	P(3 of 10, p = 0.3) = $C(10,3)\cdot 0.3^3\cdot 0.7^7 \approx$ **0.2668**
68–95–99.7 rule	±1σ, ±2σ, ±3σ of a normal	P(z > 2) ≈ 2.3%
Expectation rules	E[aX+b] = aE[X]+b; Var[aX+b] = a^2Var[X]; independent: Var[X+Y] = Var X + Var Y	Var[3X] = 9·Var[X]
Conditional probability	P(A|B) = P(A∩B)/P(B)	
Bayes	P(A|B) = P(B|A)P(A)/P(B) — posterior ∝ likelihood × prior	1% disease, 90% sensitivity, 5% FPR → P(sick|+) ≈ **0.154**; a 2nd positive → 0.766
z-score	z = (x − μ)/σ	130 with μ 100, σ 15 → 2
Standard error (CLT)	σ/√n; 4× the data halves it	σ 20, n 100 → 2
Population vs sample std	NumPy `ddof=0` (÷n), pandas `ddof=1` (÷(n−1))	
Hypothesis test	p-value = P(data this extreme | H_0); reject if p < α; Type I = α, power = 1 − β	p is **not** P(H_0 true)
Confidence interval	estimate ± critical value × SE (1.96 for 95%, large n)	bootstrap: resample, take 2.5th–97.5th percentiles
Multiple testing	Bonferroni: use α/m	20 tests at 0.05 → expect 1 false hit
Correlation	Pearson r (linear), Spearman (ranks, monotonic); r = 0 ≠ independent	y = x^2 can give r = 0

Information theory (§2.12)

Idea	Formula	Worked value (bits)
Entropy	$H(p) = -\Sigma\ p \log p$	fair coin 1; 90/10 coin 0.469; p = [0.7, 0.2, 0.1] → 1.157
Cross-entropy	$H(p, q) = -\Sigma\ p \log q \geq H(p)$	q = [0.5, 0.3, 0.2] → 1.280
KL divergence	$KL(p\|\|q) = H(p,q) - H(p) \geq 0$, **not symmetric**	0.123
Log loss (one-hot p)	$-(1/n)\ \Sigma$ [y ln p + (1−y) ln(1−p)]	labels [1,0,1,1], p [0.9,0.2,0.6,0.99] → **0.2123** (nats)

20.3 NumPy, pandas and scikit-learn API (Ch 3, §4.10)

NumPy (§3.2)

Task	Code	Remember
Create	`np.array`, `zeros`, `ones`, `eye`, `arange`, `linspace(0, 1, 5)`	one dtype per array; `float32` = 4 bytes, `float64` = 8
Inspect	`a.shape`, `a.dtype`, `a.ndim`, `a.size`, `a.nbytes`	shape `(n,)` ≠ `(n, 1)`
Reshape	`a.reshape(3, 4)`, `a.reshape(-1, 1)`, `a[:, None]`, `a.T`	scikit-learn wants 2-D `X`
Index	`M[0]`, `M[:2, 1:3]` → **view**; `M[M > 5]`, `M[[0, 2]]` → **copy**	`.copy()` when you need independence
Reduce	`M.sum(axis=0)` (one per column), `axis=1` (one per row), `keepdims=True`	the named axis disappears
Broadcast	align shapes from the right; equal or 1 → OK	(3,1)+(1,4) → (3,4); (3,2)+(3,) → error
Matrix product	`A @ B` (not `*`, which is element-wise)	
Standardise columns	`(X - X.mean(axis=0)) / X.std(axis=0)`	fit statistics on training data only
Random	`rng = np.random.default_rng(42)`; `rng.normal`, `rng.integers`, `rng.permutation`	seed once, draw everything from `rng`
Floats	`np.isclose(0.1 + 0.2, 0.3)`	`int8` 127 + 1 wraps to −128

pandas (§3.3)

Task	Code
Load / first look	`pd.read_csv(path)`; `df.head()`, `df.info()`, `df.dtypes`, `df.describe()`, `df.isnull().sum()`, `df["c"].value_counts()`
Fix types	`pd.to_numeric(s, errors="coerce")`, `pd.to_datetime(s)`, `s.astype("category")`
Select	`df["c"]` (Series), `df[["a", "b"]]` (DataFrame), `df.loc[rows, cols]` (labels, **end inclusive**), `df.iloc[0:2]` (positions, end exclusive)
Filter	`df[(df.a > 1) & (df.b == "x")]` — `&`, `|`, `~` with parentheses
Missing values	`dropna()`, `fillna(v)`, `df.groupby(g)["x"].transform("median")`, `df["x_missing"] = df.x.isna()`
Group	`df.groupby("g").agg(n=("x", "size"), mean_x=("x", "mean"))` (one row per group); `transform` keeps the original length
Join / stack	`a.merge(b, on="k", how="left", validate="many_to_one")`; `pd.concat([a, b])`
Vectorise	column arithmetic, `np.where`, `pd.cut`, `.str`, `.dt` — avoid row-wise `apply`
pandas 3	copy-on-write: assign (`df["c"] = df["c"].fillna(0)`), don't chain in-place calls

scikit-learn estimator API (§3.5, §4.10)

Convention	Meaning
`Model(hyper=...)`	hyperparameters go in the constructor
`fit(X, y)` → `self`	learns; learned attributes end in `_` (`coef_`, `mean_`, `classes_`)
`transform` / `fit_transform`	`fit_transform` on **train only**; `transform` on validation/test/production
`predict`, `predict_proba`, `decision_function`, `score`	`score` = accuracy (classifiers), R^2 (regressors)
`Pipeline` / `make_pipeline`	preprocessing + model = one estimator; refit per CV fold (no leakage), one artifact to save
`ColumnTransformer`	different preprocessing per column group; default `remainder="drop"`
`step__param`	address a parameter inside a pipeline, e.g. `prep__num__impute__strategy`, `model__C`
`set_output(transform="pandas")`	named DataFrame outputs for debugging
`joblib.dump(pipe, "m.joblib")`	save the whole pipeline; only load files you trust

```
pre = ColumnTransformer([
    ("num", make_pipeline(SimpleImputer(strategy="median", add_indicator=True), StandardScaler()), num_cols),
    ("cat", OneHotEncoder(handle_unknown="ignore"), cat_cols),
])
pipe = Pipeline([("pre", pre), ("model", LogisticRegression(max_iter=1000))])
search = GridSearchCV(pipe, {"model__C": [0.01, 0.1, 1, 10]}, cv=StratifiedKFold(5), scoring="average_precision")
search.fit(X_train, y_train)                # CV refits the preprocessing inside every fold
print(search.best_params_, search.score(X_test, y_test))   # test set used once
```

Defaults worth knowing (checked by the script): `LogisticRegression` C = 1.0 (L2), solver `lbfgs` · `RandomForestClassifier` `max_features="sqrt"` (regressor: 1.0) · `HistGradientBoosting*` learning_rate 0.1, `max_leaf_nodes` 31, `min_samples_leaf` 20 · `SVC` RBF kernel, C = 1, `gamma="scale"` · `KNeighbors*` k = 5, Minkowski p = 2 · `KMeans` `init="k-means++"`.

Module	Tools you'll use constantly
`model_selection`	`train_test_split`, `cross_val_score`, `cross_validate`, `KFold`, `StratifiedKFold`, `GroupKFold`, `TimeSeriesSplit`, `GridSearchCV`, `RandomizedSearchCV`
`preprocessing`	`StandardScaler`, `MinMaxScaler`, `RobustScaler`, `OneHotEncoder`, `OrdinalEncoder`, `TargetEncoder`, `PolynomialFeatures`, `KBinsDiscretizer`, `FunctionTransformer`
`impute`	`SimpleImputer`, `KNNImputer`, `IterativeImputer`
`metrics`	`accuracy_score`, `precision_score`, `recall_score`, `f1_score`, `roc_auc_score`, `average_precision_score`, `log_loss`, `brier_score_loss`, `mean_absolute_error`, `mean_squared_error`, `r2_score`, `ndcg_score`, `confusion_matrix`, `classification_report`
`calibration`	`CalibratedClassifierCV`, `calibration_curve`
`inspection`	`permutation_importance`, `PartialDependenceDisplay`

Frameworks (§3.7): scikit-learn (and XGBoost / LightGBM / CatBoost) for tables; PyTorch or TensorFlow/Keras for images, text, audio, GPUs and custom networks. Jupyter: seed first, Restart & Run All before sharing, move stable code into `.py` modules (§3.6).

20.4 Data preparation and feature engineering (Ch 4)

Labels (§4.1, §16.3)

Source	Speed	Weakness	Handle with
Natural outcomes (delivery time, chargeback)	Minutes → weeks	Late, incomplete, outcome ≠ truth	Train on mature rows; proxy labels for fresh data
Behaviour / implicit (clicks, watch time)	Seconds	Exposure and position bias	Log impressions and positions; correct bias (IPW)
Human annotation	Hours → days	Cost, reviewer quality	Versioned guidelines, Cohen's κ = (p_o − p_e)/(1 − p_e), gold questions, active learning
Weak supervision (labelling functions + label model)	Instant	Noisy, correlated rules	Snorkel-style label model; audit
LLM-assisted	Seconds	Correlated, systematic errors	Humans review samples, hard cases and per-subgroup slices

κ example: agreement 0.8, chance 0.5 → κ = **0.6**. Retrieval negatives: random (easy), in-batch (cheap, popularity-biased → logQ correction), hard (sharp, some false negatives).

EDA checklist (§4.2): shape & types → missingness (and is it related to the target?) → distributions (skew, sentinels like 999 / 9,999,999, cardinality) → target balance → feature–target and feature–feature relationships (**Spearman** for skewed data) → duplicates, impossible values, leaky IDs. Do detailed EDA on the training split.

Cleaning (§4.3)

Problem	Default fix
Exact duplicates	`drop_duplicates()`, then check the entity key is unique; dedupe **across** splits
Impossible values (age 999)	Set to NaN — they are errors, not outliers
Outliers	IQR fences (Q1 − 1.5·IQR, Q3 + 1.5·IQR), |z| > 3, or log first; cap at training-set percentiles; never blindly delete (fraud *is* the outlier)
Missing: MCAR / MAR / MNAR	Median (numbers) or `"missing"` (categories) **+ missing indicator**; KNN or iterative imputation when other columns predict it; HistGradientBoosting/XGBoost/LightGBM handle NaN natively
Judging an imputer	Hide known values, measure error, and compare downstream CV scores

Encoding (§4.4)

Encoder	Use for	Risk
One-hot (`handle_unknown="ignore"`)	Nominal, low–moderate cardinality	Width; dummy trap for unregularised OLS (`drop="first"`)
Ordinal	Ordered categories; fine for trees	Fake order for linear models / k-NN
Target encoding (`TargetEncoder`)	High cardinality	**Leakage** unless cross-fitted and smoothed
Hashing (`FeatureHasher`)	Unbounded IDs, streaming	Collisions, not reversible
Embeddings	IDs in deep models / recommenders	Needs data per ID; versioning

Scaling (§4.5)

Scaler	Formula	Use when
Standard	(x − mean)/std	Default for linear models, SVMs, neural nets, PCA, k-NN, k-means
Min-max	(x − min)/(max − min)	Bounded inputs (pixels ÷ 255), no big outliers
Robust	(x − median)/IQR	Outliers you keep: [10,11,11,12,12,13,100] → 100 ↦ (100 − 12)/1.5 = 58.67
Log / power	log1p(x), `PowerTransformer`	Heavy right tails (income, counts) — scaling alone never fixes skew
None	—	Trees and tree ensembles

Feature creation (§4.6)

Technique	Example
Interactions / polynomials	price × quantity; `PolynomialFeatures(2)` on 10 features → 65 columns
Binning	age buckets let a linear model fit a U-shape
Log transform	`log1p(income)`
Dates and cycles	day of week, is_weekend, "days since signup"; hour h → (sin 2πh/24, cos 2πh/24): hour 6 → (1, 0)
Text	Bag-of-words, TF-IDF: idf(t) = ln((1+n)/(1+df)) + 1, rows L2-normalised (n = 4, df = 2 → 1.511)
Aggregates and ratios	orders in last 30 min, tickets per month of tenure — must be **point-in-time correct**
Production groups	**entity** (batch), **behavioural aggregates** (streaming), **context** (request time), **cross** (pairs) — §4.6, §16.4

Splits (§4.7): random (i.i.d. data) · **stratified** (classification, keeps class ratios) · **time-based** (anything predicting the future) · **group** (all rows of one user/patient together, to generalise to new entities). Millions of rows → 98/1/1 is fine; a few thousand → cross-validation.

Leakage checklist (§4.8, §16.3): (1) would I know this value at prediction time? (2) split first, then fit everything inside a `Pipeline`; (3) time/group splits when deployment needs them; (4) dedupe across splits; (5) aggregates whose window includes the label moment; (6) label-adjacent fields (refund flag, resolution code); (7) distrust any single dominant feature or a score far above published baselines.

Imbalance (§4.9)

Technique	Effect on probabilities
Better metrics (precision, recall, PR-AUC)	—
Threshold moving	None — often all you need
Class weights (`class_weight="balanced"`)	Inflated → recalibrate
Negative downsampling (keep fraction w)	Inflated → **p_true = p·w / (p·w + 1 − p)**; w = 0.1, p = 0.5 → 0.091
Oversampling / SMOTE (a + u·(b − a) between minority neighbours)	Inflated; resample the **training** data only, after splitting

---

20.5 Every algorithm in one table (Ch 5, 7–14)

n = rows, d = features, k = neighbours/clusters, B = trees, M = boosting rounds, T = sequence length, h = hidden width. Complexities are rough orders of magnitude for intuition, not exact bounds.

Algorithm	What it does	Use when	Key hyperparameters	Pros	Cons	Cost (train / predict)	§
Linear regression (OLS)	$\hat{y} = w \cdot x + b$ minimising MSE	Roughly linear trends, baselines, explaining effects	none (fit_intercept)	Fast, interpretable, extrapolates a trend	Misses curves; outliers; multicollinearity	$O(nd^2 + d^3)$ solver or $O(nd)$/epoch GD / $O(d)$	5.2–5.3
Ridge / Lasso / ElasticNet	OLS + L2 / L1 / both penalty	Many or correlated features; want sparsity (L1)	α (and `l1_ratio`)	Less overfitting; Lasso selects features	Must scale; α tuned by CV	As OLS / $O(d)$	5.7
Polynomial regression	Linear model on powers/products	Smooth curves, few features	degree	Same solvers	Feature explosion; wild at the edges	As OLS on expanded d	5.6
Logistic regression	$p = \sigma(w \cdot x + b)$, log-loss	Binary baseline, calibrated probabilities, sparse text	C (= 1/strength), class_weight	Convex, fast, odds ratios, roughly calibrated	Linear boundary	$O(nd)$ per iteration / $O(d)$	5.8
Softmax regression	K linear scores → softmax	Mutually exclusive classes	C	Coherent probabilities	Linear boundaries	$O(ndK)$ / $O(dK)$	5.9
k-NN	Vote/average of k nearest points	Small low-dimensional data, similarity search	k, metric, weights	No training, any boundary	Slow prediction, needs scaling, curse of dimensionality	$O(1)$ / $O(nd)$ brute force	8.1
Linear SVM	Max-margin hyperplane, hinge loss	High-dimensional sparse text	C	Fast, strong on text	No probabilities	$\sim O(nd)$ / $O(d)$	8.2
Kernel SVM (RBF)	Max margin in an implicit feature space	Small/medium data with curved boundaries	C, γ (tune jointly, log scale)	Convex, flexible, compact (support vectors)	Slow beyond tens of thousands of rows; scaling; no native probabilities	$\sim O(n^2 d)$ to $O(n^3 d)$ / $O(n_{SV} \cdot d)$	8.2
SVR	Fit inside an ε-tube	Small-data regression with noise	C, ε, γ	Ignores small errors	As kernel SVM	As SVM	8.2
Naive Bayes	Bayes + "features independent given class"	Text, tiny data, streaming baselines	α (smoothing), variant (Multinomial/Bernoulli/Gaussian)	Fastest to train, few data needed	Over-confident probabilities, no interactions	$O(nd)$ / $O(dK)$	8.3
Decision tree (CART)	Greedy binary splits maximising impurity decrease	Readable rules, quick look	max_depth, min_samples_leaf, ccp_alpha	Interpretable, no scaling, non-linear	High variance, axis-aligned, no extrapolation	$\sim O(nd \log n)$ / $O(\text{depth})$	7.1
Random forest	Bagged deep trees + random feature subset per split	Strong default with little tuning	n_estimators, max_features, max_depth / min_samples_leaf	Robust, parallel, free OOB score, more trees never hurt	Bigger/slower; less accurate than tuned boosting; no extrapolation	B × tree / $O(B \cdot \text{depth})$	7.3
AdaBoost	Re-weight misclassified samples; weighted vote of stumps	Clean data, simple baseline	n_estimators, learning_rate	Simple	Sensitive to noise/outliers (exponential loss)	M × stump / $O(M)$	7.4
Gradient boosting (sklearn HGB, XGBoost, LightGBM, CatBoost)	Sequential shallow trees fitted to the negative gradient	**Best default for tabular data**	learning_rate, n_estimators (+ early stopping), depth/leaves, min leaf size, subsample, L1/L2	Top tabular accuracy, native NaN/categoricals	Overfits with too many rounds; sequential	M × histogram tree $\approx O(M \cdot nd)$ / $O(M \cdot \text{depth})$	7.4, 7.7
Voting / stacking	Combine different model families (stacking: meta-model on out-of-fold predictions)	Diverse models with different errors	base models, meta-model, cv	Reduces risk	More latency and upkeep; not guaranteed to win	Sum of models	7.5
k-means	Assign to nearest centroid, move	Round, similar-sized clusters	k, n_init (k-means++)	Fast, scales (MiniBatch)	Must pick k; spherical	$O(nkd)$ per iteration	9.1

Algorithm	What it does	Use when	Key hyperparameters	Pros	Cons	Cost (train / predict)	§
	centroids, repeat				assumption; outliers		
Agglomerative	Merge closest clusters bottom-up (dendrogram)	Small data, nested structure	linkage, n_clusters or cut height	No k up front, interpretable tree	$O(n^2)$ memory	$\geq O(n^2)$	9.2
DBSCAN / HDBSCAN	Clusters = dense regions; noise = −1	Odd shapes, outliers, unknown k	eps, min_samples (HDBSCAN: min_cluster_size)	Any shape, labels noise	One global density (DBSCAN); eps hard in high-d	~O(n log n) with an index	9.3
Gaussian mixture (EM)	Soft assignment to k Gaussians	Elliptical/overlapping clusters, need probabilities	k (by BIC), covariance_type	Soft, elliptical	Local optima; k to choose	$O(nkd^2)$ per EM step (full cov.)	9.4
PCA	Project onto top eigenvectors of the covariance	Compression, denoising, pre-step, quick 2-D look	n_components (e.g. 0.95 variance)	Fast, deterministic, `transform`	Linear only; scale first	full SVD $\sim O(nd \cdot \min(n,d))$	9.5
t-SNE / UMAP	Non-linear 2-D maps preserving neighbours	Visualisation only	perplexity / n_neighbors, min_dist	Reveals clusters	Sizes and gaps meaningless; seed-dependent	t-SNE ~O(n log n) (Barnes-Hut)	9.6
Isolation Forest	Anomalies isolate in few random splits	Multivariate anomaly default	n_estimators, max_samples (256), contamination	Fast, no scaling	Misses anomalies visible only in combinations	~linear	9.7
LOF / One-Class SVM	Local density vs neighbours / boundary around normal data	Mixed densities / novelty on clean data	k / ν, γ	Local / flexible	$O(n^2)$-ish / slow on big n	—	9.7
Apriori / FP-Growth	Frequent itemsets → rules ranked by lift	Market-basket analysis	min_support, min_confidence	Readable rules	Many trivial rules	Grows with candidates	9.8
MLP (neural network)	Layers of h = f(Wx + b), trained by backprop	Large data; building block of deep nets	depth, width, lr, batch size, dropout, weight decay	Learns features, very flexible	Data-hungry, many knobs; usually loses to GBDT on small tables	O(params) per example per step	10.1
CNN	Shared convolution kernels + pooling	Images, spatial grids	depth, channels, kernel size, augmentation	Few parameters, translation equivariance	Needs data or a pretrained backbone	$O(k^2 \cdot C_{in} \cdot C_{out} \cdot H \cdot W)$ per layer	11.1–11.2
RNN / LSTM / GRU	Hidden state carried step by step	Streaming/small sequence models, time series	hidden size, layers, clipping	Constant memory per step	Sequential (no parallelism over time)	$O(T \cdot h^2)$	12.2–12.4
Transformer	Self-attention + feed-forward blocks	Text, speech, vision at scale	layers, d_model, heads, context length	Parallel, O(1) path between tokens	$O(T^2 \cdot d)$ attention cost	$O(T^2 d + Td^2)$ per layer	12.7
Matrix factorisation (SGD/ALS)	$\hat{r} = \mu + b_u + b_i + p_u \cdot q_i$	Collaborative filtering baseline	k factors, λ, (α for implicit)	Strong, compact embeddings	Cold start; no context	SGD $O(\lvert R \rvert \cdot k)$/epoch	13.5
Two-tower	User and item encoders meeting at a dot product	Retrieval over millions of items	embedding dim, temperature, negatives	Items precomputed → ANN	Weak feature crosses; versioning	Per request: user tower + ANN	13.7
Multi-armed bandits (ε-greedy, UCB, Thompson)	Explore/exploit over k arms	Headlines, thumbnails, new-item traffic	ε, c, priors	Less regret than A/B	Non-stationarity handling	O(k) per step	14.4
Q-learning / SARSA	TD control on a Q-table	Small discrete MDPs	α, γ, ε schedule	Model-free, simple	Table must fit; sample-hungry	O(1) per update	14.7
DQN	Neural Q-function + replay + target network	Discrete actions, large state spaces	replay size, target sync C, ε	Scales to pixels	Unstable (deadly triad)	Network forward/backward	14.8
Policy gradient /	Gradient ascent on expected	Continuous actions, RLHF	lr, clip ε, entropy bonus, GAE λ	Stochastic and continuous	High variance, on-policy	Network forward/backward	14.9

Algorithm	What it does	Use when	Key hyperparameters	Pros	Cons	Cost (train / predict)	§
actor-critic / PPO	return			policies			
ARIMA / ETS	AR + differencing + MA / smoothing	Single short time series	(p, d, q), seasonality	Built-in intervals, little data	One series at a time, few extra features	Small	12.10

20.6 Loss functions (Ch 2, 5, 8, 10, 13, 14)

Loss	Formula (one example)	Task / model	Notes	§
MSE (squared error)	$(\hat{y} - y)^2$	Regression, linear regression, neural nets	Punishes big errors; optimal constant = **mean**; MLE under Gaussian noise	5.2, 10.3
MAE (L1)	$\lvert\hat{y} - y\rvert$	Robust regression	Optimal constant = **median**	6.2, 10.3
Huber	$\frac{1}{2}e^2$ if $\lvert e\rvert \le \delta$, else $\delta(\lvert e\rvert - \frac{1}{2}\delta)$	Regression with outliers; DQN	Quadratic near 0, linear far away	10.3, 14.8
Quantile (pinball)	$\max(\tau \cdot e, (\tau - 1) \cdot e)$, $e = y - \hat{y}$	Prediction intervals, p90 forecasts	$\tau = 0.9$ → 90th percentile	12.10
Log loss / binary cross-entropy	$-[y \ln p + (1-y) \ln(1-p)]$	Logistic regression, sigmoid outputs, multi-label	Convex for LR; gradient at logit = $p - y$; PyTorch: `BCEWithLogitsLoss` (logits in)	5.8, 10.3
Categorical cross-entropy	$-\ln p_{true}$	Softmax classifiers, language models	Uniform guess = ln K (ln 10 = 2.303); gradient = p − one_hot; PyTorch `CrossEntropyLoss` takes logits + class indices	5.9, 10.3
Hinge	$\max(0, 1 - y \cdot f(x))$, $y \in \{-1, +1\}$	SVM	Zero for points beyond the margin	8.2
ε-insensitive	$\max(0, \lvert y - f(x)\rvert - \varepsilon)$	SVR	Errors inside the tube are free	8.2
Exponential	$e^{-y \cdot f(x)}$	AdaBoost	Explains its outlier sensitivity	7.4
Regularised squared error	$\Sigma(r - \hat{r})^2 + \lambda(\lVert p\rVert^2 + \lVert q\rVert^2 + b^2)$ over observed cells	Matrix factorisation	Implicit version weights every cell by confidence	13.5
Sampled softmax / InfoNCE	$-\ln [e^{s^+/\tau} / \Sigma e^{s/\tau}]$ over in-batch items (logits − log Q for popularity)	Two-tower retrieval, CLIP-style contrastive learning	Temperature $\tau \approx 0.05$–0.1	13.7, 18.6
Skip-gram negative sampling	$-\ln \sigma(v \cdot u^+) - \Sigma \ln \sigma(-v \cdot u^-)$	word2vec, item2vec	Negatives ∝ frequency^0.75	12.9, 13.6
Pairwise / listwise ranking	pairwise: which of two items is better (RankNet/LambdaMART); listwise: optimise NDCG-like list metrics	Learning-to-rank	Pointwise = predict each label independently	17.3
Regularisation terms	L2: $\lambda\Sigma w^2$ · L1: $\lambda\Sigma\lvert w\rvert$	Any	L1 → exact zeros; L2 → shrinkage; AdamW = decoupled L2	5.7, 10.7
TD / Q-learning target	$(r + \gamma \max_{a'} Q(s',a'; \theta^-) - Q(s,a; \theta))^2$ (Huber in DQN)	Value-based RL	θ^- = frozen target network	14.8
Policy gradient	$-\log \pi(a\lvert s) \cdot A_t$	REINFORCE, actor-critic	A = G − V(s) or the TD error	14.9
Reward model (preferences)	$-\ln \sigma(s_{preferred} - s_{rejected})$	RLHF	PPO then maximises reward − $\beta \cdot$KL($\pi \parallel \pi_{SFT}$)	14.10
Fairness penalty	loss + $\lambda \cdot$(mean score A − mean score B)^2	In-processing bias mitigation	Larger λ → more parity, less accuracy	19.4

Rule of thumb: pick the output layer and the loss together — identity + MSE/MAE/Huber (regression), sigmoid + BCE (binary, multi-label), softmax + cross-entropy (one label out of K) (§10.2). Never train on accuracy: its gradient is zero almost everywhere.

20.7 Metrics: formula and when to use (Ch 6, 9, 11, 13, 16)

Regression (§6.2, §16.7) — worked on y = (30, 25, 40, 35, 50), ŷ = (28, 27, 35, 35, 60):

Metric	Formula	Value	Use when
MAE	$(1/n)\Sigma\|e\|$	3.8	Cost grows linearly with error; label outliers shouldn't dominate
MSE / RMSE	$(1/n)\Sigma e^2$ / $\sqrt{\text{MSE}}$	26.6 / 5.16	Big misses are disproportionately bad (a 40-min miss adds 16× what a 10-min miss adds to MSE)
R^2	$1 - \Sigma e^2/\Sigma(y - \bar{y})^2$	0.641	Share of variance explained; 0 = predicting the mean, < 0 = worse
MAPE	$(100/n)\Sigma\|e/y\|$	—	Relative error; breaks near y = 0
p90 absolute error	90th percentile of $\|e\|$	—	Promises made on the tail (ETAs)
Per-cohort error	Any of the above per segment	—	Always: averages hide failing segments

Classification (§6.3, §6.5) — worked on 1,000 transactions, 100 fraud, 80 flagged, 60 correct (TP 60, FP 20, FN 40, TN 880):

Metric	Formula	Value	Use when
Accuracy	(TP + TN)/all	0.94 ("flag nothing" = 0.90)	Balanced classes, equal costs only
Precision (PPV)	TP/(TP + FP)	0.75	False alarms are expensive
Recall (sensitivity, TPR)	TP/(TP + FN)	0.60	Misses are expensive
F1 / Fβ	$2PR/(P + R)$ / $(1+\beta^2)PR/(\beta^2P + R)$	0.667	One number, imbalanced data; F2 favours recall
Specificity / FPR	TN/(TN + FP) / FP/(FP + TN)	0.978 / 0.022	Screening; ROC axes
ROC-AUC	P(random positive scored above random negative)	positives (0.9, 0.7, 0.4) vs negatives (0.8, 0.3, 0.2) → 7/9 = 0.778	Threshold-free ranking quality, moderate imbalance
PR-AUC (average precision)	Area under precision–recall curve; no-skill = base rate	—	**Rare positives** (fraud, ads, disease)
Log loss	$-\text{mean}[y \ln p + (1-y) \ln(1-p)]$	—	Probabilities feed decisions
Brier score	$\text{mean}((p - y)^2)$	y (1,0,1,1), p (0.9,0.2,0.6,0.3) → 0.175; p ≡ 0.5 → 0.25	Calibration quality (proper scoring rule)
ECE	Weighted gap between mean score and observed rate per bin	—	Calibration monitoring (ads)
Macro / weighted averages	Mean of per-class metrics (unweighted / by support)	—	Multiclass; macro exposes weak minority classes

Choosing a threshold (§6.3): with calibrated p, flag when **$p > C_{FP} / (C_{FP} + C_{FN})$** (review $5, missed fraud $100 → $p > 0.048$). Fraud and moderation use **two thresholds**: approve / review or step-up / block.

Ranking and retrieval (§6.4, §13.11, §17.3)

Metric	Formula	Use when
Precision@k	relevant in top k ÷ k	Fixed number of slots
Recall@k	relevant in top k ÷ all relevant	Candidate generation (did the good items survive?)
Hit rate@k	1 if any relevant item in top k	Leave-one-out recommender tests
AP / MAP	mean of precision@i at each relevant rank ÷ #relevant; MAP = mean over queries	Binary relevance, whole list
MRR	mean of 1/rank of the first relevant result	One good answer fast (Q&A, navigation)
NDCG@k	DCG/IDCG, $DCG = \Sigma\ rel_i / \log_2(i + 1)$ (exponential variant: (2^rel − 1))	Graded relevance, position matters
Coverage, diversity, novelty	share of catalogue recommended; 1 − mean pairwise similarity; mean popularity	Beyond-accuracy health of a recommender

Worked: relevances [3, 0, 2, 1, 0, 0], one relevant grade-2 document not retrieved → DCG@5 = 4.431, NDCG@5 = **0.778**; `sklearn.metrics.ndcg_score` builds the ideal only from items you pass it and reports 0.930 — always say which NDCG. With exponential gain, [3, 0, 2] → NDCG@3 = 0.956. Recs A–E with relevant {A, C, F}: P@5 0.4, R@5 0.667, AP@5 0.556, NDCG@5 0.704.

Other families

Area	Metrics	§
Clustering (no labels)	Silhouette s = (b − a)/max(a, b) (higher), Davies–Bouldin (lower), Calinski–Harabasz (higher), inertia/BIC (compare k only) — all favour convex clusters	9.1, 9.9
Clustering (some labels)	Adjusted Rand Index (0 random, 1 perfect), NMI	9.9
Dimensionality reduction	Explained variance, reconstruction error, trustworthiness	9.5, 9.9
Anomaly detection	Precision@k, average precision on a reviewed sample	9.7
Detection / segmentation	IoU = intersection/union (worked 0.5625); mAP over IoU thresholds (VOC 0.5; COCO 0.5–0.95); Dice for masks	11.7
Association rules	support, confidence = supp(A∪B)/supp(A), **lift** = confidence/supp(B) (> 1 positive)	9.8
Online / business	CTR, watch time, retention, revenue per search, resolution rate, promise-kept rate + guardrails	6.1, 16.9
Drift	PSI = Σ(cur − ref)·ln(cur/ref): < 0.1 stable, 0.1–0.25 watch, > 0.25 investigate; KS statistic D; null rates	16.8
Fairness	Selection rate, TPR, FPR, PPV and calibration per group; disparate-impact ratio (four-fifths rule)	19.2–19.3

20.8 Validation and tuning (Ch 4, 6)

Splitter	Folds	Use for
`train_test_split(stratify=y)`	One hold-out	Final test set
`KFold(5, shuffle=True)`	Random equal folds	Regression, i.i.d. rows
`StratifiedKFold`	Same class mix in every fold	Classification (default in `cross_val_score` for classifiers)
`GroupKFold` / `StratifiedGroupKFold`	One entity per fold	Users, patients, devices
`TimeSeriesSplit(gap=…)`	Train on past, validate on the next block	Anything time-ordered; gap mimics label delay
`RepeatedStratifiedKFold` / `LeaveOneOut`	Repeats / k = n	Small data / tiny data only
Nested CV	Outer loop around the whole tuning procedure	Unbiased estimate of "tune then train"

Report CV as **mean ± std**; differences under about one std are not clearly real (§6.6). Expected test error = **bias² + variance + irreducible noise**; averaging B models with variance σ^2 and correlation ρ gives variance $\rho\sigma^2 + (1-\rho)\sigma^2/B$ — bagging shrinks the second term, random feature subsets shrink ρ (§6.7, §7.2).

Tool	Answers	Read it
Learning curve (score vs training size)	Would more data help?	Curves converge low → more capacity; big persistent gap → more data / regularisation
Validation curve (score vs one hyperparameter)	Where is the sweet spot?	Pick the peak of the validation curve

Tuning strategies (§6.9)

Method	Budget control	Best for
Grid search	Product of grid sizes (4 × 5 values × 5 folds = 100 fits)	1–2 hyperparameters, cheap models
Random search	`n_iter`	Default for 3+ hyperparameters (explores each dimension more finely)
Successive halving / Hyperband	Resource per round	Many candidates, scalable resource (rows, epochs)
Bayesian optimisation (Optuna TPE, Gaussian process + expected improvement)	Trials	Expensive trials (boosting on big data, deep nets)

Recipe: defaults + baseline → tune the few that matter (boosting: learning rate + tree size; linear/SVM: C, γ; trees: depth/leaf size) → log-uniform ranges → widen a range if the best value sits on its edge → refit on all training data → test once. **Early stopping** (§6.10): monitor validation loss, stop after `patience` rounds without improvement, restore the best weights; never early-stop on the test set.

Probability calibration (§6.5): reliability diagram + Brier/log-loss on held-out data; fix with **Platt scaling** (sigmoid on the score, small data) or **isotonic regression** (step function, roughly ≥ 1,000 examples) via `CalibratedClassifierCV`; recheck when the base rate shifts. ROC-AUC is unchanged by any strictly increasing map.

20.9 Deep learning: layers, activations, optimizers, regularisation, debugging (Ch 10)

Building blocks (§10.1, §10.3, §10.4)

Piece	Formula / rule
Neuron	$z = w \cdot x + b$, $a = f(z)$
Dense layer	$h = f(Wx + b)$; batch: $H = f(XW^T + b)$; params = inputs × outputs + outputs (256 → 128: 32,896)
Why nonlinearity	Without f, $W_2(W_1x + b_1) + b_2$ is still one linear map; one perceptron can't learn XOR, one hidden layer can
Forward → loss → backward → update	$\theta \leftarrow \theta - \eta \cdot \partial L/\partial \theta$; backprop = chain rule from the loss backwards, ≈ 2–3× a forward pass
Output gradient	sigmoid + BCE and softmax + CE: $\partial L/\partial \text{logits} = p - y$
Weight gradient	$(\text{layer input})^T$ @ (gradient at the layer's pre-activation)
Gradient check	$(L(\theta + \varepsilon) - L(\theta - \varepsilon))/2\varepsilon \approx$ analytic gradient

Activations (§10.2)

Name	Formula	Range	Use
Sigmoid	$1/(1 + e^{-z})$; $\sigma' \le 0.25$	(0, 1)	Binary / multi-label output; LSTM gates
Tanh	$(e^z - e^{-z})/(e^z + e^{-z})$; max slope 1	(−1, 1)	RNN hidden states
ReLU	$\max(0, z)$	[0, ∞)	**Default hidden layer**; can "die"
Leaky ReLU / PReLU / ELU	z or αz ($\alpha \approx 0.01$) / α learned / $\alpha(e^z - 1)$	—	When many ReLUs die
GELU / SiLU (Swish)	$z \cdot \Phi(z)$ / $z \cdot \sigma(z)$	—	Transformers (BERT, GPT), EfficientNet, SwiGLU in LLMs
Softmax	e^z_i / Σ e^z_j (subtract max first)	sums to 1	One label out of K; (2, 1, 0.1) → (0.659, 0.242, 0.099)
Identity	z	$\mathbb{R}$	Regression output

Optimizers (§10.5) — g = mini-batch gradient

Optimizer	Update	Default / note
SGD	$\theta \leftarrow \theta - \eta g$	Set lr explicitly
Momentum	$v \leftarrow \mu v + g$; $\theta \leftarrow \theta - \eta v$	$\mu = 0.9$ ≈ averaging ~10 steps; Nesterov = look-ahead
AdaGrad	$s \leftarrow s + g^2$; $\theta \leftarrow \theta - \eta g/(\sqrt{s} + \varepsilon)$	Sparse features; step shrinks forever
RMSProp	$s \leftarrow \rho s + (1 - \rho)g^2$; $\theta \leftarrow \theta - \eta g/(\sqrt{s} + \varepsilon)$	PyTorch lr 0.01, α (ρ) 0.99
Adam	$m \leftarrow \beta_1 m + (1-\beta_1)g$; $s \leftarrow \beta_2 s + (1-\beta_2)g^2$; $\hat{m} = m/(1-\beta_1^t)$, $\hat{s} = s/(1-\beta_2^t)$; $\theta \leftarrow \theta - \eta\hat{m}/(\sqrt{\hat{s}} + \varepsilon)$	lr 1e-3, $\beta = (0.9, 0.999)$, ε = 1e-8
AdamW	Adam + $\theta \leftarrow \theta - \eta\lambda\theta$ (decoupled)	weight_decay 0.01; the correct "Adam with weight decay"

Schedules: step decay (÷10 at milestones), exponential, reduce-on-plateau, **cosine annealing**, **linear warmup + cosine decay** (transformers/LLMs), one-cycle. LR finder: grow lr exponentially per batch, pick ≈ one-tenth of the lr at the loss minimum.

Initialisation and gradient flow (§10.6)

Scheme	Weight variance	For
Xavier / Glorot	2/(fan_in + fan_out)	tanh, sigmoid, linear
He / Kaiming	2/fan_in (fan_in 256 → 0.0078, std 0.088)	ReLU family
LeCun	1/fan_in	SELU, linear

Never initialise all weights equal (symmetry never breaks). Vanishing/exploding gradients (ten sigmoid layers scale gradients by $\le 0.25^{10} \approx 9.5 \times 10^{-7}$) → ReLU, He/Xavier init, BatchNorm/LayerNorm, residual connections, gradient clipping (`clip_grad_norm_(params, 1.0)`), gates (LSTM/GRU).

Regularisation (§10.7)

Technique	How	Watch out
Dropout (p)	Zero units at random in training; survivors × 1/(1 − p) (inverted dropout)	Call `model.eval()` for inference
Weight decay	λΣw² or AdamW's decoupled shrinkage (1e-4…1e-2 SGD; 0.01–0.1 AdamW)	Often skip biases and norm parameters
BatchNorm	x̂ = (x − μ_batch)/√(σ²_batch + ε), y = γx̂ + β; running stats at eval	Small batches; LayerNorm in transformers/RNNs, GroupNorm for small-batch vision
Early stopping	Stop after `patience` epochs without validation improvement; restore best	Report on a separate test set
Data augmentation	Label-preserving transforms (flips, crops, colour jitter, noise, Mixup/CutMix)	Training data only; don't flip a 6 into a 9
More data / smaller model	—	Often the most effective of all

Debugging checklist (§10.8)

1. Look at a few raw examples and labels **after** the data pipeline.
2. Initial loss ≈ chance: ln K for K classes (ln 10 = 2.303). Much higher → bad init/scale, wrong labels or loss.
3. **Overfit one mini-batch** to ~0 loss. Can't → a bug (labels, loss, no gradient flow, missing `optimizer.step()`).
4. LR range test; start with Adam 1e-3 (or SGD + momentum at the suggested lr).
5. Train with a validation set; plot both curves; normalise inputs with **training** statistics.
6. Only then add regularisation and tune; keep a simple baseline (logistic regression / GBDT) for "what good means".

Curve looks like	Likely cause	Try
Flat from step 0, near ln K	lr far too small; bug (frozen weights, shuffled labels, no step)	Overfit one batch; check the data pipeline
Rising, NaN, spikes	lr too high, exploding gradients, log(0)	Lower lr, clip gradients, logit-based losses
Train ↓, validation ↓ then ↑	Overfitting	Regularise, early stop, more data
Both high and close	Underfitting	Bigger model, train longer, higher lr, better features
Validation better than train	Dropout/augmentation only in training	Usually fine — check the split
Jagged	Small batch or high lr	Larger batch, lower lr

PyTorch loop (§10.9): `model.train()` → for each batch: `logits = model(xb)`; `loss = loss_fn(logits, yb)`; `opt.zero_grad()`; `loss.backward()`; `opt.step()` (then `scheduler.step()`). Evaluate under `model.eval()` + `torch.no_grad()`. Save `state_dict()`. `CrossEntropyLoss` wants `long` class indices; `BCEWithLogitsLoss` wants float targets shaped like the logits. Batch size 32–256 to start; imbalance → `weight=` / `pos_weight=` or `WeightedRandomSampler`.

20.10 CNN, RNN and attention: shapes and formulas (Ch 11, 12)

Convolutional networks (§11.1–11.2)

Quantity	Formula	Example
Output size	out = ⌊(n + 2p − k)/s⌋ + 1	n 5, k 3: s 1 p 0 → 3; s 2 → 2; p 1 → 5 ("same"); 224, k 7, s 2, p 3 → 112
Conv weights	k·k·C_in·C_out + C_out	`Conv2d(64, 128, 3)` → 73,856; `Conv2d(3, 16, 3)` → 448 vs 49,168 for a dense layer on 32×32×3
Tensor layout	PyTorch N×C×H×W; TensorFlow/NumPy images N×H×W×C	`permute(0, 3, 1, 2)`
Pooling	2×2 max, stride 2 halves H and W; no parameters; global average pooling before the head	
Receptive field	each k×k layer adds (k − 1) × product of earlier strides	stacked 3×3 (stride 1): 3, 5, 7 — three 3×3 = one 7×7 with 27C² vs 49C² weights
1×1 conv	mixes channels only	bottlenecks (Inception, ResNet)
Depthwise-separable	per-channel spatial conv + 1×1	≈ 8–9× less compute for 3×3 (MobileNet)
Residual block	y = ReLU(x + F(x))	identity gradient highway (ResNet)
ViT patches	(H/P)·(W/P) tokens	224×224, 16×16 → 196

Architecture timeline (§11.4): LeNet-5 (1998, conv-pool) → AlexNet (2012, ReLU + dropout + GPUs, top-5 15.3%) → VGG (2014, stacked 3×3) → Inception/GoogLeNet (2014, parallel branches, 1×1, GAP) → **ResNet** (2015, skip connections, 3.57% top-5 ensemble) → MobileNet (2017, depthwise-separable) → EfficientNet (2019, compound scaling of depth/width/resolution) → ViT (2020, patches + transformer) → ConvNeXt (2022).

Transfer learning (§11.5): small data similar to ImageNet → freeze backbone, train a new head; more or different data → fine-tune (all or top blocks) with a ~10× smaller lr; preprocess exactly like the pretraining data. **Augmentation (§11.6):** `RandomResizedCrop`, `RandomHorizontalFlip`, `ColorJitter`, `RandomErasing`, Mixup/CutMix, RandAugment — training only.

Vision tasks (§11.7): classification (label) · detection (box + class; IoU, **NMS**: keep the best box, drop overlaps above an IoU threshold, repeat; two-stage Faster R-CNN vs one-stage YOLO grid; mAP) · semantic segmentation (class per pixel; **U-Net** encoder–decoder with concatenated skip connections) · instance segmentation (mask per object; Mask R-CNN, SAM).

Recurrent networks (§12.2–12.5)

Model	Equations	Notes
RNN	$h_t = \tanh(W_{xh} x_t + W_{hh} h_{t-1} + b)$	Shared weights over time; BPTT; truncated BPTT for long sequences
LSTM	$f_t, i_t, o_t = \sigma(W[h_{t-1}, x_t] + b)$; $\tilde{c}_t = \tanh(\dots)$; $\mathbf{c_t = f_t \odot c_{t-1} + i_t \odot \tilde{c}_t}$; $h_t = o_t \odot \tanh(c_t)$	Additive cell path fixes vanishing gradients; forget-gate bias 1; 4 weight blocks
GRU	$z_t, r_t = \sigma(\dots)$; $\tilde{h}_t = \tanh(W[r_t \odot h_{t-1}, x_t])$; $h_t = (1 - z_t) \odot h_{t-1} + z_t \odot \tilde{h}_t$	3 weight blocks, similar accuracy
Seq2seq	Encoder → context → decoder; teacher forcing in training; greedy / **beam search** / sampling at inference	Fixed-size bottleneck → attention

Worked LSTM unit: c = 2.0, f 0.9, i 0.2, c̃ 0.5 → c_new = 1.9; o 0.7 → h = 0.7·tanh(1.9) = 0.669. PyTorch `nn.LSTM(input, hidden, num_layers, batch_first=True)` takes (batch, time, features) and returns (output, (h_n, c_n)). Parameter ratio RNN : GRU : LSTM = 1 : 3 : 4.

Attention and transformers (§12.6–12.7)

Idea	Formula / fact
Scaled dot-product attention	**$\text{Attention}(Q, K, V) = \text{softmax}(QK^T/\sqrt{d_k})\cdot V$** — score, softmax, weighted sum
Why √d_k	Dot products of random unit-variance vectors have std √d_k; scaling keeps softmax out of saturation
Worked example	Q = K = [[1,0],[0,1],[1,1]], V = [[1,2],[3,4],[5,6]] → query 1 weights (0.401, 0.198, 0.401), output [3.0, 4.0]
Self- vs cross-attention	Q, K, V from the same sequence / Q from decoder, K and V from encoder
Causal mask	Upper triangle set to −∞ before softmax (decoders)
Multi-head	h heads of size d_model/h, concatenated and projected
Positional encoding	PE(pos, 2i) = sin(pos/10000^(2i/d)), PE(pos, 2i+1) = cos(…); or learned / RoPE
Block	Multi-head attention and a position-wise FFN (≈ 4× wider), each wrapped in a residual connection + LayerNorm; original: 6 + 6 layers, d_model 512, 8 heads
Families	Encoder-only (BERT), decoder-only (GPT, Claude, LLaMA), encoder–decoder (T5, Whisper)
Cost	Attention $O(T^2 \cdot d)$ vs RNN $O(T \cdot d^2)$; path length O(1) vs O(T); KV cache grows with context

Text (§12.8–12.9): normalise → tokenize → vocabulary (+ `<pad>`, `<unk>`, `<sos>`, `<eos>`) → ids → pad + mask. Subword tokenizers (BPE: merge the most frequent adjacent pair repeatedly; WordPiece; SentencePiece) have no OOV problem; ≈ 0.75 English words per token. word2vec: skip-gram (centre → context) or CBOW (context → centre) with negative sampling; GloVe, fastText (character n-grams), contextual embeddings (BERT).

Time series (§12.10): past-only features (lags, **shifted** rolling means, calendar); chronological splits (`TimeSeriesSplit`); beat naive and **seasonal-naive** baselines; ARIMA(p, d, q) = autoregression + differencing + moving average; trees can't extrapolate a trend → model differences.

20.11 Recommenders (Ch 13, 17.1)

Topic	Key facts
Framing	Fill a huge, sparse user–item matrix; optimise **top-K ranking** on an outcome closer to value than clicks (watch time, saves, purchases)
Feedback	Explicit (stars, real negatives, scarce) vs implicit (clicks/plays, abundant, unobserved ≠ negative → confidence c = 1 + α·count and sampled negatives)
Similarity	Cosine (direction), dot product (includes magnitude/popularity), adjusted cosine (subtract each user's mean), Jaccard $\|A∩B\|/\|A∪B\|$ for sets; for unit vectors $\|a-b\|^2 = 2 - 2\cos$
Content-based vs CF	Attributes (handles new items, over-specialises) vs other users' behaviour (quality and surprise; cold start, popularity bias); hybrids win
Item-based CF	$\hat{r}(u,i) = \text{mean}(u) + \Sigma_j\, S(i,j)(r(u,j) - \text{mean}(u)) \,/\, \Sigma_j\|S(i,j)\|$; precompute item–item neighbours (Amazon, 2003)
Matrix factorisation	$\hat{r} = \mu + b_u + b_i + p_u \cdot q_i$; train on **observed** cells with L2; SGD: err = r − r̂, $p_u \leftarrow p_u + \eta(\text{err}\cdot q_i - \lambda p_u)$; ALS: fix one side, solve ridge per user/item (parallel); implicit ALS covers all cells with confidence weights
Embeddings	Short learned vectors; routes: MF, two-tower, graph (PinSage), pretrained content encoders; item2vec = word2vec on sessions; "near" only means near for the training objective
Two-tower	User tower and item tower meet only at a dot product → item vectors precomputed into an ANN index, user tower per request; in-batch softmax with temperature, **logQ correction**, a few hard negatives; ship tower + index as **one version**
Funnel	Retrieval $10^8 \to 10^3$ (recall) → ranking $10^3 \to 10^2$ (precision/NDCG, rich crosses; GBDT, DLRM, Wide & Deep, DCN) → re-ranking → 10–50 (diversity, freshness, policy)
MMR	next = $\text{argmax}\ [\lambda \cdot \text{rel}(j) - (1-\lambda) \cdot \max_s \text{sim}(j, s)]$
ANN	IVF (k-means lists; `nprobe` ↑ = recall ↑), HNSW (layered graph; M, ef_search), PQ (compressed codes; IVF-PQ), trees (Annoy); always report recall vs exact search with latency
Cold start	New user: popularity, onboarding, context, fast session updates; new item: content features + controlled exploration (bandits)
Evaluation	Time-based split, full-catalogue ranking (sampled metrics mislead); P/R/hit rate@k, MAP, NDCG, coverage, diversity, novelty; **popularity baseline**; then A/B or interleaving
Bias	Popularity bias + feedback loops → measure (coverage, Gini of exposure), correct (logQ, IPS), explore, re-rank; log impressions and positions

20.12 Reinforcement-learning update rules (Ch 14)

Idea	Formula	Notes / worked value
MDP	$(S, A, P(s'\|s,a), R, \gamma)$; Markov: next state depends only on current state and action	§14.2
Return	$G_t = \Sigma_k\ \gamma^k\ r_{t+k+1} = r_{t+1} + \gamma G_{t+1}$	$\gamma = 0.9$: horizon $\approx 1/(1-\gamma) = 10$; $0.9^{10} \approx 0.35$
Value functions	$V^\pi(s) = E[G \mid s]$; $Q^\pi(s,a) = E[G \mid s, a]$; $\pi^*(s) = \text{argmax}_a\ Q^*(s,a)$	Q needs no model to act
Bellman expectation	$V^\pi(s) = \Sigma_a\ \pi(a\|s)\ \Sigma_{s'}\ P(s'\|s,a)[R + \gamma V^\pi(s')]$	Policy evaluation
Bellman optimality	$V^*(s) = \max_a\ \Sigma_{s'}\ P[R + \gamma V^*(s')]$; $Q^*(s,a) = \Sigma_{s'}\ P[R + \gamma\ \max_{a'}\ Q^*(s',a')]$	Treasure grid: 10, 8, 6.2, 4.58, …, −0.43 at the start
ε-greedy	random arm with probability ε, else best	Decay ε
UCB1	$\text{argmax}_a\ [Q(a) + c\sqrt{(\ln t\ /\ N_a)}]$, $c = \sqrt{2}$ in theory	Tune c for your horizon
Thompson sampling	Sample $\theta_a \sim \text{Beta}(\text{wins} + 1, \text{losses} + 1)$, pull argmax	Probability matching
Value iteration	$V(s) \leftarrow \max_a\ \Sigma\ P[R + \gamma V(s')]$ until stable	Needs the model (DP)
Policy iteration	Evaluate π, make π greedy on V, repeat	Few rounds
Monte Carlo	$V(s) \leftarrow V(s) + \alpha[G_t - V(s)]$	Unbiased, high variance, end of episode
TD(0)	$V(s) \leftarrow V(s) + \alpha[r + \gamma V(s') - V(s)]$; **$\delta = r + \gamma V(s') - V(s)$**	Bootstraps, lower variance, every step
Q-learning (off-policy)	$Q(s,a) \leftarrow Q(s,a) + \alpha[r + \gamma\ \max_{a'}\ Q(s',a') - Q(s,a)]$	Learns the greedy policy; cliff edge path
SARSA (on-policy)	$Q(s,a) \leftarrow Q(s,a) + \alpha[r + \gamma Q(s',a') - Q(s,a)]$, a' = next action taken	Learns what it does; safer path
DQN	Minimise $\text{Huber}(r + \gamma\ \max_{a'}\ Q(s',a';\ \theta^-) - Q(s,a;\ \theta))$ on replay mini-batches	Experience replay + target network; Double DQN: select with online, evaluate with target
REINFORCE	$\theta \leftarrow \theta + \alpha \cdot G_t \cdot \nabla \log \pi(a_t\|s_t)$	High variance → baseline: $A_t = G_t - V(s_t)$
Actor-critic	actor: $\theta \leftarrow \theta + \alpha \cdot \delta \cdot \nabla \log \pi$; critic: TD learning on V	PPO = clipped actor-critic update
RLHF	SFT → reward model $(-\ln \sigma(s_w - s_l))$ → PPO on reward $- \beta \cdot KL(\pi \parallel \pi_SFT)$	DPO skips the RL loop; GRPO uses group-mean baselines

Pitfalls (§14.12): reward hacking (a re-collectable +3 per step is worth $3/(1 - 0.9) = 30$), sample inefficiency, sparse rewards, credit assignment, seed instability, sim-to-real gap, unsafe exploration, the **deadly triad** (function approximation + bootstrapping + off-policy).

20.13 ML system design: the 7-step framework and napkin math (Ch 15, 17, 18)



Step	Say out loud	§
1. Frame	Family (predictive / generative / agentic — does it output a score, content or an action?); the known system it resembles; scope; ML task: input, output, category, **ML objective**	15.2, 15.3
2. Success	Online business metric + offline ML metric + guardrails; latency (p95/p99); scale (QPS, peak); cost per request or per completed task	15.3
3. Data	Sources; **label source and delay**; freshness (batch / streaming / request-time); feature groups; leakage and privacy	15.3, 16.3, 16.4
4. Model	Baseline (popularity, rules, LR) → GBDT → deep (two-tower, multi-task); name the trigger to upgrade	15.3
5. Serving	What's offline vs per request; caches (with permissions); cheaper paths; timeouts and fallbacks; funnel if the catalogue is big	15.3, 16.5, 16.6
6. Keep it working	Log inputs/outputs/versions → join outcomes → monitor 4 layers → gated retraining → shadow → canary → ramp	15.3, 16.8, 16.9
7. Failures and cost	Specific failure list with controls; cost = requests × share × calls × price, in the same unit as the benefit	15.3

Business goal → ML objective (§15.3): time spent → P(watch ≥ X s) or expected watch time (not raw clicks) · fraud losses → P(fraud) + cost-based thresholds · delivery promise → minutes to delivery + a product-owned buffer · search revenue → P(purchase | query, item) · churn → P(cancel within 30 days) (label is 30 days late).

Four assumptions that break with a model (§15.1): correctness is a spectrum (need quality metrics) · behaviour depends on data (drift) · compute is not cheap (model calls cost money) · failures are silent (a wrong answer is HTTP 200).

Napkin numbers (illustrative, from the chapters)

Quantity	Arithmetic	Result	§
QPS	requests/day ÷ 86,400; peak ≈ 2–3×	10 M/day → 116 avg, ~347 peak (3×)	15.3
Homepage recs	100 M DAU × 5 loads ÷ 86,400	≈ 5,800 avg, ~17 K peak (3×); × 500 candidates ≈ 8.7 M scores/s	17.1
Feed ranking	500 M DAU × 5 sessions × 3 calls ÷ 86,400	≈ 86.8 K/s; × 500 posts ≈ 43 M scores/s	17.2
Ads scoring	100 K requests/s × 300 candidates	30 M scores/s in a 50–100 ms auction	18.1
Vector memory	N × dims × 4 bytes (float32)	50 M × 128 → 25.6 GB; 100 M × 512 → 204.8 GB; PQ to 64 B → 6.4 GB	17.1, 18.6
Batch precompute	users × items per user	25 M × 500 = 12.5 B rows; active 5 M only → 2.5 B	16.5
LLM cost	10 M req/day × $0.01	$100 K/day ≈ $3 M/month	15.1
Support bot	500 K orders × 8% contacts × 10 calls × $0.01	40 K conversations, $4 K/day; compare **per resolved issue**	15.4
Moderation cascade	200 M uploads/day, 1% flagged to heavy models, 0.1% to humans	2 M heavy/day (≈ 23/s), 200 K human decisions/day (~670 reviewer-days)	18.3
A/B sample size	$n \propto 1/\delta^2$	5% CTR, +1% relative lift → ~3.0 M users per arm; half the lift → ~4× users	16.9
Latency budget (small model)	inference 1–10 ms, online-store lookup 2–10 ms, inline features 0–15 ms, routing/auth 1–5 ms, logging 1–2 ms	batch KV lookup ~1 ms vs online 10–100 ms	16.5, 16.6
Fraud	10 K tx/s × 0.2% fraud; ~50 ms authorisation, ~10 ms for the model	~20 fraud attempts/s	18.2
Video indexing	1 M uploads/day × 600 s ÷ 2 s per sampled frame	300 M frame encodings/day ≈ 3,500/s — indexing, not querying, dominates	17.4
Blurring batch	5 M panoramas × 24 tiles × 10 ms	1.2 M GPU-s/day ≈ 14 GPUs busy all day	18.7

Thirteen case studies in one line each (§17.1–18.9)

Design	Shape	Signature idea
Video recommendations	Multi-source retrieval → ranker → rules	Recall@K + watch time; cold start; position bias; judge sources by marginal recall
Feed ranking	Social fan-in → multi-task heads → value formula → integrity layer	Product-owned weights over calibrated heads; hide/report guardrails
Search ranking	Query understanding → BM25 + semantic retrieval → L1/L2 rankers	NDCG on judged sets; IPW for position-biased clicks; relevance floor for ads
Text-to-video search	Index title/ASR/OCR + CLIP-style frame vectors → fuse channels → ranker	Indexing dominates cost; learned fusion with channel-availability flags; segment vectors for moments
Ad click prediction	Eligibility → retrieval → pCTR/pCVR → auction → pacing	**Calibration** per segment (bid × pCTR); delayed conversions
Fraud detection	Rules + GBDT per transaction → two thresholds	Velocity/graph features; late and censored labels; PR-AUC and $ loss
Harmful content	Hash/rules → fast classifiers → heavy models → humans (cascade)	Prevalence of violating **views**; action ladder; flag rate = compute bill
People You May Know	FoF + affiliations + contacts + embeddings	Score = P(send) × P(accept | sent); Adamic-Adar; privacy fails closed
Music discovery	Weekly batch + online radio	Audio embeddings for new tracks; skip-driven re-ranking; diversity guardrail
Visual search	Image/text encoder → ANN → light ranker	Shared image–text space (CLIP-style); the index churns; re-embed on encoder upgrade
Privacy blurring	Tiled detector at a low threshold → context classifier → multi-view tracking → padded blur → audit	Recall per person across views and per pixel; fail closed; audits instead of A/B tests
Event recommendation	Geo + time filter + content two-tower → GBDT → re-rank → capacity check	Every item is cold: score content, place, time, friends; point-in-time features; organiser exposure
Similar listings	Per-market k-NN on session embeddings → availability filter → ranker	Skip-gram with booked-listing context and same-market negatives; averaged vectors for new listings

20.14 Production and MLOps checklist (Ch 16)

Architecture

- [ ] Five pieces named: training pipeline, feature layer, inference path, serving platform, monitoring loop; offline plane vs online plane (§16.1).
- [ ] Training pipeline: data preparation with **point-in-time-correct joins** → training → evaluation vs production → model registry with lineage (§16.2).
- [ ] One feature definition for training and serving; serving features logged and reused for training (Rules of ML #29, #32, #37) (§16.2).
- [ ] Feature store: offline history for training, online latest values for serving; batch vs streaming vs request-time features with freshness alerts (§16.4).
- [ ] Inference mode chosen by the deciding question "does it need request-time information?": batch, online, streaming, or precompute-then-rerank (§16.5).

Serving

- [ ] Stateless, versioned model service; itemised latency budget; batched feature reads; hot-entity caches (§16.6).
- [ ] Timeouts and an agreed **fallback** (previous model, cached score, heuristic); fail-open vs fail-closed decided per risk (§16.2, §16.6).
- [ ] CPU benchmark before GPUs; distillation / quantisation / pruning if needed (§16.6).
- [ ] Model version logged with every prediction (§16.6).

Evaluation and release

- [ ] Offline metric matches the problem (PR-AUC + threshold, recall@k + NDCG, MAE/RMSE + p90 + cohorts), calibration if scores are used as probabilities, naive and production baselines (§16.7).
- [ ] Release ladder: offline gate (overall **and per segment**) → shadow → sticky canary → ramp with a pre-agreed abort rule; rehearsed rollback of model + features + config (§16.6).
- [ ] A/B test: randomisation unit, one primary metric, guardrails, power (MDE, α, 1 − β), whole weeks, no peeking (or a sequential test), sample-ratio-mismatch check; interleaving / switchback / holdback when appropriate (§16.9).

Monitoring and retraining

- [ ] Four layers: service health → input distributions (PSI, KS, **null rates**) → prediction distribution → outcomes as labels arrive (§16.8).
- [ ] Data drift vs label shift vs concept drift vs plain bugs; alerts start investigations (§16.8).
- [ ] Retraining cadence set by measured decay and label maturity; triggered retrains go through the same gates; never auto-promote (§16.8).
- [ ] Feedback loops: log impressions and selection probabilities; small risk-approved exploration (§16.8).

MLOps (§16.10)

- [ ] Experiment tracking (code version, params, **data hash**, metrics, artifacts) — MLflow, W&B.
- [ ] Data and model versioning (DVC, lakeFS, Delta), data validation that fails the pipeline (TFDV, Great Expectations, Pandera).
- [ ] Registry with stages and owners; orchestration (Airflow, Kubeflow, Dagster); CI with feature unit tests and training–serving consistency tests; CD with shadow/canary/auto-rollback; continuous training (MLOps level 1 → 2).
- [ ] Test the infrastructure independently from the ML: push a trivial model through, confirm identical offline and online predictions (Rules of ML #5).
- [ ] Labels: source, delay, cost; downsample-then-recalibrate; temporal splits; PII minimised, deletion path defined (§16.3).

20.15 Responsible-ML checklist (Ch 19)

Problem framing

- [ ] Is ML appropriate at all? Who is harmed by a wrong output? Is it high-risk (credit, hiring, …) under the EU AI Act or similar law? (§19.9)
- [ ] Does the label measure what we care about (not arrests, past hires or cost as proxies)? (§19.1)
- [ ] Which fairness criterion fits the harm — demographic parity, equal opportunity, equalized odds, calibration — agreed with legal and domain experts? (§19.2)

Data

- [ ] Datasheet: motivation, composition, collection, labelling, uses, distribution, maintenance (§19.8).
- [ ] Coverage audit per group **and intersection**; lawful basis; PII minimised; sensitive attributes stored separately for auditing (§19.1, §19.6).
- [ ] Provenance and poisoning checks on scraped or user-generated data (§19.7).

Model and evaluation

- [ ] Per-group selection rate, TPR, FPR, PPV and calibration with confidence intervals; disparate-impact ratio (< 0.8 is a warning); proxy test (predict the group from the features) (§19.3).
- [ ] Mitigation chosen (reweighing w(g, y) = P(g)P(y)/P(g, y), fairness penalty, group thresholds on validation data), its accuracy cost measured, every criterion re-audited (§19.4).
- [ ] Explanations: permutation importance on held-out data, PDP/ICE, SHAP (values add up to f(x) − E[f]), counterfactuals; reason codes for adverse decisions; never causal claims (§19.5).
- [ ] Robustness (FGSM/PGD, adversarial training), membership-inference risk, DP-SGD / federated learning where needed (§19.6, §19.7).

Deployment and monitoring

- [ ] Model card with intended and out-of-scope uses and disaggregated metrics; human oversight and an appeal path (GDPR Art. 22) (§19.8, §19.9).
- [ ] API hardening: authentication, rate limits, label-only outputs (§19.7).
- [ ] Per-group monitoring, drift and feedback-loop checks, incident and rollback plan, scheduled re-audits (§19.11).

Key formulas: disparate impact = P(Ŷ=1 | B)/P(Ŷ=1 | A) (0.35/0.50 = 0.70) · Chouldechova: FPR = p/(1−p)·(1−PPV)/PPV·(1−FNR) · ε-DP: P[M(D) ∈ O] ≤ e^ε·P[M(D') ∈ O]; Laplace noise scale Δf/ε (count, ε 0.5 → 2); k queries at ε each cost kε · FGSM: x_adv = clip(x + ε·sign(∇ₓL), 0, 1) · FedAvg = data-size-weighted average of client weights.

20.16 Decision tables: which algorithm, which metric

Which algorithm for which problem

Problem	Start with (baseline)	Then try	Avoid / notes	§
Tabular classification or regression, < ~1 M rows	Logistic / linear regression; majority-class or mean baseline	Random forest → **gradient boosting** (LightGBM, XGBoost, CatBoost, `HistGradientBoosting`)	Deep nets usually lose on small tables; k-NN beyond ~20–50 features	7.6, 8.4
Many categorical features	CatBoost or `HistGradientBoosting` with native categoricals	Target encoding (cross-fitted) + GBDT	One-hot of 100 K levels for a linear model	4.4, 7.4
High-dimensional sparse text	TF-IDF + logistic regression / linear SVM; Naive Bayes for tiny data	Fine-tuned transformer if data and budget allow	RBF SVM on sparse text	4.6, 8.2, 8.3
Images	Fine-tune a pretrained CNN/ViT (ResNet-50, EfficientNet) with augmentation	Bigger backbone, more data	Training from scratch on a small dataset	11.5
Detection / segmentation	YOLO-style one-stage (real time) or Faster R-CNN; U-Net for masks	Transformer detectors (DETR)	Judging detectors by accuracy (use mAP)	11.7
Sequences / text generation	Transformer (pretrained)	LSTM/GRU for small, streaming or on-device models	Simple RNN for long dependencies	12.4, 12.7
Time-series forecast	Naive and seasonal-naive; ETS / ARIMA for one series	Global GBDT on lag features (model differences); deep models with lots of data	Random splits; trees on trending levels	12.10
Clustering, round groups	k-means (k-means++, scaled, silhouette/elbow for k)	GMM (ellipses, soft), agglomerative (hierarchy)	k-means on moons/rings	9.1–9.4
Clustering, odd shapes / noise	DBSCAN / HDBSCAN	—	One eps for mixed densities (use HDBSCAN)	9.3
Compression / pre-step	PCA (standardise first; ~95% variance)	Kernel PCA, TruncatedSVD for sparse	PCA for visualising non-linear structure	9.5
2-D visualisation	PCA first, then t-SNE / UMAP	UMAP for big data or new points	Reading cluster sizes/gaps in t-SNE	9.6
Anomaly detection, unlabelled	Robust z / IQR per feature; Isolation Forest multivariate	LOF (mixed densities), One-Class SVM (clean novelty data), autoencoders	Plain z-scores on tiny or skewed samples	9.7
Rare-event classification (fraud)	Rules + logistic regression → GBDT with velocity and graph features	Graph neural nets for rings, anomaly scores	Accuracy; single threshold	18.2
Recommendations	Popularity + item-based CF / co-occurrence	Implicit MF (ALS) → two-tower retrieval + GBDT/deep ranker	Pure CF for always-new catalogues	13.4–13.8
Search ranking	BM25 + popularity	Hybrid lexical + semantic retrieval, LambdaMART / deep L2, cross-encoder top-k	Training on raw position-biased clicks	17.3
Choosing among a few options with live feedback	A/B test	Bandits (Thompson, UCB, contextual LinUCB)	Fixed ε forever	14.4
Sequential decisions with a simulator	Value iteration (known model) / Q-learning (small)	DQN (discrete), PPO/SAC (continuous)	Full online RL on live money or people	14.5–14.9
Must explain every decision	Linear/logistic model, small tree, rule list, GAM	GBDT + SHAP reason codes	Deep black box without oversight	19.5

Which metric for which problem

Situation	Primary metric	Also report	Don't	§
Balanced classes, equal costs	Accuracy + confusion matrix	F1, log loss	—	6.3
False positives costly (spam hiding real mail)	Precision at a recall floor	PR curve	Quote precision without threshold and base rate	6.3
Misses costly (screening, fraud)	Recall at a precision floor	Expected cost	—	6.3
Rare positives (≤ ~1%)	PR-AUC / average precision + P/R at the operating threshold	Base rate, expected $ loss	Accuracy; ROC-AUC alone	6.3, 16.7
Comparing rankers, moderate imbalance	ROC-AUC	PR-AUC	—	6.3
Probabilities used in arithmetic (auctions, expected cost)	Log loss, Brier, ECE per segment	Reliability diagram	Trust AUC for calibration	6.5, 18.1
Multiclass with weak minority classes	Macro-F1 / per-class P, R	`classification_report`	Micro-average only	6.3
Regression, errors cost linearly	MAE	p90 error, per cohort	—	6.2
Regression, big misses very costly	RMSE	MAE, p90, per cohort	R^2 alone	6.2
Retrieval / candidate generation	Recall@k	Coverage	NDCG at this stage	6.4, 13.8
Ranked list with graded relevance	NDCG@k (state the gain and ideal)	MAP, MRR	Sampled-negative metrics	6.4, 17.3
One right answer fast	MRR	Hit rate@k	—	6.4
Recommender health	NDCG/MAP + coverage, diversity, novelty	Popularity baseline	Accuracy alone	13.11
Clustering without labels	Silhouette / DB / CH to compare settings	Stability, downstream value	Trust them on non-convex shapes	9.9
Object detection	mAP at IoU thresholds	Per-class AP	Accuracy	11.7
Moderation	Prevalence of violating views per category	Wrongful removals; share of appeals won	Items removed	18.3
Launch decision	Online business metric in an A/B test	Guardrails (latency, complaints, fairness)	Offline metric alone	16.9
Fairness	The criterion that matches the harm (equal opportunity, equalized odds, parity, calibration)	All others + group sizes and CIs	One unnamed "fairness" number	19.2

20.17 Top 50 interview questions

Crisp answers; each points to the full treatment.

Foundations

1. **What's the difference between AI, ML and deep learning?** → AI is the goal of intelligent behaviour (including rules and search); ML learns behaviour from data; deep learning is ML with many-layer neural networks that learn their own features. (§1.1)
2. **Supervised vs unsupervised vs self-supervised vs reinforcement?** → Labels / no labels / labels generated from the data (next token) / rewards from actions in an environment. (§1.4)
3. **Parameters vs hyperparameters?** → Parameters are learned in training (weights); hyperparameters are set before it (learning rate, depth, C) and tuned on validation data. (§1.6)
4. **Why three data splits?** → Train fits parameters, validation chooses hyperparameters and models, the test set is used once so its score stays unbiased. (§1.6, §4.7)
5. **What is data leakage? Give examples.** → Information unavailable at prediction time reaching training or evaluation: post-outcome features, scaling or feature selection fitted before splitting, random splits of time series, duplicates across splits. Prevent with point-in-time features, split-first pipelines and time/group splits. (§1.10, §4.8)
6. **Explain the bias–variance trade-off.** → Test error = bias² + variance + noise. Simple models underfit (high bias), flexible ones overfit (high variance); total error is U-shaped in complexity. (§6.7)
7. **How do you detect and fix overfitting?** → Train score much better than validation; fix with more data, regularisation, a simpler model, early stopping, bagging or augmentation. (§1.10, §6.7)
8. **Explain gradient descent and the learning rate.** → Repeat $w \leftarrow w - \eta \nabla L$. Too small is slow, too large diverges; mini-batches are the practical default; scale features for a rounder loss surface. (§2.5, §5.4)
9. **Explain Bayes' theorem with an example.** → Posterior ∝ likelihood × prior. A 90%-sensitive, 5%-false-positive test for a 1%-prevalence disease gives only ~15% P(sick | positive) — the base-rate effect behind low precision on rare events. (§2.7)

10. **What is a p-value — and what isn't it?** → P(data at least this extreme | H_0). It is not P(H_0 is true); significance ≠ importance; correct for multiple tests and don't peek. (§2.11)
11. **Correlation vs causation?** → Correlation can come from confounders, reverse causation or chance; causal claims need randomised experiments. Models find correlations — fine for prediction, risky for decisions. (§2.9)
12. **What is cross-entropy and why is it the classification loss?** → −ln of the probability given to the true class; it's the maximum-likelihood loss, convex for logistic regression, and punishes confident mistakes hardest, with gradient p − y at the logits. (§2.12, §10.3)

Data

13. **How do you handle missing values?** → Ask why they're missing (MCAR/MAR/MNAR); median or "missing" category plus a missing indicator as a default; KNN/iterative imputation when other columns predict it; fit imputers inside the pipeline; measure by masking known values. (§4.3)
14. **One-hot vs target encoding vs hashing?** → One-hot for small nominal sets; target encoding for high cardinality (cross-fitted and smoothed to avoid leakage); hashing for unbounded IDs (collisions); embeddings in deep models. (§4.4)
15. **Which models need feature scaling?** → Anything using distances, gradients or penalties: k-NN, k-means, SVM, linear/logistic with regularisation, neural nets, PCA. Trees don't. Fit the scaler on training data only. (§4.5)
16. **How do you deal with class imbalance?** → Change the metric (precision/recall, PR-AUC); move the threshold; class weights or downsampling (then recalibrate: $p \cdot w/(p \cdot w + 1 - p)$); SMOTE sometimes; resample training data only. (§4.9)
17. **Where do labels come from, and what goes wrong?** → Outcomes (late), behaviour (biased by exposure and position), human annotation (costly, needs agreement checks), weak supervision and LLMs (correlated errors). (§4.1, §16.3)

Classic models

18. **Linear vs logistic regression?** → Linear predicts a number by minimising MSE; logistic predicts a probability through a sigmoid by minimising log loss; its boundary is w·x + b = 0 and e^w is an odds ratio. (§5.2, §5.8)
19. **Normal equation vs gradient descent?** → Exact $\theta = (X^TX)^{-1}X^Ty$, $O(d^3)$, no tuning — fine for small d; GD scales to huge n and d and any differentiable loss but needs a learning rate and scaled features. (§5.3)
20. **Ridge vs Lasso?** → L2 shrinks all weights and shares weight among correlated features; L1 sets some weights exactly to zero (feature selection). ElasticNet mixes both. More regularisation → more bias, less variance. (§5.7)
21. **How does a decision tree choose a split?** → It tries every feature and threshold and keeps the split with the largest impurity decrease (Gini or entropy; variance for regression); greedy, then prune by depth/leaf size or ccp_alpha. (§7.1)
22. **Bagging vs boosting?** → Bagging trains deep trees in parallel on bootstrap samples and averages (cuts variance); boosting adds shallow trees sequentially, each fitting the current errors (cuts bias). (§7.2–7.4)
23. **Random forest vs gradient boosting?** → RF: robust, little tuning, doesn't overfit by adding trees, free OOB score. GBDT: usually the most accurate on tables but needs a small learning rate and early stopping. (§7.3, §7.4)
24. **Why can feature importance mislead?** → Impurity importance is computed on training data, favours high-cardinality features and splits credit among correlated ones; use permutation importance on held-out data or SHAP. (§7.3, §19.5)
25. **Explain SVMs and the kernel trick.** → Maximise the margin $2/\|w\|$ (C trades width for violations); the dual needs only dot products, so a kernel $K(x, z) = \varphi(x) \cdot \varphi(z)$ gives non-linear boundaries without building φ. Tune C and γ together. (§8.2)
26. **Why is Naive Bayes "naive", and why does it still work?** → It assumes features are independent given the class; classification only needs the argmax right, so it works well for text, but its probabilities are over-confident. (§8.3)
27. **How does k-NN work and when does it fail?** → Vote/average of the k closest scaled points; prediction is O(nd) and distances concentrate in high dimensions (curse of dimensionality). (§8.1)
28. **How does k-means work and how do you choose k?** → Assign to nearest centroid, recompute means, repeat (local optimum; k-means++ and restarts). Choose k by silhouette, elbow and domain sense; it assumes round, similar clusters. (§9.1)
29. **What does PCA do?** → Rotates standardised data onto orthogonal directions of maximum variance (eigenvectors of the covariance / SVD); keep enough components for e.g. 95% variance. Linear and unsupervised. (§9.5)

Evaluation

30. **Precision vs recall — which do you optimise?** → Depends on error costs: precision when false alarms hurt, recall when misses hurt; set the threshold where p > C_FP/(C_FP + C_FN) with calibrated scores, or use two thresholds with a review band. (§6.3)
31. **ROC-AUC vs PR-AUC?** → ROC-AUC = P(a positive outranks a negative), insensitive to base rate; with rare positives, FPR's huge denominator hides false alarms, so PR-AUC (no-skill = base rate) is the honest metric. (§6.3, §16.7)
32. **What is calibration and when does it matter?** → Predicted probabilities matching observed frequencies — separate from ranking. Needed when scores feed arithmetic (auctions, expected cost, human-read risk scores). Fix with Platt or isotonic on held-out data. (§6.5, §18.1)
33. **Explain k-fold cross-validation and its variants.** → k train/validate rounds averaged (mean ± std); stratified for classes, group folds for entities, forward-in-time splits with a gap for temporal data; nested CV for an unbiased tuned estimate. (§6.6)
34. **Grid vs random search vs Bayesian optimisation?** → Grid for 1–2 parameters; random search explores each dimension better on the same budget; Bayesian (Optuna) models score vs hyperparameters for expensive trials; log scales; test once. (§6.9)
35. **Explain NDCG.** → DCG sums graded relevance discounted by $\log_2(\text{rank} + 1)$; dividing by the ideal DCG normalises to [0, 1]. Rewards putting the most relevant items at the top. (§6.4, §17.3)

Deep learning

36. **How does backpropagation work?** → The chain rule applied from the loss backwards through the computational graph, reusing intermediate values, giving every gradient for about the cost of an extra forward pass; an optimizer then updates the weights. (§10.4)
37. **Why do we need non-linear activations, and which ones?** → Without them any stack is one linear map. ReLU for hidden layers (GELU/SiLU in transformers); sigmoid/softmax/identity at the output by task. (§10.2)
38. **Vanishing and exploding gradients — causes and fixes?** → Gradients are products of per-layer (or per-time-step) factors. Fix with ReLU, He/Xavier initialisation, normalisation, residual connections, gating (LSTM/GRU) and gradient clipping. (§10.6, §12.3)

39. **SGD vs momentum vs Adam vs AdamW?** → Momentum accumulates velocity; RMSProp/Adam scale each parameter's step by its recent gradient size (Adam adds bias correction); AdamW decouples weight decay. Adam(W) is the default for transformers; SGD + momentum stays strong for CNNs. (§10.5)
40. **What do dropout and batch normalisation do?** → Dropout zeroes random units in training so the net can't rely on co-adapted features (off at eval); BatchNorm normalises activations per mini-batch, allowing higher learning rates and adding mild regularisation (running stats at eval). (§10.7)
41. **Why CNNs for images?** → Weight sharing and local connectivity give far fewer parameters and translation equivariance; stacked 3×3 convs with downsampling grow the receptive field; ResNet skip connections make very deep nets trainable. (§11.1, §11.4)
42. **What is transfer learning?** → Start from a model pretrained on a big dataset, replace the head, freeze then fine-tune with a small learning rate; biggest gains when labels are scarce. (§11.5)
43. **How does an LSTM fix the RNN's problems?** → An additive cell state $c_t = f \odot c_{t-1} + i \odot \tilde{c}_t$ controlled by sigmoid gates lets information and gradients flow across many steps. (§12.4)
44. **Explain attention and the transformer.** → softmax($QK^T/\sqrt{d_k}$)V is a learned weighted lookup; transformers stack multi-head self-attention and feed-forward layers with residuals and LayerNorm plus positional encodings — parallel over the sequence, O(1) path between tokens, $O(n^2)$ cost. (§12.6, §12.7)

Recommenders, RL and systems

45. **Content-based vs collaborative filtering, and cold start?** → Attributes vs co-behaviour; CF finds quality and surprise but fails on new users/items. Cold start: popularity, onboarding, content features and controlled exploration. (§13.4, §13.10)
46. **How do you retrieve candidates from 100 M items in milliseconds?** → Two-tower model: item vectors precomputed into an ANN index (HNSW/IVF), user tower per request; in-batch negatives with logQ correction; tower and index shipped as one version; then a ranker. (§13.7–13.9)
47. **Q-learning vs SARSA? Exploration vs exploitation?** → Q-learning bootstraps from the max next action (off-policy, learns the optimal policy); SARSA from the action actually taken (on-policy, safer while exploring). Exploration: ε-greedy, UCB, Thompson sampling. (§14.4, §14.7)
48. **Walk me through designing an ML system.** → Frame → success metrics → data and labels → baseline → serving path → keep-it-working loop → failures and cost, translating the business goal into an observable ML objective and keeping product knobs (thresholds, buffers) outside the model. (§15.3)
49. **How do you monitor a model in production, and when do you retrain?** → Health → input drift (PSI/KS/nulls) → prediction drift → outcomes; alerts trigger investigation (often a broken pipeline); retrain on measured decay through offline, shadow and canary gates. (§16.8)
50. **Your model is 94% accurate — is it fair?** → Unknown until you slice by group: selection rate, TPR, FPR, PPV and calibration per group, proxy checks; criteria conflict when base rates differ, so choose by harm and mitigate (reweighing, penalties, thresholds). (§19.2–19.4, §19.12)

20.18 Glossary (A–Z)

352 terms. Each entry: **term** — plain meaning — the section that teaches it (the link opens that chapter).

Term	Meaning	Where
A/B test	Randomised experiment splitting units between control and treatment to measure a business metric	16.9
Accuracy	Share of predictions that are correct, (TP + TN)/all; misleading on imbalanced data	6.3
Action ladder	Graded moderation responses (remove, review, reduce reach/age-gate/warn, allow) set per category and region	18.3
Activation function	Non-linear function applied to a neuron's pre-activation (ReLU, sigmoid, tanh, GELU)	10.2
Active learning	Routing the examples with the most model uncertainty (or annotator disagreement) to human labellers first	4.1
Actor-critic	Policy-gradient method where a critic's TD error δ serves as the advantage for the actor's update	14.9
AdaBoost	Boosting by re-weighting misclassified samples; each stump gets a vote α = ½ ln((1 − ε)/ε)	7.4
Adam	Optimizer combining momentum and RMSProp-style per-parameter step sizes, with bias correction	10.5
Adamic-Adar	Link-prediction score summing 1/log(degree) over shared neighbours, so rare mutual friends count more	18.4
AdamW	Adam with decoupled weight decay applied directly to the weights	10.5
Adjusted cosine	Cosine similarity after subtracting each user's mean rating	13.3
Adjusted Rand Index (ARI)	Agreement between two clusterings corrected for chance: about 0 random, 1 perfect	9.9
Adversarial example	Input perturbed slightly, on purpose, so that a model misclassifies it	19.7
Adversarial training	Including adversarial examples in each training batch to gain robustness	19.7
Agentic AI	Systems that plan and take multi-step actions toward a goal using tools	1.1
Agglomerative clustering	Bottom-up clustering that repeatedly merges the two closest clusters	9.2
ALS (alternating least squares)	Matrix-factorisation solver that fixes one side and solves a ridge regression for the other, alternately	13.5
ANN (approximate nearest neighbour)	Search that returns almost the exact nearest vectors while scanning only a fraction of them	13.9
Anomaly detection	Finding rare points that differ markedly from the majority, usually without labels	9.7
Apriori	Frequent-itemset algorithm that prunes candidates because every subset of a frequent set must be frequent	9.8
ARIMA	Time-series model: autoregression on p lags, d differences, moving average on q past errors	12.10
Attention	Weighted average of value vectors with weights softmax(q·k/√d_k) from query–key similarity	12.6
AUC (ROC-AUC)	Probability a random positive is scored above a random negative; 0.5 random, 1 perfect	6.3
Autograd	Automatic differentiation that records tensor operations and runs backprop on `.backward()`	10.9
Automatic speech recognition (ASR)	Converting speech audio into a (timestamped) transcript, e.g. to make videos searchable	17.4
Average precision (AP)	Area under the precision–recall curve, the usual PR-AUC; no-skill value equals the base rate	6.3
Backpropagation	Chain rule applied from the loss backwards to get every parameter's gradient efficiently	10.4
Backpropagation through time (BPTT)	Backprop through an RNN unrolled over the sequence; gradients summed over time steps	12.2
Bagging	Training copies of a model on bootstrap samples and averaging them to cut variance	7.3
Bandit (multi-armed)	One-state RL problem of choosing among arms with unknown payoffs; isolates exploration vs exploitation	14.4
Baseline	Score of a trivial predictor (majority class, mean, last value, popularity) every model must beat	6.1
Base rate	How often the positive class occurs in the population; drives precision and PR-AUC	6.3
Batch inference	Predictions precomputed on a schedule and stored so a request becomes a lookup	16.5
Batch learning	Training on the full dataset at once and redeploying a frozen model periodically	1.7
Batch normalisation	Layer normalising activations over the mini-batch, then scaling and shifting with learned γ and β	10.7
Bayesian optimisation	Tuning with a surrogate model of score vs hyperparameters and an acquisition function	6.9
Bayes' theorem	P(A|B) = P(B|A)·P(A)/P(B): posterior ∝ likelihood × prior	2.7
Beam search	Decoding that keeps the k most probable partial sequences at each step	12.5
Bellman equation	Value now = expected reward now + γ × value of the next state	14.3
Bias (fairness)	Systematic, unjustified difference in how a model treats or performs for groups	19.1
Bias (statistical)	Error from wrong assumptions; distance of the average model from the truth	6.7
BIC	Bayesian Information Criterion: likelihood penalised by parameter count, lower is better (choose k in GMMs)	9.4
BM25	Lexical relevance score rewarding rare query terms, with diminishing returns and length normalisation	17.3
Boosting	Building an ensemble sequentially, each weak model correcting the current errors	7.4

Term	Meaning	Where
Bootstrap sample	n rows drawn with replacement from n rows; about 36.8% of rows are left out	7.3
BPE (byte-pair encoding)	Subword tokenizer that repeatedly merges the most frequent adjacent symbol pair	12.8
Brier score	Mean squared error of predicted probabilities; a proper scoring rule for calibration	6.5
Broadcasting	NumPy rule for combining arrays of different shapes by stretching size-1 dimensions	3.2
Calibration	Predicted probabilities matching observed frequencies; separate from ranking quality	6.5
Canary release	Giving a new model to a small slice of real traffic before ramping up	16.6
Candidate generation	First funnel stage that retrieves a few hundred plausible items from millions, judged by recall	13.8
Cascade	Cheap checks on everything, expensive checks only on what earlier stages flag	18.3
CatBoost	Gradient-boosting library with ordered boosting and strong native categorical handling	7.4
Censored label	Outcome never observed because your own action (e.g. blocking a payment) prevented it	18.2
Central limit theorem (CLT)	Sample means are approximately normal around the true mean with spread σ/√n	2.10
Chain rule	Derivative of nested functions = product of the local derivatives	2.4
Classification	Supervised task predicting a category	1.5
Class imbalance	One class much rarer than the other(s), as in fraud or disease	4.9
Class weights	Loss weights that make mistakes on the rare class cost more	4.9
CLIP	Image–text model trained contrastively so images and captions share one embedding space	18.6
Cohen's kappa	Chance-corrected agreement between two annotators, (p_o − p_e)/(1 − p_e)	4.1
Cold start	Recommending with little or no history for a new user, item or system	13.10
Collaborative filtering	Recommending from other users' behaviour: people who liked what you liked also liked X	13.4
ColumnTransformer	scikit-learn tool applying different preprocessing to different column groups	3.5
Concept drift	Change in the relationship between inputs and the label, P(Y|X)	16.8
Confidence interval	Range built by a procedure that captures the true value a stated share of the time	2.11
Confusion matrix	Table of TP, FP, FN and TN counts from which classification metrics are computed	6.3
Content-based filtering	Recommending items whose attributes resemble what the user liked	13.4
Contextual bandit	Bandit whose choice depends on context features (e.g. LinUCB)	14.4
Contrastive loss	Loss pulling matching pairs together and pushing non-matching pairs apart (e.g. InfoNCE)	18.6
Convolution	Sliding a small shared kernel over an input and summing element-wise products into a feature map	11.1
Correlation	Strength of co-movement; Pearson for linear, Spearman for monotonic (ranks)	2.9
Cosine similarity	Dot product divided by both lengths; compares direction only	2.1
Cost-complexity pruning	Removing tree branches that don't pay for their leaves, controlled by ccp_alpha	7.1
Counterfactual explanation	Smallest actionable input change that flips a decision	19.5
Covariance matrix	Matrix of how each pair of features varies together; PCA takes its eigenvectors	9.5
Cross-attention	Attention with queries from the decoder and keys/values from the encoder	12.7
Cross-entropy	Average surprise −Σ p log q when reality is p and the prediction is q; the classification loss	2.12
Cross-validation	Rotating the validation role across k folds and averaging the scores	6.6
Curse of dimensionality	In high dimensions space empties and distances concentrate, so "nearest" loses meaning	8.1
Cyclical encoding	Encoding periodic values as (sin, cos) so December sits next to January	4.6
Data augmentation	Creating extra training examples with label-preserving transformations	10.7
Data drift	Change in the input distribution P(X) (covariate shift)	16.8
Data leakage	Information unavailable at prediction time reaching training or evaluation	4.8
Data poisoning	Attack that corrupts training data, possibly planting a backdoor trigger	19.7
Datasheet for datasets	Document describing how a dataset was created, what it contains and how it should be used	19.8
DBSCAN	Density-based clustering: core points with ≥ min_samples neighbours within eps; others border or noise	9.3
Deadly triad	Function approximation + bootstrapping + off-policy learning, which can make RL diverge	14.8
Decision boundary	Where the classifier's decision changes; for logistic regression, w·x + b = 0	5.8
Decision tree	Model predicting by a sequence of feature-threshold questions ending in leaves	7.1
Deep learning	Machine learning with many-layer neural networks that learn their own features	1.1

Term	Meaning	Where
Delayed feedback	Labels (conversions, chargebacks) arriving long after the prediction	18.1
Demographic parity	Fairness criterion requiring equal approval (selection) rates across groups	19.2
Dendrogram	Tree of agglomerative merges; slicing it at a chosen height yields the clusters	9.2
Differential privacy	Guarantee that an algorithm's output barely changes whether any one person is in the data (parameter ε)	19.6
Dimensionality reduction	Describing data with fewer numbers (PCA, t-SNE, UMAP)	9.5
Discount factor (γ)	Weight on future rewards; horizon ≈ 1/(1 − γ)	14.2
Disparate impact ratio	Selection rate of one group divided by another's; below 0.8 fails the four-fifths rule of thumb	19.2
Distillation	Training a small student model to mimic a large teacher	16.6
DPO	Direct Preference Optimization: trains a policy on preference pairs without a separate reward model or RL loop	14.10
DQN	Deep Q-Network: neural Q-function trained with experience replay and a target network	14.8
Dropout	Randomly zeroing units during training so the network can't rely on co-adapted features	10.7
Dummy-variable trap	One-hot columns summing to 1 are collinear with the intercept; drop one for unregularised OLS	4.4
Dynamic programming (RL)	Computing optimal values from a known model by repeated Bellman backups	14.5
Early stopping	Halting training when validation loss stops improving for a set patience	6.10
ε-greedy	Explore a random action with probability ε, otherwise exploit the best known	14.4
Eigenvector	Direction a matrix only stretches, $Av = \lambda v$; λ is the eigenvalue	2.3
ElasticNet	Linear regression with a mix of L1 and L2 penalties	5.7
Embedding	Short dense learned vector representing a discrete thing (word, user, item)	13.6
Ensemble	Combination of several models' predictions	7.5
Entropy	Average uncertainty of a distribution, $-\Sigma\ p \log_2 p$ (bits)	2.12
Epoch	One full pass over the training data	2.5
Equalized odds	Fairness criterion requiring equal TPR and FPR across groups	19.2
Equal opportunity	Fairness criterion requiring equal true-positive rates across groups	19.2
EU AI Act	EU regulation sorting AI systems into risk tiers; credit scoring and hiring are high-risk	19.9
Experience replay	Storing transitions and training on random mini-batches of them to decorrelate updates	14.8
Explainability	Ability to say why a model made a prediction in human-checkable terms	19.5
Exploration–exploitation	Trade-off between trying options to learn and using the best-known option	14.4
Exposure bias	Logs only show outcomes for items the system chose to show	4.1
F1 score	Harmonic mean of precision and recall	6.3
Fail closed	On failure, block the action (don't publish, don't suggest) rather than proceed; used where errors harm people	18.7
Feature	Measurable input property used by a model	1.6
Feature engineering	Creating new inputs that make the pattern easier to learn	4.6
Feature hashing	Mapping categories to a fixed number of buckets with a hash function (hashing trick)	4.4
Feature importance	Score of how much each feature contributes (impurity-based, permutation, SHAP)	7.3
Feature map	Output grid of one convolution kernel applied across the input	11.1
Feature store	System serving consistent features: offline history for training, online latest values for serving	16.4
Federated learning	Training across devices or institutions by averaging locally trained model updates (FedAvg)	19.6
Feedback loop	A model's outputs shaping its own future training data	16.8
FGSM	Fast Gradient Sign Method: $x + \varepsilon \cdot \text{sign}(\nabla_x \text{ loss})$ creates an adversarial example	19.7
Fine-tuning	Continuing training of a pretrained model on your task with a small learning rate	11.5
Forget gate	LSTM gate deciding which cell-state entries to keep or erase	12.4
FP-Growth	Frequent-itemset mining without candidate generation, using a prefix tree	9.8
Funnel	Multi-stage pipeline: cheap high-recall retrieval, heavy ranking, rule-based re-ranking	13.8
GELU	Smooth ReLU-like activation $z \cdot \Phi(z)$ used in transformers	10.2
Generalisation	Performing well on new, unseen data	1.3

Term	Meaning	Where
Generative AI	Models that produce new content such as text, images, audio or code	1.1
Gini impurity	$1 - \Sigma\ p_k^2$, the chance of mislabelling a random sample from the node's class mix	7.1
Global average pooling	Averaging each feature map to one number before the classifier head	11.2
GMM (Gaussian mixture model)	Clustering as a mix of Gaussians fitted with EM, giving soft assignments	9.4
Gradient	Vector of partial derivatives; points in the direction of steepest increase	2.4
Gradient boosting	Boosting where each new tree fits the negative gradient of the loss (residuals for MSE)	7.4
Gradient clipping	Rescaling gradients whose norm exceeds a threshold to prevent explosions	10.6
Gradient descent	Minimising a loss by repeated steps $w \leftarrow w - \eta \nabla L$	2.5
Graph neural network	Neural network over a graph of entities, used e.g. to spot fraud rings	18.2
Grid search	Trying every combination of listed hyperparameter values with cross-validation	6.9
Group split	Keeping all rows of one entity in the same split	4.7
GRU	Gated recurrent unit with update and reset gates; lighter than an LSTM	12.4
Guardrail metric	Metric that must not get worse in an experiment, even if the primary improves	16.9
Hallucination	Generated content that is false or unsupported	15.2
He initialisation	Weight variance 2/fan_in, designed for ReLU layers	10.6
Hierarchical clustering	Clustering that builds a nested tree of merges (see agglomerative)	9.2
Hinge loss	$\max(0, 1 - y \cdot f(x))$; the SVM loss	8.2
HNSW	Hierarchical Navigable Small World graph index for approximate nearest-neighbour search	13.9
Holdback	Small slice kept on the old experience for months to measure long-term effects	16.9
Huber loss	Quadratic for small errors, linear for large; robust regression and DQN	10.3
Hyperparameter	Setting chosen before training, e.g. learning rate, depth or C	1.6
Hypothesis test	Checking whether an observed effect could plausibly be noise under a null hypothesis	2.11
Imputation	Filling missing values (mean, median, KNN, iterative)	4.3
In-batch negatives	Using the other items in a training batch as negatives for each user	13.7
Inference	Using a trained model to make predictions	1.3
Information gain	Entropy of the parent minus the weighted entropy of the children after a split	7.1
Instance-based learning	Predicting from stored similar examples rather than a fitted formula (e.g. k-NN)	1.8
Interleaving	Merging two rankers' results into one list and seeing whose items get clicked	16.9
Inverse propensity weighting (IPW)	Weighting each logged example by 1/P(it was exposed/examined) to remove selection or position bias	17.3
IoU (intersection over union)	Overlap of two boxes divided by their union; matches detections to ground truth	11.7
Isolation Forest	Anomaly detector: anomalies are isolated by random splits in fewer steps	9.7
Isotonic regression	Non-decreasing step-function calibration mapping; needs more data than Platt	6.5
Item2vec	word2vec's skip-gram applied to sessions or playlists to learn item embeddings	13.6
Jaccard similarity	$\lvert A \cap B \rvert / \lvert A \cup B \rvert$ for sets	13.3
k-anonymity	Every quasi-identifier combination shared by at least k records	19.6
Kernel trick	Replacing dot products with a kernel $K(x, z) = \varphi(x) \cdot \varphi(z)$ without computing φ	8.2
k-fold cross-validation	Cross-validation with k equal folds, each used once for validation	6.6
KL divergence	Extra surprise from predicting with q instead of p; non-negative and asymmetric	2.12
k-means	Clustering by alternately assigning points to the nearest centroid and recomputing centroids	9.1
k-means++	Initialisation picking centroids with probability $\propto$ squared distance to those already chosen	9.1
k-nearest neighbours (k-NN)	Predicting by majority vote or average of the k closest training points	8.1
KS test	Kolmogorov–Smirnov: maximum gap between two empirical CDFs, used for drift	16.8
L1 regularisation	Penalty $\lambda \Sigma \lvert w \rvert$ that drives some weights exactly to zero	5.7
L2 regularisation	Penalty $\lambda \Sigma w^2$ that shrinks all weights smoothly (weight decay)	5.7
Label	Target value to predict (y)	1.6
Label encoding	Mapping categories to integer codes; `LabelEncoder` is meant for targets	4.4

Term	Meaning	Where
Label shift	Change in the outcome distribution P(Y)	16.8
Laplace mechanism	Adding Laplace noise with scale sensitivity/ε to achieve ε-differential privacy	19.6
Laplace smoothing	Adding α (usually 1) to every count so unseen words don't get zero probability	8.3
Lasso	Linear regression with an L1 penalty; performs feature selection	5.7
Latency budget	Milliseconds the whole prediction path may take, itemised by stage	16.6
LayerNorm	Normalisation across the features of each example; standard in transformers	10.7
Leaky ReLU	ReLU variant with a small slope α for negative inputs	10.2
Learning curve	Training and validation score vs training-set size	6.8
Learning rate	Step size η of gradient descent	2.5
Learning-rate schedule	Changing the learning rate during training (step, cosine, warmup, one-cycle)	10.5
Learning to rank	Training models to order items (pointwise, pairwise, listwise losses)	17.3
Lift	Confidence(A → B) divided by support(B); above 1 means a positive association	9.8
LightGBM	Gradient-boosting library with leaf-wise histogram trees, GOSS and EFB	7.4
LIME	Local explanation fitting a sparse linear surrogate around one prediction	19.5
Linear regression	Predicting a number as w·x + b by minimising squared error	5.2
Local Outlier Factor (LOF)	Anomaly score comparing a point's local density with its neighbours'	9.7
Logistic regression	Linear score passed through a sigmoid to give a class probability	5.8
Logit	Raw pre-sigmoid or pre-softmax score; for logistic regression, the log-odds	5.8
Log loss	Negative log-likelihood of labels under predicted probabilities; binary cross-entropy	5.8
logQ correction	Subtracting log(sampling probability) from logits so popular items aren't over-penalised as negatives	13.7
LSTM	Recurrent cell with an additive cell state and forget, input and output gates	12.4
MAE	Mean absolute error; optimal constant prediction is the median	6.2
MAP	Mean average precision over queries or users	6.4
Matrix factorisation	Approximating the user–item matrix by user and item factor vectors whose dot product predicts affinity	13.5
Max pooling	Downsampling by keeping the largest value in each window	11.2
Membership inference	Attack deciding whether a record was in the training set	19.7
Mini-batch	Small subset of examples used for one gradient update	5.4
Minimum detectable effect (MDE)	Smallest lift an experiment is sized to detect; sample size ∝ 1/MDE²	16.9
MLOps	DevOps practices (versioning, testing, CI/CD, monitoring) applied to data and models	16.10
MLP (multi-layer perceptron)	Feed-forward network of fully connected layers with non-linear activations	10.1
MMR (maximal marginal relevance)	Greedy re-ranking trading relevance against similarity to items already chosen	13.8
Model card	Short document with a model's intended use, per-group evaluation and limits	19.8
Model extraction	Copying a model by querying its API and training a surrogate	19.7
Model registry	Store of model versions with metrics, lineage, stages and owners	16.10
Momentum	Optimizer that accumulates a velocity of past gradients	10.5
Monte Carlo (RL)	Updating value estimates toward the actual return at the end of an episode	14.6
MRR (mean reciprocal rank)	Mean of 1/rank of the first relevant result	6.4
MSE	Mean squared error; optimal constant prediction is the mean	6.2
Multicollinearity	Features that are near-copies of each other, making coefficients unstable	5.5
Multi-head attention	Several attention heads in parallel subspaces, concatenated and projected	12.7
Multi-task learning	One shared network body with a head per task or event	17.2
Naive Bayes	Bayes' theorem with features assumed independent given the class	8.3
NDCG	Normalised discounted cumulative gain: position-discounted graded relevance ÷ ideal	6.4
Negative sampling	Training against a few sampled negatives instead of a full softmax	12.9
Nested cross-validation	Outer CV loop around the whole tuning procedure for an unbiased estimate	6.6
NMS (non-maximum suppression)	Keeping the most confident detection and removing boxes that overlap it above an IoU threshold	11.7
Normal equation	Closed-form least-squares solution $\theta = (X^T X)^{-1} X^T y$	5.3

Term	Meaning	Where
Novelty effect	Temporary change in behaviour because something is new; fades over time	16.9
Odds ratio	e^w for a logistic-regression coefficient: factor by which the odds change per unit	5.8
Off-policy	Learning about one policy (e.g. greedy) while following another (e.g. ε-greedy)	14.7
One-hot encoding	One 0/1 column per category	4.4
One-vs-rest	K binary classifiers, one per class against the rest	5.9
Online learning	Updating a model continuously from small chunks of data (`partial_fit`)	1.7
Out-of-bag (OOB) score	Validation from the rows each bootstrap tree never saw	7.3
Overfitting	Fitting training noise; low training error, much higher validation error	1.10
Partial dependence (PDP)	Average prediction as one feature is varied over a grid	19.5
PCA	Projection onto orthogonal directions of maximum variance	9.5
Perceptron	Single neuron with a step activation; can't learn XOR	10.1
Permutation importance	Drop in held-out score when one feature's values are shuffled	7.3
Pipeline	scikit-learn object chaining preprocessing and a model into one estimator	3.5
Platt scaling	Calibration by fitting a logistic curve on the model's scores	6.5
Point-in-time join	Joining each training example to feature values as they were at its timestamp	4.8
Policy	Rule mapping states to actions (deterministic or stochastic)	14.3
Policy gradient	Gradient ascent on expected return, raising the log-probability of good actions	14.9
Pooling	Parameter-free downsampling of feature maps (max or average)	11.2
Popularity bias	Recommenders over-recommending already-popular items	13.12
Positional encoding	Position information added to token embeddings because attention ignores order	12.7
Position bias	Items shown higher get more clicks regardless of relevance	17.3
PPO	Proximal Policy Optimization: actor-critic that clips how far each update moves the policy	14.9
PR-AUC	Area under the precision–recall curve; the metric for rare positives	6.3
Precision	TP/(TP + FP): share of flagged items that are truly positive	6.3
Prevalence (of violating views)	Share of all views that land on violating content, estimated by sampling	18.3
Principal component	New axis in PCA; a linear combination of the original features	9.5
Product quantisation (PQ)	Compressing vectors into short codes for memory-efficient approximate search	13.9
Proxy feature	Feature that stands in for a sensitive attribute (e.g. ZIP region for group)	19.3
Pruning (trees)	Stopping growth early or cutting back branches to reduce overfitting	7.1
Pseudonymisation	Replacing identifiers (e.g. hashing IDs); still personal data, not anonymous	19.6
PSI (population stability index)	Σ(cur − ref)·ln(cur/ref) over bins; > 0.25 means investigate	16.8
p-value	Probability of data at least this extreme if the null hypothesis were true	2.11
Q-learning	Off-policy TD control updating Q toward r + γ·max Q(s', ·)	14.7
Quantisation	Storing weights/activations with fewer bits (e.g. int8) to shrink and speed up a model	16.6
R^2	Coefficient of determination: share of target variance explained, 1 − SSE/SST	6.2
Random forest	Bagged decision trees with a random subset of features considered at each split	7.3
Random search	Tuning by sampling hyperparameter combinations from distributions	6.9
Ranking	Ordering items for a user or query; also the precise funnel stage after retrieval	13.8
Recall	TP/(TP + FN): share of true positives that were caught (sensitivity)	6.3
Recall@k	Share of relevant items that appear in the top k	6.4
Receptive field	Region of the input that can influence a unit	11.2
Reciprocal rank fusion (RRF)	Merging ranked lists by summing 1/(k + rank) per list (k ≈ 60); needs no training or score calibration	17.4
Recommender system	System predicting which items a user will want from a large catalogue	13.1
Regression	Supervised task predicting a number	1.5
Regularisation	Anything that limits a model's freedom to fit noise (penalties, dropout, early stopping)	5.7
Reinforcement learning	Learning a policy by trial and error to maximise long-run reward	14.1

Term	Meaning	Where
Reliability diagram	Plot of mean predicted probability vs observed frequency per bin	6.5
ReLU	max(0, z); the default hidden-layer activation	10.2
Residual	Difference between a true value and the prediction	5.5
Residual connection	Skip path y = x + F(x) that gives gradients an identity highway	11.4
Retrieval	Candidate generation: narrowing millions of items to hundreds, graded on recall	17.1
Return (RL)	Discounted sum of future rewards $G_t = r_{t+1} + \gamma G_{t+1}$	14.2
Reward hacking	Agent maximising the reward as written rather than the intended goal	14.12
Reward model	Model trained on human preference comparisons to score responses in RLHF	14.10
Reweighing	Weighting (group, label) cells so group and label are independent in the weighted data	19.4
Ridge regression	Linear regression with an L2 penalty	5.7
RLHF	Reinforcement learning from human feedback: SFT, reward model, then PPO with a KL penalty	14.10
RMSE	Root mean squared error, in the target's units; weighs big misses more	6.2
RMSProp	Optimizer dividing each step by a running RMS of recent gradients	10.5
RNN (recurrent neural network)	Network that reads a sequence step by step, carrying a hidden state	12.2
SARSA	On-policy TD control updating Q toward r + γ·Q(s', a') for the action actually taken	14.7
Scaled dot-product attention	$\text{softmax}(QK^T/\sqrt{d_k})V$	12.6
Seasonal naive	Forecast repeating the value from one season ago (e.g. same weekday last week)	12.10
Self-attention	Attention where queries, keys and values all come from the same sequence	12.7
Self-supervised learning	Learning from labels generated from the data itself (e.g. next-token prediction)	1.4
Semi-supervised learning	Learning from a few labelled examples plus many unlabelled ones	1.4
Seq2seq	Encoder–decoder model mapping an input sequence to an output sequence	12.5
Session embeddings	Item vectors learned by skip-gram over browsing sessions, so items considered together are close	18.9
Shadow deployment	New model scores live traffic in parallel; outputs are logged but not used	16.6
SHAP	Shapley-value attributions splitting one prediction into additive feature contributions	19.5
Sigmoid	$\sigma(z) = 1/(1 + e^{-z})$, squashing a score into (0, 1)	2.4
Silhouette score	Average over points of (b − a)/max(a, b), where a = own-cluster distance and b = nearest-other-cluster distance	9.1
SMOTE	Oversampling by creating synthetic minority points between minority neighbours	4.9
Softmax	$e^{z_k}/\Sigma e^{z_j}$: turns K scores into probabilities that sum to 1	5.9
Sparsity (user–item matrix)	Most user–item cells are empty because each user touches few items	13.1
Stacking	Meta-model trained on out-of-fold predictions of diverse base models	7.5
Standard error	Spread of a sample statistic, $\sigma/\sqrt{n}$ for a mean	2.10
Standardisation	Rescaling to mean 0, std 1: $z = (x - \mu)/\sigma$	2.8
Stochastic gradient descent (SGD)	Gradient descent using one example or a mini-batch per step	2.5
Stratified split	Split keeping class proportions equal in every part	4.7
Stride	How many pixels a kernel moves between positions	11.1
Supervised learning	Learning from inputs paired with correct labels	1.4
Support (association rules)	Fraction of baskets containing an itemset	9.8
Support vector	Training point on or inside the margin that defines an SVM's boundary	8.2
SVM (support vector machine)	Classifier finding the maximum-margin hyperplane, optionally with kernels	8.2
Target encoding	Replacing a category with a smoothed, out-of-fold mean of the target	4.4
Target network	Frozen copy of the Q-network used to compute stable TD targets in DQN	14.8
Teacher forcing	Feeding the true previous token to the decoder during training	12.5
Temporal difference (TD) learning	Updating a value toward reward + γ·(estimate of next value) after every step	14.6
Test set	Data used once at the end to estimate real-world performance	1.6
TF-IDF	Term frequency × inverse document frequency: down-weights words common across documents	4.6
Thompson sampling	Sampling each arm's payoff from its posterior and pulling the best sample	14.4

Term	Meaning	Where
Threshold (decision)	Score cut-off turning probabilities into decisions; sets the precision–recall trade-off	6.3
Time-based split	Training on the past and testing on the future	4.7
Tokenization	Splitting text into tokens mapped to integer ids from a vocabulary	12.8
Training–serving skew	Features computed differently in production than in training	16.2
Transfer learning	Reusing a model pretrained on a large task as the starting point for yours	11.5
Transformer	Architecture of stacked self-attention and feed-forward blocks with residuals and LayerNorm	12.7
t-SNE	Non-linear 2-D visualisation preserving local neighbourhoods	9.6
Two-tower model	Separate user and item encoders whose embeddings meet at a dot product	13.7
UCB (upper confidence bound)	Bandit strategy adding an optimism bonus that shrinks as an arm is tried	14.4
UMAP	Non-linear dimensionality reduction for visualisation that can transform new points	9.6
Underfitting	Model too simple to capture the pattern; training and validation error both high	1.10
U-Net	Encoder–decoder segmentation network with concatenated skip connections	11.7
Universal approximation theorem	One hidden layer with enough units can approximate any continuous function on a bounded region	10.1
Unsupervised learning	Finding structure in data without labels	1.4
Validation curve	Training and validation score vs one hyperparameter	6.8
Validation set	Data used to compare models and tune hyperparameters	1.6
Value function	Expected return from a state, V(s), or from a state–action pair, Q(s, a)	14.3
Value iteration	Repeating the Bellman optimality update until values converge	14.5
Vanishing gradient	Gradients shrinking exponentially through many layers or time steps	10.6
Variance (model)	How much the model changes when trained on a different sample	6.7
Vectorisation	Replacing Python loops with whole-array operations	3.2
Version skew	A new user tower querying an index built by an old item tower; silently degrades quality	13.7
Vision Transformer (ViT)	Transformer applied to image patches treated as tokens	11.4
Weak learner	Model only slightly better than chance, e.g. a stump, used inside boosting	7.4
Weak supervision	Many noisy labelling functions combined by a label model into training labels	4.1
Weight decay	Shrinking weights each step, equivalent to an L2 penalty for SGD	10.7
Word2vec	Shallow model learning word embeddings from context (skip-gram or CBOW)	12.9
Xavier initialisation	Weight variance 2/(fan_in + fan_out), designed for tanh and sigmoid	10.6
XGBoost	Gradient-boosting library with a regularised second-order objective	7.4
YOLO	One-stage detector predicting boxes and classes over a grid in a single pass	11.7
z-score	(x − mean)/std: how many standard deviations from the mean	2.8

Chapter TL;DR

- **20.1–20.4**: the workflow (frame → data → prepare → train → evaluate → deploy → monitor), the math you need (dot products, gradients, Bayes, entropy), the NumPy/pandas/scikit-learn API and data preparation — split first, pipeline everything, fit on training data only.
- **20.5–20.8**: every algorithm with its knobs and costs, every loss, every metric with a worked number, and how to validate and tune honestly (CV, nested CV, calibration, early stopping).
- **20.9–20.12**: deep learning (activations, optimizers, init, regularisation, the debugging checklist), CNN/RNN/attention formulas, recommenders (MF, two-tower, funnel, ANN) and the RL update rules.
- **20.13–20.15**: the 7-step system-design framework with napkin numbers and the thirteen case studies, then the production/MLOps and responsible-ML checklists to run before every launch.
- **20.16–20.17**: decision tables for picking an algorithm and a metric, and 50 interview questions with crisp answers.
- **20.18**: the glossary — follow each **§** back to the chapter where the idea is explained properly.