Chapter 7 — Decision Trees and Ensembles

Decision trees are the most "human" ML model: a chain of yes/no questions you can print and read. On their own they overfit easily, but when you combine many of them — by **averaging** (Random Forests) or by **correcting each other's mistakes** (gradient boosting) — you get the models that win most real-world problems on **tabular data** (rows and columns, like a spreadsheet or SQL table).

What you'll learn

1. How a decision tree picks each question (Gini, entropy, information gain — with a worked example).
2. Depth, pruning, and regression trees.
3. Why a single tree has high variance, and how bagging and Random Forests fix it (bootstrap, feature subsampling, out-of-bag score).
4. Feature importance — and why the default one can lie (permutation importance).
5. Boosting: AdaBoost intuition and gradient boosting step by step on residuals, with learning rate.
6. XGBoost vs LightGBM vs CatBoost.
7. Voting and stacking.
8. Why trees still beat neural nets on tabular data, and a hyperparameter cheat sheet.


All code lives in `code/` and runs with the shared environment (scikit-learn 1.9). Outputs below are real.

7.1 Decision trees

What it is

A **decision tree** is a model that predicts by asking a sequence of questions about the features, like "Is petal length ≤ 2.45 cm?". Each question is a **node**; each answer sends you down a **branch**; when there are no more questions you reach a **leaf**, which holds the prediction (a class for classification, a number for regression).

Analogy: the game "20 Questions". A good player asks the question that rules out the most possibilities first. A tree-learning algorithm does exactly that, greedily, one question at a time.



Why it matters

- **Interpretable**: a shallow tree is a flowchart a doctor or loan officer can check.
- **No scaling needed**: a split "x ≤ 3.2" does not care whether x is in metres or millimetres.
- **Handles mixed data and non-linear effects and interactions** automatically ("high income AND young" can be its own branch).
- It is the **building block** of Random Forests, XGBoost, LightGBM and CatBoost.

How it works — growing a tree (CART)

scikit-learn implements **CART** (Classification And Regression Trees), which always makes **binary** splits.

1. Start with all training rows at the root.
2. For every feature and every candidate threshold (midpoints between sorted unique values), split the rows into left (≤ threshold) and right (> threshold).
3. Score each split by how much it reduces **impurity** (how mixed the labels are). Pick the best one.
4. Recurse on each child.
5. Stop when a stopping rule fires: node is pure, `max_depth` reached, too few samples (`min_samples_split`, `min_samples_leaf`), or no split improves impurity enough.
6. Each leaf predicts the majority class (classification; it also stores class proportions, which become `predict_proba`) or the mean target value (regression).

This is **greedy**: the best split now, never revisited. Finding the globally optimal tree is NP-hard, so greedy is the practical choice.

Impurity measures

For a node where class k has proportion p_k:

Measure	Formula	Pure node	50/50 binary node
Gini impurity	$G = 1 - \Sigma\, p_k^2$	0	0.5
Entropy	$H = -\Sigma\, p_k \log_2 p_k$	0	1.0 bit
Misclassification error	$1 - \max_k p_k$	0	0.5 (rarely used for growing — not sensitive enough)

- **Gini** = the probability you mislabel a random sample if you label it randomly according to the node's class mix.
- **Entropy** = average number of bits (yes/no answers) needed to identify the class. From information theory.
- **Information gain** = entropy(parent) − weighted average entropy(children). The weights are the fraction of rows that go to each child. The "Gini version" is simply called Gini decrease.

Worked example: Gini vs entropy

Ten loan applicants, label 1 = defaulted. Candidate split: *income < 40k?*

Node	Labels	Gini	Entropy
Parent	4 defaults, 6 repaid	$1 - 0.4^2 - 0.6^2 = \mathbf{0.480}$	$-0.4 \cdot \log_2 0.4 - 0.6 \cdot \log_2 0.6 = \mathbf{0.971}$
Left (income < 40k)	3 defaults, 1 repaid	$1 - 0.75^2 - 0.25^2 = 0.375$	0.811
Right (income ≥ 40k)	1 default, 5 repaid	$1 - (1/6)^2 - (5/6)^2 = 0.278$	0.650

Weighted children: Gini = 0.4·0.375 + 0.6·0.278 = 0.317 → **Gini decrease 0.163**. Entropy = 0.4·0.811 + 0.6·0.650 = 0.715 → **information gain 0.256**.

The tree does not only test 40k — it tests every midpoint. `code/split_math.py`:

```python
def gini(labels):
    n = len(labels)
    return 1 - sum((c / n) ** 2 for c in Counter(labels).values())

def entropy(labels):
    n = len(labels)
    return -sum((c / n) * math.log2(c / n) for c in Counter(labels).values())

def weighted(children, fn):          # impurity of a split
    n = sum(len(c) for c in children)
    return sum(len(c) / n * fn(c) for c in children)
# ... loop over every midpoint threshold and print both scores
```

Output:

```
parent [1, 1, 1, 0, 0, 0, 0, 0, 1, 0]  -> gini=0.480  entropy=0.971
left   [1, 1, 1, 0]         -> gini=0.375  entropy=0.811
right  [0, 0, 0, 0, 1, 0]     -> gini=0.278  entropy=0.650
weighted child gini    = 0.317  -> gini decrease   = 0.163
weighted child entropy = 0.715  -> information gain = 0.256

threshold  gini_decrease  info_gain
     27.5         0.080      0.144
     32.5         0.180      0.322
     36.5         0.309      0.557
     41.5         0.163      0.256
     ...
     85.0         0.036      0.079
```

The best threshold is **36.5**, by both measures: the left side (25, 30, 35) is pure. This is typical — Gini and entropy almost always rank splits the same way. Gini is the scikit-learn default because it avoids a logarithm and is slightly faster. Do not spend tuning time on this choice.

Reading a fitted tree

`code/decision_tree_demo.py` fits a depth-2 tree on the Iris flowers and prints its rules with `export_text`:

```python
tree = DecisionTreeClassifier(max_depth=2, random_state=42).fit(iris.data, iris.target)
print(export_text(tree, feature_names=list(iris.feature_names)))
```


```
|--- petal length (cm) <= 2.45
|   |--- class: 0
|--- petal length (cm) >  2.45
|   |--- petal width (cm) <= 1.75
|   |   |--- class: 1
|   |--- petal width (cm) >  1.75
|   |   |--- class: 2
```

Two questions classify ~96% of the flowers correctly. That is the interpretability selling point.

Depth and overfitting

A tree with no limits keeps splitting until each leaf is pure — it can memorise the training set. Same script, breast-cancer dataset (30 features, 569 patients):

```
depth  train  test
    1  0.932  0.889
    2  0.942  0.906
    3  0.980  0.901
    4  0.990  0.906
    6  1.000  0.906
   10  1.000  0.906
   15  1.000  0.906
```



Training accuracy hits 100% at depth 6, but test accuracy is stuck around 0.90: the extra splits fit noise, not signal.

Pruning

Two ways to keep a tree small:

Kind	How	scikit-learn knobs
Pre-pruning (early stopping)	Stop growing early	`max_depth`, `min_samples_split`, `min_samples_leaf`, `max_leaf_nodes`, `min_impurity_decrease`
Post-pruning (cost-complexity pruning)	Grow a full tree, then cut back branches that don't pay for themselves	`ccp_alpha`


Cost-complexity pruning minimises $R_\alpha(T) = R(T) + \alpha \cdot |\text{leaves}(T)|$, where $R(T)$ is total training impurity (error) and α is a price per leaf. $\alpha = 0$ keeps the full tree; larger α removes the weakest branches first. `cost_complexity_pruning_path` lists the α values at which a branch disappears; you choose α by cross-validation.

```
full tree: 16 leaves, test acc 0.906
ccp_alpha=0.0    leaves= 16  test acc=0.906
ccp_alpha=0.005  leaves=  7  test acc=0.918
ccp_alpha=0.01   leaves=  5  test acc=0.918
ccp_alpha=0.02   leaves=  4  test acc=0.901
ccp_alpha=0.05   leaves=  2  test acc=0.889
```

A 5-leaf tree beats the 16-leaf tree: simpler *and* better. Pruning too hard (2 leaves) underfits.

Regression trees

Same algorithm, different impurity: a regression tree picks the split that most reduces the **squared error** (equivalently, the variance) of the target in the children, and each leaf predicts the **mean** of its training targets. (`criterion="absolute_error"` uses the median instead and is more robust to outliers.) The result is a **step function**:




```
|--- x <= 3.13
|   |--- x <= 0.44
|   |   |--- value: [0.24]
|   |--- x >  0.44
|   |   |--- value: [0.74]
|--- x >  3.13
|   |--- x <= 3.98
|   |   |--- value: [-0.39]
|   |--- x >  3.98
|   |   |--- value: [-0.95]
```

Depth 2 = 4 flat steps (underfit); depth 5 chases individual noisy points (overfit). A key consequence: **a tree cannot extrapolate** – outside the training range it predicts the value of the last leaf, forever flat.

Trade-offs

Strengths	Weaknesses
Readable rules, easy to explain	High variance: small data change → very different tree
No feature scaling; handles non-linearity and interactions	Overfits without depth limits or pruning
Fast prediction: O(depth)	Axis-aligned splits: a diagonal boundary needs a staircase of many splits
Works with numeric + categorical data (scikit-learn ≥ 1.3 trees also handle missing values natively)	Cannot extrapolate beyond the training range
	Greedy – may miss the best overall tree

When not to use it

- When accuracy matters more than a readable model – use a forest or boosting instead.
- For smooth or linear relationships (a linear model needs 2 parameters; a tree needs a staircase).
- For forecasting values outside the range seen in training (e.g. prices that keep rising).

Common mistakes

- Leaving `max_depth=None` and reporting training accuracy (it is ~100% and meaningless).

- Scaling features "for the tree" — harmless but pointless.
- Over-reading a single tree's structure: retrain on a slightly different sample and the top split may change.
- One-hot encoding a categorical with thousands of levels into a single tree — each split can only isolate one level; prefer target/ordinal encoding or a library with native categorical support.

Real-world examples

- Credit scoring and medical triage rules, where regulators or clinicians must read the logic.
- As the weak learner inside every gradient-boosting library.

In the interview

> **30-second answer:** "A decision tree recursively splits the data on the feature/threshold that most reduces impurity — Gini or entropy for classification, variance for regression. Leaves predict the majority class or the mean. Trees are interpretable and need no scaling, but they have high variance and overfit unless you limit depth or prune with cost-complexity pruning, which is why we usually use them inside ensembles."

- *Gini or entropy?* They agree on almost all splits; Gini is default because it's cheaper (no log). Not worth tuning.
- *Why is tree learning greedy?* Finding the optimal tree is NP-hard; greedy top-down splitting is fast and works well in practice.
- *How does a tree handle a feature that's 1000× larger in scale?* It doesn't care — splits depend only on the order of values.

Self-check

1. A node has 8 cats and 2 dogs. Gini? → $1 - 0.8^2 - 0.2^2 = \mathbf{0.32}$.
2. What does a regression-tree leaf predict? → The mean target of the training rows in that leaf.
3. What does increasing `ccp_alpha` do? → Prunes more branches (smaller tree, higher bias, lower variance).
4. Why can't a tree predict a house price higher than any it has seen? → Leaves are averages of training targets; no leaf can exceed the maximum.

TL;DR

Trees ask the best yes/no question at each step (max impurity decrease), are readable and scale-free, but overfit — control them with depth limits or cost-complexity pruning.

7.2 Bias–variance of trees

What it is

Recall: **bias** = error from wrong assumptions (model too simple); **variance** = error from sensitivity to the particular training sample (model too flexible). Test error ≈ bias² + variance + irreducible noise.

- A **shallow** tree (stump) = high bias, low variance.
- A **deep** tree = low bias, **very high variance** — retrain on a bootstrap sample and you get a noticeably different tree.

Why it matters

Deep trees have exactly the property that averaging can fix: they are accurate *on average* but noisy. If you average B models, each with variance σ^2 and pairwise correlation ρ, the variance of the average is:

$$\text{Var(average)} = \rho\sigma^2 + (1 - \rho)\sigma^2/B$$

As B grows, the second term vanishes — but the first term, $\rho\sigma^2$, stays. So **averaging helps only as much as the models disagree**. Two ideas follow:

- **Bagging** attacks variance by averaging many deep trees (lowers the second term).
- **Random Forests** additionally **de-correlate** the trees (lowers ρ, so the first term shrinks too).
- **Boosting** does the opposite: it starts from high-bias shallow trees and adds them sequentially to **reduce bias**.

Method	Base trees	Mainly reduces	Trees built
Bagging / Random Forest	Deep (low bias, high variance)	Variance	Independently, in parallel
Boosting	Shallow (high bias, low variance)	Bias (and some variance via shrinkage)	Sequentially

TL;DR

Deep trees = low bias, high variance → average them (bagging/RF). Shallow trees = high bias → chain them (boosting).

7.3 Bagging and Random Forests


What it is

Bagging (Bootstrap AGGregatING, Breiman 1996) trains many copies of the same model on different **bootstrap samples** and averages them (majority vote or averaged probabilities for classification, mean for regression).

A **bootstrap sample** is n rows drawn **with replacement** from the n training rows: some rows appear twice or more, others not at all.

A **Random Forest** (Breiman 2001) = bagged decision trees **plus** a twist: at every split, the tree may only choose from a **random subset of the features** (`max_features`).

Analogy: asking 500 doctors for a diagnosis. If they all trained at the same school and read the same chart (correlated), polling them adds little. If each saw a slightly different set of tests (bootstrap) and focuses on different symptoms (feature subsampling), their majority vote is far more reliable.



How it works

1. For b = 1..B (`n_estimators`, e.g. 100–500):
    1. Draw a bootstrap sample of n rows.
    2. Grow a deep tree on it (usually unpruned). At each node, pick `max_features` features at random and search for the best split **only among those**.
2. Predict: average the trees' predicted probabilities (scikit-learn does soft voting) or values.

Why feature subsampling helps: if one feature is very strong, each bagged tree chooses it for the first split, so the trees end up nearly identical (high ρ). Hiding it from some splits forces other trees to find other useful patterns, making trees less correlated.

Defaults (scikit-learn): `max_features="sqrt"` for classification ($\sqrt{p}$ features per split) and `1.0` (all features, i.e. plain bagging) for regression. The classic textbook suggestion for regression is p/3; try a few values.

Out-of-bag (OOB) evaluation

The chance a given row is **never** picked in n draws with replacement is $(1 - 1/n)^n \approx 1/e \approx$ **36.8%**. So each tree never sees about a third of the rows — its **out-of-bag** rows. Predict each row using only the trees that didn't train on it, and you get a free validation score without a hold-out set (`oob_score=True`).

Code — single tree vs bagging vs Random Forest

`code/forest_demo.py`:

```
models = {
    "single tree": DecisionTreeClassifier(random_state=0),
    "bagged trees (100)": BaggingClassifier(DecisionTreeClassifier(), n_estimators=100, random_state=0),
    "random forest (100)": RandomForestClassifier(n_estimators=100, random_state=0),
}
for name, m in models.items():
    s = cross_val_score(m, X, y, cv=5)

rf = RandomForestClassifier(n_estimators=300, oob_score=True, random_state=0, n_jobs=-1)
rf.fit(X_tr, y_tr)
print(rf.oob_score_, rf.score(X_te, y_te))
```

Output:

```
5-fold CV accuracy (mean +/- std)
  single tree          0.917 +/- 0.016
  bagged trees (100)   0.958 +/- 0.029
  random forest (100)  0.963 +/- 0.022

OOB accuracy  = 0.967  (free validation estimate, no hold-out used)
test accuracy = 0.953
expected out-of-bag fraction per tree = 0.367  (1/e = 0.368)
```

Averaging lifts accuracy by ~4 points; feature subsampling adds a little more. The OOB estimate is close to the true test score.

Feature importance and its pitfalls

Impurity-based importance (Mean Decrease in Impurity, **MDI**; `feature_importances_`): for each feature, sum the impurity decrease of every split that uses it, weighted by the fraction of samples reaching that node, averaged over trees, normalised to sum to 1.


Pitfalls:

1. **Biased toward high-cardinality features** — a continuous feature (or an ID column) offers many thresholds, so it can find chance splits. A pure-noise continuous column gets non-zero importance.
2. **Computed on training data** — it rewards features the model used to *overfit*, not features that help on new data.
3. **Correlated features share credit** — if radius, perimeter and area carry the same information, importance is split among them unpredictably, so each looks less important than the concept really is.

Permutation importance fixes the first two: on a **held-out set**, shuffle one column (breaking its link to the target) and measure how much the score drops. Repeat several times. A feature the model truly relies on causes a big drop; a noise feature causes ~0. It is model-agnostic (works for any model). Caveat: with correlated features, shuffling one leaves its twin intact, so **both** can look unimportant — group or drop correlated features first.

```
X = np.hstack([X, noise_cont, noise_bin])   # add a random continuous and a random binary column
rf = RandomForestClassifier(n_estimators=300, random_state=0, n_jobs=-1).fit(X_tr, y_tr)
perm = permutation_importance(rf, X_te, y_te, n_repeats=20, random_state=0, n_jobs=-1)
```

```
feature              impurity(MDI)  permutation(test)
  mean perimeter             0.278     0.063 +/- 0.017
  mean area                  0.258     0.023 +/- 0.017
  mean radius                0.212     0.012 +/- 0.008
  mean texture               0.112     0.039 +/- 0.010
  mean smoothness            0.100     0.041 +/- 0.014
  RANDOM continuous          0.034    -0.005 +/- 0.006
  RANDOM binary              0.006     0.003 +/- 0.006
```



Two lessons in one table: (1) MDI gives the random continuous column ~6× more importance than the random binary one — pure cardinality bias; permutation importance correctly puts both at ≈ 0. (2) Radius, perimeter and area are nearly the same measurement; MDI ranks them top-3, but permutation importance ranks texture and smoothness above radius and area because shuffling one of the three size features barely hurts while its twins remain.

Better still: SHAP values (Shapley-value-based per-prediction attributions; `shap` library, with a fast exact algorithm for trees) explain individual predictions and aggregate to global importance.

Trade-offs

Strengths	Weaknesses
Strong accuracy with almost no tuning	Larger, slower model than one tree; not readable
Hard to overfit by adding trees (more trees never hurts accuracy, only time)	Usually a bit less accurate than well-tuned boosting
Trees train in parallel (`n_jobs=-1`)	Cannot extrapolate (average of step functions)
OOB score for free, robust to outliers and noisy features	Memory heavy with deep trees on big data

When not to use it

- Very high-dimensional sparse data (text) — linear models are faster and often better.
- Latency- or memory-critical deployment with hundreds of deep trees.
- When you need the last percent of accuracy — try gradient boosting.

Common mistakes

- Treating `feature_importances_` as causal or as "true" importance.
- Tuning `n_estimators` as if more trees overfits — it doesn't; stop when the score plateaus.
- Forgetting `n_jobs=-1` and waiting on one core.
- Using OOB score with `bootstrap=False` (there are no OOB rows then; scikit-learn raises an error).

Real-world examples

- Microsoft's Kinect body-part recognition used randomized decision forests on depth-image features (Shotton et al., 2011).
- A standard, strong baseline in credit risk, fraud, churn and bioinformatics (gene-expression) pipelines.

In the interview

30-second answer: "A Random Forest trains many deep trees on bootstrap samples and, at each split, considers only a random subset of features. Averaging reduces variance; feature subsampling de-correlates the trees so averaging helps more. About 37% of rows are out-of-bag for each tree, which gives a free validation score. It works well out of the box and rarely overfits by adding trees."

- *Bagging vs Random Forest?* RF = bagging + random feature subset at each split, to reduce correlation between trees.
- *Why can MDI importance mislead?* It's computed on training data and favours high-cardinality features; use permutation importance on held-out data, or SHAP.
- *Does adding trees overfit?* No — the test error converges as trees are added; depth and leaf size control overfitting.

Self-check

1. What fraction of rows does a bootstrap sample leave out, on average? → ≈ 36.8% (1/e).
2. Default `max_features` for `RandomForestClassifier`? → `"sqrt"`.
3. Which term of $\rho\sigma^2 + (1-\rho)\sigma^2/B$ does feature subsampling target? → $\rho\sigma^2$ (it lowers ρ).
4. Two features are near-duplicates. What happens to their permutation importances? → Both can look small, because the model can still use the unshuffled twin.

TL;DR


Random Forest = many de-correlated deep trees, averaged. Great default, free OOB score. Use permutation importance or SHAP, not raw MDI, to explain it.

7.4 Boosting

What it is

Boosting builds an ensemble **sequentially**: each new weak model focuses on what the ensemble so far gets wrong. A **weak learner** is a model only slightly better than guessing — typically a shallow tree (a depth-1 tree is a **stump**).

Analogy: a student doing practice exams. After each exam they study only the questions they got wrong. Many small corrections add up to mastery.



AdaBoost (intuition)

AdaBoost (Adaptive Boosting, Freund & Schapire 1997) re-weights *samples*:

1. Give every training sample weight 1/n.
2. Fit a stump using those weights. Compute its weighted error ε.
3. Give the stump a vote $\alpha = \tfrac{1}{2}\cdot\ln((1-\varepsilon)/\varepsilon)$ — accurate stumps get bigger votes; $\varepsilon = 0.5$ (coin flip) gets $\alpha = 0$.
4. Multiply the weight of each **misclassified** sample by e^{α} and each correct one by $e^{-\alpha}$; renormalise so weights sum to 1.
5. Repeat. Final prediction = sign of $\Sigma\ \alpha_m \cdot h_m(x)$ (a weighted vote).

Worked numbers: $\varepsilon = 0.2 \to \alpha = \tfrac{1}{2}\cdot\ln 4 \approx 0.693$, so wrong samples ×2 and right samples ×0.5. Total weight on the wrong ones becomes $0.2\cdot 2 = 0.4$, on the right ones $0.8\cdot 0.5 = 0.4$ → after renormalising, the next stump sees the previously misclassified 20% as **half** of the problem.

(scikit-learn's `AdaBoostClassifier` uses the multi-class **SAMME** variant: its vote is $\alpha = \ln((1-\varepsilon)/\varepsilon) + \ln(K-1)$ for K classes (so exactly twice the α above when K = 2), scaled by a `learning_rate`; the idea is identical.) AdaBoost can be shown to be gradient boosting with an **exponential loss**, which also makes it sensitive to outliers and label noise: a mislabelled point keeps getting heavier.

Gradient boosting, step by step on residuals

Gradient boosting (Friedman 2001) re-fits *targets* rather than re-weighting samples. For squared error it is wonderfully simple:

1. $F_0(x) = \text{mean}(y)$ — the best constant.
2. For m = 1..M:

    1. Residuals $r_i = y_i - F_{m-1}(x_i)$.
    2. Fit a small regression tree h_m to predict r from x.
    3. Update $F_m(x) = F_{m-1}(x) + \eta \cdot h_m(x)$, where η is the **learning rate** (shrinkage), e.g. 0.1.
3. Predict with F_M.

Why "gradient"? For loss $L = \frac{1}{2}(y - F)^2$, the negative gradient with respect to the prediction F is exactly $y - F$, the residual. For other losses you fit the tree to the **negative gradient** ("pseudo-residuals") instead – e.g. for log-loss in classification, it is $y - p$ (label minus predicted probability). So gradient boosting is gradient descent in *function space*: each tree is one step downhill.

Worked example (4 houses, size in 100 m² → price in k$, $\eta = 0.5$, stumps), from `code/boosting_demo.py`:

```
round 0: predict mean = 295.0 for every house
round 1: residuals [-95. -35.   5. 125.] -> new preds [274.2 274.2 274.2 357.5]  MSE=2568.8
round 2: residuals [-74.2 -14.2  25.8  62.5] -> new preds [252.1 252.1 296.2 379.6]  MSE=1105.7
round 3: residuals [-52.1   7.9   3.8  40.4] -> new preds [226.  260.8 304.9 388.3]  MSE=427.6
```

Round 1: the stump splits size ≤ 2.5; the left group's mean residual is $(-95 - 35 + 5)/3 = -41.7$, the right's is 125. Half of each ($\eta = 0.5$) is added: $295 - 20.8 = 274.2$, $295 + 62.5 = 357.5$. Each round the residuals shrink and the MSE falls.

The whole algorithm in ~15 lines:

```python
class TinyGradientBoosting:
    def fit(self, X, y):
        self.f0 = y.mean()                      # step 0: constant prediction
        pred = np.full(len(y), self.f0)
        self.trees = []
        for _ in range(self.n):
            residual = y - pred                 # = negative gradient of 1/2 (y - pred)^2
            t = DecisionTreeRegressor(max_depth=self.depth, random_state=0).fit(X, residual)
            pred += self.lr * t.predict(X)      # take a small step toward the residuals
            self.trees.append(t)
        return self


    def predict(self, X):
        return self.f0 + self.lr * sum(t.predict(X) for t in self.trees)
```

```
from-scratch GB test RMSE = 50.86
sklearn GB      test RMSE = 51.01
```

Our toy matches scikit-learn's `GradientBoostingRegressor` with the same settings.

Learning rate and number of trees

The learning rate η and the number of trees M trade off: smaller η means each tree corrects less, so you need more trees, but the final model usually generalises better (shrinkage is a form of regularisation).



- η = 1.0: fast drop, then overfits and stalls at a poor RMSE (98).
- η = 0.3: good quickly, plateaus at 55.
- η = 0.1: best result here (49.9) by 400 trees.
- η = 0.03: still improving at 400 trees — would need more.

Practical recipe: fix η around 0.05–0.1, set a large M, and use **early stopping** on a validation set (stop when the validation score hasn't improved for, say, 50 rounds). scikit-learn: `n_iter_no_change` + `validation_fraction` (`GradientBoostingClassifier`) or `early_stopping=True` (`HistGradientBoosting*`; it's on automatically above 10,000 samples); XGBoost/LightGBM: `early_stopping_rounds` / an early-stopping callback. Other regularisers: shallow trees (depth 3–8 or `num_leaves` ≤ 31–255), **row subsampling** (`subsample` < 1 = *stochastic* gradient boosting), column subsampling, min samples per leaf, L1/L2 penalties on leaf values.

Comparison on a real dataset

```
models = {
    "AdaBoost (stumps)": AdaBoostClassifier(n_estimators=200, random_state=0),
    "RandomForest": RandomForestClassifier(n_estimators=200, random_state=0, n_jobs=-1),
    "HistGradientBoosting": HistGradientBoostingClassifier(random_state=0),
}
```

```
5-fold CV accuracy
  AdaBoost (stumps)      0.977 +/- 0.009
  RandomForest           0.960 +/- 0.019
  HistGradientBoosting   0.965 +/- 0.018
```

On a small, clean dataset all three are within ~2 points and the ranking can change with the seed — the difference between ensemble families shows more clearly on larger, messier data.

XGBoost vs LightGBM vs CatBoost (and scikit-learn)

All four are gradient-boosted decision trees (**GBDT**). They differ in engineering and defaults:

	XGBoost (2014)	LightGBM (Microsoft, 2017)	CatBoost (Yandex, 2017)	scikit-learn `HistGradientBoosting`
Split finding	Histogram (`tree_method="hist"`, default since 2.0); exact also available	Histogram	Histogram	Histogram (≤ 255 bins), inspired by LightGBM
Tree growth	Level-wise (depth-wise) by default; `grow_policy="lossguide"` for leaf-wise	**Leaf-wise** (split the leaf with the biggest gain) – often faster and more accurate, can overfit small data	**Symmetric (oblivious)** trees: same split for a whole level → very fast prediction, strong regularisation	Leaf-wise (`max_leaf_nodes=31`)
Regularisation	Built into objective: γ per leaf, L1/L2 on leaf weights; uses 1st + 2nd derivatives (Newton step)	L1/L2, min gain, min data in leaf; GOSS (keep large-gradient rows, sample small ones) and EFB (bundle exclusive sparse features) for speed	**Ordered boosting** to reduce target leakage	L2, min samples per leaf
Categorical features	Native support (`enable_categorical=True`)	Native support	**Best-in-class**: ordered target statistics, feature combinations	Native (`categorical_features="from_dtype"` default)
Missing values	Native (learns default direction)	Native	Native	Native
GPU	Yes	Yes	Yes	No
Best when	Solid all-rounder, huge ecosystem	Large datasets, speed	Many categorical features, good defaults with little tuning	Mid-size data, no extra dependency

XGBoost's regularised objective, for the curious: minimise Σ loss$(y_i, \hat{y}_i) + \Sigma_\text{trees}\ (\gamma \cdot T + \tfrac{1}{2}\lambda \cdot \|w\|^2)$, where T = number of leaves and w = leaf values. With gradients G and second derivatives H summed over a leaf, the optimal leaf value is $w^* = -G/(H + \lambda)$.

The APIs are all scikit-learn-compatible (not run here – packages not installed in the book environment):

```python
# pip install xgboost lightgbm catboost   (not run)
from xgboost import XGBClassifier
from lightgbm import LGBMClassifier
from catboost import CatBoostClassifier

xgb = XGBClassifier(n_estimators=2000, learning_rate=0.05, max_depth=6,
                    subsample=0.8, colsample_bytree=0.8, early_stopping_rounds=100)
xgb.fit(X_tr, y_tr, eval_set=[(X_val, y_val)])

lgbm = LGBMClassifier(n_estimators=2000, learning_rate=0.05, num_leaves=31)
cat = CatBoostClassifier(iterations=2000, learning_rate=0.05, cat_features=["city", "device"])
```

Trade-offs: bagging vs boosting

	Random Forest	Gradient boosting
Accuracy on tabular data	Very good	Usually best
Tuning needed	Little	Moderate (η, trees, depth/leaves, subsampling)
Overfits by adding trees?	No	**Yes** – use early stopping
Training	Parallel across trees	Sequential across trees (parallel within a tree)
Sensitivity to noise/outliers	Low	Higher (esp. AdaBoost)

When not to use it

- Unstructured data (images, audio, raw text) – deep learning wins.
- Tiny datasets with strong domain priors – a regularised linear model may be as good and more explainable.
- When you need predictions outside the training range (trees cannot extrapolate – combine with a linear model or model the trend separately).

Common mistakes

- Tuning `n_estimators` without early stopping → overfitting.
- Learning rate 1.0 "because it's faster".
- Leaking the validation set: using the same set for early stopping *and* final reporting (keep a separate test set).
- Using AdaBoost on noisy labels.
- Deep trees in boosting (depth 15) – boosting wants weak learners.

Real-world examples

- GBDT dominates Kaggle tabular competitions; XGBoost's 2016 paper noted it was used in 17 of 29 winning Kaggle solutions published in 2015.
- Web search ranking: LambdaMART (gradient-boosted trees for learning-to-rank, from Microsoft Research) was used in Bing's ranker, and an ensemble of LambdaMART models won the 2010 Yahoo! Learning to Rank Challenge.
- Fraud detection, credit scoring, click-through-rate and demand forecasting across the industry; Yandex uses CatBoost in search and recommendation.

In the interview

30-second answer: "Boosting builds trees sequentially, each one correcting the current ensemble. In gradient boosting, you start from a constant, and each new shallow tree is fitted to the negative gradient of the loss – for squared error that's just the residuals – and added with a small learning rate. It mainly reduces bias. It's usually the most accurate model on tabular data but it can overfit as you add trees, so you use a small learning rate with early stopping."

- *AdaBoost vs gradient boosting?* AdaBoost re-weights misclassified samples (exponential loss); gradient boosting fits trees to the negative gradient of any differentiable loss. AdaBoost is a special case.
- *Why a small learning rate?* Shrinkage: smaller steps mean each tree fixes only part of the error, which regularises and usually generalises better, at the cost of more trees.

- *LightGBM vs XGBoost?* LightGBM grows trees leaf-wise and uses GOSS/EFB for speed; XGBoost is depth-wise by default with a regularised second-order objective. Both are histogram-based today; results are often similar after tuning.

Self-check

1. In gradient boosting with squared error, what does tree m fit? → The residuals $y - F_{m-1}(x)$.
2. What's the negative gradient for log-loss? → $y - p$.
3. AdaBoost stump with $\varepsilon = 0.5$ gets what vote? → $\alpha = 0$.
4. Learning rate 0.1 → 0.01: what else must change? → Roughly 10× more trees (use early stopping).
5. Which library uses symmetric (oblivious) trees? → CatBoost.

TL;DR


Boosting = shallow trees in sequence, each fixing the last one's errors (residuals/gradients), scaled by a learning rate. Most accurate on tabular data; always use early stopping.

7.5 Voting and stacking

What it is

Ensembles of **different** model families:

- **Hard voting**: each model votes a class; majority wins.
- **Soft voting**: average the predicted probabilities; pick the highest. Usually better when models are well calibrated.
- **Stacking** (stacked generalisation, Wolpert 1992): train a **meta-model** (often logistic/linear regression) on the base models' predictions. To avoid leakage, the meta-model is trained on **out-of-fold** predictions — each base prediction comes from a model that did not see that row (scikit-learn does this with the `cv` argument).



Why it matters

Different families make **different errors** (low correlation → averaging helps, same math as §7.2). Stacking learns *how much to trust* each model.

Code

`code/voting_stacking.py`:

```
base = [
    ("lr", make_pipeline(StandardScaler(), LogisticRegression(max_iter=1000))),
    ("knn", make_pipeline(StandardScaler(), KNeighborsClassifier(n_neighbors=7))),
    ("rf", RandomForestClassifier(n_estimators=200, random_state=0, n_jobs=-1)),
    ("hgb", HistGradientBoostingClassifier(random_state=0)),
]
models["soft voting"] = VotingClassifier(base, voting="soft")
models["stacking (meta = LR)"] = StackingClassifier(
    base, final_estimator=LogisticRegression(max_iter=1000), cv=5)
```

```
10-fold CV accuracy
  lr                    0.981 +/- 0.015
  knn                   0.967 +/- 0.020
  rf                    0.965 +/- 0.028
  hgb                   0.968 +/- 0.022
  hard voting           0.977 +/- 0.021
  soft voting           0.975 +/- 0.016
  stacking (meta = LR)  0.979 +/- 0.019
```

An honest result: the ensembles beat three of the four base models but **not** the best single one (scaled logistic regression, since this dataset is nearly linearly separable). Ensembles reduce risk – you don't need to know in advance which model is best – but they are not guaranteed to win.

Trade-offs / when not to use it

- More models = more training time, latency, and maintenance. Netflix famously did not deploy the full Prize-winning blend of 100+ models because the extra accuracy did not justify the engineering cost.
- Gains are small when base models are highly correlated (e.g. five boosting libraries on the same features).

Common mistakes

- Training the meta-model on in-sample base predictions (leakage – the meta-model learns to trust overfit models).
- Soft voting with poorly calibrated models (e.g. SVM scores) without calibration.

In the interview

> **30-second answer:** "Voting averages diverse models' predictions – hard voting by majority, soft voting by averaged probability. Stacking trains a meta-model on out-of-fold predictions of the base models so it learns how to weight them. It helps when base models make different errors."

- *Why out-of-fold?* In-sample predictions of an overfit model look perfect, so the meta-model would over-trust it.

Self-check

1. Soft vs hard voting? → Averaged probabilities vs majority of labels.
2. What prevents leakage in stacking? → Out-of-fold (cross-validated) base predictions.

TL;DR

Combine diverse models; use soft voting for simplicity, stacking with out-of-fold predictions for the last bit of accuracy.

7.6 When trees beat neural networks

On **tabular data**, tree ensembles (especially GBDT) are still the default winner over deep learning for typical dataset sizes. Grinsztajn, Oyallon and Varoquaux (NeurIPS 2022, *"Why do tree-based models still outperform deep learning on typical tabular data?"*) benchmarked 45 medium-sized datasets (~10K samples) and identified reasons:

Property of tabular data	Why trees handle it well	Why neural nets struggle
Target functions are **irregular** (sharp jumps, thresholds)	Splits create sharp steps naturally	Networks are biased toward smooth functions
Many **uninformative features**	Splits simply ignore useless features	MLPs are hurt by them
Features have individual meaning (not rotation-invariant)	Axis-aligned splits respect each column	MLPs are rotation-invariant – they mix columns, which wastes that structure
Mixed types, skewed distributions, missing values	No scaling, native categoricals/missing	Need careful normalisation and encoding

Practical factors add up too: GBDTs train in minutes on a CPU, need far less tuning, and are easier to explain (SHAP). Neural nets win when the data is **unstructured** (images, text, audio), when there is a huge amount of data, or when you need end-to-end learning with embeddings (e.g. recommender systems with millions of IDs, or combining tabular + text + images). Newer tabular foundation models (e.g. TabPFN for small datasets) are narrowing the gap, but a tuned GBDT remains the baseline to beat.

Rule of thumb: tabular problem → start with a GBDT (LightGBM/XGBoost/CatBoost/`HistGradientBoosting`) and a Random Forest baseline.

7.7 Hyperparameter cheat sheet

Goal	Decision tree (sklearn)	Random Forest (sklearn)	GBDT (sklearn `HistGradientBoosting`)	XGBoost	LightGBM
Number of trees	–	`n_estimators` (100–500; more never hurts accuracy)	`max_iter` (use early stopping)	`n_estimators`	`n_estimators` / `num_iterations`
Step size	–	–	`learning_rate` (0.1)	`learning_rate` / `eta` (0.3)	`learning_rate` (0.1)
Tree size	`max_depth`, `max_leaf_nodes`	`max_depth` (None)	`max_leaf_nodes` (31), `max_depth`	`max_depth` (6)	`num_leaves` (31), `max_depth` (–1 = no limit)
Min data per leaf	`min_samples_leaf`	`min_samples_leaf`	`min_samples_leaf` (20)	`min_child_weight` (1)	`min_child_samples` (20)
Row sampling	–	`bootstrap`, `max_samples`	–	`subsample` (1.0)	`bagging_fraction` / `subsample` (1.0)
Feature sampling	`max_features`	`max_features` ("sqrt")	`max_features`	`colsample_bytree`	`feature_fraction` / `colsample_bytree`
Penalties	`ccp_alpha`, `min_impurity_decrease`	`ccp_alpha`	`l2_regularization`	`reg_alpha`, `reg_lambda`, `gamma`	`reg_alpha`, `reg_lambda`, `min_split_gain`
Class imbalance	`class_weight`	`class_weight`	`class_weight`	`scale_pos_weight`	`is_unbalance` / `scale_pos_weight`

(Defaults in parentheses, as of scikit-learn 1.9, XGBoost 2.x and LightGBM 4.x.)

Tuning order for GBDT: (1) set learning rate 0.05–0.1 and early stopping; (2) tune tree size (depth/leaves) and min samples per leaf; (3) tune subsampling; (4) add L1/L2 if still overfitting; (5) finally lower the learning rate and let early stopping add trees.

Chapter TL;DR

- **Decision tree**: greedy yes/no splits that maximise impurity decrease (Gini ≈ entropy); leaves predict majority/mean. Readable, scale-free, but high variance — limit depth or prune with `ccp_alpha`. Cannot extrapolate.
- **Bagging/Random Forest**: average many deep trees on bootstrap samples; RF also samples features per split to de-correlate trees. ~37% OOB rows give a free validation score. Robust default.
- **Feature importance**: MDI is biased (training data, high cardinality, correlated features) — prefer permutation importance on held-out data or SHAP.
- **Boosting**: add shallow trees sequentially, each fitting the residuals/negative gradient, scaled by a learning rate. Best tabular accuracy; use early stopping. AdaBoost = re-weighting, exponential loss.
- **XGBoost/LightGBM/CatBoost**: all histogram GBDTs; differ in tree growth (depth-wise / leaf-wise / symmetric) and categorical handling (CatBoost best).
- **Voting/stacking**: combine diverse models; stacking needs out-of-fold predictions.
- **Tabular data → start with gradient-boosted trees.**