Chapter 6 — Dictionaries, Sets and the `collections` Toolbox

Lists and tuples find things by **position**; dictionaries and sets find things by **value**, in constant time on average whether they hold ten items or ten million. That makes them the workhorses of real code: caches (stored results reused to save time — see System Design Fundamentals), indexes, counters, configuration, JSON, de-duplication, graph algorithms (route finding over networks of connected points). This chapter covers how they work (hashing — turning a value into an integer that says where to store it), every method, and which specialised container from `collections`, `heapq` and `bisect` to use when a plain dict, set or list isn't quite right.

> **Key term — Big-O notation:** how work grows with *n* items. **O(1)** (constant): independent of size; **O(n)** (linear): proportional; **O(log n)**: grows very slowly (doubling *n* adds one step). The trend, not timings.

What you'll learn

1. Dictionaries: define, access, update, remove, copy, loop, operators (`in` , `|`), insertion order.
2. Hashing: "hashable", how a dict/set finds a key, the big-O table.
3. Nested dictionaries and JSON.
4. Every dict method; `get` , `setdefault` , `update` , `|` compared; view objects.
5. Dict and set comprehensions.
6. Sets: define, add/update, remove/discard, copy, loop.
7. Set operations and every set method.
8. `frozenset` .
9. `collections` : `Counter` , `defaultdict` , `OrderedDict` , `deque` , `ChainMap` , `namedtuple` .
10. `heapq` (priority queues — the most urgent item always comes out first), `bisect` (binary search — finding a position by repeatedly halving a sorted list), and a when-to-use table.

Runnable code is in `code/` . Outputs are real (Python 3.14; runs on 3.12+). Printed sets of **strings** can change order between runs — string hashes are randomised per process (one running instance of a program; 6.2).

6.1 Dictionaries — key → value

What it is

A **dictionary** (`dict`) stores **key–value pairs**, looked up by key (`ages["Alice"]`), not position. Keys are unique; values can be anything.

- Literal: `{"Alice": 22, "Bob": 25}` .
- **Mutable:** add, change, delete pairs any time.
- **Keys must be hashable** (roughly immutable: strings, numbers, tuples of hashables, `None` , `frozenset`) — not lists, dicts, sets (6.2).
- **Insertion-ordered:** iteration follows first-insertion order — a language guarantee since **Python 3.7** (in CPython 3.6 it was an implementation detail, not promised). Tutorials calling dicts "unordered" are out of date — but dicts aren't *indexable* by position (`d[0]` looks up the key `0`).

Why it matters

Anywhere you'd search a list for "the item whose name is X", a dict does it in one step. Python itself runs on dicts: module globals, object attributes (`obj.__dict__`), keyword arguments and class namespaces.

How it works — define and access

```
ages = {"Alice": 22, "Bob": 25, "Eve": 19}
print(ages, len(ages))
print(ages["Alice"], ages.get("Bob"), ages.get("Charlie"), ages.get("Charlie", "Not Found"))
try:
    ages["Charlie"]
except KeyError as e:
    print("KeyError:", e)
other_ways = dict(a=1, b=2), dict([("x", 1), ("y", 2)]), dict(zip("pq", [7, 8]))
print(*other_ways)
print({(59.9, 10.7): "Oslo", 42: "int key", None: "None key"})
try:
    {["a", "list"]: 1}
except TypeError as e:
    print("TypeError:", e)
```

Output:

```
{'Alice': 22, 'Bob': 25, 'Eve': 19} 3
22 25 None Not Found
KeyError: 'Charlie'
{'a': 1, 'b': 2} {'x': 1, 'y': 2} {'p': 7, 'q': 8}
{(59.9, 10.7): 'Oslo', 42: 'int key', None: 'None key'}
TypeError: cannot use 'list' as a dict key (unhashable type: 'list')
```

- `d[key]` raises `KeyError` if missing — use when absence is a bug.
- `d.get(key)` returns `None` (or your default) — use when absence is normal.
- Four ways to build: literal, `dict(k=v)` (string keys only), `dict(list_of_pairs)`, `dict(zip(keys, values))`.

How it works — update, remove, copy, loop

```
ages = {"Alice": 22, "Bob": 25, "Eve": 19}
ages["Alice"] = 23                          # overwrite
ages["Dave"] = 20                           # insert (goes to the end)
print(ages)
removed = ages.pop("Eve");  print("pop:", removed, ages)
del ages["Bob"];            print("del:", ages)
print(ages.pop("Zed", "no such key"))       # default avoids KeyError
```

Output:

```
{'Alice': 23, 'Bob': 25, 'Eve': 19, 'Dave': 20}
pop: 19 {'Alice': 23, 'Bob': 25, 'Dave': 20}
del: {'Alice': 23, 'Dave': 20}
no such key
```

`d[k] = v` **updates** (existing key keeps its position) or **inserts** (new key goes to the end). `pop` returns the value; `del` just deletes.

```
original = {"Alice": 23, "Charlie": 21, "tags": ["x"]}
copied = original.copy()                    # shallow
copied["Alice"] = 24
copied["tags"].append("y")                  # shared inner list!
print(original, copied, sep="\n")
for key in original:                        # iterates keys
    print(key, end=" ")
for key, value in {"Alice": 23, "Charlie": 21}.items():
    print(f"{key} is {value} years old")
```

Output:

```
{'Alice': 23, 'Charlie': 21, 'tags': ['x', 'y']}
{'Alice': 24, 'Charlie': 21, 'tags': ['x', 'y']}
Alice Charlie tags
Alice is 23 years old
Charlie is 21 years old
```

`copy()` (or `dict(d)`) is **shallow**: both share `tags`. Use `copy.deepcopy` for nested data (Chapter 5, 5.8). Looping yields **keys**; `.values()` values; `.items()` `(key, value)` pairs.

Dictionary operators

Operator	Meaning	Example
`k in d` / `k not in d`	Is `k` a **key**? (O(1))	`"Alice" in ages`
`d[k]`, `d[k] = v`, `del d[k]`	Get / set / delete	
`d1 | d2`	New merged dict; right wins on conflicts (3.9+)	`{"a":1} | {"a":2}` → `{'a': 2}`
`d1 |= d2`	Merge into `d1` in place (like `update`)	
`{**d1, **d2}`	Merge via unpacking (3.5+)	
`==`	Same pairs (order ignored)	

```
d = {"Alice": 23, "Charlie": 21}
print("Alice" in d, "Bob" not in d, 23 in d, 23 in d.values())
a, b = {"x": 1, "y": 2}, {"y": 20, "z": 3}
print("a | b :", a | b)
a |= {"w": 0};  print("a |= :", a)
print("{**a, **b}:", {**a, **b})
print({"a": 1, "b": 2} == {"b": 2, "a": 1})
views = d.keys()
d["New"] = 0
print(views)                                # views are live
```

Output:

```
True True False True
a | b : {'x': 1, 'y': 20, 'z': 3}
a |= : {'x': 1, 'y': 2, 'w': 0}
{**a, **b}: {'x': 1, 'y': 20, 'w': 0, 'z': 3}
True
dict_keys(['Alice', 'Charlie', 'New'])
```

`23 in d` is `False`: `in` checks **keys**; `in d.values()` is an O(n) scan.

Common mistakes

- **Changing size while looping** → `RuntimeError: dictionary changed size during iteration`. Loop over a snapshot `list(d)` or build a new dict.
- `d[k]` for optional keys → `KeyError`.
- Expecting `d.copy()` to copy nested containers.
- `d.keys()[0]` — views (6.4) aren't indexable; use `next(iter(d))`.

Real-world examples

- JSON objects are dicts (`json.loads`) — every parsed API response.
- `functools.lru_cache` and hand-written memo tables are dicts from arguments to results.
- Django/Flask pass template context and request data as (dict-like) mappings.

In the interview

> **30-second answer:** "A dict maps hashable keys to values with average O(1) get, set, delete and membership, using a hash table. Since 3.7 it preserves insertion order. `d[k]` raises KeyError, `get` returns a default, `|` merges (3.9+), and `copy()` is shallow."

- *Ordered?* → Yes, insertion order since 3.7; equality ignores order.
- *`d[k] = v` on an existing key?* → Value replaced, position unchanged.
- *`in` checks?* → Keys.

Self-check

1. `{"a": 1} | {"a": 2, "b": 3}`? → `{'a': 2, 'b': 3}`.

TL;DR

Key → value, O(1) average, insertion-ordered (3.7+), hashable keys, `[]` raises, `get` defaults, `|` merges, `copy` is shallow.

6.2 Hashing — how dicts and sets find things in O(1)

What it is


A **hash** is an integer computed by `hash(x)`. A **hash table** is an array of slots; the hash picks a key's slot. Dicts and sets are hash tables. An object is **hashable** if its hash never changes during its lifetime and it supports `==`.

The data-model contract: **if** `a == b` **then** `hash(a) == hash(b)`. Not the reverse — different values may share a hash (a **collision**).

Hashing explains why lookups are O(1), why keys must be immutable, why `1` and `1.0` are one key, and why sets have no order.

How it works — a lookup, step by step

1. `h = hash(key)`.
2. Low bits of `h` choose a slot (table size is a power of two).
3. Empty slot → absent (lookup) or insert here.
4. Occupied → same hash **and** (`is` or `==`) → found.
5. Otherwise a collision: CPython uses **open addressing** — it computes the next slot with a pseudo-random probe sequence (scrambled but repeatable, mixing in more hash bits) and repeats from 3.
6. The table stays at most about **2/3 full**; beyond that CPython allocates a bigger table and re-inserts everything (**resize**) — rare enough that insertion is **amortised O(1)**.



Since 3.6 CPython's dict is a **compact dict**: a sparse *index* table of slots pointing into a dense *entries* array of `(hash, key, value)` in insertion order. That's where ordering comes from, and it made dicts 20–25% smaller. Sets use a simpler non-compact table — no order.

Growth via `sys.getsizeof` (8 slots hold 5 entries, 16 hold 10, 32 hold 21, 64 hold 42 — the 2/3 rule):

```
 len  bytes
   1  224
   6  352
  11  632
  22  1168
  43  2264
```

What is hashable?

```
42              hashable    hash=42
3.0             hashable    hash=3
'hi'            hashable    hash=<salted: differs every run>
(1, 2)          hashable    hash=-3550055125485641917
frozenset({1})  hashable    hash=-558064481276695278
None            hashable    hash=4238894112
True            hashable    hash=1
[1]             UNHASHABLE  (unhashable type: 'list')
{1: 2}          UNHASHABLE  (unhashable type: 'dict')
{1}             UNHASHABLE  (unhashable type: 'set')
(1, [2])        UNHASHABLE  (unhashable type: 'list')
```

Hashable	Not hashable
`int`, `float`, `complex`, `bool`, `str`, `bytes`, `None`, `frozenset`, `range`	`list`, `dict`, `set`, `bytearray`
`tuple` / `namedtuple` **if every item is hashable**	A tuple containing a list
Instances of your classes (hashed by identity by default)	Classes defining `__eq__` (behind `==`) without `__hash__` (behind `hash()`; Python sets `__hash__ = None`)
Frozen dataclasses (`@dataclass(frozen=True)`)	Regular dataclasses with `eq=True` (the default)

Equal values are the same key. `1 == 1.0 == True` and they hash equal:

```
d = {1: "int one"}
d[1.0] = "float one"
d[True] = "bool true"
print(d)          # {1: 'bool true'}  — one key; the first key object is kept, value replaced
```

String hashes are randomised. To stop "hash-flooding" denial of service (attackers crafting many colliding keys), `str` and `bytes` hashes are salted with a random per-process seed (default since 3.3; controlled by the `PYTHONHASHSEED` environment variable). Hence set-of-strings order varies between runs. Small ints hash to themselves (`hash(12345) == 12345`; `hash(-1)` is `-2` because `-1` signals an error in C).

Mutating a key breaks the table. If a key's hash depends on mutable state that changes while it's in a dict, the entry sits in the *old* hash's slot:

```
lookup with same object: LOST
lookup with old value  : LOST
```

The same object is looked for in the wrong slot; a fresh object with the old value finds the slot but isn't `==`. That's why built-in mutable types refuse to be hashable.

Big-O table (average case; worst case is O(n) when many keys collide)

Operation	dict	set
Lookup `d[k]` / `k in d` / `x in s`	O(1)	O(1)
Insert / update `d[k] = v`, `s.add(x)`	O(1) amortised	O(1) amortised
Delete `del d[k]`, `pop`, `s.remove(x)`, `discard`	O(1)	O(1)
`len()`	O(1)	O(1)
Iterate / `copy()` / `keys()` → list	O(n)	O(n)
`get`, `setdefault`, `popitem`	O(1)	`pop()` O(1)
`d1 | d2`, `update(other)`	O(len(other)) + copy	—
Union `s | t`	—	O(len(s) + len(t))
Intersection `s & t`	—	O(min(len(s), len(t)))
Difference `s - t`	—	O(len(s))
Symmetric difference `s ^ t`	—	O(len(s) + len(t))
`s <= t` (subset)	—	O(len(s))
Search a **value** `v in d.values()`	O(n)	—

Measured (`code/08_lookup_benchmark.py`, looking for the last element):

```
        n    list (µs)   set (µs)  dict (µs)
    1,000         5.26      0.030      0.031
   10,000        52.49      0.030      0.031
  100,000       536.93      0.030      0.031
1,000,000      5533.07      0.030      0.032
```




Figure — log–log: the list rises with slope 1 (linear); set and dict stay flat at ~30 ns. At a million items the set is ~180,000× faster.

Trade-offs

- **Memory:** spare slots (up to 1/3 empty) plus stored hashes — much more than a list.

- **No positional access**; sets have no order.
- **Worst case** O(n) under many collisions — rare, but possible with a bad `__hash__` (e.g. `return 1`).

Common mistakes

- Defining `__eq__` and losing hashability — define `__hash__` from the same immutable fields (or `@dataclass(frozen=True)`).
- A `__hash__` using mutable fields.
- Float keys after arithmetic: `0.1 + 0.2` is a different key from `0.3`.

In the interview

> **30-second answer:** "Dicts and sets are hash tables using open addressing. `hash(key)` picks a slot; collisions probe other slots; equality confirms the match. The table stays ≤ 2/3 full and resizes, so operations are O(1) average, O(n) worst. Keys must be hashable — their hash can't change — and equal objects must have equal hashes, which is why `1`, `1.0` and `True` are the same key."

- *Why can't lists be keys?* → Mutable; a changed hash loses the entry.
- *Why does set order change between runs?* → Per-process string-hash salting.
- *How are hash-table dicts ordered?* → Compact dict: index into an insertion-ordered entries array.

Self-check

1. `len({1, 1.0, True})`? → 1.

TL;DR

hash → slot → compare; ≤ 2/3 full; O(1) average. Hashable = hash never changes; equal ⇒ same hash; string hashes salted per run.

6.3 Nested dictionaries

What it is

A **nested dictionary** has dicts (or lists of dicts) as values, modelling **hierarchical** data: family trees, config files, JSON responses.

How it works

Read and write by chaining keys (`family["children"]["Alice"]["age"]`), add a branch by assigning a new dict at any level, loop one level with `.items()`.

```
family = {
    "name": "John Doe",
    "children": {
        "Alice": {"age": 10, "gender": "Female"},
        "Bob": {"age": 8, "gender": "Male"},
    },
}
print("Parent:", family["name"])
print("Alice's age:", family["children"]["Alice"]["age"])
family["children"]["Alice"]["age"] = 11                  # update deep value
family["children"]["Cara"] = {"age": 3, "gender": "Female"}  # add a new branch
for child, info in family["children"].items():
    print(f"  {child}: {info['age']} ({info['gender']})")
```

Output:

```
Parent: John Doe
Alice's age: 10
  Alice: 11 (Female)
  Bob: 8 (Male)
  Cara: 3 (Female)
```

Safe access when a level may be missing:

```python
print(family.get("children", {}).get("Zed", {}).get("age", "unknown"))   # unknown

def deep_get(d, *keys, default=None):
    for k in keys:
        if not isinstance(d, dict) or k not in d:
            return default
        d = d[k]
    return d
print(deep_get(family, "children", "Bob", "age"), deep_get(family, "x", "y", default=-1))  # 8 -1
```

JSON round trip — nested dicts are what `json` reads and writes:

```python
text = json.dumps(family, indent=2)
back = json.loads(text)
print(back == family)                                          # True
print(json.loads('{"1": [1, 2]}'), json.dumps({1: (1, 2)}))       # {'1': [1, 2]} {"1": [1, 2]}
```

JSON keys are always strings and JSON has no tuples: int keys return as strings, tuples as lists.

Trade-offs

Nested dicts	Dataclasses / Pydantic models (validating data classes)
Zero setup, matches JSON exactly	Named, typed fields, validation, IDE autocomplete
Key typos fail only at run time	Typos caught by the type checker
Ad-hoc/dynamic data	Stable, well-known schemas (agreed data shapes)

When not to use it

For deep, well-defined data used across a codebase, convert to dataclasses/Pydantic at the boundary (where data enters or leaves) and pass typed objects inside.

Common mistakes

- `KeyError` halfway down a chain — `get(..., {})` chains, `deep_get`, or `try/except KeyError`.
- Shallow-copying a nested config then mutating an inner dict — changes the original.
- Hand-written `if key not in d: d[key] = {}` — use `setdefault` or `defaultdict` (6.9).

Real-world examples

GitHub/Stripe API responses and JSON, YAML, TOML config files (TOML via `tomllib`) load as nested dicts; pandas' `json_normalize` flattens them into tables.

TL;DR

Chain keys to read and write; guard missing levels with `get(..., {})`; nested dicts ≈ JSON.

6.4 Dictionary methods and view objects

The full method table

Method	What it does	Cost
`d.get(k, default=None)`	Value for `k`, or `default` — never raises	O(1)
`d.setdefault(k, default=None)`	Return `d[k]`; if missing, first insert `k: default`	O(1)
`d.update(other, **kw)`	Merge pairs from a dict / iterable of pairs / keywords, overwriting	O(len(other))
`d.pop(k[, default])`	Remove `k`, return its value; `KeyError` if absent and no default	O(1)
`d.popitem()`	Remove and return the **last inserted** `(k, v)` (LIFO — last in, first out); `KeyError` if empty	O(1)
`d.clear()`	Remove everything	O(n)
`d.copy()`	Shallow copy	O(n)
`dict.fromkeys(keys, value=None)`	**Class method**: every key mapped to the **same** `value`	O(n)
`d.keys()` / `d.values()` / `d.items()`	Live **view** objects	O(1) to create

Plus `len(d)`, `k in d`, `del d[k]`, `reversed(d)` (3.8+), `d | other`, `d |= other` (3.9+).

```
info = {"name": "John", "age": 28, "city": "New York"}
print(info.get("name"), info.get("phone"))
info.update({"age": 29, "phone": "123-456-7890"})       # overwrite + add
info.update(zip_code="10001")                            # keyword form
print(info)
info.clear()
print(info)

new = dict.fromkeys(["a", "b", "c"], 1)
print(new)
print(new.pop("b"), new, new.items())
shared = dict.fromkeys(["x", "y"], [])                   # ONE list shared by all keys!
shared["x"].append(1)
print("fromkeys trap:", shared)
d = {"first": 1, "second": 2, "third": 3}
print(d.popitem(), d)                                    # LIFO: last inserted
```

Output:

```
John None
{'name': 'John', 'age': 29, 'city': 'New York', 'phone': '123-456-7890', 'zip_code': '10001'}
{}
{'a': 1, 'b': 1, 'c': 1}
1 {'a': 1, 'c': 1} dict_items([('a', 1), ('c', 1)])
fromkeys trap: {'x': [1], 'y': [1]}
('third', 3) {'first': 1, 'second': 2}
```

The `fromkeys` trap is the dict cousin of `[[0]*3]*3`: every key points at **one** list. Use `{k: [] for k in keys}`.

`get` vs `setdefault` vs `update` vs `|` — which one?

Want to…	Use	Changes `d`?
Read with a fallback	`d.get(k, default)`	No
Read, inserting a default if missing (grouping)	`d.setdefault(k, [])`	Only if missing
Merge another mapping into `d`	`d.update(other)` or `d |= other`	Yes
Get a **new** merged dict	`d | other` or `{**d, **other}`	No
Count / group many items	`Counter` / `defaultdict` (6.9)	—

```
words = ["apple", "avocado", "banana", "blueberry", "cherry"]
by_letter = {}
for w in words:
    by_letter.setdefault(w[0], []).append(w)            # insert [] only if missing
print(by_letter)
counts = {}
for ch in "hello":
    counts[ch] = counts.get(ch, 0) + 1                  # get with default for counting
print(counts)
```

Output:

```
{'a': ['apple', 'avocado'], 'b': ['banana', 'blueberry'], 'c': ['cherry']}
{'h': 1, 'e': 1, 'l': 2, 'o': 1}
```

`setdefault`'s default is **evaluated every call** even if the key exists — harmless for `[]`, costly for expensive defaults; `defaultdict` avoids it.

View objects

`keys()`, `values()`, `items()` return **views**: lightweight live windows onto the dict. Key views (and item views, if values are hashable) support set operations.

```
stock = {"apple": 3, "pear": 0}
k, v, it = stock.keys(), stock.values(), stock.items()
stock["fig"] = 7
print(k, v, it, sep="\n")
print(k & {"apple", "kiwi"}, sorted(k - {"pear"}))      # keys views support set ops
print(sorted(stock, key=stock.get, reverse=True))       # keys sorted by value
print(max(stock.items(), key=lambda kv: kv[1]))
```

Output:

```
dict_keys(['apple', 'pear', 'fig'])
dict_values([3, 0, 7])
dict_items([('apple', 3), ('pear', 0), ('fig', 7)])
{'apple'} ['apple', 'fig']
['fig', 'apple', 'pear']
('fig', 7)
```

Common mistakes

- `dict.fromkeys(keys, [])` shares one mutable value.
- `d.update(k=v)` with `k` a variable uses the literal name `"k"`; write `d[k] = v`.
- Assuming `popitem()` is random — since 3.7 it's always the last inserted.

In the interview

30-second answer: "`get` reads with a default, `setdefault` reads-or-inserts, `update` / `|=` merge in place, `|` returns a new merged dict with the right side winning. `pop` removes by key, `popitem`

removes the last inserted. `keys/values/items` are live views, and key views support set operations."

- *Keys common to two dicts?* → `d1.keys() & d2.keys()`.

TL;DR

`get` (read), `setdefault` (read-or-insert), `update` / `|=` (merge in place), `|` (merge new), `pop` / `popitem`; views are live and set-like; avoid `fromkeys` with mutable values.

6.5 Dict and set comprehensions

What it is

Chapter 5's comprehension syntax also builds dicts and sets:

```
{key_expr: value_expr for item in iterable if condition}   # dict
{expr for item in iterable if condition}                   # set
```

How it works

```
words = ["apple", "banana", "cherry"]
print({w: len(w) for w in words})
prices = {"apple": 1.2, "banana": 0.5, "cherry": 3.0}
print({k: v for k, v in prices.items() if v >= 1})
print({v: k for k, v in {"a": 1, "b": 2}.items()})    # invert
print(sorted({c for c in "mississippi"}))              # set comprehension
```

Output:

```
{'apple': 5, 'banana': 6, 'cherry': 6}
{'apple': 1.2, 'cherry': 3.0}
{1: 'a', 2: 'b'}
['i', 'm', 'p', 's']
```

- Filter a dict by iterating `.items()`.
- **Inverting** swaps keys and values; shared values → the later key wins (values must be hashable).
- `{}` is an **empty dict**; empty set is `set()`.

Common mistakes

- Duplicate keys silently overwrite earlier ones.
- A comprehension where `dict(zip(keys, values))` is simpler.

TL;DR

`{k: v for ...}` for dicts, `{x for ...}` for sets; `{}` alone is a dict.

6.6 Sets — unique, unordered collections

What it is

A **set** is an unordered, mutable collection of **unique, hashable** items: `{"apple", "banana"}` or `set(iterable)`. Duplicates are dropped; no indexing (`s[0]` → `TypeError`).

Why it matters

- **De-duplication** in one step: `set(emails)`.
- **Fast membership** (O(1) average): "seen this before?" in crawlers (programs following links between web pages), graph searches, validation.

- **Set algebra** answers "which users are in both groups?" with one operator (6.7).

How it works — define, add, update, remove, copy, loop

```
fruits = {"apple", "banana", "cherry", "apple"}
colors = set(["red", "blue", "red", "green"])
print(sorted(fruits), sorted(colors), len(fruits))   # sorted() only for stable printing
empty_set, empty_dict = set(), {}
print(type(empty_set).__name__, type(empty_dict).__name__)
print(set("hello"), set(range(3)))                    # str order varies run to run

nums = {1, 2, 3}
nums.add(4); nums.add(2)                  # adding an existing item: no effect
nums.update([5, 6], (7,))                 # any iterables
print(nums)
nums.remove(1)
nums.discard(60)                          # absent: silently ignored
try:
    nums.remove(60)
except KeyError as e:
    print("KeyError:", e)
backup = nums.copy()
nums.clear()
print(nums, backup)
print("pop() ->", backup.pop(), backup)    # removes an ARBITRARY element
```

Output:

```
['apple', 'banana', 'cherry'] ['blue', 'green', 'red'] 3
set dict
{'l', 'h', 'e', 'o'} {0, 1, 2}          <- letter order varies from run to run
{1, 2, 3, 4, 5, 6, 7}
KeyError: 60
set() {2, 3, 4, 5, 6, 7}
pop() -> 2 {3, 4, 5, 6, 7}
```

- `add(x)` one item; `update(*iterables)` many.
- `remove(x)` raises `KeyError` if absent; `discard(x)` doesn't.
- `pop()` removes an **arbitrary** element.
- `copy()` is independent (items are immutable, so shallow = full).
- Small ints often *look* sorted because they hash to themselves — coincidence, not guarantee.

De-duplicate keeping order — sets lose order, dicts don't:

```
items = ["b", "a", "b", "c", "a"]
print(list(dict.fromkeys(items)))       # ['b', 'a', 'c']
```

Common mistakes

- `{}` for an empty set.
- `set("hello")` splits characters; `{"hello"}` is one item.
- Lists or dicts in a set → `TypeError: unhashable type`.
- Relying on set order in output — sort it.

TL;DR


Unique, unordered, hashable items; `add` / `update`; `remove` (raises) / `discard` (silent); `set()` for empty; O(1) membership.

6.7 Set operations

What it is

Set algebra as **operators** (both sides sets/frozensets) or **methods** (any iterable, several arguments).

Operation	Operator	Method	Result
Union — in either	`a | b`	`a.union(b, ...)`	Everything from both
Intersection — in both	`a & b`	`a.intersection(b, ...)`	Common items
Difference — in `a` not `b`	`a - b`	`a.difference(b, ...)`	`a` minus `b`
Symmetric difference — in exactly one	`a ^ b`	`a.symmetric_difference(b)`	Union minus intersection
Subset	`a <= b`	`a.issubset(b)`	Every item of `a` is in `b`
Proper subset	`a < b`	—	Subset and not equal
Superset	`a >= b`	`a.issuperset(b)`	Every item of `b` is in `a`
Disjoint	—	`a.isdisjoint(b)`	No common items



```python
a, b = {1, 2, 3, 4}, {3, 4, 5, 6}
print("union        a | b :", a | b, a.union(b))
print("intersection a & b :", a & b, a.intersection(b))
print("difference   a - b :", a - b, a.difference(b), "  b - a:", b - a)
print("sym. diff    a ^ b :", a ^ b, a.symmetric_difference(b))
print("method accepts any iterable:", a.union([9, 10]), " operator needs sets")
try:
    a | [9]
except TypeError as e:
    print("TypeError:", e)
print("multi-arg:", a.intersection(b, {4, 99}))

small, big, other = {1, 2}, {1, 2, 3}, {7}
print(small <= big, small.issubset(big), small < big, big >= small, big.issuperset(small))
print(small.isdisjoint(other), small < small, small <= small)
```

Output:

```
union        a | b : {1, 2, 3, 4, 5, 6} {1, 2, 3, 4, 5, 6}
intersection a & b : {3, 4} {3, 4}
difference   a - b : {1, 2} {1, 2}   b - a: {5, 6}
sym. diff    a ^ b : {1, 2, 5, 6} {1, 2, 5, 6}
method accepts any iterable: {1, 2, 3, 4, 9, 10}  operator needs sets
TypeError: unsupported operand type(s) for |: 'set' and 'list'
multi-arg: {4}
True True True True True
True False True
```

Difference is **one-directional**; a set is a subset (`<=`) but not a proper subset (`<`) of itself.

Trade-offs

Operators are shorter and force explicit conversion (catching type mistakes); methods are flexible.

Real-world examples

- Permissions: `required <= user_permissions`.
- Sync diffs: `new_ids - old_ids` (added), `old_ids - new_ids` (removed).
- Recommendations via intersections; Jaccard similarity (shared ÷ all distinct) = `len(a & b) / len(a | b)` for near-duplicate detection.

In the interview

30-second answer: " `|` union, `&` intersection, `-` difference, `^` symmetric difference, `<=` / `>=` subset/superset, `isdisjoint` . Operators need sets; methods accept any iterable. Intersection costs O(min(len a, len b)) because it iterates the smaller set and probes the larger."

Self-check

1. `{1, 2, 3} ^ {2, 3, 4}`? → `{1, 4}`.

TL;DR

`| & - ^` plus subset/superset/disjoint; methods take any iterable; difference is one-directional.

6.8 Set methods (complete table) and `frozenset`

All set methods

Method	What it does	Operator form	Returns
`add(x)`	Add one element (no effect if present)	—	`None`
`update(*its)`	Add all elements from iterables	`|=`	`None`
`remove(x)`	Remove `x`; `KeyError` if absent	—	`None`
`discard(x)`	Remove `x` if present	—	`None`
`pop()`	Remove and return an arbitrary element; `KeyError` if empty	—	element
`clear()`	Remove everything	—	`None`
`copy()`	Shallow copy	—	new set
`union(*its)`	All elements	`|`	new set
`intersection(*its)`	Common elements	`&`	new set
`intersection_update(*its)`	Keep only common elements	`&=`	`None`
`difference(*its)`	Elements not in the others	`-`	new set
`difference_update(*its)`	Remove elements found in the others	`-=`	`None`
`symmetric_difference(it)`	In exactly one	`^`	new set
`symmetric_difference_update(it)`	Update to "in exactly one"	`^=`	`None`
`issubset(it)`	All my elements are in `it`	`<=`	bool
`issuperset(it)`	All of `it`'s elements are in me	`>=`	bool
`isdisjoint(it)`	No common elements	—	bool

`_update` methods mutate **in place** and return `None`; plain ones return a **new** set. Each `_update` has an augmented-operator twin (`&=`, `-=`, `^=`, `|=`) that requires sets on both sides.

```
s = {1, 2, 3, 4}
s.intersection_update({2, 3, 9});        print("&= :", s)
s.difference_update({3});                print("-= :", s)
s.symmetric_difference_update({2, 8});   print("^= :", s)
s |= {100};                              print("|= :", s)
```

Output:

```
&= : {2, 3}
-= : {2}
^= : {8}
|= : {8, 100}
```

`frozenset` — the immutable set

What it is

A **frozenset** can't change after creation: all non-mutating methods (`union`, `issubset`, …), none of the mutating ones (`add`, `remove`, `update`, …).

Why it matters

Immutable ⇒ **hashable**: usable as a dict key or set element — which a normal set never can be.

```python
fs = frozenset([1, 2, 3])
try:
    fs.add(4)
except AttributeError as e:
    print("AttributeError:", e)
groups = {frozenset({"alice", "bob"}): "team A"}   # usable as a dict key
print(groups[frozenset({"bob", "alice"})])
print(fs | {9}, type(fs | {9}).__name__)            # result type follows the left operand
```

Output:

```
AttributeError: 'frozenset' object has no attribute 'add'
team A
frozenset({1, 2, 3, 9}) frozenset
```

Lookup works regardless of member order — sets compare and hash by contents — ideal for "unordered pair" keys, e.g. an undirected edge (connection with no direction) `frozenset((u, v))`.

Common mistakes

- Expecting `s.union(t)` to modify `s`, or `s.update(t)` to return the result (`None`).
- Treating `pop()` as "smallest".

TL;DR

Plain methods return new sets, `_update` methods mutate; `frozenset` = immutable, hashable set for keys and sets of sets.

6.9 The `collections` module

Specialised containers for the common "plain dict/list isn't quite right" cases.

`Counter` — counting hashable things

What it is: a dict subclass mapping item → count; missing items count `0` (no `KeyError`).

```python
words = "the cat and the hat and the bat".split()
c = Counter(words)
print(c)
print(c.most_common(2), c["the"], c["dog"])          # missing key -> 0, no KeyError
c.update(["cat", "cat"]); c.subtract(["the"])
print(c.most_common(3))
a, b = Counter("aabbb"), Counter("abccc")
print(a + b, a - b, a & b, a | b, sep=" | ")
print(Counter("mississippi").total())                # 3.10+
```

Output:

```
Counter({'the': 3, 'and': 2, 'cat': 1, 'hat': 1, 'bat': 1})
[('the', 3), ('and', 2)] 3 0
[('cat', 3), ('the', 2), ('and', 2)]
Counter({'b': 4, 'a': 3, 'c': 3}) | Counter({'b': 2, 'a': 1}) | Counter({'a': 1, 'b': 1}) | Counter({'b': 3, 'c': 3, 'a': 2})
11
```

- `most_common(n)` — top-n (ties keep first-seen order).
- `update` **adds** counts (unlike `dict.update`, which replaces); `subtract` may leave zero/negative counts.
- `+` / `-` **drop** results ≤ 0; `&` = per-key minimum, `|` = maximum.
- `total()` sums counts (3.10+).

Real-world: word frequencies, log-level tallies, top-k errors, "bag of words" (text as word counts) for text classification.

`defaultdict` — dict with automatic defaults

What it is: a dict subclass calling a **factory** (zero-argument callable — `list`, `int`, `set`, …) to create a value the first time a missing key is **accessed with `[]`**.

```
groups = defaultdict(list)
for kind, name in [("fruit", "apple"), ("veg", "kale"), ("fruit", "fig")]:
    groups[kind].append(name)                       # missing key -> list() created
print(dict(groups))
counts = defaultdict(int)
for ch in "banana":
    counts[ch] += 1
print(dict(counts))
print("veg" in groups, "meat" in groups, groups.get("meat"))   # get/in don't create keys
_ = groups["meat"]                                              # [] access DOES
print("after groups['meat']:", dict(groups))
tree = lambda: defaultdict(tree)                                # autovivifying tree
t = tree(); t["a"]["b"]["c"] = 1
```

Output:

```
{'fruit': ['apple', 'fig'], 'veg': ['kale']}
{'b': 1, 'a': 3, 'n': 2}
True False None
after groups['meat']: {'fruit': ['apple', 'fig'], 'veg': ['kale'], 'meat': []}
```

Just reading `d[missing]` inserts an empty value — mysterious extra keys. Use `in` / `.get()` for read-only checks.

Real-world: graph adjacency lists (each node's neighbours, `defaultdict(list)`), inverted indexes (word → documents containing it, `defaultdict(set)`), grouping rows by a column.

`OrderedDict` — a dict with reordering tools

What it is: the pre-3.7 ordered dict; now useful only for its extras:

- `move_to_end(key, last=True)` — O(1) move to end (front with `last=False`).
- `popitem(last=False)` — pop from the **front** (FIFO — first in, first out); `dict.popitem()` only pops the end.
- **Order-sensitive equality**.

```
od = OrderedDict.fromkeys("abcde")
od.move_to_end("b")                 # to the end
od.move_to_end("e", last=False)     # to the front
print(list(od))                     # ['e', 'a', 'c', 'd', 'b']
print(od.popitem(last=False))       # ('e', None)
print(OrderedDict(a=1, b=2) == OrderedDict(b=2, a=1), dict(a=1, b=2) == dict(b=2, a=1))  # False True
```

The classic use — an LRU (least-recently-used) cache:

```python
class LRUCache:
    def __init__(self, capacity):
        self.capacity, self.data = capacity, OrderedDict()
    def get(self, key):
        if key not in self.data:
            return None
        self.data.move_to_end(key)            # mark as most recently used
        return self.data[key]
    def put(self, key, value):
        self.data[key] = value
        self.data.move_to_end(key)
        if len(self.data) > self.capacity:
            self.data.popitem(last=False)     # evict least recently used

cache = LRUCache(2)
cache.put("a", 1); cache.put("b", 2); cache.get("a"); cache.put("c", 3)
print("LRU keeps:", list(cache.data))         # LRU keeps: ['a', 'c']
```

Reading `"a"` made it recent, so adding `"c"` evicted `"b"`. For function results prefer `@functools.lru_cache`.

`deque` — double-ended queue

What it is: **O(1)** `append` / `pop` at **both** ends (a list is O(n) at the front). A doubly-linked list (each block links to next and previous) of fixed-size blocks, so middle indexing is O(n).

```python
q = deque([1, 2, 3])
q.append(4); q.appendleft(0)
print("after append/appendleft:", q)
left, right = q.popleft(), q.pop()
print("popleft ->", left, "| pop ->", right, "| now", q)
q.rotate(1); print("rotate(1):", q)
last3 = deque(maxlen=3)
for x in range(6):
    last3.append(x)                   # old items fall off the other end
print("maxlen=3:", last3)
```

Output:

```
after append/appendleft: deque([0, 1, 2, 3, 4])
popleft -> 0 | pop -> 4 | now deque([1, 2, 3])
rotate(1): deque([3, 1, 2])
maxlen=3: deque([3, 4, 5], maxlen=3)
```

- `maxlen` gives a bounded buffer — "last N lines/events" (like Unix `tail -n`).
- `append` / `popleft` are thread-safe in CPython, so deques back simple producer/consumer queues (one part adds work, another takes it); `queue.Queue` adds blocking (waiting for an item) and locking.

Real-world: BFS (breadth-first search, exploring a graph level by level) queues, sliding windows over recent items, capped undo history, rate limiters (capping requests per time period) keeping recent timestamps.

`ChainMap` — layered lookups

What it is: a view over several mappings searched **in order**; first hit wins; nothing copied.

```python
defaults = {"color": "red", "user": "guest", "debug": False}
env = {"user": "admin"}
cli = {"debug": True}
cfg = ChainMap(cli, env, defaults)    # first mapping wins
print(cfg["color"], cfg["user"], cfg["debug"])
cfg["color"] = "blue"                 # writes go to the FIRST mapping only
print(cli, defaults["color"])
child = cfg.new_child({"user": "tmp"})
print(child["user"], cfg["user"])
```

Output:

```
red admin True
{'debug': True, 'color': 'blue'} red
tmp admin
```

Real-world: configuration precedence (command line > environment variables > defaults); nested scopes in interpreters/template engines (`new_child()` pushes a scope). `string.Template.substitute` uses a `ChainMap` internally to combine a mapping with keyword arguments.

`namedtuple` — tuple with field names

Covered in Chapter 5 (5.13): `Card = namedtuple("Card", "rank suit")` → `Card("A", "spades").rank == "A"`, with `_fields`, `_asdict()`, `_replace()`.

```
A Card(rank='10', suit='hearts') ('rank', 'suit')
```

Common mistakes (collections)

- `Counter.update` expecting replacement.
- Creating `defaultdict` keys by reading.
- `list.pop(0)` instead of `deque.popleft()` for queues.
- `OrderedDict` just for ordering on 3.7+.

In the interview

30-second answer: "`Counter` counts and gives `most_common`; `defaultdict` auto-creates values for grouping; `deque` has O(1) appends and pops at both ends — use it for queues and bounded buffers; `OrderedDict` adds `move_to_end` and FIFO `popitem`, which makes an LRU cache easy; `ChainMap` layers mappings for config precedence; `namedtuple` gives tuples field names."

- *Implement an LRU cache?* → `OrderedDict`: `move_to_end` on access, `popitem(last=False)` on overflow — both O(1).
- *Why deque for BFS?* → `popleft()` O(1) vs `list.pop(0)` O(n).
- *`Counter` `+` vs `update`?* → `+` returns a new Counter dropping non-positive counts; `update` adds in place and keeps them.

Self-check

1. Keep only the last 100 log lines? → `deque(maxlen=100)`.
2. Which mapping receives `ChainMap` writes? → The first.

TL;DR

Counter = counts; defaultdict = auto-values; OrderedDict = reordering + FIFO pop (LRU); deque = fast both ends + maxlen; ChainMap = layered lookup; namedtuple = named fields.

6.10 `heapq` — priority queues on a plain list

What it is

A **binary min-heap** is a list where `heap[k] <= heap[2k+1]` and `heap[k] <= heap[2k+2]` for every `k`, so the smallest item is at `heap[0]`. `heapq` keeps a normal list in heap order. Whenever you repeatedly need "the smallest/most urgent next" — schedulers, Dijkstra's shortest path (cheapest route through a weighted network), merging sorted streams, top-k — a heap costs O(log n) per operation instead of re-sorting.

How it works

Function	Does	Cost
`heapify(list)`	Rearrange a list into a heap in place	O(n)
`heappush(h, x)`	Add `x` (sift up until heap order holds)	O(log n)
`heappop(h)`	Remove and return the smallest (sift down)	O(log n)
`h[0]`	Peek at the smallest	O(1)
`heappushpop(h, x)` / `heapreplace(h, x)`	Push then pop / pop then push, efficiently	O(log n)
`nsmallest(k, it)` / `nlargest(k, it)`	Top-k without full sort	O(n log k)
`merge(*sorted_its)`	Lazily merge sorted inputs	O(n log m)
`heapify_max`, `heappush_max`, `heappop_max`, …	Max-heap versions (**new in Python 3.14**)	as above

```
def heapify_neg(xs):                        # helper: store negatives -> behaves as a max-heap
    h = [-x for x in xs]
    heapq.heapify(h)
    return h

h = [5, 1, 8, 3, 2]
heapq.heapify(h)                            # O(n), in place; h[0] is the smallest
print("heapified:", h, "min:", h[0])
heapq.heappush(h, 0)
print("pops:", [heapq.heappop(h) for _ in range(3)], "left:", h)
print(heapq.nsmallest(2, [7, 3, 9, 1]), heapq.nlargest(2, [7, 3, 9, 1]))
print("max-heap trick (negate):", -heapq.heappop(heapify_neg([3, 9, 4])))
```

Output:

```
heapified: [1, 2, 8, 3, 5] min: 1
pops: [0, 1, 2] left: [3, 5, 8]
[1, 3] [9, 7]
max-heap trick (negate): 9
```

`[1, 2, 8, 3, 5]` is **not sorted** — only the heap property holds. Before 3.14, max-heaps push negated numbers.

Priority queue with tie-breaking:

```
tasks, counter = [], 0
for prio, name in [(2, "write docs"), (1, "fix prod bug"), (3, "refactor"), (1, "reply to CEO")]:
    heapq.heappush(tasks, (prio, counter, name))   # (priority, sequence, payload)
    counter += 1
while tasks:
    prio, _, name = heapq.heappop(tasks)
    print(f"  p{prio}: {name}")
```

Output:

```
  p1: fix prod bug
  p1: reply to CEO
  p2: write docs
  p3: refactor
```

Tuples compare element-wise: priority first; the increasing counter breaks ties in insertion order **and** stops Python ever comparing payloads (the carried data, which may not be comparable).

`heapq.merge([1, 4, 9], [2, 3, 10], [5])` → `[1, 2, 3, 4, 5, 9, 10]` — the core of external sorting (merging sorted files too big for memory).

Trade-offs

Need	Use
Smallest item repeatedly, with inserts	`heapq`
Just the top k once	`heapq.nlargest/nsmallest` (or `sorted(...)[:k]` if k ≈ n)
Only min or max once	`min()` / `max()` — O(n)
Thread-safe blocking priority queue	`queue.PriorityQueue` (heapq inside)
Sorted order at all times with lookups	`bisect` on a list, or a sorted-container library

Real-world examples

`asyncio`'s event loop keeps scheduled callbacks (`call_later`) in a heap; `sched` and `queue.PriorityQueue` use `heapq`; Python Dijkstra/A* (distance-estimate-guided shortest path) implementations almost always do.

Self-check

1. `heapify` vs n pushes? → O(n) vs O(n log n).

TL;DR

`heapify` O(n), push/pop O(log n), `h[0]` is the min; `(priority, count, item)` tuples; `nlargest` for top-k; max-heap = negate (or 3.14's `_max` functions).

6.11 `bisect` — binary search on sorted lists

What it is

`bisect` finds where a value belongs in an **already sorted** list with binary search — O(log n) comparisons.

How it works

- `bisect_left(a, x)` — first insertion index keeping order (before equal items).
- `bisect_right(a, x)` / `bisect(a, x)` — index **after** equal items.
- `insort(a, x)` (= `insort_right`) — insert in order: O(log n) search **+ O(n)** shift.
- Since 3.10, all accept `key=`.

On `[10, 20, 20, 30, 40]` searching 20: `bisect_left` lands at 1, `bisect_right` after the last 20 at 3.

```
scores = [10, 20, 20, 30, 40]
print(bisect.bisect_left(scores, 20), bisect.bisect_right(scores, 20), bisect.bisect(scores, 25))
bisect.insort(scores, 25)
print(scores)

def contains(sorted_list, x):
    i = bisect.bisect_left(sorted_list, x)
    return i < len(sorted_list) and sorted_list[i] == x
print(contains(scores, 30), contains(scores, 31))

def grade(score, cutoffs=(60, 70, 80, 90), letters="FDCBA"):
    return letters[bisect.bisect(cutoffs, score)]
print([grade(s) for s in (33, 60, 77, 89, 90, 100)])

people = [("Ann", 25), ("Bob", 31), ("Cid", 40)]           # sorted by age
i = bisect.bisect_left(people, 30, key=lambda p: p[1])      # key= is 3.10+
print("first person aged >= 30:", people[i])
```

Output:

```
1 3 3
[10, 20, 20, 25, 30, 40]
True False
['F', 'D', 'C', 'B', 'A', 'A']
first person aged >= 30: ('Bob', 31)
```

The grading function is the Python docs' classic: cutoffs become a lookup; exactly 60 lands **right** of the 60 cutoff → "D".

Trade-offs

- Search O(log n), but `insort` O(n). For many inserts plus lookups on big data, a set/dict (if order doesn't matter) or a balanced tree (self-adjusting, O(log n) inserts) / third-party `sortedcontainers.SortedList` is better.
- The list **must** be sorted by the same key — bisect doesn't check.

Real-world examples

`random.choices` bisects cumulative weights (running totals) for weighted sampling; time-series code finds the first event after a timestamp; tax brackets and grade cutoffs are one call.

TL;DR

Binary search on sorted lists: `bisect_left/right` O(log n), `insort` O(n), `key=` since 3.10.

6.12 When to use what — the decision table

You need…	Use	Why	Key costs
Ordered items, index access, append at end	`list`	Dynamic array	index O(1), append O(1)*, `in` O(n)
Fixed record / dict key / return several values	`tuple` / `namedtuple`	Immutable, hashable, light	index O(1)
Look up values by key	`dict`	Hash table	get/set/del O(1) avg
Fast membership / uniqueness	`set`	Hash table	`in` O(1) avg
A set as a key or inside a set	`frozenset`	Immutable, hashable	same as set
Count things / top-k frequencies	`Counter`	Counting dict with `most_common`	update O(k)
Group into lists/sets without key checks	`defaultdict(list/set)`	Auto-created values	O(1)
Queue / stack at both ends / last N items	`deque` (`maxlen=N`)	O(1) at both ends	append/pop O(1), middle index O(n)
LRU cache / reorder keys / FIFO pop	`OrderedDict` (or `functools.lru_cache`)	`move_to_end` , `popitem(last=False)`	O(1)
Layered config / scopes	`ChainMap`	Search mappings in order, no copying	lookup O(number of maps)
Repeatedly take the smallest/most urgent	`heapq`	Binary heap	push/pop O(log n), peek O(1)
Top-k from a large iterable	`heapq.nlargest/nsmallest`	Avoids a full sort	O(n log k)
Search/insert in a sorted list	`bisect`	Binary search	search O(log n), insert O(n)
Dedupe but keep order	`dict.fromkeys(items)`	Dicts keep insertion order	O(n)
Compact numeric storage / fast maths	`array.array` / NumPy	Chapter 5	—

(* amortised)

In the interview — putting it together

Prompt: "Find the 3 most frequent words in a log file and the first line where each appears."

Answer sketch: stream lines; `Counter` for counts; a dict with `setdefault(word, line_no)` for first occurrence; `most_common(3)` at the end. O(total words) plus O(u log 3) for the top-k — no nested loops, no `list.index` .

Chapter TL;DR

Topic	Remember
Dicts	Key → value, O(1) avg, insertion-ordered since 3.7; `[]` raises `KeyError`, `get` defaults; `|` merges (3.9+); `copy` is shallow; don't resize while iterating.
Hashing	hash → slot → compare; ≤ 2/3 full; equal ⇒ same hash; keys must be immutable/hashable; string hashes salted per run.
Nested dicts	Chain keys; guard with `get(..., {})`; map 1:1 to JSON (keys become strings).
Dict methods	`get`, `setdefault`, `update` / `|=`, `pop`, `popitem` (LIFO), `fromkeys` (shared value trap), live views with set ops.
Comprehensions	`{k: v for ...}`, `{x for ...}`; `{}` is a dict.
Sets	Unique, unordered, hashable items; `add` / `update`; `remove` raises, `discard` doesn't; `set()` for empty.
Set operations	`| & - ^`, `<= < >= >`, `isdisjoint`; methods accept iterables; `_update` versions mutate.
frozenset	Immutable, hashable set — keys and sets of sets.
collections	Counter, defaultdict, OrderedDict (LRU), deque (queues, maxlen), ChainMap (layers), namedtuple.
heapq	Min-heap on a list; push/pop O(log n); `(prio, count, item)`; `nlargest`; max-heap functions in 3.14.
bisect	Binary search on sorted lists; `insort` is O(n); `key=` since 3.10.