Chapter 3 — Control Flow and Loops

By default a program runs each statement once, top to bottom. **Control flow** changes that: *choosing* which statements run (conditionals) and *repeating* them (loops). With the values and operators of Chapter 2, these are enough to express any **algorithm** (a precise step-by-step recipe).

What you'll learn: `if` / `else if` / `else`, guard clauses and truthiness in conditions; the ternary `? :`; `switch` (cases, `default`, `break`, grouping, strict comparison, fall-through); the five loops `for`, `while`, `do…while`, `for…in`, `for…of`; nested loops; `break`, `continue`, labels; choosing a loop (or an array method).

Code: `code/`. Every "Output:" block is real Node 24 output.

3.1 Conditional statements — making decisions

What it is

A **conditional statement** evaluates a **condition** and, depending on whether it is truthy or falsy, runs one block or another.

Tool	Best for
`if … else if … else`	any conditions, including ranges and combinations (`age >= 18 && hasId`)
`switch`	comparing **one** value against many fixed options (`"Mon"`, `"Tue"` …)
`condition ? a : b`	choosing between two **values** inside an expression

Where you meet them in real applications

- **Form validation** — enable Submit only when the email looks valid.
- **Authentication and permissions** (who the user is, what they may do) — show the admin panel only if logged in *and* admin.
- **UI** (user interface) — toggle a menu; apply dark mode if preferred.
- **Filtering** — show products inside the selected price range.
- **Error handling** — HTTP status 404 → "Not found", 500 → "Try again later" (2xx success, 4xx client error, 5xx server error — System Design Fundamentals).

TL;DR


`if` handles anything, `switch` one-value-many-options, the ternary chooses between two values.

3.2 `if`, `else` and `else if`

What it is

- `if (condition) { … }` runs the block only when the condition is truthy.
- `else { … }` (optional) runs when it is falsy.
- `else if (condition) { … }` (any number) adds conditions tested **in order**; the first truthy one wins, the rest are skipped.

How it works



Conditions are converted with the truthy/falsy rules (Chapter 2 §2.11); at most **one** block of the chain runs.

Example

```
// code/01_if_else.js (part 1)
function votingMessage(age) {
  if (age >= 18) {
    return "You can vote.";
  } else {
    return "Not old enough to vote yet.";
  }
}
console.log("age 18 ->", votingMessage(18));
console.log("age 16 ->", votingMessage(16));

function letterGrade(score) {
  if (score >= 90) {
    return "A";
  } else if (score >= 80) {
    return "B";
  } else if (score >= 70) {
    return "C";
  } else if (score >= 60) {
    return "D";
  } else {
    return "F";
  }
}
for (const s of [95, 85, 75, 65, 40]) console.log(`score ${s} -> grade ${letterGrade(s)}`);

function badGrade(score) {
  if (score >= 70) return "C";   // checked first, so 95 also lands here
  if (score >= 90) return "A";
  return "F";
}
console.log("wrong order: 95 ->", badGrade(95));
```

Output:

```
age 18 -> You can vote.
age 16 -> Not old enough to vote yet.
score 95 -> grade A
score 85 -> grade B
score 75 -> grade C
score 65 -> grade D
score 40 -> grade F
wrong order: 95 -> C
```

(Functions are covered in Chapter 4; `for…of` in §3.10.) Order checks **from most specific to least specific**: in `badGrade` the broad `>= 70` catches 95 before `>= 90` is reached.

Conditions are truthy/falsy, not just `true` / `false`

```
// code/01_if_else.js (part 2)
const inputs = ["", "Ana", 0, 3, null, []];
for (const v of inputs) {
  console.log(JSON.stringify(v).padEnd(6), v ? "truthy -> if-branch" : "falsy  -> else-branch");
}
```

Output:

```
""     falsy  -> else-branch
"Ana"  truthy -> if-branch
0      falsy  -> else-branch
3      truthy -> if-branch
null   falsy  -> else-branch
[]     truthy -> if-branch
```

`if (name)` reads well for "non-empty string", but `0` / `""` are falsy and `[]` truthy — compare explicitly when it matters (`items.length > 0`).

Guard clauses — flatter code

A **guard clause** handles a special case at the top of a function and returns immediately, avoiding deep nesting:

```
// code/01_if_else.js (part 3)
function shippingCost(order) {
  if (!order) return "no order";
  if (order.items === 0) return "empty cart";
  if (order.total >= 50) return "free shipping";
  return "shipping: $4.99";
}
const user = { loggedIn: true, role: "editor" };
if (user.loggedIn && (user.role === "admin" || user.role === "editor")) {
  console.log("can publish");
}
```

Output:

```
no order | empty cart | free shipping | shipping: $4.99
can publish
```

Combine conditions with `&&`, `||`, `!`, using parentheses for explicit grouping.

Braces

Braces are optional around a single statement, but this classic bug follows:

```
if (isAdmin)
  showPanel();
  logAccess();   // looks conditional, but ALWAYS runs — only the first line belongs to the if
```

A formatter (e.g. Prettier) re-indents to expose it; many teams always use braces.

Common mistakes

- `=` **instead of** `===`: `if (role = "admin")` assigns and is always truthy.
- **Wrong ladder order** (see `badGrade`).
- `if (arr)` **for emptiness** — always truthy.
- **Overlapping or gapped conditions** (`< 60` and `> 60` miss 60) — test the boundaries.

Self-check

1. In `if (a) {…} else if (b) {…}`, can both run? → No, at most one.
2. `if ("0")`? → Runs — non-empty string is truthy.
3. Why check `>= 90` before `>= 80`? → The first truthy branch wins.

TL;DR

First truthy branch runs. Order specific → general, keep braces, prefer guard clauses to nesting.

3.3 The conditional (ternary) operator

What it is

`condition ? valueIfTruthy : valueIfFalsy` is an **expression** picking one of two values — JavaScript's only three-operand (*ternary*) operator.

Example

```
// code/02_ternary.js
const age = 20;
const label = age >= 18 ? "adult" : "minor";
console.log("label:", label);

const count = 1;
console.log(`You have ${count} new ${count === 1 ? "message" : "messages"}`);

const temp = 12;
const feel =
  temp < 0 ? "freezing" :
  temp < 15 ? "cold" :
  temp < 25 ? "pleasant" :
  "hot";
console.log("feel:", feel);

const price = 100, isMember = true;
console.log("to pay:", price * (isMember ? 0.9 : 1));
```

Output:

```
label: adult
You have 1 new message
feel: cold
to pay: 90
```

When to use it (and when not)

Use the ternary when…	Use `if` when…
choosing between two **values**	running **statements** (side effects such as printing or updating variables, several lines)
it fits on one line and reads naturally	the logic needs explanation or more than two outcomes
you need an expression: inside a template literal, an argument, a `const` initialiser, JSX in React (HTML-like syntax inside JavaScript)	—

Chained ternaries are fine one condition per line (as above); nesting inside branches gets unreadable.

TL;DR

`cond ? a : b` returns `a` or `b` — for choosing values, not running code.

3.4 `switch`

What it is

`switch` evaluates one expression once and compares it with a list of `case` values, running code from the first match — a tidy replacement for an `else if` chain testing *the same value*.

```
switch (expression) {
  case value1:
    // runs when expression === value1
    break;
  case value2:
    // runs when expression === value2
    break;
  default:
    // runs when no case matched (optional)
}
```

Part	Role
`expression`	evaluated **once**; its value is compared with each case
`case value:`	a candidate match, compared with `===` (strict equality)
`break`	leaves the switch; without it, execution **falls through** into the next case's code
`default:`	optional catch-all when nothing matched — the switch equivalent of `else`

How it works

Evaluate the expression; compare top-down with `===`; at the first match start executing *from there* and continue until `break`/`return` or the end — **through following cases' code**. No match → start at `default` if present.

Examples

```
// code/03_switch.js (selected parts)
function describeType(value) {
  switch (typeof value) {
    case "number":  return "a number";
    case "string":  return "a string";
    case "boolean": return "a boolean";
    default:        return "something else";
  }
}

function menu(option) {
  let result;
  switch (option) {
    case 1: result = "Home"; break;
    case 2: result = "Profile"; break;
    case 3: result = "Settings"; break;
    default: result = "Invalid selection";
  }
  return result;
}

function openStatus(day) {          // grouped cases share one block
  switch (day) {
    case "Mon": case "Tue": case "Wed": case "Thu": case "Fri":
      return "open 9-17";
    case "Sat": return "open 10-14";
    case "Sun": return "closed";
    default:    return "unknown day";
  }
}

function ageCase(age) {             // strict comparison: "18" is not 18
  switch (age) {
    case 18:   return "matched the NUMBER 18";
    case "18": return "matched the STRING '18'";
    default:   return "no match";
  }
}
console.log(describeType(42), "|", describeType("hi"), "|", describeType(null));
console.log([1, 2, 3, 4].map(menu).join(", "));
console.log(["Tue", "Sat", "Sun", "Funday"].map(openStatus).join(" | "));
console.log(ageCase("18"), "|", ageCase(18), "|", ageCase(18.0));
```

Output:

```
a number | a string | something else
Home, Profile, Settings, Invalid selection
open 9-17 | open 10-14 | closed | unknown day
matched the STRING '18' | matched the NUMBER 18 | matched the NUMBER 18
```

- `typeof null` is `"object"` → no case → `default`.
- `return` leaves the switch too, so no `break` is needed in functions.
- **Grouped cases**: empty cases fall through to the next non-empty one.
- **Strict comparison**: `"18"` matches only `case "18"`; `18.0` is `18`. Convert string input first: `switch (Number(age))`.

Fall-through — feature and trap

```
// code/03_switch.js — no breaks on purpose: each level also gets the lower levels' rights
function withoutBreak(level) {
  const granted = [];
  switch (level) {
    case "admin":  granted.push("delete");   // falls through
    case "editor": granted.push("edit");     // falls through
    case "viewer": granted.push("read");
  }
  return granted;
}
console.log("admin:", withoutBreak("admin"), "viewer:", withoutBreak("viewer"));
```

Output:

```
admin: [ 'delete', 'edit', 'read' ] viewer: [ 'read' ]
```

Intentional fall-through is rare; a forgotten `break` is a classic bug. Mark intentional cases with `// falls through` — ESLint's `no-fallthrough` rule recognises it.

Two useful patterns

```
// code/03_switch.js
function bmiCategory(bmi) {          // switch (true): each case is a boolean condition
  switch (true) {
    case bmi < 18.5: return "underweight";
    case bmi < 25:   return "normal";
    case bmi < 30:   return "overweight";
    default:         return "obese";
  }
}
const statusText = { 200: "OK", 404: "Not Found", 500: "Server Error" };  // lookup object
console.log([17, 22, 27, 33].map(bmiCategory).join(", "));
console.log(statusText[404], "|", statusText[418] ?? "Unknown status");
```

Output:

```
underweight, normal, overweight, obese
Not Found | Unknown status
```

- **`switch (true)`** matches the first case evaluating to `true` (ranges) — works, but `if … else if` is often clearer.
- **A lookup object** (or `Map`, Chapter 8) beats a switch that only maps values; add a fallback with `??`.

Scope inside cases

The switch body is **one block**, so `const r` in two cases collides. Wrap case bodies in braces:

```
case "circle": {
  const r = shape.r;
  return +(Math.PI * r * r).toFixed(2);
}
```

Trade-offs

	`switch`	`if … else if`	lookup object/Map
Compares	one value, `===` only	any condition	exact keys
Ranges (`< 18`)	only via `switch (true)`	natural	no
Risk	forgotten `break`	long chains	keys are strings (objects)
Best when	many discrete values, some sharing code	mixed or range conditions	pure value-to-value mapping

In the interview

"How does `switch` compare values?" With `===`, the expression evaluated once and checked against cases top-down; execution starts at the first match and continues until `break`/`return` or the end (fall-through). `default` runs when nothing matches and may appear anywhere (conventionally last).

- *`switch("1")` vs `case 1`?* Different types under `===`.
- *`let` in two cases?* One block → redeclaration `SyntaxError`; wrap case bodies in braces.

TL;DR

One value vs many `===` cases; `break`/`return` each case, group to share code, `default` as catch-all, `{ }` for per-case variables.

3.5 Loops — why and which

What it is

A **loop** repeats its **body** while a condition holds or once per item in a collection; one run is an **iteration**. You write the body once instead of copying it — for rendering every cart item, summing an order, retrying a request, reading file lines, walking a game grid, **polling** (checking repeatedly at intervals).

Loop	Repeats…	Checks condition	Typical use
`for`	a counted number of times	before each iteration	index-based loops (positions from 0) over arrays, counting
`while`	while a condition is truthy	before each iteration (may run 0 times)	unknown number of iterations
`do…while`	while a condition is truthy	**after** each iteration (runs at least once)	"do it, then decide whether to repeat"
`for…in`	once per enumerable **property name** of an object (§3.9)	—	inspecting an object's keys
`for…of`	once per **value** of an iterable (§3.10: array, string, Map, Set …)	—	the everyday way to walk a collection

---


3.6 The `for` loop

What it is

```
for (initialisation; condition; final-expression) {
  // body
}
```

Part	When it runs	Typical content
initialisation	once, before the loop starts	declare a counter: `let i = 0`
condition	before **every** iteration; falsy → stop	`i < items.length`
final-expression	after every iteration	update the counter: `i++`

How it works



Example

```
// code/04_for_loop.js (part 1)
const fruits = ["Apple", "Banana", "Cherry"];
for (let i = 0; i < fruits.length; i++) {
  console.log(i, fruits[i]);
}

const prices = [12, 5, 30, 8];
let total = 0;
for (let i = 0; i < prices.length; i++) {
  total += prices[i];
}
console.log("total:", total);

let down = "";
for (let i = 5; i > 0; i--) down += i + " ";
console.log("countdown:", down.trim());
let evens = [];
for (let i = 0; i <= 10; i += 2) evens.push(i);
console.log("evens:", evens.join(","));
for (let lo = 0, hi = 4; lo < hi; lo++, hi--) console.log(`pair lo=${lo} hi=${hi}`);
```

Output:

```
0 Apple
1 Banana
2 Cherry
total: 55
countdown: 5 4 3 2 1
evens: 0,2,4,6,8,10
pair lo=0 hi=4
pair lo=1 hi=3
```

Trace: `i = 0` → `0 < 3` true → print → `i = 1` → … → `i = 3` → `3 < 3` false → exit. Indexes start at 0, so the last is `length - 1` — hence `<`, not `<=`. The header can count down (`i--`), step (`i += 2`) or manage two comma-separated variables (the "two pointers" interview pattern — Chapter 17).

Nested loops

For **each outer iteration, the inner loop runs all of its iterations**; *m* outer × *n* inner = *m* × *n* inner-body runs.

```
// code/04_for_loop.js (part 2)
const grid = [
  [1, 2, 3],
  [4, 5, 6],
];
for (let row = 0; row < grid.length; row++) {
  let line = "";
  for (let col = 0; col < grid[row].length; col++) {
    line += `[${row},${col}]=${grid[row][col]} `;
  }
  console.log(line.trim());
}
let iterations = 0;
for (let a = 1; a <= 4; a++) {
  let row = "";
  for (let b = 1; b <= 4; b++) { row += String(a * b).padStart(3); iterations++; }
  console.log(row);
}
console.log("inner body ran", iterations, "times");
```

Output:

```
[0,0]=1 [0,1]=2 [0,2]=3
[1,0]=4 [1,1]=5 [1,2]=6
  1  2  3  4
  2  4  6  8
  3  6  9 12
  4  8 12 16
inner body ran 16 times
```

Nested loops walk 2-D data (matrices, spreadsheets, game boards, pixels) and compare every item with every other. Their *m* × *n* cost is the first suspect when code is slow (10,000 × 10,000 = 100 million iterations); interviews often ask to replace such an **O(n²)** loop (Big-O: how work grows with input size *n*; O(n²) — double the input, ~4× the work) with one loop plus a `Map` / `Set` (Chapter 8).

Edge cases

```
// code/04_for_loop.js (part 3)
let n = 0;
for (;;) { if (++n === 3) break; }       // all three parts are optional
console.log("stopped at", n);

const letters = ["a", "b"];
for (let i = 0; i <= letters.length; i++) console.log("i =", i, "->", letters[i]);
```

Output:

```
stopped at 3
i = 0 -> a
i = 1 -> b
i = 2 -> undefined
```

- `for (;;)` is an intentional infinite loop — something inside must `break`.
- **Off-by-one**: `<=` reads a missing index, which quietly gives `undefined` (no error).

`let` in the loop header

With `let` each iteration gets a **fresh copy** of `i` — important when a closure created inside the loop remembers it; with `var` all iterations share one variable (Chapter 4 §4.7).

Common mistakes

- `i <= arr.length` (off-by-one).
- **Removing items while looping by index** — later items shift and get skipped. Loop backwards or use `filter`.
- **Not updating the counter** (or `i++` in the inner loop by mistake) → infinite loop.

TL;DR

`for (init; condition; update)` — init once, check before each iteration, update after. `<` with `length`. Nested loops multiply iteration counts.


3.7 The `while` loop

What it is

`while` runs its body *as long as* the condition is truthy, checking **before** each iteration (so possibly zero times). Use it when the number of iterations is unknown (read until input ends, retry until success, halve until small). A `for` loop is a `while` with its bookkeeping gathered in the header.

```
while (condition) {
  // body — must eventually make the condition falsy (or break)
}
```

How it works



Example

```
// code/05_while_do_while.js (part 1)
let count = 1;
let out = [];
while (count <= 5) {
  out.push(count);
  count++;
}
console.log("while 1..5:", out.join(" "));

const readings = [5, 3, 7, -1, 2];
let sum = 0, i = 0;
while (i < readings.length && readings[i] >= 0) {
  sum += readings[i];
  i++;
}
console.log(`sum before first negative: ${sum} (stopped at index ${i})`);

let value = 1000, steps = 0;
while (value >= 1) { value /= 2; steps++; }
console.log("halvings:", steps);
```

Output:

```
while 1..5: 1 2 3 4 5
sum before first negative: 15 (stopped at index 3)
halvings: 10
```

In the compound condition, `i < readings.length` comes first, so short-circuiting (Chapter 2 §2.7) prevents reading past the end.

Common mistakes

- **Infinite loop** — nothing in the body changes the condition (no `count++`). Browser tab freezes; in Node press `Ctrl+C`.
- **`while` for a simple count** — `for` keeps counter logic visible in one place.
- **Busy-waiting** — `while (!dataArrived) {}` never works: the single thread is stuck in your loop, so the response can't be processed. Wait with callbacks, promises and `await` (Chapter 12).

TL;DR

`while (cond) { … }` checks first, may run zero times, for unknown counts. The body must move toward ending the loop.


3.8 The `do…while` loop

What it is

`do…while` runs the body **first** and checks afterwards — so **at least once**, even if the condition was already false.

```
do {
  // body — always runs once
} while (condition);   // note the semicolon
```

How it works



Example

```
// code/05_while_do_while.js (part 2)
let x = 10;
while (x < 5) { console.log("while body (never)"); }
do { console.log("do-while body runs once, x =", x); } while (x < 5);

let c = 1; out = [];
do {
  out.push(c);
  c++;
} while (c <= 5);
console.log("do-while 1..5:", out.join(" "));

function makeRandom(seed) {            // tiny deterministic random generator, so the output is repeatable
  return () => (seed = (seed * 1103515245 + 12345) % 2 ** 31) / 2 ** 31;
}
const random = makeRandom(42);
let roll, rolls = [];
do {
  roll = Math.floor(random() * 6) + 1;   // 1..6
  rolls.push(roll);
} while (roll !== 6);
console.log("rolled until a 6:", rolls.join(" "));

let attempt = 0, ok = false;
do {
  attempt++;
  ok = attempt === 3;                    // pretend the 3rd try succeeds
  console.log(`attempt ${attempt}: ${ok ? "success" : "failed"}`);
} while (!ok && attempt < 5);
```

Output:

```
do-while body runs once, x = 10
do-while 1..5: 1 2 3 4 5
rolled until a 6: 4 4 6
attempt 1: failed
attempt 2: failed
attempt 3: success
```

Same false condition: `while` ran zero times, `do…while` once. Dice rolling is the natural shape — you can't test a roll before rolling. (Real code uses `Math.random()`, Chapter 5; the **seeded** generator repeats the same sequence so output is stable.) The retry loop adds a safety cap on attempts.

Trade-offs — `while` vs `do…while`

	`while`	`do…while`
Condition checked	before each iteration	after each iteration
Minimum runs	0	1
Typical use	process while data remains	prompt/generate/try first, then decide
How common	very	rare — a `while` with a flag or `break` is often clearer

TL;DR

`do { … } while (cond);` runs once before testing — use only when the first run is unconditional.

3.9 The `for…in` loop

What it is

`for…in` loops over the **property names (keys)** of an object — all **enumerable string-keyed** properties, **including inherited ones** (from an object it is linked to). An **enumerable** property shows up in such loops: ones you create are, built-ins like `toString` aren't (attributes: Chapter 5).

```
for (const key in object) {
  // key is a string: the current property's name
}
```

Example

```
// code/06_for_in.js
const person = { firstName: "Grace", lastName: "Hopper", born: 1906 };
for (const key in person) {
  console.log(`${key}: ${person[key]}`);
}

const laptop = { brand: "Acme", ram: 16, ssd: 512, weight: 1.3 };
let propertyCount = 0;
for (const key in laptop) propertyCount++;
console.log("laptop has", propertyCount, "properties | Object.keys:", Object.keys(laptop).length);

const base = { kind: "vehicle" };
const bike = Object.create(base);   // bike's prototype is base (see Chapter 9)
bike.wheels = 2;
const all = [], own = [];
for (const key in bike) {
  all.push(key);
  if (Object.hasOwn(bike, key)) own.push(key);   // filter to own properties (ES2022)
}
console.log("all keys:", all, "| own keys:", own);

const colors = ["red", "green", "blue"];
colors.note = "primary-ish";
for (const index in colors) {
  console.log(typeof index, index, "->", colors[index]);
}

const mixed = { b: 1, 2: "two", a: 2, 1: "one" };
const order = [];
for (const k in mixed) order.push(k);
console.log("order:", order.join(", "));
```

Output:

```
firstName: Grace
lastName: Hopper
born: 1906
laptop has 4 properties | Object.keys: 4
all keys: [ 'wheels', 'kind' ] | own keys: [ 'wheels' ]
string 0 -> red
string 1 -> green
string 2 -> blue
string note -> primary-ish
order: 1, 2, b, a
```

1. **The loop variable is the key** — read values with `person[key]` (`person.key` looks for a property named "key").
2. **Inherited properties appear** — `kind` comes from `bike`'s prototype (Chapter 9). Filter with `Object.hasOwn(obj, key)` (ES2022; older: `obj.hasOwnProperty(key)`) or use `Object.keys`.
3. **Arrays are a trap** — you get index **strings** (`"0"`), plus extra properties (`note`) or anything enumerable added to `Array.prototype`. Use `for…of`, `for` or array methods.

4. **Order:** integer-like keys ascending, then other string keys in creation order.

Modern alternatives

Need	Use
own keys	`Object.keys(obj)`
own values	`Object.values(obj)`
own `[key, value]` pairs	`for (const [k, v] of Object.entries(obj))`
number of own properties	`Object.keys(obj).length`

`for…in` is mostly seen in older code or when you want inherited properties.

TL;DR

`for…in` iterates enumerable property **names** (strings), inherited included. Fine for plain objects (with `Object.hasOwn`); not for arrays.

3.10 The `for…of` loop

What it is

`for…of` (ES2015) loops over the **values** of an **iterable** — an object that hands out values one at a time: arrays, strings, `Map`, `Set`, typed arrays, `arguments`, DOM collections like `NodeList`, generators. (The `Symbol.iterator` protocol behind it: Chapter 8.) No index bookkeeping — the everyday choice for collections.

```
for (const value of iterable) {
  // value is the current element
}
```

Example

```
// code/07_for_of.js
const numbers = [10, 20, 30];
for (const n of numbers) console.log("number", n);

for (const ch of "Hi!") console.log("char", ch);

const word = "a😀b";
console.log("length:", word.length, "| for...of count:", [...word].length);
for (const ch of word) console.log("code point:", ch);

const tasks = ["write", "test", "ship"];
for (const [i, task] of tasks.entries()) console.log(`${i + 1}. ${task}`);

const stock = new Map([["apples", 5], ["pears", 0]]);
for (const [item, qty] of stock) console.log(item, "=", qty);
for (const tag of new Set(["js", "css", "js"])) console.log("tag", tag);

const scores = { ana: 90, ben: 72 };
try { for (const x of scores) {} } catch (e) { console.log("for...of on object ->", e.name + ":", e.message); }
for (const [name, score] of Object.entries(scores)) console.log(name, score);

const arr = ["x", "y"];
const ins = [], ofs = [];
for (const k in arr) ins.push(k);
for (const v of arr) ofs.push(v);
console.log("for...in ->", ins, "| for...of ->", ofs);

const nums = [1, 2, 3];
for (let n of nums) n *= 10;
console.log("unchanged:", nums);
```

Output:

```
number 10
number 20
number 30
char H
char i
char !
length: 4 | for...of count: 3
code point: a
code point: 😀
code point: b
1. write
2. test
3. ship
apples = 5
pears = 0
tag js
tag css
for...of on object -> TypeError: scores is not iterable
ana 90
ben 72
for...in -> [ '0', '1' ] | for...of -> [ 'x', 'y' ]
unchanged: [ 1, 2, 3 ]
```

1. **Strings** iterate by Unicode **code point** (the number Unicode assigns each character): the emoji is one character for `for…of`, but `.length` is 4 because it occupies two UTF-16 units (Chapter 6).
2. **Index too?** Iterate `array.entries()` (`[index, value]` pairs) with destructuring `[i, task]` (Chapter 5).
3. **Maps** yield `[key, value]`; **Sets** each unique value once.
4. **Plain objects aren't iterable** → `TypeError`; use `Object.keys/values/entries`.
5. The loop variable is a **copy of each value** — reassigning it doesn't change the array (object values can still be mutated, Chapter 2 §2.4). Use `const` unless reassigning.

Trade-offs — `for…in` vs `for…of`

	`for…in`	`for…of`
Gives you	keys (always strings)	values
Works on	any object	iterables only (arrays, strings, Map, Set …)
Includes inherited properties	yes (enumerable ones)	n/a
Arrays	avoid	✓
Plain objects	✓	✗ — use `Object.entries(obj)`
Supports `break` / `continue`	yes	yes

TL;DR

`for…of` walks values of iterables — the default for collections. `.entries()` for indexes, `Object.entries()` for plain objects.

3.11 `break`, `continue` and labels

What it is

Statement	Effect
`break`	exits the innermost loop (or `switch`) immediately; execution continues after it
`continue`	skips the rest of the current iteration and starts the next one (in a `for` loop, the final-expression still runs first)
`label:`	names a statement (usually an outer loop) so `break label` / `continue label` can target it from inside a nested loop

A label is an identifier plus colon before a statement: `outer: for (…) { … }`.

Example

```
// code/08_loop_control.js
for (let i = 0; i < 5; i++) {
  if (i === 3) break;           // leave the loop entirely
  console.log("break demo i =", i);
}

for (let i = 0; i < 5; i++) {
  if (i === 2) continue;        // skip the rest of this iteration only
  console.log("continue demo i =", i);
}

const orders = [{ id: 1, paid: true }, { id: 2, paid: false }, { id: 3, paid: false }];
let firstUnpaid = null;
for (const order of orders) {
  if (!order.paid) { firstUnpaid = order; break; }
}
console.log("first unpaid order:", firstUnpaid.id);

outer: for (let i = 0; i < 3; i++) {
  for (let j = 0; j < 3; j++) {
    if (i === 1 && j === 1) break outer;
    console.log(`labelled break: i=${i}, j=${j}`);
  }
}

const matrix = [[1, 2], [-3, 4], [5, 6]];
const rowsWithoutNegatives = [];
rows: for (const row of matrix) {
  for (const v of row) {
    if (v < 0) continue rows;
  }
  rowsWithoutNegatives.push(row);
}
console.log("rows without negatives:", JSON.stringify(rowsWithoutNegatives));

let k = 0; const odd = [];
while (k < 6) {
  k++;                          // advance BEFORE continue, or the loop never ends
  if (k % 2 === 0) continue;
  odd.push(k);
}
console.log("odd numbers:", odd.join(","));

console.log("some unpaid?", orders.some((o) => !o.paid), "| find:", orders.find((o) => !o.paid).id);
```

Output:

```
break demo i = 0
break demo i = 1
break demo i = 2
continue demo i = 0
continue demo i = 1
continue demo i = 3
continue demo i = 4
first unpaid order: 2
labelled break: i=0, j=0
labelled break: i=0, j=1
labelled break: i=0, j=2
labelled break: i=1, j=0
rows without negatives: [[1,2],[5,6]]
odd numbers: 1,3,5
some unpaid? true | find: 2
```

- **Search-and-stop**: `break` once the first unpaid order is found.
- **Labelled `break`**: a plain inner `break` would let the outer loop continue with `i = 2`; `break outer` ends both at `i=1, j=1`.

- **Labelled `continue`**: a negative abandons the row and advances the *outer* loop, skipping the push.
- **`continue` in `while`** jumps straight to the condition — an update placed after it would be skipped (infinite loop).

When not to use them

- Search loops are often clearer as `find`, `findIndex`, `some`, `every` (Chapter 7), which stop early themselves.
- Labels are rare; alternatively move nested loops into a function and `return`.
- `break`/`continue` don't work inside `forEach` callbacks (separate functions, not a loop statement) — use `for…of`.

In the interview

"How do you exit a nested loop from the inner loop?" Label the outer loop and `break outerLabel`, or put the loops in a function and `return`. Plain `break` exits only the innermost loop.

- *`break` out of `forEach`?* No — `SyntaxError` inside the callback; throwing works but is hacky. Use `for…of`, `some` or `find`.
- *Does `continue` skip a `for` loop's update?* No — `i++` still runs before the next check.

TL;DR

`break` exits, `continue` skips to the next iteration, labels target an outer loop. Prefer `find`/`some` for search-and-stop.

3.12 Choosing the right loop

Situation	Best choice
Visit every element of an array/string/Map/Set	`for…of`
Need the index too	`for…of` over `arr.entries()`, or a classic `for`
Iterate backwards, skip by steps, two pointers	classic `for`
Repeat until something happens (unknown count)	`while`
Must run once before checking	`do…while`
Keys of a plain object	`Object.keys/entries` + `for…of` (or `for…in` + `Object.hasOwn`)
Transform every element into a new array	`arr.map(...)` (Ch. 7)
Keep only some elements	`arr.filter(...)`
Combine all elements into one value	`arr.reduce(...)` or a `for…of` with an accumulator
Find the first match / check any / check all	`find` / `some` / `every`
Wait for asynchronous work (work that finishes later, e.g. a network request)	`for await…of`, `await` in a loop (Ch. 12) — never a busy `while`

Engines optimise all loops; choose the one that states intent most clearly.

Chapter 3 TL;DR

- **Conditionals:** `if / else if / else` (first truthy branch wins — specific to general), ternary `c ? a : b` for values, `switch` for one value vs many `===` cases (`break` against fall-through, `default` catch-all, braces for per-case variables).

- **Loops:** `for` (init; condition; update) for counting, `while` (check first, maybe 0 runs) for unknown counts, `do…while` (at least once), `for…in` (property **names**, inherited included — not arrays), `for…of` (**values** of iterables — default for collections).
- **Nested loops** run the inner loop fully per outer iteration (m × n).
- `break` exits, `continue` skips, **labels** target an outer loop; `forEach` can't be broken — use `for…of`, `find`, `some`.
- Watch off-by-one (`<` vs `<=`), infinite loops (update before `continue`), truthiness surprises.

Next: Chapter 4 — Functions, Scope and Closures.