System Design Patterns — Capstone Projects

How to use this book

What a capstone is. The modules teach patterns one at a time: a queue here, a circuit breaker there, a saga somewhere else. A capstone makes you *combine* them inside one running system, under real constraints, and then break it on purpose to see whether your design holds. Reading about consistent hashing and building a cache cluster that rebalances when a node dies are two different levels of understanding. Interviewers can tell which one you have.

What each brief gives you. Every project is a design brief, not a tutorial. It tells you *what* to build and *why* each piece exists: the problem, cited real-world systems that solve it, requirements with numbers, an architecture diagram, a data model, a suggested stack, milestones, the hard parts explained, a test plan, the trade-offs, stretch goals and the interview questions the project prepares you for. It never gives you the code. You write that, and the writing is where the learning happens.

How to pick one.

- *New to backend systems?* Start with projects 1–10. Each is a single service plus PostgreSQL and Redis, runnable with one `docker compose up`.
- *Comfortable with one service?* Projects 11–25 add a second moving part: a broker, a stream, a second datastore, an external LLM. This is where most real interview prompts sit.
- *Preparing for senior or staff interviews?* Projects 26–40 are distributed systems: several nodes, replication, partitions, failure injection, Kubernetes. Pick the one closest to your target company's domain, then one far from it.
- *Short on time?* Build milestones 1–3 of any project. They are always a working, demo-able slice.

How to use a brief.

1. Read the whole brief once. Redraw the architecture diagram from memory before you write any code.
2. Build the milestones **in order**. Each ends with a "done when" check. Do not move on until it passes. The early milestones are deliberately boring so the later ones have something solid to stand on.
3. Read "Deep dive: the hard parts" *before* the milestone that needs it, not after you get stuck.
4. Write the tests from "Testing strategy" as you go. Every advanced project includes failure injection (kill a node, partition the network, slow a dependency). That is the part most people skip and the part that teaches the most.
5. Only then try the stretch goals.
6. Finish by answering "In the interview" out loud in under two minutes per question.

Using these projects in interviews. Each "In the interview" section is built to be spoken, not just read. Open with the 30-second answer: what you built, the one design decision that mattered most and why, the hardest problem, and one number. Then make sure you can explain every entry under Key terms in plain words, because interviewers probe vocabulary to see whether you really built the thing. Practise the questions and answers out loud until they sound like your own explanation. Quote your own numbers from your build (p99 latency, throughput, data size, test counts, failover time) rather than the targets in the brief. Finally, expect two follow-ups on every project: "what would you change at 10x?" and "what breaks first?". Have a concrete answer ready for both.

Colour coding in the PDF. Section headings are coloured by role so you can scan a brief quickly: *What it is* (blue) frames the project, *The problem it solves* and *Requirements* (red) set the constraints, *The architecture* and *Deep dive* (green) explain the mechanism, *Real-world examples* (amber) ground it in production systems, *Trade-offs* (purple) weigh the choices, *In the interview* and *Self-check* test you, and *TL;DR* boxes the takeaway.

Level legend.

Level	What it means	Typical shape
Beginner	One service, one database, one cache	1–2 weekends
Intermediate	Two to four components, async messaging, real failure handling	1–3 weeks
Advanced	Multiple nodes, replication, partitions, chaos tests, Kubernetes	3–8 weeks

Prerequisites refer to this book's modules: **M2** means Module 2 — Moving Data, **M13** means Module 13 — Case Studies: Building Blocks, and so on.

Default stack. Unless a brief says otherwise: **Java 25 + Spring Boot 4.1.1** (Spring Framework 7) or **Python 3.14** for services, **PostgreSQL** for durable state, **Redis** for caching and fast counters, **Kafka** for logs and events, **Docker Compose** for local runs, and **Kubernetes** (kind or k3d locally) for the advanced projects. Use the current versions of other tools. Pick one language per project and stay with it.

A note on honesty. The real-world sections cite engineering blogs, papers and official docs so you can read how production teams solved the same problem. Your build will be smaller. That is fine. The goal is that you can explain *why* the production version looks the way it does, because you have felt the forces that shaped it.

Project map

#	Project	Level	Time	Prerequisites
1	URL shortener with cache-aside	Beginner	1 weekend	M3, M4, M13
2	Unique ID generator service	Beginner	1 weekend	M1, M13
3	Rate limiter service	Beginner	1 weekend	M4, M8
4	Postgres-backed job queue	Beginner	1–2 weekends	M2, M5
5	Idempotent payments API	Beginner	1–2 weekends	M5, M17
6	Webhook delivery service	Beginner	1–2 weekends	M2, M5
7	Real-time leaderboard	Beginner	1 weekend	M4, M15
8	Live notifications with pub/sub and SSE	Beginner	1–2 weekends	M2
9	Resilient aggregator (BFF)	Beginner	1–2 weekends	M5, M8
10	Feature flag service	Beginner	1–2 weekends	M4, M9
11	Image upload and thumbnail pipeline	Intermediate	1–2 weeks	M2, M8, M16
12	Search autocomplete	Intermediate	1–2 weeks	M4, M10, M13
13	Group chat service	Intermediate	2–3 weeks	M2, M14
14	Transactional outbox and CDC pipeline	Intermediate	1–2 weeks	M2, M5, M10
15	Hotel reservation system	Intermediate	2 weeks	M7, M17
16	Sharded cache cluster with consistent hashing	Intermediate	2 weeks	M3, M4
17	API gateway	Intermediate	2–3 weeks	M5, M8
18	CQRS and event-sourced orders	Intermediate	2 weeks	M3, M10
19	Saga-based checkout	Intermediate	2–3 weeks	M5, M7
20	Metrics and alerting pipeline	Intermediate	2–3 weeks	M9, M16
21	Proximity search service	Intermediate	1–2 weeks	M3, M15
22	Polite web crawler	Intermediate	2 weeks	M2, M13
23	Real-time clickstream analytics	Intermediate	2–3 weeks	M10
24	LLM gateway	Intermediate	2 weeks	M5, M8, M11
25	RAG document Q&A service	Intermediate	2–3 weeks	M10, M11
26	Dynamo-style key-value store	Advanced	4–6 weeks	M3, M7, M13
27	Kafka-like distributed log	Advanced	4–6 weeks	M10, M13
28	Distributed job scheduler	Advanced	3–4 weeks	M5, M7, M16
29	Multi-region payments ledger	Advanced	5–8 weeks	M6, M7, M17
30	Raft-replicated config store	Advanced	4–6 weeks	M3, M7
31	S3-like object storage	Advanced	4–6 weeks	M3, M16
32	Collaborative editor with CRDTs	Advanced	4–6 weeks	M2, M16
33	Video transcoding and streaming platform	Advanced	4–6 weeks	M2, M8, M14
34	Ride-sharing dispatch	Advanced	4–6 weeks	M12, M15

#	Project	Level	Time	Prerequisites
35	News feed at scale	Advanced	4–5 weeks	M4, M12
36	Stock exchange matching engine	Advanced	4–6 weeks	M3, M17
37	Distributed tracing pipeline	Advanced	3–5 weeks	M9, M10
38	Zanzibar-style authorization service	Advanced	4–6 weeks	M4, M8
39	Cell-based multi-tenant platform	Advanced	5–8 weeks	M6, M9
40	AI copilot platform	Advanced	6–8 weeks	M11, M12

1. URL shortener with cache-aside

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** M3, M4, M13

What it is

A service that turns a long URL into a short code (`sho.rt/aZ3kQ9`) and redirects anyone who visits the code to the original address. You build the write path (create a link), the read path (redirect) and a Redis cache in front of PostgreSQL using **cache-aside**: the application checks the cache first, and on a miss reads the database and fills the cache itself.

The problem it solves

Long URLs break in emails, overflow character limits and leak tracking parameters. A shortener also gives you one place to count clicks and to disable a malicious link. The engineering lesson is that redirects are **read-heavy**: a link is created once and may be clicked millions of times, so the read path must be cheap and must survive a viral link.

Real-world examples

- Shlink is an open-source, self-hosted shortener with visit tracking and a REST API. Read its feature list to see what "production" adds beyond the core redirect.
- The AWS whitepaper on caching patterns with Redis describes cache-aside (lazy loading) and write-through, and the staleness trade-off between them.

Requirements


Functional

- `POST /links` with a long URL (and an optional custom alias) returns a short code.
- `GET /{code}` responds `301` or `302` to the long URL, or `404` if unknown or expired.
- Links may have an expiry time. An owner can disable a link.
- Count clicks per link (approximate is fine).

Non-functional


- Redirect p99 latency under 20 ms on a cache hit, under 50 ms on a miss (local Docker).
- Read:write ratio around 100:1. Target 2,000 redirects/s on a laptop.
- Codes are 7 characters of base62 (62^7 is about 3.5 trillion codes).
- No two long URLs ever get the same code.

The architecture



- **Shortener API**: stateless HTTP service. Any number of copies can run behind a load balancer.
- **Redis cache**: holds `code -> long_url` with a time-to-live (TTL, how long an entry may live before Redis deletes it).
- **PostgreSQL**: the source of truth for links.
- **Click buffer and flusher**: clicks are incremented in Redis (`INCR clicks:{code}`) and a background job copies the totals to PostgreSQL every few seconds, so the redirect never waits for a database write.

Data model



Tech stack

Component	Choice	Why
API	Spring Boot 4.1.1 on Java 25, or FastAPI on Python 3.14	Simple HTTP, good Redis and JDBC clients
Store	PostgreSQL	Unique index on `code` enforces correctness
Cache	Redis	Sub-millisecond GET, built-in TTL
Load test	k6 or wrk	Measure p99 honestly

Milestones

1. **Create and redirect without a cache.** Done when `POST` then `GET` returns a 302 with the right `Location` header.
2. **Code generation.** Encode a database sequence value in base62, or generate random codes and retry on unique-index conflict. Done when 1 million inserts produce no duplicates.
3. **Cache-aside.** Done when a load test shows over 95% hit rate and the database sees roughly one query per unique code.
4. **Expiry, disable and invalidation.** Disabling a link deletes its cache key. Done when a disabled link returns 404 within one second.
5. **Click counting.** Done when counts in PostgreSQL match Redis within one flush interval.

Deep dive: the hard parts

- **Choosing codes.** A counter encoded in base62 never collides but makes codes guessable (people can walk your links). Random codes are unguessable but need a collision check. A common middle path: counter plus a reversible shuffle (for example a Feistel cipher over the integer), giving unique and non-sequential codes.
- **301 vs 302.** A `301 Moved Permanently` lets browsers cache the redirect forever, which saves load but means you never see repeat clicks and can never change the target. Use `302` if analytics or disabling matter.
- **Negative caching.** Bots probe random codes. Every miss hits PostgreSQL. Cache "not found" for a short TTL (say 60 s) so a scan cannot hammer the database.
- **Stampede on a hot key.** When a viral link's cache entry expires, hundreds of requests miss at once. Use a short lock (`SET lock:{code} NX PX 200`) so only one request reloads, or add random jitter to TTLs.

Testing strategy

- Unit test base62 encode and decode round-trips, including 0 and the maximum value.
- Integration test with Testcontainers (real PostgreSQL and Redis in Docker): create, redirect, disable, expire.
- Kill Redis mid-test. Redirects must still work (slower) by falling back to PostgreSQL.
- Load test with a Zipf (skewed) key distribution, because real traffic is skewed.

Trade-offs, scaling and failure modes

- Cache-aside means a brief stale window after an update. For links that almost never change, that is acceptable.
- If Redis is down, the database takes the full read load. Put a connection-pool limit and a timeout on database calls so the API sheds load instead of piling up.
- Lost click increments when Redis restarts are acceptable here. They would not be for billing.
- To scale writes later, shard links by code hash (Module 3).

Stretch goals

- Custom aliases with profanity filtering and reserved words.
- Per-owner rate limit on link creation (see Project 3).

- A Bloom filter (a compact bit array that can say "definitely not present") in front of the database to reject unknown codes cheaply.

Skills practised

- M3 — Storing Data: unique keys, the path to sharding.
- M4 — Caching: cache-aside, TTLs, stampede prevention.
- M13 — Case Studies: Building Blocks: the full URL shortener design.

In the interview

30-second answer: I built a URL shortener where `POST /links` stores a long URL under a 7-character base62 code and `GET /{code}` redirects with a 302. The key decision was cache-aside in Redis in front of PostgreSQL, because traffic is about 100 reads per write and most links go cold after a day, so only the links people actually click take up cache memory. The hardest part was protecting the database from bots probing random codes and from a viral link whose cache entry expires, which I solved with negative caching and a short reload lock. On a laptop it served about 2,000 redirects/s with a cache-hit p99 under 20 ms.

Key terms to know:

- **Cache-aside (lazy loading)** — the app checks Redis, and on a miss reads PostgreSQL and writes the value into Redis itself. It is the read path for every redirect.
- **TTL (time to live)** — how long a cache entry lives before Redis deletes it. Each `code -> long_url` entry has one, with random jitter.
- **Base62 encoding** — writing a number with 0–9, a–z, A–Z. Seven characters give 62^7, about 3.5 trillion codes.
- **Unique index** — a database constraint that rejects a second row with the same `code`. It is the real guarantee that two URLs never share a code.
- **301 vs 302** — permanent redirect (browsers cache it) versus temporary redirect (every click comes back to you). This build uses 302 so clicks are counted and links can be disabled.
- **Negative caching** — caching "not found" for a short time so repeated lookups of unknown codes do not reach the database.
- **Cache stampede (thundering herd)** — many requests miss the same expired key at once and all hit the database. Prevented here with a `SET NX` lock and TTL jitter.
- **Hot key** — one key that gets a large share of traffic, such as a viral link. It can overload one Redis node.
- **Write-behind counter** — clicks are `INCR`ed in Redis and flushed to PostgreSQL in batches, so a redirect never waits on a database write.
- **Zipf distribution** — a skewed popularity curve where a few items get most of the traffic. Used in the load test because real link traffic looks like this.

Q: What is cache-aside, and why use it here instead of write-through?

A: In cache-aside the application loads data into the cache only when someone reads it. Write-through writes every new link into the cache at creation time. Most short links are clicked a few times on day one and then never again, so write-through would fill Redis with cold entries. Cache-aside spends memory only on links that are actually read.

Q: How do you generate codes so that two URLs never get the same one?

A: Either encode a database sequence value in base62, which can never collide, or generate a random 7-character code and retry if the unique index rejects it. With 3.5 trillion possible codes and a few million links, random collisions are rare, so retries are cheap. Either way the unique index on `code` is the final guarantee, not the generator.

Q: Why not just use a counter encoded in base62?

A: It is collision-free, but codes are sequential, so anyone can walk through your links and count how many you have. A middle path is to run the counter through a reversible shuffle such as a small Feistel cipher. You keep uniqueness and lose the guessable pattern.

Q: 301 or 302, and why?

A: A 301 tells browsers the move is permanent, so they cache it and stop asking you. That saves load but means you never see repeat clicks and cannot disable or change the link for those users. I use 302 because analytics and the ability to kill a malicious link matter more than the saved requests.

Q: A celebrity tweets one of your links. What breaks first, and what do you do?

A: The single Redis key for that code becomes hot, and if its entry expires many requests miss together and hit PostgreSQL. I add a tiny in-process cache in each API instance with a few seconds of TTL, so most requests never leave the process, and a `SET lock:{code} NX PX 200` so only one request reloads on a miss. Random TTL jitter stops many keys expiring at the same moment.

Q: What happens if Redis goes down?

A: Redirects still work because every miss falls back to PostgreSQL, just slower. The danger is that the database now takes the full read load, so I cap the connection pool and put a short timeout on queries. The service then sheds excess load with errors instead of piling up requests until it falls over. Click increments in Redis may be lost, which is acceptable for approximate analytics.

Q: Bots are probing random codes. How do you protect the database?

A: Cache the "not found" result for about 60 seconds so a repeated probe is answered from Redis. A per-IP rate limit (Project 3) slows scanners down. A Bloom filter, a compact bit array that can answer "definitely not present", can reject unknown codes before any lookup.

Q: What changes at 100x the traffic?

A: Reads scale by adding stateless API instances and Redis replicas or a Redis Cluster, plus the in-process hot-key cache. Writes are still small, but if the links table outgrows one PostgreSQL node, I shard it by a hash of the code so a redirect touches exactly one shard. A CDN can also serve the 302 for the hottest links if a short staleness window is fine.

Q: How do you prove it works?

A: Unit tests round-trip base62 encode and decode, including 0 and the largest value. Testcontainers integration tests cover create, redirect, disable and expire against real PostgreSQL and Redis. A k6 load test with a Zipf key spread checks the 95%+ hit rate and p99 targets, and a chaos test kills Redis mid-run to confirm redirects keep working.

Common mistakes in answers:

- Saying the cache guarantees uniqueness. Only the unique index in PostgreSQL does. Redis is a speed layer and can lose data.
- Choosing 301 "because it is faster" without mentioning that you lose click counts and the ability to disable the link.
- Ignoring misses. Unknown codes and expired hot keys are what actually hurt the database, which is why negative caching and stampede control matter.

TL;DR

Redirects vastly outnumber new links, so optimise the lookup path: the unique index guarantees correctness, cache-aside supplies speed, and negative caching with stampede control protects the database from bots and viral spikes.

2. Unique ID generator service

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** M1, M13

What it is

A small service (and a matching library) that hands out 64-bit IDs that are unique across many machines and roughly sorted by creation time, without a database round-trip per ID. You implement the **Snowflake layout**: timestamp bits, worker-ID bits and a per-millisecond sequence.

The problem it solves

A single database sequence is a bottleneck and a single point of failure once you shard data. Random UUIDs (128-bit universally unique identifiers) avoid coordination, but random values scatter inserts across a B-tree index (the sorted tree most databases use for indexes), which hurts write performance and cache locality. Time-ordered 64-bit IDs fit in a `bigint`, sort by time, and are generated locally.

Real-world examples

- Twitter's Snowflake announcement (2010) explains why they needed roughly sorted, uncoordinated 64-bit IDs when moving off a single database.
- Instagram's Sharding IDs at Instagram generates similar IDs inside PostgreSQL with a stored function that combines time, a logical shard ID and a sequence.
- RFC 9562 standardises UUIDv7, a time-ordered UUID. Compare its layout to Snowflake's.

Requirements


Functional

- `GET /ids?count=N` returns N unique IDs.
- A client library generates IDs in-process once it has a worker ID.
- `GET /ids/{id}/decode` returns the timestamp, worker and sequence.

Non-functional

- At least 1 million IDs per second per worker in-process.
- No duplicates across 1,024 workers, ever.
- IDs increase monotonically per worker.
- Survive a clock that jumps backwards without issuing duplicates.

The architecture



- **ID library**: the core. Holds the worker ID, the last timestamp and the sequence counter.
- **Worker registry**: assigns each running process a unique worker ID (0–1023) using a lease, which is a time-limited claim that must be renewed.
- **ID HTTP service**: wraps the library for clients that cannot embed it.

Data model

Bits	Field	Meaning
1	sign	Always 0 so IDs are positive in signed 64-bit types
41	timestamp	Milliseconds since a custom epoch, about 69 years of range
10	worker	1,024 concurrent workers
12	sequence	4,096 IDs per worker per millisecond

WORKER_LEASE		
int	worker_id	PK
text	holder	
timestamptz	expires_at	

Tech stack

Component	Choice	Why
Library	Java 25 (a `long` and a lock or CAS loop) or Python 3.14	Bit operations are trivial in both
Lease store	PostgreSQL	`INSERT ... ON CONFLICT` and row locks make leasing simple
Benchmark	JMH (Java) or `timeit` (Python)	Measure IDs per second

Milestones

1. **Bit packing.** Done when encode then decode round-trips for 10,000 random field values.
2. **Generator.** Same millisecond increments the sequence. Sequence overflow waits for the next millisecond. Done when 10 million IDs in one thread are strictly increasing.
3. **Concurrency.** Done when 16 threads produce 10 million IDs with no duplicates (check with a set or sort).
4. **Worker leasing.** Workers claim the lowest free ID whose lease expired, renew every 10 s, give it up on shutdown. Done when 50 simulated workers get distinct IDs.
5. **HTTP service and decode endpoint.** Done when a batch request of 10,000 IDs returns in under 10 ms.

Deep dive: the hard parts

- **Clock going backwards.** NTP (the network time protocol) can step the clock back. If the current time is less than the last timestamp, either wait until it catches up (fine for small jumps) or refuse to issue IDs and alert. Never just carry on, or you will repeat IDs.
- **Lease expiry vs. a paused process.** A long garbage-collection pause can outlive the lease, and another process takes the same worker ID. Make the generator check its lease deadline before issuing and stop if expired. This is a **fencing** idea you will meet again in Project 28.
- **Sortable is not ordered.** IDs from different workers in the same millisecond are not in true creation order. Do not use them for strict ordering across machines.

Testing strategy

- Property test: for random sequences of "tick" and "generate", output is strictly increasing.
- Inject a fake clock that goes backwards and assert no duplicate is issued.
- Run two processes with a forced lease collision and assert the second one refuses to start.

Trade-offs, scaling and failure modes

- Snowflake IDs leak creation time and rough volume. Do not expose them where that matters to competitors.
- 41 bits of milliseconds runs out about 69 years after your epoch. Pick a recent epoch.
- UUIDv7 needs no worker registry at all, at the cost of 128 bits. For many teams that trade is worth it.

Stretch goals

- Implement UUIDv7 alongside and compare index insert speed in PostgreSQL with 50 million rows.

- Put the logical shard number into the worker bits so an ID tells you which shard holds the row.

Skills practised

- M1 — Thinking in Patterns: back-of-envelope sizing of bit fields.
- M13 — Case Studies: Building Blocks: the unique ID generator design.

In the interview

30-second answer: I built a Snowflake-style ID generator that packs a 41-bit millisecond timestamp, a 10-bit worker ID and a 12-bit sequence into one positive 64-bit integer, so any process can mint unique, roughly time-sorted IDs with no database call per ID. The key decision was leasing worker IDs from a PostgreSQL table, because two processes sharing a worker ID is the only way to get duplicates. The hardest part was the clock going backwards and a paused process outliving its lease, which I handle by waiting or refusing to issue, and by checking the lease deadline before every batch. One worker produces over 1 million IDs/s in-process, with a ceiling of 4,096 per millisecond.

Key terms to know:

- **Snowflake layout** — 1 sign bit, 41 bits of time, 10 bits of worker, 12 bits of sequence. This is the exact bit layout of the ID.
- **Custom epoch** — the zero point of the timestamp field. Picking a recent one maximises the roughly 69-year range of 41 bits.
- **Sequence** — a per-worker counter that resets each millisecond. 12 bits allow 4,096 IDs per worker per millisecond, and overflow waits for the next millisecond.
- **Worker ID lease** — a time-limited, renewable claim on one of 1,024 worker IDs, stored in PostgreSQL and renewed every 10 s.
- **Fencing / self-fencing** — a process that cannot prove its lease is still valid stops issuing IDs, so a stale holder cannot collide with the new one.
- **Clock skew and NTP step** — the network time protocol can move the clock backwards. If now is earlier than the last timestamp, the generator must wait or refuse.
- **Monotonic per worker** — each worker's IDs strictly increase. IDs from different workers are only roughly ordered.
- **UUIDv7** — a 128-bit, time-ordered UUID from RFC 9562 with a 48-bit millisecond timestamp and random bits. It needs no worker registry.
- **B-tree locality** — inserting increasing keys appends to the right edge of the index, which is why time-ordered IDs insert faster than random UUIDv4.

Q: Why not just use an auto-increment column?

A: It needs a round-trip to one database for every ID. Once data is sharded, that database becomes a bottleneck and a single point of failure. Snowflake IDs are generated locally in microseconds and still fit in a `bigint`.

Q: Why not random UUIDv4?

A: UUIDv4 needs no coordination, but its values are random, so inserts land all over the B-tree index. That causes page splits and poor cache use on large tables. It is also 128 bits instead of 64. Time-ordered IDs append near the end of the index and keep it compact.

Q: Snowflake or UUIDv7?

A: Snowflake fits a 64-bit `bigint` and is compact in every index and foreign key, but needs a worker registry. UUIDv7 is also time-ordered and needs no registry because its random bits make collisions practically impossible, at the cost of 128 bits. Pick by storage size versus operational effort.

Q: What happens if two nodes get the same worker ID?

A: In the same millisecond they produce the same timestamp, worker and sequence, so they issue identical IDs. Leases prevent this: a worker claims a free ID, renews it every 10 s, and checks its

lease deadline before issuing. If the lease might have expired, for example after a long garbage-collection pause, it stops instead of guessing.

Q: The clock jumps backwards by 2 seconds. What does your generator do?

A: It compares the current time to the last timestamp it used. For a small jump it waits until the clock catches up. For a large one it refuses to issue IDs and raises an alert. Carrying on would reuse timestamp and sequence pairs and create duplicates.

Q: What limits throughput, and what changes at 10x?

A: Each worker can issue at most 4,096 IDs per millisecond, about 4 million per second, and 1,024 workers can run at once. At 10x more instances the 10-bit worker field runs out first. You can steal bits from the sequence for more workers, or switch to UUIDv7 and drop the registry.

Q: Can I sort by these IDs to get exact creation order?

A: Only within one worker. Two workers issuing in the same millisecond, or with slightly different clocks, can produce IDs whose order does not match real time. Use them for "roughly newest first", not for strict global ordering.

Q: How do you test it?

A: Encode and decode round-trips for 10,000 random field values. A fake clock that goes backwards proves no duplicate is issued. A 16-thread run of 10 million IDs is sorted and checked for duplicates, and a forced lease collision checks that the second process refuses to start.

Q: Hands-on: How do you build the ID from its fields?

A: Shift each field into place and OR them together. With `ts` in milliseconds since the epoch:

```
long id = (ts << 22) | (worker << 12) | sequence;
long tsBack = id >>> 22;          // decode timestamp
long workerBack = (id >>> 12) & 0x3FF;
```

Common mistakes in answers:

- Claiming the IDs are globally ordered. They are only k-sorted (roughly ordered) across workers.
- Forgetting the backwards-clock case or answering "use NTP". NTP is what moves the clock back.
- Saying worker IDs can be picked from hostnames or randomly. Without a lease, collisions are a matter of time.

TL;DR

Pack time, worker and sequence into 64 bits, lease worker IDs safely, and never issue IDs when the clock goes backwards.

3. Rate limiter service

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** M4, M8

What it is

A rate limiter decides whether a request may proceed based on how many requests the same caller made recently. You build it as a library plus an HTTP check endpoint, backed by Redis so many API servers share one count. You implement two algorithms: **token bucket** (a bucket refills at a steady rate, each request takes a token) and **sliding window counter** (an estimate of requests over the last N seconds).

The problem it solves

Without limits, one buggy client or one scraper can exhaust your capacity and take the service down for everyone. Limits also enforce pricing tiers and protect expensive endpoints. The limiter must be shared across servers, fast enough to sit on every request, and must fail in a safe direction when Redis is unavailable.

Real-world examples

- Stripe's Scaling your API with rate limiters describes several limiter types they run (request rate, concurrency, load shedding) and uses token buckets in Redis.
- Cloudflare's Counting things, a lot of different things explains the sliding window approximation they use to rate limit at the edge.

Requirements


Functional

- Rules per key and endpoint: for example "free tier: 100 requests per minute".
- `POST /check {key, rule}` returns allowed or denied plus remaining quota and retry-after seconds.
- Responses carry `RateLimit` and `Retry-After` headers. Denied requests get `429 Too Many Requests`.

Non-functional

- Added latency under 2 ms p99 per check (Redis on the same network).
- Over-admission under 1% at 5,000 checks/s from 4 API instances.
- If Redis is down, follow a configured policy: fail open (allow) or fail closed (deny).

The architecture



- **Limiter library**: builds the Redis key (`rl:{rule}:{caller}`) and runs one Lua script per check. A Lua script runs atomically inside Redis, so read-modify-write cannot interleave.
- **Redis**: stores bucket state with an expiry so idle callers cost nothing.
- **Rules config**: a YAML file loaded at startup and reloaded on change.

Data model

Key	Value	TTL
`tb:{rule}:{caller}`	hash: `tokens`, `last_refill_ms`	capacity / rate, rounded up
`sw:{rule}:{caller}:{window}`	integer count for the window	2 windows

Tech stack

Component	Choice	Why
Library	Spring filter (Java 25) or ASGI middleware (Python 3.14)	Runs before the handler
Store	Redis with Lua scripting	Atomic check-and-update in one round-trip
Load test	k6	Multiple virtual users and key spread

Milestones

1. **In-memory token bucket.** Done when unit tests with a fake clock show exact refill behaviour.
2. **Redis token bucket via Lua.** Done when 4 instances together admit within 1% of the limit.
3. **Sliding window counter.** Weight the previous window's count by how much of it overlaps the last N seconds. Done when burst at a window boundary admits at most limit plus a small error.
4. **Headers and 429s.** Done when clients receive correct `Retry-After` values.
5. **Failure policy.** Done when stopping Redis switches behaviour to the configured mode within one timeout (say 50 ms).

Deep dive: the hard parts

- **Why not GET then SET?** Two servers can read "9 used" at the same moment and both allow request 10. Lua (or `INCR` with `EXPIRE`) makes the update atomic.
- **Fixed windows burst at the edges.** With a fixed per-minute window, a caller can send 100 at 0:59 and 100 at 1:00. The sliding counter smooths this cheaply. A sliding log (store every timestamp in a sorted set) is exact but costs memory per request.
- **Clock source.** Use Redis's own clock (`TIME` inside the script) rather than each server's clock, so skew between servers does not create free tokens.
- **Fail open or closed?** Fail open protects availability (customers keep working) but removes protection during an outage. Fail closed protects downstream systems. Many teams fail open with a local in-memory fallback limit.

Testing strategy

- Fake-clock unit tests for both algorithms.
- Concurrency test: 200 threads hammer one key, count admits.
- Chaos: pause Redis with `docker pause`, verify latency stays bounded and the policy applies.

Trade-offs, scaling and failure modes

- One Redis is a single point of failure and a throughput ceiling. Shard keys across a Redis Cluster, which works because each check touches one key.
- Very hot keys (one huge customer) can overload a single Redis shard. Add a local pre-limiter that only asks Redis for every Nth request, or hands out token batches.

Stretch goals

- A concurrency limiter (max in-flight requests) using a sorted set of request IDs with timestamps.
- Adaptive limits that tighten when backend latency rises (load shedding).

Skills practised

- M8 — API and Edge: rate limiting algorithms and placement.
- M4 — Caching: Redis as shared fast state.

In the interview

30-second answer: I built a shared rate limiter as a library plus a `/check` endpoint, backed by Redis so every API instance sees the same counts. I implemented a token bucket and a sliding window counter, each as a single Lua script, because a Lua script runs atomically in Redis and two servers can never both admit the "last" request. The hard part was deciding what happens when Redis is down, so the limiter has a configured fail-open or fail-closed policy with a 50 ms timeout and a local in-memory fallback. Across 4 instances at 5,000 checks/s it over-admitted by less than 1% and added under 2 ms p99.

Key terms to know:

- **Token bucket** — a bucket holds up to N tokens and refills at a fixed rate. Each request takes one. It allows short bursts up to the bucket size.
- **Fixed window** — count requests per calendar minute. Simple, but allows a double burst at the boundary.
- **Sliding window counter** — estimates the last N seconds as the current window's count plus the previous window's count weighted by overlap. Cheap and smooth.
- **Sliding window log** — store every request timestamp in a sorted set. Exact, but costs memory per request.
- **Atomic read-modify-write** — read the count, decide, write back with nothing else in between. Done here with a Lua script.
- **Fail open / fail closed** — when the limiter's store is unreachable, either allow everything (keep availability) or deny everything (protect the backend).
- **429 and Retry-After** — the HTTP status for "too many requests" and the header that tells the client how long to wait.
- **Hot key** — one very large customer whose bucket key overloads a single Redis shard.
- **Clock skew** — different servers disagree on time. Using Redis's `TIME` inside the script avoids free tokens from skew.

Q: Token bucket or sliding window?

A: Token bucket lets a caller burst up to the bucket size and then settles to the refill rate. That suits APIs where short bursts are normal. The sliding window counter caps the rate more smoothly over any N-second span. Pick by whether bursts are acceptable.

Q: Why can't each server just do GET then SET on a counter?

A: Two servers can both read "99 used" at the same moment and both allow request 100, so the limit is exceeded. A Lua script or `INCR` plus `EXPIRE` makes the check and the update one atomic step inside Redis. Redis runs one script at a time, so there is no interleaving.

Q: What is the problem with a fixed per-minute window?

A: A caller can send the full limit at 0:59 and again at 1:00, which is twice the limit within two seconds. The sliding window counter blends the previous window's count by how much it overlaps, which removes most of that edge burst at almost no extra cost.

Q: Redis is down. What happens?

A: The limiter follows a deliberate policy after a short timeout, say 50 ms. Fail open keeps customers working but removes protection. Fail closed protects downstream systems but turns a Redis outage into a full outage. Most teams fail open with a local per-instance limit as a rough safety net, and alert.

Q: Why use Redis's clock instead of the application server's clock?

A: Each API server's clock can be off by a few hundred milliseconds. If a fast clock computes refills, it hands out tokens that should not exist yet. Calling `TIME` inside the Lua script gives every check the same clock.

Q: What changes at 10x the traffic?

A: A single Redis becomes a throughput ceiling and a single point of failure. Each check touches one key, so the keys can be sharded across a Redis Cluster without cross-shard work. For a single huge customer, a local pre-limiter that fetches tokens from Redis in batches cuts round-trips for that hot key.

Q: Where should the limiter sit?

A: As early as possible, at the gateway or in a filter before the handler, so rejected requests cost almost nothing. Limits are keyed by API key or user ID, not just IP, because many users can share one IP behind a NAT (network address translation).

Q: How do you test that the limit is accurate?

A: Unit tests with a fake clock check exact refill behaviour. A concurrency test fires 200 threads at one key and counts admits. A chaos test runs `docker pause` on Redis and checks that latency stays bounded and the failure policy applies.

Q: Hands-on: What does a token bucket refill compute?

A: Tokens are refilled lazily on each check, not by a timer:

```
local elapsed = now_ms - last_ms
tokens = math.min(capacity, tokens + elapsed * rate_per_ms)
if tokens >= 1 then tokens = tokens - 1; allowed = 1 end
```

Common mistakes in answers:

- Using a timer or background job to refill buckets. Lazy refill on each check is simpler and exact.
- Saying "fail closed" by default without noting it turns a cache outage into an API outage.
- Keying limits only by IP, which punishes users behind shared NATs and is easy for attackers to rotate.

TL;DR

A shared, atomic counter in Redis plus a clear failure policy is a production rate limiter. The algorithm choice is about how much burst you tolerate.

4. Postgres-backed job queue

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M2, M5

What it is

A background job system where web requests enqueue work (send an email, resize an image) and worker processes pick it up, run it, retry it on failure and move it to a **dead-letter queue** (DLQ, a holding area for jobs that keep failing) after too many attempts. Instead of a separate broker you use PostgreSQL itself with `SELECT ... FOR UPDATE SKIP LOCKED`.

The problem it solves

Slow or unreliable work does not belong in a user-facing request. A queue lets the request return fast while the work happens later, and lets you retry safely. Using the database you already run means the job is enqueued **in the same transaction** as the business change, so you never get "order saved but email job lost".

Real-world examples

- PostgreSQL's SELECT documentation describes `SKIP LOCKED`, which lets many workers take different rows without blocking each other.
- River (Go) and Rails' Solid Queue are open-source job queues built on this technique.
- Slack's Scaling Slack's job queue shows what happens when a Redis-based queue outgrows itself and Kafka is added in front.

Requirements

Functional


- Enqueue a job with type, JSON payload, priority and optional run-at time.
- Workers claim, run and mark jobs done. Failures retry with exponential backoff.
- After N attempts the job moves to a dead state. An admin endpoint lists and re-queues dead jobs.
- Jobs can be enqueued inside an application transaction.

Non-functional

- 1,000 jobs/s throughput with 8 workers on a laptop.
- Pickup latency under 1 s for ready jobs.

- At-least-once execution: a job may run twice, never zero times.

The architecture



- **Jobs table**: the queue. Each row carries state and attempt count.
- **Workers**: loop: claim a batch, run, update. `LISTEN/NOTIFY` (PostgreSQL's built-in pub/sub) wakes them instantly instead of polling every second.
- **Reaper**: finds jobs claimed long ago whose worker died and makes them available again.

Data model

JOB		
bigint	id	PK
text	kind	
jsonb	payload	
int	priority	
text	state	
int	attempts	
int	max_attempts	
timestamptz	run_at	
timestamptz	locked_until	
text	locked_by	
text	last_error	

States: `available -> running -> completed`, `running -> available` on retry, `running -> dead` after max attempts.

Tech stack

Component	Choice	Why
Queue store	PostgreSQL	Transactional enqueue, no new infra
Workers	Java 25 virtual threads, or Python 3.14 asyncio	Cheap concurrency for I/O-bound jobs
Metrics	Prometheus counters	Queue depth and age are the key signals

Milestones

1. **Enqueue and claim.** Claim with `UPDATE ... WHERE id IN (SELECT id ... FOR UPDATE SKIP LOCKED LIMIT 10) RETURNING *`. Done when 4 workers process 10,000 jobs with none run twice in the happy path.

2. **Retries with backoff and jitter.** Next run is `base * 2^attempts` plus random jitter. Done when a failing job's run times spread out.
3. **Dead-letter and re-queue.** Done when an always-failing job lands in `dead` and can be replayed.
4. **Visibility timeout and reaper.** Done when killing a worker mid-job causes the job to run again within the timeout.
5. **NOTIFY wakeups and metrics.** Done when p50 pickup latency is under 100 ms and a dashboard shows depth and oldest job age.

Deep dive: the hard parts

- **At-least-once means handlers must be idempotent.** A worker can finish the work and crash before marking it done. The job runs again. Design handlers so a repeat is harmless (Project 5).
- **Table bloat.** PostgreSQL never updates in place: every state change writes a new row version, and `VACUUM` cleans up. A busy queue table bloats fast. Keep the table small (delete or archive completed jobs) and tune autovacuum for it.
- **Retry storms.** If a downstream service is down, every job fails and retries together. Exponential backoff with jitter spreads retries. Pair with a circuit breaker (Project 9) per job kind.

Testing strategy

- Concurrency test: N workers, M jobs, assert each completed exactly once in the happy path.
- Crash test: kill a worker process with `SIGKILL` mid-job, assert the job completes later.
- Transaction test: enqueue inside a transaction that rolls back, assert no job exists.

Trade-offs, scaling and failure modes

- PostgreSQL queues comfortably handle thousands of jobs per second. Beyond that, or for fan-out to many consumers, move to Kafka or a dedicated broker.
- Long-running jobs hold a claim for a long time. Use a heartbeat that extends `locked_until`.
- The queue shares the database with your app. A huge backlog can slow the app. Watch it.

Stretch goals

- Unique jobs (at most one pending job per key).
- Cron-style recurring jobs (a preview of Project 28).
- Per-kind concurrency limits.

Skills practised

- M2 — Moving Data: message queues and async work.
- M5 — Reliability: retries with backoff, DLQ, idempotency.

In the interview

30-second answer: I built a background job queue on PostgreSQL itself: workers claim batches with `SELECT ... FOR UPDATE SKIP LOCKED`, run them, retry failures with exponential backoff and jitter, and move jobs to a dead state after N attempts. The key decision was using the database I already had, because the job is inserted in the same transaction as the business change, so "order saved but email job lost" cannot happen. The hardest part was a worker dying mid-job, which I solved with a `locked_until` visibility timeout and a reaper that makes stale claims available again. It handles about 1,000 jobs/s with 8 workers on a laptop, with p50 pickup under 100 ms thanks to `LISTEN/NOTIFY`.

Key terms to know:

- **SKIP LOCKED** — a PostgreSQL row-locking option that skips rows another transaction has locked, so many workers can claim different jobs without waiting on each other.
- **Transactional enqueue** — inserting the job row in the same transaction as the business write, so both commit or neither does.

- **At-least-once delivery** — every job runs one or more times, never zero. Duplicates are possible after a crash.
- **Idempotent handler** — a job handler that can run twice with the same effect as once. Required because of at-least-once.
- **Visibility timeout (`locked_until`)** — a claim expires if the worker does not finish or extend it, so a dead worker's job is retried.
- **Exponential backoff with jitter** — wait `base * 2^attempts` plus a random amount before retrying, so failing jobs do not retry in lockstep.
- **Dead-letter queue (DLQ)** — where jobs go after too many failures, for a human to inspect and re-queue.
- **LISTEN/NOTIFY** — PostgreSQL's built-in pub/sub, used to wake idle workers instantly instead of polling.
- **MVCC bloat** — PostgreSQL writes a new row version on every update, so a busy queue table fills with dead rows that `VACUUM` must clean.

Q: What does `SKIP LOCKED` do, and why does it matter here?

A: A normal `FOR UPDATE` waits if another transaction already locked the row. With `SKIP LOCKED`, the query simply ignores locked rows and takes the next free ones. So 8 workers running the same claim query each get different jobs immediately, instead of queuing behind one another.

Q: Why not just use Kafka or RabbitMQ?

A: At thousands of jobs per second, a PostgreSQL queue gives you transactional enqueue and one less system to operate, back up and monitor. A separate broker cannot join your database transaction, so you would need an outbox (Project 14) to get the same guarantee. Kafka wins at much higher volume or when many independent consumers need the same events.

Q: A worker dies halfway through a job. What happens?

A: Its claim has a `locked_until` deadline. If the worker neither finishes nor extends it, the reaper sets the job back to available and another worker runs it. Long jobs send a heartbeat that pushes `locked_until` forward, so they are not stolen while still running.

Q: What delivery guarantee do you give, and how do you get exactly-once effects?

A: At-least-once. A worker can finish the work and crash before marking the job done, so the job runs again. Exactly-once effects come from idempotent handlers, for example by passing an idempotency key to the payment provider or using an upsert.

Q: A downstream email provider is down for 10 minutes. What happens to the queue?

A: Every email job fails and retries. Exponential backoff with jitter spreads the retries out so they do not hammer the provider the moment it comes back. A circuit breaker per job kind can pause that kind entirely, and jobs that exhaust their attempts land in the DLQ to be replayed later.

Q: What breaks first as volume grows?

A: Table bloat and vacuum pressure, because every state change creates a dead row version. Then the queue starts competing with the application for the same database's CPU and I/O. Keep the jobs table small by deleting or archiving completed jobs, tune autovacuum for it, and move to a dedicated broker when you outgrow that.

Q: Why poll at all if you have LISTEN/NOTIFY?

A: NOTIFY is a hint, not a guarantee. A worker that was disconnected misses notifications, and jobs with a future `run_at` time need no insert to become ready. So workers wake on NOTIFY for low latency but still poll on a slow timer as a safety net.

Q: How do you prove nothing is lost or run twice in the happy path?

A: A concurrency test runs N workers over M jobs and asserts each completed exactly once. A crash test sends `SIGKILL` to a worker mid-job and asserts the job completes later. A transaction test enqueues inside a transaction that rolls back and asserts no job row exists.

Q: Hands-on: what does the claim query look like?

A: One statement claims and marks a batch atomically:

```
UPDATE job SET state='running', locked_until=now()+interval '5 min'
WHERE id IN (SELECT id FROM job
  WHERE state='available' AND run_at <= now()
  ORDER BY priority, run_at
  FOR UPDATE SKIP LOCKED LIMIT 10)
RETURNING *;
```

Common mistakes in answers:

- Claiming the queue gives exactly-once execution. It gives at-least-once, and handlers must be idempotent.
- Forgetting the visibility timeout, so a crashed worker's job stays "running" forever.
- Ignoring MVCC bloat, which is the usual reason PostgreSQL queues slow down over time.

TL;DR

`SKIP LOCKED` turns PostgreSQL into a solid job queue with transactional enqueue. Add backoff, a DLQ and a reaper, and make every handler idempotent.

5. Idempotent payments API

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M5, M17

What it is

A tiny "charge" API that accepts an `Idempotency-Key` header. If the client retries the same request with the same key, the server returns the original result instead of charging twice. You build the key store, the request fingerprint check, the in-progress lock and a fake payment processor that randomly times out.

The problem it solves

Networks fail in the worst place: after the server did the work but before the client heard back. The client cannot know whether the charge happened, so it retries. Without idempotency, the customer pays twice. **Idempotent** means doing an operation twice has the same effect as doing it once.

Real-world examples

- Stripe's Designing robust and predictable APIs with idempotency explains why clients retry and how keys make retries safe.
- Brandur Leach's Implementing Stripe-like idempotency keys in Postgres walks through recovery points and atomic phases in a real schema.
- The IETF draft The Idempotency-Key HTTP header field is standardising the header.

Requirements


Functional

- `POST /charges` with `Idempotency-Key`, amount, currency and customer.
- Same key and same body: return the stored response with the same status code.
- Same key and different body: return `422` (the key was reused for something else).
- Same key while the first request is still running: return `409` and let the client retry later.
- Keys expire after 24 hours.

Non-functional


- Zero double charges under 1,000 concurrent retries of the same key.
- Overhead under 5 ms p99 per request.

The architecture



- **Charges API**: owns the key lifecycle.
- **PostgreSQL**: one table for keys, one for charges. The unique constraint on the key is the lock.
- **Fake processor**: simulates a card network. It also accepts the key, so a retry after a timeout does not double charge downstream either.

Data model



Tech stack

Component	Choice	Why
API	Spring Boot 4.1.1 or FastAPI	Middleware or filter for key handling
Store	PostgreSQL	Unique constraint gives an atomic first-writer-wins
Amounts	`numeric` or integer minor units	Never floats for money

Milestones

1. **Plain charge API.** Done when a charge is stored and returned.
2. **Key table and replay.** Done when a retry returns the identical stored response.
3. **Fingerprint check.** Hash method, path and body. Done when a mismatched body returns 422.
4. **In-progress handling.** Done when 1,000 concurrent identical requests produce exactly one charge, one 201 and the rest 409 or the replayed 201.
5. **Recovery.** If the API crashes after calling the processor, a retry must reconcile by asking the processor about key K. Done when a crash injected at each step never double charges.

Deep dive: the hard parts

- **Where to crash.** List each step and ask "what if the process dies right here?". Before the processor call: safe to retry. After the call but before storing the response: you must look up the outcome downstream, not charge again. This is why the processor also needs the key.
- **Stale locks.** A crashed request leaves the key in `started` forever. Allow a retry to take over after `locked_at` is older than a timeout.

- **Scope keys.** Keys are unique per account, not globally. Otherwise one customer's key could collide with another's.

Testing strategy

- Table-driven crash tests: inject a failure at each step, retry, assert one charge.
- Concurrency test with many threads and the same key.
- Expiry test: after 24 hours (fake clock), the same key is treated as new.

Trade-offs, scaling and failure modes

- Storing full responses costs space. 24-hour expiry with a nightly delete keeps it bounded.
- Keys add a write per request. For read-only GETs they are unnecessary, since GETs are naturally idempotent.
- The client must generate a new key per intent and reuse it only for retries. Document this clearly.

Stretch goals

- A client SDK that generates keys and retries with backoff and jitter automatically.
- Move the key store to Redis with `SET NX` and compare the failure behaviour honestly.

Skills practised

- M5 — Reliability: idempotency, timeouts, retries.
- M17 — Case Studies: Money and Reservations: how money moves and why double charges matter.

In the interview

30-second answer: I built a charges API that takes an `Idempotency-Key` header, so a client retrying after a timeout gets the original response instead of a second charge. The key decision was to use a PostgreSQL unique constraint on (account, key) as the lock, because an insert either wins or fails atomically and needs no separate lock service. The hardest part was a crash after the processor charged the card but before I stored the response, which I solved by passing the same key to the processor and reconciling on retry. Under 1,000 concurrent retries of the same key it produced exactly one charge, with under 5 ms p99 overhead.

Key terms to know:

- **Idempotency** — doing an operation twice has the same effect as doing it once. The whole API is built around it.
- **Idempotency key** — a unique value the client generates per intent and reuses only on retries. Scoped per account here.
- **Request fingerprint** — a hash of method, path and body stored with the key. A different body with the same key returns `422`.
- **First-writer-wins** — the unique constraint lets exactly one insert of a key succeed. That insert owns the request.
- **In-progress state (409)** — a second request arriving while the first is still `started` gets `409 Conflict` and retries later.
- **Stale lock takeover** — if `locked_at` is older than a timeout, a retry may take over a request left behind by a crash.
- **Recovery point / reconciliation** — after a crash, ask the processor what happened to key K instead of charging again.
- **Minor units** — store money as integer cents or `numeric`, never as floating point.
- **Key expiry** — keys live 24 hours, then a nightly job deletes them to bound storage.

Q: What is an idempotency key, and why is it needed?

A: It is a unique token the client attaches to a request that changes state. If the network fails after the server charged but before the client heard back, the client cannot know whether it worked, so it retries with the same key. The server sees the key, finds the stored result and returns it instead of charging again.

Q: Why can't the server detect duplicates by amount and customer?

A: Two real purchases of the same amount by the same customer are legal, such as two coffees. Only the client knows whether a request is a retry of an earlier attempt or a new intent. That is why the client must generate the key.

Q: What if the same key arrives while the first request is still running?

A: The first request inserted the key with status `started`. The second sees that row and returns `409`, so the client backs off and retries. An alternative is to block briefly until the first finishes, but that ties up server threads.

Q: Your server crashes right after the processor charged the card. What happens on retry?

A: The retry finds the key stuck in `started` with an old `locked_at`, so it takes over. It does not charge again. It asks the processor about key K, because the processor also received the key, and records the true outcome. If the processor says nothing happened, it is safe to charge.

Q: Why return 422 when the body differs?

A: It means the client reused a key for a different request, which is a bug. Replaying the old response would hide the bug, and processing the new body would break the "one key, one intent" rule. A clear error makes the client fix it.

Q: Why PostgreSQL instead of Redis `SET NX` for the key store?

A: In PostgreSQL the key row and the charge row can be written in the same transaction, and both are durable. Redis is faster, but a failover can lose a recent write, which would let a retry charge twice. For money, durability wins over a few milliseconds.

Q: What changes at 10x the volume?

A: Every POST adds a write and a lookup on the key table, so it grows fast. Shard it by account ID along with the charges, keep the 24-hour expiry with a nightly delete, and partition the table by day so cleanup is a cheap partition drop instead of a big `DELETE`.

Q: How do you test that you never double charge?

A: Table-driven crash tests inject a failure at every step (before the insert, after the processor call, before storing the response), retry, and assert exactly one charge. A concurrency test fires 1,000 identical requests and asserts one 201 and the rest 409 or replayed 201. A fake clock tests 24-hour expiry.

Common mistakes in answers:

- Saying the server can generate the idempotency key. It must come from the client, or a retry looks like a new request.
- Forgetting the crash-after-charge case. The processor must also receive the key so you can reconcile instead of re-charging.
- Making keys global instead of per account, which lets one customer's key collide with another's.

TL;DR

An idempotency key plus a unique constraint, a request fingerprint and crash-aware recovery turns "maybe charged" into "charged exactly once".

6. Webhook delivery service

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M2, M5

What it is

A service that lets your platform notify customers' servers when something happens ("invoice paid") by sending an HTTP POST to a URL they register. It signs each message, retries failures with backoff, isolates slow receivers and lets customers replay missed events.

The problem it solves

Customers need to react to events without polling. But their endpoints are slow, flaky, misconfigured or down for hours. A naive "POST in the request thread" blocks your app and loses events. A delivery service must be durable, retry patiently, never let one bad endpoint delay everyone else, and prove to receivers that a message really came from you.

Real-world examples

- Stripe's webhooks guide covers signature verification, retries over several days, and the advice to return 2xx quickly and process asynchronously.
- Standard Webhooks is an open specification for webhook headers and signing.
- Svix is an open-source webhook sending service you can read for design ideas.

Requirements


Functional

- Customers register endpoints with a URL and the event types they want.
- Producers publish events. The service fans each event out to matching endpoints.
- Each delivery carries an ID, a timestamp and an HMAC signature (a hash keyed with a shared secret).
- Retries on non-2xx or timeout, on a schedule over about 24 hours, then mark failed.
- Endpoints that fail for days are auto-disabled. Customers can replay a time range.

Non-functional


- First attempt within 2 s of the event at 500 events/s.
- One endpoint timing out must not delay deliveries to others.
- Per-attempt timeout 10 s. No event lost once accepted.

The architecture



- **Ingest API**: stores the event and one pending delivery per subscribed endpoint, in one transaction.
- **Dispatcher**: claims due deliveries (the Project 4 pattern) and hands them to workers.
- **Per-endpoint pools**: a **bulkhead**, meaning each endpoint gets a small capped concurrency so a slow one cannot use all workers.
- **Portal**: delivery log, retry button, replay.

Data model



Tech stack

Component	Choice	Why
Service	Java 25 with virtual threads, or Python 3.14 with httpx async	Thousands of concurrent outbound calls
Store	PostgreSQL	Durable queue and audit log
Signing	HMAC-SHA256	Standard, simple to verify
Test receivers	A tiny mock server with configurable failures	Reproduce bad endpoints

Milestones

1. **Register, publish, deliver once.** Done when a mock receiver gets the event.
2. **Signing.** Sign `id.timestamp.body`. Done when a sample receiver verifies and rejects tampered bodies and old timestamps (replay protection).
3. **Retries.** Schedule such as 5 s, 30 s, 2 min, 10 min, 1 h, then hourly. Done when a receiver down for 20 minutes eventually receives everything.
4. **Bulkheads.** Done when one endpoint sleeping 10 s per request does not raise p99 first-attempt latency for others.
5. **Auto-disable, portal and replay.** Done when replaying a range re-sends exactly those events with the same event IDs.

Deep dive: the hard parts

- **At-least-once and receiver dedup.** You will sometimes deliver twice (timeout after the receiver processed it). Send a stable event ID and tell receivers to dedupe on it.
- **Ordering.** Retries reorder events: "invoice updated" may arrive before "invoice created". Either document that order is not guaranteed and include a version or timestamp, or deliver per endpoint strictly in order, which means one stuck event blocks the rest.
- **SSRF.** Server-side request forgery: a customer registers `http://169.254.169.254/` (a cloud metadata address) or an internal IP and your service fetches it. Resolve DNS, block private ranges, and re-check on every attempt because DNS can change.

Testing strategy

- A chaos receiver that returns 500, times out, closes connections, or returns 200 slowly.
- Assert every event is eventually delivered or marked failed, never silently dropped.
- Signature tests with known vectors.

Trade-offs, scaling and failure modes

- Fan-out multiplies load: one event to 10,000 endpoints is 10,000 jobs. Partition deliveries by endpoint across dispatcher instances.
- A large backlog after a receiver outage can flood it when it recovers. Ramp up gradually per endpoint.

Stretch goals

- Kafka in front of ingest for very high volume.
- Secret rotation with two valid signatures during the overlap.

Skills practised

- M2 — Moving Data: webhooks and push delivery.
- M5 — Reliability: retries, bulkheads, DLQ.
- M8 — API and Edge: security at the boundary.

In the interview

30-second answer: I built a webhook delivery service that stores each event plus one pending delivery per subscribed endpoint in a single transaction, then dispatches signed HTTP POSTs with retries over about 24 hours. The key decision was per-endpoint worker pools (bulkheads), because customer endpoints are slow and flaky and one hanging receiver must never delay everyone else. The hardest parts were security and duplicates: every message carries an HMAC-SHA256 signature over ID, timestamp and body, I block private IP ranges to stop SSRF, and receivers dedupe on a stable event ID because delivery is at-least-once. First attempts go out within 2 s at 500 events/s, and no accepted event is lost.

Key terms to know:

- **Webhook** — an HTTP POST your platform sends to a URL the customer registered, telling them an event happened.
- **Fan-out** — one event becomes one delivery row per matching endpoint. One event to 10,000 endpoints is 10,000 jobs.
- **HMAC signature** — a hash of the message keyed with a shared secret. The receiver recomputes it to prove the sender and detect tampering.
- **Replay protection** — the signed timestamp must be within a tolerance (say 5 minutes), so an attacker cannot resend an old captured message.
- **At-least-once delivery** — a timeout after the receiver processed a message causes a resend. Receivers dedupe on the event ID.

- **Bulkhead** — a capped concurrency pool per endpoint, so a slow endpoint can only use its own few workers.
- **Retry schedule with backoff** — 5 s, 30 s, 2 min, 10 min, 1 h, then hourly, up to about 24 h, then mark failed.
- **SSRF (server-side request forgery)** — tricking your server into calling internal addresses such as the cloud metadata IP `169.254.169.254`.
- **Auto-disable and replay** — endpoints failing for days are switched off, and customers can re-send a time range with the same event IDs.

Q: How does a receiver know the call really came from you?

A: Each delivery has an HMAC-SHA256 signature over `id.timestamp.body` computed with a secret only you and the customer know. The receiver recomputes it with a constant-time compare and rejects mismatches. It also rejects timestamps older than a few minutes, so a captured message cannot be replayed later.

Q: Why not send the webhook directly from the request that caused the event?

A: The customer's endpoint might take 10 seconds or be down, which would block your user-facing request and lose the event on failure. Writing the event and its deliveries to PostgreSQL in the same transaction makes it durable. Dispatchers then deliver it asynchronously with retries.

Q: One customer's endpoint hangs for 10 seconds on every call. What protects others?

A: Each endpoint has a small capped worker pool and a 10 s per-attempt timeout. The hanging endpoint fills only its own pool, and its other deliveries wait in the database. Workers for every other endpoint keep running at normal speed.

Q: Can you guarantee exactly-once delivery?

A: No. If the receiver processes the message but your request times out before you get the 2xx, you must retry, so it arrives twice. You guarantee at-least-once and send a stable event ID so receivers can dedupe, for example with a unique index on processed event IDs.

Q: Do webhooks arrive in order?

A: Not by default, because retries reorder them: "invoice updated" can arrive before "invoice created". You either document that order is not guaranteed and include a version or timestamp so receivers can ignore stale events, or deliver strictly in order per endpoint. Strict order means one stuck event blocks all later ones for that endpoint.

Q: What is SSRF, and how do you stop it here?

A: A customer registers a URL that points at an internal address, such as a metadata service or an admin panel, and your server fetches it from inside your network. You resolve DNS yourself, block private, loopback and link-local ranges, and connect to the checked IP. You re-check on every attempt because DNS answers can change between registration and delivery.

Q: A big customer's endpoint was down for 6 hours and just came back. What could go wrong?

A: Thousands of queued deliveries are now due at once and can flood the endpoint, knocking it straight back over. Ramp up concurrency for that endpoint gradually and keep the bulkhead cap. Their backlog must not starve other endpoints of dispatcher capacity.

Q: What changes at 10x the events?

A: Fan-out multiplies writes, so the deliveries table becomes the bottleneck. Partition deliveries by endpoint across dispatcher instances so each one owns a slice. Put Kafka in front of ingest to absorb bursts, and archive old delivery rows.

Q: How do you test it?

A: A chaos receiver returns 500s, times out, drops connections or answers slowly. Tests assert every event is eventually delivered or marked failed, never silently dropped. Signature tests use known vectors, and a latency test checks that one sleeping endpoint does not raise others' p99.

Common mistakes in answers:

- Promising exactly-once delivery. It is at-least-once plus receiver dedup on the event ID.

- Retrying with a fixed short interval forever, which hammers a down endpoint and never gives up.
- Forgetting SSRF. Fetching arbitrary customer URLs from inside your network is a real security hole.

TL;DR

Durable fan-out, signed messages, patient retries, per-endpoint isolation and SSRF protection are what turn "POST a URL" into a webhook platform.

7. Real-time leaderboard

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** M4, M15

What it is

A game leaderboard API: players submit scores, and anyone can ask for the top 100, a player's rank, or the players just above and below them. Updates appear within a second. You build it on Redis **sorted sets**, a data structure that keeps members ordered by a numeric score with logarithmic-time inserts and rank lookups.

The problem it solves

`SELECT ... ORDER BY score DESC` with `COUNT(*)` to find a rank works for thousands of players and collapses at millions, because computing one player's rank means counting everyone above them. A leaderboard needs rank queries in milliseconds while scores change constantly.

Real-world examples

- Redis's sorted sets documentation uses a leaderboard as its main example and lists the complexity of `ZADD`, `ZRANK` and `ZRANGE`.
- Module 15 of this book works through the full leaderboard case study, including sharding.

Requirements


Functional

- `POST /scores {player, score}` (keep the best or add points, configurable per board).
- `GET /boards/{id}/top?n=100`, `GET /boards/{id}/players/{p}` (rank and score), `GET .../around?n=5`.
- Daily, weekly and all-time boards.
- Ties broken by who reached the score first.

Non-functional


- 10 million players per board, 5,000 score updates/s, 20,000 reads/s.
- p99 under 10 ms for rank and top-N.
- Boards survive a Redis restart.

The architecture



- **Leaderboard API**: validates scores (anti-cheat hooks go here) and writes to both stores.
- **Redis**: one sorted set per board and period, for example `lb:global:2026-W40`.
- **PostgreSQL score log**: the durable record. The rebuild job can recreate any board from it.

Data model



Tech stack

Component	Choice	Why
Ranking	Redis sorted sets	O(log N) updates and ranks
Durability	PostgreSQL append-only log, plus Redis AOF	Rebuild from truth
API	Spring Boot 4.1.1 or FastAPI	Thin layer

Milestones

1. **Single all-time board.** Done when top-N and rank work for 1 million seeded players.
2. **Best-score vs. additive modes.** Use `ZADD GT` (only raise) or `ZINCRBY`. Done when both behave correctly.
3. **Tie-breaking.** Encode the score as `score * 2^20 + (MAX_TS - seconds_since_season_start)` in a double-safe range, so earlier achievers rank higher. Done when ties order by time.
4. **Periodic boards with expiry.** Done when weekly keys expire after the season plus a grace period.
5. **Rebuild from PostgreSQL.** Done when flushing Redis and running the job restores identical ranks.

Deep dive: the hard parts

- **Score precision.** Redis stores scores as 64-bit floats, exact only up to 2^53. Packing a tie-breaker into the score must stay below that.

- **Display names.** Do not put names in the sorted set member. Store player IDs and fetch names with a pipelined `HMGET` or a cached lookup.
- **Very large boards.** A single sorted set lives on one Redis node. For hundreds of millions of players, shard by score range or accept approximate ranks for the long tail ("top 37%") and exact ranks for the top.

Testing strategy

- Compare Redis ranks against a SQL window function (`RANK() OVER`) on the same data.
- Load test with k6: mixed reads and writes at target rates.
- Restart Redis without persistence and verify the rebuild path.

Trade-offs, scaling and failure modes

- Dual writes (Redis and PostgreSQL) can diverge if one fails. Treat PostgreSQL as truth and rebuild Redis, or write to PostgreSQL first and update Redis from a change stream (Project 14).
- Read replicas of Redis can serve top-N reads, with slight lag.

Stretch goals

- Friends leaderboard: intersect a friends set with the global board (`ZINTER`).
- Live top-10 pushed to clients over SSE (Project 8).

Skills practised

- M4 — Caching: Redis data structures beyond key-value.
- M15 — Case Studies: Location and Real-Time: the leaderboard case study.

In the interview

30-second answer: I built a leaderboard API on Redis sorted sets, one per board and period, so top-N and "what is my rank" are O(log N) instead of counting every higher score in SQL. The key decision was to keep PostgreSQL as an append-only score log and treat Redis as a rebuildable view, because Redis is fast but can lose data. The hardest part was tie-breaking, which I solved by folding the time a player reached the score into the sorted-set score while staying under 2^53, the largest integer a 64-bit float holds exactly. With 10 million players per board it serves rank and top-N under 10 ms p99.

Key terms to know:

- **Sorted set (ZSET)** — a Redis structure that keeps unique members ordered by a numeric score, with O(log N) insert and rank lookup.
- **`ZADD GT` / `ZINCRBY`** — "only raise the score" for best-score boards, and "add points" for additive boards.
- **`ZREVRANK` / `ZREVRANGE`** — get a member's rank and a range of members from highest to lowest score.
- **Tie-breaking** — ordering equal scores by who got there first, encoded into the score itself.
- **Float precision (2^53)** — Redis scores are 64-bit floats, exact for integers only up to 2^53. The packed score must stay below that.
- **Periodic boards** — separate keys per period, such as `lb:global:2026-W40` , that expire after the season.
- **Source of truth vs derived view** — PostgreSQL holds the durable score log. Redis can be rebuilt from it.
- **Dual write** — writing to two stores in one request. They can diverge if one write fails.
- **Hot shard** — one sorted set lives on one Redis node, which limits how large a single board can grow.

Q: Why not just use SQL with `ORDER BY score DESC` ?

A: Top-N with an index is fine, but a player's rank means counting everyone with a higher score, which is O(N) per query. With 10 million players and 20,000 reads/s that is far too slow. A sorted set is a skip list that tracks span counts, so a rank lookup is O(log N).

Q: How do you break ties?

A: Pack the score and a time component into one number, such as `score * 2^20 + (MAX_TS - seconds_since_season_start)`. Higher scores still win, and among equal scores the earlier achiever has a larger value. The whole number must stay below 2^53 or the float loses precision and ties order randomly.

Q: Redis restarts and loses the board. Now what?

A: Rebuild it from the PostgreSQL score log, which the rebuild job replays into a fresh sorted set. Redis AOF persistence shortens the gap, but the log is the real guarantee. My test flushes Redis, runs the rebuild and checks that ranks match exactly.

Q: You write to Redis and PostgreSQL in the same request. What if one fails?

A: They diverge. Simple fix: treat PostgreSQL as truth and periodically rebuild or reconcile Redis. Stronger fix: write only to PostgreSQL, then update Redis from a change stream (Project 14), so Redis can never get a score the database does not have.

Q: Why store player IDs instead of display names in the sorted set?

A: Names change, and a member's identity in the set must be stable or the player appears twice. IDs are also smaller. Names are fetched for the top 100 with a pipelined `HMGET` or a cached lookup.

Q: What happens at 500 million players?

A: A single sorted set must fit on one Redis node, and every update to it goes through one CPU core. You can shard by score range so each node holds a band, with ranks computed as "players in higher bands plus rank in my band". Or keep exact ranks for the top and show percentiles ("top 37%") for the long tail.

Q: How do you serve 20,000 reads/s?

A: Most reads are the top 100, which is the same for everyone, so cache that result for a second or serve it from Redis replicas with slight lag. Rank queries are per player and go to the primary or a replica depending on how fresh they must be.

Q: How do you prove the ranks are right?

A: Load the same data into PostgreSQL and compare Redis ranks with `RANK() OVER (ORDER BY score DESC)`, a SQL window function. A k6 load test runs mixed reads and writes at the target rates. A restart test without persistence exercises the rebuild path.

Common mistakes in answers:

- Treating Redis as the durable store. It is a fast derived view that must be rebuildable.
- Encoding tie-breakers without considering float precision, so large scores silently lose the tie-break.
- Assuming one sorted set scales forever. It lives on one node and one core.

TL;DR

Sorted sets make rank queries logarithmic. Keep a durable log for rebuilds and be careful with float precision and tie-breaks.

8. Live notifications with pub/sub and SSE

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M2

What it is

A notification service that pushes events ("Ana commented on your post") to users' open browser tabs within a second, using **Server-Sent Events** (SSE: a long-lived HTTP response the server keeps writing

lines to). Several app servers share events through **Redis pub/sub**, a fire-and-forget broadcast channel. A durable inbox in PostgreSQL covers users who were offline.

The problem it solves

Polling every few seconds wastes requests and still feels slow. Push needs a persistent connection, and with many app servers the event is produced on one server while the user's connection lives on another. You need a fan-out layer between them and a fallback so nothing is lost when the user is offline.

Real-world examples

- MDN's Server-sent events guide documents `EventSource`, automatic reconnection and the `Last-Event-ID` header.
- Uber's real-time push platform describes RAMEN, the push system that replaced polling in its apps (its first version was built on SSE).

Requirements


Functional

- Users receive notifications in real time on any open tab.
- Notifications are stored. Users see unread ones on login and can mark them read.
- Reconnecting clients receive anything they missed since their last event ID.

Non-functional

- 10,000 concurrent connections per server instance.
- Event to screen under 1 s p95.
- Server restart: clients reconnect automatically and miss nothing.

The architecture



- **Inbox in PostgreSQL**: durable list per user. The notification ID doubles as the SSE event ID.
- **Redis pub/sub**: each SSE server subscribes to a channel per connected user (or a sharded set of channels).
- **SSE servers**: hold connections, send heartbeats, and on reconnect query the inbox for IDs greater than `Last-Event-ID`.

Data model

NOTIFICATION		
bigint	id	PK
bigint	user_id	
text	kind	
jsonb	body	
boolean	read	
timestamptz	created_at	

Tech stack

Component	Choice	Why
SSE server	Spring WebFlux or Spring MVC with virtual threads, or Python Starlette	Many idle connections cheaply
Fan-out	Redis pub/sub	Simple broadcast across servers
Inbox	PostgreSQL	Durable, queryable by user and ID
Client	Browser `EventSource`	Built-in reconnect

Milestones

1. **Single server SSE.** Done when a curl client sees events as they are produced.
2. **Inbox and catch-up.** Done when a client that reconnects with `Last-Event-ID` gets exactly the missed events.
3. **Multi-server fan-out via Redis.** Done when a producer on server A reaches a user connected to server B.
4. **Heartbeats and timeouts.** Send a comment line every 15 s so proxies keep connections open. Done when connections survive 10 minutes idle behind Nginx.
5. **Load test.** Done when one instance holds 10,000 connections with stable memory.

Deep dive: the hard parts

- **Pub/sub is not durable.** If a server is restarting when the message is published, the message is gone. That is why the inbox exists: pub/sub is the fast path, the database is the safety net.
- **Write then publish ordering.** Publish only after the database commit, otherwise a fast client could reconnect, query the inbox and not find the event yet.
- **Connection limits.** Each SSE connection is an open socket. Tune file-descriptor limits, and know that browsers cap HTTP/1.1 connections per domain (around six). HTTP/2 multiplexing removes that limit.

Testing strategy

- Kill an SSE server, assert clients reconnect to another and lose nothing.
- Publish during a Redis outage, assert catch-up delivers on reconnect.
- Use many lightweight clients (a k6 SSE script or a custom asyncio client) for the connection test.

Trade-offs, scaling and failure modes

- SSE is one-way. For typing indicators or chat, use WebSockets (Project 13).
- Redis pub/sub sends every message to every subscriber of the channel. For millions of users, shard channels or switch to Redis Streams or Kafka with per-server routing.

Stretch goals

- Batched digests: collapse "10 people liked your post" into one notification.
- Mobile push fallback when no tab is open.

Skills practised

- M2 — Moving Data: pub/sub, SSE, push vs. poll.
- M18 — Client and Mobile System Design: push and reconnect behaviour on the client.

In the interview

> **30-second answer:** I built a notification service that pushes events to open browser tabs over Server-Sent Events, with Redis pub/sub carrying each event to whichever server holds the user's connection. The key decision was to treat pub/sub as the fast path only and keep a durable inbox in

PostgreSQL, because pub/sub drops messages when a subscriber is offline. The hard part was never losing a notification across reconnects, which I solved by using the inbox row ID as the SSE event ID and replaying everything after `Last-Event-ID` when a client reconnects. One instance held 10,000 connections with stable memory, and events reached the screen in under 1 s p95.

Key terms to know:

- **Server-Sent Events (SSE)** — a long-lived HTTP response the server keeps writing `data:` lines to. One-way, server to client.
- **EventSource** — the browser API for SSE. It reconnects automatically and sends the last seen ID.
- **Last-Event-ID** — the header a reconnecting client sends, so the server can replay what was missed.
- **Redis pub/sub** — fire-and-forget broadcast to whoever is subscribed right now. Nothing is stored.
- **Durable inbox** — the PostgreSQL notification table. It makes delivery reliable and powers the unread list.
- **Write-then-publish** — commit to the database before publishing, so a fast reconnect always finds the event.
- **Heartbeat** — a comment line every 15 s so proxies and load balancers do not close an idle connection.
- **Connection fan-out problem** — the event is produced on server A while the user's socket is on server B.
- **File-descriptor limit** — every open connection is a socket, and the OS caps how many a process may hold.

Q: Why SSE over WebSockets here?

A: Notifications only flow from server to client. SSE is plain HTTP, passes through proxies and load balancers easily, and the browser reconnects on its own with a resume point. WebSockets are two-way, which this feature does not need, and you would have to build reconnect and resume yourself.

Q: Why not just poll every few seconds?

A: Polling sends a request from every user every few seconds even when nothing happened, which wastes most of the load. It still adds up to one interval of delay. A held-open connection costs a little memory and delivers the moment an event exists.

Q: The user's tab is connected to server B, but the event is created on server A. How does it get there?

A: Server A publishes to a Redis channel for that user. Every SSE server subscribes to the channels of the users connected to it, so server B receives the message and writes it to the stream. The producer never needs to know where the user is.

Q: How do you avoid losing notifications?

A: Store first, publish second. The notification is committed to the inbox, then published. If the publish is lost because a server was restarting, the client reconnects with `Last-Event-ID` and the server queries the inbox for any IDs greater than that, so the event is delivered anyway.

Q: Why must you publish only after the commit?

A: If you publish first, a client can receive the event, or reconnect and query the inbox, before the row is visible. The catch-up query would then miss it, and the client's last ID could skip past it. Commit-then-publish keeps the inbox and the stream consistent.

Q: An SSE server crashes. What happens to its 10,000 users?

A: Their connections drop, and `EventSource` reconnects through the load balancer to another server with its last event ID. That server subscribes to their channels and replays missed events from the inbox. To avoid all 10,000 reconnecting in the same second, the server sends a `retry:` value and clients add jitter.

Q: What breaks first at a million connected users?

A: Redis pub/sub delivers each message to every subscriber of a channel, and one Redis becomes a CPU and network bottleneck as servers and channels multiply. Shard channels across Redis nodes, or route events through Redis Streams or Kafka partitioned by user so each server consumes only its users. On the servers, file-descriptor limits and memory per connection need tuning.

Q: Why does a browser sometimes stop opening new SSE connections?

A: Over HTTP/1.1, browsers allow about six connections per domain, and each SSE stream holds one open. A user with many tabs runs out. HTTP/2 multiplexes many streams over one connection, which removes that limit.

Q: How do you test it?

A: Kill an SSE server and assert clients reconnect elsewhere and lose nothing. Publish during a Redis outage and assert catch-up delivers on reconnect. A load test with many lightweight asyncio clients checks that one instance holds 10,000 connections with stable memory.

Common mistakes in answers:

- Treating Redis pub/sub as reliable. It drops messages when no one is listening, so a durable inbox is required.
- Publishing before the database commit, which creates a window where catch-up misses the event.
- Choosing WebSockets by default for a one-way feed, adding complexity without benefit.

TL;DR

Durable inbox for correctness, pub/sub for speed, SSE with event IDs for seamless reconnects.

9. Resilient aggregator (BFF)

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M5, M8

What it is

A **backend-for-frontend** (BFF: an API tailored to one client screen) that builds a product page by calling four downstream services: catalog, pricing, reviews and recommendations. You deliberately make the downstreams flaky and add timeouts, retries, circuit breakers, bulkheads and fallbacks until the page stays fast and mostly complete no matter what fails.

The problem it solves

A page that depends on four services fails if any one fails, unless you design for it. Worse, a slow dependency ties up threads until the whole BFF stops responding: a **cascading failure**. The patterns in Module 5 exist to contain that.

Real-world examples

- Martin Fowler's CircuitBreaker article defines the closed, open and half-open states.
- Resilience4j's circuit breaker docs describe the sliding-window failure rate calculation you will configure.
- Netflix's Hystrix (now in maintenance) popularised bulkheads and fallbacks. Its README explains the motivation.
- AWS's Timeouts, retries and backoff with jitter explains why retries need jitter and limits.

Requirements


Functional

- `GET /product-page/{id}` returns catalog (required), price (required), reviews and recommendations (optional).
- If an optional part fails, return the page without it plus a flag. If pricing fails, use the last cached price marked stale.

Non-functional

- p99 under 300 ms even when any one downstream is slow or down.
- No thread or connection exhaustion under 500 requests/s with a dependency hanging.

The architecture



- **BFF**: calls downstreams in parallel, each with its own timeout, breaker and bulkhead.
- **Downstream stubs**: tiny services with configurable latency and error rate.
- **Redis last-known-good**: stores the latest good response per dependency for fallbacks.
- **Toxiproxy**: a proxy that injects latency, resets and timeouts between services.

Data model

State	Meaning
Closed	Calls flow. Failures counted in a sliding window
Open	Calls fail fast without touching the dependency, for a cool-down period
Half-open	A few trial calls allowed. Success closes, failure re-opens

Tech stack

Component	Choice	Why
BFF	Spring Boot 4.1.1 with Resilience4j, or Python with tenacity and a small breaker	Mature libraries
Fault injection	Toxiproxy	Realistic network failures
Observability	Micrometer or OpenTelemetry metrics	See breaker states live

Milestones

1. **Parallel fan-out.** Done when page latency equals the slowest call, not the sum.
2. **Timeouts per call.** Done when a hanging reviews service no longer slows the page past its budget.

3. **Circuit breakers.** Done when, at 50% errors, the breaker opens and the dependency gets almost no traffic until the cool-down.
4. **Bulkheads.** Cap concurrent calls per dependency. Done when a hang in one does not affect calls to others.
5. **Fallbacks.** Done when pricing outage serves stale prices with a flag, and the page still loads.
6. **Retries, carefully.** One retry with jitter for idempotent GETs, inside the overall budget. Done when transient 503s vanish without raising p99.

Deep dive: the hard parts

- **Timeout budgets.** If the page has 300 ms, child timeouts plus retries must fit inside it. Pass a deadline down so a retry that cannot finish in time is skipped.
- **Retry amplification.** If every layer retries three times, one failure at the bottom of a three-layer stack becomes 27 calls. Retry at one layer only, and use a retry budget (for example at most 10% extra requests).
- **Breaker tuning.** Too sensitive and it flaps on noise. Too slow and it does nothing. Use a minimum number of calls before judging and a failure-rate threshold.

Testing strategy

- Scripted Toxiproxy scenarios: latency 2 s on reviews, reset on pricing, 50% errors on recommendations.
- Assert p99 and response completeness for each scenario.
- Watch breaker state metrics during the tests.

Trade-offs, scaling and failure modes

- Stale prices can be wrong. Show them as such, and never use a stale price at checkout.
- Fallbacks add code paths that rarely run. Test them on a schedule, or they will be broken when you need them.

Stretch goals

- Adaptive concurrency limits (adjust in-flight caps from observed latency).
- Hedged requests: send a second copy of a slow call after the p95 latency and use whichever returns first.

Skills practised

- M5 — Reliability: timeouts, retries, circuit breaker, bulkhead, graceful degradation.
- M8 — API and Edge: the BFF pattern.

In the interview

30-second answer: I built a backend-for-frontend that assembles a product page from four services (catalog, pricing, reviews, recommendations) and then used Toxiproxy to make them slow, flaky and dead until the page stayed fast anyway. The key decision was calling all four in parallel, each with its own timeout, circuit breaker and bulkhead, and splitting them into required and optional parts with defined fallbacks. The hardest part was retries, because they can multiply load, so I allowed one jittered retry for idempotent GETs only and only inside the page's deadline. With any one dependency hanging, the page held p99 under 300 ms at 500 requests/s.

Key terms to know:

- **BFF (backend-for-frontend)** — an API shaped for one client screen that aggregates several backend services.
- **Cascading failure** — a slow dependency ties up threads until the caller also stops responding, and the failure spreads upward.
- **Timeout** — a limit on how long one call may take. Each dependency here has its own (80–150 ms).

- **Circuit breaker** — closed (calls flow), open (fail fast for a cool-down), half-open (a few trial calls). Stops calling a dependency that is clearly failing.
- **Bulkhead** — a cap on concurrent calls per dependency, so one hang cannot consume every thread or connection.
- **Fallback / graceful degradation** — what to return when a part fails: omit reviews, or show the last known price marked stale.
- **Deadline propagation** — passing the remaining time budget down so a retry that cannot finish is skipped.
- **Retry amplification and retry budget** — retries at every layer multiply calls. A budget caps retries at, say, 10% extra traffic.
- **Fault injection (Toxiproxy)** — a proxy that adds latency, resets or timeouts to test failure handling.

Q: What is the difference between a timeout and a circuit breaker?

A: A timeout bounds one call: wait at most 100 ms, then give up. A circuit breaker watches many calls, and once the failure rate crosses a threshold it stops calling the dependency for a cool-down period and fails instantly. That saves your latency and gives the struggling dependency room to recover.

Q: Why bulkheads if you already have timeouts?

A: At 500 requests/s with a 150 ms timeout, a hanging dependency still holds about 75 calls in flight at all times. Without a cap, those calls can use up the shared thread or connection pool and starve calls to healthy services. A bulkhead limits each dependency to its own small pool.

Q: Why call the four services in parallel?

A: In sequence, page latency is the sum of all four calls. In parallel it is roughly the slowest one. That is the only way four calls fit a 300 ms budget.

Q: When is retrying harmful?

A: For non-idempotent calls, where a retry can repeat a side effect such as a charge. And when a dependency is overloaded, because retries add load exactly when it can least take it. If three layers each retry three times, one failure at the bottom becomes 27 calls, so retry at one layer only and within a budget.

Q: Pricing is down. What does the page show?

A: Pricing is required, so the BFF serves the last known good price from Redis with a "stale" flag and the UI shows it as such. That is fine for browsing but never for checkout, which must fetch a live price. If there is no cached price either, the page shows "price unavailable" rather than failing entirely.

Q: How do you tune a circuit breaker so it does not flap?

A: Require a minimum number of calls in the sliding window before judging, so three errors out of four calls do not trip it. Use a failure-rate threshold such as 50% and a cool-down long enough for the dependency to recover. In half-open, allow a few trial calls and re-open on failure.

Q: What changes at 10x the traffic?

A: The BFF scales horizontally since it is stateless, but its fan-out hits every dependency 10x as well, so caching catalog data and recommendations becomes important. Bulkhead and connection-pool sizes need resizing from measured latency. Adaptive concurrency limits, which adjust in-flight caps from observed latency, replace hand-tuned numbers.

Q: How do you test that the resilience actually works?

A: Scripted Toxiproxy scenarios: 2 s latency on reviews, connection resets on pricing, 50% errors on recommendations. For each, assert p99 stays under budget and check which parts the response contains. Watching breaker state metrics during the test shows it opening and closing as expected.

Common mistakes in answers:

- Adding retries everywhere "for reliability", which multiplies load on a failing service.

- Treating a circuit breaker as a replacement for timeouts. You need both, plus bulkheads.
- Writing fallbacks that are never tested, so they fail the first time a real outage triggers them.

TL;DR

Parallel calls with per-dependency timeouts, breakers, bulkheads and honest fallbacks keep a page fast when its dependencies are not.

10. Feature flag service

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** M4, M9

What it is

A service plus SDK that lets teams turn features on or off, or roll them out to a percentage of users, without deploying. The SDK evaluates flags locally from a cached rule set and receives updates in near real time.

The problem it solves

Deploying and releasing are different things. Flags let you deploy code dark, release gradually, run experiments and kill a bad feature in seconds. The service must never become a dependency that can take your app down: evaluation has to work even when the flag server is unreachable.

Real-world examples

- Martin Fowler's site hosts Feature Toggles by Pete Hodgson, which classifies release, experiment, ops and permission toggles.
- OpenFeature is a CNCF vendor-neutral flag evaluation API. Model your SDK interface on it.
- Unleash is an open-source flag server with local SDK evaluation.

Requirements


Functional

- Flags have rules: on or off, percentage rollout, target user IDs or attributes.
- SDK `isEnabled(flag, context)` evaluates locally.
- Admin UI or API to edit flags, with an audit log.
- Changes reach SDKs within 5 s.

Non-functional


- Evaluation takes around a microsecond (pure in-memory work, no network call).
- If the server is down, SDKs keep the last rules and keep working for days.
- Same user always lands in the same bucket for a given flag.

The architecture



- **Admin API**: validates and stores flag changes, writes an audit row, publishes a change.
- **Flag delivery service**: serves the full rule set with a version (ETag) and streams updates.
- **SDK**: holds rules in memory, evaluates locally, writes a snapshot to disk for cold starts.

Data model



Tech stack

Component	Choice	Why
Server	Spring Boot 4.1.1 or FastAPI	CRUD plus SSE
Store	PostgreSQL	Audit and versions
Push	SSE plus Redis pub/sub between server instances	Same pattern as Project 8
Hashing	MurmurHash3 of `flag:user`	Stable, well distributed buckets

Milestones

1. **CRUD and audit.** Done when every change has a before and after row.
2. **SDK with polling.** Done when an app sees changes within the poll interval.
3. **Deterministic rollout.** Bucket = `hash(flagKey + userId) mod 100`. Done when 10% rollout hits 10% plus or minus 0.5% of 1 million IDs and is stable across restarts.
4. **Streaming updates.** Done when changes arrive in under 2 s.
5. **Offline resilience.** Done when an app started with the server down evaluates from the disk snapshot.

Deep dive: the hard parts

- **Why hash flag plus user?** Hashing only the user ID would put the same 10% of users into every experiment. Including the flag key makes buckets independent across flags.
- **Monotonic rollouts.** Raising from 10% to 20% must keep the original 10% enabled. With `bucket < percent`, it does.
- **Safe defaults.** Every `isEnabled` call takes a default used when the flag is unknown, so a deleted flag or empty cache does not crash or flip behaviour unexpectedly.

Testing strategy

- Statistical test of bucket distribution.
- Kill the server, assert SDKs keep serving.
- Contract test: SDK and server agree on rule semantics for a shared set of fixtures.

Trade-offs, scaling and failure modes

- Local evaluation means the SDK must receive full rules, which could leak targeting info to client-side apps. For browsers, evaluate on the server and send only results.
- Flags are debt. Track age and owners, and remove release flags after rollout.

Stretch goals

- Experiment metrics: log exposures and compute conversion per variant.
- Kill switch with a guaranteed propagation SLO and a red button in the UI.

Skills practised

- M9 — Operating in Production: feature flags, canaries, safe rollout.
- M4 — Caching: local caches, versioned invalidation.

In the interview

30-second answer: I built a feature flag service where teams edit flags centrally and an SDK evaluates them locally from an in-memory rule set, so `isEnabled` takes about a microsecond and needs no network call. The key decision was local evaluation with a disk snapshot, because a flag service must never be able to take the application down. The hardest part was stable percentage rollouts, which I solved by hashing flag key plus user ID into 100 buckets, so the same user always gets the same answer and raising 10% to 20% keeps the first 10% enabled. Changes stream to SDKs over SSE in under 2 s, and every change is audited.

Key terms to know:

- **Feature flag (toggle)** — a runtime switch that turns code paths on or off without a deploy. Types: release, experiment, ops, permission.
- **Local evaluation** — the SDK holds the full rule set and decides in-process. The server is only used to refresh rules.
- **Percentage rollout** — enable a feature for N% of users, chosen deterministically.
- **Deterministic bucketing** — `hash(flagKey + userId) mod 100`. The same input always lands in the same bucket.
- **Monotonic rollout** — with `bucket < percent`, increasing the percentage only adds users, never removes them.
- **Safe default** — each `isEnabled` call passes a value used when the flag is unknown or rules are missing.
- **Versioned rule set (ETag)** — each change bumps a version so SDKs can fetch only when something changed.
- **Kill switch** — a flag that turns a bad feature off in seconds.
- **Audit log** — a before-and-after row for every change, with who made it.
- **OpenFeature** — a vendor-neutral flag evaluation API that the SDK interface is modelled on.

Q: How do you make flag evaluation not a runtime dependency?

A: The SDK downloads the full rule set, keeps it in memory and evaluates locally. The network is only used to refresh rules over a stream, and the latest rules are written to a disk snapshot. If the flag server is down, apps keep using the last rules for days.

Q: How do percentage rollouts stay stable across requests and restarts?

A: The bucket is a hash of flag key plus user ID modulo 100, so it never changes for a given user and flag. A user in bucket 7 is enabled whenever the rollout is above 7%. No state needs to be stored per user.

Q: Why hash the flag key together with the user ID?

A: If you hashed only the user ID, the same 10% of users would land in the low buckets of every flag and get every experiment at once. That biases experiments and exposes the same users to every risky change. Including the flag key makes each flag's buckets independent.

Q: Why must raising a rollout keep previously enabled users enabled?

A: Users would see a feature appear and then vanish, which is confusing and corrupts experiment data. With the rule "enabled if bucket < percent", going from 10 to 20 keeps buckets 0–9 and adds 10–19.

Q: The app cold-starts while the flag server is down and there is no snapshot. What happens?

A: The SDK has no rules, so every `isEnabled` call returns the default the caller passed in. That is why defaults must be the safe choice, usually "off" for new features. The SDK keeps trying to connect and switches to real rules once they arrive.

Q: Why not evaluate flags in the browser with the full rule set?

A: The rules contain targeting details, such as user IDs, internal customer names or unreleased feature names, which would leak to anyone who opens dev tools. For client-side apps, evaluate on the server and send only the results for that user.

Q: What changes at 10x the number of SDK instances?

A: Evaluation cost does not change because it is local. The delivery service now holds many more streaming connections and sends each change to all of them. Put a CDN or several stateless delivery replicas in front, serve versioned snapshots so reconnecting SDKs fetch nothing when unchanged, and fan changes out through Redis pub/sub between replicas.

Q: How do you test it?

A: A statistical test buckets 1 million IDs and checks a 10% rollout lands within 10% plus or minus 0.5%. A resilience test kills the server and asserts SDKs keep serving from memory and from the disk snapshot. A contract test runs the same fixtures through every SDK and the server so they agree on rule semantics.

Q: Hands-on: what does bucketing look like in code?

A: Hash a stable string and map it to 0–99:

```
int h = MurmurHash3.hash32(flagKey + ":" + userId);
int bucket = Math.floorMod(h, 100);
boolean on = bucket < rolloutPercent;
```

`floorMod` avoids negative buckets from a negative hash.

Common mistakes in answers:

- Calling the flag server on every request, which makes it a single point of failure on the hot path.
- Using `random()` for rollouts, so the same user flips between on and off.
- Never cleaning up flags. Release flags are technical debt and need owners and expiry dates.

Self-check

- Why must a rollout increase keep previously enabled users enabled?
- What happens on cold start with the server down and no snapshot?

TL;DR

Store and audit centrally, distribute by stream, evaluate locally with deterministic hashing, and always have a safe default.

11. Image upload and thumbnail pipeline

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** M2, M8, M16

What it is

A media service where users upload photos directly to object storage, a background pipeline creates thumbnails in several sizes, strips metadata and scans the file, and a CDN (content delivery network: caches spread around the world that serve files close to users) delivers the results. You run it locally with MinIO, an S3-compatible object store.

The problem it solves

Uploading large files through your API servers wastes their bandwidth and memory, and image processing is CPU-heavy and slow. The fix is three patterns working together: **presigned URLs** (time-limited upload links the client uses to talk to storage directly), a **queue** that decouples upload from processing, and a **CDN** for the read path.

Real-world examples

- AWS's presigned URL guide explains how to grant time-limited upload and download access without sharing credentials.
- imgproxy is an open-source on-the-fly image resizing server with signed URLs, a useful contrast to precomputing sizes.
- Facebook's Haystack paper (OSDI 2010) explains why storing billions of small photos as individual files hurt, and how they packed them into large volumes.

Requirements


Functional

- Client asks for an upload URL, uploads the original directly to storage, then confirms.
- Pipeline generates 3 sizes (150, 600, 1,200 px wide) as WebP and JPEG, removes EXIF data (camera metadata including GPS location) and rejects non-images.
- `GET /media/{id}` returns status and CDN URLs. Owners can delete media.

Non-functional


- Files up to 25 MB. 50 uploads/s sustained.
- Thumbnails ready within 5 s p95 of upload confirmation.
- Original and derived files durable once acknowledged.
- CDN cache hit ratio above 95% for thumbnails.

The architecture



- **Media API**: creates a media row in `pending`, returns a presigned PUT URL with size and content-type limits.
- **Raw bucket**: private, holds originals.
- **Queue**: receives storage notifications (MinIO can publish to Kafka, Redis or AMQP) or a message the API emits after confirmation.
- **Thumbnail workers**: decode, validate, resize, strip metadata, write outputs, mark `ready`.
- **CDN**: in front of the public bucket. Locally, Nginx with a cache can stand in.

Data model



Tech stack

Component	Choice	Why
API	Spring Boot 4.1.1 or FastAPI	Presign with the AWS SDK
Storage	MinIO locally, S3 in cloud	S3 API everywhere
Queue	Kafka or RabbitMQ	Retries and DLQ
Image work	libvips (via a binding)	Fast and memory-light compared with many alternatives
CDN	Nginx cache locally	Mimics edge caching

Milestones

1. **Presigned upload.** Done when a 20 MB file goes to MinIO without passing through the API.
2. **Event-driven processing.** Done when thumbnails appear and status flips to `ready`.
3. **Validation and safety.** Check magic bytes (the first bytes that identify a file type), cap pixel dimensions, strip EXIF. Done when a renamed PDF and a "decompression bomb" (tiny file, enormous dimensions) are rejected.
4. **Idempotent retries and DLQ.** Done when a crashed worker's message is retried and produces the same object keys without duplicates.
5. **CDN and cache headers.** Immutable, content-addressed keys with `Cache-Control: max-age=31536000, immutable`. Done when repeated GETs are cache hits.
6. **Delete flow.** Done when deleting removes objects and the CDN no longer serves them (purge or short TTL on a manifest).

Deep dive: the hard parts

- **Trusting the client.** The client says "image/jpeg, 2 MB". It might lie. The presigned policy enforces size limits, but only the worker can verify content. Never mark media ready until the worker has decoded it.
- **Idempotency via deterministic keys.** Name outputs `{mediaId}/{variant}.webp`. A retry overwrites the same object, so duplicates cannot pile up.
- **Cache invalidation.** CDNs make deletes and edits hard. Prefer new keys on change (versioned URLs) over purging, and use purges only for deletes and legal takedowns.
- **Orphans.** Users request upload URLs and never upload, or upload and never confirm. A lifecycle rule on the raw bucket and a sweeper for stale `pending` rows clean up.

Testing strategy

- A corpus of awkward files: CMYK JPEGs, animated GIFs, huge PNGs, truncated files, wrong extensions.
- Kill workers mid-processing, assert eventual `ready` with exactly the expected objects.
- Load test uploads at 50/s and watch queue lag.

Trade-offs, scaling and failure modes

- Precompute sizes (predictable CDN hits, more storage) vs. resize on the fly (flexible, CPU on cache miss). Many systems precompute a few sizes and resize on the fly for the rest behind the CDN.
- Workers are the scaling knob: autoscale on queue lag.
- If storage notifications are lost, media stays `pending`. A reconciliation job that lists recent objects and compares with the table catches gaps.

Stretch goals

- Resumable multipart uploads for large videos.
- Perceptual hashing to detect duplicate or banned images.
- Content moderation via an ML classifier stage.

Skills practised

- M2 — Moving Data: event-driven processing with queues.
- M8 — API and Edge: CDN, signed URLs.
- M16 — Case Studies: Infrastructure: object storage design.

In the interview

30-second answer: I built a media pipeline where clients upload photos straight to object storage with a presigned URL, a storage event puts a message on a queue, and workers create three thumbnail sizes, strip EXIF data and validate the file before the image is served through a CDN. The key decision was keeping file bytes out of the API entirely, because proxying 25 MB uploads wastes API bandwidth and memory. The hardest part was not trusting the client, so nothing is marked `ready` until a worker has decoded it, checked magic bytes and capped pixel dimensions to stop decompression bombs. It sustains 50 uploads/s with thumbnails ready within 5 s p95 and over 95% CDN hits.

Key terms to know:

- **Presigned URL** — a time-limited, signed link that lets the client PUT one object to storage without holding storage credentials. It can also limit size and content type.
- **Object storage (S3 / MinIO)** — a flat key-to-blob store with high durability. Raw originals go in a private bucket, renditions in a public one.
- **Event-driven processing** — the "object created" notification goes to a queue, so upload and processing are decoupled.
- **Rendition** — a derived file such as the 150, 600 or 1,200 px WebP and JPEG versions.

- **Magic bytes** — the first bytes of a file that reveal its real type, regardless of extension or declared content type.
- **Decompression bomb** — a tiny file that decodes to enormous dimensions and exhausts memory. Stopped by a pixel cap.
- **EXIF stripping** — removing camera metadata, including GPS location, for privacy.
- **Deterministic output keys** — names like `{mediaId}/{variant}.webp`, so a retry overwrites instead of duplicating.
- **CDN with immutable URLs** — content-addressed keys served with `Cache-Control: max-age=31536000, immutable`, so edges never need to recheck.
- **Orphan sweeper** — cleans up `pending` rows and raw objects for uploads never confirmed.

Q: Why not upload through the API?

A: Every byte would cross the network twice and sit in API memory, so 50 uploads of 25 MB per second would need a large API fleet doing nothing but copying. A presigned URL lets the client write directly to storage with a scoped, time-limited permission. The API only handles small metadata requests.

Q: Why process thumbnails asynchronously instead of in the upload request?

A: Resizing is CPU-heavy and can take seconds, and the user should not wait on it or lose the upload if a worker fails. The queue absorbs bursts, and workers retry from it. Workers are also the natural scaling knob: autoscale on queue lag.

Q: How do you make processing safe to retry?

A: Output keys are derived from the media ID and variant, so a retried job writes the same objects again instead of creating new ones. Marking `ready` is an idempotent status update. A crashed worker's message is simply redelivered.

Q: The client says the file is a 2 MB JPEG. Do you believe it?

A: No. The presigned policy can enforce the size limit, but only the worker can check the content. It reads magic bytes, decodes the image with a pixel cap, re-encodes it, and only then marks it ready. A renamed PDF or a decompression bomb is rejected.

Q: How do you change an image that is already cached on the CDN?

A: Publish the new version under a new URL, for example with a version or content hash in the key, and point the media record at it. Old URLs stay cached but are no longer referenced. Purging is slow and incomplete across edges, so keep it for deletes and legal takedowns.

Q: Precompute sizes or resize on the fly?

A: Precomputing gives predictable CDN hits and no CPU on the read path, but costs storage for sizes nobody may request. Resizing on the fly (like imgproxy) is flexible but spends CPU on every cache miss. A common mix is a few precomputed sizes plus on-the-fly resizing behind the CDN for the rest.

Q: A storage notification is lost. What happens?

A: The media row stays `pending` forever and the user never sees thumbnails. A reconciliation job lists recent objects in the raw bucket, compares them with the table and re-enqueues anything missing. Alerting on the age of the oldest `pending` row catches it early.

Q: What changes at 10x uploads?

A: Object storage and the CDN scale on their own. The bottleneck is worker CPU, so autoscale workers on queue lag and use libvips, which is fast and light on memory. The media table is small per row, but shard it by owner or media ID if write volume grows.

Q: How do you test it?

A: A corpus of awkward files: CMYK JPEGs, animated GIFs, huge PNGs, truncated files, wrong extensions. A crash test kills workers mid-processing and asserts the media ends `ready` with exactly the expected objects. A 50 uploads/s load test watches queue lag.

Common mistakes in answers:

- Streaming uploads through the API servers "for validation". Validation belongs in the worker after upload.
- Relying on the file extension or declared content type instead of decoding the file.
- Planning to purge the CDN on every edit instead of using versioned, immutable URLs.

TL;DR

Direct-to-storage uploads, an event-driven worker pool with deterministic outputs, and an immutable CDN read path form a media pipeline that scales.

12. Search autocomplete

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** M4, M10, M13

What it is

A typeahead service: as the user types "sys", it returns the 10 most popular completions in a few milliseconds. Suggestions are built offline from query logs by a batch job and served from an in-memory **trie** (a prefix tree where each node is one character) with the top results precomputed at every node.

The problem it solves

Each keystroke is a request, so autocomplete gets several times more traffic than search itself, and it must answer faster than a person types (under about 100 ms end to end). Scanning a database with `LIKE 'sys%'` and sorting by popularity on every keystroke is far too slow. Precomputing answers per prefix moves the work offline.

Real-world examples

- Elasticsearch's suggesters documentation describes the completion suggester, which uses in-memory finite-state structures for fast prefix lookups.
- Module 13 of this book has a full autocomplete case study with sizing.

Requirements


Functional

- `GET /suggest?q=prefix` returns up to 10 completions ranked by popularity.
- Data refreshes from the last 7 days of query logs at least hourly.
- Block-list for offensive terms takes effect within minutes.
- Basic personalisation is a stretch goal.

Non-functional

- p99 under 10 ms server-side. 20,000 requests/s across 3 instances.
- 10 million distinct queries in the dataset.
- Serving keeps working if the build pipeline is down (serve the last good index).


The architecture



- **Client debounce**: wait about 50–100 ms after the last keystroke before calling.
- **CDN or HTTP cache**: popular short prefixes are identical for everyone and cache well.
- **Aggregator**: counts queries per hour and writes rollups.

- **Index builder**: builds the trie with top-10 lists, serialises it and uploads a versioned snapshot.
- **Suggest servers**: hot-swap to new snapshots atomically.

Data model



Tech stack

Component	Choice	Why
Serving	Java 25 (compact arrays) or Python 3.14 with a compiled trie library	Memory layout matters
Logs	Kafka	Durable, replayable query stream
Rollups	PostgreSQL	Simple aggregates for a project-sized dataset
Snapshots	Object storage	Versioned, easy rollback

Milestones

1. **Naive trie with top-K at each node.** Done when lookups for 1 million queries run under 1 ms.
2. **Offline builder.** Generate a synthetic Zipf-distributed query log. Done when the builder writes a snapshot from counts.
3. **Hot swap.** Done when servers load a new version without dropping requests.
4. **Streaming counts.** Kafka to hourly rollups with time decay (recent hours weigh more). Done when a newly trending query appears within one build cycle.
5. **Block-list fast path.** Filter at serve time from a small set reloaded every minute. Done when a blocked term disappears within 60 s.
6. **Caching and debouncing.** Done when load test shows most short-prefix traffic served from cache.

Deep dive: the hard parts

- **Memory.** A naive trie with an object per node is huge. Store top-K as integer IDs into a string table, compress single-child chains (a radix tree), or use a sorted array of queries with binary search for the prefix range plus precomputed top-K for short prefixes only.
- **Freshness vs. stability.** Rebuilding every minute makes suggestions jumpy and expensive. Hourly builds plus a small "trending" overlay from the stream is a common compromise.
- **Ranking signal.** Raw counts favour old evergreen queries. Exponential decay `score = sum(count_h * 0.9^age_h)` balances recent and all-time.

Testing strategy

- Golden tests: fixed log in, expected suggestions out.
- Memory benchmark on 10 million entries, record heap size.
- Load test with a realistic prefix distribution (many 1–3 character prefixes).

Trade-offs, scaling and failure modes

- Whole trie on every server is simple and fast. If it outgrows memory, shard by first characters, accepting skew (far more queries start with "s" than "x").

- If the builder fails, servers keep the last snapshot. Alert on index age.

Stretch goals

- Typo tolerance with edit distance 1 on short prefixes.
- Per-user recent searches merged with global suggestions.

Skills practised

- M13 — Case Studies: Building Blocks: the autocomplete design.
- M10 — Batch and Streaming: offline builds plus streaming counts.
- M4 — Caching: edge caching of hot prefixes.

In the interview

30-second answer: I built a typeahead service that returns the 10 most popular completions for a prefix in under 10 ms p99. The key decision was moving all ranking offline: a batch builder turns the last 7 days of query counts into a trie with the top 10 precomputed at every node, and servers load it as a versioned snapshot, so a lookup is just a walk down the prefix. The hardest part was memory for 10 million queries, which I handled with integer IDs into a string table and compressed single-child chains. Debouncing and edge caching of short prefixes let 3 instances handle 20,000 requests/s.

Key terms to know:

- **Trie (prefix tree)** — a tree where each edge is a character, so all queries sharing a prefix share a path.
- **Precomputed top-K** — each node stores its 10 best completions, so query time does no sorting.
- **Radix tree** — a trie where single-child chains are merged into one edge, saving memory.
- **Offline index build** — a batch job builds the structure from aggregated counts and uploads a versioned snapshot.
- **Hot swap** — servers load a new snapshot in the background and switch with one atomic pointer change.
- **Time decay** — `score = sum(count_h * 0.9^age_h)`, so recent hours weigh more than old ones.
- **Debounce** — the client waits 50–100 ms after the last keystroke before sending a request.
- **Edge caching** — short prefixes are the same for everyone and cache well at a CDN.
- **Block-list fast path** — offensive terms are filtered at serve time from a small set reloaded every minute.

Q: Why precompute the top-K at each node?

A: Without it, a lookup for "s" would have to visit every query starting with "s" and sort them, which could be millions of entries. With top-K stored at the node, the lookup walks a few characters down the tree and returns a stored list. The cost moves to the offline build, which runs once an hour.

Q: Why not `LIKE 'sys%'` in a database?

A: A B-tree index can find the matching range, but you still have to sort that range by popularity on every keystroke. Autocomplete gets several requests per search, so that cost multiplies. In-memory precomputed answers are orders of magnitude faster.

Q: How does a new trending query show up?

A: Query logs stream through Kafka into hourly rollups with time decay, and the next build picks them up. For faster reaction, a small real-time "trending" overlay computed from the stream is merged into results at serve time. Rebuilding the whole index every minute would make suggestions jumpy and expensive.

Q: A journalist reports an offensive suggestion. How fast can you remove it?

A: Within about 60 seconds. Servers filter results against a small block-list reloaded every minute, so the fix does not wait for the next hourly build. The build also excludes the term so it does not come back.

Q: What if the index no longer fits in memory?

A: First compress it: integer IDs, a radix tree, or a sorted array of queries with binary search plus top-K only for short prefixes. If it still does not fit, shard by prefix. Shards will be skewed, because far more queries start with "s" than "x", so split by measured load rather than by letter.

Q: The build pipeline has been down for a day. What happens?

A: Servers keep serving the last good snapshot, so users see slightly stale suggestions but no errors. An alert on index age tells you something is wrong. Because snapshots are versioned, a bad build can also be rolled back by loading the previous version.

Q: How do you handle 20,000 requests/s with 3 instances?

A: Most traffic is 1–3 character prefixes, which are identical for everyone, so a CDN or HTTP cache answers them. Client debouncing cuts requests per word. What reaches servers is a sub-millisecond in-memory lookup, so each instance has plenty of headroom.

Q: How do you test it?

A: Golden tests feed a fixed log and assert the exact suggestions. A memory benchmark loads 10 million entries and records heap size. A load test uses a realistic prefix distribution weighted toward short prefixes.

Q: Hands-on: what is the lookup complexity?

A: O(L) to walk L characters of the prefix, plus O(K) to return the stored list, independent of how many queries match. Building costs O(total characters) for insertion plus merging top-K lists bottom-up.

Common mistakes in answers:

- Sorting matches at query time, which does not scale for short, popular prefixes.
- Rebuilding the index on every new query for "freshness" instead of a batch build plus a trending overlay.
- Ignoring the client side. Debouncing and caching remove most of the load before it reaches servers.

TL;DR

Do the heavy ranking offline, serve precomputed top-K from memory, and swap versioned snapshots safely.

13. Group chat service

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M2, M14

What it is

A Slack-style chat backend with channels, real-time delivery over WebSockets (a full-duplex connection where both sides can send at any time), message history, read markers and presence. The key design idea is a **per-channel sequence number**: every message in a channel gets the next number, which gives total order, gap detection and cheap sync.

The problem it solves

Chat looks simple but combines hard properties: messages must appear in the same order for everyone, survive reconnects without gaps or duplicates, reach users connected to different servers, and load history quickly. Clients go offline constantly (phones, tunnels, laptops closing), so sync after reconnect is the common case, not the exception.

Real-world examples

- Slack's Real-time messaging describes gateway servers holding client connections and channel servers that own channels, located by consistent hashing.
- Discord's How Discord stores trillions of messages covers their move from Cassandra to ScyllaDB and partitioning messages by channel and time bucket.

Requirements


Functional

- Create channels, join, leave, send text messages, edit and delete.
- Real-time delivery to online members. History paging (`before=seq`).
- Per-user read marker per channel and unread counts.
- Presence: online, away, offline.

Non-functional


- 50,000 concurrent connections across 3 gateway instances.
- Send to receive under 200 ms p95 within one region.
- No message loss once acknowledged. No duplicates shown.

The architecture



- **Gateways**: hold WebSockets, authenticate, track which channels each local connection cares about, subscribe to those channel topics.
- **Channel service**: validates membership, assigns the sequence number, stores, publishes.
- **PostgreSQL**: messages partitioned by channel. Read markers in a separate table.
- **Presence**: Redis keys with short TTLs refreshed by heartbeats.

Data model



Tech stack

Component	Choice	Why
Gateways	Spring WebSocket on Java 25 virtual threads, or Python websockets	Many idle connections
Messages	PostgreSQL, primary key `(channel_id, seq)`	Range scans by channel
Fan-out	Redis Streams or pub/sub	Cross-gateway delivery
Presence	Redis with TTL	Ephemeral state

Milestones

1. **Single server WebSocket chat.** Done when two clients in a channel see each other's messages.
2. **Sequence numbers.** `UPDATE channel SET last_seq = last_seq + 1 RETURNING last_seq` in the same transaction as the insert. Done when concurrent senders produce gap-free, unique seqs.
3. **Client dedup.** Clients send a `client_msg_id`. Retries return the existing seq. Done when a resend after a dropped ack shows one message.
4. **Multi-gateway fan-out.** Done when clients on different gateways chat.
5. **Reconnect sync.** Client sends its last seen seq per channel. Gateway returns the gap from PostgreSQL then switches to live. Done when a client offline for 10 minutes catches up with no gaps or duplicates.
6. **Read markers, unread counts and presence.** Unread = `last_seq - read_seq`. Done when counts are correct across devices.

Deep dive: the hard parts

- **Ordering.** The sequence row lock serialises writes per channel, which caps a single channel's throughput (hundreds to low thousands per second), but channels are independent. That is acceptable for chat, and the reason channels are the unit of partitioning.
- **Gap detection.** A client receiving seq 41 then 43 knows it missed 42 and fetches it. Without sequence numbers you cannot tell a gap from silence.
- **Live vs. history race.** On reconnect, subscribe to live events first, buffer them, fetch history up to the latest seq, then apply the buffer and drop anything already seen. Otherwise a message sent during the fetch is lost.
- **Presence cost.** Broadcasting every status change to every channel member is quadratic in big channels. Send presence only for users visible on screen or in small channels, and batch updates.

Testing strategy

- Simulated clients that randomly disconnect and reconnect while others send. Assert every client's final log equals the server's.
- Concurrency test on one channel for seq uniqueness.
- Load test connection count and fan-out latency.

Trade-offs, scaling and failure modes

- One very large channel (100,000 members) makes fan-out heavy. Fan out to gateways (few) rather than users (many): each gateway then delivers locally.
- PostgreSQL is fine for a project. At very large scale, wide-column stores partitioned by `(channel, time bucket)` are typical.
- If Redis fan-out drops a message, the gap detection plus history fetch repairs it.

Stretch goals

- Threads and reactions. Typing indicators (ephemeral, never stored).
- End-to-end encryption design sketch: what the server can no longer do.

Skills practised

- M2 — Moving Data: bidirectional streaming, pub/sub.
- M14 — Case Studies: Messaging and Media: the chat system with per-conversation sequencer.
- M18 — Client and Mobile System Design: offline sync on the client.

In the interview

30-second answer: I built a Slack-style chat backend with WebSocket gateways, a channel service that stores messages in PostgreSQL, and Redis to fan messages out to whichever gateway holds each recipient. The key decision was a per-channel sequence number assigned in the same transaction as the insert, because it gives every member the same order, lets clients detect gaps, and makes reconnect sync a simple "give me everything after seq N". The hardest part was the race between live events and history on reconnect, which I solved by subscribing first, buffering, fetching history, then deduping by seq. It handled 50,000 connections across 3 gateways with send-to-receive under 200 ms p95.

Key terms to know:

- **WebSocket** — a full-duplex connection where client and server can both send at any time.
- **Gateway** — a server that only holds client connections, authenticates them and forwards events.
- **Per-channel sequence number** — each message in a channel gets `last_seq + 1`, giving a total order within the channel.
- **Gap detection** — receiving seq 41 then 43 tells the client it missed 42 and must fetch it.

- **Client message ID** — a client-generated ID with a unique constraint, so a resend after a lost ack does not create a duplicate.
- **Reconnect sync** — the client sends its last seq per channel and gets the missing range before switching to live.
- **Fan-out to gateways** — publish once per gateway that has interested users, not once per user.
- **Presence** — online, away or offline, stored as Redis keys with short TTLs refreshed by heartbeats.
- **Read marker** — the last seq a user has read. Unread count is `last_seq - read_seq`.

Q: How do you guarantee message order?

A: The channel service increments `channel.last_seq` and inserts the message in one transaction, so every message in a channel gets a unique, gap-free number. Clients display by seq, not by arrival time or client clock. Order across different channels is not defined and is not needed.

Q: Does the sequence lock limit throughput?

A: Yes, per channel. Updating one row serialises writes to that channel, which caps it at roughly hundreds to low thousands of messages per second. That is far above what a human chat channel produces, and different channels never contend, which is why the channel is the unit of partitioning.

Q: How does a client catch up after being offline?

A: It sends its last seen seq for each channel. The gateway fetches the missing range from PostgreSQL, sends it, then switches to live delivery. To avoid losing messages sent during the fetch, it subscribes to live events first, buffers them, and drops any it already sent from history.

Q: How do you avoid duplicate messages when a client resends?

A: The client attaches a `client_msg_id` generated once per message. If the ack is lost and the client resends, the unique constraint finds the existing row and the server returns its seq. The user sees one message.

Q: Redis pub/sub drops a message on its way to a gateway. Is it lost?

A: No. The message is already stored. The client sees the next message with a seq one higher than expected, detects the gap, and fetches the missing message from history. The database is the source of truth, and pub/sub is just the fast path.

Q: One channel has 100,000 members. What breaks?

A: Fan-out per message becomes huge, and presence updates become quadratic if every status change goes to every member. Publish each message once per gateway, and let each gateway deliver to its local connections. Send presence only for users on screen, and batch it.

Q: WebSockets or SSE for chat?

A: Chat is two-way and latency-sensitive, with sends, typing indicators and acks, so WebSockets fit. SSE is one-way, so sending would need separate HTTP requests. The cost is that WebSockets need your own reconnect and resume logic, which the seq numbers provide.

Q: What changes at 100x the message volume?

A: PostgreSQL storage and write throughput become the limit. At that scale, teams use wide-column stores partitioned by channel and time bucket, as Discord does with ScyllaDB. Gateways scale horizontally, and fan-out moves to a partitioned broker such as Kafka or Redis Streams keyed by channel.

Q: How do you test it?

A: Simulated clients randomly disconnect and reconnect while others send, and at the end every client's log must equal the server's. A concurrency test on one channel checks seq uniqueness. A load test measures connection count and fan-out latency.

Common mistakes in answers:

- Ordering by timestamp. Clocks differ between clients and servers, so only a server-assigned sequence is reliable.

- Assuming pub/sub delivery is reliable. Gap detection plus history fetch is what makes it safe.
- Promising global order across all channels, which needs a single sequencer and does not scale.

TL;DR

Per-channel sequence numbers give order, gap detection and resumable sync. Gateways plus pub/sub handle fan-out, and the database repairs whatever pub/sub drops.

14. Transactional outbox and CDC pipeline

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** M2, M5, M10

What it is

An order service that publishes `OrderPlaced` events to Kafka reliably, using the **transactional outbox** (write the event into an `outbox` table in the same database transaction as the business change) and **change data capture** (CDC: reading the database's own write-ahead log to stream every committed change) via Debezium to move outbox rows into Kafka.

The problem it solves

The **dual-write problem**: if a service writes to its database and then publishes to Kafka, a crash between the two leaves them disagreeing. Either the order exists with no event (downstream never ships it) or the event exists with no order. You cannot wrap PostgreSQL and Kafka in one transaction cheaply, so you make the database the only write and derive the event from it.

Real-world examples

- Chris Richardson's Transactional outbox pattern describes the pattern and its relay options (polling vs. log tailing).
- Debezium's Outbox Event Router documents the transform that turns outbox inserts into Kafka messages with routing by aggregate type.

Requirements


Functional

- `POST /orders` creates an order and an `OrderPlaced` outbox row atomically.
- Events land in Kafka topic `orders.events`, keyed by order ID.
- A downstream consumer (shipping) processes each event once in effect.
- Order status changes produce further events in order per order.

Non-functional


- Zero lost or phantom events under crashes of the service, Debezium or Kafka brokers.
- Commit to Kafka under 1 s p95.
- 1,000 orders/s on a laptop setup.

The architecture



- **Order service**: inserts into `orders` and `outbox` in one transaction. Never talks to Kafka.
- **WAL**: the write-ahead log, PostgreSQL's append-only journal of changes, exposed through logical replication slots.
- **Debezium**: a Kafka Connect source connector that reads the slot and emits changes.
- **Shipping consumer**: records processed event IDs in its own database in the same transaction as its work (an **inbox** table) to dedupe.
- **Outbox cleaner**: deletes old outbox rows (they have already been captured from the WAL).

Data model



Tech stack

Component	Choice	Why
Service	Spring Boot 4.1.1 with JDBC, or Python with psycopg	Plain transactions
CDC	Debezium PostgreSQL connector on Kafka Connect	Reads the WAL, no polling
Broker	Kafka	Ordered per key, replayable
Consumer	Kafka client with manual commits	Control over offsets

Milestones

1. **Naive dual write.** Publish after commit. Done when you can reproduce a lost event by killing the process between the two calls. (Proving the problem matters.)
2. **Outbox table with polling relay.** A loop selects unsent rows, publishes, marks sent. Done when crash tests lose nothing (but may duplicate).
3. **Switch to Debezium.** Done when outbox inserts appear in Kafka with the order ID as key.
4. **Idempotent consumer.** Done when replaying the topic from offset 0 does not double-ship.
5. **Failure drills.** Kill Debezium for 5 minutes under load, then restart. Done when it resumes from its slot position with no gaps.
6. **Operations.** Monitor replication slot lag. Done when an alert fires if retained WAL grows past a threshold.

Deep dive: the hard parts

- **At-least-once end to end.** Debezium may re-emit events after a restart (it resumes from its last committed offset). Consumers must dedupe by event ID. Exactly-once inside Kafka does not extend to your database.
- **Replication slots can fill your disk.** PostgreSQL keeps WAL until the slot's consumer confirms it. If Debezium is down for a day, WAL piles up. Set `max_slot_wal_keep_size` (PostgreSQL 13+) and alert.
- **Ordering.** Keying by aggregate ID keeps all events for one order in one partition, in commit order. Events for different orders have no global order, and should not need one.
- **Schema evolution.** Event payloads are a public contract. Version them and add fields compatibly. A schema registry enforces this.

Testing strategy

- Crash matrix: kill service, Debezium, a Kafka broker, the consumer, each at random points during a load run. Compare `orders` with consumed events: every order has exactly one effect.
- Consumer replay test from offset 0.

Trade-offs, scaling and failure modes

- Polling relay: no extra infrastructure, adds database load and latency. CDC: low latency and load, but Kafka Connect and slots are new things to operate.

- The outbox table is a hot insert table. Partition or delete aggressively.
- CDC on the business tables directly (no outbox) leaks your internal schema to consumers. The outbox lets you publish deliberate, versioned events.

Stretch goals

- Build the read model of Project 18 from these events.
- Use the same CDC stream to keep an Elasticsearch index in sync.

Skills practised

- M10 — Batch and Streaming: CDC, exactly-once, Kafka internals.
- M5 — Reliability: idempotent consumers.
- M2 — Moving Data: event-driven architecture.

In the interview

30-second answer: I built an order service that publishes `OrderPlaced` events to Kafka without the dual-write problem: it writes the order and an outbox row in one PostgreSQL transaction and never talks to Kafka itself. Debezium reads the write-ahead log through a replication slot and turns outbox inserts into Kafka messages keyed by order ID. The hardest part was that the whole chain is at-least-once, so the shipping consumer stores processed event IDs in an inbox table in the same transaction as its work. In a crash matrix that killed the service, Debezium, a broker and the consumer, every order produced exactly one effect, with commit-to-Kafka under 1 s p95.

Key terms to know:

- **Dual-write problem** — writing to the database and then to Kafka. A crash between the two leaves them disagreeing.
- **Transactional outbox** — an `outbox` table written in the same transaction as the business change, so the event exists if and only if the change committed.
- **Change data capture (CDC)** — streaming committed changes from the database's own log.
- **Write-ahead log (WAL)** — PostgreSQL's append-only journal of changes, read through logical replication.
- **Replication slot** — PostgreSQL's bookmark for a CDC consumer. It keeps WAL until the consumer confirms it.
- **Debezium outbox router** — a transform that turns outbox inserts into Kafka messages routed by aggregate type and keyed by aggregate ID.
- **Idempotent consumer / inbox table** — the consumer records event IDs it has processed in the same transaction as its side effect, to skip duplicates.
- **Per-key ordering** — Kafka keeps order within a partition, so keying by order ID keeps one order's events in sequence.
- **Polling relay** — the simpler alternative: a loop selects unsent outbox rows, publishes and marks them sent.
- **Schema evolution** — events are a public contract, so fields are added compatibly and versioned.

Q: What is the dual-write problem?

A: The service commits an order to PostgreSQL and then publishes to Kafka. If it crashes between the two, the order exists but no event was sent, so shipping never happens. If it publishes first and the commit fails, consumers act on an order that does not exist. You cannot cheaply put PostgreSQL and Kafka in one transaction.

Q: Why not publish to Kafka inside the database transaction?

A: Kafka is not part of the database transaction. Publishing before commit can announce an order that then rolls back, and publishing after commit can be lost to a crash. The outbox makes the database the only write, and the event is derived from what actually committed.

Q: Polling relay or CDC?

A: Polling needs no new infrastructure, but it adds query load and latency equal to the poll interval. CDC reads the WAL, so latency is low and there is no extra query load. The cost is operating Kafka Connect, Debezium and replication slots.

Q: Can the consumer see an event twice?

A: Yes. Debezium resumes from its last committed offset after a restart and may re-emit events, and the consumer can crash after acting but before committing its Kafka offset. The consumer inserts the event ID into its inbox table in the same transaction as the shipment, so a duplicate fails the unique check and is skipped.

Q: Doesn't Kafka offer exactly-once?

A: Kafka's transactions give exactly-once for read-process-write flows that stay inside Kafka. They do not cover side effects in your own database or calls to other services. So end to end you still need an idempotent consumer.

Q: Debezium is down for a day. What happens?

A: No events are lost, because the replication slot keeps the WAL until Debezium confirms it. But that WAL piles up on the database disk and can fill it, which takes the whole database down. Set `max_slot_wal_keep_size` (PostgreSQL 13+) and alert on slot lag well before that point.

Q: Why use an outbox table instead of running CDC directly on the `orders` table?

A: CDC on business tables exposes your internal schema to every consumer, so renaming a column breaks other teams. The outbox lets you publish deliberate, versioned events with only the fields you choose. Internal tables can then change freely.

Q: What changes at 10x order volume?

A: The outbox becomes a very hot insert table, so delete captured rows aggressively or partition it by time and drop old partitions. Increase Kafka partitions for `orders.events` so more consumers can work in parallel; keying by order ID keeps per-order order. Watch WAL volume and slot lag, since CDC throughput now matters.

Q: How do you prove nothing is lost or duplicated?

A: First reproduce the bug with a naive dual write by killing the process between commit and publish. Then run a crash matrix under load, killing each component at random points, and compare `orders` with consumed effects: every order must have exactly one. A replay from offset 0 must not double-ship.

Common mistakes in answers:

- Saying "use Kafka transactions" to solve the dual write. They do not include your database.
- Forgetting consumer idempotency. The outbox guarantees no loss, not no duplicates.
- Ignoring replication slot growth, which can fill the database disk during a CDC outage.

TL;DR

Write once to the database, derive events from its log, and dedupe on the consumer side. That closes the dual-write gap.

15. Hotel reservation system

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** M7, M17

What it is

A booking backend for a hotel chain: search availability by date range, hold a room type while the guest pays, confirm or release the hold, and allow a controlled amount of overbooking. The core lesson is **concurrency control on scarce inventory**: two guests must never both get the last room.

The problem it solves

Inventory is shared and contended, especially for popular dates. Reads (searches) vastly outnumber writes (bookings), but the writes must be strictly correct. Payment takes seconds to minutes, so you cannot hold a database lock during it. And partners (travel agencies) retry requests, which must not create duplicate bookings.

Real-world examples

- PostgreSQL's range types documentation shows exclusion constraints that prevent overlapping reservations at the database level.
- Airbnb's Avoiding double payments in a distributed payments system describes their idempotency framework, relevant to the booking-plus-payment flow.

Requirements


Functional

- Search room-type availability for a hotel and date range.
- Create a hold for 10 minutes. Confirm with a payment reference. Holds expire automatically.
- Cancel a booking and return inventory.
- Configurable overbooking per room type (for example 105% of physical rooms).
- Idempotent create and confirm.

Non-functional


- Search p99 under 100 ms, 1,000 searches/s.
- Bookings: 50/s normally, 500/s during a flash sale for one hotel.
- Never exceed the allowed inventory for any night.

The architecture



- **Reservation API**: search, hold, confirm, cancel.
- **Inventory in PostgreSQL**: one row per hotel, room type and night with `total`, `reserved`.
- **Availability cache**: precomputed summaries per hotel and month for fast search. Slightly stale is fine because booking re-checks in the database.
- **Hold expiry worker**: releases expired holds.

Data model



Tech stack

Component	Choice	Why
API	Spring Boot 4.1.1 or FastAPI	Transactions and retries
Inventory	PostgreSQL	Row locks, check constraints
Cache	Redis	Search fan-out reads
Load test	k6 flash-sale scenario	Many buyers, one room type

Milestones

1. **Schema and search.** Done when search returns correct availability for seeded data.
2. **Hold with a conditional update.** `UPDATE ... SET reserved = reserved + 1 WHERE ... AND reserved < total * (100 + overbook_pct) / 100` for every night in range, all in one transaction. If any night's update affects zero rows, roll back. Done when 500 concurrent buyers for the last room produce exactly one success.
3. **Idempotent create and confirm.** Done when a partner retry returns the same reservation.
4. **Hold expiry.** Done when unpaid holds release inventory within 30 s of expiry.
5. **Availability cache.** Updated from inventory change events. Done when search hits the cache and booking still never oversells.
6. **Flash sale test.** Done when p99 booking latency stays under 500 ms at 500/s on one hotel.

Deep dive: the hard parts

- **Pessimistic vs. optimistic.** `SELECT ... FOR UPDATE` then update is pessimistic: simple, but contended rows queue up. A version column with retry-on-conflict is optimistic: great when conflicts are

rare, terrible in a flash sale. The single conditional `UPDATE` is atomic and avoids both an explicit lock and a retry loop.

- **Lock ordering.** A multi-night booking locks several rows. Always update nights in date order so two transactions never wait on each other in opposite orders (a deadlock).
- **Holds vs. payment.** Never keep a transaction open during payment. Commit the hold, call payment with an idempotency key, then confirm. If payment succeeds after the hold expired, either re-acquire or refund. Decide and test.
- **Overbooking.** Hotels overbook because some guests do not show up. The rule lives in the database condition, so no code path can bypass it.

Testing strategy

- Concurrency test for the last room, repeated hundreds of times.
- Property test: random sequences of hold, confirm, cancel and expire never leave `reserved` above the limit or below zero.
- Clock-controlled expiry tests.

Trade-offs, scaling and failure modes

- Hot rows during a flash sale serialise. Options: a queue in front of the hotel (users wait in line), or split inventory into buckets (several rows each holding part of the count) at the cost of more complex "last room" logic.
- Cached search can show a room that is actually gone. The booking step rejects politely and refreshes search.
- Shard by hotel ID: bookings never cross hotels.

Stretch goals

- Rate plans and prices per night.
- Partner channel manager integration with eventual sync and conflict reports.

Skills practised

- M17 — Case Studies: Money and Reservations: hotel reservation and last-room concurrency.
- M7 — Consistency: strong consistency where it matters.
- M5 — Reliability: idempotency keys.

In the interview

30-second answer: I built a hotel booking backend with search, 10-minute holds, confirm, cancel and controlled overbooking. The key decision was to store inventory as one row per hotel, room type and night, and to take a hold with a single conditional `UPDATE ... WHERE reserved < limit` for each night in one transaction, so the database decides atomically who gets the last room. The hardest part was payment taking minutes, so I never hold a lock during it: I commit a hold with an expiry, call payment with an idempotency key, then confirm. In a test of 500 concurrent buyers for the last room, exactly one succeeded every time.

Key terms to know:

- **Contended inventory** — many buyers competing for a few units, such as the last room on a popular date.
- **Conditional (atomic) update** — `UPDATE ... SET reserved = reserved + 1 WHERE reserved < limit`. Zero rows updated means sold out.
- **Pessimistic locking** — `SELECT ... FOR UPDATE` locks the row first. Simple, but waiting transactions queue up.
- **Optimistic locking** — read a version, update only if it is unchanged, retry on conflict. Good when conflicts are rare.

- **Deadlock and lock ordering** — two transactions waiting on each other's rows. Avoided by always updating nights in date order.
- **Hold with expiry** — reserves inventory for 10 minutes without an open transaction. A worker releases expired holds.
- **Overbooking** — allowing, say, 105% of physical rooms because some guests do not show. The limit lives in the SQL condition.
- **Idempotency key** — lets partners retry create and confirm without making a second reservation.
- **Stale availability cache** — search reads a Redis summary that may be slightly out of date. The booking step re-checks in the database.

Q: How do you prevent double-booking the last room?

A: In one transaction, for every night of the stay, run `UPDATE inventory SET reserved = reserved + 1 WHERE ... AND reserved < total * (100 + overbook_pct) / 100`. If any night updates zero rows, roll back the whole booking. PostgreSQL's row lock makes each update atomic, so only one buyer can take the last unit.

Q: Pessimistic, optimistic, or conditional update?

A: Pessimistic `SELECT FOR UPDATE` works but adds a round-trip while holding the lock. Optimistic version checks are great when conflicts are rare, but in a flash sale almost everyone conflicts and retries. The conditional update checks and changes in one statement, with no explicit lock step and no retry loop.

Q: Why not keep a transaction open while the guest pays?

A: Payment can take minutes, and an open transaction holds row locks the whole time, blocking every other booking for those nights. A hold commits immediately and expires after 10 minutes. You get the same guarantee without blocking anyone.

Q: Payment succeeds just after the hold expired and the room was resold. What now?

A: Confirm first tries to re-acquire inventory with the same conditional update. If that fails, the system refunds automatically, using the payment idempotency key so the refund matches exactly one charge. The rule must be decided up front and tested, not discovered in production.

Q: How do you avoid deadlocks on multi-night bookings?

A: Always update the night rows in ascending date order. Two transactions then lock shared rows in the same order, so one simply waits for the other instead of each holding a row the other needs.

Q: Search says a room is available, but booking fails. Is that a bug?

A: No, it is a deliberate trade-off. Search reads a cache that may be a few seconds stale, which keeps search fast at 1,000 requests/s. Correctness is enforced only at booking time in the database, which rejects politely and refreshes search.

Q: A flash sale sends 500 bookings/s to one hotel. What breaks first?

A: The inventory rows for those nights become hot, and every booking queues on the same row locks, so latency rises. Options: a waiting room or queue in front of that hotel to meter users in, or split the count across several bucket rows, at the cost of more complex "last room" logic. Search stays on the cache.

Q: How do you scale to many hotels?

A: Shard by hotel ID. A booking never spans hotels, so every transaction stays on one shard. Search across hotels reads cached availability summaries.

Q: How do you test correctness?

A: A last-room concurrency test runs hundreds of times. A property test applies random sequences of hold, confirm, cancel and expire and checks `reserved` never exceeds the limit or goes below zero. A controllable clock tests that expiry releases inventory within 30 s.

Q: Hands-on: how do you know the hold failed?

A: Check the affected row count of each night's update:

```sql
UPDATE room_type_inventory SET reserved = reserved + 1
WHERE hotel_id=$1 AND room_type_id=$2 AND night=$3
  AND reserved < total * (100 + overbook_pct) / 100;
-- 0 rows updated -> ROLLBACK, return "sold out"
```

Common mistakes in answers:

- Reading availability, checking it in application code, then writing. Two requests can both pass the check.
- Holding a database lock or transaction during payment.
- Using the search cache to decide whether a booking succeeds.

TL;DR

Model inventory per night, change it with one atomic conditional update, hold instead of lock, and make every write idempotent.

16. Sharded cache cluster with consistent hashing

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** M3, M4

What it is

A memcached-like cache cluster you build yourself: several cache nodes, and a client library that decides which node owns each key using a **consistent hash ring** with virtual nodes. You add and remove nodes live and measure how many keys move, then add replication for hot keys and a protection against thundering herds.

The problem it solves

One cache server runs out of memory or network. Splitting keys across N servers with `hash(key) mod N` works until N changes: then almost every key maps to a different server and the hit rate falls to near zero, sending the full load to the database at the worst moment. **Consistent hashing** moves only about 1/N of keys when a node joins or leaves.

Real-world examples

- Facebook's Scaling Memcache at Facebook (NSDI 2013) describes leases to stop stale sets and thundering herds, regional pools and the mcrouter proxy.
- Google's A fast, minimal memory, consistent hash algorithm introduces Jump Consistent Hash, an alternative to rings that needs no memory but only supports adding or removing the last bucket.

Requirements


Functional

- `GET`, `SET` with TTL, `DELETE` over a simple TCP or HTTP protocol.
- Client library routes keys with a ring of virtual nodes.
- Nodes can be added and removed while traffic runs.
- Optional replication of a key to the next R nodes on the ring.

Non-functional

- Each node: LRU eviction (least recently used first) within a memory cap.
- When going from 4 to 5 nodes, at most about 25% of keys move.
- Key distribution across nodes within plus or minus 10% of even with 100+ virtual nodes each.
- 50,000 ops/s across 4 nodes on a laptop.

The architecture



- **Cache nodes**: a hash map plus doubly linked list for LRU, with a byte budget.
- **Client and ring**: each physical node is placed at many points (virtual nodes) on a 64-bit ring. A key goes to the first point clockwise from its hash.
- **Membership config**: a list of live nodes in a file or etcd, watched by clients.

Data model

Structure	Purpose
Sorted array of `(hash, nodeId)`	The ring. Binary search finds the owner
`HashMap<key, Entry>` plus linked list	LRU cache on each node
`Entry{value, expiresAt, size, leaseToken}`	Value with TTL and optional lease

Tech stack

Component	Choice	Why
Nodes	Java 25 with Netty or virtual threads, or Python asyncio	Network server practice
Hash	xxHash or MurmurHash3 64-bit	Fast, well distributed
Membership	Static file first, then etcd	Learn the simple path first
Bench	A custom load generator with Zipf keys	Realistic skew

Milestones

1. **Single node LRU with TTL.** Done when eviction respects the memory cap and TTLs expire lazily and by a sweeper.
2. **Mod-N client.** Measure: going 4 to 5 nodes moves about 80% of keys. Keep the number for comparison.
3. **Ring with virtual nodes.** Done when 4 to 5 moves about 20% and load is even within 10%.
4. **Live membership.** Done when clients pick up node changes within 2 s and errors during the change stay below 0.1%.
5. **Replication and hot keys.** Write to R=2 nodes, read from either. Done when killing one node keeps hit rate above 90% for replicated keys.
6. **Leases.** On a miss the node hands the first requester a lease token. Others are told to wait briefly. Only the token holder can fill. Done when 1,000 simultaneous misses on one key cause one database query.

Deep dive: the hard parts

- **Why virtual nodes.** With one point per server, arcs are uneven and one server can own twice its share. Many points per server average this out and spread a dead server's keys across all survivors instead of one neighbour.

- **Membership disagreement.** During a change, some clients see the new ring and some the old. They write the same key to different nodes, and a later reader may hit a stale copy. TTLs bound the damage. Versioned membership plus a short dual-read window reduces it.
- **Leases.** Facebook's paper describes leases solving two problems: stale sets (a slow writer overwriting a newer value after a delete) and herds. A delete invalidates outstanding leases, so a slow filler cannot write old data back.

Testing strategy

- Statistical tests of key spread and movement for several node counts.
- Chaos: kill a node under load, measure hit rate and database QPS over time.
- Herd test: expire a hot key and count database queries.

Trade-offs, scaling and failure modes

- Client-side routing is fast but every client needs the ring. A proxy (like mcrouter) centralises routing at the cost of a hop.
- Replication doubles memory and writes. Use it only for hot or expensive keys.
- Cold cache after a big topology change can overload the database. Warm new nodes gradually, or move a few virtual nodes at a time.

Stretch goals

- Implement Jump Consistent Hash and rendezvous hashing and compare movement and speed.
- Gossip-based membership (a preview of Project 26).

Skills practised

- M3 — Storing Data: sharding and consistent hashing.
- M4 — Caching: eviction, stampede prevention.

In the interview

30-second answer: I built a memcached-like cache cluster with LRU nodes and a client library that routes keys with a consistent hash ring of virtual nodes. The key decision was the ring instead of `hash mod N` : I measured that going from 4 to 5 nodes moved about 80% of keys with mod-N and about 20% with the ring, which is the difference between a hit-rate collapse and a small dip. The hardest part was a thundering herd when a hot key expires, which I solved with Facebook-style leases so only one caller refills it. 1,000 simultaneous misses on one key caused a single database query, and the cluster handled 50,000 ops/s on 4 nodes.

Key terms to know:

- **Consistent hashing** — nodes and keys are hashed onto the same ring, and a key belongs to the first node clockwise. Adding a node moves only about 1/N of keys.
- **Virtual nodes (vnodes)** — each physical node is placed at many points on the ring, which evens out load and spreads a dead node's keys across all survivors.
- **Mod-N hashing** — `hash(key) mod N` . Changing N remaps almost every key.
- **LRU eviction** — when memory is full, evict the least recently used entry. Built from a hash map plus a doubly linked list.
- **Thundering herd / stampede** — many requests miss the same key at once and all hit the database.
- **Lease** — a token handed to the first requester on a miss. Only the token holder may fill the key, and a delete invalidates outstanding leases.
- **Stale set** — a slow writer puts an old value back after a newer delete. Leases prevent it.
- **Membership** — the list of live nodes, in a file or etcd, watched by every client.
- **Hot key replication** — storing a key on the next R nodes so reads spread out and one node failure does not cause misses.

- **Jump consistent hash / rendezvous hashing** — alternatives to rings with different trade-offs.

Q: Why not just use `hash(key) mod N`?

A: When N changes from 4 to 5, a key stays put only if its hash gives the same result mod 4 and mod 5, which is true for about 1 in 5 keys. So roughly 80% of keys move, the hit rate collapses and the full load hits the database exactly when you were adding capacity. Consistent hashing moves only about 1/N of keys.

Q: What problem do virtual nodes solve?

A: With one point per server, arcs on the ring are uneven, so one server can own twice its share. When it dies, all its keys go to a single neighbour, which may then fall over too. With 100+ points per server, load averages out within about 10%, and a dead server's keys spread across all the others.

Q: How do you stop a thundering herd on one key?

A: On a miss, the node gives the first requester a lease token and tells other requesters to wait briefly and retry. Only the token holder may fill the key. The others then read the new value, so 1,000 misses become one database query.

Q: How do leases prevent stale data?

A: Suppose a reader misses, starts loading from the database, and meanwhile someone updates the row and deletes the cache key. Without leases, the slow reader then writes the old value back. The delete invalidates the outstanding lease, so the slow reader's set is rejected.

Q: During a membership change, clients disagree about the ring. What goes wrong?

A: Some clients send a key to the old owner and some to the new one, so a later read can hit a stale copy. TTLs bound how long stale data lives. Versioned membership and a short window where clients read from both old and new owners reduce the damage.

Q: A node dies. What happens to hit rate and the database?

A: Its keys now map to the survivors, which do not have them, so those keys miss until refilled. With vnodes the extra misses spread across all nodes. Replicating hot or expensive keys to R=2 nodes keeps their hit rate above 90% through the failure.

Q: Client-side routing or a proxy like mcrouter?

A: Client routing has no extra hop and no central bottleneck, but every client needs the ring and must be updated on changes. A proxy centralises routing and connection pooling and makes clients simple, at the cost of an extra hop and another tier to run.

Q: What changes when you go from 4 to 40 nodes?

A: Movement per change gets smaller (about 1/40), but membership changes happen more often, so automated membership through etcd or gossip matters. Adding many empty nodes at once still sends a burst to the database, so add them gradually or move a few vnodes at a time.

Q: How do you test it?

A: Statistical tests of key spread and movement for several node counts, compared with the mod-N baseline. A chaos test kills a node under load and graphs hit rate and database queries over time. A herd test expires a hot key and counts database queries.

Q: Hands-on: how does the client find a key's owner?

A: The ring is a sorted array of vnode hashes. Binary search finds the first hash at or after the key's hash, wrapping to the start:

```
long h = hash64(key);
int i = Arrays.binarySearch(ringHashes, h);
if (i < 0) i = -i - 1;          // insertion point
if (i == ringHashes.length) i = 0;
return ringNodes[i];
```

Common mistakes in answers:

- Saying consistent hashing moves "no keys". It moves about 1/N, the minimum needed.
- Explaining the ring without virtual nodes, which leaves load uneven and failures concentrated on one neighbour.
- Using a simple lock for stampedes but forgetting stale sets, which leases also solve.

TL;DR

A ring with virtual nodes keeps key movement near 1/N. Leases and replication protect the database when keys or nodes go away.

17. API gateway

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M5, M8

What it is

A reverse proxy that sits in front of several microservices and handles cross-cutting concerns once: routing by path and host, authentication with JWTs (JSON Web Tokens: signed tokens carrying identity claims), rate limiting, request IDs, timeouts, retries, circuit breaking and access logs. You build the core yourself, then compare it with Envoy.

The problem it solves

Without a gateway, every service re-implements auth, limits and logging slightly differently, and clients must know every service's address. A gateway gives one entry point and one place to enforce policy. It also becomes a critical shared component: if it is slow or down, everything is.

Real-world examples

- Envoy's documentation covers its filter chain architecture, routing, retries, outlier detection and rate limiting. It is the data plane behind several gateways and service meshes.
- Netflix's Zuul is an open-source edge gateway built around filters.

Requirements


Functional

- Route table: host and path prefix to upstream cluster, with path rewrite.
- JWT validation against a JWKS endpoint (a published set of signing keys), with key caching.
- Per-consumer rate limits (reuse Project 3).
- Inject `X-Request-ID` and trace headers. Structured access log per request.
- Per-route timeout, retry policy (idempotent methods only) and circuit breaker.
- Hot reload of routes without dropping connections.

Non-functional

- Added latency under 2 ms p99 for a pass-through request.
- 10,000 requests/s on one instance.
- Horizontally scalable: no state in the gateway except caches.

The architecture



- **Filter chain**: an ordered list of steps each request passes through. Each filter can reject, modify or pass.
- **Router**: picks an upstream cluster and a healthy instance (round-robin or least-requests).
- **Config store**: route definitions in a file or database, pushed to gateways on change.

Data model



Tech stack

Component	Choice	Why
Gateway	Java 25 with Netty or Spring Cloud Gateway, or Python with an async proxy	Non-blocking I/O
Limits	Redis	Shared counters
Config	YAML file plus a watch, later PostgreSQL	Hot reload
Comparison	Envoy	Industrial reference

Milestones

1. **Reverse proxy with a static route table.** Done when two upstreams are reachable via paths.
2. **Streaming bodies and connection pooling.** Done when a 1 GB upload passes through with flat memory.
3. **Auth filter.** Done when expired, wrongly signed and missing tokens are rejected and JWKS keys are cached and refreshed on unknown key ID.
4. **Rate limit, request ID and access logs.** Done when logs show one structured line per request with latency and upstream.
5. **Resilience.** Timeouts, retries on idempotent methods with budget, outlier ejection of failing instances. Done when killing an upstream instance causes at most a brief error blip.
6. **Hot reload and Envoy comparison.** Done when a route change applies without dropped requests, and you have the same setup working in Envoy with a latency comparison.

Deep dive: the hard parts

- **Streaming.** Buffering whole bodies is the classic gateway mistake: memory explodes on large uploads. Proxy as streams and only buffer when a filter truly needs the body.
- **Retries at the edge.** Retrying a `POST` can duplicate an order. Only retry idempotent methods or requests carrying an idempotency key, and only when the failure happened before the upstream received the request (connect errors) unless the call is idempotent.
- **Auth caching and revocation.** JWTs are verified locally, so revoking one before expiry needs a deny-list or short expiries plus refresh tokens.
- **Config safety.** A bad route pushed to every gateway at once is a global outage. Validate config, roll it out gradually and keep the last good config.

Testing strategy

- Conformance tests for routing, headers and auth cases.
- Latency overhead benchmark vs. direct upstream.
- Fault injection on upstreams with Toxiproxy.

Trade-offs, scaling and failure modes

- Gateway vs. service mesh: a gateway handles north-south traffic (clients to services). A mesh sidecar handles east-west traffic (service to service). Many companies run both.
- Putting business logic in the gateway couples it to every team's release cycle. Keep it to cross-cutting policy.

Stretch goals

- gRPC and WebSocket pass-through.
- A control plane API that pushes config using Envoy's xDS protocol.

Skills practised

- M8 — API and Edge: reverse proxy, API gateway, rate limiting, sidecar.
- M5 — Reliability: timeouts, retries, circuit breaking.
- M9 — Operating in Production: tracing headers, safe config rollout.

In the interview

30-second answer: I built an API gateway as a reverse proxy with a filter chain (JWT auth, rate limiting, request IDs, access logs) and a router with per-route timeouts, retries and outlier ejection, then compared it with Envoy. The key decision was keeping the gateway stateless and streaming request and response bodies, because it sits in front of every service and must scale horizontally with flat memory. The hardest parts were safe retries, only for idempotent requests and within a budget, and safe config rollout, because a bad route pushed everywhere is a global outage. It added under 2 ms p99 at 10,000 requests/s and passed a 1 GB upload with flat memory.

Key terms to know:

- **Reverse proxy** — a server that receives client requests and forwards them to backend services.
- **Filter chain** — an ordered list of steps (auth, limits, logging) each request passes through. Any filter can reject, modify or pass.
- **JWT** — a signed token carrying identity claims. The gateway verifies the signature locally.
- **JWKS** — the published set of public signing keys. Cached, and refreshed when a token has an unknown key ID.
- **Streaming vs buffering** — forwarding bodies chunk by chunk instead of loading them into memory.
- **Idempotent methods and retry budget** — GET, PUT and DELETE are safe to retry. A budget caps retries at a small share of traffic.
- **Outlier ejection** — temporarily removing an upstream instance that returns too many errors.
- **Hot reload** — applying new routes without restarting or dropping connections.
- **North-south vs east-west traffic** — client-to-service traffic (gateway) versus service-to-service traffic (service mesh).
- **Request ID / trace headers** — an ID injected at the edge and passed through every service so logs and traces can be joined.

Q: What belongs in a gateway, and what does not?

A: Cross-cutting policy that every service needs: TLS termination, authentication, rate limits, routing, request IDs and access logs. Business logic does not, because it would tie every team's releases to the gateway's release cycle and make the shared component riskier to change.

Q: How do you stop the gateway from becoming a bottleneck?

A: Keep it stateless so you can add instances behind the load balancer. Stream bodies instead of buffering, reuse upstream connections through pools, and verify JWTs locally with cached keys instead of calling an auth service per request. Shared state such as rate-limit counters lives in Redis.

Q: When should the gateway retry?

A: Only for idempotent requests, or requests carrying an idempotency key, and only within the request's deadline and a retry budget. A failed connection, where the upstream never received the request, is safe to retry for any method. Retrying a `POST` that timed out can create a second order.

Q: Why is buffering bodies the classic gateway mistake?

A: A gateway handling many large uploads at once would hold every body in memory and run out of heap. Streaming forwards chunks as they arrive, so memory stays flat no matter the size. Only buffer when a filter truly needs the whole body, and cap the size.

Q: JWTs are verified locally. How do you revoke one before it expires?

A: Local verification means the gateway never asks anyone whether a token is still valid. Use short expiries (minutes) with refresh tokens so a revoked user loses access quickly, and add a small deny-list of revoked token IDs for urgent cases. That is the trade-off for not calling an auth service on every request.

Q: An upstream instance starts returning 500s. What happens?

A: Outlier ejection removes it from the load-balancing pool after a run of errors, and traffic goes to healthy instances. A per-route circuit breaker fails fast if the whole cluster is unhealthy. Idempotent

requests that failed may be retried once on another instance.

Q: You push a bad route config. How do you limit the damage?

A: Validate config before accepting it, roll it out to one gateway or a small percentage first, and keep the last good config to roll back instantly. Gateways should refuse an invalid config and keep running the old one rather than crash.

Q: Gateway or service mesh?

A: A gateway handles traffic entering from clients. A mesh puts a sidecar proxy next to each service to handle traffic between services, with mTLS and retries. Many companies run both, often with the same proxy (Envoy) underneath.

Q: How do you test it?

A: Conformance tests cover routing, header injection and auth cases (expired, wrongly signed, missing token). A benchmark measures added latency against calling the upstream directly. Toxiproxy injects upstream faults, and killing an upstream instance must cause at most a brief error blip.

Common mistakes in answers:

- Retrying every failed request at the edge, which duplicates non-idempotent writes.
- Calling an auth service on every request instead of verifying JWTs locally with cached keys.
- Putting business rules in the gateway, turning a shared policy layer into a deployment bottleneck.

TL;DR

A gateway is a filter chain plus a router. Stream everything, retry carefully, and roll out its config as cautiously as code.

18. CQRS and event-sourced orders

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** M3, M10

What it is

An order management service where the source of truth is an append-only **event store** (every change is recorded as an event: `OrderCreated`, `ItemAdded`, `OrderPaid`), current state is rebuilt by replaying events, and separate **read models** (query-optimised tables) are built by projections. Splitting the write model from read models is **CQRS** (command query responsibility segregation).

The problem it solves

A single table that stores only current state loses history: you cannot answer "what did this order look like before the discount?" or rebuild a report after a bug. Different screens also need different shapes of data (customer history, warehouse pick lists, finance totals), and one normalised schema serves none of them well. Event sourcing keeps full history, and CQRS lets each reader get its own model.

Real-world examples

- Martin Fowler's Event Sourcing and CQRS articles define both patterns and warn that CQRS adds real complexity and suits only some domains.
- Module 3 of this book covers event sourcing and CQRS with their costs.

Requirements

Functional


- Commands: create order, add or remove item, apply coupon, pay, ship, cancel. Each validated against current state.
- Event store with optimistic concurrency: append fails if the stream version moved.
- Read models: order detail, customer order history, daily sales totals.

- Rebuild any read model from scratch by replaying.
- Temporal query: state of an order at a given time.

Non-functional


- Command p99 under 50 ms. Read model lag under 1 s p95.
- 1 million events replayable into a fresh read model in under 5 minutes.

The architecture



- **Command handler**: loads an aggregate's events, folds them into current state, validates the command, appends new events.
- **Event store**: append-only table with a unique `(stream_id, version)`.
- **Projections**: consumers that update read tables, tracking their own position for restart and rebuild.
- **Query API**: reads only from read models.

Data model



Add a unique index on `(stream_id, version)`.

Tech stack

Component	Choice	Why
Event store	PostgreSQL	Unique index gives optimistic concurrency
Transport	Kafka via outbox or CDC (Project 14)	Fan-out to projections
Read DB	PostgreSQL (separate schema) or Elasticsearch for search	Shape per query
Language	Java 25 records and sealed interfaces, or Python dataclasses	Clean event types

Milestones

1. **Aggregate and events in memory.** Done when unit tests express "given events, when command, then events".

2. **Event store with concurrency.** Done when two concurrent commands on one order produce one success and one conflict that retries.
3. **Projections.** Done when all three read models update within 1 s.
4. **Rebuild.** Done when deleting a read model and replaying restores it identically.
5. **Snapshots.** Every 100 events. Done when loading an order with 10,000 events stays under 10 ms.
6. **Event versioning.** Change `ItemAdded` to include a currency. Done when old events are upcast (converted on read) and replay still works.

Deep dive: the hard parts

- **Eventual consistency for readers.** After a command, the read model may not show the change yet. Return the new version from the command, and let the query API wait until the projection reaches it if the user must see their own write.
- **Events are forever.** You cannot edit history, only add compensating events. Schema evolution needs upcasters, and deleting personal data (for GDPR) needs designs like keeping personal data outside events or encrypting it per user and deleting the key.
- **Projection idempotency.** Projections may process an event twice after a crash. Store the checkpoint in the same transaction as the read-model update.

Testing strategy

- Given-when-then tests for every command.
- Replay determinism: replay twice, compare read models byte for byte.
- Concurrency tests for version conflicts.

Trade-offs, scaling and failure modes

- Event sourcing adds real complexity. Use it where history and audit carry business value (orders, money, workflows), not for every table.
- Global ordering across all streams is expensive. Usually per-stream order is enough.
- A bug in a projection is cheap to fix: fix code, rebuild. A bug that wrote wrong events is expensive: you need compensating events.

Stretch goals

- Temporal debugging UI that scrubs through an order's history.
- Process manager that reacts to `OrderPaid` by issuing `ReserveStock` (a preview of Project 19).

Skills practised

- M3 — Storing Data: event sourcing and CQRS.
- M10 — Batch and Streaming: projections as stream consumers.

In the interview

30-second answer: I built an order service where the source of truth is an append-only event store in PostgreSQL. Commands load an order's events, fold them into current state, validate, and append new events. Separate projections build three read models (order detail, customer history, daily sales) from those events. The key decision was optimistic concurrency through a unique `(stream_id, version)` index, so two concurrent commands on one order give one success and one retry with no locks. The hardest part was that readers are eventually consistent, so commands return the new version and the query API can wait for the projection to reach it. Read-model lag stays under 1 s p95, and 1 million events replay into a fresh read model in under 5 minutes.

Key terms to know:

- **Event sourcing** — storing every change as an immutable event and deriving current state by replaying them.
- **Aggregate / stream** — one entity's events, here one order, with its own version counter.

- **Fold** — applying events in order to build current state.
- **Optimistic concurrency** — append with an expected version. If the stream moved, the unique index rejects the write and the command retries.
- **CQRS** — separate models for writes (commands) and reads (queries).
- **Projection / read model** — a consumer that turns events into query-shaped tables. It can be deleted and rebuilt.
- **Checkpoint** — a projection's last processed position, stored in the same transaction as its update.
- **Snapshot** — saved state every 100 events, so loading a long stream does not replay everything.
- **Upcasting** — converting old event versions to the new shape when reading them.
- **Compensating event** — the only way to "fix" history: append a new event that reverses an earlier one.

Q: What does event sourcing buy you?

A: Full history and audit for free, because nothing is overwritten. You can answer "what did this order look like before the discount?" by replaying up to a point in time. You can also build brand-new read models from past events, or fix a buggy projection by rebuilding it.

Q: How does optimistic concurrency work in the event store?

A: A command reads the order at, say, version 7 and appends its new event as version 8. If another command already wrote version 8, the unique index on `(stream_id, version)` rejects the insert. The losing command reloads, re-validates against the new state and tries again.

Q: How do you handle read-your-own-writes with CQRS?

A: The command returns the new stream version. The query API can wait briefly until the projection's checkpoint reaches that version before answering. For a single screen that must be instant, it can read the write model directly by folding the stream.

Q: Why do you need snapshots?

A: An order with 10,000 events would need all 10,000 folded on every command. A snapshot stores state at, say, version 9,900, so loading means reading the snapshot plus 100 events. Snapshots are an optimisation and can always be rebuilt from events.

Q: A projection crashes halfway through an event. What happens?

A: On restart it resumes from its checkpoint and may process that event again. Because the checkpoint is stored in the same transaction as the read-model update, either both committed or neither did. So the event is applied exactly once in effect.

Q: You need to change the shape of an event. How?

A: You cannot rewrite stored events. Add a new version of the event, and register an upcaster that converts old events to the new shape when they are read. Replay then works on old and new events alike.

Q: How do you delete a customer's personal data when events are forever?

A: Keep personal data out of events and reference it by ID, or encrypt it per user and delete the key (crypto-shredding). The events remain, but the personal data is unreadable.

Q: What changes at 10x the events?

A: Per-stream work stays the same thanks to snapshots. The event table grows large, so partition it by time or stream. Projections become the bottleneck, so run them in parallel partitioned by stream ID, which is safe because order only matters within a stream. Rebuilds take longer, so build a new read model alongside the old one and switch over when it catches up.

Q: How do you test it?

A: Given-when-then tests for each command: given these past events, when this command, then these new events. A replay determinism test replays twice and compares read models byte for byte. Concurrency tests check that version conflicts produce one success and one retry.

Q: When would you avoid event sourcing?

A: In simple CRUD domains where history has no business value. It adds event versioning, eventual consistency and projection operations. Use it where audit and history matter, such as orders, money and workflows.

Common mistakes in answers:

- Treating CQRS and event sourcing as the same thing. CQRS can use ordinary tables, and event sourcing can have a single read model.
- Saying you can edit or delete wrong events. You append compensating events instead.
- Ignoring that read models lag, then promising users they will see their write immediately.

TL;DR

Events are the truth, state is a fold, read models are disposable projections. Powerful for history-heavy domains, costly everywhere else.

19. Saga-based checkout

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M5, M7

What it is

An e-commerce checkout spanning four services (orders, inventory, payments, shipping), each with its own database. A **saga** coordinates them: a sequence of local transactions where each step has a **compensating action** that undoes it if a later step fails. You build an orchestrated saga with a durable state machine, then compare it with a Temporal workflow.

The problem it solves

When each service owns its data, you cannot use one database transaction across them. Two-phase commit (2PC: a coordinator asks all participants to prepare, then commit) locks resources across services and blocks if the coordinator dies. Sagas give up atomic isolation in exchange for availability: every step commits locally, and failures are undone by compensation.

Real-world examples

- Garcia-Molina and Salem's original Sagas paper (1987) introduced long-lived transactions broken into steps with compensations.
- Chris Richardson's Saga pattern compares choreography (services react to events) with orchestration (a coordinator tells services what to do).
- Temporal's workflow docs describe durable execution: workflow code whose state survives crashes by replaying an event history.

Requirements


Functional

- Checkout steps: create order (pending) → reserve stock → authorise payment → create shipment → mark order confirmed.
- On failure at any step, compensate completed steps in reverse: cancel shipment, void payment, release stock, cancel order.
- Each step and compensation is idempotent and retried until it succeeds or is marked for manual action.
- Status endpoint shows saga progress.

Non-functional


- Happy path under 1 s p95.
- Survives a crash of the orchestrator or any service at any point without leaving partial state.
- 200 checkouts/s.

The architecture



- **Orchestrator**: a state machine per checkout. It persists the current state, sends a command, waits for a reply, moves on or compensates.
- **Saga log**: durable record of each saga's state and step history.
- **Participants**: each consumes commands, does a local transaction with an inbox for dedup, and replies via its own outbox.

Data model



Tech stack

Component	Choice	Why
Services	Spring Boot 4.1.1 or FastAPI, one DB schema each	Real service boundaries
Messaging	Kafka with outbox (Project 14)	Reliable commands and replies
Orchestration	Hand-rolled state machine, then Temporal	Learn the mechanics, then the tool
Chaos	Random process kills via a script	Exercise recovery

Milestones

1. **Happy path, synchronous.** Done when checkout works over HTTP calls.
2. **State machine with saga log.** Done when restarting the orchestrator mid-saga resumes from the stored step.
3. **Async commands with outbox and inbox.** Done when duplicated messages never double-reserve or double-charge.
4. **Compensation.** Done when payment decline releases stock and cancels the order.
5. **Timeouts.** A step without reply by its deadline is retried, then compensated. Done when a hung shipping service leads to a clean rollback.
6. **Temporal port.** Rewrite the orchestrator as a Temporal workflow. Done when the same chaos tests pass and you can list what Temporal handled for you.

Deep dive: the hard parts

- **No isolation.** Between steps, other transactions can see intermediate state ("reserved but not paid"). Use **semantic locks** (a status like `PENDING` that others respect) and design so intermediate states are harmless.
- **Compensations can fail.** A void after a successful capture may be refused. Compensations must be retried indefinitely and, after a threshold, raise a manual task. Some steps are not compensable at all (an email sent). Order steps so irreversible ones come last (the **pivot** transaction).
- **Timeout ambiguity.** A timed-out payment may have succeeded. Before compensating, query the participant's status by the saga's idempotency key.

Testing strategy

- Fault injection at every step and every compensation, including crashes between "action done" and "reply sent".
- Invariant check after each run: either all four local states are "done" or all are "undone".

Trade-offs, scaling and failure modes

- Orchestration: one place to see the flow, a central component. Choreography: no coordinator, but the flow is spread across services and hard to follow beyond three or four steps.
- Sagas give eventual consistency. Users may briefly see "processing". Design the UX for it.

Stretch goals

- Partial compensation (one item out of stock: ship the rest after customer consent).
- Saga dashboard showing stuck sagas and a "retry" or "force compensate" button.

Skills practised

- M7 — Consistency: 2PC vs. saga.
- M5 — Reliability: idempotency, timeouts, retries.
- M10 — Batch and Streaming: outbox and exactly-once processing.

In the interview

30-second answer: I built a checkout that spans four services (orders, inventory, payments, shipping), each with its own database, coordinated by an orchestrated saga: a durable state machine that runs one local transaction per step and runs compensations in reverse when a step fails. The key decision was a saga instead of two-phase commit, because 2PC holds locks across services and blocks if the coordinator dies. The hardest parts were that compensations can fail and timeouts are ambiguous, so every step is idempotent, compensations retry until they succeed or raise a manual task, and before compensating a timed-out payment I query its real status. It survived crashes at every step without partial state, at 200 checkouts/s.

Key terms to know:

- **Saga** — a sequence of local transactions where each step has a compensating action that undoes it.
- **Compensating action** — the semantic undo of a step, such as void payment or release stock. It is a new action, not a rollback.
- **Two-phase commit (2PC)** — a coordinator asks all participants to prepare, then commit. Atomic, but locks resources and blocks if the coordinator fails.
- **Orchestration vs choreography** — a central coordinator issues commands, versus services reacting to each other's events.
- **Saga log** — the durable record of each saga's state, so a restarted orchestrator resumes where it stopped.
- **Outbox and inbox** — reliable sending of commands and replies, and deduplication of received messages (Project 14).
- **Semantic lock** — a status such as `PENDING` that other operations respect, since sagas have no isolation.
- **Pivot transaction** — the step after which the saga can only go forward. Irreversible steps go last.
- **Durable execution (Temporal)** — workflow code whose state survives crashes by replaying its event history.

Q: Why not use 2PC across the four services?

A: In 2PC, every participant holds its locks from "prepare" until the coordinator says "commit". If the coordinator crashes in between, participants are stuck holding locks. It also needs every service's database to support it. Sagas commit each step locally right away and undo with compensations, trading isolation for availability.

Q: What does "sagas have no isolation" mean in practice?

A: Between steps, other transactions can see intermediate states, such as stock reserved but not yet paid. You make those states explicit and harmless with semantic locks, such as an order status of `PENDING` that other flows respect. You also design so that a reader seeing the intermediate state does nothing harmful.

Q: What if a compensation fails?

A: Compensations must be idempotent and are retried with backoff, potentially for a long time, because giving up leaves inconsistent state. After a threshold, the saga raises a manual task for a human. Some steps cannot be undone at all, like sending an email, so they are placed after the pivot.

Q: The payment step times out. Do you compensate?

A: Not immediately, because a timeout does not mean failure: the payment may have succeeded. The orchestrator queries the payment service using the saga's idempotency key. If it succeeded, the saga continues. If it failed or never happened, compensate.

Q: The orchestrator crashes mid-saga. What happens?

A: Its state and step history are in the saga log. On restart it reloads unfinished sagas and resumes from the stored step, resending the last command if needed. Participants dedupe with their inbox tables, so a resent command does not double-reserve or double-charge.

Q: Orchestration or choreography?

A: Orchestration puts the whole flow in one place, which makes it easy to see, change and debug, at the cost of a central component. Choreography has no coordinator, but the flow is spread across services' event handlers and gets hard to follow beyond three or four steps. I chose orchestration for a five-step checkout with compensations.

Q: What did Temporal handle for you?

A: Persisting workflow state, retries with backoff, timers and timeouts, and resuming after crashes by replaying the workflow's history. The hand-rolled version needed a saga log, a timeout scanner and retry bookkeeping. The constraint is that workflow code must be deterministic, so side effects go in activities.

Q: What changes at 10x checkouts?

A: The orchestrator is stateless apart from the saga log, so run several instances and partition sagas by ID. Kafka topics for commands and replies get more partitions, keyed by saga ID to keep each saga's messages ordered. The saga log grows, so archive completed sagas.

Q: How do you prove it never leaves partial state?

A: Inject faults at every step and every compensation, including crashes between "action done" and "reply sent". After each run, check an invariant: either all four local states are done or all are undone. Run it many times with random kill points.

Common mistakes in answers:

- Describing compensation as a database rollback. Each step already committed, so compensation is a new forward action.
- Treating a timeout as a failure and compensating without checking what actually happened.
- Forgetting idempotency. Every step and compensation will eventually be delivered twice.

TL;DR

A saga is a durable state machine of local transactions with compensations. Make every step idempotent, persist progress, and place irreversible steps last.

20. Metrics and alerting pipeline

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M9, M16

What it is

A small monitoring system: agents push metrics (named time series like `http_requests_total{service="api",status="500"}`), an ingest tier writes them into a time-series store you build on compressed blocks, a query API supports rates and aggregations, and an alert evaluator fires notifications when rules hold for a duration.

The problem it solves

You cannot operate what you cannot see. Metric data is large (many series times many points) but very regular: timestamps arrive at fixed intervals and values change slowly. A general-purpose database wastes space and is slow for "rate over 5 minutes, summed by service". Purpose-built storage compresses points to a byte or two and answers range queries fast.

Real-world examples

- Facebook's Gorilla paper (VLDB 2015) describes delta-of-delta timestamp encoding and XOR value compression for an in-memory time-series database.

- Prometheus's overview explains its data model of metric names plus labels, pull-based scraping and alerting rules.

Requirements


Functional

- Ingest: `POST /write` with batches of `(series labels, timestamp, value)`.
- Query: range query with `rate()`, `sum by (label)`, and instant queries.
- Alert rules: expression, threshold, `for: 5m`, labels. Notifications to a webhook with dedup and grouping.
- Retention: raw 15 days, 5-minute rollups for 1 year.

Non-functional

- 100,000 samples/s ingest on one node.
- Under 2 bytes per sample on disk after compression.
- Query of 24 hours for 100 series under 200 ms.
- Alert evaluation every 15 s.

The architecture



- **Ingest API**: validates and appends samples to the WAL and the head block.
- **Head block**: recent data in memory, per-series compressed chunks.
- **Blocks**: immutable files covering a time range with an index from label pairs to series IDs (an **inverted index**: label value to list of series).
- **Compactor**: merges blocks and writes downsampled rollups.
- **Alert evaluator and notifier**: run rules, track pending vs. firing state, group and dedupe notifications.

Data model

Structure	Purpose
`series_id -> labels`	Series dictionary
`label=value -> sorted series_ids`	Postings lists for selection
Chunk: delta-of-delta timestamps + XOR values	Compressed samples
Alert state: `inactive, pending, firing`	With `active_since`

Tech stack

Component	Choice	Why
Storage engine	Java 25 or Python 3.14 with bit-level encoding	Learn compression by doing
Rollups and alerts metadata	PostgreSQL	Rules and silences
Visualisation	Grafana with a simple JSON datasource	Free dashboards
Comparison	Prometheus	Reference behaviour

Milestones

1. **Data model and in-memory store.** Done when queries by label match a brute-force scan.
2. **Compression.** Done when synthetic data compresses below 2 bytes per sample and round-trips exactly.
3. **WAL and block flush.** Done when killing the process loses no acknowledged samples.
4. **Query functions.** `rate` with counter resets handled, `sum by`. Done when results match Prometheus on the same data within rounding.
5. **Alerting.** Done when a rule with `for: 5m` fires once, stays firing, resolves, and duplicate notifications are suppressed.
6. **Retention and downsampling.** Done when old raw blocks are deleted and long queries use rollups.

Deep dive: the hard parts

- **Cardinality.** Each unique label combination is a series. A label like `user_id` turns one metric into millions of series and kills memory and index size. Enforce per-metric series limits and reject high-cardinality labels at ingest.
- **Counter resets.** Counters restart from zero when a process restarts. `rate()` must detect a drop and treat it as a reset, not a huge negative rate.
- **Alert flapping.** A value hovering around the threshold fires and resolves repeatedly. `for:` durations and hysteresis (a lower resolve threshold) calm it.
- **Who watches the watcher?** If the alerting pipeline dies, you get silence, which looks like health. Add a "dead man's switch": an always-firing alert whose absence pages someone.

Testing strategy

- Golden-file tests for compression and query functions.
- Crash recovery from WAL.
- Alert state machine tests with a fake clock.

Trade-offs, scaling and failure modes

- Push vs. pull: pull (Prometheus) knows when a target is down. Push suits short-lived jobs and firewalled clients.
- Scale out by sharding series across ingest nodes by hash of labels, then fan out queries. That is what large-scale systems layer on top of a Prometheus-style engine.

Stretch goals

- Histograms and percentile queries.
- Multi-tenant ingest with per-tenant limits.

Skills practised

- M16 — Case Studies: Infrastructure: metrics monitoring and alerting.
- M9 — Operating in Production: health signals and alerting practice.
- M3 — Storing Data: write-ahead logs.

In the interview

30-second answer: I built a small Prometheus-style monitoring system: an ingest API writes samples to a write-ahead log and an in-memory head block, which is flushed every 2 hours into compressed, immutable blocks with an inverted index from labels to series. A query API supports `rate()` and `sum by`, and an alert evaluator runs rules every 15 s with pending and firing states. The key decision was Gorilla-style compression (delta-of-delta timestamps, XOR values), because metric data is extremely regular and it gets samples under 2 bytes each. The hardest problems were cardinality, which I cap at ingest, and noisy alerts, which `for:` durations and dedup solve. One node ingests 100,000 samples/s.

Key terms to know:

- **Time series** — a metric name plus a set of labels, with a sequence of (timestamp, value) samples.
- **Cardinality** — the number of unique label combinations, which is the number of series. It drives memory and index size.
- **Delta-of-delta encoding** — store the change in the gap between timestamps. Regular scrapes give zero, which takes 1 bit.
- **XOR value compression** — XOR each value with the previous one and store only the differing bits. Slowly changing values compress well.
- **Head block and WAL** — recent data in memory, protected by a write-ahead log so a crash loses no acknowledged samples.
- **Inverted index / postings list** — for each `label=value`, the sorted list of series IDs that have it. Queries intersect lists.
- **Counter reset** — a counter drops to zero when a process restarts. `rate()` must treat the drop as a reset.
- **Downsampling / rollups** — 5-minute summaries kept for a year after raw data expires after 15 days.
- **Alert states** — inactive, pending (condition true but `for:` not yet met), firing.
- **Dead man's switch** — an always-firing alert whose absence pages someone, proving the alerting pipeline is alive.

Q: Why not store metrics in PostgreSQL?

A: Each sample is an 8-byte timestamp and an 8-byte value, but a PostgreSQL row adds a header of roughly 24 bytes plus index entries, so overhead dwarfs the data. Queries like "rate over 5 minutes summed by service" scan many points per series. Compressed per-series chunks are often an order of magnitude smaller and much faster to scan.

Q: How do you get under 2 bytes per sample?

A: Timestamps arrive at a fixed interval, so the delta of deltas is usually zero and costs one bit. Values change slowly, so XOR with the previous value is mostly zero bits and stores only the meaningful middle bits. Facebook's Gorilla paper reports about 1.37 bytes per sample on real data.

Q: What is cardinality, and why does it matter?

A: Every unique combination of label values is a separate series with its own memory and index entries. Adding a label like `user_id` can turn one metric into millions of series and run the node out of memory. So I enforce per-metric series limits and reject high-cardinality labels at ingest.

Q: How does `rate()` handle a process restart?

A: A counter normally only goes up. If a sample is lower than the previous one, the process restarted and the counter reset to zero. `rate()` treats the new value as an increase from zero instead of computing a huge negative rate.

Q: How do you avoid alert noise?

A: A `for: 5m` duration means a rule must stay true for 5 minutes before firing, which ignores short spikes. Hysteresis uses a lower threshold to resolve than to fire, which stops flapping. The notifier groups related alerts and dedupes repeats, and alerts target user-facing symptoms, not every cause.

Q: The process crashes. What is lost?

A: Nothing that was acknowledged, because every sample is appended to the WAL before the write returns. On restart the head block is rebuilt by replaying the WAL. Older data is already in immutable blocks on disk.

Q: Push or pull?

A: Pull, as in Prometheus, means the server scrapes targets, so a failed scrape tells you the target is down and targets cannot flood you. Push suits short-lived batch jobs and clients behind firewalls. This build uses push for simplicity, so detecting a dead target needs an explicit "no data" alert.

Q: What changes at 100x ingest?

A: One node runs out of memory and CPU for the head block. Shard series across ingest nodes by a hash of their labels, replicate for availability, and fan queries out to every shard and merge results. Long-range queries use downsampled rollups, and old blocks move to object storage.

Q: How do you test it?

A: Golden-file tests for compression round-trips and query functions, with results compared against Prometheus on the same data. A crash test kills the process and checks recovery from the WAL. A fake clock drives the alert state machine through pending, firing and resolved.

Common mistakes in answers:

- Adding unbounded labels such as user ID or request ID to metrics. That belongs in logs or traces.
- Forgetting counter resets, which produce absurd negative rates.
- Not monitoring the monitoring system. Silence from a dead alert pipeline looks like health.

TL;DR

Metrics are regular data: compress with deltas and XOR, index labels with postings lists, guard cardinality, and make alerts stateful and quiet.

21. Proximity search service

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** M3, M15

What it is

A "find nearby" service for places (restaurants, shops): given a latitude, longitude and radius, return the closest matching places sorted by distance, with filters like category and "open now". You implement two spatial indexes, **geohash** (encodes a location as a string where a shared prefix means nearby cells) and PostGIS's R-tree-based GiST index, and compare them.

The problem it solves

A normal B-tree index handles one dimension. "Within 2 km of here" is two-dimensional, so filtering latitude and longitude separately scans a huge strip of the map. Spatial indexes turn the plane into cells or bounding boxes so a query touches only nearby data. The read path is heavy and latency-sensitive, while place data changes rarely.

Real-world examples

- Uber's H3 blog post explains why they built a hexagonal hierarchical grid: hexagons have uniform neighbour distances, which squares do not.
- Redis's geospatial docs describe `GEOADD` and `GEOSEARCH`, built on sorted sets with geohash-encoded scores.

Requirements


Functional

- `GET /nearby?lat=..&lng=..&radius=2000&category=cafe&limit=20`.
- CRUD for places by business owners. Changes visible within a minute.
- Results sorted by distance, with distance in metres.

Non-functional

- 10 million places worldwide, 5,000 queries/s, p99 under 50 ms.
- Writes are rare (about 100/s).
- Dense cities and empty deserts both handled gracefully.

The architecture



- **Nearby API**: computes the geohash cells covering the search circle, fetches candidates per cell (cache, then replica), filters by exact distance and attributes, sorts, trims.
- **Redis cell cache**: `cell:{geohash6} -> list of place summaries`. Cells are shared by many queries, so they cache far better than raw coordinates.
- **PostGIS replicas**: serve the read load. Writes go to the primary.
- **Cache invalidator**: deletes affected cells on place changes.

Data model

PLACE		
bigint	id	PK
text	name	
text	category	
numeric	lat	
numeric	lng	
text	geohash6	
jsonb	hours	
boolean	active	
timestamptz	updated_at	

Add a GiST index on a `geography(Point)` column and a B-tree on `geohash6`.

Tech stack

Component	Choice	Why
Database	PostgreSQL with PostGIS	Mature spatial index and distance functions
Cache	Redis	Cell-level caching
API	Spring Boot 4.1.1 or FastAPI	Simple read path
Data	OpenStreetMap extract	Realistic density

Milestones

1. **PostGIS baseline.** `ST_DWithin` on a geography column with GiST. Done when queries return correct results on a city extract.
2. **Geohash approach.** Compute the covering cells (centre plus 8 neighbours at a precision whose cell size exceeds the radius). Done when results equal the PostGIS baseline.
3. **Cell cache.** Done when the database sees only cache misses and hit rate exceeds 90% under a realistic query mix.

4. **Density handling.** In a dense centre a cell may hold thousands of places. Use finer precision there or an adaptive structure. Done when p99 stays under 50 ms for both Manhattan-like and rural queries.
5. **Writes and invalidation.** Done when an edited place shows correct data within 60 s.

Deep dive: the hard parts

- **Edge effects.** Two points across a cell boundary can be metres apart with completely different geohash prefixes. That is why you always query neighbours, not just the centre cell.
- **Precision choice.** Geohash cells halve in one dimension per bit. Pick a precision per radius. Adaptive structures (a **quadtree** that splits only dense cells) avoid overloaded cells in cities and empty cells elsewhere.
- **Distance on a sphere.** Euclidean distance on raw degrees is wrong away from the equator because a degree of longitude shrinks with latitude. Use the haversine formula or PostGIS geography types.

Testing strategy

- Compare geohash results with PostGIS on random queries (they must match exactly after the distance filter).
- Boundary tests at the antimeridian (longitude 180) and near the poles.
- Load test with queries clustered in cities, as real traffic is.

Trade-offs, scaling and failure modes

- Geohash in Redis or a key-value store is simple and shards well by prefix, but hot city prefixes skew load. PostGIS is accurate and flexible but scales by replicas, not sharding.
- Stale cache after an edit is usually fine for places. For moving objects (drivers), see Project 34.

Stretch goals

- Ranking by distance plus rating plus popularity.
- Implement a quadtree in memory and compare with geohash.

Skills practised

- M15 — Case Studies: Location and Real-Time: geohash, quadtree, S2 and H3.
- M3 — Storing Data: read replicas and sharding.
- M4 — Caching: cache keys designed for reuse.

In the interview

30-second answer: I built a "find nearby" service that returns places within a radius, sorted by distance, over 10 million places at 5,000 queries/s. The key decision was turning the two-dimensional search into lookups of geohash cells (the centre cell plus its 8 neighbours) and caching results per cell in Redis, because cells are shared by many queries and cache far better than raw coordinates. I compared it with a PostGIS GiST baseline, and both must return identical results after the exact distance filter. The hardest part was density skew, since a Manhattan cell can hold thousands of places, so I used finer precision there and kept p99 under 50 ms for both city and rural queries.

Key terms to know:

- **Geohash** — encodes latitude and longitude as a string by repeatedly halving the map. A shared prefix usually means nearby, and longer strings mean smaller cells.
- **Covering cells / neighbours** — the cells a search circle touches. Always the centre cell plus its 8 neighbours.
- **Edge effect** — two points a few metres apart across a cell boundary can have completely different geohash prefixes.

- **Quadtree** — a tree that splits a square into four only where it is dense, so cells adapt to density.
- **R-tree / GiST index** — PostGIS's spatial index of bounding boxes, used by `ST_DWithin`.
- **Haversine distance** — great-circle distance on a sphere. Euclidean distance on raw degrees is wrong away from the equator.
- **Cell cache** — `cell:{geohash6} -> place summaries` in Redis, invalidated through CDC when a place changes.
- **Read replicas** — copies of the database that serve the heavy read load. Writes go to the primary.
- **H3 / S2** — hexagonal (Uber) and spherical (Google) hierarchical grids, alternatives to geohash.

Q: Why can't a normal B-tree index answer "within 2 km"?

A: A B-tree orders by one value. An index on latitude finds a horizontal strip around the world, and filtering longitude still scans everything in that strip. Spatial indexes split the plane into cells or boxes so a query only touches nearby data.

Q: Why query the neighbouring cells, not just the centre one?

A: The user might stand near a cell edge, and a café 50 metres away can sit in the next cell with a different prefix. Querying the centre plus 8 neighbours at a precision where a cell is larger than the radius guarantees the whole circle is covered. Then an exact distance filter removes points outside the radius.

Q: Geohash or quadtree?

A: Geohash is a fixed grid: each place gets one string, which is easy to store, index, cache and shard by prefix. But cell sizes are the same everywhere, so cities overload cells and deserts are empty. A quadtree splits only dense areas, so cells hold similar counts, but it is an in-memory structure you must build and rebuild.

Q: Why is Euclidean distance on latitude and longitude wrong?

A: A degree of longitude is about 111 km at the equator but shrinks toward the poles. Treating degrees as flat coordinates over-weights east-west distance at high latitudes. Use haversine or PostGIS geography types, which compute distance on the sphere in metres.

Q: Why cache by cell instead of by query?

A: Every user stands at slightly different coordinates, so a cache keyed by exact location almost never hits. Many users fall into the same cell, so a cell cache gets over 90% hits. The API then filters and sorts the cell's candidates for each user in memory.

Q: A business owner edits their place. When do users see it?

A: The write goes to the primary, and CDC triggers the invalidator to delete the affected cell keys. The next query refills them from a replica, so the change appears within a minute. A short staleness window is acceptable for places, unlike moving drivers (Project 34).

Q: What changes at 10x queries?

A: Add read replicas and Redis capacity. Both scale horizontally because the read path is stateless. If the dataset outgrows one database, shard by geohash prefix, but city prefixes are hot, so split shards by measured load rather than evenly by prefix.

Q: What edge cases break naive implementations?

A: The antimeridian at longitude 180, where neighbours wrap from +180 to -180, and areas near the poles, where cells become very narrow. Dense cities where one cell has thousands of candidates, and empty areas where the radius finds nothing.

Q: How do you test correctness?

A: Run random queries against both the geohash path and PostGIS and require identical results after the distance filter. Add boundary tests at the antimeridian and poles. Load test with queries clustered in cities, as real traffic is.

Common mistakes in answers:

- Querying only the centre cell, which misses close points just across a boundary.
- Treating a shared prefix as the definition of "near". Close points can have different prefixes.
- Using one geohash precision for everything and ignoring density skew.

TL;DR

Turn 2D search into cell lookups, always include neighbours, cache by cell, and handle density skew explicitly.

22. Polite web crawler

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** M2, M13

What it is

A crawler that starts from seed URLs, fetches pages, extracts links and keeps going, while obeying `robots.txt`, limiting requests per host, avoiding duplicate URLs and duplicate content, and storing pages for later indexing. The heart is the **URL frontier**: the prioritised, per-host-throttled queue of URLs to fetch next.

The problem it solves

The web is huge, full of traps (infinite calendars, session IDs in URLs) and run by servers that will block you if you are rude. A crawler must stay polite per host while still keeping thousands of fetches in flight overall, must not fetch the same thing twice, and must resume after crashes without losing its place.

Real-world examples

- RFC 9309 standardises the Robots Exclusion Protocol: how crawlers must parse and apply `robots.txt`.
- The Mercator paper describes a scalable crawler design with a frontier of per-host queues, which most later crawlers follow.
- Common Crawl publishes open crawl archives and is a good dataset to compare against.

Requirements


Functional

- Seed list, configurable max depth and domain allow-list.
- Fetch, parse HTML, extract and normalise links, store raw content and metadata.
- Respect `robots.txt` (cached per host) and crawl-delay.
- Deduplicate URLs (seen set) and near-duplicate content (fingerprints).
- Recrawl pages on a schedule based on how often they change.

Non-functional


- 200 pages/s on a laptop across thousands of hosts.
- At most 1 request per host per second by default.
- Crash and resume without refetching everything.

The architecture



- **Frontier**: front queues by priority, back queues one per host, and a heap of hosts ordered by the next time they may be fetched.
- **Fetchers**: async HTTP clients with timeouts, size limits and redirects capped.
- **URL seen filter**: a Bloom filter for fast "probably seen" plus an exact store for confirmation.
- **Content fingerprint**: SimHash (a hash where similar documents get similar bit patterns) for near-duplicate detection.

Data model



Tech stack

Component	Choice	Why
Fetchers	Python 3.14 asyncio with httpx, or Java 25 virtual threads with HttpClient	Thousands of concurrent fetches
Frontier state	PostgreSQL (durable) plus in-memory heaps	Resume after crash
Pages	Object storage (MinIO) as WARC files	Standard archive format
Parsing	A tolerant HTML parser	Real HTML is messy

Milestones

1. **Single-threaded crawl of one site.** Done when it respects robots and depth.
2. **Per-host queues and politeness.** Done when logs show no host hit more than once per second while overall rate exceeds 100 pages/s.
3. **URL normalisation and dedup.** Lowercase host, remove default ports and fragments, sort query parameters, strip known tracking parameters. Done when variants of one URL are fetched once.
4. **Durable frontier.** Done when killing and restarting resumes without refetching completed URLs.
5. **Near-duplicate detection.** Done when mirrors and printer-friendly copies are flagged.
6. **Trap defences and recrawl.** Cap URLs per host and path depth. Recrawl interval adapts to observed change rate. Done when a synthetic infinite calendar is contained.

Deep dive: the hard parts

- **Politeness vs. throughput.** Politeness is per host. Throughput comes from many hosts at once. A heap keyed by "host may be fetched at" time lets fetchers always grab a ready host.
- **DNS is a bottleneck.** Resolving each URL from scratch is slow. Cache DNS per host with TTL.
- **Traps.** Generated URLs can be infinite. Limits per host, URL length caps and pattern detection (repeating path segments) keep the crawler sane.
- **Partitioning at scale.** With many crawler nodes, assign hosts to nodes by hash of hostname, so politeness stays local to one node.

Testing strategy

- A local fake web: a server generating linked pages with configurable traps, robots rules and duplicate content.
- Assert politeness from server-side request logs.
- Crash and resume tests.

Trade-offs, scaling and failure modes

- Bloom filters have false positives: a few new URLs will be wrongly skipped. Tune size to accept, say, 1 in 10,000.
- BFS (breadth-first) finds important pages early, while DFS gets stuck deep in single sites. Priority by link-based importance is better still.

Stretch goals

- JavaScript rendering for a subset of pages with a headless browser pool.
- Sitemap and RSS discovery.

Skills practised

- M13 — Case Studies: Building Blocks: the web crawler design.
- M2 — Moving Data: queues and backpressure.
- M5 — Reliability: timeouts and retries against unreliable servers.

In the interview

30-second answer: I built a web crawler that fetches pages from seed URLs, extracts and normalises links, obeys `robots.txt`, and stores pages as WARC files for later indexing. The key piece is the URL frontier: per-host queues plus a heap of hosts ordered by the next time each may be fetched, so every host gets at most 1 request per second while thousands of hosts are crawled in parallel. The hardest parts were not fetching things twice and not getting stuck, which I solved with URL normalisation, a Bloom filter in front of an exact seen-store, SimHash for near-duplicate content, and per-host limits for traps. It reached 200 pages/s on a laptop and resumes after a crash without refetching completed URLs.

Key terms to know:

- **URL frontier** — the prioritised, per-host-throttled queue of URLs to fetch next. Front queues by priority, back queues one per host.
- **Politeness** — never overload a host: default 1 request per second per host, plus any crawl-delay it asks for.
- **robots.txt (RFC 9309)** — a site's rules for which paths crawlers may fetch. Cached per host.
- **Ready-time heap** — a min-heap of hosts keyed by "may be fetched at", so fetchers always pick a host that is ready.
- **URL normalisation** — lowercase host, drop default ports and fragments, sort query parameters, strip tracking parameters, so variants of one URL count once.
- **Bloom filter** — a compact bit array that says "definitely not seen" or "probably seen". It has false positives but no false negatives.
- **SimHash** — a fingerprint where similar documents have similar bits, used to spot near-duplicates such as mirrors.
- **Crawler trap** — infinite generated URLs, like calendars or session IDs. Contained with per-host caps and path-depth limits.
- **DNS caching** — resolving each host once per TTL instead of per URL, since DNS lookups are slow.

Q: How do you stay polite and still be fast?

A: Politeness is per host and throughput comes from crawling many hosts at once. Each host has its own queue, and a heap orders hosts by the next time they may be fetched. Fetchers pop a ready host, take one URL, and push the host back with its next allowed time, so thousands of hosts run in parallel while each is throttled.

Q: How do you avoid fetching the same URL twice?

A: First normalise the URL, so `HTTP://Example.com:80/a?b=2&a=1#top` and `http://example.com/a?a=1&b=2` become the same string. Then check a Bloom filter: "definitely not seen" goes straight to the frontier, and "probably seen" is confirmed against an exact store. This keeps most checks in memory.

Q: What does the Bloom filter's false positive mean here?

A: A Bloom filter can wrongly say "probably seen" for a new URL. If you skip the exact check, that URL is never crawled. Size the filter for an acceptable rate, such as 1 in 10,000, or confirm positives against the exact store. It never says "not seen" for a URL you did add.

Q: How do you detect duplicate content at different URLs?

A: An exact content hash catches identical copies. Near-duplicates, such as printer-friendly pages or mirrors with a different footer, need SimHash. Similar documents have fingerprints that differ in only a few bits, so a small Hamming distance (number of differing bits) flags them.

Q: How do you handle crawler traps?

A: Cap URLs per host and path depth, cap URL length, and detect repeating path segments like `/a/b/a/b/a/b`. A synthetic infinite calendar in my fake web must stay within those caps. Without them, one site can absorb the whole crawl.

Q: The crawler crashes. What happens?

A: Frontier state and each URL's status are stored in PostgreSQL, and in-memory heaps are rebuilt from them on restart. Completed URLs are not refetched. A URL that was in flight is fetched again, which is harmless because storage is keyed by URL hash.

Q: How do you scale across many machines?

A: Partition by a hash of the hostname, so every host belongs to exactly one node. Politeness then stays a local decision, with no cross-node coordination. Discovered links for hosts owned by other nodes are forwarded to them.

Q: BFS or DFS?

A: Breadth-first finds important pages early, because well-linked pages are close to seeds. Depth-first gets stuck deep inside one site. A priority based on link importance (how many pages link to it) is better still.

Q: How do you test it?

A: A local fake web generates linked pages with traps, robots rules and duplicate content. Politeness is asserted from the fake server's own request logs, not the crawler's claims. Kill-and-resume tests check no completed URL is refetched.

Common mistakes in answers:

- One global queue with a global rate limit, which is either rude to some hosts or very slow overall.
- Skipping URL normalisation, so the same page is fetched under many spellings.
- Resolving DNS for every URL, which quietly becomes the main bottleneck.

TL;DR

Most crawler design lives in the URL frontier: per-host queues keep you polite, a ready-time heap keeps throughput high, normalisation plus Bloom filters stop repeats, and hard limits contain traps.

23. Real-time clickstream analytics

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M10

What it is

A streaming pipeline that ingests website click events into Kafka, computes per-minute page views, unique visitors and top pages with a stream processor using **event-time windows** (grouping by when the click happened, not when it arrived), and serves live dashboards. You handle late events with **watermarks** and get exactly-once results into the output store.

The problem it solves

Batch jobs give yesterday's answers. Product teams want to see a launch's effect within a minute. But events arrive late (mobile phones offline), out of order and sometimes twice. Counting correctly in real time means separating event time from processing time, deciding how long to wait for stragglers, and making failures not double-count.

Real-world examples

- Google's The Dataflow Model paper introduced the vocabulary of windows, watermarks and triggers used by Beam and Flink.
- Apache Flink's documentation covers event time, watermarks and checkpoint-based exactly-once state.

Requirements

Functional


- Ingest click events `{event_id, user_id, session_id, url, ts}` over HTTP into Kafka.
- 1-minute tumbling windows: page views per URL, unique users (approximate).
- Top 10 pages per 5-minute sliding window.

- Session windows: a session ends after 30 minutes of inactivity.
- Late events up to 10 minutes update results. Later ones go to a side output.

Non-functional

- 20,000 events/s. Dashboard freshness under 10 s.
- Exactly-once counts despite duplicate events and processor restarts.

The architecture



- **Collector**: validates, adds server receive time, writes to Kafka keyed by user ID.
- **Stream processor**: Flink or Kafka Streams, keyed state per URL and user, window operators, HyperLogLog (a small sketch that estimates distinct counts) for uniques.
- **Checkpoints**: periodic consistent snapshots of operator state plus Kafka offsets.
- **Results store**: upserts keyed by window and URL so replays overwrite rather than add.
- **Raw archive**: for batch backfills and reprocessing.

Data model

PAGE_MINUTE		
text	url	PK
timestamptz	window_start	PK
bigint	views	
bigint	uniques_est	
timestamptz	updated_at	

SESSION_SUMMARY		
text	session_id	PK
bigint	user_id	
timestamptz	started_at	
timestamptz	ended_at	
int	pages	

Tech stack

Component	Choice	Why
Broker	Kafka	Replayable, partitioned
Processor	Apache Flink (Java 25) or Kafka Streams, or PyFlink for Python	Event-time windows and state
Results	ClickHouse or PostgreSQL	Fast aggregates for dashboards
Load	A generator that injects late, duplicate and out-of-order events	Test the hard cases

Milestones

1. **Collector to Kafka.** Done when 20,000 events/s flow with no loss.
2. **Processing-time counts.** Done when a dashboard shows per-minute counts, and you can demonstrate them being wrong for delayed events.

3. **Event-time windows with watermarks.** Watermark = max event time seen minus 30 s. Done when shuffled events produce the same totals as a sorted batch run.
4. **Allowed lateness and side output.** Done when events 5 minutes late update their window and events 20 minutes late land in the late topic.
5. **Exactly-once.** Enable checkpoints, dedupe by `event_id` in state with a TTL, and write idempotent upserts. Done when killing the processor mid-run yields identical final results.
6. **Sessions and top-K.** Done when session counts and top pages match a batch reference.

Deep dive: the hard parts

- **Watermarks are a bet.** A watermark says "I believe no events older than T are still coming". Too aggressive and you drop late data. Too lax and results arrive late. Allowed lateness gives a second chance at the cost of updated (retracted) results downstream.
- **Exactly-once is end to end.** Flink's checkpoints give exactly-once *state*. The sink must be transactional (two-phase commit with Kafka) or idempotent (upsert by key) for exactly-once *output*.
- **Skew.** One viral URL makes one key hot. Pre-aggregate with a random salt (split the key into N sub-keys), then combine.

Testing strategy

- Deterministic replay test comparing streaming output with a batch computation over the raw archive.
- Chaos: kill task managers, restart Kafka brokers, assert results unchanged.
- Measure end-to-end latency from event time to dashboard.

Trade-offs, scaling and failure modes

- Lambda architecture (batch plus speed layer) vs. Kappa (one streaming path, reprocess by replay). This project is Kappa with a raw archive for backfills.
- State size grows with keys and window length. Use TTLs and RocksDB-backed state for large state.

Stretch goals

- Funnel analysis (view → add to cart → purchase) with pattern detection.
- Anomaly alerts when traffic deviates from a seasonal baseline.

Skills practised

- M10 — Batch and Streaming: stream processing, exactly-once, Lambda vs. Kappa, backpressure, partitioned consumption.
- M3 — Storing Data: logs as the source of truth.

In the interview

30-second answer: I built a streaming pipeline that takes website click events into Kafka and uses a stream processor (Flink) to compute per-minute page views, approximate unique visitors, top pages and sessions for a live dashboard. The key decision was windowing by event time with watermarks, because mobile events arrive late and out of order, and processing-time counts were measurably wrong. The hardest part was exactly-once results through restarts and duplicate events, which I got from checkpointed state with Kafka offsets, dedup by event ID, and idempotent upserts keyed by window and URL. At 20,000 events/s the dashboard stays under 10 s fresh, and killing the processor mid-run gives identical final numbers.

Key terms to know:

- **Event time vs processing time** — when the click happened versus when the pipeline saw it.
- **Tumbling window** — fixed, non-overlapping intervals, such as 1-minute page counts.
- **Sliding window** — overlapping intervals, such as top pages over the last 5 minutes, recomputed every minute.
- **Session window** — groups a user's events until 30 minutes of inactivity.

- **Watermark** — the processor's estimate that no events older than time T are still coming. Here, max event time seen minus 30 s.
- **Allowed lateness / side output** — late events up to 10 minutes still update their window. Later ones go to a late-events topic.
- **Checkpoint** — a consistent snapshot of all operator state plus source offsets, used to restart without double counting.
- **Idempotent sink** — upserts keyed by window and URL, so a replay overwrites instead of adding.
- **HyperLogLog** — a small sketch that estimates distinct counts with about 1% error in kilobytes of memory.
- **Kappa architecture** — one streaming path, with reprocessing done by replaying the log or raw archive.

Q: What is the difference between event time and processing time, and why does it matter?

A: Event time is when the user clicked. Processing time is when your processor saw it. A phone that was offline for 5 minutes sends old clicks late, and processing-time windows count them in the wrong minute. Grouping by event time gives the same answer however late or shuffled the events arrive.

Q: What is a watermark?

A: It is the processor's running estimate of how complete the data is: "I believe all events before time T have arrived". When the watermark passes the end of a window, the window can emit its result. Here it is the maximum event time seen minus 30 seconds.

Q: How do you choose how long to wait for late events?

A: A watermark is a bet. Too aggressive, and late events are dropped and counts are low. Too relaxed, and every result is delayed. I emit on the watermark for freshness, keep windows open for 10 minutes of allowed lateness so stragglers update the result, and send anything later to a side output.

Q: How do you get exactly-once counts?

A: Flink checkpoints save operator state and Kafka offsets together, so after a crash it rewinds both to the same point and reprocesses without double counting. Duplicate events from clients are removed by keeping seen event IDs in state with a TTL. The sink is an upsert keyed by window and URL, so re-emitted results overwrite rather than add.

Q: Why HyperLogLog for unique users instead of a set?

A: An exact set of user IDs per URL per minute grows with traffic and would blow up state size. HyperLogLog estimates distinct counts with about 1% error in a fixed few kilobytes. Sketches can also be merged, so minute uniques combine into hourly uniques.

Q: One URL goes viral. What happens?

A: All its events go to one key and one parallel task, which becomes a hot spot while others sit idle. Split the key with a random salt into N sub-keys, pre-aggregate each, then combine the partial counts in a second step.

Q: A task manager crashes. What do users see?

A: The job restarts from the last checkpoint and replays from the saved Kafka offsets. The dashboard pauses for a few seconds, then catches up. Because the sink is idempotent, numbers come out exactly as if nothing had happened.

Q: What changes at 10x events?

A: Add Kafka partitions and processor parallelism, since work is partitioned by key. State grows with keys and window lengths, so use RocksDB-backed state and TTLs on dedup state. ClickHouse handles high-volume aggregate writes and dashboard queries better than PostgreSQL at that point.

Q: How do you prove the streaming numbers are right?

A: Run a batch computation over the raw archive and compare it with the streaming output for the same period. The load generator deliberately injects late, duplicate and out-of-order events. A chaos test kills task managers and restarts brokers, and the final results must be unchanged.

Common mistakes in answers:

- Windowing by processing time, which gives wrong numbers whenever events arrive late.
- Claiming Flink alone gives exactly-once output. The sink must also be idempotent or transactional.
- Treating a watermark as a guarantee. It is an estimate, and you need a plan for events behind it.

TL;DR

Window by event time, close windows with watermarks, allow some lateness, and make the sink idempotent. Then restarts and stragglers stop corrupting your numbers.

24. LLM gateway

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** M5, M8, M11

What it is

A gateway that sits between your applications and several large language model (LLM) providers. It offers one API, routes requests to models by policy, retries and falls back across providers, enforces per-team token budgets and rate limits, caches responses (exact and **semantic**: reusing an answer for a question that means the same thing), streams tokens, and logs cost and latency.

The problem it solves

Teams calling LLM APIs directly each reinvent keys management, retries, rate-limit handling and cost tracking. Providers have outages and rate limits, prices differ by orders of magnitude between models, and nobody knows which team spent what. A gateway centralises these concerns, the same way an API gateway does for microservices (Project 17).

Real-world examples

- LiteLLM is an open-source proxy offering one API over many providers with fallbacks, budgets and logging.
- Cloudflare AI Gateway documents caching, rate limiting, retries and analytics for AI traffic at the edge.
- GPTCache is an open-source semantic cache library.

Requirements


Functional

- One chat-completions style endpoint with streaming. Model aliases (for example `fast`, `smart`) mapped to concrete models.
- Fallback chain per alias on errors, rate limits (429) or timeouts.
- Per-team API keys, token budgets per day and requests per minute.
- Exact cache and opt-in semantic cache with a similarity threshold.
- Usage log: team, model, input and output tokens, cost, latency, cache hit.

Non-functional


- Gateway overhead under 20 ms p99 excluding model time.
- Time to first token unaffected by logging (logging is async).
- No prompt content stored unless the team opts in.

The architecture



- **Key and budget check**: Redis counters per team for tokens and requests (Project 3).
- **Exact cache**: key = hash of model plus normalised request. Only safe for deterministic settings (temperature 0).
- **Semantic cache**: embed the prompt, find the nearest cached prompt, reuse if similarity exceeds a threshold.
- **Router**: chooses a model by alias, health (circuit breakers per provider) and cost. Falls back on failures.
- **Usage pipeline**: events to Kafka, aggregated into a cost table.

Data model



Tech stack

Component	Choice	Why
Gateway	Python 3.14 (FastAPI, async) or Spring Boot 4.1.1 WebFlux	Streaming responses
Counters and exact cache	Redis	Atomic, fast
Semantic cache	PostgreSQL with pgvector	Vector similarity in SQL
Usage	Kafka to PostgreSQL	Async, durable
Test providers	A mock LLM server with configurable latency, errors and streaming	Deterministic tests

Milestones

1. **Pass-through proxy with streaming.** Done when tokens stream to the client as the provider sends them.
2. **Keys, rate limits and budgets.** Count estimated tokens up front, reconcile with actual usage after. Done when a team over budget gets 429 with a clear message.
3. **Router with fallback and breakers.** Done when a provider returning 500s or 429s is skipped automatically and traffic recovers when it heals.
4. **Exact cache.** Done when repeated deterministic requests are served from cache in under 10 ms.
5. **Semantic cache.** Done when paraphrased FAQ questions hit the cache at a chosen threshold and you have measured the false-hit rate on a labelled set.
6. **Usage and cost dashboard.** Done when per-team daily cost matches the sum of usage events.

Deep dive: the hard parts

- **Fallback during streaming.** If a provider fails after sending half the answer, you cannot silently switch: the client already has partial text. Fallback is only safe before the first token. After that, surface an error the client can retry.
- **Semantic cache risk.** "Cancel my order" and "Don't cancel my order" can embed close together. Use high thresholds, scope caches per tenant and use case, include system prompt and model in the key, and never cache personalised answers.
- **Token budgets before the answer exists.** Output length is unknown up front. Reserve `max_tokens`, then refund the difference after the response. Otherwise concurrent requests overshoot.
- **Retries cost money.** A retry after a timeout may mean you pay twice. Use timeouts that match model latency, and do not retry long generations blindly.

Testing strategy

- Mock provider scenarios: slow first token, mid-stream disconnect, 429 with `Retry-After`, malformed JSON.
- Budget concurrency test: 100 parallel requests near the limit.
- Semantic cache precision and recall on a labelled paraphrase set.

Trade-offs, scaling and failure modes

- The gateway is on the critical path of every AI feature. Keep it stateless and horizontally scaled, and decide whether it fails open (allow without budget checks) if Redis is down.
- Central logging of prompts is a privacy and compliance risk. Default to metadata only.

Stretch goals

- Cost-aware routing: send easy prompts to a small model, escalate on low confidence.
- PII redaction filter before requests leave your network.

Skills practised

- M11 — AI-Era Systems: LLM gateway, semantic caching.
- M8 — API and Edge: gateways and rate limiting.
- M5 — Reliability: circuit breakers, fallbacks.

In the interview

30-second answer: I built an LLM gateway that gives applications one chat-completions API over several model providers, with model aliases, fallback chains, per-team token budgets and rate limits, exact and semantic caching, streaming, and asynchronous cost logging. The key decision was centralising this in a stateless gateway instead of an SDK in every app, so keys, routing and budgets can change without redeploying anything. The hardest parts were token budgets, because output length is unknown up front, so I reserve `max_tokens` and refund the difference, and fallback, which is only safe before the first token is streamed. Overhead stays under 20 ms p99, and logging never delays time to first token.

Key terms to know:

- **Model alias** — a name like `fast` or `smart` mapped to concrete models, so apps never hard-code a provider.
- **Fallback chain** — the ordered list of models to try when one fails, returns 429 or times out.
- **Circuit breaker per provider** — stops sending traffic to a provider that keeps failing, then tests it again after a cool-down.
- **Token budget** — a team's daily token allowance, enforced by Redis counters.
- **Reserve and refund** — charge `max_tokens` before the call, then return the unused part when actual usage is known.

- **Exact cache** — key = hash of model plus normalised request. Only safe when output is deterministic (temperature 0).
- **Semantic cache** — embed the prompt, find the most similar cached prompt, and reuse its answer above a similarity threshold.
- **Time to first token (TTFT)** — how long until the first streamed token arrives. The main latency users feel.
- **Streaming (SSE)** — tokens are forwarded to the client as the provider produces them.
- **Async usage pipeline** — usage events go to Kafka and are aggregated into a cost table, off the request path.

Q: Why a gateway rather than an SDK in each app?

A: Provider keys stay in one place instead of in every service. Budgets, routing, fallbacks and caching are enforced consistently and changed without redeploying apps. Every request is logged the same way, so you finally know which team spent what.

Q: How do you enforce a token budget when you do not know the output length?

A: Before the call, reserve the estimated input tokens plus `max_tokens` from the team's Redis counter atomically. After the response, compare with actual usage and refund the difference. Without the reservation, 100 concurrent requests near the limit would all pass the check and overshoot it.

Q: How do you fall back to another provider mid-stream?

A: You generally cannot. The client already has half an answer, and a different model would continue with different text. Fallback is only safe before the first token is sent. After that, surface an error the client can retry as a whole.

Q: When is semantic caching dangerous?

A: When a small wording change flips the meaning. "Cancel my order" and "don't cancel my order" can embed very close together. Also when answers are personalised, because one user's answer could be served to another. Use high thresholds, scope the cache per tenant and use case, include model and system prompt in the key, and measure the false-hit rate on a labelled set.

Q: Why is the exact cache only for deterministic requests?

A: With temperature above 0, the same prompt is supposed to produce varied answers, and a cache would return the same one every time. At temperature 0, a repeated identical request can safely reuse the stored answer, served in under 10 ms instead of seconds.

Q: A provider starts returning 429s. What happens?

A: The router respects `Retry-After`, and the provider's circuit breaker opens after repeated failures. New requests for that alias go to the next model in its fallback chain. When the breaker's trial calls succeed, traffic returns.

Q: Why can retries be expensive here?

A: A timed-out generation may have completed on the provider's side, and you are billed for it. Retrying means paying twice. Use timeouts that match real model latency, and do not blindly retry long generations.

Q: Redis is down. What does the gateway do?

A: Budgets, rate limits and the exact cache all live there. You choose a policy: fail open (serve requests without budget checks, accept some overspend, alert) or fail closed (refuse AI traffic). Most teams fail open with a local per-instance rate limit, because the gateway is on the critical path of every AI feature.

Q: What changes at 10x traffic?

A: The gateway is stateless, so add instances. Redis counters may need sharding by team. Provider rate limits become the real ceiling, so spread load across providers and regions and use cost-aware routing that sends easy prompts to smaller models.

Q: How do you test it?

A: A mock provider simulates a slow first token, a mid-stream disconnect, 429 with `Retry-After`, and malformed JSON. A budget test fires 100 parallel requests near the limit and checks it is not exceeded.

The semantic cache is scored for precision and recall on a labelled paraphrase set.

Common mistakes in answers:

- Checking the budget only after the response, which lets concurrent requests overspend.
- Promising seamless mid-stream failover between models.
- Logging full prompts by default. That is a privacy and compliance risk, so the default is metadata only.

TL;DR

An LLM gateway is an API gateway with token-aware budgets, provider fallback, careful caching and cost accounting.

25. RAG document Q&A service

Level: Intermediate · **Time:** 2–3 weeks · **Prerequisites:** M10, M11

What it is

A service that answers questions about your own documents using **retrieval-augmented generation** (RAG): split documents into chunks, turn each into an **embedding** (a vector of numbers where similar meanings sit close together), store them in a vector index, retrieve the most relevant chunks for a question and give them to an LLM to answer with citations. You build ingestion, hybrid retrieval, answer generation and an evaluation harness.

The problem it solves

LLMs do not know your private or recent documents and will confidently make things up. Fine-tuning is expensive and goes stale. RAG fetches the relevant facts at question time, so answers are grounded in sources you control and can cite, and updating knowledge means re-indexing a document, not retraining.

Real-world examples

- Lewis et al., Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks, introduced the term and the retrieve-then-generate approach.
- Anthropic's Introducing Contextual Retrieval describes adding chunk-specific context before embedding and combining embeddings with BM25 keyword search to reduce failed retrievals.
- pgvector adds vector similarity search with HNSW and IVFFlat indexes to PostgreSQL.

Requirements


Functional

- Ingest PDFs, Markdown and HTML. Re-ingest on change. Delete removes all chunks.
- Answer questions with inline citations to document and section.
- Per-user document permissions respected at retrieval time.
- "I don't know" when retrieval finds nothing relevant.

Non-functional


- 100,000 documents, about 2 million chunks.
- Retrieval p95 under 150 ms. Full answer first token under 2 s.
- New documents searchable within 5 minutes.
- Quality tracked: retrieval recall@10 and answer faithfulness on a test set.

The architecture



- **Ingestion queue and chunker**: parse, split by headings into chunks of a few hundred tokens with overlap, attach metadata (title, section, permissions).
- **Embedding workers**: batch chunks to an embedding model.
- **Vector plus keyword store**: pgvector HNSW index for semantic search and PostgreSQL full-text search (BM25-like ranking) for exact terms such as error codes.
- **Hybrid retriever**: runs both, merges with reciprocal rank fusion (sum of `1/(k + rank)` from each list).
- **Reranker**: a cross-encoder model scores question-chunk pairs more precisely for the top 50.
- **LLM via gateway**: Project 24's gateway, with a prompt that demands citations.

Data model



In PostgreSQL, `embedding` is a `vector(n)` column and `tsv` a `tsvector`. The diagram shows them as text for portability.

Tech stack

Component	Choice	Why
Pipeline	Python 3.14	Best parsing and ML libraries
Store	PostgreSQL with pgvector	One system for vectors, text, metadata, ACLs
Queue	Kafka or the Project 4 queue	Ingestion backpressure
Evaluation	A labelled question set plus an LLM-as-judge script	Measure, don't guess

Milestones

1. **Naive RAG.** Fixed-size chunks, vector search, stuff top 5 into the prompt. Done when it answers simple questions with citations.
2. **Evaluation harness.** 100 question-answer-source triples. Done when you can print recall@10 and faithfulness for any config.
3. **Structure-aware chunking and metadata.** Done when recall@10 improves measurably over milestone 1.
4. **Hybrid search and reranking.** Done when queries with exact identifiers (error codes, part numbers) are found reliably.
5. **Permissions.** Filter by ACL inside the retrieval query, not after. Done when a user never sees a chunk they cannot access, even in citations.
6. **Incremental ingestion and deletion.** Content hash skips unchanged docs. Done when edits appear within 5 minutes and deleted docs disappear immediately.

Deep dive: the hard parts

- **Chunking decides quality.** Too small and chunks lack context. Too large and the right sentence drowns. Split on document structure, keep overlap, and prepend the document title and section to each chunk before embedding.
- **Approximate search trade-offs.** HNSW (a layered graph for approximate nearest neighbours) trades recall for speed through its search-width parameter. Filtering by ACL can starve the graph search of matches. pgvector's iterative scans in recent versions help. Measure recall with filters on.
- **Faithfulness.** The model may ignore context. Instruct it to answer only from sources, require citations, and check in evaluation that each cited chunk supports the claim.
- **Embedding model changes.** Switching models invalidates every vector. Version the embedding column and re-embed in the background, then flip.

Testing strategy

- Offline evaluation on every change to chunking, retrieval or prompts.
- Permission tests with users in different groups.
- Load test retrieval at 50 queries/s with 2 million chunks.

Trade-offs, scaling and failure modes

- pgvector keeps everything in one database and is simple to run. Dedicated vector databases scale further and shard more naturally (Project 40).
- Bigger context windows reduce the need for precise retrieval but raise cost and latency, and models still miss facts buried in long contexts.
- If the LLM is down, return the top retrieved passages as "related documents". Search alone is still useful.

Stretch goals

- Contextual chunk enrichment (an LLM writes a short context line per chunk before embedding).
- Conversation memory with question rewriting from chat history.

Skills practised

- M11 — AI-Era Systems: RAG, vector databases, semantic caching.

- M10 — Batch and Streaming: ingestion pipelines.
- M8 — API and Edge: authorization at the data layer.

In the interview

30-second answer: I built a document Q&A service using retrieval-augmented generation: documents are split into structure-aware chunks, embedded and stored in PostgreSQL with pgvector and full-text search, and each question retrieves, fuses and reranks the best chunks before an LLM answers with citations. The key decision was hybrid retrieval, vector plus keyword merged with reciprocal rank fusion, because embeddings capture meaning but miss exact tokens like error codes. The hardest parts were permissions, which I enforce inside the retrieval query so forbidden text never reaches the prompt, and proving quality, which I do with a fixed evaluation set measuring recall@10 and faithfulness. Over 2 million chunks, retrieval runs under 150 ms p95.

Key terms to know:

- **RAG (retrieval-augmented generation)** — fetch relevant passages at question time and give them to the LLM, so answers are grounded in your documents.
- **Embedding** — a vector of numbers where texts with similar meaning are close together.
- **Chunking** — splitting documents into pieces of a few hundred tokens, by headings, with overlap and the title and section prepended.
- **HNSW** — a layered graph index for approximate nearest-neighbour search. Trades recall for speed through its search-width parameter.
- **Hybrid search** — run vector search and keyword search together and merge the results.
- **Reciprocal rank fusion (RRF)** — merge ranked lists by summing `1/(k + rank)` from each list.
- **Reranker (cross-encoder)** — a model that scores each question-chunk pair together. More precise but slower, so used on the top 50 only.
- **ACL filtering** — restricting retrieval to chunks the user may see, inside the query itself.
- **Recall@10** — the share of questions where the correct source appears in the top 10 retrieved chunks.
- **Faithfulness** — whether every claim in the answer is supported by the cited chunks.

Q: Why RAG instead of fine-tuning the model on your documents?

A: Fine-tuning is expensive, goes stale as documents change, and does not reliably make the model recall exact facts or cite them. RAG fetches facts at question time, so updating knowledge means re-indexing one document. Answers can also cite their sources, which users can check.

Q: Why hybrid search?

A: Embeddings match meaning, so "how do I reset my password" finds "account recovery steps". But they are weak on exact tokens such as `ERR_4012` or part numbers, which keyword search finds easily. Running both and fusing the rankings gets both kinds of match.

Q: Why does chunking matter so much?

A: Retrieval returns chunks, not documents. Chunks that are too small lose the context needed to understand them, and chunks that are too large bury the one relevant sentence among unrelated text. Splitting on document structure with overlap, and prepending the title and section, measurably improved recall@10 over fixed-size chunks.

Q: How do you enforce document permissions?

A: Each chunk stores its ACL group, and the retrieval query filters by the user's groups inside the same SQL statement. Filtering after retrieval is unsafe and also returns too few results. Forbidden text must never reach the prompt, because the model can leak it in its answer or citations.

Q: What goes wrong when you combine an ACL filter with HNSW?

A: The graph search finds the nearest vectors first and then applies the filter. If the user can see only a small share of documents, most candidates are filtered out and too few results remain.

pgvector's iterative index scans (added in 0.8) keep searching until enough rows pass, and you should measure recall with filters on.

Q: How do you stop the model from making things up?

A: Instruct it to answer only from the provided sources, require a citation for each claim, and return "I don't know" when retrieval finds nothing relevant above a score threshold. In evaluation, check that each cited chunk actually supports the claim. That is the faithfulness metric.

Q: You want to switch embedding models. What happens?

A: Vectors from different models are not comparable, so every chunk must be re-embedded. Add a new versioned embedding column, re-embed in the background, then switch queries to it in one step. Never mix vectors from two models in one index.

Q: The LLM provider is down. What do users get?

A: Retrieval still works, so the service returns the top passages as "related documents" with links. Search alone is useful, and it is far better than an error page.

Q: What changes at 10x the documents?

A: 20 million chunks strain a single PostgreSQL node's memory for the HNSW index. Options are partitioning by tenant, or moving to a dedicated vector database that shards naturally. Ingestion needs more embedding workers behind the queue, and content hashes keep unchanged documents from being re-embedded.

Q: How do you know a change made it better?

A: A fixed set of 100 question-answer-source triples is run on every change to chunking, retrieval or prompts. It reports recall@10 for retrieval and faithfulness for answers, scored partly by an LLM judge. Permission tests run with users in different groups.

Common mistakes in answers:

- Filtering permissions after retrieval or in the prompt. Forbidden text must never be retrieved.
- Judging quality by trying a few questions by hand instead of a fixed evaluation set.
- Assuming a bigger context window removes the need for good retrieval. It raises cost and latency, and models still miss facts buried in long contexts.

TL;DR

RAG quality is mostly retrieval quality: structure-aware chunks, hybrid search, reranking, permission filters and a real evaluation set.

26. Dynamo-style key-value store

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M3, M7, M13

What it is

A distributed, always-writable key-value store modelled on Amazon's Dynamo paper. Keys are spread over nodes by **consistent hashing**, each key is replicated to N nodes, reads and writes use tunable **quorums** (R and W replicas must answer), conflicts are tracked with **vector clocks** (per-node version counters that reveal whether two versions are ordered or concurrent), and the cluster heals itself with **hinted handoff**, **read repair** and **Merkle-tree anti-entropy**.

The problem it solves

Some workloads (shopping carts, session state, user preferences) value accepting writes during failures more than strict consistency. A single-leader database rejects writes when the leader is unreachable. A leaderless design lets any replica accept writes, and pays for it by having to detect and reconcile conflicting versions. Building one teaches every trade-off in Module 7 by feel.

Real-world examples

- DeCandia et al., Dynamo: Amazon's Highly Available Key-value Store (SOSP 2007), the paper this project follows: consistent hashing, sloppy quorums, vector clocks, hinted handoff and Merkle trees.
- Module 13 of this book has a full Dynamo-style case study, which this brief extends into a build.

Requirements


Functional

- `PUT key value [context]`, `GET key` returning one value or several concurrent siblings with a context, `DELETE` via tombstones.
- Replication factor N=3, configurable R and W per request.
- Nodes join and leave. Gossip spreads membership.
- Hinted handoff when a replica is down. Read repair on reads. Background anti-entropy.

Non-functional

- 5-node cluster in Docker Compose, then Kubernetes StatefulSet.
- With N=3, R=2, W=2: p99 under 20 ms on a LAN, 10,000 ops/s.
- Writes accepted with any 2 of 3 replicas reachable. No acknowledged write lost if fewer than N nodes fail permanently.

The architecture



- **Coordinator**: the node a client contacts. It finds the key's **preference list** (the first N distinct physical nodes clockwise on the ring), sends to all N and waits for W or R replies.
- **Storage engine**: an append-only log plus an in-memory index (a Bitcask-style design) or RocksDB. Values carry vector clocks.
- **Gossip**: each node periodically exchanges membership and heartbeat state with a random peer, so failures and joins spread without a master.
- **Anti-entropy**: replicas compare Merkle trees (hash trees where each parent hashes its children) per key range and sync only differing branches.

Data model

Type	Fields
`VersionedValue`	`bytes value`, `VectorClock clock`, `boolean tombstone`, `long ts`
`VectorClock`	map of `nodeId -> counter`
`Hint`	`targetNode`, `key`, `VersionedValue` stored on a stand-in node
`Member`	`nodeId`, `address`, `tokens`, `heartbeat`, `status`

Tech stack

Component	Choice	Why
Nodes	Java 25 (gRPC or Netty)	Concurrency and performance
Storage	Append-only log with hash index, or RocksDB	Learn the WAL, or focus on distribution
Deployment	Docker Compose, then Kubernetes StatefulSet	Stable network identities
Chaos	Toxiproxy, `tc netem`, process kills	Partitions and latency
Verification	Jepsen-style history checker	Prove guarantees

Milestones

1. **Single node store with log and index.** Done when restarts recover all data from the log.
2. **Ring and replication.** Static membership, coordinator writes to N, waits for W. Done when killing one node of three keeps reads and writes working at R=W=2.
3. **Vector clocks and siblings.** Done when concurrent writes from partitioned clients produce two siblings on read, and a write with the merged context collapses them.
4. **Hinted handoff and read repair.** Done when a node down for 5 minutes receives its missed writes within a minute of returning.
5. **Gossip membership and joins.** Done when adding a sixth node streams its key ranges and the ring converges on all nodes.
6. **Merkle anti-entropy and chaos testing.** Done when, after random partitions and kills, all replicas converge and a history checker finds no lost acknowledged writes.

Deep dive: the hard parts

- **Quorums are not linearizable.** R + W > N means read and write sets overlap, so a read sees the latest acknowledged write *if* nothing else goes wrong. Sloppy quorums (writing to stand-in nodes during failures) break that overlap. Concurrent writes still produce siblings. Be precise about what you guarantee.
- **Vector clock growth.** Clocks grow with the number of coordinators that touched a key. Dynamo truncated old entries, risking false conflicts. Cassandra chose last-write-wins timestamps instead, which silently drops concurrent writes. Pick one and document the consequence.
- **Deletes.** Removing a key outright lets an old replica resurrect it during anti-entropy. Write a tombstone, and only purge it after a grace period longer than any repair cycle.
- **Merkle trees on changing data.** Build trees per key range on a snapshot. Rebuilding on every write is too costly. Rebuild periodically and exchange only top-level hashes first.

Testing strategy

- Deterministic simulation: run nodes in one process with a fake network and clock, inject drops, delays and partitions from a seed, and replay failures exactly.
- Jepsen-style tests on the real cluster: record every operation and result, then check that no acknowledged write is lost and siblings appear only for truly concurrent writes.
- Rolling restart test under load.

Trade-offs, scaling and failure modes

- Leaderless gives high write availability and no failover. It costs conflict handling in the application and weaker read guarantees.
- Hot keys still land on N nodes. Consistent hashing spreads keys, not load.
- Clock skew affects only LWW timestamps and TTLs, not vector clocks, which is a reason to prefer them for correctness.

Stretch goals

- CRDT values (a grow-only counter and an observed-remove set) that merge automatically instead of returning siblings.
- Per-request consistency levels like `ONE`, `QUORUM`, `ALL` and the latency curve for each.

Skills practised

- M3 — Storing Data: consistent hashing, WAL, replication.
- M7 — Consistency: quorum and vector clocks.
- M13 — Case Studies: Building Blocks: the distributed key-value store design.
- M9 — Operating in Production: StatefulSets on Kubernetes.

In the interview

30-second answer: I built a leaderless, Dynamo-style key-value store: keys are placed on a consistent hash ring, replicated to N=3 nodes, and read and written with tunable quorums, so any 2 of 3 replicas can accept a write during a failure. The key decision was vector clocks instead of last-write-wins, because they detect truly concurrent writes and return both versions as siblings instead of silently dropping one. The hardest part was convergence after failures, which needed three mechanisms: hinted handoff for short outages, read repair on access, and Merkle-tree anti-entropy for everything else, plus tombstones so deletes do not come back. On 5 nodes with R=W=2 it ran 10,000 ops/s at p99 under 20 ms, and a Jepsen-style checker found no lost acknowledged writes.

Key terms to know:

- **Leaderless replication** — any replica can accept a write. There is no failover, but conflicts must be detected and resolved.
- **Preference list** — the first N distinct physical nodes clockwise from a key's position on the ring.
- **Quorum (N, R, W)** — N replicas per key, a write waits for W acks, a read for R replies. R + W > N makes read and write sets overlap.
- **Sloppy quorum** — during failures, writes go to stand-in nodes outside the preference list to stay available.
- **Hinted handoff** — the stand-in stores a hint and forwards the write to the real owner when it returns.
- **Vector clock** — a map of node to counter per value. Comparing two clocks says whether one version came after the other or they are concurrent.
- **Siblings** — concurrent versions returned together on read. The client merges them and writes back with the merged context.
- **Read repair** — when a read sees a stale replica, the coordinator writes the newest version back to it.
- **Merkle tree anti-entropy** — replicas compare hash trees per key range and sync only the branches that differ.
- **Tombstone** — a delete marker kept until every replica has seen it, so old data is not resurrected.

Q: What does R + W > N give you?

A: Every read set overlaps every write set in at least one node, so a read normally sees the latest acknowledged write. With N=3, R=2, W=2, any two replicas share at least one member. It is not linearizability: sloppy quorums break the overlap, and concurrent writes still produce siblings.

Q: Vector clocks or last-write-wins?

A: Vector clocks detect when two writes are concurrent and keep both versions for the application to merge, such as merging two shopping carts. Last-write-wins keeps the one with the higher timestamp and silently loses the other, and clock skew decides who "wins". LWW is simpler, and Cassandra chose it, but it loses data under concurrency.

Q: How do replicas converge after a partition?

A: Hinted handoff covers short outages: a stand-in holds the write and delivers it when the owner comes back. Read repair fixes stale replicas on keys that are read. Merkle-tree anti-entropy runs in the background and finds differences in keys nobody reads, transferring only the ranges that differ.

Q: Why tombstones instead of simply deleting the key?

A: If one replica missed the delete, anti-entropy would see that it has the key and the others do not, and copy the old value back. A tombstone is a newer version that says "deleted", so it wins. It is purged only after a grace period longer than any repair cycle.

Q: With N=3, W=1, R=1, what can a client see right after its own write?

A: Its read may go to a replica that has not received the write yet, so it sees the old value. W=1 and R=1 do not overlap. You get the lowest latency and highest availability, but not even read-your-own-writes.

Q: Why is this store "AP" in CAP terms?

A: During a network partition it keeps accepting reads and writes on both sides (availability) instead of refusing them, and it reconciles conflicting versions afterwards. A single-leader system would refuse writes on the side without the leader. That is why Dynamo suits carts and sessions, not bank balances.

Q: What happens with a hot key?

A: Consistent hashing spreads keys, not load. A hot key still lands on the same N nodes, which can overload them. Options are caching in front, reading from any one replica for that key (R=1), or splitting the key at the application level.

Q: What changes as the cluster grows from 5 to 50 nodes?

A: Gossip spreads membership in O(log n) rounds, so it still converges, but joins and leaves happen more often, so streaming key ranges must be throttled. Vector clocks grow with the number of coordinators that touched a key, so they need truncation. Anti-entropy must be rate-limited so it does not compete with live traffic.

Q: How do you test it?

A: A deterministic simulation runs all nodes in one process with a fake network and clock, injects drops, delays and partitions from a seed, and replays any failure exactly. On the real cluster, Jepsen-style tests record every operation and check that no acknowledged write is lost and siblings appear only for truly concurrent writes. A rolling restart runs under load.

Common mistakes in answers:

- Saying R + W > N makes the store strongly consistent or linearizable.
- Forgetting deletes. Without tombstones, deleted data comes back through anti-entropy.
- Assuming consistent hashing solves hot keys. It balances key counts, not traffic.

Self-check

- With N=3, W=1, R=1, what anomaly can a client see immediately after its own write?
- Why must tombstones outlive the anti-entropy interval?

TL;DR

A ring places data, quorums tune consistency against latency, vector clocks expose conflicts, and hinted handoff, read repair and Merkle trees make replicas converge.

27. Kafka-like distributed log

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M10, M13

What it is

A partitioned, replicated, append-only log service like Kafka. Producers append records to topic partitions. Each partition is a sequence of segment files with an offset index. A leader replicates to followers and tracks the **in-sync replica set** (ISR: followers that are caught up). Consumers in **consumer groups** split partitions between them and commit offsets. You implement the storage engine, replication protocol, acknowledgement levels and group coordination.

The problem it solves

Services need a shared, durable, ordered stream of events that many consumers can read at their own pace and replay from any point. A queue that deletes messages on consumption cannot do replay or multiple independent readers. A log can, and sequential disk writes make it fast. Building one shows why Kafka's guarantees depend on settings like `acks` and `min.insync.replicas`.

Real-world examples

- The Apache Kafka documentation has a design section explaining reliance on the page cache, sequential I/O, the replication model with ISR and the meaning of producer acknowledgements.
- Redpanda is a Kafka-API-compatible log that uses Raft per partition instead of ISR, a useful alternative design to compare.

Requirements


Functional

- Topics with P partitions and replication factor 3.
- `Produce(topic, key, value, acks=0|1|all)` returns partition and offset. Key determines partition.
- `Fetch(topic, partition, offset, maxBytes)` returns records from that offset.
- Consumer groups with partition assignment, rebalancing and committed offsets.
- Retention by time and size, deleting whole segments.
- Idempotent producer: retries never duplicate (producer ID plus sequence number).

Non-functional

- 3 brokers. 100 MB/s aggregate produce on a laptop with batching.
- With `acks=all` and `min.insync.replicas=2`, no acknowledged record lost when any one broker dies.
- Leader failover under 10 s.

The architecture



- **Brokers**: host partition replicas. Leaders accept writes. Followers pull from leaders like consumers.
- **Segments**: each partition directory has files named by base offset, with a sparse offset index (every few KB) mapping offsets to file positions.
- **High watermark**: the highest offset replicated to all ISR members. Consumers only see up to it.
- **Controller**: one broker (elected via a lease in etcd, or Raft) that decides leaders and ISR membership.
- **Group coordinator**: tracks group members, triggers rebalances, stores committed offsets in an internal compacted topic.

Data model

Structure	Fields
Record batch	base offset, producer ID, base sequence, CRC, records
Segment	`00000000000000123456.log` , `.index`
Partition state	leader, ISR list, leader epoch, high watermark, log end offset
Group state	members, generation, assignment, committed offsets

Tech stack

Component	Choice	Why
Brokers	Java 25 with Netty, FileChannel and zero-copy `transferTo`	Kafka's own techniques
Metadata	etcd (or your Project 30 Raft store)	Controller election and partition state
Protocol	A simple binary protocol or gRPC	Batching and backpressure
Deploy	Kubernetes StatefulSet with persistent volumes	Stable identities

Milestones

1. **Single-broker log.** Append, segment roll at a size, sparse index, fetch by offset, retention. Done when 10 million records round-trip and survive restart with CRC checks.
2. **Batching and throughput.** Done when batched produce exceeds 100 MB/s on one broker.

3. **Replication with ISR and high watermark.** Done when `acks=all` waits for ISR, slow followers drop out of ISR after a lag timeout and rejoin when caught up.
4. **Controller and failover.** Done when killing a leader elects an ISR member, and consumers see no gaps or rewrites for acknowledged data.
5. **Consumer groups.** Range or sticky assignment, heartbeats, rebalances, offset commits. Done when adding or removing consumers reassigns partitions and processing resumes from committed offsets.
6. **Idempotent producer and chaos.** Done when retries during leader failover never create duplicates, and a randomised kill test finds no lost acknowledged records.

Deep dive: the hard parts

- **Leader epochs and truncation.** A deposed leader may have records the new leader never got. When it rejoins as a follower it must truncate to the point where its log diverged, found using the **leader epoch** (a counter bumped on every leader change). Using only the high watermark here historically allowed data loss in edge cases, which is why Kafka added epochs.
- **`acks` and `min.insync.replicas`.** `acks=all` means "all *current* ISR members". If ISR shrinks to just the leader, `acks=all` is no safer than `acks=1`. `min.insync.replicas=2` makes the leader refuse writes rather than accept unsafe ones. Availability vs. durability, made explicit.
- **Unclean leader election.** If every ISR member is dead, you can wait (unavailable) or elect an out-of-sync replica (data loss). Make it a per-topic setting and test both.
- **Rebalance storms.** Eager rebalancing stops all consumers in a group for each membership change. Sticky or incremental cooperative assignment moves only affected partitions.

Testing strategy

- Linearizability-style checks on single partitions: every acknowledged offset is readable, in order, with no gaps after any failure.
- Chaos runs: kill leaders during produce, partition the controller, pause followers.
- Throughput and latency benchmarks with various batch sizes and `acks` settings.

Trade-offs, scaling and failure modes

- Ordering is per partition only. More partitions means more parallelism but more files, more metadata and longer failovers.
- Followers pulling (rather than leaders pushing) gives natural backpressure and lets followers batch.
- Page cache reliance means brokers do not fsync every write by default. Durability comes from replication, not disk flush. Know that trade-off.

Stretch goals

- Log compaction: keep only the latest record per key.
- Transactions across partitions (atomic writes plus offset commits for exactly-once read-process-write).
- Tiered storage: move old segments to object storage.

Skills practised

- M10 — Batch and Streaming: inside Kafka, partitioned consumption, exactly-once.
- M13 — Case Studies: Building Blocks: the distributed message queue design.
- M3 — Storing Data: logs and replication.

In the interview

30-second answer: I built a Kafka-like log: topics split into partitions, each partition a set of segment files with a sparse offset index, replicated from a leader to followers that pull, with consumer groups that share partitions and commit offsets. The key decision was the in-sync replica set plus `min.insync.replicas=2`, so with `acks=all` an acknowledged record is on at least two brokers and survives any single broker failure. The hardest part was leader failover, where a deposed

leader may hold records the new leader never got, so I used leader epochs to find exactly where to truncate. It reached 100 MB/s of batched produce on 3 brokers, with failover under 10 s and no lost acknowledged records in chaos tests.

Key terms to know:

- **Partition** — an ordered, append-only sequence of records. Ordering is guaranteed only within one partition.
- **Offset** — a record's position in its partition. Consumers track progress by offset.
- **Segment and sparse index** — a partition is stored as files rolled by size. The index maps every few KB of offsets to file positions.
- **ISR (in-sync replicas)** — the leader plus followers that are caught up within a lag timeout.
- **High watermark** — the highest offset copied to every ISR member. Consumers only read up to it.
- **acks=0/1/all** — the producer waits for no ack, the leader's ack, or acks from all current ISR members.
- **min.insync.replicas** — the minimum ISR size for the leader to accept an `acks=all` write.
- **Leader epoch** — a counter bumped on every leader change, used to truncate divergent log tails safely.
- **Consumer group and rebalance** — consumers split partitions among themselves. A membership change triggers reassignment.
- **Idempotent producer** — a producer ID plus sequence number lets the broker drop retried duplicates.

Q: What does `acks=all` actually guarantee?

A: The record is written to every replica currently in the ISR. If the ISR has shrunk to only the leader, that is just one copy, no safer than `acks=1`. Setting `min.insync.replicas=2` makes the leader refuse writes when fewer than two replicas are in sync, so an ack always means at least two copies.

Q: How is ordering guaranteed?

A: Within a partition, one leader appends records in sequence and assigns increasing offsets. The producer hashes the key to pick a partition, so all records for one key stay in order. There is no ordering across partitions.

Q: What happens when a leader dies?

A: The controller picks a new leader from the ISR, so it has every acknowledged record, and bumps the leader epoch. When the old leader returns as a follower, it uses the epoch history to find where its log diverged and truncates the extra records before catching up. Unacknowledged records on the old leader may be lost, which is allowed.

Q: What if every ISR member is dead?

A: You choose. Wait for an ISR member to return, which keeps data but leaves the partition unavailable, or allow unclean leader election of an out-of-sync replica, which restores availability but loses acknowledged records. It is a per-topic setting and a direct availability-versus-durability trade-off.

Q: Why is Kafka fast even though it writes to disk?

A: Appends are sequential, which disks handle very well. Producers batch many records per request. Data is served from the OS page cache, and zero-copy `transferTo` sends file bytes to the socket without copying through the application. Durability comes from replication rather than an fsync per write.

Q: Why do followers pull instead of the leader pushing?

A: Pulling gives natural backpressure: a slow follower simply fetches less instead of being overwhelmed. Followers can fetch large batches. It also reuses the same fetch path that consumers use.

Q: How does the idempotent producer prevent duplicates?

A: Each producer gets an ID and numbers its batches per partition. If a retry arrives with a sequence number the broker already wrote, the broker acknowledges it without appending again. So a retry during a leader failover does not create a duplicate.

Q: What changes at 10x throughput?

A: Add partitions and brokers to spread load, since one partition is limited by one leader. More partitions mean more files, more metadata, and longer failovers, so there is a cost. Use sticky or cooperative rebalancing so adding consumers does not pause the whole group, and tiered storage to move old segments to object storage.

Q: How do you test it?

A: For each partition, check that every acknowledged offset is readable, in order, with no gaps after any failure. Chaos runs kill leaders during produce, partition the controller and pause followers. Benchmarks compare throughput and latency across batch sizes and `acks` settings.

Common mistakes in answers:

- Saying `acks=all` alone guarantees multiple copies. Without `min.insync.replicas`, it may be one copy.
- Claiming Kafka keeps global order across a topic. Order is per partition.
- Assuming every write is fsynced. Durability comes from replication across brokers.

TL;DR

A distributed log is segmented files plus leader-follower replication. ISR, high watermarks and leader epochs decide what is safe to acknowledge and what must be truncated.

28. Distributed job scheduler

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** M5, M7, M16

What it is

A cluster service that runs jobs at scheduled times (cron expressions, one-off delays) and on demand, distributes them to a pool of workers, guarantees each scheduled run happens once in effect even when schedulers and workers crash, supports dependencies between jobs and keeps a full run history. Think of a small Airflow scheduler crossed with a distributed cron.

The problem it solves

`cron` on one machine is a single point of failure, and running the same crontab on two machines runs every job twice. A distributed scheduler needs leader election or partitioned ownership so each trigger fires once, durable state so nothing is forgotten across restarts, and **fencing** so a scheduler that was paused and lost its role cannot keep acting as if it still held it.

Real-world examples

- Dropbox's Asynchronous task scheduling at Dropbox describes their ATF system for scheduling and executing async tasks at scale with at-least-once semantics.
- Module 16 of this book has the distributed job scheduler case study, which this project builds.

Requirements

Functional


- Register jobs with a cron or a one-off time, a target (container image, HTTP call or worker function), timeout and retry policy.
- Each scheduled tick creates exactly one run record. Workers execute runs.
- DAGs: job B runs after job A succeeds.
- Pause, resume, trigger now, cancel. Run history and logs.
- Misfire policy: after downtime, either run once to catch up or skip missed ticks.

Non-functional

- 1 million job definitions, 10,000 runs/minute at peak (top of the hour).
- Trigger latency under 2 s after the scheduled time.


- No duplicate run records for a tick, ever. At-least-once execution with idempotency guidance.
- Scheduler failover under 15 s.

The architecture



- **Job API**: CRUD on job definitions, computes `next_fire_at` for each.
- **Schedulers**: each holds leases on a subset of shards (jobs are hashed into, say, 64 shards). Every second, each scheduler claims due jobs in its shards, creates run records, advances `next_fire_at`, and enqueues runs.
- **Run queue**: Kafka or the Project 4 queue.
- **Workers**: execute runs with timeouts, send heartbeats, report results.
- **Run monitor**: detects runs whose heartbeats stopped and retries or fails them.

Data model



Add a unique index on `RUN (job_id, scheduled_for)`.

Tech stack

Component	Choice	Why
State	PostgreSQL	Unique constraints, transactions
Leases	etcd (or Project 30)	Leases with revision numbers usable as fencing tokens
Queue	Kafka or Postgres queue	Decouple trigger from execution
Workers	Kubernetes Jobs, or in-process executors	Isolation for untrusted jobs
Language	Java 25 or Python 3.14	Cron parsing libraries exist in both

Milestones

1. **Single scheduler.** Poll due jobs with `SKIP LOCKED`, insert runs, advance next fire. Done when 10,000 jobs on a 1-minute cron fire on time.
2. **Exactly one run per tick.** Done when two schedulers running against the same shard (forced) still create one run per `(job, scheduled_for)` thanks to the unique index.
3. **Sharded ownership with leases.** Done when killing a scheduler moves its shards to another within 15 s.
4. **Fencing.** Every write by a scheduler includes its lease revision. The database rejects writes with an older token. Done when a scheduler paused past its lease (use `SIGSTOP`) cannot create runs after resuming.
5. **Workers, heartbeats and retries.** Done when killing a worker mid-run triggers a retry after the heartbeat timeout.
6. **DAGs and misfire policy.** Done when B waits for A, and a 30-minute scheduler outage follows the configured catch-up rule.

Deep dive: the hard parts

- **Fencing tokens.** A lease says "you are the owner until time T", but a process can pause (garbage collection, VM migration) and wake after T believing it still owns the shard. A monotonically increasing token checked by the storage layer is the only reliable guard: the storage refuses a write carrying a token older than the newest it has seen.
- **Thundering top of the hour.** Many crons fire at `0 * * * *`. Spread load by adding per-job jitter where users allow it, pre-computing runs a few seconds early, and batching inserts.
- **Time zones and DST.** A daily 02:30 job does not exist on a spring-forward day and happens twice on a fall-back day in many zones. Store schedules with an explicit time zone and define the behaviour.
- **At-least-once execution.** A worker can finish and crash before reporting. The run is retried. Expose a stable run ID so job code can be idempotent.

Testing strategy

- Fake clock tests for cron calculation including DST transitions.
- Chaos: kill schedulers and workers, pause processes, partition etcd. Assert the unique-run invariant and no lost ticks.
- Load test the top-of-hour spike.

Trade-offs, scaling and failure modes

- Single leader (simple) vs. sharded ownership (scales, more moving parts). Start with one leader and shard when one cannot keep up.
- Polling the database every second is simple. A timing wheel (an in-memory ring of buckets by time) reduces load for very large numbers of near-term timers.

Stretch goals

- Priority classes and per-tenant concurrency quotas.
- Backfills: run a job for a date range with controlled parallelism.

Skills practised

- M16 — Case Studies: Infrastructure: the distributed job scheduler.
- M7 — Consistency: leases, coordination.
- M5 — Reliability: retries, timeouts, idempotency.

In the interview

30-second answer: I built a distributed cron: job definitions live in PostgreSQL and are hashed into 64 shards, schedulers hold etcd leases on subsets of shards and create run records for due jobs, and workers execute runs from a queue with heartbeats and retries. The key decision was layering two guards, a unique index on `(job_id, scheduled_for)` so a tick can never produce two run records, and fencing tokens so a scheduler that paused past its lease cannot keep writing. The hardest parts were the top-of-the-hour spike and time zones with DST. It handles 10,000 runs/minute at peak, fires within 2 s of schedule, and fails a scheduler over in under 15 s.

Key terms to know:

- **Sharded ownership** — jobs are hashed into shards, and each scheduler owns a subset, so work scales across schedulers.
- **Lease** — time-limited ownership of a shard in etcd, renewed by keepalives. It expires if the owner dies.
- **Fencing token** — a number that increases with every new lease. Storage rejects writes carrying an older token than it has seen.
- **Unique run constraint** — `UNIQUE (job_id, scheduled_for)` guarantees one run record per tick even if two schedulers try.
- **At-least-once execution** — a worker can finish and crash before reporting, so the run is retried. Jobs get a stable run ID to dedupe.
- **Heartbeat and run monitor** — workers report liveness, and the monitor retries runs whose heartbeats stop.
- **Misfire policy** — after downtime, either run once to catch up or skip missed ticks.
- **DAG dependency** — job B starts only after job A succeeds.
- **DST (daylight saving time)** — some local times do not exist or happen twice on transition days.
- **Timing wheel** — an in-memory ring of time buckets, an alternative to polling for many near-term timers.

Q: How do you make sure a job fires once per tick?

A: Two layers. Shard ownership through leases means normally only one scheduler looks at each job. And the unique index on `(job_id, scheduled_for)` means even if two schedulers race, only one run insert succeeds. Fencing tokens stop a stale owner from writing at all.

Q: What is a fencing token, and why is a lease not enough?

A: A lease says "you own this shard until time T", but a process can freeze in a long garbage-collection pause or VM migration and wake after T, still believing it is the owner. A fencing token is a number that rises every time the lease changes hands, and the database rejects writes with an older token than the newest it has seen. The check happens in storage, so the paused process cannot do damage.

Q: What about jobs that actually run twice?

A: Execution is at-least-once: a worker can finish and crash before recording success, and the monitor retries it. Exactly-once execution of arbitrary side effects is not achievable. Each run gets a stable ID, and job code uses it to dedupe.

Q: A scheduler crashes. What happens to its shards?

A: Its etcd leases stop being renewed and expire. Other schedulers watch for free shards, take them with new leases (and higher fencing tokens), and start scanning from each job's stored `next_fire_at`.

Nothing is forgotten because all state is in PostgreSQL, and failover finishes within 15 s.

Q: Many jobs are scheduled at `0 * * * *`. What breaks?

A: A huge burst of run inserts and queue messages lands in the same second, so trigger latency spikes. Precompute runs a few seconds early, batch the inserts, and add per-job jitter where users allow it. The queue absorbs the burst so workers can drain it steadily.

Q: How do you handle daylight saving time?

A: Store each schedule with an explicit time zone and define the behaviour. A daily 02:30 job does not exist on spring-forward day in many zones, and 01:30 happens twice on fall-back day. Typical rules: run at the next valid time when skipped, and run once when repeated. Test both with a fake clock.

Q: The whole scheduler cluster was down for 30 minutes. What happens on restart?

A: Each job's misfire policy decides. "Catch up" runs the job once for the missed period, and "skip" moves `next_fire_at` to the next future tick. You rarely want to fire all 30 missed runs at once, because that floods workers.

Q: Why start with sharding instead of one leader?

A: One leader is simpler, and you should start there. It becomes a ceiling when one process cannot scan and insert fast enough at the hourly peak. Sharding spreads that work, at the cost of lease management and rebalancing.

Q: How do you test it?

A: Fake-clock tests cover cron calculation, including DST transitions. Chaos tests kill schedulers and workers, `SIGSTOP` a scheduler past its lease, and partition etcd, then assert the unique-run invariant and no lost ticks. A load test reproduces the top-of-hour spike.

Common mistakes in answers:

- Relying on a distributed lock alone to prevent duplicate runs. Without fencing, a paused process still acts on an expired lock.
- Promising exactly-once execution of jobs. It is exactly one run record, but at-least-once execution.
- Ignoring time zones, so jobs silently skip or double-fire on DST changes.

TL;DR

Shard ownership with leases, fence every write, let a unique index guarantee one run per tick, and accept at-least-once execution with idempotent jobs.

29. Multi-region payments ledger

Level: Advanced · **Time:** 5–8 weeks · **Prerequisites:** M6, M7, M17

What it is

A double-entry ledger service that records every movement of money as balanced journal entries, runs active-passive across two regions with a defined recovery point, moves money between accounts on different shards with a saga, processes requests exactly once in effect, and reconciles daily against an external bank file. **Double-entry** means every transaction debits one or more accounts and credits others by the same total, so the books always sum to zero.

The problem it solves

Money systems cannot lose, duplicate or invent a cent, must explain every balance from history, and must keep running when a region fails. Balances stored as a mutable number drift when bugs or retries hit. A ledger of immutable entries makes every balance derivable and auditable. Sharding and multi-region add the distributed-systems layer: cross-shard transfers, replication lag and failover without double spending.

Real-world examples

- Stripe's Ledger: Stripe's system for tracking and validating money movement describes modelling fund flows as an immutable log of double-entry events and detecting problems by checking that balances settle to zero.
- Modern Treasury's Accounting for developers, part I explains debits, credits and normal balances in programmer terms.
- TigerBeetle is an open-source database designed specifically for double-entry accounting.

Requirements


Functional

- Accounts with currency and type (asset, liability). Transfers with idempotency keys.
- Each transfer posts a journal entry of two or more lines that sum to zero.
- Pending (authorised) and posted (settled) states. Voids.
- Balance at any point in time. Overdraft rules per account.
- Cross-shard transfers. Daily reconciliation against an external settlement file.

Non-functional


- 2,000 transfers/s across 4 shards in the primary region.
- Zero imbalance: the sum over all lines is always zero.
- Region failover with RPO (recovery point objective: how much recent data you may lose) of zero for acknowledged transfers when using synchronous cross-region replication, or a documented few seconds with asynchronous. RTO (recovery time objective) under 5 minutes.

The architecture



- **Ledger API**: validates, deduplicates with idempotency keys (Project 5), routes by account.
- **Shards**: each holds a set of accounts with their entries and cached balances. Same-shard transfers are one local transaction.
- **Saga orchestrator**: for cross-shard transfers, debits into a **suspense** (clearing) account on the source shard, then credits from the clearing account on the destination shard, with compensation if the second step fails. Every step is itself a balanced entry, so the books balance at every moment.
- **Region B standbys**: streaming replicas for failover.
- **Reconciliation**: compares ledger events with the bank's file and flags breaks.

Data model



Amounts are signed integers in minor units (cents). Debits positive, credits negative, by convention.

Tech stack

Component	Choice	Why
Ledger service	Java 25 with Spring Boot 4.1.1	Strong typing for money, mature transactions
Shards	PostgreSQL, one primary per shard	Serializable or row-locked updates
Cross-region	PostgreSQL streaming replication (sync or async)	Measure the latency cost
Events	Kafka via CDC	Downstream reporting and reconciliation
Orchestration	Your Project 19 saga engine or Temporal	Durable cross-shard flow
Platform	Kubernetes in two clusters	Simulate regions

Milestones

1. **Single-node ledger.** Post balanced entries, reject unbalanced ones in the database (a deferred constraint trigger or check in the posting function). Done when 1 million random transfers keep the global sum at zero.
2. **Balances and concurrency.** Update account balances with row locks in a consistent order, or optimistic versions. Done when concurrent transfers on hot accounts never overdraw a no-overdraft account.
3. **Idempotency and pending or posted.** Done when retries never double-post and voids reverse pending entries correctly.
4. **Sharding and cross-shard sagas.** Done when cross-shard transfers balance at every intermediate step and failed credits compensate.
5. **Two regions.** Replicate each shard to region B. Measure p99 with synchronous vs. asynchronous replication. Done when a scripted region failover promotes standbys and the API resumes with no duplicate or lost acknowledged transfers (synchronous mode).
6. **Reconciliation.** Done when a seeded mismatch in the bank file is reported with the exact transfer IDs.

Deep dive: the hard parts

- **Immutability.** Never update or delete an entry line. Corrections are new reversing entries. That is what makes audit, replay and reconciliation possible.
- **Hot accounts.** A platform fee account receives a line from every transfer and becomes a lock hotspot. Split it into N sub-accounts and sum them for the balance, or post to it in batches asynchronously.
- **Failover and split brain.** If region A is only partitioned, not dead, and region B is promoted, both may accept transfers: double spending. Fence the old primary (revoke its credentials or stop its traffic at the routing layer) *before* promoting. Asynchronous replication means the last few seconds of acknowledged transfers may be missing in B. They must be recovered and re-applied or reconciled after A returns.
- **Exactly-once in effect.** Idempotency keys stored in the same transaction as the entry give exactly-once posting. Downstream consumers get at-least-once events and dedupe by entry ID.

Testing strategy

- Invariant checks after every test: global sum zero, per-account balance equals sum of its lines, no negative balance where forbidden.
- Property-based tests over random sequences of transfers, voids, retries and crashes.
- Region failover drills with traffic running, including a partition (not just a kill) of the primary region.

Trade-offs, scaling and failure modes

- Synchronous cross-region replication gives RPO zero but adds the inter-region round-trip to every write. Asynchronous is faster but loses the tail on failover. Many systems choose synchronous for the ledger and asynchronous for everything else.
- Sagas mean cross-shard transfers are briefly "in flight" through clearing accounts. Reports must account for that.
- Choosing shard keys by account makes most transfers cross-shard if accounts are random. Co-locate a customer's accounts on one shard.

Stretch goals

- Multi-currency with FX entries balanced per currency.
- Point-in-time balance queries using a balance snapshot table plus entries since.
- Active-active with accounts homed in one region each, and cross-region transfers as sagas.

Skills practised

- M17 — Case Studies: Money and Reservations: how money moves, the digital wallet ledger.
- M6 — Scaling: multi-region, DR strategies, RPO and RTO.
- M7 — Consistency: sagas vs. 2PC.
- M12 — Capstones: the payment platform design.

In the interview

30-second answer: I built a double-entry ledger where every money movement is an immutable journal entry whose lines sum to zero, sharded by account across 4 PostgreSQL primaries and replicated to a second region for failover. The key decision was immutability plus double entry, because every balance can then be recomputed from history and any bug shows up as books that no longer sum to zero. The hardest parts were cross-shard transfers, which run as a saga through a clearing account so the books balance at every step, and region failover without split brain, which needs the old primary fenced before the standby is promoted. It handles 2,000 transfers/s with a global sum of exactly zero, and synchronous replication gives an RPO of zero for acknowledged transfers.

Key terms to know:

- **Double-entry** — every transaction debits some accounts and credits others by the same total, so all lines sum to zero.
- **Journal entry and lines** — one entry per transfer, with two or more signed lines in minor units (cents).
- **Immutability** — lines are never updated or deleted. Corrections are new reversing entries.
- **Pending vs posted** — authorised but not settled, versus final. Voids reverse pending entries.
- **Clearing (suspense) account** — an intermediate account used by cross-shard sagas so each step is itself balanced.
- **Hot account** — an account hit by nearly every transfer, such as a fee account, causing lock contention.
- **RPO / RTO** — how much acknowledged data you may lose in a disaster, and how long recovery may take.
- **Synchronous vs asynchronous replication** — wait for the remote region before acknowledging, or not.
- **Split brain** — two regions both believe they are primary and both accept writes, which can double-spend.
- **Reconciliation** — comparing the ledger with an external bank file and flagging mismatches ("breaks").

Q: Why double-entry instead of a balance column?

A: A balance column is a single mutable number: if a bug or retry changes it wrongly, the history to prove what happened is gone. With double-entry, every balance is the sum of immutable lines, and all lines across the system must sum to zero. An error shows up as a non-zero sum or a balance that does not match its lines.

Q: How do you transfer money between shards without 2PC?

A: A saga. Step 1 on the source shard debits the customer and credits a clearing account, a balanced local entry. Step 2 on the destination shard debits the clearing account and credits the recipient, another balanced entry. If step 2 fails, a compensating entry on the source reverses step 1. The books balance at every moment, and reports treat clearing balances as in flight.

Q: How do you stop double-posting when clients retry?

A: Each transfer carries an idempotency key, stored with a unique constraint in the same transaction as the journal entry. A retry finds the existing entry and returns it. Downstream consumers of ledger events receive at-least-once delivery and dedupe by entry ID.

Q: How do you prevent overdrafts under concurrent transfers?

A: Update account balances with row locks taken in a consistent order (for example by account ID) to avoid deadlocks, or with optimistic version checks, and check the overdraft rule inside the same transaction. Two concurrent debits cannot both see the old balance.

Q: One fee account receives a line from every transfer. What happens?

A: It becomes a lock hotspot that serialises all transfers. Split it into N sub-accounts and pick one at random per transfer, then sum them for the reported balance. Or post fees to it in batches asynchronously.

Q: What is your RPO on region failure?

A: Zero for acknowledged transfers with synchronous replication, because a write is only acknowledged once region B has it. That adds the inter-region round-trip to every write. With asynchronous replication, it is the replication lag, a few seconds, and those tail transfers must be recovered and reconciled when region A returns.

Q: How do you avoid split brain on failover?

A: If region A is only cut off, not dead, promoting B lets both accept transfers. So fence A first: revoke its database credentials or stop its traffic at the routing layer, and only then promote B. A

single authority decides which region is active.

Q: What changes at 10x volume?

A: Add shards, and co-locate each customer's accounts on one shard so most transfers stay single-shard and avoid sagas. Hot accounts need sub-accounts or batching. Point-in-time balance queries use periodic balance snapshots plus entries since, instead of summing all history.

Q: How do you prove correctness?

A: After every test, check invariants: the global sum is zero, each account's balance equals the sum of its lines, and no forbidden negative balance exists. Property-based tests run random sequences of transfers, voids, retries and crashes. Failover drills run with live traffic and include a partition, not just a kill.

Q: Hands-on: how do you check a journal entry balances?

A: Sum its lines in the posting transaction and reject anything non-zero:

```
SELECT entry_id FROM entry_line
WHERE entry_id = $1
GROUP BY entry_id
HAVING SUM(amount_minor) <> 0;  -- any row -> ROLLBACK
```

Common mistakes in answers:

- Using floating point for money. Use integer minor units.
- Correcting mistakes by editing entries instead of posting reversing entries.
- Promoting the standby region without fencing the old primary first.

TL;DR

Immutable balanced entries make money auditable. Sagas through clearing accounts cross shards, idempotency makes retries safe, and fenced failover with a known RPO keeps it alive across regions.

30. Raft-replicated config store

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M3, M7

What it is

A small etcd-like service: a strongly consistent key-value store replicated across 3 or 5 nodes with the **Raft consensus algorithm** (a protocol that lets a group of servers agree on one ordered log of commands, as long as a majority is alive). It supports linearizable reads and writes, watches (clients get notified on change), leases with TTL, and compare-and-swap. Other projects (the scheduler, the Kafka-like controller) can use it.

The problem it solves

Configuration, leader election, locks and service discovery need one answer everyone agrees on, even when nodes fail and the network partitions. Eventually consistent stores cannot give that. Raft provides a replicated log where a committed entry is never lost or reordered while a majority survives, and is designed to be understandable compared with Paxos.

Real-world examples

- Ongaro and Ousterhout's In Search of an Understandable Consensus Algorithm (Raft) is the paper you implement: leader election, log replication, safety and membership changes.
- etcd's documentation describes the API you are imitating: revisions, watches, leases and transactions. etcd is the store behind Kubernetes.

Requirements


Functional

- `Put`, `Get`, `Delete`, `Txn` (compare-and-swap), `Watch(prefix, fromRevision)`, `LeaseGrant`, `KeepAlive`, keys attached to leases.
- A global, monotonically increasing revision on every change.
- Linearizable reads by default. Optional stale reads from followers.
- Snapshots and log compaction. Adding and removing members.

Non-functional

- 3-node and 5-node clusters. Survives (N-1)/2 failures.
- Write p99 under 20 ms on a LAN with fsync on.
- Leader re-election under 2 s after a crash.

The architecture



- **Raft module**: terms, votes, log, commit index. Elections by randomised timeout.
- **State machine**: applies committed commands in log order to a key-value map with revisions.
- **Watch hub**: streams events to watchers from a ring buffer of recent revisions.
- **Lease manager**: on the leader, expires leases and proposes delete commands through the log.
- **Snapshotter**: periodically snapshots state and truncates the log.

Data model

Type	Fields
`LogEntry`	`term`, `index`, `command`
Persistent Raft state	`currentTerm`, `votedFor`, log (fsynced before replying)
`KeyValue`	`key`, `value`, `createRevision`, `modRevision`, `version`, `leaseId`
`Lease`	`id`, `ttl`, `expiresAt`, attached keys

Tech stack

Component	Choice	Why
Nodes	Java 25 or Go-style design in Python 3.14	Careful concurrency either way
Transport	gRPC	Typed RPCs, streaming for watches
Storage	Append-only log file with fsync, plus snapshot files	Raft requires durable votes and log
Testing	Deterministic simulator plus Jepsen-style tests	Raft bugs hide in rare interleavings

Milestones

1. **Leader election.** Done when exactly one leader per term emerges across thousands of simulated runs with random delays and drops.
2. **Log replication and commit.** Done when entries committed by a majority are applied in the same order on all nodes despite crashes.

3. **Persistence and restart.** Done when a fully restarted cluster recovers all committed data.
4. **KV state machine, revisions and CAS.** Done when concurrent compare-and-swap clients see linearizable results.
5. **Linearizable reads.** Use ReadIndex: the leader confirms it is still leader with a heartbeat round before serving. Done when a deposed leader in a minority partition cannot serve stale reads.
6. **Watches, leases, snapshots and membership changes.** Done when watchers resume from a revision after reconnect, keys vanish when leases expire, and adding a node one at a time works under load.

Deep dive: the hard parts

- **Election safety.** A node grants its vote only if the candidate's log is at least as up to date as its own (higher last term, or same term and longer). That guarantees the new leader has every committed entry.
- **Commit rule subtlety.** A leader may only count replicas to commit entries from its *current* term. Older-term entries become committed indirectly. The Raft paper's figure 8 shows the data loss that happens otherwise. Reproduce it in your simulator.
- **Stale leaders and reads.** An old leader in a minority partition still thinks it leads. Serving reads from local state returns stale data. ReadIndex or leader leases (relying on bounded clock drift) fix this.
- **Membership changes.** Switching from 3 to 5 nodes at once can create two majorities. Change one node at a time, or use joint consensus.

Testing strategy

- Deterministic simulation with a seeded random scheduler for message delivery, drops, duplication and crashes. Run hundreds of thousands of seeds. Check safety properties after each step.
- Linearizability checking (with a tool like Porcupine or Knossos) on recorded client histories from real-cluster chaos tests.
- Fsync-disabled vs. enabled latency comparison, and a crash test showing why fsync matters.

Trade-offs, scaling and failure modes

- Every write needs a majority round-trip plus fsync. Consensus stores are for small, critical data, not bulk storage.
- 5 nodes tolerate 2 failures but add write latency. Cross-region Raft pays inter-region latency on every write.
- Watches with a bounded history mean very slow watchers must re-list and restart from a fresh revision.

Stretch goals

- Pre-vote to stop a partitioned node from disrupting the cluster with ever-higher terms when it returns.
- Multi-Raft: shard the keyspace into ranges, each its own Raft group (how TiKV and CockroachDB scale).

Skills practised

- M7 — Consistency: quorum, strong consistency, coordination.
- M3 — Storing Data: WAL, replication, snapshots.
- M9 — Operating in Production: the store behind Kubernetes.

In the interview

30-second answer: I built an etcd-like config store: a key-value state machine on top of my own Raft implementation, with revisions, compare-and-swap, watches, leases and snapshots, on 3- and 5-node clusters. The key decision was linearizable reads through ReadIndex, because a deposed leader in a minority partition still believes it leads and would otherwise serve stale data. The hardest part was finding bugs that only show up in rare message orderings, so I built a deterministic

simulator that runs hundreds of thousands of seeded schedules with drops, duplicates and crashes, and reproduced the Raft paper's figure-8 commit bug in it. Writes run under 20 ms p99 with fsync on, and a new leader is elected within 2 s of a crash.

Key terms to know:

- **Consensus** — getting a group of servers to agree on one ordered log of commands while a majority is alive.
- **Term** — a numbered election period. At most one leader per term.
- **Leader election** — a follower that hears no heartbeat within a randomised timeout becomes a candidate and requests votes.
- **Log replication and commit index** — the leader sends `AppendEntries`. An entry is committed once a majority stores it.
- **Election restriction** — a node votes only for a candidate whose log is at least as up to date as its own.
- **ReadIndex** — the leader confirms it is still leader with a quorum heartbeat before serving a read.
- **Revision** — a global counter bumped on every change, used for watches and compare-and-swap.
- **Watch** — a stream of changes to a key prefix from a given revision.
- **Lease** — a TTL that keys attach to. When it expires, the leader proposes deleting them through the log.
- **Snapshot and log compaction** — save the state and discard old log entries so the log does not grow forever.

Q: How does Raft guarantee a committed entry is never lost?

A: An entry is committed only once a majority stores it. A new leader needs votes from a majority, and nodes only vote for candidates whose log is at least as up to date as theirs. Any two majorities overlap, so at least one voter has the entry and would refuse a candidate missing it. The new leader therefore always has every committed entry.

Q: How do you serve linearizable reads?

A: With ReadIndex: the leader records its current commit index, sends a heartbeat round and waits for a majority to confirm it is still leader, waits until that index is applied, then reads. An old leader in a minority partition cannot get that confirmation, so it cannot serve a stale read. Leader leases are faster but depend on bounded clock drift.

Q: Why an odd number of nodes?

A: A cluster needs a majority to make progress. Three nodes need 2 and tolerate 1 failure. Four nodes need 3 and still tolerate only 1, so the fourth node adds latency and cost without more fault tolerance. Five nodes tolerate 2.

Q: Why must `currentTerm` and `votedFor` be fsynced before replying to a vote?

A: If a node votes, crashes, loses the vote from memory and restarts, it could vote again in the same term for a different candidate. Two leaders in one term would break Raft's safety. Persisting the vote first prevents that.

Q: What is the figure-8 problem?

A: A leader must not mark an entry from an older term as committed just because it now sits on a majority. A later leader that lacks it could still be elected and overwrite it. Raft only commits by counting replicas for entries from the leader's current term, which commits earlier entries indirectly.

Q: How do you change membership from 3 to 5 nodes?

A: Not all at once: during the switch, the old configuration and the new one could each form a separate majority and elect two leaders. Add one node at a time, letting each change commit before the next, or use joint consensus, where decisions need majorities of both old and new configurations.

Q: A follower is partitioned for a while and then rejoins. What can go wrong?

A: While isolated, it keeps timing out and raising its term. On return its higher term forces the healthy leader to step down, causing a needless election. Pre-vote fixes this: a node first checks it could win before incrementing its term.

Q: Why not use this store for application data?

A: Every write needs a majority round-trip plus fsync, and the whole dataset is held by every node. That is fine for small, critical data such as config, leader election and locks. To scale, you shard the keyspace into ranges, each its own Raft group (multi-Raft), as TiKV and CockroachDB do.

Q: How do you test it?

A: A deterministic simulator with a seeded random scheduler controls message delivery, drops, duplication and crashes, and checks safety properties after every step across hundreds of thousands of seeds. Client histories from chaos tests on the real cluster are checked with a linearizability checker such as Porcupine. A crash test with fsync disabled shows why durability matters.

Common mistakes in answers:

- Serving reads from the leader's local state without confirming leadership, which allows stale reads.
- Saying more nodes always means more fault tolerance. Even numbers add nothing.
- Treating Raft as a database for bulk data instead of a small, strongly consistent coordination store.

Self-check

- Why must `currentTerm` and `votedFor` be fsynced before replying to a vote request?
- What goes wrong if a leader commits an old-term entry by counting replicas?

TL;DR

Raft gives a majority-replicated, ordered log. Put a key-value state machine on it, serve reads safely, and test with deterministic simulation because the bugs live in rare interleavings.

31. S3-like object storage

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M3, M16

What it is

A distributed object store with an S3-compatible subset of the API: buckets, `PUT`, `GET` (with byte ranges), `DELETE`, `LIST` with prefixes, and multipart upload. A **metadata service** maps object names to locations, and **storage nodes** hold the bytes, protected first by 3-way replication and then by **erasure coding** (splitting data into k data pieces plus m parity pieces so any k of them can rebuild the original, using far less space than copies).

The problem it solves

Applications need cheap, durable storage for huge numbers of files of any size, without managing disks. Durability at scale means surviving disk, node and rack failures routinely. Replication is simple but triples storage cost. Erasure coding cuts the overhead (for example 1.5x for 6+3) at the price of more complex reads, writes and repairs. Separating metadata from data lets each scale on its own terms.

Real-world examples

- Facebook's f4: Facebook's Warm BLOB Storage System (OSDI 2014) explains moving less frequently accessed photos from replication to Reed-Solomon erasure coding to cut the replication factor.
- Facebook's Haystack paper shows how packing small objects into large append-only volumes avoids per-file filesystem metadata overhead.
- MinIO's documentation describes an open-source S3-compatible store using erasure sets.

Requirements


Functional

- Bucket CRUD. Object `PUT` up to 5 GB single, larger via multipart. `GET` with `Range`. `HEAD`. `DELETE`.
- `LIST` with prefix, delimiter and continuation token.
- Versioning (optional per bucket). Checksums on upload and on every read.
- Background scrubbing and automatic repair after node loss.

Non-functional


- 6 storage nodes plus 3 metadata nodes in Kubernetes.
- Durability design target: survive any 2 simultaneous node failures without data loss.
- Small object `GET` p99 under 50 ms. Large object throughput limited by the network, not the service.
- Read-after-write consistency for new objects and overwrites.

The architecture



- **API front end**: stateless. Authenticates (AWS Signature V4 if you want real clients to work), splits objects into chunks, computes checksums, writes chunks, then commits metadata.
- **Metadata service**: bucket and object records, version IDs, chunk lists. Partitioned by bucket plus key hash. Use your Project 30 Raft store or PostgreSQL.
- **Placement service**: chooses nodes for each chunk across failure domains (different nodes and simulated racks).
- **Storage nodes**: append chunks into large volume files with an index of `chunk_id -> (file, offset, length, crc)`.
- **Repair and scrubber**: reads chunks to verify checksums, rebuilds missing or corrupt ones.
- **Garbage collector**: deletes chunks no longer referenced, compacts volumes.

Data model



Tech stack

Component	Choice	Why
Services	Java 25 (Netty or virtual threads)	Streaming I/O
Metadata	PostgreSQL first, then Project 30 store	Strong consistency for names
Erasure coding	A Reed-Solomon library	Do not write Galois-field maths from scratch first
Test clients	AWS CLI and SDKs pointed at your endpoint	Real compatibility
Platform	Kubernetes StatefulSets with volumes	Node identity and disks

Milestones

1. **Single-node store.** PUT, GET, DELETE, LIST with metadata in PostgreSQL and data in volume files. Done when the AWS CLI can upload and download.
2. **Replication across nodes.** Write 3 copies on distinct nodes, acknowledge after all succeed (or 2 of 3 with repair). Done when killing a node keeps every object readable.
3. **Multipart upload and ranges.** Done when a 10 GB upload with parallel parts succeeds and range reads return exact bytes.
4. **Erasure coding.** 4+2 for objects above a size threshold. Done when any 2 of 6 nodes can be lost and every object still reads.
5. **Scrubbing and repair.** Done when deliberately corrupting a chunk on disk is detected and repaired, and a dead node's chunks are rebuilt elsewhere.
6. **Versioning and garbage collection.** Done when overwrites keep history, delete markers hide objects, and unreferenced chunks are reclaimed.

Deep dive: the hard parts

- **Commit order.** Write data chunks first, then commit metadata in one atomic step. A crash in between leaves orphan chunks (harmless, collected later) but never metadata pointing to missing data.
- **Read-after-write.** Because metadata commit is the single point of truth, any GET after a successful PUT sees the new version. Caches in front of metadata must be invalidated or versioned.
- **Erasure coding costs.** A small read needs k chunks from k nodes, and repairing one lost chunk reads k others, multiplying network traffic during recovery. That is why small or hot objects are often replicated and large or cold objects erasure-coded.
- **Listing.** `LIST` with a prefix needs keys sorted. Hash-partitioned metadata breaks sort order, so partition by range of `bucket/key` or maintain a sorted index per bucket.

Testing strategy

- S3 compatibility tests with real SDKs (upload, multipart, ranges, listing pagination).
- Fault injection: kill nodes during writes, corrupt bytes on disk, fill a disk.
- Durability simulation: randomly fail nodes over simulated months and check that repair keeps up.

Trade-offs, scaling and failure modes

- Replication: fast reads and simple repair, 3x cost. Erasure coding: around 1.5x cost, slower small reads and costlier repair.
- Metadata is the scaling bottleneck and the consistency anchor. Partition it carefully, and keep it small (no data bytes).
- Correlated failures (a whole rack, a bad firmware batch) break independence assumptions. Spread placements across failure domains.

Stretch goals

- Lifecycle rules: transition to erasure-coded "cold" class after N days, expire after M days.
- Presigned URLs (Project 11 against your own store).
- Cross-region asynchronous replication.

Skills practised

- M16 — Case Studies: Infrastructure: S3-like object storage.
- M3 — Storing Data: replication, partitioning, WAL.
- M7 — Consistency: read-after-write.

In the interview

30-second answer: I built an S3-compatible object store with buckets, PUT, ranged GET, prefix LIST and multipart upload, which the real AWS CLI can talk to. The key decision was separating a strongly consistent metadata service, which maps names to chunk locations, from storage nodes that append chunks into large volume files, because names need consistency and bytes need cheap bandwidth. Durability comes from 3-way replication for small objects and 4+2 erasure coding for large ones, spread across failure domains, plus a scrubber that finds and repairs corrupt or missing chunks. The hardest part was commit order: data first, metadata last, so a crash leaves only harmless orphans. On 6 storage nodes it survives any 2 node failures with no data loss.

Key terms to know:

- **Metadata vs data separation** — names, versions and chunk lists in a consistent store, and bytes on storage nodes. Each scales separately.
- **Chunk and volume file** — objects are split into chunks appended into large files, with an index of `chunk_id -> (file, offset, length, crc)` .
- **Replication factor** — keeping 3 full copies. Simple and fast to read, but 3x storage.

- **Erasure coding (k+m)** — k data pieces plus m parity pieces, where any k rebuild the object. 4+2 costs 1.5x storage and survives 2 losses.
- **Failure domain** — a unit that can fail together, such as a node or rack. Pieces of one object go to different domains.
- **Placement service** — chooses which nodes store each chunk.
- **Scrubbing** — reading stored chunks in the background to verify checksums and catch silent corruption.
- **Read-after-write consistency** — any GET after a successful PUT sees the new version.
- **Multipart upload** — uploading a large object as independent parts, in parallel and resumable, then completing it.
- **Garbage collection and orphans** — chunks with no metadata pointing at them are deleted later.

Q: Why separate metadata from data?

A: Metadata is small but must be strongly consistent and fast to look up, because it decides what a name means. Data is huge and needs cheap bulk bandwidth and disk. Separating them lets you run metadata on a consistent, partitioned store and scale storage nodes independently.

Q: Replication or erasure coding?

A: Replication gives fast reads from any one copy and simple repair, at 3x storage. Erasure coding cuts overhead to about 1.5x, but a read needs k pieces from k nodes, and repairing one lost piece reads k others, which multiplies network traffic. So small or hot objects are replicated, and large or cold objects are erasure-coded.

Q: How do you avoid metadata pointing at missing data?

A: Write all chunks first and verify their checksums, then commit the metadata in one atomic step. A crash before the commit leaves orphan chunks that nothing references, and the garbage collector removes them. A crash can never leave a name pointing at data that does not exist.

Q: How do you get read-after-write consistency?

A: The metadata commit is the single point of truth. Once it succeeds, every GET looks up that metadata and finds the new version. Any cache in front of metadata must be invalidated or keyed by version, or it would serve the old object.

Q: Why does LIST make metadata partitioning hard?

A: LIST with a prefix must return keys in sorted order. If metadata is partitioned by a hash of the key, sorted order is scattered across every partition. So partition by key range within a bucket, or keep a sorted index per bucket.

Q: A disk silently corrupts a few bytes. How do you notice?

A: Every chunk has a checksum, verified on every read and by a background scrubber that reads everything periodically. A mismatch triggers repair from other replicas or by rebuilding from erasure-coded pieces, and the bad copy is replaced.

Q: A storage node dies permanently. What happens?

A: Objects stay readable from the other replicas or the remaining erasure pieces. The repair service finds every chunk that had a piece on the dead node and rebuilds it on another node in a different failure domain. Repair speed matters, because a second and third failure before repair finishes could lose data.

Q: Why pack chunks into large volume files instead of one file per object?

A: Billions of small files overwhelm a filesystem's metadata: each needs an inode and several disk seeks to open. Appending chunks to large volumes, as Facebook's Haystack does, makes a read one seek using an in-memory index.

Q: What changes at 100x the objects?

A: Metadata becomes the bottleneck and must be partitioned carefully while staying small (no data bytes). Storage nodes scale out, with placement spreading data across more failure domains. Correlated failures, such as a whole rack or a bad firmware batch, matter more, so placement must spread across them.

Q: How do you test it?

A: Real AWS SDKs and the CLI run compatibility tests for upload, multipart, ranges and listing pagination. Fault injection kills nodes during writes, corrupts bytes on disk and fills a disk. A durability simulation fails nodes randomly over simulated months to check repair keeps up.

Common mistakes in answers:

- Committing metadata before data, which can leave names pointing at missing bytes.
- Recommending erasure coding for everything without mentioning slower small reads and expensive repair.
- Ignoring correlated failures. Three replicas in one rack are one failure away from loss.

TL;DR

A metadata service names things, storage nodes hold bytes in big volumes, placement spreads risk, erasure coding saves space, and scrubbing plus repair keep durability real.

32. Collaborative editor with CRDTs

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M2, M16

What it is

A Google-Docs-style rich-text editor where many people edit the same document at once, each sees others' cursors live, edits made offline merge cleanly on reconnect, and the server persists history. You use a **CRDT** (conflict-free replicated data type: a data structure whose replicas can be edited independently and always merge to the same result) for the text, a WebSocket sync server, and an append-only update log with snapshots.

The problem it solves

If two users type at the same position at the same time, naive "last write wins" loses one person's text. Locking the document destroys the real-time feel. The two families of solutions are **operational transformation** (OT: transform each operation against concurrent ones, usually via a central server) and CRDTs (design the data so merges are automatic). CRDTs also enable offline and peer-to-peer editing, at a cost in metadata size.

Real-world examples

- Figma's How Figma's multiplayer technology works explains why they chose a server-authoritative, CRDT-inspired design rather than OT for design documents.
- Automerge and Yjs are open-source CRDT libraries for JSON-like documents and shared text.
- Ink and Switch's Local-first software essay sets out the case for CRDT-based apps that work offline.

Requirements


Functional

- Create and open documents. Real-time collaborative editing with formatting.
- Presence: live cursors and selections with names and colours.
- Offline edits merge on reconnect without data loss.
- Version history and restore. Permissions: owner, editor, viewer.

Non-functional


- Remote edits visible within 200 ms p95 in one region.
- 50 simultaneous editors per document. 10,000 open documents per sync server.
- Document load under 1 s for a 100-page document.
- Server restart loses no acknowledged edits.

The architecture



- **Editor clients**: hold a full CRDT replica, apply local edits immediately, send compact binary updates.
- **Sync server**: one in-memory room per open document. It merges incoming updates, broadcasts them to others and appends them to the log.
- **Room router**: ensures all clients of a document connect to the same server (consistent hashing by document ID).
- **Update log and snapshots**: every update is appended. Periodically the merged state is snapshotted and older updates compacted.
- **Awareness channel**: ephemeral cursor and presence state, never persisted.

Data model



In PostgreSQL store `payload` and `state` as `bytea`.

Tech stack

Component	Choice	Why
CRDT	Write a simple sequence CRDT first, then use Yjs or Automerge	Learn the idea, then use a tuned library
Client	React 19 with a rich-text editor binding	Real UI
Sync server	Node 24 (Yjs ecosystem) or Java 25 with an Automerge binding	Library availability
Storage	PostgreSQL	Ordered log and snapshots

Milestones

1. **Toy sequence CRDT.** Each character gets a unique ID `(clientId, counter)` and a reference to the character it was inserted after. Deletes are tombstones. Done when random concurrent edits on 3 simulated replicas converge to identical text in a property test.
2. **Sync server with one room.** Done when two browsers edit together in real time.
3. **Persistence.** Append updates, snapshot every N updates. Done when restarting the server and reloading shows the same document.
4. **Offline and reconnect.** Client sends its **state vector** (how many updates it has from each client). Server replies with only what is missing. Done when 10 minutes of offline edits on both sides merge cleanly.
5. **Presence and permissions.** Done when cursors move live and viewers cannot send updates (enforced server-side).
6. **Multi-server routing and history.** Done when documents are spread across servers by ID and any past snapshot can be restored as a new version.

Deep dive: the hard parts

- **Why CRDTs converge.** Every replica applies the same set of operations, and the merge rules (insert positions by unique ID, deterministic tie-breaks by client ID) do not depend on arrival order. Order-independence is the whole trick.
- **Interleaving.** Two users typing "abc" and "xyz" at the same spot can, in naive CRDTs, produce "axbycz". Production algorithms (YATA in Yjs, RGA variants) add rules that keep each user's run of characters together.
- **Tombstones and metadata growth.** Deleted characters stay as tombstones so concurrent references still resolve. Documents grow with history. Libraries garbage-collect what is safe and encode IDs compactly. Measure document size after a long editing session.
- **Rich text intent.** Concurrent "bold this word" and "insert inside the word" must produce intuitive results. Formatting as marks over ranges anchored to character IDs is the usual approach (Peritext explores this).

Testing strategy

- Property tests: random ops on N replicas, random delivery order, assert convergence.
- Fuzzing the sync protocol with dropped and duplicated messages.
- Load test: 50 bots editing one document, measure latency and server CPU.

Trade-offs, scaling and failure modes

- OT: compact operations, needs a central server and complex transform functions. CRDT: works offline and peer to peer, larger metadata.
- One room per document on one server is simple and fast, but a document is limited by one server's capacity. That is fine for text documents.
- Server-side validation is harder with CRDTs: you must decode updates to enforce rules (like size limits) before applying them.

Stretch goals

- Comments anchored to text that survive edits.
- End-to-end encrypted documents (the server stores opaque updates and cannot compact them).

Skills practised

- M16 — Case Studies: Infrastructure: collaborative editor, OT vs. CRDT.
- M2 — Moving Data: bidirectional streaming.
- M18 — Client and Mobile System Design: offline-first and sync.

In the interview

30-second answer: I built a Google-Docs-style collaborative editor where every client holds a full CRDT replica of the document, applies its own edits instantly, and syncs compact updates through a WebSocket server with one in-memory room per document. The key decision was a CRDT instead of operational transformation, because CRDT merges are order-independent, so offline edits on two sides merge cleanly on reconnect without transform logic. The hardest parts were metadata growth from tombstones and efficient reconnect, which I handled with snapshots plus an update log, and state vectors so the server sends only what a client is missing. Remote edits appear within 200 ms p95 with 50 editors on one document.

Key terms to know:

- **CRDT (conflict-free replicated data type)** — a data structure whose replicas can be edited independently and always merge to the same result.
- **Operational transformation (OT)** — the alternative: transform each operation against concurrent ones, usually through a central server.
- **Sequence CRDT** — each character gets a unique ID `(clientId, counter)` and a reference to the character it was inserted after.
- **Convergence** — all replicas that received the same set of operations show identical content, regardless of arrival order.
- **Tombstone** — a deleted character kept as a marker, so concurrent inserts that reference it can still be placed.
- **State vector** — how many updates a replica has from each client. Used to compute exactly what is missing.
- **Interleaving anomaly** — concurrent typing at one spot producing "axbycz". Algorithms like YATA (Yjs) keep each user's run together.
- **Awareness / presence** — cursors and selections. Ephemeral, broadcast but never persisted.
- **Room** — the in-memory state of one open document on one sync server, located by consistent hashing of the document ID.
- **Update log and snapshots** — every update appended in order, with periodic merged snapshots so loading is fast.

Q: OT or CRDT?

A: OT sends small operations and transforms them against concurrent ones, which works well with a central server but needs complex, error-prone transform functions. CRDTs need no transforms: merges are automatic and order-independent, which enables offline and peer-to-peer editing. The cost is extra metadata per character and tombstones.

Q: Why do CRDT replicas converge?

A: Every replica eventually applies the same set of operations, and the merge rules do not depend on the order they arrive. Insert positions are defined by unique IDs, not numeric indexes, and ties are broken deterministically, such as by client ID. So any delivery order gives the same text.

Q: Why keep tombstones for deleted characters?

A: Another user may concurrently insert text "after character X" while you delete X. If X were removed completely, their replica and yours could not agree where the insert goes. The tombstone keeps X's position as an invisible anchor.

Q: How does a reconnecting client sync efficiently?

A: It sends its state vector, which says how many updates it has from each client. The server compares with its own and returns only the missing updates, and the client sends the server what the server is missing. After 10 minutes offline on both sides, only the difference crosses the network.

Q: Two users type "abc" and "xyz" at the same spot. What do they see?

A: A naive CRDT can produce "axbycz", which is technically converged but useless. Production algorithms such as YATA in Yjs add ordering rules that keep each user's run of characters together, giving "abcxyz" or "xyzabc" on every replica.

Q: Why route all editors of one document to the same server?

A: The room holds the merged state in memory, broadcasts updates between connected clients and appends to the log. If editors were spread across servers, every update would need cross-server fan-out. Consistent hashing on the document ID makes one server the owner. One document is limited to one server's capacity, which is fine for text.

Q: The sync server crashes. Are edits lost?

A: Not acknowledged ones, because each update is appended to the PostgreSQL log before it is acknowledged. Clients reconnect to the new owner, which loads the latest snapshot plus later updates, and each client sends anything it had not yet had acknowledged. CRDT merging makes duplicate updates harmless.

Q: How do you enforce permissions with CRDTs?

A: Every client has a full replica and could generate any update, so the server must enforce rules. Viewers' updates are rejected at the server before merging. Rules like size limits require decoding updates before applying them, which is harder than with simple operations.

Q: What grows over time, and how do you control it?

A: Tombstones and per-character IDs make documents grow with their edit history, not just their visible length. Libraries garbage-collect tombstones that are safe to drop and encode IDs compactly. Snapshots and log compaction keep load time under 1 s for a 100-page document.

Q: How do you test it?

A: Property tests apply random operations on several replicas, deliver them in random orders, and assert identical results. The sync protocol is fuzzed with dropped and duplicated messages. A load test runs 50 bots editing one document and measures latency and server CPU.

Common mistakes in answers:

- Using character indexes as positions. Indexes shift under concurrent edits, so CRDTs use unique IDs.
- Saying CRDTs have no costs. Metadata and tombstones grow with history.
- Persisting cursor and presence data, which is ephemeral and should never hit the database.

TL;DR

Give every character a unique ID and order-independent merge rules, sync with state vectors, persist an update log with snapshots, and keep each document's room on one server.

33. Video transcoding and streaming platform

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M2, M8, M14

What it is

A mini video platform: creators upload videos, a pipeline splits each into chunks, transcodes them in parallel into a ladder of resolutions and bitrates, packages them for **HLS** (HTTP Live Streaming: video served as short segment files plus playlists) and serves them through a cache tier so players can do **adaptive bitrate** (ABR: switching quality based on measured bandwidth).

The problem it solves

Raw uploads are huge and in arbitrary formats. Viewers have phones on bad networks and TVs on fibre. Transcoding a 2-hour video on one machine takes hours, so it must be parallelised as a **DAG** (directed acyclic graph of tasks with dependencies). Delivery must scale to many viewers per video, which only works if segments are cacheable at the edge.

Real-world examples

- Netflix's Per-Title Encode Optimization explains choosing the bitrate ladder per title based on its complexity rather than a fixed ladder.
- RFC 8216 specifies HLS playlists and segments.
- FFmpeg is the open-source tool you will drive for transcoding and packaging.

Requirements


Functional

- Resumable upload of files up to 10 GB.
- Pipeline: validate, split into segments of a few seconds at keyframes, transcode to 4 renditions (for example 240p to 1080p), package HLS, generate thumbnails, publish.
- Playback with ABR in a web player. Basic view counting.
- Status API and webhooks on completion (reuse Project 6).

Non-functional


- A 10-minute 1080p video ready within 5 minutes on 8 worker pods.
- Failed tasks retried without redoing the whole video.
- Segment cache hit ratio above 95% for popular videos.
- Start-up time under 2 s on a good connection.

The architecture



- **Upload service**: resumable uploads (the tus protocol or S3 multipart), then hands off to the orchestrator.
- **Orchestrator**: expands a video into a DAG: split → N chunks × M renditions transcode → per-rendition concatenate and package → master playlist → publish. Tracks task state in PostgreSQL.
- **Workers**: stateless containers pulling tasks, autoscaled on queue depth (Kubernetes with KEDA or HPA on a custom metric).
- **Edge cache and origin shield**: a two-tier cache (Nginx locally). The shield collapses many edge misses into one origin fetch.

Data model



Tech stack

Component	Choice	Why
Orchestrator	Java 25 Spring Boot 4.1.1 or Python 3.14, or Temporal	DAG state and retries
Workers	FFmpeg in containers	Industry standard
Queue	Kafka or RabbitMQ	Task distribution
Storage	MinIO or your Project 31 store	Segments and playlists
Delivery	Nginx edge plus shield caches	Request collapsing
Player	hls.js in a React 19 page	ABR in the browser

Milestones

1. **Single-machine pipeline.** Upload, one FFmpeg command to HLS with 4 renditions, play in hls.js. Done when ABR switches on a throttled network (browser dev tools).
2. **Split and parallel transcode.** Split at keyframes into chunks, transcode chunks in parallel, concatenate. Done when an 8-worker run is about 5x faster than single-machine with no visible glitches at chunk boundaries.
3. **DAG orchestration with retries.** Done when killing workers mid-task causes only those tasks to rerun.
4. **Autoscaling workers on Kubernetes.** Done when queue depth drives pod count up and back down.
5. **Two-tier caching.** Done when 1,000 simulated viewers of one new video produce one origin fetch per segment (request collapsing at the shield).

6. **Per-title ladder.** Measure complexity with a quick test encode, then choose bitrates. Done when a cartoon gets lower bitrates than an action scene at similar quality (compare with a VMAF or SSIM score).

Deep dive: the hard parts

- **Keyframe-aligned chunks.** Decoders can only start at keyframes. Split only at keyframes, and force the same keyframe interval across renditions so players can switch quality at every segment boundary.
- **Idempotent tasks.** Output keys are deterministic (`video/rendition/chunk_0007.ts`), so a retried task overwrites rather than duplicates. Mark the task done only after the upload completes.
- **Request collapsing.** When a popular video publishes, thousands of edge requests for segment 1 arrive at once. Caches must hold all but one request until the first fetch returns (Nginx `proxy_cache_lock`). Without it the origin melts.
- **Cost.** Transcoding is the biggest compute bill. Cache-friendly ladders, skipping renditions above the source resolution and encoding rarely watched videos lazily all save money.

Testing strategy

- Golden videos: odd frame rates, variable frame rate, rotated phone video, audio-only, corrupt files.
- Chaos: kill workers and the orchestrator during processing.
- Load test the delivery tier with many concurrent players using a segment-fetching script.

Trade-offs, scaling and failure modes

- Chunked parallel encoding is fast but can slightly reduce compression efficiency at chunk edges compared with one pass.
- HLS segment length: shorter segments mean faster start and switching, but more requests and lower cache efficiency.
- Origin outage: edges keep serving cached segments of popular videos. Long-tail videos fail first.

Stretch goals

- Low-latency live streaming with short partial segments.
- DRM key delivery design (no implementation required, but sketch the flow).
- Watch-time analytics via Project 23's pipeline.

Skills practised

- M14 — Case Studies: Messaging and Media: video platform, chunked transcoding DAG, ABR, tiered CDN.
- M8 — API and Edge: CDN design.
- M9 — Operating in Production: autoscaling on Kubernetes.

In the interview

30-second answer: I built a mini video platform: resumable uploads, a pipeline that splits each video at keyframes, transcodes the chunks in parallel into 4 renditions, packages them as HLS, and serves segments through an edge cache plus an origin shield so players can switch quality as bandwidth changes. The key decision was modelling the pipeline as a DAG of small idempotent tasks, so a 10-minute 1080p video is ready in under 5 minutes on 8 workers and a crashed worker only reruns its own chunk. The hardest part on the delivery side was a new popular video, which I solved with request collapsing at the shield so 1,000 viewers cause one origin fetch per segment. I also chose bitrates per title, so a cartoon gets a lower ladder than an action scene.

Key terms to know:

- **Transcoding** — decoding a video and re-encoding it at a different resolution, bitrate or codec.

- **Rendition / bitrate ladder** — the set of versions, such as 240p to 1080p, each at a target bitrate.
- **HLS** — HTTP Live Streaming: video served as short segment files plus playlists that list them.
- **Adaptive bitrate (ABR)** — the player measures bandwidth and picks a rendition per segment to avoid stalls.
- **Keyframe** — a frame that can be decoded on its own. Chunks and segments must start on one.
- **DAG pipeline** — tasks with dependencies: split, then chunks times renditions transcode in parallel, then package, then publish.
- **Idempotent task** — deterministic output keys, so a retry overwrites instead of duplicating.
- **Origin shield** — a cache tier between edges and storage that collapses many edge misses into one origin fetch.
- **Request collapsing** — holding concurrent misses for the same object until the first fetch returns (Nginx `proxy_cache_lock`).
- **Per-title encoding** — choosing the ladder from the content's complexity, measured with a quality score such as VMAF.

Q: How do you transcode a long video quickly?

A: Split it at keyframes into chunks of a few seconds, and transcode every chunk for every rendition as a separate task in parallel. Then concatenate per rendition and package as HLS. Time drops roughly with the number of workers, minus split and package overhead.

Q: Why must chunks and segments align on keyframes?

A: A decoder can only start decoding at a keyframe. Splitting elsewhere produces glitches at chunk boundaries. Forcing the same keyframe interval across all renditions also means segment boundaries line up, so the player can switch quality at any segment.

Q: Why multiple renditions?

A: Viewers range from phones on weak mobile signal to TVs on fibre. With ABR, the player picks the best rendition its measured bandwidth can sustain for each segment, dropping quality instead of stalling and going back up when the network improves.

Q: A worker dies mid-task. What reruns?

A: Only that task. The orchestrator tracks each task's state in PostgreSQL, and the queue redelivers the unfinished task. Its output key, such as `video/720p/chunk_0007.ts`, is deterministic, so the retry overwrites any partial upload, and the task is marked done only after the upload completes.

Q: How do you serve a viral video's first minute?

A: Thousands of players request segment 1 at once, and every edge misses. The shield collapses those into one fetch per segment, and each edge also holds duplicate requests with a cache lock. After that, segments are immutable and cache with very high hit rates.

Q: Short or long HLS segments?

A: Short segments (2 s) give faster start-up and quicker quality switches, but more requests, more playlist entries and lower cache efficiency. Long segments (6–10 s) are more efficient but slower to start and adapt. A common default is around 4–6 seconds.

Q: What happens if the origin storage goes down?

A: Edges and the shield keep serving cached segments, so popular videos keep playing. Long-tail videos, which are mostly cache misses, fail first. New uploads cannot be processed until storage is back.

Q: What changes at 100x uploads?

A: Transcoding compute is the biggest cost and scales with workers, so autoscale on queue depth and save money with per-title ladders, by skipping renditions above the source resolution, and by encoding rarely watched videos lazily. The orchestrator and task table must be partitioned, and delivery leans harder on the CDN.

Q: How do you test it?

A: A set of awkward golden videos: odd and variable frame rates, rotated phone video, audio-only, corrupt files. Chaos tests kill workers and the orchestrator mid-pipeline. A delivery load test runs

many concurrent players with a segment-fetching script and checks the origin sees one request per segment.

Common mistakes in answers:

- Splitting chunks at fixed times instead of keyframes, which breaks decoding at boundaries.
- Serving video from origin storage without a shield and request collapsing.
- Using one fixed bitrate ladder for all content, which wastes bandwidth on simple videos.

TL;DR

Chunk at keyframes, transcode as a parallel DAG with idempotent tasks, package for ABR, and protect the origin with tiered caches that collapse requests.

34. Ride-sharing dispatch

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M12, M15

What it is

The real-time core of a ride-hailing app: drivers stream GPS locations every few seconds, riders request trips, a dispatch service finds nearby available drivers and offers the trip, trips move through a state machine, and the whole system is partitioned by geography so a city's traffic stays local. You simulate thousands of drivers and riders in a city.

The problem it solves

Location data changes constantly (every driver, every 4 seconds), queries are spatial ("available drivers within 2 km"), and matching must be fast and must never assign one driver to two riders. It is a two-sided marketplace with real-time state, where staleness, races and partial failures directly cost money and trust. Module 12 designs it at whiteboard level. This project makes you feel the race conditions.

Real-world examples

- Uber's H3: Uber's Hexagonal Hierarchical Spatial Index describes the grid they built for analysing and partitioning location data.
- Lyft's Matchmaking in Lyft Line series discusses matching riders for shared rides and the cost of each matching approach.

Requirements


Functional

- Driver app: go online or offline, send location every 4 s, accept or decline offers.
- Rider app: request a trip, see the driver approach, cancel.
- Dispatch: find candidate drivers by ETA (estimated time of arrival), offer to the best one with a 10 s timeout, then the next.
- Trip lifecycle: requested → matched → driver arriving → in progress → completed, with cancellations.
- Surge: price multiplier per hex cell from supply and demand.

Non-functional


- Simulated city: 20,000 online drivers, 5,000 location updates/s, 50 trip requests/s.
- Match within 5 s p95.
- A driver is never matched to two active trips.
- Losing a dispatch node loses no trips and recovers within 30 s.

The architecture



- **Location gateway**: validates and writes updates to Kafka keyed by H3 cell at a coarse resolution (city region).
- **Location index**: Redis sets per fine H3 cell with driver IDs and a hash per driver for last position, status and timestamp. Stale entries expire.
- **Trip service**: owns trip state in PostgreSQL. The source of truth.
- **Dispatch service**: one leader per city shard. It searches rings of cells around the rider, ranks by ETA, and runs the offer loop.
- **ETA service**: road-network travel time (start with straight-line distance times a factor, then a real routing engine like OSRM).
- **Push gateway**: delivers offers to drivers over WebSockets.

Data model



Tech stack

Component	Choice	Why
Services	Java 25 Spring Boot 4.1.1	Concurrency and a typed state machine
Spatial index	H3 library plus Redis	Uniform neighbour rings
Stream	Kafka	Location firehose and replay for analytics
Trips	PostgreSQL	Transactions for assignments
Simulator	Python 3.14 agents moving on a road graph	Realistic load
Platform	Kubernetes with one dispatch deployment per city shard	Geo-partitioning

Milestones

1. **Simulator and location ingest.** Done when 20,000 simulated drivers stream positions and the index answers "drivers within k rings" in under 10 ms.
2. **Trip state machine.** Done when illegal transitions are rejected and every state change is versioned.
3. **Single-offer dispatch.** Rank by ETA, offer, timeout, next. Done when trips match within 5 s p95 in the simulation.
4. **No double assignment.** Assign by conditional update `UPDATE driver SET status='on_trip', current_trip_id=? WHERE id=? AND status='available'`. Done when a test where two dispatchers race for one driver yields exactly one success.
5. **Geo-sharded dispatch.** One dispatcher leader per city region with lease-based election. Done when killing a dispatcher moves its region within 30 s and in-flight trips resume from the database.
6. **Surge.** Done when demand spikes in a cell raise its multiplier smoothly (with damping) and drivers drift toward it in the simulator.

Deep dive: the hard parts

- **Stale locations.** A driver's position is up to 4 s old and may come from a phone in a tunnel. Expire entries after a few missed updates, and confirm availability at offer time, not at search time.
- **Greedy vs. batched matching.** Matching each request immediately to its nearest driver is fast but globally poor: a driver can be taken by a rider who had other options. Batching requests for a second or two and solving a small assignment problem improves total ETA at the cost of latency.
- **Shard boundaries.** A rider near a region edge needs drivers from the neighbouring shard. Either query neighbouring shards' indexes (read-only) or overlap regions, while assignment stays with the rider's shard.
- **Offer races.** A driver accepts just as the offer times out and the next driver is offered. The accept must be a conditional update on the offer and trip versions, so only one acceptance can win.

Testing strategy

- The simulator is the test harness: run scenarios (rush hour, stadium event, a dispatcher crash) and check invariants: no driver on two trips, every request eventually matched or cancelled.
- Chaos on Redis (index loss rebuilds from the next 4 s of updates) and Kafka.
- Measure match latency and average pickup ETA as quality metrics.

Trade-offs, scaling and failure modes

- Redis index is ephemeral and rebuildable from the stream within seconds. Trips must never be ephemeral, so they live in PostgreSQL.
- Geo-sharding keeps traffic local and failures contained to a city, but uneven cities need splitting.
- If dispatch is down, requests queue. Riders see "finding your driver" rather than errors.

Stretch goals

- Shared rides with route insertion.
- Driver positioning recommendations from demand forecasts.

Skills practised

- M12 — Capstones: ride-sharing dispatch design.
- M15 — Case Studies: Location and Real-Time: spatial indexes, nearby friends fan-out.
- M7 — Consistency: conditional updates and leases.
- M6 — Scaling: partitioning by geography.

In the interview

30-second answer: I built the real-time core of a ride-hailing app: 20,000 simulated drivers stream GPS every 4 s through Kafka into a Redis index keyed by H3 hexagon cells, and a dispatch service per city shard searches rings of cells around a rider, ranks drivers by ETA and offers the trip with a 10 s timeout. The key decision was splitting state: locations are ephemeral and rebuildable in Redis, while trips and driver assignments live in PostgreSQL as the source of truth. The hardest part was never assigning one driver to two riders, which I enforce with a conditional update on driver status and versioned offers. Trips match within 5 s p95, and a dispatcher crash moves its region to another node within 30 s with no lost trips.

Key terms to know:

- **H3** — Uber's hexagonal grid. Hexagons have uniform distances to all neighbours, which makes "k rings around a cell" a clean radius search.
- **Location index** — Redis sets of driver IDs per fine H3 cell plus a hash of each driver's last position, status and timestamp. Stale entries expire.
- **ETA (estimated time of arrival)** — road travel time, used for ranking instead of straight-line distance.
- **Offer loop** — offer the trip to the best driver, wait up to 10 s, then offer to the next.
- **Conditional update** — `UPDATE driver ... WHERE status='available'` . Only one concurrent assignment can succeed.
- **Trip state machine** — requested, matched, driver arriving, in progress, completed, plus cancellations. Illegal transitions are rejected.
- **Geo-sharding** — one dispatch leader per city region, elected with a lease, so traffic and failures stay local.
- **Greedy vs batched matching** — assign each request immediately, or collect requests for a second or two and solve an assignment problem.
- **Surge** — a per-cell price multiplier from supply and demand, damped so it changes smoothly.

Q: How do you store fast-changing driver locations?

A: In an in-memory index by H3 cell, fed by the location stream from Kafka, with TTLs so drivers who stop reporting disappear. It is not the source of truth: if Redis is lost, the next 4 seconds of updates rebuild it. Writing 5,000 updates/s into a transactional database would be wasteful for data that is stale in seconds.

Q: How do you prevent double assignment?

A: Assignment is `UPDATE driver SET status='on_trip', current_trip_id=? WHERE id=? AND status='available'` . If two dispatchers race for the same driver, only one update changes a row and the other sees zero rows and moves on. Offers also carry versions, so a late accept of an expired offer cannot win.

Q: A driver accepts just as the offer times out and the next driver gets it. What happens?

A: Both accepts are conditional updates on the trip and offer versions. Whichever commits first wins, and the other gets a clear "offer expired" response. The trip ends up with exactly one driver.

Q: Why rank by ETA instead of distance?

A: A driver 500 metres away across a river or on the wrong side of a motorway can be 10 minutes away by road. ETA from a routing engine reflects real travel time. I started with straight-line distance times a factor and then switched to a real routing engine.

Q: Greedy or batched matching?

A: Greedy gives each rider the nearest driver right away, which is fast but globally poor: a driver can be taken by a rider who had other good options, leaving the next rider with a long wait. Batching requests for a second or two and solving a small assignment problem lowers total wait time, at the cost of that short delay.

Q: A rider stands at the edge of a shard. Which drivers can they get?

A: Drivers just across the boundary belong to the neighbouring shard. The rider's shard reads the neighbour's location index (read-only) to find candidates, but the assignment itself stays with the rider's shard and uses the conditional update, so there is still only one writer per driver.

Q: A dispatch node dies. What happens?

A: Its region's lease expires and another node takes over within 30 s. In-flight trips are in PostgreSQL, so the new leader reloads requested and matching trips and resumes their offer loops. Riders see "finding your driver" a little longer instead of errors.

Q: What changes at 10x drivers?

A: Location ingest scales by adding Kafka partitions keyed by coarse cell. Dense cities need their regions split into more shards so one dispatcher is not overloaded. The ETA service becomes a hot dependency and needs caching and its own scaling.

Q: How do you test it?

A: The simulator is the harness: rush hour, a stadium emptying, a dispatcher crash. After each run, check invariants: no driver on two trips, and every request eventually matched or cancelled. Quality is measured as match latency and average pickup ETA.

Common mistakes in answers:

- Storing live locations in the primary database as the source of truth.
- Checking driver availability at search time only, instead of atomically at assignment time.
- Ranking by straight-line distance and ignoring the road network.

TL;DR

Stream locations into a cell-based index, keep trips in a transactional store, assign drivers with atomic conditional updates, and shard dispatch by geography.

35. News feed at scale

Level: Advanced · **Time:** 4–5 weeks · **Prerequisites:** M4, M12

What it is

A social feed backend: users post, follow others and load a home timeline of recent posts from people they follow. You implement **fan-out on write** (push each new post into every follower's precomputed feed), **fan-out on read** (assemble the feed at request time) and the **hybrid** that pushes for normal users and pulls for celebrities, then measure where each breaks.

The problem it solves

Reads outnumber writes many times over, and users expect feeds in milliseconds. Fan-out on write makes reads cheap but makes a post by someone with 50 million followers into 50 million writes. Fan-out on read makes posting cheap but every feed load merges hundreds of lists. The skew in follower counts means no single strategy works for everyone.

Real-world examples

- Raffi Krikorian's QCon talk Timelines at Scale describes Twitter's fan-out into in-memory timelines and special handling for accounts with huge follower counts.
- Facebook's TAO paper (USENIX ATC 2013) describes the graph-aware caching layer that serves social data at read-heavy scale.

Requirements


Functional

- Post text (images optional via Project 11). Follow and unfollow.
- Home timeline: most recent 50 posts from followees, cursor pagination.
- User timeline: a user's own posts.
- Deleted posts disappear from feeds. Muted users are filtered.

Non-functional


- Synthetic graph: 1 million users, follower counts power-law distributed with some accounts above 500,000 followers.
- 500 posts/s, 25,000 feed reads/s across the cluster.
- Feed read p99 under 100 ms. A new post visible to followers within 5 s p95.

The architecture



- **Post service**: writes the post to a store sharded by author ID and emits an event.
- **Fan-out workers**: look up followers in batches and push the post ID into each follower's timeline list (capped at about 800 entries). Skip authors above a follower threshold.
- **Timeline cache**: Redis lists of post IDs per user. Only active users get one.
- **Celebrity cache**: recent post IDs of celebrity authors, merged into feeds at read time.
- **Hydration**: turns post IDs into full posts from a post cache (multi-get).

Data model



Post IDs come from Project 2's generator, so they sort by time and merges are simple.

Tech stack

Component	Choice	Why
Services	Java 25 or Python 3.14	Your choice
Posts and graph	PostgreSQL sharded by user ID (Citus or app-level)	Familiar, shardable
Timelines and post cache	Redis Cluster	Lists and multi-get
Events	Kafka	Durable fan-out work queue
Load	A generator replaying a power-law graph	Skew is the whole point

Milestones

1. **Fan-out on read baseline.** Query followees, fetch recent posts per followee, merge. Done when you have p99 numbers at 25,000 reads/s (they will be bad).
2. **Fan-out on write.** Done when reads are fast and you measure the write amplification and lag for a 500,000-follower account (it will be bad).
3. **Hybrid.** Push for authors under a threshold, pull for celebrities at read time. Done when both read p99 and post-visibility lag meet targets.
4. **Active-user optimisation.** Only maintain timelines for users active in the last 30 days. Rebuild on login. Done when Redis memory falls substantially without hurting active users.
5. **Deletes, mutes and pagination.** Filter at hydration. Done when deleted posts vanish within seconds and cursors stay stable during new posts.

6. **Failure modes.** Lose a Redis shard, then rebuild affected timelines from the graph and posts on demand. Done when users see a slower first load, not an error.

Deep dive: the hard parts

- **Choosing the threshold.** Count the fan-out work per post vs. the extra merge work per read. The right threshold depends on the read/write ratio. Make it a config value and plot both costs.
- **Lag and ordering.** Fan-out is async, so followers see a post at slightly different times. Insert by post ID (time-sortable) rather than arrival, so late inserts still land in the right place.
- **Unfollows.** Removing a followee's posts from a precomputed timeline is expensive. Filter at read time against the current follow set for recent entries, and let the rest age out.
- **Hot posts.** One viral post is hydrated millions of times. Keep a small local cache in each API instance in front of Redis.

Testing strategy

- Correctness: compare hybrid feeds with a brute-force fan-out-on-read result for sampled users.
- Load tests with realistic skew, including a celebrity posting during peak reads.
- Chaos: lose a timeline shard, pause fan-out workers, verify degradation is graceful.

Trade-offs, scaling and failure modes

- Push costs storage and write work. Pull costs read latency. The hybrid costs code complexity. Name the cost of each choice aloud.
- If fan-out falls behind, feeds are stale, not broken. Serve stale feeds and prioritise fan-out for active users.
- Ranked feeds change the read path: candidate generation from the timeline, then a ranking model. Keep the candidate stage as built here.

Stretch goals

- Ranking with a simple engagement model and a candidate-then-rank pipeline.
- Real-time "new posts" banner via SSE (Project 8).

Skills practised

- M12 — Capstones: the news feed design.
- M4 — Caching: precomputed views, hot keys.
- M3 — Storing Data: sharding by user.
- M18 — Client and Mobile System Design: client-side feed pagination.

In the interview

30-second answer: I built a social feed backend on a synthetic 1-million-user power-law graph and measured three strategies: fan-out on read, fan-out on write into Redis timelines, and a hybrid. The key decision was the hybrid, pushing posts into followers' timelines for normal authors and pulling celebrity posts at read time, because pure push turns one celebrity post into 500,000 writes and pure pull makes every feed read merge hundreds of lists. I chose the follower threshold from measured costs, not a guess. The hardest parts were lag and ordering, solved by inserting time-sortable post IDs, and cache loss, solved by rebuilding timelines on demand. It serves 25,000 feed reads/s at p99 under 100 ms, with new posts visible within 5 s p95.

Key terms to know:

- **Fan-out on write (push)** — when someone posts, add the post ID to every follower's precomputed timeline. Cheap reads, expensive writes.
- **Fan-out on read (pull)** — build the feed at read time by merging recent posts from every followee. Cheap writes, expensive reads.

- **Hybrid fan-out** — push for most authors, pull for authors above a follower threshold, merge at read time.
- **Power-law distribution** — most users have few followers, and a few have millions. This skew is why no single strategy works.
- **Write amplification** — one post causing many writes, one per follower timeline.
- **Timeline cache** — a Redis list of post IDs per active user, capped at about 800 entries.
- **Hydration** — turning post IDs into full posts with a multi-get from a post cache, filtering deleted and muted content.
- **Time-sortable IDs** — Snowflake IDs from Project 2, so merging and late inserts order by time.
- **Active-user optimisation** — only maintain timelines for users active in the last 30 days, and rebuild on login.

Q: Push or pull?

A: Push makes reads a single list lookup but costs one write per follower per post. Pull makes posting a single write but makes every read merge many lists. With a skewed graph, push for typical users and pull for high-follower accounts, merged at read time. The threshold comes from plotting fan-out work per post against extra merge work per read.

Q: How do you handle a celebrity post?

A: Do not fan it out. The post goes into a "celebrity recent posts" cache, and when a follower loads their feed, the API merges posts from the celebrities they follow into their precomputed timeline. One post is one write instead of 500,000.

Q: Why cap timelines and only keep them for active users?

A: Most users rarely scroll beyond a few hundred posts, so storing more wastes memory. Many accounts are inactive, and maintaining their timelines is pure cost. Inactive users get their timeline rebuilt from the graph and posts when they log in.

Q: Fan-out is asynchronous. How do you keep order right?

A: Followers see a post at slightly different times, and fan-out jobs can complete out of order. Inserting by post ID, which sorts by creation time, rather than by arrival puts a late insert in the right place. Feed pagination uses an ID cursor, so new posts do not shift pages.

Q: How do you handle deletes and unfollows?

A: Removing a post from millions of precomputed timelines is expensive. Instead, filter at hydration: deleted posts and muted authors are dropped when IDs become posts. For unfollows, recent entries are filtered against the current follow set and older ones age out.

Q: What if a timeline cache shard is lost?

A: Affected users' timelines are rebuilt on demand from the follow graph and recent posts, effectively a one-time fan-out on read. They see a slower first load instead of an error. The cache is a derived view, never the source of truth.

Q: Fan-out workers fall behind during a peak. What do users see?

A: Feeds are stale, not broken: new posts appear late. Kafka holds the backlog durably. Prioritise fan-out for recently active users, and add workers.

Q: One post goes viral and is hydrated millions of times. What breaks?

A: Its key in the Redis post cache becomes hot and can overload one shard. A small local in-process cache in each API instance absorbs most of those reads before they reach Redis.

Q: How do you test it?

A: For sampled users, compare the hybrid feed with a brute-force fan-out-on-read result. Load tests use the realistic skew, including a celebrity posting during peak reads. Chaos tests drop a timeline shard and pause fan-out workers to check that degradation is graceful.

Common mistakes in answers:

- Picking pure push or pure pull for everyone and ignoring follower skew.

- Choosing the celebrity threshold by intuition instead of measured costs.
- Treating the timeline cache as the source of truth instead of a rebuildable view.

TL;DR

Push posts into timelines for ordinary authors, pull celebrity posts at read time, merge by time-sortable IDs, and treat the timeline cache as rebuildable from the posts and follow graph.

36. Stock exchange matching engine

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M3, M17

What it is

A simplified exchange: clients send limit and market orders over a gateway, a **sequencer** stamps every inbound message with a global sequence number and writes it to a journal, a single-threaded **matching engine** applies price-time priority against an in-memory **order book** (all resting buy and sell orders for a symbol, sorted by price then time), and market data and execution reports flow back out. Replicas replay the same journal to stay hot for failover.

The problem it solves

Exchanges need fairness (first come, first served at each price), determinism (the same inputs always give the same trades), very low and predictable latency, and zero tolerance for lost or duplicated orders. Traditional request-response with a database per order is far too slow and too nondeterministic. The answer is an event-sourced design: a single ordered input log and a deterministic in-memory state machine.

Real-world examples

- Martin Fowler's The LMAX Architecture describes a single-threaded business logic processor fed by an input journal, with replay for recovery, that processes millions of orders per second.
- The LMAX Disruptor is the open-source ring buffer they built for passing messages between threads with very low latency.

Requirements


Functional

- Order types: limit, market, cancel, and immediate-or-cancel.
- Price-time priority matching. Partial fills. Execution reports to both sides.
- Market data: top of book and depth (aggregated levels), trade prints.
- Per-account pre-trade risk check (enough balance or position).
- End-of-day: trades exported to a clearing ledger (Project 29).

Non-functional

- 100 symbols. 100,000 orders/s in the engine on one core.
- Engine latency (sequenced in to execution out) p99 under 100 µs. End-to-end on a laptop under 5 ms.
- Deterministic replay: replaying the journal reproduces identical trades and book state.
- Failover to a hot standby in under 5 s with no lost acknowledged orders.

The architecture



- **Order gateway**: sessions, authentication, message validation, per-client rate limits.

- **Pre-trade risk**: rejects orders that exceed balances or limits before they reach the book.
- **Sequencer**: assigns a strictly increasing sequence number and writes to the journal. Acknowledgement happens only after the journal is durable on a majority (use your Raft store or Kafka with `acks=all`).
- **Matching engine**: single thread per symbol group, consumes the journal in order, mutates order books, emits events.
- **Standby engine**: consumes the same journal and holds identical state, ready to take over.
- **Market data publisher**: builds book snapshots and incremental updates, sequenced so subscribers detect gaps.

Data model

Structure	Purpose
Price level: FIFO queue of orders	Time priority within a price
Bids: sorted map price → level (descending)	Best bid first
Asks: sorted map price → level (ascending)	Best ask first
Order index: `orderId -> (side, price, node)`	O(1) cancels
Journal record: `seq, type, payload, checksum`	The source of truth



Tech stack

Component	Choice	Why
Engine	Java 25 with primitive collections and no allocation on the hot path	Predictable latency
Journal	Kafka (`acks=all`) or your Project 27 log, or Aeron if you want low latency	Ordered, durable input
Gateway	Netty with a FIX-like or binary protocol	Many sessions
Market data	UDP multicast simulation or WebSockets	Fan-out
Prices	Integer ticks, never floats	Exact arithmetic

Milestones

1. **Order book.** Limit, market, cancel with price-time priority. Done when a large table of test scenarios (partial fills, sweeps across levels, cancels) passes.
2. **Throughput.** Done when one thread handles 100,000 orders/s with p99 under 100 µs (JMH plus a latency histogram).

3. **Sequencer and journal.** Done when killing the engine and replaying the journal from zero reproduces identical book state (compare hashes).
4. **Hot standby and failover.** Done when killing the primary promotes the standby within 5 s and clients resume without lost acknowledged orders.
5. **Market data with gap detection.** Done when a subscriber that drops a message detects the gap by sequence number and recovers from a snapshot.
6. **Risk and clearing.** Done when orders over limits are rejected pre-trade and end-of-day trades post balanced entries to the ledger.

Deep dive: the hard parts

- **Determinism.** The engine must not read clocks, random numbers or anything outside the journal. Timestamps come from the sequencer and are part of the input. Then replay is exact and standbys never diverge.
- **Why single-threaded?** Locks and context switches add unpredictable latency. One thread owning one book has no contention. Scale by partitioning symbols across threads or machines, not by sharing books.
- **Snapshots.** Replaying a full day's journal on recovery is slow. Snapshot the books periodically with the sequence number they reflect, and replay only from there.
- **Failover without double execution.** Only one engine may publish executions. Use a fenced leadership lease, and make downstream consumers dedupe by sequence number in case of overlap during switchover.

Testing strategy

- Scenario tests for matching rules, plus property tests (book never crossed: best bid below best ask after matching).
- Replay determinism test on large random journals.
- Latency histograms under load. Watch for garbage-collection pauses.
- Failover drills during heavy load.

Trade-offs, scaling and failure modes

- In-memory plus journal is very fast but needs careful snapshotting and failover. The journal's replication latency bounds acknowledgement latency.
- Fairness in the gateway layer matters too: randomised or strict FIFO across gateways changes who wins at a price.
- A bug in matching is replayed faithfully. Kill switches and per-symbol trading halts are part of the design.

Stretch goals

- Auctions (opening and closing cross).
- Self-trade prevention.
- Co-located latency measurement with timestamps at each hop.

Skills practised

- M17 — Case Studies: Money and Reservations: stock exchange order book, sequencer, matching engine.
- M3 — Storing Data: event sourcing and WAL.
- M5 — Reliability: failover and fencing.

In the interview

30-second answer: I built a simplified stock exchange: a sequencer stamps every inbound order with a global sequence number and writes it to a replicated journal, and a single-threaded matching engine applies price-time priority against in-memory order books. The key decision was making the engine a deterministic state machine over the journal, reading no clocks or random numbers, so replaying the journal reproduces identical trades and a hot standby stays in lockstep. The hardest

part was failover without double execution, which needs a fenced leadership lease plus downstream dedup by sequence number. One core handles 100,000 orders/s with engine p99 under 100 µs, and a standby takes over in under 5 s with no lost acknowledged orders.

Key terms to know:

- **Order book** — all resting buy (bid) and sell (ask) orders for a symbol, sorted by price, then by time within a price.
- **Price-time priority** — the best price trades first, and among equal prices the earliest order trades first.
- **Limit / market / IOC order** — trade at this price or better and rest if unfilled / trade now at any price / fill what you can now and cancel the rest.
- **Partial fill** — an order matched against less than its full quantity, with the remainder resting or cancelled.
- **Sequencer** — assigns a strictly increasing number to every input and writes it to the journal, defining one total order.
- **Journal** — the durable, replicated input log and the source of truth. Orders are acknowledged only once it is durable on a majority.
- **Deterministic state machine** — the same inputs in the same order always give the same outputs. The basis for replay and standbys.
- **Hot standby** — a second engine consuming the same journal with identical state, ready to take over.
- **Snapshot** — book state saved with the sequence number it reflects, so recovery replays only from there.
- **Integer ticks** — prices stored as integers in the minimum price increment, never as floats.

Q: Why a sequencer?

A: It defines one total order for all inputs, so "first come, first served" is objective: whichever order has the lower sequence number arrived first. Every replica that applies the journal in that order reaches the same state. Fairness and replication both come from that one decision.

Q: Why not a database transaction per order?

A: A database round-trip per order costs milliseconds, and concurrent transactions can interleave nondeterministically. A deterministic in-memory engine fed by a durable journal processes each order in microseconds and can be replayed exactly. Durability comes from the journal, not from the engine's memory.

Q: Why single-threaded?

A: Locks and context switches add unpredictable latency, which hurts the p99 target. One thread owning a book never contends with anything. To scale, partition symbols across threads or machines, since books for different symbols are independent.

Q: What must the engine never do, and why?

A: Read the system clock, generate random numbers, or depend on anything outside the journal. Any of those would make the primary and standby, or a replay, produce different results. Timestamps are assigned by the sequencer and are part of the input.

Q: How do you recover from a crash?

A: Load the latest book snapshot and replay the journal from the sequence number it reflects. Because the engine is deterministic, the result is identical to the state before the crash. In practice you fail over to the hot standby, which already holds that state.

Q: During failover, how do you avoid executing an order twice?

A: Only one engine may publish executions, enforced with a fenced leadership lease so a paused old primary cannot keep publishing. Executions carry the input sequence number, so downstream consumers drop duplicates if both engines publish briefly during the switch.

Q: A market data subscriber misses a message. What happens?

A: Market data updates are sequenced, so the subscriber sees a jump in sequence numbers and knows it has a gap. It requests a fresh book snapshot and applies updates after it. Without sequence numbers, it would silently show a wrong book.

Q: What changes at 10x the order rate?

A: Partition symbols into groups, each with its own sequencer, journal and engine thread, since matching for one symbol never needs another's book. A single very hot symbol is still limited to one thread, so the hot path must allocate nothing and avoid garbage-collection pauses.

Q: How do you test it?

A: Scenario tables cover partial fills, sweeps across price levels and cancels. A property test checks the book is never crossed after matching: best bid below best ask. A replay test runs large random journals twice and compares book hashes, and failover drills run under heavy load.

Q: Hands-on: what data structures give O(1) cancel?

A: Each price level is a FIFO doubly linked list of orders, and a hash map `orderId -> node` points directly at each order. A cancel looks up the node and unlinks it in O(1). Bids and asks are sorted maps keyed by price, so finding the best price is fast.

Common mistakes in answers:

- Using floating-point prices, which cause rounding errors in matching and settlement.
- Adding threads and locks to one book for speed, which adds latency jitter and breaks determinism.
- Letting the engine read the wall clock, which makes replay and standbys diverge.

TL;DR

Sequence every input into a durable journal, match on a single deterministic thread with price-time priority, and recover or fail over by replay.

37. Distributed tracing pipeline

Level: Advanced · **Time:** 3–5 weeks · **Prerequisites:** M9, M10

What it is

An end-to-end tracing system: services are instrumented with OpenTelemetry so each request carries a **trace ID** and each operation records a **span** (name, start, duration, parent span, attributes). Spans flow through collectors that apply **tail-based sampling** (decide whether to keep a trace after seeing all of it, so errors and slow traces are kept), into Kafka, then into a storage tier with a query API and a trace view UI.

The problem it solves

In a system of dozens of services, "the checkout is slow" could be any hop. Logs per service do not connect. Tracing stitches one request's path across services and shows where time went. Tracing everything is expensive, so sampling decides what to keep, and keeping only random traces misses the rare errors you care about most.

Real-world examples

- Google's Dapper paper describes low-overhead, always-on tracing with sampling, and the trace and span model that later systems copied.
- The OpenTelemetry documentation and its Collector cover context propagation, SDKs and the processing pipeline, including tail sampling.
- Jaeger is an open-source tracing backend you can use as a reference UI and storage.

Requirements


Functional

- Instrument 5 demo services (HTTP and Kafka hops) with W3C Trace Context propagation (the standard `traceparent` header).
- Collectors receive OTLP (the OpenTelemetry protocol), batch, apply tail sampling: keep all error traces, all traces over 1 s, and 5% of the rest.
- Store spans. Query by trace ID, by service plus operation plus duration range, by attribute.
- Trace view: waterfall of spans. Service dependency graph from aggregated spans.

Non-functional

- 50,000 spans/s ingest.
- Trace available for query within 30 s of the request ending.
- Instrumentation overhead under 5% CPU in services.
- 7-day retention with storage cost measured per million spans.

The architecture



- **Agent collectors**: run near services, batch spans and forward them. They route by trace ID (consistent hashing) so all spans of one trace reach the same tail-sampling collector.
- **Tail sampling collectors**: buffer spans per trace for a decision window (say 10 s after the last span), then keep or drop the whole trace.
- **Kafka**: buffers kept spans for indexing and other consumers.
- **Indexer and span store**: writes spans keyed by trace ID plus secondary indexes for service, operation, duration and tags.
- **Dependency graph job**: aggregates parent-child service pairs per minute.

Data model

SPAN		
text	trace_id	PK
text	span_id	PK
text	parent_span_id	
text	service	
text	operation	
timestamptz	start_time	
bigint	duration_us	
int	status_code	
jsonb	attributes	

SERVICE_EDGE		
text	parent_service	PK
text	child_service	PK
timestamptz	minute	PK
bigint	calls	
bigint	errors	

Tech stack

Component	Choice	Why
Instrumentation	OpenTelemetry Java agent or Python SDK	Standard, vendor-neutral
Collectors	OpenTelemetry Collector, then write your own tail sampler	Compare with the reference
Buffer	Kafka	Smooth bursts, replay
Store	ClickHouse	Columnar, fast filters and aggregations
UI	Jaeger UI against your query API, or a React 19 waterfall	Visual debugging

Milestones

1. **Instrument the demo services.** Done when one request produces a connected trace across HTTP and Kafka hops in Jaeger.
2. **Collector pipeline to Kafka and storage.** Done when traces are queryable by ID from your store.
3. **Search.** Done when "service=checkout, duration > 500 ms, last hour" returns in under 1 s on 100 million spans.
4. **Tail sampling.** Your own sampler with trace-ID routing. Done when 100% of error traces and slow traces survive and total volume drops to around 10%.
5. **Dependency graph and RED metrics.** Rate, errors and duration per service from spans. Done when the graph matches the real topology.
6. **Overhead and cost.** Done when you have measured service CPU overhead and storage bytes per span, and have one optimisation for each.

Deep dive: the hard parts

- **Context propagation through async hops.** HTTP headers carry `traceparent` automatically, but Kafka messages, thread pools and scheduled jobs need it injected and extracted explicitly. Broken propagation produces orphaned traces.
- **Tail sampling needs all spans in one place.** Spans of one trace come from many services and collectors. Route by trace ID consistently, and accept that collector scaling events reshuffle routing and may split a few traces.
- **Late spans and clock skew.** Spans from different hosts carry different clocks, so a child can appear to start before its parent. UIs adjust by parent-child relationships. Spans arriving after the sampling decision must follow the stored decision for that trace (keep a short-lived decision cache).
- **Cardinality in attributes.** Indexing every attribute explodes storage. Index a chosen few and store the rest as unindexed blobs.

Testing strategy

- Propagation tests per hop type.
- Sampling tests: inject known error and slow traces, assert they are all kept.
- Load test ingest and query with synthetic span generators.

Trade-offs, scaling and failure modes

- Head sampling (decide at the start) is cheap and simple but misses rare errors. Tail sampling catches them but needs buffering and stateful routing.
- If the tracing pipeline is overloaded it must drop data, never slow down the services. Instrumentation uses bounded queues that drop on overflow.
- Traces, metrics and logs answer different questions. Link them with trace IDs in logs and exemplars in metrics.

Stretch goals

- Exemplars: link metric spikes in Project 20 to example traces.
- Critical-path analysis that highlights which spans actually determined end-to-end latency.

Skills practised

- M9 — Operating in Production: distributed tracing, health and observability.
- M10 — Batch and Streaming: partitioned consumption, backpressure.
- M8 — API and Edge: sidecars and gateways as instrumentation points.

In the interview

30-second answer: I built a distributed tracing pipeline: five services instrumented with OpenTelemetry propagate W3C trace context over HTTP and Kafka, collectors route spans by trace ID to tail-sampling collectors, and kept traces flow through Kafka into ClickHouse with a query API and waterfall UI. The key decision was tail sampling instead of head sampling, because deciding after seeing the whole trace lets me keep every error and every trace over 1 s while dropping total volume to about 10%. The hardest part was that tail sampling needs all spans of a trace on one collector, so agents route by consistent hashing of the trace ID. It ingests 50,000 spans/s, makes traces queryable within 30 s, and costs services under 5% CPU.

Key terms to know:

- **Trace** — the full path of one request across services, identified by a trace ID.
- **Span** — one operation within a trace: name, start, duration, parent span ID and attributes.
- **Context propagation** — passing trace ID and parent span ID along with each call, using the W3C `traceparent` header.
- **OpenTelemetry / OTLP** — the vendor-neutral standard for instrumentation, and its wire protocol.
- **Head sampling** — decide at the start of a request whether to keep it. Cheap and stateless, but blind to how the request ends.
- **Tail sampling** — buffer all spans of a trace and decide after it finishes. Keeps errors and slow traces.
- **Trace-ID routing** — consistent hashing on trace ID so every span of a trace reaches the same sampling collector.
- **Decision cache** — remembers keep or drop per trace for a while, so late spans follow the same decision.
- **RED metrics** — rate, errors and duration per service, derived from spans.
- **Bounded queue with drop** — the SDK's buffer drops spans when full, so tracing never slows the service.

Q: Head or tail sampling?

A: Head sampling decides at the first span with a random coin, so it is cheap and stateless, but at 5% it keeps only 5% of the rare errors you most want to see. Tail sampling waits until the trace is complete and keeps all errors and slow traces plus a sample of the rest. The cost is buffering spans for a decision window and routing all spans of a trace to one place.

Q: Why must spans be routed by trace ID?

A: Spans of one trace come from many services through many agent collectors. To decide on the whole trace, one collector must see all of them. Agents hash the trace ID to pick the tail-sampling collector, so every span of a trace lands in the same place.

Q: How do traces cross a Kafka hop?

A: HTTP instrumentation propagates `traceparent` automatically, but a message queue does not. The producer injects the trace context into the message headers, and the consumer extracts it and starts a span linked to the producer's span. Thread pools and scheduled jobs need the same explicit handling, or traces break into orphans.

Q: A span arrives after the sampling decision was made. What happens?

A: The collector keeps a short-lived decision cache by trace ID. If the trace was kept, the late span is kept too. If it was dropped, the late span is dropped. Without the cache, you would get partial traces.

Q: A child span appears to start before its parent. Is that a bug?

A: Usually it is clock skew: spans from different hosts use different clocks. The UI uses parent-child relationships to lay spans out sensibly. You cannot trust absolute timestamps across hosts to the millisecond.

Q: What if the tracing backend is down?

A: Services must not notice. The SDK sends through bounded in-memory queues that drop spans when full, and exports happen off the request path. Losing some traces is acceptable, while slowing production is not.

Q: What happens when you scale the tail-sampling collectors up or down?

A: The consistent hash ring changes, so some trace IDs move to a different collector mid-trace. Those few traces get split and may be sampled inconsistently. Consistent hashing keeps the number of moved traces small, and you accept the loss during scaling events.

Q: What changes at 10x span volume?

A: Add agent and sampling collectors, Kafka partitions and ClickHouse shards. Storage cost grows fastest, so index only a few chosen attributes and store the rest as unindexed blobs, and tune sampling rates for healthy traffic. Measure bytes per span and cost per million spans.

Q: How do you test it?

A: Propagation tests for each hop type (HTTP, Kafka, thread pool). Sampling tests inject known error and slow traces and assert every one survives. Synthetic span generators load-test ingest and queries, and service CPU overhead is measured with and without instrumentation.

Common mistakes in answers:

- Choosing head sampling and expecting to find rare errors.
- Assuming context propagates through queues and thread pools automatically.
- Letting tracing exports block requests, so an observability outage becomes a production outage.

TL;DR

Propagate context everywhere, route spans by trace ID, sample at the tail to keep what matters, store in a columnar store, and never let tracing hurt the traced.

38. Zanzibar-style authorization service

Level: Advanced · **Time:** 4–6 weeks · **Prerequisites:** M4, M8

What it is

A central permissions service based on Google's Zanzibar model: permissions are stored as **relation tuples** like `doc:readme#viewer@user:ana` or `doc:readme#viewer@group:eng#member`, a schema defines how relations combine (an editor is also a viewer, a folder's viewers can view its documents), and a `Check(object, permission, user)` API answers in milliseconds by walking the relationship graph. You add consistency tokens so a check never ignores a permission change the user just made.

The problem it solves

Every app eventually needs sharing: documents shared with people, groups nested in groups, folders granting access to everything inside. Hard-coding this per service leads to inconsistent rules and slow, duplicated queries. Role-based access control (RBAC: users get roles, roles get permissions) does not express "Ana can view this one document". Relationship-based access control (ReBAC) does, and centralising it gives one consistent answer everywhere.

Real-world examples

- Pang et al., Zanzibar: Google's Consistent, Global Authorization System (USENIX ATC 2019), describes tuples, namespace configs with userset rewrites, zookies (consistency tokens) and the Leopard index for nested groups.
- OpenFGA and SpiceDB are open-source Zanzibar-inspired systems you can compare against.

Requirements


Functional

- Schema language: types, relations, permissions with union, intersection, exclusion and arrow (`parent->viewer`).
- `Write` tuples (with preconditions), `Delete` tuples. Returns a consistency token.
- `Check`, `Expand` (show why), `LookupResources` ("which docs can Ana view?").
- Consistency modes: fully consistent, at-least-as-fresh-as a token, or minimise latency.

Non-functional

- 10 million tuples, group nesting up to 10 levels.
- Check p95 under 10 ms with warm caches, 20,000 checks/s across 3 instances.
- No "new enemy" problem: after removing someone's access and then adding sensitive content, that person must not see the new content.

The architecture



- **Schema compiler**: parses the schema into a rewrite tree per permission.
- **Check evaluator**: recursively evaluates the rewrite tree: direct tuples, computed relations, tuple-to-userset (arrows), unions in parallel, with request deduplication and depth limits.
- **Tuple store**: tuples with the revision (transaction ID or snapshot) at which they were written and deleted, so evaluation can run at a specific revision.
- **Check cache**: results keyed by `(object, permission, subject, revision bucket)`.
- **Group membership index**: a precomputed flattening of deep group nesting (a small version of Zanzibar's Leopard) updated from the watch stream.

Data model



Tech stack

Component	Choice	Why
Service	Java 25 (virtual threads for parallel subchecks) or Python 3.14	Recursive concurrent evaluation
Store	PostgreSQL with MVCC-style revision columns	Snapshot reads at a revision
Cache	In-process plus Redis	Hot checks
API	gRPC	Low overhead, streaming for watch
Comparison	OpenFGA or SpiceDB with the same schema	Validate semantics

Milestones

1. **Tuples and direct checks.** Done when `doc#viewer@user` checks work.
2. **Schema with computed relations and arrows.** `viewer = direct viewer + editor + parent->viewer`. Done when folder inheritance and group membership resolve correctly.
3. **Revisions and consistency tokens.** Writes return a token (the revision). Checks with a token evaluate at or after that revision. Done when a test reproduces the new enemy problem without tokens and passes with them.
4. **Performance.** Parallel union branches, dedup of identical subproblems within a request, caching by revision bucket. Done when p95 meets 10 ms on the 10 million tuple dataset.
5. **Nested groups index.** Done when deep group nesting checks become one index lookup, kept up to date from the change stream.
6. **LookupResources and Expand.** Done when "list docs Ana can view" returns correct results and Expand shows the path that granted access.

Deep dive: the hard parts

- **The new enemy problem.** Ana is removed from a folder, then a secret doc is added to it. If a check for Ana on the new doc runs against a stale replica or cache that still has her membership, she sees it. Zanzibar's fix: the content write stores a token from after the ACL change, and checks on that content must be evaluated at least that fresh.
- **Caching with correctness.** Cache entries keyed by a revision bucket (for example revisions rounded to 5 seconds) let many requests share results while staying bounded in staleness. Requests with a

newer token skip older buckets.

- **Recursion limits and cycles.** Group A contains B contains A. Track visited nodes and enforce a maximum depth, returning an error rather than looping.
- **Reverse lookups are hard.** Check is a graph walk from one object. "Which objects can Ana see?" is the reverse and can be huge. Paginate, and for very large results precompute indexes or push filtering into the data store.

Testing strategy

- Semantic tests against OpenFGA or SpiceDB: same schema and tuples, same answers for random checks.
- Consistency tests for new enemy scenarios with lagging replicas.
- Load tests with skewed objects (a doc shared with everyone) and deep groups.

Trade-offs, scaling and failure modes

- Central authorization is a critical dependency. Callers need timeouts and a decision on fail-closed (deny) which is the safe default for authorization.
- Fully consistent checks cost latency. Most checks can use the minimise-latency mode, and only content-sensitive flows need tokens.
- Policy engines (attribute-based rules over request data) complement ReBAC for conditions like time of day or IP range.

Stretch goals

- Caveats: conditional tuples (access only from a corporate network).
- Multi-region read replicas with token-aware routing.

Skills practised

- M8 — API and Edge: authorization service, RBAC, ABAC, ReBAC and Zanzibar tuples.
- M4 — Caching: revision-keyed caching.
- M7 — Consistency: snapshot reads and bounded staleness.

In the interview

30-second answer: I built a Zanzibar-style authorization service: permissions are stored as relation tuples like `doc:readme#viewer@group:eng#member`, a schema defines how relations combine (editors are viewers, a folder's viewers can view its documents), and `Check` answers by walking that graph at a known revision. The key decision was relationship-based access control, because roles cannot express "Ana can view this one document" or inheritance through folders and nested groups. The hardest part was the "new enemy" problem, which I solved with consistency tokens so a check is never evaluated against data older than a recent permission change. With parallel evaluation, revision-bucketed caching and a flattened group index, checks run under 10 ms p95 on 10 million tuples.

Key terms to know:

- **RBAC** — role-based access control: users get roles, and roles get permissions.
- **ReBAC** — relationship-based access control: access follows relationships between objects and users, like owner, member or parent.
- **Relation tuple** — `object#relation@subject`, for example `doc:readme#viewer@user:ana`. The only data stored.
- **Userset** — a subject that is itself a set, such as `group:eng#member`.
- **Schema rewrite** — rules like `viewer = direct viewer + editor + parent->viewer`, including union, intersection and exclusion.
- **Arrow (tuple-to-userset)** — `parent->viewer`: follow the parent relation, then check viewer on the parent.

- **Revision** — the database position at which tuples were written or deleted, so checks can run at a consistent snapshot.
- **Consistency token (zookie)** — a revision returned by a write. Later checks must be at least that fresh.
- **New enemy problem** — a stale check grants access to content added after the user's access was removed.
- **Group membership index** — a precomputed flattening of nested groups (a small version of Zanzibar's Leopard).

Q: Why ReBAC over RBAC?

A: RBAC answers "can editors edit documents?" but not "can Ana view this specific document because it sits in a folder shared with a group she is in?". ReBAC models per-object sharing, folder inheritance and nested groups in one graph. A central service then gives every application the same answer.

Q: What is the new enemy problem?

A: Ana is removed from a folder, then a secret document is added to it. If the check for Ana on the new document reads a stale replica or cache that still has her membership, she sees the secret. The fix: the content write stores a token from after the permission change, and checks on that content must be evaluated at that revision or later.

Q: How does a check work?

A: The schema compiles each permission into a rewrite tree. The evaluator looks for a direct tuple, then follows computed relations (editors are viewers) and arrows (the parent folder's viewers), recursing through groups. Union branches run in parallel, and the first "yes" short-circuits the rest.

Q: How do you make checks fast?

A: Run branches in parallel, deduplicate identical subproblems within a request, and cache results keyed by `(object, permission, subject, revision bucket)` so many requests share them. Deep group nesting is precomputed into a flattened membership index, kept fresh from the tuple change stream, so a 10-level chain becomes one lookup.

Q: Why bucket revisions in the cache key?

A: Exact revisions change with every write, so a cache keyed by exact revision would almost never hit. Rounding to, say, 5-second buckets lets many requests share entries with bounded staleness. A request carrying a newer token skips older buckets.

Q: Group A contains group B, which contains group A. What happens?

A: A naive recursive walk loops forever. The evaluator tracks visited nodes per request and enforces a maximum depth, returning an error rather than looping or guessing.

Q: Why is "which documents can Ana see?" harder than Check?

A: Check walks from one object toward one user. The reverse lookup must find every object reachable from Ana, which can be millions of results. Paginate it, and for large result sets use precomputed indexes or push the filter into the application's own data query.

Q: The authorization service is down. What should callers do?

A: Fail closed, meaning deny, because wrongly granting access is worse than a temporary outage for authorization. Callers set short timeouts so they do not hang. That makes this service a critical dependency, so run it with replicas, caches and its own strict SLOs.

Q: What changes at 10x checks?

A: Checks are read-heavy, so add stateless evaluator instances, read replicas and cache capacity. Most checks can use the minimise-latency mode served from replicas and caches, and only content-sensitive flows pay for token freshness. Very popular objects, like a doc shared with everyone, need hot-key caching.

Q: How do you test it?

A: Load the same schema and tuples into OpenFGA or SpiceDB and compare answers for random checks. Consistency tests reproduce the new enemy problem with lagging replicas, first failing without tokens and then passing with them. Load tests use skewed objects and deep groups.

Common mistakes in answers:

- Caching check results without revisions, which reintroduces the new enemy problem.
- Failing open when the authorization service is unavailable.
- Ignoring cycles and depth limits in nested groups.

TL;DR

Store relationships as tuples, define permissions as rewrites over them, evaluate checks as graph walks at a known revision, and use tokens so permission changes are never outrun.

39. Cell-based multi-tenant platform

Level: Advanced · **Time:** 5–8 weeks · **Prerequisites:** M6, M9

What it is

A multi-tenant SaaS backend (a simple project-tracking API) deployed as several identical **cells**: each cell is a complete, independent copy of the stack (services, database, cache, queue) serving a subset of tenants. A thin **cell router** maps each tenant to its cell. You add **shuffle sharding** for shared components, **static stability** (keep working without the control plane), cell-by-cell deployments with automated rollback, and tenant migration between cells.

The problem it solves

In a single shared deployment, one bad deploy, one runaway tenant or one corrupt database affects every customer. Cells cap the **blast radius**: a failure hits only the tenants in one cell. They also give a unit of scaling (add cells instead of growing one giant system) and a unit of deployment (roll out to one cell, watch, continue). The price is a routing layer, duplicated infrastructure and tooling to move tenants.

Real-world examples

- AWS's whitepaper Reducing the scope of impact with cell-based architecture covers cell sizing, the routing layer, partition keys and migration.
- The Amazon Builders' Library articles on shuffle sharding and static stability explain the two complementary techniques.
- Slack's Slack's migration to a cellular architecture describes reorganising services so traffic can be drained from an availability zone.

Requirements


Functional

- Tenants sign up and are placed in a cell. All of a tenant's requests route to its cell.
- Admin: create a cell, drain a cell, migrate a tenant between cells with brief read-only time.
- Deployments roll out cell by cell with health gates and automatic rollback.

Non-functional


- 4 cells locally (namespaces in one kind cluster, or several clusters).
- Router adds under 2 ms p99. Router keeps routing for 24 hours with the control plane down.
- A poison deploy or a noisy tenant affects at most one cell.
- Tenant migration with under 60 s of read-only time.

The architecture



- **Cell router**: stateless proxies holding the full tenant-to-cell map in memory, refreshed by version. If the control plane is gone, they keep the last map (static stability).
- **Cells**: identical Kubernetes namespaces with their own PostgreSQL, Redis and queue. No calls between cells.
- **Control plane**: tenant placement, cell inventory, map publishing. Not on the request path.
- **Deployment orchestrator**: canary cell first, bake time, health checks (error rate, latency), then waves. Rolls back automatically on regressions.
- **Tenant migrator**: copies a tenant's data to the target cell, catches up via CDC, flips the map entry, then deletes the source.

Data model



Tech stack

Component	Choice	Why
Cells	Kubernetes namespaces (kind or k3d), Helm chart per cell	Identical, reproducible stacks
Router	Envoy with a small control plane, or your Project 17 gateway	Header or subdomain routing
Data	PostgreSQL per cell, Debezium for migration catch-up	Isolation and online moves
Deploys	Argo Rollouts or your own orchestrator	Progressive delivery with analysis
Chaos	Scripts that kill a cell's DB, deploy a broken image, flood from one tenant	Prove containment

Milestones

1. **One cell.** The project-tracking API with its datastore, deployed by Helm. Done when it passes its own test suite.
2. **Four cells and a router.** Done when tenants are spread across cells and every request lands in the right cell.
3. **Static stability.** Done when the control plane is stopped for an hour and routing continues normally from cached maps, while new sign-ups queue.
4. **Progressive deployments.** Done when a deliberately broken build is stopped at the first cell and rolled back automatically, with other cells untouched.
5. **Noisy neighbour containment.** Per-tenant rate limits plus cell isolation. Done when one tenant's load test degrades only its own cell, and only partially.
6. **Tenant migration.** Bulk copy, CDC catch-up, short read-only freeze, map flip. Done when a tenant moves with under 60 s read-only and no lost writes.

Deep dive: the hard parts

- **Choosing the partition key.** Tenant ID works when tenants do not interact. Cross-tenant features (shared channels, marketplaces) break isolation and need a separate, carefully designed global service.
- **The router is the new single point.** Keep it very simple, horizontally scaled, with no dependencies on the request path. Its map must be small enough to hold in memory and versioned so a bad map can be rolled back.
- **Shuffle sharding for shared parts.** Some components (for example a shared search cluster) are not cellular. Give each tenant a random subset of k of n nodes. Two tenants then rarely share all their nodes, so one bad tenant takes out only a tiny fraction of others' capacity.
- **Cell sizing.** Small cells mean small blast radius but more overhead and more tenants to move. Large tenants may outgrow a cell and need a dedicated one.

Testing strategy

- Game days: poison deploy, database loss in one cell, control plane outage, router instance loss. Measure the share of tenants affected each time.
- Migration correctness: checksums of tenant data before and after, writes during migration verified.
- Load tests per cell and through the router.

Trade-offs, scaling and failure modes

- Cells multiply infrastructure cost and the number of things to monitor. Automation is not optional.
- Global features (billing, login, tenant directory) still exist. Keep them small, highly available and off the hot path where possible.
- Cells contain failures from bad code and bad data, but not a bug that is deployed to every cell at once. Hence progressive, cell-by-cell rollout.

Stretch goals

- Cells in two regions with tenant home regions and DR failover (connects to Project 29).
- Automatic cell rebalancing based on capacity units.

Skills practised

- M6 — Scaling: multi-region and cell-based architecture, shuffle sharding, static stability.
- M9 — Operating in Production: Kubernetes, CI/CD, canary and blue-green.
- M8 — API and Edge: the routing layer.
- M10 — Batch and Streaming: CDC for migrations.

In the interview

30-second answer: I deployed a multi-tenant project-tracking API as four identical cells, each a complete stack with its own database, cache and queue, behind a thin router that maps each tenant to its cell. The key decision was cells for blast-radius control: a bad deploy, a noisy tenant or a corrupt database affects one cell's tenants instead of everyone. The hardest parts were keeping the router statically stable, so it routes from its cached map for 24 hours without the control plane, and moving tenants between cells online with bulk copy, CDC catch-up and under 60 s of read-only time. A deliberately broken build was stopped at the first cell and rolled back automatically, and the router adds under 2 ms p99.

Key terms to know:

- **Cell** — a full, independent copy of the stack serving a subset of tenants. Cells never call each other.
- **Blast radius** — how many customers one failure affects. Cells cap it at one cell.
- **Cell router** — a stateless proxy holding the whole tenant-to-cell map in memory, versioned so bad maps can be rolled back.
- **Partition key** — the field used to place work in cells, here tenant ID.
- **Control plane vs data plane** — management (placement, map publishing, deploys) versus serving requests.
- **Static stability** — the data plane keeps working with its last known configuration when the control plane is down.
- **Shuffle sharding** — each tenant gets a random subset of k of n shared nodes, so two tenants rarely share all of them.
- **Progressive (wave) deployment** — deploy to a canary cell, wait, check health, then continue in waves, with automatic rollback.
- **Noisy neighbour** — a tenant whose load hurts others on the same infrastructure.
- **Tenant migration** — bulk copy, CDC catch-up, short write freeze, map flip, then cleanup.

Q: What is a cell and why use one?

A: A cell is a complete copy of the stack (services, database, cache, queue) serving only some tenants. A failure from bad code, bad data or a runaway tenant hits only that cell's tenants. Cells are also the unit of scaling (add cells instead of growing one giant system) and of deployment.

Q: What is static stability?

A: The data plane keeps working with its last known configuration when the control plane is unavailable. Routers hold the full map in memory and keep using it, so existing tenants are unaffected while only new sign-ups queue. The control plane is never on the request path.

Q: The router is in front of every cell. Isn't it a new single point of failure?

A: Yes, which is why it must be extremely simple: stateless, horizontally scaled, no calls to other services per request, and a small in-memory map. Map changes are versioned so a bad one can be rolled back instantly. Its simplicity is what makes it safer than the rich services behind it.

Q: How does shuffle sharding help shared components?

A: Some parts, like a shared search cluster, are not cellular. Give each tenant a random subset of, say, 2 of 8 nodes. If one tenant's traffic breaks its 2 nodes, any other tenant shares both nodes with it only rarely (1 in 28 combinations here), so almost everyone keeps at least one healthy node.

Q: Cells isolate failures. Why do you still need progressive deployment?

A: Cells contain bad code only if the bad code is not deployed everywhere at once. Deploying to one canary cell first, baking, and checking error rate and latency turns every release into a one-cell experiment. A regression is rolled back before it reaches the other cells.

Q: How do you move a tenant between cells?

A: Bulk-copy the tenant's data to the target cell, then stream ongoing changes with CDC until the copy is caught up. Freeze the tenant's writes briefly, apply the last changes, flip its routing map entry, and resume. Verify with checksums before deleting the source. Read-only time stays under 60 s.

Q: How do you choose the partition key?

A: Tenant ID works when tenants do not interact. Features that cross tenants, like shared channels or marketplaces, break isolation and need a separate global service designed carefully. Global services such as login and billing should be small, highly available and off the hot path.

Q: How big should a cell be?

A: Small cells give a small blast radius but more overhead per tenant and more migrations. Large cells are cheaper but each failure hurts more. A very large tenant may outgrow any shared cell and need a dedicated one. Size cells in capacity units and test them at their maximum.

Q: What changes at 10x tenants?

A: Add cells, which is the whole point, rather than growing existing ones. The routing map grows but stays small enough for memory. Cost and the number of things to monitor multiply, so cell creation, deploys and rebalancing must be fully automated.

Q: How do you prove containment?

A: Game days: deploy a poison build, delete one cell's database, stop the control plane, kill router instances, and flood from one tenant. For each, measure the share of tenants affected. Migration tests compare checksums before and after and verify writes during migration were not lost.

Common mistakes in answers:

- Putting the control plane on the request path, so its outage takes every cell down.
- Deploying to all cells at once, which defeats isolation for bad code.
- Allowing cells to call each other, which turns separate failures back into shared ones.

TL;DR

Cells cap blast radius, a simple statically stable router keeps them reachable, progressive rollout turns deploys into one-cell experiments, and migration tooling keeps cells balanced.

40. AI copilot platform

Level: Advanced · **Time:** 6–8 weeks · **Prerequisites:** M11, M12

What it is

A multi-tenant AI assistant platform that combines everything in Modules 10–11: a self-hosted model served on GPUs with **continuous batching** (adding new requests into a running batch instead of waiting for the batch to finish), autoscaling on GPU-relevant signals, an LLM gateway (Project 24), per-tenant RAG over a **sharded vector index**, an agent loop that calls tools with guardrails, conversation memory, streaming responses, and evaluation plus cost tracking. It goes deeper than Module 12's AI copilot design by making you run the serving and retrieval layers yourself.

The problem it solves

A demo chatbot is a prompt and an API call. A platform serving many tenants must keep each tenant's data separate, answer from their documents, call their tools safely, stream answers within a second, survive provider outages, keep GPU spend under control, and prove quality does not regress. These concerns pull against each other: batching improves GPU throughput but adds queueing delay, and more retrieval improves answers but costs latency and tokens.

Real-world examples

- Kwon et al., Efficient Memory Management for Large Language Model Serving with PagedAttention, introduces the KV-cache paging used by vLLM to raise serving throughput. The vLLM documentation covers continuous batching and deployment.
- KServe is a Kubernetes model-serving platform with autoscaling and inference graph features.
- Anthropic's Contextual Retrieval post describes retrieval improvements directly applicable to the RAG layer.

Requirements


Functional

- Tenants upload documents and register tools (HTTP endpoints with JSON schemas).
- Chat API with streaming. Answers cite tenant documents.
- Agent loop: the model may call tools, with per-tool permissions, argument validation and human confirmation for risky actions.
- Conversation memory: recent turns verbatim, older turns summarised.
- Routing: small self-hosted model for simple turns, a hosted frontier model for hard ones, with fallback.
- Per-tenant quotas, usage and cost reports. Offline evaluation suite and online feedback.

Non-functional

- 50 tenants, 200 concurrent chats. Time to first token under 1.5 s p95.
- Strict tenant isolation in retrieval, memory, tools and logs.
- GPU utilisation above 60% at peak, scale to a minimum overnight.
- Survive loss of the self-hosted model (fall back to hosted) and of a vector shard (degrade to keyword search).


The architecture



- **Copilot API**: auth, tenant resolution, streaming responses to clients.

- **Agent orchestrator**: builds the prompt (system, memory, retrieved context), runs the model, executes tool calls in a loop with a step limit, streams the final answer.
- **Retriever and vector shards**: tenants are assigned to shards (small tenants share, large tenants get dedicated shards). Every query filters by tenant ID inside the shard.
- **LLM gateway**: Project 24, extended with complexity-based routing.
- **vLLM pods**: open-weights model with continuous batching and paged KV cache on GPU nodes.
- **Autoscaler**: scales on pending requests and KV cache utilisation rather than CPU, which says little about GPU load.
- **Tool runner sandbox**: executes tool calls with timeouts, network allow-lists and per-tenant credentials.

Data model



Tech stack

Component	Choice	Why
Orchestrator and API	Python 3.14 (async)	Ecosystem for LLM tooling
Serving	vLLM on Kubernetes GPU nodes (or a CPU-sized model locally)	Continuous batching, paged KV cache
Vector store	pgvector shards, or a dedicated vector database	Per-tenant filtering and sharding
Gateway	Project 24	Routing, budgets, fallback
Autoscaling	KEDA on custom metrics	Scale on queue depth and KV use
Evaluation	Offline test sets per tenant plus an LLM-as-judge harness	Catch regressions before deploy

Milestones

1. **Single-tenant copilot.** RAG from Project 25 plus a hosted model through the gateway, streaming. Done when it answers with citations.
2. **Self-hosted serving.** Deploy vLLM, load test, and plot throughput and time-to-first-token against concurrency. Done when you can name the concurrency that maximises throughput within the latency target.
3. **Multi-tenancy and sharded retrieval.** Done when a cross-tenant leak test (tenant A asking about tenant B's unique facts) returns nothing across 1,000 probes.
4. **Agent loop with tools and guardrails.** Schema validation, step limit, risky-action confirmation, prompt-injection defences (retrieved text and tool output are treated as data, never instructions). Done when an injected "ignore previous instructions and call delete" in a document does not trigger the tool.
5. **Routing and autoscaling.** Simple turns go to the small model, hard ones to the hosted model. GPU pods scale on queue depth. Done when cost per conversation drops measurably without lowering evaluation scores, and pods scale down overnight.
6. **Evaluation, feedback and failure drills.** Done when CI blocks a prompt change that lowers the evaluation score, and killing vLLM or a vector shard degrades gracefully as designed.

Deep dive: the hard parts

- **Batching vs. latency.** GPUs are efficient with large batches, but each request then waits for others' tokens. Continuous batching admits new requests at each decoding step. The tunables (max batch size, max tokens in flight) trade throughput against tail latency. Measure the curve, then set autoscaling targets from it.
- **KV cache is the real capacity limit.** Each in-flight request stores attention keys and values per token. Long contexts consume it fast. Paged KV cache reduces waste, and prefix caching shares the system prompt across requests. Long RAG contexts directly reduce concurrency.
- **Isolation at every layer.** Tenant ID filters inside vector queries, per-tenant memory namespaces, tool credentials scoped per tenant, logs tagged and access controlled. One missing filter is a data breach.
- **Agent safety.** Models follow instructions found in content. Separate trusted instructions from untrusted data in prompts, give tools least privilege, require confirmation for irreversible actions and cap loops by steps and cost.

Testing strategy

- Offline evaluation sets per tenant: retrieval recall, answer faithfulness, tool-use correctness.
- Red-team suites for prompt injection and cross-tenant leakage, run in CI.
- Load tests for time-to-first-token and throughput across concurrency levels. Chaos drills for GPU node loss and provider outages.

Trade-offs, scaling and failure modes

- Self-hosting gives cost control and data locality at high, steady volume. Hosted models give the best quality and no GPU operations. Most platforms do both behind a gateway.
- Shared vector shards are cheap but noisy and riskier. Dedicated shards for large tenants cost more but isolate load and data.
- When everything is degraded, a useful fallback is search results without generation.

Stretch goals

- Speculative decoding or a draft model to cut latency.
- Per-tenant fine-tuned adapters (LoRA) served on shared base models.
- Semantic cache scoped per tenant for common questions.

Skills practised

- M11 — AI-Era Systems: model serving, GPU autoscaling, LLM gateway, semantic caching, vector DB sharding, RAG.
- M12 — Capstones: the AI copilot design.
- M6 — Scaling: autoscaling and multi-tenant isolation.
- M9 — Operating in Production: Kubernetes, CI gates, canaries.

In the interview

30-second answer: I built a multi-tenant AI copilot platform: a self-hosted open-weights model on vLLM with continuous batching, routing through the Project 24 gateway to a hosted model for hard turns, per-tenant RAG over sharded vector indexes, and an agent loop that calls tenant tools with guardrails. The key decision was measuring the batching curve (throughput and time to first token against concurrency) and autoscaling GPU pods on queue depth and KV-cache use, not CPU. The hardest problems were tenant isolation and prompt injection, so tenant filters live inside every query, and retrieved text and tool output are treated as data, never instructions. Time to first token stays under 1.5 s p95, and 1,000 cross-tenant probes leaked nothing.

Key terms to know:

- **Continuous batching** — new requests join the running batch at each decoding step instead of waiting for the batch to finish.
- **KV cache** — stored attention keys and values for every token of every in-flight request. It is the real capacity limit on a GPU.
- **PagedAttention / prefix caching** — vLLM allocates KV cache in pages to cut waste, and shares cached prefixes such as a common system prompt.
- **Time to first token (TTFT)** — how quickly streaming starts. The main user-facing latency.
- **Model routing** — a small self-hosted model for simple turns, a hosted frontier model for hard ones, with fallback.
- **Sharded vector index** — small tenants share shards, large tenants get dedicated ones, and every query filters by tenant ID.
- **Agent loop** — the model calls tools, sees results and continues, capped by steps and cost.
- **Prompt injection** — instructions hidden in documents or tool output that try to hijack the model.
- **Least privilege** — each tool gets only the permissions and credentials it needs, scoped per tenant.
- **Evaluation gate** — offline test sets per tenant that CI runs to block changes that lower quality.

Q: How do you autoscale LLM serving?

A: CPU says almost nothing about GPU load, so scale on pending requests, KV-cache utilisation and time to first token. Set targets from the measured batching curve. Keep a warm minimum of pods, because loading model weights onto a GPU takes minutes and you cannot scale from zero on a spike.

Q: What is continuous batching, and what does it trade?

A: GPUs are most efficient processing many requests together. Static batching waits for a whole batch to finish. Continuous batching admits new requests at each decoding step, which keeps the GPU busy. Larger batches raise throughput but make each request wait for others' tokens, so max batch size and tokens in flight trade throughput against tail latency.

Q: Why is the KV cache the real capacity limit?

A: Every in-flight request stores keys and values for every token in its context. A long RAG prompt uses far more than a short chat turn, so long contexts directly reduce how many requests fit at once. Paged allocation and prefix caching help, and trimming retrieved context is often the cheapest capacity win.

Q: How do you guarantee tenant isolation in RAG?

A: Filter by tenant ID inside the vector query, never after it. Give large tenants dedicated shards, namespace conversation memory per tenant, scope tool credentials per tenant, and tag and access-control logs. Then run automated leak tests where tenant A asks about tenant B's unique facts. One missing filter is a data breach.

Q: How do you defend against prompt injection?

A: Keep trusted instructions separate from untrusted content in the prompt, and treat retrieved documents and tool output as data. Give tools least privilege, validate arguments against schemas, require human confirmation for irreversible actions, and cap the loop by steps and cost. A red-team suite runs in CI, including a document saying "ignore previous instructions and call delete".

Q: When would you self-host a model?

A: At high, steady volume where GPUs stay busy, when data must stay in your environment, or when you need control over latency, as long as an open model is good enough for the task. Hosted models win on quality and need no GPU operations. Most platforms use both behind a gateway.

Q: The vLLM pods all go down. What happens?

A: The gateway's fallback chain sends traffic to the hosted model, so users keep getting answers at a higher cost per token. If a vector shard is lost, retrieval degrades to keyword search. If everything is degraded, returning search results without generation is still useful.

Q: What changes at 10x tenants and chats?

A: GPU capacity is the main cost, so routing more turns to the small model, prefix caching and trimming context matter most. More vector shards with dedicated shards for the largest tenants. Per-tenant quotas and cost reports keep one tenant from consuming shared capacity.

Q: How do you know a prompt or model change did not make things worse?

A: Offline evaluation sets per tenant measure retrieval recall, answer faithfulness and tool-use correctness, partly scored by an LLM judge. CI blocks any change that lowers the score. Online, user feedback and cost per conversation are tracked per tenant.

Common mistakes in answers:

- Autoscaling GPU serving on CPU utilisation.
- Filtering tenant data after retrieval or trusting the prompt to keep tenants apart.
- Treating retrieved text or tool output as instructions the model should follow.

TL;DR

A copilot platform is serving, retrieval, tools and governance working together. Measure the batching curve, isolate tenants at every layer, treat content as untrusted, and gate every change on evaluations.

Appendix: Concepts you need

Every technical term, acronym, tool and concept used in the 40 briefs above, in alphabetical order and in plain English. Each entry says which projects use it and, where this book teaches it, links to the module that explains it in depth. The general system-design vocabulary (latency, throughput, caching, replication, sharding, queues and so on) is explained from scratch in System Design Fundamentals.

0–9

- **301 vs 302** — HTTP redirect codes. 301 means "moved permanently" (browsers remember it and stop asking); 302 means "found elsewhere for now" (every visit comes back to the server). Used in project 1. (Module 13)
- **409 Conflict** — HTTP status meaning the request clashes with the current state, for example the same idempotency key is still being processed or a version check failed. Used in project 5.
- **429 Too Many Requests** — HTTP status a server returns when a caller is over its rate limit; usually paired with a `Retry-After` header. Used in projects 3, 24. (Module 8)

A

- **ABAC (attribute-based access control)** — Deciding access from attributes of the user, resource and request (department, time of day, IP range) rather than from fixed roles or relationships. Used in project 38.
- **`acks` (Kafka producer acknowledgements)** — How many replicas must confirm a write before the producer is told it succeeded: `acks=0` (none), `acks=1` (the leader) or `acks=all` (every in-sync replica). Used in projects 27, 36. (Module 10)
- **ACL (access control list)** — A list attached to a resource saying who may do what with it. Used in projects 25, 38. (Module 8)
- **Active-passive** — A setup where one copy (region, server) serves traffic and another stands by, ready to take over on failure. Used in project 29. (Module 6)
- **Adaptive bitrate (ABR)** — The video player switches between quality levels segment by segment, based on measured bandwidth and how much video is buffered. Used in project 33. (Module 14)
- **Agent loop** — An LLM repeatedly decides on an action (such as calling a tool), sees the result and decides again, until it produces a final answer or hits a step limit. Used in project 40. (Module 11)
- **Aggregate (event sourcing)** — One consistency unit, such as one order, whose events form a single ordered stream and whose rules are checked together. Used in projects 14, 18. (Module 3)
- **Airflow** — Apache Airflow, a popular open-source tool for scheduling and running workflows defined as DAGs of tasks. Used in project 28. (Module 16)
- **Allowed lateness** — In stream processing, how long after a window closes the system still accepts late events and updates the result. Used in project 23. (Module 10)
- **AMQP** — Advanced Message Queuing Protocol, an open standard protocol for message brokers (RabbitMQ speaks it). Used in project 11.
- **Anti-entropy** — A background process where replicas compare their data (often with Merkle trees) and copy over whatever differs, so they converge even without new writes. Used in project 26. (Module 13)
- **API (application programming interface)** — The set of requests a service accepts and the responses it returns; the contract other programs code against. Used in most projects (30 of 40). (Module 8)
- **API gateway** — A single entry point in front of many services that handles shared concerns once: routing, authentication, rate limits, logging. Used in projects 17, 24, 36, 40. (Module 8)
- **Append-only log** — A file or table you only ever add to at the end, never edit in place; the basis of WALs, Kafka and event stores. Used in projects 7, 14, 18, 26, 27, 30, 31, 32. (Module 3)
- **Argo Rollouts** — A Kubernetes add-on that performs canary and blue-green deployments with automated analysis and rollback. Used in project 39. (Module 9)
- **Arrow (tuple-to-userset)** — In Zanzibar-style schemas, a rule that follows a relation to another object and reuses its permissions, e.g. "viewers of a doc include viewers of its parent folder" (`parent->viewer`). Used in project 38. (Module 8)

- **asyncio** — Python's standard library for asynchronous programming: one thread runs many tasks that pause while waiting for I/O. Used in projects 4, 8, 16, 22.
- **At-least-once delivery** — A guarantee that every message is delivered, possibly more than once; receivers must therefore handle duplicates. Used in projects 4, 6, 14, 28, 29. (Module 5)
- **Atomic operation** — An operation that happens completely or not at all, with no other operation able to see or interleave with a half-done state. Used in projects 3, 4, 5, 12, 14, 15, 19, 24, 27, 31, 34.
- **Audit log** — An append-only record of who changed what and when, kept for security, debugging and compliance. Used in projects 6, 10, 18, 29. (Module 9)
- **Autoscaling** — Automatically adding or removing machines (or pods) based on a signal such as CPU, queue depth or pending requests. Used in projects 11, 33, 40. (Module 6)
- **Availability** — The share of time a system is up and answering requests correctly. Used in projects 3, 4, 15, 19, 20, 26, 27, 32, 34, 37, 39.
- **Awareness / presence channel** — A side channel in collaborative apps that shares short-lived state such as cursors and who is online; it is never stored. Used in project 32. (Module 16)
- **AWS SDK / AWS CLI** — Amazon's official client libraries and command-line tool; pointing them at your own server tests S3 compatibility. Used in projects 11, 31.
- **AWS Signature V4** — Amazon's scheme for signing HTTP requests with a secret key so the server can verify who sent them and that nothing was changed. Used in project 31.

B

- **B-tree** — The standard database index structure: a balanced tree of sorted keys that supports fast lookups and range scans. Used in projects 2, 12, 21.
- **Backend for Frontend (BFF)** — A small API layer built for one client (a web page, a mobile app) that calls several backend services and returns exactly what that screen needs. Used in project 9. (Module 8)
- **Backfill** — Re-running processing over past data, for example to fill a new table or fix results after a bug. Used in projects 23, 28. (Module 10)
- **Backpressure** — A way for a slow consumer to make a fast producer slow down (or for the system to drop or buffer data) instead of being overwhelmed. Used in projects 22, 23, 25, 27, 37. (Module 10)
- **Base62 encoding** — Writing a number using 62 characters (0–9, a–z, A–Z), which makes short, URL-safe codes. Used in project 1. (Module 13)
- **Batching** — Grouping many small operations into one bigger one (one network call, one disk write) to cut per-operation overhead. Used in projects 1, 2, 3, 4, 8, 12, 13, 14, 18, 19, 20, 23, 25, 27, 28, 29, 31, 34, 35, 37, 39, 40.
- **BFS / DFS** — Breadth-first search explores everything one step away before going deeper; depth-first search follows one path as far as possible first. Used in project 22.
- **Bitcask** — A simple storage design: values appended to a log file plus an in-memory hash index from each key to its position in the file. Used in project 26.
- **Bitrate ladder** — The set of quality levels (resolution and bitrate pairs) a video is encoded into so players can pick one. Used in project 33. (Module 14)
- **Blast radius** — How much of the system (users, tenants, services) is affected when one part fails or a bad change ships. Used in project 39. (Module 6)
- **Block-list** — A list of forbidden items (search terms, IPs, URLs) that are filtered out. Used in projects 12, 17.
- **Bloom filter** — A compact bit array that answers "definitely not in the set" or "probably in the set"; it can have false positives but never false negatives. Used in projects 1, 22. (Module 13)
- **BM25** — A classic keyword-ranking formula that scores documents by how often query words appear, adjusted for word rarity and document length. Used in project 25. (Module 11)
- **Bucket (object storage)** — A named container for objects, like a top-level folder, in S3-style storage. Used in projects 11, 31. (Module 16)
- **Bulkhead** — Isolating resources (thread pools, connections, workers) per dependency or customer so one slow or failing part cannot use up everything. Used in projects 6, 9. (Module 5)

C

- **Cache hit ratio** — The share of requests answered from the cache instead of the slower source. Used in projects 1, 11, 16, 21, 24, 33. (Module 4)
- **Cache invalidation** — Removing or updating cached copies when the underlying data changes, so readers do not see stale values. Used in projects 1, 10, 11, 16, 21, 25, 31. (Module 4)
- **Cache stampede (thundering herd)** — Many requests miss the same cache entry at the same moment and all hit the backend together; prevented with locks, request collapsing or jittered expiry. Used in projects 1, 16, 28. (Module 4)
- **Cache-aside (lazy loading)** — The application checks the cache first; on a miss it reads the database and writes the result into the cache itself. Used in project 1. (Module 4)
- **Canary deployment** — Releasing a change to a small slice of traffic (one cell, a few percent of users) first and watching metrics before rolling it out further. Used in project 39. (Module 9)
- **Cardinality** — The number of distinct values; in metrics, the number of distinct label combinations, i.e. separate time series. Used in projects 20, 37. (Module 16)
- **CAS (compare-and-swap)** — An atomic "set this value only if it is still X" operation, used to update shared data safely without locks. Used in projects 2, 30.
- **CDC (change data capture)** — Reading a database's own change log (its WAL) to stream every committed insert, update and delete to other systems. Used in projects 14, 15, 18, 21, 29, 38, 39. (Module 10)
- **CDN (content delivery network)** — A worldwide set of cache servers that keep copies of files close to users, so most requests never reach your servers. Used in projects 1, 10, 11, 12, 33. (Module 8)
- **Cell (cell-based architecture)** — A complete, independent copy of the whole stack serving a subset of customers, so one failure or bad deploy only affects that subset. Used in project 39. (Module 6)
- **Cell router** — The thin layer that looks up which cell a tenant lives in and forwards its requests there. Used in project 39. (Module 6)
- **Checkpoint** — A saved position or state (such as "processed up to offset 812") that lets a consumer or stream job restart where it left off. Used in projects 18, 23. (Module 10)
- **Checksum** — A small value computed from data (CRC, SHA-256) and stored with it, so corruption can be detected by recomputing and comparing. Used in projects 27, 31, 36, 39. (Module 16)
- **Chunking** — Splitting big data (a file, a video, a document) into smaller pieces that can be stored, sent, retried or processed independently. Used in projects 17, 20, 25, 31, 33. (Module 14)
- **Circuit breaker** — A wrapper that stops calling a dependency after repeated failures, fails fast for a while, then lets a few test calls through to see if it recovered. Used in projects 4, 9, 17, 24. (Module 5)
- **Citus** — A PostgreSQL extension that shards tables across several PostgreSQL servers. Used in project 35. (Module 3)
- **Clearing (suspense) account** — An internal account that holds money "in transit" between two steps, so the books balance at every moment of a multi-step transfer. Used in projects 29, 36. (Module 17)
- **ClickHouse** — An open-source columnar database built for fast analytical queries over large volumes of events. Used in projects 23, 37. (Module 10)
- **Clock skew** — Different machines' clocks disagreeing by some amount, which makes timestamps from different hosts unreliable for ordering. Used in projects 2, 3, 26, 37. (Module 7)
- **Cold start** — The first requests after a process or cache starts, which are slow because nothing is loaded or cached yet. Used in projects 10, 16. (Module 18)
- **Columnar storage** — Storing each column's values together on disk, which makes scanning and aggregating a few columns over many rows very fast. Used in project 37. (Module 10)
- **Compaction** — Rewriting stored data to drop obsolete versions, deleted items or old log entries and reclaim space. Used in projects 20, 27, 30, 31, 32. (Module 3)
- **Compensating action / event** — A step that semantically undoes an earlier completed step (refund a payment, release stock), used in sagas and event-sourced systems instead of a rollback. Used in projects 18, 19, 29. (Module 7)
- **Concurrency** — Several operations in progress at the same time, which can interfere with each other if they touch shared data. Used in projects 2, 3, 4, 5, 6, 8, 9, 13, 15, 18, 22, 24, 26, 28, 29, 30, 32, 33, 34, 36, 38, 40.

- **Conditional (atomic) update** — An `UPDATE ... WHERE <condition>` that changes a row only if a check still holds, doing the check and the write in one step. Used in projects 15, 34. (Module 17)
- **Connection pool** — A set of open database connections reused across requests, with a cap so the database is not flooded. Used in projects 1, 9, 16, 17. (Module 6)
- **Consensus** — Getting a group of machines to agree on one value or one ordered log even if some of them fail; Raft and Paxos are consensus algorithms. Used in project 30. (Module 7)
- **Consistency token (zookie)** — An opaque token from a write that later reads pass back to say "answer with data at least this fresh". Used in project 38. (Module 8)
- **Consistent hashing** — Placing keys and servers on a hash ring so each key belongs to the next server clockwise; adding or removing a server moves only a small share of keys. Used in projects 13, 16, 26, 32, 37. (Module 3)
- **Consumer group** — A set of consumers sharing the work of reading a topic: each partition is read by exactly one member at a time. Used in project 27. (Module 10)
- **Container** — A packaged process with its own filesystem and dependencies that runs the same way on any machine (Docker builds and runs them). Used in projects 28, 33. (Module 9)
- **Context propagation** — Passing request identifiers (such as a trace ID) along with every call, including through queues and thread pools, so work can be linked back to the original request. Used in projects 9, 10, 37. (Module 9)
- **Continuous batching** — An LLM-serving technique that adds new requests into a running GPU batch at every decoding step instead of waiting for the whole batch to finish. Used in project 40. (Module 11)
- **Control plane vs data plane** — The control plane manages configuration and placement (slow, rarely called); the data plane handles the actual user requests (fast, on every call). Used in projects 17, 39. (Module 6)
- **Convergence** — After all replicas have seen the same set of updates, they end up with the same state regardless of the order updates arrived in. Used in projects 26, 32. (Module 16)
- **Counter reset** — A metrics counter dropping back to zero because the process restarted; rate calculations must treat the drop as a restart, not a negative rate. Used in project 20. (Module 16)
- **CPU** — The processor that runs program instructions; CPU usage is a common load signal. Used in projects 4, 7, 8, 11, 20, 32, 37, 40.
- **CQRS (command query responsibility segregation)** — Using one model for writes (commands) and separate, query-shaped models for reads. Used in project 18. (Module 3)
- **Crash recovery** — What a component does on restart to get back to a correct state, typically by replaying a log from the last checkpoint. Used in projects 4, 5, 8, 10, 11, 14, 17, 18, 19, 20, 22, 23, 28, 29, 30, 31, 32, 33, 34, 36.
- **Crawl-delay** — A `robots.txt` hint telling crawlers how many seconds to wait between requests to the site. Used in project 22. (Module 13)
- **Crawler trap** — A site region that generates endless URLs (calendars, session IDs) and can keep a crawler busy forever. Used in project 22. (Module 13)
- **CRDT (conflict-free replicated data type)** — A data structure whose copies can be edited independently, even offline, and always merge to the same result without a coordinator. Used in projects 26, 32. (Module 16)
- **Cron expression** — A compact schedule format such as `0 2 * * *` ("02:00 every day") from the classic Unix scheduler cron. Used in projects 4, 28. (Module 16)
- **Cross-encoder (reranker)** — A model that reads the question and a candidate passage together and scores how well they match; slower but more precise than comparing embeddings. Used in project 25. (Module 11)
- **CRUD** — Create, read, update, delete: the four basic operations on stored records. Used in projects 10, 18, 21, 28, 31.
- **Cursor pagination** — Returning results a page at a time, where each page ends with a bookmark (cursor) for "continue after this item", so inserts do not shift pages. Used in projects 32, 35. (Module 8)

D

- **DAG (directed acyclic graph)** — A set of steps with "must happen before" arrows and no loops; used to describe pipelines and job dependencies. Used in projects 28, 33. (Module 16)
- **Dead man's switch** — An alert that is always firing on purpose; if it ever stops arriving, the monitoring pipeline itself is broken and someone is paged. Used in project 20. (Module 16)
- **Dead-letter queue (DLQ)** — A holding queue for messages or jobs that keep failing, so they stop blocking others and humans can inspect and replay them. Used in projects 4, 6, 11. (Module 5)
- **Deadline propagation** — Passing the remaining time budget of a request down to every call it makes, so downstream work that cannot finish in time is skipped. Used in project 9. (Module 5)
- **Deadlock** — Two or more transactions each waiting for a lock the other holds, so none can proceed; avoided by always locking in the same order. Used in projects 15, 29. (Module 17)
- **Debezium** — An open-source CDC tool that reads database change logs (such as the PostgreSQL WAL) and publishes the changes to Kafka. Used in projects 14, 39. (Module 10)
- **Debounce** — Waiting until input stops changing for a short time (for example 100 ms after the last keystroke) before acting on it. Used in project 12. (Module 18)
- **Decompression bomb** — A small file (image, archive) that expands to a huge size when decoded, used to exhaust a server's memory. Used in project 11.
- **Delta-of-delta encoding** — Compressing timestamps by storing the change in the gap between consecutive points; for regular intervals that is almost always zero. Used in project 20. (Module 16)
- **Deterministic** — Always producing the same output from the same input, with no dependence on clocks, randomness or thread timing. Used in projects 10, 11, 18, 19, 23, 24, 26, 30, 32, 33, 36. (Module 17)
- **Deterministic bucketing** — Hashing a stable key (flag plus user ID) to a number from 0–99 so the same user always lands in the same rollout bucket. Used in project 10. (Module 9)
- **DNS (Domain Name System)** — The internet's directory that turns names like `example.com` into IP addresses. Used in projects 6, 22.
- **Docker / Docker Compose** — Docker builds and runs containers; Docker Compose starts a group of containers (app, database, cache) from one file with `docker compose up`. Used in projects 1, 3, 26. (Module 9)
- **Double-entry bookkeeping** — Recording every money movement as matching debits and credits that sum to zero, so money can only move, never appear or vanish. Used in project 29. (Module 17)
- **Downsampling / rollups** — Replacing many fine-grained data points with summaries over larger intervals (for example 5-minute min/max/sum/count) to save space for old data. Used in projects 12, 20. (Module 16)
- **DST (daylight saving time)** — Seasonal clock changes that make some local times happen twice and others not at all, which complicates schedules. Used in project 28. (Module 16)
- **Dual write** — An application writing the same change to two systems separately (database and cache, database and Kafka); a failure between them leaves them disagreeing. Used in projects 7, 14. (Module 10)
- **Durability** — The guarantee that data, once acknowledged, survives crashes and hardware failures. Used in projects 5, 6, 7, 8, 11, 12, 19, 22, 24, 27, 28, 29, 30, 31, 35, 36.
- **Durable execution (Temporal)** — Workflow engines such as Temporal that record every step so a workflow resumes exactly where it stopped after a crash. Used in projects 19, 29, 33. (Module 7)
- **Dynamo** — Amazon's 2007 design for a highly available, leaderless key-value store; the inspiration for Cassandra and Riak. Used in project 26. (Module 13)

E

- **Edge (edge cache)** — Servers at the network's edge, close to users, such as CDN points of presence that cache content. Used in projects 11, 12, 33. (Module 8)
- **Edge effect (geospatial)** — Two nearby points falling in different grid cells across a boundary, so a search must also check neighbouring cells. Used in project 21. (Module 15)
- **Elasticsearch** — A popular search engine built on inverted indexes, used for full-text search and log analytics. Used in projects 12, 14, 18.

- **Election restriction (Raft)** — A node only votes for a candidate whose log is at least as up to date as its own, which guarantees the new leader has every committed entry. Used in project 30. (Module 7)
- **Embedding** — A list of numbers (a vector) produced by a model to represent the meaning of a text or image; similar meanings get nearby vectors. Used in projects 24, 25. (Module 11)
- **Envoy** — A widely used open-source proxy for API gateways and service meshes. Used in projects 17, 39. (Module 8)
- **Epoch (ID generation)** — The custom start date from which an ID's timestamp is counted, chosen recent so the time bits last as long as possible. Used in project 2. (Module 13)
- **Erasure coding (k+m)** — Splitting data into k pieces and computing m extra parity pieces so any k of the k+m can rebuild the original, using far less space than full copies. Used in project 31. (Module 16)
- **ETA (estimated time of arrival)** — A prediction of how long a trip or delivery will take. Used in project 34. (Module 15)
- **ETag** — An HTTP header holding a version tag for a resource; clients send it back to ask "has this changed?" and get `304 Not Modified` if not. Used in projects 10, 31. (Module 18)
- **etcd** — A small, strongly consistent key-value store replicated with Raft, used by Kubernetes and others for configuration, leases and leader election. Used in projects 16, 27, 28, 30. (Module 7)
- **Event sourcing** — Storing every change as an immutable event and rebuilding current state by replaying them, instead of storing only the latest state. Used in projects 18, 36. (Module 3)
- **Event time vs processing time** — Event time is when something actually happened; processing time is when the system sees it. They differ when events arrive late or out of order. Used in project 23. (Module 10)
- **Event-driven processing** — Components react to events ("file uploaded", "order placed") published by others instead of being called directly. Used in projects 11, 14. (Module 2)
- **EventSource** — The browser API that opens a Server-Sent Events stream and reconnects automatically, sending `Last-Event-ID`. Used in project 8. (Module 2)
- **Eventual consistency** — Replicas may briefly disagree after a write but will converge if no new writes arrive; readers can see stale data meanwhile. Used in projects 6, 11, 15, 18, 19, 30, 32, 34, 38. (Module 7)
- **Exactly-once (in effect)** — Every operation takes effect once even though messages may be delivered more than once, achieved with idempotent processing or transactions. Used in projects 4, 5, 6, 14, 18, 19, 23, 27, 28, 29. (Module 10)
- **EXIF** — Metadata stored inside photos (camera model, time, often GPS location); stripped before publishing for privacy. Used in project 11.
- **Exponential backoff with jitter** — Waiting longer after each failed retry (1 s, 2 s, 4 s...) plus a random extra delay, so many clients do not retry in lockstep. Used in projects 4, 5, 6, 9, 19. (Module 5)

F

- **Fail open / fail closed** — When a check cannot run (its store is down), failing open lets requests through; failing closed rejects them. Open protects availability, closed protects safety. Used in projects 3, 24, 38. (Module 5)
- **Failover** — Switching to a standby or replica when the primary fails. Used in projects 5, 24, 26, 27, 28, 29, 36, 39. (Module 3)
- **Failure domain** — A group of components that can fail together (a disk, a host, a rack, a zone); copies are spread across them. Used in project 31. (Module 16)
- **Fallback** — A cheaper or older answer used when the normal path fails (cached data, a default, another provider). Used in projects 3, 8, 9, 24, 40. (Module 5)
- **Fan-out** — One input producing many outputs, such as one post pushed to thousands of followers' feeds or one event sent to many webhooks. Used in projects 4, 6, 8, 9, 13, 15, 18, 20, 32, 34, 35, 36. (Module 2)
- **Fan-out on write / on read** — On write (push): copy each new post into every follower's feed when it is created. On read (pull): assemble the feed from followees when it is requested. Hybrids push for

most users and pull for celebrities. Used in project 35. (Module 12)

- **FastAPI** — A popular Python web framework for building HTTP APIs with async support. Used in projects 1, 5, 7, 10, 11, 15, 19, 21, 24.
- **Fault injection / chaos testing** — Deliberately breaking things (killing processes, adding latency, cutting networks) to check the system handles failures as designed. Used in projects 1, 3, 6, 9, 16, 17, 19, 23, 26, 27, 28, 30, 31, 33, 34, 35, 39, 40. (Module 9)
- **Feature flag** — A switch, read at runtime, that turns a code path on or off for some or all users without deploying. Used in project 10. (Module 9)
- **Feistel cipher** — A reversible scrambling construction that can shuffle integers one-to-one, turning sequential IDs into non-guessable but still unique codes. Used in project 1.
- **Fencing token** — A number that increases each time ownership changes; storage rejects writes carrying an older token, so a paused former owner cannot do damage. Used in projects 2, 28, 29, 36. (Module 7)
- **FFmpeg** — The standard open-source command-line tool and libraries for decoding, encoding and converting audio and video. Used in project 33. (Module 14)
- **FIFO** — First in, first out: items are processed in the order they arrived. Used in project 36.
- **File descriptor limit** — The operating system's cap on how many open files and sockets one process may hold; long-lived connections hit it. Used in project 8.
- **Filter chain** — An ordered list of steps (auth, rate limit, logging) each request passes through in a proxy or framework; any step can reject or modify it. Used in project 17. (Module 8)
- **First-writer-wins** — When two writers race, the one whose insert lands first succeeds and the other is rejected, typically enforced by a unique constraint. Used in project 5. (Module 5)
- **FIX protocol** — The Financial Information eXchange message standard used between brokers and exchanges. Used in project 36. (Module 17)
- **Flink** — Apache Flink, a stream-processing engine with event-time windows, managed state and exactly-once checkpoints. Used in project 23. (Module 10)
- **Fold (event sourcing)** — Computing current state by applying events one by one, in order, starting from an empty state. Used in project 18. (Module 3)
- **fsync** — The system call that forces written data from memory buffers onto the physical disk, so it survives a power loss. Used in projects 27, 30. (Module 3)

G

- **Gap detection** — Using gap-free sequence numbers so a receiver that sees 41 then 43 knows 42 is missing and fetches it. Used in projects 13, 36. (Module 14)
- **Garbage collection (storage)** — A background job that finds and deletes data nothing refers to any more, such as orphan chunks or expired versions. Used in projects 2, 28, 31, 32, 36. (Module 16)
- **Garbage-collection pause** — A moment when a language runtime (such as the JVM) pauses the program to free memory; a long pause can make a process miss lease deadlines. Used in projects 2, 28, 36.
- **Gateway (connection gateway)** — A server tier that holds client connections (WebSockets, SSE) and forwards messages, keeping the rest of the system stateless. Used in projects 13, 34. (Module 14)
- **Geo-sharding** — Partitioning data and services by geographic region (city, cell) so local traffic stays on local servers. Used in project 34. (Module 12)
- **Geohash** — Encoding a latitude/longitude as a short string where a shared prefix means the points are in the same grid cell. Used in project 21. (Module 15)
- **GiST index** — PostgreSQL's generalised search-tree index, used by PostGIS to index shapes and locations (R-tree style). Used in project 21. (Module 15)
- **Gossip protocol** — Nodes periodically exchange state with random peers, so information (membership, failures) spreads through the cluster without a central server. Used in projects 16, 26. (Module 13)
- **GPU** — A graphics processor; its many parallel cores make it the hardware of choice for running ML models such as LLMs. Used in project 40. (Module 11)
- **Graceful degradation** — Keeping the core function working with reduced features or quality when a dependency fails, instead of failing completely. Used in projects 9, 35, 39, 40. (Module 5)

- **Grafana** — An open-source dashboard tool for charting metrics from many data sources. Used in project 20. (Module 9)
- **Greedy vs batched matching** — Greedy assigns each request immediately to the best current option; batched collects requests for a moment and solves them together for a better overall result. Used in project 34. (Module 12)
- **gRPC** — A high-performance remote-procedure-call framework from Google using HTTP/2 and typed Protocol Buffers messages, with streaming support. Used in projects 17, 26, 27, 30, 38.

H

- **H3 / S2** — Uber's hexagonal and Google's square-cell hierarchical grids that divide the Earth into numbered cells at many resolutions. Used in projects 21, 34. (Module 15)
- **Hash function** — A function that turns any input into a fixed-size number or string; the same input always gives the same output. Used in projects 1, 3, 5, 6, 10, 11, 13, 16, 20, 22, 24, 25, 26, 27, 28, 31, 32, 34, 36, 37. (Module 3)
- **Haversine distance** — The formula for great-circle distance between two latitude/longitude points on a sphere. Used in project 21. (Module 15)
- **Head block** — In a time-series database, the most recent data held in memory (backed by a WAL) before it is compressed and written as an immutable block. Used in project 20. (Module 16)
- **Head sampling vs tail sampling** — Head sampling decides whether to keep a trace when it starts (cheap, misses rare errors); tail sampling decides after seeing the whole trace (catches errors and slow requests, needs buffering). Used in project 37. (Module 9)
- **Health check** — An endpoint or probe that reports whether a service instance is working, used by load balancers and deploy tools. Used in project 39. (Module 9)
- **Heap (data structure)** — A tree-shaped structure that always gives you the smallest (or largest) item quickly; used for "next due" queues. Used in projects 12, 17, 22.
- **Heartbeat** — A small periodic "I'm alive" message; when heartbeats stop, the sender is presumed dead. Used in projects 4, 8, 13, 26, 27, 28, 30. (Module 2)
- **Helm** — A package manager for Kubernetes that installs an application from a templated chart. Used in project 39. (Module 9)
- **High watermark (Kafka)** — The highest offset copied to all in-sync replicas; consumers can only read up to it, so they never see records that could be lost. Used in project 27. (Module 10)
- **Hinted handoff** — When a replica is down, another node accepts its writes with a note (hint) and hands them over once it recovers. Used in project 26. (Module 13)
- **HLS (HTTP Live Streaming)** — Apple's streaming format: video cut into short segment files plus playlists that list them, served over plain HTTP. Used in project 33. (Module 14)
- **HMAC signature** — A hash of a message computed with a shared secret key; the receiver recomputes it to verify the sender and that nothing was altered. Used in project 6. (Module 2)
- **HNSW** — Hierarchical Navigable Small World, a layered graph index for fast approximate nearest-neighbour search over vectors. Used in project 25. (Module 11)
- **Hot key / hot shard / hot account** — One key, partition or account that receives a disproportionate share of traffic and overloads the node holding it. Used in projects 1, 3, 7, 15, 16, 23, 26, 29, 35. (Module 4)
- **Hot reload / hot swap** — Replacing configuration or data (routes, an index) in a running process without restarting or dropping requests. Used in projects 12, 17.
- **Hot standby** — A replica kept fully up to date and ready to take over immediately if the primary fails. Used in projects 29, 36. (Module 17)
- **HPA (Horizontal Pod Autoscaler)** — Kubernetes' built-in autoscaler that changes the number of pods based on a metric. Used in project 33. (Module 6)
- **HTTP** — The request/response protocol of the web; HTTP/2 and HTTP/3 multiplex many requests over one connection. Used in projects 1, 2, 3, 5, 6, 8, 12, 13, 16, 19, 22, 23, 28, 33, 37, 40.
- **Hybrid search** — Combining keyword search (exact words) and vector search (meaning) and merging their result lists. Used in project 25. (Module 11)
- **Hydration (feed)** — Turning a list of IDs into full objects (posts with authors and counts) by fetching them, usually with one multi-get. Used in project 35. (Module 12)

- **HyperLogLog** — A tiny probabilistic sketch that estimates how many distinct items it has seen (unique users) within about 1% error. Used in project 23. (Module 16)
- **Hysteresis** — Using different thresholds for switching on and switching off, so a value hovering near one threshold does not flip back and forth. Used in project 20.

I

- **Idempotency / idempotent** — Doing an operation twice has the same effect as doing it once, so retries are safe. Used in projects 4, 5, 9, 11, 14, 15, 17, 18, 19, 23, 27, 28, 29, 33. (Module 5)
- **Idempotency key** — A unique ID the client attaches to one logical request and reuses on every retry, so the server can recognise and dedupe repeats. Used in projects 4, 5, 15, 17, 19, 29. (Module 5)
- **Idempotent producer (Kafka)** — A producer that tags records with a producer ID and sequence number so the broker drops retried duplicates. Used in project 27. (Module 10)
- **Immutability** — Never modifying data once written; corrections are new records, which makes history, audit and caching simpler. Used in projects 11, 18, 20, 29, 33. (Module 17)
- **In-sync replicas (ISR)** — In Kafka, the followers that are fully caught up with the leader; only they count for `acks=all`. Used in project 27. (Module 10)
- **Inbox table (idempotent consumer)** — A table where a consumer records processed message IDs in the same transaction as its work, so redelivered messages are skipped. Used in projects 8, 14, 19. (Module 10)
- **Integer minor units / ticks** — Storing money or prices as whole numbers of the smallest unit (cents, price ticks) instead of floating-point numbers, so arithmetic is exact. Used in projects 5, 28, 29, 36. (Module 17)
- **Interleaving anomaly** — In collaborative editing, two users' concurrent typing being mixed character by character ("axbycz") instead of kept as separate runs. Used in project 32. (Module 16)
- **Inverted index / postings list** — A map from each term (a word, a label value) to the list of documents or series containing it; the core of search engines. Used in project 20. (Module 16)

J

- **Java virtual threads** — Lightweight threads in modern Java that make it cheap to run thousands of concurrent blocking tasks. Used in projects 4, 6, 8, 13, 16, 22, 31, 38.
- **Jepsen** — A tool and method for testing distributed databases by injecting failures and checking the recorded history of operations for consistency violations. Used in projects 26, 30.
- **Jitter** — A small random variation added to timers, TTLs or retry delays so many clients do not act at exactly the same moment. Used in projects 1, 4, 5, 8, 9, 28, 36. (Module 5)
- **JMH** — Java Microbenchmark Harness, the standard tool for accurate micro-benchmarks in Java. Used in projects 2, 36.
- **Journal** — A durable, ordered, append-only record of inputs or changes (a ledger's journal entries, an exchange's order journal). Used in projects 12, 14, 29, 36. (Module 17)
- **JSON** — JavaScript Object Notation, a simple text format for structured data used by most web APIs. Used in projects 4, 17, 20, 24, 32, 40.
- **Jump consistent hash / rendezvous hashing** — Alternatives to a hash ring: jump hash computes a bucket with a tiny formula; rendezvous hashing picks the node with the highest hash score for each key. Used in project 16. (Module 3)
- **JWT / JWKS** — A JSON Web Token is a signed token carrying identity claims that services verify locally; a JWKS is the published set of public keys used to verify them. Used in project 17. (Module 8)

K

- **k6 / wrk** — Load-testing tools that fire many concurrent HTTP requests and report latency percentiles and throughput. Used in projects 1, 3, 7, 8, 15.
- **Kafka** — Apache Kafka, a distributed, partitioned, replicated append-only log used as a durable message bus and event stream. Used in projects 4, 6, 8, 11, 12, 13, 14, 18, 19, 23, 24, 25, 27, 28, 29, 30, 33, 34, 35, 36, 37. (Module 10)

- **Kafka Connect** — Kafka's framework for running connectors that move data between Kafka and other systems (Debezium runs on it). Used in project 14. (Module 10)
- **Kafka Streams** — A Java library for building stream-processing applications directly on Kafka topics. Used in project 23. (Module 10)
- **Kappa vs Lambda architecture** — Lambda runs a batch path and a streaming path side by side; Kappa uses only a streaming path and reprocesses history by replaying the log. Used in project 23. (Module 10)
- **KEDA** — Kubernetes Event-Driven Autoscaling: scales workloads on external metrics such as queue length. Used in projects 33, 40. (Module 11)
- **Key-value store** — A database that stores values under keys and supports get/put by key (Redis, Dynamo, etcd). Used in projects 7, 21, 26, 30. (Module 13)
- **Keyframe** — A video frame that can be decoded on its own; players can only start or switch quality at keyframes. Used in project 33. (Module 14)
- **Kill switch** — A flag that instantly turns off a feature, route or trading path when something goes wrong. Used in projects 10, 36. (Module 9)
- **kind / k3d** — Tools that run a small Kubernetes cluster inside Docker containers on a laptop. Used in project 39. (Module 9)
- **Kubernetes** — The standard container orchestrator: it schedules containers onto machines, restarts them, scales them and wires up networking. Used in projects 26, 27, 28, 29, 30, 31, 33, 34, 39, 40. (Module 9)
- **KV cache** — In LLM serving, the stored attention keys and values for every token of each in-flight request; its GPU memory size limits how many requests can run at once. Used in project 40. (Module 11)

L

- **Last-Event-ID** — The header a reconnecting SSE client sends with the ID of the last event it received, so the server can resend what it missed. Used in project 8. (Module 2)
- **Last-writer-wins (LWW)** — Resolving conflicting writes by keeping the one with the latest timestamp; simple, but silently drops the others. Used in project 26. (Module 7)
- **Latency** — How long one request takes from start to finish. Used in most projects (27 of 40).
- **Leader election** — Choosing one node to coordinate (accept writes, assign work), and choosing a new one when it fails. Used in projects 27, 28, 30, 34. (Module 7)
- **Leader epoch / term** — A counter increased every time a new leader takes over, so messages from an old leader can be recognised and rejected. Used in projects 27, 30. (Module 7)
- **Leaderless replication** — Replication with no single leader: clients write to several replicas directly and use quorums (Dynamo style). Used in project 26. (Module 7)
- **Lease** — A time-limited claim (on a worker ID, shard or lock) that must be renewed before it expires or ownership passes to someone else. Used in projects 2, 16, 27, 28, 30, 34, 36. (Module 7)
- **Least privilege** — Giving each user, service or tool only the permissions it strictly needs. Used in project 40.
- **libvips** — A fast, memory-efficient image-processing library used for resizing and converting images. Used in project 11.
- **Limit / market / IOC order** — A limit order trades only at a set price or better; a market order trades now at the best available price; an immediate-or-cancel order fills what it can at once and cancels the rest. Used in project 36. (Module 17)
- **Linearizability** — The strongest single-object consistency: every operation appears to happen at one instant between its start and end, so reads always see the latest write. Used in projects 26, 27, 30. (Module 7)
- **LISTEN/NOTIFY** — PostgreSQL's built-in publish-subscribe: a session listening on a channel is notified when another session calls `NOTIFY`. Used in project 4. (Module 2)
- **LLM (large language model)** — A neural network trained on huge amounts of text that generates text one token at a time (GPT, Claude, Llama). Used in projects 24, 25, 40. (Module 11)
- **LLM-as-judge** — Using a language model to grade another model's answers against a rubric, as part of automated evaluation. Used in projects 25, 40. (Module 11)

- **Load balancer** — A component that spreads incoming requests across several server instances (round-robin, least-requests) and skips unhealthy ones. Used in projects 1, 8, 17. (Module 6)
- **Load shedding** — Deliberately rejecting some requests when overloaded so the rest still succeed. Used in projects 1, 3. (Module 5)
- **Local evaluation (feature flags)** — The SDK evaluates flag rules in memory inside the application, so checks need no network call. Used in project 10. (Module 9)
- **Log compaction / snapshot (Raft)** — Periodically saving the full state machine and deleting the log entries it already includes, so the log does not grow forever. Used in projects 27, 30, 32. (Module 7)
- **Lost update** — Two read-modify-write operations overlap and one overwrites the other's change. Used in project 3.
- **LRU eviction** — When memory is full, remove the least recently used entries first. Used in project 16. (Module 4)
- **Lua script (Redis)** — A small script Redis runs atomically, so a multi-step read-check-write cannot be interleaved with other commands. Used in project 3. (Module 8)

M

- **Magic bytes** — The first bytes of a file that identify its real format (JPEG, PNG), regardless of its name or declared type. Used in project 11.
- **MapReduce / batch job** — Processing a large dataset offline in parallel chunks (map) and combining the results (reduce), as opposed to processing events as they arrive. Used in projects 12, 20, 23. (Module 10)
- **Market data** — The public feed of an exchange's prices, order-book changes and trades. Used in project 36. (Module 17)
- **Matching engine** — The core of an exchange that pairs buy and sell orders according to price-time priority. Used in project 36. (Module 17)
- **Membership** — The current list of live nodes in a cluster, which clients and nodes must agree on to route keys correctly. Used in projects 16, 26, 27, 30. (Module 13)
- **Merkle tree** — A tree of hashes where each parent hashes its children; comparing roots and then branches finds differences between replicas quickly. Used in project 26. (Module 13)
- **Metadata** — Data about data: an object's name, size, owner and chunk locations, as opposed to the bytes themselves. Used in projects 6, 11, 18, 20, 22, 24, 25, 27, 31, 32. (Module 16)
- **Microservices** — An architecture where an application is split into many small services, each owning its own data and deployed independently. Used in projects 14, 17, 19, 24.
- **min.insync.replicas** — A Kafka setting: the minimum number of in-sync replicas required for an `acks=all` write; below it the leader refuses writes. Used in project 27. (Module 10)
- **MinIO** — An open-source, S3-compatible object store you can run locally. Used in projects 11, 22, 31, 33. (Module 16)
- **Misfire policy** — What a scheduler does about runs it missed while it was down: run once to catch up, run all, or skip them. Used in project 28. (Module 16)
- **Model alias / routing** — Mapping a stable name such as `fast` or `smart` to a concrete model, and choosing a model per request by policy, cost or difficulty. Used in projects 24, 40. (Module 11)
- **Monotonic** — Only ever increasing (or never going backwards); used for IDs, revisions, fencing tokens and rollouts. Used in projects 2, 10, 28, 30.
- **Multi-tenant** — One deployed system serving many separate customers (tenants), whose data and load must be kept apart. Used in projects 20, 24, 25, 28, 39, 40. (Module 6)
- **Multipart upload** — Uploading a large object as many separately sent and retried parts, then committing them as one object. Used in projects 11, 31, 33. (Module 16)
- **MurmurHash3 / xxHash** — Fast non-cryptographic hash functions with good distribution, used for bucketing and placing keys. Used in projects 10, 16.
- **MVCC (multi-version concurrency control)** — Keeping several versions of each row so readers see a consistent snapshot while writers create new versions; PostgreSQL works this way, which is why old versions must be vacuumed. Used in projects 4, 38.

N

- **Negative caching** — Caching a "not found" answer for a short time so repeated lookups of missing keys do not reach the database. Used in project 1. (Module 4)
- **Netty** — A Java library for building high-performance, non-blocking network servers. Used in projects 16, 17, 26, 27, 31, 36.
- **New enemy problem** — A stale permission check lets a user see content created after their access was removed; fixed by evaluating checks at least as fresh as the content's write. Used in project 38. (Module 8)
- **Nginx** — A widely used web server and reverse proxy that can also act as a cache. Used in projects 8, 11, 33. (Module 8)
- **Noisy neighbour** — One tenant whose heavy usage degrades performance for others sharing the same resources. Used in projects 20, 39, 40. (Module 6)
- **North-south vs east-west traffic** — North-south is traffic from clients into the system (handled by a gateway); east-west is traffic between internal services (handled by a service mesh). Used in project 17. (Module 8)
- **NTP (Network Time Protocol)** — The protocol machines use to synchronise their clocks; it can step a clock backwards. Used in project 2.

O

- **O(log N)** — Big-O notation: work grows with the logarithm of the data size, so doubling the data adds only one step. Used in projects 7, 26.
- **Object storage** — A store for large files (objects) addressed by bucket and key, such as Amazon S3 or MinIO; cheap and durable but not a filesystem. Used in projects 11, 12, 20, 22, 23, 27, 31, 33. (Module 16)
- **Observability** — Being able to understand what a running system is doing from its outputs: metrics, logs and traces. Used in projects 9, 37. (Module 9)
- **Offset** — A record's position number within a log partition; consumers save the offset they have processed up to. Used in projects 14, 23, 27, 31. (Module 10)
- **OpenFeature** — A vendor-neutral standard API for evaluating feature flags. Used in project 10. (Module 9)
- **OpenFGA / SpiceDB** — Open-source authorization services that implement the Zanzibar relationship-based model. Used in project 38. (Module 8)
- **OpenStreetMap** — A free, community-built map of the world whose data can be downloaded and used. Used in project 21.
- **OpenTelemetry / OTLP** — The vendor-neutral standard and SDKs for producing traces, metrics and logs; OTLP is its protocol for sending them to collectors. Used in projects 9, 37. (Module 9)
- **Operational transformation (OT)** — A technique for real-time co-editing that rewrites the positions of concurrent edits against each other; it relies on a central server to order operations. Used in project 32. (Module 16)
- **Optimistic vs pessimistic locking** — Pessimistic locks a row before changing it so others wait; optimistic does not lock but checks a version number at write time and retries on conflict. Used in projects 15, 18, 29. (Module 17)
- **Orchestration vs choreography** — In orchestration a central coordinator tells each service what to do next; in choreography each service reacts to the others' events with no coordinator. Used in projects 19, 29, 33, 39, 40. (Module 7)
- **Order book** — All resting buy and sell orders for one symbol, sorted by price and then by arrival time. Used in project 36. (Module 17)
- **Origin shield** — A middle cache tier between edge caches and the origin server that merges many edge misses into one origin fetch. Used in project 33. (Module 14)
- **Orphan (sweeper)** — Data left behind with nothing referring to it (an upload never confirmed, a chunk with no metadata), cleaned up by a background sweeper. Used in projects 11, 31, 37. (Module 16)
- **OSRM** — Open Source Routing Machine, a fast route planner over OpenStreetMap road data. Used in project 34. (Module 15)

- **Outbox (transactional outbox)** — Writing an event into an `outbox` table in the same database transaction as the business change, then publishing it from there, so the change and the event never disagree. Used in projects 4, 14, 18, 19. (Module 10)
- **Outlier ejection** — A load balancer temporarily removing an instance that returns many errors. Used in project 17. (Module 8)
- **Overbooking** — Deliberately selling a little more inventory than exists, because some customers will not show up. Used in project 15. (Module 17)

P

- **p95 / p99 (percentile latency)** — The latency below which 95% or 99% of requests fall; it shows how bad the slow tail is, which averages hide. Used in most projects (29 of 40). (Module 1)
- **Paged KV cache / prefix caching** — LLM-serving techniques (PagedAttention) that store the KV cache in fixed-size pages to cut waste, and share the cache for a common prompt prefix across requests. Used in project 40. (Module 11)
- **Partial fill** — An order executed for only part of its quantity, with the rest still resting or cancelled. Used in project 36. (Module 17)
- **Partition (Kafka / data)** — One independent slice of a topic or dataset; ordering is guaranteed only within a partition, and partitions are spread across servers. Used in projects 5, 6, 8, 13, 14, 18, 19, 22, 23, 26, 27, 28, 29, 30, 31, 33, 34, 36, 37, 39. (Module 10)
- **Partition key** — The field that decides which partition, shard or cell a record belongs to. Used in projects 3, 29, 39. (Module 3)
- **Percentage rollout** — Enabling a feature for a chosen percentage of users, increased step by step. Used in projects 10, 17, 39. (Module 9)
- **pgvector** — A PostgreSQL extension that adds a vector column type and nearest-neighbour indexes (HNSW, IVFFlat). Used in projects 24, 25, 40. (Module 11)
- **Pivot transaction** — In a saga, the step after which the saga can no longer be undone and must complete; irreversible steps are placed at or after it. Used in project 19. (Module 7)
- **Placement service** — The component that chooses which storage nodes hold each chunk, spreading them across failure domains. Used in project 31. (Module 16)
- **Point-in-time / temporal query** — Asking what the state was at a past moment, possible when history is kept as events or versions. Used in projects 18, 29. (Module 3)
- **Politeness (crawler)** — Limiting how often a crawler hits each host so it does not overload websites. Used in project 22. (Module 13)
- **Polling** — Checking repeatedly on a timer whether something changed; simple but wasteful compared with being notified. Used in projects 4, 6, 8, 10, 14, 28. (Module 2)
- **PostGIS** — The PostgreSQL extension for geographic data: geometry types, spatial indexes and distance functions. Used in project 21. (Module 15)
- **PostgreSQL** — A popular open-source relational database with strong transactions; the default durable store in these projects. Used in most projects (32 of 40).
- **Power-law / Zipf distribution** — A skewed distribution where a few items (keys, accounts, posts) get most of the traffic and a long tail gets very little. Used in projects 1, 12, 16, 35. (Module 1)
- **Pre-trade risk check** — Validating an order against the trader's balance and limits before it reaches the order book. Used in project 36. (Module 17)
- **Precomputed top-K** — Storing the best K results for every prefix or key ahead of time so a query is a lookup, not a search. Used in projects 12, 23. (Module 13)
- **Preference list** — In Dynamo-style stores, the N distinct nodes (walking clockwise around the ring) that hold copies of a key. Used in project 26. (Module 13)
- **Presence** — Showing whether users are online, away or typing; short-lived data kept in memory with TTLs. Used in projects 13, 32. (Module 14)
- **Presigned URL** — A temporary URL signed by the server that lets a client upload or download one object directly from storage without credentials. Used in projects 11, 31. (Module 14)
- **Price-time priority** — The exchange matching rule: better prices trade first, and at the same price the earlier order trades first. Used in project 36. (Module 17)

- **Primary / replica** — The primary copy of a database accepts writes; replicas copy its changes and can serve reads or take over. Used in projects 1, 7, 10, 13, 21, 26, 27, 29, 30, 31, 32, 34, 36, 38. (Module 3)
- **Projection / read model** — A query-shaped table or view built by processing events; it can be thrown away and rebuilt from the events. Used in projects 14, 18. (Module 3)
- **Prometheus** — An open-source monitoring system that pulls metrics from targets, stores them as time series and evaluates alert rules. Used in projects 4, 20. (Module 9)
- **Prompt injection** — Text inside retrieved documents or tool output that tries to make an LLM follow attacker instructions; content must be treated as data, not commands. Used in project 40. (Module 11)
- **Pub/sub (publish-subscribe)** — Publishers send messages to a named channel or topic and every current subscriber receives a copy. Used in projects 4, 8, 10, 13. (Module 2)
- **Push vs pull** — Push: the source sends data as it happens. Pull: the receiver asks for data when it wants it. Pull gives the receiver control; push gives lower delay. Used in project 20. (Module 2)

Q

- **QPS / throughput** — Queries (or operations) handled per second; how much work a system completes per unit of time. Used in projects 2, 3, 4, 13, 14, 16, 22, 26, 27, 31, 36, 40. (Module 1)
- **Quadtree** — A tree that splits a map square into four smaller squares only where there are many points, adapting to density. Used in project 21. (Module 15)
- **Queue depth / lag** — How many messages are waiting, or how far behind a consumer is; the main signal for scaling workers. Used in projects 4, 11, 33, 40. (Module 10)
- **Quorum (N, R, W)** — With N copies, a write waits for W acknowledgements and a read for R replies; if R + W > N, every read overlaps the latest write's replicas. Used in projects 26, 30. (Module 7)

R

- **R-tree** — A spatial index that groups nearby shapes into nested bounding rectangles. Used in project 21. (Module 15)
- **RabbitMQ** — RabbitMQ, a widely used open-source message broker with queues, acknowledgements and dead-lettering. Used in projects 4, 11, 33. (Module 2)
- **Radix tree** — A compressed trie where chains of single-child nodes are merged into one node, saving memory. Used in project 12. (Module 13)
- **Raft** — A consensus algorithm that elects a leader and replicates an ordered log to a majority of nodes; used by etcd and many databases. Used in projects 27, 30, 31, 36. (Module 7)
- **RAG (retrieval-augmented generation)** — Answering a question by first retrieving relevant passages from your documents and then giving them to an LLM to answer from. Used in projects 25, 40. (Module 11)
- **Range scan** — Reading all rows whose keys fall in a range, in key order, which sorted indexes make cheap. Used in projects 13, 20.
- **Rate limiting** — Capping how many requests a caller may make in a time window, rejecting or delaying the rest. Used in projects 1, 3, 17, 22, 24, 26, 36, 39. (Module 8)
- **RBAC / ReBAC** — Role-based access control grants permissions through roles; relationship-based access control derives them from relationships (owner of, member of, parent folder). Used in project 38. (Module 8)
- **React** — A popular JavaScript library for building browser user interfaces. Used in projects 32, 33, 37.
- **Read repair** — When a read finds replicas with different versions, the coordinator writes the newest version back to the stale ones. Used in project 26. (Module 13)
- **Read replica** — A copy of the database that receives the primary's changes and serves read queries, slightly behind. Used in projects 7, 21, 38. (Module 3)
- **Read-after-write consistency** — After a successful write, every later read sees it. Used in projects 18, 31. (Module 7)
- **Rebalance (consumer group)** — Redistributing partitions among consumers when one joins or leaves; naive versions pause the whole group. Used in projects 27, 28, 39. (Module 10)

- **Recall@k** — Of the relevant items that exist, the share found in the top k results; the standard retrieval-quality metric. Used in projects 24, 25, 40. (Module 11)
- **Reciprocal rank fusion (RRF)** — Merging ranked lists by summing 1/(k + rank) for each item across lists, a simple way to combine keyword and vector search. Used in project 25. (Module 11)
- **Reconciliation** — Comparing two independently produced records (your ledger and a bank file, a table and storage) and investigating every difference. Used in projects 5, 7, 11, 24, 26, 29. (Module 17)
- **Redis** — A fast in-memory data store with rich types (strings, hashes, sorted sets, streams, pub/sub) used for caches, counters and queues. Used in projects 1, 3, 4, 5, 7, 8, 9, 10, 11, 13, 15, 17, 21, 24, 34, 35, 38, 39. (Module 4)
- **Redis Cluster** — Redis's built-in sharding mode that spreads keys over several nodes by hash slot. Used in projects 1, 3, 35. (Module 4)
- **Redis Streams** — A Redis data type that is an append-only log with consumer groups, more durable than pub/sub. Used in projects 8, 13. (Module 2)
- **Reed-Solomon** — The classic erasure code family used to build k-of-n parity schemes for storage. Used in project 31. (Module 16)
- **Relation tuple** — One fact in a Zanzibar-style store, such as `doc:readme#viewer@user:ana` ("Ana is a viewer of readme"). Used in project 38. (Module 8)
- **Rendition** — One encoded version of a media file at a specific size or quality. Used in projects 11, 33. (Module 14)
- **Replay** — Re-processing stored events or messages from an earlier point to rebuild state or redeliver data. Used in projects 4, 5, 6, 7, 8, 12, 14, 18, 19, 20, 23, 26, 27, 29, 34, 35, 36, 37. (Module 10)
- **Replay protection** — Rejecting an old, captured message that is sent again, typically by checking a timestamp and a unique ID in the signed payload. Used in project 6. (Module 2)
- **Replication** — Keeping copies of data on several machines so it survives failures and can serve more reads. Used in projects 14, 16, 20, 21, 26, 27, 29, 30, 31, 32, 36. (Module 3)
- **Replication factor** — How many copies of each piece of data the system keeps (often 3). Used in projects 26, 27, 31. (Module 3)
- **Replication slot** — A PostgreSQL object that makes the server keep WAL until a consumer (like Debezium) has read it; an idle slot can fill the disk. Used in project 14. (Module 10)
- **Request collapsing / single-flight** — When many requests ask for the same missing item at once, only one goes to the backend and the rest wait for its result. Used in project 33. (Module 4)
- **Request fingerprint** — A hash of a request's body stored with its idempotency key, so a reused key with a different body can be detected. Used in projects 5, 22. (Module 5)
- **Request ID / trace header** — A unique ID added to every request (for example `X-Request-ID` or W3C `traceparent`) so its logs and spans can be found across services. Used in projects 3, 17, 20, 37. (Module 9)
- **Resilience4j** — A Java library providing circuit breakers, retries, bulkheads, rate limiters and time limiters. Used in project 9. (Module 5)
- **Retention** — How long data (logs, metrics, messages) is kept before it is deleted or downsampled. Used in projects 20, 27, 37. (Module 10)
- **Retry amplification / retry budget** — When several layers each retry, one failure multiplies into many calls; a retry budget caps retries to a small share of normal traffic. Used in projects 9, 17. (Module 5)
- **Retry-After** — An HTTP header telling the client how many seconds to wait before retrying. Used in projects 3, 24. (Module 8)
- **Reverse proxy** — A server that receives client requests and forwards them to backend servers, hiding them behind one address. Used in projects 9, 16, 17, 24, 39. (Module 8)
- **Revision** — A monotonically increasing version number for the whole store, assigned to every change; reads and watches can be asked "as of" a revision. Used in projects 28, 30, 38. (Module 7)
- **Ring buffer** — A fixed-size circular array where new entries overwrite the oldest; used for recent-history buffers. Used in projects 30, 36.
- **robots.txt** — A file at a website's root telling crawlers which paths they may fetch and how often (standardised as RFC 9309). Used in project 22. (Module 13)

- **RocksDB** — An embedded key-value storage engine based on an LSM tree, used inside many databases and stream processors. Used in projects 23, 26.
- **Rollback** — Undoing a change: a database transaction's uncommitted writes, or a deployment back to the previous version. Used in projects 4, 12, 14, 15, 17, 19, 29, 39. (Module 9)
- **RPO / RTO** — Recovery point objective: how much recent data you may lose in a disaster. Recovery time objective: how long recovery may take. Used in project 29. (Module 6)

S

- **S3** — Amazon Simple Storage Service, the reference object store; its API is copied by MinIO and many others. Used in projects 11, 31, 33. (Module 16)
- **SaaS** — Software as a service: an application sold as a hosted subscription shared by many customers. Used in project 39.
- **Saga** — A long business transaction split into local steps, each with a compensating action that undoes it if a later step fails. Used in projects 19, 29. (Module 7)
- **Saga log** — The durable record of a saga's current state and completed steps, so it can resume after a crash. Used in project 19. (Module 7)
- **Sandbox** — An isolated environment that limits what untrusted code can access (network, files, credentials). Used in project 40.
- **Schema evolution / upcasting** — Changing the shape of events or messages over time while staying compatible with old ones; upcasting converts old event versions into the current shape when read. Used in projects 14, 18. (Module 10)
- **Schema registry** — A service that stores message schemas and rejects incompatible changes. Used in project 14. (Module 10)
- **Scrubbing** — Periodically re-reading stored data and checking checksums to find and repair silent corruption. Used in project 31. (Module 16)
- **Semantic cache** — Reusing a previous LLM answer when a new question is close in meaning (by embedding similarity) to a cached one. Used in projects 24, 25, 40. (Module 11)
- **Semantic lock** — A status value (such as `PENDING`) that marks a record as in the middle of a saga so other operations treat it carefully. Used in project 19. (Module 7)
- **Sequence CRDT** — A CRDT for ordered lists such as text, where every element has a unique, permanent ID so concurrent inserts merge deterministically. Used in project 32. (Module 16)
- **Sequence number** — A gap-free counter assigned to each message in a stream, giving a total order, duplicate detection and gap detection. Used in projects 13, 27, 32, 36. (Module 14)
- **Sequencer** — The single component that stamps every input with the next sequence number, defining one global order. Used in projects 13, 36. (Module 17)
- **Server-Sent Events (SSE)** — A long-lived HTTP response that the server keeps writing events to; one-way (server to client) with built-in browser reconnect. Used in projects 7, 8, 10, 13, 24, 35. (Module 2)
- **Service mesh / sidecar** — A layer of proxies (sidecars) next to every service that handles service-to-service traffic: retries, encryption, metrics. Used in projects 17, 37. (Module 8)
- **Session window** — A stream window that groups a user's events until a gap of inactivity (such as 30 minutes) closes it. Used in project 23. (Module 10)
- **Shard / sharding** — Splitting data across several databases or nodes by a key, so each holds only part of the data and load. Used in projects 1, 2, 3, 5, 7, 8, 11, 12, 15, 16, 20, 21, 24, 25, 28, 29, 30, 34, 35, 37, 39, 40. (Module 3)
- **Shuffle sharding** — Giving each tenant a random small subset of shared nodes, so two tenants rarely share all of theirs and one bad tenant hurts few others. Used in project 39. (Module 6)
- **Siblings** — Several concurrent versions of one key returned together because the store could not decide which is newer; the application merges them. Used in project 26. (Module 7)
- **Side output** — A separate stream where a stream processor sends records that missed their window, so they are not silently dropped. Used in project 23. (Module 10)
- **SimHash** — A fingerprint where similar documents get similar bit patterns, used to detect near-duplicate pages. Used in project 22. (Module 13)

- **SKIP LOCKED** — A PostgreSQL `SELECT ... FOR UPDATE SKIP LOCKED` option that skips rows other transactions have locked, letting many workers claim different jobs safely. Used in projects 4, 28. (Module 16)
- **Sliding window** — A time window that moves continuously (or in small steps), so each moment sees the last N seconds; used in rate limiting and analytics. Used in projects 3, 9, 23. (Module 8)
- **SLO (service level objective)** — A target for a service's reliability or speed, such as "99.9% of requests succeed within 300 ms". Used in projects 10, 38. (Module 9)
- **Sloppy quorum** — During failures, writing to stand-in nodes outside a key's normal replica set to stay available, which weakens the quorum overlap guarantee. Used in project 26. (Module 13)
- **Snapshot** — A saved copy of the full state at one point (with the log position it reflects), so recovery only replays what came after. Used in projects 10, 12, 18, 23, 26, 29, 30, 32, 36, 38. (Module 3)
- **Snowflake ID** — A 64-bit ID made of a timestamp, a worker ID and a per-millisecond sequence, unique across machines and roughly time-sorted. Used in projects 2, 35. (Module 13)
- **Sorted set (Redis ZSET)** — A Redis type that keeps members ordered by a numeric score, with fast inserts, rank lookups and range reads (`ZADD` , `ZREVRANK` , `ZREVRANGE`). Used in projects 3, 7, 21. (Module 15)
- **Source of truth** — The one authoritative store whose data wins when copies disagree; caches and read models are derived from it. Used in projects 1, 7, 13, 18, 23, 31, 34, 35, 36. (Module 3)
- **Span** — One timed operation inside a trace, with a name, start, duration, parent and attributes. Used in project 37. (Module 9)
- **Split brain** — Two nodes or regions both believing they are the primary and accepting writes, which causes conflicting data. Used in project 29. (Module 7)
- **Spring Boot** — The most popular Java framework for building services; it wires up web servers, database access and configuration automatically. Used in projects 1, 3, 5, 7, 8, 9, 10, 11, 13, 14, 15, 17, 19, 21, 24, 29, 33, 34.
- **SSRF (server-side request forgery)** — Tricking a server into making requests to internal addresses (cloud metadata, private services) on the attacker's behalf. Used in project 6.
- **Stale lock takeover** — Letting a later request take over a lock (or idempotency key) left behind by a crashed request after it is older than a timeout. Used in project 5. (Module 5)
- **Stale read / stale set** — Reading an out-of-date value, or a slow writer putting an old value back into a cache after a newer change. Used in projects 1, 2, 4, 5, 6, 9, 11, 12, 15, 16, 21, 25, 26, 28, 30, 34, 35, 38. (Module 4)
- **State machine** — A model with a fixed set of states and allowed transitions between them (an order or trip lifecycle). Used in projects 19, 20, 30, 34, 36.
- **State vector** — In Yjs-style CRDTs, a summary of how many operations each client has contributed, used to send a peer only what it is missing. Used in project 32. (Module 16)
- **StatefulSet** — A Kubernetes workload type that gives each pod a stable name and its own persistent disk, needed for databases and brokers. Used in projects 26, 27, 31. (Module 9)
- **Stateless service** — A service that keeps no client data between requests, so any instance can handle any request and you can add copies freely. Used in projects 1, 9, 10, 17, 19, 21, 24, 31, 33, 37, 38, 39. (Module 6)
- **Static stability** — Designing a component to keep working with its last known configuration when its control plane is unavailable. Used in project 39. (Module 6)
- **Storage engine** — The part of a database that lays data out on disk and in memory (B-tree, LSM tree, append-only log with index). Used in projects 20, 26, 27. (Module 3)
- **Stream processing** — Continuously computing results over an unbounded flow of events as they arrive (counts per minute, joins, alerts). Used in project 23. (Module 10)
- **Streaming (LLM responses)** — Sending generated tokens to the client as they are produced instead of waiting for the full answer. Used in projects 24, 40. (Module 11)
- **Surge pricing** — Raising prices in an area where demand exceeds supply, to attract supply and ration demand. Used in project 34. (Module 12)
- **Synchronous vs asynchronous replication** — Synchronous waits for the replica before acknowledging a write (no data loss, slower); asynchronous acknowledges first (faster, the latest writes can be lost on failover). Used in projects 29, 31. (Module 3)

T

- **Tail latency** — The latency of the slowest requests (p99, p99.9), which users notice and which grows with fan-out. Used in project 40. (Module 1)
- **Tenant migration** — Moving one customer's data and traffic from one cell or shard to another while the system keeps running. Used in project 39. (Module 6)
- **Testcontainers** — A library that starts real dependencies (PostgreSQL, Redis, Kafka) in Docker containers for integration tests. Used in project 1.
- **Tie-breaking** — A deterministic rule for ordering equal values (the earlier score wins, the lower client ID wins), so every node agrees. Used in projects 7, 32. (Module 15)
- **Time series** — A sequence of timestamped measurements identified by a metric name and labels. Used in project 20. (Module 16)
- **Time to first token (TTFT)** — How long an LLM request takes before the first output token arrives; the latency users feel in chat. Used in projects 24, 25, 40. (Module 11)
- **Time-sortable ID** — An ID whose leading bits are a timestamp, so sorting by ID sorts by creation time (Snowflake, UUIDv7). Used in projects 2, 35. (Module 13)
- **Timeout** — The maximum time a caller waits for a response before giving up, so a slow dependency cannot hold resources forever. Used in projects 1, 3, 4, 5, 6, 8, 9, 17, 19, 22, 24, 27, 28, 30, 34, 38, 40. (Module 5)
- **Timing wheel** — An in-memory circular array of time buckets that makes scheduling and expiring huge numbers of timers cheap. Used in project 28. (Module 16)
- **Token (LLM)** — The unit of text a language model reads and writes, roughly a word piece; usage and cost are counted in tokens. Used in projects 24, 25, 40. (Module 11)
- **Token bucket** — A rate-limiting algorithm: a bucket refills with tokens at a steady rate and each request spends one, allowing short bursts up to the bucket size. Used in project 3. (Module 8)
- **Token budget** — A per-team or per-request cap on how many LLM tokens may be used, reserved before the call and refunded after. Used in project 24. (Module 11)
- **Tombstone** — A marker recording that something was deleted, kept for a while so replicas or merges do not bring the item back. Used in projects 26, 32. (Module 13)
- **Toxiproxy** — A proxy for testing that injects latency, timeouts and connection resets between services on command. Used in projects 9, 17, 26. (Module 5)
- **Trace / trace ID** — The record of one request's path through all services, made of spans that share one trace ID. Used in projects 17, 20, 37. (Module 9)
- **Transaction (database)** — A group of reads and writes that the database applies all together or not at all, isolated from other transactions. Used in projects 4, 5, 6, 13, 14, 15, 18, 19, 23, 27, 28, 29, 30, 34, 36, 38.
- **Transcoding** — Converting media from one encoding or format to another, for example into several resolutions and bitrates. Used in project 33. (Module 14)
- **Trie (prefix tree)** — A tree where each node is one character, so all words sharing a prefix share a path; ideal for autocomplete. Used in project 12. (Module 13)
- **TTL (time to live)** — How long a cached entry, key or lease lives before it expires automatically. Used in projects 1, 3, 11, 13, 16, 22, 23, 26, 30, 34. (Module 4)
- **Tumbling window** — Fixed, non-overlapping time windows (each minute) in stream processing; every event belongs to exactly one. Used in project 23. (Module 10)
- **tus protocol** — An open protocol for resumable file uploads over HTTP. Used in project 33. (Module 14)
- **Two-phase commit (2PC)** — A protocol where a coordinator first asks every participant "can you commit?" and only if all say yes tells them all to commit. Correct but blocking: if the coordinator dies mid-way, participants wait holding locks. Used in projects 19, 23, 29. (Module 7)

U

- **UDP multicast** — Sending one network packet that the network delivers to many subscribers at once; fast and fair, but packets can be lost. Used in project 36. (Module 17)

- **Unique constraint / unique index** — A database rule that rejects a second row with the same value in a column, the simplest reliable guard against duplicates. Used in projects 1, 5, 6, 13, 18, 28, 29.
- **Upsert** — Insert a row, or update it if a row with that key already exists, in one statement. Used in projects 4, 23.
- **URL frontier** — A crawler's prioritised, per-host-throttled queue of URLs still to fetch. Used in project 22. (Module 13)
- **URL normalisation** — Rewriting URLs into one canonical form (lower-case host, no default port, sorted parameters) so duplicates are recognised. Used in project 22. (Module 13)
- **Userset** — In Zanzibar, a set of users defined by a relation on an object, such as "members of group eng" (`group:eng#member`). Used in project 38. (Module 8)
- **UUID / UUIDv7** — A 128-bit universally unique ID that needs no coordination; version 4 is random, version 7 starts with a timestamp so IDs sort by creation time. Used in projects 2, 5, 6, 11, 14, 15, 18, 19, 25, 29, 32, 33, 39, 40. (Module 13)

V

- **VACUUM / table bloat** — PostgreSQL never overwrites rows in place; old row versions pile up (bloat) until `VACUUM` (or autovacuum) cleans them. Used in project 4.
- **Vector clock** — A per-node counter list attached to each version that reveals whether one version happened before another or both were concurrent. Used in project 26. (Module 7)
- **Vector index / vector database** — A store that indexes embeddings for fast nearest-neighbour search. Used in projects 25, 40. (Module 11)
- **Versioned URL** — A URL that includes a version or content hash, so changed content gets a new URL and caches never serve the old version. Used in project 11. (Module 8)
- **Virtual nodes (vnodes)** — Placing each physical server at many points on a hash ring so keys spread evenly and a dead server's load spreads over all survivors. Used in project 16. (Module 3)
- **Visibility timeout** — How long a claimed job or message stays hidden from other workers; if not finished by then, it becomes available again. Used in project 4. (Module 2)
- **vLLM** — An open-source LLM inference server known for continuous batching and paged KV cache. Used in project 40. (Module 11)

W

- **WAL (write-ahead log)** — An append-only log a database writes every change to before applying it, used for crash recovery, replication and CDC. Used in projects 14, 20, 26, 30, 31, 36. (Module 3)
- **WARC** — Web ARChive, the standard file format for storing crawled web pages with their HTTP metadata. Used in project 22.
- **Watch** — A subscription that streams every change to a key or prefix from a given revision onward. Used in projects 9, 11, 20, 30, 38. (Module 7)
- **Watermark (stream processing)** — The processor's estimate that no more events older than time T will arrive, which lets it close event-time windows. Used in projects 23, 27. (Module 10)
- **WebFlux** — Spring's non-blocking (reactive) web framework. Used in projects 8, 24.
- **Webhook** — An HTTP POST your platform sends to a URL a customer registered, to tell their server that an event happened. Used in projects 6, 20, 33. (Module 2)
- **WebSocket** — A persistent, full-duplex connection over which client and server can both send messages at any time. Used in projects 8, 13, 17, 32, 34, 36. (Module 2)
- **Write amplification** — One logical write causing many physical writes, such as one post copied into a million follower timelines. Used in project 35. (Module 12)
- **Write-behind (write-back)** — Writing to a fast store (cache) first and flushing to the database later in batches. Used in project 1. (Module 4)
- **Write-through** — Writing to the cache and the database together on every write, so the cache is always populated. Used in project 1. (Module 4)

X

- **XOR value compression** — Compressing a series of floating-point values by storing each one XOR-ed with the previous one; slowly changing values leave mostly zero bits. Used in project 20. (Module

16)

Y

- **YAML** — A human-friendly text format for configuration files. Used in projects 3, 17.
- **Yjs / Automerge** — Open-source CRDT libraries for building collaborative and offline-first apps. Used in project 32. (Module 16)

Z

- **Zanzibar** — Google's global authorization system that stores relation tuples and answers permission checks by walking the relationship graph. Used in project 38. (Module 8)