Low-Level Design (Java) — Capstone Projects

How to use this book

A **capstone** is a project big enough to pull many chapters together and small enough to finish. Each brief here describes one object-oriented system, or one reusable component, that you build yourself in **Java 25**, with tests, from an empty folder. The handbook chapters teach the pieces: classes, relationships, SOLID, patterns, concurrency. The capstones make you choose which pieces to use, which is the skill the low-level design (LLD) interview and the machine-coding round actually test.

How to pick one. Start at your level, not above it. If you have never written a class diagram for a whole system, do two or three Beginner projects first: they are small enough that you can focus on naming, responsibilities and tests. Intermediate projects add a real pattern or a concurrency problem at their core. Advanced projects are small libraries or engines where correctness under concurrency, undo, or failure is the whole point. If you are preparing for interviews in a few weeks, the project map below flags the classics (parking lot, elevator, movie booking, Splitwise, rate limiter, cache, order book) that come up again and again.

How to use a brief.

1. Read *What it is*, *The problem it solves* and *Requirements*. Write down your own list of nouns (classes) and verbs (methods) before looking at *The architecture*.
2. Compare your design with the class diagram. Differences are fine; be able to explain why yours is better or worse.
3. Build the **milestones in order**. Each one ends with a "done when" check — usually a test that passes. Do not start the next milestone until the check is green.
4. Read *Deep dive* when you hit the hard part, not before: struggling first makes the explanation stick.
5. Only then try the **stretch goals**. They are where the design is stress-tested: if adding one forces you to edit ten classes, your design has a coupling problem worth fixing.
6. Finish with *In the interview*: say the answers out loud, in under a minute each.

Using these projects in interviews. Each *In the interview* section is built to be spoken, not just read. Lead with the **30-second answer**: what you built, the one design decision that matters and why, the hardest problem, and one number. Make sure you can define every entry under **Key terms** in a sentence and point to the class where it lives, because interviewers probe vocabulary first. Practise the Q&As out loud until you can answer without notes, then swap in your own numbers from the build: test counts, operations per second, latency, data sizes. Finally, prepare for the two follow-ups every machine-coding round ends with: "what would you change at 10x load or 10x features?" and "what breaks first?"

What "architecture" means here. In LLD the architecture is the **class diagram** (Mermaid `classDiagram`): which classes exist, which interfaces they implement, who owns whom. The **data model** is the set of key classes, enums and **state machines** (drawn as `stateDiagram-v2`). An entity-relationship diagram (`erDiagram`) appears only in the few projects where saving data to a database is part of the brief.

Colour coding. In the PDF, section headings are colour-coded so you can find your way at a glance: *What it is* and *The problem it solves* introduce the project, *Requirements* frames the problem, *The architecture* and *Deep dive* explain how it works, *Real-world examples* show where it exists for real, *Trade-offs* covers costs and failure modes, *In the interview* and *Self-check* are for practice, and *TL;DR* is the one-line summary.

Level legend.

Level	What it means	Typical time
Beginner	One process, one thread, 5–12 classes. Focus on OOP, SOLID and one or two patterns.	1–2 weekends
Intermediate	A real pattern or concurrency problem at the core. 10–25 classes, thread-safety tests.	1–2 weeks
Advanced	An engine or library: concurrency, undo, failure handling or performance are the point.	2–4 weeks

Shared toolkit for every project. Java 25 (records, sealed interfaces, pattern matching for `switch`, virtual threads), a build tool (Maven or Gradle, current version), **JUnit 6** for tests, **AssertJ** for readable assertions, **Mockito** for test doubles (fake collaborators). Advanced projects add **jcstress** (OpenJDK's harness for testing concurrent code) and **JMH** (OpenJDK's micro-benchmark harness). Keep the domain free of frameworks: a plain `main` method or a small command-line interface is enough.

Java version. The capstones target **Java 25**, while the chapter examples are written and run on **Java 21**. Everything the chapters teach (records, sealed types, pattern matching for `switch`, virtual threads, `java.util.concurrent`) carries over unchanged, and almost every brief can be built on Java 21 as well. The few places that rely on something newer are flagged where they appear: **scoped values** (`ScopedValue`, final in Java 25 via JEP 506; projects 27 and 36), the **JEP 491** fix that stops `synchronized` from pinning virtual threads (Java 24+; project 40), and **structured concurrency** (`StructuredTaskScope`, still a preview API in Java 25 with a different API from Java 21's preview; projects 23, 39 and 40).

> These briefs describe **what** to build and **why**. They contain no solution code on purpose — you write the code. The chapter links under *Skills practised* point to where each idea is taught.

Project map

#	Project	Level	Time	Prerequisites (chapters)
1	Parking Lot	Beginner	1 weekend	Ch 2, 3, 4, 14
2	Vending Machine	Beginner	1 weekend	Ch 2, 11, 14
3	Library Management System	Beginner	1–2 weekends	Ch 2, 3, 15
4	Tic-Tac-Toe (N x N)	Beginner	1 weekend	Ch 2, 11, 17
5	ATM	Beginner	1–2 weekends	Ch 9, 10, 11, 14
6	Snake and Ladder	Beginner	1 weekend	Ch 2, 4, 17
7	Traffic Signal Controller	Beginner	1 weekend	Ch 11, 12, 14
8	Task Manager CLI	Beginner	1–2 weekends	Ch 6, 8, 21
9	Coffee Machine	Beginner	1 weekend	Ch 8, 9, 14
10	Digital Wallet	Beginner	1–2 weekends	Ch 5, 12, 21
11	Elevator System	Intermediate	1–2 weeks	Ch 11, 12, 14
12	Movie Ticket Booking with Seat Locks	Intermediate	2 weeks	Ch 12, 15
13	Splitwise	Intermediate	1–2 weeks	Ch 11, 20
14	Rate Limiter Library	Intermediate	1 week	Ch 11, 13, 20
15	LRU and LFU Cache	Intermediate	1 week	Ch 9, 13, 20
16	Logging Framework	Intermediate	1–2 weeks	Ch 8, 10, 20
17	In-Process Pub/Sub Broker	Intermediate	1–2 weeks	Ch 11, 12, 20
18	Notification Service	Intermediate	1–2 weeks	Ch 8, 11, 20
19	Car Rental System	Intermediate	1–2 weeks	Ch 3, 5, 16
20	Food Delivery Order Lifecycle	Intermediate	2 weeks	Ch 11, 19
21	Meeting Room Scheduler	Intermediate	1–2 weeks	Ch 5, 21
22	Inventory and Point of Sale	Intermediate	2 weeks	Ch 9, 19, 21
23	Unix find Clone	Intermediate	1 week	Ch 9, 10, 21
24	Online Auction	Intermediate	2 weeks	Ch 11, 12, 19
25	Q&A Platform with Reputation	Intermediate	2 weeks	Ch 3, 11, 18
26	In-Memory KV Store with TTL and Transactions	Advanced	3–4 weeks	Ch 10, 12, 13, 20
27	Thread Pool and Task Scheduler	Advanced	2–3 weeks	Ch 12, 13
28	Concurrent Order-Matching Engine	Advanced	3–4 weeks	Ch 12, 13, 19
29	Ride-Hailing Dispatch	Advanced	3–4 weeks	Ch 11, 12, 20
30	Chess with Undo and Replay	Advanced	3 weeks	Ch 10, 11, 17
31	Rules Engine	Advanced	3 weeks	Ch 9, 10, 11
32	Text Editor with Undo/Redo	Advanced	3 weeks	Ch 9, 10
33	Durable Job Queue	Advanced	3–4 weeks	Ch 12, 13, 20

#	Project	Level	Time	Prerequisites (chapters)
34	Double-Entry Ledger	Advanced	3 weeks	Ch 5, 12, 21
35	Circuit Breaker and Retry Library	Advanced	2–3 weeks	Ch 9, 11, 12
36	Dependency Injection Container	Advanced	3 weeks	Ch 4, 8, 9
37	Checkout with Inventory Reservation	Advanced	3–4 weeks	Ch 11, 12, 19
38	Database Connection Pool	Advanced	2–3 weeks	Ch 8, 12, 13
39	Spreadsheet Engine	Advanced	3–4 weeks	Ch 10, 11
40	Concurrent Web Crawler	Advanced	3 weeks	Ch 12, 13, 20

Interview classics (do these first if time is short): 1, 2, 11, 12, 13, 14, 15, 28.

1. Parking Lot

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 2, Ch 3, Ch 4, Ch 14

What it is

A program that models a multi-level car park: vehicles arrive, get a spot that fits them, receive a **ticket** (a record of entry time and spot), and pay a fee when they leave. It is the "hello world" of LLD interviews because it has just enough nouns to practise finding classes, and just enough variation (vehicle sizes, pricing rules) to practise the Open/Closed Principle.

The problem it solves

A real garage operator needs to answer three questions instantly: *is there a spot for this vehicle?*, *where is it?*, and *how much does this person owe?* Doing that by hand causes queues at the gate and lost revenue. In software the hidden problem is change: new vehicle types (electric cars needing chargers), new pricing (weekend flat rate) and new spot-picking rules (nearest to the lift) arrive constantly. A design that hard-codes any of them with `if/else` chains breaks every time the business changes its mind.

Real-world examples

- The parking lot appears in the open-source awesome-low-level-design problem collection and in most LLD interview lists — it is the standard warm-up.
- Java's sealed classes (JEP 409) are a natural fit for a closed family of vehicle and spot types: the compiler knows every subtype, so a `switch` over them can be checked for completeness.

Requirements


Functional

- Several levels, each with spots of type `SMALL` (motorbike), `COMPACT` (car) and `LARGE` (van/bus).
- `park(vehicle)` returns a ticket or a clear "lot full" result. `unpark(ticket)` frees the spot and returns the fee.
- Pricing is per started hour, different per vehicle type. Show free spots per level on a display board.
- Allow a bigger spot to be used when no exact fit is free (a car may take a large spot).

Non-functional

- `park` and `unpark` in O(1) or O(log n) time for lots up to 10,000 spots.
- Adding a new pricing rule or spot-picking rule must not require editing existing classes.
- Every rule covered by unit tests; whole test suite runs in under 2 seconds.

The architecture



- **ParkingLot** — the facade (single entry point) the gate code talks to. It coordinates but holds no pricing or allocation logic itself.
- **Level / ParkingSpot** — the physical layout. A spot knows its type and whether it is free; a level keeps free spots grouped by type.
- **SpotAllocationStrategy** — the Strategy pattern: "first free", "nearest to exit" and "fill lowest level first" are interchangeable classes.
- **PricingStrategy** — computes the fee from a ticket and the exit time. Hourly, flat-weekend and free-first-15-minutes are separate implementations.
- **TicketRepository** — stores open tickets by id. An in-memory map now; a database later without touching the rest.

Data model

Type	Kind	Purpose
`Vehicle`	sealed interface, records `Car`, `Motorbike`, `Van`	plate number, size
`SpotType`	enum	`SMALL`, `COMPACT`, `LARGE`, with `fits(VehicleType)`
`Ticket`	record	id, plate, spot id, entry `Instant`
`Money`	record	amount as `long` minor units (cents) + currency

Tech stack

Component	Choice	Why
Language	Java 25	records and sealed types keep the model tiny
Time	`java.time.Clock` injected	lets tests freeze or advance time
Tests	JUnit 6 + AssertJ	readable, parameterised fee tests
Build	Maven or Gradle	standard layout, one command to test

Milestones

1. **Model.** Vehicles, spot types, `fits` rules. *Done when:* a parameterised test proves every vehicle/spot combination.
2. **Single level.** Park and unpark with "first free" allocation. *Done when:* parking into a full level returns "full", not an exception.

3. **Multi-level + display board.** Free counts per level and type. *Done when:* counts stay correct after 1,000 random park/unpark operations.
4. **Pricing.** Hourly pricing with an injected `Clock`. *Done when:* a test parks at 10:00, moves the clock to 12:01 and sees a 3-hour fee.
5. **Swap strategies.** Add "nearest spot" allocation and "weekend flat" pricing without editing old classes. *Done when:* `git diff` shows only new files plus wiring.

Deep dive: the hard parts

Finding a spot fast. Scanning every spot is O(n). Instead keep, per level, a `Deque<ParkingSpot>` (or a `TreeSet` ordered by distance) of *free* spots for each `SpotType`. Parking pops from the right queue; unparking pushes back. The display board is then just the size of each queue — no counting.

The "bigger spot" fallback. Write the fallback order once, on the enum: `COMPACT.fallbacks()` returns `[COMPACT, LARGE]`. Allocation strategies iterate that list. If the rule lives inside each strategy, you will duplicate it and they will drift apart.

Money and time. Never use `double` for money: `0.1 + 0.2` is not `0.3` in binary floating point. Store cents in a `long` (or use `BigDecimal`). For "per started hour", compute `Duration.between(entry, exit)`, then round *up* with `(minutes + 59) / 60`. Inject a `Clock` instead of calling `Instant.now()`, or your pricing tests will be flaky.

Testing strategy

Unit-test `fits` and each pricing strategy with `@ParameterizedTest` tables. Test `ParkingLot` against a fake `Clock` and a real in-memory repository. Add one randomised test: perform thousands of random park/unpark calls and check the invariant *free + occupied = capacity* after each one.

Trade-offs, scaling and failure modes

Allowing big vehicles nowhere but big spots while letting cars spill into them can starve vans at peak time; some operators reserve a percentage of large spots — a policy that belongs in a strategy. A lost ticket is a real failure mode: support lookup by plate. If two gates call `park` at once, the free-spot queue is shared state; the simplest fix is making `park`/`unpark` `synchronized` on the level (at gate rates of a few cars per second, lock contention is irrelevant).

Stretch goals

- Electric-vehicle spots with chargers, billed per kWh as a decorator on the pricing strategy.
- Reservations made in advance, held for 15 minutes past their start.
- Two entry gates running on separate virtual threads, with a concurrency test proving no spot is ever assigned twice.

Skills practised

- Ch 2 — OOP fundamentals: encapsulation of spot state.
- Ch 3 — Relationships and UML: composition (lot owns levels owns spots).
- Ch 4 — SOLID principles: Open/Closed via strategies.
- Ch 14 — Everyday objects: the reference parking-lot case study.

In the interview

> **30-second answer:** I built a multi-level parking lot where `ParkingLot` is a thin facade and the two things the business keeps changing, spot allocation and pricing, are Strategy interfaces. Each level keeps a queue of free spots per spot type, so `park` and `unpark` are O(1) and the display board is just queue sizes. The hardest part was keeping fees and tests deterministic, which I solved by storing money as `long` cents and injecting a `java.time.Clock`. Adding "weekend

flat rate" or "nearest spot" was a new class plus one line of wiring, and a randomised test proves free plus occupied always equals capacity.

Key terms to know:

- **Facade** — one simple entry point hiding several collaborators; `ParkingLot` is what the gate code calls.
- **Strategy pattern** — an interface with interchangeable implementations chosen at runtime; `SpotAllocationStrategy` and `PricingStrategy`.
- **Open/Closed Principle (OCP)** — add behaviour by adding classes, not editing old ones; milestone 5 checks this with `git diff`.
- **Composition** — a whole owns its parts' lifetime; the lot owns levels, a level owns spots.
- **Sealed interface** — a type whose permitted subtypes are listed, so `switch` over `Car`, `Motorbike`, `Van` is checked for completeness.
- **Value object / record** — immutable data compared by value; `Ticket` and `Money`.
- **Minor units** — storing money as whole cents in a `long` to avoid floating-point rounding.
- **Injected clock** — passing `java.time.Clock` in so tests control "now".
- **Invariant** — a fact that must always hold; here *free + occupied = capacity*.

Q: Why is pricing a strategy and not a method on `Vehicle`?

A: Pricing is a business policy that changes independently of what a vehicle is. Putting it on `Vehicle` would mean editing vehicle classes whenever marketing runs a promotion, which breaks the Single Responsibility Principle. As a strategy, a new tariff is a new class and the vehicle model stays untouched.

Q: How do you find a free spot in O(1) instead of scanning?

A: Each level keeps a `Deque<ParkingSpot>` of free spots for each `SpotType`. Parking polls from the right deque and unparking pushes the spot back, both O(1). If allocation needs "nearest first", a `TreeSet` ordered by distance gives O(log n) instead.

Q: How do you let a car use a large spot without duplicating the rule in every strategy?

A: Put the fallback order on the enum once, for example `COMPACT.fallbacks()` returns `[COMPACT, LARGE]`. Every allocation strategy iterates that list. If each strategy encoded its own fallback, they would drift apart and give inconsistent answers.

Q: How would you handle two gates parking at the same time?

A: Spot assignment must be atomic so one spot is never handed out twice. The simplest fix is to make `park` / `unpark` `synchronized` per level; a `ConcurrentLinkedDeque` whose `poll()` hands each spot out exactly once also works. At a few cars per second contention is irrelevant, so I pick the simpler lock and prove it with a two-thread test.

Q: How do you test time-based pricing?

A: Inject `java.time.Clock`. Tests use `Clock.fixed(...)` or a small mutable test clock, so "two hours later" is one line instead of a two-hour wait. Calling `Instant.now()` directly would make the tests flaky.

Q: Code-level: how do you charge "per started hour"?

A: Take the duration in minutes and round up with integer arithmetic, never `double`.

```
long minutes = Duration.between(ticket.entry(), exit).toMinutes();
long hours = Math.max(1, (minutes + 59) / 60);   // 121 min -> 3 hours
return new Money(hours * ratePerHourCents, currency);
```

The `Math.max(1, ...)` decides whether a 0-minute stay costs one hour; state that rule explicitly.

Q: What changes at 10x the spots or 10x the gates?

A: 100,000 spots still fit in memory and the deques stay O(1), so the data structures survive. What breaks first is the single lock if one lot-wide lock was used, so lock per level, and the in-memory `TicketRepository`, which loses open tickets on restart; swap it for a database behind the same interface. Many lots would become separate `ParkingLot` instances, not one giant object.

Q: What happens if a driver loses the ticket or the process crashes?

A: Support lookup by plate, which needs an index from plate to open ticket. A crash with an in-memory repository loses all open tickets, which is acceptable for the exercise but not in production; persisting tickets on `park` and rebuilding free-spot queues from them on start fixes it.

Q: How do you prove the allocation logic is correct?

A: Parameterised tests for every vehicle/spot fit, fee tables per pricing strategy, and one randomised test that performs thousands of park/unpark calls and checks the invariant after each step. For concurrency, two virtual threads parking into a nearly full level must never receive the same spot.

Common mistakes in answers:

- Using `double` for fees; say "cents in a `long` or `BigDecimal`" and explain why `0.1 + 0.2` is not `0.3`.
- Making `Car extends Vehicle` carry pricing or parking logic; behaviour that varies by policy belongs in strategies.
- Scanning every spot on each `park`; interviewers expect the per-type free list.

TL;DR

A facade over levels and spots, with allocation and pricing as swappable strategies, money in integer cents and time from an injected clock.

2. Vending Machine

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 2, Ch 11, Ch 14

What it is

A software model of a snack vending machine: the user inserts coins, picks a product, receives it and gets change back. The machine behaves differently depending on its **state** (idle, has money, dispensing, out of service), which makes it the textbook exercise for the **State pattern** — each state is its own class that decides what each button press means.

The problem it solves

Without the State pattern, every method (`insertCoin`, `select`, `cancel`) starts with a growing `if (state == ...)` block, and adding a new state ("maintenance mode") means editing every one of them. The real-world problem is equally sharp: the machine must never dispense without payment, never keep money for a product it cannot deliver, and must give correct change with the coins it actually has.

Real-world examples

- Java 21+ pattern matching for switch (JEP 441) lets you write the transition table as an exhaustive `switch` over a sealed set of events — a lightweight alternative to one-class-per-state.

- Production state-machine libraries such as Spring Statemachine model exactly these ideas — states, events, transitions, guards and actions — for business workflows.

Requirements


Functional

- Accept coins of fixed denominations (e.g. 5, 10, 25, 100 cents). Reject unknown coins.
- Select a product by slot code. Dispense if paid enough and in stock, otherwise explain why.
- Return change using the fewest coins available. Refuse the sale up front if exact change is impossible.
- Cancel at any time before dispensing returns all inserted money.
- Admin: restock products and coins, collect cash, put the machine out of service.

Non-functional


- No sequence of user actions may lose or create money: *coins in = coins out + revenue*.
- New states must be addable without editing existing state classes.
- 100% branch coverage on the state transitions.

The architecture



- **VendingMachine** — the context object. It forwards every button press to its current `State` and holds the shared parts.
- **State implementations** — one class per state. `IdleState.select` says "insert money first"; `HasMoneyState.select` checks price and stock.
- **Inventory** — slot code to product and quantity.
- **CoinBox** — counts of each coin denomination inside the machine, plus the coins of the current transaction kept separately until the sale completes.
- **ChangeMaker** — computes change from available coins (a strategy, so you can swap greedy for exact).

Data model



Key types: `Coin` enum (value in cents), `Product` record (name, price), `Slot` (product + count).

Tech stack

Component	Choice	Why
States	interface + one class each (or sealed + switch)	compare both styles
Money	`int` cents	coins are integers anyway
Tests	JUnit 6, AssertJ	assert on states and coin counts
CLI	plain `Scanner` loop	enough to demo

Milestones

1. **Coins and inventory.** *Done when:* inserting an unknown coin is rejected and counted nowhere.
2. **Idle and HasMoney states.** Insert and cancel. *Done when:* cancel returns exactly the inserted coins.
3. **Selling.** Dispensing with change. *Done when:* buying a 65-cent item with a 100-cent coin returns 35 cents as 25 + 10.
4. **Change feasibility.** *Done when:* when change cannot be made, the sale is refused and the money stays refundable.
5. **Out of service + admin.** *Done when:* every user action in `OutOfService` is rejected with a message.

Deep dive: the hard parts

Change-making. Greedy (take the largest coin that fits, repeat) is optimal for standard coin systems like 1/5/10/25, but fails with odd denominations or when some coins run out: owing 30 with only 25s and 10s, greedy takes 25 and gets stuck at 5, while 10+10+10 works. Implement a small dynamic-programming or backtracking `ChangeMaker` that respects coin counts; the numbers are tiny so it is fast.

Where the transaction's coins live. Keep the current customer's coins in a separate "escrow" until the sale completes. Only then merge them into the cash box. This makes cancel trivial and guarantees the refund is exactly what was inserted.

Who changes the state? Either the states call `machine.setState(next)` (simple, but states know each other) or each handler returns the next state (states stay independent and testable). The second style is easier to unit-test: call a method, assert the returned state.

Testing strategy

One test class per state, asserting the next state and side effects. A property test (with jqwik or a plain random loop) runs random action sequences and checks the money-conservation invariant after each step. Mock nothing: everything is in memory and fast.

Trade-offs, scaling and failure modes

One-class-per-state is very clear but scatters the transition table over files; a sealed `switch` keeps the whole table on one screen but grows as states multiply. Real machines face power loss mid-dispense; a robust design writes "about to dispense slot A3" before acting so it can reconcile on restart. A jammed product (motor turns, nothing drops) should trigger a refund path, not a silent loss.

Stretch goals

- Card payments via a `PaymentMethod` interface, alongside coins.
- A `Display` observer that shows messages, decoupled from states.
- Persist inventory and coin counts so a restart resumes correctly.

Skills practised

- Ch 11 — Behavioral patterns 2: State and Strategy.
- Ch 14 — Everyday objects: vending and coffee machine case studies.
- Ch 2 — OOP fundamentals: polymorphism replacing conditionals.

In the interview

30-second answer: I built a vending machine using the State pattern: `VendingMachine` is the context and `Idle`, `HasMoney`, `Dispensing` and `OutOfService` are separate classes that decide what each button means. The current customer's coins sit in an escrow until the sale completes, so cancel returns exactly what was inserted. The hard part was change: greedy fails when some coins run out, so my `ChangeMaker` searches using real coin counts and refuses the sale up front if exact change is impossible. A random-action test checks that coins in always equal coins out plus revenue.

Key terms to know:

- **State pattern** — each state is an object implementing the same interface; the context delegates to the current one.
- **Context** — the object whose behaviour changes with state; `VendingMachine`.
- **Transition** — moving from one state to another on an event, such as `HasMoney -> Dispensing` on a paid `select`.
- **Escrow** — holding the customer's coins apart from the cash box until the sale is final.
- **Greedy change-making** — always take the largest coin that fits; optimal only for canonical coin systems with unlimited coins.
- **Dynamic programming / backtracking** — exhaustive but cheap search that respects coin counts; used in `ChangeMaker`.
- **Invariant (money conservation)** — coins inserted = coins returned + price of goods sold.
- **Sealed switch alternative** — a single exhaustive `switch` over sealed events/states instead of one class per state.

Q: Why State and not a big switch?

A: Each state's rules live in one class, so adding `Maintenance` means one new class rather than editing every method. The cost is that the transition table is scattered over files. With three or four states a sealed `switch` that keeps the table on one screen is perfectly fine, and I say which I chose and why.

Q: Is greedy change-making always correct?

A: Only for "canonical" coin systems with unlimited coins, like 1/5/10/25. Owing 30 with only 25s and 10s, greedy takes 25 and is stuck at 5, while 10+10+10 works. With limited coins you need a small search or dynamic programming over the coin counts.

Q: Who should change the state: the state objects or the machine?

A: Either states call `machine.setState(next)`, which is simple but means states know each other, or each handler returns the next state and the machine applies it. The second style is easier to unit-test because you call a method and assert the returned state, with no machine needed.

Q: What invariant would you test, and how?

A: Money conservation: coins inserted equal coins returned plus the price of goods dispensed. A property test (jqwik or a seeded random loop) fires thousands of random actions and checks the invariant after every step. It finds ordering bugs, such as cancel after a refused sale, that hand-written tests miss.

Q: What happens when exact change cannot be made?

A: The sale is refused before dispensing, the state stays `HasMoney`, and the escrowed coins stay refundable. Checking feasibility first avoids the worst outcome: product dispensed and the machine owes change it cannot pay.

Q: Code-level: what does the state interface look like if handlers return the next state?

A: Each method takes the machine (for inventory and coins) and returns the following state.

```
sealed interface State permits Idle, HasMoney, Dispensing, OutOfService {
    State insertCoin(VendingMachine m, Coin c);
    State select(VendingMachine m, String slot);
    State cancel(VendingMachine m);
}
```

Sealing it means a `switch` over states elsewhere (for display) is checked for completeness.

Q: What happens on power loss mid-dispense or a jammed product?

A: Write an intent record such as "about to dispense A3, escrow 100" before driving the motor, and on restart reconcile it with the sensor: refund if nothing dropped. A jam (motor turned, drop sensor saw nothing) takes the refund path, never a silent loss.

Q: How would you add card payments?

A: Introduce a `PaymentMethod` interface with coin and card implementations; the states ask "is the price covered?" instead of counting coins. Change-making only applies to the coin implementation, so the card path skips it.

Common mistakes in answers:

- Claiming greedy change is always optimal; it fails with odd denominations or empty coin tubes.
- Merging customer coins into the cash box immediately, which makes cancel and refunds error-prone.
- Saying "State pattern" without explaining what each state does differently for the same button.

TL;DR

A context object delegating to state classes, an escrow for the current customer's coins, and a change-maker that respects real coin counts.

3. Library Management System

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** Ch 2, Ch 3, Ch 15

What it is

A system for a lending library: members search the catalogue, borrow and return copies, place holds on books that are out, and pay fines for late returns. The key modelling idea is the difference between a **book** (the title, identified by ISBN) and a **book item** (one physical copy with a barcode) — a distinction many beginners miss.

The problem it solves

Libraries lend thousands of physical copies to thousands of people. Without a system, nobody knows who has what, when it is due, or who is next in line for a popular title. In design terms the problem trains you to separate catalogue data from inventory, to enforce business rules (borrow limits, hold queues) in one place, and to keep notification and fine logic out of the core lending flow.

Real-world examples

- Koha is a widely used open-source integrated library system (ILS); its circulation module handles exactly these flows — checkout, return, holds and fines.
- The ISBN-versus-copy split is the same "type versus instance" split found in retail inventory and car rental (project 19).

Requirements


Functional

- Catalogue: add books (ISBN, title, authors, subject) and copies. Search by title, author, subject.
- Members can borrow up to 5 items for 14 days, renew once if no hold exists, and return.
- Holds: if no copy is free, a member joins a first-in-first-out queue for that ISBN. On return, the copy is held for the first person in the queue for 3 days.
- Fines: a fixed amount per day late, capped at the item's price. Members with unpaid fines over a threshold cannot borrow.
- Notify members when a hold is ready or an item is due tomorrow.

Non-functional


- Search returns in under 50 ms for 100,000 titles in memory.
- Business rules (limits, durations, fine rates) configurable without code changes.
- All date logic testable with an injected clock.

The architecture



- **Catalog** — owns books and indexes for search (maps from lowercase author/title tokens to ISBNs).
- **Book / BookItem** — title-level data versus a physical copy with status and location.
- **Member / Loan** — a loan links one member to one copy with due and returned dates.
- **CirculationService** — the application service enforcing every lending rule. Controllers or a CLI call only this.
- **HoldQueue** — per-ISBN FIFO of member ids.
- **FinePolicy / Notifier** — interfaces so the fine formula and the delivery channel (email, SMS, console) can change independently.

Data model



Persistence is optional here; in memory, repositories are interfaces backed by `HashMap`s.

Tech stack

Component	Choice	Why
Domain	Java 25 records + classes	`Book` is a record, `BookItem` is mutable
Search	in-memory inverted index	teaches indexing without a search engine
Time	`Clock` + `LocalDate`	due dates are calendar days
Tests	JUnit 6, AssertJ, Mockito for `Notifier`	verify notifications without sending

Milestones

1. **Catalogue and search.** *Done when:* searching "tolkien" finds all of his books regardless of case.
2. **Checkout and return.** *Done when:* a member at the 5-item limit is refused with a specific reason.
3. **Holds.** *Done when:* returning a copy with two people queued puts it on the hold shelf for the first and notifies them (verified with a Mockito mock).
4. **Fines.** *Done when:* a 3-day-late return produces the configured fine, and a member over the threshold cannot borrow.
5. **Renewals and reminders.** *Done when:* renewal is refused if anyone is waiting for that ISBN.

Deep dive: the hard parts

Holds are per title, not per copy. A member wants "any copy of this ISBN". So the queue hangs off the `Book`, and on *any* copy's return you check that queue. Getting this wrong (queue per copy) makes members wait for one specific copy while others sit on the shelf.

Where rules live. Borrow limits, durations and fine rates should be in a `LendingRules` value object passed to the service, not sprinkled as constants. Different member types (student, staff) then become different rule objects, not subclasses of `Member`.

Search index. Tokenise titles and author names into lowercase words and keep `Map<String, Set<String>>` from token to ISBNs. A query with several words intersects the sets. This is the core idea of an inverted index, the structure behind every search engine.

Testing strategy

Test `CirculationService` with in-memory repositories and a mock `Notifier` (`verify(notifier).holdReady(member, book)`). Use a mutable test clock to jump 15 days and check overdue logic. Parameterise fine tests over days late, including the cap.

Trade-offs, scaling and failure modes

In memory, a restart forgets everything — acceptable for the exercise, and repositories as interfaces make swapping to a database a local change. A hold shelf item uncollected for 3 days must expire automatically; that needs a scheduled job, which is a source of bugs if it runs twice — make it idempotent (safe to run repeatedly). Deep inheritance (`StudentMember extends Member`) is tempting but brittle; prefer composition with a membership type.

Stretch goals

- Persist to PostgreSQL behind the repository interfaces.
- Inter-branch transfers: a hold can be filled from another branch's copy.
- Ranking search results by how many words matched.

Skills practised

- Ch 2 — OOP fundamentals: identity versus value objects.
- Ch 3 — Relationships and UML: composition versus aggregation.

- Ch 15 — Booking 1: the library case study.
- Ch 5 — Design principles: information expert, separation of concerns.

In the interview

30-second answer: I built a library system whose key modelling decision is splitting `Book` (the title, by ISBN) from `BookItem` (one physical copy with a barcode and status). All lending rules, borrow limits, renewals, holds and fines, live in one `CirculationService` that reads a configurable `LendingRules` object. Holds are a FIFO queue per ISBN, so any returned copy goes to the first waiter. Search uses an in-memory inverted index that answers in well under 50 ms over 100,000 titles, and all date logic runs against an injected clock.

Key terms to know:

- **Type versus instance** — `Book` is the title shared by copies; `BookItem` is one copy with its own state.
- **Application service** — `CirculationService`, the one class coordinating members, items and rules for a use case.
- **Composition versus aggregation** — a book owns its copies (composition); a member refers to loans that outlive the link (aggregation).
- **Inverted index** — a map from word to the set of ISBNs containing it; multi-word queries intersect sets.
- **Hold queue** — FIFO of member ids per ISBN; on return the copy goes to the hold shelf for the head.
- **Rules as a value object** — `LendingRules` holds limits, durations and fine rates so member types are data, not subclasses.
- **Idempotent job** — a scheduled task that is safe to run twice, such as expiring hold-shelf items.
- **Test double (mock)** — a fake `Notifier` verified with Mockito.

Q: Why separate `Book` and `BookItem`?

A: Title data is shared by all copies; status, barcode and location belong to each copy. Merging them duplicates title data on every copy and pushes you towards holds per copy instead of per title, so members wait for one specific copy while another sits on the shelf.

Q: Where would you put the borrow-limit check?

A: In the circulation service, using the `LendingRules` object, because it is the one place that already coordinates members, items and rules. Putting it in `Member` would make the member class know about inventory and fines.

Q: How do student and staff members get different limits without inheritance?

A: Each member has a membership type that maps to a `LendingRules` instance (limit 5 for students, 10 for staff). That is composition over inheritance: adding "visiting scholar" is new configuration, not a new subclass, and rules can change without code changes.

Q: How does the search index work and what is its complexity?

A: At insert, tokenise title and authors to lowercase words and add the ISBN to `Map<String, Set<String>>` under each word. A query looks up each word (O(1) each) and intersects the sets, starting with the smallest. Cost depends on the size of the result sets, not the 100,000 titles.

Q: How do you avoid sending the hold-ready email twice?

A: Record on the hold that the notification was sent, and make the sender check that flag before sending. The operation becomes idempotent, so a retried job or double `checkin` does no harm.

Q: What happens if the hold-expiry job runs twice or a hold owner never collects?

A: The job checks "on hold shelf and older than 3 days" before acting and moves the copy to the next waiter or back to Available, so a second run finds nothing to do. Without that guard, a double run could skip a waiter.

Q: How do you test overdue fines?

A: Use a mutable test clock: check out, advance 17 days, check in, and assert the fine. Parameterise over days late including the cap at the item price, and verify the over-threshold member is refused at checkout.

Q: What changes at 10x members and titles, or across branches?

A: Memory and the inverted index still cope at a million titles, but restarts lose data, so repositories move to a database behind the same interfaces. Concurrent checkouts of the last copy need a transaction or optimistic version check on `BookItem`. Inter-branch holds make the hold queue span branches with a transfer step.

Common mistakes in answers:

- Modelling only `Book` with a `count` field; you then cannot track which copy is late or lost.
- Using deep inheritance (`StudentMember extends Member`) for rule differences.
- Putting the hold queue on the copy instead of the title.

TL;DR

Split titles from copies, put lending rules in one service, queue holds per title, and test dates with an injected clock.

4. Tic-Tac-Toe (N x N)

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 2, Ch 11, Ch 17

What it is

The noughts-and-crosses game, generalised: an N x N board, K-in-a-row to win, two or more players who can be humans or computer players. The project is small enough to finish quickly but rich enough to practise separating rules, board, players and user interface.

The problem it solves

Most first attempts put everything in one `Game` class with a 3x3 array and eight hard-coded win lines. That code cannot grow to a 15x15 board with five-in-a-row, cannot plug in a computer opponent, and cannot be tested without typing moves. The design problem is to find the seams: who validates a move, who detects a win, who decides the next move.

Real-world examples

- The computer player is the classic application of the minimax algorithm, which searches the game tree assuming both sides play optimally.
- Generalised K-in-a-row on a large board is the game Gomoku; the same O(K) win check you build here is what keeps it fast.

Requirements

Functional


- Configurable N (3 to 15), K (3 to N) and 2–4 players with distinct symbols.
- Players take turns. Reject moves outside the board or on occupied cells.

- Detect win, draw (board full) and continue states after each move.
- Player types: human (console input) and computer (random, then minimax for 3x3).
- Undo the last move.

Non-functional

- Win detection after a move in O(K), not O(N^2).
- Game logic has zero dependency on the console — the UI is swappable.
- Minimax on an empty 3x3 board responds in under 1 second.

The architecture



- **Game** — owns the turn order, history (for undo) and status. It is the only class that changes the board.
- **Board** — a grid of cells; knows nothing about winning.
- **WinChecker** — the win rule as a strategy, so variants (e.g. "connect four with gravity") plug in.
- **Player** — humans and bots behind one interface; the game loop does not care which.
- **GameObserver** — the Observer pattern; the console view (or a future GUI) subscribes to moves and results.

Data model

Type	Kind	Notes
`Position`	record (row, col)	value object, validated in constructor
`Move`	record (position, symbol)	pushed onto a history deque
`Symbol`	record or enum	`X`, `O`, `#`, `@`
`GameStatus`	sealed: `InProgress`, `Won(player)`, `Draw`	exhaustive switch in the UI

Tech stack

Component	Choice	Why
Model	records + sealed status	immutable values, exhaustive handling
UI	console via `ConsoleView` observer	swappable for JavaFX later
AI	minimax with alpha-beta pruning	teaches recursion and pruning
Tests	JUnit 6 + AssertJ	scripted games as tests

Milestones

1. **Board and moves.** *Done when:* invalid moves are rejected with specific errors.
2. **Win checking in O(K).** *Done when:* tests cover horizontal, vertical, both diagonals and near-misses on a 7x7 board with K=4.
3. **Game loop with observers.** *Done when:* a scripted game of `Player` stubs plays to a win with no console.
4. **Undo.** *Done when:* undo after a winning move returns status to in-progress.
5. **Computer players.** *Done when:* minimax never loses a 3x3 game in 1,000 games against the random player.

Deep dive: the hard parts

Checking a win in O(K). Only the last move can create a win. From it, walk in four directions — horizontal, vertical, two diagonals — counting consecutive same symbols both ways. If any direction reaches K, it is a win. There is no need to scan the whole board.

Minimax and pruning. Minimax recursively tries every move, scoring terminal positions +1/-1/0, and assumes the opponent picks the worst score for you. On 3x3 that is at most 9! paths, fine; on larger boards it explodes. Alpha-beta pruning stops exploring a branch once it cannot beat an option already found, which typically cuts the work dramatically. For N greater than 3, cap the depth and use a heuristic (count open lines).

Undo without copying the board. Keep a `Deque<Move>` of history. Undo pops the last move and clears that cell, then rewinds the turn index. This is the Command pattern in miniature, and the same trick that makes minimax cheap: make a move, recurse, undo.

Testing strategy

Describe boards as strings in tests (`"XO.|.X.|..X"`) and parse them into `Board`, making win tests readable. Stub players returning scripted moves let you test the full game loop. Property: after any sequence of legal moves, the number of each symbol differs by at most one (for two players).

Trade-offs, scaling and failure modes

A 2D `char[][]` is simplest; a flat `int[]` is faster and easier to copy for AI search. Observers make the UI pluggable but add indirection — for a pure console toy, direct printing is acceptable if tests do not need it. A slow AI blocks the game loop; run it on a separate thread with a timeout in a GUI version.

Stretch goals

- Network play: two clients, a server-side `Game` per match.
- Ultimate tic-tac-toe (a 3x3 board of 3x3 boards) via the Composite pattern.
- A memoised minimax with a transposition table keyed by board hash.

Skills practised

- Ch 17 — Games: the tic-tac-toe case study.
- Ch 11 — Behavioral patterns 2: Strategy and Observer.
- Ch 2 — OOP fundamentals: interfaces for players.

In the interview

> **30-second answer:** I built an N x N, K-in-a-row tic-tac-toe where `Game` owns turn order and history, `Board` only stores cells, `WinChecker` is a strategy and humans and bots both implement `Player`. Win detection looks only at lines through the last move, so it is O(K) instead of rescanning the board. Undo is a stack of moves, which also lets the minimax player do make-move,

recurse, undo without copying the board. With alpha-beta pruning the 3x3 bot never lost in 1,000 games against a random player and answers in well under a second.

Key terms to know:

- **Separation of concerns** — board storage, rules, players and UI are separate classes.
- **Strategy** — `WinChecker` and `Player` implementations are swappable.
- **Observer pattern** — `ConsoleView` subscribes to moves and results so the UI can change.
- **O(K) win check** — counting same symbols in four directions from the last move only.
- **Command pattern / history stack** — each `Move` is recorded so it can be undone.
- **Minimax** — recursive game search assuming both players play optimally.
- **Alpha-beta pruning** — skipping branches that cannot change the minimax result.
- **Sealed status** — `GameStatus` is `InProgress`, `Won` or `Draw`, handled by an exhaustive switch.

Q: How do you detect a win efficiently on a large board?

A: Only the last move can create a win. From it, walk in four directions (row, column, two diagonals), counting consecutive matching symbols both ways; if any count reaches K it is a win. That is O(K) per move rather than O(N^2).

Q: How would you add a computer player?

A: It implements `Player.nextMove(board)`. The game loop is unchanged because it only knows the interface, which is the point of programming to interfaces (Dependency Inversion). A random bot, a minimax bot and a network player are all the same shape.

Q: How does undo work?

A: A `Deque<Move>` of history; undo pops the last move, clears that cell, moves the turn pointer back and resets status to in-progress. No board copies are needed.

Q: What is alpha-beta pruning and why does it matter?

A: Alpha is the best score the maximiser can already guarantee, beta the best for the minimiser. When a branch's score can no longer beat what the other side already has, you stop exploring it. It returns the same move as plain minimax but often searches far fewer nodes, which is what makes the 3x3 bot instant.

Q: Why can't minimax play a 15x15 board, and what do you do instead?

A: The game tree grows roughly as (cells remaining)! so it explodes beyond 3x3 or 4x4. Cap the search depth and score non-terminal boards with a heuristic such as counting open lines, and use a transposition table to avoid re-evaluating the same position.

Q: Code-level: what does the direction count look like?

A: Count from the last move in one direction and its opposite.

```
int count(Position p, int dr, int dc, Symbol s) {
    int n = 0, r = p.row() + dr, c = p.col() + dc;
    while (board.inBounds(r, c) && board.at(r, c) == s) { n++; r += dr; c += dc; }
    return n;
}
// win if 1 + count(p,dr,dc,s) + count(p,-dr,-dc,s) >= k for any of (0,1),(1,0),(1,1),(1,-1)
```

Q: How do you test the game without a console?

A: Parse boards from strings like `"XO.|.X.|..X"` for readable win tests, and use stub players returning scripted moves to drive the whole loop. A property test checks that symbol counts never differ by more than one for two players.

Q: What breaks if the AI is slow in a GUI version?

A: A slow `nextMove` blocks the UI thread. Run the bot on a separate thread (a virtual thread is fine) with a time budget, and fall back to the best move found so far when time runs out.

Common mistakes in answers:

- Hard-coding the eight 3x3 win lines; it does not generalise to N and K.
- Letting `Board` decide wins or print itself, which mixes storage, rules and UI.
- Claiming alpha-beta changes the chosen move; it only skips work.

TL;DR

Board, rules, players and view as separate pieces; O(K) win check from the last move; history stack for undo and AI search.

5. ATM

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** Ch 9, Ch 10, Ch 11, Ch 14

What it is

The software inside a cash machine: read a card, check the PIN, then let the customer check a balance, withdraw cash or deposit. The ATM talks to the bank over a network, holds a limited supply of notes, and must never pay out cash the bank has not approved.

The problem it solves

An ATM is a small machine coordinating unreliable parts: a card reader, a keypad, a cash dispenser that can jam, and a remote bank that can time out. The design teaches you to model a session as a state machine, to hide hardware and the bank behind interfaces, and to dispense notes using a **Chain of Responsibility** (each note-size handler pays what it can and passes the rest on).

Real-world examples

- Card-based ATM transactions travel to the bank as financial messages in formats such as ISO 8583, which defines request/response pairs and reversal messages — the same "authorise, then reverse if dispensing fails" flow you build here.
- The note-dispensing chain is the standard teaching example for Chain of Responsibility, covered in the handbook's behavioral patterns chapter.

Requirements


Functional

- Insert card, enter PIN (3 wrong attempts retain the card).
- Balance enquiry, cash withdrawal in multiples of the smallest note, deposit, and eject card.
- Dispense using the fewest notes possible from what the cassettes hold.
- If the dispenser fails after the bank approved, send a reversal so the account is credited back.
- Daily withdrawal limit per card.

Non-functional


- Never dispense without an approval. Never debit without either dispensing or reversing.
- Bank calls time out after 10 seconds, with a clear message to the customer.
- Hardware and bank are interfaces; the whole session is testable with fakes.

The architecture



- **Atm** — the context: holds the session, current state and the hardware facades.
- **AtmState** — Idle, CardInserted (waiting for PIN), Authenticated (menu), plus OutOfCash/Maintenance.
- **BankGateway** — the adapter to the bank's network protocol. Tests use a fake.
- **CashDispenser** — the hardware interface; a fake can be told to jam.
- **NoteHandler chain** — computes a dispense plan from the largest note down, respecting cassette counts.

Data model



Key types: `Card` (record: number, expiry), `Session` (card, PIN attempts, withdrawn today), `AuthResult` (sealed: `Approved(authId)`, `Declined(reason)`).

Tech stack

Component	Choice	Why
States	State pattern	many buttons, behaviour per state
Dispensing	Chain of Responsibility	add a new note size as one class
Bank	`BankGateway` adapter + fake	no network in tests
Tests	JUnit 6, Mockito, AssertJ	verify `reverse` is called on jam

Milestones

1. **Session states and PIN.** *Done when:* three wrong PINs retain the card and return to Idle.
2. **Balance and withdrawal with fake bank.** *Done when:* a decline shows the reason and nothing is dispensed.
3. **Note chain.** *Done when:* withdrawing 170 with 100/50/20 notes yields 100+50+20, an impossible amount (like 30) is refused before contacting the bank, and tests cover empty cassettes.

4. **Failure handling.** *Done when:* a jammed dispenser triggers exactly one `reverse(authId)` call (Mockito `verify`).
5. **Limits and timeout.** *Done when:* a bank fake that sleeps 11 s produces a timeout message and no debit.

Deep dive: the hard parts

Plan before you dispense. First compute a full plan of notes (the chain fills a map), and only if the remainder is zero ask the bank for approval, then dispense. If you dispense note by note and run out mid-way, you have paid out half the money with no clean way back.

Authorise, dispense, then confirm or reverse. The bank debits on approval. If the dispenser then fails, the ATM must send a reversal referencing the approval id. Network calls can fail too, so a reversal that cannot be sent is written to a local queue and retried later. This "compensating action" idea reappears in project 37.

Greedy is not always enough. With notes 50 and 20, withdrawing 60: greedy takes 50 and is stuck at 10, but 20+20+20 works. Let each handler try fewer of its notes when the rest of the chain fails (simple backtracking), or validate amounts against the available note set up front.

Testing strategy

Fakes for `BankGateway` and `CashDispenser` that you can program ("decline next", "jam after 2 notes"). Mockito verifies the reversal call. Parameterised tests over amounts and cassette states for the note chain. One end-to-end session test walks card-in to card-out.

Trade-offs, scaling and failure modes

Keeping session state in memory is fine — one customer at a time per machine. The real risk is ambiguity: did the bank receive the debit before the timeout? Production systems assume "maybe" and send a reversal for any timed-out authorisation. Retaining cards is a security feature but also a support burden; make the threshold configurable.

Stretch goals

- Deposit with a note-recognition interface and a hold until counted.
- Multi-currency cassettes.
- A persistent journal of every hardware and bank event for audit.

Skills practised

- Ch 10 — Behavioral patterns 1: Chain of Responsibility.
- Ch 11 — Behavioral patterns 2: State.
- Ch 9 — Structural patterns: Adapter for the bank, Facade for hardware.
- Ch 14 — Everyday objects: the ATM case study.

In the interview

> **30-second answer:** I built ATM software where the session is a state machine (Idle, CardInserted, Authenticated, Dispensing), the bank sits behind a `BankGateway` adapter and the cash dispenser behind an interface, so everything is testable with fakes. Notes are planned by a Chain of Responsibility, largest denomination first, and the full plan is computed before asking the bank. The key guarantee is authorise, dispense, then reverse on failure: if the dispenser jams after approval, exactly one reversal is sent and retried from a local queue until acknowledged. A timed-out authorisation is treated as "maybe debited" and reversed too.

Key terms to know:

- **State pattern** — session behaviour depends on state; the same keypad press means different things.
- **Chain of Responsibility** — handlers linked in order, each paying what it can and passing the remainder on.
- **Adapter** — `BankGateway` translates the bank's network protocol into simple Java methods.
- **Authorisation** — the bank approves and reserves or debits the amount, returning an auth id.
- **Reversal / compensating action** — a message undoing an approved debit when cash was not dispensed.
- **Timeout ambiguity** — after a timeout you do not know whether the bank applied the debit.
- **Plan before acting** — compute the full note plan first so you never stop halfway through a dispense.
- **Fake versus mock** — a fake is a working stand-in (programmable dispenser); a mock verifies calls (`reverse` called once).

Q: What happens if cash jams after the bank approved?

A: The ATM sends a reversal referencing that authorisation id. If the reversal itself cannot be sent, it is written to a local durable queue and retried until the bank acknowledges, so the customer is not charged for cash they did not get.

Q: Why Chain of Responsibility for notes?

A: Each handler knows one denomination and its cassette count; adding a 200 note is one new class linked into the chain, without editing the others. The chain fills a plan map rather than dispensing directly, so nothing physical happens until the plan is complete.

Q: Is the greedy note chain always correct?

A: No. With 50 and 20 notes, 60 fails greedily (50 then stuck at 10) but 20+20+20 works. Either let handlers back off and try fewer of their notes, or validate the amount against available notes before contacting the bank.

Q: Why compute the full plan before asking the bank?

A: If the plan is impossible you refuse without a debit at all. If you dispensed note by note and ran out midway, you would have paid out part of the money with no clean way to account for it.

Q: How do you handle a bank timeout?

A: After 10 seconds show a clear message and dispense nothing. Because the bank may have applied the debit before the reply was lost, send a reversal for that request anyway; reversals must be idempotent on the bank side, keyed by the request id.

Q: How do you test without hardware?

A: Hardware and bank are interfaces; tests use programmable fakes ("decline next", "jam after 2 notes", "sleep 11 s"). Mockito's `verify(bank, times(1)).reverse(authId)` proves the jam path, and one end-to-end test walks card-in to card-out.

Q: Code-level: how do you model the bank's answer?

A: A sealed result type forces callers to handle both outcomes.

```
sealed interface AuthResult permits Approved, Declined {}
record Approved(String authId) implements AuthResult {}
record Declined(String reason) implements AuthResult {}
switch (bank.authorize(card, amount)) {
    case Approved a -> dispenseOrReverse(a.authId());
    case Declined d -> screen.show(d.reason());
}
```

Q: What breaks first if the ATM crashes mid-transaction?

A: In-memory state is lost, so an approved but not-dispensed withdrawal would leave the customer debited. A persistent journal written before each step (approved, dispensing, dispensed) lets the machine reconcile on restart and send any missing reversal.

Common mistakes in answers:

- Dispensing before approval, or debiting without a reversal path on failure.
- Assuming a timeout means "not debited"; the safe assumption is "maybe".
- Putting bank protocol code inside the state classes instead of behind an adapter.

TL;DR

A state machine for the session, a chain for note planning, and an authorise/dispense/reverse protocol that never loses money.

6. Snake and Ladder

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 2, Ch 4, Ch 17

What it is

The board game: players roll a die and move along squares 1 to 100; landing on a snake's head sends you down to its tail, landing on a ladder's foot sends you up. First to reach exactly 100 wins. As a project it is about clean modelling of a simple rule set and, above all, making randomness testable.

The problem it solves

Games with dice are hard to test because the outcome is random. A design that calls `Math.random()` inside the game loop can only be tested statistically. This project teaches you to inject the source of randomness, to represent board jumps as data rather than code, and to keep rule variations (exact finish, extra turn on a six) pluggable.

Real-world examples

- Java's RandomGenerator interface (JEP 356) gives a common type for all random number generators, so the game can accept any generator — including a seeded one in tests.
- Snake and Ladder is a standard machine-coding problem in the handbook's games chapter, often used in timed rounds.

Requirements

Functional


- Board of configurable size (default 100) with snakes and ladders loaded from a config file.
- 2–6 players take turns. Roll one die (or N dice).
- Rules: optional "exact roll to finish", optional "three sixes in a row forfeits the turn", optional "extra roll on six".

- Print each move and announce the winner.

Non-functional

- Validation at load time: no snake and ladder on the same square, no cycles, no jumps off the board, no snake at the final square.
- A game with a fixed seed is fully reproducible.
- 10,000 simulated games complete in under 1 second.

The architecture



- **Game** — turn order, player positions and termination.
- **Board** — maps a square to its final destination after any snake or ladder; stored as an `int[]` so lookup is O(1).
- **Jump** — a record (from, to). Snakes and ladders are both jumps; only direction differs.
- **Dice** — injected; `RandomDice` wraps a `RandomGenerator`, `ScriptedDice` returns a fixed sequence for tests.
- **RuleSet** — the variant rules, so the game loop does not change when rules do.
- **BoardLoader** — reads and validates the config, the factory for `Board`.

Data model

Type	Kind	Notes
`Jump`	record	`isSnake()` is `to < from`
`Player`	record (name)	position kept in `Game`, not on the player
`TurnResult`	record	player, roll, from, to, jump taken
`BoardConfig`	record	size + list of jumps, validated

Tech stack

Component	Choice	Why
Randomness	`RandomGenerator` injected	seeded and scripted dice for tests
Config	a small text or JSON file	data, not code, for boards
Tests	JUnit 6 + AssertJ	scripted dice make games deterministic
Simulation	plain loop	measure average game length

Milestones

1. **Board with jumps.** *Done when:* loading a config with a cycle or overlapping jump fails with a clear error.
2. **Single-player turn with scripted dice.** *Done when:* a scripted roll onto a ladder foot lands at its top.
3. **Multiplayer game loop.** *Done when:* a scripted 2-player game ends with the expected winner on the expected turn.
4. **Rule variants.** *Done when:* exact-finish and extra-turn-on-six are toggled by config, each with its own tests.
5. **Simulation.** *Done when:* running 10,000 seeded games prints the average number of turns, identical across runs.

Deep dive: the hard parts

Positions belong to the game. Putting `position` on `Player` couples the player to one board. Keep a `Map<Player, Integer>` (or an array indexed by turn order) in `Game`; a player can then be in several games, and resetting is trivial.

Validating the board. Follow jumps from every square: if you ever revisit a square, there is a cycle (a ladder top that is a snake head leading back down to the ladder). Decide whether chained jumps are allowed; if yes, resolve them once at load time into the final destination so play is O(1).

Testable randomness. The game depends on the `Dice` interface only. `ScriptedDice` takes a list of numbers; tests read like stories ("roll 6, 6, 3"). For simulation, a seeded `RandomGenerator` gives repeatable results, so a failing run can be replayed exactly.

Testing strategy

Scripted dice for rule tests; seeded random for simulation tests; property test: positions are always in [0, size]. Test the loader separately with good and bad configs.

Trade-offs, scaling and failure modes

Representing the board as an array of destinations is fast but hides which squares are snakes; keep the `Jump` list for display. Rule variants as a strategy keep the loop clean but can conflict (extra turn on six plus three-sixes forfeit) — document the order rules apply in. An infinite game is possible with "exact finish" and no ladders; add a turn cap in simulation.

Stretch goals

- Multiple dice and special squares (skip a turn, swap places).
- A GUI observer animating moves.
- A Markov-chain calculation of the expected game length, compared to your simulation.

Skills practised

- Ch 17 — Games: the snake and ladder case study.

- Ch 4 — SOLID principles: Dependency Inversion for dice.
- Ch 2 — OOP fundamentals: records for value types.

In the interview

30-second answer: I built Snake and Ladder with the randomness injected: the game depends on a `Dice` interface, so tests use `ScriptedDice` ("roll 6, 6, 3") and simulations use a seeded `RandomGenerator`, making every game replayable. Snakes and ladders are both a `Jump` record, and the loader validates the board (no cycles, no overlaps, nothing off the board) and resolves chained jumps into an `int[]` of destinations, so each move is O(1), and variant rules are a `RuleSet` strategy. 10,000 seeded games run in under a second with identical averages on every run.

Key terms to know:

- **Dependency Inversion** — `Game` depends on the `Dice` abstraction, not on `Math.random()`.
- **Test double** — `ScriptedDice` returns a fixed sequence for deterministic tests.
- **Seeded random generator** — same seed, same sequence; `RandomGenerator` from JEP 356.
- **Data over code** — snakes and ladders are `Jump(from, to)` records loaded from config.
- **Cycle detection** — following jumps until a square repeats, done once at load time.
- **Factory** — `BoardLoader` validates config and builds `Board`.
- **Strategy** — `RuleSet` holds optional rules so the game loop does not change.
- **Simulation** — many seeded games to measure average length.

Q: How do you unit-test a dice game?

A: Inject the dice. Tests pass scripted dice with fixed rolls, so each test is a deterministic story. Simulation tests use a seeded generator so a failing run can be replayed exactly.

Q: Snakes and ladders: two classes or one?

A: One `Jump` record; the behaviour is identical and only the direction differs (`isSnake()` is `to < from`). Two classes would duplicate logic for no gain.

Q: Why keep positions in `Game` rather than on `Player`?

A: Position is a fact about a player in one game, not about the player. Keeping a map or array in `Game` lets the same player join several games and makes reset trivial; `Player` stays an immutable record.

Q: How do you validate a board config?

A: Reject jumps off the board, two jumps from one square, and a snake on the final square. Then follow jumps from every square, and if a square repeats there is a cycle. If chained jumps are allowed, resolve each square to its final destination once, so play is a single array lookup.

Q: How would you add "skip a turn" squares?

A: Add a square-effect type and let the rule set apply effects after movement, without touching the dice or board loading. The game loop only asks the rule set what happens next.

Q: What edge cases can make a game never end?

A: With "exact roll to finish" and bad luck, or a board design that keeps sending players back, a game can run very long. Simulations need a turn cap, and rule combinations such as extra turn on six plus three sixes forfeit need a documented order of application.

Q: Code-level: how do you make the dice injectable?

A: Wrap Java's common random interface.

```java
interface Dice { int roll(); }
record RandomDice(RandomGenerator rng, int faces) implements Dice {
    public int roll() { return rng.nextInt(1, faces + 1); }   // 1..faces inclusive
}
var dice = new RandomDice(RandomGenerator.of("L64X128MixRandom"), 6);
```

For a seeded run in tests, pass `new SplittableRandom(42)` or `new Random(42)`, both of which implement `RandomGenerator`.

Q: What changes at 10x players or a 10,000-square board?

A: Nothing structural: the destination array stays O(1) per move and validation is O(squares) once at load. The extra rules and display get more complex, and for simulations of millions of games you parallelise with one independent seeded generator per thread.

Common mistakes in answers:

- Calling `Math.random()` inside the game, making tests statistical.
- Separate `Snake` and `Ladder` classes with duplicated logic.
- Not validating config, so a cycle hangs the game at runtime.

TL;DR

Jumps as data, positions in the game, rules as a strategy and dice injected so every game can be replayed.

7. Traffic Signal Controller

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 11, Ch 12, Ch 14

What it is

The controller for a four-way road junction: it cycles lights through green, yellow and red for each direction, never shows green to conflicting directions at once, handles pedestrian crossing requests, and gives way to emergency vehicles. It is a gentle introduction to time-driven state machines and to scheduling work with `java.util.concurrent`.

The problem it solves

A junction controller must be safe first (never two conflicting greens) and efficient second (do not hold a green for an empty road). Code that changes lights with `Thread.sleep` inside loops is hard to test and impossible to interrupt for an emergency. The design separates *what* the light sequence is (a state machine of phases) from *when* transitions happen (a scheduler), so both can be tested and changed independently.

Real-world examples

- Adaptive systems such as SCATS adjust phase timings from vehicle detector data instead of fixed cycles — the "adaptive timing" stretch goal here.
- The JDK's ScheduledThreadPoolExecutor is the standard way to run delayed tasks in Java and is what drives phase changes in this design.

Requirements

Functional


- A junction has approaches (North, South, East, West). Phases group non-conflicting approaches (North+South green, then East+West).

- Each phase goes green, then yellow (3 s), then all-red clearance (2 s) before the next phase.
- Pedestrian button: shortens the current green (not below a minimum) and inserts a walk phase.
- Emergency override: move safely (via yellow and all-red) to green for the emergency direction.
- Night mode: flashing yellow.

Non-functional


- Safety invariant: no two conflicting approaches are ever green or yellow simultaneously — checked by tests and assertions.
- Timing accuracy within 100 ms is sufficient.
- Tests run in milliseconds using a fake clock/scheduler, not real seconds.

The architecture



- **JunctionController** — owns the current phase and state; all events (timer fired, button pressed) are processed on one thread so no locks are needed.
- **PhasePlan / Phase** — configuration: which approaches go green together and their timings.
- **SignalState** — the State pattern for the green/yellow/all-red cycle.
- **Scheduler** — an interface; production wraps a `ScheduledExecutorService`, tests use `ManualScheduler` that advances virtual time.
- **SignalHead** — the output device for one approach (console print in this project).

Data model



Key types: `Approach` enum, `Light` enum (`RED`, `YELLOW`, `GREEN`, `FLASHING_YELLOW`), `ConflictMatrix` (which approaches may not be green together).

Tech stack

Component	Choice	Why
Timing	`ScheduledExecutorService` (single thread)	serialises all events
Tests	`ManualScheduler` + JUnit 6	simulate an hour in milliseconds
Safety check	`ConflictMatrix.assertSafe()` after every change	invariant enforced at runtime
Output	console `SignalHead`	swappable for hardware

Milestones

1. **Phase plan and conflict matrix.** *Done when:* a plan with conflicting approaches in one phase is rejected at startup.
2. **Fixed-time cycle.** *Done when:* with the manual scheduler, advancing 60 virtual seconds shows the exact expected sequence.
3. **Pedestrian requests.** *Done when:* a request during green ends it at `minGreen` at the earliest, then runs the walk phase.
4. **Emergency override.** *Done when:* an emergency during East-West green reaches North-South green via yellow and all-red, never directly.
5. **Night mode.** *Done when:* switching modes at any time passes the safety assertion.

Deep dive: the hard parts

One thread, no locks. Button presses come from other threads; timers fire on the scheduler thread. If both change state, you need locks. Instead, submit every event as a task to the same single-

threaded executor — the "actor" idea: one thread owns the state, others send it messages. Bugs from races disappear.

Cancelling timers. When an emergency arrives during green, the pending "go yellow at max green" timer must be cancelled, or it will fire later and break the sequence. Keep a handle to the scheduled task and cancel it on every transition.

Never skip clearance. The safety rule is in the transitions: green can only go to yellow, yellow only to all-red, all-red only to green. Emergency and pedestrian logic change *which* phase comes next, never the path. Encode this in the state classes so no caller can bypass it.

Testing strategy

`ManualScheduler` keeps a priority queue of (due time, task) and an `advance(Duration)` method that runs due tasks in order. Every test asserts the safety invariant after each step. Scenario tests: rush of pedestrian presses, emergency during yellow, emergency during all-red.

Trade-offs, scaling and failure modes

Fixed timing is simple but wastes green on empty roads; adaptive timing needs sensors and can starve a quiet approach without a max-wait rule. Real controllers fail safe: on any internal error they go to flashing red/yellow. Do the same — catch exceptions in the event loop and enter `Flashing`.

Stretch goals

- Vehicle detectors that extend green while cars keep arriving, up to `maxGreen`.
- Coordinated junctions ("green wave") sharing a cycle offset.
- A JavaFX view showing the junction live.

Skills practised

- Ch 11 — Behavioral patterns 2: State.
- Ch 12 — Concurrency concepts: executors and scheduled tasks.
- Ch 14 — Everyday objects: the traffic signal case study.

In the interview

30-second answer: I built a four-way junction controller that separates *what* the light sequence is (a green, yellow, all-red state machine over a phase plan) from *when* it changes (an injected `Scheduler`). Every event, whether a timer firing, a pedestrian button or an emergency, is submitted to one single-threaded executor, so state has one owner and needs no locks. Safety is enforced three ways: a conflict matrix rejects bad phase plans at startup, transitions can only go green to yellow to all-red, and an assertion runs after every change. With a manual scheduler, tests simulate an hour of traffic in milliseconds.

Key terms to know:

- **Phase** — a group of non-conflicting approaches that are green together, such as North+South.
- **Conflict matrix** — a table of which approaches may never be green or yellow at the same time.
- **All-red clearance** — a short period with every light red so the junction empties before the next phase.
- **State pattern** — `SignalState` classes for green, yellow, all-red and flashing.
- **Single-threaded executor (actor style)** — one thread owns the state; other threads send it tasks as messages.
- **ScheduledFuture / cancellation** — the handle to a pending timer, cancelled when an emergency changes the plan.
- **Manual (fake) scheduler** — a test scheduler that advances virtual time instantly.

- **Fail safe** — on internal error, go to flashing mode rather than an unknown state.

Q: How do you guarantee no conflicting greens?

A: A conflict matrix checked when the phase plan loads, transitions that always pass through yellow and all-red, and a runtime assertion after every change. Emergency and pedestrian logic only change which phase comes next, never the path through clearance.

Q: How do you test a system that runs on timers?

A: Hide time behind a scheduler interface and use a `ManualScheduler` that keeps a priority queue of (due time, task) and runs due tasks when the test calls `advance(Duration)`. Sixty virtual seconds take microseconds, and the order is deterministic.

Q: Why a single-threaded executor instead of locks?

A: It serialises all events, so state has a single writer, needs no locks and has a predictable order. Timing accuracy of 100 ms is easy for one thread, so there is no throughput reason to add parallelism and the race conditions that come with it.

Q: What goes wrong if you forget to cancel the pending timer on an emergency?

A: The old "go yellow at max green" task fires later and moves the junction out of the emergency phase or skips a step. Keep the `ScheduledFuture` returned by `schedule` and call `cancel(false)` on every transition, or tag tasks with a phase generation number and ignore stale ones.

Q: Why is `Thread.sleep` in a loop a bad design here?

A: A sleeping loop cannot react to an emergency until it wakes, cannot be tested without waiting real seconds, and mixes sequence logic with timing. A scheduler plus event handlers can be interrupted at any moment and tested with virtual time.

Q: Code-level: how do you push every event onto the controller thread?

A: Callers never touch state directly; they submit work.

```
private final ScheduledExecutorService loop = Executors.newSingleThreadScheduledExecutor();
public void pedestrianPressed(Approach a) { loop.execute(() -> onPedestrian(a)); }
private void enter(SignalState s, Duration d) {
    if (pending != null) pending.cancel(false);
    state = s; heads.show(s); conflicts.assertSafe(heads);
    pending = loop.schedule(this::onTimer, d.toMillis(), TimeUnit.MILLISECONDS);
}
```

Q: What happens if a handler throws an exception?

A: In a scheduled executor an uncaught exception silently cancels that task, so the cycle could just stop. Catch everything inside the event loop and enter `Flashing`, which is how real controllers fail safe, then log the error.

Q: What changes with adaptive timing or a "green wave" of many junctions?

A: Adaptive timing adds detector inputs that extend green up to `maxGreen`, plus a max-wait rule so a quiet road is not starved. Coordinated junctions share a cycle length and per-junction offset; each controller stays single-threaded and only the schedule parameters change.

Common mistakes in answers:

- Jumping from green straight to the emergency direction's green; the path must always pass yellow and all-red.
- Using `synchronized` everywhere instead of noticing that one owner thread removes the need for locks.

- Testing with real `sleep`, which makes the suite slow and flaky.

TL;DR

A phase plan plus a green/yellow/all-red state machine, driven by an injectable scheduler on one thread, with safety enforced in the transitions.

8. Task Manager CLI

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** Ch 6, Ch 8, Ch 21

What it is

A command-line to-do manager: add tasks with titles, priorities, due dates and tags; list and filter them; mark them done; undo the last action; and save to a file. It looks like a CRUD app (create, read, update, delete), but the interesting design is in the command parsing, filtering and undo.

The problem it solves

A task tool has many commands and many filters, and both grow over time. The usual mess is a giant `switch` over command names in `main`, with filtering logic copy-pasted per command. This project practises the **Command** pattern (each command is an object), the **Builder** for tasks with many optional fields, a composable filter (the **Specification** idea), and the clean-code habits — small functions, clear names — that machine-coding rounds grade.

Real-world examples

- Taskwarrior is a mature open-source command-line task manager with filters, tags, priorities and undo — a good reference for features and command syntax.
- picocli is a widely used Java library for building command-line apps with subcommands and typed options.

Requirements


Functional

- `add "title" --priority high --due 2026-11-01 --tag work`
- `list` with filters: status, priority, tag, due before/after, text search; sort by due or priority.
- `done <id>`, `edit <id> ...`, `delete <id>`, `undo`.
- Recurring tasks (daily, weekly): completing one creates the next.
- Persist to a JSON file on every change.

Non-functional

- Startup and any command under 200 ms for 10,000 tasks.
- A crash mid-save never corrupts the file.
- Each command class under 50 lines; parser and domain decoupled.

The architecture



- **Cli / CommandParser** — turn arguments into a `Command` object. Only this layer knows the text syntax.
- **Command** — one class per action with `execute` and `undo`. Read-only commands have a no-op undo.
- **History** — a stack of executed commands for `undo`.
- **TaskService** — the domain operations, including recurrence.
- **TaskFilter** — small predicates combined with `and` / `or`, built from `--tag`, `--priority` etc.
- **TaskRepository** — persistence behind an interface; JSON file now.

Data model

Type	Kind	Notes
`Task`	class built with `Task.builder()`	id, title, priority, due, tags, status, recurrence
`Priority`	enum	`LOW`, `MEDIUM`, `HIGH` with ordering
`Recurrence`	sealed: `None`, `Daily`, `Weekly(DayOfWeek)`	computes next due date
`Status`	enum	`OPEN`, `DONE`, `DELETED` (soft delete enables undo)

Tech stack

Component	Choice	Why
CLI parsing	hand-written parser, then picocli	learn it, then use the tool
JSON	Jackson (current version)	standard, records supported
Safe writes	write temp file + atomic move	no corrupted file on crash
Tests	JUnit 6, AssertJ, `@TempDir`	real files in a temp folder

Milestones

1. **Domain + builder.** *Done when:* building a task without a title throws a clear error.
2. **Commands and parser.** *Done when:* `add`, `list`, `done`, `delete` work end-to-end in tests that call `Cli.run`.
3. **Filters.** *Done when:* `list --tag work --priority high --due-before 2026-11-01` returns the right set.
4. **Undo.** *Done when:* `add`, `done`, `delete` are each undoable and tests check the store afterwards.
5. **Persistence and recurrence.** *Done when:* completing a weekly task creates next week's task and both survive a restart.

Deep dive: the hard parts

Undo needs enough information. `DeleteCommand.undo` must restore the exact task, so the command records the task it deleted during `execute`. `AddCommand.undo` records the id it created. Soft delete (status `DELETED`) makes undo trivial and keeps ids stable.

Composable filters. Each option maps to a tiny `TaskFilter`; combine with `and`. This is Java's `Predicate` idea with a domain name, and it keeps `TaskService.find` to one line. New filters are new small classes, never edits to a long `if` chain — Open/Closed in practice.

Atomic saves. Writing directly over `tasks.json` and crashing halfway leaves half a file. Write to `tasks.json.tmp`, then `Files.move(tmp, target, ATOMIC_MOVE, REPLACE_EXISTING)`. On most file systems the rename is atomic: readers see either the old file or the new one.

Testing strategy

Unit-test each filter and command. Use JUnit's `@TempDir` for repository tests with real files. A golden-output test runs a script of commands through `Cli.run` and compares the printed output to an expected text file.

Trade-offs, scaling and failure modes

Rewriting the whole JSON file on every change is O(n) but simple and fine for thousands of tasks; an append-only log is faster but needs compaction. Undo history in memory is lost on exit — persist it

if needed. Time zones matter for due dates: store `LocalDate` for date-only due dates, `Instant` for exact deadlines.

Stretch goals

- Projects and subtasks (Composite pattern), with completion rolling up.
- A SQLite or PostgreSQL repository behind the same interface.
- Natural-language dates ("next friday").

Skills practised

- Ch 6 — Clean Code: small functions, naming.
- Ch 8 — Creational patterns: Builder.
- Ch 10 — Behavioral patterns 1: Command for undo.
- Ch 21 — Machine coding: the task management system case.

In the interview

30-second answer: I built a command-line task manager where every action is a `Command` object with `execute` and `undo`, and a history stack makes undo work for add, done, edit and delete. Filters such as `--tag work --priority high` map to small `TaskFilter` predicates combined with `and`, so a new filter is a new class plus one parser line. Tasks are built with a Builder because they have many optional fields, and deletes are soft so undo can restore the exact task. Saves write a temp file and atomically rename it, so a crash never leaves a half-written JSON file, and any command runs in under 200 ms for 10,000 tasks.

Key terms to know:

- **Command pattern** — an action wrapped as an object with `execute` and `undo`.
- **History stack** — executed commands pushed in order; `undo` pops and reverses the latest.
- **Builder pattern** — step-by-step construction of an object with many optional fields, validated in `build()`.
- **Specification / composable predicate** — small filters combined with `and` / `or`, like `Predicate<Task>`.
- **Soft delete** — marking a task `DELETED` instead of removing it, which keeps ids stable and undo simple.
- **Atomic rename** — writing to a temp file, then `Files.move` with `ATOMIC_MOVE`, so readers see old or new, never half.
- **Repository** — persistence behind an interface (`TaskRepository`), JSON file now, database later.
- **Golden-output test** — run a script of commands and compare printed output with a saved expected file.

Q: How do you implement undo?

A: Every mutating command implements `undo` using state it captured during `execute`: `AddCommand` remembers the id it created, `DeleteCommand` remembers the task it deleted. A history stack undoes in reverse order. Read-only commands such as `list` are not pushed.

Q: How do you add a new filter without touching existing code?

A: Write a new `TaskFilter` class and add one line in the parser mapping an option to it. `TaskService.find` just applies the combined filter, so it never changes. That is the Open/Closed Principle in practice.

Q: How do you avoid corrupting the save file?

A: Write to `tasks.json.tmp`, then rename it over `tasks.json` with `Files.move(tmp, target, ATOMIC_MOVE)`. On local Linux and macOS file systems a rename is atomic and replaces the target, so a crash leaves either the old file or the new one. Note that with `ATOMIC_MOVE` the Javadoc says replacing an existing target is implementation-specific, so test it on your platform.

Q: Why a Builder for `Task` rather than a constructor?

A: A task has a required title and many optional fields (priority, due, tags, recurrence). A constructor with seven parameters is easy to call in the wrong order, and telescoping constructors multiply. The builder names each field and validates once in `build()`, for example throwing if the title is missing.

Q: How does recurrence interact with undo?

A: Completing a weekly task does two things: mark it done and create next week's task. `DoneCommand` must record both so `undo` reopens the original and removes the generated one; otherwise undo leaves a stray future task.

Q: Code-level: how do you combine filters?

A: Make the filter a functional interface with a default `and`.

```
@FunctionalInterface
interface TaskFilter {
    boolean test(Task t);
    default TaskFilter and(TaskFilter o) { return t -> test(t) && o.test(t); }
    static TaskFilter tag(String tag) { return t -> t.tags().contains(tag); }
}
```

Q: What changes at 10x tasks or if two terminals run commands at once?

A: Rewriting the whole file on every change is O(n); at 100,000 tasks it gets slow, so move to an append-only log with compaction or SQLite behind the repository interface. Two processes writing the same file can lose each other's changes, so use a file lock or a database.

Q: How do you test the CLI end to end?

A: Call `Cli.run(args)` directly with output captured, use JUnit's `@TempDir` for real files, and compare a scripted session's output with a golden file. Each filter and command also has its own small unit test.

Common mistakes in answers:

- One giant `switch` in `main` that parses, executes and prints; interviewers want parser, commands and domain separated.
- An undo that "re-reads the file" instead of reversing captured state.
- Overwriting the save file in place and assuming the OS will not crash midway.

TL;DR

Commands as objects with undo, composable filters, a builder for tasks and atomic file saves.

9. Coffee Machine

Level: Beginner · **Time:** 1 weekend · **Prerequisites:** Ch 8, Ch 9, Ch 14

What it is

A model of a café coffee machine that brews drinks from recipes (espresso, latte, cappuccino), lets customers add extras (extra shot, oat milk, syrup) and tracks ingredient stock. It is the classic

playground for **Decorator** (stacking extras onto a base drink) and **Builder/Factory** (creating drinks from a menu).

The problem it solves

Drinks combine freely: a latte with oat milk, two extra shots and vanilla. A subclass per combination ("LatteWithOatAndVanilla") explodes combinatorially. Ingredient stock must be checked *before* brewing, for the whole order, so the machine never starts a drink it cannot finish. The project trains composition over inheritance and the "check all, then commit" pattern.

Real-world examples

- Java's I/O streams are the best-known Decorator in the JDK: a `BufferedInputStream` wraps another `InputStream` and adds buffering, just as an "extra shot" wraps a drink and adds cost and ingredients.
- The coffee shop example is the Decorator chapter of *Head First Design Patterns*, summarised in the handbook's structural patterns chapter.

Requirements


Functional

- Menu of base drinks, each a recipe of ingredients (espresso shots, milk ml, water ml, foam).
- Extras as add-ons with their own price and ingredients. Any number, any order.
- Check stock for the full drink; brew or refuse with "not enough milk".
- Refill ingredients; low-stock alerts at a threshold.
- Price and description computed from the composed drink ("Latte + oat milk + extra shot").

Non-functional

- New drink or extra = new data or one new class; no edits elsewhere.
- Stock never goes negative, even with concurrent orders from two dispensers.
- Price arithmetic exact (integer cents).

The architecture



- **Beverage** — the common interface for drinks and decorated drinks.
- **BaseDrink** — espresso, latte etc., loaded from a menu file.
- **AddOn** — the Decorator: wraps a `Beverage`, adds cost and ingredients, delegates the rest.

- **DrinkFactory** — maps menu names (and an order like `"latte+oat+shot"`) to composed objects.
- **Inventory** — stock per ingredient with all-or-nothing `reserve`.
- **StockObserver** — notified on low stock.

Data model

Type	Kind	Notes
`Ingredient`	enum	`COFFEE_G`, `MILK_ML`, `OAT_MILK_ML`, `WATER_ML`, `SYRUP_ML`
`Recipe`	record (`Map<Ingredient,Integer>`)	`plus(Recipe)` merges amounts
`Money`	record (cents)	`plus`
`Cup`	record	description + price, the result of brewing

Tech stack

Component	Choice	Why
Composition	Decorator	free combination of extras
Menu	JSON/YAML file	add drinks without code
Concurrency	`synchronized` reserve	all-or-nothing is one critical section
Tests	JUnit 6, AssertJ	price/description tables

Milestones

1. **Recipes and base drinks.** *Done when:* the menu file loads and each drink prints its price.
2. **Decorators.** *Done when:* `ExtraShot(OatMilk(Latte))` has the right cost, description and merged recipe.
3. **Inventory.** *Done when:* an order needing more milk than in stock is refused and stock is unchanged.
4. **Factory from order strings.** *Done when:* `"cappuccino+syrup+syrup"` builds correctly and unknown add-ons are rejected.
5. **Concurrency + alerts.** *Done when:* two threads placing 1,000 orders each never drive stock negative, and the observer fires once per threshold crossing.

Deep dive: the hard parts

Oat milk replaces milk. A naive `OatMilk` decorator adds oat milk *and* keeps the base's dairy milk. Make `ingredients()` able to substitute: the decorator takes the inner recipe, removes `MILK_ML`, and adds the same amount of `OAT_MILK_ML`. This shows decorators can transform, not just add.

Check then commit, atomically. `reserve(recipe)` must check every ingredient and then subtract all of them in one critical section. Checking outside the lock and subtracting inside lets two orders both pass the check — a classic "check-then-act" race.

Decorator versus a list of extras. A `Drink` with a `List<Extra>` is often simpler and serialises more easily. Decorator wins when extras change behaviour (substitution, conditional pricing). Build the decorator version, then write a paragraph on when you would choose the list.

Testing strategy

Table-driven tests for cost and description of many combinations. Inventory tests for boundary amounts (exactly enough, one short). A concurrency test with an `ExecutorService` and a `CountDownLatch` to start threads together, asserting final stock equals initial minus successful orders.

Trade-offs, scaling and failure modes

Deep decorator stacks are hard to debug (stack traces through many wrappers) and to inspect ("does this drink have syrup?" needs a walk). Equality of decorated objects is awkward. The machine may fail mid-brew; reserve stock before brewing and release it if brewing fails.

Stretch goals

- Size multipliers (small/medium/large) applied to the whole recipe.
- Loyalty discounts as a pricing strategy applied after decoration.
- A brewing pipeline with steps (grind, tamp, extract, steam) via Template Method.

Skills practised

- Ch 9 — Structural patterns: Decorator.
- Ch 8 — Creational patterns: Factory and Builder.
- Ch 14 — Everyday objects: the coffee machine case.
- Ch 12 — Concurrency concepts: check-then-act races.

In the interview

30-second answer: I built a coffee machine where base drinks come from a menu file and extras like an extra shot or oat milk are Decorators that wrap a `Beverage` and adjust its price, description and recipe. That avoids a subclass for every combination, and decorators can transform as well as add: oat milk removes dairy milk and adds the same amount of oat milk. Stock is reserved all-or-nothing in one critical section, because checking outside the lock is a check-then-act race. Two threads placing 1,000 orders each never drove stock negative.

Key terms to know:

- **Decorator pattern** — a wrapper implementing the same interface that adds behaviour and delegates the rest; `ExtraShot(OatMilk(Latte))`.
- **Composition over inheritance** — combining objects instead of creating `LatteWithOatAndVanilla` subclasses.
- **Recipe value object** — immutable map of ingredient amounts with `plus` for merging.
- **Factory** — `DrinkFactory` turns an order string like `"latte+oat+shot"` into a decorated object.
- **Check-then-act race** — two threads both pass a check before either acts; fixed by doing both inside one lock.
- **All-or-nothing reservation** — check every ingredient and subtract all, or change nothing.
- **Observer** — `StockObserver` notified when stock crosses a low threshold.
- **Integer cents** — exact prices, no floating-point drift.

Q: Why Decorator here?

A: Extras combine freely and in any number; wrapping avoids a subclass per combination while keeping one `Beverage` interface. Adding "caramel syrup" is one class or one menu entry, and nothing else changes.

Q: How do you stop stock going negative with two dispensers?

A: Check and deduct all ingredients inside one lock (one `synchronized reserve(recipe)`), never check outside the lock. If the check passes and the deduct happens later, two orders can both see "enough milk" and both subtract.

Q: When would you not use Decorator?

A: When extras are plain data with no behaviour, a `List<Extra>` on the drink is simpler, easier to serialise and easier to query ("does it have syrup?"). Decorator wins when an extra changes behaviour, like substituting milk or conditional pricing.

Q: How does the oat milk decorator avoid keeping dairy milk?

A: Its `recipe()` takes the inner recipe, removes `MILK_ML`, and adds the same amount as `OAT_MILK_ML`. That shows a decorator can transform what it wraps, not only append to it.

Q: Code-level: what does a decorator look like?

A: It holds the inner beverage and delegates.

```
record ExtraShot(Beverage inner) implements Beverage {
    public Money price()       { return inner.price().plus(Money.cents(60)); }
    public String description() { return inner.description() + " + extra shot"; }
    public Recipe recipe()     { return inner.recipe().plus(Recipe.of(COFFEE_G, 9)); }
}
```

Q: What happens if brewing fails halfway?

A: Stock was reserved before brewing, so on failure the machine releases the reservation (adds the amounts back). Without that, a failed brew would silently lose ingredients from the books.

Q: How do you prove the concurrency is right?

A: Start many threads together with a `CountDownLatch`, have each place orders, then assert final stock equals initial stock minus the recipes of successful orders, and that nothing is negative. Also test boundaries: exactly enough milk succeeds, one ml short fails and leaves stock unchanged.

Q: What changes at 10x dispensers or many machines?

A: One lock around `reserve` is microseconds, so ten dispensers are still fine. Many machines sharing one central stock would need a database transaction or per-ingredient atomic counters, and the low-stock observer should fire once per threshold crossing, not on every order.

Common mistakes in answers:

- Proposing a subclass per drink combination.
- Checking stock and then deducting in separate steps "because it is fast".
- Saying Decorator is always better than a list; it is a trade-off.

TL;DR

Base drinks plus decorators for extras, recipes as mergeable values, and an all-or-nothing inventory reservation.

10. Digital Wallet

Level: Beginner · **Time:** 1–2 weekends · **Prerequisites:** Ch 5, Ch 12, Ch 21

What it is

An in-memory wallet service: users open wallets, top up money, transfer to each other, and see a statement. It is a small project with two big lessons: money must be modelled exactly, and transfers between two accounts must be safe when many happen at once.

The problem it solves

Money bugs are the most expensive bugs. Floating-point rounding loses cents; two concurrent transfers can both read the same balance and overdraw; a retried request can transfer twice. This

project teaches the **Money** value object, immutable transaction records, lock ordering to avoid deadlock, and **idempotency keys** — a client-chosen id that makes retries safe.

Real-world examples

- Martin Fowler's Money pattern describes pairing an amount with a currency in one value object, the basis of this design.
- Stripe's post on idempotency keys explains why payment APIs accept a client-generated key so a retried request does not charge twice.
- JavaMoney (JSR 354) is the Java standard API for monetary amounts and currencies, if you prefer a library to a hand-written `Money`.

Requirements


Functional

- Create a wallet for a user, top up from an "external" source, withdraw, transfer between wallets.
- Reject transfers that would overdraw. Reject currency mismatches.
- Statement: list of transactions with running balance, filterable by date.
- Every mutating call accepts an idempotency key; repeating a call with the same key returns the first result.
- Optional cashback offer: 1% on the first transfer of the day (a pluggable offer strategy).

Non-functional

- Total money in the system changes only by top-ups and withdrawals: transfers conserve it.
- 100 threads doing 10,000 random transfers: no deadlock, no lost update, no negative balance.
- Transfer latency in memory under 1 ms at the 99th percentile.

The architecture



- **WalletService** — the application service: validation, locking order, idempotency, offers.
- **Wallet** — holds a balance and its own lock; `debit` refuses to go negative.
- **Money** — immutable amount in minor units plus currency; arithmetic refuses mixed currencies.
- **Txn** — an immutable record of every movement; the statement is a view over these.
- **IdempotencyStore** — remembers key to result.
- **OfferStrategy** — cashback rules, pluggable.

Data model

Type	Kind	Notes
`Money`	record (long minor units, `Currency`)	never `double`
`Txn`	record	id, type (`TOPUP`, `WITHDRAW`, `TRANSFER_OUT`, `TRANSFER_IN`, `CASHBACK`), amount, counterparty, time
`Wallet`	class	id, owner, balance, lock, list of txn ids
`TransferResult`	sealed: `Ok(txn)`, `Insufficient`, `CurrencyMismatch`	no exceptions for business outcomes

Tech stack

Component	Choice	Why
Money	`long` cents or `BigDecimal` with scale 2	exact arithmetic
Locks	`ReentrantLock` per wallet	fine-grained, `tryLock` with timeout
Concurrency tests	`ExecutorService` with virtual threads	thousands of cheap threads
Tests	JUnit 6, AssertJ	invariant assertions

Milestones

1. **Money.** *Done when:* adding EUR to USD throws, and 0.10 + 0.20 equals exactly 0.30.
2. **Single-threaded wallet service.** *Done when:* overdraft is refused and the statement shows correct running balances.
3. **Idempotency.** *Done when:* calling `transfer` twice with one key moves money once and returns the same txn id.
4. **Concurrent transfers.** *Done when:* 100 virtual threads doing random transfers among 50 wallets finish without deadlock and total money is unchanged.
5. **Offers.** *Done when:* cashback is applied only to the first transfer per user per day, verified with an injected clock.

Deep dive: the hard parts

Deadlock in transfers. Thread 1 transfers A to B (locks A, then wants B) while thread 2 transfers B to A (locks B, wants A): both wait forever. Fix by always locking in a global order — e.g. by wallet id — regardless of transfer direction. Lock the smaller id first, then the larger. This removes the circular wait, one of the four conditions for deadlock.

Conservation as a test oracle. After any concurrent run, the sum of all balances must equal the sum of top-ups minus withdrawals. This single check catches lost updates, double-applies and partial transfers. Write it first.

Idempotency race. Two retries with the same key can arrive at the same time. Use `ConcurrentHashMap.computeIfAbsent(key, ...)` storing a future, so the second caller waits for and returns the first caller's result instead of running the transfer again.

Testing strategy

Unit tests for `Money` and `Wallet`. A stress test using `Executors.newVirtualThreadPerTaskExecutor()` with a `CountDownLatch` start gate, followed by the conservation assertion. A deadlock test with a timeout (`assertTimeoutPreemptively`) that fails instead of hanging the build.

Trade-offs, scaling and failure modes

Per-wallet locks scale well until one wallet is hot (a merchant receiving thousands of payments): every transfer to it serialises. A ledger of immutable entries (project 34) with balances derived from entries is more auditable than mutable balances. In-memory idempotency keys must expire, or memory grows forever — keep them for 24 hours.

Stretch goals

- Persist to PostgreSQL with `SELECT ... FOR UPDATE` row locks in id order.
- Multi-currency with an exchange-rate provider and explicit conversion transactions.
- Scheduled payments using a `ScheduledExecutorService`.

Skills practised

- Ch 5 — Design principles: immutability, fail fast.

- Ch 12 — Concurrency concepts: locks, deadlock, virtual threads.
- Ch 21 — Machine coding: the digital wallet case.

In the interview

30-second answer: I built an in-memory wallet service with an immutable `Money` value object in integer minor units, a per-wallet `ReentrantLock`, and immutable transaction records that the statement is built from. Transfers lock both wallets in a fixed global order (lower id first), which removes the circular wait that causes deadlock. Every mutating call takes an idempotency key, stored as a future in a `ConcurrentHashMap`, so a retried request returns the first result instead of moving money twice. 100 virtual threads doing random transfers finished with no deadlock and total money unchanged.

Key terms to know:

- **Money value object** — immutable amount plus currency; arithmetic refuses mixed currencies.
- **Minor units** — whole cents in a `long` (or `BigDecimal` with fixed scale) instead of `double`.
- **Deadlock** — threads waiting on each other's locks forever; requires mutual exclusion, hold and wait, no preemption and circular wait.
- **Lock ordering** — always acquiring locks in a global order to remove circular wait.
- **Lost update** — two threads read the same balance and one write overwrites the other.
- **Idempotency key** — a client-chosen id so a retried request has the same effect as one request.
- **Conservation invariant** — total balances change only by top-ups and withdrawals.
- **Virtual threads** — cheap JVM-managed threads, used to run thousands of concurrent test transfers.

Q: How do you prevent deadlock when transferring between two wallets?

A: Acquire both locks in a fixed global order, such as by wallet id, regardless of transfer direction. A to B and B to A both lock the smaller id first, so no two threads can wait on each other in a cycle.

Q: Why not `double` for money?

A: Binary floating point cannot represent most decimal fractions exactly, so `0.1 + 0.2` is `0.30000000000000004` and sums drift by fractions of a cent. Use integer minor units or `BigDecimal` with an explicit scale and rounding mode.

Q: A client times out and retries a transfer. What happens?

A: It sends the same idempotency key; the service finds the stored result and returns it without moving money again. Keys are kept for a bounded time (say 24 hours) so memory does not grow forever.

Q: Two retries with the same key arrive at the same moment. How do you avoid running the transfer twice?

A: Use `computeIfAbsent(key, k -> new CompletableFuture<>())`, which is atomic per key. Only the caller that created the future runs the transfer and completes it; the other caller waits on the same future and gets the same result.

Q: Code-level: what does the ordered locking look like?

A: Pick the order by id, then lock with try/finally.

```
Wallet first = a.id().compareTo(b.id()) < 0 ? a : b;
Wallet second = first == a ? b : a;
first.lock().lock();
try { second.lock().lock();
      try { from.debit(amt); to.credit(amt); } finally { second.lock().unlock(); }
} finally { first.lock().unlock(); }
```

Q: Why return a sealed `TransferResult` instead of throwing for "insufficient funds"?

A: Insufficient funds is an expected business outcome, not a bug. A sealed result (`Ok`, `Insufficient`, `CurrencyMismatch`) forces the caller to handle each case in an exhaustive `switch`, and is cheaper and clearer than exceptions for control flow.

Q: What breaks first at 10x traffic?

A: A hot wallet, such as a merchant receiving thousands of payments, serialises every transfer on its one lock. Options are sharding the merchant's balance into sub-accounts, or moving to an append-only ledger (project 34) where credits are inserts and balances are derived. In-memory state is also lost on restart, so production uses a database with `SELECT ... FOR UPDATE` in id order.

Q: How do you test for deadlocks and lost updates?

A: Run random transfers from many virtual threads behind a start latch, wrapped in `assertTimeoutPreemptively` so a deadlock fails instead of hanging the build. Then check the conservation invariant and that no balance is negative; that one assertion catches lost updates and partial transfers.

Common mistakes in answers:

- "Use `synchronized` on the transfer method" without discussing the lock order or the hot-wallet bottleneck.
- Treating a timeout as failure and letting the client retry without an idempotency key.
- Storing money in `double` or `float`.

TL;DR

Exact `Money`, immutable transaction records, ordered locking for transfers and idempotency keys for safe retries.

11. Elevator System

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 11, Ch 12, Ch 14

What it is

A controller for a bank of elevators in one building. People press **hall calls** (up/down buttons on a floor) and **car calls** (floor buttons inside a cabin); a **dispatcher** decides which cabin serves each hall call; each cabin moves, stops, opens doors and keeps going in a sensible order. It is the most common intermediate LLD question because it mixes state machines, scheduling strategy and concurrency.

The problem it solves

Serving requests in arrival order makes cabins zig-zag and passengers wait. Real controllers minimise waiting time while never starving a floor. The software challenge is to separate three concerns that beginners merge: the **per-cabin state machine** (moving, stopped, doors open), the **per-cabin stop ordering** (which floor next), and the **cross-cabin dispatch** (which cabin gets a new hall call) — and to run it all safely while requests keep arriving from many threads.

Real-world examples

- The single-cabin ordering rule is the elevator algorithm (SCAN): keep moving in one direction serving stops until none remain ahead, then reverse. The same idea schedules disk-head movement.
- The handbook's everyday-objects chapter works the elevator case study in detail; this project turns it into a running simulation.

Requirements


Functional

- N floors (up to 100), M cabins (up to 8), each with capacity and current floor.
- Hall calls (floor + direction) and car calls (target floor).
- Cabins serve stops in SCAN/LOOK order; doors open for a fixed time; overweight blocks closing.
- Dispatcher assigns each hall call to one cabin using a pluggable strategy (nearest suitable car, least loaded, zoning).
- Maintenance mode removes a cabin from dispatch; fire mode sends all cabins to the ground floor.

Non-functional


- Simulation runs in discrete ticks; 10,000 simulated passengers process in under 2 seconds.
- Metrics: average and 95th-percentile wait time per strategy.
- Thread-safe request intake from many caller threads.

The architecture



- **ElevatorSystem** — the facade: takes requests, drives the clock (`tick`), owns cars.
- **Dispatcher** — strategy for hall-call assignment. Swap it and compare metrics.
- **ElevatorCar** — one cabin: current floor, direction, load, state and pending stops.
- **StopSet** — two sorted sets (stops above, stops below) giving LOOK order in O(log n).
- **CarState** — State pattern for idle, moving and doors-open behaviour.
- **SystemMode** — normal, maintenance, fire; changes what the system accepts.

Data model



Type	Notes
`Direction`	enum `UP`, `DOWN`, `NONE`
`HallCall`	record (floor, direction, time created)
`Passenger` (simulation)	origin, destination, arrival tick, boarded tick

Tech stack

Component	Choice	Why
Stops	two `TreeSet<Integer>` per car	ordered next-stop lookup
Intake	`ConcurrentLinkedQueue` drained each tick	threads never touch car state
Simulation	discrete ticks, seeded random traffic	reproducible metrics
Tests	JUnit 6, AssertJ, parameterised scenarios	per-strategy comparisons

Milestones

1. **One car, LOOK ordering.** *Done when:* car at floor 5 going up with stops {7, 2, 9} visits 7, 9, then 2.
2. **Car state machine.** *Done when:* tests show doors open for exactly the configured ticks and overweight keeps them open.

3. **Multiple cars + nearest-car dispatch.** *Done when:* a hall call at 10 up goes to the car at 8 moving up, not the idle car at 1.
4. **Simulation and metrics.** *Done when:* a seeded morning-rush scenario prints average and p95 wait for two strategies.
5. **Concurrency and modes.** *Done when:* 50 threads issuing calls while the clock ticks lose no request, and fire mode sends every car to floor 0 without stopping.

Deep dive: the hard parts

What "suitable" means for dispatch. A car is a good candidate for an "up at floor 10" call if it is idle, or moving up and still below 10. A car moving up past 10 would have to finish its run and come back, so its cost is much higher. Write a cost function: distance plus a penalty for each stop already queued plus a large penalty for direction mismatch. Every strategy is a different cost function — a clean Strategy pattern.

LOOK in O(log n). Keep `up = TreeSet` and `down = TreeSet`. Going up, the next stop is `up.ceiling(currentFloor)`; if null, reverse and use `down.floor(currentFloor)`. Never sort a list on each tick.

Concurrency without locking cars. Caller threads only enqueue requests into a concurrent queue. The single simulation thread drains the queue at the start of each tick and is the only writer of car state. This "one writer" design avoids locks and makes ticks deterministic, which is also what makes the simulation testable.

Starvation. A busy express zone can keep cars away from a quiet floor. Track each hall call's age and boost its priority once it exceeds a threshold.

Testing strategy

Scenario tests with a scripted list of calls and expected stop sequence. Strategy comparison as a test that asserts the smarter dispatcher's average wait is lower than a round-robin baseline on a fixed seed. A concurrency test: many producer threads, then assert every request was served exactly once.

Trade-offs, scaling and failure modes

Assigning a hall call immediately is simple but may be wrong a second later; "destination dispatch" systems ask for the destination at the lobby and group passengers, at the cost of a different user interface. A car that fails mid-run must have its hall calls reassigned — keep assignments in the dispatcher, not only in the car. Tick-based simulation is deterministic; a real-time version uses a scheduler but should still use one owner thread.

Stretch goals

- Destination dispatch: passengers enter destination at the lobby keypad.
- Energy metric: count starts and stops; add a strategy that trades wait time for fewer starts.
- A live text visualisation of the shaft.

Skills practised

- Ch 14 — Everyday objects: the elevator case.
- Ch 11 — Behavioral patterns 2: State and Strategy.
- Ch 12 — Concurrency concepts: concurrent queues, single-writer design.

In the interview

> **30-second answer:** I built a multi-cabin elevator simulation that separates three concerns: each car's state machine (idle, moving, doors open), each car's stop ordering using LOOK with two `TreeSet`s, and cross-car dispatch as a Strategy that scores cars with a cost function. Button

presses from any thread go into a `ConcurrentLinkedQueue`, and one simulation thread drains it each tick and is the only writer of car state, so there are no locks and runs are deterministic. I compared dispatch strategies on a seeded morning-rush scenario by average and 95th-percentile wait, and 10,000 passengers simulate in under 2 seconds.

Key terms to know:

- **Hall call vs car call** — a floor's up/down button versus a floor button inside a cabin.
- **SCAN / LOOK** — keep moving one way serving stops; LOOK reverses as soon as no stops remain ahead.
- **Dispatcher strategy** — picks a car for a hall call by minimising a cost function.
- **Cost function** — distance plus penalties for queued stops and direction mismatch.
- **State pattern** — `CarState` for idle, moving and doors-open behaviour.
- **Single-writer principle** — only one thread mutates car state; others enqueue requests.
- **Discrete-tick simulation** — time advances in steps, making runs reproducible with a seed.
- **Starvation** — a request waiting indefinitely; fixed by ageing (boosting old calls).
- **p95 wait** — the wait time 95% of passengers beat; shows the tail, not just the average.

Q: How does one car decide its next stop?

A: LOOK: continue in the current direction to the nearest pending stop ahead; when none remain, reverse. Going up, the next stop is `up.ceiling(currentFloor)`; if that is null, switch to `down.floor(currentFloor)`. Both are O(log n), so you never sort a list each tick.

Q: How do you assign a hall call among cars?

A: A dispatcher strategy computes a cost per car (distance, direction compatibility, queued stops) and picks the cheapest. A car moving up below floor 10 is cheap for an "up at 10" call; a car already past it is expensive because it must finish its run and come back. Strategies are swappable and compared in simulation.

Q: How do you handle concurrent button presses?

A: Presses go into a thread-safe queue; one controller thread drains it at the start of each tick and applies them. Car state has a single writer, so it needs no locks and every tick is deterministic.

Q: Why separate stop ordering from dispatch?

A: They change for different reasons: LOOK ordering is a property of one cabin, while dispatch policy (nearest car, least loaded, zoning) is a building-level business choice. Keeping them apart lets you swap dispatch strategies without touching cabin code, and test each alone.

Q: How do you prevent a quiet floor from starving?

A: Record each hall call's creation time and add an age term to the cost or force-assign calls older than a threshold. The p95 wait metric catches starvation that the average hides.

Q: What happens if a car breaks down mid-run or fire mode starts?

A: Assignments live in the dispatcher, not only in the car, so a failed car's hall calls are reassigned to others. Fire mode is a system mode that stops accepting calls and sends every car to the ground floor without intermediate stops.

Q: Code-level: what does the next-stop lookup look like?

A: Two sorted sets per car.

```
Integer next(int floor, Direction dir) {
    if (dir == UP) { Integer s = up.ceiling(floor); return s != null ? s : down.floor(floor); }
    Integer s = down.floor(floor); return s != null ? s : up.ceiling(floor);
}
```

`ceiling` returns the least element at or above `floor`, `floor` the greatest at or below.

Q: How do you prove one dispatch strategy is better?

A: Run the same seeded passenger stream through each strategy and assert the smarter one's average and p95 waits beat a round-robin baseline. Fixed seeds make the comparison repeatable, and a concurrency test asserts every request is served exactly once.

Q: What changes at 10x cars or floors?

A: Scoring is O(cars) per hall call, still trivial at 80 cars. Very tall buildings use zoning (cars serve floor bands) or destination dispatch, where passengers enter their destination at the lobby and are grouped, which changes the input model rather than the cabin code.

Common mistakes in answers:

- Serving requests first-come-first-served, which zig-zags cars.
- Letting caller threads lock and modify car objects directly.
- Mixing the cabin state machine, stop ordering and dispatch into one `Elevator` class.

TL;DR

Per-car state machine plus LOOK stop ordering, a cost-based dispatcher strategy across cars, and a single-writer loop fed by a concurrent request queue.

12. Movie Ticket Booking with Seat Locks

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** Ch 12, Ch 15

What it is

The core of a cinema booking service (like BookMyShow or Fandango): browse shows, view a seat map, pick seats, **hold** them for a few minutes while paying, and confirm. The defining problem is the seat hold: two people clicking the same seat at the same moment must not both get it.

The problem it solves

Popular shows open for sale and thousands of people click at once. Without careful locking, two users can pay for the same seat ("double booking"), or seats can stay locked forever when a user abandons payment. The project teaches **temporary holds with expiry**, atomic multi-seat reservation (all seats or none), and the difference between a lock held in memory and the final confirmed booking.

Real-world examples

- The handbook's booking chapter covers the BookMyShow-style design; this capstone implements the seat-hold engine underneath it.
- When holds move to a database, PostgreSQL's row locks (explicit locking) and `SELECT ... FOR UPDATE SKIP LOCKED` (SELECT docs) are the standard tools for "grab these rows unless someone else has them".
- In memory, ConcurrentHashMap offers atomic per-key operations such as `compute` and `putIfAbsent`, which can implement per-seat holds.

Requirements


Functional

- Cinemas, screens with seat layouts (rows, seat types, prices), movies, and shows (movie + screen + start time).
- Seat map for a show: each seat `AVAILABLE`, `HELD`, or `BOOKED`.
- `hold(show, seats, user)` holds all requested seats for 10 minutes or fails if any is taken.
- `confirm(holdId, payment)` books them if the hold has not expired. `release(holdId)` frees them.
- Expired holds are released automatically. A user may have one active hold per show.

Non-functional


- No double booking under any interleaving — proven by concurrency tests.
- `hold` under 5 ms in memory with 500 concurrent users on one show.
- Expiry accuracy within 1 second.

The architecture



- **BookingService** — orchestrates hold, payment and confirmation.
- **ShowInventory** — the seat states of one show; the only place seat status changes, using atomic operations.
- **Hold** — a temporary claim with an expiry time.
- **HoldExpiryScheduler** — releases holds at expiry (a `ScheduledExecutorService` or a `DelayQueue`).
- **PaymentGateway** — external payment behind an interface.
- **PricingStrategy** — seat-type pricing, weekend surcharges.
- **BookingRepository** — confirmed bookings, the durable record.

Data model



Type	Notes
`SeatId`	record (row, number)
`SeatState`	sealed: `Available`, `Held(holdId, expiresAt)`, `Booked(bookingId)`
`Show`	id, movie, screen, start, layout reference
`Booking`	id, show, seats, user, amount, payment reference

Tech stack

Component	Choice	Why
Seat states	`ConcurrentHashMap<SeatId, SeatState>` per show	atomic per-seat updates
Multi-seat atomicity	lock seats in sorted order, or one lock per show	all-or-nothing
Expiry	`DelayQueue` or `ScheduledExecutorService`	timed release
Tests	JUnit 6, AssertJ, virtual threads	massive contention tests

Milestones

1. **Catalogue and seat maps.** *Done when:* a show's seat map renders with prices from the strategy.
2. **Single-seat hold.** *Done when:* 1,000 virtual threads holding the same seat produce exactly one success.

3. **Multi-seat all-or-nothing.** *Done when:* two users holding overlapping sets {A1, A2} and {A2, A3} never both succeed and no seat is left half-held.
4. **Confirm and expiry.** *Done when:* confirm after expiry fails, and expired seats become available within 1 s (test clock + manual expiry run).
5. **Payment failure paths.** *Done when:* a failing gateway leaves seats held until expiry or explicit release, never booked.

Deep dive: the hard parts

All-or-nothing across seats. Per-seat atomic operations are not enough: you might hold A1, then fail on A2, and must roll back A1 — while someone else may have seen A1 as held and given up. Two clean options: (1) one `ReentrantLock` per show: check all seats, then mark all — simple, and fine because a single show rarely exceeds a few hundred requests per second; (2) per-seat locks acquired in sorted seat order (preventing deadlock), then check and mark. Build (1), measure, then try (2).

Expiry that does not race confirm. The expiry task and a late `confirm` can run at the same time. Both must go through the same atomic check: release only "if still held by this hold id", confirm only "if still held by this hold id and not expired". Using `compute` per seat (or the show lock) makes these conditional updates atomic.

Holding is not paying. Payment calls are slow and can fail or time out. Never hold a lock during the payment call. Sequence: hold (fast, locked) → pay (slow, no lock) → confirm (fast, locked, checks hold still valid). If confirm fails after payment succeeded, refund — a compensating action.

Testing strategy

Contention tests with `Executors.newVirtualThreadPerTaskExecutor()` and a start latch. Invariant check after each run: every seat is in exactly one state, and no seat appears in two bookings. Mockito for the payment gateway to script success, failure and timeout. A test clock to drive expiry deterministically.

Trade-offs, scaling and failure modes

In-memory holds vanish on restart; a production version stores holds in a database or Redis with expiry. A per-show lock serialises a blockbuster's opening, but each operation is microseconds, so it is usually acceptable; shard by section if not. Showing stale seat maps is fine (refresh on failure), but the hold itself must be strongly consistent. Bots grabbing seats call for per-user hold limits.

Stretch goals

- Persist with PostgreSQL: a `seat_hold` table, `FOR UPDATE` in seat order, expiry by `expires_at`.
- Waitlist for sold-out shows, notified when a hold expires.
- "Best available" seat suggestion (adjacent seats nearest the centre).

Skills practised

- Ch 15 — Booking 1: the BookMyShow case.
- Ch 12 — Concurrency concepts: locks, atomic compute, lock ordering.
- Ch 13 — Concurrency problems: TTL caches and timed expiry.

In the interview

30-second answer: I built the seat-hold engine of a cinema booking service: a user holds a set of seats for 10 minutes, pays, then confirms, and two users can never get the same seat. Holds are all-or-nothing under one `ReentrantLock` per show, which is simple and fast enough because each operation takes microseconds. The key decision is never holding a lock during payment: hold

(locked, fast), pay (no lock, slow), confirm (locked, checks the hold is still valid), with a refund if confirm fails. 1,000 virtual threads racing for one seat produced exactly one success.

Key terms to know:

- **Seat hold** — a temporary, expiring claim on seats, different from a confirmed booking.
- **Double booking** — two users confirmed for one seat; the invariant this design prevents.
- **All-or-nothing reservation** — every requested seat is held or none is.
- **Conditional update** — change state only if it is still what you expect, such as "release if still held by hold 42".
- **Lock ordering** — acquiring per-seat locks in sorted seat order to avoid deadlock.
- **Expiry** — automatic release via a `ScheduledExecutorService` or `DelayQueue`.
- **Compensating action** — refunding a payment when confirmation fails afterwards.
- **`SELECT ... FOR UPDATE SKIP LOCKED`** — the database version: lock rows, skipping ones others hold.

Q: Two users click the same seat at the same time. What happens?

A: The hold is an atomic conditional update on the seat (or done under the show lock); exactly one succeeds, the other gets "seat unavailable". The seat's state moves from `Available` to `Held(holdId, expiresAt)` only once.

Q: Why hold before payment instead of locking during payment?

A: Payments are slow and can hang; a lock held across them would block everyone else trying to book that show. A timed hold reserves the seat as data, not as a thread lock, so threads are free while the user pays.

Q: What if payment succeeds but the hold expired?

A: Confirm fails its check, and the system refunds the payment, a compensating action, rather than double-booking. The seat may already belong to someone else, so confirmation must never skip the check.

Q: Why are per-seat atomic operations not enough for multiple seats?

A: You might hold A1, then fail on A2, and must roll A1 back, while another user saw A1 as taken and gave up. Either take one lock per show and check-then-mark all seats, or take per-seat locks in sorted order (so two overlapping requests cannot deadlock) and then check and mark.

Q: How do expiry and a late confirm avoid racing?

A: Both go through the same atomic check: release only "if still held by this hold id", confirm only "if still held by this hold id and not expired". With `ConcurrentHashMap.compute` per seat, or under the show lock, those conditional updates cannot interleave.

Q: Code-level: how do you hold one seat atomically with a map?

A: `compute` runs the function atomically for that key.

```
boolean[] ok = {false};
seats.compute(seat, (id, s) -> {
    if (s instanceof Available) { ok[0] = true; return new Held(holdId, now.plus(TEN_MIN)); }
    return s;   // unchanged: someone else has it
});
```

Keep the function short and side-effect free apart from the flag, because other updates to that key wait while it runs.

Q: What changes for a blockbuster opening or across many servers?

A: A per-show lock serialises that show, but each hold is microseconds, so thousands per second still fit; if not, shard by seat section. Across servers, in-memory locks no longer work, so holds move to a database row lock or Redis key with an expiry, and the seat map display can be slightly stale while the hold itself stays strongly consistent.

Q: How do you prove there is no double booking?

A: Contention tests with a virtual-thread executor and a start latch, then an invariant check: every seat is in exactly one state and no seat appears in two bookings. Overlapping requests like {A1, A2} and {A2, A3} must never both succeed, and a test clock drives expiry deterministically.

Q: What happens if the server restarts with active holds?

A: In memory they vanish, which frees the seats early; payments in flight then fail confirmation and are refunded. Production stores holds with an `expires_at` column so a restart neither loses nor leaks them.

Common mistakes in answers:

- Holding a lock or a database transaction open while waiting for the payment provider.
- Holding seats one by one with no rollback, leaving seats half-held.
- Forgetting that the expiry job and confirm can run at the same moment.

TL;DR

Timed holds via atomic conditional updates, all-or-nothing multi-seat reservation, no locks across payment, and expiry that races safely with confirm.

13. Splitwise

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 11, Ch 20

What it is

An expense-sharing service: friends in a group add expenses ("I paid 120 for dinner, split equally among 4"), the system tracks who owes whom, and suggests a short list of payments to settle up. Split types include equal, exact amounts, percentages and shares.

The problem it solves

Group spending creates a web of small debts that nobody can track mentally. The design problems are: modelling different split types without a pile of conditionals, keeping balances exact (no lost cents when 100 is split three ways), and **simplifying debts** — replacing many payments with as few as possible while everybody still ends up even.

Real-world examples

- Splitwise's own blog post Debts made simple describes its debt-simplification feature and the fairness rules it keeps — for example, nobody ends up owing more in total than before.
- The handbook's components chapter has the full Splitwise case study; this project adds exact rounding and simplification.

Requirements

Functional


- Users and groups. Add an expense: payer(s), amount, participants and split type (equal, exact, percent, shares).
- Validate splits: exact amounts sum to the total; percentages sum to 100.

- Balances per pair of users and net balance per user, per group and overall.
- Settle up: record a payment between two users.
- Simplify: compute a minimal-ish list of transfers that settles the group.
- Edit or delete an expense; balances update accordingly.

Non-functional

- Exact arithmetic: no cent is created or lost; rounding remainders assigned deterministically.
- Balance queries O(1) after each update (maintained incrementally).
- Simplification for a 50-person group in under 100 ms.

The architecture



- **ExpenseService** — validates requests, picks the split strategy, records the expense and updates balances.
- **SplitStrategy** — one class per split type; each returns a map from user to owed amount that sums exactly to the total.
- **BalanceSheet** — maintains pairwise and net balances incrementally; `revert` supports edits and deletes.
- **DebtSimplifier** — computes settlement transfers from net balances.
- **Expense** — immutable record of who paid what and who owes what.

Data model

Type	Notes
`Money`	long minor units + currency
`Expense`	id, group, description, `paidBy: Map<User, Money>`, `owed: Map<User, Money>`, created time
`Settlement`	from, to, amount (also stored as an expense-like record)
`Transfer`	output of simplification: from, to, amount
`SplitType`	`EQUAL`, `EXACT`, `PERCENT`, `SHARES`

Tech stack

Component	Choice	Why
Money	long cents	exact sums
Strategy selection	`Map<SplitType, SplitStrategy>`	no switch in the service
Simplification	two priority queues	greedy pairing of largest creditor and debtor
Tests	JUnit 6, AssertJ, jqwik	property: sums always balance

Milestones

1. **Split strategies.** *Done when:* 100.00 split equally among 3 yields 33.34, 33.33, 33.33, and the assignment of the extra cent is deterministic.
2. **Expenses and balances.** *Done when:* after a set of expenses, `net` for each user matches a hand-calculated table and all nets sum to zero.
3. **Settle-up and edit/delete.** *Done when:* deleting an expense restores balances exactly.
4. **Simplification.** *Done when:* a group with 6 pairwise debts settles in at most n-1 transfers and every net reaches zero.
5. **CLI or REST front end.** *Done when:* a scripted session of commands reproduces the expected output.

Deep dive: the hard parts

Rounding remainders. 100 cents split three ways is 33 each with 1 left over. Compute the base share with integer division, then hand out the remainder one cent at a time in a deterministic order (e.g. sorted by user id, or payer last). For percentages, compute each share with floor, then distribute the leftover cents to the largest fractional parts. The invariant: shares always sum to exactly the total.

Net balances make simplification easy. Pairwise debts are a graph; what matters for settling is each person's *net* (paid minus owed). Split people into creditors (positive) and debtors (negative). Repeatedly match the largest debtor with the largest creditor, transfer the smaller of the two amounts, and requeue whoever is not yet at zero. This produces at most n-1 transfers. Finding the true minimum is NP-hard in general (it relates to partitioning into zero-sum subsets), so greedy is the practical choice — say this in an interview.

Fairness constraints. Greedy can create a payment between two people who never shared an expense. Splitwise's post lists rules to avoid surprises; a stricter simplifier only nets within existing debt relationships. Make it a second `DebtSimplifier` implementation.

Testing strategy

Property-based tests (jqwik): for random expenses and split types, shares sum to the total and nets sum to zero; after applying simplification transfers, every net is zero. Example tests for each split type's validation errors. Mutation check: deleting then re-adding an expense leaves balances unchanged.

Trade-offs, scaling and failure modes

Storing only expenses and recomputing balances is simple and always consistent but slow for long histories; incremental balances are fast but must be updated in the same transaction as the expense. Multi-currency groups need conversion at a recorded rate per expense. Concurrent edits to one group should be serialised (a per-group lock), since balance updates touch many users.

Stretch goals

- Multiple payers for one expense.
- Multi-currency groups with per-expense exchange rates.

- Activity feed and notifications via an observer.

Skills practised

- Ch 20 — Components: the Splitwise case.
- Ch 11 — Behavioral patterns 2: Strategy for splits.
- Ch 5 — Design principles: immutability, single responsibility.

In the interview

30-second answer: I built an expense-sharing service where each split type (equal, exact, percent, shares) is a `SplitStrategy` that returns shares summing exactly to the total, with leftover cents handed out in a deterministic order. A `BalanceSheet` keeps pairwise and net balances incrementally, so balance queries are O(1) and deleting an expense reverts it exactly. Settle-up uses net balances and greedily matches the largest debtor with the largest creditor, which needs at most n-1 payments. Finding the true minimum is NP-hard, so greedy is the practical choice, and a property test checks that nets always sum to zero.

Key terms to know:

- **Split strategy** — one class per split type, chosen from a `Map<SplitType, SplitStrategy>`.
- **Rounding remainder** — the leftover cents after integer division, distributed deterministically.
- **Largest remainder method** — for percentages, floor every share then give extra cents to the largest fractional parts.
- **Net balance** — total paid minus total owed for one person; all nets in a group sum to zero.
- **Pairwise balance** — who owes whom directly, kept for display and fairness rules.
- **Debt simplification** — replacing many debts with fewer transfers that leave every net at zero.
- **Greedy matching** — pair largest debtor and creditor using two priority queues; at most n-1 transfers.
- **NP-hard** — no known fast exact algorithm; the minimum-transfer problem relates to splitting into zero-sum subsets.
- **Property-based test** — random inputs checked against invariants (jqwik).

Q: How do you split 100 among 3 without losing a cent?

A: Work in cents: 10,000 / 3 = 3,333 with remainder 1. Give everyone 3,333, then hand out the remaining cent one at a time in a deterministic order, such as sorted by user id. Shares always sum exactly to the total, and the same input always gives the same split.

Q: How do you minimise the number of settlement payments?

A: Compute net balances, then greedily match the largest debtor to the largest creditor, transfer the smaller amount, and requeue whoever is not yet at zero. Each step zeroes at least one person, so it needs at most n-1 payments. The exact minimum is NP-hard, so greedy is the practical answer.

Q: How do you add a new split type?

A: Write a new `SplitStrategy` class and register it in the map; `ExpenseService` does not change. Each strategy validates its own input, for example percentages summing to 100.

Q: Why keep balances incrementally instead of recomputing from all expenses?

A: Incremental balances make reads O(1), which matters when the UI shows balances on every screen. The cost is that the balance update must happen together with saving the expense, ideally in one transaction or under one per-group lock, otherwise they drift. Recomputing from expenses is always correct, so it doubles as a test oracle.

Q: How do edit and delete work?

A: An expense is immutable. Delete applies the reverse of its shares to the balance sheet; edit is delete-old plus add-new. A test that deletes and re-adds an expense checks balances come back unchanged.

Q: Code-level: how do you split equally with exact cents?

A: Integer division plus a remainder loop over a sorted list.

```
long base = total / n, rem = total % n;
Map<User, Long> shares = new LinkedHashMap<>();
for (int i = 0; i < users.size(); i++)          // users sorted by id
    shares.put(users.get(i), base + (i < rem ? 1 : 0));
```

Q: What is the fairness problem with greedy simplification?

A: Greedy can make Alice pay Carol even though they never shared an expense, which surprises users. A stricter simplifier only nets debts along existing relationships; it is a second `DebtSimplifier` implementation, chosen per group.

Q: What happens with concurrent edits or 10x bigger groups?

A: Two edits to one group touch many balances, so serialise them with a per-group lock or a database transaction. Simplification is O(n log n) with heaps, so a 500-person group is still milliseconds; long histories are fine because balances are incremental.

Q: How do you test it?

A: Property tests: for random expenses and split types, shares sum to the total and nets sum to zero; after applying the simplifier's transfers, every net is zero. Example tests cover each split type's validation errors.

Common mistakes in answers:

- Using `double` and rounding each share, which creates or loses a cent.
- Claiming greedy gives the minimum number of transfers.
- A `switch` on split type inside the service instead of strategies.

TL;DR

Split strategies that sum exactly, incremental net balances, and a greedy creditor/debtor matcher for settle-up.

14. Rate Limiter Library

Level: Intermediate · **Time:** 1 week · **Prerequisites:** Ch 11, Ch 13, Ch 20

What it is

A reusable Java library that decides whether a request may proceed, given a limit such as "100 requests per minute per API key". It offers several algorithms behind one interface — token bucket, fixed window, sliding window log and sliding window counter — and can be dropped into any service as a filter.

The problem it solves

Without rate limiting, one misbehaving client (or attacker) can exhaust a service for everyone. Limits also protect expensive downstream resources and enforce pricing tiers. The engineering problem is to make the check **fast** (it runs on every request), **thread-safe** (many requests at once), **memory-bounded** (millions of keys) and **fair** at window boundaries.

Real-world examples

- Guava's RateLimiter hands out permits at a configured rate and can block callers until a permit is available — a smoothed token-bucket style limiter.
- Bucket4j is a Java token-bucket library that also supports distributed buckets backed by shared stores.
- Stripe's engineering post Scaling your API with rate limiters describes using token buckets plus concurrency limits and load shedding in production.

Requirements


Functional

- `RateLimiter.tryAcquire(key)` returns allowed/denied plus "retry after" when denied. Optional `tryAcquire(key, permits)`.
- Algorithms: token bucket, fixed window counter, sliding window log, sliding window counter.
- Per-key limits from a rule set (by API key, by user, by IP), with defaults.
- Optional blocking `acquire(key, timeout)`.
- Expose metrics: allowed, denied per key.

Non-functional

- `tryAcquire` under 1 microsecond median in memory; no global lock.
- Memory: idle keys evicted; bounded total keys (e.g. 1 million).
- Correct under 64 concurrent threads: never more than the limit allowed per window.

The architecture



- **RateLimiter** — the public interface. Callers never see algorithms.
- **KeyedRateLimiter** — maps each key to its own algorithm instance, created lazily with `computeIfAbsent`.
- **LimitAlgorithm** — the Strategy; each instance holds the state for one key.
- **RuleResolver** — chooses the limit for a key (tier, route, default).
- **TimeSource** — injected clock so tests can move time.

Data model

Algorithm	State per key	Memory	Boundary behaviour
Token bucket	tokens, last refill time	O(1)	allows bursts up to capacity
Fixed window	window start, count	O(1)	up to 2x limit across a boundary
Sliding log	deque of timestamps	O(limit)	exact
Sliding counter	current + previous counts	O(1)	close approximation

Tech stack

Component	Choice	Why
Per-key map	`ConcurrentHashMap`	lock-free reads, atomic create
Per-key state	`AtomicLong` CAS loop or small `synchronized` block	no global lock
Time	`System.nanoTime` behind `TimeSource`	monotonic, testable
Benchmarks	JMH	measure, do not guess
Tests	JUnit 6, AssertJ, jcstress for races	concurrency correctness

Milestones

1. **Token bucket, single thread.** *Done when:* with capacity 10 and 1 token/s, 10 immediate calls pass, the 11th fails, and after 1 s of fake time one more passes.
2. **Other algorithms.** *Done when:* a shared test suite runs against every algorithm, and a boundary test shows fixed window allowing a 2x burst while sliding log does not.
3. **Keyed limiter with rules.** *Done when:* two keys with different tiers get different limits.
4. **Thread safety.** *Done when:* 64 threads hammering one key allow exactly the limit within a window (no over-admission).
5. **Eviction + benchmarks.** *Done when:* idle keys are evicted after a TTL, and a JMH run reports median `tryAcquire` latency.

Deep dive: the hard parts

Lazy refill. A token bucket does not need a timer thread. On each call, compute elapsed time since last refill, add `elapsed * rate` tokens (capped at capacity), then try to take. Store tokens as a scaled integer (e.g. micro-tokens) to avoid floating point drift.

Atomic update without a big lock. Two threads reading "1 token left" must not both take it. Either guard the tiny refill-and-take section with `synchronized` on the per-key object (contention is per key, usually low) or pack state into one `AtomicLong` and loop with `compareAndSet`. Measure both with JMH; the simple lock is often fast enough.

Sliding window counter. Keep counts for the current and previous fixed windows. Estimate the rolling count as `current + previous * (1 - elapsedFractionOfCurrentWindow)`. It costs O(1) memory and is accurate enough for most APIs; sliding log is exact but stores one timestamp per request.

Memory. A key per IP can mean millions of entries. Evict idle buckets: a full token bucket that has not been touched is equivalent to a new one, so it is safe to drop it.

Testing strategy

One abstract test class with the behavioural contract, extended per algorithm. A fake `TimeSource` to step time precisely. Concurrency tests with a start latch and an exact count assertion; jcstress tests for the CAS loop. JMH benchmarks for single-key and many-key workloads.

Trade-offs, scaling and failure modes

In-process limits are per instance: with 10 servers each allowing 100/min, a client gets 1,000/min. A shared store (Redis, or Bucket4j's distributed mode) gives a global limit at the cost of a network hop per request; a hybrid gives each instance a share of the budget. Decide whether to fail open (allow) or fail closed (deny) when the shared store is down — most APIs fail open.

Stretch goals

- A servlet filter or Spring `HandlerInterceptor` that returns HTTP 429 with a `Retry-After` header.
- A concurrency limiter (max in-flight requests) using `Semaphore`.
- A Redis-backed implementation behind the same interface.

Skills practised

- Ch 20 — Components: the rate limiter case.
- Ch 13 — Concurrency problems: thread-safe token bucket.
- Ch 11 — Behavioral patterns 2: Strategy.

In the interview

30-second answer: I built a rate-limiting library with one `RateLimiter.tryAcquire(key)` interface and four algorithms behind it as strategies: token bucket, fixed window, sliding log and sliding window counter. Each key gets its own algorithm instance from a `ConcurrentHashMap`, so there is no global lock, and the token bucket refills lazily from elapsed time instead of using a timer thread. 64 threads hammering one key never got more than the limit, and JMH measured the median `tryAcquire` cost. Idle keys are evicted because a full untouched bucket is the same as a new one.

Key terms to know:

- **Token bucket** — tokens refill at a fixed rate up to a capacity; each request takes one; allows bursts.
- **Fixed window counter** — count per calendar window; can allow up to 2x the limit across a boundary.
- **Sliding window log** — stores each request's timestamp; exact but O(limit) memory per key.
- **Sliding window counter** — weights the previous window's count; O(1) memory, close approximation.
- **Lazy refill** — compute tokens added since the last call instead of a background thread.
- **Compare-and-set (CAS)** — atomically update a value only if it still equals what you read; retry otherwise.
- **Monotonic clock** — `System.nanoTime`, which never jumps backwards like wall-clock time can.
- **Fail open / fail closed** — allow or deny traffic when the shared limit store is down.
- **HTTP 429 + Retry-After** — the standard "too many requests" response.

Q: Token bucket or sliding window?

A: Token bucket if short bursts are acceptable and you want O(1) state; sliding window counter for smoother limits with O(1) state; sliding log only if you need exactness and can afford one timestamp per request. Fixed window is simplest but allows a 2x burst at boundaries.

Q: Why can a fixed window allow twice the limit?

A: With 100 per minute, a client can send 100 at 0:59 and 100 more at 1:00, because they fall into different windows. That is 200 requests in two seconds. Sliding approaches look at the last 60 seconds instead.

Q: How do you avoid a background refill thread?

A: Refill lazily on each request: tokens = min(capacity, tokens + elapsed * rate), then try to take one. Store tokens as a scaled integer (micro-tokens) to avoid floating-point drift.

Q: How do you make `tryAcquire` thread-safe without a global lock?

A: State is per key, so contention is per key. Either guard the tiny refill-and-take step with `synchronized` on the key's bucket, or pack the state into one `AtomicLong` and loop with `compareAndSet`. Measure both with JMH; the simple lock is often fast enough.

Q: Code-level: what does a CAS loop look like?

A: Read, compute, and retry if another thread changed the value first.

```
while (true) {
    long cur = state.get();
    long next = refillAndTake(cur, timeSource.nanos());   // returns -1 if no token
    if (next < 0) return false;
    if (state.compareAndSet(cur, next)) return true;
}
```

Q: How do you enforce a global limit across servers?

A: In-process limits are per instance, so 10 servers at 100/min give a client 1,000/min. Keep the counter in a shared store with atomic operations (Redis, Bucket4j's distributed mode), or give each instance a share of the budget. Then choose fail-open or fail-closed for store outages; most public APIs fail open.

Q: What breaks first with millions of keys?

A: Memory: one bucket per IP address grows without bound. Evict idle keys after a TTL (safe because a full bucket equals a new one) and cap total keys. The `ConcurrentHashMap` itself scales fine.

Q: How do you test the algorithms?

A: One abstract contract test class extended per algorithm, driven by a fake `TimeSource` so you can step time exactly. A boundary test shows fixed window admitting a 2x burst while sliding log does not, and a concurrency test with a start latch asserts exactly the limit is admitted; jcstress checks the CAS loop.

Common mistakes in answers:

- One `synchronized` method around the whole limiter, which makes every key contend on one lock.
- Using `System.currentTimeMillis()`, which can jump when the clock is adjusted.
- Forgetting that per-instance limits multiply by the number of servers.

TL;DR

One `RateLimiter` interface, several algorithm strategies holding per-key state, lazy refill, per-key atomic updates and eviction of idle keys.

15. LRU and LFU Cache

Level: Intermediate · **Time:** 1 week · **Prerequisites:** Ch 9, Ch 13, Ch 20

What it is

A generic in-memory cache library with a fixed capacity and pluggable **eviction policies**: LRU (least recently used — throw out what was touched longest ago) and LFU (least frequently used — throw out

what is used least often), both with O(1) `get` and `put`. Later milestones add thread safety, time-to-live and statistics.

The problem it solves

Caches make slow things fast by keeping recent results in memory, but memory is finite, so something must be thrown away. Choosing the wrong item to evict wastes the cache. The coding problem — O(1) LRU and LFU — is a top interview question, and the design problem is making eviction policy, storage and concurrency separate concerns.

Real-world examples

- Caffeine is the leading Java caching library; its efficiency wiki page explains W-TinyLFU, which combines a small LRU admission window with frequency-based admission into a main segmented LRU.
- The JDK's LinkedHashMap supports access order and a `removeEldestEntry` hook — a two-line LRU you should compare against yours.

Requirements


Functional

- `Cache<K, V>` with `get`, `put`, `remove`, `size`, and `getOrLoad(key, loader)`.
- Policies: LRU, LFU (ties broken by recency), and FIFO as a baseline.
- Optional per-entry or global TTL (time-to-live).
- Eviction listener callback. Statistics: hits, misses, evictions, hit ratio.

Non-functional

- O(1) average `get` and `put` for every policy.
- Thread-safe variant: correct under 32 threads; throughput benchmarked with JMH.
- `getOrLoad` loads each missing key once even if many threads ask at once.

The architecture



- **Cache** — the public interface.
- **BoundedCache** — the storage map plus capacity enforcement; asks the policy for a victim when full.
- **EvictionPolicy** — Strategy that tracks usage and nominates victims.
- **ConcurrentCache** — a Decorator adding thread safety (and later striping) around any cache.
- **StatsRecorder / RemovalListener** — observability and callbacks.

Data model

Policy	Structure	Operations
LRU	hash map + doubly linked list	move node to head on access, evict tail
LFU	key to node, frequency to linked list, `minFreq`	move node to freq+1 list, evict from `minFreq` list tail
FIFO	queue	evict head
TTL	per-entry `expiresAt` + lazy check on read	optional sweeper

Tech stack

Component	Choice	Why
Lists	hand-written doubly linked nodes	O(1) unlink, interview-ready
Concurrency	`ReentrantLock`, then lock striping	measure the difference
Single-flight load	`ConcurrentHashMap<K, CompletableFuture<V>>`	one load per key
Benchmarks	JMH, compare with Caffeine	honest baseline
Tests	JUnit 6, AssertJ, jqwik	model-based tests

Milestones

1. **LRU, single-threaded.** *Done when:* capacity 2, put a, put b, get a, put c evicts b.
2. **LFU.** *Done when:* the least-frequent key is evicted, with ties broken by least recent; all operations O(1).
3. **Policy as strategy.** *Done when:* one `BoundedCache` works with all three policies via constructor injection.
4. **TTL and stats.** *Done when:* an entry expires after its TTL on a fake clock, and hit ratio is reported.
5. **Concurrency.** *Done when:* 32 threads pass a stress test, `getOrLoad` calls the loader once per key under contention, and JMH shows throughput vs Caffeine.

Deep dive: the hard parts

O(1) LRU. The map gives O(1) lookup of a node; the doubly linked list gives O(1) move-to-front and remove-tail because each node knows its neighbours. Sentinel head and tail nodes remove all null checks.

O(1) LFU. Keep a map from frequency to a doubly linked list of nodes with that frequency, plus a `minFreq` variable. On access, move the node from list f to list f+1; if list f is now empty and f was `minFreq`, increment `minFreq`. On insert, the new node has frequency 1 and `minFreq` becomes 1. Evict from the tail of the `minFreq` list (least recent among least frequent).

Concurrency: why a plain lock hurts LRU. Even `get` mutates the list (move to front), so reads need the write lock. Options: lock striping (N independent caches by key hash — approximate global LRU), or Caffeine's approach of recording reads in buffers and replaying them in batches. Implement striping and measure.

Cache stampede. When a hot key expires, hundreds of threads miss and call the loader at once. Store a `CompletableFuture` in a `ConcurrentHashMap` via `computeIfAbsent`; the first caller loads, the rest wait for the same future.

Testing strategy

Model-based testing: run random operation sequences against your cache and a simple reference model (e.g. a `LinkedHashMap` in access order for LRU) and assert identical results. Concurrency tests with invariants (size never above capacity). JMH for throughput. A fake ticker for TTL.

Trade-offs, scaling and failure modes

LRU is cheap but a one-off scan of many keys flushes the hot set; LFU resists scans but keeps once-popular items too long unless counts decay — which is why W-TinyLFU exists. Striped locks scale but each stripe evicts independently. Caches hide bugs: stale data after writes needs invalidation or short TTLs.

Stretch goals

- Weight-based capacity (entries cost different amounts of memory).
- Frequency decay (halve all counts periodically) for LFU.
- Refresh-ahead: reload hot entries in the background before they expire.

Skills practised

- Ch 20 — Components: cache and LRU case.
- Ch 13 — Concurrency problems: TTL cache, lock striping.
- Ch 9 — Structural patterns: Decorator for thread safety.

In the interview

30-second answer: I built a generic cache with pluggable eviction policies: LRU with a hash map plus a doubly linked list, and LFU with frequency buckets of linked lists plus a `minFreq` pointer, both O(1) for `get` and `put`. Storage and policy are separate (Strategy), and thread safety is a Decorator, first one lock and then lock striping. `getOrLoad` stores a `CompletableFuture` per key so a hot key is loaded once even when many threads miss together, which prevents a cache stampede. Model-based tests compare every random operation against a `LinkedHashMap` reference, and JMH compares throughput with Caffeine.

Key terms to know:

- **LRU** — evict the entry used longest ago.
- **LFU** — evict the entry used least often; ties broken by least recent here.
- **Doubly linked list with sentinels** — O(1) unlink and move-to-front; dummy head and tail remove null checks.
- **`minFreq`** — the lowest frequency currently present, so LFU eviction is O(1).
- **Eviction policy as Strategy** — `EvictionPolicy` tracks usage and nominates victims.
- **Lock striping** — N independent locked segments chosen by key hash; approximate global LRU.
- **Cache stampede (thundering herd)** — many threads missing one key and loading it at once.
- **Single-flight loading** — one shared future per key so the loader runs once.
- **TTL** — time-to-live after which an entry is treated as missing.
- **W-TinyLFU** — Caffeine's policy combining a small LRU window with frequency-based admission.

Q: How is LRU O(1)?

A: A hash map from key to list node gives O(1) lookup, and a doubly linked list ordered by recency gives O(1) move-to-front and remove-tail because each node knows its neighbours. Every operation is a map lookup plus a few pointer updates.

Q: How is LFU O(1)?

A: A map from frequency to a linked list of nodes with that frequency, plus `minFreq`. On access, move the node from list f to list f+1, and if list f became empty and f was `minFreq`, increment `minFreq`. A new key has frequency 1 so `minFreq` becomes 1, and eviction takes the tail of the `minFreq` list.

Q: What is a cache stampede and how do you prevent it?

A: Many threads miss the same key, often right after it expires, and all call the slow loader at once. Coalesce loads with `computeIfAbsent(key, k -> new CompletableFuture<>())`: the first caller loads, the rest wait on the same future.

Q: Code-level: what is the two-line JDK LRU?

A: `LinkedHashMap` in access order with an eviction hook.

```
var lru = new LinkedHashMap<K, V>(16, 0.75f, true) {          // true = access order
    @Override protected boolean removeEldestEntry(Map.Entry<K, V> e) { return size() > capacity; }
};
```

It is not thread-safe; wrapping it in `Collections.synchronizedMap` works but every `get` takes the same lock.

Q: Why does a plain read-write lock not help LRU?

A: Even `get` mutates the list (move to front), so reads need exclusive access and a read lock gives no parallelism. Lock striping gives parallelism at the cost of approximate global order; Caffeine instead records reads in buffers and replays them in batches.

Q: LRU or LFU: which and why?

A: LRU is cheap and adapts quickly but a one-off scan of many keys flushes the hot set. LFU resists scans but keeps once-popular items too long unless counts decay. W-TinyLFU exists to get both, so for production I would use Caffeine.

Q: How do you implement TTL without a busy sweeper thread?

A: Store `expiresAt` per entry and check it lazily on read, treating expired entries as misses and removing them. An optional periodic sweep frees memory for keys never read again. Use an injected ticker so tests can jump time.

Q: How do you prove the cache is correct?

A: Model-based testing: run random sequences of get/put/remove against your cache and a simple reference (a `LinkedHashMap` in access order for LRU) and assert identical results. Concurrency tests assert size never exceeds capacity and the loader runs once per key under contention.

Q: What changes at 10x data or across many servers?

A: Size by memory weight rather than entry count, and watch garbage-collection pressure from millions of nodes. Across servers each instance has its own cache, so invalidation after writes needs short TTLs or an invalidation message, or a shared cache tier such as Redis.

Common mistakes in answers:

- Using a `PriorityQueue` for LFU, which makes updates O(log n), when O(1) is asked.
- Forgetting that `get` changes LRU order and so is a write.
- Ignoring the stampede when a hot key expires.

TL;DR

Storage plus pluggable eviction strategies with O(1) linked structures, a decorator for thread safety, and single-flight loading.

16. Logging Framework

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 8, Ch 10, Ch 20

What it is

A small logging library in the spirit of SLF4J and Logback: application code calls `log.info("Order {} placed", id)`; the framework filters by level, formats the message, and writes it to one or more destinations (**appenders**: console, file, rolling file). Configuration decides levels per package, and an async mode keeps logging off the request path.

The problem it solves

Every application logs, and badly designed logging is slow (string building for messages that are filtered out), blocks request threads on disk I/O, and is impossible to reconfigure without code changes. This project exercises a lot of patterns at once: **Factory** for loggers, a **hierarchy** of loggers by package name, **Chain of Responsibility** for filters, **Strategy** for layouts, **Observer**-like fan-out to appenders, and a **producer-consumer** queue for async writing.

Real-world examples

- SLF4J is the facade most Java code logs through; it separates the API from the implementation, the same split you build here.
- Logback's appenders manual documents console, file and rolling-file appenders and their policies.
- Log4j 2's asynchronous loggers explain how moving formatting and I/O to a background thread reduces latency for the caller.

Requirements


Functional

- `LoggerFactory.getLogger(Class)` returns a cached logger named by class.
- Levels TRACE, DEBUG, INFO, WARN, ERROR; per-logger level inherited from the nearest configured ancestor (`com.shop` configures `com.shop.order.Service`).
- Parameterised messages `{}` formatted only if the level is enabled. Exceptions printed with stack traces.
- Appenders: console, file, size- or time-based rolling file. Layouts: pattern and JSON.
- Filters per appender (e.g. only ERROR to an alert file).
- Async mode with bounded queue and a policy when full (block, drop lowest levels).
- Config from a properties or YAML file, reloadable at runtime.

Non-functional

- Disabled-level calls cost under 10 ns (a level check and return).
- Async logging adds under 1 microsecond to the caller at the median.
- No log line lost on clean shutdown.

The architecture



- **LoggerFactory / LoggerContext** — create and cache loggers; compute effective levels from the name hierarchy; swap configuration atomically.
- **Logger** — the API. Checks level first, then builds a `LogEvent` and passes it to its appenders (and ancestors' appenders, if additive).
- **Appender** — a destination. **Layout** turns an event into text. **Filter** accepts, denies or stays neutral (a chain).
- **AsyncAppender** — a Decorator: queues events and lets a background thread call the real appender.

Data model

Type	Notes
`LogEvent`	record: timestamp, level, logger name, thread name, message pattern, args, throwable, MDC snapshot
`Level`	enum with integer severity
`Config`	immutable tree: logger name to level and appender refs
MDC (mapped diagnostic context)	per-thread key-value map (request id) copied into each event

Tech stack

Component	Choice	Why
Async queue	`ArrayBlockingQueue` + one consumer thread	bounded memory
Files	`FileChannel` / buffered writer	fast appends
Config swap	`volatile` reference to immutable config	lock-free reads
Benchmarks	JMH	disabled-call and async latency
Tests	JUnit 6, AssertJ, `@TempDir`	real files, rolling checks

Milestones

1. **Logger + console appender + pattern layout.** *Done when:* `log.info("x={}", 5)` prints a formatted line with time, level, logger and thread.
2. **Hierarchy and levels.** *Done when:* configuring `com.shop` at WARN silences INFO from `com.shop.order.Service` but not from `com.other`.
3. **File and rolling appenders.** *Done when:* writing 10 MB with a 1 MB limit leaves 10 numbered files (in `@TempDir`) with no line split across files.
4. **Filters and JSON layout.** *Done when:* an ERROR-only filter on a second appender routes correctly.
5. **Async + shutdown + reload.** *Done when:* JMH shows the async caller cost, a shutdown hook flushes everything, and editing the config file changes levels without restart.

Deep dive: the hard parts

Fast path for disabled levels. The most frequent call is one that is filtered out. Cache each logger's effective level in a field; `info()` first compares integers and returns. Use `{}` placeholders so message strings are not concatenated until needed. Never compute an expensive argument eagerly — offer `Supplier` overloads.

Hierarchical levels and reconfiguration. Effective level = nearest configured ancestor's level. Recomputing on every call is slow; compute it on configuration change for all cached loggers. Publish the new configuration with a single `volatile` write so threads see either all-old or all-new.

Async without losing data. A bounded queue protects memory; when full, choose: block the caller (no loss, but latency), or drop TRACE/DEBUG/INFO and keep WARN/ERROR (Logback's async appender offers a similar discard rule). On shutdown, stop accepting, drain the queue, flush and close files. Capture thread name and MDC *at the call site*, not in the background thread, or the data will be wrong.

Testing strategy

An in-memory `ListAppender` for most tests. `@TempDir` for files and rolling. A concurrency test where 16 threads log 100,000 lines each and the output contains all lines, none interleaved mid-line. JMH benchmarks for the disabled path and async enqueue.

Trade-offs, scaling and failure modes

Sync logging is simple and never loses data but couples latency to disk; async is fast but can lose events on crash (not clean shutdown). A full disk must not crash the app: appenders should catch I/O errors, report once to stderr, and keep going. Logging sensitive data is a security risk — provide a masking layout decorator.

Stretch goals

- SLF4J provider: make your framework a backend for the real SLF4J API.
- Network appender with batching and retry.
- Structured logging with key-value pairs and a JSON schema.

Skills practised

- Ch 20 — Components: the logging framework case.
- Ch 10 — Behavioral patterns 1: Chain of Responsibility for filters.
- Ch 8 — Creational patterns: factory and singleton context.
- Ch 9 — Structural patterns: Decorator (async appender).

In the interview

30-second answer: I built a small SLF4J/Logback-style logging library: `LoggerFactory` caches named loggers in a dotted-name hierarchy, each logger caches its effective level so a disabled call is one integer comparison, and messages use `{}` placeholders so nothing is formatted unless enabled. Appenders write to console or rolling files through a Layout and a Chain of Responsibility of filters. An `AsyncAppender` decorator puts events on a bounded `ArrayBlockingQueue` drained by one background thread, with a drop-low-levels policy when full and a shutdown hook that drains and flushes. Configuration is an immutable tree published through one `volatile` reference, so it can reload without restart.

Key terms to know:

- **Facade (SLF4J)** — an API separated from the implementation that does the work.
- **Logger hierarchy** — `com.shop.order.Service` inherits its level from the nearest configured ancestor such as `com.shop`.
- **Effective level** — the level actually used after inheritance, cached per logger.
- **Appender / Layout** — where events go, and how an event becomes text or JSON.
- **Filter chain** — Chain of Responsibility where each filter accepts, denies or stays neutral.
- **AsyncAppender (Decorator)** — wraps a real appender and moves I/O to a background thread.
- **Bounded queue / backpressure** — a fixed-size queue that forces a choice when full: block or drop.
- **MDC** — mapped diagnostic context, a per-thread map such as request id copied into each event.
- **`volatile` publication** — writing a reference to an immutable object so all threads see all-old or all-new.

Q: How do you make disabled log statements cheap?

A: Cache the effective level per logger, check it first with an integer comparison, and use placeholders or `Supplier` overloads so no string is built and no expensive argument computed unless the level is enabled. The target is under 10 ns, which JMH confirms.

Q: Why an async appender, and what can go wrong?

A: It moves formatting and disk I/O off the caller's thread, so request latency does not depend on the disk. The queue can fill, so you must block or drop by level, and a crash (not a clean shutdown) loses events still in the queue.

Q: How do logger levels inherit?

A: By dotted name: a logger uses the level of its nearest configured ancestor, falling back to the root. Effective levels are recomputed for all cached loggers when configuration changes, not on every call.

Q: Why must thread name and MDC be captured at the call site?

A: In async mode the background thread does the formatting. If it reads `Thread.currentThread().getName()` or the MDC then, it gets its own values, not the caller's. The `LogEvent` record must snapshot them when created.

Q: Code-level: what is wrong with `log.debug("user " + user)`?

A: The string is concatenated, and `user.toString()` runs, even when DEBUG is off.

```
log.debug("user " + user);                // always builds the string
log.debug("user {}", user);               // formats only if DEBUG is enabled
log.debug("stats {}", () -> computeStats()); // supplier: expensive work skipped too
```

The supplier form is how SLF4J 2's fluent API and Log4j 2 avoid eager work; in your library it is an overload.

Q: How do you reload configuration safely while threads are logging?

A: Build a new immutable `Config`, recompute effective levels, then publish with one `volatile` write. Readers never lock and never see a half-applied configuration.

Q: What happens when the disk is full or a file cannot be written?

A: Logging must never crash the application. Appenders catch I/O errors, report once to stderr (not on every line), and keep going, ideally retrying periodically.

Q: How do you test it, including concurrency?

A: An in-memory `ListAppender` for most tests, `@TempDir` for files and rolling. A concurrency test has 16 threads log 100,000 lines each and checks every line is present and none is split mid-line, and a shutdown test checks the async queue is fully flushed.

Q: What changes at 10x log volume?

A: The single consumer thread or the disk becomes the bottleneck, so the queue fills and the drop policy kicks in. Batch writes, use a buffered `FileChannel`, cut DEBUG in production, or ship structured logs to a network appender with batching and retry.

Common mistakes in answers:

- Building the message string before checking the level.
- An unbounded async queue, which turns a slow disk into an out-of-memory crash.
- Reading thread name or MDC in the background thread.

TL;DR

Named loggers in a hierarchy, a cheap level check, appenders with layouts and filter chains, and a bounded async decorator that flushes on shutdown.

17. In-Process Pub/Sub Broker

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 11, Ch 12, Ch 20

What it is

A message broker that lives inside one JVM: publishers send messages to named **topics**; **subscribers** register for topics and receive every message published after they subscribed. Each subscriber gets its own delivery thread and queue, so a slow subscriber does not slow down others. Later milestones add consumer groups, replay from an offset and backpressure.

The problem it solves

Components that call each other directly are tightly coupled: the order service must know about email, analytics and inventory. Publish/subscribe decouples them — the publisher only knows a topic name. Doing it well in-process teaches the Observer pattern under real concurrency: isolation

between subscribers, ordering guarantees, bounded memory and what to do when a consumer cannot keep up.

Real-world examples

- The JDK ships `Flow` (the Reactive Streams interfaces) and `SubmissionPublisher`, an in-process publisher with per-subscriber buffers and demand-based backpressure.
- Guava's `EventBus` is a well-known in-process event bus; its own documentation now discourages new use in favour of dependency injection and reactive libraries — a useful trade-off discussion.

Requirements


Functional

- `createTopic`, `publish(topic, message)`, `subscribe(topic, subscriber)` returning a handle to unsubscribe.
- Per-subscriber ordering: messages arrive in publish order.
- Each topic keeps a bounded log; a subscriber can start from "latest" or from an earlier offset (replay).
- Consumer groups: messages on a topic are split among members of a group (each message to one member).
- Backpressure policy per subscriber when its queue is full: block publisher, drop oldest, or drop newest.
- Acknowledgement and redelivery for failed handlers (up to N attempts, then a dead-letter topic).

Non-functional

- Publishing to a topic with 10 subscribers under 5 microseconds median (enqueue only).
- A subscriber that throws or hangs does not affect others.
- 1 million messages per second aggregate on a laptop for small messages (benchmark and report your real number).

The architecture



- **Broker** — the facade and registry of topics.
- **Topic** — appends to its log and fans out to subscriptions and groups.
- **RingLog** — fixed-size circular buffer of recent messages with monotonically increasing offsets, enabling replay.
- **Subscription** — one per subscriber: a bounded inbox, a delivery thread (virtual thread), current offset, retry state.
- **ConsumerGroup** — chooses one member per message (round robin, or by key hash for per-key ordering).
- **OverflowPolicy** — Strategy for full inboxes.

Data model

Type	Notes
`Message`	record: key, payload, headers, publish time
`Envelope`	message + offset + attempt count
`SubscriptionSpec`	start position, group name, overflow policy, max attempts
`DeliveryState`	sealed: `Pending`, `Acked`, `Failed(attempts)`, `DeadLettered`

Tech stack

Component	Choice	Why
Delivery threads	virtual threads, one per subscription	cheap isolation
Inboxes	`ArrayBlockingQueue`	bounded, blocking
Log	array ring buffer + `AtomicLong` offset	O(1) append, replay
Benchmarks	JMH	throughput, latency
Tests	JUnit 6, AssertJ, Awaitility-style polling helper	async assertions

Milestones

1. **Topics and fan-out.** *Done when:* 3 subscribers each receive all 1,000 messages in order.
2. **Isolation.** *Done when:* a subscriber that sleeps 1 s per message does not delay the others (measured).
3. **Overflow policies.** *Done when:* each policy behaves as specified in tests with a tiny inbox.
4. **Ring log and replay.** *Done when:* a late subscriber starting at offset 0 receives retained history, then live messages, with no gap or duplicate at the switch-over.
5. **Groups, retries, dead letters.** *Done when:* a group of 3 shares messages, and a handler failing 3 times routes the message to the dead-letter topic.

Deep dive: the hard parts

Replay-to-live handover. A late subscriber reads history from the log while new messages keep arriving. If it reads history then subscribes, it can miss messages in between; if it subscribes then reads history, it gets duplicates. The clean approach: the subscription itself reads from the log by offset, so "history" and "live" are the same loop — read offset n, then n+1 — and it only waits when it catches up with the head.

Backpressure is a policy decision. A slow consumer with an unbounded queue eventually exhausts memory. Bounded queues force a choice: block the publisher (protects data, couples speeds), drop (protects the publisher, loses data), or let the subscriber fall behind in the log and skip ahead if overwritten (report the gap). `SubmissionPublisher` uses demand signalling; compare it with your approach.

Ordering with groups. Round-robin across group members loses per-key order. Hash the message key to choose the member (like Kafka partitions) so all messages for one order go to the same consumer, in order.

Testing strategy

Deterministic tests use a test executor that runs deliveries synchronously; concurrency tests use real virtual threads and wait with timeouts. Assert ordering per subscriber, no loss under "block" policy, exact drop counts under drop policies. JMH for publish latency with N subscribers.

Trade-offs, scaling and failure modes

In-process means messages die with the JVM; durable brokers (Kafka, RabbitMQ) persist and replicate at the cost of network and disk. One thread per subscription is simple with virtual threads; a shared pool is more economical but risks one subscriber starving others. Retrying a poison message forever blocks a partition — always cap attempts and dead-letter.

Stretch goals

- Topic wildcards (`orders.*`) via a trie of topic names.
- Persist the log to an append-only file and recover offsets on restart.

- Implement `Flow.Publisher` so reactive libraries can consume your topics.

Skills practised

- Ch 20 — Components: the pub-sub case.
- Ch 11 — Behavioral patterns 2: Observer.
- Ch 12 — Concurrency concepts: blocking queues, virtual threads.
- Ch 13 — Concurrency problems: bounded blocking queue.

In the interview

30-second answer: I built an in-JVM pub/sub broker where each topic appends to a bounded ring log with increasing offsets and each subscription has its own bounded inbox and virtual delivery thread, so a slow subscriber never delays others. Because subscriptions read from the log by offset, replay and live delivery are the same loop, so a late subscriber gets no gap and no duplicate at the switch-over. Full inboxes follow a per-subscription overflow policy (block, drop oldest, drop newest), consumer groups route by key hash to keep per-key order, and failing handlers are retried up to N times then dead-lettered. I report publish latency and throughput from JMH.

Key terms to know:

- **Publish/subscribe** — publishers send to a topic name without knowing who listens; Observer pattern across threads.
- **Topic** — a named stream of messages with its own log.
- **Ring buffer log** — fixed-size circular array; old messages are overwritten, offsets keep increasing.
- **Offset** — a message's position number, used for replay and progress tracking.
- **Backpressure** — how a fast producer is slowed or data dropped when a consumer cannot keep up.
- **Consumer group** — members share a topic's messages; each message goes to one member.
- **Key-hash routing** — same key always to the same member, preserving per-key order like Kafka partitions.
- **Dead-letter topic** — where messages go after the maximum failed attempts.
- **At-least-once delivery** — retries may deliver a message more than once; handlers should be idempotent.

Q: How do you stop one slow subscriber from slowing everyone?

A: Give each subscription its own bounded inbox and delivery thread; the publisher only enqueues. A subscriber that sleeps or throws affects only its own thread, and virtual threads make one thread per subscription cheap.

Q: What happens when an inbox is full?

A: A per-subscription policy decides: block the publisher (no loss, but speeds are coupled), drop oldest or drop newest (publisher protected, data lost), or let the subscriber fall behind in the log and report a gap if overwritten. Each trades data loss against coupling.

Q: How do you keep per-key ordering with multiple consumers?

A: Route by key hash so each key always goes to the same group member, which processes its messages in order. Round-robin spreads load more evenly but loses per-key order.

Q: How do you hand a late subscriber from history to live messages without gaps or duplicates?

A: Read history then subscribe and you miss messages in between; subscribe then read history and you get duplicates. Instead the subscription reads the log by offset, n then n+1, and only waits when it

catches up with the head, so history and live are one loop.

Q: What do you do with a poison message that always fails?

A: Count attempts in the envelope, retry up to a maximum (optionally with backoff), then publish it to a dead-letter topic and move on. Retrying forever would block that subscriber or partition permanently.

Q: Code-level: how do you run one delivery loop per subscription?

A: Start a virtual thread that drains the bounded inbox.

```
Thread.ofVirtual().name("sub-" + id).start(() -> {
    while (running) {
        Envelope e = inbox.take();                  // blocks cheaply on a virtual thread
        try { handler.accept(e.message()); } catch (Exception ex) { retryOrDeadLetter(e); }
    }
});
```

Q: How does this compare with `SubmissionPublisher` or Kafka?

A: `SubmissionPublisher` gives per-subscriber buffers with demand signalling (subscribers request N items), a cleaner backpressure model than blocking. Kafka persists and replicates the log on disk across machines; mine loses everything when the JVM dies, which is the main trade-off.

Q: What changes at 10x subscribers or messages?

A: Fan-out cost grows with subscribers per topic, since each publish enqueues N times. Memory grows with inbox sizes, so they must stay bounded; at very high rates batch deliveries or share a ring buffer where subscribers only track offsets instead of copying messages into inboxes.

Q: How do you test asynchronous delivery reliably?

A: For logic, inject an executor that delivers synchronously so tests are deterministic. For real concurrency, use virtual threads and poll with timeouts (Awaitility style) rather than `sleep`, then assert per-subscriber order, no loss under "block", and exact drop counts under drop policies.

Common mistakes in answers:

- Calling every subscriber synchronously on the publisher's thread.
- Unbounded queues "so nothing is lost", which only delays an out-of-memory crash.
- Promising exactly-once delivery from an in-memory broker with retries.

TL;DR

Topics with a replayable ring log, isolated bounded subscriptions on virtual threads, policy-driven backpressure, key-hashed consumer groups and dead letters.

18. Notification Service

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 8, Ch 11, Ch 20

What it is

A service other parts of a product call to notify users: "send order-shipped to user 42". It picks channels (email, SMS, push, in-app) based on user preferences, renders a template, respects quiet hours and rate limits, retries failed sends with backoff, and records delivery status.

The problem it solves

Every feature team ends up writing its own email code, with inconsistent opt-out handling, no retries and no audit trail. A central notification service owns the hard cross-cutting rules: never notify someone who opted out, never send the same notification twice, do not spam, survive provider outages. In design terms it combines **Factory** (channel senders), **Strategy** (channel selection), **Template Method** (send pipeline), **Chain of Responsibility** (pre-send checks) and retry logic.

Real-world examples

- Novu is an open-source notification infrastructure project with multi-channel workflows, templates and subscriber preferences — a reference for the feature set.
- Resilience4j Retry documents configurable retry with backoff for Java, the behaviour you implement for provider failures.
- AWS's Builders' Library article on timeouts, retries and backoff with jitter explains why retries need jitter to avoid synchronised retry storms.

Requirements


Functional

- `notify(userId, eventType, data, idempotencyKey)`.
- User preferences per event type and channel; global opt-out; quiet hours in the user's time zone (except critical events).
- Templates per event type and channel with variable substitution and locale.
- Channel providers behind interfaces (fake email/SMS/push providers in this project); fallback order (push, then SMS).
- Retry with exponential backoff and jitter; dead-letter after N attempts.
- Delivery log with status per attempt; per-user rate limit (e.g. 5 per hour for marketing).

Non-functional


- Accept requests in under 10 ms (enqueue only); deliver asynchronously.
- No duplicate sends for the same idempotency key.
- A provider outage does not block other channels.

The architecture



- **NotificationService** — validates, de-duplicates by idempotency key, enqueues, returns an id.
- **NotificationQueue** — an in-memory delay queue (so retries can be scheduled for later).
- **DeliveryWorker** — the pipeline: checks, channel selection, rendering, sending, logging, retry.
- **PreSendCheck** — a chain: opt-out, quiet hours, rate limit, each may block or defer.
- **ChannelSelector / SenderFactory / ChannelSender** — choose channels and get the right provider adapter.
- **RetryPolicy / DeliveryLog** — backoff schedule and audit trail.

Data model



Key types: `Notification` (id, user, event, data, attempts, state), `Preference` (user, event type, channels, enabled), `DeliveryAttempt` (notification, channel, time, result, provider message id).

Tech stack

Component	Choice	Why
Queue	`DelayQueue` of notifications	built-in delayed retry
Workers	virtual-thread executor	many concurrent provider calls
Templates	simple `{{var}}` engine, then Mustache	learn, then use a library
Time zones	`ZonedDateTime` + user `ZoneId`	correct quiet hours
Tests	JUnit 6, Mockito, AssertJ	mock providers and clock

Milestones

1. **Synchronous happy path.** *Done when:* a notify call renders a template and the fake email provider receives the right content.
2. **Preferences and checks chain.** *Done when:* opted-out users are suppressed and quiet-hours requests are deferred to the correct local time (tests in two time zones).
3. **Async queue and workers.** *Done when:* `notify` returns in under 10 ms while a slow provider takes 2 s.
4. **Retries and fallback.** *Done when:* a provider failing twice then succeeding produces 3 attempts with growing delays, and a permanently failing push falls back to SMS.
5. **Idempotency and rate limits.** *Done when:* duplicate keys send once, and the 6th marketing message in an hour is suppressed.

Deep dive: the hard parts

Transient versus permanent failure. A timeout or HTTP 503 should be retried; an invalid phone number should not. The sender adapter maps provider errors into a sealed `SendResult` (`Ok`, `Transient`, `Permanent`), so the worker's retry logic never parses provider-specific codes.

Backoff with jitter. Delay = `base * 2^attempt`, capped, then randomised (e.g. a random value between 0 and that delay). Without jitter, every notification that failed during an outage retries at the same instant when the provider recovers, knocking it over again.

Idempotency end to end. De-duplicate on accept (same key returns the same notification id). But a worker can also crash after the provider accepted the message and before logging success, then retry and send twice. Pass your notification id to providers that support idempotency keys; otherwise, accept at-least-once delivery and document it.

Quiet hours across time zones. Store quiet hours as local times plus the user's `ZoneId`, compute the next allowed `Instant` with `ZonedDateTime`, and handle daylight-saving gaps (02:30 may not exist on the change day).

Testing strategy

Mockito mocks for providers (programmed to fail N times). A fake clock and manual delay queue to test retries without waiting. Parameterised tests for quiet hours across zones and DST change dates. Concurrency test: 10,000 notifications with duplicate keys sprinkled in; assert exactly one send per key.

Trade-offs, scaling and failure modes

An in-memory queue loses pending notifications on restart; production uses a durable queue (see project 33). Per-channel worker pools isolate a slow SMS provider from email. Rate limits protect users but can suppress important messages — mark event types as critical to bypass them. Delivery receipts from providers arrive later via callbacks; model them as events updating the log.

Stretch goals

- Digest mode: batch low-priority notifications into one daily email.
- A/B testing of templates.
- Provider failover with a circuit breaker per provider (see project 35).

Skills practised

- Ch 20 — Components: the notification service case.
- Ch 10 — Behavioral patterns 1: Chain of Responsibility.
- Ch 11 — Behavioral patterns 2: Strategy, Template Method.
- Ch 8 — Creational patterns: Factory for senders.

In the interview

30-second answer: I built a notification service that accepts `notify(user, event, data, idempotencyKey)` in under 10 ms by de-duplicating and enqueuing, then delivers asynchronously through a worker pipeline. The pipeline runs a Chain of Responsibility of pre-send checks (opt-out, quiet hours in the user's time zone, rate limit), picks channels from preferences, renders a template, and calls a channel sender from a factory. Provider errors are mapped to a sealed `Transient` or `Permanent` result, so only transient ones are retried with exponential backoff and jitter, and permanent push failures fall back to SMS. Duplicate keys send once, and I document that a worker crash after a provider accepted a message gives at-least-once delivery.

Key terms to know:

- **Chain of Responsibility** — `PreSendCheck` links that may allow, block or defer a notification.
- **Factory** — `SenderFactory` returns the right `ChannelSender` for email, SMS or push.
- **Adapter** — each sender wraps one provider's API and maps its errors.

- **Transient vs permanent failure** — retry a timeout or HTTP 503; never retry an invalid phone number.
- **Exponential backoff with jitter** — delays grow as base x 2^attempt, capped and randomised to spread retries.
- **Idempotency key** — the same key returns the same notification id instead of sending again.
- **At-least-once delivery** — a message may be sent twice after a crash but is never silently lost.
- `DelayQueue` — a blocking queue that releases items only after their delay, used for scheduled retries.
- **Quiet hours / `ZoneId`** — local do-not-disturb times computed in the user's time zone, DST included.

Q: How do you avoid sending a notification twice?

A: Idempotency keys on accept, so a repeated request returns the same notification id. A worker can still crash after the provider accepted the message and before logging success; pass your notification id to providers that support idempotency keys, and otherwise state an at-least-once guarantee honestly.

Q: Why jitter on retries?

A: Without jitter, every notification that failed during an outage retries at the same instant when the provider recovers, knocking it over again. Randomising each delay spreads retries out so the recovering provider sees a smooth load.

Q: How do you add WhatsApp as a channel?

A: Write a new `ChannelSender` adapter, register it in the factory, and add templates; the pipeline, checks and retry logic are untouched. That is the Open/Closed Principle applied to channels.

Q: How do quiet hours work across time zones and daylight saving?

A: Store quiet hours as local times plus the user's `ZoneId`, and compute the next allowed `Instant` through `ZonedDateTime`. On a daylight-saving change, a time like 02:30 may not exist or may happen twice, and `ZonedDateTime` resolves gaps by shifting forward, so test those dates explicitly.

Q: Code-level: how do you compute a backoff delay with full jitter?

A: Exponential, capped, then a random value up to that cap.

```
long exp = Math.min(maxDelayMs, baseMs * (1L << Math.min(attempt, 20)));
long delay = ThreadLocalRandom.current().nextLong(exp + 1);   // 0..exp inclusive
queue.put(notification.retryAfter(Duration.ofMillis(delay)));
```

Q: Why accept-and-enqueue instead of sending synchronously?

A: Providers can take seconds or time out, and callers such as checkout should not wait or fail because SMS is slow. Enqueuing keeps `notify` under 10 ms and lets workers retry independently.

Q: What happens during a long provider outage?

A: Transient failures retry with growing delays and dead-letter after N attempts, while per-channel worker pools keep a slow SMS provider from starving email. A circuit breaker per provider (project 35) stops calling a provider that is clearly down and switches to fallback channels sooner.

Q: What breaks first at 10x volume or on a restart?

A: The in-memory queue loses pending notifications on restart, so production uses a durable queue (project 33). Provider rate limits are usually hit before CPU, so workers need per-provider concurrency limits, and the rate-limit and idempotency stores must be shared if there are several instances.

Q: How do you test retries without waiting?

A: Mockito providers programmed to fail N times, a fake clock, and a manual delay queue you advance. Parameterised tests cover quiet hours in several zones and DST dates, and a concurrency test with duplicate keys asserts exactly one send per key.

Common mistakes in answers:

- Retrying every error, including permanent ones like an invalid address.
- Claiming exactly-once delivery to an external SMS or email provider.
- Computing quiet hours in server time instead of the user's time zone.

TL;DR

Accept fast and enqueue, then a worker pipeline of pre-send checks, channel selection, templating, pluggable senders and jittered retries, all idempotent.

19. Car Rental System

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 3, Ch 5, Ch 16

What it is

A rental service for a company with several branches: customers search for available cars by location, dates and category, reserve one, pick it up, return it (possibly at another branch) and pay — including extras like insurance and late fees. The core is **availability over time ranges**, not just "is the car free now".

The problem it solves

A car can be booked many times in the future, so availability is a question about overlapping date ranges. Customers book a *category* ("compact"), while the fleet is individual cars that move between branches. Pricing has many add-ons. The project trains modelling with time ranges, category versus instance (like book versus copy in project 3), and keeping pricing and policies outside the entities.

Real-world examples

- Martin Fowler's Range pattern describes representing a start/end pair as one object with `includes` and `overlaps` operations — the key value type here.
- The handbook's booking chapter has the car rental case study; this project adds category-level availability and one-way rentals.

Requirements

Functional


- Branches, car categories (economy, compact, SUV), and individual cars with plate, category, mileage, branch.
- Search: category availability for a pickup branch and date range.
- Reserve a category (not a specific car); assign a specific car at pickup.
- Pickup, return (same or different branch), with mileage and fuel recorded.
- Pricing: daily rate per category, weekend rates, add-ons (insurance, child seat, extra driver), one-way fee, late return fee.
- Cancel with a policy (free until 24 h before).

Non-functional

- Availability query under 20 ms for 5,000 cars and 1 year of reservations.


- No overbooking of a category at a branch: reservations at any time never exceed cars expected there.
- Pricing rules testable in isolation.

The architecture



- **RentalService** — application service orchestrating search, reserve, pickup and return.
- **AvailabilityService** — counts cars of a category expected at a branch versus overlapping reservations.
- **Reservation / Rental** — the booking promise versus the actual use of a specific car.
- **PriceCalculator + PricingRule** — a pipeline of rules (base daily rate, weekend, add-ons, one-way, late fee).
- **CarAssigner** — strategy for picking a specific car at pickup (lowest mileage, most fuel, oldest service).

Data model



Type	Notes
`DateRange`	record (start, end) half-open, `overlaps` and `days`
`Car`	plate, category, branch, mileage, status (`AVAILABLE`, `RENTED`, `MAINTENANCE`)
`Quote` / `Invoice`	line items + total in `Money`

Tech stack

Component	Choice	Why
Ranges	`DateRange` record, half-open	no off-by-one at boundaries
Index	per branch and category, `TreeMap` by start	fast overlap queries
Pricing	rule pipeline	add rules without editing others
Tests	JUnit 6, AssertJ, parameterised pricing	many combinations

Milestones

1. **DateRange.** *Done when:* overlap tests cover touching ranges, contained ranges and same-day returns.

2. **Fleet and reservations.** *Done when:* reserving the 4th compact at a branch with 3 compacts over overlapping dates is refused.
3. **Pricing pipeline.** *Done when:* a weekend rental with insurance and a one-way fee matches a hand-computed invoice line by line.
4. **Pickup and return.** *Done when:* returning at another branch moves the car there and affects that branch's availability from the return date.
5. **Policies.** *Done when:* cancellation fees and no-show handling follow the rules on a test clock.

Deep dive: the hard parts

Half-open ranges. Represent ranges as [start, end): a car returned on the 5th can be picked up on the 5th. Overlap is `a.start < b.end && b.start < a.end`. Closed ranges cause endless off-by-one bugs.

Category availability is a counting problem. For a request, count reservations of that category at that branch whose ranges overlap, and compare with cars expected there. But "overlaps the request at some point" overcounts: two reservations may overlap the request without overlapping each other. The precise check is the *maximum concurrent* reservations within the range: sweep over start/end events sorted by time, tracking a running count. Implement the sweep.

One-way rentals change the fleet in the future. A car returning to branch B next week increases B's supply from that date. Supply is therefore also time-dependent: model expected arrivals and departures per branch as events, and run the same sweep on supply minus demand.

Testing strategy

Exhaustive `DateRange` tests. Scenario tests for availability with tables of reservations. Parameterised pricing tests. A randomised test: generate random reservation attempts and assert that at every day, reserved count never exceeds supply (checked by brute force).

Trade-offs, scaling and failure modes

Reserving categories (not cars) maximises utilisation but means a specific car may be unavailable at pickup (breakdown) — keep a small buffer or allow free upgrades. A per-branch-category lock prevents two concurrent reservations from overbooking. Time zones: branches are local; store pickup times as `ZonedDateTime` with the branch zone.

Stretch goals

- Dynamic pricing by utilisation (the more booked, the higher the rate).
- Maintenance scheduling that blocks cars and reduces supply.
- Loyalty tiers with free upgrades as a pricing rule.

Skills practised

- Ch 16 — Booking 2: car rental case.
- Ch 3 — Relationships and UML: category versus instance.
- Ch 5 — Design principles: value objects, information expert.

In the interview

30-second answer: I built a multi-branch car rental system where customers reserve a *category* such as "compact" and a specific car is assigned only at pickup by a `CarAssigner` strategy. Availability is a time-range problem: I use half-open `DateRange` values and a sweep over reservation start and end events to find the maximum concurrent demand, and compare it with supply, which also changes over time when one-way returns arrive. Pricing is a pipeline of rules (daily rate, weekend, add-ons, one-way fee, late fee), so new rules are new classes. A randomised test checks by brute force that reservations never exceed supply on any day.

Key terms to know:

- **Category versus instance** — customers book a category; the fleet is individual cars, like book versus copy.
- **Half-open range [start, end)** — the end is excluded, so a return on the 5th and a pickup on the 5th do not clash.
- **Overlap test** — `a.start < b.end && b.start < a.end` for half-open ranges.
- **Sweep line** — sort start (+1) and end (-1) events by time and track a running count to find the peak.
- **Time-dependent supply** — one-way rentals add or remove cars at a branch from a future date.
- **Reservation vs Rental** — the promise for a category versus the actual use of one car.
- **Pricing rule pipeline** — each `PricingRule` adds line items; the calculator runs them in order.
- **Overbooking** — accepting more reservations than cars; the invariant this design prevents.

Q: How do you check overlap of two date ranges?

A: With half-open ranges, `a.start < b.end && b.start < a.end`. Touching ranges such as [1, 5) and [5, 8) do not overlap, which matches how rentals work: return in the morning, rent out again the same day.

Q: Why reserve categories rather than specific cars?

A: It maximises fleet use: any compact can satisfy any compact reservation, so the branch assigns the best car at pickup. The trade-off is that if a car breaks down there may be none left, so keep a small buffer or allow free upgrades.

Q: How do you compute whether a category is available over a range?

A: Counting every reservation that overlaps the request overcounts, because two of them may not overlap each other. Instead sweep the start and end events inside the range and track the maximum number active at once; the request fits if that peak plus one is at most the supply.

Q: Code-level: what does the sweep look like?

A: Turn each overlapping reservation into +1 and -1 events and track the running maximum.

```
List<long[]> ev = new ArrayList<>();
for (var r : overlapping) { ev.add(new long[]{r.start().toEpochDay(), +1}); ev.add(new long[]
{r.end().toEpochDay(), -1}); }
ev.sort(Comparator.<long[]>comparingLong(e -> e[0]).thenComparingLong(e -> e[1])); // ends before
starts
int cur = 0, peak = 0;
for (var e : ev) { cur += e[1]; peak = Math.max(peak, cur); }
```

Sorting -1 before +1 on the same day is what makes ranges half-open.

Q: How do one-way rentals affect availability?

A: A car returning to branch B next week increases B's supply only from that date, and decreases A's. Model supply as arrival and departure events too, and run the same sweep on supply minus demand.

Q: How do you add a new price rule, such as a loyalty discount?

A: Add a `PricingRule` class to the pipeline; it reads the quote so far and adds a line item. Existing rules do not change, and each rule is tested alone with parameterised tables.

Q: What stops two concurrent reservations from overbooking the last car?

A: The availability check and the insert must be atomic, so take a lock per (branch, category) around check-then-reserve. In a database, the equivalent is a transaction that locks that branch-

category row.

Q: What breaks first at 10x fleet or branches?

A: Scanning all reservations for a category gets slow, so index them per branch and category in a `TreeMap` by start date and only sweep the ones in range. Time zones also start to matter, so store pickup times as `ZonedDateTime` with the branch's zone.

Common mistakes in answers:

- Closed ranges [start, end], which create off-by-one clashes on same-day returns.
- Counting overlapping reservations instead of the maximum concurrent ones.
- Reserving a specific car at booking time, which wastes fleet capacity.

TL;DR

Half-open date ranges, category-level reservations checked by an event sweep, specific cars assigned at pickup and pricing as a rule pipeline.

20. Food Delivery Order Lifecycle

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** Ch 11, Ch 19

What it is

The order-management core of a food delivery app (like Swiggy or DoorDash): a customer places an order with a restaurant, the restaurant accepts and prepares it, a delivery partner is assigned, picks it up and delivers. Every step is a state transition with rules about who may trigger it, timeouts, cancellations and refunds.

The problem it solves

An order passes through many hands, and each can fail: the restaurant rejects, no rider is available, the customer cancels after cooking started. Ad-hoc status strings and `if` checks scattered across controllers lead to impossible states ("delivered but never picked up") and inconsistent refunds. The project centres on an explicit **state machine** with guarded transitions, events emitted on each change, and **policies** (refunds, timeouts) separated from the machine itself.

Real-world examples

- Spring Statemachine is a framework for exactly this: states, events, guards and actions configured for a business process. You build a minimal one yourself first.
- The handbook's platforms chapter covers the Swiggy/FoodKart design; this capstone zooms into the order lifecycle.

Requirements


Functional

- Restaurants with menus and opening hours; customers place orders with items and an address.
- Order states: placed, accepted, preparing, ready, picked up, delivered, cancelled, rejected.
- Role-based transitions: only the restaurant accepts; only the rider picks up.
- Auto-reject if the restaurant does not accept within 5 minutes.
- Rider assignment when the order is accepted (simple nearest-free-rider strategy).
- Cancellation policy: free before acceptance, partial refund during preparation, none after pickup.
- Every transition emits an event (for notifications, analytics, ETA updates).

Non-functional


- Illegal transitions are impossible — rejected by the machine, not by callers.
- Concurrent transitions on the same order are serialised (no lost updates).
- Full audit history of transitions per order.

The architecture



- **OrderService** — loads the order, asks the state machine whether the event is allowed for this actor, applies it, saves, publishes.
- **OrderStateMachine** — a table of transitions (from, event) to (to, guard, actions). Pure, easily tested.
- **Order** — aggregate with current state, version number for optimistic locking, and history.
- **RiderAssigner** — strategy for choosing a rider.
- **CancellationPolicy** — computes refunds from state and timing.
- **TimeoutScheduler** — fires "accept timeout" events.
- **EventBus** — in-process publish/subscribe for side effects.

Data model



Key types: `OrderEvent` (sealed: `Accept`, `Reject`, `StartPreparing`, `MarkReady`, `PickUp`, `Deliver`, `Cancel`, `AcceptTimeout`), `Actor` (sealed: `Customer`, `Restaurant`, `Rider`, `System`), `StateChange` (from, to, event, actor, time).

Tech stack

Component	Choice	Why
Machine	transition table in an `EnumMap`	data, not nested ifs
Events	sealed interface + pattern-matching switch	exhaustive handling
Concurrency	per-order version (optimistic locking)	detect conflicting updates
Timeouts	`ScheduledExecutorService`	accept timeout
Tests	JUnit 6, AssertJ, Mockito for event bus	verify side effects

Milestones

1. **State machine table.** *Done when:* a test enumerates every (state, event) pair and only listed transitions succeed.
2. **Actor guards.** *Done when:* a rider attempting `Accept` is rejected with "not allowed for actor".

3. **Order service and events.** *Done when:* placing and fully delivering an order emits exactly the expected event list (Mockito `InOrder`).
4. **Timeouts and cancellation policy.** *Done when:* an unaccepted order auto-rejects at 5 minutes on a test clock, and refunds match the policy table.
5. **Concurrency.** *Done when:* a cancel and an accept racing on the same order produce one winner and a clear conflict error for the other.

Deep dive: the hard parts

Guards and actions live in the table. A transition has a guard (who may trigger it, extra conditions like "within opening hours") and actions (assign rider, refund, schedule timeout). Keeping these as data alongside the transition makes the machine reviewable: one table answers "what can happen from Preparing?".

Timeouts racing with real events. The 5-minute timer fires at the same moment the restaurant accepts. Treat the timer as just another event (`AcceptTimeout`) that goes through the same machine: if the order is already `Accepted`, the event is invalid and ignored. Never let the timer write state directly.

Optimistic locking. Each order has a version. Updates say "set state to X where version = 7"; if someone else updated first (version 8), the update fails and the loser reloads and retries or reports a conflict. In memory, implement with `ConcurrentHashMap.replace(key, oldOrder, newOrder)` on immutable order snapshots.

Testing strategy

Table-driven tests generated from the transition table itself, plus negative tests for every unlisted pair. Scenario tests for full lifecycles. Test clock for timeouts. Race tests with two virtual threads and a start latch.

Trade-offs, scaling and failure modes

A hand-rolled table is simple and transparent; a framework adds hierarchy, persistence and tooling at the cost of learning curve. Side effects after a state change (notify customer) can fail independently — publish events after saving, and make handlers idempotent. Riders may never pick up; add a timeout that reassigns.

Stretch goals

- Partial order fulfilment (an item out of stock) with customer approval.
- Batching: one rider carries two orders from the same restaurant.
- Event sourcing: rebuild an order's state purely from its event history.

Skills practised

- Ch 19 — Platforms 2: Swiggy/FoodKart case.
- Ch 11 — Behavioral patterns 2: State, Observer, Strategy.
- Ch 12 — Concurrency concepts: optimistic concurrency.

In the interview

> **30-second answer:** I built the order lifecycle of a food delivery app around an explicit state machine: a transition table in an `EnumMap` maps (state, event) to the next state, a guard such as "only the restaurant may accept", and actions such as assigning a rider. Everything goes through that table, so impossible states like "delivered but never picked up" cannot happen. The 5-minute auto-reject timer is just another event (`AcceptTimeout`) through the same machine, so if the restaurant accepted first the timeout is simply invalid. Concurrent updates use optimistic locking with a version number, and events are published only after the state is saved.

Key terms to know:

- **Finite state machine** — a fixed set of states and allowed transitions between them.
- **Transition table** — data listing (from, event) to (to, guard, actions); one place answers "what can happen from Preparing?".
- **Guard** — a condition that must hold for a transition, such as the actor being the restaurant.
- **Action** — a side effect run on a transition: assign rider, refund, schedule timeout.
- **Actor** — who triggers an event: customer, restaurant, rider or system.
- **Optimistic locking** — save only if the version is unchanged; otherwise reload and retry or report a conflict.
- **Domain event** — a record that something happened (`OrderAccepted`), published for notifications and analytics.
- **Policy object** — `CancellationPolicy` computes refunds outside the machine.

Q: How do you prevent impossible states?

A: All changes go through a transition table that lists the only legal (state, event, actor) combinations; anything else is rejected by the machine, not by each caller. A test enumerates every (state, event) pair and checks that only listed ones succeed.

Q: How do you handle the auto-reject timer racing with acceptance?

A: The timer emits an `AcceptTimeout` event processed by the same machine; whichever applies first wins, and the other becomes an invalid transition and is ignored. The timer never writes state directly.

Q: Two updates to the same order at once?

A: Optimistic locking with a version number: an update says "set state where version = 7". If someone else already moved it to version 8, the update fails and the loser reloads, then retries or reports a conflict. A cancel racing an accept produces one winner and one clear error.

Q: Why optimistic rather than pessimistic locking here?

A: Conflicts on one order are rare and transitions are quick, so taking a lock every time costs more than occasionally retrying. Pessimistic locks make more sense when conflicts are frequent or retries are expensive.

Q: Code-level: how do you implement optimistic updates in memory?

A: Store immutable order snapshots and swap only if unchanged.

```
Order current = orders.get(id);
Order next = machine.apply(current, event, actor);          // throws if illegal
if (!orders.replace(id, current, next.withVersion(current.version() + 1)))
    throw new ConcurrentUpdateException(id);                // someone else won
```

`ConcurrentHashMap.replace(key, old, new)` is atomic and compares with `equals`.

Q: Where do refunds and notifications live, and what if a notification fails?

A: Refund amounts come from a `CancellationPolicy` based on state and time, outside the machine. Notifications are event handlers that run after the order is saved; if one fails, the order state is still correct, and handlers must be idempotent so they can retry.

Q: How would you add a new state, such as "partially fulfilled"?

A: Add the state and its rows in the transition table, plus any guard or action classes. Because the sealed event and state types feed exhaustive `switch` statements, the compiler points out every place that must handle the new case.

Q: What happens at 10x orders or with several servers?

A: Orders are independent, so throughput scales with partitioning by order id. With several servers, the version check moves to the database (`UPDATE ... WHERE id = ? AND version = ?`), and timers move to a durable scheduler so a restart does not lose pending timeouts.

Q: How do you test it?

A: Generate table-driven tests from the transition table itself, plus negative tests for every unlisted pair. Scenario tests assert the exact event list with Mockito `InOrder`, a test clock drives the timeout, and two virtual threads behind a latch race cancel against accept.

Common mistakes in answers:

- Status strings with `if` checks scattered across controllers.
- Letting the timeout thread set `REJECTED` directly, which races with acceptance.
- Publishing events before the state change is saved.

TL;DR

An explicit transition table with actor guards and actions, timeouts as ordinary events, versioned updates and events published after each change.

21. Meeting Room Scheduler

Level: Intermediate · **Time:** 1–2 weeks · **Prerequisites:** Ch 5, Ch 21

What it is

A calendar and room-booking service for an office: people create events with attendees, book meeting rooms with enough seats and equipment, see free/busy times, and get suggestions for the earliest slot when everyone and a suitable room are free. Recurring events ("every Monday at 10:00") make it interesting.

The problem it solves

Finding a time that works for five people and a room is tedious and error-prone. The software must answer interval questions fast — "is this room free from 14:00 to 15:00?", "when are all these people free this week?" — while handling time zones, recurring events and concurrent bookings of the same room. The project trains interval algorithms, value objects for time, and clean separation of query and booking logic.

Real-world examples

- Calendar data is standardised by iCalendar (RFC 5545), including the `RRULE` recurrence-rule syntax you implement a subset of.
- Fast overlap queries are what an interval tree is for; Java's TreeMap gives a simpler sorted-by-start alternative that works well for non-overlapping room bookings.

Requirements

Functional


- Rooms with capacity, floor and equipment (projector, video). Users with a home time zone.
- Create, update, cancel events with organiser, attendees, optional room, start/end.
- Recurring events: daily, weekly on given days, with an end date or count; exceptions (skip one occurrence).
- Free/busy for a user or room over a range.

- Suggest: earliest N slots of a given length within working hours where all required attendees and some room meeting the constraints are free.
- Reject double-booking of rooms. Attendees may be double-booked (with a warning).

Non-functional

- Room availability check under 1 ms for 1,000 rooms and a year of bookings.
- Correct across time zones and daylight-saving changes.
- Concurrent bookings of the same room never both succeed.

The architecture



- **CalendarService** — application service for all use cases.
- **Event / Recurrence** — an event with a recurrence rule that expands into concrete occurrences within a window.
- **RoomBookingIndex** — per-room `TreeMap<Instant, Booking>` keyed by start; free check looks at neighbours only.
- **AvailabilityFinder** — merges busy intervals of many people and finds gaps of the requested length.
- **RoomMatcher** — capacity and equipment rules as a composable predicate.

Data model

Type	Notes
`TimeRange`	record (start `Instant`, end `Instant`) half-open, `overlaps`, `minus`
`Recurrence`	sealed: `OneOff`, `Daily(interval, until)`, `Weekly(days, interval, until)`, with `exceptions: Set<LocalDate>`
`Event`	id, title, organiser, attendees, room, local start time + `ZoneId`, duration, recurrence, version
`Room`	id, capacity, equipment set, floor

Tech stack

Component	Choice	Why
Time	`ZonedDateTime` for rules, `Instant` for storage	DST-safe expansion
Room index	`TreeMap` per room + per-room lock	O(log n) free check
Merging	sort + sweep	standard interval merge
Tests	JUnit 6, AssertJ, parameterised time zones	DST cases

Milestones

1. **TimeRange and room index.** *Done when:* booking 14:00–15:00 then 15:00–16:00 succeeds and 14:30–15:30 fails.
2. **Events and attendees.** *Done when:* free/busy for a user lists all their events in a week.
3. **Recurrence.** *Done when:* "weekly on Mon/Wed until Dec 31" expands correctly, with one skipped date, across a DST change.
4. **Suggestions.** *Done when:* for 4 people with busy calendars, the earliest 30-minute common slot inside 09:00–17:00 local time is found with a matching room.
5. **Concurrency.** *Done when:* 100 threads booking the same room slot yield exactly one success.

Deep dive: the hard parts

Recurring events across daylight saving. "Every Monday at 10:00 Berlin time" must stay at 10:00 local when the clocks change, which means its UTC instant shifts by an hour. Store the rule in local time with a `ZoneId`, and expand to instants with `ZonedDateTime` per occurrence. Storing a fixed UTC time breaks twice a year.

Free check in O(log n). With non-overlapping bookings sorted by start, a new range [s, e) is free if the booking with the greatest start before e (`lowerEntry(e)`) ends at or before s. One lookup, no scan.

Common free time. Collect everyone's busy ranges in the window (expanding recurrences), sort by start, merge overlaps into a single busy list, then walk the gaps, intersecting with working hours, and emit gaps at least as long as the meeting. Then, for each candidate, ask the room index for a matching free room. This is the classic "merge intervals" interview problem in a real setting.

Testing strategy

Parameterised tests across time zones including DST transition days. Property test: suggested slots never overlap any attendee's busy range. Concurrency test for room booking. Test clock for "now" when suggesting future slots.

Trade-offs, scaling and failure modes

Expanding recurrences on every query is simple but slow for long ranges; caching expanded occurrences for the next 90 days is a common compromise, invalidated on edits. "Edit this and following occurrences" splits a series into two — model it explicitly. Attendees in different time zones mean working hours differ per person; intersect each person's own working hours.

Stretch goals

- iCalendar export of events (a subset of RFC 5545).
- Room auto-release when nobody checks in within 10 minutes.
- Priority bumping: an executive meeting can request a booked room with approval.

Skills practised

- Ch 21 — Machine coding: the event calendar case.
- Ch 5 — Design principles: value objects, immutability.
- Ch 12 — Concurrency concepts: per-resource locks.

In the interview

> **30-second answer:** I built a calendar and room-booking service where each room keeps its bookings in a `TreeMap` keyed by start, so a free check is one `lowerEntry` lookup in O(log n). Recurring events are stored as a local time plus a `ZoneId` and a rule, and expanded per date with `ZonedDateTime`, so "Mondays at 10:00 Berlin" stays at 10:00 across daylight-saving changes. Slot

suggestions use the classic merge-intervals algorithm over all attendees' busy times, intersected with each person's working hours, then ask the room index for a matching room. A per-room lock means 100 threads booking one slot produce exactly one success.

Key terms to know:

- **Half-open** `TimeRange` — [start, end) so back-to-back meetings at 15:00 do not clash.
- `Instant` **vs** `ZonedDateTime` — an absolute point in UTC versus a local date-time with time-zone rules.
- **Daylight saving time (DST)** — clocks shift, so a fixed UTC time drifts by an hour in local time.
- **Recurrence rule (RRULE)** — iCalendar's syntax for repeating events; this project implements a subset.
- **Exception date** — one skipped occurrence of a series.
- `TreeMap.lowerEntry` — greatest key strictly less than a given key, in O(log n).
- **Merge intervals** — sort busy ranges by start, merge overlaps, then walk the gaps.
- **Composable predicate** — `RoomMatcher` combines capacity and equipment rules.
- **Per-resource lock** — one lock per room so different rooms book in parallel.

Q: How do you check a room is free quickly?

A: Keep bookings sorted by start in a `TreeMap`. For a new range [s, e), look up the booking with the greatest start before e (`lowerEntry(e)`); the room is free if there is none or it ends at or before s. Because bookings never overlap, that one neighbour is enough.

Q: How do you store a weekly 10:00 meeting?

A: As a local time plus time zone and a recurrence rule. Occurrences are expanded to instants per date with `ZonedDateTime`, so DST is handled; storing a fixed UTC instant would make the meeting jump an hour twice a year.

Q: How do you find a common free slot?

A: Collect everyone's busy ranges in the window (expanding recurrences), sort by start, merge overlaps, then walk the gaps intersected with working hours and emit gaps at least as long as the meeting. For each candidate, ask the room index for a free room that matches the constraints.

Q: Code-level: what does the free check look like?

A: One lookup in the per-room map.

```
boolean isFree(TreeMap<Instant, Booking> b, Instant s, Instant e) {
    var prev = b.lowerEntry(e);                    // last booking starting before e
    return prev == null || !prev.getValue().end().isAfter(s);
}
```

Q: What happens with a meeting at 02:30 on a DST change day?

A: In spring, 02:30 may not exist in that zone; `ZonedDateTime.of` shifts it forward by the gap. In autumn, it happens twice and Java picks the earlier offset by default. Decide the rule, document it, and test those dates in parameterised tests.

Q: Why can attendees be double-booked but rooms cannot?

A: A person can choose which meeting to attend, so a warning is enough; a room physically cannot host two meetings. So room booking is a strict check under a per-room lock, while attendee conflicts are just reported.

Q: How do you handle "edit this and all following occurrences"?

A: Split the series: end the original rule the day before and create a new series from that date with the edits. Modelling it explicitly avoids quietly rewriting past occurrences.

Q: What changes at 10x users or a year-long search window?

A: Expanding recurrences on every query becomes the bottleneck, so cache expanded occurrences for the next 90 days and invalidate on edit. With many servers, the room check-and-book moves into a database transaction or a unique constraint on room plus time slot.

Q: How do you test it?

A: Parameterised tests across time zones and DST transition days, a property test that suggested slots never overlap any attendee's busy range, and a concurrency test where 100 threads book the same slot and exactly one wins.

Common mistakes in answers:

- Storing recurring events as UTC instants, which breaks at DST changes.
- Scanning all bookings for a free check instead of using the sorted neighbour.
- Using one working-hours window for attendees in different time zones.

TL;DR

Half-open time ranges, recurrence rules in local time, a sorted per-room index for O(log n) checks and merge-intervals for suggestions.

22. Inventory and Point of Sale

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** Ch 9, Ch 19, Ch 21

What it is

A system for a small chain of grocery stores: products with barcodes, stock per store, a checkout (**point of sale**, or POS) that scans items, applies promotions, takes payment and prints a receipt, and an inventory side that receives deliveries, tracks low stock and raises purchase orders. It combines a busy transactional flow (checkout) with bookkeeping (stock movements).

The problem it solves

Stores lose money when stock counts drift from reality (sold items not deducted, deliveries not recorded) and when promotions are applied inconsistently. A design that updates a single `quantity` field from many places loses the history needed to find out why counts are wrong. This project uses an append-only **stock movement** log, a **promotion engine** built from composable rules, and adapters for payment devices.

Real-world examples

- Odoo is an open-source business suite whose inventory and point-of-sale apps model stock moves between locations — a mature reference for the domain.
- Fowler's Money pattern applies directly to receipts, where rounding promotions per line versus per basket changes totals.

Requirements

Functional


- Products: SKU, barcode, name, price, tax category, unit (each or weight).
- Checkout: scan or key in items, weighed items priced by kg, quantity changes, void a line, suspend/resume a basket.

- Promotions: percentage off, buy X get Y free, multi-buy price ("3 for 5.00"), basket threshold discount; best combination applied deterministically.
- Payment: cash with change, card via a terminal adapter, split payment.
- Receipt with line items, promotions, tax breakdown.
- Inventory: stock per store, movements (sale, delivery, transfer, adjustment, return), reorder point alerts, purchase orders.

Non-functional

- Scanning an item updates the basket total in under 50 ms.
- Stock on hand always equals the sum of movements.
- Checkout keeps working if the inventory service is slow (sales recorded, stock updated asynchronously).

The architecture



- **CheckoutSession** — one customer's transaction: basket, totals, payment, receipt. Publishes `SaleCompleted`.
- **Basket** — line items with quantities or weights.
- **PromotionEngine / Promotion** — each promotion proposes discounts; the engine picks a non-conflicting best set.
- **TaxCalculator** — tax per category, computed after discounts.
- **PaymentTerminal** — adapter to card hardware; cash is another implementation.
- **InventoryService / MovementLog** — append-only movements, with on-hand as a derived, cached sum.
- **ReorderPolicy** — when and how much to reorder.

Data model

Type	Notes
`StockMovement`	record: id, sku, store, quantity (signed), type (`SALE`, `DELIVERY`, `TRANSFER_IN`, `TRANSFER_OUT`, `ADJUSTMENT`, `RETURN`), reference, time
`BasketLine`	product, quantity or weight, unit price, line number
`Discount`	promotion id, affected lines, amount
`Receipt`	lines, discounts, tax lines, payments, change

Tech stack

Component	Choice	Why
Money	`BigDecimal` with explicit rounding	weights produce fractions
Promotions	strategy per type + engine	add promotion types freely
Sale to stock	in-process event, async consumer	checkout never waits for inventory
Tests	JUnit 6, AssertJ, Mockito for terminal	receipt golden files

Milestones

1. **Catalogue and basket.** *Done when:* scanning, quantity change and void produce correct totals including weighed items.
2. **Promotions.** *Done when:* "3 for 5.00" and "buy 2 get 1 free" on the same product resolve to the better deal for the customer, deterministically.
3. **Tax and receipt.** *Done when:* a golden-file test matches the printed receipt exactly.
4. **Payments.** *Done when:* split cash/card payments work and a declined card leaves the basket payable.
5. **Inventory.** *Done when:* sales, deliveries and transfers update on-hand; a reorder alert fires when stock crosses the reorder point.

Deep dive: the hard parts

Choosing among overlapping promotions. Two promotions may want the same items. A simple, explainable rule: evaluate each promotion's discount, sort by value, apply greedily while marking consumed items so they cannot be used twice. Finding the true optimum is a combinatorial search; for a few lines you can brute-force, but greedy with a stable tie-break is what most shops ship. Document the rule.

Rounding. Weighed items (0.347 kg at 3.99/kg) and percentage discounts create fractions of a cent. Decide where rounding happens (per line, half-up) and apply it in one place. Tax computed per line versus per receipt gives different totals; follow one rule consistently.

Stock as a ledger. Never `UPDATE quantity`. Append a movement and update a cached on-hand total in the same step. When counts look wrong, the movement history explains why. A physical stock count becomes an `ADJUSTMENT` movement with a reason.

Testing strategy

Promotion tests as tables (basket in, discounts out). Golden-file receipt tests. Property test: on-hand equals the sum of movements after random operations. Mockito for the payment terminal (approve, decline, timeout).

Trade-offs, scaling and failure modes

Async stock updates keep checkout fast but allow selling an item the system thinks is out of stock — usually fine for groceries (the item is physically there). Offline mode: if the central server is down, the till must keep selling and sync later, so sales need client-generated ids. Promotion engines grow complex; keep promotions as data with a small set of rule types.

Stretch goals

- Returns with refund to the original payment method.
- Loyalty points as a promotion and a payment method.
- Offline tills that queue sales and sync with idempotent upload.

Skills practised

- Ch 19 — Platforms 2: grocery POS case.

- Ch 21 — Machine coding: inventory management case.
- Ch 9 — Structural patterns: Adapter for payment terminals.
- Ch 11 — Behavioral patterns 2: Strategy for promotions.

In the interview

30-second answer: I built a grocery point-of-sale and inventory system where checkout is a `CheckoutSession` with a pluggable promotion engine and payment adapters, and stock is an append-only ledger of signed movements (sale, delivery, transfer, adjustment) with on-hand as a cached sum. Overlapping promotions are resolved greedily by value, marking consumed items, with a stable tie-break so the same basket always gets the same receipt. Checkout publishes a `SaleCompleted` event and inventory consumes it asynchronously, so a slow inventory service never blocks the till. A property test checks that on-hand always equals the sum of movements.

Key terms to know:

- **Point of sale (POS)** — the till: scan, total, promotions, payment, receipt.
- **Append-only movement log** — stock changes recorded as signed rows, never as an overwritten quantity.
- **Derived / cached balance** — on-hand computed from movements and cached for speed.
- **Promotion engine** — each promotion proposes discounts; the engine picks a non-conflicting set.
- **Greedy with stable tie-break** — apply biggest discounts first, ties broken by a fixed key such as promotion id.
- **Adapter** — `PaymentTerminal` hides card hardware; cash is another implementation.
- **Rounding policy** — where and how fractions of a cent are rounded, such as per line, half-up.
- **Eventual consistency** — stock is updated shortly after the sale rather than in the same step.
- **Reorder point** — the stock level that triggers a purchase order.

Q: Why record stock movements instead of updating a quantity?

A: The log is auditable and explains discrepancies, and on-hand is derived from it. It also makes concurrent updates simpler since appends do not overwrite each other. A physical count becomes an `ADJUSTMENT` movement with a reason, not a silent overwrite.

Q: How do you resolve overlapping promotions?

A: Evaluate every candidate promotion, apply them greedily by discount value while marking consumed items so none is used twice, and use a stable tie-break so results are reproducible. The true optimum is a combinatorial search; brute force works for tiny baskets, but greedy with a documented rule is what most shops ship.

Q: What if inventory is down during checkout?

A: Checkout completes and publishes a sale event; inventory consumes it later. Sales are never blocked on stock bookkeeping, at the cost of briefly selling something the system thinks is out of stock, which is fine for groceries because the item is physically there.

Q: Why `BigDecimal` here when other projects use `long` cents?

A: Weighed items (0.347 kg at 3.99/kg) and percentage discounts produce fractions of a cent mid-calculation, so you need decimal arithmetic with an explicit rounding step. Choose one rounding point, per line with `HALF_UP` for example, and apply it in one place.

Q: Code-level: what is the `BigDecimal` gotcha?

A: `equals` compares scale as well as value, and division needs a rounding mode.

```
new BigDecimal("2.0").equals(new BigDecimal("2.00"));       // false: scale differs
new BigDecimal("2.0").compareTo(new BigDecimal("2.00"));    // 0: same value
price.multiply(kg).setScale(2, RoundingMode.HALF_UP);       // round once, explicitly
BigDecimal.ONE.divide(new BigDecimal(3));                   // ArithmeticException
```

Also build from strings, not doubles: `new BigDecimal(0.1)` carries the binary error.

Q: How do you add a new promotion type?

A: Implement the `Promotion` interface (propose discounts for a basket) and register it; the engine and checkout do not change. Keep promotions as data using a small set of rule types so the business can configure them without code.

Q: What happens if the till goes offline?

A: The till keeps selling and queues sales locally with client-generated ids, then uploads them when the server returns. Client ids make the upload idempotent, so a retried sync does not double-count stock.

Q: What breaks first at 10x stores or transactions?

A: Summing movements on every read gets slow, so keep a cached on-hand per (SKU, store) updated with each append, plus periodic snapshots. The event consumer may lag at peak, so monitor its backlog and partition consumers by store.

Q: How do you test receipts and promotions?

A: Table tests for promotions (basket in, discounts out), golden-file tests that compare printed receipts exactly, a property test that on-hand equals the sum of movements, and Mockito for the card terminal's approve, decline and timeout paths.

Common mistakes in answers:

- `UPDATE quantity = quantity - 1` with no history, so nobody can explain wrong counts.
- Rounding in many places, giving receipts that do not add up.
- Making checkout wait synchronously for inventory.

TL;DR

A checkout session with a pluggable promotion engine and payment adapters, and stock kept as an append-only movement ledger fed by sale events.

23. Unix find Clone

Level: Intermediate · **Time:** 1 week · **Prerequisites:** Ch 9, Ch 10, Ch 21

What it is

A Java command-line tool that walks a directory tree and prints files matching an expression, like the Unix `find` command: `jfind src -name "*.java" -size +10k -not -path "*/test/*"`. The core is a small **expression language** of tests combined with AND, OR and NOT, parsed into a tree of objects and evaluated per file.

The problem it solves

Filters on files combine in endless ways. Hard-coding each combination is impossible; the right design treats each test as an object and combines them — the **Composite** and **Interpreter** patterns, also known as the Specification pattern. The project also teaches safe file-tree walking (symbolic link loops, permission errors) and writing a tiny parser.

Real-world examples

- GNU findutils' find manual documents the expression grammar (tests, actions, operators and precedence) that this project implements a subset of.
- The JDK's Files class provides `walkFileTree` and `walk` with options for following links — the traversal engine you build on.

Requirements


Functional

- Starting paths; tests `-name`, `-iname` (glob), `-type f|d|l`, `-size`, `-mtime`, `-path`, `-empty`, `-perm`.
- Operators: implicit AND, `-or`, `-not`, parentheses, with standard precedence (NOT > AND > OR).
- Options: `-maxdepth`, `-mindepth`, `-follow` (follow symbolic links).
- Actions: `-print` (default), `-delete` (with confirmation flag), `-exec cmd {} ;` (later).
- Clear error messages for invalid expressions and unreadable directories (continue walking).

Non-functional

- Walk 1 million files in a time comparable to native `find` (measure and report).
- Never loop forever on symbolic link cycles.
- Adding a new test is one class plus a parser registration.

The architecture



- **FindCommand** — wiring: parse args, build the walker and expression, run.
- **Parser** — recursive-descent parser turning tokens into an expression tree.
- **Expr** — the Composite: leaf tests and operator nodes share one interface.
- **Walker** — wraps `Files.walkFileTree`, applying depth limits, link handling and error reporting.
- **Action** — what to do with matches.

Data model

Type	Notes
`FileInfo`	record: path, `BasicFileAttributes`, depth — read once per file
`Expr`	sealed interface: `And`, `Or`, `Not`, and leaf test records
`SizeSpec`	record (comparison `+`/`-`/exact, amount, unit)
`WalkOptions`	max/min depth, follow links, starting points

Tech stack

Component	Choice	Why
Walking	`Files.walkFileTree` + `FileVisitor`	handles errors, links, pruning
Glob	`FileSystems.getDefault().getPathMatcher("glob:...")`	correct glob semantics
Parsing	hand-written recursive descent	tiny grammar, great practice
Tests	JUnit 6, AssertJ, `@TempDir`	build real trees in tests

Milestones

1. **Walker.** *Done when:* walking a `@TempDir` tree prints every path, respects `-maxdepth`, and reports (not crashes on) an unreadable folder.
2. **Leaf tests.** *Done when:* `-name`, `-type` and `-size` each pass table-driven tests.
3. **Parser and operators.** *Done when:* `-name a -or -name b -type f` parses as `a OR (b AND f)` (precedence test on the tree's `toString`).
4. **Links and safety.** *Done when:* a symlink cycle with `-follow` terminates and reports the loop.
5. **Actions + performance.** *Done when:* `-delete` removes matched files bottom-up, and a benchmark on a large tree is reported against native `find`.

Deep dive: the hard parts

Precedence in a recursive-descent parser. Write one method per precedence level: `parseOr` calls `parseAnd` and loops on `-or`; `parseAnd` calls `parseNot` and loops while the next token starts a primary (implicit AND); `parseNot` handles `-not` and `!`; `parsePrimary` handles parentheses and leaf tests. This structure enforces precedence naturally.

Short-circuiting and cheap tests first. `And` must stop at the first false, `Or` at the first true, exactly like `find` — users rely on it to avoid expensive checks. An optional optimiser can reorder AND children so cheap tests (name) run before expensive ones (reading content), as long as there are no side-effecting actions in between.

Symbolic links and cycles. When following links, the same directory can be reached forever. `walkFileTree` with `FOLLOW_LINKS` detects cycles using file keys and reports `FileSystemLoopException` to `visitFileFailed`; handle it by printing a warning and continuing.

Testing strategy

Build trees in `@TempDir` with known sizes and times (`Files.setLastModifiedTime`). Table tests for each leaf. Parser tests comparing printed trees. End-to-end tests running `FindCommand.run` and capturing stdout. Skip link tests on systems that do not support symlinks.

Trade-offs, scaling and failure modes

Reading attributes once per file into `FileInfo` avoids repeated system calls. Parallel walking (one virtual thread per subdirectory) can speed up network drives but loses deterministic output order —

offer it as an option. `-delete` is dangerous; require an explicit flag and process depth-first so directories empty before deletion.

Stretch goals

- `-exec` with `{}` substitution and batching (`+`).
- Content search `-contains "text"` with a size cap.
- Parallel walking with structured concurrency (`StructuredTaskScope`, a preview API in Java 25 — needs `--enable-preview`).

Skills practised

- Ch 21 — Machine coding: the Unix find case.
- Ch 9 — Structural patterns: Composite.
- Ch 10 — Behavioral patterns 1: Interpreter.

In the interview

30-second answer: I built a Java clone of Unix `find`: a hand-written recursive-descent parser turns arguments like `-name "*.java" -not -path "*/test/*"` into a tree of `Expr` objects, where leaf tests and AND, OR, NOT nodes share one interface (Composite plus Interpreter). Evaluation short-circuits exactly like `find`, so cheap tests can guard expensive ones. Walking uses `Files.walkFileTree`, reading attributes once per file, applying depth limits, reporting unreadable folders instead of crashing, and detecting symlink loops through `FileSystemLoopException`. Adding a new test is one record plus a parser registration, and I report walk time against native `find`.

Key terms to know:

- **Composite pattern** — leaves and containers share an interface, so `And(Not(Name), Size)` is evaluated uniformly.
- **Interpreter pattern** — a grammar represented as classes, each knowing how to evaluate itself.
- **Specification pattern** — business rules as combinable predicate objects; the same idea for files.
- **Recursive-descent parser** — one method per grammar rule, calling each other.
- **Operator precedence** — NOT binds tighter than AND, which binds tighter than OR.
- **Short-circuit evaluation** — AND stops at the first false, OR at the first true.
- **`FileVisitor`** — callbacks (`preVisitDirectory`, `visitFile`, `visitFileFailed`) used by `walkFileTree`.
- **Symlink cycle** — a link pointing to an ancestor; detected with file keys when following links.
- **Glob** — shell-style pattern (`*.java`) matched with `PathMatcher`.

Q: How do you support arbitrary combinations of filters?

A: Each filter is an `Expr`; AND, OR and NOT are composite nodes over `Expr`s. Evaluation is recursive, so any nesting works without new code.

Q: How do you get operator precedence right?

A: A recursive-descent parser with one function per precedence level: `parseOr` calls `parseAnd` and loops on `-or`; `parseAnd` calls `parseNot` and loops while the next token starts a primary (implicit AND); `parseNot` handles `-not`; `parsePrimary` handles parentheses and leaf tests. So `-name a -or -name b -type f` parses as `a OR (b AND f)`.

Q: How do you avoid infinite loops with symlinks?

A: With `FOLLOW_LINKS`, `walkFileTree` tracks the file keys of open directories and, on a cycle, calls `visitFileFailed` with a `FileSystemLoopException`. Handle it by printing a warning and continuing.

Q: Code-level: how do you model the expression tree in Java 25?

A: A sealed interface with records, evaluated by pattern matching.

```
sealed interface Expr permits And, Or, Not, Name, Type {}
record And(Expr l, Expr r) implements Expr {}
// ... Or(l, r), Not(Expr e), Name(PathMatcher m), Type(char t)
static boolean eval(Expr e, FileInfo f) { return switch (e) {
    case And a -> eval(a.l(), f) && eval(a.r(), f);   case Or o -> eval(o.l(), f) || eval(o.r(), f);
    case Not x -> !eval(x.e(), f);  case Name n -> n.m().matches(f.path().getFileName());
    case Type t -> t.matches(f.attrs()); }; }
```

The compiler checks the `switch` covers every permitted type, with no `default`.

Q: Why does short-circuiting matter?

A: Users write `-name "*.log" -size +1G` expecting the size check only on log files, and `-exec` actions must not run when an earlier test fails. An optional optimiser may reorder AND children so cheap tests run first, but only when there are no side-effecting actions between them.

Q: What happens with an unreadable directory or a file deleted mid-walk?

A: `visitFileFailed` receives the `IOException`; print a clear message to stderr and return `CONTINUE`, like native `find`. The exit code can still signal that errors occurred.

Q: How do you make `-delete` safe?

A: Require an explicit confirmation flag and delete in `postVisitDirectory`, after a directory's children, so directories are empty by the time you remove them. Tests run only inside `@TempDir`.

Q: What changes at 1 million files or on a network drive?

A: Reading attributes once per file into `FileInfo` avoids repeated system calls, which dominate the cost. On slow network drives, parallel walking (a virtual thread per subdirectory, or `StructuredTaskScope` as a Java 25 preview) helps, but output order is no longer deterministic, so offer it as an option.

Common mistakes in answers:

- One method with a growing `if` chain per flag combination.
- Ignoring precedence so `a -or b c` evaluates left to right.
- Following symlinks without loop detection.

TL;DR

A recursive-descent parser building a composite expression tree, evaluated with short-circuiting over a safe file walker.

24. Online Auction

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** Ch 11, Ch 12, Ch 19

What it is

An auction service where sellers list items with a starting price and end time, and bidders place bids until the auction closes. It supports **proxy bidding** (you enter your maximum, the system bids for you just enough to stay ahead), bid increments, reserve prices, and an anti-sniping extension.

The problem it solves

In the final seconds of an auction many bids arrive at once; the system must order them correctly, never accept a bid lower than the current price, and close at exactly the right time. Proxy bidding adds logic: two maximum bids compete automatically. The project trains concurrency around a hot object, time-driven state changes and the Observer pattern for outbid notifications.

Real-world examples

- eBay's help page on automatic bidding describes proxy bidding: you enter a maximum and the system raises your bid by increments only as needed.
- eBay also publishes its bid increments table, where the minimum raise depends on the current price — a good data-driven rule to implement.
- Proxy bidding behaves much like a second-price (Vickrey) auction: the winner pays about the second-highest maximum plus an increment.

Requirements


Functional

- Sellers create auctions: item, start price, optional reserve price, start and end times.
- Bidders place bids with a maximum; the visible price is set by proxy logic and an increment table.
- Reject bids below the minimum next bid, on closed auctions, or by the seller.
- Anti-sniping: a bid in the last 2 minutes extends the end by 2 minutes (configurable).
- Close at end time: winner if reserve met, otherwise unsold. Notify outbid bidders, winner and seller.
- Bid history per auction.

Non-functional

- Bids on one auction are totally ordered; 1,000 concurrent bids on one auction are all processed correctly.
- Closing happens within 1 second of the end time.
- Bid acceptance under 5 ms.


The architecture



- **AuctionService** — validates and routes bids; publishes events.
- **Auction** — the aggregate holding price, leader and end time; all rule checks happen inside, under one lock.
- **ProxyBidResolver** — decides who leads and the new visible price when a new maximum arrives.
- **IncrementTable** — data-driven minimum increments.
- **AuctionCloser** — schedules closing at `endsAt`, rescheduling when sniping extends it.
- **SnipingPolicy** — extension rule as a strategy.

- **AuctionListener** — Observer for notifications.

Data model



Type	Notes
`Bid`	record: bidder, max amount, time, sequence number
`BidResult`	sealed: `Leading(price)`, `Outbid(price)`, `Rejected(reason)`
`Outcome`	sealed: `Sold(winner, price)`, `Unsold`

Tech stack

Component	Choice	Why
Per-auction serialisation	`ReentrantLock` per auction	hot object, simple ordering
Closing	`ScheduledExecutorService`, reschedulable	timed transitions
Events	in-process listener list	decoupled notifications
Tests	JUnit 6, AssertJ, test clock	sniping and closing

Milestones

1. **Auction lifecycle.** *Done when:* bids before start or after close are rejected on a test clock.
2. **Increments and simple bids.** *Done when:* the increment table drives the minimum next bid at each price band.

3. **Proxy bidding.** *Done when:* A max 100, then B max 80, leaves A leading at 80 + increment; then C max 150 leads at 100 + increment.
4. **Sniping and closing.** *Done when:* a bid 30 s before the end extends it, and the closer fires at the new time, not the old.
5. **Concurrency + notifications.** *Done when:* 1,000 concurrent random bids produce the same winner and price as replaying them sequentially in acceptance order, and each outbid bidder is notified.

Deep dive: the hard parts

Proxy resolution. When a challenger arrives with maximum M2 and the leader has M1: if M2 > M1, the challenger leads at `min(M2, M1 + increment(M1))`; if M2 <= M1, the leader stays and the price becomes `min(M1, M2 + increment(M2))`. Ties go to the earlier bid. Encode this as a pure function and test it exhaustively — it is the heart of the system.

Serialising a hot auction. Every bid reads and writes price and leader. One lock per auction gives a total order and is fast since each bid is microseconds of work. Never hold the lock while notifying listeners; collect events inside, publish after unlocking.

Closing with extensions. The closer schedules a task for `endsAt`; when sniping extends the time, cancel and reschedule (or have the task check the current `endsAt` and re-schedule itself if it is now later). The close itself takes the auction lock so it cannot interleave with a last bid; a bid arriving after close fails its state check.

Testing strategy

Exhaustive tests of `ProxyBidResolver` over tables of (leader max, challenger max). A linearisability-style test: run concurrent bids, record the acceptance order, replay sequentially and compare. Test clock for sniping and closing. Mockito for listeners to verify notifications.

Trade-offs, scaling and failure modes

A per-auction lock scales to many auctions in parallel; a single auction is limited by one core, which is plenty. Distributed deployments route all bids for one auction to one owner (sharding by auction id). Clock skew between servers would make "end time" ambiguous — use one authoritative clock per auction owner. Showing other bidders' maxima would leak information — never expose them.

Stretch goals

- Dutch (descending price) auctions as another auction type.
- Buy-it-now that closes the auction immediately.
- Fraud signal: a bidder repeatedly bidding on one seller's items.

Skills practised

- Ch 19 — Platforms 2: auction case.
- Ch 11 — Behavioral patterns 2: Observer, State, Strategy.
- Ch 12 — Concurrency concepts: locks and scheduling.

In the interview

30-second answer: I built an online auction with proxy bidding: bidders submit a maximum and the system bids just enough to keep them ahead, using a data-driven increment table. The heart is a pure `ProxyBidResolver` function, tested exhaustively, and each `Auction` serialises its bids under one `ReentrantLock` so bids are totally ordered. Anti-sniping extends the end time when a bid arrives in the last two minutes, and the closer reschedules itself and takes the same lock, so no bid can land after close. 1,000 concurrent bids produced the same winner and price as replaying them sequentially in acceptance order.

Key terms to know:

- **Proxy (automatic) bidding** — the system bids on your behalf up to your hidden maximum.
- **Bid increment** — the minimum raise, which depends on the current price band.
- **Reserve price** — the hidden minimum the seller will accept; below it the item is unsold.
- **Anti-sniping** — extending the end when a late bid arrives so others can respond.
- **Second-price (Vickrey) behaviour** — the winner pays about the second-highest maximum plus an increment.
- **Aggregate** — `Auction` owns its price, leader and end time and enforces all rules inside its lock.
- **Total order** — every bid on one auction is processed one at a time in a single sequence.
- **Observer** — `AuctionListener` notified of outbid, win and close events after unlocking.
- **Linearisability check** — a concurrent run must equal some sequential replay of the same operations.

Q: How does proxy bidding decide the price?

A: The higher maximum leads at the lower maximum plus one increment, capped at the higher maximum; ties go to the earlier bid. For example, A max 100 then B max 80 leaves A leading at 80 + increment; then C max 150 leads at 100 + increment.

Q: How do you handle many bids in the last second?

A: Serialise bids per auction with a lock so each sees the latest price and leader; each bid takes microseconds, so one auction still handles thousands per second. Closing takes the same lock, so no bid lands after close.

Q: What is anti-sniping and how do you implement the extension?

A: It extends the end time when a bid arrives near the close, so others have time to respond. When a bid extends `endsAt`, cancel and reschedule the closer, or have the closer check the current `endsAt` when it fires and reschedule itself if it is now later.

Q: Why never notify listeners while holding the lock?

A: A listener may be slow (sending email) or may call back into the auction, which would block every bidder or deadlock. Collect events inside the lock and publish them after unlocking.

Q: Code-level: what does the resolver look like as a pure function?

A: No state, no clock, just inputs and a result, so it can be tested with tables.

```
static Lead resolve(Bid leader, Bid challenger, IncrementTable inc) {
    long m1 = leader.max(), m2 = challenger.max();
    if (m2 > m1) return new Lead(challenger, Math.min(m2, m1 + inc.at(m1)));
    return new Lead(leader, Math.min(m1, m2 + inc.at(m2)));   // ties keep the earlier bid
}
```

Q: What edge cases do you reject?

A: Bids below the minimum next bid, bids before start or after close, and bids from the seller. Results are a sealed `BidResult` (`Leading`, `Outbid`, `Rejected(reason)`), so callers handle each case explicitly.

Q: What changes at 10x auctions or across several servers?

A: Different auctions run in parallel because each has its own lock, so more auctions just use more cores. Across servers, route all bids for one auction to one owner (shard by auction id) and use that owner's clock as the single authority for end time to avoid clock-skew disputes.

Q: How do you test correctness under concurrency?

A: Exhaustive table tests of the resolver over (leader max, challenger max). For concurrency, fire random bids from many threads, record the acceptance order, replay sequentially and assert the same winner and price. A test clock drives sniping and closing, and Mockito verifies outbid notifications.

Common mistakes in answers:

- Exposing other bidders' maximums, which leaks information and breaks the auction.
- Closing from a timer without taking the auction lock, so a last bid can slip in after close.
- Making the winner pay their own maximum rather than just enough to beat the runner-up.

TL;DR

A per-auction serialised aggregate, a pure proxy-bid resolver, a reschedulable closer for anti-sniping, and listeners notified after unlocking.

25. Q&A Platform with Reputation

Level: Intermediate · **Time:** 2 weeks · **Prerequisites:** Ch 3, Ch 11, Ch 18

What it is

The core of a question-and-answer site like Stack Overflow: users ask questions with tags, others answer and comment, everyone votes, the asker accepts an answer, and users earn **reputation** that unlocks privileges (editing, closing votes). Feeds rank questions by recency, votes or activity.

The problem it solves

A Q&A site's value comes from its incentive rules: votes surface good content, reputation rewards good contributors, and privileges let trusted users moderate. These rules interact (an upvote changes reputation, which may unlock a privilege) and change over time. Hard-coding them into entity classes creates a tangle; the design challenge is to model content with inheritance or composition sensibly and drive reputation from **events** through configurable rules.

Real-world examples

- Stack Overflow's help centre explains what reputation is and how it is earned and lists the privileges unlocked at each reputation level.
- The handbook's platforms chapter has the Stack Overflow case study; this project adds event-driven reputation and ranking.

Requirements

Functional


- Users, questions (title, body, tags), answers, comments on both.
- Upvote and downvote questions and answers; one vote per user per post; change or retract.
- Accept one answer per question.
- Reputation rules: e.g. +10 for an upvote on a question or answer, +15 for an accepted answer, -2 for a downvote received; daily cap on reputation from votes.
- Privileges by threshold: comment, upvote, downvote, edit, close vote.
- Search by tag and text. Feeds: newest, top-voted this week, active (recent answers).
- Bounties (stretch).

Non-functional

- Vote counts consistent under concurrent votes on a hot post.

- Reputation recomputable from history (audit).
- Feed queries under 50 ms for 1 million posts in memory.

The architecture



- **Post / Question / Answer** — content hierarchy; shared behaviour (score, comments, edits) in `Post`.
- **VoteService** — enforces one vote per user per post and privilege checks; publishes `VoteCast`, `VoteChanged`, `AnswerAccepted` events.
- **ReputationEngine** — subscribes to events; each `ReputationRule` turns an event into reputation deltas; writes to a ledger.
- **ReputationLedger** — append-only reputation changes; a user's reputation is the sum (cached).
- **PrivilegePolicy** — thresholds as data.
- **FeedRanker** — strategies for ordering feeds.

Data model

Type	Notes
`Vote`	record: user, post, type (`UP`, `DOWN`), time; key (user, post)
`DomainEvent`	sealed: `VoteCast`, `VoteRetracted`, `AnswerAccepted`, `PostDeleted`
`ReputationChange`	record: user, delta, reason, source event id, time
`Privilege`	enum with threshold: `COMMENT`, `UPVOTE`, `DOWNVOTE`, `EDIT`, `CLOSE_VOTE`

Tech stack

Component	Choice	Why
Events	in-process bus (or your project 17 broker)	decouple reputation from votes
Votes	`ConcurrentHashMap` keyed by (user, post)	atomic one-vote rule
Search	inverted index by tag and word	fast filters
Tests	JUnit 6, AssertJ, jqwik	recompute-equals-incremental property

Milestones

1. **Content model.** *Done when:* questions, answers and comments can be created and fetched with authorship.
2. **Voting.** *Done when:* double votes are rejected, changing a vote adjusts the score by 2, and concurrent votes keep scores exact.

3. **Reputation from events.** *Done when:* a scripted sequence of events produces the expected reputation, including the daily cap.
4. **Privileges.** *Done when:* a 10-reputation user cannot downvote until crossing the configured threshold.
5. **Feeds and search.** *Done when:* "top this week" and tag search return the right ordered results on a seeded dataset.

Deep dive: the hard parts

Reversible reputation. Votes can be retracted and posts deleted; reputation must follow. Since every change is a ledger entry linked to its source event, a retraction emits compensating entries (the negative of the original). Recomputing reputation from scratch must equal the cached value — a powerful test.

Daily caps. A cap of N reputation per day from votes means a rule must know how much the user already earned today. Give rules read access to the ledger's "earned today" query; the rule emits a reduced delta when the cap is hit. Timezone choice for "day" (UTC, as many sites use) must be explicit.

Hot ranking. A "hot" score decays with age: for example `score / (ageHours + 2)^gravity`. It changes with time, so you cannot store it once; recompute for candidates in a recent window, or bucket by hour. Keep it a strategy so you can experiment.

Content inheritance. `Question` and `Answer` share a lot, so an abstract `Post` is reasonable. But avoid putting voting rules on `Post`; they belong in `VoteService`, which can check privileges and publish events.

Testing strategy

Event-sequence tests for reputation, including retractions and caps. Property test: for random event sequences, incremental reputation equals a full recompute. Concurrency test for votes. Ranking tests with a fixed clock.

Trade-offs, scaling and failure modes

Event-driven reputation decouples features but adds eventual consistency (a vote's effect on reputation lags slightly). Vote fraud (sock-puppet accounts voting for each other) needs detection rules over the vote log. Large sites move search to a dedicated engine; keep yours behind a `SearchIndex` interface.

Stretch goals

- Bounties: reputation escrowed and awarded to an answer.
- Badges as more event-driven rules.
- Duplicate-question detection by tag and title similarity.

Skills practised

- Ch 18 — Platforms 1: Stack Overflow case.
- Ch 3 — Relationships and UML: inheritance versus composition.
- Ch 11 — Behavioral patterns 2: Observer and Strategy.

In the interview

> **30-second answer:** I built the core of a Stack Overflow-style Q&A site where a `VoteService` enforces one vote per user per post and publishes domain events, and a `ReputationEngine` turns those events into reputation through configurable rule objects. Reputation is an append-only ledger linked to source events, so retracting a vote appends a compensating entry and the cached total can always be recomputed from history. Privileges are thresholds stored as data, and feeds

use ranking strategies including a time-decaying "hot" score. A property test checks that incremental reputation always equals a full recompute, even with retractions and the daily cap.

Key terms to know:

- **Domain event** — a record of something that happened, such as `VoteCast` or `AnswerAccepted`.
- **Observer / event-driven rules** — `ReputationRule`s subscribe to events instead of being called by voting code.
- **Append-only ledger** — every reputation change is a new row linked to its source event.
- **Compensating entry** — the negative of an earlier entry, used to undo it without deleting history.
- **Daily cap** — a limit on reputation earned from votes per day; rules read "earned today" from the ledger.
- **Privilege threshold** — reputation needed to comment, downvote, edit or vote to close.
- **Hot score with decay** — popularity divided by a growing function of age, recomputed over recent candidates.
- **Eventual consistency** — reputation updates a moment after the vote, not in the same step.
- **Inheritance vs composition** — `Question` and `Answer` share an abstract `Post`, but rules stay out of it.

Q: How do you keep reputation correct when votes are retracted?

A: Reputation is an append-only ledger linked to source events; a retraction appends compensating entries that reverse the original. The total is a sum and can be recomputed at any time, which doubles as an audit and a test oracle.

Q: How do you enforce one vote per user per post under concurrency?

A: Key votes by (user, post) in a concurrent map and update atomically with `compute`, adjusting the post score in the same critical section. Changing an upvote to a downvote adjusts the score by 2, and two simultaneous votes from one user cannot both count.

Q: Where do reputation rules live?

A: In rule objects subscribed to domain events, not in the post or user classes, so rules can change without touching content code. Adding a badge or bounty is another subscriber.

Q: How does the daily cap interact with retractions?

A: The capped rule asks the ledger how much the user earned today and emits a reduced delta when the cap is reached. A retraction must reverse exactly what was granted, which may be less than the nominal +10, so compensation copies the original entry's delta rather than recomputing the rule. Define "today" in one explicit time zone, usually UTC.

Q: Why an abstract `Post` class but not voting logic on it?

A: `Question` and `Answer` share real data and behaviour (score, comments, edits), so inheritance fits. Voting needs privilege checks and event publishing, which involve users and other services, so it belongs in `VoteService`; putting it on `Post` would give the entity too many reasons to change.

Q: Code-level: how do you make the one-vote rule atomic?

A: Use the (user, post) record as a key and `compute`.

```
record VoteKey(UserId user, PostId post) {}
votes.compute(new VoteKey(u, p), (k, old) -> {
    int delta = (newType == UP ? 1 : -1) - (old == null ? 0 : (old.type() == UP ? 1 : -1));
    scores.merge(p, delta, Integer::sum);           // score updated with the vote
    return new Vote(u, p, newType, clock.instant());
});
```

Records give correct `equals` and `hashCode` for free, which a map key needs. Updating a different map inside `compute` is allowed, but never modify the same map from inside its own `compute` function.

Q: How do you rank a "hot" feed?

A: Use a score that decays with age, such as `votes / (ageHours + 2)^gravity`. Because it changes as time passes you cannot store it once; recompute it for candidates in a recent window, or bucket by hour, and keep the formula a strategy so it can be tuned.

Q: What changes at 10x users or with vote fraud?

A: The in-memory inverted index and feed sorting move to a search engine behind the `SearchIndex` interface, and the event bus becomes a durable queue. Sock-puppet voting rings are found by rules over the vote log, such as many votes between the same two accounts, which then emit compensating reputation entries.

Q: How do you test it?

A: Event-sequence tests for reputation including retractions and the cap, a jqwik property that incremental equals recompute for random event streams, a concurrency test for votes on a hot post, and ranking tests with a fixed clock.

Common mistakes in answers:

- Storing reputation as a mutable integer with no history, so retractions and audits are impossible.
- Putting reputation rules inside `Post` or `User`.
- Forgetting that the hot score changes over time and cannot be stored once.

TL;DR

A post hierarchy for content, a vote service that publishes events, and a rule-driven reputation ledger that can always be recomputed.

26. In-Memory KV Store with TTL and Transactions

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 10, Ch 12, Ch 13, Ch 20

What it is

A small Redis-like key-value store inside the JVM (and optionally behind a simple text protocol over TCP). It stores strings, lists and hashes; keys can expire after a time-to-live (TTL); clients can group commands in **transactions** that apply atomically; and the store can snapshot to disk and recover. It is the advanced cousin of the cache project, where correctness under concurrency and failure is the main subject.

The problem it solves

Many systems need a fast shared store for sessions, counters and locks. Building one teaches the problems real stores solve: expiring millions of keys without scanning them all, making a group of commands atomic without stopping the world, and surviving a crash without losing (too much) data.

The design work is choosing a concurrency model (single-threaded command loop versus fine-grained locks) and implementing transactions on top.

Real-world examples

- Redis documents EXPIRE, including how it combines passive expiry on access with periodic active sampling of keys with a TTL — the scheme you implement.
- Redis transactions queue commands with MULTI and run them together on EXEC, with optimistic WATCH for check-and-set — the model for milestone 4.
- The handbook's concurrency-problems chapter builds a thread-safe TTL cache; this project generalises it.

Requirements


Functional

- Commands: `GET`, `SET` (with optional `EX` seconds), `DEL`, `EXISTS`, `INCR`, `EXPIRE`, `TTL`, list ops (`LPUSH`, `RPOP`, `LRANGE`), hash ops (`HSET`, `HGET`).
- Transactions: `MULTI`, queued commands, `EXEC` applies all atomically; `DISCARD`; `WATCH key` aborts EXEC if the key changed since WATCH.
- Expiry: expired keys are never returned; memory reclaimed by background sampling.
- Persistence: periodic snapshot to a file plus an append-only command log; recovery on start.
- A text protocol over TCP served by virtual threads (stretch for milestone 5).

Non-functional

- 500,000 simple operations per second in-process on a laptop (benchmark and report).
- Expiry precision within 100 ms of the deadline for reads; memory reclaimed within seconds.
- After a crash, recovery loses at most 1 second of acknowledged writes (with log fsync every second).

The architecture



- **KvServer / CommandParser** — network edge: one virtual thread per connection reads lines, parses into commands.
- **Command** — the Command pattern; each command knows how to execute against the keyspace and whether it writes (for logging).
- **Engine** — the single owner of the keyspace. All commands run on one engine thread in order (Redis-style), which makes every command and every EXEC atomic for free.
- **Keyspace** — data map plus a separate map of expiry deadlines.
- **ExpiryManager** — lazy check on access plus periodic random sampling.

- **TxManager** — per-session queues and watched-key versions.
- **Persistence** — append-only log and snapshots.

Data model

Type	Notes
`Value`	sealed: `StrVal(bytes)`, `ListVal(Deque)`, `HashVal(Map)`
`Entry` metadata	version counter per key (for WATCH), expiry deadline (`long` millis)
`Session`	connection id, in-transaction flag, queued commands, watched keys with versions
`Reply`	sealed: `Ok`, `Bulk(value)`, `Int(n)`, `Nil`, `Err(msg)`, `Multi(list)`

Tech stack

Component	Choice	Why
Concurrency model	single engine thread + `BlockingQueue` of requests	atomicity without locks
Connections	virtual thread per client	simple blocking I/O, many clients
Persistence	`FileChannel` append + periodic `force`	durability control
Benchmarks	JMH + a load-generator client	throughput, latency
Tests	JUnit 6, AssertJ, `@TempDir`, jqwik	model-based testing

Milestones

1. **Keyspace and commands (in-process).** *Done when:* a model-based test (random commands vs a reference `HashMap`) agrees on 100,000 operations.
2. **TTL.** *Done when:* a key with `EX 1` is invisible after 1 s on a test clock, and active sampling reclaims 95% of 1 million expired keys within a few cycles.
3. **Engine thread.** *Done when:* 64 client threads doing `INCR` on one key end with the exact total, without any locks in `Keyspace`.
4. **Transactions and WATCH.** *Done when:* EXEC applies all queued commands with no interleaving, and EXEC after a watched key changed returns nil and applies nothing.
5. **Persistence and network.** *Done when:* killing the process and restarting recovers state from snapshot + log, and a TCP client can run commands.

Deep dive: the hard parts

Two-part expiry. Checking every key's deadline on a timer is O(n). Instead: (1) *passive* — on each access, if the key's deadline has passed, delete it and return nil, so correctness never depends on the background job; (2) *active* — every 100 ms, sample, say, 20 random keys from the expires map and delete the expired ones; if more than a quarter were expired, repeat immediately. This keeps memory bounded with tiny cost. Random sampling needs O(1) random access — keep expiring keys in an array-backed structure alongside the map.

Why one engine thread makes transactions trivial. If only the engine thread touches data, then running all of a transaction's commands in one go on that thread is automatically atomic and isolated. WATCH is optimistic concurrency: each key has a version incremented on every write; WATCH records the version; EXEC checks all watched versions before running and aborts if any changed. No locks are held while the client builds its transaction.

Durability trade-off. Append each write command to the log before replying. Calling `force` (fsync) on every write is safest but slow; every second loses at most a second of writes. Snapshots bound recovery time: write the keyspace to a temp file and atomically rename, then truncate the log.

Taking a snapshot without pausing writes is hard (Redis forks the process); in Java, iterate a copy-on-write view or accept a brief pause.

Testing strategy

Model-based testing against a simple reference implementation. Test clock injected into the engine for TTL. Concurrency tests for INCR and transactions. Crash tests: run writes, kill the engine without a clean shutdown (stop the thread abruptly), recover from `@TempDir` files and compare. JMH for throughput with and without logging.

Trade-offs, scaling and failure modes

A single engine thread caps throughput at one core but removes all data races; sharding keys across N engines (by hash) scales, at the cost of cross-shard transactions. Fine-grained locking uses more cores but makes transactions need lock ordering or two-phase locking. Large values or `LRANGE 0 -1` on a huge list block the engine — cap response sizes. Clock jumps (NTP corrections) can expire keys early; use a monotonic clock for deadlines within one process.

Stretch goals

- Pub/sub commands on the same server.
- Replication: a follower applying the leader's command log.
- `maxmemory` with LRU or LFU eviction (reuse project 15).

Skills practised

- Ch 20 — Components: in-memory cache design.
- Ch 13 — Concurrency problems: TTL cache and concurrent maps.
- Ch 12 — Concurrency concepts: virtual threads, single-writer design.
- Ch 10 — Behavioral patterns 1: Command.

In the interview

30-second answer: I built a Redis-like in-JVM key-value store with strings, lists and hashes, TTLs, MULTI/EXEC transactions with WATCH, and snapshot-plus-log persistence. All commands run in order on one engine thread fed by a queue, so every command and every EXEC is atomic with no locks in the keyspace. Expiry is two-part: a passive check on every read guarantees expired keys are never returned, and active random sampling reclaims memory without scanning millions of keys. Writes go to an append-only log fsynced every second, so a crash loses at most one second of acknowledged writes, and I measured throughput with JMH.

Key terms to know:

- **TTL** — time-to-live; the key disappears after a deadline.
- **Passive (lazy) expiry** — check the deadline on access and delete if passed.
- **Active expiry by sampling** — periodically test a random sample of keys with TTLs; repeat if many were expired.
- **Single-threaded engine** — one thread owns all data, so operations are serialised without locks.
- **MULTI / EXEC / DISCARD** — queue commands, then run them together or throw them away.
- **WATCH** — optimistic check-and-set: EXEC aborts if a watched key's version changed.
- **Append-only file (AOF) / command log** — every write command recorded for replay after a crash.
- **fsync (`FileChannel.force`)** — forces data from the OS cache to disk; the durability versus speed knob.
- **Snapshot** — a full copy of the keyspace that bounds replay time.

Q: How do you expire millions of keys efficiently?

A: Lazily on access for correctness, plus periodic random sampling of keys with TTLs to reclaim memory: sample about 20, delete expired ones, and repeat immediately if more than a quarter were expired. Sampling needs O(1) random access, so keep expiring keys in an array-backed structure alongside the map.

Q: How are transactions atomic?

A: All commands run on one engine thread; EXEC runs the queued commands back to back, so nothing interleaves. WATCH adds optimistic checks using per-key version numbers incremented on every write.

Q: How do you survive a crash?

A: An append-only command log flushed at a chosen interval, plus periodic snapshots to cap replay time. On start, load the latest snapshot and replay the log after it.

Q: Does EXEC roll back if one queued command fails?

A: No, and neither does Redis. A command that fails at run time, such as `INCR` on a list, returns an error in its slot while the others still apply; only errors detected while queuing, such as an unknown command, abort the whole transaction. Atomic here means "no interleaving", not "all-or-nothing on errors".

Q: Why a single engine thread rather than fine-grained locks?

A: One thread removes every data race and makes transactions trivial, and an in-memory command takes well under a microsecond, so one core handles hundreds of thousands per second. Fine-grained locks use more cores but transactions then need lock ordering or two-phase locking. To scale past one core, shard keys across several engines by hash.

Q: Code-level: how does WATCH work with versions?

A: Record versions at WATCH time and compare them at EXEC on the engine thread.

```
// WATCH k
session.watched().put(k, keyspace.version(k));
// EXEC (runs on the engine thread)
for (var w : session.watched().entrySet())
    if (keyspace.version(w.getKey()) != w.getValue()) return Reply.NIL;   // abort
return new Reply.Multi(session.queued().stream().map(c -> c.execute(keyspace)).toList());
```

Q: What blocks the engine, and what breaks first at 10x load?

A: Any slow command stalls everyone: `LRANGE 0 -1` on a million-item list or a snapshot that copies the whole keyspace. Cap response sizes, and snapshot from a copy-on-write view or accept a short pause. At 10x load the single core saturates first, so shard by key hash, accepting that cross-shard transactions are no longer simple.

Q: What about clock jumps?

A: If deadlines use wall-clock time and NTP moves the clock forward, keys expire early. Use a monotonic clock such as `System.nanoTime` for in-process deadlines, and convert to wall time only when persisting.

Q: How do you test it?

A: Model-based testing: run random commands against the store and a plain `HashMap` reference and compare every reply. A test clock drives TTL, 64 threads doing `INCR` must reach the exact total, and crash tests stop the engine abruptly and recover from `@TempDir` files.

Common mistakes in answers:

- A timer per key or a full scan to expire keys.

- Claiming Redis-style transactions roll back on errors.
- fsync on every write without noting the throughput cost, or never fsyncing without noting the data-loss window.

TL;DR

A single-threaded command engine for lock-free atomicity, two-part TTL expiry, optimistic WATCH transactions and log-plus-snapshot durability.

27. Thread Pool and Task Scheduler

Level: Advanced · **Time:** 2–3 weeks · **Prerequisites:** Ch 12, Ch 13

What it is

Your own implementation of the machinery behind `ExecutorService` and `ScheduledExecutorService`: a fixed or elastic pool of worker threads taking tasks from a queue, futures for results, graceful shutdown, rejection when overloaded, and a scheduler for delayed and periodic tasks — plus a cron-like front end. You then compare it with the JDK and with virtual threads.

The problem it solves

Creating a platform thread per task is expensive and unbounded; a pool reuses a fixed set of threads and queues work. Getting a pool right is subtle: workers must survive task exceptions, shutdown must not lose or hang tasks, and an overloaded pool must push back instead of exhausting memory. Building one is the best way to understand what `ThreadPoolExecutor` parameters really do and when virtual threads make pools unnecessary.

Real-world examples

- The JDK's ThreadPoolExecutor documentation describes core and maximum pool sizes, queueing strategies and rejection policies — the reference you are reimplementing.
- Virtual threads (JEP 444) make one-thread-per-task cheap for blocking I/O work, and the JEP explicitly advises against pooling virtual threads.
- The JDK's DelayQueue holds elements until their delay expires, a building block for schedulers.

Requirements


Functional

- `submit(Callable)` returns a future supporting `get`, `get(timeout)`, `cancel(interrupt)`.
- Core size, max size, keep-alive for idle extra threads, bounded queue.
- Rejection policies: abort (throw), caller-runs, discard, discard-oldest.
- `shutdown` (finish queued work), `shutdownNow` (interrupt and return pending tasks), `awaitTermination`.
- Scheduler: `schedule(task, delay)`, `scheduleAtFixedRate`, `scheduleWithFixedDelay`, and a cron expression parser for "every 5 minutes" style jobs.
- Metrics: active threads, queue size, completed tasks, rejected tasks.

Non-functional


- No task lost or run twice, verified under stress.
- A throwing task never kills the pool (worker replaced or loop continues).
- Scheduling accuracy within 10 ms for delays under 1 minute on an idle machine.

The architecture



- **SimpleExecutor** — queue, worker set and a control state (running, shutdown, stop, terminated) plus worker count.
- **Worker** — a loop: take a task, run it, catch everything, repeat; exits when the pool shuts down or it has been idle beyond keep-alive.
- **TaskFuture** — the future: state machine from new to completed/failed/cancelled, with waiting callers.
- **RejectionPolicy** — Strategy for overload.
- **Scheduler** — a single timer thread takes due tasks from a `DelayQueue` and hands them to the executor; periodic tasks re-enqueue themselves.
- **CronExpression** — parses a 5-field cron string and computes the next fire time.

Data model



Task future states (as in the JDK's `FutureTask`): `NEW` → `COMPLETING` → `NORMAL` / `EXCEPTIONAL`, or `NEW` → `CANCELLED`, or `NEW` → `INTERRUPTING` → `INTERRUPTED` for `cancel(true)`.

Tech stack

Component	Choice	Why
Queue	`LinkedBlockingQueue` / `ArrayBlockingQueue`	blocking take with timeout
Future waiting	`LockSupport.park/unpark` or a `CountDownLatch`	learn the primitive
State	`AtomicInteger` with CAS	lock-free state checks
Stress tests	JUnit 6 + jcstress	races in future and state
Benchmarks	JMH vs JDK pool vs virtual threads	real comparison

Milestones

1. **Fixed pool.** *Done when:* 100,000 tasks complete exactly once with 8 workers, and a throwing task does not reduce the worker count.
2. **Futures.** *Done when:* `get(timeout)` times out correctly, `cancel(true)` interrupts a running task, and jcstress finds no race between completion and cancel.

3. **Elastic sizing and rejection.** *Done when:* with core 2, max 4, queue 10, the 15th concurrent long task is rejected per policy, and extra threads exit after keep-alive.
4. **Shutdown semantics.** *Done when:* `shutdown` runs all queued tasks and then terminates; `shutdownNow` returns unstarted tasks and interrupts running ones.
5. **Scheduler and cron.** *Done when:* fixed-rate and fixed-delay differ as documented under a slow task, and the cron expression `*/5 * * * *` yields the right next times across a DST change.

Deep dive: the hard parts

When to add a thread. The JDK's rule surprises people: below core size, always start a new thread; at core size, queue the task; only when the queue is *full* add threads up to max; when at max and full, reject. With an unbounded queue, max size is never reached. Implement exactly this, then write down why a bounded queue matters.

The future's race. A task completing and a caller cancelling can happen at the same moment. Use a single atomic state: completion does CAS from NEW to COMPLETING, cancel does CAS from NEW to CANCELLED; only one wins. Waiters must be released in both cases and must not miss the wake-up — park in a loop that re-checks state.

Fixed rate versus fixed delay. Fixed rate computes the next start from the *previous scheduled start* (catching up if late); fixed delay computes it from the *end* of the previous run. If a periodic task throws, the JDK stops future runs — decide your behaviour and document it.

Virtual threads change the question. For blocking I/O tasks, a virtual thread per task (`Executors.newVirtualThreadPerTaskExecutor()`) removes queueing and sizing decisions. Pools remain useful to *limit* concurrency for CPU-bound work or scarce resources — which a `Semaphore` can also do. Benchmark both.

Testing strategy

Stress tests counting executions with `LongAdder` and asserting exact totals. jcstress tests for the future's state machine. Tests with latches to control when tasks start and finish, so shutdown semantics can be checked precisely. A fake clock for cron next-time calculation.

Trade-offs, scaling and failure modes

Bounded queues provide backpressure but force a rejection policy; caller-runs is a neat throttle because the submitting thread slows itself. Thread-local state leaks between tasks on pooled threads — clear it or use scoped values (JEP 506, final in Java 25 — on Java 21 the API is preview-only, so clearing the `ThreadLocal` in a `finally` block is the portable fix). A deadlock occurs when pool tasks wait on other tasks queued in the same full pool — a classic interview trap.

Stretch goals

- A work-stealing pool with per-worker deques (the Fork/Join idea).
- Priority tasks with a `PriorityBlockingQueue`.
- Pool metrics exported every second and an adaptive core size.

Skills practised

- Ch 12 — Concurrency concepts: executors, futures, virtual threads.
- Ch 13 — Concurrency problems: bounded blocking queue, Fork/Join.
- Ch 11 — Behavioral patterns 2: Strategy for rejection.

In the interview

> **30-second answer:** I reimplemented the core of `ThreadPoolExecutor` and `ScheduledExecutorService`: workers looping over a blocking queue, the JDK's growth rule (core threads first, then queue, then extra threads only when the queue is full), pluggable rejection policies, and precise

`shutdown` versus `shutdownNow` semantics. Futures are a CAS-driven state machine so a completion and a cancel racing each other have exactly one winner, which jcstress confirmed. The scheduler uses a `DelayQueue` and handles fixed rate versus fixed delay and cron expressions. I benchmarked it against the JDK pool and virtual threads, and the lesson is that pools now mainly limit concurrency rather than save thread creation.

Key terms to know:

- **Core / max pool size** — threads kept alive versus the most allowed when the queue is full.
- **Bounded queue** — fixed-capacity work queue that provides backpressure.
- **Rejection policy** — abort, caller-runs, discard or discard-oldest when queue and threads are full.
- **Future** — a handle to a result that may not exist yet; `get`, `cancel`, `isDone`.
- **CAS state machine** — `NEW` moves to completing or cancelled through one atomic compare-and-set.
- **Fixed rate vs fixed delay** — next start from the previous scheduled start, or from the previous run's end.
- **Graceful shutdown** — `shutdown` finishes queued work; `shutdownNow` interrupts and returns unstarted tasks.
- **Virtual threads** — JVM-scheduled threads cheap enough to create per task; not meant to be pooled.
- **Thread-starvation deadlock** — tasks in a full pool waiting for other tasks queued behind them.

Q: When does a `ThreadPoolExecutor` create threads beyond core size?

A: Only when the queue is full. Below core size it always starts a thread; at core size it queues; with a full queue it adds threads up to max; at max with a full queue it rejects. With an unbounded queue it never grows beyond core.

Q: What happens to a worker if a task throws?

A: With `submit`, the exception is captured into the future and rethrown wrapped in `ExecutionException` from `get()`. With `execute`, it escapes to the worker; my worker catches everything and continues (the JDK replaces the dying worker). Either way the pool must not shrink silently.

Q: Do we still need thread pools with virtual threads?

A: Not for blocking I/O concurrency: use `Executors.newVirtualThreadPerTaskExecutor()` and a thread per task. Pools or semaphores still limit CPU-bound work to the number of cores and protect scarce resources such as database connections.

Q: Why is caller-runs a good rejection policy?

A: When the pool is saturated, the submitting thread runs the task itself, so it cannot submit more until it finishes. That throttles the producer naturally without losing work, at the cost of the caller's own latency.

Q: What is the race inside a future, and how do you avoid it?

A: A task completing and a caller cancelling can happen at the same instant. A single atomic state with CAS from `NEW` to either `COMPLETING` or `CANCELLED` lets only one win. Waiters must park in a loop that re-checks state, so no wake-up is missed.

Q: Code-level: what is the classic pool deadlock?

A: A task that submits a subtask to the same small pool and waits for it.

```
var pool = Executors.newFixedThreadPool(1);
pool.submit(() -> {
    Future<?> inner = pool.submit(() -> "child");
    return inner.get();   // waits forever: the only thread is busy waiting
});
```

Use a separate pool, a fork/join pool designed for this, or virtual threads.

Q: What leaks between tasks on pooled threads?

A: `ThreadLocal` values set by one task stay on the thread for the next task, which can leak user identity or memory. Clear them in a `finally` block, or use `ScopedValue` (final in Java 25 via JEP 506), whose bindings end automatically when the scope exits.

Q: What happens if a periodic task throws?

A: In the JDK, the exception cancels all future runs of that task silently, visible only through its future. My scheduler documents its choice: log and keep scheduling, or stop like the JDK. Wrapping the body in try/catch is the usual fix.

Q: How do you test shutdown semantics precisely?

A: Control task timing with latches so you know exactly which tasks are running and which are queued, then call `shutdown` or `shutdownNow` and assert what ran, what was returned, and that `awaitTermination` returns. Count executions with `LongAdder` to prove no task ran twice or was lost under stress.

Common mistakes in answers:

- Thinking max pool size is used with an unbounded queue.
- Pooling virtual threads.
- Forgetting that a throwing periodic task stops being scheduled.

TL;DR

A queue plus workers with JDK-style growth rules, a CAS-driven future state machine, explicit shutdown states and a delay-queue scheduler — benchmarked against virtual threads.

28. Concurrent Order-Matching Engine

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 12, Ch 13, Ch 19

What it is

The heart of a stock exchange: an **order book** per instrument holds buy orders (bids) and sell orders (asks) sorted by price, and a **matching engine** pairs incoming orders with resting ones using **price-time priority** (best price first; at the same price, earliest first). It supports limit and market orders, cancels and amendments, and emits trades and market data.

The problem it solves

Exchanges must match orders fairly, deterministically and very fast, while thousands of clients submit concurrently. Fairness means strict price-time priority; determinism means the same input sequence always yields the same trades (essential for audit and recovery). The design lesson: serialise matching per instrument on a single thread fed by a queue, rather than locking a shared book — the approach popularised by LMAX.

Real-world examples

- Martin Fowler's article on the LMAX architecture describes a financial exchange whose business logic runs on a single thread in memory, fed by ring buffers, with event sourcing for recovery.
- The LMAX Disruptor is the open-source inter-thread messaging library that came out of that work.
- An order book is the standard structure; the handbook's stock brokerage/exchange case gives the domain model.

Requirements


Functional

- Instruments with tick size (minimum price step) and lot size.
- Order types: limit, market, immediate-or-cancel (IOC), fill-or-kill (FOK).
- Price-time priority matching; partial fills; trades at the resting order's price.
- Cancel and amend (reducing quantity keeps priority; changing price loses it).
- Output: execution reports to order owners, trade prints, top-of-book and depth updates.
- Self-trade prevention (an account cannot trade against itself).

Non-functional


- Matching latency under 10 microseconds median for one instrument in memory (measure with JMH, report honestly).
- Deterministic: replaying the input log reproduces identical output.
- Throughput of at least 1 million orders per second across instruments on a laptop as a goal.

The architecture



- **Gateway** — validates client input (tick size, lot size, account) on many threads.
- **Sequencer** — assigns a global sequence number and journals the command before matching.
- **InstrumentRouter** — sends each command to its instrument's engine queue.
- **MatchingEngine** — one thread per instrument (or per group): the only writer of its book.
- **OrderBook / PriceLevel** — sorted price levels, each a FIFO queue of orders.
- **EventPublisher** — execution reports and market data out to subscribers.
- **CommandJournal** — the input log for deterministic replay.

Data model



Type	Notes
`Order`	id, account, side, type, price in ticks (`long`), quantity, remaining, sequence
`Trade`	buy id, sell id, price, quantity, sequence, aggressor side
`EngineEvent`	sealed: `Accepted`, `Rejected`, `Fill`, `Cancelled`, `BookUpdate`

Tech stack

Component	Choice	Why
Prices	`long` ticks	no floating point, fast compares
Book sides	`TreeMap<Long, PriceLevel>` (bids descending)	sorted best-price access
Engine input	`ArrayBlockingQueue` first, Disruptor as stretch	single-writer pipeline
Latency	JMH + `HdrHistogram`-style percentile recording	tail latency matters
Tests	JUnit 6, AssertJ, jqwik, golden replay files	determinism

Milestones

1. **Book and limit matching.** *Done when:* scenario tests show price-time priority, partial fills and trades at resting prices.
2. **Order types and cancels.** *Done when:* IOC leaves no residue, FOK either fills fully or does nothing, and quantity-down amends keep queue position.
3. **Single-writer engine with queues.** *Done when:* 16 producer threads submitting 1 million orders produce no data races and identical results to sequential replay of the journal.
4. **Market data and reports.** *Done when:* top-of-book events match the book state after every command.
5. **Performance.** *Done when:* JMH reports median and 99th-percentile matching latency, and you have removed at least one allocation hot spot with evidence.

Deep dive: the hard parts

Price-time priority with O(1) cancels. Price levels are a sorted map; within a level, orders sit in FIFO order. Cancelling an order in the middle of a deque is O(n). Use an intrusive doubly linked list per level (each order node has prev/next) plus `ordersById` map, so cancel is O(1). Remove empty levels from the tree immediately so best price is always `firstKey`.

Single writer, no locks. Matching needs read-modify-write of both sides of the book in one step. Instead of locking, give each instrument's book to exactly one thread and feed it commands through a queue. Producers never touch the book. This removes lock contention and makes behaviour deterministic given the input order — which the sequencer fixes and the journal records.

Determinism and recovery. If the engine is a pure function of its input sequence (no wall-clock reads, no hash-order iteration, no randomness), then replaying the journal rebuilds exactly the same book after a crash. Pass timestamps in on commands from the sequencer instead of reading the clock inside the engine.

Allocation and latency. Garbage collection pauses show up in tail latency. Reuse order objects from a pool, avoid boxing `Long` keys in hot paths (a primitive-keyed map or arrays indexed by price offset), and keep the per-command path free of logging. Measure before and after each change.

Testing strategy

Scenario tests written as tables (incoming orders → expected trades and book). Property tests: the book is never crossed (best bid < best ask) after any command; total quantity is conserved (submitted = filled + resting + cancelled). Determinism test: replay the journal twice and compare outputs byte for byte. JMH for latency.

Trade-offs, scaling and failure modes

One thread per instrument scales across instruments, but a single very hot instrument is capped at one core — exchanges accept this because it buys determinism. A `TreeMap` is simple; arrays indexed by tick offset are faster when prices sit in a narrow band. The journal write is on the critical path; batch writes or replicate to a standby in memory (as LMAX does) to keep latency low while staying durable.

Stretch goals

- Replace the queue with the LMAX Disruptor and compare latency.
- Stop orders triggered by last trade price.
- A hot standby engine replaying the same journal, with failover.

Skills practised

- Ch 19 — Platforms 2: stock brokerage and exchange case.
- Ch 12 — Concurrency concepts: single-writer principle, queues.
- Ch 13 — Concurrency problems: blocking queues and producer-consumer.

In the interview

> **30-second answer:** I built a price-time priority matching engine: each instrument's order book is a `TreeMap` of price levels, each level an intrusive FIFO linked list, with an id map so cancels are O(1). Instead of locking a shared book, many gateway threads validate orders and a sequencer journals them, then one engine thread per instrument is the only writer of its book. Because the engine reads no wall clock, no randomness and no hash-order iteration, replaying the journal reproduces identical trades, which is both the recovery mechanism and my main test. 16 producer threads sending a million orders gave the same output as sequential replay, and I report median and p99 matching latency from JMH.

Key terms to know:

- **Order book** — resting buy orders (bids) and sell orders (asks) sorted by price.
- **Price-time priority** — best price first; at equal price, earliest first.
- **Limit / market / IOC / FOK** — rest at a price; take any price; fill what you can now and cancel the rest; fill completely now or do nothing.
- **Partial fill** — an order matched for part of its quantity.
- **Tick size** — the minimum price step; prices stored as `long` ticks.
- **Single-writer principle** — one thread owns the book; others send it commands.
- **Sequencer and journal** — assign a global order and record inputs before processing.
- **Determinism** — same input sequence, same output, which enables replay recovery.
- **Crossed book** — best bid at or above best ask; must never remain after matching.

Q: What is price-time priority?

A: Better prices match first; among orders at the same price, the earliest one matches first. Trades execute at the resting order's price, so an aggressive buyer at 101 hitting a resting sell at 100 trades at 100.

Q: Why a single thread per book instead of locks?

A: Matching reads and modifies both sides of the book in one step. A single writer avoids lock contention and gives deterministic, replayable behaviour, which a lock-based design cannot, because lock acquisition order varies between runs.

Q: How do you recover after a crash?

A: Journal every sequenced command before matching and replay it into a fresh engine; determinism guarantees the same book. Timestamps come in on the commands from the sequencer rather than being read from the clock inside the engine.

Q: How do you make cancel O(1)?

A: Removing from the middle of a deque is O(n). Each order node keeps prev and next pointers within its price level (an intrusive doubly linked list), and `ordersById` finds the node in O(1), so unlinking is constant time. Empty levels are removed from the tree immediately so the best price is always `firstKey`.

Q: Why does reducing quantity keep priority but changing price lose it?

A: Reducing quantity does not disadvantage anyone behind you in the queue. Changing price, or increasing size, would let you jump ahead unfairly, so it is treated as a cancel plus a new order with a new time.

Q: Code-level: how do you keep bids in descending order?

A: Give the bid side a reversed comparator so `firstKey` is always the best price.

```
NavigableMap<Long, PriceLevel> bids = new TreeMap<>(Comparator.reverseOrder());
NavigableMap<Long, PriceLevel> asks = new TreeMap<>();
boolean crosses(Order buy) { return !asks.isEmpty() && buy.priceTicks() >= asks.firstKey(); }
```

For latency work, replace the boxed `Long` keys with arrays indexed by tick offset when prices sit in a narrow band.

Q: What breaks first at 10x load?

A: A single very hot instrument is capped at one core, which exchanges accept because it buys determinism; different instruments scale across cores. The synchronous journal write is often the

real bottleneck, so batch writes or replicate to a hot standby in memory as LMAX does. Garbage-collection pauses then dominate tail latency, so pool objects and avoid allocation in the hot path.

Q: How do you prove correctness?

A: Table-driven scenario tests (incoming orders to expected trades and book). Property tests that the book is never crossed after any command and that quantity is conserved: submitted = filled + resting + cancelled. A determinism test replays the journal twice and compares output byte for byte.

Common mistakes in answers:

- Using `double` for prices.
- A global lock around a shared book, then claiming it is deterministic.
- Reading `System.currentTimeMillis()` inside the engine, which breaks replay.

TL;DR

Sorted price levels of FIFO orders with O(1) cancel, one deterministic single-writer engine per instrument fed by a sequenced journal, and latency measured not guessed.

29. Ride-Hailing Dispatch

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 11, Ch 12, Ch 20

What it is

The dispatch core of a ride-hailing app (like Uber or Lyft): drivers stream location updates, riders request trips, and the system finds nearby available drivers, offers the trip to one at a time (or several), handles accept/decline/timeout, and tracks the trip through pickup and drop-off. Pricing includes a surge multiplier based on local supply and demand.

The problem it solves

Dispatch must answer "which available drivers are near this point?" thousands of times a second while drivers move constantly, and must never assign one driver to two trips. Offers time out, drivers go offline mid-offer, riders cancel. The design combines a **spatial index**, a **trip state machine**, concurrency-safe driver reservation and pluggable matching strategies.

Real-world examples

- Uber's engineering blog post on H3 explains its hexagonal hierarchical spatial index, used to bucket the world into cells for analysis such as pricing and dispatch.
- H3 is open source with bindings for many languages, including Java.
- The handbook's components chapter has the Uber case study; this project implements the matching loop and spatial index.

Requirements

Functional


- Drivers: go online/offline, send location every few seconds, accept or decline offers.
- Riders: request a ride (pickup, drop-off, vehicle type), cancel.
- Find the K nearest available drivers of the right type within a radius.
- Offer flow: offer to the best driver, 15-second timeout, then next candidate; give up after N attempts.
- Trip states: requested, driver assigned, arriving, in progress, completed, cancelled.
- Surge: per cell, multiplier from open requests versus available drivers.

- Fare: base + per km + per minute, times surge.

Non-functional


- Location update processing under 1 ms; nearest-driver query under 5 ms for 100,000 online drivers.
- A driver is never assigned to two trips.
- Simulation of a city with 10,000 drivers runs in real time on a laptop.

The architecture



- **DispatchService** — orchestrates request → candidates → offers → assignment.
- **LocationIndex / GridIndex** — maps cells to sets of driver ids; nearby queries search the rider's cell and expanding rings of neighbours.
- **DriverRegistry** — driver status (offline, available, offered, on trip) with atomic reserve.
- **MatchingStrategy** — ranks candidates (nearest estimated time of arrival, ratings, fairness).
- **OfferManager** — sends offers and schedules timeouts.
- **Trip** — state machine for the trip.
- **SurgeCalculator** — supply/demand per cell.

Data model



Type	Notes
`GeoPoint`	record (lat, lon) with haversine distance
`CellId`	record from a fixed grid (or an H3 index)
`DriverStatus`	enum `OFFLINE`, `AVAILABLE`, `OFFERED`, `ON_TRIP`
`Offer`	id, trip, driver, expires at

Tech stack

Component	Choice	Why
Spatial index	square grid, then H3 Java binding as stretch	simple first, real later
Driver status	`ConcurrentHashMap` + atomic `compute`	single assignment guarantee
Offers/timeouts	`ScheduledExecutorService`	timed transitions
Simulation	virtual thread per simulated driver	realistic concurrency
Tests	JUnit 6, AssertJ, test clock, seeded simulation	reproducible scenarios

Milestones

1. **Spatial index.** *Done when:* nearby queries match a brute-force scan on 100,000 random drivers, and are at least 50x faster.
2. **Driver registry.** *Done when:* 1,000 concurrent reservation attempts on one driver yield exactly one success.
3. **Offer flow.** *Done when:* a scripted scenario of decline, timeout, accept assigns the third driver and releases the first two.
4. **Trip lifecycle and fare.** *Done when:* a completed trip produces the correct fare with surge applied.
5. **City simulation.** *Done when:* 10,000 simulated drivers and a stream of requests run for 10 minutes with metrics (match rate, average pickup time) and no double assignment.

Deep dive: the hard parts

Spatial bucketing. Divide the map into cells of roughly the search radius. A driver's location update removes it from its old cell's set and adds it to the new one (only when the cell changes). A nearby query checks the rider's cell and its 8 neighbours, computes exact distances and keeps the K best with a bounded priority queue; if fewer than K are found, expand to the next ring. Hexagonal cells (H3) have equal-distance neighbours, which avoids the square grid's diagonal distortion.

Exactly one trip per driver. Between finding candidates and offering, a driver may be taken by another request. Reserve before offering: `compute(driverId, (id, s) -> s == AVAILABLE ? OFFERED : s)` and check the result. On decline or timeout, CAS back from `OFFERED` to `AVAILABLE` — but only if the offer is still this one (track offer id), or a late timeout might free a driver who has since accepted another trip.

Timeouts racing responses. A driver accepts at 14.99 seconds while the timeout fires at 15.00. Both go through the trip's state machine under the trip's lock: the first transition wins; the second sees the trip already moved and becomes a no-op. Same principle as projects 20 and 24.

Testing strategy

Index correctness against brute force. Concurrency tests for reservation. Scenario tests with a manual scheduler for offers. A seeded simulation as an integration test with assertions on invariants (no driver in two active trips; every request ends in a terminal state).

Trade-offs, scaling and failure modes

Offering to one driver at a time is fair but slow in busy areas; broadcasting to several and taking the first acceptance is fast but wastes drivers' attention. Greedy nearest matching is simple; batch matching (collect requests for a second, then solve an assignment problem, e.g. with the Hungarian algorithm) improves overall pickup times. Stale locations (a driver's phone loses signal) must expire — drop drivers whose last update is older than 30 seconds from the index.

Stretch goals

- Batch matching every 2 seconds with an assignment solver.
- Ride pooling: match a second rider going the same way.
- Replace the square grid with H3 cells and compare query cost.

Skills practised

- Ch 20 — Components: the Uber case.
- Ch 11 — Behavioral patterns 2: State, Strategy.
- Ch 12 — Concurrency concepts: atomic compute, scheduled tasks.

In the interview

30-second answer: I built the dispatch core of a ride-hailing app: drivers are bucketed into grid cells so a nearby query checks the rider's cell and neighbours, ranks by exact distance with a bounded priority queue, and expands rings if too few are found. Before sending an offer, a driver is atomically moved from `AVAILABLE` to `OFFERED` in a `ConcurrentHashMap`, tied to an offer id, so a driver can never be on two trips and a late timeout cannot free a driver who has since accepted something else. Timeouts and driver responses both go through the trip state machine, so the first wins. Nearby queries matched brute force on 100,000 drivers and were well over 50 times faster.

Key terms to know:

- **Spatial index (grid / H3)** — bucketing locations into cells so nearby search checks a few cells, not every driver.
- **Ring expansion** — searching neighbouring cells outward until enough candidates are found.
- **Haversine distance** — great-circle distance between two latitude/longitude points.
- **K-nearest with a bounded heap** — keep only the K best candidates in a priority queue.
- **Atomic reservation** — compare-and-set of driver status before offering.
- **Offer id** — identifies which offer may release or confirm a driver, preventing stale timeouts.
- **Trip state machine** — requested, assigned, arriving, in progress, completed or cancelled.
- **Surge multiplier** — price factor per cell from open requests versus available drivers.
- **Batch matching / Hungarian algorithm** — solving many rider-driver pairs together to minimise total pickup time.

Q: How do you find nearby drivers quickly?

A: Bucket drivers by grid or hex cell; search the rider's cell and its 8 neighbours, rank by exact distance, and expand rings if fewer than K are found. A location update only touches the index when the driver changes cell, so updates stay well under a millisecond.

Q: How do you avoid assigning a driver twice?

A: Atomically move the driver from available to offered before sending an offer; only that offer can move them to on-trip or back to available. Two requests racing for one driver both try the compare-and-set and exactly one succeeds.

Q: One driver at a time or broadcast?

A: Sequential offers are fair and simple; broadcast is faster but wastes drivers' attention when most of them lose. Many systems batch requests for a second or two and solve a global assignment instead.

Q: Why does releasing a driver need the offer id?

A: Suppose an offer times out, the driver is released, gets a new offer and accepts it, and then a delayed decline from the first offer arrives. Without the id it would set the driver back to available while they are on a trip. Releasing "only if still OFFERED for offer 17" makes stale events harmless.

Q: Code-level: what does the reservation look like?

A: A conditional update inside `compute`, then a check of the result.

```
record Status(DriverStatus s, String offerId) {}
Status after = drivers.compute(driverId, (id, cur) ->
        cur.s() == AVAILABLE ? new Status(OFFERED, offerId) : cur);
boolean reserved = offerId.equals(after.offerId());
```

Q: Why hexagons (H3) instead of squares?

A: In a square grid, diagonal neighbours are further away than side neighbours, which skews "nearby". All six neighbours of a hexagon are the same distance from the centre, so rings are more uniform; the cost is a more complex library.

Q: What happens when a driver's phone loses signal?

A: Their location goes stale and they might be offered trips they cannot take. Store the last update time and drop drivers from the index if it is older than about 30 seconds; an offer to an unreachable driver simply times out and moves to the next candidate.

Q: What changes at 10x drivers or many cities?

A: Location updates dominate traffic, so partition the index by city or region, each on its own node, and keep updates in memory. Greedy nearest matching starts to give poor global pickup times in dense areas, which is where batch matching pays off.

Q: How do you test it?

A: Index results against a brute-force scan on random drivers, 1,000 concurrent reservations on one driver yielding exactly one success, scripted decline-timeout-accept scenarios on a manual scheduler, and a seeded city simulation asserting that no driver is ever on two active trips.

Common mistakes in answers:

- Scanning every driver per request.
- Checking availability and then offering in two non-atomic steps.
- Letting a timeout set the driver available without checking which offer it belongs to.

TL;DR

A cell-based spatial index, atomic driver reservation tied to offer ids, a trip state machine that absorbs timeout races, and pluggable matching strategies.

30. Chess with Undo and Replay

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 10, Ch 11, Ch 17

What it is

A complete chess engine core: full legal move generation (including castling, en passant and promotion), check, checkmate and stalemate detection, draw rules, unlimited undo/redo, saving and loading games in standard notations (FEN for positions, PGN for games), and a pluggable player interface for humans and a simple AI.

The problem it solves

Chess rules are full of special cases that break naive designs: a move may be illegal only because it exposes your own king; castling depends on history (has the king moved?); en passant depends on the previous move. Undo must restore all of that history exactly. The project teaches modelling complex rules cleanly, the **Command** and **Memento** patterns for undo, and rigorous testing against known reference results.

Real-world examples

- Forsyth–Edwards Notation (FEN) describes a full position (pieces, side to move, castling rights, en passant square, move clocks) in one line — the exact state your board must capture.
- Portable Game Notation (PGN) is the standard text format for recording games.
- Lichess's open-source rules library scalachess is a production example of a complete, tested chess rules implementation.

Requirements


Functional

- Board setup from the initial position or any FEN; export FEN.
- Legal move generation for all pieces with castling, en passant, promotion.
- Game end: checkmate, stalemate, threefold repetition, fifty-move rule, insufficient material.
- Undo and redo any number of moves; replay a game move by move.
- PGN export and import (standard algebraic notation such as `Nf3`, `exd5`, `O-O`, `e8=Q+`).
- Players: human via console, random AI, simple minimax AI with material evaluation.
- Clocks (optional): time per side.

Non-functional

- Move generation verified by **perft** (counting all positions at a given depth) against published reference counts.
- Generating legal moves for one position in under 50 microseconds.
- Undo restores the exact previous state, including castling rights and en passant.

The architecture



- **Game** — history of (move, undo info) pairs, redo stack, result, repetition counts.
- **Board** — the full position state with `make` and `unmake` operations.
- **MoveGenerator** — generates pseudo-legal moves per piece, then filters out those leaving the king in check.
- **Move / UndoInfo** — the Command (what to do) and the Memento-like record of what it destroyed.
- **EndConditionChecker** — checkmate, stalemate, repetition, fifty-move, material.
- **Notation codecs** — FEN and PGN conversion.
- **Player** — strategy interface for move choice.

Data model

Type	Notes
`Piece`	enum of 12 coloured pieces, or record (type, colour)
Board squares	`Piece[64]` (0 = a1), simple and fast enough
`CastlingRights`	4 bits: white/black king/queen side
`Move`	compact `int` or record: from, to, promotion, flags (capture, castle, en passant, double push)
Position hash	Zobrist hash (`long`) for repetition detection

Tech stack

Component	Choice	Why
Board	0..63 array with direction offsets	easy to reason about
Hashing	Zobrist hashing	O(1) incremental position hash
Verification	perft against known counts	finds rule bugs
Tests	JUnit 6, AssertJ, FEN-driven parameterised tests	position-based tests

Milestones

1. **Board and FEN.** *Done when:* FEN round-trips (parse then print) for 20 varied positions.
2. **Pseudo-legal moves.** *Done when:* each piece's moves are correct in hand-built positions.
3. **Legal filtering + make/unmake.** *Done when:* perft from the start position matches reference counts to depth 4, and make followed by unmake leaves the board identical (equals and hash).
4. **Special rules and endings.** *Done when:* perft passes on a well-known tricky test position covering castling, en passant and promotion, and end conditions are detected.
5. **Undo/redo, PGN, players.** *Done when:* importing a PGN game, undoing to move 10 and replaying gives the same final FEN; minimax beats the random player consistently.

Deep dive: the hard parts

Legal versus pseudo-legal. Generating only strictly legal moves directly is complex. The common approach: generate pseudo-legal moves (ignoring self-check), then for each, make the move, test whether your king is attacked, and unmake. "Is square attacked" is computed by looking outward from the king: knight jumps, sliding rays, pawn diagonals.

Make/unmake instead of copying. Copying the board for every candidate move is simple but slow for search. `make` returns an `UndoInfo` with exactly what is not recoverable from the move itself — captured piece, previous castling rights, previous en passant square, previous halfmove clock and previous hash. `unmake` restores those. Your undo/redo feature is then just a stack of (move, undo info) pairs: the Command pattern with a Memento for the lost state.

Perft as the test oracle. Perft counts leaf nodes of the move tree to a given depth. Published counts for the starting position and special test positions are known exactly; any rule bug changes the count. When counts differ, "divide" (perft per root move) narrows down which move is wrong.

Repetition. Threefold repetition needs position identity, including side to move, castling rights and en passant possibility. A Zobrist hash (XOR of random numbers per piece-square and state) is updated incrementally in make/unmake and stored in history; count occurrences of the current hash.

Testing strategy

Perft as the main correctness test. FEN-driven parameterised tests for special moves and end conditions. Property test: for random legal move sequences, make then unmake restores the exact board and hash. PGN round-trip tests on sample games.

Trade-offs, scaling and failure modes

A 64-square array is easy; bitboards (one `long` per piece type) are much faster for move generation but harder to read — a good stretch. Object-heavy moves (records) are clean but create garbage in AI search; an `int` encoding is faster. Standard algebraic notation needs disambiguation (`Nbd2`); generate legal moves first, then choose the shortest unambiguous string.

Stretch goals

- Bitboard move generation and a speed comparison.
- Alpha-beta search with iterative deepening and a transposition table keyed by Zobrist hash.
- Play over the UCI protocol so chess GUIs can use your engine.

Skills practised

- Ch 17 — Games: the chess case.
- Ch 10 — Behavioral patterns 1: Command and Memento.
- Ch 11 — Behavioral patterns 2: Strategy for players.

In the interview

30-second answer: I built a full chess rules engine with castling, en passant, promotion, all draw rules, FEN and PGN, and unlimited undo/redo. Moves are generated pseudo-legally and filtered by making each move, checking whether my king is attacked, and unmaking, so `make` returns an `UndoInfo` holding exactly what the move destroyed (captured piece, castling rights, en passant square, halfmove clock, hash). Undo/redo is then a stack of (move, undo info), which is Command plus Memento. Correctness is proven by perft: my node counts match the published reference values, for example 197,281 positions at depth 4 from the start.

Key terms to know:

- **Pseudo-legal vs legal move** — follows piece movement rules versus also not leaving your own king in check.
- **Make / unmake** — apply and exactly reverse a move in place instead of copying the board.
- **Command pattern** — a `Move` object that can be applied and undone.
- **Memento** — `UndoInfo`, a snapshot of the state a move overwrote.
- **Perft** — counting all leaf positions to a fixed depth and comparing with known values.
- **FEN / PGN** — one-line position notation, and the text format for whole games.
- **Zobrist hashing** — XOR of random numbers per piece-square and state, updated incrementally in O(1).
- **Threefold repetition** — a draw when the same position, including side to move and rights, occurs three times.
- **Square attacked test** — look outward from the king for knights, sliders and pawns.

Q: How do you check that a move does not leave the king in check?

A: Make it, test whether the king's square is attacked by the opponent, then unmake. Pseudo-legal moves that fail are discarded. The attack test looks outward from the king along knight jumps, sliding rays and pawn diagonals.

Q: How does undo restore castling rights and en passant?

A: Each made move returns undo info holding the state it overwrote: captured piece, previous castling rights, en passant square, halfmove clock and hash. Unmake restores it exactly, which a property test checks by comparing board and hash after make then unmake.

Q: How do you know your move generator is correct?

A: Perft counts against published reference values for several test positions, such as 20, 400, 8,902 and 197,281 from the start position at depths 1 to 4. When a count is wrong, "divide" prints perft per root move so you can find the faulty branch.

Q: Why make/unmake instead of copying the board?

A: Copying is simple but allocates a new board for every candidate move, which is slow and creates garbage during search. Make/unmake changes a few squares in place and reverses them, and the same mechanism powers undo/redo.

Q: Why is the position hash part of undo info?

A: The Zobrist hash is updated incrementally by XOR. Restoring it from undo info is cheaper and safer than recomputing it, and the hash history is what threefold repetition counts.

Q: Code-level: what does a compact undo record look like?

A: A small record that captures only what the move cannot reconstruct.

```
record UndoInfo(Piece captured, int castlingRights, int epSquare,
                int halfmoveClock, long zobrist) {}
UndoInfo u = board.make(move);
boolean legal = !board.isAttacked(board.kingSquare(mover), mover.opponent());
board.unmake(move, u);
```

Q: What are the tricky rules that break naive designs?

A: Castling needs history (has the king or rook moved?) and cannot pass through attacked squares; en passant is only legal on the move right after a double pawn push and can itself expose the king; promotion creates four possible moves. All three show up in perft test positions.

Q: What would you change for a faster engine or AI?

A: Bitboards (one `long` per piece type) make move generation far faster at the cost of readability, and encoding moves as `int` instead of records cuts garbage in search. For the AI, alpha-beta with iterative deepening and a transposition table keyed by the Zobrist hash.

Q: How do you produce correct algebraic notation like `Nbd2`?

A: Generate all legal moves first, then find other pieces of the same type that can reach the same square and add the file, rank or both only when needed to disambiguate. Check and mate suffixes come from making the move and testing the opponent's position.

Common mistakes in answers:

- Checking only that pieces move correctly, forgetting moves that expose your own king.
- An undo that forgets castling rights, en passant or the halfmove clock.
- Testing with a few hand-picked games instead of perft.

TL;DR

A position with make/unmake and undo info, pseudo-legal generation filtered by king safety, perft as the oracle, and a history stack that gives unlimited undo for free.

31. Rules Engine

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 9, Ch 10, Ch 11

What it is

A small business-rules engine: rules like "IF customer.tier == GOLD AND order.total > 100 THEN discount 10%" are written in a tiny text language (or JSON), parsed into an expression tree, validated, and evaluated against **facts** (the input data). It supports priorities, conflict resolution, chaining (one rule's action creates a fact that triggers another) and an explanation of why each rule fired.

The problem it solves

Business people change rules — discounts, fraud checks, eligibility — far more often than developers can redeploy code. Hard-coded `if` chains become unreadable and unauditable. A rules engine moves rules into data, and the design problem is building a safe, fast, explainable interpreter: the **Interpreter** and **Composite** patterns for expressions, **Specification** for reusable conditions, **Command** for actions and a **Visitor** for validation and pretty-printing.

Real-world examples

- Drools is a mature open-source Java rules engine with its own rule language and forward chaining, historically built on the Rete algorithm, which avoids re-checking all rules when a single fact changes.
- Easy Rules is a lightweight Java rules library built on the same Rule / Facts / RulesEngine concepts you build here; its README notes it has been in maintenance mode since December 2020.

Requirements


Functional

- Rule syntax: `rule "gold discount" priority 10 when customer.tier == "GOLD" and order.total > 100 then set order.discount = 0.10`.
- Expressions: comparisons, `and` / `or` / `not`, arithmetic, `in [..]`, string functions, field paths into nested facts (maps or records).
- Actions: set a field, add a fact, emit an event, stop processing.
- Engine modes: first-match, all-matches (by priority), and forward chaining until no new facts (with a cycle limit).
- Validation at load time: unknown fields, type mismatches (number compared with string), unreachable rules.
- Explanation: for each evaluation, which rules fired and the values of each condition.

Non-functional

- Evaluate 1,000 rules against one fact set in under 1 ms (single-match mode, compiled trees).
- Rules hot-reloadable without dropping in-flight evaluations.
- A buggy rule cannot loop forever or crash the engine.

The architecture



- **RuleParser** — tokenizer plus recursive-descent parser producing rules and expression trees.
- **Rule** — name, priority, condition tree, list of actions.
- **Expr** — Interpreter/Composite nodes; `eval` records intermediate values into a `Trace` for explanations.
- **ExprVisitor** — the Visitor pattern: type checking, pretty printing, field-dependency extraction, all without changing node classes.
- **Action** — Command objects applied to facts.
- **Agenda** — the list of rules whose conditions are true, ordered for firing (conflict resolution).
- **RuleEngine** — runs the match–resolve–act cycle.

Data model

Type	Notes
`Value`	sealed: `Num(BigDecimal)`, `Str`, `Bool`, `ListVal`, `Null`
`Facts`	map of name to fact object; field paths resolved by reflection over records or nested maps
`RuleSet`	immutable list of rules + version; swapped atomically on reload
`EvaluationResult`	fired rules in order, changed facts, emitted events, trace

Tech stack

Component	Choice	Why
Parsing	hand-written tokenizer + recursive descent	full control of errors
Nodes	sealed interfaces + records	exhaustive pattern matching
Reload	`AtomicReference<RuleSet>`	in-flight evaluations keep old set
Benchmarks	JMH	1,000-rule evaluation
Tests	JUnit 6, AssertJ, golden explanation files	readable rule tests

Milestones

1. **Expressions.** *Done when:* `1 + 2 * 3 > 6 and not false` evaluates to true and precedence tests pass.
2. **Rules and facts.** *Done when:* the gold-discount rule fires for a gold customer with total 150 and not for total 50, with nested field paths.
3. **Validation visitor.** *Done when:* `order.total > "abc"` and `customr.tier` (typo) are rejected at load time with line and column.
4. **Engine modes and chaining.** *Done when:* forward chaining derives facts across three rules and a self-triggering rule is stopped by the cycle limit with a clear error.
5. **Explanations, reload, performance.** *Done when:* each result explains fired rules with condition values, reload swaps rules atomically under load, and JMH meets the 1 ms target.

Deep dive: the hard parts

Evaluation that explains itself. A rule that did not fire should say why: "order.total > 100 was false (total = 80)". Pass a `Trace` into `eval`; each node records its value. The same tree serves evaluation and explanation, and the visitor can pretty-print the condition next to its values.

Conflict resolution and chaining. When several rules match, order them by priority, then by specificity or rule order (be explicit). In forward chaining, firing an action can make other conditions true or false, so after each firing you re-evaluate affected rules. Naively re-evaluating all rules each cycle is O(rules × cycles). A dependency index (field → rules that read it, built by a visitor) re-checks only rules touching changed fields — a small step toward what Rete does more thoroughly.

Termination. A rule like "when x > 0 then set x = x + 1" loops forever under chaining. Defences: a cycle limit, refusing to re-fire a rule for the same unchanged facts ("refraction"), and a load-time warning when a rule writes a field it reads.

Safety. Rules come from non-programmers; never evaluate them as Java code or scripts with full access. Your interpreter only knows the operations you implement, so it is sandboxed by construction. Add timeouts and limits on list sizes.

Testing strategy

Expression tests from a table of strings and expected values. Parser error tests with positions. Golden-file tests for explanations. Property test: pretty-print then re-parse yields an equal tree. JMH for evaluation speed. A concurrency test reloading rules while 16 threads evaluate.

Trade-offs, scaling and failure modes

A custom language is easy for business users but needs tooling (error messages, editors); JSON rules are easier to generate but harder to read. Interpreting trees is fast enough for most needs; compiling to bytecode or lambdas is faster but harder to explain. Rules hide logic from code review — require versioning, tests per rule and an audit of who changed what.

Stretch goals

- Decision tables (a grid of conditions and outcomes) compiled to rules.
- Compile expression trees into nested Java lambdas and compare speed.
- A Rete-style network that shares common condition nodes across rules.

Skills practised

- Ch 10 — Behavioral patterns 1: Interpreter and Command.
- Ch 11 — Behavioral patterns 2: Visitor and Specification.
- Ch 9 — Structural patterns: Composite.

In the interview

30-second answer: I built a small business-rules engine: rules written in a tiny text language are parsed by a recursive-descent parser into expression trees (Interpreter plus Composite), validated at load time by Visitors for unknown fields and type mismatches, and evaluated against facts. The engine runs a match, resolve, act cycle with priority-based conflict resolution and optional forward chaining, guarded by a cycle limit and refraction so a buggy rule cannot loop forever. Every evaluation records a trace, so each result explains which rules fired and why others did not ("order.total > 100 was false, total = 80"). Rule sets are immutable and swapped through an `AtomicReference`, so hot reload never disturbs in-flight evaluations, and 1,000 rules evaluate in under 1 ms.

Key terms to know:

- **Facts** — the input data rules are evaluated against, such as customer and order.
- **Interpreter pattern** — each grammar construct is a class that evaluates itself.
- **Visitor pattern** — new operations (type check, pretty-print, dependency extraction) over a fixed set of node classes.
- **Specification pattern** — reusable, combinable conditions.
- **Agenda / conflict resolution** — the ordered list of matching rules and the rule for which fires first.
- **Forward chaining** — firing a rule adds or changes facts, which may make other rules match.
- **Refraction** — a rule does not fire again for the same unchanged facts.
- **Rete algorithm** — Drools' classic network that shares condition checks and re-evaluates only what a fact change affects.
- **Sandboxing by construction** — the interpreter can only do the operations you implemented.

Q: How would you let business users change discount rules without redeploying?

A: Store rules as data in a small, sandboxed language; parse them into expression trees, validate at load, and swap the rule set atomically. A rule change is then a reviewed, versioned data change with its own tests, not a code release.

Q: Why a Visitor here?

A: Several operations (type checking, printing, dependency extraction) walk the same tree. A visitor adds operations without editing node classes, which suits a stable node set with growing operations. With Java's sealed interfaces, a pattern-matching `switch` over node types is a lighter alternative that the compiler checks for completeness.

Q: How do you stop rules looping?

A: Cycle limits, refraction (do not re-fire on the same facts) and load-time detection of rules that write a field they read. A self-triggering rule like "when x > 0 then set x = x + 1" is stopped by

the limit with a clear error naming the rule.

Q: Why not just evaluate rules as Java or JavaScript with a script engine?

A: Rules come from non-programmers, and a general scripting engine can call any code, read files or loop forever. A custom interpreter only knows the operations you implemented, so it is safe by construction, and its errors can point at the rule's line and column.

Q: How does forward chaining stay efficient?

A: Naively re-evaluating every rule after each firing costs O(rules x cycles). A visitor extracts which fields each rule reads, building an index from field to rules, so after an action only rules reading the changed fields are re-checked. Rete goes further by sharing common conditions between rules.

Q: Code-level: how does hot reload work without locks?

A: Each evaluation reads the current immutable rule set once and uses it to the end.

```
private final AtomicReference<RuleSet> rules = new AtomicReference<>(RuleSet.EMPTY);
public EvaluationResult evaluate(Facts f) { return rules.get().evaluate(f); } // one snapshot
public void reload(String source) {
    RuleSet next = parser.parse(source);   // validate fully before publishing
    rules.set(next);                        // in-flight calls keep the old set
}
```

Q: What happens if a rule file has a typo or type error?

A: The validation visitor rejects `customr.tier` (unknown field) and `order.total > "abc"` (number versus string) at load time with line and column, and the old rule set stays active. Failing at load is far cheaper than failing on a customer's order.

Q: What changes at 10x rules or 10x traffic?

A: Tree interpretation stays fast, but 10,000 rules make "check every rule" costly, so index rules by the fields and constant values they test, or compile trees into nested lambdas. Traffic scales easily because evaluation is stateless over an immutable rule set, so threads share it freely.

Q: How do you test a rules engine?

A: Table tests from expression strings to expected values, parser error tests with positions, golden files for explanations, a property test that pretty-print then re-parse gives an equal tree, and a concurrency test that reloads rules while 16 threads evaluate.

Common mistakes in answers:

- Proposing `eval` of arbitrary scripts for rules written by business users.
- Forward chaining with no termination guard.
- Mutating the live rule list during reload instead of swapping an immutable set.

TL;DR

A parser to expression trees, an explaining interpreter, visitors for validation, a match–resolve–act cycle with termination guards and atomic hot reload.

32. Text Editor with Undo/Redo

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 9, Ch 10

What it is

The core engine of a text editor (no fancy UI required): an efficient text buffer that handles large files, cursor and selection, insert/delete/replace, find and replace, unlimited undo/redo with sensible grouping (typing a word is one undo step), and multiple cursors. A simple terminal or Swing view sits on top.

The problem it solves

Storing a document as one `String` makes every keystroke copy the whole file — fine for a tweet, unusable for a 50 MB log. Undo is equally tricky: undoing per character is annoying, and undo must restore the cursor too. The project teaches buffer data structures (gap buffer, piece table, rope), the **Command** pattern with merging, and **Memento** for cursor state.

Real-world examples

- The VS Code team's blog post on its text buffer reimplementation explains why they replaced an array of lines with a *piece tree* (a piece table stored in a balanced tree) to cut memory use and speed up opening large files.
- The piece table and gap buffer are the two classic editor buffer structures you will compare.

Requirements


Functional

- Open, edit and save files; insert, delete, replace at positions; line/column to offset conversion.
- Cursor movement (char, word, line), selection, copy/cut/paste.
- Undo/redo, unlimited, with grouping: consecutive typed characters merge until a pause, cursor jump or space.
- Find (plain and regex) and replace all as one undoable step.
- Multiple cursors applying the same edit.
- Change listeners for views (Observer).

Non-functional

- Open a 100 MB file in under 1 second (no full copy into a `String`).
- Insert/delete in O(log n) or amortised O(1) near the cursor.
- Memory overhead under 2x file size for typical editing sessions.

The architecture



- **Document** — the facade combining buffer, line index, cursors, undo and listeners.
- **TextBuffer** — Strategy for storage; implement both a gap buffer and a piece table.
- **LineIndex** — line-start offsets for line/column mapping, updated incrementally.
- **EditCommand** — Command with `execute`, `undo` and `mergeWith` for grouping; `CompositeEdit` (Composite) for replace-all and multi-cursor edits.
- **UndoManager** — two stacks; a new edit clears redo.
- **CursorSet / CursorMemento** — cursor positions captured with each command so undo restores them.

Data model

Type	Notes
`Piece`	record (source `ORIGINAL` or `ADDED`, start, length)
`Cursor`	position + selection anchor
`EditRecord`	offset, removed text, inserted text, cursor before, cursor after
`DocumentEvent`	offset, removed length, inserted length — for views and line index

Tech stack

Component	Choice	Why
Buffers	piece table and gap buffer	compare trade-offs
Large files	`FileChannel` memory-map for original	open without copying
View	terminal (JLine, current version) or Swing	keep UI thin
Benchmarks	JMH on edit patterns	measure structures
Tests	JUnit 6, AssertJ, jqwik model tests	compare with `StringBuilder`

Milestones

1. **Gap buffer.** *Done when:* a model-based test of random inserts/deletes agrees with a `StringBuilder` for 100,000 operations.
2. **Piece table.** *Done when:* the same model test passes, and opening a 100 MB file takes under 1 second.
3. **Line index and cursors.** *Done when:* line/column ↔ offset conversion is correct after random edits, including at line ends.
4. **Undo/redo with grouping.** *Done when:* typing "hello world" then undo removes "world" then "hello " (or your documented grouping), restoring the cursor each time.
5. **Find/replace and multi-cursor.** *Done when:* replace-all of 1,000 matches is one undo step, and multi-cursor typing inserts at all cursors with correct offsets.

Deep dive: the hard parts

Piece table. The original file is read-only; everything typed is appended to an "added" buffer. The document is a list of pieces pointing into either buffer. Inserting splits one piece into up to three; deleting trims or removes pieces. Nothing is ever copied, which makes undo cheap and large files fast. A plain list of pieces makes finding the piece for an offset O(pieces); a balanced tree keyed by cumulative length (VS Code's piece tree) makes it O(log n).

Gap buffer. An array with a gap at the cursor; typing fills the gap in O(1), moving the cursor moves the gap by copying the characters between. Excellent for local edits, poor for jumping around a huge file.

Undo grouping. `InsertCommand.mergeWith(next)` returns true if next is an insert immediately after this one, typed within a short time, and not crossing a word boundary; then it absorbs the text. This keeps the undo stack meaningful. Every command stores cursor state before and after (Memento) so undo puts the cursor where the user expects.

Multi-cursor offsets. Applying the same insertion at several cursors shifts the offsets of later cursors. Apply edits from the last cursor to the first (descending offset) so earlier edits do not invalidate later positions, and wrap them in one `CompositeEdit`.

Testing strategy

Model-based tests against a `StringBuilder` for every buffer. Undo property: after any sequence of edits, undoing all returns the original text and cursor; redoing all returns the final text. Line index tests with mixed `\n` and `\r\n`. JMH benchmarks for typing, random jumps and large paste.

Trade-offs, scaling and failure modes

Gap buffers are simplest and fastest for typing; piece tables shine for large files and cheap undo; ropes (balanced trees of strings) suit very large documents and concurrent editing. Memory-mapping the original file means another program changing it underneath corrupts your view — detect changes by timestamp. Unicode: Java `char` is a UTF-16 unit; cursor movement must skip surrogate pairs and ideally grapheme clusters.

Stretch goals

- Syntax highlighting with incremental re-tokenising of changed lines.
- Persistent undo history saved with the file.
- Collaborative editing with operational transformation between two documents.

Skills practised

- Ch 10 — Behavioral patterns 1: Command and Memento.
- Ch 9 — Structural patterns: Composite and Facade.
- Ch 11 — Behavioral patterns 2: Observer and Strategy.

In the interview

30-second answer: I built a text-editor engine with a swappable buffer, a gap buffer and a piece table, behind a `TextBuffer` strategy, so a 100 MB file opens in under a second without copying it into a `String`. Edits are Command objects with `execute`, `undo` and `mergeWith`, so typing a word becomes one undo step, and each command stores cursor positions before and after (a Memento) so undo puts the cursor back. Replace-all and multi-cursor edits are one `CompositeEdit`, applied from the last cursor to the first so earlier edits do not shift later offsets. Every buffer passed a model-based test against `StringBuilder` for 100,000 random edits.

Key terms to know:

- **Gap buffer** — an array with an empty gap at the cursor; typing fills the gap in O(1).
- **Piece table** — read-only original plus an append-only "added" buffer, with a list of pieces describing the document.
- **Piece tree / rope** — balanced trees that make finding an offset O(log n) in large documents.
- **Command pattern with merging** — edits that can absorb the next edit to form one undo step.
- **Memento** — cursor and selection state saved with each command.
- **Composite edit** — several edits grouped as one undoable command.
- **Line index** — line-start offsets for line/column to offset conversion, updated incrementally.
- **Observer** — views subscribe to document change events.
- **UTF-16 surrogate pair** — two Java `char`s for one character outside the Basic Multilingual Plane, such as most emoji.

Q: Why not store the document as a `String`?

A: Strings are immutable, so every edit would copy the whole text: fine for a tweet, unusable for a 50 MB log. A gap buffer, piece table or rope makes edits local.

Q: How do you group typing into one undo step?

A: A command can merge with the next one when it is a continuation: an adjacent insert, within a short pause, not crossing a word boundary or cursor jump. The merged command absorbs the text, so one undo removes the whole word.

Q: How does a piece table support undo cheaply?

A: Buffers are append-only; an edit only changes the piece list, so undo restores the previous piece arrangement without copying text. The original file is never modified and typed text is never deleted from the added buffer.

Q: Gap buffer or piece table: which and why?

A: A gap buffer is simplest and fastest for typing in one place, but jumping to the other end of a huge file moves the gap by copying everything in between. A piece table opens large files instantly (the original can be memory-mapped) and makes undo cheap, at the cost of more complex offset lookup. That is why VS Code moved to a piece tree.

Q: How do multi-cursor edits avoid corrupting offsets?

A: Inserting at an earlier cursor shifts every later offset. Apply the edits in descending offset order so earlier edits never invalidate later positions, and wrap them in one `CompositeEdit` so undo reverts them together.

Q: Code-level: what is the Unicode gotcha when moving the cursor?

A: A Java `char` is one UTF-16 unit, so an emoji is two `char`s and moving by one would split it.

```
int next = Character.offsetByCodePoints(text, cursor, 1);   // skips a whole code point
// String.length() counts UTF-16 units: "\uD83D\uDE00".length() == 2 (one emoji)
```

Even code points are not enough for combined characters such as flags or accented letters; `java.text.BreakIterator.getCharacterInstance()` finds grapheme boundaries.

Q: What happens if another program changes the file while it is open?

A: If the original is memory-mapped, the view can change or become invalid underneath you. Record the file's modification time and size at open, check before saving, and warn the user or reload.

Q: What changes for a 1 GB file or collaborative editing?

A: A flat list of pieces becomes O(pieces) per lookup, so use a balanced tree keyed by cumulative length, and the line index must also be a tree. Collaborative editing needs operational transformation or CRDTs so concurrent edits from two users converge.

Q: How do you prove the buffers are correct?

A: Model-based tests: apply the same random inserts and deletes to the buffer and a `StringBuilder` and compare after each step. An undo property checks that undoing everything returns the original text and cursor, and redoing everything returns the final text.

Common mistakes in answers:

- One undo step per keystroke, or undo that does not restore the cursor.
- Applying multi-cursor edits in ascending order.
- Treating `char` as a character and splitting emoji.

TL;DR

A swappable buffer (gap buffer or piece table), an incremental line index, mergeable edit commands with cursor mementos, and composite edits for replace-all and multi-cursor.

33. Durable Job Queue

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 12, Ch 13, Ch 20

What it is

A background-job system backed by PostgreSQL: application code enqueues jobs ("send this email", "resize this image"); several worker processes claim jobs, run them, and mark them done; failed jobs are retried with backoff; jobs can be scheduled for later, de-duplicated, and limited per queue. It is "distributed-ish": multiple JVMs share one database, which is the coordination point.

The problem it solves

Work that should not block a user request must run in the background — reliably, even if a worker crashes mid-job. In-memory queues lose jobs on restart. The design problems are: claiming a job so exactly one worker gets it, recovering jobs from dead workers (**leases**), retrying safely (**at-least-once** delivery plus idempotent handlers), and keeping the database from becoming a bottleneck.

Real-world examples

- PostgreSQL's `SELECT` documents `FOR UPDATE SKIP LOCKED`, which lets many workers claim different rows concurrently without blocking each other — the foundation of database-backed queues.
- Amazon SQS's visibility timeout hides a received message for a period; if it is not deleted in time it becomes visible again — the same lease idea you implement.

- JobRunr is an open-source Java library for background jobs persisted in a database, with retries and a dashboard.

Requirements


Functional

- `enqueue(queue, type, payload, options)` with options: run-at time, priority, max attempts, unique key.
- Workers poll queues, claim a batch, run handlers by job type, and complete or fail jobs.
- Leases: a claimed job is invisible for a lease period; workers heartbeat long jobs; expired leases make the job claimable again.
- Retries with exponential backoff and jitter; dead-letter after max attempts.
- Unique jobs: enqueue with a unique key is a no-op if an unfinished job has that key.
- Per-queue concurrency limits; pause/resume a queue; a small admin CLI to list, retry and cancel jobs.

Non-functional


- At-least-once execution: no job is lost if a worker crashes at any point.
- 1,000 jobs per second claim throughput on a single PostgreSQL instance (benchmark and report your number).
- Claim latency under 50 ms when jobs are waiting.

The architecture



- **JobClient** — the producer API, used inside the caller's own transaction when possible.
- **WorkerProcess** — runs pollers and executes jobs on virtual threads, limited per queue by a semaphore.
- **Poller** — claims batches; backs off when empty; can be woken by PostgreSQL `LISTEN/NOTIFY`.
- **JobRepository** — the persistence port; an in-memory version for fast tests, PostgreSQL for real.
- **HandlerRegistry / JobHandler** — maps job types to code.
- **RetryPolicy** — backoff schedule.
- **LeaseReaper** — returns jobs with expired leases to the queue (or claim queries include them directly).

Data model



Job status: `READY` → `RUNNING` → `DONE`, or `RUNNING` → `READY` (retry, with later `run_at`) → ... → `DEAD`. The unique key is enforced by a partial unique index on unfinished jobs.

Tech stack

Component	Choice	Why
Store	PostgreSQL (`FOR UPDATE SKIP LOCKED`, partial indexes)	durable, concurrent claims
Access	plain JDBC + a connection pool (project 38 or HikariCP)	see every query
Workers	virtual threads + `Semaphore` per queue	cheap concurrency, limits
Wake-up	`LISTEN/NOTIFY` (docs)	low latency without hot polling
Tests	JUnit 6, AssertJ, Testcontainers PostgreSQL	real database in tests

Milestones

1. **In-memory queue with the full interface.** *Done when:* enqueue, claim, complete, fail and retry pass a contract test suite.
2. **PostgreSQL repository.** *Done when:* the same contract suite passes against a Testcontainers database.

3. **Concurrent claiming.** *Done when:* 8 worker threads across 2 JVMs process 100,000 jobs with each job completed exactly once in the attempts table (no double claim without a crash).
4. **Leases and crash recovery.** *Done when:* killing a worker mid-job makes the job run again after the lease expires, and heartbeats keep a long job's lease alive.
5. **Uniqueness, limits, admin.** *Done when:* duplicate unique keys are ignored, per-queue concurrency is respected, and the CLI retries a dead job.

Deep dive: the hard parts

Claiming without contention. The claim is one statement: select up to N ready rows ordered by priority and `run_at`, `FOR UPDATE SKIP LOCKED`, and update them to `RUNNING` with `locked_by` and `lease_until`, returning the rows. `SKIP LOCKED` makes concurrent workers skip rows another transaction is claiming instead of waiting. An index on (queue, status, priority, run_at) keeps the selection cheap.

At-least-once is the honest guarantee. A worker can finish the work and crash before marking it done; after the lease expires, another worker runs it again. You cannot fix this inside the queue alone. Handlers must be idempotent: use the job id as an idempotency key for side effects (e.g. "email for job 123 already sent"). If the job's work is a database write in the same database, complete the job in the same transaction as the work — that gives effectively-once for that case.

Transactional enqueue. If the application saves an order and enqueues "send confirmation" in two separate steps, a crash between them loses or orphans the job. Because the queue is in the same PostgreSQL database, enqueue inside the application's transaction: both commit or neither does. This is the transactional outbox idea for free.

Table bloat. Constant updates and deletes create dead rows in PostgreSQL. Move finished jobs to an archive table or delete them in batches, keep the hot table small, and let autovacuum keep up.

Testing strategy

One contract test suite run against both repositories. Testcontainers for PostgreSQL. Crash tests: run a worker in a separate process (or thread you abruptly stop) and verify reclamation. Concurrency tests counting completions per job id. Load test reporting claim throughput and latency.

Trade-offs, scaling and failure modes

A database-backed queue is simple to operate and transactional with your data, but tops out well below dedicated brokers (Kafka, RabbitMQ, SQS); beyond that, use a broker plus an outbox table. Short leases recover faster from crashes but risk duplicate runs of slow jobs if heartbeats lag. Polling adds load; `LISTEN/NOTIFY` reduces it but notifications are not durable, so keep a slow poll as a fallback.

Stretch goals

- Cron-style recurring jobs with a single scheduler elected by an advisory lock.
- Job dependencies (run B after A completes).
- A web dashboard showing queue depth, throughput and failures.

Skills practised

- Ch 12 — Concurrency concepts: virtual threads, semaphores.
- Ch 13 — Concurrency problems: producer-consumer queues.
- Ch 20 — Components: notification and pub-sub designs that sit on queues.
- Ch 4 — SOLID principles: repository port with two adapters.

In the interview

30-second answer: I built a durable background job queue on PostgreSQL where several worker JVMs claim jobs with one `UPDATE ... SELECT ... FOR UPDATE SKIP LOCKED` statement, so each job goes to exactly one worker without workers blocking each other. A claim sets a lease; workers heartbeat long jobs, and if a worker dies its lease expires and the job becomes claimable again. That makes delivery at-least-once, so handlers are idempotent using the job id, and jobs can be enqueued inside the application's own transaction so a business write and its job commit together. A contract test suite runs against both the in-memory and PostgreSQL repositories, and I report claim throughput from a load test.

Key terms to know:

- **`FOR UPDATE SKIP LOCKED`** — lock selected rows and skip rows other transactions have locked, instead of waiting.
- **Lease (visibility timeout)** — a claimed job is hidden until a deadline; expiry makes it claimable again.
- **Heartbeat** — a worker periodically extends the lease of a long-running job.
- **At-least-once** — a job may run more than once after a crash but is never lost.
- **Idempotent handler** — running a job twice has the same effect as once, using the job id as a key.
- **Transactional enqueue / outbox** — inserting the job in the same transaction as the business data.
- **Partial unique index** — uniqueness only for unfinished jobs, enforcing unique keys.
- **`LISTEN/NOTIFY`** — PostgreSQL messages that wake idle workers without hot polling.
- **Table bloat** — dead row versions from updates and deletes that autovacuum must clean.

Q: How do multiple workers claim jobs without double-processing?

A: A single `UPDATE ... WHERE id IN (SELECT ... FOR UPDATE SKIP LOCKED LIMIT n)` marks claimed rows with a worker and a lease; other workers skip locked rows rather than waiting. An index on (queue, status, priority, run_at) keeps the inner select cheap.

Q: What if a worker dies mid-job?

A: Its lease expires and the job becomes claimable again. That is why delivery is at-least-once and handlers must be idempotent.

Q: How do you avoid losing a job enqueued alongside a business write?

A: Enqueue in the same database transaction as the business write, so both commit or neither does. Because the queue lives in the same PostgreSQL database, you get the transactional outbox for free.

Q: Code-level: what does the claim query look like?

A: One statement selects, locks and updates.

```
UPDATE job SET status = 'RUNNING', locked_by = ?, lease_until = now() + interval '30 seconds',
               attempts = attempts + 1
WHERE id IN (SELECT id FROM job
             WHERE queue = ? AND status = 'READY' AND run_at <= now()
             ORDER BY priority DESC, run_at LIMIT ? FOR UPDATE SKIP LOCKED)
RETURNING *;
```

Expired leases can be included by also matching `status = 'RUNNING' AND lease_until < now()`.

Q: Can you get exactly-once processing?

A: Not in general: a worker can finish the side effect and crash before marking the job done. If the job's work is a write to the same database, completing the job in the same transaction as that write gives effectively-once for that case. For external side effects, pass the job id as an idempotency key.

Q: How do you choose the lease length?

A: Short leases recover from crashes quickly but risk a second worker starting a slow job whose heartbeat lagged. Long leases avoid duplicates but delay recovery. A moderate lease plus heartbeats every third of the lease is the usual compromise.

Q: What breaks first at 10x jobs?

A: The database: constant updates create dead rows and index churn, and polling adds load. Archive or batch-delete finished jobs, keep the hot table small, use `LISTEN/NOTIFY` with a slow poll fallback (notifications are not durable), and beyond a few thousand jobs per second move to a dedicated broker fed by an outbox table.

Q: How do you test crash recovery?

A: Run a worker in a separate process or a thread you stop abruptly mid-job, then assert another worker picks the job up after the lease expires and the attempts table shows two attempts. A concurrency test with workers in two JVMs counts completions per job id and requires exactly one when nothing crashed.

Common mistakes in answers:

- `SELECT` then `UPDATE` in separate steps without locking, so two workers claim the same job.
- Promising exactly-once delivery for jobs with external side effects.
- Enqueuing after the business transaction commits, which loses jobs on a crash in between.

TL;DR

A PostgreSQL table claimed with `SKIP LOCKED`, leases with heartbeats for crash recovery, jittered retries, transactional enqueue and idempotent handlers for honest at-least-once processing.

34. Double-Entry Ledger

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 5, Ch 12, Ch 21

What it is

A ledger service that records money movements using **double-entry bookkeeping**: every transaction consists of entries that debit some accounts and credit others, and the debits always equal the credits. Balances are derived from entries, never edited directly. The service supports transfers with idempotency, holds (authorise now, capture later), reversals and point-in-time balances.

The problem it solves

Payment systems, wallets and marketplaces must be able to prove where every cent went. Mutable balance columns cannot: if a balance is wrong, there is no trail. Double entry makes errors visible (unbalanced transactions are rejected) and gives a complete audit history. The engineering challenges are concurrency (no overdrafts under parallel transfers), idempotent APIs, and fast balance reads without giving up the append-only log.

Real-world examples

- Double-entry bookkeeping is the centuries-old accounting principle the data model follows.

- Stripe's idempotency post explains why money-moving APIs need client-supplied keys to make retries safe.
- TigerBeetle is an open-source database built specifically for financial transactions, centred on accounts and transfers with debits and credits.

Requirements


Functional

- Accounts with type (asset, liability, revenue, expense), currency and a "may go negative" flag.
- `post(transaction)`: a set of entries (account, amount, debit or credit); rejected unless balanced per currency.
- Transfers between user accounts as balanced transactions; overdraft prevention.
- Holds: reserve funds (pending), later capture (all or part) or void.
- Reversals: a new transaction negating an earlier one (never delete).
- Balance now and at any past timestamp; account statement with pagination.
- Idempotency keys on every write.

Non-functional


- Invariant: sum of all debits equals sum of all credits, always.
- 2,000 transfers per second on one PostgreSQL instance (or in-memory equivalent) with no lost updates.
- Balance read under 5 ms using cached balances that always equal the sum of entries.

The architecture



- **LedgerService** — the API: validate, lock, append, update balances, record idempotency — in one database transaction.
- **TransactionValidator** — balanced per currency, accounts exist, currency matches, amounts positive.
- **AccountLocker** — locks involved accounts in sorted id order to prevent deadlock.
- **LedgerRepository** — append-only entries plus a balance table updated in the same transaction.
- **IdempotencyStore** — key → request fingerprint and stored response.
- **BalanceProjector** — recomputes balances from entries for audits and point-in-time queries.

Data model



Available balance = posted minus pending holds. Entries are insert-only; a database rule or permission revokes `UPDATE` and `DELETE` on `ENTRY`.

Tech stack

Component	Choice	Why
Store	PostgreSQL, `SELECT ... FOR UPDATE` on balance rows	strong consistency
Amounts	`bigint` minor units	exact, fast
Isolation	READ COMMITTED + explicit row locks	predictable locking
Tests	JUnit 6, AssertJ, Testcontainers, jqwik	invariants under load

Milestones

1. **In-memory ledger.** *Done when:* unbalanced transactions are rejected and balances equal the sum of entries after random postings (property test).
2. **Transfers and overdraft rules.** *Done when:* 100 threads doing random transfers never overdraw a non-negative account and total money is conserved.
3. **PostgreSQL implementation.** *Done when:* the same tests pass against Testcontainers, with accounts locked in id order and no deadlock errors under load.
4. **Idempotency and reversals.** *Done when:* replaying a request with the same key returns the original transaction id; replaying with the same key but a different body is rejected; a reversal restores balances.
5. **Holds and point-in-time.** *Done when:* hold, partial capture and void move pending and posted correctly, and balance-at-timestamp matches a recomputation.

Deep dive: the hard parts

Lock ordering and hot accounts. A transfer touches at least two balance rows. Lock them in a fixed order (sorted account id) with `SELECT ... FOR UPDATE` to prevent deadlocks. A hot account (the platform's fee account, credited by every transfer) serialises everything. Mitigations: split it

into N sub-accounts and pick one at random, or skip updating its cached balance synchronously and compute it from entries asynchronously, since it may go negative anyway.

Idempotency correctness. Insert the idempotency key in the *same* transaction as the entries. If two identical requests race, the unique constraint makes one fail; it then reads and returns the winner's stored result. Store a hash of the request body so a client reusing a key for a different request gets an error instead of a wrong answer.

Cached balances that are provably right. Reading balances by summing millions of entries is slow; caching them risks drift. Update the cache in the same transaction as the entries, include a version, and run a periodic reconciliation job that recomputes from entries and alerts on any difference. The ledger, not the cache, is the source of truth.

Testing strategy

Property tests on the in-memory implementation (random balanced postings, conservation, non-negativity). Concurrency stress against PostgreSQL in Testcontainers. Idempotency race tests with two threads and one key. Reconciliation test: corrupt a cached balance deliberately and assert the job detects it.

Trade-offs, scaling and failure modes

Strong consistency with row locks is simple and correct but limits throughput per hot account. Sharding accounts across databases makes cross-shard transfers distributed transactions (two-phase commit or sagas with pending states). Never "fix" a mistaken entry by editing it — post a correcting transaction; auditors depend on immutability. Currency conversion must be explicit entries through FX accounts, never silent.

Stretch goals

- Multi-currency transfers via FX accounts with a recorded rate.
- Daily balance snapshots to speed up point-in-time queries.
- A sharded design with a saga for cross-shard transfers.

Skills practised

- Ch 21 — Machine coding: the Ledger Co and wallet cases.
- Ch 12 — Concurrency concepts: lock ordering and deadlock avoidance.
- Ch 5 — Design principles: immutability, design by contract.

In the interview

30-second answer: I built a double-entry ledger where every transaction is a set of debit and credit entries that must balance per currency, entries are insert-only, and balances are derived. For speed I cache balances, but update them in the same database transaction as the entries and run a reconciliation job that recomputes from entries, so the ledger, not the cache, is the source of truth. Transfers lock the involved balance rows in sorted id order with `SELECT ... FOR UPDATE` to avoid deadlocks, and idempotency keys are stored in the same transaction with a hash of the request body. 100 concurrent threads never overdrew an account and total debits always equalled total credits.

Key terms to know:

- **Double-entry bookkeeping** — every movement debits some accounts and credits others by equal amounts.
- **Entry vs transaction** — one line on one account versus the balanced group of lines posted together.

- **Append-only / immutable entries** — never updated or deleted; mistakes are fixed by new transactions.
- **Reversal** — a new transaction with the opposite entries of an earlier one.
- **Hold (authorise, capture, void)** — reserve funds as pending, later post all or part, or cancel.
- **Available balance** — posted balance minus pending holds.
- **Cached balance + reconciliation** — a fast balance row checked periodically against the sum of entries.
- **Lock ordering** — locking accounts by sorted id so concurrent transfers cannot deadlock.
- **Hot account** — an account touched by most transactions, such as a fee account, that serialises traffic.

Q: Why double entry instead of a balance column?

A: Every movement is recorded twice and must balance, so errors are detectable and the full history explains every balance. A mutable balance column can be wrong with no trail to show how it got there.

Q: How do you prevent deadlocks between concurrent transfers?

A: Lock the involved account rows in a consistent order, such as sorted by id. A to B and B to A then both lock the lower id first, so no circular wait can form.

Q: How do you correct a mistaken transaction?

A: Post a reversing transaction; entries are never updated or deleted. Auditors rely on that immutability, and the database can enforce it by revoking `UPDATE` and `DELETE` on the entry table.

Q: How does idempotency stay correct when two identical requests race?

A: Insert the idempotency key in the same transaction as the entries, with a unique constraint. The second request's insert fails, so it reads and returns the winner's stored result. Storing a hash of the request body means a client reusing a key for a different request gets an error, not someone else's answer.

Q: Code-level: how do you validate that a transaction balances?

A: Sum signed amounts per currency and require zero for each.

```
Map<Currency, Long> net = new HashMap<>();
for (Entry e : tx.entries())
    net.merge(e.currency(), e.direction() == DEBIT ? e.amountMinor() : -e.amountMinor(),
Math::addExact);
if (net.values().stream().anyMatch(v -> v != 0)) throw new UnbalancedTransactionException(tx);
```

`Math::addExact` throws on overflow instead of silently wrapping.

Q: How do holds work?

A: A hold increases the account's pending amount and reduces available balance, without posting entries. Capture posts real entries for all or part of the hold and releases the rest; void releases it all. Holds expire, so an abandoned authorisation does not lock funds forever.

Q: What breaks first at 10x volume?

A: The hot fee account, credited by every transfer, serialises everything on one row lock. Split it into N sub-accounts chosen at random, or skip its synchronous cached balance and derive it asynchronously. Beyond one database, accounts are sharded and cross-shard transfers need a saga with pending states or two-phase commit.

Q: How do you prove the ledger is right?

A: Property tests on the in-memory version (random balanced postings, conservation, non-negativity), a concurrency stress test against PostgreSQL in Testcontainers, an idempotency race test, and a reconciliation test that corrupts a cached balance on purpose and checks the job catches it.

Common mistakes in answers:

- Editing or deleting an entry to fix a mistake.
- Updating the cached balance in a separate transaction from the entries.
- Treating idempotency as a cache lookup outside the write transaction.

TL;DR

Balanced, append-only transactions; balances cached in the same database transaction and reconciled; ordered row locks; idempotency keys stored with the write.

35. Circuit Breaker and Retry Library

Level: Advanced · **Time:** 2–3 weeks · **Prerequisites:** Ch 9, Ch 11, Ch 12

What it is

A resilience library that wraps calls to unreliable dependencies: a **circuit breaker** stops calling a failing service for a while (instead of piling up timeouts), **retry** repeats transient failures with backoff, a **timeout** bounds each call, and a **bulkhead** caps concurrent calls. Decorators compose them: `bulkhead(retry(circuitBreaker(timeout(call))))` — retry sits outside the breaker so an open breaker stops retries at once.

The problem it solves

When a downstream service slows down, callers wait, threads pile up, and the slowness spreads upstream until everything fails — a cascading failure. Naive retries make it worse by multiplying load on the struggling service. A circuit breaker "fails fast" when a dependency is unhealthy and probes carefully to detect recovery. Building one teaches sliding-window statistics, a concurrent state machine and the **Decorator** and **Proxy** patterns.

Real-world examples

- Martin Fowler's CircuitBreaker article explains the closed/open/half-open idea with a simple implementation.
- Resilience4j's CircuitBreaker documents count-based and time-based sliding windows, failure-rate and slow-call thresholds, and the half-open state — the feature set you mirror.
- AWS's timeouts, retries and backoff with jitter explains why retries need limits and jitter.

Requirements

Functional


- `CircuitBreaker` with closed, open and half-open states; count-based window (last N calls) and time-based window (last N seconds).
- Open when failure rate or slow-call rate exceeds thresholds (with a minimum number of calls).
- Stay open for a wait duration, then half-open: allow K trial calls; close if they succeed, reopen if not.
- `Retry` with max attempts, exponential backoff with jitter, retry-on predicates (exception types, results).
- `TimeLimiter` and `Bulkhead` (semaphore-based max concurrent calls).

- Composable decorators for `Supplier`, `Callable` and `CompletionStage`; events and metrics (state transitions, rejected calls).

Non-functional


- Overhead per call in the closed state under 1 microsecond median.
- Thread-safe under heavy concurrency; exactly K calls admitted in half-open.
- Deterministic tests via injected clock and random source.

The architecture



- **Resilience / DecoratorBuilder** — fluent API composing decorators around a call, in a documented order.
- **CircuitBreaker** — permission check before the call, outcome recording after; state held in an `AtomicReference`.
- **CbState** — State pattern; each state decides permissions and transitions.
- **SlidingWindow** — Strategy: ring buffer of outcomes (count-based) or per-second buckets (time-based).
- **Retry / BackoffPolicy** — attempt loop with pluggable delays.
- **Bulkhead / TimeLimiter** — concurrency cap and per-call timeout.
- **EventPublisher** — Observer for metrics and logging.

Data model



Type	Notes
`Outcome`	enum `SUCCESS`, `FAILURE`, `SLOW_SUCCESS`, `SLOW_FAILURE`
`Snapshot`	total calls, failures, slow calls, failure rate
`CbConfig`	thresholds, window type and size, wait duration, permitted half-open calls, minimum calls

Tech stack

Component	Choice	Why
State	`AtomicReference<CbState>` + CAS	lock-free transitions
Window	ring buffer of `byte` outcomes or `LongAdder` buckets	O(1) record
Async	`CompletableFuture` integration	non-blocking callers
Benchmarks	JMH	closed-state overhead
Tests	JUnit 6, AssertJ, jcstress, fake clock	timing and races

Milestones

1. **Count-based breaker.** *Done when:* with window 10, threshold 50%, minimum 5, the 5th failure out of 10 opens the circuit.
2. **Open and half-open.** *Done when:* after the wait (fake clock) exactly K concurrent trial calls are admitted, verified with 100 threads.
3. **Time-based window and slow calls.** *Done when:* calls slower than the threshold count toward opening, and old buckets age out.
4. **Retry, time limiter, bulkhead.** *Done when:* retry stops at max attempts with growing jittered delays, and a bulkhead of 10 rejects the 11th concurrent call.
5. **Composition and metrics.** *Done when:* the decorated stack behaves correctly in a scenario test with a flaky fake service, and JMH reports closed-state overhead.

Deep dive: the hard parts

Admitting exactly K trial calls. In half-open, many threads ask for permission at once. Give the `HalfOpen` state an `AtomicInteger` of remaining permits and `decrementAndGet`; only threads that see a value at or above zero proceed. Transitions (half-open → closed/open) use `compareAndSet` on the state reference so only one thread performs each transition and stale states are ignored.

Windows that are cheap. A count-based window is a ring buffer of the last N outcomes plus running totals: on record, subtract the outcome being overwritten and add the new one — O(1). A time-based window uses one bucket per second in a ring; on record, reset buckets that are older than the window.

Decorator order matters. Retry outside the circuit breaker means each retry asks the breaker, so an open breaker stops retries immediately — usually what you want. Retry inside the breaker hides individual failures from it. Bulkhead outermost prevents queued retries from consuming permits. Document the default order and test both.

What counts as failure. A 404 is usually the caller's problem, not the dependency's health; counting it would open the circuit wrongly. Let users configure which exceptions or results count, with sensible defaults (timeouts and 5xx count; 4xx do not).

Testing strategy

Fake clock and seeded random for deterministic timing and jitter. Scenario tests with a programmable fake dependency (fail N times, then slow, then recover). jcstress tests for half-open permits and concurrent transitions. JMH for the closed-state hot path.

Trade-offs, scaling and failure modes

Breakers are per instance, so each server learns independently — usually fine and avoids a shared dependency. Too-sensitive thresholds flap (open/close repeatedly); require minimum calls and use longer windows. Retries multiply load: 3 retries at each of 3 layers is up to 64 calls for one user request — retry at one layer only. Fallbacks (cached data, defaults) are part of the design, not an afterthought.

Stretch goals

- Adaptive concurrency limits that grow and shrink with observed latency.
- Integration as a Spring AOP aspect with annotations.
- Retry budgets: cap retries to a percentage of total traffic.

Skills practised

- Ch 9 — Structural patterns: Decorator and Proxy.
- Ch 11 — Behavioral patterns 2: State, Strategy, Observer.
- Ch 12 — Concurrency concepts: atomics, CAS, semaphores.

In the interview

30-second answer: I built a resilience library with a circuit breaker, retry, time limiter and bulkhead that compose as decorators around any call. The breaker is a closed, open, half-open state machine held in an `AtomicReference` and changed only by compare-and-set, over an O(1) sliding window (a ring buffer for count-based, per-second buckets for time-based), with a minimum-calls rule to avoid flapping. In half-open an `AtomicInteger` of permits admits exactly K trial calls, which I verified with 100 threads and jcstress. Retries use exponential backoff with jitter and sit outside the breaker, so an open breaker stops them immediately, and JMH measured the closed-state overhead.

Key terms to know:

- **Circuit breaker** — stops calling a failing dependency for a while so callers fail fast.
- **Closed / open / half-open** — calls flow; calls rejected; a few trial calls test recovery.
- **Failure-rate and slow-call thresholds** — percentages over the window that trip the breaker.
- **Count-based vs time-based window** — last N calls versus last N seconds.
- **Bulkhead** — a cap on concurrent calls (a semaphore) so one dependency cannot consume every thread.
- **Time limiter** — bounds each call's duration.
- **Cascading failure** — slowness spreading upstream as callers wait and pile up.
- **Retry amplification** — retries at several layers multiply load (3 retries at 3 layers is up to 4^3 = 64 calls).
- **Decorator / Proxy** — wrapping a call to add behaviour without changing it.

Q: What does half-open do?

A: After the open wait, it admits a limited number of trial calls; their results decide whether to close or reopen. Admitting only K protects a recovering service from a flood.

Q: Retry inside or outside the circuit breaker?

A: Usually outside, so an open breaker short-circuits retries and every individual failure is visible to the breaker. Retry inside would hide failures from the breaker and keep hammering a dead service. Resilience4j's default aspect order also puts Retry outermost, around CircuitBreaker, TimeLimiter and Bulkhead.

Q: Why jitter?

A: To avoid synchronised retries from many clients hitting a recovering service at the same moment. Each client waits a random fraction of its backoff delay, which spreads the load.

Q: How do you admit exactly K trial calls under heavy concurrency?

A: The half-open state holds an `AtomicInteger` of remaining permits; each caller does `decrementAndGet` and proceeds only if the result is at or above zero. The state transition back to closed or open uses `compareAndSet` on the state reference, so only one thread performs it and late results from an old state are ignored.

Q: Code-level: how is the count-based window O(1)?

A: A ring buffer of outcomes plus running totals; overwrite the oldest slot and adjust totals.

```
synchronized void record(boolean failed) {
    if (count == size && ring[idx]) failures--;   // drop the oldest outcome
    ring[idx] = failed; if (failed) failures++;
    idx = (idx + 1) % size; count = Math.min(count + 1, size);
}
double failureRate() { return count < minCalls ? 0 : 100.0 * failures / count; }
```

Q: What should count as a failure?

A: Failures that say the dependency is unhealthy: timeouts, connection errors, HTTP 5xx. A 404 or validation error is the caller's problem; counting it would open the circuit wrongly. Make the predicate configurable with those defaults.

Q: What happens if thresholds are too sensitive?

A: The breaker flaps, opening and closing repeatedly on a few unlucky calls. Require a minimum number of calls before computing the rate, use a longer window, and alert on state changes so flapping is visible.

Q: What happens with many servers or 10x traffic?

A: Each instance has its own breaker and learns independently, which is usually fine and avoids a shared dependency. Retries become the danger at scale, so retry at one layer only, add retry budgets (a percentage of traffic), and design fallbacks such as cached data or defaults.

Q: How do you test timing behaviour deterministically?

A: Inject a fake clock and a seeded random source, then drive a programmable fake dependency (fail N times, then slow, then recover) through scenario tests. jcstress checks the half-open permits and concurrent transitions, and JMH measures the closed-state hot path.

Common mistakes in answers:

- Retrying every error immediately with no backoff, jitter or limit.
- Letting all waiting threads through in half-open.
- Counting client errors (4xx) as dependency failures.

TL;DR

A CAS-driven closed/open/half-open state machine over O(1) sliding windows, plus retry, timeout and bulkhead decorators composed in a deliberate order.

36. Dependency Injection Container

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 4, Ch 8, Ch 9

What it is

A minimal dependency injection (DI) container, like a tiny Guice or Spring core: you register or annotate classes, and the container constructs object graphs for you — resolving constructor parameters, managing scopes (singleton, prototype), binding interfaces to implementations, calling lifecycle hooks and detecting circular dependencies. Optionally it adds simple proxies for cross-cutting concerns like timing or transactions.

The problem it solves

Dependency Inversion says high-level code should depend on interfaces, but *someone* still has to create concrete objects and wire them together. Doing it by hand in `main` works until there are hundreds of classes. A container automates wiring while keeping classes framework-free (plain constructors). Building one demystifies what Spring does at startup, and exercises reflection, graph algorithms (cycle detection, ordering), the Factory and Proxy patterns, and good error messages.

Real-world examples

- Martin Fowler's article Inversion of Control Containers and the Dependency Injection pattern named and explained constructor, setter and interface injection.
- Guice is a reflection-based Java DI framework built around modules and bindings; Dagger does the same wiring at compile time with generated code — a key trade-off to discuss.
- The Spring Framework reference on the IoC container documents bean scopes, lifecycle callbacks and constructor injection.

Requirements


Functional

- Register bindings: interface → implementation, instance bindings, provider (factory) bindings, qualifiers (named bindings).
- Constructor injection: choose the single public constructor or the one annotated `@Inject`.
- Scopes: singleton (one per container) and prototype (new each time); a request-like custom scope as a stretch.
- Lifecycle: `@PostConstruct`-style init and `@PreDestroy`-style close, called in dependency order and reverse order.
- Inject `Provider<T>` for lazy or repeated access.
- Classpath scanning of a package for annotated components (optional).
- Clear errors: missing binding with the full dependency path; circular dependency with the cycle printed.

Non-functional

- Container start for 500 components under 500 ms.
- Thread-safe singleton creation (no duplicates under concurrent `get`).
- Zero framework annotations required on domain classes when using explicit modules.

The architecture



- **Container** — the public face: builds from modules, validates eagerly, resolves keys.
- **Module / Binder** — the configuration DSL (a Builder).
- **Key** — type (including generics) plus optional qualifier.
- **Binding** — what provides a key and in which scope.
- **InternalProvider** — the Factory: `ConstructorProvider` reflects on a constructor and resolves its parameters.
- **Scope** — a Decorator around a provider; `SingletonScope` caches the instance.
- **GraphValidator** — builds the dependency graph and finds missing bindings and cycles before any object is created.
- **LifecycleManager** — records creation order for init and shutdown hooks.

Data model

Type	Notes
`Key<T>`	record (java.lang.reflect.Type, qualifier) — must handle `List<String>` vs `List<Integer>`
`Dependency`	record (key, injection point description) for error paths
`ResolutionContext`	stack of keys being constructed — detects cycles at runtime and prints paths
Graph	adjacency map key → dependency keys, for validation and topological order

Tech stack

Component	Choice	Why
Reflection	`java.lang.reflect`, `MethodHandles` for speed	constructor invocation
Generic keys	a `TypeLiteral`-style super-type token	capture `List<String>`
Proxies	`java.lang.reflect.Proxy` for interfaces	timing and logging aspects
Tests	JUnit 6, AssertJ	error message assertions

Milestones

1. **Explicit bindings and constructor injection.** *Done when:* a three-level graph (controller → service → repository) is built from a module with no annotations on the classes.
2. **Scopes.** *Done when:* singletons are created once even under 100 concurrent `get` calls, and prototypes are new each time.
3. **Validation and errors.** *Done when:* a missing binding reports the full path (`A -> B -> C: no binding for C`), and a cycle reports `A -> B -> A` before anything is constructed.
4. **Providers, qualifiers, lifecycle.** *Done when:* `Provider<T>` breaks a cycle legally, named bindings resolve, and close hooks run in reverse creation order.
5. **Scanning and proxies.** *Done when:* annotated components in a package are discovered, and a `@Timed` interface method is wrapped by a dynamic proxy that records durations.

Deep dive: the hard parts

Cycle detection, twice. At startup, run a depth-first search over the graph with three colours (unvisited, in progress, done); hitting an "in progress" node means a cycle — print the stack. At runtime (for dynamic cases), keep a per-resolution stack in `ResolutionContext`. `Provider<T>` injection legitimately breaks cycles because it defers resolution, so the validator must treat provider edges as non-blocking.

Generic type keys. `Class<T>` erases generics, so `List<String>` and `List<Integer>` look the same. Capture the full `Type` with a "super type token": an anonymous subclass `new TypeLiteral<List<String>>() {}` whose generic superclass reveals the type argument via reflection. Keys compare full `Type`s.

Thread-safe singletons without a global lock. Two threads asking for the same singleton must get one instance. Use per-key `computeIfAbsent` on a `ConcurrentHashMap` — but beware: the JDK forbids recursively modifying the same map inside `computeIfAbsent`, and constructing a singleton often requests other singletons. Use a per-key lock (or a future per key) instead, created with `computeIfAbsent`, then construct outside the map's internal lock.

Reflection versus compile time. Reflection-based containers find wiring errors at startup and pay reflection costs; Dagger generates plain Java at compile time, finding errors at build time and starting faster. Write a paragraph on when each is better.

Testing strategy

Graph tests with tiny test classes covering every binding type. Error-message tests asserting the exact path text (error quality is a feature). Concurrency test for singleton uniqueness. Startup benchmark with 500 generated classes.

Trade-offs, scaling and failure modes

Auto-scanning is convenient but hides wiring; explicit modules are verbose but searchable. Field injection is tempting but hides dependencies and blocks immutability — support constructor injection first. Proxies only work for interfaces with the JDK `Proxy`; class proxies need bytecode generation libraries. Too much magic makes debugging hard: provide a `container.explain(Key)` that prints how a key is built.

Stretch goals

- Request scope backed by a `ScopedValue` (JEP 506, final in Java 25; a Java 25-only feature).
- Compile-time wiring with an annotation processor generating factory classes.
- Conditional bindings by environment (dev/prod).

Skills practised

- Ch 4 — SOLID principles: Dependency Inversion.
- Ch 5 — Design principles: Hollywood principle and inversion of control.

- Ch 8 — Creational patterns: Factory, Builder, Singleton scope.
- Ch 9 — Structural patterns: Proxy and Decorator.

In the interview

30-second answer: I built a small dependency injection container, like a minimal Guice: modules bind interfaces to implementations, instances or providers, keyed by the full generic type plus an optional qualifier, and the container builds object graphs by constructor injection. Before creating any object, a graph validator runs a three-colour depth-first search and reports missing bindings and cycles with the full path, such as `A -> B -> A`. Scopes are decorators around providers, and singletons are created exactly once under concurrency using a per-key lock rather than `computeIfAbsent`, because building one singleton recursively asks for others. Domain classes need no framework annotations, and 500 components start in under 500 ms.

Key terms to know:

- **Dependency injection (DI)** — objects receive their dependencies from outside, usually through the constructor.
- **Inversion of control (IoC) container** — the framework creates and wires objects instead of your code doing it.
- **Binding / Key** — a rule saying what provides a type; the key is the full generic type plus qualifier.
- **Scope** — how long an instance lives: singleton (one per container) or prototype (new each time).
- **Provider** — a factory injected instead of an instance, for lazy or repeated access; it can break cycles.
- **Super type token** — `new TypeLiteral<List<String>>() {}` captures a generic type that erasure would lose.
- **Three-colour DFS** — unvisited, in progress, done; reaching an in-progress node means a cycle.
- **Dynamic proxy** — `java.lang.reflect.Proxy` creates an interface implementation at runtime to add timing or logging.
- **Service locator** — the anti-pattern where a class asks a global registry for its dependencies.

Q: What is the difference between DI and a service locator?

A: With DI, dependencies are passed in (usually via the constructor) and classes do not know the container exists. A service locator is called by the class to fetch dependencies, which hides them from the constructor signature and couples every class to the locator, making tests harder.

Q: How do you detect circular dependencies?

A: Depth-first search over the binding graph at startup with three colours, reporting the cycle path from the recursion stack. Provider injections are allowed to break cycles because they defer resolution, so the validator treats provider edges as non-blocking.

Q: Reflection or code generation?

A: Reflection is flexible and simple and finds wiring errors at startup; code generation (like Dagger) moves errors to build time, avoids reflection and starts faster, which matters on mobile or serverless. I would pick reflection for a learning container and compile-time wiring when startup time or build-time safety matters.

Q: Why is constructor injection preferred over field injection?

A: Constructor parameters make every dependency visible and required, allow `final` fields and immutability, and let tests create the class with plain `new`. Field injection hides dependencies,

needs reflection to set private fields, and lets a half-built object exist.

Q: Code-level: why not `computeIfAbsent` for singletons?

A: The mapping function must not modify the same map, and building singleton A triggers a request for singleton B.

```
singletons.computeIfAbsent(keyA, k -> create(k)); // create(A) asks for B -> same map again
// JDK may throw IllegalStateException("Recursive update") or deadlock
var lock = locks.computeIfAbsent(key, k -> new ReentrantLock()); // tiny, non-recursive
lock.lock();
try { return instances.containsKey(key) ? instances.get(key) : createAndStore(key); }
finally { lock.unlock(); }
```

Q: How do you tell `List<String>` and `List<Integer>` apart?

A: `Class<T>` loses type arguments through erasure. A super type token, an anonymous subclass of `TypeLiteral<List<String>>`, keeps the argument in its generic superclass, which reflection reads with `getGenericSuperclass()`. Keys then compare full `Type` objects.

Q: What happens when a binding is missing?

A: The validator fails at startup, before any object is created, with the full path: `OrderController -> OrderService -> PaymentGateway: no binding for PaymentGateway`. Good error messages are a feature, so tests assert the exact text.

Q: What changes at 10x components?

A: Reflection and classpath scanning dominate startup, so cache constructor lookups, use `MethodHandles`, scan only listed packages, or move to compile-time generated factories. Debugging also gets harder, so an `explain(Key)` that prints how a key is built pays off.

Q: How do lifecycle hooks run in the right order?

A: Record the order in which singletons finished construction; dependencies always finish before their dependents. Init hooks run in that order and close hooks in reverse, so nothing is closed while something still uses it.

Common mistakes in answers:

- Describing a service locator and calling it dependency injection.
- Forgetting that a cycle through `Provider<T>` is legal.
- Using `computeIfAbsent` with a recursive factory.

TL;DR

Bindings keyed by full generic type, providers as factories wrapped by scopes, an eager graph validator with readable cycle and missing-binding errors, and thread-safe singletons.

37. Checkout with Inventory Reservation

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 11, Ch 12, Ch 19

What it is

The checkout flow of an online shop, built as a small modular monolith with separate modules for cart, inventory, payment, and orders that communicate only through interfaces and events. Placing an order **reserves** stock, **authorises** payment, **confirms** the order, and on any failure runs **compensations** (release stock, void payment) — a **saga**, the standard way to keep several independent parts consistent without one big transaction.

The problem it solves

Overselling (taking money for items you do not have) and charging for orders that fail are expensive and anger customers. When inventory, payment and orders are separate services or modules with their own data, a single database transaction cannot cover them. The project teaches sagas, reservations with expiry, idempotent steps, the **transactional outbox** for reliable events, and how to design module boundaries that could later become services.

Real-world examples

- The Saga pattern on microservices.io describes coordinating a sequence of local transactions with compensating actions, either by choreography (events) or orchestration (a coordinator).
- Stripe's idempotency post shows why each step that moves money must be safe to retry — every saga step here takes an idempotency key.
- The handbook's platforms chapter covers the Amazon-style e-commerce design; this capstone implements its checkout core.

Requirements


Functional

- Cart: add, remove and change quantities; price snapshot at checkout.
- Inventory: stock per SKU per warehouse; reservations with a 15-minute expiry; commit reservation on confirmation; release on cancellation.
- Payment: authorise, capture, void, refund via a gateway interface (fake provider).
- Order: states from pending to confirmed, cancelled or failed; customer-visible history.
- Saga orchestrator: reserve → authorise → confirm order → commit stock → capture; compensate on failure at any step.
- Events emitted for each state change via an outbox.

Non-functional

- No overselling under 500 concurrent checkouts for the last 10 units of a SKU.
- A crash at any step leaves the system recoverable to a consistent end state (completed or fully compensated).
- Checkout response under 300 ms with fake providers.


The architecture



- **CheckoutOrchestrator** — runs the saga steps in order and the compensations in reverse on failure; resumes incomplete sagas after a crash.
- **SagaLog** — durable record of each step's status: the orchestrator's memory.

- **InventoryPort / PaymentPort / OrderPort** — module interfaces (ports); every method is idempotent per saga id.
- **Outbox** — events written in the same local transaction as the state change, published afterwards.
- **ReservationExpirer** — releases reservations whose saga never completed.

Data model



Type	Notes
`Reservation`	id, saga id, lines, status (`HELD`, `COMMITTED`, `RELEASED`, `EXPIRED`), expires at
`SagaInstance`	id, cart id, current step, step results (reservation id, auth id, order id), attempts
`OutboxEvent`	id, aggregate, type, payload, created, published flag

Tech stack

Component	Choice	Why
Modules	Java packages with module-info or ArchUnit rules	enforce boundaries
Storage	PostgreSQL (one schema per module) or in-memory	local transactions per module
Stock check	conditional update `available >= qty`	atomic oversell guard
Tests	JUnit 6, Mockito, AssertJ, ArchUnit, Testcontainers	boundaries and failures

Milestones

1. **Modules and ports.** *Done when:* ArchUnit tests prove no module touches another's internals.
2. **Happy-path saga.** *Done when:* a checkout reserves, authorises, confirms, commits and captures, recording each step.
3. **Oversell protection.** *Done when:* 500 concurrent checkouts for 10 units produce exactly 10 completed orders.
4. **Compensations.** *Done when:* a declined payment releases stock, and a failure after authorisation voids the payment and releases stock — each verified.
5. **Crash recovery and outbox.** *Done when:* killing the orchestrator after each step and calling `resume` always reaches Completed or Failed with no leaked reservation or authorisation, and events are published exactly once per outbox row (at-least-once to subscribers).

Deep dive: the hard parts

Atomic stock reservation. The check "is there enough stock?" and the decrement must be one atomic operation: `UPDATE stock SET available = available - :qty WHERE sku = :sku AND available >= :qty` and check the affected row count. In memory, `ConcurrentHashMap.compute` per SKU does the same. Multi-line carts reserve lines in sorted SKU order inside one local transaction to avoid deadlocks.

Idempotent steps make recovery simple. After a crash, the orchestrator does not know whether the last step happened. If every port method is idempotent on the saga id (`reserve(sagaId, ...)` returns the existing reservation if one exists), recovery is just "re-run the current step". Compensations must be idempotent too: releasing an already-released reservation is a no-op.

The outbox. Writing to the database and publishing an event are two systems; a crash between them loses or duplicates events. Insert the event into an outbox table in the same transaction as the state change; a relay publishes unpublished rows and marks them. Subscribers must tolerate duplicates.

Orchestration versus choreography. An orchestrator is easy to follow and test, but central. Choreography (each module reacts to the previous module's event) has no centre but makes the flow hard to see. Build orchestration, then sketch choreography and compare.

Testing strategy

Mockito-scripted failures at each step to test compensations. A crash-injection test harness that stops after step N and resumes. Concurrency test for overselling. ArchUnit rules for module boundaries. Testcontainers for the PostgreSQL version.

Trade-offs, scaling and failure modes

Reserving at checkout holds stock that may never be bought; short expiry and releasing on cart abandonment limit the damage. Some shops reserve only at payment, accepting rare overselling and apologising. Compensations are not rollbacks — a voided authorisation may still show briefly on a card statement. Sagas give eventual consistency: for a moment, stock is reserved but the order is not yet confirmed; the UI must show "processing".

Stretch goals

- Split modules into separate processes communicating over HTTP, keeping the same ports.
- Partial fulfilment from multiple warehouses.
- Choreography version driven by events, compared with the orchestrator.

Skills practised

- Ch 19 — Platforms 2: Amazon-style e-commerce case.
- Ch 11 — Behavioral patterns 2: State and Observer; sagas as beyond-GoF patterns.
- Ch 12 — Concurrency concepts: atomic conditional updates.

- Ch 4 — SOLID principles: ports and dependency inversion.

In the interview

30-second answer: I built an online checkout as a modular monolith where cart, inventory, payment and orders talk only through ports, and placing an order is an orchestrated saga: reserve stock, authorise payment, confirm the order, commit stock, capture payment, with compensations in reverse order on failure. Stock is reserved with an atomic conditional decrement (`available >= qty`), so 500 concurrent checkouts for the last 10 units produced exactly 10 orders. Every port method is idempotent on the saga id and the saga log is durable, so after a crash recovery just re-runs the current step. Events go through a transactional outbox, so a state change and its event are never split.

Key terms to know:

- **Saga** — a sequence of local transactions with a compensating action for each step.
- **Orchestration vs choreography** — a central coordinator runs the steps, versus each module reacting to the previous event.
- **Compensation** — a business-level undo such as releasing stock or voiding a payment; not a database rollback.
- **Reservation with expiry** — stock held for 15 minutes and released if the saga does not finish.
- **Authorise vs capture** — reserve money on the card versus actually take it.
- **Idempotent step** — calling `reserve(sagaId, ...)` twice returns the same reservation.
- **Transactional outbox** — events written in the same transaction as the state change, published later by a relay.
- **Ports and adapters** — module interfaces that hide internals, enforced with ArchUnit.
- **Eventual consistency** — for a moment, stock is reserved but the order is not yet confirmed.

Q: How do you keep inventory, payment and orders consistent without a distributed transaction?

A: A saga: a sequence of local transactions with compensations for each completed step, driven by an orchestrator with a durable log. If payment authorisation fails, the orchestrator releases the reservation; if confirmation fails after authorisation, it voids the payment and releases stock.

Q: How do you prevent overselling?

A: A conditional decrement that only succeeds if enough stock is available, executed atomically per SKU: `UPDATE stock SET available = available - :qty WHERE sku = :sku AND available >= :qty`, then check the affected row count. Multi-line carts lock SKUs in sorted order to avoid deadlocks.

Q: How do you publish events reliably?

A: A transactional outbox: write events in the same transaction as the state change, publish afterwards from a relay, and make consumers idempotent because the relay may publish a row twice after a crash.

Q: Why orchestration rather than choreography?

A: An orchestrator puts the whole flow in one readable place, which is easy to test and to resume after a crash. Choreography has no central point, but the flow is spread across event handlers and hard to see; it suits loosely related teams better than a tight checkout flow.

Q: What happens if the orchestrator crashes between steps?

A: The saga log says which step was in progress but not whether it completed. Because every port is idempotent on the saga id, `resume` simply re-runs that step: a repeated `reserve` returns the existing reservation, a repeated `void` is a no-op. A crash-injection test stops after each step and checks the saga always ends Completed or fully compensated.

Q: Code-level: how do you reserve stock atomically in memory?

A: A conditional update per SKU with `compute`.

```
boolean[] ok = {false};
stock.compute(sku, (k, available) -> {
    if (available == null || available < qty) return available;   // not enough: unchanged
    ok[0] = true; return available - qty;
});
if (!ok[0]) return ReserveResult.insufficient(sku);
```

Q: Why is a compensation not the same as a rollback?

A: A rollback makes it as if nothing happened; a compensation is a new action that undoes the business effect. A voided card authorisation may still show briefly on the customer's statement, and an email already sent cannot be unsent, so the UI shows "processing" until the saga finishes.

Q: What changes at 10x traffic or when modules become services?

A: A flash sale makes one SKU row hot, so split its stock into several buckets or reserve from an in-memory counter that is synced to the database. When modules become separate services, the same ports become HTTP or messaging clients, and timeouts mean "unknown outcome", which idempotent steps already handle.

Q: How do you test compensations?

A: Mockito-scripted failures at each step, verifying exactly which compensations ran and in reverse order; a crash-injection harness for resume; a concurrency test for overselling; and ArchUnit rules proving no module touches another's internals.

Common mistakes in answers:

- Proposing a two-phase commit across payment providers that do not support it.
- Check-then-decrement stock in two steps.
- Non-idempotent steps, which make crash recovery guesswork.

TL;DR

An orchestrated saga over idempotent module ports, atomic conditional stock reservations with expiry, compensations in reverse order and an outbox for reliable events.

38. Database Connection Pool

Level: Advanced · **Time:** 2–3 weeks · **Prerequisites:** Ch 8, Ch 12, Ch 13

What it is

A JDBC connection pool, like a small HikariCP: it keeps a set of open database connections, lends one to each request, takes it back when the caller closes it, validates connections, replaces broken ones, and bounds how long callers wait. Callers use the standard `javax.sql.DataSource` interface, so any JDBC code can use your pool unchanged.

The problem it solves

Opening a database connection costs a network round trip, authentication and server-side setup — far too slow per request. A pool reuses connections, but must handle hard problems: fair and fast hand-off under contention, connections that die silently (network blips, server restarts), callers that forget to return connections (leaks), and bounding total connections so the database is not overwhelmed. It is the canonical **Object Pool** pattern plus serious concurrency.

Real-world examples

- HikariCP is the default connection pool in Spring Boot; its wiki page Down the Rabbit Hole describes its custom lock-free `ConcurrentBag` with thread-local caching and direct hand-off.
- HikariCP's About Pool Sizing page argues that small pools usually outperform large ones and suggests a starting formula based on CPU cores and disks.

Requirements


Functional

- Implements `DataSource.getConnection()`; returns a proxy connection whose `close()` returns it to the pool.
- Minimum idle and maximum pool size; connection timeout for waiting callers.
- Validation: test idle connections before lending (`isValid`) when idle longer than a threshold.
- Max lifetime: retire connections after N minutes (with jitter) to avoid all expiring at once.
- Leak detection: warn with the borrower's stack trace if a connection is held longer than a threshold.
- Reset state on return (auto-commit, isolation, read-only) and roll back uncommitted work.
- Metrics: active, idle, waiting, creation time, wait time.

Non-functional

- Borrow/return overhead under 1 microsecond median when connections are idle (JMH).
- No connection lent to two callers; no connection lost from the pool under stress.
- Waiting callers time out exactly at the configured limit (within 10 ms).


The architecture



- **PooledDataSource** — the public `DataSource`; orchestrates borrow, validation and wrapping.
- **ConnectionBag** — the core data structure: all entries, a thread-local list of recently used entries, and a hand-off queue for waiters.
- **PoolEntry** — one physical connection with an atomic state (`NOT_IN_USE`, `IN_USE`, `RESERVED`, `REMOVED`).
- **ProxyConnection** — a Proxy around the real connection; `close()` returns to the pool; tracks open statements.
- **ConnectionFactory** — creates physical connections (via `DriverManager` or a driver's `DataSource`).

- **HouseKeeper** — background task: retire old connections, fill to minimum idle, remove idle extras.
- **LeakDetector / PoolMetrics** — observability.

Data model



Configuration record: pool name, JDBC URL, credentials, min idle, max size, connection timeout, idle timeout, max lifetime, validation timeout, leak threshold.

Tech stack

Component	Choice	Why
Entry state	`AtomicInteger` CAS	lock-free claim
Waiters	`SynchronousQueue` hand-off, or `Semaphore` + queue first	direct hand-off
Proxy	hand-written delegating class (or `java.lang.reflect.Proxy`)	intercept `close`
Database for tests	H2 in-memory and PostgreSQL via Testcontainers	fast and realistic
Tests	JUnit 6, AssertJ, jcstress, JMH	correctness and speed

Milestones

1. **Simple pool.** *Done when:* a `Semaphore` plus `ConcurrentLinkedQueue` pool passes a 64-thread borrow/return stress test with no double lending.
2. **Proxy connection.** *Done when:* closing the proxy returns the connection, a second close is a no-op, and using a closed proxy throws.
3. **Timeouts and validation.** *Done when:* waiters time out at the limit, and a connection killed on the server side is detected and replaced on borrow.
4. **Housekeeping and lifetime.** *Done when:* connections retire after max lifetime (fake clock), and idle extras shrink to min idle.
5. **Lock-free bag and benchmarks.** *Done when:* a `ConcurrentBag`-style implementation with thread-local reuse beats the simple pool in JMH under contention, and leak detection logs the borrower's stack.

Deep dive: the hard parts

Claiming an entry exactly once. Each entry's state is an `AtomicInteger`; borrowing is `compareAndSet(NOT_IN_USE, IN_USE)`. Whichever thread wins owns it. Scanning the shared list for a free entry is O(n), so first check a thread-local list of entries this thread used recently (likely free and warm in CPU cache), then the shared list, then wait on the hand-off queue.

Hand-off to waiters. When a connection is returned and threads are waiting, giving it directly to a waiter (via `SynchronousQueue.offer`) avoids a race where a newly arriving thread steals it and the waiter times out. Track the waiter count; only attempt hand-off when someone is waiting.

Resetting state on return. A caller may leave auto-commit off, change isolation or leave a transaction open. On return, roll back if not auto-commit, then restore defaults — only for properties that changed (track "dirty bits" in the proxy) because each reset may cost a round trip.

Sizing. More connections are not faster: the database has limited cores and disks, and extra connections add context switching and lock contention. Little's law ($L = \lambda W$) helps: connections needed ≈ requests per second × average time each holds a connection. With virtual threads, thousands of tasks may want a connection at once — the pool becomes the limiter, which is exactly its job.

Testing strategy

Stress tests counting borrows and returns per entry and asserting no overlaps (record owner thread in each entry). jcstress for the CAS claim. Fault injection: a `ConnectionFactory` wrapper that kills connections or slows creation. JMH comparing implementations and HikariCP as baseline.

Trade-offs, scaling and failure modes

Validation on every borrow is safe but adds a round trip; validating only after idle time is the usual compromise. A database restart breaks all connections at once: borrowers must get a fresh connection rather than an error, and creation must be rate-limited to avoid a stampede. Leak detection is diagnostic only — killing leaked connections risks breaking a slow but legitimate transaction.

Stretch goals

- Fairness option: strict FIFO for waiters.
- JMX or Micrometer-style metrics export.
- A generic `ObjectPool<T>` extracted from the connection-specific parts.

Skills practised

- Ch 8 — Creational patterns: Object Pool.
- Ch 9 — Structural patterns: Proxy.
- Ch 12 — Concurrency concepts: CAS, semaphores, thread-locals.

- Ch 13 — Concurrency problems: bounded resources and blocking queues.

In the interview

30-second answer: I built a JDBC connection pool, like a small HikariCP, behind the standard `DataSource` interface: callers get a proxy connection whose `close()` resets state and returns the physical connection to the pool. Each pooled entry has an atomic state, so borrowing is a `compareAndSet(NOT_IN_USE, IN_USE)` and a connection can never be lent to two callers; a thread-local list of recently used entries makes the common case fast, and returns are handed directly to waiting threads. A housekeeper validates idle connections, retires them after a jittered max lifetime and keeps the minimum idle. Under a 64-thread stress test nothing was double-lent or lost, and JMH measured sub-microsecond borrow and return.

Key terms to know:

- **Object Pool pattern** — reuse expensive objects instead of creating them per request.
- **Proxy pattern** — `ProxyConnection` intercepts `close()` to return rather than close.
- **CAS claim** — `compareAndSet` on each entry's state so exactly one thread wins it.
- **Direct hand-off** — giving a returned connection straight to a waiting thread (`SynchronousQueue`).
- **Connection timeout** — how long a caller waits for a connection before failing.
- **Validation (`isValid`)** — checking a connection that has been idle before lending it.
- **Max lifetime with jitter** — retiring connections at slightly different times so they do not all expire together.
- **Leak detection** — logging the borrower's stack trace when a connection is held too long.
- **Little's law** — L = lambda x W: connections needed is roughly request rate times hold time.

Q: How does `close()` return a connection instead of closing it?

A: Callers get a proxy; its `close()` rolls back any open transaction, resets changed settings and gives the underlying connection back to the pool. A second `close()` is a no-op and any other call on a closed proxy throws, so a caller cannot use a connection someone else now holds.

Q: How do you handle connections that died while idle?

A: Validate connections idle longer than a threshold before lending, retire them after a maximum lifetime, and replace broken ones. Validating on every borrow is safest but costs a round trip, so the idle threshold is the usual compromise.

Q: How big should the pool be?

A: Usually small: enough to keep the database busy, estimated by Little's law and measured. At 1,000 requests per second each holding a connection for 5 ms, about 5 connections are busy on average, so 10 gives headroom. Extra connections add context switching and lock contention on the database; HikariCP's sizing page suggests roughly cores x 2 plus disks as a starting point.

Q: Why hand a returned connection directly to a waiter?

A: If the connection just goes back into the bag, a newly arriving thread may grab it first and the waiter, who has been waiting longest, times out. Direct hand-off is fairer and avoids that race; only attempt it when the waiter count is above zero.

Q: Code-level: how is an entry claimed exactly once?

A: One atomic state per entry and a compare-and-set.

```
static final int NOT_IN_USE = 0, IN_USE = 1;
final AtomicInteger state = new AtomicInteger(NOT_IN_USE);
boolean tryClaim() { return state.compareAndSet(NOT_IN_USE, IN_USE); }
void release()     { state.set(NOT_IN_USE); }   // then offer to a waiter if any
```

Q: What happens when the database restarts?

A: Every connection breaks at once. Borrowers should get a freshly created connection rather than an error, and creation must be rate-limited so the pool does not stampede the database with hundreds of simultaneous logins as it comes back.

Q: What changes with virtual threads?

A: Thousands of virtual threads may want a connection at the same moment, far more than the database can serve. The pool becomes the limiter, which is exactly its job, so the connection timeout and a clear "pool exhausted" error matter more than ever.

Q: Should the pool close a leaked connection?

A: No. Leak detection is diagnostic: it logs the stack trace of the code that borrowed the connection. Forcibly closing it could break a slow but legitimate transaction, so the fix is in the caller, usually with try-with-resources.

Q: How do you prove no connection is lent twice?

A: Record the owner thread in each entry on claim and assert it is free on claim and owned by the same thread on return, across a 64-thread stress test; jcstress checks the CAS claim. Fault injection kills connections or slows creation, and JMH compares against HikariCP.

Common mistakes in answers:

- Thinking a bigger pool is always faster.
- Returning a connection without rolling back an open transaction or resetting auto-commit.
- Forgetting the waiter race and letting new arrivals steal returned connections.

TL;DR

An object pool of CAS-claimed entries with thread-local reuse and direct hand-off, proxy connections that reset and return on close, and a housekeeper for lifetime and validation.

39. Spreadsheet Engine

Level: Advanced · **Time:** 3–4 weeks · **Prerequisites:** Ch 10, Ch 11

What it is

The calculation engine of a spreadsheet: cells hold values or formulas (`=SUM(A1:A10) * B2`), formulas are parsed into expression trees, and when a cell changes, every cell that depends on it — directly or indirectly — is recalculated in the right order. It detects circular references, reports errors like `#DIV/0!` and supports undo.

The problem it solves

A spreadsheet is a reactive program written by non-programmers. Recalculating every cell on every change is too slow for large sheets; recalculating in the wrong order shows wrong values. The engine needs a **dependency graph**, **topological ordering** for recalculation, **cycle detection**, an **Interpreter** for formulas, and **Observer** notifications to update the view — a satisfying combination of algorithms and patterns.

Real-world examples

- Apache POI's formula evaluation documentation explains that spreadsheet files cache formula results and that changed cells and their dependents must be re-evaluated — the same problem your engine solves.
- Topological sorting orders recalculation so every cell is computed after its inputs; the shunting yard algorithm is one classic way to parse infix formulas with precedence.

Requirements


Functional

- Grid addressed as `A1`; cells contain numbers, text, booleans or formulas starting with `=`.
- Formula language: arithmetic with precedence, comparison, cell refs, ranges (`A1:B10`), functions (`SUM`, `AVERAGE`, `MIN`, `MAX`, `IF`, `COUNT`), absolute refs (`$A$1`).
- Incremental recalculation of only affected cells, in dependency order.
- Circular references detected and shown as `#CYCLE!` on all cells in the cycle.
- Errors propagate: `#DIV/0!`, `#REF!`, `#VALUE!`, `#NAME?`.
- Copy/paste formulas with relative reference adjustment. Undo/redo of edits.
- Save and load as CSV (values) and a simple JSON (formulas).

Non-functional

- Changing one input cell in a 100,000-cell sheet with a chain of 10,000 dependents recalculates in under 100 ms.
- Parse errors reported with position.
- Evaluation is deterministic and side-effect free.

The architecture



- **Sheet** — the facade: set cell input, read values, undo.
- **Cell** — raw input, parsed expression and cached value.
- **FormulaParser** — tokenizer and recursive-descent (or shunting-yard) parser into `Expr` trees.
- **Expr** — Interpreter nodes; `references()` extracts dependencies.
- **DependencyGraph** — two maps: cell → cells it reads, and cell → cells that read it.

- **Recalculator** — finds affected cells, orders them topologically, evaluates, detects cycles.
- **FunctionRegistry** — built-in functions as strategies; add new ones without touching the parser.
- **SheetListener** — Observer for views.

Data model

Type	Notes
`CellRef`	record (column, row, absolute flags), parse/format `A1`
`Value`	sealed: `Num(double)`, `Text`, `Bool`, `Empty`, `Err(ErrorCode)`
`ErrorCode`	enum `DIV0`, `REF`, `VALUE`, `NAME`, `CYCLE`
`Edit`	record (cell, old raw, new raw) — the undo command

Tech stack

Component	Choice	Why
Storage	`HashMap<CellRef, Cell>` (sparse)	most cells are empty
Graph	adjacency maps both directions	fast dependents lookup
Ordering	Kahn's algorithm on the affected subgraph	detects cycles too
UI	Swing `JTable` or terminal grid	keep it thin
Tests	JUnit 6, AssertJ, jqwik	compare incremental vs full recalc

Milestones

1. **Values and refs.** *Done when:* `A1`, `$B$12`, `AA100` parse and format round-trip.
2. **Formula parser and evaluator.** *Done when:* `=1+2*3`, `=(A1+A2)/2`, `=SUM(A1:A3)` evaluate correctly with errors for bad syntax.
3. **Dependency graph and incremental recalc.** *Done when:* changing A1 recalculates exactly its transitive dependents, in topological order, verified by an evaluation log.
4. **Cycles and errors.** *Done when:* `A1=B1+1, B1=A1+1` marks both `#CYCLE!`, breaking the cycle restores values, and `#DIV/0!` propagates.
5. **Copy/paste, undo, persistence, performance.** *Done when:* pasting `=A1+B1` one row down yields `=A2+B2`, undo restores formulas and values, and the 10,000-cell chain benchmark meets the target.

Deep dive: the hard parts

Incremental recalculation. When cell X changes: (1) update X's dependencies in the graph (its formula may read different cells now); (2) collect the transitive closure of cells that depend on X (BFS over the "dependents" map); (3) topologically order that set using only edges within it (Kahn's algorithm: repeatedly take cells whose in-set inputs are all done); (4) evaluate in order. Only affected cells are touched.

Cycle detection for free. If Kahn's algorithm finishes with cells left over, those cells are in or downstream of a cycle. Mark the ones on cycles as `#CYCLE!` (find them with a strongly-connected-components pass, or mark all leftovers for simplicity) and make their dependents propagate the error.

Ranges are dependencies too. `=SUM(A1:A1000)` depends on 1,000 cells; storing 1,000 edges per range formula is heavy. A refinement keeps range dependencies separately and checks "does this changed cell fall inside any watched range?" with an interval structure per column. Start with expanded edges, measure, then refine.

Relative references on paste. Store references with absolute flags. When pasting a formula from (r1, c1) to (r2, c2), shift every non-absolute row by r2 - r1 and column by c2 - c1. A reference shifted off the sheet becomes `#REF!`. Implement as a visitor that rewrites the expression tree.

Testing strategy

Parser tests from tables of formulas and expected trees. Property test: after random edits, incremental values equal a full recalculation from scratch (the oracle). Cycle tests including self-reference and long cycles. Benchmarks with long chains and wide fan-outs.

Trade-offs, scaling and failure modes

`double` for numbers matches real spreadsheets (and their rounding quirks); `BigDecimal` is exact but slower and differs from users' expectations elsewhere. Volatile functions (`NOW()`, `RAND()`) must recalculate every time — mark them and include them in every recalc. Very large dependency closures (a cell everything depends on) make one edit slow; multi-threaded recalculation of independent branches is a possible optimisation.

Stretch goals

- Named ranges and cross-sheet references.
- Parallel recalculation of independent subgraphs with structured concurrency (a preview API in Java 25 — needs `--enable-preview`).
- Formula auto-complete using the function registry.

Skills practised

- Ch 10 — Behavioral patterns 1: Interpreter and Command for undo.
- Ch 11 — Behavioral patterns 2: Observer, Visitor, Strategy for functions.
- Ch 9 — Structural patterns: Composite expression trees.

In the interview

30-second answer: I built a spreadsheet calculation engine: formulas are parsed by a recursive-descent parser into expression trees (Interpreter), each cell's references feed a two-way dependency graph, and an edit recalculates only the transitive dependents of the changed cell in topological order using Kahn's algorithm. If Kahn's algorithm leaves cells unprocessed, there is a cycle, so those cells show `#CYCLE!` and errors like `#DIV/0!` propagate as values. Copy/paste uses a Visitor that shifts relative references and leaves absolute ones, and undo is a stack of edit commands. A property test checks that incremental results always equal a full recalculation, and a 10,000-cell chain recalculates in under 100 ms.

Key terms to know:

- **Dependency graph** — cell to the cells it reads, and the reverse map of cell to the cells that read it.
- **Transitive dependents** — every cell affected directly or indirectly by a change, found by BFS.
- **Topological order** — an order in which every cell comes after all its inputs.
- **Kahn's algorithm** — repeatedly take nodes with no remaining inputs; leftovers mean a cycle.
- **Interpreter / Composite** — formula trees whose nodes evaluate themselves.
- **Visitor** — rewrites references on paste or extracts dependencies without changing node classes.
- **Relative vs absolute reference** — `A1` shifts on paste; `$A$1` does not.
- **Error values** — `#DIV/0!`, `#REF!`, `#VALUE!`, `#NAME?`, `#CYCLE!` treated as values that flow through formulas.
- **Volatile function** — `NOW()` or `RAND()`, recalculated on every change.

Q: How do you recalculate efficiently after one cell changes?

A: Find the transitive dependents through a reverse dependency graph, topologically sort that subset, and evaluate in that order. First update the edited cell's own dependencies, because its new formula may read different cells.

Q: How do you detect circular references?

A: Kahn's algorithm leaves unprocessed nodes when there is a cycle; mark them with a cycle error. A strongly-connected-components pass can separate cells actually on the cycle from cells merely downstream of it.

Q: How do you adjust formulas on copy/paste?

A: A visitor rewrites relative references by the row and column offset, leaving absolute ones alone. A reference shifted off the sheet becomes `#REF!`.

Q: Why not just recalculate every cell in row order?

A: Row order is wrong whenever a cell depends on a cell below or to the right, so it would show stale values, and recalculating all 100,000 cells on every keystroke is far too slow. Topological order over only the affected cells is both correct and minimal.

Q: Code-level: what does Kahn's algorithm look like over the affected set?

A: Count in-set inputs, start from cells with none, and release dependents as you go.

```
Map<CellRef, Integer> indeg = new HashMap<>();
for (var c : affected) indeg.put(c, (int)
graph.inputs(c).stream().filter(affected::contains).count());
Deque<CellRef> ready = new ArrayDeque<>(affected.stream().filter(c -> indeg.get(c) == 0).toList());
List<CellRef> order = new ArrayList<>();
while (!ready.isEmpty()) { var c = ready.poll(); order.add(c);
    for (var d : graph.dependents(c)) if (affected.contains(d) && indeg.merge(d, -1, Integer::sum) ==
0) ready.add(d); }
// affected.size() > order.size()  ->  the remainder is in or behind a cycle
```

Q: How do range formulas like `=SUM(A1:A1000)` affect the graph?

A: Expanding a range into 1,000 edges is simple but heavy for big ranges. A refinement stores range dependencies separately and asks "is the changed cell inside any watched range?" with an interval structure per column. Start with expanded edges, measure, then refine.

Q: `double` or `BigDecimal` for cell values?

A: `double` matches what users see in real spreadsheets, including their rounding quirks such as `0.1 + 0.2`, and is fast. `BigDecimal` is exact but slower and would give different answers from the tools users compare against, so `double` with display rounding is the usual choice.

Q: What breaks first at 10x sheet size?

A: A cell that everything depends on makes one edit recalculate the whole sheet, and expanded range edges consume memory. Independent branches of the affected subgraph can be evaluated in parallel, and range indexing cuts the edge count.

Q: How do you test the engine?

A: Parser tests from tables of formulas and expected trees; a property test that after random edits incremental values equal a full recalculation from scratch; cycle tests including self-reference and long cycles; and benchmarks with long chains and wide fan-outs.

Common mistakes in answers:

- Recalculating everything, or in row order.

- Forgetting to update the edited cell's own outgoing dependencies.
- Throwing exceptions for `#DIV/0!` instead of propagating error values.

TL;DR

Formulas parsed to expression trees, a two-way dependency graph, incremental recalculation by topological order over affected cells, and cycles detected by Kahn's algorithm.

40. Concurrent Web Crawler

Level: Advanced · **Time:** 3 weeks · **Prerequisites:** Ch 12, Ch 13, Ch 20

What it is

A polite, concurrent web crawler: starting from seed URLs, it fetches pages, extracts links, and keeps crawling within limits — respecting `robots.txt`, limiting requests per host, de-duplicating URLs, retrying failures and stopping cleanly. It uses virtual threads for I/O and structured concurrency to keep tasks organised.

The problem it solves

Crawling is the textbook concurrent I/O problem: thousands of slow network requests that should overlap, but with constraints — never hammer one site, never fetch the same URL twice, never run out of memory on an infinite web. The design forces you to separate the **frontier** (what to crawl next, with per-host politeness), **fetching**, **parsing** and **storage**, and to make shutdown and cancellation correct.

Real-world examples

- The Robots Exclusion Protocol (RFC 9309) standardises `robots.txt`, including how crawlers match user agents and allow/disallow rules.
- crawler4j is an open-source Java crawler with politeness delays, robots handling and a pluggable page processor.
- Java 25's structured concurrency (JEP 505), still a preview API, treats a group of related subtasks as one unit for cancellation and error handling — a good fit for "fetch page, then fetch its resources".

Requirements


Functional

- Seeds, max depth, max pages, allowed domains or URL patterns.
- URL normalisation (lowercase host, remove fragments, resolve relative links, sort query parameters optionally).
- De-duplication of seen URLs.
- Politeness: per-host minimum delay (e.g. 1 s), per-host concurrency of 1–2, `robots.txt` fetched and cached per host, `Crawl-delay` respected where present.
- Fetch with timeouts, redirects (limited), retries with backoff for 5xx and network errors.
- Extract links from HTML; store page metadata (URL, status, title, outlinks, fetch time).
- Graceful stop: finish in-flight fetches, persist the frontier, resume later.

Non-functional

- Sustain 200 pages per second across many hosts on a laptop (against a local test server).
- Memory bounded: seen-set and frontier sizes capped or spilled to disk.
- No more than one request per host per delay interval — verified by a test server log.

The architecture



- **Crawler** — runs the worker loop on virtual threads; owns lifecycle and shutdown.
- **Frontier** — per-host queues plus a priority queue of hosts ordered by `nextAllowed`; hands out only URLs whose host is ready.
- **HostQueue** — URLs for one host and its politeness timer.
- **SeenSet** — de-duplication; exact set or Bloom filter for memory efficiency.
- **RobotsCache** — fetch, parse and cache robots rules per host.
- **Fetcher** — wraps `java.net.http.HttpClient` with timeouts, redirects and retries.
- **LinkExtractor / PageSink / UrlNormalizer** — parsing, storage and canonical URLs as pluggable parts.

Data model

Type	Notes
`UrlTask`	record: URI, depth, discovered-from, attempt
`FetchResult`	sealed: `Ok(status, headers, body)`, `Redirect(location)`, `Failed(reason, retryable)`
`PageRecord`	URL, status, title, outlinks, fetched at, content hash
`RobotsRules`	allow/disallow path rules for the matched user agent, crawl delay, fetched at

Tech stack

Component	Choice	Why
HTTP	`java.net.http.HttpClient`	built in, async or blocking
Concurrency	virtual threads + `Semaphore` for global limit	thousands of blocking fetches
Task grouping	`StructuredTaskScope` (preview in Java 25)	scoped cancellation
HTML parsing	jsoup (current version)	robust real-world HTML
Tests	JUnit 6, AssertJ, local test HTTP server (`com.sun.net.httpserver`)	deterministic web

Milestones

1. **Normaliser and seen-set.** *Done when:* URLs differing only by fragment, case of host or default port are treated as the same.
2. **Single-threaded crawl of a local site.** *Done when:* a 1,000-page generated test site is crawled completely with correct depth limits.
3. **Politeness frontier.** *Done when:* the test server's access log shows no host received two requests closer than the configured delay, while multiple hosts are crawled in parallel.
4. **Robots and retries.** *Done when:* disallowed paths are never requested, and a page returning 503 twice then 200 is fetched on the third attempt with backoff.
5. **Concurrency, stop and resume.** *Done when:* 500 virtual-thread workers reach the throughput target on the local server, `stop()` completes in-flight work within 5 s, and resume continues from the saved frontier without refetching.

Deep dive: the hard parts

A politeness-aware frontier. A single global queue makes workers pick URLs from the same host back to back. Instead keep one queue per host and a priority queue of hosts keyed by the earliest time they may be fetched again. `next()` takes the host at the head; if its time has not arrived, the worker waits until it has (or until a new host is added). After a fetch, the host's next-allowed time is set to now plus the delay and it goes back into the priority queue. This guarantees politeness by construction.

Concurrency with virtual threads. Blocking HTTP calls on virtual threads are cheap, so code can be simple and sequential per task. Limit global in-flight fetches with a `Semaphore` (sockets and memory are finite). Since JEP 491 (Java 24), blocking inside `synchronized` no longer pins a virtual thread to its carrier (platform) thread in most cases — pinning remains for native frames and class initialisation. On Java 21, `synchronized` around a blocking call *does* pin, so prefer `ReentrantLock` there. Either way, the frontier's timed waits are clearer with `ReentrantLock` and `Condition`.

De-duplication at scale. A `ConcurrentHashMap.newKeySet()` of URL strings grows without bound. A Bloom filter uses a few bits per URL with a tunable false-positive rate (some new URLs are wrongly skipped, never duplicates fetched) — acceptable for many crawls. Also hash page content to skip duplicate pages under different URLs.

Clean shutdown. `stop()` sets a flag so workers stop taking new tasks, waits for in-flight fetches (with a deadline), then snapshots the frontier and seen-set to disk. Structured concurrency helps: closing the scope cancels outstanding subtasks and waits for them, so no fetch outlives the crawl.

Testing strategy

A local HTTP test server generating sites with known link graphs, configurable latency, errors and `robots.txt`. Assertions on the server's access log for politeness. Unit tests for normalisation and robots matching from RFC 9309 examples. Load test measuring pages per second.

Trade-offs, scaling and failure modes

Breadth-first crawling finds important pages early; depth-first finds deep content but risks spider traps (infinite calendars, session ids in URLs) — cap depth and URL length and detect repeating path patterns. A single process is bounded by one machine; distributed crawlers partition hosts across nodes (by host hash) so politeness stays local. Being a good citizen matters: identify your crawler in the `User-Agent`, honour robots rules and back off on errors.

Stretch goals

- Persist the frontier in an embedded store and crawl millions of URLs.
- Re-crawl scheduling based on how often pages change.
- Distributed mode: several crawler processes sharing hosts by consistent hashing.

Skills practised

- Ch 12 — Concurrency concepts: virtual threads, semaphores, conditions.
- Ch 13 — Concurrency problems: concurrent Bloom filter, blocking queues.
- Ch 20 — Components: rate limiter ideas applied per host.
- Ch 4 — SOLID principles: pluggable fetcher, extractor and sink.

In the interview

30-second answer: I built a polite concurrent web crawler: the frontier keeps one URL queue per host plus a priority queue of hosts ordered by the next time each may be fetched, so politeness is guaranteed by construction while many hosts are crawled in parallel. Workers are virtual threads doing simple blocking HTTP calls, with a `Semaphore` capping global in-flight fetches, and URLs are normalised and de-duplicated, optionally with a Bloom filter to bound memory. `robots.txt` is fetched and cached per host, 5xx and network errors retry with backoff, and `stop()` finishes in-flight work, then saves the frontier so the crawl can resume. Against a local test server it sustained the throughput target, and the server's access log proves no host was hit faster than the delay.

Key terms to know:

- **Frontier** — the set of URLs waiting to be crawled, organised per host here.
- **Politeness** — a minimum delay and limited concurrency per host.
- **`robots.txt` (RFC 9309)** — a site's rules about which paths crawlers may fetch.
- **URL normalisation** — lowercase host, drop fragment and default port, resolve relative links.
- **Bloom filter** — a compact bit array answering "maybe seen" or "definitely not seen"; false positives skip a few new URLs.
- **Virtual threads** — cheap threads for blocking I/O; thousands of fetches without callback code.
- **Semaphore** — a counter of permits used to cap global in-flight requests.
- **Pinning** — a virtual thread stuck to its carrier thread; since JEP 491 (Java 24) `synchronized` no longer pins in most cases.
- **Spider trap** — infinite URL spaces such as calendars or session ids.
- **Structured concurrency** — subtasks owned by a scope that cancels and waits for them (preview in Java 25).

Q: How do you stay polite to each host while crawling many hosts in parallel?

A: Per-host queues and a priority queue of hosts by next-allowed time; a worker only takes a URL from a host whose delay has passed. After a fetch, the host's next-allowed time becomes now plus the delay and it goes back into the priority queue.

Q: Why virtual threads here?

A: The work is mostly waiting on network I/O; virtual threads let you write simple blocking code for thousands of concurrent fetches cheaply. The JVM parks a virtual thread during blocking I/O and frees its carrier thread for other work.

Q: How do you avoid crawling the same page twice with limited memory?

A: Normalise URLs and use a Bloom filter for the seen-set, accepting a small chance of skipping a new URL but never fetching a duplicate; hash content to catch duplicate pages under different URLs.

Q: If threads are cheap, why limit concurrency with a semaphore?

A: Virtual threads are cheap, but sockets, file descriptors, memory for page bodies and the target servers are not. A global semaphore bounds those resources, and per-host limits protect each site.

Q: Code-level: what does a worker look like?

A: One virtual thread per task, bounded by a semaphore.

```
try (var exec = Executors.newVirtualThreadPerTaskExecutor()) {
    while (running) {
        UrlTask t = frontier.next();          // blocks until some host is ready
        permits.acquire();
        exec.submit(() -> { try { process(t); } finally { permits.release(); } });
    }
}   // close() waits for submitted tasks to finish
```

Q: Does `synchronized` still pin virtual threads?

A: Since JEP 491 in Java 24, blocking inside `synchronized` no longer pins a virtual thread to its carrier in most cases; pinning remains for native frames and class initialisation. On Java 21 it does pin, so `ReentrantLock` is the safe portable choice, and its `Condition` makes the frontier's timed waits clearer anyway.

Q: What happens with spider traps or a host that keeps failing?

A: Cap depth and URL length and detect repeating path patterns, so infinite calendars do not eat the crawl. Failing hosts get exponential backoff, and after repeated failures the host is parked for a while instead of retried immediately.

Q: What changes at 10x or 100x pages?

A: The in-memory seen-set and frontier run out first, so spill the frontier to an embedded store and use a Bloom filter. Beyond one machine, partition hosts across nodes by host hash so each host's politeness stays on one node.

Q: How do you test a crawler without hitting the real web?

A: A local HTTP test server generates sites with known link graphs, latency, errors and `robots.txt`. Tests assert the server's access log shows politeness, that disallowed paths are never requested, and that a 503-503-200 page succeeds on the third attempt; normalisation and robots matching are unit-tested from RFC 9309 examples.

Common mistakes in answers:

- One global FIFO queue, which fetches the same host back to back.
- "Virtual threads mean no limits", ignoring sockets, memory and politeness.
- Treating unnormalised URLs as distinct, which crawls duplicates.

TL;DR

A host-aware frontier that enforces politeness by construction, virtual-thread workers bounded by a semaphore, robots and retries, compact de-duplication and a clean, resumable shutdown.

Appendix: Concepts you need

Every technical term, acronym, library and tool that appears in the 40 briefs above, in alphabetical order and in plain English, so you can start any project without stopping to look words up. Each entry lists the projects that use the term and, where this book teaches it, a link to the chapter. Broader system-design ideas (latency, caching, queues, replication, eventual consistency) are explained in depth in System Design Fundamentals.

A

- **Abstraction** — Showing callers only what they need (an interface) and hiding how the work is done. Used in project 6. (Ch 2)
- **Action (state machine)** — A side effect that runs when a transition happens, such as assigning a rider or issuing a refund. Used in project 20. (Ch 11)
- **Active expiry by sampling** — A background task that checks a random handful of keys with TTLs and deletes the expired ones, repeating if many were stale. Used in project 26. (Ch 13)
- **Actor** — Two meanings: in requirements, whoever triggers a use case (customer, rider, system); in concurrency, an object owned by one thread that other threads talk to only by sending it messages. Used in projects 7, 20. (Ch 1, Ch 12)
- **Adapter pattern** — A wrapper that converts a vendor's interface (a bank network, an SMS provider, a card terminal) into the interface your code expects. Used in projects 5, 18, 22, 33, 37. (Ch 9)
- **Ageing** — Gradually raising the priority of a request the longer it waits, so it cannot starve. Used in project 11. (Ch 12)
- **Agenda / conflict resolution** — In a rules engine, the list of rules currently able to fire, plus the rule (priority, recency) for choosing which fires first. Used in project 31.
- **Aggregate** — A cluster of objects changed as one unit through a single root object that enforces all the rules, such as an `Auction` and its bids. Used in projects 17, 20, 24, 37. (Ch 5)
- **Aggregation** — A "has-a" link where the part can exist without the whole (a member and the loans that refer to it). Used in project 3. (Ch 3)
- **All-or-nothing reservation** — Either every requested item (seats, ingredients, stock lines) is reserved, or none is and nothing changes. Used in projects 9, 12, 26. (Ch 12, Ch 15)
- **All-red clearance** — A short period with every traffic light red so the junction empties before the next group gets green. Used in project 7. (Ch 14)
- **Alpha-beta pruning** — An optimisation of minimax that skips branches which cannot change the final choice. Used in projects 4, 30. (Ch 17)
- **Annotation** — A marker like `@Inject` or `@Test` attached to code that tools or frameworks read. Used in projects 1, 8, 15, 16, 23, 26, 35, 36. (Ch 2)
- **Anti-pattern** — A common solution that looks reasonable but reliably causes trouble, such as a service locator. Used in project 36. (Ch 8)
- **Anti-sniping** — Extending an auction's end time when a bid arrives in the last moments, so others can respond. Used in project 24. (Ch 19)
- **API** — Application Programming Interface: the public methods or endpoints other code is allowed to call. Used in projects 10, 14, 16, 18, 23, 27, 33–35, 39, 40. (Ch 2)
- **Appender / Layout** — Logging roles: an appender sends a log event somewhere (console, file); a layout turns the event into text or JSON. Used in projects 1, 12, 16. (Ch 20)
- **Append-only file (AOF)** — A file of every write command, replayed after a crash to rebuild an in-memory store. Used in project 26.
- **Append-only log** — A record that only ever grows at the end; nothing is updated or deleted, so history can be replayed. Used in projects 8, 10, 17, 22, 25, 26, 32, 34. (Ch 20)
- **Application service** — The class that runs one use case by coordinating domain objects, repositories and rules, without holding business rules itself. Used in projects 3, 10, 19, 21.
- **ArchUnit** — A Java library that checks architecture rules (which package may call which) as ordinary unit tests. Used in project 37.
- **ArrayBlockingQueue** — A fixed-capacity, thread-safe queue backed by an array; producers wait when it is full. Used in projects 16, 17, 27, 28. (Ch 12)
- **AssertJ** — A Java testing library for fluent, readable assertions such as `assertThat(x).isEqualTo(3)`. Used in projects 1–6, 8–26, 28–40. (Ch 6)
- **Async appender** — A logging wrapper that queues events and writes them on a background thread so callers don't wait for I/O. Used in project 16. (Ch 20)

- **At-least-once delivery** — A message or job may be delivered more than once but is never lost; the receiver must be idempotent. Used in projects 17, 18, 33, 37. (Ch 20)
- **ATM** — Automated teller machine: the cash machine that dispenses money from a bank account. Used in project 5. (Ch 14)
- **Atomic operation** — A step that completes entirely or not at all, with no other thread able to see it half-done. Used in projects 1, 8–10, 12, 14, 16, 19, 20, 25–27, 29, 31, 37, 38. (Ch 12)
- **Atomic rename / move** — Write to a temporary file and then rename it in one step, so readers see either the old file or the new one, never half of it. Used in project 8.
- **Atomic variable (AtomicInteger, AtomicLong, AtomicReference)** — Java classes that update a single value safely across threads without locks, using compare-and-set. Used in projects 14, 17, 27, 31, 35, 38. (Ch 12)
- **Authorisation (payment)** — Asking the bank to approve and set aside an amount; the money is actually taken later (capture) or released (void). Used in projects 5, 34, 37. (Ch 14, Ch 19)
- **Authorise vs capture** — Reserving money on a card first, then taking it only when the order is confirmed. Used in projects 34, 37.
- **Autovacuum** — PostgreSQL's background process that cleans up dead row versions left by updates and deletes. Used in project 33.
- **Available balance** — Posted balance minus money currently held for pending payments. Used in project 34. (Ch 14)
- **Awaitility** — A testing helper for asynchronous code that polls until a condition becomes true or a timeout passes. Used in project 17.

B

- **Backpressure** — Slowing down or refusing a fast producer when the consumer can't keep up, usually via a bounded queue. Used in projects 16, 17, 27. (Ch 12)
- **Backtracking** — Searching by trying a choice, and undoing it if it leads to a dead end. Used in projects 2, 5.
- **Batch matching / Hungarian algorithm** — Solving many rider-driver pairings together to minimise the total pickup time, instead of one rider at a time. Used in project 29.
- **Benchmark (micro-benchmark)** — A controlled timing test of a small piece of code; JMH runs these correctly on the JVM. Used in projects 14–17, 23, 26, 27, 31–33, 35, 36, 38, 39.
- **BFS / DFS** — Breadth-first search visits neighbours level by level; depth-first search goes down one path before backing up. Used in projects 23, 36, 39, 40.
- **Bid / ask** — In trading, a buy order (bid) and a sell order (ask); in auctions, a bid is an offer to pay. Used in projects 24, 28. (Ch 19)
- **Bid increment** — The smallest amount by which a new auction bid must beat the current price. Used in project 24. (Ch 19)
- **BigDecimal** — Java's exact decimal number type, used for money when cents in a `long` are not enough. Used in projects 1, 10, 22, 31, 39. (Ch 1)
- **Big-O notation** — Shorthand for how time or memory grows with input size: O(1) constant, O(log n) slow growth, O(n) proportional. Used in projects 1, 3, 4, 6, 8, 11, 13–15, 17, 21, 26, 28, 30, 32, 35, 38.
- **Binding / key (DI)** — In a DI container, a rule saying which class or factory supplies a requested type (the key). Used in project 36. (Ch 11)
- **BlockingQueue** — A thread-safe queue whose `put` waits when full and `take` waits when empty; the backbone of producer–consumer. Used in projects 16, 17, 26–28. (Ch 12)
- **Bloom filter** — A compact bit array that answers "definitely not seen" or "maybe seen"; it never misses an item it has seen but may give false positives. Used in project 40. (Ch 13)
- **Bounded queue** — A queue with a maximum size, so it pushes back on producers instead of growing until memory runs out. Used in projects 16, 17, 27. (Ch 12)

- **Build tool (Maven, Gradle)** — Programs that download libraries, compile the code, run the tests and package the result with one command. Used in project 1.
- **Builder pattern** — Builds an object with many optional fields step by step and validates it once in `build()`. Used in projects 8, 9, 18, 35, 36. (Ch 8)
- **Bulkhead** — A cap on concurrent calls to one dependency so it can't use up every thread (named after ship compartments). Used in project 35.

C

- **Cache** — A fast store of recently used results so they don't have to be fetched or computed again. Used in projects 12, 15, 16, 21, 22, 25, 26, 34–36, 38–40. (Ch 20)
- **Cache stampede (thundering herd)** — Many threads miss the same key at once and all hit the slow loader together. Used in projects 15, 38. (Ch 20)
- **Caffeine** — A high-performance Java caching library, used as the benchmark to compare your cache against. Used in project 15. (Ch 20)
- **Cancellation** — Stopping a pending task or timer before it runs, via its `Future` or `ScheduledFuture` handle. Used in projects 2, 7, 12, 17, 19–21, 24, 27–29, 33, 34, 37, 40.
- **CAS (compare-and-set)** — An atomic "change this value only if it still equals what I read"; the building block of lock-free code. Used in projects 14, 27, 29, 35, 38. (Ch 12)
- **CAS state machine** — A lifecycle whose state field moves only through compare-and-set, so exactly one thread wins each transition. Used in project 27. (Ch 12)
- **Cascading failure** — A slowdown in one service spreading upstream as callers wait, pile up and fail too. Used in project 35.
- **Category vs instance** — A type of thing that customers choose (a book title, a car category) versus one physical item (a copy, a specific car). Used in projects 3, 19. (Ch 15)
- **Chain of Responsibility** — A pattern passing a request along linked handlers, each of which may handle it, pass it on, or stop it. Used in projects 5, 16, 18. (Ch 10)
- **Check-then-act race** — A bug where a thread checks a condition and then acts, but another thread changes things in between. Used in project 9. (Ch 12)
- **Circuit breaker** — A wrapper that stops calling a failing dependency for a while so callers fail fast, then tests recovery with a few trial calls. Used in projects 18, 35.
- **Class diagram** — A UML picture of classes, their fields and methods, and how they relate. Used in all 40 projects. (Ch 3)
- **CLI (command-line interface)** — A program driven by typed text commands in a terminal rather than a graphical window. Used in projects 2, 3, 8, 13, 23, 33. (Ch 21)
- **Clock (java.time.Clock)** — Java's injectable source of the current time; tests pass a fixed or adjustable clock to control "now". Used in projects 1, 3, 24, 26, 30. (Ch 15)
- **Closed / open / half-open** — The three circuit-breaker states: calls flow normally; calls are rejected; a few trial calls test whether the dependency has recovered. Used in project 35.
- **Command merging** — Letting consecutive small edits (typing letters) combine into one undo step. Used in project 32.
- **Command pattern** — Wraps an action as an object with `execute` (and often `undo`), so it can be queued, logged, replayed or undone. Used in projects 4, 8, 23, 26, 28, 30, 32. (Ch 10)
- **Comparator** — An object that decides the order of two values, used to sort or to order a `TreeMap` or priority queue. Used in projects 10, 19, 22, 28.
- **Compensating action** — A new action that undoes the business effect of an earlier one (a refund, a release, a reversal), used when a real rollback is impossible. Used in projects 5, 12, 25, 37. (Ch 15)
- **Compensating entry** — A new ledger line equal and opposite to an earlier one, which cancels it without deleting history. Used in project 25.
- **CompletableFuture** — A Java future that can be completed by any thread and chained with follow-up steps. Used in projects 10, 15, 35. (Ch 12)

- **Composable predicate** — Small true/false tests that combine with `and`, `or` and `not` into bigger rules. Used in projects 8, 21–23, 35. (Ch 11)
- **Composite edit** — Several edits grouped into one command so a single undo reverses them all. Used in project 32.
- **Composite pattern** — Lets single objects and groups (trees) share one interface, so `And(Not(...), ...)` or a folder of files is handled uniformly. Used in projects 4, 8, 23, 31, 32, 39. (Ch 9)
- **Composition** — A strong "owns" link: the whole creates its parts and they die with it. Used in projects 1, 3, 9, 25, 35. (Ch 3)
- **Composition over inheritance** — Reusing behaviour by holding and delegating to other objects instead of subclassing. Used in projects 3, 9, 25. (Ch 5)
- **Concurrency** — Several tasks in progress at the same time, often touching shared data. Used in projects 1, 3, 7, 9–29, 31–40. (Ch 12)
- **ConcurrentHashMap** — A thread-safe Java map with atomic helpers such as `compute`, `merge` and `putIfAbsent`. Used in projects 10, 12, 14–16, 20, 25, 29, 36, 37, 40. (Ch 12)
- **ConcurrentLinkedQueue / Deque** — Lock-free thread-safe queues; each `poll()` hands an element to exactly one thread. Used in projects 1, 11, 38. (Ch 12)
- **Conditional update** — Change a record only if it is still in the expected state ("release if still held by hold 42"); otherwise do nothing. Used in projects 12, 29, 37. (Ch 15)
- **Conflict matrix** — A table recording which traffic approaches must never be green at the same moment. Used in project 7.
- **Connection pool** — A set of open database connections that threads borrow and return, because opening a new one is slow. Used in projects 33, 38. (Ch 8)
- **Connection timeout** — How long a caller waits for a free pooled connection before giving up with an error. Used in project 38.
- **Connection validation** — Checking that an idle pooled connection still works before lending it out. Used in project 38. (Ch 8)
- **Consumer group** — A set of subscribers that share a topic's messages so each message goes to only one of them. Used in project 17. (Ch 20)
- **Context (State pattern)** — The object whose behaviour depends on its current state object, such as the vending machine. Used in project 2. (Ch 11)
- **Core / max pool size** — The threads a pool keeps alive at all times versus the most it may start when the queue is full. Used in projects 27, 38. (Ch 12)
- **Cost function** — A formula that scores each option (distance plus penalties) so the cheapest can be picked. Used in project 11.
- **Count-based vs time-based window** — Measuring failures over the last N calls versus over the last N seconds. Used in project 35.
- **CountDownLatch** — A one-time gate that opens when a counter reaches zero; useful to start threads together in tests. Used in projects 9, 10, 27. (Ch 12)
- **Crossed book** — An order book whose best buy price is at or above its best sell price; matching must never leave it that way. Used in project 28. (Ch 19)
- **CRUD** — Create, read, update, delete: the four basic storage operations. Used in project 8.
- **CSV** — Comma-separated values: a plain-text table, one row per line. Used in project 39.
- **Currency** — The unit of money (USD, EUR, INR); amounts in different currencies must never be added directly. Used in projects 1, 5, 10, 13, 34. (Ch 7)
- **Cycle detection** — Finding a loop in links or dependencies (A needs B needs A) before it causes infinite work. Used in projects 6, 7, 10, 23, 26, 31, 36, 39.

D

- **Daily cap** — A limit on how much of something (reputation, withdrawals) can be earned or used per day. Used in project 25.

- **Data over code** — Describing variation (board layouts, rules) as data that the program loads, instead of writing a class for each case. Used in project 6.
- **Daylight saving time (DST)** — Seasonal clock shifts that make some local times happen twice or not at all. Used in projects 18, 21, 27.
- **Dead-letter topic / queue** — Where messages or jobs go after too many failed attempts, so someone can inspect them. Used in projects 17, 18, 33. (Ch 20)
- **Deadlock** — Threads each holding a lock the other needs, so all wait forever. Used in projects 10, 12, 24, 27, 34, 36, 37. (Ch 12)
- **Debt simplification** — Replacing many IOUs in a group with fewer payments that leave everyone's net balance the same. Used in project 13. (Ch 20)
- **Decorator pattern** — A wrapper with the same interface that adds behaviour and delegates the rest, and can be stacked. Used in projects 1, 9, 15, 16, 35, 36. (Ch 9)
- **DelayQueue** — A Java blocking queue that releases each item only after its delay has passed. Used in projects 12, 18, 27. (Ch 12)
- **Dependency graph** — A map of what depends on what (cells reading cells, classes needing classes), used to order work and find cycles. Used in projects 36, 39.
- **Dependency injection (DI)** — Handing an object its collaborators from outside, usually through the constructor, instead of letting it create them. Used in projects 1, 3, 6, 7, 10, 14, 15, 17, 26, 35–38. (Ch 11)
- **Dependency Inversion Principle** — High-level policy depends on interfaces it owns; low-level details implement them. Used in projects 4, 6, 36, 37. (Ch 4)
- **Deque / ArrayDeque** — A double-ended queue: add or remove at either end; Java's usual stack and queue. Used in projects 1, 4, 14, 26, 28, 32, 39, 40.
- **Derived balance** — A balance computed from the history of movements (and maybe cached), rather than stored as the only truth. Used in projects 10, 22, 34. (Ch 21)
- **Design pattern** — A named, reusable solution shape for a recurring design problem. Used in projects 1, 2, 4, 5, 7–11, 13–20, 22–27, 29–32, 35–40. (Ch 8)
- **Determinism** — The same inputs always produce the same outputs, which makes tests, replays and debugging reliable. Used in projects 1, 6, 7, 11–13, 17, 22, 23, 28, 35, 39, 40. (Ch 17)
- **Direct hand-off** — Passing a returned item straight to a thread already waiting for it, instead of putting it back in a shared queue. Used in project 38. (Ch 12)
- **Discrete-tick simulation** — A simulation where time jumps forward in fixed steps, making each run reproducible. Used in projects 11, 28. (Ch 14)
- **Dispatcher** — The component that decides which worker or vehicle takes each request. Used in projects 11, 29. (Ch 14)
- **Domain event** — A record that something business-relevant happened (`OrderAccepted`, `VoteCast`) that other parts react to. Used in projects 20, 25. (Ch 5)
- **Double booking** — Two customers confirmed for the same seat, room or time slot; the core bug booking systems must prevent. Used in projects 12, 21. (Ch 15)
- **Double-entry bookkeeping** — Every money movement is recorded as matching debits and credits that sum to zero. Used in project 34. (Ch 21)
- **Doubly linked list** — A chain of nodes linked both forwards and backwards, so any node can be unlinked in O(1); sentinels are dummy head and tail nodes. Used in projects 15, 28. (Ch 20)
- **Drools / Rete algorithm** — Drools is a well-known Java rules engine; Rete is its classic algorithm that shares condition checks across rules. Used in project 31.
- **Durability** — The promise that saved data survives a crash or power loss. Used in projects 5, 12, 17, 18, 20, 25, 26, 28, 33, 37.
- **Dynamic programming** — Solving a problem by building answers to small sub-problems and reusing them. Used in project 2. (Ch 14)
- **Dynamic proxy** — A class generated at run time (`java.lang.reflect.Proxy`) that implements an interface and forwards each call through one handler. Used in projects 36, 38. (Ch 9)

E

- **Encapsulation** — Keeping data private so only the owning class can change it, and enforcing its rules there. Used in project 1. (Ch 2)
- **Entity–relationship diagram** — A diagram of database tables (entities) and the keys linking them. Used in projects 33, 34. (Ch 3)
- **Entry vs transaction (ledger)** — An entry is one debit or credit line on one account; a transaction is the balanced group of entries posted together. Used in projects 10, 25, 34. (Ch 21)
- **Enum** — A Java type with a fixed set of named values, which can carry fields and methods. Used in projects 1, 2, 4, 7–9, 11, 16, 25, 29, 30, 35, 39. (Ch 2)
- **EnumMap** — A fast Java map whose keys are the values of one enum. Used in project 20. (Ch 2)
- **equals / hashCode** — The methods that define when two objects count as the same value; equal objects must have equal hash codes. Used in projects 20, 22, 25, 29. (Ch 2)
- **Error values (spreadsheet)** — Results like `#DIV/0!` or `#REF!` that are treated as values and flow through dependent formulas. Used in project 39.
- **Escrow** — Holding money apart until a deal is final (coins kept separate from the cash box until the item drops). Used in projects 2, 25. (Ch 14)
- **ETA** — Estimated time of arrival. Used in project 20.
- **Event sourcing** — Storing the list of events and rebuilding current state by replaying them. Used in projects 20, 28. (Ch 11)
- **Eventual consistency** — Different parts of the system may disagree for a short time but catch up shortly afterwards. Used in projects 17, 22, 25, 37.
- **Eviction policy** — The rule a full cache uses to choose which entry to throw out (LRU, LFU). Used in projects 14, 15, 26, 38. (Ch 20)
- **Exactly-once** — Each message has its effect exactly one time; in practice achieved by at-least-once delivery plus idempotent handling. Used in projects 17, 18, 33. (Ch 20)
- **Exception** — An object thrown to signal an error, which travels up the call stack until code catches it. Used in projects 1, 7, 10, 16, 17, 21, 27, 35, 39. (Ch 6)
- **Exception date** — One occurrence of a repeating event that is skipped or changed. Used in project 21.
- **ExecutorService** — Java's interface for running submitted tasks on a pool of threads. Used in projects 7, 9, 10, 12, 17, 18, 20, 24, 27, 29, 40. (Ch 12)
- **Expiry** — Automatically ending something (a hold, a cache entry, a lease) after a deadline. Used in projects 3, 5, 10, 12, 15, 26, 27, 29, 33, 34, 37, 38. (Ch 13, Ch 15)
- **Exponential backoff with jitter** — Waiting longer after each retry (doubling) plus a random amount, so retries don't all hit at once. Used in projects 17, 18, 33, 35, 38, 40. (Ch 6)

F

- **Facade pattern** — One simple class in front of several collaborators, so callers have a single entry point. Used in projects 1, 5, 11, 16, 17, 32, 39. (Ch 9)
- **Factory pattern** — A class or method whose job is to create the right object from some input, hiding the concrete class. Used in projects 6, 9, 14, 16, 18, 36, 38. (Ch 8)
- **Facts (rules engine)** — The input data that rules are evaluated against, such as a customer and an order. Used in project 31.
- **Fail fast** — Detect a problem early and report it loudly instead of carrying on with bad data. Used in projects 10, 35. (Ch 5)
- **Fail open / fail closed** — When a safety check's backing store is down: let traffic through (open) or block it (closed). Used in project 14.
- **Fail safe** — On error, move to a known safe mode (flashing lights) rather than an unknown state. Used in project 7.

- **Failure-rate and slow-call thresholds** — The percentage of failed or slow calls in the recent window that makes a circuit breaker open. Used in project 35.
- **Fake vs mock** — Test doubles: a fake is a simple working stand-in; a mock records calls so the test can verify them. Used in projects 1–3, 5, 7, 14, 15, 18, 27, 35, 37, 38. (Ch 6)
- **FEN / PGN** — Standard chess text formats: FEN describes one position on one line; PGN records a whole game. Used in project 30. (Ch 17)
- **FIFO** — First in, first out: the oldest waiting item is served first, like a queue. Used in projects 3, 15, 28, 38, 40. (Ch 12)
- **FileChannel / fsync** — Low-level Java file access; `force` (fsync) makes the OS write data to disk so a crash cannot lose it. Used in projects 16, 26, 32.
- **FileVisitor / walkFileTree** — Java's callback interface for walking a directory tree, with hooks before, during and after each folder. Used in project 23. (Ch 21)
- **Filter chain** — A Chain of Responsibility of filters, each of which can accept, reject or pass an item to the next. Used in project 16. (Ch 10)
- **Finite state machine** — A fixed set of states with the allowed transitions between them, triggered by events. Used in projects 2, 3, 5, 7, 11, 12, 18–20, 24, 27–29, 35, 37, 38. (Ch 3, Ch 11)
- **Fixed rate vs fixed delay** — Scheduling the next run from the previous planned start, or from when the previous run ended. Used in projects 14, 27.
- **Fixed window counter** — A rate limit that counts requests per clock window; simple but can allow double the limit around a boundary. Used in project 14. (Ch 20)
- **Flaky test** — A test that sometimes passes and sometimes fails without any code change, usually because of time or threads. Used in projects 1, 7, 35. (Ch 6)
- **Forward chaining** — Rules fire, change the facts, and those changes may make more rules fire, until nothing changes. Used in project 31.
- **Frontier** — A web crawler's list of URLs still waiting to be fetched. Used in project 40.
- **Future / ScheduledFuture** — A handle to a result that may not exist yet; you can wait for it, check it or cancel it. Used in projects 7, 27. (Ch 12)

G

- **Gap buffer** — A text buffer with an empty gap at the cursor so typing there is O(1). Used in project 32.
- **Garbage collection** — The JVM automatically freeing memory of objects that nothing refers to any more. Used in projects 15, 28, 30. (Ch 12)
- **Generics** — Type parameters such as `List<T>` that make code reusable and type-safe. Used in projects 15, 36, 38. (Ch 2)
- **Git** — The version-control tool that records every change; `git diff` shows exactly what was changed. Used in project 1.
- **Glob** — A filename wildcard pattern such as `*.java`. Used in project 23. (Ch 21)
- **Golden-output test** — A test that runs a script and compares the output with a saved, known-good file. Used in projects 8, 22, 28, 31. (Ch 7)
- **Graceful shutdown** — Stopping a service so that accepted work finishes cleanly before it exits. Used in projects 27, 40. (Ch 12)
- **Graph** — Nodes connected by edges, such as cells and the cells they read. Used in projects 13, 36, 39, 40.
- **Greedy algorithm** — Always take the choice that looks best right now; fast, but not always optimal. Used in projects 2, 5, 13, 22, 29. (Ch 14, Ch 20)
- **Guard (state machine)** — A condition that must be true for a transition to happen. Used in projects 2, 20. (Ch 3, Ch 11)
- **GUI / UI** — User interface (graphical or text): the screens and controls a person uses; kept separate from the domain classes. Used in projects 4, 6, 13, 32, 37, 39.

H

- **H2 database** — A small Java database that can run entirely in memory, handy for tests. Used in project 38.
- **H3 / spatial grid** — Splitting a map into cells so a nearby search only checks a few cells; H3 is Uber's hexagon grid system. Used in project 29. (Ch 20)
- **Half-open interval [start, end)** — A time range that includes its start but not its end, so back-to-back bookings don't clash. Used in projects 19, 21. (Ch 15, Ch 21)
- **Hall call vs car call** — An elevator request from a floor's up/down button versus a floor button pressed inside a car. Used in project 11. (Ch 14)
- **Hash / hashing** — Turning a value into a number used to place or find it quickly (hash maps, routing, Zobrist keys). Used in projects 4, 15, 17, 26, 28, 30, 34, 40. (Ch 2)
- **HashMap / hash table** — A key-value store that finds entries in about constant time by hashing the key. Used in projects 3, 10, 12–16, 20, 25, 26, 28, 29, 34, 36, 37, 39, 40. (Ch 2)
- **Haversine distance** — The formula for the straight-over-the-globe distance between two latitude/longitude points. Used in project 29.
- **HdrHistogram** — A library (and idea) for recording latencies so that percentiles can be read accurately. Used in project 28.
- **Heap / priority queue** — A structure that always gives back the smallest (or largest) item first, in O(log n) per operation. Used in projects 7, 13, 15, 29, 40.
- **Heartbeat** — A periodic "I'm still alive" signal; here it extends a worker's lease on a long job. Used in project 33.
- **HikariCP** — A popular, fast JDBC connection pool for Java. Used in projects 33, 38. (Ch 8)
- **History stack** — Executed commands kept in order so the latest can be undone (and redone). Used in projects 4, 8, 30, 32. (Ch 10)
- **Hold queue** — A first-come, first-served waiting list of members for a book that is currently out. Used in project 3. (Ch 15)
- **Hold (temporary claim)** — A temporary, expiring reservation (of seats, stock or money) made before a purchase is confirmed. Used in projects 3, 12, 34. (Ch 15)
- **Hot account** — An account touched by most transactions, which forces them to queue on one lock. Used in project 34.
- **Hot score with decay** — A popularity score divided by something that grows with age, so new active posts rise and old ones sink. Used in projects 15, 25. (Ch 18)
- **HTTP** — The request/response protocol of the web; status codes such as 429 (too many requests) and 503 (unavailable) signal problems. Used in projects 14, 18, 35, 37, 40.
- **HTTP 429 + Retry-After** — The standard "too many requests" reply, with a header telling the client how long to wait. Used in project 14. (Ch 20)

I

- **iCalendar** — The standard file format for calendar events, which defines recurrence rules (RRULE). Used in project 21.
- **Idempotency key** — A client-chosen id sent with a request so a retry has the same effect as a single request. Used in projects 10, 18, 33, 34, 37. (Ch 20, Ch 21)
- **Idempotent** — Doing it twice has the same effect as doing it once. Used in projects 3, 5, 10, 17, 18, 20, 22, 33, 34, 37. (Ch 20)
- **Immutability** — An object that never changes after creation, so it is safe to share and easy to reason about. Used in projects 1, 4, 6, 9, 10, 13, 16, 20, 21, 31, 32, 34, 36. (Ch 2, Ch 5)
- **Information Expert** — Give a job to the class that already has the data needed to do it. Used in projects 3, 19. (Ch 5)
- **Inheritance** — A subclass reusing and specialising a parent class; correct only for a true "is-a" relationship. Used in projects 1, 3, 9, 16, 24, 25, 33. (Ch 2)

- **In-memory** — Kept only in the program's RAM, so it is fast but lost when the process stops. Used in projects 1, 3, 5, 10, 12, 15–18, 25, 26, 33, 34, 37, 38, 40. (Ch 1)
- **Interface** — A contract of methods that classes promise to implement; the main seam for swapping behaviour. Used in all 40 projects. (Ch 2)
- **Interpreter pattern** — Represents a small language's grammar as classes, each able to evaluate itself. Used in projects 23, 31, 39. (Ch 10)
- **Interrupt** — A request to a thread to stop; blocking calls react by throwing `InterruptedException`. Used in projects 7, 27. (Ch 12)
- **Invariant** — A fact that must always be true, such as "free + occupied = capacity" or "debits equal credits". Used in projects 1, 2, 7, 10, 12, 13, 15, 19, 29, 34. (Ch 5)
- **Inversion of Control (IoC) container** — A framework that creates and wires your objects and calls your code, instead of your code doing the wiring. Used in projects 28, 36. (Ch 5, Ch 11)
- **Inverted index** — A map from each word or tag to the items containing it, used for fast search. Used in projects 3, 25. (Ch 18)
- **IOC / FOK orders** — Immediate-or-cancel fills what it can now and cancels the rest; fill-or-kill trades everything at once or nothing. Used in project 28. (Ch 19)
- **ISBN** — International Standard Book Number: the id of a book title, shared by all its copies. Used in project 3. (Ch 15)
- **Isolation level (READ COMMITTED)** — How much one database transaction can see of others still in progress; READ COMMITTED sees only committed data. Used in project 34.

J

- **Jackson** — The most widely used Java library for reading and writing JSON. Used in project 8.
- **Java 25 / JEP** — The Java version these projects target; a JEP (JDK Enhancement Proposal) is the document that introduces each new Java feature. Used in projects 1–3, 6, 23, 27, 36, 39, 40.
- **jcstress** — OpenJDK's harness that runs concurrent code millions of times to expose rare race conditions. Used in projects 14, 27, 35, 38. (Ch 12)
- **JDBC** — Java's standard API for connecting to and querying relational databases. Used in projects 33, 38.
- **JDK / JVM** — The Java Development Kit (compiler and standard library) and the Java Virtual Machine that runs compiled code. Used in projects 7, 9, 10, 15, 17, 23, 26, 27, 36, 40. (Ch 12)
- **JMH** — OpenJDK's micro-benchmark harness for timing small pieces of Java code without JVM warm-up tricks fooling you. Used in projects 14–17, 26–28, 31, 32, 35, 38.
- **Journal / write-ahead log** — A durable list of inputs written before they are applied, so the system can replay it after a crash. Used in projects 5, 28.
- **jqwik** — A property-based testing library for JUnit that generates many random inputs and checks invariants. Used in projects 2, 13, 15, 25, 26, 28, 32, 34, 39.
- **JSON** — A text format for structured data (objects in braces, lists in brackets). Used in projects 6, 8, 9, 16, 31, 39.
- **jsoup / HttpClient** — `java.net.http.HttpClient` fetches web pages; jsoup parses HTML to find links. Used in project 40.
- **JUnit** — The standard Java unit-testing framework. Used in all 40 projects. (Ch 6)

K

- **Kafka** — A distributed, durable message log; producers append, consumers read by offset. Used in projects 17, 33. (Ch 20)
- **Kahn's algorithm** — A way to order a dependency graph: repeatedly take items with no remaining inputs; anything left over is in a cycle. Used in project 39.
- **Key-hash routing** — Sending every message with the same key to the same consumer, so per-key order is kept. Used in project 17.

- **K-nearest with a bounded heap** — Keeping only the K best candidates in a small priority queue while scanning many. Used in project 29.

L

- **Lambda** — A short anonymous function such as `x -> x * 2`. Used in projects 31, 38. (Ch 2)
- **Largest remainder method** — Splitting an amount by percentages: round every share down, then give leftover cents to the largest fractions. Used in project 13.
- **Latency** — How long one operation takes from start to finish. Used in projects 10, 14, 16, 17, 26–28, 33, 35, 40.
- **Lazy (passive) expiry** — Deleting an expired entry only when someone next reads it. Used in project 26. (Ch 13)
- **Lazy refill** — Computing how many rate-limit tokens were earned since the last call, instead of adding them with a timer. Used in project 14. (Ch 13)
- **Leak / leak detection** — A leak is memory or a resource (a connection, a listener) that is taken but never released; leak detection notices this and logs who took it. Used in projects 12, 24, 27, 37, 38.
- **Lease (visibility timeout)** — A claim that expires unless renewed, so a crashed worker's job becomes available again. Used in project 33. (Ch 12)
- **LFU (least frequently used)** — A cache eviction rule that drops the entry used the fewest times. Used in projects 15, 26. (Ch 20)
- **Line index** — A list of the offsets where each line starts, used to convert between (line, column) and a position in the text. Used in project 32.
- **Linearisability** — Concurrent operations behave as if they ran one at a time in some order consistent with real time. Used in project 24.
- **LISTEN / NOTIFY** — PostgreSQL's built-in messaging that wakes waiting workers without constant polling. Used in project 33.
- **Little's law** — Average items in a system = arrival rate × time each stays; used to size pools. Used in project 38.
- **LMAX Disruptor** — A very fast inter-thread messaging library built on a pre-allocated ring buffer. Used in project 28.
- **Lock** — A tool that lets only one thread at a time into a section of code that touches shared data. Used in projects 1, 7–16, 19–21, 24, 26–29, 31, 33–38. (Ch 12)
- **Lock ordering** — Always taking several locks in one fixed order (such as by id) so threads cannot deadlock. Used in projects 10, 12, 15, 26, 28, 34, 37. (Ch 12)
- **Lock striping** — Using an array of locks, each guarding part of the data chosen by key hash, so unrelated keys don't block each other. Used in project 15. (Ch 13)
- **Logger hierarchy / effective level** — Loggers named like packages inherit their level from the nearest configured parent. Used in project 16. (Ch 20)
- **LOOK / SCAN (elevator)** — Elevator scheduling: keep moving one way serving stops; LOOK turns back as soon as nothing is ahead. Used in project 11. (Ch 14)
- **Lost update** — Two threads read the same value and one write silently overwrites the other. Used in projects 10, 20, 34. (Ch 12)
- **LRU (least recently used)** — A cache eviction rule that drops the entry unused for the longest time. Used in projects 15, 26. (Ch 20)

M

- **Make / unmake** — Applying a chess move to the board in place and then exactly reversing it, instead of copying the board. Used in project 30.
- **Manual (fake) scheduler** — A test scheduler you advance by hand, so timed behaviour runs instantly and predictably. Used in project 7.

- **Market vs limit order** — A market order trades now at any price; a limit order trades only at the given price or better and otherwise waits. Used in project 28. (Ch 19)
- **Max lifetime with jitter** — Retiring pooled connections after a set age, randomised a little so they do not all expire together. Used in project 38.
- **MDC (Mapped Diagnostic Context)** — A per-thread map of values (request id, user) copied into every log line. Used in project 16. (Ch 20)
- **Memento pattern** — Saving a snapshot of an object's state so it can be restored later, without exposing its internals. Used in projects 30, 32. (Ch 10)
- **Merge intervals** — Sort time ranges by start and combine overlapping ones; the gaps are the free time. Used in project 21.
- **Mermaid** — A text syntax that renders diagrams (class, state, sequence) from plain text. Used in all 40 projects. (Ch 3)
- **minFreq** — In an LFU cache, the lowest use count currently present, tracked so the next victim can be found in O(1). Used in project 15.
- **Minimax** — Game search that picks the move with the best outcome assuming the opponent also plays perfectly. Used in projects 4, 30. (Ch 17)
- **Minor units** — Storing money as whole cents (or paise) in an integer to avoid floating-point rounding errors. Used in projects 1, 2, 9, 10, 13, 22, 34. (Ch 1)
- **Mockito** — A Java library for creating mocks and stubs in unit tests. Used in projects 3, 5, 12, 18, 20, 22, 24, 37. (Ch 6)
- **Money value object** — An immutable amount plus currency that refuses to mix currencies and never uses `double`. Used in projects 1, 2, 9, 10, 13, 19, 20, 22, 24, 34, 37. (Ch 1, Ch 5)
- **Monotonic clock** — A clock (`System.nanoTime`) that never goes backwards, used for measuring durations. Used in projects 14, 17, 26.
- **MULTI / EXEC / DISCARD / WATCH** — Redis-style transactions: queue commands, then run them together (EXEC) or throw them away (DISCARD); WATCH aborts the EXEC if a watched key changed first. Used in project 26.
- **Mutex** — A lock that lets only one thread into a critical section at a time. Used in project 10. (Ch 12)

N

- **Net vs pairwise balance** — What one person owes or is owed overall, versus what they owe each specific person. Used in project 13. (Ch 20)
- **NP-hard** — A problem with no known fast exact algorithm; large cases need approximations. Used in project 13.

O

- **Object Pool pattern** — Reusing a limited set of expensive objects that callers borrow and return. Used in project 38. (Ch 8)
- **Observer pattern** — A subject notifies a changing set of registered listeners when something happens. Used in projects 2, 4, 6, 9, 13, 15–18, 20, 24, 25, 28, 32, 35, 37, 39. (Ch 11)
- **Offer id** — A unique id for each job offer to a driver, so a late timeout or reply for an old offer is ignored. Used in project 29.
- **Offset** — A position number in a log or document; readers keep their own offset to resume or replay. Used in projects 7, 17, 21, 28, 30, 32, 39. (Ch 20)
- **O(K) win check** — Checking for a win only along the lines through the last move, instead of scanning the whole board. Used in project 4. (Ch 17)
- **Open/Closed Principle** — Add new behaviour by adding classes, not by editing working code. Used in projects 1, 8, 18. (Ch 4)
- **Operator precedence** — Which operator binds tighter, such as NOT before AND before OR. Used in projects 23, 31, 39. (Ch 10)

- **Optimistic locking** — Read a version number, and save only if it hasn't changed; otherwise retry or report a conflict. Used in projects 3, 20, 26. (Ch 12)
- **Optional** — A Java container that may be empty; returned when "not found" is a normal outcome. Used in projects 1, 10, 14, 15, 34. (Ch 1)
- **Orchestration vs choreography** — A central coordinator runs each step, versus each module reacting to the previous one's events. Used in projects 12, 19, 29, 37, 38.
- **Order book** — The waiting buy and sell orders for one stock, sorted by price and then time. Used in project 28. (Ch 19)
- **Outbox (transactional)** — Writing outgoing events into a table in the same transaction as the data change, then publishing them afterwards. Used in projects 33, 37. (Ch 5)
- **Overbooking** — Accepting more reservations than there are items to serve them. Used in project 19. (Ch 15, Ch 16)
- **Overlap test** — Two half-open ranges overlap exactly when each starts before the other ends. Used in projects 19, 21. (Ch 21)

P

- **p95 / percentile** — The value that 95% (or 99%) of measurements are below; shows the slow tail, not just the average. Used in projects 10, 11, 28.
- **Parameterised test** — One test method run against a table of inputs and expected outputs. Used in projects 1, 5, 11, 16, 18, 19, 21, 30. (Ch 6)
- **Partial fill** — An order matched for only part of its quantity, with the rest still open. Used in project 28. (Ch 19)
- **Partial unique index** — A database uniqueness rule that applies only to rows meeting a condition, such as unfinished jobs. Used in project 33.
- **Pattern matching for switch** — A `switch` that branches on an object's type and pulls out its fields, checked for completeness on sealed types. Used in projects 2, 20, 23, 31. (Ch 2, Ch 11)
- **Perft** — A chess-engine test that counts every position reachable to a set depth and compares with published totals. Used in project 30.
- **Per-resource lock** — A separate lock for each item (room, wallet, auction), so work on different items runs in parallel. Used in projects 1, 10, 12, 21, 24. (Ch 12)
- **Persistence** — Saving data so it survives a restart, in a file or database. Used in projects 1–3, 5, 8, 10, 12, 17, 20, 26, 32, 33, 39, 40.
- **Phase (traffic)** — A group of traffic approaches that can safely be green at the same time. Used in project 7. (Ch 14)
- **picocli / JLine** — Java libraries for command-line apps: picocli parses arguments, JLine gives a rich interactive terminal. Used in projects 8, 32.
- **Piece table / rope** — Text-editor structures: a piece table describes the document as slices of an original and an added buffer; a rope is a balanced tree of text chunks. Used in project 32.
- **PIN** — Personal identification number: the short secret code a card holder types at an ATM. Used in project 5. (Ch 14)
- **Pinning (virtual threads)** — A virtual thread stuck to its carrier OS thread while blocking, which wastes that thread. Used in project 40. (Ch 12)
- **Pipeline** — A fixed sequence of steps, each taking the previous step's output (pricing rules, filters, appenders). Used in projects 9, 18, 19, 28.
- **Plan before acting** — Work out every step (such as the full set of notes to dispense) before changing anything, so you never stop halfway. Used in project 5.
- **Policy object** — A small class that holds one business rule (refunds, rounding, lending limits) so it can change independently. Used in projects 1, 3, 11, 15–20, 22, 24, 25, 27, 33, 35. (Ch 4)
- **Politeness (crawler)** — Limiting how often and how many requests a crawler sends to one site. Used in project 40.

- **Ports and adapters** — The core defines interfaces (ports); databases, payment providers and UIs plug in through adapters. Used in projects 29, 37. (Ch 4)
- **POS (point of sale)** — The till where items are scanned, totalled and paid for. Used in project 22. (Ch 19)
- **PostgreSQL** — A popular open-source relational database. Used in projects 3, 8, 10, 12, 33, 34, 37, 38.
- **Price-time priority** — Matching the best price first, and among equal prices the earliest order first. Used in project 28. (Ch 19)
- **Primary key / foreign key** — A column that uniquely identifies each row / a column that refers to another table's primary key. Used in projects 33, 34.
- **Privilege threshold** — The reputation score a user needs before a site lets them do something (comment, vote down, edit). Used in project 25.
- **Producer–consumer** — Some threads create work and put it in a queue; others take it out and process it. Used in projects 11, 16, 17, 22, 23, 27, 28, 33, 35, 37. (Ch 12)
- **Promotion engine** — The component that finds applicable discounts on a basket and picks a non-conflicting set. Used in project 22. (Ch 19)
- **Property-based test** — Tests that generate many random inputs and check that stated rules (properties) always hold. Used in projects 2, 13, 15, 25, 26, 28, 32, 34, 39. (Ch 6)
- **Prototype** — Creating new objects by copying an existing one; in DI, the scope that makes a fresh instance on every request. Used in project 36. (Ch 8)
- **Provider** — An injected factory you call to get an instance later or repeatedly, instead of receiving the instance directly. Used in projects 18, 36.
- **Proxy (automatic) bidding** — The auction bids for you, one step at a time, up to the hidden maximum you set. Used in project 24. (Ch 19)
- **Proxy pattern** — A stand-in with the same interface that controls access to the real object (here, intercepting `close()` to return a connection). Used in projects 35, 36, 38. (Ch 9)
- **Pseudo-legal vs legal move** — A move that follows the piece's movement rules versus one that also doesn't leave your own king in check. Used in project 30. (Ch 17)
- **Pub/sub (publish/subscribe)** — Publishers send messages to a topic without knowing who receives them; subscribers listen to topics. Used in projects 17, 20, 26, 33. (Ch 20)

Q

- **Quiet hours** — A do-not-disturb period in the user's own time zone during which non-urgent messages are delayed. Used in project 18.

R

- **Race condition** — A bug where the result depends on the unlucky timing of threads touching shared data. Used in projects 7, 9, 10, 12, 14, 16, 20, 26–29, 34, 35, 38. (Ch 12)
- **RandomGenerator / seeded random** — Java's interface for random numbers; giving it a fixed seed makes the sequence repeat, so tests are reproducible. Used in projects 2, 6, 11, 25, 29, 35, 40. (Ch 17)
- **Rate limiter** — Caps how many requests a user or key may make in a period of time. Used in projects 14, 18, 40. (Ch 13, Ch 20)
- **Read-write lock** — A lock that lets many readers in together but only one writer at a time. Used in project 15. (Ch 12)
- **Reconciliation** — Periodically checking a cached total against the full history and flagging any difference. Used in projects 2, 5, 34. (Ch 14)
- **Record (Java)** — A compact Java class for immutable data; `equals`, `hashCode` and `toString` are generated. Used in projects 1–6, 8–13, 16, 17, 19, 21–25, 29–32, 34–37, 39, 40. (Ch 2)
- **Recurrence rule (RRULE)** — The iCalendar syntax for repeating events, such as "every Tuesday until June". Used in projects 8, 21, 33.

- **Recursive-descent parser** — A parser with one method per grammar rule, each calling the others. Used in projects 23, 31, 39. (Ch 10, Ch 21)
- **Redis** — A fast shared in-memory key-value store, often used for caches, counters and rate limits. Used in projects 12, 14, 15, 26. (Ch 20)
- **ReentrantLock** — Java's explicit lock with try-lock, timeouts and fairness options. Used in projects 10, 12, 15, 24, 36, 40. (Ch 12)
- **Reflection** — Code inspecting and calling classes, constructors and methods at run time. Used in projects 31, 36, 38. (Ch 8)
- **Refraction (rules engine)** — A rule does not fire again for the same unchanged facts, which prevents endless loops. Used in project 31.
- **Rejection policy** — What a thread pool does when its queue and threads are full: throw, run in the caller, or drop. Used in project 27. (Ch 12)
- **Relative vs absolute reference** — A spreadsheet reference that shifts when a formula is copied (`A1`) versus one that stays fixed (`$A$1`). Used in project 39.
- **Reorder point** — The stock level at which a new purchase order should be raised. Used in project 22. (Ch 21)
- **Replica** — A copy of data kept on another machine for safety or extra read capacity. Used in projects 17, 26, 28.
- **Repository pattern** — A collection-like interface that hides how objects are stored (memory now, database later). Used in projects 1, 3, 8, 10, 12, 13, 19–21, 24, 29, 33, 34, 36. (Ch 11)
- **Reservation vs rental** — A promise of something in future (a car category, seats) versus actually using a specific item. Used in projects 1, 9, 12, 19, 29, 37. (Ch 15, Ch 16)
- **Reserve price** — The hidden minimum a seller will accept in an auction. Used in project 24. (Ch 19)
- **Retry** — Trying a failed operation again; only safe when it is idempotent and the failure was temporary. Used in projects 3, 5, 10, 14, 16–18, 20, 22, 33–35, 37, 40. (Ch 6)
- **Retry amplification** — Retries at several layers multiply load: 3 retries at each of 3 layers can turn one call into 64. Used in project 35.
- **Reversal** — A new transaction with the opposite entries of an earlier one, undoing it without deleting history. Used in projects 5, 34. (Ch 21)
- **Ring buffer** — A fixed-size circular array where new items overwrite the oldest. Used in projects 17, 28, 35. (Ch 20)
- **Ring expansion** — Searching map cells outward in growing rings around a point until enough candidates are found. Used in project 29.
- **robots.txt** — A file on a website saying which paths crawlers may fetch. Used in project 40.
- **Rounding policy** — The stated rule for where and how fractions of a cent are rounded, so totals are predictable. Used in projects 1, 10, 13, 22, 39. (Ch 20)
- **Rounding remainder** — The cents left over after dividing an amount with integer maths, which must be handed out by a fixed rule. Used in project 13. (Ch 20)

S

- **Saga** — A multi-step business process made of local steps, each with a compensating action if a later step fails. Used in projects 34, 37.
- **Sandboxing by construction** — Making a rule language safe simply by implementing only the operations it is allowed to perform. Used in project 31.
- **ScheduledExecutorService** — Java's thread pool that runs tasks after a delay or repeatedly. Used in projects 7, 10, 12, 20, 24, 27, 29. (Ch 13)
- **Scope (DI)** — How long an injected instance lives: one for the whole container (singleton) or a new one each time (prototype). Used in project 36. (Ch 11)

- **Scoped values / structured concurrency** — Newer Java features: scoped values share read-only data with called code and child tasks; structured concurrency treats a group of subtasks as one unit that is cancelled and awaited together. Used in projects 23, 27, 36, 39, 40. (Ch 12)
- **Sealed interface / class** — A type that lists all its permitted subtypes, so the compiler can check a `switch` covers every case. Used in projects 1, 2, 4, 5, 8, 10, 12, 17, 18, 20, 21, 23–26, 28, 31, 39, 40. (Ch 11)
- **Seat hold** — A temporary, expiring claim on seats while the customer pays. Used in project 12. (Ch 15)
- **Second-price (Vickrey) auction** — The winner pays roughly the second-highest bid (plus one step) rather than their own maximum. Used in project 24.
- **Semaphore** — A counter of permits; each user takes one and gives it back, capping how many run at once. Used in projects 14, 27, 33, 35, 38, 40. (Ch 12)
- **Separation of concerns** — Each part of the program handles one kind of job (storage, rules, display). Used in projects 3, 4. (Ch 4, Ch 5)
- **Sequencer** — The component that gives every incoming command a global order number before it is processed. Used in project 28.
- **Service locator** — An anti-pattern where a class fetches its dependencies from a global registry, hiding what it needs. Used in project 36. (Ch 11)
- **Sharding** — Splitting data into independent parts, each with its own lock or server, so they can work in parallel. Used in projects 10, 12, 24, 26, 34. (Ch 20)
- **Short-circuit evaluation** — AND stops at the first false and OR at the first true, skipping the rest. Used in projects 23, 35.
- **Simulation** — Running the system against generated events (cars, passengers, games) to measure behaviour. Used in projects 6, 7, 11, 29.
- **Single Responsibility Principle** — A class should have one reason to change. Used in projects 1, 13. (Ch 4)
- **Single-flight loading** — Letting only one thread load a missing key while the others wait for that same result. Used in project 15. (Ch 13)
- **Single-threaded executor** — A pool of exactly one thread that runs submitted tasks one after another, so the state it owns needs no locks. Used in project 7. (Ch 12)
- **Singleton** — A class with exactly one instance; in DI, the scope where the container shares one instance. Used in projects 16, 36. (Ch 8)
- **Single-writer principle** — Only one thread ever changes a piece of state; others send it requests, so no locks are needed on that state. Used in projects 7, 11, 26, 28. (Ch 12)
- **SKU** — Stock-keeping unit: one sellable product variant tracked in inventory. Used in projects 22, 37. (Ch 21)
- **Sliding window (log / counter)** — Rate limits over the last N seconds: either storing each request time (exact) or weighting the previous window's count (cheap). Used in projects 14, 35. (Ch 20)
- **Snapshot** — A full copy of state at one moment, used to restore it or to shorten replay after a crash. Used in projects 14, 16, 20, 22, 26, 30–32, 34, 35, 37, 40. (Ch 10)
- **Soft delete** — Marking a record as deleted instead of removing it, which keeps ids stable and makes undo easy. Used in project 8.
- **Specification pattern** — Business rules as small objects with `isSatisfiedBy` that combine with and/or/not. Used in projects 8, 23, 31. (Ch 11)
- **Spider trap** — An endless set of URLs (calendars, session ids) that can keep a crawler busy forever. Used in project 40.
- **Split strategy** — One class per way of dividing an expense (equal, exact amounts, percentages). Used in project 13. (Ch 20)
- **SQL / SELECT … FOR UPDATE** — SQL is the database query language; `SELECT … FOR UPDATE` locks the selected rows until the transaction ends, and `SKIP LOCKED` skips rows others have locked. Used in projects 10, 12, 33, 34. (Ch 12, Ch 15)

- **SQS** — Amazon Simple Queue Service: a managed message queue whose "visibility timeout" works like a lease. Used in project 33.
- **Square attacked test** — Checking whether any enemy piece could capture on a square, used to decide if a king is in check. Used in project 30. (Ch 17)
- **Stack trace** — The list of method calls active when an exception was thrown or a resource was taken; shows where it came from. Used in projects 9, 16, 38. (Ch 6)
- **Starvation** — A request or thread that waits indefinitely while others keep being served. Used in projects 1, 7, 11, 17, 18, 27. (Ch 12)
- **State pattern** — Each state is an object implementing the same interface; the owning object delegates to its current state. Used in projects 2, 5, 7, 11, 12, 17, 20, 24, 29, 35. (Ch 11)
- **Strategy pattern** — Interchangeable implementations of one interface, chosen at run time (pricing, allocation, splitting). Used in all 40 projects. (Ch 11)
- **Stream (Java)** — A pipeline over a collection (`filter`, `map`, `collect`) that describes the result rather than the loop. Used in projects 26, 28, 34, 39. (Ch 2)
- **Super type token** — A trick (`new TypeLiteral<List<String>>() {}`) that keeps a generic type visible at run time despite erasure. Used in project 36.
- **Surge multiplier** — A price factor that rises where demand outstrips available drivers. Used in project 29. (Ch 20)
- **Sweep line** — Sort start and end events by time and walk through them with a running count to find overlaps or the peak. Used in projects 19, 21.
- **Swing / JTable** — Java's built-in desktop GUI toolkit; `JTable` is its grid component. Used in projects 32, 39.
- **Symlink cycle** — A symbolic link that points back to a parent folder, which would make a tree walk loop forever. Used in project 23.
- **synchronized** — The Java keyword that lets only one thread at a time run a block or method guarded by the same object. Used in projects 1, 7, 9, 10, 14, 15, 35, 40. (Ch 12)
- **SynchronousQueue** — A queue with no capacity: each hand-over waits until a giver and a taker meet. Used in project 38. (Ch 12)

T

- **Table bloat** — Dead row versions that pile up in a database table after many updates and deletes until cleaned up. Used in project 33.
- **Template engine** — A tool that fills placeholders such as `{{name}}` in a message template. Used in project 18.
- **Template Method pattern** — A base class fixes the steps of an algorithm and lets subclasses fill in some of them. Used in projects 9, 18. (Ch 11)
- **Test double** — Any stand-in for a real collaborator in a test (fake, stub, mock). Used in projects 3, 4, 6. (Ch 6)
- **Testcontainers** — A Java library that starts real services (such as PostgreSQL) in throwaway containers for tests. Used in projects 33, 34, 37, 38. (Ch 6)
- **Thread** — An independent path of execution inside a program; threads share the program's memory. Used in projects 1, 4, 6, 7, 9–12, 14–18, 20, 21, 23, 24, 26–29, 31, 33–36, 38, 40. (Ch 12)
- **Thread pool** — A fixed set of reusable worker threads fed from a queue of tasks. Used in projects 7, 27, 38. (Ch 12)
- **ThreadLocal** — A variable with a separate value for each thread, such as the current request id. Used in projects 18, 27, 38. (Ch 12)
- **Thread-safe** — Works correctly even when many threads use it at the same time. Used in projects 11, 14, 15, 26, 35, 36. (Ch 12)
- **Thread-starvation deadlock** — Tasks in a full pool wait for other tasks stuck in the queue behind them, so nothing progresses. Used in project 27. (Ch 12)

- **Three-colour DFS** — Depth-first search that marks nodes unvisited, in progress or done; reaching an in-progress node means a cycle. Used in project 36.
- **Threefold repetition** — A chess draw when the same position, with the same side to move and rights, occurs three times. Used in project 30. (Ch 17)
- **Tick size** — The smallest allowed price step; prices are stored as whole ticks in a `long`. Used in project 28. (Ch 19)
- **Time limiter / timeout** — A maximum time to wait for a call or resource before giving up. Used in projects 4, 5, 10, 12, 14, 17, 18, 20, 22, 27, 29, 31, 33, 35, 37, 38, 40. (Ch 12)
- **Time zone (ZoneId, ZonedDateTime, Instant)** — `Instant` is an absolute moment (UTC); `ZonedDateTime` is a local date-time in a `ZoneId` with its daylight-saving rules. Used in projects 1, 8, 12, 18, 19, 21, 24, 25, 27, 33, 34, 40.
- **Time-dependent supply** — Stock that changes on future dates, such as cars arriving at a branch from one-way rentals. Used in project 19.
- **Timeout ambiguity** — After a timeout you cannot tell whether the other side did the work, so you must check or reverse instead of simply retrying. Used in project 5.
- **Token bucket** — A rate limit where tokens refill at a steady rate up to a cap and each request spends one; allows short bursts. Used in project 14. (Ch 13, Ch 20)
- **Topic** — A named stream of messages that publishers write to and subscribers read from. Used in project 17. (Ch 20)
- **Topological order** — An ordering where each item comes after everything it depends on. Used in projects 36, 39.
- **Total order** — Every operation is placed in one single sequence, so everyone agrees which came first. Used in project 24.
- **Transaction (database)** — A group of changes that succeed or fail together; in a ledger, a balanced set of entries posted at once. Used in projects 2, 3, 5, 9, 10, 12, 13, 19, 21, 22, 26, 33, 34, 36–38. (Ch 12, Ch 21)
- **Transient vs permanent failure** — A temporary error worth retrying (timeout, HTTP 503) versus one that will never succeed (an invalid phone number). Used in projects 17, 18, 35. (Ch 6)
- **Transition table** — A data table listing, for each state and event, the next state, its guard and its actions. Used in projects 2, 20. (Ch 11)
- **Transitive dependents** — Everything affected by a change directly or through a chain of dependencies. Used in project 39.
- **TreeMap / TreeSet** — Sorted Java map and set; they answer "nearest lower/higher key" and range questions in O(log n). Used in projects 1, 11, 19, 21, 28.
- **TTL (time to live)** — How long an entry stays valid before it is treated as gone. Used in projects 12, 14, 15, 26. (Ch 13)
- **Two-phase (commit / locking)** — Doing a change in two steps, first preparing or reserving everything, then committing, so it can be abandoned cleanly in between. Used in projects 26, 34, 37.
- **Type erasure** — Java drops generic type arguments after compiling, so `List<String>` and `List<Integer>` look the same at run time. Used in project 36. (Ch 2)

U

- **UCI** — Universal Chess Interface: the text protocol chess engines and chess GUIs use to talk. Used in project 30.
- **UML** — Unified Modeling Language: standard diagrams (class, sequence, state) for describing designs. Used in projects 1, 3, 19, 25. (Ch 3)
- **Undo / redo** — Reversing the last change and re-applying it, usually with a history stack of commands. Used in projects 4, 5, 8, 25, 30, 32, 37, 39. (Ch 10)
- **Unit test** — A fast test of one small piece of code in isolation. Used in projects 1, 2, 6, 8, 10, 37, 40. (Ch 6)

- **URL** — A web address; a URI is the more general name for such identifiers. Used in projects 38, 40.
- **URL normalisation** — Rewriting URLs into one standard form (lowercase host, no fragment) so duplicates are detected. Used in project 40.
- **UTF-16 surrogate pair** — Two Java `char` values that together encode one character, such as most emoji. Used in project 32.

V

- **Value object** — A small immutable object defined only by its values (money, a date range), usually a record. Used in projects 1, 3, 4, 9, 10, 19, 21. (Ch 5)
- **Version (optimistic)** — A counter stored with a record and increased on every change, used to detect conflicting updates. Used in projects 3, 20, 26, 31. (Ch 12)
- **Virtual threads** — Very lightweight JVM-managed threads, cheap enough to create one per task, ideal for blocking I/O. Used in projects 1, 4, 10, 12, 17, 18, 20, 23, 26, 27, 29, 33, 38, 40. (Ch 12)
- **Visitor pattern** — Adds new operations over a fixed set of node classes without changing those classes. Used in projects 23, 31, 39. (Ch 11)
- **volatile** — A Java field modifier that makes writes visible to all threads at once; it does not make compound updates atomic. Used in projects 16, 27, 39. (Ch 12)
- **Volatile function (spreadsheet)** — A formula such as `NOW()` or `RAND()` that must be recalculated on every change. Used in project 39.

W

- **W-TinyLFU** — Caffeine's eviction policy: a small LRU window plus a frequency filter that decides what may enter the main cache. Used in project 15.

X

- **XOR** — Exclusive or: a bit operation that flips bits; applying the same XOR twice cancels out. Used in project 30.

Y

- **YAML** — A human-friendly text format for configuration files. Used in projects 9, 16.

Z

- **Zobrist hashing** — A chess position fingerprint built by XOR-ing random numbers per piece and square, updated in O(1) per move. Used in project 30.