Chapter 15 — Rapid Review, Future Trends and Glossary

Last reviewed: September 2026. The review sheets summarise this book as written; the trends section describes directions visible in 2026, not predictions of fact.

Earlier chapters built understanding at chapter depth; an interview or design review asks you to pull it out at conversation speed, aloud, under mild pressure — a separate skill needing separate practice. This chapter compresses the book into revision tools, then looks outward: where the field is heading, how to keep learning, and every key term in one place.

What you'll learn

- A two-minute review sheet for each of Chapters 1–14, with links to the sections behind every bullet
- Decision cheat sheets: each major either-or with its deciding variable and default
- Twelve "red flag" phrases that make an answer sound junior, and what to say instead
- A 52-question interview bank with compressed answers, plus a script that drills it
- Future trends (model capabilities, agents, AI with IoT/AR/VR/robotics/quantum — internet-connected devices, augmented and virtual reality, robots and quantum computers — the future of work, regulation), stated as trends
- A staged learning roadmap with a project per stage
- An alphabetical glossary defining each key term once, each pointing to the chapter that explains it

How to revise with this chapter

Tool	Rhythm	Why
Review sheets (§15.1)	One chapter a day in the last two weeks	Rebuilds the map of each topic
Decision cheat sheets (§15.2)	Ten minutes daily; cover the right column and reproduce it	The deciding variables must become automatic
Red flags (§15.3)	Read carefully once now, skim the night before	Cheap fixes with the biggest effect on how you come across
Question bank (§15.4)	Shuffled, aloud, ~30 s each, in the final week	Interviews grade spoken recall, not recognition
One full design per session	Pair every drill with one narrated case from Chapter 14 or §13.11	Drills keep vocabulary ready; full designs keep assembly ready

Three drilling rules: **random order, out loud, timed**; after answering, **check the deciding variable** (if you can't say what drives the choice, reread the section rather than memorising words); **re-drill misses after a day or two**, not immediately — answering again at once only tests short-term memory.

15.1 Rapid-review sheets, chapter by chapter

How to use them

One sheet per chapter: ideas to explain without notes, numbers worth remembering, and a "can you…?" test. Read a sheet in two minutes, explain it aloud in five; follow the section link for any shaky bullet. Sheets don't re-teach — **every term is defined once in the glossary (§15.7)**; keep it open beside you.

Chapter 1 — The World of AI (Chapter 1)

- **AI** = agents acting rationally: maximise expected performance given percepts; specify tasks with **PEAS**, classify the environment. (§1.1)
- **Turing test** measures imitation, not understanding. (§1.2)

- **History**: 1956 Dartmouth → symbolic AI → AI winters → statistical ML → deep learning (2012) → transformers (2017) → ChatGPT (Nov 2022) → reasoning models and agents. (§1.3)
- Everything deployed is **narrow** AI; AGI has no agreed definition. (§1.4)
- **Family tree**: AI ⊃ ML ⊃ deep learning ⊃ generative AI ⊃ LLMs; agentic AI wraps models in a plan–act–observe loop; symbolic vs statistical knowledge. (§1.5)
- **Constraints** decide projects: data, cost, latency, reliability compounding over steps (p^n), integration, regulation. (§1.8)
- **Can you…** write PEAS for a self-driving taxi? explain why a 95%-reliable step repeated 10 times is only ~60% reliable?

Chapter 2 — Classical AI and Search (Chapter 2)

- **Formulate**: states, actions, transition model, goal test, path cost. (§2.1)
- **Uninformed**: BFS (shallowest first, memory-hungry), DFS (low memory, no guarantees), iterative deepening, uniform-cost (cheapest path). (§2.2)
- **Informed**: greedy (f = h) fast, not optimal; **A*** (f = g + h) optimal with an admissible heuristic. (§2.3)
- **Local search**: hill climbing, random restarts, simulated annealing, genetic algorithms. (§2.4)
- **Games**: minimax, alpha-beta (same answer, far fewer nodes); **MCTS** + learned policy/value networks → AlphaGo. (§2.5, §2.6)
- **CSPs**: backtracking with MRV and forward checking. (§2.7)
- **Can you…** explain why Manhattan distance is admissible on a 4-connected grid (moves only up, down, left, right)? trace one alpha-beta cut-off?

Chapter 3 — Transformers and Embeddings (Chapter 3)

- **Tokens**: BPE-style subword pieces, ~4 English characters each; everything is counted and priced in tokens. (§3.1)
- **Embeddings**: closeness = similar meaning; compare with cosine similarity. (§3.2)
- **Position**: attention is order-blind → sinusoidal, learned or RoPE positions. (§3.3)
- **Self-attention**: $\text{softmax}(QK^T/\sqrt{d_k})V$, all tokens in parallel, cost $\propto T^2$; **multi-head**; GQA/MQA share K/V. (§3.4, §3.5)
- **Block**: attention + feed-forward, each with residual and normalisation, stacked; **causal mask** for generation. (§3.6, §3.7)
- **Encoder / decoder / encoder–decoder**: BERT / GPT-Claude-Llama / T5-Whisper. (§3.8)
- **Can you…** compute attention weights for three tokens by hand? say why decoders need the mask?

Chapter 4 — Large Language Models (Chapter 4)

- An LLM is a decoder-only transformer trained to **predict the next token**, generating one at a time. (§4.1, §4.2)
- **Scaling laws**: compute $C \approx 6 \cdot N \cdot D$ (N parameters, D tokens); Chinchilla ≈ 20 tokens per parameter; smaller over-trained models are cheaper to serve. (§4.4)
- **Post-training**: SFT → RLHF or DPO → RL on verifiable rewards for reasoning models. (§4.5, §4.6, §4.11)
- **Decoding**: greedy, beam, temperature, top-k, top-p. (§4.7)
- **Context**: the model is stateless, the window finite; history is selected, summarised or retrieved. (§4.8)
- **Inference**: prefill sets time-to-first-token; decode is memory-bound; the KV cache trades memory for speed. (§4.9)
- **Limits**: hallucination, knowledge cutoff, no private knowledge, prompt injection, output variance. **Open vs closed** models. (§4.10, §4.13)
- **Can you…** estimate training compute for a 7B model on 2T tokens ($\approx 8.4 \times 10^{22}$ FLOPs)? explain why temperature 0 is still not perfectly deterministic?

Chapter 5 — Prompt Engineering (Chapter 5)

- A prompt is a **specification**: role, task, context, constraints, output format, examples; plain direct language, with reasons for rules. (§5.2)
- **Zero-shot vs few-shot**; diverse, tagged examples are the clearest spec. (§5.3)
- **System prompts** for stable rules; **scenario ("act as") prompts** for a stakeholder's viewpoint. (§5.4)
- **Delimit** instructions from data (XML-style tags); **structured output** with schema, validation and retry. (§5.5, §5.6)
- **Reasoning**: chain-of-thought for standard models, effort settings for reasoning models; **self-consistency** votes; **chaining** and **ReAct** split work into checked steps. (§5.7–§5.10)
- **Iterate** one or two changes at a time; **troubleshoot** by finding the missing information; outside text is untrusted. (§5.12, §5.13)
- **Evaluate prompts like code**: criteria, test set, graders, versions. (§5.14)
- **Can you…** rewrite a vague one-line prompt into a full specification? name two defences against injected instructions?

Chapter 6 — Building LLM Apps in Python (Chapter 6)

- **API call** = model + system prompt + messages + max_tokens (+ tools); response = content blocks, stop reason, token usage; the API is stateless. (§6.2)
- **Streaming** reduces perceived latency. (§6.3)
- **Structured output**: schema-constrained modes or strict tools; still validate. (§6.4)
- **Tool-use loop**: JSON-Schema tools → model asks → your code validates and runs → result back by id → repeat, with limits. (§6.5)
- **Cost** = input tokens × input price + output tokens × output price. (§6.6)
- **Reliability**: backoff + jitter on 429, 5xx and timeouts; no retries on other 4xx. **Caching**: stable prefix first. **Memory**: recent turns + summary + durable facts under a budget. (§6.7–§6.9)
- **MCP**: host / client / server over JSON-RPC; tools (model-controlled), resources (app-controlled), prompts (user-controlled). (§6.10)
- **Can you…** sketch the tool loop from memory? estimate the monthly cost of 10,000 requests a day?

Chapter 7 — Embeddings, Vector Databases and RAG (Chapter 7)

- **RAG** = retrieve evidence, then generate from it: an offline indexing system plus an online request path, evaluated separately. (§7.1)
- **ANN indexes** (HNSW, IVF, PQ) trade recall for speed and memory — measure recall against exact search. (§7.3)
- A **vector database** adds filtering during search, updates/deletes and replication to an index. (§7.4)
- **Ingestion** decides quality: parsing, structure-aware chunks with overlap, metadata, sync. (§7.5)
- **Request path**: process the query (rewrite, HyDE, routing), retrieve, assemble a budgeted context, generate, post-check with a fallback. (§7.6)
- **Hybrid** BM25 + vectors fused with RRF (Σ 1/(60 + rank)); cross-encoder reranking. (§7.7)
- **Grounding**, **permissions inside retrieval (fail closed)**, freshness and deletion. (§7.8, §7.9)
- **Evaluate**: recall@k, faithfulness, answer relevance, refusal correctness, zero leaks. (§7.11)
- **Can you…** size raw vectors for 10M chunks × 1,024 float32 dims (≈ 41 GB)? say which stage failed when the right document exists but is never retrieved?

Chapter 8 — Prompting vs Fine-Tuning vs RAG, and LLM Evaluation (Chapter 8)

- **Adaptation**: prompting is the baseline; **RAG supplies knowledge** (fresh, private, permissioned, citable); **fine-tuning changes behaviour** (format, tone, narrow skill, cheaper small models). Diagnose first; never use weights as access control. (§8.1)
- **LoRA**: $h = W_0x + (\alpha/r)\cdot BAx$ — ~65K trainable parameters instead of 16.8M for one 4096 × 4096 matrix at r = 8; **QLoRA** adds a 4-bit base; full fine-tuning of 7B needs ~16 bytes per parameter. (§8.2)
- **Tuning data**: instruction pairs (SFT), preference pairs (RLHF/DPO), teacher outputs (distillation); re-run every eval — forgetting and safety erosion happen. (§8.3)

- **Evaluation pyramid**: programmatic checks → LLM-as-judge (position, verbosity, self-preference bias) → human review, over a versioned golden set run like CI. (§8.4, §8.5)
- **Metrics**: exact match/F1, pass@k for code, BLEU/ROUGE only as rough signals, faithfulness/relevance/refusal for RAG — report uncertainty. (§8.6)
- **Online evaluation** (A/B tests, canaries, outcome metrics) and **guardrail suites** as hard gates. (§8.7, §8.8)
- **Can you…** pick RAG, prompting or tuning for three different failures? compute LoRA's trainable parameters for one matrix?

Chapter 9 — AI Agents (Chapter 9)

- **Agent** = LLM + tools + memory + a loop where the model picks the next step at run time; drawable flowchart → **workflow**. (§9.1)
- **Loop / ReAct**: reason → act → observe, bounded by steps, tokens, money, time and actions; $0.95^{10} \approx 0.60$, so verify intermediate results. (§9.2)
- **Tool calling**: the model *requests*; the runtime validates, authorises, executes, logs. Few, coarse, well-described tools; idempotent writes. (§9.3)
- **Guardrails**: least privilege, user-scoped credentials, consequence tiers, an action gate, targeted human approval — injection is stopped by the gate, not the prompt. (§9.4)
- **Planning** (plan-and-execute, reflection) and **memory** (window, compaction, long-term, durable task state). (§9.5, §9.6)
- **Multi-agent**: default to one; split only for isolation, parallelism or specialisation. **MCP** standardises the plug, not authorisation. (§9.7, §9.8)
- **Evaluate** whole trajectories in a sandbox (success with cost, pass^k); **control** with a four-rung autonomy ladder per action tier, budgets, kill switches, alarms. (§9.9, §9.10)
- **Can you…** design the customer-support agent's tools, tiers and approval gates (§9.11)? explain pass^k?

Chapter 10 — Generative Models Beyond Text (Chapter 10)

- **Families**: VAEs (smooth latent space, blurrier), GANs (sharp, fast, mode collapse), autoregressive (token by token), diffusion/flow (top quality, slow without tricks). (§10.1)
- **VAE**: encode to a distribution, sample $z = \mu + \sigma\varepsilon$, loss = reconstruction + KL; the compressor inside latent diffusion. (§10.2)
- **GAN**: generator vs discriminator game. (§10.3)
- **Diffusion**: noise on a schedule, train to predict the noise, generate by step-by-step denoising (U-Net or diffusion transformer). (§10.4)
- **Text-to-image**: CLIP aligns text and images; cross-attention injects the prompt; classifier-free guidance trades diversity for adherence; Stable Diffusion = VAE + text encoder + denoiser in latent space. (§10.5)
- **Audio** (ASR with Whisper, TTS, voice cloning), **video** (temporal consistency is the hard part), **multimodal** models. (§10.6–§10.8)
- **Evaluate** with FID (lower better), precision/recall, CLIP score, human comparisons; **risks**: deepfakes, consent, copyright; watermarks and C2PA provenance. (§10.9, §10.10)
- **Can you…** explain classifier-free guidance in two sentences? say why diffusion runs in latent space?

Chapter 11 — LLM Serving and Inference (Chapter 11)

- Treat the LLM as a **production component** with latency, cost and failure modes. (§11.1)
- **Prefill** (parallel, compute-bound) sets TTFT; **decode** (sequential, bandwidth-bound) sets tokens/s; E2E ≈ TTFT + TPOT × (n − 1). (§11.2, §11.3)
- **KV cache** per token = 2 × layers × KV-heads × head-dim × bytes — usually the real concurrency limit. (§11.4)
- **Continuous batching** and **PagedAttention** (vLLM) keep GPUs busy and waste less memory. (§11.5, §11.6)
- Cheaper models: **quantization**, **distillation**, **speculative decoding** (same output distribution, fewer large-model passes). (§11.7–§11.9)

- **Memory sizing** = weights + users × context × KV-per-token + overhead; tensor parallelism inside a node, pipeline across nodes. (§11.10, §11.11)
- **Avoid calls**: exact, semantic and prefix caching; **routing/cascades** to cheaper models (caching basics: System Design Fundamentals). (§11.13, §11.14)
- **Cost**: per unit → price → volume → decision; API vs fleet; operate with rate limits, backpressure, fallbacks, observability. (§11.15–§11.17)
- **Can you…** size memory for a 70B model at 16-bit (weights ≈ 140 GB)? price the inference layer for a large user base out loud (§11.18)?

Chapter 12 — Safety, Ethics and Governance (Chapter 12)

- **Root cause**: instructions and data share one channel; the model is never the security boundary — enforce what matters in code. (§12.1)
- **Hallucination**: ground with retrieval and citations, allow abstention, humans on high-stakes outputs. (§12.2)
- **Bias** from history, representation, proxies, associations; measure per group; dropping the sensitive column isn't enough. (§12.3)
- **Prompt injection**: direct vs indirect; screening, data tagging, least privilege, **action gates**. (§12.4)
- **Privacy**: consent, GDPR/CCPA rights, PII redaction, per-user scoping of retrieval and caches. (§12.5)
- **Guardrails**: input gate → hardened assembly → output gate → action gate; measure over-refusal too. (§12.6)
- **Misuse** and unreliable AI-text detection; **alignment** (SFT, RLHF, Constitutional AI, DPO) makes good behaviour likely, not guaranteed; continuous **red-teaming**. (§12.7–§12.9)
- **Copyright**, **environmental cost**, **governance**: EU AI Act tiers (high-risk duties from 2 Dec 2027 for Annex III uses such as hiring and credit, 2 Aug 2028 for Annex I products), NIST AI RMF (Govern, Map, Measure, Manage); a deployment checklist. (§12.10–§12.13)
- **Can you…** explain indirect prompt injection with an email-summarising assistant? list the four gates?

Chapter 13 — AI System Design and GenAI Products (Chapter 13)

- Identify the **interview form**; confirm the depth wanted in minute one. (§13.1)
- **What changes when the system learns**: quality becomes a metric, a feedback loop is required, cost/latency budgets matter, failures are silent. (§13.2)
- **Three families**: prediction (funnel), content (context + cost + evaluation + safety), action (tools + permissions + limits). (§13.3)
- **Seven steps** with a time budget: frame → success metrics → data → model → serving → keep it working → failures and cost. (§13.4)
- **Requirements as numbers**: TTFT/p95, quality metric, cost per unit, safety rules, scale, privacy. (§13.5)
- **Build vs buy**: API → RAG for facts → fine-tune for behaviour → self-host for control or high steady volume. (§13.6)
- **Reference architecture**: gateway → input guard → cache → context assembly (prompt registry, memory, permission-filtered RAG) → router → model → output guard → action gate; traces feed evaluation. (§13.7)
- **LLMOps**: version everything, golden sets, regression tests, shadow → canary → A/B. **Cost modelling** and scale estimates. (§13.8, §13.9)
- **Archetypes**: chat, code, search, image, SaaS platform. (§13.10, §13.11)
- **Can you…** draw the reference architecture from memory with a latency budget per arrow? explain why chat-history cost grows quadratically with turns?

Chapter 14 — AI Case Studies (Chapter 14)

- **Running a case**: time budget per phase, exit sentences, timeboxing aloud; answer redirects, stress tests and disagreement by naming the deciding variable. (§14.1)

- **Legal research**: wrong citations bind; per-claim verification before release; refusal is a feature; fail closed. (§14.2)
- **Meeting assistant**: workflow, not agent; bursty load behind a queue; access rights bound what can be said; deletion propagates to summaries. (§14.3)
- **Text-to-image at scale**: maths first (requests/s × seconds per image = busy GPUs); queues drive pricing, autoscaling and UX; gates on prompt and image. (§14.4)
- **Coding agent**: tests inside, CI outside, humans at the end; sandbox without credentials; the repository is untrusted input. (§14.5)
- **Critiquing a design**: invariants → loops → reliability → economics → quality, each finding with consequence and fix. (§14.6, §14.7)
- **Email completion**: small distilled LM under ~100 ms; avoid requests on the client; beam search + confidence threshold on trigger vs acceptance; never guess people's attributes. (§14.8)
- **Machine translation**: one multilingual encoder-decoder with language tags, not 9,900 pair models; back-translation for low-resource languages; per-pair chrF/COMET and human MQM, never BLEU alone. (§14.9)
- **Image captioning**: image encoder + bridge + LM, async at upload; grounding rerank and CHAIR against hallucinated objects; attribute policy outside the model. (§14.10)
- **GAN faces**: StyleGAN mapping network and styles; judge by coverage, FID and precision/recall, not losses; truncation trades diversity for quality; a near-duplicate filter makes "not a real person" measurable. (§14.11)
- **High-resolution synthesis**: compress first (latent f = 8), generate at trained resolution, upscale only kept images; 2× side = 4× tokens = 16× attention. (§14.12)
- **Personalised headshots**: per-user LoRA with a rare token and prior preservation (or a zero-shot identity encoder); photo QC and same-person check before GPU spend; biometric consent, verified deletion. (§14.13)
- **Text-to-video**: spacetime latents, factorised attention, frames denoised jointly; recaptioned training video; async multi-GPU jobs with previews and checkpoints. (§14.14)
- **Can you…** narrate one of these cases in 45 minutes without notes?

15.2 Decision cheat sheets

What it is

Most AI design questions reduce to a handful of either-or choices. Each sheet gives the **options**, the **deciding variable** (the requirement fact that picks the option) and a **default** with its main exception. Sentence shape to practise: *"The deciding variable here is X; ours is Y, so I'd choose Z, which costs us W."* Defaults are starting points; several choices depend on more than one requirement, and exceptions matter as much as defaults.

Which kind of system is this?

What the model outputs	Family	The design centres on	Where in this book
Scores or labels about items or events	**Predictive**	Features, candidate funnel, metrics, feedback loop	ML Handbook ch. 15–18
New content: text, code, images	**Generative**	Retrieval, cost per request, evaluation, safety	Chapters 4–8, 10, 13
Tool calls that change things in the world	**Agentic**	What it may touch, loop limits, who signs off	Chapter 9

Many products mix families (a support assistant retrieves, generates *and* acts); design the dominant one's concerns first.

Workflow or agent?

- **Deciding variable:** can you draw the flowchart at design time?
- **Default:** yes → a fixed **workflow** (cheaper, testable, readable); an **agent** loop only for the part whose path depends on runtime discoveries, bounded (steps, cost, time, which actions).

Build a model or call an API?

- **Deciding variable:** does quality come from your own proprietary data (clicks, purchases, outcomes)?
- **Predictive** systems usually train on it (bought or managed models can still fit). **Generative** features usually start on a hosted API; privacy, licensing, availability or scale can later favour self-hosting. Revisit with measured costs.

Prompt, RAG or fine-tune?

What is failing	Reach for	Why
Missing, stale, private or per-user facts	**RAG**	Sources can be updated, cited and permission-filtered
Wrong format, tone, length, or a narrow skill	**Prompting first**, then **fine-tuning**	Behaviour is learned into the parameters — needs training examples and a test set
Answers good but the bill too high at scale	A **smaller fine-tuned model**, with a router sending it easy traffic	The problem is cost, not capability

Tuning can inject knowledge, but poorly when facts change or must be traceable. Training from scratch needs an exceptional reason and budget.

Batch, online or streaming inference?

Situation	Mode
Inputs known in advance; slightly stale results are fine	**Batch** — precompute into a key-value store
Inputs only exist at request time	**Online** — with a latency budget and fallbacks
Events, not users, trigger the work	**Streaming** — queue-fronted scoring
Huge catalogue plus need for fresh context	**Hybrid** — precomputed candidates, light online re-ranking

The serving-optimisation order

1. **Avoid work** — safe caching, routing easy requests to smaller models, sending less context.
2. **Execute faster** — batching, KV-cache management, prefix caching, speculative decoding.
3. **Shrink the model** — quantisation, distillation (check quality!).

Measure the bottleneck first; every optimisation has a cost (cache invalidation, stale answers, routing mistakes).

Hosted API or self-host?

- **Deciding variable:** sustained token volume vs the cost of a GPU fleet at realistically achievable utilisation, gated by governance needs and team skills.
- **Default:** API first; mixed setups (tiers per task, overflow capacity) are common.

Synchronous or asynchronous serving?

- **Deciding variable:** generation time vs user patience.
- A few seconds of text → synchronous, streamed. Long jobs (images, video, long documents) → a persistent **job queue** with priority levels and visible progress.

Vector, keyword or hybrid retrieval?

- **Deciding variable:** query shape. IDs, codes, exact phrases → **keyword** (lexical, e.g. BM25); paraphrases and concepts → **vector** (dense) search.
- **Default: hybrid** with **reciprocal rank fusion**, plus a **cross-encoder reranker** when top results aren't precise enough. Choose a vector store by benchmarking your corpus, filters, traffic and update rate — not by brand.

Where do permissions live?

The one sheet with no trade-off: **below the model** — in the retrieval query and tool services, checking current permissions before content reaches the model, **failing closed**. Never "in the prompt", never after generation.

How much grounding?

- **Deciding variable:** stakes.
- Low → context-only instructions, citations that must resolve, sampled review. High → mandatory checks before release, refuse or escalate when support is weak, expert review where needed.

Which evaluation layer?

- **Can code assert it?** → programmatic checks (format, schema, exact values, citations resolve).
- **Judgement at scale?** → an **LLM judge** with a written rubric, calibrated against human scores.
- **High stakes or new failure kinds?** → human experts.
- Offline results must be confirmed online; engagement gains never override safety or correctness.

How does anything ship?

Offline eval against the current version → **shadow** → **canary** or **A/B test** on a small sticky slice with a named rollback metric → ramp. Agents also climb a four-rung **autonomy ladder** per action tier — proposals only, human-approved, bounded autonomy, audited autonomy — dropping a rung automatically on regression.

How often to retrain?

- **Deciding variable:** measured quality decay, plus adversarial pressure (fraud, spam).
- A drift alarm triggers **investigation**, not automatic retraining. Online learning suits some workloads but needs validation, rollback and protection against poisoned feedback.

The one-table interview

Moment	Move
Question lands	Classify the family; name a known system it resembles
~Minute 2	Ask which depth they want: modelling or system
~Minute 8	Success metrics **with numbers**; say what is out of scope
Middle	Funnel, pipeline or loop skeleton, with a latency/cost budget on each arrow
Every choice	Deciding variable first, then its cost
~Minute 38	Close the loop: logs → evals → retrain → safe rollout
Closing	Top failure modes with their alarms; unit cost × volume

Rehearsal: cover the right column and reproduce it from the left.

15.3 Red flags that sound junior (and what to say instead)

Interviewers listen for signs you could operate what you propose. These twelve phrases restate the book's lessons in negative form.

Three that can sink an interview

Red flag	Why it hurts	Say instead
"Let's have an LLM order the feed."	An off-the-shelf LLM has never seen your users' clicks; calling it per candidate is too slow and costly at feed scale	"Ranking is a model trained on our interaction logs; LLMs can help offline, e.g. enriching item features or generating labels."
"Step one: we pretrain our own model on everything we have."	Pretraining is a huge, rarely justified investment; even fine-tuning needs a named failure	"Prompt a hosted model first; add retrieval when knowledge is missing; only then tune a compact model, if behaviour stops improving or traffic makes it pay."
An agent loop with no limits and admin credentials	Uncontrolled cost and damage	"Caps on steps, spend, time and actions; tools tiered by risk; approval gates on irreversible actions; autonomy earned step by step."

The three you will hear most often (all easy to repair)

Red flag	Say instead
Requirements without numbers ("fast and accurate")	"Resolve >50% of tickets; first token < 1 s, streamed; cost per conversation < 10% of a human-handled one."
The diagram stops at the response arrow	Log predictions and outcomes, evaluate, retrain, roll out safely — draw it and say how often each step runs
Model calls treated as free	Estimate cost per request × volume aloud; then avoid calls → speed them up → shrink the model

The control flags — a control the model can bypass

Red flag	Say instead
"We'll fine-tune the hallucinations away."	Retrieval for current or private facts, citations that must resolve, per-claim checks, refusal as a designed outcome
"Permissions are in the prompt."	Access filters in the retrieval query, user-scoped tool credentials, action gates — the model never decides authorisation
"The model will just know" / no evaluation plan	"Every change runs against a golden test set, like code through CI; these online metrics decide promotion."

The remaining three

Red flag	Say instead
Multi-agent by default	One agent by default; more only for context isolation, parallel independent subtasks, or specialised tools/models — and say which
Brand names as architecture ("Pinecone, LangChain, GPT" — a vector database, an LLM app framework, a model family)	Describe the component and its deciding variable, then a product as one example; benchmark what you already run first
Assuming failures raise errors	Wrong answers return HTTP 200. Name the silent failure, how far it spreads before anyone notices, and the alarm (drift monitors, groundedness sampling, action-rate anomalies)

Meta-flags across the whole hour

1. **Depth only when asked** — pair every choice with its cost unprompted ("batch: degrades gracefully, but results are stale").

2. **Treating follow-ups as attacks** — "what if the provider is down?" invites the fallback, its limits and its alarm.
3. **The invisible user** — say what the person experiences during waits, errors and refusals: progress messages, partial results, a way to recover.

Self-audit drill: record one mock interview and count flags in the second group — numbers, the loop, the bill.

15.4 Interview question bank

How to use it

Each answer is a **compressed recall anchor**, not a full explanation — the linked section does the teaching. Drill using the three rules above (`code/drill.py` shuffles the bank for you), and count an answer as correct only when the **deciding variable** or core mechanism came out without peeking.

Foundations (Chapters 1–3)

Q1. What is a rational agent, and how do you specify its task? A. An agent that picks the action expected to maximise its performance measure, given what it has perceived. Specify the task with PEAS — Performance measure, Environment, Actuators, Sensors — then classify the environment (observable? deterministic? static?). *(→ §1.1)*

Q2. How do AI, ML, deep learning, generative AI and LLMs relate? A. Nested sets: AI ⊃ machine learning (learns from data) ⊃ deep learning (many-layer neural networks) ⊃ generative AI (creates content) ⊃ LLMs (generate text). Agentic AI wraps models in a plan–act–observe loop. *(→ §1.5)*

Q3. BFS, DFS or A* — which and why? A. BFS finds the fewest-steps path but stores the whole frontier ($O(b^d)$ memory); DFS uses little memory but gives no optimality guarantee; A* expands by $f = g + h$ and is optimal when the heuristic never overestimates (admissible) — the cost is memory. *(→ §2.2, §2.3)*

Q4. What does alpha-beta pruning change about minimax? A. Nothing about the answer — it skips branches that cannot affect the final decision, so it searches far fewer nodes (best case roughly the square root of minimax's count with good move ordering). *(→ §2.5)*

Q5. How did AlphaGo combine search and learning? A. Monte Carlo tree search guided by a policy network (which moves to try) and a value network (how good a position is). The networks were first trained on human expert games, then improved by self-play reinforcement learning; AlphaGo Zero later dropped the human data. Search improves play, and play generates training data. *(→ §2.6)*

Q6. What is a token, and why should an engineer care? A. A subword piece produced by a tokenizer such as BPE — roughly four characters of English. Context limits, latency and price are all counted in tokens, and odd behaviour (spelling, arithmetic, non-English cost) often traces back to tokenization. *(→ §3.1)*

Q7. What is an embedding and how are two compared? A. A dense vector learned so that similar meanings land close together; compare with cosine similarity (the angle between vectors). *(→ §3.2)*

Q8. Write the attention formula and explain the √d_k. A. $\text{Attention}(Q, K, V) = \text{softmax}(QK^T/\sqrt{d_k})\cdot V$. Each token's query is scored against every key; the softmax weights mix the values. Dividing by $\sqrt{d_k}$ keeps dot products from growing with dimension, which would saturate the softmax and shrink gradients. *(→ §3.4)*

Q9. Encoder, decoder, or encoder–decoder? A. Encoders (BERT) read the whole input bidirectionally — good for understanding and embeddings. Decoders (GPT, Claude, Llama) use a causal mask and generate left to right. Encoder–decoders (T5, Whisper) transform one sequence into another. *(→ §3.8)*

Large language models (Chapter 4)

Q10. How is an LLM trained, end to end? A. Pretraining on next-token prediction over trillions of tokens → supervised fine-tuning on instruction/response examples → preference tuning (RLHF with a reward model, or DPO) → often reinforcement learning on verifiable rewards for reasoning. *(→ §4.3, §4.5, §4.6)*

Q11. What did the Chinchilla scaling result say? A. For a fixed compute budget, train on about 20 tokens per parameter; many earlier models were too big for their data. In practice teams now over-train smaller models because they are cheaper to serve. *(→ §4.4)*

Q12. What do temperature and top-p do? A. Temperature divides the logits before softmax (low = sharper, more predictable; high = more varied). Top-p samples only from the smallest set of tokens whose probabilities sum to p. Neither guarantees determinism, and some reasoning models reject these settings and are steered with an effort setting instead. *(→ §4.7)*

Q13. Why do LLMs hallucinate? A. They are trained to produce plausible continuations, not to check facts; missing, outdated or private knowledge gets filled with fluent guesses. Defences: grounding (retrieval, tools), validation, citations, evaluation, and letting the model say "I don't know". *(→ §4.10)*

Q14. What is the KV cache and what does it cost? A. Stored key and value vectors for earlier tokens, so each new token attends to them without recomputing. It saves compute but uses GPU memory that grows with context length × batch size — often the real limit on concurrency. *(→ §4.9, §11.4)*

Prompting and LLM apps (Chapters 5–6)

Q15. What goes into a good prompt? A. A clear task, relevant context, constraints (audience, length, tone), the output format, and examples when the format is subtle; delimiters to separate instructions from data; then iterate against test cases. *(→ §5.2)*

Q16. Zero-shot, few-shot, or chain-of-thought? A. Zero-shot for simple, well-known tasks; few-shot when format or style must be shown; step-by-step reasoning prompts (or a reasoning model) for multi-step logic and maths. *(→ §5.3, §5.7)*

Q17. Why is prompt injection structurally hard to stop? A. Your instructions and untrusted text arrive mixed together in one context window, with no hard wall the model is guaranteed to respect. Design as if it will sometimes be tricked: screen inputs, mark untrusted content, check outputs and actions, and keep tool permissions minimal so a tricked model has little it can break. *(→ §5.13, §12.4)*

Q18. How do you get reliable JSON out of a model? A. Use schema-constrained structured outputs or strict tool definitions where the API offers them; still validate the values; fall back to validate-and-retry. *(→ §6.4)*

Q19. Walk through the tool-use loop. A. Describe tools with JSON Schema → the model returns a tool call → your code validates the arguments, checks permissions and runs it → the result goes back to the model tied to the call's id → repeat until the model gives a final answer, with a step limit. *(→ §6.5)*

Q20. Which API errors do you retry, and how? A. Retry rate limits (429), server errors (5xx) and timeouts with exponential backoff plus jitter, honouring any retry-after header (the server's hint for how long to wait); do not retry other client errors (400 bad request, 401/403 auth) — fix the request instead; make side effects idempotent. *(→ §6.7)*

Q21. What is MCP and what problem does it solve? A. The Model Context Protocol: an open standard where a host application's clients talk JSON-RPC to servers exposing tools, resources and prompts. It turns M apps × N integrations into M + N; every server still runs with your permissions, so vet and scope it. *(→ §6.10)*

Retrieval, adaptation and evaluation (Chapters 7–8)

Q22. Describe a RAG pipeline. A. Offline: ingest documents → clean → chunk → embed → index (with metadata and permissions). Online: rewrite the query if needed → retrieve (hybrid) → rerank → assemble context → generate with citations → verify. *(→ §7.1, §7.6)*

Q23. Why combine keyword and vector retrieval rather than use vectors alone? A. Keyword search nails exact IDs and rare terms; vector search handles paraphrase and concepts. Real query mixes need both, fused (e.g. reciprocal rank fusion) and optionally reranked — evaluate on your own queries. *(→ §7.7)*

Q24. Where do most RAG failures come from? A. Don't assume one stage. Check separately: is the answer in the corpus (coverage)? was it retrieved (recall)? did it make it into the context? did the model use it faithfully? Each failure has a different fix. *(→ §7.11)*

Q25. In a RAG system, where and how are access rights enforced? A. Filter by the user's current access inside the retrieval query and re-check before anything reaches the model, caches or logs; fail closed.

Filtering after generation is too late — the model has already seen it. *(→ §7.9, §7.12)*

Q26. Does RAG eliminate hallucination? A. No. Models can still contradict or embellish retrieved text. Defend in layers: answer-only-from-context instructions, citations checked to resolve, per-claim support checks for high-stakes answers, and refusal as a designed outcome. *(→ §7.8)*

Q27. RAG or fine-tuning? A. Ask what is failing. Missing or changing facts → RAG (updatable, citable, permission-aware). Wrong behaviour, format or narrow skill → prompting, then fine-tuning. Correct but too expensive → fine-tune a smaller model. *(→ §8.1)*

Q28. How do you evaluate outputs with no single right answer? A. Layer it: programmatic checks for what code can assert; an LLM judge with a rubric, validated against human labels; expert review for high stakes; a held-out golden set run on every change; online outcomes to confirm. *(→ §8.5)*

Q29. What biases do LLM judges have? A. Preference for longer answers, for the first-position option, and for their own model family's style; mitigate with swapped orderings, clear rubrics, calibration against humans, and a different judge model. *(→ §8.5)*

Agents (Chapter 9)

Q30. Agent or workflow? A. Ask whether the sequence of steps is knowable in advance. If it can be drawn as a flowchart today, build a workflow — cheaper, testable, readable. Use an agent loop only where the path depends on discoveries, and bound it (steps, cost, time, actions). *(→ §9.1)*

Q31. Why treat a model's tool call as a proposal rather than an order? A. Authorisation lives in the runtime, not the model: it validates arguments, uses user-scoped credentials, ranks tools by consequence, and puts approval gates on irreversible actions. A fooled model can only propose. *(→ §9.3, §9.4)*

Q32. When do multiple agents beat one? A. Three cases: a subtask benefits from its own clean, small context; independent pieces can run side by side; or a stage needs its own tools or model. Otherwise multi-agent just adds cost and a longer trace. *(→ §9.7)*

Q33. How does an agent earn more autonomy? A. One action tier at a time, up a four-rung ladder: suggest only (shadow) → human-approved execution → bounded autonomy inside caps → audited autonomy. Promotion needs representative tests, reliable reviewers and verified outcomes (not approval rate alone); a regression demotes the tier automatically; caps, alarms and a per-tool kill switch never switch off. *(→ §9.10)*

Generative models beyond text (Chapter 10)

Q34. How does a diffusion model generate an image? A. Training teaches a network to predict the noise added to images at many noise levels; generation starts from pure noise and removes it step by step, steered by a text embedding (with classifier-free guidance). Latent diffusion does this in a compressed latent space for speed. *(→ §10.4, §10.5)*

Q35. Why is text-to-image serving asynchronous? A. One image can occupy a GPU for many seconds, so requests become jobs in priority queues (which also drive pricing and autoscaling), served by long-lived batched GPU workers, with moderation on both the prompt and the output. *(→ §14.4)*

Serving and inference (Chapter 11)

Q36. Time-to-first-token vs total latency? A. TTFT covers network, queueing, preprocessing and prefill of the prompt; total latency adds decoding every output token and any checks. Shorter prompts and prefix caching help TTFT; shorter outputs and faster decoding help the rest; streaming helps perceived latency. *(→ §11.2, §11.3)*

Q37. What limits how many requests one GPU can serve? A. Memory first — weights plus a KV cache per active sequence; then compute, memory bandwidth and scheduling. Continuous batching and paged KV memory raise concurrency. *(→ §11.5, §11.10)*

Q38. In what order do you optimise inference cost? A. Avoid work (caching, routing to smaller models, trimming context) → run faster (batching, KV/prefix caching, speculative decoding) → shrink the model (quantisation, distillation) — measuring quality, latency and cost at each step. *(→ §11.13, §11.14, §11.7)*

Q39. How do you estimate the cost of an LLM feature? A. Requests per day × (input tokens × input price + output tokens × output price), adjusted for cache hits and routing; say the number out loud and compare it to the value or the human baseline. *(→ §11.15)*

Q40. API or self-host? A. Sustained token volume versus the cost of a GPU fleet at realistic utilisation, gated by data governance and team skills. Start on an API; revisit with measured traffic. *(→ §11.15, §11.18)*

Safety and governance (Chapter 12)

Q41. What guardrail layers would you put around an LLM product? A. Input checks (injection, abuse, PII), untrusted-data tagging when assembling context, output checks (policy, groundedness, PII), action gates with least privilege, and monitoring plus incident response. *(→ §12.6)*

Q42. How can an AI system be biased, and what do you do about it? A. Through skewed training data, labels, proxies for protected attributes, or feedback loops. Measure outcomes per group with fairness metrics, fix data and thresholds, document decisions, and keep humans accountable for high-impact uses. *(→ §12.3)*

Q43. What privacy risks are specific to LLM apps? A. Sensitive data in prompts and logs, memorised training data, leakage across users via caches or retrieval, and third-party data retention. Minimise and redact inputs, scope retrieval by user, set retention, and check provider terms. *(→ §12.5)*

System design (Chapters 13–14; predictive systems in the ML Handbook)

Q44. Outline a framework for an AI system design interview. A. Pin down the problem → quantified success targets → where data and labels come from → the simplest model that could work → serving path with budgets → the feedback loop (logs, evals, retraining, rollout) → failure modes with alarms, and cost × volume. *(→ §13.4)*

Q45. How do you ship a new model or prompt safely? A. Offline eval against the current version → shadow → a small, fixed group of users on the new version (canary or A/B) with a pre-agreed metric that triggers rollback → gradual ramp; for agents, an autonomy ladder per action tier. *(→ §13.8)*

Q46. Why must training and serving be separate systems, and what is training–serving skew? A. Training favours throughput (how much work gets done per unit of time) over history; serving favours low latency and availability. Skew is when features are computed differently in the two paths — prevent it by reusing the same feature code in both paths, joining historical data as of each event's time, logging the features actually served, and testing that both paths agree. *(→ ML Handbook ch. 16)*

Q47. Why is every large ranking system a funnel? A. Scoring millions of items with an expensive model is too slow, so stages shrink the set: cheap retrieval of hundreds of candidates → heavier ranking → business and diversity rules. Evaluate retrieval recall and ranking quality separately. *(→ ML Handbook ch. 15, ch. 17)*

Q48. What is position bias in search and feeds? A. Items shown higher get more clicks regardless of relevance, so raw clicks mix relevance with exposure. Correct with randomised data or exposure models such as propensity weighting (counting each click more when the item was unlikely to be seen), and evaluate the correction. *(→ ML Handbook ch. 17)*

Q49. Data drift vs concept drift? A. Data drift: the input distribution changes. Concept drift: the relationship between inputs and outcomes changes. Distribution monitors hint at the first; only (often delayed) outcome labels prove the second. A drift alarm triggers investigation, not automatic retraining. *(→ ML Handbook ch. 16)*

Q50. Your fraud model blocks a transaction. What data problem does that create? A. Selective labels: you never learn what would have happened if it had been approved. Use investigated cases and other permitted evidence; any exploration must stay within approved low-risk limits — never approve known high-risk activity just to get labels. *(→ ML Handbook ch. 18)*

Q51. Why keep a small exploration slice in a learning loop? A. The model decides what users see, so it shapes its own future training data. Controlled exploration shows outcomes outside its usual choices (record the selection probabilities); it reduces but does not remove bias, and must respect safety limits. *(→ ML Handbook ch. 16)*

Q52. Why do ad-click models need calibration, not just good ranking? A. Predicted click probabilities feed into auction ranking and expected value, so the numbers themselves must be right, not only their order. Check calibration per segment and validate any correction on held-out data. *(→ ML Handbook ch. 18)*

Scoring yourself

- **Pass mark:** you name the variable that drives the choice without a hint — for example how late labels arrive, whether tokens are mostly input or output, how risky an action is, what queries look like, or how much is at stake. A memorised answer collapses when the interviewer changes the scenario; one you can re-derive adapts.
- **40+ strong answers** suggests good recall; it does not prove readiness — also practise whole designs and follow-ups.
- **Below 30:** work through the decision cheat sheets, then the linked sections.

Drilling it with code

`code/drill.py` reads the questions straight from this README, draws a seeded random session of five, and shows how a **Leitner** spaced-repetition schedule (a flash-card system that reviews well-known cards less and less often) spaces reviews: a correct answer promotes a card to a box reviewed less often (1 → 3 → 7 → 14 days); a miss sends it back to box 1, to be seen again after a day.

```
# code/drill.py (core)
REVIEW_EVERY_DAYS = {1: 1, 2: 3, 3: 7, 4: 14}      # box -> days until next review

def load_bank(path):
    text = path.read_text(encoding="utf-8")
    pairs = re.findall(r"^\*\*Q\d+\.\s*(.+?)\*\*\s*\nA\.\s*(.+)$", text, flags=re.M)
    return [(q.strip(), a.strip()) for q, a in pairs]

def leitner(results, box=1):
    steps = []
    for ok in results:
        box = min(box + 1, 4) if ok else 1
        steps.append((box, REVIEW_EVERY_DAYS[box]))
    return steps
```

Output (abridged):

```
Loaded 52 questions from the README.

1. What is the KV cache and what does it cost?
   (30 s, out loud)  anchor: Stored key and value vectors for earlier tokens, so each new token attends to them
without recomputing.
...
5. BFS, DFS or A* — which and why?
   (30 s, out loud)  anchor: BFS finds the fewest-steps path but stores the whole frontier (O(bᵈ) memory); ...

Leitner schedule for one card answered right, right, wrong, right:
  review 1: box 2 -> next review in 3 day(s)
  review 2: box 3 -> next review in 7 day(s)
  review 3: box 1 -> next review in 1 day(s)
  review 4: box 2 -> next review in 3 day(s)
```

15.5 Future trends (as of 2026)

Directions of travel visible today, not forecasts of products or dates; revisit yearly — some will stall.

Where models are heading

In more depth in §4.15 of Chapter 4: longer, more reliable multi-step reasoning; answers grounded in tools and cited sources; multimodal input and output as standard; more capable agents; interpretability

research; small specialised and on-device models; better data efficiency; architectural efficiency (mixture-of-experts, quantisation, speculative decoding, hybrid attention/state-space designs).

Agents maturing

The practical trend is **bounded autonomy**, not "fully autonomous AI": narrow tool sets, spending limits, audit trails and approval gates, with independence widened as evidence accumulates (Chapter 9). Open standards such as MCP (§6.10) make agents easier to plug into real systems — and permission design more important.

AI converging with other technologies

Pairing	What AI adds	Realistic now	Still largely experimental
AI + IoT (internet-connected sensors and devices)	Learns from sensor streams to predict and adapt	Predictive maintenance (unusual vibration before a machine fails); thermostats that learn schedules; wearables flagging abnormal heart rhythms	City-wide adaptive traffic, fully automated infrastructure repair scheduling
AI + AR/VR (digital overlays on the real world / fully virtual worlds)	Understands scene, gestures and speech in real time	Live translation and captions, object-recognition overlays, adaptive training simulations (surgery, aviation, factory work)	Seamless multilingual virtual workplaces with AI co-designers
AI + robotics	Perception, planning and adaptation for machines that act physically	Warehouse picking and sorting, cobots beside people, agricultural drones, sidewalk delivery pilots	General-purpose household or humanoid robots; fully automated end-to-end logistics
AI + quantum computing	—	Quantum computers are small and error-prone; research focuses on simulating molecules and materials	Any practical ML speed-up is **unproven**; quantum speed-ups exist only for specific problem types

Two accuracy notes: quantum computers are not "exponentially faster" in general — only for particular problems (e.g. factoring large numbers into primes via Shor's algorithm, certain simulations). And the security story runs the other way from what is often claimed: a large quantum computer would break today's common public-key encryption (the maths behind HTTPS and digital signatures), which is why NIST published its first **post-quantum cryptography** standards in 2024 and systems are migrating.

The future of work: augmentation first

- **Automation** fits repetitive, rule-like tasks (routine data checks, document sorting, parts of assembly); **augmentation** fits most knowledge work — AI drafts, summarises, searches and flags, a person decides (AI screens large applicant pools but people interview; clinicians use AI for diagnosis support but keep responsibility).
- **Changing roles more than new titles**: the biggest shift is *AI fluency inside existing jobs* — directing AI with clear instructions and context, checking outputs. "Prompt engineer" was widely forecast as a big job category but rarely stuck as a title, because the skill is useful in nearly every role.
- **Growing roles**: AI/LLM engineers who build and evaluate AI features; people who **audit** AI for bias, privacy and compliance (ethics, governance, risk); **AI product and project managers** linking technical teams to business goals, budgets and rollout; evaluation and red-teaming specialists.
- **Lasting skills**: fundamentals (data, statistics, systems), evaluation and measurement, communication, domain knowledge, ethical judgement.

Regulation and governance

Rules arrive in stages and dates move. The EU AI Act (in force since August 2024): bans and general-purpose-model duties already apply; the 2026 Digital Omnibus on AI (Regulation (EU) 2026/1744, in force 27 July 2026) moved high-risk obligations to 2 December 2027 for Annex III uses (hiring, credit) and 2

August 2028 for AI inside Annex I products, added bans on generating non-consensual intimate imagery or child sexual abuse material from 2 December 2026, and gave generative systems already on the market until 2 December 2026 to mark output as AI-generated under Article 50. Organisations also adopt frameworks such as the NIST AI RMF. Expect documentation, evaluation evidence and human oversight to become normal parts of shipping AI; check the current text before quoting a date (§12.12).

Self-check

1. Is quantum computing a near-term way to speed up training? → No; ML speed-ups are unproven and today's machines are small and noisy.
2. Most common way AI changes jobs today? → People in current jobs learn to direct AI well; replacement and new titles are smaller effects.
3. "Bounded autonomy"? → Limited tools, budgets and approvals, with independence widened only on evidence.

15.6 A learning roadmap

How to use it

Move through the stages in order; each ends with a project proving you can do it. Skip a stage only if you can already build its project without notes.

Stage	Learn	Where	Prove it with
0. Python	Syntax, functions, data structures, OOP, type hints, testing	Python Handbook (ch. 1–15)	A tested command-line tool
1. ML foundations	Learning types, maths intuition, NumPy/pandas/scikit-learn, evaluation	ML Handbook (ch. 1–9)	A classifier with a proper train/validation/test split and a written evaluation
2. Deep learning to transformers	Neural nets, attention, tokens, embeddings	ML Handbook ch. 10–12; Chapters 3–4 here	Train a tiny model in PyTorch; explain attention with worked numbers
3. Building with LLMs	Prompting, API calls, structured output, tools, MCP	Chapters 5–6	A small assistant that calls one tool and returns validated JSON
4. Grounding and evaluation	Embeddings, vector search, RAG, fine-tuning vs RAG, eval sets	Chapters 7–8	A RAG app over your own notes with a 30-question golden test set
5. Agents	Tool loops, planning, memory, guardrails, multi-agent trade-offs	Chapter 9	A bounded agent with step/cost limits and an approval gate
6. Beyond text; production	Diffusion and multimodal models; serving, latency, cost; safety and governance	Chapters 10–12	A cost/latency estimate and a threat model for your RAG app
7. Design and interviews	Design frameworks, case studies, this review	Chapters 13–15; ML Handbook ch. 15–18	Narrate two full designs aloud in 45 minutes each

Keeping it sharp

1. **Drill the question bank** (§15.4) in any interview week, with the three drilling rules.
2. **Narrate one full design per session** — e.g. the inference-cost exercise in Chapter 11 (arithmetic) and a Chapter 14 case (control and safety).
3. **Critique real systems** at work: invariants first (permissions below the model, a feedback loop, a cost estimate, alarms for silent failure).
4. **Read primary sources** — model cards, official docs, papers — and date-check every claim (§1.9).

Where to go next

AI systems still stand on classic distributed-systems machinery. Companion notes in this repository:

- System Design Patterns — caching, sharding, queues, replication and end-to-end designs; start with System Design Fundamentals.
- Designing Data-Intensive Applications notes — storage, replication, partitioning, streams, consistency in depth.
- Microservices patterns — service boundaries, communication, resilience, data consistency.
- Low-Level Design Handbook — object-oriented design for the code inside those services.

Final thoughts

Three habits outlast every model release: **experiment** (small prototypes; failures teach fastest), **collaborate** (technical and non-technical people together catch what either misses), **stay grounded** (measure quality, count the cost, keep the affected people in view).

15.7 Glossary

Alphabetical; each term is defined once here (alternative names in brackets). "Ch. N" links to the chapter that explains it; "ML N" to the companion ML Handbook.

Term	Meaning	Where
A* search	Best-first search ordering nodes by f = g + h (cost so far + heuristic estimate); optimal with an admissible heuristic	Ch. 2
A2A (Agent2Agent)	Open protocol for AI agents built by different vendors to discover each other and hand off tasks	Ch. 9
A/B test	Randomly splitting live traffic between two versions to compare a metric	Ch. 13
AC-3 (arc consistency)	CSP algorithm that removes values with no compatible partner in a neighbouring variable	Ch. 2
Access control list (ACL)	List recording which users or groups may read or change each item	Ch. 7
Accountability	Clear responsibility for an AI system's outcomes, with a named owner who can be held to account	Ch. 12
Action gate	Deterministic code check that approves, blocks or escalates every action a model proposes	Ch. 9
Activation	Intermediate value produced inside a network as data flows through a layer	Ch. 11
Actuators	The parts through which an agent acts on its environment (wheels, API calls, messages)	Ch. 1
Admissible heuristic	A heuristic that never overestimates the true remaining cost	Ch. 2
Agent (AI agent)	A system that uses a model in a loop to choose and take actions through tools toward a goal	Ch. 9
Agentic AI	AI that plans and acts (calls tools, takes steps) rather than only producing a single output	Ch. 1
AGI (artificial general intelligence)	Hypothetical AI matching humans across most cognitive tasks; no agreed definition	Ch. 1
AI gateway	Single service in front of all model calls that handles auth, routing, limits, logging and cost	Ch. 13
AI literacy	Basic understanding of what AI can and cannot do; required of staff by the EU AI Act	Ch. 12
AI winter	Period when AI funding and interest collapsed after over-promising (mid-1970s, late 1980s)	Ch. 1
ALiBi	Positional method that adds a distance-based penalty to attention scores instead of position vectors	Ch. 3
Alignment	Making a model's behaviour match human intentions and values	Ch. 12
Alpha-beta pruning	Minimax optimisation that skips branches which cannot change the decision	Ch. 2
AlphaGo	DeepMind's Go program combining tree search with policy and value networks (2016)	Ch. 2
Answer relevance	Whether a RAG answer actually addresses the question asked	Ch. 7
API (application programming interface)	Defined way for one program to call another, usually over HTTP for model providers	Ch. 6
API key	Secret string identifying your account to a model provider; keep it out of code	Ch. 6
Approximate nearest neighbour (ANN)	Search that finds almost-closest vectors much faster than exact search	Ch. 7

Term	Meaning	Where
Artificial intelligence (AI)	Building machines that perceive, reason and act to achieve goals	Ch. 1
Artificial superintelligence (ASI)	Hypothetical AI far beyond human ability in nearly every domain	Ch. 1
ASR (automatic speech recognition)	Converting spoken audio into text (Whisper is one model)	Ch. 10
Attention	Mechanism that lets each token weigh and mix information from other tokens	Ch. 3
Audit trail	Tamper-resistant log of who or what did each action, when and why	Ch. 9
Autoencoder	Network trained to compress input into a small code and reconstruct it	Ch. 10
Autoregressive	Generating one token at a time, each conditioned on those before it	Ch. 4
Autoscaling	Automatically adding or removing servers or GPU workers as load changes	Ch. 14
AWQ	Activation-aware weight quantization: 4-bit weight compression that protects the most important channels	Ch. 11
Backoff (exponential)	Waiting progressively longer between retries, usually with random jitter	Ch. 6
Back-of-the-envelope estimation	Quick rounded arithmetic to size cost, storage or traffic before designing	Ch. 13
Backpressure	Slowing or rejecting incoming work when a system is saturated	Ch. 11
Backpropagation	Algorithm that computes how much each weight contributed to the error, so gradients can update it	Ch. 3
Backtracking search	CSP search that assigns variables one at a time and undoes a choice when a constraint fails	Ch. 2
Back-translation	Translating target-language text back into the source language to create extra training pairs	Ch. 14
Barge-in	A user speaking over a voice assistant, which must stop talking and listen	Ch. 13
Base model	A pretrained model before instruction or preference tuning	Ch. 4
Batch inference	Precomputing predictions ahead of time for later lookup	ML 16
Batching (continuous)	Adding and removing sequences from a GPU batch at every decoding step to keep the GPU busy	Ch. 11
Beam search	Decoding that keeps the k most probable partial sequences at each step	Ch. 4
BERT	Encoder-only transformer (2018) trained by masked-word prediction; used for understanding and embeddings	Ch. 3
Best-first search	Search that always expands the node with the best evaluation score	Ch. 2
BF16 / FP16 / FP8	Compact number formats with 16 or 8 bits used to store weights and run maths faster (vs 32-bit FP32/float32, 4 bytes per number)	Ch. 11
Bias (fairness)	Systematically worse or unfair outcomes for some groups	Ch. 12
BLEU	Translation metric based on overlapping word sequences with a reference; a rough signal only	Ch. 8

Term	Meaning	Where
BM25	Classic keyword-ranking formula based on term frequency and document length	Ch. 7
Bootstrap	Estimating uncertainty by recomputing a metric on many random resamples of the data	Ch. 14
Bounded autonomy	Letting an agent act alone only within set tools, budgets and approval rules	Ch. 9
BPE (byte-pair encoding)	Tokenizer that builds a vocabulary by repeatedly merging the most frequent symbol pairs	Ch. 3
Breadth-first search (BFS)	Uninformed search that expands the shallowest nodes first (FIFO queue)	Ch. 2
C2PA (content credentials)	Open standard for signed "content credentials" metadata recording how a piece of media was made and edited	Ch. 10
Calibration	Whether predicted probabilities match observed frequencies (70% confident = right 70% of the time)	Ch. 4
Canary release	Sending a small slice of traffic to a new version before full rollout	Ch. 13
Cascade (model)	Trying a cheap model first and escalating to a stronger one only when needed	Ch. 11
Catastrophic forgetting	A model losing earlier skills after being fine-tuned on new data	Ch. 8
Causal mask	Attention mask that stops a token from seeing tokens after it	Ch. 3
CCPA / CPRA	California's consumer privacy laws giving rights to know, delete and opt out	Ch. 12
Chain-of-thought (CoT)	Prompting or training a model to write intermediate reasoning steps	Ch. 5
CHAIR	Captioning hallucination metric: share of objects mentioned in captions that are not in the image	Ch. 14
Chat template	Model-specific format that marks system, user and assistant turns in the token stream	Ch. 4
ChatGPT	OpenAI's chat assistant whose launch (Nov 2022) brought LLMs to the mass market	Ch. 1
Chinchilla scaling	Finding that compute-optimal training uses about 20 tokens per parameter	Ch. 4
chrF	Translation metric based on character n-gram overlap; works better than BLEU for many languages	Ch. 14
Chunking	Splitting documents into passages sized for embedding and retrieval	Ch. 7
CI/CD (continuous integration / delivery)	Automatically testing every change and shipping it when the tests pass	Ch. 8
Citation (grounded)	A pointer from a claim in the answer to the source passage supporting it	Ch. 7
Classifier-free guidance	Diffusion technique that strengthens adherence to the prompt by mixing conditional and unconditional predictions	Ch. 10
CLIP	Model trained to place matching images and captions close together in one embedding space	Ch. 10

Term	Meaning	Where
Closed (proprietary) model	Model available only through the vendor's API; weights are not published	Ch. 4
Cobot (collaborative robot)	Robot designed to work safely alongside people	Ch. 9
Cohen's kappa	Agreement between two labellers corrected for agreement expected by chance	Ch. 8
Cold start	Lack of history for a new user or item, making personalisation hard	ML 13
COMET	Learned translation-quality metric that scores output with a trained model	Ch. 14
Compaction (context)	Summarising older conversation or agent history to free room in the context window	Ch. 9
Compute-bound	Limited by arithmetic speed rather than by memory bandwidth (prefill is compute-bound)	Ch. 4
Concept drift	Change in the relationship between inputs and the outcome	ML 16
Constitutional AI	Anthropic's method of training a model to follow a written set of principles, using AI feedback	Ch. 12
Constraint satisfaction problem (CSP)	Problem of assigning values to variables so that all constraints hold	Ch. 2
Context assembly	Building the prompt from instructions, memory, retrieved passages and the user turn within a token budget	Ch. 13
Context rot	Quality decline as a long context fills with stale or irrelevant material	Ch. 9
Context window	Maximum number of tokens a model can read (and write) in one request	Ch. 4
Contextual retrieval	Prepending a short model-written summary of the surrounding document to each chunk before indexing	Ch. 7
ControlNet	Add-on network that steers a diffusion model with an extra input such as a pose or edge map	Ch. 10
Copilot	Assistant that drafts or suggests while a person stays in charge of the final action	Ch. 13
Cosine similarity	Similarity of two vectors measured by the angle between them	Ch. 3
Counterfactual test	Changing only a sensitive attribute (e.g. a name) to see whether the output changes	Ch. 12
CPU / GPU / TPU	Processor types: general-purpose CPU; massively parallel GPU; Google's ML-specific TPU	Ch. 11
Cross-attention	Attention where queries come from one sequence and keys/values from another (e.g. prompt into image)	Ch. 10
Cross-encoder / reranker	Second-stage model that scores query and document together to reorder retrieved candidates; accurate but slow, so used only on a shortlist	Ch. 7
Cross-entropy loss	Training loss that punishes low probability on the correct token	Ch. 3
CRUD	Create, read, update, delete: the basic operations on stored data	Ch. 13
CSAT	Customer satisfaction score, usually from a post-interaction survey	Ch. 13

Term	Meaning	Where
DALL·E	OpenAI's family of text-to-image models	Ch. 10
Data drift	Change in the distribution of model inputs over time	ML 16
Dead-letter queue (DLQ)	Holding area for jobs that failed repeatedly, kept for inspection instead of retrying forever	Ch. 14
Debounce	Waiting until input pauses before acting, to avoid one request per keystroke	Ch. 13
Decode (phase)	Generating output tokens one at a time after prefill	Ch. 11
Decoder-only transformer	Transformer that generates text left to right using causal masking (GPT, Claude, Llama)	Ch. 3
Deep learning	Machine learning with many-layer neural networks	Ch. 1
Deepfake	Realistic synthetic image, audio or video of a real person	Ch. 10
DeepSeek	Chinese AI lab whose open-weight models (V3, R1) showed strong results at low training cost	Ch. 4
Defence in depth	Several independent safety layers, so one failure is not enough to cause harm	Ch. 12
Degradation ladder	Planned sequence of cheaper fallbacks used as load rises or a dependency fails	Ch. 11
Delimiters	Markers (e.g. XML tags) that separate instructions from data in a prompt	Ch. 5
Depth-first search (DFS)	Uninformed search that expands the deepest node first (LIFO stack)	Ch. 2
Diffusion model	Generative model that learns to reverse a gradual noising process	Ch. 10
Dijkstra's algorithm	Shortest-path algorithm that always expands the cheapest known node (uniform-cost search)	Ch. 2
Disaggregated serving	Running prefill and decode on separate GPU pools so each can be tuned	Ch. 11
Distillation (teacher / student)	Training a smaller "student" model to imitate a larger "teacher"	Ch. 11
DiT (diffusion transformer)	Diffusion model whose denoiser is a transformer over image or video patches	Ch. 10
DPO (direct preference optimization)	Preference tuning directly from pairs of preferred and rejected answers, without a separate reward model	Ch. 4
DreamBooth	Fine-tuning a diffusion model on a few photos so a rare token (an unused word that comes to mean "this subject") generates that subject	Ch. 10
Durable task state	Agent progress saved outside the model so a task can resume after a crash	Ch. 9
Edge AI	Running models on the device itself (phone, car, sensor) instead of in the cloud	Ch. 4
ELBO	Evidence lower bound: the VAE training objective (reconstruction minus KL penalty)	Ch. 10
ELIZA effect	People attributing understanding to a program because its replies sound human	Ch. 1
Embedding	Dense vector representing the meaning of a token, text or item	Ch. 3

Term	Meaning	Where
Encoder	Transformer stack that reads the whole input bidirectionally (BERT)	Ch. 3
Encoder-decoder	Architecture where an encoder reads the input and a decoder generates the output (T5, Whisper)	Ch. 3
Encryption	Scrambling data so only holders of the key can read it	Ch. 12
Entailment / NLI	Natural language inference: judging whether one text logically supports another	Ch. 7
Episodic vs semantic memory	Memory of specific past events vs memory of general facts	Ch. 9
EU AI Act	EU regulation sorting AI uses by risk tier, with duties scaling from transparency to bans; Annex III lists high-risk uses (hiring, credit…), Annex I covers AI inside already-regulated products	Ch. 12
Evaluation function	Game-search estimate of how good a position is, used when search stops early	Ch. 2
Factorised attention	Video attention split into spatial attention within each frame and temporal attention across frames, far cheaper than full spacetime attention	Ch. 14
Golden set (evaluation set)	Fixed, representative test cases with expected outcomes, run on every change	Ch. 8
Exact match (EM)	Metric: 1 if the output equals the reference exactly, else 0	Ch. 8
Expert parallelism	Placing different mixture-of-experts experts on different GPUs	Ch. 11
Expert system	Rule-based AI encoding specialist knowledge as if-then rules (1970s–80s)	Ch. 1
Exploration (vs exploitation)	Occasionally trying options the model would not choose, to learn about them	ML 16
F1 score	Harmonic mean of precision and recall	Ch. 8
Fail closed	If a safety or permission check cannot run, deny rather than allow	Ch. 13
Fair use	US legal doctrine allowing some unlicensed use of copyrighted work; its application to AI training is contested	Ch. 12
FAISS	Meta's open-source library for fast vector similarity search	Ch. 7
Faithfulness	Whether every claim in an answer is supported by the retrieved context	Ch. 7
Feature store	System holding feature values: offline for training, online for low-latency serving	ML 16
Feedback loop	Logging predictions and outcomes to evaluate, retrain and improve the system	Ch. 13
Feed-forward network (FFN)	Small two-layer network applied to each token inside every transformer block	Ch. 3
Few-shot prompting	Including a handful of worked examples in the prompt	Ch. 5
FID (Fréchet Inception Distance)	Image-quality metric comparing feature statistics of real and generated images; lower is better	Ch. 10
Fill-in-the-middle (FIM)	Code-completion training where the model predicts a gap given code before and after it	Ch. 13
Fine-tuning	Continuing training of a pretrained model on task-specific data	Ch. 8

Term	Meaning	Where
FlashAttention	Attention implementation that avoids storing the full score matrix, cutting memory traffic	Ch. 3
FLOPs	Floating-point operations; the count of arithmetic steps used to measure compute	Ch. 4
Forward checking	CSP technique that removes now-illegal values from neighbours after each assignment	Ch. 2
Foundation model	Large model pretrained on broad data and adapted to many tasks	Ch. 1
Frequency / presence penalty	Sampling settings that discourage repeating tokens already used	Ch. 4
Frontier (search)	The set of discovered but not yet expanded nodes	Ch. 2
Funnel (ranking)	Multi-stage pipeline: cheap retrieval of many candidates, then heavier ranking of few	ML 15
GAN (generative adversarial network)	A generator (turns random noise into samples) and a discriminator (tells real samples from generated ones) trained against each other	Ch. 10
GDPR	EU data-protection law (2018) covering consent, access, deletion and lawful processing	Ch. 12
Generative AI	AI that creates new content (text, images, audio, code)	Ch. 1
Genetic algorithm	Local search that evolves a population with selection, crossover and mutation	Ch. 2
GGUF	File format for quantized models used by llama.cpp and Ollama for local inference	Ch. 11
Goal test	Check that decides whether a search state is a solution	Ch. 2
Goodput	Throughput counting only requests that met their latency target	Ch. 11
GPAI (general-purpose AI) model	EU AI Act term for foundation models usable across many tasks, with their own duties	Ch. 12
GPT	OpenAI's decoder-only "generative pre-trained transformer" model family	Ch. 4
GPTQ	Post-training 4-bit quantization that adjusts remaining weights to offset rounding error	Ch. 11
GPU memory sizing	Estimating memory for weights plus KV cache plus overhead	Ch. 11
Gradient	Direction and size of change in the loss for a small change in each weight	Ch. 3
Greedy decoding	Always choosing the single most probable next token	Ch. 4
Groundedness check	Post-generation check that each claim is supported by the supplied sources	Ch. 7
Grounding	Tying model answers to supplied sources or tool results	Ch. 7
Grouped-query attention (GQA)	Attention variant where several query heads share one key/value head, shrinking the KV cache	Ch. 3
GRPO	Group relative policy optimization: RL that scores each answer against others sampled for the same prompt, without a value model	Ch. 4
Guardrails	Checks around a model (input, output, action) that enforce policy	Ch. 12
Hallucination	Fluent but false or unsupported model output	Ch. 4
Heuristic	Estimate of the remaining cost to the goal, used to guide search	Ch. 2

Term	Meaning	Where
Hill climbing	Local search that always moves to a better neighbour; can get stuck in local optima	Ch. 2
HNSW	Graph-based approximate nearest-neighbour index (Hierarchical Navigable Small World)	Ch. 7
HTTP status codes	Numeric results of a web request: 200 OK, 4xx client error (429 rate-limited), 5xx server error	Ch. 6
Hugging Face	Hub and libraries (Transformers, Datasets, PEFT, TGI) for sharing and running open models	Ch. 4
Human-in-the-loop	A person reviews or approves model outputs or actions	Ch. 9
Hybrid search	Combining keyword and vector retrieval results	Ch. 7
HyDE	Retrieving with a hypothetical answer's embedding instead of the raw question	Ch. 7
Idempotency	Property that repeating an operation has the same effect as doing it once	Ch. 6
Imagen	Google's family of text-to-image models	Ch. 10
Image-to-image / inpainting	Editing an existing image, or regenerating only a masked region	Ch. 10
Implicit vs explicit feedback	Signals from behaviour (copies, edits, retries) vs direct ratings (thumbs up/down)	Ch. 8
Inference	Running a trained model to get outputs	Ch. 11
Inference server	Software that loads a model and serves requests efficiently (vLLM, TGI, TensorRT-LLM)	Ch. 11
InstructGPT	OpenAI's 2022 model that popularised SFT followed by RLHF	Ch. 4
Instruction tuning (SFT)	Supervised fine-tuning on instruction–response pairs to make a model follow requests	Ch. 4
Interpretability	Understanding why a model produced an output, or what its internals represent	Ch. 4
Inverted index	Map from each word to the documents containing it; the core of keyword search	Ch. 7
Iterative deepening	Repeated depth-limited DFS with growing limits; BFS's completeness with DFS's memory	Ch. 2
IVF index	ANN index that clusters vectors and searches only the nearest clusters (nprobe)	Ch. 7
Jailbreak	Prompt crafted to make a model ignore its safety rules	Ch. 12
Jitter	Random variation added to retry delays so clients do not retry in lockstep	Ch. 6
JSON	Lightweight text format for structured data built from objects, arrays, strings and numbers	Ch. 6
JSON mode	API setting that guarantees syntactically valid JSON but not a specific schema	Ch. 6
JSON Schema	Standard for describing the shape of JSON data; used for tools and structured output	Ch. 6
JSON-RPC	Protocol for calling remote functions by sending JSON request and response messages; MCP uses version 2.0	Ch. 6
Kill switch	Control that instantly disables a feature, tool or agent	Ch. 9

Term	Meaning	Where
KL divergence	Measure of how one probability distribution differs from another	Ch. 4
Knowledge cutoff	Date after which a model's training data has no information	Ch. 4
KV cache	Stored attention keys and values for earlier tokens, reused during decoding	Ch. 11
LangChain / LlamaIndex	Popular open-source frameworks for building LLM and RAG pipelines	Ch. 7
Large language model (LLM)	Transformer trained on huge text corpora to predict the next token	Ch. 4
Latency	Time one request takes, start to finish	Ch. 11
Latency budget	Maximum time allotted to each stage of a request	Ch. 13
Latent diffusion	Diffusion performed in a compressed latent space (Stable Diffusion)	Ch. 10
Latent space	Compressed internal representation a model maps data into	Ch. 10
Layer normalization	Rescaling activations within a layer to stabilise training	Ch. 3
Least privilege	Granting only the minimum permissions a component needs	Ch. 9
Legal hold	Requirement to preserve data that might be evidence, overriding normal deletion	Ch. 7
Lexical search	Matching on the actual words in a query (keyword search)	Ch. 7
Llama	Meta's family of open-weight LLMs	Ch. 4
Llama Guard	Open model that classifies prompts and responses against a safety policy	Ch. 12
llama.cpp / Ollama	Tools for running quantized LLMs locally on laptops and CPUs	Ch. 11
LLM-as-a-judge	Using a model with a rubric to grade other model outputs	Ch. 8
LLM.int8()	8-bit quantization method that keeps outlier features in 16-bit	Ch. 11
LLMOps	Practices for versioning, evaluating, deploying and monitoring LLM features	Ch. 13
Local search	Optimisation that improves a single current state step by step	Ch. 2
Logits	Raw, unnormalised scores a model outputs before softmax	Ch. 4
LoRA	Low-rank adaptation: fine-tuning by training small added matrices instead of all weights	Ch. 8
Lost in the middle	LLMs using information at the start and end of a long context better than the middle	Ch. 7
LSTM	Long short-term memory: a recurrent network that carries state through a sequence; pre-transformer	Ch. 3
Machine learning (ML)	Systems that learn patterns from data rather than following hand-written rules	Ch. 1
Manhattan distance	Sum of horizontal and vertical distance; admissible on a grid with four-way moves	Ch. 2
Map-reduce (summarisation)	Summarise each chunk separately (map), then combine the partial summaries (reduce)	Ch. 14
Masked language modeling	Pretraining by hiding some words and predicting them from both sides (BERT)	Ch. 3

Term	Meaning	Where
MCP (Model Context Protocol)	Open protocol connecting AI hosts to servers exposing tools, resources and prompts	Ch. 6
Medusa / EAGLE	Speculative-decoding methods that add small heads to the model to draft several tokens	Ch. 11
Memory (agent/conversation)	Stored information carried across turns or sessions within a context budget; long-term memory is stored outside the context window and retrieved when relevant	Ch. 6
Memory-bound	Limited by how fast data moves from memory rather than by arithmetic (decode is memory-bound)	Ch. 4
Metadata filtering	Restricting search to items whose attributes (date, owner, type) match a condition	Ch. 7
Midjourney	Commercial text-to-image service	Ch. 10
Minimax	Game search assuming both players play optimally	Ch. 2
Mistral	French AI company and its family of open-weight and hosted models	Ch. 4
Mixture of experts (MoE)	Layer where a router sends each token to a few of many expert sub-networks	Ch. 3
MLA (multi-head latent attention)	Attention variant that compresses keys and values into a small latent vector to shrink the KV cache	Ch. 3
MLOps	Practices for deploying, monitoring and retraining ML models in production	Ch. 1
Mode collapse	A GAN producing only a few kinds of output instead of the full variety	Ch. 10
Model card	Document describing a model's intended use, data, evaluation and limits	Ch. 12
Monte Carlo tree search (MCTS)	Game search that grows a tree using random playouts and UCB1 selection	Ch. 2
MOS (mean opinion score)	Average of human 1–5 ratings, used to judge speech quality	Ch. 10
MQM	Multidimensional Quality Metrics: human annotation of translation errors by type and severity	Ch. 14
MRR (mean reciprocal rank)	Average of 1 / rank of the first relevant result	Ch. 7
MRV heuristic	Minimum remaining values: in a CSP, assign the variable with the fewest legal values first	Ch. 2
Multi-agent system	Several cooperating agents, each with its own context, tools or role	Ch. 9
Multi-head attention	Several attention heads in parallel, each learning different relations	Ch. 3
Multimodal model	Model that handles more than one data type (text, image, audio, video)	Ch. 4
Multi-query attention (MQA)	Attention variant where all query heads share one key/value head	Ch. 3
Narrow AI	AI built for specific tasks	Ch. 1
NDCG	Ranking metric that rewards relevant items near the top, with graded relevance	Ch. 7
Negative prompt	Text describing what a diffusion model should avoid	Ch. 10
NER (named-entity recognition)	Finding names of people, places, organisations and similar in text	Ch. 12

Term	Meaning	Where
Next-token prediction	Training objective: predict the following token given all previous ones	Ch. 4
NIST AI RMF	US AI Risk Management Framework organised as Govern, Map, Measure, Manage	Ch. 12
Noise schedule	How much noise a diffusion model adds at each step	Ch. 10
Non-functional requirements (NFRs)	Qualities a system must have (latency, availability, cost, privacy) rather than features	Ch. 13
NumPy / pandas / scikit-learn	Python libraries for numeric arrays, data tables and classic ML	ML 1
NVLink	NVIDIA's high-speed link between GPUs in a server	Ch. 11
OAuth	Standard for granting an app limited access to an account without sharing the password	Ch. 6
Observability	Logs, metrics and traces that show what a system is doing and why	Ch. 11
OCR	Optical character recognition: reading text from images or scanned pages	Ch. 14
One-hot vector	Vector of zeros with a single 1 marking which item it is	Ch. 3
Online inference	Computing predictions at request time	ML 16
OOP (object-oriented programming)	Organising code as objects that bundle data with the methods that act on it	Python Handbook
Open-weight model	Model whose trained weights are published for download (Llama, Qwen, Mistral)	Ch. 4
Orchestrator-workers	Agent pattern where a lead agent splits a task and hands parts to worker agents	Ch. 9
Overfitting	Model memorises training data and fails on new data	Ch. 8
Over-refusal	Refusing safe requests because they superficially resemble harmful ones	Ch. 12
OWASP Top 10 for LLMs	Security community's list of the most critical LLM application risks	Ch. 12
p50 / p95 / p99	Percentile latency: the time that 50%, 95% or 99% of requests finish within	Ch. 11
PagedAttention	KV-cache memory managed in fixed-size pages to cut fragmentation (vLLM)	Ch. 11
Parameters (weights)	The learned numbers inside a model; model size is counted in parameters	Ch. 4
pass@k / pass^k	Chance at least one of k attempts succeeds / chance all k attempts succeed	Ch. 9
Path cost	Total cost of the actions taken along a search path	Ch. 2
PEAS	Performance measure, Environment, Actuators, Sensors: a way to specify an agent's task (percepts = everything the agent has sensed so far)	Ch. 1
PEFT	Parameter-efficient fine-tuning: adapting a model by training a small fraction of parameters	Ch. 8
Perplexity	Exponential of average negative log-likelihood; lower = model less "surprised"	Ch. 4

Term	Meaning	Where
pgvector	PostgreSQL extension that stores vectors and supports nearest-neighbour search	Ch. 7
PII	Personally identifiable information	Ch. 12
Pinecone / Weaviate / Qdrant / Milvus	Dedicated vector-database products	Ch. 7
Pipeline parallelism	Placing different layers of a model on different GPUs or nodes	Ch. 11
Plan-and-execute	Agent pattern that writes a whole plan first, then carries out the steps	Ch. 9
Policy network / value network	AlphaGo's networks that suggest promising moves / estimate who is winning	Ch. 2
Position bias	Higher-ranked items get more attention and clicks regardless of relevance	ML 17
Positional encoding	Information added so a transformer knows token order (sinusoidal, learned, RoPE)	Ch. 3
PPO	Proximal policy optimization: the RL algorithm classically used in RLHF	Ch. 4
Precision and recall	Of what was flagged, how much was right / of what should be flagged, how much was found	Ch. 8
Prefill	Processing the whole prompt in parallel before generation starts	Ch. 11
Prefix caching (prompt caching)	Reusing the computed KV state of a prompt prefix shared by many requests, to save cost and latency; sold by providers as discounted cached input	Ch. 11
Pre-LN / Post-LN	Placing layer normalisation before each sublayer (Pre-LN, more stable to train) or after it (Post-LN, the original design)	Ch. 3
Presidio	Microsoft's open-source toolkit for detecting and masking PII	Ch. 12
Pretraining	Initial large-scale training on general data	Ch. 4
Prior preservation	Training on generic class images alongside a subject's photos so the model keeps its general knowledge	Ch. 14
Priority queue	Data structure that always returns the item with the smallest (or largest) key first	Ch. 2
Product quantization (PQ)	Compressing vectors by encoding sub-vectors as short codes	Ch. 7
Prompt chaining	Splitting a task into several prompts where each output feeds the next	Ch. 5
Prompt / prompt engineering	The instructions and context given to a model; prompt engineering is designing and testing them for reliable behaviour	Ch. 5
Prompt injection (direct / indirect)	Instructions in text the model reads that hijack it: direct = typed by the user to override the rules; indirect = hidden in content the model ingests (web page, email, document)	Ch. 12
Prompt registry	Versioned store of prompts used by an application	Ch. 13
Provenance	Record of where data or media came from and how it was changed	Ch. 10
PyTorch	The most widely used open-source deep-learning library	Ch. 3
QLoRA	LoRA fine-tuning on top of a base model quantized to 4 bits	Ch. 8
Quantization	Storing weights or activations with fewer bits (e.g. 8- or 4-bit) to save memory and time	Ch. 11

Term	Meaning	Where
Query rewriting	Reformulating a user question (adding context, expanding terms) before retrieval	Ch. 7
Qwen	Alibaba's family of open-weight LLMs	Ch. 4
RAG (retrieval-augmented generation)	Retrieving relevant documents and adding them to the prompt before generating	Ch. 7
Random restarts	Re-running local search from fresh random starts to escape local optima	Ch. 2
Rate limit	Cap on requests or tokens per unit time	Ch. 6
Rational agent	An agent that acts to maximise its expected performance measure	Ch. 1
ReAct	Pattern interleaving reasoning steps with tool actions and observations	Ch. 9
Reasoning model	LLM trained (often with RL) to think in extended intermediate steps before answering	Ch. 4
Recall / recall@k (retrieval)	Share of all relevant items the system found; recall@k counts only those in the top k results	Ch. 7
Reciprocal rank fusion (RRF)	Merging ranked lists by summing 1/(k + rank) for each item	Ch. 7
Recurrent neural network (RNN)	Network that processes a sequence one step at a time while carrying a hidden state	Ch. 3
Red teaming	Deliberately attacking a system to find failures before users do	Ch. 12
Reflection / Reflexion	Agent pattern where the model critiques its own result and retries with the lesson	Ch. 9
Regression test	Test that checks a change did not break behaviour that used to work	Ch. 8
Reinforcement learning from AI feedback (RLAIF)	RLHF where an AI model, often guided by principles, supplies the preference labels	Ch. 4
Reinforcement learning (RL)	Learning by trial and error from rewards	Ch. 4
ReLU / GELU / SwiGLU	Activation functions inside transformer feed-forward layers; SwiGLU is a gated variant used in many LLMs	Ch. 3
Replication	Keeping copies of data on several machines for availability and read capacity	Ch. 7
Residual connection	Adding a layer's input to its output, easing training of deep stacks	Ch. 3
Responsible AI	Building and running AI with attention to fairness, safety, privacy, transparency and accountability	Ch. 12
REST API	Common style of web API using standard HTTP verbs on resource URLs	Ch. 16
Reward model	Model trained on human preference data to score responses, used in RLHF	Ch. 4
RLHF	Reinforcement learning from human feedback: reward model trained on preferences, then policy optimisation	Ch. 4
RLVR	Reinforcement learning from verifiable rewards: rewarding answers a program can check (maths, tests)	Ch. 4
RMSNorm	Simpler normalisation that rescales by root-mean-square only; used in many LLMs	Ch. 3
RoPE	Rotary positional embedding: rotates query/key vectors by position	Ch. 3

Term	Meaning	Where
ROUGE	Summarisation metric based on overlapping words with a reference; a rough signal only	Ch. 8
Routing (model)	Picking, per request, the least expensive model able to do the job well	Ch. 11
Row-level security (RLS)	Database feature that filters rows per user or tenant automatically	Ch. 13
Rubric	Written scoring criteria a grader (human or LLM judge) follows	Ch. 8
SaaS	Software as a service: software sold by subscription and run by the vendor for many customers	Ch. 13
Sandbox	Isolated environment where code or agent actions cannot reach real systems or secrets	Ch. 9
Scaling laws	Power-law relationships between loss and model size, data and compute	Ch. 4
Scenario-based prompting	Asking the model to play a stakeholder ("act as a recruiter") to get feedback from that viewpoint	Ch. 5
SDK	Software development kit: a provider's client library that wraps its API	Ch. 6
Self-attention	Attention where queries, keys and values all come from the same sequence	Ch. 3
Self-consistency	Sampling several reasoning paths and taking the majority answer	Ch. 5
Self-hosting	Running open-weight models on your own or rented GPUs instead of a hosted API	Ch. 11
Self-supervised learning	Learning from labels hidden in the data itself (e.g. the next word)	Ch. 4
Semantic cache	Cache that returns a stored answer for a query similar in meaning	Ch. 11
SentencePiece / WordPiece	Subword tokenizer algorithms used by many models (T5, Llama / BERT)	Ch. 3
Server-sent events (SSE)	One-way HTTP stream from server to client, commonly used to stream tokens	Ch. 6
SGLang	Open-source LLM serving engine with RadixAttention prefix sharing	Ch. 11
Shadow deployment	Running a new version on live traffic without showing its outputs to users	Ch. 13
Sharding	Splitting data or an index across several machines	Ch. 13
Simulated annealing	Local search that sometimes accepts worse moves, less often as "temperature" falls	Ch. 2
SLO / SLA	Service-level objective (internal target such as p95 < 1 s) / agreement (contractual promise)	Ch. 11
Softmax	Function turning scores into probabilities that sum to 1	Ch. 3
Sora / Veo	Text-to-video models from OpenAI and Google	Ch. 10
Spacetime latents / patches	Compressed video representation whose tokens each span several pixels and frames	Ch. 10
Speaker diarization	Working out who spoke when in a recording	Ch. 14
Spectrogram	Picture of audio showing energy at each frequency over time	Ch. 10

Term	Meaning	Where
Speculative decoding	A small draft model proposes tokens that the large model verifies in one pass; the acceptance rate is the share of drafted tokens it keeps	Ch. 11
Spotlighting	Marking untrusted text (tags, encoding) so the model can tell it apart from instructions	Ch. 12
Stable Diffusion	Open latent diffusion text-to-image model	Ch. 10
State space (search)	All states reachable from the start by sequences of actions	Ch. 2
Stateless	Keeping no memory between calls; each request must carry everything needed	Ch. 6
State-space model	Sequence architecture that carries a fixed-size running state instead of attending to every token	Ch. 3
stdio / Streamable HTTP	The two MCP transports: a local child process over standard input/output, or a remote server over HTTP	Ch. 6
Stop reason	Why the model stopped generating (end of turn, max tokens, tool use, stop sequence)	Ch. 6
Stop sequence	String that makes the model stop generating when it appears	Ch. 4
Streaming	Sending output tokens to the client as they are generated	Ch. 6
Structured output (constrained decoding)	Model output forced to match a schema such as JSON, by restricting token choices during generation	Ch. 6
StyleGAN	GAN that controls image features through per-layer style inputs from a mapping network	Ch. 14
Supervised learning	Learning from examples paired with correct labels	Ch. 1
Sycophancy	A model telling users what they want to hear rather than what is true	Ch. 4
Symbolic AI	AI built on explicit symbols, logic and hand-written rules	Ch. 1
Synthetic data	Training or evaluation data generated by models or programs	Ch. 8
SynthID	Google's invisible watermarking for AI-generated content	Ch. 10
System prompt	High-priority instructions setting a model's role and rules for a conversation	Ch. 5
Temperature	Sampling setting that sharpens (low) or flattens (high) the next-token distribution	Ch. 4
Temporal consistency	Video frames agreeing with each other over time (no flicker or changing identities)	Ch. 10
Tensor parallelism	Splitting each layer's matrices across several GPUs	Ch. 11
TensorRT-LLM	NVIDIA's optimised LLM inference library	Ch. 11
Test-time compute	Spending more computation while answering (longer reasoning, more samples) to improve quality	Ch. 4
TF-IDF	Word weighting by frequency in a document times rarity across documents	Ch. 7
TGI	Text Generation Inference: Hugging Face's LLM serving server	Ch. 11
Threat model	Written account of who might attack a system, how, and what they want	Ch. 12

Term	Meaning	Where
Throughput	Amount of work (e.g. tokens per second) a system completes per unit time	Ch. 11
Time to first token (TTFT)	Delay from sending a request until the first output token arrives	Ch. 11
Token budget	Maximum tokens allowed for a request, conversation or agent run	Ch. 6
Token / tokenizer	Token: the unit of text a model processes, often a subword; tokenizer: splits text into tokens and maps them to IDs	Ch. 3
Tombstone	Marker recording that an item was deleted, so caches and indexes drop it too	Ch. 7
Tool use (function calling)	Model requests to call external functions, which your code executes and returns	Ch. 6
Top-k sampling	Sampling only from the k most likely next tokens	Ch. 4
Top-p (nucleus) sampling	Sampling from the smallest set of tokens whose probabilities sum to p	Ch. 4
TPOT (time per output token; ≈ inter-token latency, ITL)	Average time between consecutive output tokens during decoding	Ch. 11
Training data	The examples a model learned from; its gaps and biases carry into the model	Ch. 1
Training–serving skew	Features computed differently in training and in production	ML 16
Trajectory	The full sequence of thoughts, tool calls and observations in one agent run	Ch. 9
Transformer	Neural architecture built from attention and feed-forward blocks (2017)	Ch. 3
Transition model	Description of the state that results from taking an action in a state	Ch. 2
TTL (time to live)	How long a cached item stays valid before it expires	Ch. 11
TTS (text-to-speech)	Generating spoken audio from text	Ch. 10
Turing test	Imitation game: can a machine pass as human in text conversation?	Ch. 1
Two-tower model	Separate encoders for users/queries and items whose embeddings are compared for retrieval	ML 13
UCB1	Formula balancing exploration and exploitation when choosing which move to simulate in MCTS	Ch. 2
U-Net	Encoder–decoder image network with skip connections; the classic diffusion denoiser	Ch. 10
Uniform-cost search	Expands the node with the lowest path cost g (Dijkstra's algorithm on graphs)	Ch. 2
Unsupervised learning	Finding structure in data without labels (clustering, compression)	Ch. 1
VAE (variational autoencoder)	Generative model that encodes data into a probabilistic latent space and decodes samples	Ch. 10
Vector database	Store and index for embeddings supporting fast nearest-neighbour search	Ch. 7
vLLM	Open-source LLM serving engine built around PagedAttention and continuous batching	Ch. 11
Vocoder	Model that turns a spectrogram into an audio waveform	Ch. 10

Term	Meaning	Where
Voice cloning	Generating speech in a specific person's voice from samples	Ch. 10
Watermark	Hidden signal embedded in generated content so it can later be identified	Ch. 10
Webhook	HTTP callback: a service calls your URL when an event happens	Ch. 7
Weighted A*	A* with the heuristic multiplied by w > 1: faster, with cost at most w times optimal	Ch. 2
WER (word error rate)	Speech-recognition error: (substitutions + deletions + insertions) / reference words	Ch. 10
Whisper	OpenAI's open speech-recognition model	Ch. 10
Workflow (vs agent)	Fixed, pre-designed sequence of LLM and code steps	Ch. 9
XML tags (in prompts)	Tags such as `<document>` used to separate instructions from data	Ch. 5
Zero-shot classification	Labelling inputs into categories never trained on, e.g. by comparing CLIP embeddings with label text	Ch. 10
Zero-shot prompting	Asking a model to do a task with instructions but no examples	Ch. 5

Verifying the cross-references

`code/check_refs.py` checks every chapter README's relative links mechanically: the target file must exist and, when the link text names a section such as "§7.9", the target must have a `## 7.9` heading. Run it after editing any chapter.

```
# code/check_refs.py (core)
LINK = re.compile(r"(!?)\[([^\]]*)\]\(([^)\s]+)\)")
SECTION = re.compile(r"§\s?(\d+\.\d+)")

for bang, label, target in LINK.findall(line):
    path = (readme.parent / target.split("#")[0]).resolve()
    if not path.exists():
        problems.append(f"missing {target}")
    for sec in SECTION.findall(label):           # "§7.9" must be a real "## 7.9" heading
        if sec not in headings(path):
            problems.append(f"§{sec} not in {target}")
```

Output:

```
Checked 17 README file(s): 0 problem(s).
```

Chapter TL;DR

- **Revise with rhythm**: review sheets per chapter, decision sheets daily, red flags once plus the night before, the question bank shuffled and aloud, one full design per session; re-drill misses after a day or two.
- **The sentence to master**: "The deciding variable here is X; ours is Y, so Z — at the cost of W."
- **Absolutes**: permissions enforced below the model and failing closed; every design closes the loop (logs → evals → retraining → safe rollout); every design says its cost (unit cost × volume) and its silent failures with alarms.
- **Most common red flags**: no numbers, no feedback loop, no cost estimate — all cheap to fix.
- **Trends (2026)**: stronger reasoning, grounded and multimodal models, bounded agents, small on-device models, AI combined with IoT, AR/VR and robotics; quantum speed-ups for ML unproven; work is mostly augmented rather than replaced; regulation phasing in.

- **Roadmap**: Python → ML foundations → deep learning and transformers → building with LLMs → grounding and evaluation → agents → production and safety → design and interviews, each stage proved by a project.
- **Glossary**: 418 terms, each defined once and linked to the chapter that teaches it.