
Chapter 12 — Decorators, Context Managers and Metaprogramming

What you will learn. How decorators work (plain, with arguments, stacked, class decorators, class-based decorators), why `functools.wraps` matters, and the decorators you use every day (`@property`, `@classmethod`, `@staticmethod`, `@lru_cache` / `@cache`, `@dataclass`). Then context managers: the `with` protocol, class-based managers, `@contextlib.contextmanager`, `suppress`, and `ExitStack`, plus async and reentrant managers. Finally metaprogramming — code that manipulates code: descriptors (the machinery behind properties and methods), `__getattr__` vs `__getattribute__`, metaclasses (what they are and why you rarely need them), `__init_subclass__`, the caveats of monkey patching, and everyday introspection (`getattr`, `inspect`, and why not `eval`).

Prerequisites. Chapter 10 (classes, dunders) and Chapter 11 (generators — `@contextmanager` is built on them). Key idea: **functions and classes are objects** you can pass around, wrap and create at run time.

Code. `chapters/12-decorators-context-managers-metaprogramming/code/` — `decorators.py`, `context_managers.py`, `descriptors_attrs.py`, `metaprogramming.py`. Timings in outputs vary by machine.



12.1 Decorators

What it is

A **decorator** is a callable (anything you can call with `()` — a function, a class, or an object with `__call__`) that takes a function (or class) and returns a replacement — usually a **wrapper** that adds behaviour before/after calling the original. The `@` syntax is shorthand:

```
@timed
def slow_add(a, b): ...
# is exactly
def slow_add(a, b): ...
slow_add = timed(slow_add)
```

Analogy: gift-wrapping — the present (your function) is unchanged, but whoever receives it gets the wrapping first.

Two building blocks make this possible:

1. **First-class functions** — functions can be passed as arguments and returned.
2. **Closures** — an inner function remembers variables from the enclosing function (`func` inside `wrapper`) even after the outer function has returned.

(Closures and a first look at decorators are in Chapter 7 §7.4–7.6; this chapter goes deeper.)

Why it matters

Decorators separate **cross-cutting concerns** (needs that show up in many unrelated functions) — logging, timing, caching (keeping results so they can be reused), retries, authentication (checking who the caller is), registration — from business logic (the code that does the actual job the program exists for), and apply them with one line. This is Python's native form of the Decorator pattern (see LLD Handbook ch. 9) and of aspect-oriented programming (a style where such shared concerns are written once and "woven" around many functions).

How it works

1. At **definition time** (usually import time — the moment a module is first loaded by an `import` statement) Python creates the function, then calls `decorator(func)` and binds the name to the result.
2. At **call time**, callers actually call the wrapper, which calls the original via the closure.
3. The wrapper should accept `*args, **kwargs` and **return** the original's result, so it works for any signature (the list of parameters a function accepts).

```
def timed(func):
    @functools.wraps(func)                        # copy name, docstring, etc.
    def wrapper(*args, **kwargs):
        start = time.perf_counter()
        try:
            return func(*args, **kwargs)          # call the original, return its result
        finally:
            elapsed = (time.perf_counter() - start) * 1000
            print(f"  [timed] {func.__name__} took {elapsed:.1f} ms")
    return wrapper

@timed
def slow_add(a, b):
    """Add slowly."""
    time.sleep(0.02)
    return a + b
```

Output:

```
by hand: HELLO ANN
without wraps, name is: wrapper
  [timed] slow_add took 21.3 ms
slow_add: 5 | name: slow_add | doc: Add slowly. | original: slow_add
```

`functools.wraps`

Without it, the decorated function's `__name__` is `"wrapper"` and its docstring (the descriptive string literal written as the first line of a function body) is gone — which breaks debugging, logs, `help()`, documentation tools and frameworks that look up functions by name (e.g. Flask endpoints — Flask is a small web framework, and an endpoint is a URL path the server answers). `@functools.wraps(func)` copies `__module__`, `__name__`, `__qualname__`, `__doc__`, `__annotations__` (and more), merges `__dict__`, and sets `wrapper.__wrapped__ = func` so tools (and you) can reach the original. **Always use it.**

Decorators with arguments — three levels

`@retry(times=3)` first *calls* `retry(times=3)`, which must *return* the real decorator. So there are three nested functions: factory → decorator → wrapper.

```python
def retry(times: int = 3, exceptions=(Exception,)):   # 1. factory: receives the options
    def decorator(func):                               # 2. decorator: receives the function
        @functools.wraps(func)
        def wrapper(*args, **kwargs):                  # 3. wrapper: runs on every call
            for attempt in range(1, times + 1):
                try:
                    return func(*args, **kwargs)
                except exceptions as e:
                    print(f"  [retry] attempt {attempt} failed: {e}")
                    if attempt == times:
                        raise
        return wrapper
    return decorator

@retry(times=3, exceptions=(ConnectionError,))
def flaky_fetch(): ...        # fails twice, then returns "data"
```

Output:

```
  [retry] attempt 1 failed: timeout
  [retry] attempt 2 failed: timeout
flaky_fetch -> data
```

(Real retry code should also wait between attempts with exponential backoff (doubling the wait after each failure: 1 s, 2 s, 4 s …) and jitter (a small random amount added so many clients don't all retry at the same instant) — libraries such as `tenacity` do this.)

Stacking

```python
@tag("b")
@tag("i")
def text(): return "hi"
# == text = tag("b")(tag("i")(text))
```

Decorators are **applied bottom-up** (closest to `def` first) and their wrappers **run top-down** (outermost first). Output: `stacked: <b><i>hi</i></b>`. Order matters: e.g. put `@app.route` outermost and an auth check inside it, or the route registers the unprotected function.

Stateful and registering decorators

A decorator doesn't have to wrap. It can **register** the function and return it unchanged — this is how many frameworks work:

```python
REGISTRY = {}
def register(func):
    REGISTRY[func.__name__] = func       # side effect at definition time
    return func

def count_calls(func):
    @functools.wraps(func)
    def wrapper(*args, **kwargs):
        wrapper.calls += 1               # state stored as a function attribute
        return func(*args, **kwargs)
    wrapper.calls = 0
    return wrapper
```

Output: `registry: ['export_csv', 'export_json']` and `ping.calls: 2`.

Class decorators and classes as decorators

- A **class decorator** receives a *class* and returns a class (often the same one, modified). `@dataclass` is one.
- A **class used as a decorator** is callable because instances implement `__call__`; use `functools.update_wrapper(self, func)` in `__init__`.

```
def add_repr(cls):
    def __repr__(self):
        fields = ", ".join(f"{k}={v!r}" for k, v in vars(self).items())
        return f"{cls.__name__}({fields})"
    cls.__repr__ = __repr__
    return cls

class CountCalls:
    def __init__(self, func):
        functools.update_wrapper(self, func)
        self.func, self.calls = func, 0
    def __call__(self, *args, **kwargs):
        self.calls += 1
        return self.func(*args, **kwargs)
```

Output: `class decorator: Point(x=1, y=2)` and `CountCalls: 2 | name: square`.

Caveat: a class-based decorator applied to a *method* won't bind `self` automatically (the instance isn't a descriptor unless you implement `__get__`, §12.4). Function-based decorators don't have this problem — prefer them.

Trade-offs

Approach	Pros	Cons
Function decorator	Simple, works on methods	State via closure/attributes
Decorator factory (with args)	Configurable	Three levels of nesting; easy to forget the call parentheses
Class-based decorator	Natural place for state	Needs `__get__` to work on methods
Class decorator	Modify/register whole classes	Can surprise readers; metaclass-like power
No decorator (call helper explicitly)	Obvious control flow	Repetition

When not to use it

When the "cross-cutting" logic is used once; when it changes the function's signature or return type in surprising ways; when stacking five decorators makes the call path impossible to follow.

Common mistakes

- Forgetting `return` in the wrapper → the decorated function returns `None`.
- Forgetting `@functools.wraps`.
- Using a factory without calling it: `@retry` instead of `@retry()` → `retry` receives the function as `times`.
- Heavy work at decoration time (it runs on import).
- Wrong stacking order (e.g. caching outside an auth check caches responses across users).

Real-world examples

Flask `@app.route("/")` and FastAPI `@app.get("/")` register view functions (the functions that handle a web request for a URL); pytest `@pytest.fixture` and `@pytest.mark.parametrize`; Click (a library for building CLIs — command-line interfaces) `@click.command()` / `@click.option()`; Celery (a background-job queue) `@app.task`; Django (a large web framework) `@login_required`; `@functools.singledispatch` (function overloading by argument type); `@contextlib.contextmanager`; `@unittest.mock.patch`.

In the interview

> **30-second answer:** "A decorator is a callable that takes a function and returns a replacement, usually a closure wrapper that runs code around the original; `@d` above `def f` is `f = d(f)` at definition time. I always use `functools.wraps` to keep the name, docstring and `__wrapped__`. A decorator with arguments is a factory returning a decorator — three levels. Stacked decorators apply bottom-up and run top-down."

- *When does a decorator run?* — Once, when the decorated function is defined (typically import); the wrapper runs on each call.
- *Write a decorator that times a function.* — See `timed` above (use `perf_counter`, `try/finally`, `wraps`).
- *How do you decorate a class?* — A function that takes and returns a class, e.g. `@dataclass`.

Self-check

1. Rewrite `@a @b def f` without `@`. → `f = a(b(f))`.
2. What does `functools.wraps` set that lets you reach the original? → `__wrapped__`.
3. Why three functions in a decorator with arguments? → Outer takes options, middle takes the function, inner runs per call.
4. What happens if the wrapper doesn't `return func(...)`? → Callers get `None`.

TL;DR

Decorator = function in, function out, applied at definition time. Use `*args, **kwargs`, return the result, `@functools.wraps`. Factories for arguments; stack with care.

12.2 Everyday built-in decorators

Decorator	What it does	Where covered
`@property` (+ `.setter`, `.deleter`)	Method accessed like an attribute; implemented as a descriptor	Ch. 10 §10.1, §12.4
`@classmethod`	Passes the class as `cls` (alternative constructors)	Ch. 10 §10.1
`@staticmethod`	No implicit first argument	Ch. 10 §10.1
`@abstractmethod`	Marks methods an ABC (abstract base class — a class meant only to be inherited from) subclass must implement	Ch. 10 §10.7
`@dataclass`	Class decorator generating `__init__`/`__repr__`/`__eq__` …	Ch. 10 §10.10
`@functools.total_ordering`	Class decorator filling in comparison methods	Ch. 10 §10.2
`@functools.lru_cache(maxsize=128)` / `@functools.cache`	Memoisation (below)	here
`@functools.cached_property`	Compute once per instance, store in the instance	§12.4
`@functools.wraps`	Copies metadata onto wrappers	§12.1
`@contextlib.contextmanager`	Generator → context manager	§12.3
`@typing.override` (3.12)	Marks a method as overriding a parent's, so type checkers (tools like mypy that verify type hints without running the code) can flag typos	—

`@lru_cache` and `@cache` — memoisation

Memoisation stores the result of a function call keyed by its arguments, so a repeated call returns instantly. `lru_cache(maxsize=N)` keeps the N most recently used results and evicts the **least recently used** (LRU) when full; `maxsize=None` or `@functools.cache` (3.9) is unbounded. Default `maxsize` is 128.

```
@functools.lru_cache(maxsize=None)
def fib(n: int) -> int:
    return n if n < 2 else fib(n - 1) + fib(n - 2)
```

Output:

```
fib(25) plain 6 ms vs cached 0.01 ms -> cached faster: True
cache_info: CacheInfo(hits=23, misses=26, maxsize=None, currsize=26)
unhashable arg: unhashable type: 'list'
```

Worked numbers: plain recursive `fib(25)` makes 242,785 calls (exponential); cached, each `fib(k)` for k = 0…25 is computed once → **26 misses**, and each of `fib(3)…fib(25)` finds its second sub-call `fib(k−2)` already cached → **23 hits**.

Rules and caveats:

1. Arguments must be **hashable** (have a fixed hash value, which in practice means immutable — numbers, strings, tuples; the cache is a dict, and dict keys must be hashable) — no lists/dicts.
2. Only for **pure** functions (same input → same output, no side effects). Don't cache `now()` or database reads that must be fresh.
3. Returned objects are shared — mutating a cached list corrupts the cache.
4. On **methods**, the cache holds a reference to `self`, keeping instances alive (a memory leak — memory that is never freed because something still references it) and sharing one cache across instances; prefer `cached_property` or a per-instance cache.
5. `fib.cache_clear()` empties it; `typed=True` caches `f(3)` and `f(3.0)` separately.

Real world: caching parsed config, compiled regexes (regular expressions — text-matching patterns; `re` keeps its own internal cache), expensive pure computations, dynamic-programming solutions in interviews (dynamic programming solves a problem by reusing answers to smaller overlapping sub-problems).

12.3 Context managers

What it is

A **context manager** is an object that sets something up at the start of a `with` block and **guarantees** tear-down at the end — even if the block raises or `return`s. It implements `__enter__` and `__exit__`.


Analogy: a hotel key card — you get it on check-in (`__enter__`), and checkout (`__exit__`) happens no matter how your stay ends.

Why it matters

Resource leaks (files, sockets — open network connections, locks — objects that let only one thread into a section of code at a time, DB transactions — a group of database changes that must all succeed or all be undone, temporary state) are a top source of bugs. `with` replaces fragile `try/finally` boilerplate (repetitive code you have to write every time) and makes clean-up impossible to forget.

How it works — `with EXPR as VAR: BODY`

1. Evaluate `EXPR` to get the manager `m`.
2. Call `m.__enter__()`; bind its **return value** to `VAR` (it doesn't have to be `m` — `open()` returns the file itself, a lock returns `True`).
3. Run `BODY`.
4. Always call `m.__exit__(exc_type, exc_value, traceback)` — all three `None` if no exception. (A traceback is the record of which function calls were active when the error happened.)
5. If `__exit__` returns a **truthy** value, the exception is **suppressed**; otherwise it propagates (keeps travelling up to the calling code). Return `False`/`None` unless suppressing is the whole point.



Class-based

```python
class Timer:
    def __enter__(self):
        self.start = time.perf_counter()
        return self
    def __exit__(self, exc_type, exc, tb):
        self.elapsed = time.perf_counter() - self.start
        return False                    # propagate exceptions

class Suppress:                         # our own contextlib.suppress
    def __init__(self, *excs): self.excs = excs
    def __enter__(self): return self
    def __exit__(self, exc_type, exc, tb):
        return exc_type is not None and issubclass(exc_type, self.excs)
```

Generator-based: `@contextlib.contextmanager`

Write a generator that **yields exactly once**: code before `yield` is `__enter__`, the yielded value goes to `as`, code after is `__exit__`. If the `with` body raises, the exception is **re-raised at the `yield`** — so wrap it in `try/finally` (or `except`) or your clean-up is skipped.

```python
@contextlib.contextmanager
def cd(path):                           # same idea as contextlib.chdir (3.11+)
    old = os.getcwd()
    os.chdir(path)
    try:
        yield path                      # the with-body runs here
    finally:
        os.chdir(old)                   # runs even if the body raises

@contextlib.contextmanager
def transaction(log):
    log.append("BEGIN")
    try:
        yield
    except Exception:
        log.append("ROLLBACK")
        raise                           # re-raise: don't hide the error
    else:
        log.append("COMMIT")
```

`ExitStack` — a dynamic number of managers

`contextlib.ExitStack` lets you enter an unknown number of context managers (e.g. open N files from a list) and registers arbitrary clean-up callbacks (functions you hand over to be called later). On exit it unwinds them in **reverse (LIFO — last in, first out, like a stack of plates)** order, and if entering the k-th one fails, the k−1 already entered are still closed. `stack.pop_all()` transfers ownership out if setup succeeded (useful in constructors).

```python
with contextlib.ExitStack() as stack:
    files = [stack.enter_context(Resource(n, log)) for n in names]
    stack.callback(log.append, "callback ran")
    log.append(f"using {len(files)} resources")
```

Output (`context_managers.py`):

```
Timer: elapsed > 0: True
Suppress: survived ZeroDivisionError
contextlib.suppress: survived FileNotFoundError
cd restored: True | was inside tmp: True
transaction log: ['BEGIN', 'insert row', 'COMMIT', 'BEGIN', 'bad insert', 'ROLLBACK']
ExitStack: ['open a.txt', 'open b.txt', 'open c.txt', 'using 3 resources', 'callback ran', 'close
c.txt', 'close b.txt', 'close a.txt']
ExitStack partial failure: ['open ok1', 'close ok1'] | cannot open
redirect_stdout captured: 'captured!\n'
nullcontext gives: x
two managers: ['open r1', 'open r2', 'close r2', 'close r1']
```

The `contextlib` toolbox

Tool	Use
`contextmanager` / `asynccontextmanager`	Generator (or async generator) → context manager
`suppress(*excs)`	Ignore specific exceptions (`with suppress(FileNotFoundError): os.remove(p)`)
`ExitStack` / `AsyncExitStack`	Dynamic number of managers + callbacks
`closing(obj)`	Call `obj.close()` on exit for objects without `__exit__`
`redirect_stdout` / `redirect_stderr`	Temporarily capture output
`nullcontext(x)`	A do-nothing manager, for "optional" context (`with lock if threaded else nullcontext():`)
`chdir(path)` (3.11)	Temporarily change the working directory
`AbstractContextManager`	ABC base giving a default `__enter__` that returns `self`

Several managers in one statement: `with A() as a, B() as b:` — or, since 3.10, parenthesised across lines. They are exited in reverse order (see "two managers" above).

Async context managers. In `async def` code (Chapter 16) the statement is `async with`, and the protocol methods are the coroutines `__aenter__` / `__aexit__`, so setup and clean-up can `await` I/O (input/output — reading or writing files, network or databases; e.g. opening a network connection, releasing a pooled DB connection — one borrowed from a shared, reusable set of open connections). `@contextlib.asynccontextmanager` builds one from an `async def` generator exactly like `@contextmanager`. Examples: `async with aiohttp.ClientSession() as s:`, `async with asyncio.TaskGroup() as tg:`, `async with lock:` for an `asyncio.Lock`.

Reusable and reentrant managers. A *single-use* manager (a `@contextmanager` object, an open file) can be entered only once. A *reusable* one can be entered again after it exits. A *reentrant* one can even be entered again **while it is already active** (nested `with m:` inside `with m:`) — `threading.RLock` and `contextlib.redirect_stdout` are reentrant; a plain `threading.Lock` is not (re-acquiring it from the same thread deadlocks — the thread waits forever for a lock that it itself holds).

Trade-offs

	Class-based	`@contextmanager`
Code size	More	Less
Reusable object with state/methods	Yes	No (one-shot generator)
Can be re-entered / reused	If you design it so	No — each call makes a new one
Exception handling	Explicit `__exit__` args	`try/except/finally` around `yield`
Also usable as a decorator	Via `ContextDecorator`	Yes — `@contextmanager` objects work as decorators too

Common mistakes

- `@contextmanager` without `try/finally` around `yield` → clean-up skipped on error.
- Yielding more than once → `RuntimeError: generator didn't stop`.

- Returning `True` from `__exit__` accidentally → silently swallowing all exceptions.
- Using the resource after the block (`f.read()` after `with open(...)` → `ValueError: I/O operation on closed file`).

Real-world examples

`open()`, `threading.Lock`, `sqlite3.connect()` (as a context manager it commits or rolls back the transaction — it does *not* close the connection), `requests.Session`, `tempfile.TemporaryDirectory`, `decimal.localcontext`, `unittest.mock.patch`, `pytest.raises`, PyTorch `torch.no_grad()`, `concurrent.futures.ThreadPoolExecutor` (waits for tasks on exit).

In the interview

> **30-second answer:** "A context manager implements `__enter__` and `__exit__`; `with` calls enter, binds its return value to `as`, runs the body, and always calls exit with the exception info, which can suppress it by returning true. For simple cases I write a generator with `@contextmanager` — setup, `yield`, clean-up in `finally`. For a variable number of resources I use `ExitStack`, which unwinds them in reverse order even if one fails to open."

- *How do you suppress an exception?* — Return a truthy value from `__exit__`, or use `contextlib.suppress`.
- *What happens to an exception inside a `@contextmanager` body?* — It's thrown into the generator at the `yield`.

Self-check

1. What gets bound by `as`? → The return value of `__enter__`.
2. Three arguments of `__exit__`? → Exception type, value, traceback (all `None` if no error).
3. Order managers exit in `with A(), B():`? → B then A.
4. Why use `ExitStack`? → Unknown number of managers, or conditional ones, with guaranteed LIFO clean-up.

TL;DR

`with` guarantees clean-up: `__enter__` → body → `__exit__` (truthy return suppresses). `@contextmanager` = setup / `yield` / `finally` clean-up. `ExitStack` for dynamic sets. Know `suppress`, `closing`, `nullcontext`, `redirect_stdout`, `chdir`.

12.4 Descriptors — how properties and methods really work

What it is

A **descriptor** is any object, stored as a **class attribute**, that defines at least one of:

- `__get__(self, obj, objtype=None)` — runs on attribute read,
- `__set__(self, obj, value)` — runs on assignment,
- `__delete__(self, obj)` — runs on `del`.

Optionally `__set_name__(self, owner, name)` (3.6) is called at class creation so the descriptor learns the attribute name it was assigned to.

Two kinds:

- **Data descriptor** — defines `__set__` or `__delete__`. `property` is one.
- **Non-data descriptor** — only `__get__`. Plain functions and `functools.cached_property` are.

Why it matters

Descriptors are the mechanism behind `property`, `classmethod`, `staticmethod`, bound methods, `__slots__`, and ORM fields (an ORM — object-relational mapper — maps database tables to Python classes; e.g. Django/SQLAlchemy model columns). Writing your own gives **reusable** attribute logic — one `Positive` validator used for many fields, instead of copy-pasted property pairs.

How it works — attribute lookup precedence for `obj.attr`

1. Find `attr` on `type(obj)` along the MRO (method resolution order — the fixed order in which a class and its parents are searched). If it's a **data descriptor**, call its `__get__` — it **wins over the instance dict**.
2. Else, if `attr` is in `obj.__dict__`, return that.
3. Else, if the class attribute is a **non-data descriptor**, call its `__get__`; if it's a plain class attribute, return it.
4. Else call `__getattr__` if defined; otherwise raise `AttributeError`.

(All of this is implemented by `object.__getattribute__`.) Assignment `obj.attr = v` calls a data descriptor's `__set__` if there is one; otherwise it writes to `obj.__dict__`.

Consequences:

- **Methods:** a function is a non-data descriptor; `Greeter.__dict__["hello"].__get__(g)` returns the bound method — this is what `g.hello` does.
- `property` always defines `__set__` (raising `AttributeError` if there's no setter), so it's a data descriptor and an instance-dict entry can't shadow it.
- `cached_property` is non-data: the first access computes and stores the value in `obj.__dict__`; later accesses find it in step 2 and never call the descriptor again.

```
class Positive:
    def __set_name__(self, owner, name):
        self.private = "_" + name               # e.g. "_qty"
    def __get__(self, obj, objtype=None):
        if obj is None:                          # accessed on the class
            return self
        return getattr(obj, self.private)
    def __set__(self, obj, value):
        if value <= 0:
            raise ValueError(f"{self.private[1:]} must be > 0, got {value}")
        setattr(obj, self.private, value)

class Order:
    qty = Positive()                             # one reusable validator...
    price = Positive()                           # ...for many fields
    def __init__(self, qty, price):
        self.qty = qty                           # runs Positive.__set__
        self.price = price

class my_property:                               # property, re-implemented
    def __init__(self, fget, fset=None):
        self.fget, self.fset = fget, fset
    def __get__(self, obj, objtype=None):
        return self if obj is None else self.fget(obj)
    def __set__(self, obj, value):
        if self.fset is None:
            raise AttributeError("read-only")
        self.fset(obj, value)
```

Output (`descriptors_attrs.py`, first part):

```
Order: 2 9.99 | instance dict: {'_qty': 2, '_price': 9.99}
descriptor refused: qty must be > 0, got 0
on the class: Positive object (the descriptor itself)
my_property: 212.0
AttributeError: read-only
  (computing data once)
first: [1, 2, 3]
second: [1, 2, 3] | stored in instance dict: True
function has __get__: True | f.__get__(g)(): hello
data descriptor? True | cached_property has __set__? False
```

Common mistakes

- Storing the value on the descriptor itself (`self.value = v`) — the descriptor is shared by **all instances**, so every object would see the same value. Store per-instance data on `obj`.
- Putting a descriptor in `__init__` (`self.qty = Positive()`) — descriptors only work as **class** attributes.
- Forgetting the `obj is None` case (class access).

In the interview

30-second answer: "A descriptor is a class attribute with `__get__`, and optionally `__set__`/`__delete__`. Data descriptors (with `__set__`) take priority over the instance dict; non-data ones don't. `property`, `classmethod`, `staticmethod` and even bound methods are built on this — a function's `__get__` returns a bound method (a method with its `self` already filled in). I'd write one for reusable validation across fields, like ORMs do for columns."

- *Why can `cached_property` be overwritten by the instance?* — It's a non-data descriptor, so the instance dict wins.

TL;DR

Descriptors = class attributes that intercept get/set/delete. Data descriptors beat the instance dict; non-data don't. They power properties, methods, `cached_property`, `__slots__` and ORM fields.

12.5 `__getattr__` vs `__getattribute__`

What it is

Hook	Called when	Typical use
`__getattr__(self, name)`	Only when **normal lookup fails** (would raise `AttributeError`)	Delegation/proxies (objects that stand in for another and forward requests to it), lazy attributes, friendly defaults, deprecation shims (thin layers that keep old names working while warning they'll be removed)
`__getattribute__(self, name)`	On **every** attribute access (it *is* normal lookup)	Rare: tracing, access control, very special proxies
`__setattr__` / `__delattr__`	Every assignment / deletion	Validation, immutability, change tracking
Module-level `__getattr__(name)` (PEP 562, 3.7)	Missing attribute on a *module*	Lazy imports, deprecation warnings

```python
class Proxy:
    def __init__(self, target):
        self._target = target
    def __getattr__(self, name):                  # only for names not found normally
        print(f"  __getattr__({name!r}) -> delegating")
        return getattr(self._target, name)

class Logged:
    def __init__(self):
        self.x = 1
    def __getattribute__(self, name):             # every access
        if not name.startswith("__"):
            print(f"  __getattribute__({name!r})")
        return super().__getattribute__(name)     # MUST delegate via super()/object
```

Output:

```
  __getattr__('upper') -> delegating
proxy.upper(): HELLO WORLD
proxy._target found normally (no __getattr__ call): hello world
  __getattribute__('x')
value: 1
```

Common mistakes

- Inside `__getattribute__`, writing `self.anything` → calls `__getattribute__` again → infinite recursion. Use `super().__getattribute__(name)` or `object.__getattribute__(self, name)`.
- In `__getattr__`, accessing an attribute that may not exist yet (e.g. `self._target` before `__init__` has set it, as during unpickling — rebuilding an object from bytes saved with `pickle` — or copying) → infinite recursion. Guard or raise `AttributeError`.
- Returning `None` for unknown names instead of raising `AttributeError` → breaks `hasattr`, `getattr(obj, n, default)` and copy/pickle.
- Implicit special-method lookup (`len(p)`, `p + 1`) **bypasses** both hooks — Python looks up dunders on the type directly. A proxy must define those dunders explicitly.

Real-world examples

`unittest.mock.Mock` uses `__getattr__` to create child mocks on the fly; RPC/SDK clients (RPC = remote procedure call, calling a function on another machine; SDK = software development kit, a ready-made library for a service) build dynamic endpoints (`client.users.list`); pandas lets you access columns as attributes (`df.price`) via `__getattr__`; lazy-loading packages use module `__getattr__`.

TL;DR

`__getattr__` = fallback for missing attributes (safe, common). `__getattribute__` = intercepts everything (rare, recursion-prone). Dunders used by syntax skip both.

12.6 Metaclasses and `__init_subclass__`

What it is

Classes are objects too, so something must create them: a **metaclass** is "the class of a class". The default metaclass is **`type`**: `type(42)` is `int`, `type(int)` is `type`, and even `type(type)` is `type`. A `class` statement is roughly `Name = type("Name", bases, namespace)`.

```
def speak(self): return f"{self.name} speaks"
Dog = type("Dog", (object,), {"name": "Rex", "speak": speak})   # a class, built by a call
```

How a class is created

1. Python collects the class body into a namespace dict (a mapping from names to the objects they refer to) by executing it.
2. It determines the metaclass (explicit `metaclass=`, or the most derived metaclass of the bases, default `type`).
3. It calls `Meta(name, bases, namespace)` → `Meta.__new__` builds the class object, `Meta.__init__` initialises it.
4. While the class object is being built (inside `type.__new__`, so before `Meta.__init__`), descriptors' `__set_name__` hooks run, then the parent's `__init_subclass__`.
5. Class decorators run last, on the finished class.

A custom metaclass subclasses `type` and overrides `__new__`/`__init__` (or `__call__`, to control **instance** creation — e.g. a Singleton metaclass, which ensures a class can only ever have one instance).

`__init_subclass__` — the simpler hook

PEP 487 (Python 3.6) added `__init_subclass__(cls, **kwargs)`: a classmethod on a parent that runs **every time a subclass is created**, receiving any keyword arguments from the class line (`class Home(Handler, route="/")`). It covers the most common metaclass uses — registries, validation, configuration — with ordinary inheritance and no metaclass conflicts.

```python
class RegistryMeta(type):                          # metaclass version
    registry: dict[str, type] = {}
    def __new__(mcls, name, bases, namespace):
        cls = super().__new__(mcls, name, bases, namespace)
        if bases:
            mcls.registry[name.lower()] = cls
        return cls

class Plugin(metaclass=RegistryMeta): pass
class CsvExporter(Plugin): ...

class Handler:                                     # __init_subclass__ version (preferred)
    handlers: dict[str, type] = {}
    def __init_subclass__(cls, /, route: str, **kwargs):
        super().__init_subclass__(**kwargs)
        Handler.handlers[route] = cls

class Home(Handler, route="/"): ...

class RequiresRun:                                 # enforce a rule at class-creation time
    def __init_subclass__(cls, **kwargs):
        super().__init_subclass__(**kwargs)
        if not callable(cls.__dict__.get("run")):
            raise TypeError(f"{cls.__name__} must define run()")
```

Output (`metaprogramming.py`):

```
Rex speaks | type(Dog): type | type(type): type
type(42): int | type(int): type
metaclass registry: {'csvexporter': <class '__main__.CsvExporter'>, 'jsonexporter': <class
'__main__.JsonExporter'>}
type(CsvExporter): RegistryMeta
__init_subclass__ routes: {'/': 'Home', '/about': 'About'}
GoodJob: ran
TypeError: BadJob must define run()
```

Note `type(CsvExporter)` is `RegistryMeta` — the metaclass is inherited by every subclass.

When to use what (least power first)

Need	Use
Add/modify methods of one class	Class decorator
Reusable attribute behaviour	Descriptor
React to / register / validate every subclass	`__init_subclass__`
Control the class namespace itself, customise `isinstance`, change how instances are created, or build framework-level DSLs (domain-specific languages — mini-languages tailored to one job)	Metaclass

Python core developer Tim Peters famously remarked that metaclasses are deeper magic than 99% of users should worry about — and since 3.6, `__init_subclass__` and `__set_name__` have removed most remaining reasons.

Common mistakes

- **Metaclass conflict:** combining two base classes with unrelated metaclasses → `TypeError: metaclass conflict`. (One reason to avoid custom metaclasses in libraries.)

- Forgetting `super().__init_subclass__(**kwargs)` — breaks cooperative inheritance (every class in a hierarchy calling `super()` so that each parent gets its turn).
- Using a metaclass for something a decorator could do.

Real-world examples

`abc.ABCMeta` (enforces abstract methods), `enum.EnumType` (formerly `EnumMeta`, makes members), Django's `ModelBase` (turns field declarations into a model with a manager and metadata), Pydantic's `ModelMetaclass` (collects fields and builds validators). Many plugin systems use `__init_subclass__` registries.

In the interview

> **30-second answer:** "A metaclass is the class of a class — `type` by default — and it runs when a class statement executes, so it can inspect or change the class being created. Frameworks like Django's ORM and `abc` use them. In application code I almost never need one: class decorators, descriptors and `__init_subclass__` cover registration and validation with less magic and no metaclass conflicts."

- *What's `type(type)`?* — `type`.
- *What is `__init_subclass__` for?* — A parent hook that runs for each new subclass (registries, validation, per-subclass config).

TL;DR

Everything is an object; classes are made by metaclasses (`type`). Prefer class decorators → descriptors → `__init_subclass__` → metaclasses, in that order.

12.7 Monkey patching — caveats

What it is

Monkey patching is replacing attributes (functions, methods, classes) of modules or classes **at run time**, from outside, e.g. `Greeter.hello = lambda self: "patched!"`. Because Python classes and modules are mutable objects, this always works — which is exactly the danger.

Output (`descriptors_attrs.py`, last part):

```
monkey patched: patched! | existing instance too: patched!
restored: hello
```

Patching a class affects **every existing instance** too, because methods are looked up on the class.

Legitimate uses

- **Tests** — replacing slow or external dependencies (network, time, randomness). Use `unittest.mock.patch` or pytest's `monkeypatch` fixture, which **undo the change automatically**.
- **Hot-fixing a third-party bug** until an upstream fix (a fix made in the library's own source by its maintainers) ships (document it and pin the version — fix the dependency to one exact version).
- Framework-level instrumentation, e.g. gevent's `monkey.patch_all()` makes the standard library cooperative (blocking calls yield control to other tasks), and APM/tracing agents (APM = application performance monitoring; tracing records how long each step of a request takes; OpenTelemetry auto-instrumentation) wrap library functions.

Caveats

1. **Global and invisible**: every user of the module/class sees the change, including other libraries and other threads.
2. **Patch where it's looked up, not where it's defined**: if `app.py` did `from utils import send_email`, you must patch `app.send_email`; patching `utils.send_email` doesn't affect the name already bound in `app`.
3. **Order-dependent**: code that imported or cached the original before the patch keeps it.
4. **Fragile across upgrades**: private internals you patch may change without notice.
5. **Always restore** (try/finally, or tools that do it for you), otherwise test pollution (one test leaving changed state behind that affects others) causes failures in unrelated tests.
6. Built-in types implemented in C (`str`, `int`, `list`) can't be patched: `str.upper = ...` raises `TypeError`.

> **In the interview**

"Monkey patching is modifying classes or modules at run time. It's fine in tests via `mock.patch` or pytest's `monkeypatch`, which restore automatically and must target the name where it's used. In production I avoid it — it's global, order-dependent and breaks on upgrades — and prefer dependency injection, subclassing or a wrapper." (**Dependency injection** means passing the collaborators a piece of code needs — a database client, a clock — in as arguments, instead of having the code reach out and create them itself, so they are easy to swap.)

> **TL;DR**

Monkey patching is powerful and global. Use it in tests with auto-restoring tools, patch where the name is looked up, and prefer dependency injection in production.

12.8 Introspection and dynamic code (brief)

Introspection means a program examining its own objects at run time. It is the everyday side of metaprogramming:

Tool	Does	Example
`getattr(obj, name, default)`, `setattr`, `hasattr`, `delattr`	Read/write attributes whose names are strings	`getattr(handler, f"do_{verb}")` to dispatch by name
`vars(obj)`, `dir(obj)`	Instance `__dict__`; all attribute names	Debugging, generic `__repr__`
`type(x)`, `isinstance`, `issubclass`, `callable`	Types and capabilities	
`inspect.signature(f)`	Parameter names, defaults, annotations	FastAPI and pytest read signatures to inject arguments/fixtures
`inspect.getsource(f)`, `inspect.getmembers(obj)`	Source text; all members	Documentation tools
`eval(expr)`, `exec(code)`	Run a string as Python	Almost never needed; **never on untrusted input** (anything an outsider can influence) — it can run any code
`ast.literal_eval(s)`	Safely parse a literal (`"[1, 2, {'a': 3}]"`)	The safe replacement for `eval` on data

Rule of thumb: `getattr`-style introspection is normal Python; `eval`/`exec` on anything a user can influence is a security hole (the same class of bug as unpickling untrusted data, Chapter 9).

12.9 Chapter self-check

1. What does `@d` above `def f` do, and when? → `f = d(f)`, once at definition time.
2. Why `functools.wraps`? → Keeps `__name__`, `__doc__`, etc. and sets `__wrapped__`.
3. `@retry` vs `@retry()` for a factory decorator? → The factory needs to be called: `@retry()`.
4. Order of application/execution of stacked decorators? → Applied bottom-up, run top-down.
5. What's required of `lru_cache` arguments? → Hashable.
6. How does `__exit__` suppress an exception? → By returning a truthy value.
7. What must surround `yield` in a `@contextmanager`? → `try/finally` so clean-up runs on errors.
8. Data vs non-data descriptor precedence? → Data descriptor > instance dict > non-data descriptor.
9. When is `__getattr__` called? → Only when normal lookup fails.
10. Simplest way to register every subclass? → `__init_subclass__`.

Chapter TL;DR

- **Decorators:** function in, function out, at definition time. `*args, **kwargs`, return the result, `@functools.wraps`. Factories (three levels) for arguments; stacking applies bottom-up, runs top-down; class decorators modify classes; decorators can simply register.
- **Built-ins:** `property`, `classmethod`, `staticmethod`, `dataclass`, `total_ordering`, `lru_cache`/`cache` (hashable args, pure functions, beware methods), `cached_property`.
- **Context managers:** `__enter__`/`__exit__` guarantee clean-up; truthy `__exit__` suppresses. `@contextmanager` = setup, `yield` in `try`, clean-up in `finally`. `ExitStack` for dynamic resources (LIFO). `suppress`, `closing`, `nullcontext`, `redirect_stdout`, `chdir`.
- **Descriptors:** `__get__`/`__set__`/`__delete__` on class attributes; they power properties and methods. Data descriptors beat the instance dict.
- **Attribute hooks:** `__getattr__` for missing names (delegation), `__getattribute__` for everything (rare, use `super()`).
- **Class creation:** metaclasses (`type` by default) are rarely needed; prefer decorators, descriptors, `__init_subclass__`.
- **Monkey patching:** tests only (auto-restore, patch where used); avoid in production.