Chapter 18 — Cheat Sheets and Glossary

Chapters 1–17 squeezed into pages you can scan in a minute: one **cheat sheet** per area, a **"which API for which job"** table, a verified **ECMAScript version table** (ES2015 → ES2026), a study plan, an **interview question index**, and an A–Z **glossary** of 700+ terms — each defined once, in one line, linked to the section that explains it. Nothing here is new; follow a line's link (written **§12.2** = Chapter 12, section 2) when it doesn't make sense, and look up unfamiliar words in the glossary.

How to revise: read a sheet with the right-hand column covered and say the answer first. Last check before an interview: if you can't define a glossary term in one sentence, follow its link.

Every concrete value quoted on the sheets (outputs, orderings, return values, errors thrown) is asserted by `code/cheatsheet_checks.mjs`, which runs on Node 24 with jsdom for the DOM sheet:

```
OK   18.1 syntax & types
OK   18.2 operators & coercion
OK   18.3 control flow
OK   18.4 functions/closures/this
OK   18.5 objects/Math/Date/JSON
OK   18.6 classes & prototypes
OK   18.7 strings & regex
OK   18.8 arrays
OK   18.9 Map/Set/iterators
OK   18.10 modules
OK   18.11 errors
OK   18.12 async & event loop
OK   18.13 DOM & events
OK   18.14 browser APIs
OK   18.15 Node core
OK   18.16 testing
      Node v24.11.1 - not yet available: Math.sumPrecise (ES2026), Uint8Array.fromBase64 (ES2026), Map#getOrInsert
(ES2026), Iterator.concat (ES2026), Temporal (ES2027)
OK   18.18 versions (Node 24 availability)
all 17 cheat-sheet checks passed
```

18.1 Syntax, variables and types

Running code (§1.5): the browser console, `<script defer src="app.js">` or `<script type="module">` in a page, `node file.js` / `node file.mjs`, or the Node REPL (`node` with no file).

Basic rules (§1.6): case-sensitive; identifiers use letters, digits, `_` and `$` and can't start with a digit; statements end with `;` (automatic semicolon insertion exists, but never break a line straight after `return`). Comments: `//`, `/* */`, `/** JSDoc */` (§1.7).

Strict mode (§1.8) is on automatically in modules and class bodies, and opt-in with `"use strict"` at the top of a script or function. It turns silent mistakes into errors:

Mistake	Sloppy mode	Strict mode
`x = 1` with no declaration	creates a global	`ReferenceError`
`this` in a plain call `f()`	`globalThis`	`undefined`
Writing a frozen / read-only property	ignored	`TypeError`
`function f(a, a)`, `010`, `with`	allowed	`SyntaxError`

Declaring variables (§2.1, §2.2):

	`const` (default choice)	`let` (when you reassign)	`var` (legacy)
Scope	block `{}`	block `{}`	function
Reassign	✗ `TypeError`	✓	✓
Redeclare in same scope	✗ `SyntaxError`	✗	✓ silently
Read before its line	`ReferenceError` (TDZ)	`ReferenceError` (TDZ)	`undefined`
Top level of a classic script	not on `globalThis`	not on `globalThis`	becomes `globalThis.x`

`const` stops *reassignment*, not *mutation*: `const o = { n: 1 }; o.n = 2` is fine.

The eight types (§2.3): seven primitives plus objects.

Value	`typeof`	Remember
`42`, `3.14`, `NaN`, `Infinity`	`"number"`	one 64-bit float type for all numbers
`10n`	`"bigint"`	whole numbers of any size; can't mix with `number`
`'hi'`	`"string"`	immutable UTF-16 text
`true`	`"boolean"`	
`undefined`	`"undefined"`	"not set yet" — what the language gives you
`null`	**`"object"`**	a historic bug; test with `x === null`
`Symbol('id')`	`"symbol"`	unique keys
`{}`, `[]`, `new Date()`	`"object"`	arrays too — use `Array.isArray`
`function () {}`, `class {}`	`"function"`	functions are callable objects
an undeclared name	`"undefined"`	`typeof` never throws, except in the TDZ

Primitives vs objects (§2.4): primitives are copied by value and compared by value; objects are copied as a **reference** and compared by identity, so `{} === {}` is `false` and two variables can point at one object.

18.2 Operators and the coercion table

Arithmetic (§2.5):

Expression	Result	Why
`7 / 2`	`3.5`	`/` is always floating point; integer division is `Math.trunc(a / b)`
`-7 % 3`	`-1`	`%` is a remainder that keeps the **left** operand's sign; true modulo is `((a % n) + n) % n` → `2`
`2 ** 10`	`1024`	exponent (ES2016)
`n++` / `++n` (n = 5)	`5` / `7`	postfix returns the old value, prefix the new one
`1 + '2'`	`"12"`	`+` concatenates if either side is a string
`'5' - 2`, `'3' * '4'`	`3`, `12`	other arithmetic converts to numbers
`true + 1`	`2`	`true` → `1`
`[] + []` / `[] + {}` / `[1,2] + [3]`	`""` / `"[object Object]"` / `"1,23"`	objects become strings first

Equality (§2.6). Use `===`. The only common `==` idiom is `x == null` (true for `null` **or** `undefined`).

Expression	==	Rule behind it
`0 == ''`	`true`	string → number (`''` → `0`)
`0 == '0'`	`true`	string → number
`'' == '0'`	`false`	both strings: compared as text — so `==` is **not transitive**
`false == '0'`	`true`	boolean → number first: `0 == '0'`
`'2' == true`	`false`	`true` → `1`, then `2 == 1`
`null == undefined`	`true`	they equal each other…
`null == 0`	`false`	…and nothing else
`null >= 0`	`true`	relational operators turn `null` into `0`
`NaN == NaN`	`false`	`NaN` equals nothing, not even itself
`[1] == 1`, `[] == ![]`	`true`, `true`	object → primitive (`[]` → `''` → `0`)
`1n == 1`	`true`	BigInt vs number compares the maths value
`'10' < '9'` / `'10' < 9`	`true` / `false`	two strings compare by character code; otherwise numerically
`Object.is(NaN, NaN)` / `Object.is(0, -0)`	`true` / `false`	`===` except for those two cases

Conversions (§2.12):

Value	Number(v)	String(v)	Boolean(v)
`''` / `' '`	`0` / `0`	`''` / `' '`	`false` / `true`
`'42'` / `'4px'` / `'0x1f'`	`42` / `NaN` / `31`	same text	`true`
`null`	`0`	`'null'`	`false`
`undefined`	`NaN`	`'undefined'`	`false`
`true` / `false`	`1` / `0`	`'true'` / `'false'`	—
`[]` / `[7]` / `[1,2]`	`0` / `7` / `NaN`	`''` / `'7'` / `'1,2'`	`true` (all objects)
`{}`	`NaN`	`'[object Object]'`	`true`

`parseInt('08.5kg', 10)` → `8` (reads a prefix, **always pass the radix**) but `Number('08.5kg')` → `NaN` (all or nothing).

Falsy (§2.11) — the complete list: `false`, `0`, `-0`, `0n`, `''`, `null`, `undefined`, `NaN`. Everything else is truthy, including `[]`, `{}`, `'0'`, `'false'` and `new Boolean(false)`.

Logical operators (§2.7):

Operator	Returns	Example
`a && b`	`a` if falsy, else `b`	`0 && 'b'` → `0`; `'a' && 'b'` → `'b'`
`a || b`	`a` if truthy, else `b`	`0 || 'x'` → `'x'`
`a ?? b`	`a` unless `null`/`undefined`	`0 ?? 'x'` → `0`, `'' ?? 'x'` → `''`
`a?.b`, `a?.[k]`, `a?.()`	`undefined` if `a` is `null`/`undefined`	`null?.deep.prop` → `undefined` (short-circuits the whole chain)
`a ||= b`, `a &&= b`, `a ??= b`	assign only when falsy / truthy / nullish	`cfg.port ??= 8080`

Mixing `??` with `||` or `&&` without parentheses is a `SyntaxError`.

Numbers (§2.10): `0.1 + 0.2` is `0.30000000000000004`; integers are exact only up to `Number.MAX_SAFE_INTEGER` = $2^{53} - 1$ (so `2 ** 53 === 2 ** 53 + 1` is `true`); `1 / 0` is `Infinity`; `Math.max()` is `-Infinity`. Use `Number.isNaN(x)` (the global `isNaN('abc')` converts first and says `true`), `toFixed(2)` for display (`(123.456).toFixed(2)` → `'123.46'`), integer cents for money, `BigInt` beyond 2^{53}. Numeric separators: `1_000_000`. Bitwise operators (§2.8) work on 32-bit integers: `5 & 3` = 1, `5 | 3` = 7, `5 ^ 3` = 6, `~5` = −6.

Precedence in one breath (§2.9): member access/calls → postfix → unary (`!`, `typeof`, `await`) → `**` → `* / %` → `+ -` → shifts → `< > in instanceof` → equality → bitwise → `&&` → `|| ??` → `? :` → assignment and `=>` → comma. When unsure, add parentheses.

18.3 Control flow and loops

Need	Use	Watch out
Choose between code paths	`if / else if / else` (§3.2)	first truthy branch wins — order specific → general
Choose between two **values**	`cond ? a : b` (§3.3)	don't nest deeply
One value vs many fixed options	`switch` (§3.4)	compares with `===`; forgetting `break` **falls through**; `switch (1) { case 1: … case 2: … break }` runs both cases
Pure value → value mapping	lookup object or `Map`	object keys are strings
Count / index loop	`for (let i = 0; i < n; i++)` (§3.6)	`<` vs `<=` off-by-one
Unknown number of repeats	`while (cond)` (§3.7)	update the condition or it never ends
Run at least once	`do { } while (cond)` (§3.8)	`do {…} while (false)` runs once
Values of an array, string, Map, Set	`for (const v of it)` (§3.10)	plain objects aren't iterable — use `Object.entries(obj)`
Keys of a plain object	`for (const k in obj)` (§3.9)	keys are **strings** (`for…in` over `['a','b']` gives `'0'`, `'1'`), includes inherited ones — avoid on arrays
Index and value	`for (const [i, v] of arr.entries())`	
Leave a loop / skip one pass	`break` / `continue` (§3.11)	`forEach` can't be stopped — use `for…of`, `some`, `find`
Leave an **outer** loop	`outer: for (…) { for (…) { break outer; } }`	labels work with `continue outer` too

Closures in loops (§4.7): `for (var i…)` shares one `i`, so three saved callbacks all return `3`; `for (let i…)` makes a fresh binding per iteration, giving `0, 1, 2`.

18.4 Functions, scope, closures and `this`

Forms (§4.1–§4.3):

```
function add(a, b) { return a + b; }        // declaration: hoisted with its body
const sub = function (a, b) { return a - b; }; // expression: follows const (TDZ)
const sq = (x) => x * x;                    // arrow, implicit return
const mk = (x, y) => ({ x, y });            // returning an object literal needs ( )
(() => { /* IIFE: runs immediately */ })();
```

	Regular `function`	Arrow `=>`
`this`	set by the call site	lexical — taken from where it's written; `call`/`bind` can't change it
`arguments`	yes	no — use `...args`
`new`	allowed	`TypeError` (no `prototype`)
Best as	object methods, constructors	callbacks, especially inside methods

Parameters (§4.4): with `f = (a, b = 2, ...rest) => [a, b, rest]`, `f(1)` → `[1, 2, []]`; `f(1, undefined, 3, 4)` → `[1, 2, [3, 4]]`; `f(1, null)` → `[1, null, []]` — **defaults replace only** `undefined`. `fn.length` counts parameters before the first default/rest (`(a, b = 1, c) => 0` has length `1`). Use an options object for named parameters: `function f({ a = 1, b = 2 } = {})`.

Scope and hoisting (§4.5, §4.6):

Declaration	Before its line
`function f() {}`	callable
`var x`	`undefined`
`let` / `const` / `class`	`ReferenceError` (TDZ)
`var f = function…`	`undefined` → calling it is a `TypeError`

Lookups walk the **lexical scope chain** outward from where the code is *written*; an inner name shadows an outer one.

Closures (§4.7): a function keeps live access to the variables of the scope it was created in.

```
function counter() { let c = 0; return () => ++c; }
const c1 = counter(); c1(); c1();
const c2 = counter();
c1(); // 3   - c1 has its own c
c2(); // 1   - c2 has a separate c
```

Uses: private state, factories, `once`, `memoize`, event handlers, debounce/throttle (§17.3).

Higher-order functions (§4.8): take or return functions — `map/filter/reduce`, `pipe` (left → right, `reduce`), `compose` (right → left, `reduceRight`), currying `f(a)(b)(c)`, partial application. **Recursion** (§4.10): base case + smaller case; too deep → `RangeError: Maximum call stack size exceeded`. **Pure functions** (§4.11): same input → same output, no side effects.

`this` — decided at call time (§9.1), highest priority first:

Call site	`this`
`new Fn()`	the new object
`fn.call(obj, a, b)`, `fn.apply(obj, [a, b])`, `fn.bind(obj)()`	`obj`
`obj.fn()`	`obj` (the thing before the dot)
plain `fn()`	`undefined` in strict code (`globalThis` in sloppy scripts)
arrow function	whatever `this` was where the arrow was written

Checked facts: `user.hi()` → `'Ada'`, but `const lost = user.hi; lost()` → `this` is `undefined` (the method "loses" its object when passed around — fix with an arrow wrapper or `bind`). Binding twice keeps the **first** binding. `call` runs now with arguments listed, `apply` runs now with an array, `bind` returns a new function (§9.2).

`['1', '7', '11'].map(parseInt)` → `[1, NaN, 3]`, because `map` passes `(value, index)` and `parseInt` treats the index as the radix.

18.5 Objects, Math, Date and JSON

Objects (§5.1–§5.5):

```
const key = 'dyn';
const o = { b: 1, 2: 'two', a: 2, 1: 'one', [key]: 3 };   // computed key
Object.keys(o);            // ['1', '2', 'b', 'a', 'dyn'] - integer-like keys first, then insertion order
const { a, b: renamed, missing = 'def' } = o;            // 2, 1, 'def'
const merged = { ...{ x: 1, y: 1 }, ...{ y: 2 } };       // { x: 1, y: 2 } - later wins
```

Task	Code	Note
Read with a fixed / dynamic key	`o.name` / `o[expr]`	brackets for spaces, dashes, variables
Own key?	`Object.hasOwn(o, k)`	`'toString' in {}` is `true` (inherited); `Object.hasOwn({}, 'toString')` is `false`
Remove	`delete o.k`	
List	`Object.keys / values / entries`, rebuild with `Object.fromEntries`	own, enumerable, string keys
Shallow copy / merge	`{ ...a, ...b }`, `Object.assign({}, a, b)`	nested objects are **shared**
Deep copy	`structuredClone(o)`	handles Date, Map, Set, cycles; throws on functions
Lock	`Object.preventExtensions` < `Object.seal` < `Object.freeze`	all **shallow**: a frozen object's nested objects stay writable
Prototype	`Object.create(proto)`, `Object.create(null)` for a bare dictionary	§18.6
Getter / setter	`get total() {…}`, `set total(v) {…}` (§5.7)	keep them cheap

Descriptors (§5.6): `writable`, `enumerable`, `configurable` (+ `get`/`set`). Normal assignment makes them all `true`; `Object.defineProperty` defaults them to `false`.

Math (§5.10):

Call	Result
`Math.round(2.5)` / `Math.round(-2.5)`	`3` / `-2` (halves go toward +∞)
`Math.floor(-1.5)` / `Math.trunc(-1.5)` / `Math.ceil(1.1)`	`-2` / `-1` / `2`
`Math.max(...[3, 9, 1])`	`9` (spread — `max` takes separate arguments)
Random int in [min, max]	`Math.floor(Math.random() * (max - min + 1)) + min`
Secure random	`crypto.getRandomValues`, `crypto.randomUUID()` — never `Math.random`

Date (§5.11): a `Date` is milliseconds since 1970-01-01 UTC. Months are **0-based** (`new Date(2024, 0, 31)` is 31 January); `getDay()` is the weekday (0 = Sunday), `getDate()` the day of month; setters mutate and roll

over (setting month 1 on 31 January gives a date in March); a date-only ISO string like `'2024-03-10'` is parsed as **UTC midnight**; `new Date(0).toISOString()` → `'1970-01-01T00:00:00.000Z'`. Show dates with `Intl.DateTimeFormat` / `toLocaleDateString`. **Temporal** reached Stage 4 in March 2026 (it goes into ES2027); it is not in Node 24, so feature-detect it.

JSON (§5.12):

Input to `JSON.stringify`	Output
`{ u: undefined, f() {}, n: NaN, d: new Date(0), m: new Map([[1, 2]]) }`	`{"n":null,"d":"1970-01-01T00:00:00.000Z","m":{}}`
`[undefined, () => 1]`	`[null,null]`
`undefined` (top level)	`undefined` (not a string)
`{ big: 1n }` or an object with a cycle	throws `TypeError`
`JSON.stringify(v, null, 2)`	pretty-printed with 2-space indent

`JSON.parse` is strict: double-quoted keys and strings only, no trailing commas, no comments (`JSON.parse("{'a':1}")` throws `SyntaxError`). A **reviver** `(key, value) => …` can turn ISO strings back into `Date`s.

18.6 Classes and prototypes

```
class Animal {
  #secret = 's';                    // private field (ES2022)
  static count = 0;                 // static field
  static { Animal.ready = true; }   // static block, runs once
  constructor(name) { this.name = name; Animal.count++; }
  speak() { return `${this.name} makes a sound`; }   // on Animal.prototype
  get upper() { return this.name.toUpperCase(); }     // accessor
  static isAnimal(x) { return #secret in x; }        // brand check
}
class Dog extends Animal {
  speak() { return `${super.speak()} - woof`; }
}
new Dog('Rex').speak();  // 'Rex makes a sound - woof'
```

Fact	Checked result
`Object.keys(new Dog('Rex'))`	`['name']` — methods are non-enumerable, `#private` is invisible
`Object.getPrototypeOf(Dog.prototype) === Animal.prototype`	`true` — `extends` links the chains
`Animal('x')` without `new`	`TypeError`
Using `this` before `super()` in a subclass constructor	`ReferenceError`
`typeof class {}`	`'function'` — a class is a special function
`Object.getPrototypeOf(Object.prototype)`	`null` — the end of every chain
`'toString' in Object.create(null)`	`false` — no inherited keys

How lookup works (§9.3): reading a missing property walks the `[[Prototype]]` chain until it finds it or reaches `null`; writing always creates an **own** property (shadowing). `Fn.prototype` is the object that *instances* of `new Fn()` get as their prototype, not `Fn`'s own prototype. `__proto__` is a legacy accessor — use `Object.getPrototypeOf` / `Object.create`.

`new Fn(args)` (§9.4): 1. create an object linked to `Fn.prototype`; 2. run `Fn` with `this` = that object; 3. return it, unless `Fn` returns a different **object** (a returned primitive is ignored).

Type checks (§9.7): `typeof` for primitives, `Array.isArray` for arrays, `Error.isError` (ES2026) for errors, `x instanceof C` for "made by C" (walks the chain; breaks across realms), `#brand in x` inside a class, duck typing (`typeof x?.then === 'function'`) for "behaves like", `Object.prototype.toString.call(x)` → `'[object Date]'` for built-in tags.

Design (§9.8, §9.9): inheritance (is-a) only for stable taxonomies such as `HttpError extends Error`; composition (has-a) for most application code; mixins to share a capability between unrelated classes. TypeScript's `private` is compile-time only; JavaScript's `#private` is enforced at runtime.

18.7 Strings and regular expressions

Strings (§6.2–§6.6) are immutable UTF-16 primitives. Methods always return a **new** string.

Job	Method	Example → result
Interpolate / multi-line	template literal	`` `${1 + 1}` `` → `'2'`
Last char, out-of-range	`at(-1)`, `s[i]`, `charAt(i)`	`'Hello'.at(-1)` → `'o'`; `'Hello'[10]` → `undefined`; `charAt(10)` → `''`
Substring	`slice(start, end?)` (negatives OK)	`'Hello'.slice(-3)` → `'llo'`, `slice(1, 3)` → `'el'`
Search	`includes`, `startsWith`, `endsWith`, `indexOf` (−1 if absent)	
Replace first / all	`replace` / `replaceAll`	`'a-b-c'.replace('-', '+')` → `'a+b-c'`; `replaceAll` → `'a+b+c'`
Pad, repeat	`padStart`, `padEnd`, `repeat`	`'5'.padStart(3, '0')` → `'005'`
Trim	`trim`, `trimStart`, `trimEnd`	
Split / join	`split(sep)`, `arr.join(sep)`	`'a,b,,c'.split(',')` → `['a', 'b', '', 'c']`
Case	`toUpperCase`, `toLowerCase`, `toLocale…`	
Human ordering	`a.localeCompare(b)`, `Intl.Collator`	default `sort` gives `'Cab'` for `['b','a','C']`; with `localeCompare` → `'abC'`

Unicode (§6.5): `length` counts 16-bit code units — `'😀'.length` is `2`, `[...'😀'].length` is `1` (code points), and a family emoji `'👨‍👩‍👧'` is one grapheme to `Intl.Segmenter`. Normalize with `normalize('NFC')` before comparing accented text.

Regex syntax (§6.7):

Piece	Meaning
`.` `\d` `\w` `\s` (`\D` `\W` `\S`)	any char (not newline) / digit / word char / whitespace (and complements)
`[abc]` `[^abc]` `[a-z]`	class / negated class / range
`*` `+` `?` `{n,m}`	0+ / 1+ / 0–1 / n to m — **greedy**; add `?` for lazy
`^` `$` `\b`	start / end / word boundary
`( )` `(?<name> )` `(?: )`	capture / named capture / group only
`(?= )` `(?! )` `(?<= )` `(?<! )`	lookahead / negative lookahead / lookbehind / negative lookbehind
`\1`, `\k<name>`	backreference
`\p{L}` (with `u` or `v`)	any letter in any script
Flags	`g` all, `i` ignore case, `m` multiline anchors, `s` dot matches newline, `u` Unicode, `v` Unicode sets, `y` sticky, `d` indices

Regex methods (§6.8):

Call	Result
`/^\d{3}-\d{4}$/.test('555-1234')`	`true`
`'x'.match(/y/)`	`null` (not `[]`)
`'a1b22'.match(/\d+/g)`	`['1', '22']`
`'2024-03-10'.match(/(?<y>\d{4})-…/).groups.y`	`'2024'`
`'2024-03-10'.replace(/(\d+)-(\d+)-(\d+)/, '$3/$2/$1')`	`'10/03/2024'`
`[...'a1b2'.matchAll(/\d/g)].map(m => m.index)`	`[1, 3]`; `matchAll` without `g` throws `TypeError`
`'<b>x</b>'.replace(/<.+>/, '')` vs `/<.+?>/`	`''` (greedy) vs `'x</b>'` (lazy)
`/a/g.test('aa')` then `lastIndex`	`1` — a `g` regex remembers its position between calls
`new RegExp(RegExp.escape(userText))`	matches the text literally (ES2025)

Prefer plain string methods for fixed text and real parsers (`URL`, `JSON.parse`, `DOMParser`) for structured formats (§6.9).

18.8 Arrays: mutating vs non-mutating

✎ = changes the original array (§7.4).

Mutates ✎	Returns	Copying twin / alternative (leaves the original alone)
`push(x)` / `pop()`	new length / removed item	`[...arr, x]` / `arr.slice(0, -1)`
`unshift(x)` / `shift()`	new length / removed item	`[x, ...arr]` / `arr.slice(1)`
`splice(i, n, ...items)`	array of **removed** items	`toSpliced(i, n, ...items)` (ES2023)
`sort(cmp)`	the **same** array	`toSorted(cmp)` (ES2023)
`reverse()`	the same array	`toReversed()` (ES2023)
`arr[i] = x`	—	`with(i, x)` (ES2023; negative `i` OK, out of range → `RangeError`)
`fill(v, s, e)`, `copyWithin(t, s, e)`	the same array	`Array.from` / `map`
`arr.length = n`	truncates	`slice(0, n)`

Never mutated: `slice`, `concat`, `map`, `filter`, `reduce`, `flat`, `flatMap`, `find*`, `some`, `every`, `includes`, `indexOf`, `at`, `join`, `keys/values/entries`, spread.

Checked behaviours: `const s = arr.sort(); s === arr` → `true`; `[1].push(2)` → `2` (not the array); `[10, 1, 2].sort()` → `[1, 10, 2]` (default sort compares **strings**) but `.sort((a, b) => a - b)` → `[1, 2, 10]`; `[3, 1, 2].toSorted()` → `[1, 2, 3]` with the original unchanged.

Iteration methods (§7.5):

Want	Method	Checked example
Transform each	`map`	
Keep some	`filter`	
Fold to one value	`reduce(fn, init)`	`[1,2,3].reduce((s, x) => s + x, 0)` → `6`; `[].reduce(fn)` with no init → `TypeError`
First match / its index	`find` / `findIndex`	`find(x => x > 1)` → `2`; `findIndex(x => x > 5)` → `-1`
Last match	`findLast` / `findLastIndex` (ES2023)	`findLast(x => x > 1)` → `3`
Any / all	`some` / `every`	`[].every(…)` → `true` (vacuous truth)
Contains	`includes`	`[NaN].includes(NaN)` → `true`, `[NaN].indexOf(NaN)` → `-1`
Flatten	`flat(depth = 1)`, `flatMap`	`[1,[2,[3,[4]]]].flat()` → `[1,2,[3,[4]]]`; `flat(Infinity)` → `[1,2,3,4]`
Side effects only	`forEach` / `for…of`	`forEach` can't `break` or `await`

Sorting (§7.6): numbers `(a, b) => a - b`; text `a.localeCompare(b)`; several keys chained with `||`: `(p, q) => p.age - q.age || p.name.localeCompare(q.name)`. `sort` is stable (guaranteed since ES2019).

Creating and destructuring (§7.2, §7.7): `Array.from({ length: 3 }, (_, i) => i * 2)` → `[0, 2, 4]`; `Array.of(3)` → `[3]` but `new Array(3)` has length 3 and holes; `Array(2).fill([])` puts the **same** inner array in both slots. `[x, y] = [y, x]` swaps; `const [first, , third = 'd', ...others] = [1, 2, undefined, 4, 5]` → `1`, `'d'`, `[4, 5]`. `join` turns `null`/`undefined` into empty strings.

Immutable updates (React/Redux style): add `[...arr, x]`; insert `arr.toSpliced(i, 0, x)`; remove by id `arr.filter(t => t.id !== id)`; replace `arr.with(i, x)`; update one `arr.map(t => t.id === id ? { ...t, done: true } : t)`.

Which collection (§7.8): array for ordered lists, object for fixed-shape records, `Map` for dynamic keyed lookup, `Set` for uniqueness. **Typed arrays** (§7.9) hold fixed-size binary numbers over an

`ArrayBuffer`; values wrap (`new Uint8Array([256, 257])` → `[0, 1]`).

18.9 Map, Set, iterators and generators

`Map` (§8.1) — keys of any type, insertion order, `size`:

```
const m = new Map([[1, 'num'], ['1', 'str']]);   // 1 and '1' are different keys
m.set({}, 'obj').set(NaN, 'nan');                 // set() returns the map, so it chains
m.get(NaN);           // 'nan' - keys compare with SameValueZero
JSON.stringify(m);    // '{}'  - convert first: Object.fromEntries(m) or [...m]
for (const [k, v] of m) { /* insertion order */ }
```

`Set` (§8.2) — unique values, O(1) `has`: `[...new Set([3, 1, 3, 2, 1])]` → `[3, 1, 2]` (dedupe, first-seen order). ES2025 set algebra, with A = {1,2,3} and B = {2,3,4}:

Method	Result
`A.union(B)`	{1, 2, 3, 4}
`A.intersection(B)`	{2, 3}
`A.difference(B)`	{1}
`A.symmetricDifference(B)`	{1, 4}
`A.isSubsetOf(B)`, `isSupersetOf`, `isDisjointFrom`	booleans

Use	When
`Map`	dynamic dictionaries, counting, caches (an LRU cache is one `Map`), non-string keys
plain object	fixed-shape records, config, JSON
`Set`	membership tests, dedupe, visited sets in BFS/DFS
`WeakMap` / `WeakSet` (§8.3)	data attached to objects you don't own; entries vanish with the key object; no `size`, no iteration
`WeakRef` / `FinalizationRegistry`	advanced caches; GC timing is never guaranteed

Iteration protocol (§8.4): an **iterable** has a `[Symbol.iterator]()` method returning an **iterator**, an object whose `next()` returns `{ value, done }`. Arrays, strings, Maps, Sets, typed arrays, NodeLists and generators are iterable; plain objects are not (`[...{ a: 1 }]` → `TypeError`). Consumers: `for…of`, spread, array destructuring, `Array.from`, `new Map/Set`, `Promise.all`, `yield*`.

Generators (§8.5):

```
function* nat() { let n = 1; while (true) yield n++; }   // infinite, lazy
nat().next();                          // { value: 1, done: false }
const iterable = { *[Symbol.iterator]() { yield 1; yield 2; } };
[...iterable];                         // [1, 2]
function* two() { yield 'a'; return 'r'; }
[...two()];                            // ['a'] - the return value is not iterated
```

Iterator helpers (ES2025, §8.6) are lazy: `nat().filter(n => n % 2).map(n => n * n).take(3).toArray()` → `[1, 9, 25]`. Arrays need `.values()` first; `Iterator.from(x)` wraps custom iterators.

Grouping (ES2024, §8.7): `Object.groupBy([1,2,3,4], n => n % 2 ? 'odd' : 'even')` → `{ odd: [1, 3], even: [2, 4] }` (a null-prototype object); `Map.groupBy` when keys aren't strings.

Async iteration (§12.12): `async function*` + `for await (const page of pages())`; `await Array.fromAsync(pages())` (ES2026) collects them.

18.10 Modules and tooling

```
// math.mjs
export const PI = 3.14;                 // named export
export function area(r) { return PI * r * r; }
export default class Circle {}          // one default per module
// app.mjs
import Circle, { area, PI as pi } from './math.mjs';
import * as math from './math.mjs';     // namespace object: math.area, math.default
export { area } from './math.mjs';      // re-export (barrel file)
const { heavy } = await import('./heavy.mjs');  // dynamic import -> promise, code splitting
import data from './data.json' with { type: 'json' };  // JSON module (ES2025)
```

ES module fact (§10.3)	Consequence
Loads in 3 phases: parse → link → evaluate	imports are hoisted; a missing export fails before any code runs
Imports are **live, read-only bindings**	you see the exporter's updates; you can't assign to them
Each module is evaluated **once** (singleton)	module-level state is shared by every importer
Always strict; top-level `this` is `undefined`	checked by the sheet script
Top-level `await` allowed (§10.5)	importers wait for it
`import.meta.url`, `import.meta.dirname` / `filename` (Node) (§10.6)	replace CommonJS `__dirname` / `__filename`

CommonJS vs ESM in Node (§10.8): `.mjs` = ESM, `.cjs` = CommonJS, `.js` follows `"type"` in the nearest `package.json`. CommonJS uses `require()` / `module.exports`, loads synchronously, has `__dirname`. ESM can import CommonJS (default import = `module.exports`); since Node 22.12 / 20.19, CommonJS can `require()` an ES module unless it uses top-level `await` (`ERR_REQUIRE_ASYNC_MODULE`). **Browsers** (§10.7): `<script type="module">` is deferred, strict, needs CORS and a server (not `file://`); import maps resolve bare names.

npm (§10.9, §10.10):

Item	Meaning
`dependencies` / `devDependencies` / `peerDependencies`	needed at runtime / only to build and test / "use the host's copy"
`^1.2.3`	≥1.2.3 <2.0.0 (npm's default)
`~1.2.3`	≥1.2.3 <1.3.0
`^0.2.3`	≥0.2.3 <0.3.0 (caret is stricter below 1.0)
`package-lock.json`	commit it; CI runs `npm ci` (exact, clean install)
`npx tool`, `npm run x`, `node --run x`	run a package binary / a script

Tools (§10.11–§10.13): bundlers (Vite, esbuild, webpack, Rollup/Rolldown) do resolution, tree shaking, code splitting, minification, source maps and HMR. **Transpile syntax, polyfill APIs**: a transpiler rewrites new syntax for old engines; a polyfill adds missing built-ins. ESLint finds bugs (flat config `eslint.config.js`); Prettier formats.

18.11 Errors and debugging

Error type (§11.1)	Checked trigger
`TypeError`	`null.length`, calling a non-function, `1n + 1`, assigning to a `const`
`ReferenceError`	undeclared name, TDZ access
`SyntaxError`	`JSON.parse('{bad}')`, bad code in `eval` / `new Function`
`RangeError`	`new Array(-1)`, `(1).toFixed(101)`, stack overflow
`URIError`	`decodeURIComponent('%')`
`AggregateError`	`Promise.any` when all reject — `.errors` holds them

```
class ValidationError extends Error {                // §11.3
  constructor(msg, opts) { super(msg, opts); this.name = 'ValidationError'; this.code = 'E_VALID'; }
}
try {
  save();
} catch (err) {
  if (!(err instanceof ValidationError)) throw err;   // catch narrowly, rethrow the rest
  throw new Error('save failed', { cause: err });     // §11.4 error chaining
} finally {
  release();                                          // always runs; never return from it
}
```

Rules: always throw `Error` objects (they carry a `stack`); `String(err)` → `'ValidationError: save failed'`; a `return` in `try` still runs `finally` first; `catch {}` without a binding is legal (ES2019) but never swallow errors silently. **`try/catch` is synchronous**: it catches a rejected `await` inside an `async` function, but not an error thrown later in a timer callback (§11.5). Global last-resort handlers: browser `error` / `unhandledrejection` events; Node `uncaughtException` / `unhandledRejection` — log, then exit. `using` + `Symbol.dispose` gives automatic cleanup (§11.6; finished proposal, edition ES2027).

Debugging (§11.7–§11.9): `console.table`, `dir`, `group`, `count`, `time` / `timeEnd`, `trace`, `assert` (logs, doesn't throw). Stack traces list the newest frame first; source maps map bundled code back to your files. Breakpoints (conditional, logpoints, pause on exceptions), step over / into / out, Scope and Watch panes; `debugger;` statement; Node: `node --inspect` then `chrome://inspect`. Method: reproduce → read the message → hypothesize → inspect → fix the root cause → add a test. Common messages decoded: §11.10.

18.12 Async and the event loop




*Figure — one turn of the event loop: one task, then **all** microtasks, then maybe a render (§12.2).*

The ordering rule (§12.3): synchronous code first (including promise executors and an async function's body up to its first `await`), then microtasks in FIFO order, then the next task.

```
log('A');
setTimeout(() => log('B timeout'), 0);
Promise.resolve().then(() => log('C then')).then(() => log('D then2'));
queueMicrotask(() => log('M micro'));
new Promise((res) => { log('P executor'); res(); });
(async () => { log('F before await'); await null; log('F after await'); })();
log('E');
// A, P executor, F before await, E, C then, M micro, F after await, D then2, B timeout
```

Node extras (§12.4): phases timers → pending → poll (I/O) → check (`setImmediate`) → close. Inside a callback, `process.nextTick` runs before promise microtasks, and both run before `setImmediate` — checked order: `nextTick, promise, immediate`.

Promises (§12.7, §12.8): pending → fulfilled or rejected, settle **once**; `then` returns a new promise, so always `return` inside it and end the chain with `catch`.

Combinator	Fulfils when	Rejects when	Checked
`Promise.all`	all fulfil — values in **input order**	first rejection	`[ok(1, 5ms), ok(2, 1ms)]` → `[1, 2]`
`Promise.allSettled`	all settle	never	statuses `['fulfilled', 'rejected']`
`Promise.race`	first to **settle** fulfils	first to settle rejects	fastest wins
`Promise.any`	first to **fulfil**	all reject → `AggregateError`	skips a rejection
`Promise.withResolvers()` (ES2024)	`{ promise, resolve, reject }`		
`Promise.try(fn)` (ES2025)	a sync throw becomes a rejection		

None of the combinators cancel the losing operations.

async/await (§12.9): an `async` function always returns a promise; `await` unwraps it and **throws** on rejection (so `try/catch` works). Two independent awaits one after another take the sum of their times (checked: ~80 ms); `await Promise.all([...])` takes the longest (~40 ms). `arr.forEach(async …)` doesn't wait — use `for…of` (one at a time) or `Promise.all(arr.map(async …))` (all at once). Use `return await` inside `try` so the `catch` sees the rejection.

Timers (§12.5): delays are minimums; nested timers clamp to 4 ms in browsers; delays above $2^{31} - 1$ ms overflow; prefer recursive `setTimeout` to `setInterval` for polling. **Cancellation** (§12.11): `const ac = new AbortController(); fetch(url, { signal: ac.signal }); ac.abort()`; `AbortSignal.timeout(ms)`; `AbortSignal.any([...])`. **Patterns** (§12.13): retry with exponential backoff + jitter, concurrency limits, last-request-wins, debounce/throttle.

18.13 DOM and events

Task	API (§13.1–§13.4)
Find one / many	`document.getElementById('id')`, `el.querySelector(css)` / `querySelectorAll(css)` (static `NodeList`)
Live collections	`getElementsByTagName` / `ByClassName` — update automatically (checked: after appending an `<li>`, the live list has 2 items, the static one still 1)
Relatives	`el.closest(css)` (self or ancestor), `el.matches(css)`, `parent.contains(node)`, `children`, `nextElementSibling`
Create and insert	`document.createElement('li')`, `append`, `prepend`, `before`, `after`, `replaceWith`, `remove`, `replaceChildren`; `DocumentFragment` / `<template>` for bulk
Text vs HTML	`el.textContent = userText` (never parsed — `'<b>safe</b>'` shows as text); `innerHTML` only for trusted markup (XSS risk)
Classes, data, style	`classList.add/remove/toggle/contains`, `el.dataset.id` (from `data-id`, always a string), `el.style.x` (inline), `getComputedStyle(el)` (final)
Attribute vs property	`input.getAttribute('value')` = initial HTML value; `input.value` = current value

Events (§13.5–§13.8):

```
list.addEventListener('click', (e) => {          // one listener for all items (delegation)
  const item = e.target.closest('li');           // target = where it started
  if (!item || !list.contains(item)) return;
  console.log(item.dataset.id, e.currentTarget); // currentTarget = list (the listener's element)
}, { signal: controller.signal });                // options: once, passive, capture, signal
```

Fact	Checked
Propagation: capture (window → target), target, bubble (target → window)	order: `body capture`, `delegated 7`, `body bubble target=BUTTON current=BODY`
`new Event('ping')` doesn't bubble	parent heard 0; with `{ bubbles: true }` → 1
`{ once: true }`	handler ran once for two clicks
`e.preventDefault()`	cancels the default action (link navigation, form submit); `e.defaultPrevented` → `true`
`stopPropagation()`	stops the journey — use rarely
`dispatchEvent`	runs listeners **synchronously**

Forms (§13.9): listen for `submit`, call `preventDefault()`, read `new FormData(form)` (`getAll('t')` → `['a', 'b']` for repeated names), check `input.validity` / `setCustomValidity`, use `form.requestSubmit()`; always validate again on the server. **Watch changes**: `MutationObserver` (§13.10). **Performance** (§13.11): batch all layout reads, then all writes (interleaving them causes **layout thrashing**); animate `transform`/`opacity`; use `requestAnimationFrame`. **Script timing** (§13.12): `defer` and modules run after parsing, in order, before `DOMContentLoaded`; `async` runs whenever downloaded; `load` waits for images and styles.

18.14 Browser APIs and security

fetch (§14.1):

```
async function getJSON(url, { timeout = 5000 } = {}) {
  const res = await fetch(url, { signal: AbortSignal.timeout(timeout),
                                 headers: { Accept: 'application/json' } });
  if (!res.ok) throw new Error(`HTTP ${res.status}`);   // fetch resolves on 404/500!
  return res.json();                                    // the body can be read only once
}
await fetch('/api/items', { method: 'POST',
  headers: { 'Content-Type': 'application/json' }, body: JSON.stringify(item) });
```

`fetch` rejects only on network failure or abort; a 404 `Response` has `ok === false`. Reading a body twice throws `TypeError`.

URL (§14.6): `new URL('https://shop.example.com:8443/search?q=red shoes')` → `.origin` = `'https://shop.example.com:8443'`, `.searchParams.get('q')` = `'red shoes'`; after `set('page','3')` and `append('tag','a&b')` the search string is `'?q=red+shoes&page=3&tag=a%26b'` (encoding done for you). `new URL('../img/a.png', 'https://x.dev/app/page/')` resolves to `https://x.dev/app/img/a.png`; `new URL('not a url')` throws `TypeError` (a cheap validator). `encodeURIComponent('a b&c')` → `'a%20b%26c'`.

Storage (§14.3, §14.4):

	Cookie	localStorage	sessionStorage	IndexedDB
Size	~4 KB	~5 MB	~5 MB	large
API	strings, sync	strings, sync (`setItem('n', 42)` stores `'42'`; missing → `null`)	same, per tab	async, structured data
Sent to server	automatically	no	no	no
Use for	session ID (`HttpOnly; Secure; SameSite`)	preferences	wizard state	offline data, big caches

Never put tokens or secrets in `localStorage` — any script on the page can read it.

Other APIs: `requestAnimationFrame` for visual updates, once per frame, paused in background tabs (§14.5); History API `pushState` / `replaceState` + `popstate` for SPA routing (§14.7); Web Workers for CPU work off the main thread, talking via `postMessage` + structured clone (§14.8); `IntersectionObserver` (visibility, lazy loading) and `ResizeObserver` (element size) (§14.9). `structuredClone` copies Dates and Maps but throws `DataCloneError` on functions.

Security (§14.2, §14.10–§14.12):

Threat / rule	Remember
Origin	scheme + host + port; the browser lets a page *send* anywhere but *read* only same-origin responses
CORS	the **server** opts in with `Access-Control-Allow-Origin`; non-simple requests get an `OPTIONS` preflight; `*` can't be combined with credentials
XSS	treat data as text (`textContent`), escape by context (`<` → `<`), sanitize HTML with DOMPurify, allow-list URL schemes, CSP, `HttpOnly` cookies
CSRF	`SameSite` cookies + CSRF token or `Origin` check; GET must never change state; CORS is not a CSRF defence
CSP	`Content-Security-Policy: default-src 'self'; script-src 'self'; object-src 'none'; frame-ancestors 'none'` — blocks inline scripts and clickjacking
Other headers	HSTS, `X-Content-Type-Options: nosniff`, `Referrer-Policy`, `Permissions-Policy`
Supply chain	lockfiles, `npm audit`, few dependencies, Subresource Integrity for CDN scripts

---

18.15 Node.js core modules

Node = V8 + **libuv** (event loop, async I/O, a 4-thread pool for fs, DNS lookup, crypto, zlib) + core modules (§15.1, §15.2). Import built-ins with the `node:` prefix. Never block the loop; move CPU-heavy work to `worker_threads`.

Module	Everyday calls	Checked / remember
`node:fs/promises` (§15.4)	`readFile(p, 'utf8')`, `writeFile`, `appendFile`, `mkdir(p, { recursive: true })`, `readdir`, `stat`, `rm(p, { recursive: true, force: true })`	branch on `err.code` (`'ENOENT'`); don't check-then-act
`node:path` (§15.5)	`join`, `resolve`, `basename`, `extname`, `dirname`, `parse`, `relative`	`join('/srv','app','..','data')` → `/srv/data`; `extname('price.test.mjs')` → `.mjs`
`node:url`	`fileURLToPath(import.meta.url)`, `pathToFileURL`	or `import.meta.dirname`
`process` (§15.6)	`argv`, `env`, `exitCode`, `cwd()`, `on('SIGTERM')`	`process.env.X = 5` reads back `'5'` — env values are strings; `--env-file=.env`
`node:util`	`parseArgs`, `promisify`, `inspect`	`parseArgs` on `['--port','8080','file.txt']` → `port: '8080'`, positionals `['file.txt']`
`Buffer` (§15.7)	`Buffer.from(str)`, `.toString('hex' / 'base64')`	`Buffer.from('é').length` → `2` bytes, `'é'.length` → `1`
`node:events` (§15.8)	`on`, `once`, `off`, `emit`; `events.once(em, name)` → promise	`emit` is **synchronous**; an unhandled `'error'` event throws
`node:stream` (§15.9)	Readable, Writable, Duplex, Transform; `pipeline` from `node:stream/promises`	`pipeline` handles **backpressure** and errors
`node:http` (§15.10)	`createServer((req, res) => { … res.end() })`, `listen(0)` in tests	always end the response; limit body size
`node:child_process` (§15.11)	`execFile(cmd, args)`, `spawn`	pass argument arrays — no shell injection
`node:test`, `node:assert/strict`	§18.16	

Flags (§15.12): `--watch`, `--env-file`, `--run`, `--test`, `--inspect`, `--permission`; `node app.ts` strips types (no type check). **Alternatives**: Deno (secure by default, V8) and Bun (JavaScriptCore, fast tooling); Node stays the default choice.

18.16 Testing and TypeScript

```mjs
// price.test.mjs - run with: node --test
import { test, describe, beforeEach } from 'node:test';
import assert from 'node:assert/strict';
import { applyDiscount } from './price.mjs';

describe('applyDiscount', () => {
  test('takes 10 percent off', () => assert.equal(applyDiscount(100, 10), 90));
  test('rejects negative percentages', () => assert.throws(() => applyDiscount(100, -1), RangeError));
  test('async loader rejects', async () => { await assert.rejects(load('bad'), /not found/); });
  test('calls the logger once', (t) => {
    const log = t.mock.fn();                    // spy, auto-restored
    applyDiscount(100, 10, { log });
    assert.equal(log.mock.callCount(), 1);
  });
});
```

Assertion (§16.2)	Passes when	Checked
`equal(a, b)`	`Object.is(a, b)` — same primitive or same object	`equal({a:1}, {a:1})` fails
`deepEqual(a, b)`	same structure, type-strict	`{a:1}` vs `{a:'1'}` fails
`throws(fn, Class | /regex/)`	`fn()` throws a match	
`await rejects(promise, …)`	the promise rejects — **must be awaited**	
`match(str, /re/)`	regex matches	

`node:test` (§16.3–§16.6): `test`/`it`, `describe`, hooks `before`/`beforeEach`/`afterEach`/`after`, `skip`/`todo`/`only`; `node --test` (finds `*.test.*`), `--watch`, `--test-name-pattern`; `t.mock.fn` / `t.mock.method` spies; fake timers `t.mock.timers.enable()` + `tick(ms)`; snapshots; `--experimental-test-coverage`. Test pyramid: many unit, some integration, few end-to-end (Playwright). Vitest/Jest use `expect(x).toBe(y)` (§16.7).

TypeScript (§16.8–§16.13):

```
type Shape = { kind: 'circle'; r: number } | { kind: 'rect'; w: number; h: number }; // discriminated union
function area(s: Shape): number {
  switch (s.kind) {                              // narrowing by discriminant
    case 'circle': return Math.PI * s.r ** 2;
    case 'rect': return s.w * s.h;
    default: { const never: never = s; return never; }   // exhaustive check
  }
}
function first<T>(xs: readonly T[]): T | undefined { return xs[0]; }   // generic
const ROLES = ['admin', 'user'] as const;            // readonly literal tuple
type Role = (typeof ROLES)[number];                  // 'admin' | 'user'
```

Concept	One line
Types are erased	nothing is checked at runtime — validate JSON with a schema (e.g. Zod)
Structural typing	shapes match, names don't matter
`unknown` vs `any`	`unknown` must be narrowed before use; `any` switches checking off
Narrowing	`typeof`, `instanceof`, `in`, discriminant property, type predicates `x is T`, `asserts` functions
Utility types	`Partial`, `Required`, `Readonly`, `Pick`, `Omit`, `Record`, `ReturnType`, `Parameters`, `Awaited`, `NonNullable`
`interface` vs `type`	both describe objects; `type` also does unions/tuples; interfaces merge
`satisfies`	checks a value against a type without widening it
Running	`tsc --noEmit` type-checks; `node file.ts` only strips erasable syntax (no `enum`, no parameter properties)
JSDoc	`// @ts-check` + `/** @param {number} x */` type-checks plain `.js` files (§16.15)

18.17 Which API for which job

Job	Reach for	Not	See
Default variable	`const` (`let` if reassigned)	`var`	§2.1
Compare values	`===`, `Object.is` for `NaN`/`-0`	`==` (except `x == null`)	§2.6
Default for a missing value	`??` / `??=`	`||` when `0` or `''` are valid	§2.7
Read possibly-missing nested data	`a?.b?.c`	long `&&` chains	§5.8
Money	integer cents, `Intl.NumberFormat` for display	floats	§2.10
Integers beyond 2^{53}	`BigInt`	`number`	§2.10
Parse user input to a number	`Number(s)` + `Number.isNaN`	`parseInt` without a radix	§2.12
Walk an array / string / Map	`for…of`	`for…in`	§3.12
Walk a plain object	`Object.entries(obj)` + `for…of`	`for…in` without `hasOwn`	§5.6
Transform / select / fold	`map` / `filter` / `reduce`	`forEach` + push	§7.5
Sort without touching the original	`toSorted(cmp)`	`sort()` on shared data	§7.4
Last element	`arr.at(-1)`	`arr[arr.length - 1]`	§7.3
Copy an object / array (top level)	`{ ...o }`, `[...a]`	`Object.assign` into the original	§5.4
Deep copy	`structuredClone`	`JSON.parse(JSON.stringify(x))`	§5.4
Dictionary with dynamic or non-string keys	`Map`	plain object	§8.1
Unique values, fast membership	`Set`	`array.includes` in a loop	§8.2
Metadata on objects you don't own	`WeakMap`	`Map` (leaks)	§8.3
Group items by a key	`Object.groupBy` / `Map.groupBy`	hand-written `reduce`	§8.7
Lazy or infinite sequence	generator + iterator helpers	building a huge array	§8.5
Text search / replace of fixed text	`includes`, `replaceAll`	regex	§6.6
Pattern matching	regex (`test`, `matchAll`, named groups)	manual char loops	§6.8
Count visible characters	`Intl.Segmenter`	`length`	§6.5
Format dates / numbers for people	`Intl.DateTimeFormat`, `toLocaleString`	string concatenation	§5.11
Callback that keeps `this`	arrow function	`const self = this`	§9.1
Truly private state	`#private` fields or closures	`_underscore` names	§9.5

Job	Reach for	Not	See
Share code between modules	ES modules (`import` / `export`)	globals, IIFEs	§10.2
Load code only when needed	`import()`	one giant bundle	§10.4
Reproducible installs	lockfile + `npm ci`	`npm install` in CI	§10.10
Report a failure	`throw new Error(msg, { cause })` / custom subclass	throwing strings	§11.3
Several independent async jobs	`await Promise.all([...])`	sequential awaits	§12.9
Report every outcome	`Promise.allSettled`	`all`	§12.8
Timeout or cancel	`AbortSignal.timeout(ms)`, `AbortController`	`Promise.race` alone (doesn't cancel)	§12.11
Wrap an old callback API	`util.promisify` or `new Promise` once	nesting callbacks	§12.7
Paged / streamed data	`async function*` + `for await…of`	loading everything first	§12.12
Insert user text into the page	`textContent`	`innerHTML`	§13.3
Handle events on many children	delegation with `closest`	a listener per item	§13.7
Remove many listeners at once	`{ signal }` + `controller.abort()`	tracking every function	§13.5
Animate	CSS transitions, or `requestAnimationFrame` changing `transform`	`setInterval` changing `top` / `left`	§14.5
React to scroll visibility / element size	`IntersectionObserver` / `ResizeObserver`	`scroll` / `resize` handlers with measurements	§14.9
HTTP request	`fetch` + check `res.ok`	`XMLHttpRequest`	§14.1
Build or parse URLs	`URL`, `URLSearchParams`	string concatenation	§14.6
Store a session	`HttpOnly; Secure; SameSite` cookie	`localStorage` token	§14.4
Large offline data	IndexedDB	`localStorage`	§14.4
Heavy computation in a page	Web Worker	a long loop on the main thread	§14.8
Heavy computation in Node	`worker_threads`	blocking the event loop	§15.2
Big files / HTTP bodies	streams + `pipeline`	`readFile` of gigabytes	§15.9
Run another program	`execFile` / `spawn` with an argument array	`exec` with user input	§15.11
Tests without dependencies	`node:test` + `node:assert/strict`	ad-hoc `console.log` checks	§16.3
Time-dependent tests	fake timers (`t.mock.timers`)	real `setTimeout` waits	§16.5
Types for untrusted data	`unknown` + narrowing / a schema	`any`	§16.10

Job	Reach for	Not	See
A fixed set of names in TS	union of literals or `as const` object	`enum` (not erasable)	§16.13

18.18 ECMAScript versions ES2015 → ES2026

Each edition is published in June and contains every proposal that reached **Stage 4** in the year before (§1.2). The years below were checked against TC39's list of finished proposals (github.com/tc39/proposals, "finished-proposals"), and the Node 24 column was checked by running the features in Node v24.11 (the `18.18` block of `cheatsheet_checks.mjs`).

Edition	Main features	Node 24
ES2015 (ES6)	`let` / `const`, arrow functions, classes, ES modules, promises, template literals, destructuring, default / rest / spread parameters, `Map` / `Set` / `WeakMap` / `WeakSet`, `Symbol`, iterators and generators, `for…of`, `Proxy` / `Reflect`, typed arrays, `Array.from` / `of`, `find` / `findIndex`, `Object.assign`, `String` `includes` / `startsWith` / `repeat`, `Number.isNaN` / `isInteger`, regex `u` and `y` flags	✓
ES2016	`Array.prototype.includes`, exponent operator `**`	✓
ES2017	`async` / `await`, `Object.values` / `entries`, `padStart` / `padEnd`, `Object.getOwnPropertyDescriptors`, trailing commas in parameter lists, `SharedArrayBuffer` and `Atomics`	✓
ES2018	object rest/spread `{ ...o }`, async iteration (`for await…of`, async generators), `Promise.prototype.finally`, regex `s` flag, named groups, lookbehind, `\p{…}` escapes	✓
ES2019	`flat` / `flatMap`, `Object.fromEntries`, `trimStart` / `trimEnd`, optional `catch` binding, `Symbol.prototype.description`, well-formed `JSON.stringify`; `sort` required to be stable	✓
ES2020	`BigInt`, `??`, `?.`, dynamic `import()`, `import.meta`, `globalThis`, `Promise.allSettled`, `String.prototype.matchAll`, defined `for…in` order	✓
ES2021	`replaceAll`, `Promise.any` + `AggregateError`, logical assignment `||=` `&&=` `??=`, numeric separators `1_000`, `WeakRef` / `FinalizationRegistry`	✓
ES2022	class fields, `#private` methods and fields, `static` blocks, `#x in obj`, top-level `await`, `.at()`, `Object.hasOwn`, error `cause`, regex `d` flag (match indices)	✓
ES2023	`toSorted` / `toReversed` / `toSpliced` / `with`, `findLast` / `findLastIndex`, hashbang `#!` lines, symbols as `WeakMap` keys	✓
ES2024	`Object.groupBy` / `Map.groupBy`, `Promise.withResolvers`, regex `v` flag, `isWellFormed` / `toWellFormed`, resizable `ArrayBuffer`, `ArrayBuffer.prototype.transfer`, `Atomics.waitAsync`	✓
ES2025	iterator helpers + `Iterator.from`, `Set` methods (`union`, `intersection`, …), `Promise.try`, `RegExp.escape`, regex pattern modifiers `(?i:…)`, duplicate named groups, import attributes + JSON modules, `Float16Array` / `Math.f16round`	✓
ES2026	`Array.fromAsync`, `Error.isError`, `JSON.parse` source text access (`JSON.rawJSON`), `Math.sumPrecise`, `Uint8Array` to/from base64 and hex, `Iterator.concat`, upsert (`Map.prototype.getOrInsert` / `getOrInsertComputed`)	partial: first three ✓; the rest ✗ (feature-detect)
Next: ES2027	finished but not yet published: **Temporal**, explicit resource management (`using`, `Symbol.dispose`), `Atomics.pause`, joint iteration (`Iterator.zip`)	`using` and `Atomics.pause` already work; Temporal and `Iterator.zip` don't

"Node 24 ✓" means Node's V8 ships the feature. For browsers, check MDN's compatibility tables or the Baseline badge before relying on anything from the last two editions. A transpiler can rewrite new *syntax*, but only a polyfill can add missing *APIs* (§10.12).

18.19 Where to go next

A four-step study path built on this book.

Step 1 — Lock in the core (1–2 weeks)

1. Re-read the TL;DR at the end of each chapter, then do each sheet in this chapter with the right-hand column covered.
2. Work through the ordering puzzles in §12.3 and the 53 questions in §17.4 until you can explain each answer out loud.
3. Rebuild from memory: `debounce`, `throttle`, `curry`, `memoize`, a `Promise.all` polyfill and an LRU cache (§17.3).

Step 2 — Build small, real things (2–4 weeks)

Pick projects that force you to combine chapters:

Project	Exercises
To-do list with filters, saved in `localStorage`	DOM, events, delegation, immutable array updates, storage (Ch 13, Ch 14)
Search-as-you-type against a public API	`fetch`, `AbortController`, debounce, last-request-wins, error states (Ch 12)
A command-line tool that summarizes a CSV or log file	`node:fs/promises`, streams, `parseArgs`, exit codes (Ch 15)
A tiny JSON REST API with tests	`node:http`, validation, `node:test`, TypeScript via type stripping (Ch 15, Ch 16)

Write tests for each one, run ESLint and Prettier, and put it in a git repository.

Step 3 — Choose a direction

Direction	Next topics	In this library
Front end	semantic HTML, CSS layout (flexbox, grid), accessibility, then React (components, state, effects, routing, data fetching)	HTML & CSS Handbook, React Handbook
Back end with Node	a framework (Express, Fastify or Hono), SQL and schema design, authentication, caching, queues	SQL Handbook, Database modeling
Types at scale	strict TypeScript, generics, declaration files, typing React components	§16.8, TypeScript with React
Interviews	DSA patterns in JS, machine-coding rounds, object-oriented and system design	Ch 17, LLD Handbook, DDIA notes

Step 4 — Keep up to date

- **MDN Web Docs** is the reference for every API in this book, with browser-compatibility tables.
- **The ECMAScript spec** (tc39.es/ecma262) and the TC39 proposals repository show what's coming; features at Stage 3 are usually safe to learn.
- **Node.js release notes and docs** (nodejs.org): use an even-numbered LTS line.
- **Books for depth**: *You Don't Know JS Yet* (scope, closures, `this`, types), *Eloquent JavaScript* (fundamentals with exercises), and javascript.info as a free, well-structured tutorial.
- Read other people's code: small, well-maintained npm packages are a good place to start.

18.20 Interview question index

- **53 tricky questions with real output** — §17.4: coercion and equality Q1–14 (§17.4.1) · scope, hoisting, closures Q15–22 (§17.4.2) · `this`, arrows, `call`/`apply`/`bind`, `new` Q23–28 (§17.4.3) · prototypes and classes Q29–34 (§17.4.4) · event loop and async Q35–42 (§17.4.5) · objects, arrays, copies Q43–50 (§17.4.6) · memory Q51–53 (§17.4.7).

- **Built-in complexity table** — §17.1; **21 coding patterns** with a summary table — §17.2; **implement-from-scratch classics** (debounce, throttle, curry, compose/pipe, memoize, flatten, `bind`, deep clone, deep equal, LRU, EventEmitter, promise polyfills) — §17.3.
- **300+ short say-it-out-loud answers**, output puzzles and coding tasks by topic — Chapter 19.

18.21 Glossary (A–Z)

Each term has a one-line definition and a link to the section that explains it. Symbols and backticks are ignored when sorting.

A

- **AbortController** — Object whose `signal` is passed to `fetch`, listeners or timers; calling `abort()` cancels them all. §12.11
- `AbortSignal.any` — Combines several signals into one that aborts as soon as any of them does, e.g. a user's cancel button plus a timeout. §12.11
- **AbortSignal.timeout** — Ready-made signal that aborts itself after a number of milliseconds with a `TimeoutError`. §12.11
- **Abstract class** — Class meant only to be extended, never created directly; JavaScript has no `abstract` keyword (a constructor can throw if `new.target` is the base class), while TypeScript adds one. §9.6
- **Abstract syntax tree (AST)** — Tree-shaped description of your code's structure that a parser builds before the engine compiles or runs it; linters and transpilers work on it too. §1.3
- **Accessor property** — Property backed by a getter and/or setter function instead of a stored value. §5.7
- **Accidental global** — Variable that becomes a property of the global object because it was assigned without `let`/`const`/`var` in sloppy mode; strict mode turns it into a `ReferenceError`. §17.4
- `addEventListener` — Registers a function to run when an event of a given type reaches an element; accepts `once`, `passive`, `capture` and `signal` options. §13.5
- **AggregateError** — Error that wraps several errors in its `errors` array; `Promise.any` rejects with one when every input rejects. §11.1
- **AMD / UMD** — Older module formats: AMD loads modules asynchronously with `define()`; UMD wraps a file so it works as AMD, CommonJS or a global. §10.1
- **Amortized cost** — Average cost per operation over a long run: `push` is O(1) amortized even though the array sometimes has to grow and copy. §17.1
- **Anchor (regex)** — Position rather than a character: `^` start, `$` end, `\b` word boundary. §6.7
- `any` **(TS)** — The TypeScript type that switches checking off for a value; anything goes in and out, so prefer `unknown`. §16.10
- **API** — Application Programming Interface: the set of functions, objects and rules one piece of software offers for others to use, such as the DOM API or a web server's HTTP endpoints. §1.4
- **Argument** — Actual value you pass when calling a function; the parameter is the name that receives it. §4.1
- `arguments` — Array-like object holding every argument passed to a non-arrow function; replaced in modern code by rest parameters. §4.4
- **Arrange–Act–Assert (AAA)** — Layout for a test: set up the data, perform the one action under test, then check the result. §16.3
- **Array destructuring** — Unpacking values by position: `const [a, , c = 0, ...rest] = arr`. §7.7
- **Array-like** — Object with `length` and numeric indexes but no array methods (e.g. `arguments`, a `NodeList`); convert with `Array.from`. §4.4
- `Array.from` — Builds a real array from an iterable or array-like, with an optional mapping function. §7.2
- `Array.fromAsync` — Collects an async iterable (or iterable of promises) into an array, returning a promise (ES2026). §12.12
- `Array.isArray` — Reliable array test; works across realms, unlike `instanceof Array`. §7.1

- **ArrayBuffer** — Fixed block of raw bytes that typed arrays and `DataView` read and write. §7.9
- **Arrow function** — Short function syntax `(x) => x * 2` with lexical `this`, no `arguments` and no `new`. §4.3
- **`as const` (TS)** — Tells TypeScript to treat a literal as deeply read-only with its exact values (`'admin'` rather than `string`). §16.13
- **ASCII** — Old 7-bit character set covering 128 characters (English letters, digits, punctuation); its codes are the first 128 Unicode code points. §6.9
- **Assertion** — Check in a test that fails loudly when a value isn't what you expected (`assert.equal`, `assert.throws`). §16.2
- **Assertion function (TS)** — A TypeScript function declared `asserts v is T` that narrows its argument for the code after the call. §16.11
- **Assignment operators** — `=` plus compound forms such as `+=`, `**=`, `||=`, `&&=` and `??=`. §2.8
- **Associativity** — Which side groups first when operators of equal precedence meet: `-` is left-to-right (`8 - 3 - 1` is 4), while `**` and `=` are right-to-left. §2.9
- **`async` function** — Function that always returns a promise and may use `await` inside. §12.9
- **Async generator** — `async function*` that yields values over time; consumed with `for await…of`. §12.12
- **Async iteration** — Walking a sequence whose items arrive asynchronously, using `Symbol.asyncIterator` and `for await…of`. §12.12
- **`async` script** — `<script async>` downloads in parallel and runs as soon as it arrives, in no guaranteed order; fine for independent scripts such as analytics. §13.12
- **Attribute (HTML)** — Text written in markup (`value="init"`); read with `getAttribute`. Often the initial value only. §13.4
- **Auto-boxing** — Engine briefly wraps a primitive in its object wrapper so that `'abc'.toUpperCase()` works. §6.4
- **Automatic Semicolon Insertion (ASI)** — Parser's rule for adding missing semicolons; it is why a line break straight after `return` returns `undefined`. §1.6
- **`await`** — Pauses an async function until a promise settles; gives the value or throws the rejection reason. §12.9

B

- **Babel** — Transpiler that rewrites modern JavaScript (and JSX/TypeScript) into syntax older engines understand. §10.12
- **Backpressure** — Stream's signal that the consumer is slower than the producer; `write()` returns `false` until `'drain'`. §15.9
- **Backreference** — `\1` or `\k<name>` in a regex: match the same text a group matched earlier. §6.7
- **Backtracking** — Building a solution step by step and undoing the last choice when it leads to a dead end; used to list subsets, permutations and N-Queens boards. §17.2
- **Bare specifier** — Import name without a path, such as `'lodash'`; Node finds it in `node_modules`, a browser needs an import map. §10.7
- **Barrel file** — Module that only re-exports other modules (`export * from './a.mjs'`) to offer one import path. §10.2
- **Base case** — Condition that stops a recursive function from calling itself again. §4.10
- **Base64** — Way to write arbitrary bytes using only 64 safe text characters (A–Z, a–z, 0–9, `+`, `/`), so binary data can travel inside text such as JSON or URLs. §15.7
- **Baseline** — Label on MDN and web.dev saying a web feature works in all major current browsers ("newly" or "widely" available). §18.18
- **Basic Multilingual Plane (BMP)** — First 65,536 Unicode code points; characters outside it, like most emoji, need two UTF-16 code units (a surrogate pair). §6.5
- **BigInt** — Primitive for integers of any size, written `10n`; can't be mixed with `number` in arithmetic. §2.10
- **Big-O notation** — Way to describe how running time or memory grows with input size `n`, ignoring constants: O(1) constant, O(log n), O(n) linear, O(n log n), O(n²). §17.1
- **Binary search** — Finding a target in sorted data by repeatedly checking the middle and discarding half, taking O(log n) steps. §17.2

- **Binary search tree (BST)** — Binary tree where every left descendant is smaller and every right descendant larger than the node, so an in-order walk is sorted. §17.2
- **Binary tree** — Tree in which each node has at most two children, `left` and `right`. §17.2
- `bind` — Returns a new function with `this` (and optionally leading arguments) fixed permanently. §9.2
- **Binding** — Link between a name and the storage it refers to; `let` in a `for` loop creates a fresh binding each iteration. §4.7
- **Bitwise operators** — `& | ^ ~ << >> >>>`: operate on the 32-bit integer form of numbers. §2.8
- **Block** — Statements grouped in `{ }`, as in an `if` body or loop body; `let` and `const` are scoped to it. §1.6
- **Block scope** — Visibility limited to the nearest `{ }`; applies to `let`, `const` and `class`. §4.5
- **Blocking** — Code that keeps the single JavaScript thread busy (a long loop, synchronous file read), so nothing else, not even clicks or other requests, can run meanwhile. §12.1
- **Bound function** — New function returned by `bind`, with `this` (and optionally some arguments) fixed permanently. §9.2
- **Brand check** — Testing whether an object was really made by a class by checking for one of its private fields: `#secret in obj`. §9.7
- **Breadth-first search (BFS)** — Exploring a graph or grid level by level using a queue; finds the fewest-steps path when all steps cost the same. §17.2
- **Breakpoint** — Marker in DevTools or an editor that pauses execution at a line so you can inspect variables; can be conditional. §11.9
- **browserslist** — Shared config listing which browsers a project supports; Babel, autoprefixer and other tools read it to decide what to transform. §10.12
- **Bubbling** — Phase in which an event travels from the target back up through its ancestors. §13.6
- **Buffer** — Node's type for raw bytes; its length is in bytes, not characters. §15.7
- **Built-in objects** — Objects the language provides everywhere, such as `Object`, `Array`, `Math`, `JSON`, `Date`, `Map` and `Promise`. §5.9
- **Bun** — A JavaScript runtime built on JavaScriptCore with its own package manager, bundler and test runner. §15.12
- **Bundler** — Tool that follows imports and produces optimized files for the browser (Vite, esbuild, webpack, Rollup). §10.11
- **Busy-waiting** — Burning CPU in a loop until a condition changes, instead of waiting for an event or timer; it freezes the page in JavaScript. §3.7
- **Bytecode** — Compact, low-level instruction format an engine's interpreter runs; V8's Ignition turns your parsed code into it. §1.3

C

- **Cache API** — Browser store of request/response pairs, used mostly by service workers for offline support. §14.4
- `call` / `apply` — Invoke a function right now with a chosen `this`; `call` takes listed arguments, `apply` an array. §9.2
- **Call site** — Place in the code where a function is called; for regular functions it decides what `this` is. §9.1
- **Call stack** — Stack of function calls currently running; the newest frame is on top. §12.2
- **Callback** — Function passed to another function to be called later or for each item. §4.8
- **Callback hell** — Deeply nested callbacks where each step depends on the previous one; hard to read and to handle errors. §12.6
- **camelCase** — Naming style where the first word is lower-case and later words start with a capital (`totalPrice`); the JavaScript convention for variables and functions. §2.1
- **Cancelable event** — Event whose default action `preventDefault()` can stop; `event.cancelable` tells you. §13.8
- **Capture phase** — First event phase, travelling from `window` down to the target; listen with `{ capture: true }`. §13.6

- **Capturing group** — `( … )` in a regex: groups a sub-pattern and remembers its match as `$1`, `m[1]`. §6.7
- **Caret range (`^`)** — Npm version range allowing newer minor and patch releases of the same major (`^1.2.3` means at least 1.2.3, below 2.0.0). §10.10
- **`cause` (error)** — Option `new Error(msg, { cause })` that links an error to the one that caused it (ES2022). §11.4
- **Character class** — `[abc]`, `[a-z]` or shorthands like `\d`: matches one character from a set. §6.7
- **Child process** — Another OS program started from Node with `node:child_process` (`execFile`, `spawn`, `fork`). §15.11
- **Chunk** — One piece of data delivered by a stream (often a `Buffer` of up to 64 KB); also a separate file a bundler emits for code splitting. §15.9
- **CI (continuous integration)** — Server that automatically installs, lints, tests and builds every change pushed to a repository. §10.10
- **Circular dependency** — Two or more modules that import each other; ES modules allow it, but one side may see the other's bindings before they are initialised. §10.3
- **Class** — Syntax for a constructor plus prototype methods, with fields, `#private` members, statics and `extends`. §9.5
- **Class field** — Property declared in the class body (`count = 0`) and created on each instance (ES2022). §9.5
- **Classic script** — Normal `<script>` without `type="module"`: sloppy by default, top-level `var` becomes a global, and it blocks HTML parsing unless `defer` or `async` is set. §1.8
- **`classList`** — Element's list of CSS classes with `add`, `remove`, `toggle` and `contains`. §13.4
- **CLI** — Command-line interface: a program you run by typing commands in a terminal, such as `node`, `npm` or `tsc`. §10.9
- **Clickjacking** — Tricking a user into clicking something on your site hidden inside an invisible frame on another site; blocked with CSP `frame-ancestors`. §14.12
- **`closest`** — Returns the element itself or its nearest ancestor that matches a CSS selector, or `null`; the workhorse of event delegation. §13.2
- **Closure** — Function together with the variables of the scope where it was created, which it can still read and change. §4.7
- **Code point** — A Unicode character number (U+0000 to U+10FFFF); some need two UTF-16 code units. §6.5
- **Code splitting** — Breaking a bundle into chunks that load on demand, usually at each dynamic `import()`. §10.11
- **Code unit** — One 16-bit value of UTF-16; `length` and indexes count these. §6.5
- **Coercion** — Automatic type conversion done by operators such as `+`, `==` and `if`. §2.12
- **Combinator (promise)** — Function that turns several promises into one: `Promise.all`, `allSettled`, `race` and `any`. §12.8
- **Command injection** — Attack where user input passed to a shell is run as extra commands; avoided by `execFile`/`spawn` with an argument array. §15.11
- **CommonJS** — Node's original module system: `require()` and `module.exports`, loaded synchronously. §10.8
- **Comparator** — Function passed to `sort`: negative keeps `a` first, positive puts `b` first, 0 keeps their order. §7.6
- **Compile** — Translating source code into another form, such as machine code or bytecode, before it runs; JavaScript engines do this on the fly. §1.3
- **Composition** — Building behaviour by combining objects or functions (has-a) instead of inheriting (is-a). §9.9
- **Compound assignment** — Operator that combines an operation with assignment: `x += 1` means `x = x + 1`. §2.8
- **Computed property name** — Object key written as an expression in brackets: `{ [key]: value }`. §5.2
- **Concatenation** — Joining strings end to end, with `+`, `concat` or a template literal. §6.3
- **Concurrency limit** — Running many async jobs but only N at a time, so you don't flood a server or run out of file handles. §12.13

- **Conditional breakpoint** — Breakpoint that pauses only when an expression you give is truthy (e.g. `i === 500`). §11.9
- **Conditional statement** — Code that chooses what to run based on a condition: `if`, `else if`, `else` and `switch`. §3.1
- **Conditional types (TS)** — Types that pick one of two results based on a test, written `T extends U ? X : Y`. §16.12
- `const` — Declares a block-scoped binding that can't be reassigned (the value may still be mutated). §2.1
- **Constraint Validation API** — Built-in form validation from HTML attributes (`required`, `min`, `pattern`), read via `input.validity` and customised with `setCustomValidity`. §13.9
- **Constructor** — Function that sets up a new object: the `constructor` method of a class, or a function called with `new`. §9.5
- **Constructor function** — Regular function called with `new` to create objects; the pre-class way to make "types". §9.4
- **Content Security Policy (CSP)** — Response header that tells the browser which sources of scripts, styles and frames are allowed. §14.12
- **Content-Type / MIME type** — Header naming the format of a body, such as `application/json` or `text/html`; MIME types are those standard format names. §14.1
- **Cookie** — Small string the server sets and the browser sends back automatically with matching requests. §14.4
- **core-js** — Widely used library of polyfills for modern JavaScript built-ins. §10.12
- **CORS** — Cross-Origin Resource Sharing: headers by which a server allows pages from other origins to read its responses. §14.2
- **Coverage** — Share of code lines or branches your tests executed; a hint, not a goal. §16.6
- **CPU-bound / I/O-bound** — CPU-bound work is limited by computation (hashing, image resizing); I/O-bound work mostly waits for disks or networks. Node is great at the second, needs workers for the first. §15.2
- **CSRF** — Cross-site request forgery: another site makes the victim's browser send an authenticated request. §14.11
- **CSRF token** — Secret, unpredictable value the server puts in a form and checks on submit, proving the request came from its own page. §14.11
- **CSS** — Cascading Style Sheets: the language that controls how HTML looks (colours, layout, fonts). §1.1
- `currentTarget` — Element whose listener is running now, as opposed to `target`, where the event started. §13.5
- **Currying** — Turning `f(a, b, c)` into `f(a)(b)(c)` so arguments can be supplied one at a time. §4.8
- **CustomEvent** — Event you create with your own `detail` data and fire with `dispatchEvent`. §13.5

D

- `dataset` — Access to `data-*` attributes as camelCase string properties (`data-user-id` → `dataset.userId`). §13.4
- `Date` — Built-in object holding milliseconds since 1970-01-01 UTC, with local and UTC getters. §5.11
- **Daylight-saving time (DST)** — Seasonal clock changes that make some local days 23 or 25 hours long; a reason to store and compute dates in UTC. §5.11
- **Debounce** — Run a function only after calls have stopped for a given time (e.g. search-as-you-type). §17.3
- `debugger` — Statement that pauses execution when developer tools are attached. §11.9
- **Declaration** — Code that introduces a name: `let x`, `const y = 1`, `function f() {}` or `class C {}`. §2.1
- **Declarative code** — Code that says what result you want (`items.filter(isActive)`) rather than spelling out each step in a loop (imperative code). §7.5
- **Deep copy** — Copy in which nested objects are copied too, e.g. `structuredClone(obj)`. §5.4
- **Default action** — What the browser does on its own after an event, such as following a link or submitting a form; stopped with `preventDefault()`. §13.8

- **Default binding** — `this` rule for a plain call `f()`: `undefined` in strict code, the global object in sloppy scripts. §9.1
- **Default export** — Single unnamed export of a module, imported under any name: `import x from './m.mjs'`. §10.2
- **Default parameter** — Value used when an argument is missing or `undefined`: `function f(n = 1)`. §4.4
- **Defence in depth** — Using several independent protections (escaping, CSP, `HttpOnly` cookies) so one failure doesn't expose you. §14.10
- `defer` — Script attribute: download in parallel, run after the HTML is parsed, in document order. §13.12
- `delete` — Operator that removes an own property from an object. §5.2
- **Deno** — A V8-based runtime with deny-by-default permissions, built-in TypeScript and tooling. §15.12
- **Deoptimization** — When the optimizing compiler's assumptions about your code (e.g. "this is always a number") turn out wrong, so the engine throws away the fast machine code and goes back to slower code. §1.3
- **Dependency** — Package your project uses, listed in `package.json`; transitive dependencies are the packages your dependencies use in turn. §10.9
- **Dependency injection** — Passing collaborators (clock, database, HTTP client) in as arguments so tests can swap them for fakes. §16.5
- **Depth-first search (DFS)** — Exploring a graph or tree by going as deep as possible down one path before backing up, using recursion or a stack. §17.2
- **Destructuring** — Syntax that unpacks properties or elements into variables, with renames and defaults. §5.5
- `devDependencies` — Packages needed only to build and test (linters, bundlers), not at runtime. §10.9
- **DevTools** — Developer tools built into browsers (F12): console, element inspector, debugger, network and performance panels. §1.5
- **Dijkstra's algorithm** — Finds the cheapest path from one node to all others in a graph with non-negative edge weights, using a priority queue. §17.2
- **Directive** — String statement that changes how code is treated, such as `"use strict"` at the top of a script or function. §1.8
- **Discriminated union** — A TypeScript union whose members share a literal "kind" property used to narrow between them. §16.11
- `dispatchEvent` — Fires an event object at a node; its listeners run synchronously. §13.5
- **Document** — Root object of the DOM for one page (`document`); everything you select or create starts from it. §13.1
- **DocumentFragment** — Lightweight container for building many nodes off-page before inserting them at once. §13.3
- **DOM** — Document Object Model: the live tree of objects the browser builds from HTML and exposes to scripts. §13.1
- **DOM-based XSS** — XSS that happens entirely in the browser when script copies attacker-controlled data (often from the URL) into a dangerous sink like `innerHTML`. §14.10
- `DOMContentLoaded` — Event fired when the HTML is parsed and deferred scripts have run; images may still be loading. §13.12
- **DOMPurify** — Widely used library that sanitizes untrusted HTML before it goes into `innerHTML`. §14.10
- **dotAll flag** — Regex `s` flag: lets `.` match newline characters too. §6.7
- **Dual package hazard** — When both the CommonJS and ESM builds of one package get loaded, so the app ends up with two separate copies of its state. §10.8
- **Duck typing** — Checking whether a value has the methods you need rather than which class made it. §9.7
- **Dummy (test double)** — Placeholder argument a test passes only to fill a parameter; it is never actually used. §16.5
- **Duplex stream** — Stream that is both readable and writable, like a network socket. §15.9
- **Dutch national flag partition** — Sorting an array of three kinds of value (e.g. 0, 1, 2) in one pass with three pointers. §17.2

- **Dynamic import** — `import(specifier)`: loads a module at runtime and returns a promise for its namespace. §10.4
- **Dynamic programming (DP)** — Solving a problem by combining answers to overlapping smaller subproblems, storing each so it is computed once (memo top-down or table bottom-up). §17.2
- **Dynamic typing** — Types belong to values, not variables; a variable may hold a number and later a string. §1.1

E

- **Ecma International** — Standards organisation that publishes ECMAScript (as ECMA-262); its TC39 committee designs the language. §1.2
- **ECMAScript** — Official language standard (ECMA-262) that JavaScript engines implement; a new edition every June. §1.2
- **Electron** — Framework for desktop apps (VS Code, Slack) built from Chromium plus Node.js, written in HTML, CSS and JavaScript. §1.4
- **Element** — A DOM node that represents an HTML tag, such as `<li>` or `<button>`; it has attributes, children and methods like `querySelector`. §13.1
- **Encapsulation** — Hiding internal state so outside code can only use a public interface; achieved with closures, `#private` fields or module scope. §4.7
- **Encoding** — Rule that turns text into bytes and back; UTF-8 is the usual one (`'é'` is 2 bytes in UTF-8). §15.7
- **Endianness** — Byte order of multi-byte numbers in memory: little-endian stores the least significant byte first; `DataView` lets you choose. §7.9
- **End-to-end (E2E) test** — Test that drives the whole application through its real interface, often a browser. §16.1
- **Engine** — Program that parses, compiles and runs JavaScript: V8, SpiderMonkey, JavaScriptCore. §1.3
- **`ENOENT`** — Node's error code for "no such file or directory"; check `err.code` rather than the message. §15.4
- **Entry point** — First module or file that starts an app (or that a bundler starts from) and from which all imports are followed. §10.3
- **Enum (TS)** — A TypeScript construct that creates a named set of constants as a real runtime object; not erasable, so plain unions or `as const` objects are often preferred. §16.13
- **Enumerable** — Property attribute; enumerable properties appear in `for…in`, `Object.keys` and spread. §5.6
- **Environment variable** — Named string setting given to a process by the OS or shell (e.g. `PORT=3000`), read in Node with `process.env`. §15.6
- **Erasable syntax (TS)** — TypeScript syntax that disappears when types are deleted (annotations, interfaces); `enum` and parameter properties are not erasable because they generate code. §16.9
- **Error-first callback** — Node's callback convention `(err, result) => …`, where `err` is checked first. §12.6
- **`Error.isError`** — Reliable check that a value is a genuine error object, even across realms (ES2026). §9.7
- **ES module (ESM)** — Standard module system: static `import` / `export`, strict mode, live bindings. §10.2
- **esbuild** — Very fast bundler and transpiler written in Go. §10.11
- **Escape sequence** — Backslash code inside a string literal for a character that is hard to type: `\n` newline, `\t` tab, `\'`, `\u{1F600}`. §6.2
- **ESLint** — Configurable linter that reports likely bugs and style problems in JavaScript and TypeScript. §10.13
- **Event** — Object describing something that happened (click, key press, load) delivered to listeners. §13.5
- **Event delegation** — One listener on a container handles events from many children using `event.target.closest()`. §13.7
- **Event listener** — Function registered for an event type on a target; the browser calls it with an event object when that event happens. §13.5

- **Event loop** — Host scheduler that runs one task, then all microtasks, then possibly a render, repeatedly. §12.2
- **Event object** — Object passed to a listener, describing what happened: `type`, `target`, `currentTarget`, key or mouse details, and methods like `preventDefault`. §13.5
- **EventEmitter** — Node's publish/subscribe class: `on`, `once`, `off` and synchronous `emit`. §15.8
- **Exception** — Error that has been thrown and interrupts normal flow until a `catch` handles it; uncaught, it ends the script or process. §11.1
- **Excess property check (TS)** — TypeScript's error when an object literal has a property its target type doesn't declare, usually a typo. §16.10
- **Execution context** — Engine's record for a running piece of code (its variables, scope chain and `this`); each call pushes one onto the call stack. §4.1
- **Executor** — Function passed to `new Promise((resolve, reject) => …)`; it runs immediately and synchronously. §12.7
- **Exit code** — Number a process returns to the OS when it ends: 0 for success, anything else for failure; set with `process.exitCode`. §15.6
- **Explicit binding** — Setting `this` yourself with `call`, `apply` or `bind`. §9.1
- **Explicit resource management** — `using` / `await using` declarations plus `Symbol.dispose`, which clean up a resource automatically when its block ends (ES2027). §11.6
- **Exponential backoff** — Retrying a failed request with waits that double each time (100 ms, 200 ms, 400 ms …), usually plus random jitter. §12.13
- **Exponentiation operator** — `**`: raises to a power (`2 ** 10` is 1024). §2.5
- `export` — Makes a binding available to other modules, by name or as the default. §10.2
- **Express** — Most widely used Node.js web framework, adding routing and middleware on top of `node:http`. §15.10
- **Expression** — Code that produces a value (`2 + 3`, `f(x)`, `a ? b : c`). §1.6
- `extends` — Makes one class inherit from another (or from a built-in such as `Error`), linking their prototype chains. §9.6

F

- **Factory function** — Plain function that builds and returns a new object, an alternative to classes and `new`. §9.9
- **Fake (test double)** — Working but simplified stand-in, such as an in-memory database used in place of a real one. §16.5
- **Fake timers** — Test tool that replaces `setTimeout`/`Date` so you can move time forward instantly. §16.5
- **Fall-through** — In a `switch`, running on into the next `case` because a `break` (or `return`) is missing. §3.4
- **Falsy** — Value that becomes `false` in a boolean context: `false`, `0`, `-0`, `0n`, `''`, `null`, `undefined`, `NaN`. §2.11
- **Fast and slow pointers** — Two pointers moving through a list at different speeds; they meet if there is a cycle, and the slow one finds the middle. §17.2
- **Fastify / Hono / Koa** — Alternative Node.js web frameworks to Express: Fastify focuses on speed, Hono is tiny and runs on many runtimes, Koa is a minimal async-first design. §15.10
- **Feature detection** — Checking whether an API exists before using it (`if ('Temporal' in globalThis)`), instead of guessing from the browser name. §1.4
- `fetch` — Promise-based HTTP API in browsers and Node; resolves even for 4xx/5xx responses. §14.1
- **FinalizationRegistry** — Lets you ask for a callback some time after an object has been garbage-collected; timing is never guaranteed. §8.3
- `finally` — Block that runs after `try`/`catch` whatever happened, for cleanup. §11.2
- **First-class function** — Functions are values: stored in variables, passed as arguments and returned from other functions. §4.1
- **Fisher–Yates shuffle** — Correct way to shuffle an array fairly: walk from the end, swapping each item with a random earlier one (or itself). §7.6
- `flat` / `flatMap` — Flatten nested arrays by a depth / map then flatten one level. §7.5

- **Floating point** — Way computers store fractional numbers in binary with limited precision, which is why `0.1 + 0.2` isn't exactly `0.3`. §2.10
- **`for await…of`** — Loops over an async iterable, awaiting each value. §12.12
- **Forced synchronous layout** — When reading a layout value (like `offsetHeight`) after a style change makes the browser recalculate layout immediately; repeated, it causes layout thrashing. §13.11
- **`for…in`** — Loops over enumerable property names (strings), including inherited ones. §3.9
- **Formatter** — Tool that rewrites code to a consistent style (spacing, quotes, line breaks) without changing behaviour; Prettier is the common one. §10.13
- **`for…of`** — Loops over the values of any iterable (arrays, strings, Maps, Sets, generators). §3.10
- **FormData** — Object holding a form's field names and values; can be sent directly with `fetch`. §13.9
- **Framework** — Larger toolkit that shapes how a whole app is structured and calls your code (React, Angular, Express); a library is something your code calls. Ch 1
- **Fulfilled** — State of a promise that finished successfully with a value. §12.7
- **Function** — Reusable, named (or anonymous) block of code that takes inputs (parameters), runs, and may return a value; in JavaScript it is also an object. §4.1
- **Function composition** — Combining functions so the output of one feeds the next: `compose(f, g)(x)` is `f(g(x))`; `pipe` runs left to right. §4.8
- **Function declaration** — `function name() {}` as a statement; hoisted with its body. §4.2
- **Function expression** — Function used as a value (`const f = function () {}`); follows its variable's hoisting. §4.2
- **Function scope** — Scope created by each function call; `var` declarations and parameters live here. §4.5

G

- **Garbage collection** — Automatic freeing of memory for objects no longer reachable from roots such as globals and the stack. §17.4.7
- **Generational garbage collection** — Collecting young objects often and old ones rarely, because most objects die young; V8 works this way. §17.4
- **Generator** — `function*` that can pause at `yield`; calling it returns an iterator. §8.5
- **Generics (TS)** — Type parameters such as `<T>` that let one function or type work for many types safely. §16.12
- **`getComputedStyle`** — Returns the final CSS values the browser applied to an element after all stylesheets and inline styles. §13.4
- **Getter** — `get` method that runs when a property is read. §5.7
- **Global object** — Object that holds the host's global variables (`window` in browsers, `global` in Node), always reachable as `globalThis`. §1.4
- **Global scope** — Outermost scope, visible to all code; names declared there can clash across scripts. §4.5
- **`globalThis`** — Standard name for the global object in every environment (ES2020). §1.4
- **Graceful shutdown** — Stopping a server cleanly on a signal like `SIGTERM`: stop accepting new work, finish what's in flight, close connections, then exit. §15.10
- **Gradual typing** — Adding static types to a codebase a little at a time; typed and untyped code coexist (TypeScript, JSDoc checking). §16.8
- **Graph** — Set of nodes connected by edges, possibly directed or weighted; maps, dependency lists and social networks are graphs. §17.2
- **Grapheme cluster** — What a reader sees as one character, possibly several code points (flags, family emoji). §6.5
- **Greedy algorithm** — Making the best-looking local choice at each step, which is correct only when you can prove those choices never hurt the final answer. §17.2
- **Greedy quantifier** — Regex repetition that matches as much as possible; add `?` to make it lazy. §6.7
- **`groupBy`** — `Object.groupBy` / `Map.groupBy` put items into buckets by a key function (ES2024). §8.7
- **Guard clause** — Early `return` (or `throw`) at the top of a function for invalid or special cases, so the main logic needn't be nested. §3.2

H

- **Hash map** — Structure that maps keys to values with average O(1) lookup by hashing the key; in JavaScript use `Map` or a plain object. §17.1
- **Hashbang** — `#!/usr/bin/env node` first line that tells Unix shells which program runs the file; allowed by JavaScript since ES2023. §18.18
- `hasOwn` — `Object.hasOwn(obj, key)`: is this an own (not inherited) property? (ES2022) §5.2
- **Heap (data structure)** — Tree kept in an array so the smallest (min-heap) or largest (max-heap) item is always on top; push and pop are O(log n). §17.2
- **Heap (memory)** — Area of memory where objects live until the garbage collector frees them. §17.4
- **Higher-order function** — Function that takes or returns another function. §4.8
- **History API** — `pushState`, `replaceState` and `popstate` for changing the URL without reloading the page. §14.7
- **HMR** — Hot Module Replacement: a dev server swaps changed modules into the running page without a full reload. §10.11
- **Hoisting** — Declarations are registered before code runs: functions fully, `var` as `undefined`, `let`/`const`/`class` in the TDZ. §4.6
- **Hooks (testing)** — `before`, `beforeEach`, `afterEach` and `after`: functions a test runner calls around tests for setup and cleanup. §16.3
- **Host** — Environment around the engine that supplies extra APIs: a browser, Node.js, Deno, Bun. §1.4
- **HSTS** — HTTP Strict Transport Security: a response header telling the browser to use only HTTPS for this site from now on. §14.12
- **HTML** — HyperText Markup Language: the tag-based language that describes a web page's structure and content. §1.1
- **HTML Sanitizer API** — Newer browser API that cleans untrusted HTML of scripts and dangerous attributes, the built-in counterpart to DOMPurify. §14.10
- **HTTP** — HyperText Transfer Protocol: the request/response rules browsers and servers use to exchange data; HTTPS is HTTP encrypted with TLS. §14.1
- **HTTP header** — `Name: value` line of metadata on a request or response, such as `Content-Type`, `Authorization` or `Set-Cookie`. §14.1
- **HTTP method** — Verb of a request: `GET` reads, `POST` creates, `PUT`/`PATCH` update, `DELETE` removes, `OPTIONS` asks what is allowed. §14.1
- **HTTP status code** — Three-digit number in a response: 2xx success, 3xx redirect, 4xx client error (404 not found), 5xx server error. §14.1
- `HttpOnly` — Cookie attribute that hides the cookie from JavaScript, protecting sessions from XSS theft. §14.4
- **HTTPS** — HTTP over an encrypted TLS connection, so nobody in between can read or change the traffic; required for `Secure` cookies. §14.12

I

- **Idempotent** — Operation that has the same effect whether it runs once or several times (e.g. "set status to paid"); only these are safe to retry blindly. §12.13
- **Identifier** — Name you give to a variable, function, class or parameter; letters, digits, `_` and `$`, not starting with a digit. §1.6
- **IEEE 754** — The 64-bit floating-point format behind every JavaScript `number`. §2.10
- **Ignition / Sparkplug / Maglev / TurboFan** — V8's tiers: Ignition interprets bytecode, Sparkplug and Maglev compile it quickly to machine code, TurboFan produces the most optimized code for hot functions. §1.3
- **IIFE** — Immediately Invoked Function Expression `(() => { … })()`: an old way to get a private scope. §4.9
- **Immutability** — Not changing data in place; producing new values instead (important in React and Redux). §7.4
- **Imperative code** — Code that spells out each step (counters, loops, pushes) to reach a result; contrast with declarative code. §7.5
- **Implicit binding** — `this` rule for `obj.method()`: `this` is the object before the dot. §9.1

- **Implicit return** — Arrow function with an expression body returns that expression without `return`. §4.3
- `import` — Brings exported bindings from another module into this one. §10.2
- **Import attributes** — `with { type: 'json' }` on an import, telling the host how to load the module (ES2025). §10.6
- **Import map** — Browser `<script type="importmap">` that maps bare specifiers like `'lodash'` to URLs. §10.7
- `import.meta` — Per-module metadata such as `url`, `dirname`, `filename` and `resolve()`. §10.6
- **Impure function** — Function that has side effects or depends on outside state, so the same input may give a different result. §4.11
- **In-degree** — Number of edges pointing into a node of a directed graph; Kahn's topological sort starts from nodes with in-degree 0. §17.2
- **IndexedDB** — Browser's asynchronous, transactional database for large structured data. §14.4
- **Infinite loop** — Loop whose condition never becomes false, so it runs forever and freezes the page or process. §3.7
- `Infinity` — Special number bigger than any other, produced by `1 / 0` or overflow; `-Infinity` is its negative. §2.10
- **Inheritance** — One class extending another (`extends`) and reusing its behaviour through the prototype chain. §9.6
- **Inline style** — CSS set directly on one element via its `style` attribute or `el.style.x`; overrides most stylesheet rules. §13.4
- `innerHTML` — Gets or sets an element's children as an HTML string; setting it parses markup (XSS risk). §13.3
- **Inspector** — Debugging interface of an engine; `node --inspect` opens it so Chrome DevTools can attach to Node. §11.9
- `instanceof` — Tests whether `C.prototype` appears in an object's prototype chain. §9.7
- **Integer** — Whole number with no fractional part; JavaScript numbers hold integers exactly only up to $2^{53} - 1$. §2.10
- **Integration test** — Test that runs several real components together, such as a handler and a database. §16.1
- **Interface (TS)** — Named object type in TypeScript; can be extended and merged. §16.10
- **Interpolation** — Inserting values into a string, as with `${expr}` in a template literal. §6.3
- **Interpreter** — Program that runs code instruction by instruction without first compiling all of it to machine code; engines start this way and compile hot code later. §1.3
- **Intersection type (TS)** — `A & B`: a value that has all the properties of both types. §16.10
- **IntersectionObserver** — Reports when an element enters or leaves the viewport; used for lazy loading and infinite scroll. §14.9
- `Intl` — Internationalization namespace: `DateTimeFormat`, `NumberFormat`, `Collator`, `Segmenter` and more. §5.11
- `Intl.NumberFormat` — Formats numbers for people in a given locale, including currency and percentages (`€1,234.50`). §2.10
- **Invalid Date** — `Date` whose time value is `NaN` because parsing failed; `isNaN(d)` or `Number.isNaN(d.getTime())` detects it. §5.11
- **Inversion of control** — Handing your callback to someone else's code and trusting it to call it once, at the right time; promises reduce that trust problem. §12.6
- **ISO 8601** — International date-time text format `YYYY-MM-DDTHH:mm:ss.sssZ`; the safe format to send and parse. §5.11
- **Iterable** — Object with a `[Symbol.iterator]()` method, usable in `for…of` and spread. §8.4
- **Iterator** — Object with a `next()` method returning `{ value, done }`. §8.4
- **Iterator helpers** — Lazy `map`, `filter`, `take`, `drop`, `flatMap` and consuming `toArray`, `reduce` on iterators (ES2025). §8.6

J

- **JavaScriptCore** — Apple's JavaScript engine, used by Safari and Bun. §1.3

- **Jest** — Popular all-in-one JavaScript test runner with `expect` assertions, mocking and snapshots. §16.7
- **JIT compilation** — Just-in-time compilation: the engine compiles frequently run code to machine code while the program runs. §1.3
- **Jitter** — Random extra delay added to retries so many clients don't all retry at the same instant. §12.13
- **JSDoc** — Structured comments (`/** @param {number} x */`) that document code and can drive TypeScript checking. §16.15
- **jsdom** — A JavaScript implementation of the DOM that runs in Node, used to test browser code without a browser. §13.3
- **JSON** — Text data format with double-quoted keys and strings, numbers, booleans, `null`, arrays and objects. §5.12
- **JSON module** — `.json` file imported directly with `with { type: 'json' }` (ES2025). §10.6
- `JSON.parse` — Turns JSON text into values; strict syntax; an optional reviver transforms values. §5.12
- `JSON.stringify` — Turns values into JSON text; drops functions and `undefined` in objects, throws on BigInt and cycles. §5.12
- **JSX** — HTML-like syntax inside JavaScript used by React (`<Button />`); a build tool compiles it into function calls. §10.11
- **JWT** — JSON Web Token: a signed, Base64-encoded JSON token often used to prove who a user is; its timestamps are in seconds, not milliseconds. §5.11

K

- **Kahn's algorithm** — Topological sort by repeatedly taking nodes with no remaining incoming edges (in-degree 0) from a queue. §17.2

L

- **Label** — Name before a loop (`outer:`) that `break outer` / `continue outer` can target. §3.11
- `lastIndex` — Position where a `g` or `y` regex will start its next search; it makes repeated `test` calls stateful. §6.8
- **Last-request-wins** — Ignoring or cancelling responses from older requests so only the latest one updates the UI (e.g. in search-as-you-type). §12.13
- **Layout thrashing** — Alternating DOM writes and layout reads so the browser recalculates layout again and again. §13.11
- **Lazy evaluation** — Computing values only when they're requested, as generators and iterator helpers do. §8.5
- **Lazy quantifier** — Regex repetition with a trailing `?` (`.+?`) that matches as little as possible. §6.7
- `let` — Declares a block-scoped variable that can be reassigned. §2.1
- **Lexical scope** — Scope decided by where code is written, not where it's called from. §4.5
- **Lexical `this`** — Arrow function's `this` is the `this` of the surrounding code. §4.3
- **Library** — Reusable code you call from your own program, such as Lodash or date-fns; contrast with a framework, which calls your code. §1.1
- **libuv** — The C library that gives Node its event loop, async I/O and thread pool. §15.1
- **Linked list** — Chain of nodes where each holds a value and a reference (`next`) to the following node; O(1) insert at a known spot, O(n) lookup. §17.2
- **Linter** — Tool that analyses source code for bugs and style problems without running it (ESLint). §10.13
- **Literal** — Value written directly in code: `42`, `'hi'`, `true`, `[1, 2]`, `{ a: 1 }`, `/re/`. §1.6
- **Literal type (TS)** — Type that allows only one exact value, such as `'admin'` or `42`; unions of them make safe string options. §16.10
- **Live binding** — An ES module import stays connected to the exporter's variable and sees updates. §10.3

- **Live collection** — A DOM collection (`getElementsByTagName`) that updates automatically when the document changes. §13.2
- **`load` event** — Fires when the page and all its images, stylesheets and frames have finished loading, after `DOMContentLoaded`. §13.12
- **Local time** — Date and time in the user's own time zone, as `getHours()` and `toString()` show it; contrast with UTC. §5.11
- **`localeCompare`** — Compares two strings by a language's alphabet rules, returning a negative, zero or positive number; use it to sort text. §6.6
- **Localhost (`127.0.0.1`)** — Address that always means "this same computer"; servers bound to it can't be reached from other machines. §15.10
- **`localStorage`** — Per-origin string key-value storage that survives reloads; synchronous, about 5 MB. §14.3
- **Lockfile** — `package-lock.json`: records the exact installed version of every dependency. §10.10
- **Logical assignment** — `a ||= b`, `a &&= b`, `a ??= b`: assign only when the condition holds (ES2021). §2.7
- **Logpoint** — Breakpoint that logs a message instead of pausing, so you can add logging without editing code. §11.9
- **Lone surrogate** — Half of a surrogate pair with no partner, which makes a string not well-formed; `isWellFormed` detects it. §6.5
- **Lookahead / lookbehind** — Regex assertions `(?=…)`, `(?!…)`, `(?<=…)`, `(?<!…)` that check surrounding text without consuming it. §6.7
- **LRU cache** — Fixed-size cache that throws out the Least Recently Used entry when full; a `Map` (which keeps insertion order) can implement it. §17.3
- **LTS** — Long-Term Support: a Node.js release line (the even-numbered ones) that gets fixes for about 30 months; use one in production. §15.1

M

- **Macrotask** — See **Task**. §12.2
- **Main thread** — Single thread that runs your JavaScript, and in a browser also handles rendering and input; keep it free of long work. §12.1
- **Major / minor / patch** — Three parts of a semantic version `MAJOR.MINOR.PATCH`: breaking changes, new features that don't break anything, bug fixes. §10.10
- **`Map`** — Key-value collection with keys of any type, insertion order and a `size`. §8.1
- **Mapped types (TS)** — Types built by transforming every property of another type, e.g. `{ [K in keyof T]?: T[K] }` (how `Partial` works). §16.12
- **Mark-and-sweep** — Garbage collection by marking everything reachable from the roots, then freeing everything unmarked. §17.4
- **`Math`** — Namespace object with maths constants and functions (`round`, `max`, `random`). §5.10
- **MDN Web Docs** — Mozilla's free reference for JavaScript and web APIs, with browser-compatibility tables. §18.19
- **Memoization** — Caching a function's results by its arguments so repeated calls are instant. §4.7
- **Memory leak** — Memory that stays reachable by mistake (forgotten listeners, timers, growing caches, detached DOM nodes). §17.4.7
- **Merge sort** — Sorting by splitting the array in halves, sorting each recursively, and merging them; O(n log n) and stable. §17.2
- **Message passing** — Communicating between threads by sending copies of data (`postMessage`) instead of sharing variables. §14.8
- **Method** — Function stored as an object property and called through the object (`user.greet()`), where `this` is that object. §5.3
- **Method borrowing** — Calling one object's method on another object with `call`/`apply`, e.g. `Array.prototype.slice.call(arguments)`. §9.2
- **Method shorthand** — Writing `greet() { … }` inside an object literal instead of `greet: function () { … }`. §5.3

- **Microtask** — Job that runs right after the current task finishes: promise reactions, code after `await`, `queueMicrotask`. §12.2
- **Microtask queue** — Queue for promise callbacks, code after `await` and `queueMicrotask`; it is emptied completely after every task. §12.2
- **Microtask starvation** — When microtasks keep scheduling more microtasks, so the event loop never gets to timers, input or rendering. §12.2
- **Middleware** — Function in a web framework's request pipeline that can inspect or change the request and response, or pass control to the next one (logging, auth, parsing). §15.10
- **Minification** — Removing whitespace and shortening names so bundles download faster. §10.11
- **Mixin** — Reusable set of methods added to unrelated classes, by copying or by a subclass factory. §9.8
- **Mock** — Test double that records calls so the test can verify how it was used. §16.5
- **Module** — File with its own scope that exports and imports bindings. §10.1
- **Module graph** — All the modules an app loads, linked by their imports, starting from the entry point. §10.3
- **Module pattern** — An IIFE that returns an object of public functions while keeping private state in a closure. §4.9
- **Module scope** — Private top-level scope of an ES module; its names are invisible to other files unless exported. §4.5
- **Module specifier** — String after `from` in an import: relative (`'./a.js'`), absolute URL, or bare (`'lodash'`). §10.2
- **Monotonic stack** — Stack kept in increasing or decreasing order, used for "next greater element" style problems in O(n). §17.2
- **Multi-paradigm** — Language that supports several styles of programming; JavaScript allows procedural, object-oriented and functional code. §1.1
- **Mutating method** — Array method that changes the original array (`push`, `splice`, `sort`, `reverse`). §7.4
- **Mutation** — Changing an existing object or array in place (`o.n = 2`, `arr.push(x)`); everyone holding a reference sees the change. §2.4
- **MutationObserver** — Calls back (as a microtask) with a batch of changes when the observed DOM changes. §13.10

N

- **Named capture group** — `(?<name>…)` in a regex; its match appears as `match.groups.name`. §6.7
- **Named export** — Export referenced by its name: `export const x`, imported with `import { x }`. §10.2
- **Named function expression** — Function expression with its own name (`const f = function fact(n) {…}`); the name is visible inside for recursion and in stack traces. §4.2
- **Namespace import** — `import * as ns from './m.mjs'`: one object holding all of a module's exports. §10.2
- `NaN` — "Not a Number": a `number` value from failed maths; not equal to anything, including itself. §2.10
- **Narrowing (TS)** — Refining a broad type to a specific one via checks like `typeof`, `in` or a discriminant. §16.11
- **Navigation API** — Newer browser API (`navigation`) for single-page-app routing that intercepts all navigations, a cleaner successor to the History API. §14.7
- **NDJSON** — Newline-delimited JSON: one JSON value per line, handy for logs and streaming because each line parses on its own. §5.12
- `never` **(TS)** — Type with no values, used for code that can't be reached; assigning to it makes `switch` checks exhaustive. §16.11
- `new` — Creates an object linked to `Fn.prototype`, runs the constructor with it as `this` and returns it. §9.4
- `new` **binding** — `this` rule for `new Fn()`: `this` is the brand-new object; it has the highest priority. §9.1
- `new.target` — Inside a function, tells whether it was called with `new` (and which constructor). §9.4

- **Node (DOM)** — Any item in the DOM tree: elements, text nodes, comments and the document itself. §13.1
- `node:` **prefix** — Writing built-in Node modules as `node:fs` or `node:path`, which makes it clear they aren't npm packages. §15.3
- `node_modules` — Folder where npm installs a project's packages; never edit or commit it. §10.9
- `node:test` — Node's built-in test runner with suites, hooks, mocks, snapshots and coverage. §16.3
- **Node.js** — A JavaScript runtime built from V8 and libuv, for servers, CLIs and tools. §15.1
- **NodeList** — List of DOM nodes; `querySelectorAll` returns a static one that has `forEach`. §13.2
- **Non-blocking I/O** — Starting a disk or network operation and continuing with other work, getting a callback or promise when it finishes. §12.1
- **Non-capturing group** — `(?:…)`: groups part of a regex without remembering the match. §6.7
- **Nonce (CSP)** — Random value generated for each response and placed in both the CSP header and allowed `<script>` tags, so only those inline scripts run. §14.12
- **Normalization (Unicode)** — Converting text to a standard form (NFC) so visually identical strings, like a precomposed é and e plus an accent, compare equal. §6.5
- **npm** — Node's package manager and public registry. §10.9
- `npm ci` — Clean, exact install from the lockfile; the right command for CI and deploys. §10.10
- **npm scripts** — Commands named under `"scripts"` in `package.json` and run with `npm run name` or `node --run name`. §15.11
- `npx` — Runs a command from an npm package, using the local install or downloading it temporarily. §10.9
- `null` — Primitive meaning "deliberately empty"; `typeof null` is `'object'`. §2.3
- **Nullish** — Two "no value" values: `null` and `undefined`. §2.7
- **Nullish coalescing** — `a ?? b`: `b` only when `a` is `null` or `undefined` (ES2020). §2.7
- **Null-prototype object** — Object made with `Object.create(null)` that inherits nothing, so keys like `toString` or `__proto__` are safe to use as data. §8.7
- `Number.EPSILON` — Gap between 1 and the next double, about 2.2e-16; a tolerance for float comparisons. §2.10
- `Number.MAX_SAFE_INTEGER` — $2^{53} - 1$, the largest integer that numbers represent exactly. §2.10
- **Numeric separator** — Underscores inside number literals for readability: `1_000_000` (ES2021). §2.10

O

- **O(1), O(n), O(log n)** — Big-O labels for constant time, time growing in proportion to input size, and time growing with the logarithm of input size. §17.1
- **Object** — Collection of key–value properties; arrays, functions, dates and maps are all objects, and they are passed around by reference. §2.3
- **Object literal** — Creating an object directly with braces: `{ name: 'Ada', age: 36 }`. §5.1
- `Object.create` — Makes a new object with a chosen prototype, or none: `Object.create(null)`. §9.3
- `Object.entries` — Returns an object's own enumerable `[key, value]` pairs. §5.6
- `Object.freeze` — Makes an object's own properties read-only and blocks new ones; shallow. §5.6
- `Object.is` — Like `===` except `Object.is(NaN, NaN)` is true and `Object.is(0, -0)` is false. §2.6
- **Observer pattern** — Design where an object keeps a list of listeners and notifies them when something happens; `EventEmitter` and DOM events follow it (also called publish/subscribe). §15.8
- **Off-by-one error** — Loop or index that runs one step too many or too few, often `<=` used where `<` was meant. §3.6
- **OLOO** — "Objects linked to other objects": a style that skips classes and links plain objects with `Object.create`. §9.9
- **Operand** — Value an operator works on; in `a + b`, `a` and `b` are the operands. §2.5
- **Operator** — Symbol or keyword that computes a value from operands, such as `+`, `===`, `&&`, `typeof` or `?:`. §2.5
- **Optional catch binding** — `try { } catch { }` without naming the error (ES2019). §11.2
- **Optional chaining** — `a?.b`, `a?.[k]`, `a?.()`: stop and return `undefined` if the left side is `null`/`undefined`. §5.8

- **Options object** — Passing one object of named settings instead of many positional arguments: `connect({ host, port })`. §4.4
- **Origin** — Scheme, host and port of a URL; the unit of the same-origin policy. §14.2
- **Override** — Defining a method in a subclass with the same name as one in its parent so it replaces it; `super.method()` still reaches the parent's. §9.6
- **Own property** — Property stored directly on an object rather than inherited. §9.3

P

- **Package** — Folder of code with a `package.json`, published to a registry such as npm so others can install it. §10.9
- `package.json` — Project's manifest: name, version, scripts, dependencies, `type` and entry points. §10.9
- `padStart` / `padEnd` — Pad a string to a length with a fill string (`'5'.padStart(3, '0')` → `'005'`). §6.6
- **Parameter** — Name in a function's definition that receives a value (the argument) when the function is called. §4.1
- **Parameter properties (TS)** — TypeScript shorthand `constructor(private name: string)` that declares and assigns a field; not erasable. §16.9
- `parseInt` — Reads an integer from the start of a string, stopping at the first invalid character; always pass the radix (`parseInt(s, 10)`). §2.10
- **Partial application** — Fixing some of a function's arguments now and supplying the rest later. §4.8
- **PascalCase** — Naming style where every word starts with a capital (`ShoppingCart`); the convention for classes and constructors. §2.1
- **Passive listener** — Listener registered with `{ passive: true }`, promising not to call `preventDefault()`, so scrolling stays smooth. §13.8
- `path` **module** — Node's utilities for joining, resolving and splitting file paths. §15.5
- **Path traversal** — Attack using `../` in a user-supplied path to reach files outside an allowed folder; resolve the path and check its prefix. §15.5
- **Peer dependency** — Package a library expects the host app to install itself (e.g. a React plugin needs `react`), so only one copy exists. §10.9
- **Pending** — Starting state of a promise, before it is fulfilled or rejected. §12.7
- **Percent-encoding** — Writing unsafe URL characters as `%` plus hex bytes (`' '` → `%20`, `&` → `%26`); `URLSearchParams` and `encodeURIComponent` do it. §14.6
- **Permission model** — Node's `--permission` flag that denies file-system reads and writes, child processes, worker threads and more unless each is allowed (`--allow-fs-read=…`). §15.12
- **Phantom dependency** — Package your code imports that isn't in your own `package.json` and only works because some other package pulled it in. §10.9
- `pipeline` — Connects streams, handles backpressure and errors, and returns a promise (from `node:stream/promises`). §15.9
- **Playwright** — Tool from Microsoft for end-to-end testing that drives real Chromium, Firefox and WebKit browsers. §16.1
- **Poll phase** — The Node event-loop phase that waits for and runs I/O callbacks. §12.4
- **Polyfill** — Code that implements a missing built-in API for older environments. §10.12
- **Polymorphism** — Different classes offering the same method name so calling code can treat them alike (`shape.area()`), each doing its own thing. §9.6
- `popstate` — Event fired when the user moves back or forward through history entries. §14.7
- **Precedence** — Order in which operators are evaluated when parentheses don't decide it. §2.9
- **Pre-commit hook** — Script git runs before each commit (often lint and format) that can block a bad commit. §10.13
- **Prefix / postfix increment** — `++n` adds one and returns the new value; `n++` adds one but returns the old value. §2.5
- **Prefix sum** — Array where each entry is the total of all earlier values, letting you answer any range-sum question in O(1). §17.2

- **Preflight** — `OPTIONS` request a browser sends before a non-simple cross-origin request to ask permission. §14.2
- **Prettier** — Opinionated code formatter. §10.13
- `preventDefault` — Cancels the browser's default action for an event, such as following a link or submitting a form. §13.8
- **Primitive** — Immutable value that isn't an object: number, bigint, string, boolean, undefined, null, symbol. §2.4
- **Priority queue** — Queue that always hands out the highest-priority (smallest or largest) item next; usually built on a heap. §17.1
- **Private field** — `#name` class member only reachable inside the class body, enforced at runtime (ES2022). §9.5
- `process` — Node's global object for arguments, environment variables, exit codes and signals. §15.6
- `process.nextTick` — Node queue that runs before promise microtasks after the current operation. §12.4
- **Promise** — Object representing a value that will be available later; pending, then fulfilled or rejected. §12.7
- `Promise.all` — Waits for all promises; values in input order; rejects on the first rejection. §12.8
- `Promise.allSettled` — Waits for every promise and reports each outcome; never rejects. §12.8
- `Promise.any` — Fulfils with the first fulfilment; rejects with `AggregateError` if all reject. §12.8
- `Promise.race` — Settles like whichever input settles first. §12.8
- **Promisify** — Converting a callback-style function into one that returns a promise (`util.promisify`). §12.7
- **Property (DOM)** — Live JavaScript value on an element object (`input.value`), as opposed to the HTML attribute. §13.4
- **Property descriptor** — Settings of a property: `value`, `writable`, `enumerable`, `configurable`, or `get`/`set`. §5.6
- **Proposal (TC39)** — Suggested new language feature that moves through Stages 0–4, guided by a "champion" on the committee. §1.2
- **Prototype** — Object another object delegates missing property reads to, via its `[[Prototype]]` link. §9.3
- **Prototype chain** — Linked series of prototypes searched when a property isn't found on the object itself. §9.3
- **Prototype pollution** — Attack that writes to `Object.prototype` (e.g. via a `__proto__` key in merged JSON), affecting every object. §9.3
- **Proxy** — Object that wraps another and intercepts operations like get and set. §5.9
- **Pure function** — Function whose output depends only on its inputs and which has no side effects. §4.11

Q

- `querySelector` — Returns the first element matching a CSS selector, or `null`. §13.2
- **Queue** — First-in, first-out (FIFO) list: add at the back, remove from the front. §7.3
- `queueMicrotask` — Schedules a function as a microtask. §12.5
- **Quickselect** — Finding the k-th smallest item in average O(n) by partitioning around a pivot and recursing into one side only. §17.2

R

- **Race condition** — Bug where the result depends on which of several async operations finishes first. §12.13
- **Radians** — Unit `Math.sin`, `cos` and friends use for angles: 180° is π radians. §5.10
- **Radix** — Base of a number system: 10 for decimal, 16 for hex, 2 for binary; the second argument of `parseInt` and `toString`. §2.10
- `RangeError` — Thrown when a number is outside an allowed range: `new Array(-1)`, `toFixed(101)`, or too-deep recursion. §11.1
- **Reachability** — Object is reachable if some chain of references leads to it from a root (globals, the stack); unreachable objects are garbage-collected. §17.4

- **React** — Popular JavaScript library for building user interfaces from components; it relies heavily on immutable updates and closures. §2.4
- **Realm** — Separate global environment (an iframe, a `vm` context) with its own copies of built-ins. §9.7
- **Recursion** — Function solving a problem by calling itself on a smaller version of it. §4.10
- **ReDoS** — Regular-expression denial of service: a badly written pattern that takes exponential time on crafted input and freezes the thread. §6.9
- **`reduce`** — Folds an array into one value by running an accumulator function; pass an initial value. §7.5
- **Redux** — State-management library whose reducers must be pure functions that return new state instead of mutating the old one. §4.11
- **Reference** — Address an object variable holds; copying the variable copies the address, so both names point at the same object. §2.4
- **`ReferenceError`** — Thrown when you use a name that doesn't exist, or a `let`/`const` before its declaration (TDZ). §11.1
- **`Referrer-Policy`** / **`Permissions-Policy`** — Security headers: the first limits how much of the current URL is sent to other sites, the second turns off browser features (camera, geolocation) a page doesn't need. §14.12
- **Reflect** — Built-in object of methods mirroring basic object operations (`Reflect.get`, `Reflect.ownKeys`); handy inside `Proxy` handlers. §5.9
- **Reflected XSS** — XSS where the attack script comes from the request (e.g. a URL parameter) and the server echoes it straight back into the page. §14.10
- **Reflow** — Browser recalculating element positions and sizes (layout) after DOM or style changes. §13.11
- **`RegExp.escape`** — Escapes special regex characters so a string can be matched literally (ES2025). §6.9
- **Registry (npm)** — Online database (registry.npmjs.org) that npm downloads packages from and publishes them to. §10.9
- **Regression** — Bug in something that used to work; tests guard against regressions when code changes. §16.1
- **Regular expression** — Pattern for matching text, written `/pattern/flags` or with `new RegExp`. §6.7
- **Rejection** — Promise settling with an error (reason) instead of a value. §12.7
- **Remainder operator** — `%`: the remainder of division, with the sign of the left operand. §2.5
- **Rendering (event loop)** — Step where the browser runs `requestAnimationFrame` callbacks, then style, layout and paint. §12.2
- **Repaint** — Redrawing pixels after a visual change that doesn't affect layout. §13.11
- **REPL** — Read–Eval–Print Loop: an interactive prompt that runs each line you type and prints the result (`node` with no file, the browser console). §1.5
- **`replaceAll`** — Replaces every occurrence of a string or global regex (ES2021). §6.6
- **Replacer** — Optional second argument of `JSON.stringify`: a function or key list that changes or filters what is written. §5.12
- **Request / response** — Two halves of an HTTP exchange: the client sends a request (method, URL, headers, body); the server answers with a response (status, headers, body). §14.1
- **`requestAnimationFrame`** — Runs a callback right before the next paint; the right tool for animations. §14.5
- **ResizeObserver** — Reports when an element's size changes. §14.9
- **Rest parameter** — `...args` as the last parameter: collects remaining arguments into a real array. §4.4
- **Return value** — Value a function hands back with `return`; without one, a call gives `undefined`. §4.1
- **Reviver** — Function passed to `JSON.parse` to transform each parsed value. §5.12
- **Runtime** — Environment that runs your code (Node, a browser, Deno, Bun); also "at runtime" means while the program is running, as opposed to while compiling. §1.3

- **Run-to-completion** — Once a task starts, it runs until the call stack is empty; nothing interrupts it. §12.1

S

- **Same-origin policy (SOP)** — Browser rule that a page may read responses only from its own origin unless the other server allows it with CORS. §14.2
- `SameSite` — Cookie attribute (`Strict`, `Lax`, `None`) controlling whether it's sent on cross-site requests. §14.11
- **SameValueZero** — Equality `Map`, `Set` and `includes` use: like `===`, except `NaN` equals `NaN`. §8.1
- `satisfies` — TypeScript operator that checks a value against a type without widening the value's own type. §16.13
- **Scope** — Region of code where a name is visible: global, module, function or block. §4.5
- **Scope chain** — Nested scopes searched outward when a variable is looked up. §4.5
- **Seal** — `Object.seal`: no properties can be added or removed, but values can change. §5.6
- **Semantic versioning** — `MAJOR.MINOR.PATCH`: breaking changes, new features, bug fixes. §10.10
- **Serialization** — Turning an in-memory value into a format that can be stored or sent (such as a JSON string); deserialization turns it back. §5.2
- **Service worker** — Background script that acts as a network proxy for offline support, caching and push. §14.8
- **Session cookie** — Cookie with no expiry date that disappears when the browser session ends; also loosely, the cookie holding a login session ID. §14.4
- `sessionStorage` — Like `localStorage` but scoped to one tab and cleared when it closes. §14.3
- `Set` — Collection of unique values in insertion order with O(1) average `has`. §8.2
- **Set methods** — `union`, `intersection`, `difference`, `symmetricDifference` and subset tests on Sets (ES2025). §8.2
- `setImmediate` — Node timer that runs in the check phase, after I/O callbacks. §12.4
- `setInterval` — Runs a function repeatedly roughly every N milliseconds until cleared. §12.5
- **Setter** — `set` method that runs when a property is assigned. §5.7
- `setTimeout` — Runs a function once after at least N milliseconds, as a new task. §12.5
- **Settled** — Promise that is no longer pending: it has been either fulfilled or rejected, and never changes again. §12.7
- **Shadowing** — Inner variable or own property hiding one with the same name further out. §4.5
- **Shallow copy** — Copy of the top level only; nested objects are still shared. §5.4
- **SharedArrayBuffer / Atomics** — Memory that several workers can read and write at once, plus `Atomics` operations to update it safely without races. §15.2
- **Short-circuit evaluation** — `&&`, `||`, `??` and `?.` stop evaluating as soon as the result is known. §2.7
- **Side effect** — Anything a function does beyond returning a value: mutating inputs, I/O, logging, changing globals. §4.11
- `SIGTERM` / `SIGINT` — OS signals asking a process to stop: `SIGTERM` comes from tools such as Docker or `kill`, `SIGINT` from pressing Ctrl+C. §15.6
- **Simple request (CORS)** — Cross-origin `GET`, `HEAD` or `POST` with only basic headers and content types, sent without a preflight. §14.2
- **Single-page application (SPA)** — Web app that loads one page and updates the view with JavaScript, changing the URL with the History API instead of full page loads. §14.7
- **Single-threaded** — JavaScript runs one piece of your code at a time on one thread; waiting is handed to the host. §12.1
- **Singleton** — Something that exists only once; every importer of an ES module shares the same single instance of it. §10.3
- **Sink (XSS)** — An API that turns a string into HTML or code (`innerHTML`, `eval`, `document.write`); untrusted data must never reach it unescaped. §14.10
- **Sliding window** — Keeping a moving range `[left, right]` over an array or string and adjusting its ends, to solve contiguous-range problems in O(n). §17.2

- **Sloppy mode** — Default, non-strict mode of classic scripts, which silently allows mistakes strict mode reports. §1.8
- **Snapshot test** — Test that saves a serialized output and fails when it changes. §16.6
- **Soundness (TS)** — Whether a type system guarantees values really match their types; TypeScript is deliberately not fully sound (`any`, casts). §16.8
- **Source map** — File mapping minified or transpiled code back to the original source for debugging. §11.8
- **Sparse array** — Array with holes, indexes that were never set, as made by `new Array(3)` or `delete arr[i]`. §7.3
- **SpiderMonkey** — Firefox's JavaScript engine, the first one ever written. §1.3
- `splice` — Mutating array method that removes and/or inserts items at an index and returns the removed items. §7.4
- **Spread syntax** — `...` expanding an iterable into elements or arguments, or an object's properties into another object. §5.4
- **Spy** — Test double that records its calls (`t.mock.fn()`). §16.5
- **Stable sort** — Sort that keeps items with equal keys in their original order; `Array.prototype.sort` has been stable since ES2019. §7.6
- **Stack** — Last-in, first-out (LIFO) list: `push` and `pop` at the same end. §7.3
- **Stack overflow** — Error when too many nested calls fill the call stack, usually recursion without a reachable base case: `RangeError: Maximum call stack size exceeded`. §4.10
- **Stack trace** — List of function calls active when an error was created, newest first. §11.8
- **Stage (TC39)** — Proposal's maturity from 0 (idea) to 4 (finished, goes into the next edition). §1.2
- **Stale closure** — Callback still seeing old values because it closed over variables from an earlier render or call. §4.7
- **Statement** — Complete instruction such as a declaration, an `if` or a loop. §1.6
- **Static initialization block** — `static { … }` inside a class: code that runs once when the class is defined (ES2022). §9.5
- **Static member** — Method or field on the class itself, not on instances: `static create()`. §9.5
- **Static typing** — Checking types before the program runs, from annotations and inference; TypeScript adds it to JavaScript. §16.8
- `stdout` / `stderr` — Process's two output streams: normal output and error/diagnostic output; `console.log` writes to one, `console.error` to the other. §15.6
- **Step over / into / out** — Debugger controls: run the next line, enter the function being called, or run until the current function returns. §11.9
- **Sticky flag (`y`)** — Regex flag that only matches starting exactly at `lastIndex`, useful for writing tokenizers. §6.7
- `stopPropagation` — Stops an event from travelling to further elements. §13.6
- **Stored XSS** — XSS where the attacker's script is saved on the server (a comment, a profile name) and served to every visitor. §14.10
- **Stream** — Node's abstraction for data processed in chunks: Readable, Writable, Duplex, Transform. §15.9
- **Strict equality** — `===`: same type and value, no conversion. §2.6
- **Strict mode** — Restricted mode that turns silent mistakes into errors; automatic in modules and classes. §1.8
- **String** — Immutable sequence of UTF-16 code units. §6.1
- `String.raw` — Tag for template literals that keeps backslashes as written, handy for regex sources and Windows paths. §6.3
- **Structural typing** — TypeScript's rule that types are compatible if their shapes match, whatever their names. §16.8
- **Structured clone / `structuredClone`** — Deep-copy algorithm used by `structuredClone()`, `postMessage` and IndexedDB; handles Dates, Maps, Sets and cycles, throws `DataCloneError` on functions. §5.4, §14.8
- **Stub** — Test double that returns canned answers. §16.5

- **`submit` event** — Fires on a `<form>` when it is submitted; listen for it (not button clicks) and call `preventDefault()` to handle it in JavaScript. §13.9
- **Subresource Integrity** — `integrity` hash on a `<script>` so the browser refuses a tampered CDN file. §14.12
- **Subtest** — Test nested inside another test with `t.test()`, reported as part of its parent. §16.3
- **`super`** — Calls the parent class's constructor (`super()`) or methods (`super.m()`). §9.6
- **Supply-chain attack** — Malicious code slipped into a package you depend on (or its dependencies) so it runs in your app. §10.10
- **SuppressedError** — Error thrown when cleanup with `using` fails while another error is already in flight; it holds both. §11.6
- **Surrogate pair** — Two UTF-16 code units that together encode one character outside the Basic Multilingual Plane, like most emoji. §6.5
- **SWC** — Very fast transpiler written in Rust, used by Next.js and others to strip types and transform syntax. §10.12
- **`switch`** — Compares one value against `case` values with `===`; falls through without `break`. §3.4
- **Symbol** — Primitive creating unique identifiers, often used as property keys. §2.3
- **`Symbol.dispose`** — Well-known symbol naming the cleanup method that a `using` declaration calls automatically. §11.6
- **`Symbol.iterator`** — Well-known symbol naming the method that makes an object iterable. §8.4
- **Synchronous** — Code that runs step by step and blocks until each step finishes. §12.1
- **Syntax** — Grammar rules for how code must be written; breaking them gives a `SyntaxError` before anything runs. §1.6
- **`SyntaxError`** — Thrown when code or text can't be parsed: malformed source, bad `JSON.parse` input, an invalid regex. §11.1

T

- **Table-driven test** — One test body run over a table of inputs and expected outputs, so new cases are a single line. §16.3
- **Tagged template** — Function called with a template literal's pieces: `tag`Hi ${name}``. §6.3
- **Task** (macrotask) — A unit of work in the event loop: a script, timer callback, I/O callback or UI event; one runs per loop turn. §12.2
- **TC39** — The Ecma committee that designs and maintains ECMAScript. §1.2
- **TCP** — Transmission Control Protocol: the reliable, ordered byte-stream connection that HTTP runs on top of. §15.2
- **Template literal** — Backtick string with `${}` interpolation and real line breaks. §6.3
- **Temporal** — Modern date-time API (Stage 4 in March 2026, planned for ES2027); not in Node 24. §5.11
- **Temporal Dead Zone (TDZ)** — Time between entering a scope and a `let`/`const`/`class` declaration running; access throws. §2.2
- **Terminal** — Text window where you type commands (the command line), such as `node app.js` or `npm install`. §1.5
- **Ternary operator** — `cond ? a : b`: chooses between two values. §3.3
- **Test double** — Any stand-in for a real dependency in a test: dummy, stub, spy, mock or fake. §16.5
- **Test pyramid** — Guideline to have many fast unit tests, fewer integration tests and only a few slow end-to-end tests. §16.1
- **Test runner** — Tool that finds tests, runs them and reports passes and failures: `node --test`, Vitest, Jest. §16.1
- **Test suite** — Group of related tests, or all of a project's tests together. §16.1
- **Test-driven development (TDD)** — Writing a failing test first, then the code that makes it pass, then tidying up (red, green, refactor). §16.7
- **Testing trophy** — Alternative to the test pyramid that puts most effort into integration tests, on top of static checks. §16.1
- **Text node** — A DOM node holding plain text inside an element, including the whitespace between tags. §13.1

- `textContent` — All text inside a node; setting it inserts plain text, never HTML. §13.3
- `then` — Registers callbacks on a promise and returns a new promise. §12.7
- **Thenable** — Any object with a `then` method; `await` and promise resolution treat it like a promise. §12.7
- `this` — Context object of a function call, set by how the function is called. §9.1
- **Thread** — Independent line of execution the CPU can run; JavaScript code runs on one, while the host may use others behind the scenes. §12.1
- **Thread pool** — libuv's worker threads (4 by default) that run file-system, DNS lookup, crypto and zlib jobs for Node. §15.2
- **Throttle** — Run a function at most once per interval during a burst of calls (e.g. scroll handlers). §17.3
- `throw` — Raises an exception, stopping normal flow until a `catch` handles it. §11.2
- **Tilde range (`~`)** — Npm version range that allows only patch updates (`~1.2.3` means at least 1.2.3, below 1.3.0). §10.10
- **Timers phase** — The Node event-loop phase that runs expired `setTimeout` and `setInterval` callbacks. §12.4
- **TOCTOU (check-then-act)** — "Time of check to time of use": a race where something changes between checking (does the file exist?) and acting on it; just try the action and handle the error. §15.4
- `toJSON` — Method `JSON.stringify` calls if present, letting an object choose its own JSON form (`Date` uses it to give an ISO string). §5.12
- **Top-level `await`** — Using `await` at the top level of an ES module; importers wait for it (ES2022). §10.5
- **Topological sort** — Ordering the nodes of a directed graph so every node comes after everything it depends on; impossible if there is a cycle. §17.2
- `toSorted` / `toReversed` / `toSpliced` / `with` — Non-mutating copies of `sort`, `reverse`, `splice` and index assignment (ES2023). §7.4
- **Transform stream** — Duplex stream that changes data as it passes through, like gzip compression. §15.9
- **Transitive dependency** — Package you don't install directly but get because one of your dependencies (or theirs) needs it. §10.9
- **Transpiler** — Tool that rewrites source code into another syntax (TypeScript or new JavaScript → older JavaScript). §10.12
- **Tree shaking** — Removing unused exports from a bundle, made possible by static ES module syntax. §10.11
- **Trie** — Tree of characters where each path from the root spells a prefix; fast for "starts with" lookups. §17.2
- **Trusted Types** — Browser feature that makes dangerous sinks like `innerHTML` accept only values produced by approved sanitizing policies. §14.10
- **Truthy** — Any value that is not falsy, including `[]`, `{}` and `'0'`. §2.11
- `try…catch` — Runs code and handles exceptions thrown synchronously inside it. §11.2
- `tsc` — The TypeScript compiler: it type-checks code and, unless given `--noEmit`, writes JavaScript output. §16.8
- `tsconfig.json` — Configuration file for a TypeScript project: which files to check and with which compiler options (e.g. `strict`). §16.8
- `tsx` — Popular command-line tool that runs TypeScript files directly in Node using esbuild. §16.9
- **Tuple (TS)** — Fixed-length array type with a type per position, e.g. `[string, number]`. §16.10
- **Two pointers** — Using two indexes that move through an array (often from both ends of sorted data) to solve pair problems in O(n). §17.2
- **Type annotation** — A TypeScript declaration of a value's type, such as `x: number`. §16.10
- **Type assertion (TS)** — `value as Type`: telling TypeScript to trust you about a type; it checks nothing at runtime. §16.8
- **Type checker** — Part of TypeScript that verifies values are used consistently with their types and reports errors before running. §16.8

- **Type erasure** — TypeScript types are deleted when code is compiled or stripped, so none of them exist at runtime. §16.8
- **Type inference** — TypeScript working out a type from how a value is created (`let n = 1` is `number`) so you needn't write it. §16.10
- **Type predicate** — A TypeScript return type `x is T` that narrows the argument when the function returns true. §16.11
- **Type stripping** — Node running `.ts` files by deleting type syntax without checking it. §16.9
- **Typed array** — Array-like view of fixed-size numbers over an `ArrayBuffer`, such as `Uint8Array`. §7.9
- `TypeError` — Thrown when a value is the wrong type for an operation: reading a property of `null`, calling a non-function, assigning to a `const`. §11.1
- `typeof` — Operator returning a string naming a value's type; `typeof null` is `'object'`. §2.3
- **TypeScript** — JavaScript plus static types that are checked by `tsc` and erased before running. §16.8

U

- **Unary operator** — Operator with one operand: `-x`, `+x` (converts to number), `!x`, `typeof x`, `++x`. §2.5
- `uncaughtException` — Node's `process` event for an error nobody caught; log it and exit, because the app may be in a broken state. §11.5
- `undefined` — Primitive meaning "no value assigned yet"; what missing properties and arguments give. §2.3
- **Unhandled rejection** — Rejected promise with no handler; reported by the browser and fatal by default in Node. §11.5
- **Unicode** — Standard that gives every character in every writing system a number (code point), plus encodings such as UTF-8 and UTF-16 to store them. §6.5
- **Unicode property escape** — `\p{…}` in a `u`/`v` regex, matching characters by Unicode property such as `\p{L}`. §6.9
- **Union type (TS)** — `A | B`: a value that may be any one of several types; narrow it before using type-specific features. §16.10
- **Union-find** — Structure (disjoint-set union) that tracks which items are in the same group and merges groups quickly. §17.2
- **Unit test** — Fast test of one function or module in isolation. §16.1
- **Unix epoch** — Moment 1970-01-01T00:00:00Z; JavaScript dates count milliseconds since it. §5.11
- `unknown` **(TS)** — Type-safe "anything" type: you must narrow it before using it. §16.10
- **Upsert (**`getOrInsert`**)** — Getting a key's value or inserting a default if it is missing, in one call: `map.getOrInsert(k, [])` (ES2026). §8.1
- `URIError` — Thrown when `encodeURIComponent` or `decodeURIComponent` gets malformed input, like `decodeURIComponent('%')`. §11.1
- **URL / URLSearchParams** — Built-ins for parsing, building and encoding URLs and query strings. §14.6
- `using` — Declaration that automatically calls `[Symbol.dispose]()` when the block ends (finished proposal, ES2027; works in Node 24). §11.6
- **UTC** — Coordinated Universal Time: the time-zone-free world clock; store and transmit dates in UTC and convert to local time only for display. §5.11
- **UTF-16** — Encoding JavaScript strings use: characters as one or two 16-bit code units. §6.5
- **UTF-8** — Most common text encoding on the web and in files: 1 to 4 bytes per code point, ASCII stays 1 byte. §6.5

V

- **V8** — Google's JavaScript engine, used in Chrome, Edge, Node.js and Deno. §1.3
- `var` — Original function-scoped, hoisted variable declaration; avoid in new code. §2.1
- **Variable** — Named box for a value, declared with `let`, `const` or `var`. §2.1
- **Virtualization (lists)** — Rendering only the rows currently visible in a long list and reusing them as you scroll, to keep the DOM small. §13.11
- **Visual Studio Code (VS Code)** — Free code editor from Microsoft with built-in JavaScript/TypeScript support, a terminal and a debugger. §1.5

- **Vite** — Dev server plus production bundler; the default choice for new front-end apps. §10.11
- **Vitest** — Fast test runner built on Vite with a Jest-compatible `expect` API. §16.7
- **Void operator** — `void expr` evaluates the expression and returns `undefined`. §2.9

W

- **Watch expression** — Expression the debugger re-evaluates and shows every time execution pauses. §11.9
- **WeakMap** — Map with object keys held weakly: entries disappear when the key object is garbage-collected. §8.3
- **WeakRef** — Weak reference to an object; `deref()` returns it or `undefined` once collected. §8.3
- **WeakSet** — Set of objects held weakly; used to tag objects without keeping them alive. §8.3
- **Web Streams API** — Standard `ReadableStream` / `WritableStream` / `TransformStream` classes, shared by browsers and Node (`fetch` bodies use them). §15.9
- **Web Worker** — Background thread with no DOM access that talks to the page via `postMessage`. §14.8
- **webpack** — Long-established, highly configurable bundler. §10.11
- **Well-known symbol** — Built-in `Symbol` the language uses as a hook, such as `Symbol.iterator`, `Symbol.asyncIterator` or `Symbol.dispose`. §8.4
- **Worker threads** — Node's `worker_threads` module for running CPU-heavy JavaScript in parallel. §15.2

X

- `X-Content-Type-Options: nosniff` — Header telling the browser to trust the declared `Content-Type` instead of guessing, so an uploaded text file can't be run as a script. §14.12
- **XOR** — "Exclusive or": a bit is 1 when exactly one input bit is 1 (`^` in JavaScript); `x ^ x` is 0, which helps find a single unpaired number. §2.8
- **XSS** — Cross-site scripting: attacker-controlled script runs in your page, usually through unescaped HTML. §14.10

Y

- `yield` — Pauses a generator and hands a value to the consumer; `yield*` delegates to another iterable. §8.5

Z

- **Zalgo** — Callback API that is sometimes synchronous and sometimes asynchronous, making ordering unpredictable. §12.6
- **Zero-width joiner (ZWJ)** — Invisible character (U+200D) that glues emoji into one picture, such as a family emoji made of several people. §6.5
- **Zod** — A TypeScript-first library for describing data shapes and validating untrusted input at runtime. §16.8

Chapter 18 TL;DR

- Use this chapter for **revision**: cover the answer column of a sheet, say the answer, then follow the § link for anything you missed.
- **Language core**: `const` by default, `===` always, `??` for defaults, eight types with `typeof null === 'object'`, eight falsy values, floats that aren't exact (`0.1 + 0.2`), closures that remember their scope, and `this` decided at the call site (arrows excepted).
- **Data**: shallow spread vs `structuredClone`; `Object.freeze` is shallow; `toSorted` / `with` instead of mutating shared arrays; `Map` / `Set` for keyed lookup and uniqueness; generators and iterator helpers for lazy sequences.
- **Async**: one task, then **all** microtasks, then render; sync code → microtasks → tasks; `Promise.all` for parallel work, `allSettled` for every outcome, `AbortController` to cancel.
- **Platform**: `textContent` over `innerHTML`, delegation with `closest`, check `res.ok` after `fetch`, `HttpOnly; Secure; SameSite` cookies for sessions, CSP against XSS; in Node, `node:` modules, streams with `pipeline`, never block the loop.

- **Quality**: `node:test` + `assert/strict`, `tsc --noEmit` for types, ESLint + Prettier, lockfile + `npm ci`.
- **Versions**: ES2015 was the big one; since then one edition every June. ES2026 is only partly in Node 24; Temporal and `using` belong to ES2027.

This is the end of the JavaScript Handbook. Next: the React Handbook, or back to Chapter 1 for a second pass.