Chapter 17 — Modern Java: 17 to 25

Java ships every six months, and a lot changed between the two **long-term-support** (LTS) releases — versions vendors patch for years, so most companies standardise on them — most teams run today: **Java 17** (September 2021) and **Java 25** (September 2025). This chapter is a **concise tour**: one table of everything finalised in each release, one tiny runnable example per final feature the rest of the book doesn't already teach, and an exact list of what is still *preview* or *incubating* — what you can and can't use in production today. Features taught elsewhere get a two-line reminder and a link: this chapter is the map, the linked sections the territory.

How the code was run. Programs are in `code/` (package `ch17.v17` … `ch17.v25`, one sub-package per release), compiled with `javac --release 25` **without** `--enable-preview`, and run on OpenJDK 26. Only **final** features appear in runnable code. Every JEP number and status was checked against the release pages on openjdk.org (`openjdk.org/projects/jdk/<N>/`) and the individual JEP pages.

17.1 Reading a feature's status

Each change to the JDK is described in a **JEP** (JDK Enhancement Proposal) — see Chapter 1 §1.12 for the release model. A JEP title tells you the maturity:

Title contains	Status	Can you use it in production?
nothing (e.g. *JEP 444: Virtual Threads*)	**Final / permanent**	Yes
(Preview), *(Second Preview)* …	**Preview**: complete, but may still change	Only with `--enable-preview` on both `javac` and `java`, for experiments
(Incubator)	**Incubating API** in a `jdk.incubator.*` module	Only with `--add-modules jdk.incubator.…`; API will change
(Experimental)	**Experimental VM feature**	Needs `-XX:+UnlockExperimentalVMOptions`; not for production
status *Closed / Withdrawn*	**Withdrawn**	No — removed before finalisation

A feature usually goes preview → preview → … → final, and sometimes gets renamed along the way (e.g. *Statements before super(...)* became *Flexible Constructor Bodies*). This book marks every feature with the release that **finalised** it.

17.2 The version table

GA = general availability date. "Final" rows list what you can rely on; previews are in 17.11.

Release	GA	Language and library — final	JVM, GC and tools — final
17 LTS	2021-09-14	Sealed classes (409), enhanced pseudo-random generators (356), always-strict floating point (306), context-specific deserialization filters (415)	Strong encapsulation of JDK internals (403), macOS/AArch64 port (391), new macOS rendering pipeline (382); experimental AOT/Graal JIT removed (410); RMI activation removed (407)
18	2022-03-22	UTF-8 by default (400), code snippets in Javadoc `@snippet` (413), internet-address resolution SPI (418)	Simple web server `jwebserver` (408), core reflection reimplemented with method handles (416); finalization deprecated for removal (421)
19	2022-09-20	*(no final language/API features)*	Linux/RISC-V port (422)
20	2023-03-21	*(no final features — previews and incubators only)*	—
21 LTS	2023-09-19	Record patterns (440), pattern matching for `switch` (441), virtual threads (444), sequenced collections (431), key encapsulation mechanism API (452)	Generational ZGC (439); warnings for dynamically loaded agents (451); Windows 32-bit x86 port deprecated (449)
22	2024-03-19	Unnamed variables and patterns (456), Foreign Function & Memory API (454), launch multi-file source programs (458)	Region pinning for G1 (423)
23	2024-09-17	Markdown documentation comments (467)	ZGC generational mode by default (474); `sun.misc.Unsafe` memory-access methods deprecated for removal (471)
24	2025-03-18	Stream gatherers (485), Class-File API (484), quantum-resistant ML-KEM (496) and ML-DSA (497)	Virtual threads synchronize without pinning (491), ahead-of-time class loading and linking (483), ZGC non-generational mode removed (490), Security Manager permanently disabled (486), linking run-time images without JMODs (493), late barrier expansion for G1 (475), JNI restriction warnings (472), `Unsafe` memory-access warnings (498), Windows 32-bit port removed (479), 32-bit x86 port deprecated (501)
25 LTS	2025-09-16	Compact source files and instance `main` methods (512), module import declarations (511), flexible constructor bodies (513), scoped values (506), key derivation function API (510)	Compact object headers (519, opt-in), generational Shenandoah (521), AOT command-line ergonomics (514) and method profiling (515), JFR cooperative sampling (518) and method timing and tracing (520); 32-bit x86 port removed (503)

Numbers in parentheses are JEP numbers. Glosses for the less obvious entries: **sealed** classes restrict which classes may extend them; **deserialization filters** reject unwanted classes when turning bytes back into objects; **SPI** = *service provider interface*, a plug-in point; **method handles** are fast, typed references to methods; **finalization** is the old `finalize()` clean-up hook; a *port* is a build for another OS/CPU (**RISC-V** is an open CPU architecture, **x86** the Intel/AMD family); **agents** are JARs that instrument (modify) classes as they load; **ML-KEM/ML-DSA** are *quantum-resistant* algorithms meant to stay secure against future quantum computers; the **Security Manager** was an old in-process sandbox; **JMODs** are the JDK's module packaging files. In three words each: **21** = virtual threads + patterns, **22** = FFM + `_`, **24** = gatherers, **25** = simpler Java (compact source files, module imports, flexible constructors) + scoped values.

17.3 The Java 17 baseline

Teams moving from Java 11 got a whole set of features finalised in 14–17. They are taught in depth elsewhere:

Feature	Final in	JEP	Where in this book
Switch expressions (`->` , `yield`)	14	361	Chapter 3 §3.3
Helpful `NullPointerException` messages (on by default since 15)	14	358	below
Text blocks `"""`	15	378	Chapter 2 §2.12
Records	16	395	Chapter 6 §6.8
Pattern matching for `instanceof`	16	394	Chapter 3 §3.5
`Stream.toList()`	16	—	Chapter 12
`jpackage` (builds native installers such as `.msi` , `.dmg` , `.deb`)	16	392	—
Sealed classes and interfaces	17	409	Chapter 6 §6.7

All of them in one small program: `code/ch17/v17/Java17Baseline.java`

```
sealed interface Shape permits Circle, Square {}                // sealed classes: Java 17
record Circle(double r) implements Shape {}                     // records: Java 16
record Square(double side) implements Shape {}

static double area(Shape s) {
    if (s instanceof Circle c) return Math.PI * c.r() * c.r();   // pattern matching for instanceof: Java 16
    if (s instanceof Square q) return q.side() * q.side();
    throw new AssertionError();
}
static String kind(int day) {
    return switch (day) {                                         // switch expression: Java 14
        case 6, 7 -> "weekend";
        case 1, 2, 3, 4, 5 -> "weekday";
        default -> throw new IllegalArgumentException("day " + day);
    };
}
// main: a text block, then c.address().city().length() with a null address
```

Output:

```
text block : {"shape": "circle", "r": 1.5}
areas      : 7.07 4.00
switch     : weekend, weekday
record     : Circle[r=1.5]
NPE says   : Cannot invoke "ch17.v17.Java17Baseline$Address.city()" because the return value of
"ch17.v17.Java17Baseline$Customer.address()" is null
```

The **helpful NPE** message names exactly which part of a chain was `null` — no more guessing which of three calls on one line failed.

Enhanced pseudo-random generators (JEP 356, Java 17)

What it is: a common interface `java.util.random.RandomGenerator` for every random source (old `Random` , `SplittableRandom` , `ThreadLocalRandom` and new *LXM* algorithms — mixing a linear congruential generator with an XOR-based one), selectable by name. (*Pseudo-random* = from a deterministic formula; the same **seed** gives the same sequence.) **Why it matters:** code can accept "any generator", and you can pick algorithms

with better statistical quality or splitting support for parallel work.
`code/ch17/v17/RandomGenerators.java` :

```
RandomGenerator g = RandomGeneratorFactory.of("L64X128MixRandom").create(42); // seeded: repeatable
System.out.println("L64X128MixRandom dice: " + g.ints(8, 1, 7).boxed().toList());
RandomGenerator legacy = new java.util.Random(42);          // old classes implement the interface too
```

Output:

```
L64X128MixRandom dice: [1, 2, 1, 1, 4, 4, 6, 2]
java.util.Random dice: [3, 4, 1, 3, 1, 2, 6, 3]
default algorithm    : L32X64MixRandom
a few algorithms     : [L128X1024MixRandom, L128X128MixRandom, L128X256MixRandom, L32X64MixRandom,
L64X1024MixRandom, L64X128MixRandom]
```

For everyday use `ThreadLocalRandom.current()` or `RandomGenerator.getDefault()` is fine; for security use `SecureRandom` (unpredictable, suitable for passwords and keys; Chapter 7 §7.12).

Strong encapsulation (JEP 403, Java 17)

The JDK's internal packages (`sun.*` , `jdk.internal.*`) are closed to reflection by default — the `--illegal-access` escape hatch was removed. Old libraries that poke at internals fail with `InaccessibleObjectException` unless you add `--add-opens` . This is the #1 upgrade issue from Java 8/11; see Chapter 16 §16.12.

17.4 Java 18

UTF-8 by default (JEP 400)

The problem it solved: before 18, APIs such as `FileReader` , `FileWriter` , `InputStreamReader` , `PrintStream` and `String.getBytes()` used the **platform** charset — UTF-8 on Linux/macOS but often Windows-1252 on Windows — so a file written on one machine could be garbled on another. Since 18 the default is **UTF-8 everywhere**; the OS encoding is still available as the `native.encoding` property. (Console output uses `stdout.encoding` , which still follows the terminal.) Full treatment: §13.7.

`code/ch17/v18/Utf8Default.java` :

```
System.out.println("Charset.defaultCharset(): " + Charset.defaultCharset());
System.out.println("native.encoding (OS)    : " + System.getProperty("native.encoding"));
Files.writeString(tmp, "café ☕");                          // no charset argument needed
try (var reader = new java.io.FileReader(tmp.toFile())) { ... }   // FileReader also uses UTF-8 now
```

Output (macOS — on Windows `native.encoding` would typically be `Cp1252` , but the first two lines would still say UTF-8):

```
Charset.defaultCharset(): UTF-8
file.encoding           : UTF-8
native.encoding (OS)    : UTF-8
read back               : café ☕ (9 bytes)
```

9 bytes for 6 characters: `é` takes 2 bytes and `☕` 3 in UTF-8. Still best practice: pass a charset explicitly when reading data you did not write.

Simple web server (JEP 408)

`jwebserver` serves the current directory as **static files** over HTTP — handy for testing HTML or sharing files on a LAN, **not** for production (HTTP/1.1 only, no HTTPS). Run `jwebserver -p 8000` (`-p` = port) then open `http://localhost:8000/` (not run here — the book's programs don't use the network). The same server is available as an API: `com.sun.net.httpserver.SimpleFileServer` .

Code snippets in Javadoc (JEP 413)

`{@snippet : …}` replaces `<pre>{@code …}</pre>` for examples in Javadoc; it supports highlighting, regions and snippets pulled from real, compiled source files — so documentation examples can be tested.

Finalization deprecated for removal (JEP 421)

`Object.finalize()` still works but is *deprecated for removal* (discouraged and scheduled for deletion); use try-with-resources and `java.lang.ref.Cleaner` (registers clean-up code to run after an object becomes unreachable) instead (Chapter 8).

17.5 Java 19 and 20: the preview years

Neither release finalised a language or library feature. They matter because the big Java 21 features were previewed here:

JEP	Feature in 19	JEP	Feature in 20
425	Virtual Threads (Preview)	436	Virtual Threads (Second Preview)
405	Record Patterns (Preview)	432	Record Patterns (Second Preview)
427	Pattern Matching for switch (Third Preview)	433	Pattern Matching for switch (Fourth Preview)
424	Foreign Function & Memory API (Preview)	434	Foreign Function & Memory API (Second Preview)
428	Structured Concurrency (Incubator)	437	Structured Concurrency (Second Incubator)
426	Vector API (Fourth Incubator)	438	Vector API (Fifth Incubator)
—	—	429	Scoped Values (Incubator)

Java 19 also added the Linux/RISC-V port (JEP 422). If you are on 17 and skipping to 21 or 25, you can ignore 19 and 20 entirely.

17.6 Java 21 LTS

Pattern matching for `switch` and record patterns (JEPs 441, 440)

`switch` can match on **types** and **deconstruct records** (pull components into variables), with `when` **guards**, explicit `case null`, and **exhaustiveness** checking over sealed hierarchies — no `default` needed. Full treatment: Chapter 3 §3.6 and §3.7. `code/ch17/v21/PatternsDemo.java` evaluates a small expression tree:

```java
sealed interface Expr permits Num, Add, Mul, Neg {}
record Num(int value) implements Expr {}
record Add(Expr left, Expr right) implements Expr {}
record Mul(Expr left, Expr right) implements Expr {}
record Neg(Expr e) implements Expr {}

static int eval(Expr e) {
    return switch (e) {                                          // exhaustive: no default needed (sealed)
        case Num(int v) -> v;
        case Add(Expr l, Expr r) -> eval(l) + eval(r);
        case Mul(Num(int a), Num(int b)) when a == 0 || b == 0 -> 0;   // nested pattern + guard
        case Mul(Expr l, Expr r) -> eval(l) * eval(r);
        case Neg(Neg(Expr inner)) -> eval(inner);                // double negation
        case Neg(Expr inner) -> -eval(inner);
    };
}
static String describe(Object o) {
    return switch (o) {
        case null -> "null!";
        case Integer i when i > 100 -> "big int " + i;
        case Integer i -> "int " + i;
        case String s -> "string of length " + s.length();
        default -> "something else: " + o.getClass().getSimpleName();
    };
}
```

Output:

```
Add[left=Num[value=2], right=Mul[left=Num[value=3], right=Neg[e=Neg[e=Num[value=4]]]]] = 14
int 7
big int 700
string of length 3
something else: Double
null!
```

If you add a new `Expr` subtype, every `switch` like `eval` stops compiling until you handle it — the compiler finds the places to update. This "data-oriented" style (sealed types + records + pattern switch) is the modern alternative to the Visitor pattern (LLD handbook, behavioural patterns).

Virtual threads (JEP 444)

Virtual threads are lightweight JVM-managed threads: you can have millions, and a **blocking** call (sleep, socket read, JDBC query) unmounts the virtual thread from its **carrier** OS thread instead of blocking it. They make the simple **thread-per-request** style scale for **I/O-bound** servers. Full coverage, including pinning and when they *don't* help: Chapter 15. `code/ch17/v21/VirtualThreadsDemo.java` :

```java
try (var executor = Executors.newVirtualThreadPerTaskExecutor()) {   // close() waits for all tasks
    for (int i = 0; i < 10_000; i++) {
        executor.submit(() -> {
            Thread.sleep(Duration.ofMillis(200));            // simulated blocking I/O
            done.incrementAndGet();
            return null;
        });
    }
}
```

Output:

```
tasks finished: 10000
took < 2 s    : true   (10,000 x 200 ms sequentially would be 2,000 s)
is virtual    : true
```

(The program prints a yes/no instead of the elapsed time, which varies by machine; on the author's machine it was a few hundred milliseconds.)

Sequenced collections (JEP 431)

New interfaces `SequencedCollection`, `SequencedSet` and `SequencedMap` give every ordered collection `getFirst`, `getLast`, `addFirst`, `addLast`, `removeFirst/Last` and `reversed()` (maps: `firstEntry`, `lastEntry`, `pollFirstEntry`, `putFirst`, …). Full coverage: Chapter 10 §10.11. `code/ch17/v21/SequencedDemo.java`:

```
List<String> list = new ArrayList<>(List.of("b", "c"));
list.addFirst("a"); list.addLast("d");
LinkedHashSet<Integer> set = new LinkedHashSet<>(List.of(3, 1, 2));
set.addFirst(2);                                    // moves an existing element to the front
SequencedMap<String, Integer> map = new LinkedHashMap<>();
map.put("x", 1); map.put("y", 2); map.putFirst("w", 0);
```

Output:

```
[a, b, c, d] first=a last=d reversed=[d, c, b, a]
[2, 3, 1] reversed=[1, 3, 2]
{w=0, x=1, y=2} firstEntry=w=0 pollLast=y=2 -> {w=0, x=1}
```

Also final in 21

- **Generational ZGC** (JEP 439) — opt-in with `-XX:+UseZGC -XX:+ZGenerational` in 21; default mode from 23, the only mode from 24 (Chapter 16 §16.5).
- **Key Encapsulation Mechanism API** (JEP 452) — `javax.crypto.KEM`, the building block for hybrid and **post-quantum** key exchange.
- **Warnings for dynamically loaded agents** (JEP 451) — attaching a Java agent to a running JVM now prints a warning; tools like Mockito's inline mock maker (Chapter 18) should be loaded with `-javaagent` at start-up.

17.7 Java 22

Unnamed variables and patterns (JEP 456)

Use `_` for anything you must declare but never read: loop variables, `catch` parameters, lambda parameters, try-with-resources variables, and parts of record patterns. It documents intent and silences "unused" warnings. `code/ch17/v22/UnnamedDemo.java`:

```
for (var _ : List.of("a", "b", "c")) count++;                // loop variable not needed
catch (NumberFormatException _) { ... }                      // exception object not needed
m.forEach((k, _) -> System.out.print(k + " "));              // lambda parameter not needed
if (o instanceof Line(Point(var x1, _), Point(var x2, _)))   // ignore the y components
    System.out.println("horizontal distance = " + Math.abs(x2 - x1));
String kind = switch (o) {
    case Line(Point _, Point(int x, int y)) when x == y -> "ends on the diagonal";
    case Line _ -> "a line";                                 // unnamed pattern variable
    default -> "other";
};
```

Output:

```
count = 3
not a number
x y
horizontal distance = 3
a line
```

`_` has been a reserved keyword since Java 9, so no valid old code breaks. You can use several `_` in the same scope.

Foreign Function & Memory API (JEP 454)

What it is: a pure-Java way to call **native** (C) libraries and to work with *off-heap* memory — the safe, fast replacement for JNI (the Java Native Interface, which needed hand-written C glue) and for `sun.misc.Unsafe` memory access. **Key types:** `Linker` (makes a Java `MethodHandle` for a C function), `FunctionDescriptor` (the C signature), `Arena` (owns off-heap memory and frees it when closed), `MemorySegment` (a bounded, checked region of memory), `ValueLayout` (C types like `int`, `long`, pointer).

`code/ch17/v22/ForeignStrlen.java` calls the C library's `strlen`:

```
Linker linker = Linker.nativeLinker();
MethodHandle strlen = linker.downcallHandle(
        linker.defaultLookup().find("strlen").orElseThrow(),
        FunctionDescriptor.of(ValueLayout.JAVA_LONG, ValueLayout.ADDRESS));   // size_t strlen(const char*)

try (Arena arena = Arena.ofConfined()) {                    // off-heap memory freed at the end of the block
    MemorySegment cString = arena.allocateFrom("Hello, native world!");     // UTF-8, NUL-terminated
    long len = (long) strlen.invokeExact(cString);
    MemorySegment ints = arena.allocate(ValueLayout.JAVA_INT, 5);           // like int[5] in C
    for (int i = 0; i < 5; i++) ints.setAtIndex(ValueLayout.JAVA_INT, i, i * i);
}
```

Output of `java -cp out ch17.v22.ForeignStrlen` (warnings go to standard error; path shortened):

```
WARNING: A restricted method in java.lang.foreign.Linker has been called
WARNING: java.lang.foreign.Linker::downcallHandle has been called by ch17.v22.ForeignStrlen in an unnamed module
(file:.../out17/)
WARNING: Use --enable-native-access=ALL-UNNAMED to avoid a warning for callers in this module
WARNING: Restricted methods will be blocked in a future release unless native access is enabled

strlen = 20
off-heap ints: [0, 1, 4, 9, 16], 20 bytes
```

Calling native code can crash the JVM, so such methods are **restricted**: grant access explicitly with `--enable-native-access=ALL-UNNAMED` (or a module name). Real-world users: Apache Lucene (the search library behind Elasticsearch; memory-mapped index files), database drivers, and **bindings** (ready-made Java wrappers for a C library) generated by the **jextract** tool from C header files.

Launch multi-file source-code programs (JEP 458)

`java Main.java` now compiles and runs a program spread over several source files in a directory tree — no build step for small tools and learning. See Chapter 1 §1.10.

Region pinning for G1 (JEP 423)

Native code holding a pointer into a Java array (a JNI "critical region") no longer blocks G1 garbage collection; G1 just avoids moving that one region.

17.8 Java 23

Markdown documentation comments (JEP 467)

Javadoc comments can be written in **Markdown** using `///` lines instead of HTML inside `/** … */`. `code/ch17/v23/MarkdownDoc.java`:

```java
/// JEP 467 (Java 23): documentation comments written in **Markdown**.
///
/// Lines start with `///` instead of the `/** ... */` block, and use Markdown instead of HTML:
///
/// - lists like this one
/// - `inline code` and **bold**
/// - links to program elements: [String#strip()]
///
/// @param <T> the element type (block tags such as `@param` still work)
public class MarkdownDoc<T> {
```

`javadoc -d docs MarkdownDoc.java` turns it into this HTML (real output, the class description block):

```html
<p>JEP 467 (Java 23): documentation comments written in <strong>Markdown</strong>.</p>
<p>Lines start with <code>///</code> instead of the <code>/** ... */</code> block, and use Markdown instead of
HTML:</p>
<ul>
<li>lists like this one</li>
<li><code>inline code</code> and <strong>bold</strong></li>
<li>links to program elements: <a
href="https://docs.oracle.com/en/java/javase/26/docs/api/java.base/java/lang/String.html#strip()" class="external-
link"><code>String.strip()</code></a></li>
</ul>
```

`[String#strip()]` became a link to the JDK's API page — reference links to program elements are the Markdown replacement for `{@link …}`.

Also in 23

- **ZGC generational mode by default** (JEP 474).
- `sun.misc.Unsafe` **memory-access methods deprecated for removal** (JEP 471) — the FFM API and `VarHandle` (a typed handle for reading/writing a variable with chosen memory-ordering guarantees) are the replacements.
- **String templates withdrawn.** They were previewed in 21 (JEP 430) and 22 (JEP 459); a third preview (JEP 465) was proposed for 23 but **withdrawn**, and the feature was removed from JDK 23. The designers decided the syntax (`STR."Hello \{name}"`) and processor model needed rethinking. There is no replacement yet — use `String.formatted` , `+` , `StringBuilder` or `MessageFormat` (Chapter 7 §7.4). Don't trust tutorials from 2023–24 that show `STR.` templates: that code doesn't compile on any current JDK.

17.9 Java 24

Stream gatherers (JEP 485)

`Stream.gather(Gatherer)` adds **custom intermediate operations** — the missing counterpart to custom collectors. Built-ins in `java.util.stream.Gatherers` : `windowFixed` , `windowSliding` , `fold` , `scan` , `mapConcurrent` . Full coverage, including writing your own: Chapter 12 §12.9.
code/ch17/v24/GatherersDemo.java :

```java
Stream.of(1, 2, 3, 4, 5, 6, 7).gather(Gatherers.windowFixed(3)).toList()
Stream.of(1, 2, 3, 4, 5).gather(Gatherers.windowSliding(2)).toList()
Stream.of(1, 2, 3, 4, 5).gather(Gatherers.scan(() -> 0, Integer::sum)).toList()
Stream.of("a", "b", "c").gather(Gatherers.fold(() -> "", String::concat)).toList()
```

Output:

```
[[1, 2, 3], [4, 5, 6], [7]]
[[1, 2], [2, 3], [3, 4], [4, 5]]
[1, 3, 6, 10, 15]
[abc]
```

Class-File API (JEP 484)

What it is: a standard API (`java.lang.classfile`) for reading, writing and transforming `.class` files. **Why:** frameworks and tools (Spring, Hibernate, Mockito, the JDK itself) generate or rewrite bytecode, traditionally with the third-party ASM library, which always lags behind new class-file versions. The JDK's own API is updated in lock-step with each release. `code/ch17/v24/ClassFileDemo.java` parses its own class file:

```
ClassModel cm = ClassFile.of().parse(bytes);
for (MethodModel m : cm.methods()) {
    for (CodeElement e : m.code().get()) {               // walk the bytecode as typed objects
        if (e instanceof Instruction) instructions++;
        if (e instanceof InvokeInstruction inv) calls.add(inv.name().stringValue());
    }
}
```

Output:

```
class   : ch17/v24/ClassFileDemo  (class-file major version 69)
method  : <init>   ()V                        3 instructions, 1 calls [<init>]
method  : square   (I)I                       4 instructions, 0 calls []
method  : main     ([Ljava/lang/String;)V   133 instructions, 36 calls
square(7) = 49
```

Major version 69 = Java 25 (Chapter 1 §1.6). Note how pattern matching (`instanceof InvokeInstruction inv`) makes walking a model natural. Application developers rarely need this API directly.

Virtual threads without pinning (JEP 491)

Before 24, a virtual thread that blocked **inside a `synchronized` block** stayed *pinned* to its carrier OS thread, which could starve the scheduler of free carriers — the standard advice was "replace `synchronized` with `ReentrantLock`". Since 24, virtual threads can release their carrier while holding or waiting for a **monitor** (the lock behind `synchronized`), so that advice is largely obsolete. (Pinning still happens in native frames.) Details: Chapter 15.

Also final in 24

- **Ahead-of-time class loading and linking** (JEP 483): record a **training run** into an AOT cache, start faster in production (Chapter 1 §1.7).
- **Security Manager permanently disabled** (JEP 486): `System.setSecurityManager` throws; `-Djava.security.manager` is an error.
- **Post-quantum cryptography**: ML-KEM key encapsulation (JEP 496) and ML-DSA signatures (JEP 497), standardised by NIST in FIPS 203/204.
- **ZGC non-generational mode removed** (JEP 490), **late barrier expansion for G1** (JEP 475, a JIT-internal simplification of GC barrier code), **linking run-time images without JMODs** (JEP 493, lets `jlink` work on JDKs shipped without the `jmods` folder).
- Integrity warnings: **JNI** use prints a warning unless enabled (JEP 472); **`Unsafe` memory access** prints a warning on first use (JEP 498).

17.10 Java 25 LTS

Compact source files and instance `main` methods (JEP 512)

A source file can now contain just methods and fields — the class around them is implicit — and `main` can be an instance method without `String[] args`. A new class `java.lang.IO` offers `IO.println` and `IO.readln`, and compact source files automatically import all of `java.base`. This is covered with runnable examples in Chapter 1 §1.10 and Chapter 4 §4.9:

```
void main() {
    IO.println("Hello, Java 25");
}
```

It was previewed four times under different names: *Unnamed Classes and Instance Main Methods* (21, JEP 445), *Implicitly Declared Classes…* (22 JEP 463, 23 JEP 477), *Simple Source Files…* (24, JEP 495).

Module import declarations (JEP 511)

`import module M;` imports every public top-level type in every package that module `M` exports (and that it transitively reads through `requires transitive`). It saves long import lists in scripts, prototypes and teaching code; ordinary code can use it too. `code/ch17/v25/ModuleImportDemo.java`:

```
package ch17.v25;

import module java.base;          // JEP 511 (Java 25): imports every package exported by java.base

public class ModuleImportDemo {
    public static void main(String[] args) {
        List<String> words = List.of("modules", "import", "java", "base");
        Map<Integer, List<String>> byLength = words.stream().collect(Collectors.groupingBy(String::length));
        IO.println("by length : " + new TreeMap<>(byLength));               // java.lang.IO: Java 25 (JEP 512)
        IO.println("a path    : " + Path.of("docs", "ch17.md"));
        IO.println("a date    : " + LocalDate.of(2025, 9, 16).getDayOfWeek()); // Java 25 GA day
    }
}
```

Output:

```
by length : {4=[java, base], 6=[import], 7=[modules]}
a path    : docs/ch17.md
a date    : TUESDAY
```

Trade-off: ambiguity. Add `import module java.desktop;` next to `java.base` and a plain `List` becomes ambiguous (`java.util.List` or `java.awt.List`?) — fix it with a normal single-type import (`import java.util.List;`), which always wins over module imports. The importing class does not have to be in a named module: this demo lives on the class path.

Flexible constructor bodies (JEP 513)

Statements may now appear **before** `super(…)` or `this(…)`, as long as they don't use the object being constructed (except to assign its own fields) — validation, computing arguments, early field assignment. **The problem it solves:** validating or computing arguments used to need a static helper or wasted superclass work; and a superclass constructor calling an overridden method saw the subclass's fields still at default values. `code/ch17/v25/FlexibleConstructors.java`:

```
static class Account {
    final String id;
    Account(String id) { this.id = id; describe(); }
    void describe() { System.out.println("  Account(" + id + ")"); }
}
static class SavingsAccount extends Account {
    final double rate;
    SavingsAccount(String id, double rate) {
        if (rate < 0 || rate > 0.2)                                  // validate BEFORE the superclass runs
            throw new IllegalArgumentException("bad rate " + rate);
        this.rate = rate;                                            // allowed: initialise own field early
        super(id.strip().toUpperCase());                             // prepare the argument, then call super
    }
    @Override void describe() {                                     // called from Account's constructor:
        System.out.println("  SavingsAccount(" + id + ", rate=" + rate + ")");   // rate is already set
    }
}
```

Output:

```
  SavingsAccount(SA-1, rate=0.03)
  rejected before any superclass work: bad rate 5.0
```

Before Java 25 the overridden `describe()` would have printed `rate=0.0` (the field wasn't assigned yet). Calling overridable methods from constructors is still a design smell (Chapter 6); this feature makes it safe where it can't be avoided. Not allowed in the **prologue** (the code before `super(…)`): reading fields, calling instance methods, using `this` as a value.

Scoped values (JEP 506)

A `ScopedValue` passes read-only context (the current user, a request ID, a transaction) to code deep in a call chain **without** method parameters — like a `ThreadLocal`, but immutable, automatically unbound when the scope ends (no leaks on thread pools), and cheap to inherit into child threads in **structured concurrency** (still preview, §17.11). Details and comparison with `ThreadLocal`: Chapter 15.
`code/ch17/v25/ScopedValueDemo.java`:

```
static final ScopedValue<String> USER = ScopedValue.newInstance();

static void handle() { audit("read order 17"); }                // no user parameter threaded through
static void audit(String action) {
    System.out.println("  audit: " + (USER.isBound() ? USER.get() : "<anonymous>") + " -> " + action);
}
// main:
ScopedValue.where(USER, "ana").run(ScopedValueDemo::handle); // bound only while run() executes
ScopedValue.where(USER, "bo").run(() -> {
    handle();
    ScopedValue.where(USER, "admin").run(ScopedValueDemo::handle);   // rebinding for a nested scope
    handle();                                                       // back to "bo"
});
handle();                                                            // unbound again
```

Output:

```
  audit: ana -> read order 17
  audit: bo -> read order 17
  audit: admin -> read order 17
  audit: bo -> read order 17
  audit: <anonymous> -> read order 17
bound outside? false
```

Key derivation function API (JEP 510)

`javax.crypto.KDF` derives **keys** from a secret, e.g. with **HKDF** (HMAC-based Key Derivation Function, used by TLS 1.3 and many protocols). `code/ch17/v25/HkdfDemo.java` checks the JDK against test case 1 of RFC 5869, the HKDF standard:

```
KDF hkdf = KDF.getInstance("HKDF-SHA256");
byte[] okm = hkdf.deriveData(HKDFParameterSpec.ofExtract()
        .addIKM(ikm).addSalt(salt).thenExpand(info, 42));    // extract-then-expand, 42 bytes out
```

Output:

```
OKM      = 3cb25f25faacd57a90434f64d0362f2a2d2d0a90cf1a5a4c5db02d56ecc4c5bf34007208d5b887185865
RFC 5869 = 3cb25f25faacd57a90434f64d0362f2a2d2d0a90cf1a5a4c5db02d56ecc4c5bf34007208d5b887185865
match    : true
```

Use `deriveKey("AES", spec)` to get a `SecretKey` instead of raw bytes.

JVM and tooling in 25

JEP	Feature	One line
519	Compact object headers	8-byte object headers with `-XX:+UseCompactObjectHeaders`: smaller heaps (Chapter 16 §16.4)
521	Generational Shenandoah	`-XX:+UseShenandoahGC -XX:ShenandoahGCMode=generational`, now a product feature
514	AOT command-line ergonomics	One-step AOT cache creation: `-XX:AOTCacheOutput=app.aot`
515	AOT method profiling	The AOT cache also stores method profiles, so the JIT warms up faster
518	JFR cooperative sampling	Safer, more robust stack sampling in Flight Recorder
520	JFR method timing and tracing	Time or trace chosen methods via JFR without changing code
503	Remove the 32-bit x86 port	Only 64-bit x86 remains

17.11 Still preview or incubating in Java 25 — and what came next

These are **not** final in Java 25. Don't use them in production code; the book has no runnable examples of them. Each row shows every round up to JDK 27 (GA 15 September 2026).

Feature	History (JEP numbers)	Status in 25	After 25
Structured concurrency — treat a group of subtasks as one unit (fail together, cancel together)	Incubator 19 (428), 20 (437); preview 21 (453), 22 (462), 23 (480), 24 (499)	**Fifth preview** (505)	Sixth preview in 26 (525), seventh in 27 (533)
Primitive types in patterns, `instanceof` and `switch` — e.g. `case int i when i > 0`, `x instanceof byte b`	Preview 23 (455), 24 (488)	**Third preview** (507)	Fourth preview in 26 (530), fifth in 27 (532)
Stable values — lazily initialised constants the JIT can treat as `final`	—	**Preview** (502)	Renamed **Lazy Constants**: second preview in 26 (526), third in 27 (531)
PEM encodings of cryptographic objects — read/write keys and certificates as PEM text (the `-----BEGIN …-----` Base64 format)	—	**Preview** (470)	Second preview in 26 (524), third in 27 (538)
Vector API — portable SIMD computations (`jdk.incubator.vector`)	Incubating since 16; 17 (414) … 24 (489)	**Tenth incubator** (508)	11th incubator in 26 (529), 12th in 27 (537) — waiting for Project Valhalla's value classes (objects without identity, stored as compactly as primitives)
JFR CPU-time profiling (Linux only)	—	**Experimental** (509)	—

To try a preview on JDK 25: `javac --release 25 --enable-preview Foo.java` and `java --enable-preview Foo`; single-file launch: `java --enable-preview --source 25 Foo.java`.

What JDK 26 (GA 17 March 2026) and JDK 27 (GA 15 September 2026) finalised — both non-LTS, noted briefly:

- **26**: HTTP/3 (over the UDP-based QUIC protocol) for the HTTP Client API (517), AOT object caching with any GC (516), G1 throughput improvement by reducing synchronization (522), *Prepare to Make Final Mean Final* (500 — warnings when deep reflection mutates `final` fields), Applet API removed (504).
- **27**: G1 the default collector in all environments (523), compact object headers on by default (534), post-quantum hybrid key exchange for TLS 1.3 (527), JFR in-process data redaction (536).

The next LTS is expected to be **Java 29** (September 2027).

17.12 Upgrading 17 → 21 → 25: removals and deprecations

Change	JEP, release	What breaks / what to do
JDK internals strongly encapsulated	403, 17	Reflection into `sun.*` / `java.*` private members fails → upgrade the library, or `--add-opens` temporarily
Security Manager deprecated → permanently disabled	411 (17) → 486 (24)	Code calling `System.setSecurityManager` fails; remove it
Finalization deprecated for removal	421, 18	Replace `finalize()` with try-with-resources / `Cleaner`
Applet API deprecated → removed	398 (17) → 504 (26)	Nothing for server code
Dynamic agent loading warns	451, 21	Load agents with `-javaagent` at start-up (e.g. Mockito in tests: add the agent to the test JVM)
`sun.misc.Unsafe` memory access deprecated → warns	471 (23) → 498 (24)	Upgrade libraries (Netty, older serializers) to versions using FFM/`VarHandle`
JNI use warns	472, 24	Add `--enable-native-access=…` for libraries that use native code
ZGC non-generational mode removed	490, 24	Drop `-XX:-ZGenerational`
32-bit ports removed	479 (24, Windows x86), 503 (25, x86)	Use 64-bit JDKs
String templates withdrawn	465, 23	Code written against the 21/22 preview must be rewritten

A practical upgrade checklist

1. Run the test suite on the new JDK with `--release` still at the old version, then raise `--release`.
2. Upgrade build plugins (Chapter 18) and bytecode-heavy libraries first (Lombok, Mockito, Byte Buddy, Spring, Hibernate): they must understand the new class-file version.
3. Run `jdeps --jdk-internals your.jar` to find uses of JDK internals and `jdeprscan your.jar` to find deprecated APIs.
4. Watch the startup warnings (agents, JNI, `Unsafe`) — they become errors in future releases.
5. Re-check GC and memory settings; defaults changed (generational ZGC, compact headers in 27).

17.13 In the interview

Q: What changed in Java between 17 and 21, and between 21 and 25? 17 → 21: pattern matching for `switch` and record patterns (with sealed types, a new data-oriented style), **virtual threads**, sequenced collections, generational ZGC. 21 → 25: unnamed `_` variables, the Foreign Function & Memory API, stream gatherers, the Class-File API, virtual threads no longer pinned by `synchronized`, and in 25

itself compact source files with instance `main`, module import declarations, flexible constructor bodies, scoped values and AOT start-up improvements.

- *Is structured concurrency final?* No — it is still in preview (fifth preview in 25, seventh in 27).
- *What happened to string templates?* Previewed in 21 and 22, withdrawn in 23; no replacement yet.
- *Why upgrade from 21 to 25?* LTS support horizon, no `synchronized` pinning with virtual threads, faster start-up with AOT caches, smaller heaps with compact object headers, and the new language conveniences.
- *Can you use a preview feature in production?* Technically with `--enable-preview`, but it may change or disappear in the next release and class files compiled with previews only run on that exact release — so no.

Chapter TL;DR

- Status words matter: **final** = use it; **preview/incubator/experimental** = experiments only; **withdrawn** = gone. Check the JEP title on openjdk.org.
- **17**: sealed classes, new random generators, strong encapsulation (plus records, text blocks, `switch` expressions, `instanceof` patterns from 14–16).
- **18**: UTF-8 by default, `jwebserver`, `@snippet`. **19–20**: previews only.
- **21 LTS**: pattern matching for `switch`, record patterns, **virtual threads**, sequenced collections, generational ZGC.
- **22**: `_` unnamed variables and patterns, **FFM API**, multi-file source launch. **23**: Markdown doc comments; string templates withdrawn.
- **24**: **stream gatherers**, Class-File API, virtual threads without `synchronized` pinning, AOT class loading, Security Manager disabled, ML-KEM/ML-DSA.
- **25 LTS**: compact source files + instance `main` + `IO`, `import module`, flexible constructor bodies, **scoped values**, KDF API, compact object headers (opt-in), generational Shenandoah.
- Still preview in 25: structured concurrency, primitive patterns, stable values (→ lazy constants), PEM; Vector API incubating. JDK 26/27 finalised HTTP/3, G1-everywhere and compact headers by default.
- Next: Chapter 18 — Testing, build and tooling.