Chapter 5 — Linear and Logistic Regression

Linear regression and logistic regression are the "hello world" of machine learning — and they are still everywhere in production: as baselines (simple reference models any fancier model must beat), as the final layer of neural networks (models built from layers of simple numeric units), as click-through-rate models (predicting the share of shown items that get clicked), credit scores and A/B-test analyses (experiments that compare two versions on random groups of users). They are also the best place to learn the machinery every other model uses: a **model**, a **loss function**, and an **optimizer** (gradient descent) that lowers the loss.

What you'll learn

1. The supervised-learning workflow end to end, on a small real dataset.
2. Linear regression: the model, the MSE loss, and two ways to fit it — the normal equation and gradient descent — both written in NumPy and checked against scikit-learn.
3. Gradient descent in practice: learning rate, batch vs mini-batch vs stochastic, and why feature scaling changes everything.
4. The assumptions of linear regression and how to check them with residual plots.
5. Polynomial regression and how model complexity leads to under- and over-fitting.
6. Regularization: Ridge (L2), Lasso (L1), ElasticNet — with coefficient-path plots.
7. Logistic regression: sigmoid, log-loss, decision boundary, gradient descent from scratch vs scikit-learn.
8. Multiclass: one-vs-rest and softmax.
9. How to interpret coefficients (and when not to trust them).

All code is in `code/` and runs with the shared environment (Python 3.14, scikit-learn 1.9, NumPy 2.5). Outputs are real; timings will differ on your machine.

5.1 The supervised-learning workflow

What it is

Supervised learning means learning from **labeled data** — examples where the correct answer is attached (an email marked "spam", a house with its sale price). The model studies these examples, finds the pattern linking inputs to answers, and then predicts answers for new, **unseen** examples. It's called "supervised" because the answer key guides training, like a student checking homework against a teacher's marked solutions.

- **Regression** = the answer is a number (price, temperature, petal length).
- **Classification** = the answer is a category (spam / not spam, species).

How it works — the steps

1. **Get data.** Download a public dataset (Kaggle and the UCI repository are well-known websites hosting free datasets; `sklearn.datasets` ships some with scikit-learn) or collect your own; it may arrive as CSV (a plain-text table, one row per line), Excel, database tables or text.
2. **Inspect and clean.** Look for missing values (`NaN`, blanks). Drop rows or columns that are mostly empty and unimportant, or **impute** (fill in) with the mean, median, mode (the most common value) or a default. Some models refuse missing values entirely; others just get worse.
3. **Encode categories.** Models need numbers. **Label (integer) encoding** maps Red → 0, Blue → 1, Green → 2 — fine for trees, but it tells a linear model that Green > Blue > Red, which is meaningless. **One-hot encoding** creates `is_Red`, `is_Blue`, `is_Green` 0/1 columns and avoids the fake order. (Chapter 4 covers all encoders.)
4. **Split** into training and test sets — commonly 80/20 or 70/30 — so you measure performance on data the model has never seen.
5. **Choose a model**, fit it on the training set.

6. **Evaluate** on the test set with a suitable metric, and compare with a trivial baseline (e.g. always predicting the average).
7. **Iterate** — features, model, hyperparameters (settings you choose before training, such as tree depth; Chapter 6).

Choosing between linear regression and a decision tree

	Linear regression	Decision tree
Task	Regression (logistic regression for classification)	Regression and classification
How it works	Fits a line / plane / **hyperplane** (a flat surface in many dimensions) that minimises squared error	Splits the data with if-then questions into groups with similar outcomes
Strengths	Simple, fast, interpretable coefficients, extrapolates (extends beyond the data seen) a trend	Captures non-linear patterns and interactions (one feature's effect depending on another), handles mixed feature types, easy to visualise
Weaknesses	Misses non-linear patterns unless you engineer features	Overfits (memorises training noise) if grown too deep; can't extrapolate beyond training range
Pick it when	The relationship looks roughly linear (e.g. weight vs height)	The data has clear thresholds or if-then structure

(Chapter 7 covers trees in depth.)

The workflow in code

Predict **petal length** from the other iris measurements plus the species (one-hot encoded):

```
# code/supervised_walkthrough.py
iris = load_iris(as_frame=True)                          # bundled with sklearn, no download
df = iris.frame.rename(columns=lambda c: c.replace(" (cm)", "").replace(" ", "_"))
df["species"] = iris.target_names[df.pop("target")]
print(df.head(3).to_string(), "\n")
print("missing values (total):", df.isna().sum().sum())

X = pd.get_dummies(df.drop(columns="petal_length"), columns=["species"], dtype=int)
y = df["petal_length"]
X_tr, X_te, y_tr, y_te = train_test_split(X, y, test_size=0.2, random_state=42)   # 80/20

lin = LinearRegression().fit(X_tr, y_tr)
print("coefficients:", {c: round(float(w), 3) for c, w in zip(X.columns, lin.coef_)})
print("intercept:", round(float(lin.intercept_), 3))
for name, m in [("linear regression", lin),
                ("tree, no depth limit", DecisionTreeRegressor(random_state=0)),
                ("tree, max_depth=3", DecisionTreeRegressor(max_depth=3, random_state=0))]:
    m.fit(X_tr, y_tr)
    print(name, mean_squared_error(y_tr, m.predict(X_tr)), mean_squared_error(y_te, m.predict(X_te)))
```

Output:

```
   sepal_length  sepal_width  petal_length  petal_width species
0           5.1          3.5           1.4          0.2  setosa
1           4.9          3.0           1.4          0.2  setosa
2           4.7          3.2           1.3          0.2  setosa

missing values (total): 0
model inputs: ['sepal_length', 'sepal_width', 'petal_width', 'species_setosa', 'species_versicolor',
'species_virginica']

coefficients: {'sepal_length': 0.585, 'sepal_width': -0.145, 'petal_width': 0.64, 'species_setosa': -1.144,
'species_versicolor': 0.315, 'species_virginica': 0.829}
intercept: 0.019

y range: 1.0 to 6.9 cm, std 1.77
model                        train MSE  test MSE
baseline (predict mean)                     3.302
linear regression                0.061     0.088
tree, no depth limit             0.001     0.142
tree, max_depth=3                0.078     0.121
```

Interpreting the result. **MSE** (mean squared error) is in squared units (cm²), and "lower is better" only means something against the target's scale and a baseline. Petal length spans 1–6.9 cm; predicting the mean gives MSE 3.3, so 0.088 (an average error of roughly $\sqrt{0.088} \approx 0.3$ cm) is good, while an MSE of 5 would be worse than guessing the mean. The unlimited tree scores almost 0 on training data but worse on test: it **overfit** (memorised the training set). Limiting `max_depth` (or raising `min_samples_split`) trades a bit of training accuracy for better generalisation (performance on new, unseen data).

One subtlety: the three species columns always sum to 1, which duplicates the intercept (the **dummy-variable trap**). `LinearRegression` still works — it returns the minimum-norm solution (of all equally good weight sets, the one with the smallest weights), which is why the three species coefficients sum to 0 — but the individual species coefficients are then only meaningful relative to each other. Use `drop="first"` in `OneHotEncoder` (or `drop_first=True` in `get_dummies`) if you want each one read against a reference species.

Self-check

1. Test MSE 0.088 — good or bad? → Only meaningful against the target's scale and a baseline: the mean-predictor scores 3.3, so it's good.
2. Train MSE 0.001, test MSE 0.142 — what happened? → Overfitting: the model memorised the training set.
3. Why one-hot rather than integer-encode `species` for linear regression? → Integers impose a fake order and equal spacing.

TL;DR

Get data → clean → encode → split → fit → evaluate against a baseline → iterate. Linear models for roughly linear trends; trees for thresholds and interactions, with depth limits against overfitting.

5.2 Linear regression: model and loss

What it is

Linear regression predicts a number as a weighted sum of the features plus a constant:

$\hat{y} = w_1 x_1 + w_2 x_2 + \ldots + w_d x_d + b = \mathbf{w \cdot x + b}$

- $\hat{y}$ ("y-hat") — the prediction.
- $x = (x_1 \ldots x_d)$ — the **feature vector** for one example.
- w — the **weights** (coefficients): how much $\hat{y}$ changes when that feature increases by 1, holding the others fixed.
- b — the **bias** or **intercept**: the prediction when all features are 0.

With one feature it's a line; with two, a plane; with more, a hyperplane. A trick used in all the maths: add a constant feature $x_0 = 1$ to every example, so b becomes weight w_0 and the model is just $\hat{y} = \theta^T x$ (θ = all parameters).

The loss: mean squared error

Training means choosing θ to make predictions close to the targets. For m training examples, the **mean squared error** is:

$MSE(\theta) = (1/m)\ \Sigma_i\ (\hat{y}_i - y_i)^2$

Worked example: targets y = (3, 5, 7), predictions $\hat{y}$ = (2.5, 5, 8). Errors = (−0.5, 0, 1). Squared = (0.25, 0, 1). MSE = 1.25/3 = **0.417**. RMSE (root mean squared error) = $\sqrt{0.417}$ = 0.65 (back in the target's units).

Why squares? They make every error positive, punish big errors more than small ones, and give a smooth bowl-shaped (convex) function with a single minimum that calculus can find. Minimising MSE is also what you get from **maximum likelihood** (choosing the parameters under which the observed data is most probable) if the noise is Gaussian (normally distributed, bell-shaped).

Self-check

1. Errors (1, −1, 2): MSE? → (1 + 1 + 4)/3 = 2.
2. What does the intercept b mean? → The prediction when every feature is 0.
3. Why is the MSE "bowl" easy to minimise? → It's convex: one minimum, no local traps.

TL;DR

$\hat{y} = w \cdot x + b$; fit by minimising the average squared error, a convex bowl with one minimum.

5.3 Fitting it: the normal equation vs gradient descent

What it is

Two ways to find the bottom of the MSE bowl:

1. **Normal equation** — solve for θ directly in one step with linear algebra.
2. **Gradient descent (GD)** — start somewhere, repeatedly step downhill until you reach the bottom.

Analogy: the normal equation is reading the lowest point off a map; gradient descent is walking downhill in fog, feeling the slope under your feet.

How it works

Normal equation. At the bottom of the bowl the slope is zero. The gradient of MSE is $(2/m)\ X^T(X\theta - y)$ (derived just below); setting it to zero gives $X^TX\theta = X^Ty$ — the "normal equations" — and, if X^TX is invertible (has an inverse, so the equations have exactly one solution):

$\theta = (X^TX)^{-1}\ X^Ty$

where X is the m × (d+1) matrix of examples (with the column of 1s) and y the vector of targets. In code, never compute the inverse explicitly; solve the linear system $X^TX\ \theta = X^Ty$ (`np.linalg.solve`) or use a least-squares routine (`np.linalg.lstsq`, which uses the SVD, singular value decomposition, a standard way of factoring a matrix, and also works when X^TX is not invertible). scikit-learn's `LinearRegression` calls SciPy's (the scientific-computing library built on NumPy) least-squares solver.

Gradient descent. The gradient (vector of slopes) of MSE is:

$\nabla MSE(\theta) = (2/m)\ X^T(X\theta - y)$

Why: $MSE = (1/m)\ \Sigma_i\ (\theta^T x_i - y_i)^2$. By the chain rule (the calculus rule for nested functions: multiply the slopes of each layer), the derivative of one squared term with respect to weight θ_j is $2(\theta^T x_i - y_i) \cdot x_{ij}$ — "twice the error times that feature". Averaging over the m examples and stacking all j gives $(2/m)\ X^T$(error vector).

Then repeat: **θ ← θ − η ∇MSE(θ)**, where η (eta) is the **learning rate** (step size). Each full pass over the training data is an **epoch**.

Worked single step on one feature, data x = (1, 2), y = (2, 4), starting at w = 0, b = 0, η = 0.1:

- predictions (0, 0); errors (−2, −4)
- ∂/∂b = (2/2)(−2 − 4) = −6; ∂/∂w = (2/2)(1·−2 + 2·−4) = −10
- new b = 0 − 0.1·(−6) = 0.6; new w = 0 − 0.1·(−10) = 1.0 → already heading toward the true line y = 2x.

```
# code/linreg_from_scratch.py (key parts)
def add_bias(X):
    return np.c_[np.ones(len(X)), X]                  # column of ones -> intercept is w0

def normal_equation(X, y):
    Xb = add_bias(X)
    return np.linalg.solve(Xb.T @ Xb, Xb.T @ y)         # solves (X^T X) theta = X^T y

def batch_gd(X, y, lr=0.1, epochs=1000):
    Xb = add_bias(X)
    theta = np.zeros(Xb.shape[1])
    for _ in range(epochs):
        err = Xb @ theta - y
        theta -= lr * (2 / len(y)) * Xb.T @ err         # gradient step on MSE
    return theta

x = 2 * rng.random((100, 1)); y = 4 + 3 * x[:, 0] + rng.normal(0, 1, 100)    # truth: b=4, w=3
# ... then the 10-feature diabetes dataset, standardized, compared with sklearn
```

Output:

```
normal equation  [b, w]: [3.949 3.038]
batch GD         [b, w]: [3.949 3.038] (MSE 51.39 -> 0.959)
sklearn          [b, w]: [3.949 3.038]

method            test MSE   max |diff vs sklearn|      time
normal eq.          3424.3               1.46e-12    0.07ms
batch GD            3424.6               2.68e-01   35.06ms
sklearn             3424.3               0.00e+00
baseline (predict train mean) test MSE: 5134.8
GD after 5000 epochs, coef for s1, s2 (correlated pair): [-31.   15.1] exact: [-31.2  15.3]

largest standardized effects (+1 std in feature -> change in disease score):
    s5:   +35.8
    s1:   -31.2
   bmi:   +27.5
    s2:   +15.3
intercept = mean training target: 151.6 = 151.6
```

All three methods agree on the toy problem (3.949, 3.038 — close to the true 4 and 3; the gap is noise). On the diabetes data the normal equation matches scikit-learn to 12 decimal places. Gradient descent is close but still slightly off after 5,000 epochs on the coefficients of `s1` and `s2` — two strongly correlated blood-serum measurements that create a long, narrow valley in the loss surface (the loss drawn as a landscape over all weight values) where GD crawls (section 5.4 shows why). Because the features are standardized (mean 0), the intercept equals the mean training target.

Trade-offs

	Normal equation / least squares	Gradient descent
Result	Exact, one shot	Approximate, iterative
Hyperparameters	None	Learning rate, epochs (and batch size)
Cost	About $O(m \cdot d^2)$ to form X^TX plus $O(d^3)$ to solve — fine for d up to a few thousand	$O(m \cdot d)$ per epoch; scales to huge m and d
Memory	Needs X^TX ($d \times d$)	Can stream mini-batches from disk
Feature scaling	Not needed	Needed for fast convergence
Works for other losses	Only squared error (and Ridge)	Any differentiable loss — logistic regression, neural networks

(The O(…) "big-O" notation says how cost grows with m rows and d features, ignoring constant factors: $O(d^3)$ means doubling the features makes solving about 8× slower. *Mini-batches* are small chunks of rows, §5.4; a *differentiable* loss is one smooth enough to have a slope everywhere.)

When not to use each

- Don't use the normal equation when d is very large (tens of thousands of features) or data doesn't fit in memory.
- Don't hand-roll GD when a closed form (a direct formula for the answer) or a well-tuned library solver exists — use it for learning and for losses without closed forms.

Common mistakes

- Computing `np.linalg.inv(X.T @ X)` explicitly — slower and numerically less stable (more prone to rounding errors) than `solve` / `lstsq`.
- Forgetting the column of ones (no intercept).
- Running GD on unscaled features and concluding "GD doesn't work".

Real-world examples

- `LinearRegression` in scikit-learn (least squares via SciPy); `statsmodels` OLS (ordinary least squares) for statistical inference (p-values: how likely a result this strong would be by pure chance; confidence intervals: ranges of plausible values).
- `SGDRegressor` / `SGDClassifier` and Vowpal Wabbit fit linear models one small batch at a time with SGD (stochastic gradient descent, §5.4), so the dataset never has to fit in RAM (the computer's working memory).
- Every neural network is trained by variants of gradient descent (SGD with momentum, Adam: refinements that smooth the step direction and adapt the step size per weight).

In the interview

30 seconds: *"Linear regression minimises MSE. You can solve it exactly with the normal equation, $\theta = (X^TX)^{-1}X^Ty$ — in practice with a least-squares solver — which is cheap when there are few features. Gradient descent iterates $\theta \leftarrow \theta - \eta \cdot (2/m)X^T(X\theta - y)$; it scales to huge data, works for any differentiable loss, but needs a learning rate and scaled features."*

- *"When would the normal equation fail?"* — X^TX singular (non-invertible: duplicate or perfectly collinear features, or more features than rows); use the pseudo-inverse (a generalised inverse that still returns a least-squares answer, computed with the SVD) or Ridge, which makes $X^TX + \alpha I$ invertible (I is the identity matrix: 1s on the diagonal, 0s elsewhere).
- *"Is the MSE loss convex?"* — Yes, for linear regression; GD with a small enough learning rate reaches the global minimum.

Self-check

1. Write the GD update for linear regression. → $\theta \leftarrow \theta - \eta \ (2/m) \ X^T(X\theta - y)$.

2. Why add a column of ones? → So the intercept is learned as an ordinary weight.
3. Which scales better to 10 million features: normal equation or GD? → GD.
4. Why did GD lag on `s1`/`s2`? → Correlated features make a narrow valley; GD needs many steps along it.

TL;DR

Normal equation: exact, no tuning, $O(d^3)$ — great for small d. Gradient descent: iterative, scalable, general — needs a learning rate and scaled features.

5.4 Gradient descent in practice

What it is

Gradient descent comes in three flavours, differing only in **how many examples are used to compute each gradient**:

Variant	Examples per update	Updates per epoch (m = 100)	Behaviour
Batch GD	All m	1	Smooth, exact gradient; slow per step on big data
Mini-batch GD	A batch, e.g. 16–512	m / batch size (100/16 → 7)	Noisy but efficient; uses vectorised hardware (GPUs, graphics chips built for parallel arithmetic); the default in deep learning
Stochastic GD (SGD)	1	m (100)	Very noisy, cheap steps; noise can escape shallow local minima (dips that are lowest only nearby); never settles unless the learning rate decays

How it works

1. Shuffle the training data at the start of each epoch.
2. For each batch, compute the gradient on that batch only and take a step.
3. Optionally decay the learning rate over time (a **learning-rate schedule**), e.g. $\eta_t = \eta_0 / (1 + k \cdot t)$, so the noisy steps shrink and the parameters settle.

```python
# code/gd_variants.py (key parts)
def run(Xb, y, lr, epochs, batch_size, seed=0, lr_decay=False):
    rng = np.random.default_rng(seed)
    theta, step = np.array([-1.0, -1.0]), 0
    for epoch in range(epochs):
        idx = rng.permutation(len(y))                    # reshuffle every epoch
        for start in range(0, len(y), batch_size):
            b = idx[start:start + batch_size]
            eta = lr / (1 + 0.05 * step) if lr_decay else lr
            theta = theta - eta * mse_grad(Xb[b], y[b], theta)
            step += 1
    return theta

run(Xb, y, lr=0.1, epochs=50, batch_size=100)            # batch
run(Xb, y, lr=0.1, epochs=8,  batch_size=16)             # mini-batch
run(Xb, y, lr=0.1, epochs=1,  batch_size=1, lr_decay=True)  # stochastic
```

Output:


```
lr=0.01  MSE after 60 epochs: 1.37
lr=0.1   MSE after 60 epochs: 0.963
lr=0.6   MSE after 60 epochs: 1.92e+23


exact (normal eq.): [3.949 3.038]
batch (m=100)               updates=  50  final=[3.762 3.203]
mini-batch (16)             updates=  56  final=[3.814 3.109]
stochastic (1), decaying lr  updates= 100  final=[3.574 3.434]
unscaled      condition number        36  lr=1.36e-02  iterations to converge: 485
standardized  condition number         1  lr=4.86e-01  iterations to converge: 5
```

The learning rate

- **Too small** (0.01): steady but slow — still at MSE 1.37 after 60 epochs.
- **Good** (0.1): reaches the minimum (≈ 0.96, the noise level).
- **Too large** (0.6): every step overshoots further; the loss explodes to 10^{23} — **divergence**.

For MSE the rule is concrete: GD converges if $\eta < 2/\lambda_{max}$, where λ_{max} is the largest eigenvalue (the stretch factor along the matrix's steepest direction, Chapter 2) of the loss's curvature matrix (the **Hessian**, here $(2/m)X^TX$). In practice you try values on a log scale (0.001, 0.01, 0.1, …) and watch the loss curve.






Batch GD moves in a smooth line; mini-batch wiggles; SGD bounces around the minimum and only settles because its learning rate decays. With equal numbers of updates, batch GD saw 50× more data than SGD — in terms of *compute*, SGD and mini-batch are far cheaper per unit of progress on large datasets, which is why they dominate.

Why feature scaling matters for GD

If one feature has a much larger spread than another, the MSE bowl becomes a long, narrow valley. The learning rate must be small enough for the steep direction (or it diverges), which makes progress along the flat direction painfully slow. The **condition number** (λ_max / λ_min) measures how stretched the bowl is: GD's number of steps grows roughly in proportion to it.



Here a feature with 6× the spread of the other gives a condition number of 36 and needs **485** iterations; after standardizing both features the bowl is round (condition number ≈ 1) and GD converges in **5**. With 100× spread the unscaled version needs well over 100,000 iterations. Correlated features (like `s1` / `s2` in the diabetes data) stretch the bowl too — scaling doesn't fully fix that; regularization helps.

Trade-offs / common mistakes

- Batch size: larger batches give smoother gradients and better hardware use, but fewer updates per epoch; very large batches may need a larger learning rate or warm-up (starting with a small learning rate and ramping it up over the first steps).
- Forgetting to shuffle — batches become unrepresentative (e.g. sorted by class).
- Judging SGD by its final iterate (the parameter values after the last step) without a decaying learning rate — it keeps bouncing.
- Stopping by a fixed number of epochs instead of monitoring validation loss (**early stopping**, Chapter 6).

In the interview

30 seconds: *"Batch GD uses all data per step — smooth but expensive; SGD uses one example — cheap and noisy, needs a decaying learning rate; mini-batch is the practical middle ground and fits GPUs. The learning rate is the key hyperparameter: too small is slow, too large diverges. Scale features first — otherwise the loss surface is a narrow valley and GD zig-zags or crawls."*

- *"Why does SGD sometimes generalise better?"* — Its noise acts like a regularizer (anything that discourages overfitting; §5.7) and can escape sharp minima; this is an empirical observation in deep learning, not a guarantee.
- *"How do you pick a learning rate?"* — Log-scale search, look at the training-loss curve; or a learning-rate range test (raise the rate a little every step and note where the loss starts to blow up); then add a schedule.

Self-check

1. With m = 1,000 and batch size 50, how many updates per epoch? → 20.
2. What happens with η above 2/λ_max on MSE? → Divergence.
3. Why does scaling speed up GD? → It makes the loss bowl rounder (lower condition number), so one learning rate suits all directions.

TL;DR

Batch = exact and slow, SGD = noisy and cheap, mini-batch = the default. Tune the learning rate on a log scale, decay it for SGD, and always scale features.

5.5 Assumptions of linear regression

What it is

Linear regression will always return *some* line. Whether that line's **predictions** are good and its **coefficients and p-values** are trustworthy depends on assumptions:


Assumption	Meaning	If violated
Linearity	y is a linear function of the (possibly transformed) features	Systematic errors; add polynomial/log terms or use a non-linear model
Independence	Errors of different rows are unrelated	Typical with time series or repeated measures (several rows from the same subject); standard errors (estimated uncertainty of each coefficient) too small
Homoscedasticity	Error spread is constant across predictions	"Funnel" residuals; coefficients still unbiased (right on average) but standard errors wrong; try log(y) or weighted least squares (noisier rows count less)
Normal errors	Residuals roughly normal	Matters mainly for small-sample confidence intervals and p-values
No (perfect) multicollinearity	Features aren't (near-)copies of each other	Coefficients unstable and hard to interpret (predictions can still be fine)

For pure prediction, linearity and a stable data distribution matter most; the others matter most when you interpret coefficients or report statistical significance (evidence that an effect is unlikely to be pure chance).

How to check: residual plots

A **residual** is $y_i - \hat{y}_i$. Plot residuals against fitted values: a good model leaves a structureless horizontal band around 0.

```
# code/polynomial_and_assumptions.py (residual part)
lin = LinearRegression().fit(x[:, None], y)           # straight line on quadratic data
resid = y - lin.predict(x[:, None])
ax.scatter(lin.predict(x[:, None]), resid); ax.axhline(0)
```



- **U-shape** (left): the straight line misses curvature — add x^2, or transform.
- **Random band** (middle): the quadratic model captures the pattern.
- **Funnel** (right): noise grows with x — heteroscedasticity. Log-transform y, use weighted least squares, or report robust standard errors (uncertainty estimates that stay valid when the error spread varies).

Common mistakes

- Checking only R^2 (the share of the target's variance the model explains) and never plotting residuals.
- Interpreting coefficients causally ("raising x by 1 *causes* y to rise by w"). Regression finds associations in observational data (data recorded as it happened, not from a controlled experiment).

In the interview

30 seconds: *"Linear regression assumes a linear relationship, independent errors with constant variance, roughly normal errors, and no strong multicollinearity. For prediction, linearity and a stable distribution matter most; the rest matter when you interpret coefficients or p-values. I check with a residuals-vs-fitted plot."*

- *"What does a funnel-shaped residual plot mean?"* — Heteroscedasticity: error variance grows with the prediction; log-transform y, use weighted least squares or robust standard errors.

Self-check

1. Residuals form a U shape — what's wrong? → The model misses curvature; add x^2 or transform.
2. Does heteroscedasticity bias the coefficients? → No, it makes their standard errors wrong.
3. Can multicollinearity hurt predictions? → Usually not much; it makes individual coefficients unstable.

TL;DR

Plot residuals vs fitted values: a U means missing non-linearity, a funnel means non-constant variance, and correlated features make coefficients unreliable.

5.6 Polynomial regression

What it is

Polynomial regression is linear regression on polynomial features. For one feature x and degree 2: $\hat{y} = w_2x^2 + w_1x + b$. It is still "linear" — linear in the *weights* — so the same solvers work; only the inputs are expanded (`PolynomialFeatures`).

Why it matters


It is the simplest way to fit curves, and the clearest demonstration of **underfitting vs overfitting**:

- **Underfitting** — the model is too simple to capture the pattern: high error on training *and* test data (high **bias**: systematic error from a model too rigid for the pattern).
- **Overfitting** — the model is so flexible that it fits the noise: low training error, higher test error (high **variance**: the fit changes a lot depending on which training sample it happened to get).

```
# code/polynomial_and_assumptions.py (key parts) — truth: y = 0.5x² + x + 2 + noise, 40 training points
for deg in [1, 2, 15]:
    model = make_pipeline(PolynomialFeatures(deg, include_bias=False), StandardScaler(), LinearRegression())
    model.fit(x[:, None], y)
```

Output:

```
degree  train MSE  test MSE
     1       3.73      2.83
     2       1.14      1.04
    15       0.90      1.35
degree-2 learned: y = 0.54 x^2 + 1.08 x + 2.16   (truth 0.5, 1, 2)
```



Degree 2 recovers the true coefficients (0.54, 1.08, 2.16 vs 0.5, 1, 2). Degree 15 has the *lowest training error* but a higher test error, and its curve wiggles between points and shoots off at the edges. (Here the test points lie inside the training range; outside it, a degree-15 polynomial is wildly wrong.) The noise level is 1.0 (variance of the added noise), so a test MSE ≈ 1.0 is the best any model can do.

Trade-offs / when not to use it

- Features explode with degree and number of inputs: d features at degree k gives C(d+k, k) − 1 columns (10 features at degree 2 → 65; at degree 3 → 285).
- High-degree polynomials are unstable at the edges and extrapolate badly. For smooth curves prefer low degrees, **splines** (smooth curves built from short low-degree polynomial pieces joined end to end; `SplineTransformer`) or tree/boosting models.
- Always scale after expanding: x^{15} dwarfs x.

In the interview

30 seconds: *"Polynomial regression expands the inputs with powers and products and fits an ordinary linear model — linear in the weights. The degree is a complexity knob: too low underfits, too high overfits and extrapolates wildly. I'd choose the degree, or add Ridge, using validation data."*

Self-check

1. Is polynomial regression a linear model? → Yes, linear in its parameters.
2. Degree-15 has the lowest training MSE — why not use it? → It fits noise; test error is higher.
3. How many degree-2 features from 3 inputs (no bias)? → 3 + 3 squares + 3 pairwise = 9.

TL;DR

Expand features with powers and products, then fit a linear model. Too low a degree underfits; too high overfits — pick the degree (or regularize) using validation data.

5.7 Regularization: Ridge, Lasso, ElasticNet

What it is

Regularization adds a penalty on the size of the weights to the loss, so the model prefers simpler explanations. It's like a budget: the model can still use features, but each unit of weight costs

something, so it only spends where the data strongly justifies it.

Model	Penalty	scikit-learn objective	Effect
Ridge (L2)	$\alpha \sum w_j^2$	$\|y - Xw\|^2 + \alpha\|w\|_2^2$	Shrinks all weights smoothly toward 0; never exactly 0; splits weight among correlated features
Lasso (L1)	$\alpha \sum \|w_j\|$	$(1/2m)\|y - Xw\|^2 + \alpha\|w\|_1$	Sets some weights **exactly 0** → automatic feature selection; picks one of a correlated group
ElasticNet	mix of both	$(1/2m)\|y - Xw\|^2 + \alpha \cdot r\|w\|_1 + \frac{1}{2}\alpha(1 - r)\|w\|_2^2$	Sparse (many weights exactly 0) *and* stable with correlated features; r = `l1_ratio`

Notes:

- **α** (alpha) is the regularization strength: α = 0 is plain least squares; large α pushes weights toward 0. Note that Ridge's and Lasso's α are on different scales in scikit-learn (Ridge's squared-error term is a sum, Lasso's is divided by 2m), so the same α means different amounts of shrinkage.
- The **intercept is not penalized**.
- **Scale features first.** The penalty treats all weights equally, so it only makes sense if features are on the same scale.
- In logistic regression and SVMs (support vector machines, Chapter 8), scikit-learn uses **C = 1/regularization strength** instead: *smaller* C means *stronger* regularization.

Why it matters

- Reduces overfitting when there are many features relative to rows, or correlated features.
- Makes $X^TX + \alpha I$ always invertible, so Ridge has a closed form: $\theta = (X^TX + \alpha I)^{-1}X^Ty$ (with the intercept left unpenalized).
- Lasso gives compact, interpretable models.

Why does L1 produce exact zeros and L2 doesn't? Geometrically, the L1 "budget" region is a diamond with corners on the axes; the loss contours usually first touch it at a corner, where some weights are 0. The L2 region is a circle with no corners. Computationally, the L1 penalty's slope is a constant ±α however small the weight, so it keeps pushing a weight all the way to 0; the L2 penalty's slope 2αw fades as w shrinks.

```
# code/regularization.py (key parts) — diabetes data, standardized
ridge_path = np.array([Ridge(alpha=a).fit(X, y).coef_ for a in np.logspace(-2, 4, 60)])
lasso_path = np.array([Lasso(alpha=a, max_iter=50_000).fit(X, y).coef_ for a in np.logspace(-2, 2, 60)])

X_dup = np.c_[X[:, [2]], X[:, [2]] + rng.normal(0, 0.01, (len(X), 1))]    # bmi twice (near-copy)


poly = PolynomialFeatures(2, include_bias=False)                          # 65 features, ~330 rows
models = {"OLS": make_pipeline(poly, StandardScaler(), LinearRegression()),
          "RidgeCV": make_pipeline(poly, StandardScaler(), RidgeCV(alphas=np.logspace(-3, 3, 50))),
          "LassoCV": make_pipeline(poly, StandardScaler(), LassoCV(cv=5, random_state=0)),
          "ElasticNetCV": make_pipeline(poly, StandardScaler(),
                                        ElasticNetCV(l1_ratio=[0.2, 0.5, 0.8], cv=5, random_state=0))}
```

Output:

```
Lasso alpha=0.1 :  9 of 10 coefficients non-zero
Lasso alpha=1   :  7 of 10 coefficients non-zero
Lasso alpha=5   :  5 of 10 coefficients non-zero
Lasso alpha=20  :  3 of 10 coefficients non-zero


bmi duplicated -> OLS: [ 434.3 -389.1]  Ridge(1): [31.5 13.5]  Lasso(1): [44.2  0. ]

model          test MSE    alpha l1_ratio non-zero
OLS                4112      nan      nan       65
RidgeCV            3291   59.636      nan       65
LassoCV            3113    4.256      nan       11
ElasticNetCV       3178    0.754      0.8       41
```



What the numbers show:

- **Sparsity:** as Lasso's α grows, coefficients drop out: 9 → 7 → 5 → 3 non-zero. The last survivors (`bmi`, `s5`) are the strongest predictors.
- **Correlated features:** with `bmi` duplicated, plain least squares produces absurd, opposite-signed weights (+434, −389) that nearly cancel. Ridge shares the weight (31.5 + 13.5 ≈ 45); Lasso keeps one (44.2) and zeroes the other.
- **Generalisation:** with 65 polynomial features and ~330 training rows, unregularized OLS overfits (test MSE 4112). Ridge, Lasso and ElasticNet with α chosen by cross-validation all do much better (≈ 3100–3300); Lasso keeps only 11 of the 65 features. (Honest footnote: on this split plain OLS on the *original* 10 features scores about 2900 — regularization rescues an over-expanded model, but it doesn't make needless features useful.)



Trade-offs

	Ridge	Lasso	ElasticNet
Feature selection	No	Yes	Yes (less aggressive)
Correlated features	Shares weight — stable	Picks one arbitrarily — unstable	Groups them — stable
Closed form	Yes	No (coordinate descent: one weight at a time)	No
When p > n (more features than rows)	Works	Selects at most n features	Works
Good default when	Many small effects	Few features truly matter	Correlated groups + want sparsity

When not to use it

Regularization matters little when you have plenty of rows per feature (diabetes with its raw 10 features: OLS, Ridge, Lasso and ElasticNet all score within about 2% of each other, test MSE ≈ 2900–2950). Don't use Lasso's selected set as "the true causes" — with correlated features its choice can flip between resamples.

Common mistakes

- Regularizing unscaled features.
- Choosing α on the test set — use `RidgeCV` / `LassoCV` / `GridSearchCV`.
- Forgetting that C in `LogisticRegression` is the *inverse* of the strength.

Real-world examples

- Ridge is the classic fix for multicollinearity in econometrics (statistics applied to economic data); L2 "weight decay" (the deep-learning name for an L2 penalty) is standard when training neural networks.
- L1-regularized logistic regression is used for sparse, high-dimensional text and click models (e.g. Google's FTRL-Proximal ad click model from 2013, an online learning method that updates as each example arrives, used L1 to keep models sparse).
- In genomics (thousands of genes, few patients), Lasso and ElasticNet are standard tools for selecting predictive genes.

In the interview

30 seconds: *"Regularization adds a weight penalty to fight overfitting. Ridge (L2) shrinks all weights smoothly and handles correlated features; Lasso (L1) zeroes some weights, doing feature selection; ElasticNet mixes both. Scale features first and tune α with cross-validation."*

- *"Why does Lasso give zeros?"* — The L1 penalty's constant slope pushes small weights all the way to 0; geometrically, the diamond-shaped constraint has corners on the axes.
- *"Ridge vs Lasso with two identical features?"* — Ridge splits the weight equally; Lasso picks one.
- *"Effect of regularization on bias and variance?"* — More regularization → more bias, less variance.

Self-check

1. Large α in Ridge does what? → Shrinks all weights toward 0 (more bias, less variance).
2. Which penalty can do feature selection? → L1 (Lasso, ElasticNet).
3. In `LogisticRegression`, does C = 0.01 mean strong or weak regularization? → Strong.
4. Why scale before regularizing? → The penalty is on raw weights, whose size depends on feature units.

TL;DR

Penalize big weights: L2 shrinks, L1 selects, ElasticNet does both. Scale first, tune α (or C) by cross-validation.

5.8 Logistic regression

What it is

Logistic regression is a linear model for **binary classification** (exactly two possible classes, such as spam / not spam). It computes the same weighted sum z = w·x + b (called the **logit**), then squashes it into a probability with the **sigmoid** (logistic) function:

p = P(y = 1 | x) = σ(z) = 1 / (1 + e^−z)

Despite the name, it's a classifier. The name comes from the logistic function it uses.

How it works

1. Sigmoid. σ maps any real number to (0, 1): σ(−2) = 0.119, σ(0) = 0.5, σ(2) = 0.881. Large positive z → close to 1; large negative → close to 0.

2. Log-odds interpretation. Inverting the sigmoid: z = ln(p / (1 − p)). The quantity p/(1 − p) is the **odds** (p = 0.8 → odds 4, "4 to 1"). So logistic regression is linear in the **log-odds**. Each weight w_j says: increasing x_j by 1 adds w_j to the log-odds, i.e. **multiplies the odds by e^w_j** (the **odds ratio**).

3. Decision rule and boundary. Predict class 1 when p ≥ threshold (default 0.5). Since p = 0.5 exactly when z = 0, the **decision boundary** is the set of points where w·x + b = 0 — a straight line (in 2-D) or a hyperplane. Changing the threshold shifts the boundary parallel to itself (Chapter 6 covers choosing thresholds).

4. Loss: log-loss (binary cross-entropy). Squared error would make the optimisation non-convex (a landscape with several dips, where the optimiser can get stuck), so logistic regression uses:

Loss = −(1/m) Σ [y_i ln p_i + (1 − y_i) ln(1 − p_i)]

Only one term is active per example: −ln p if y = 1, −ln(1 − p) if y = 0.

True y	Predicted p	Loss	Reading
1	0.9	−ln 0.9 = 0.105	confident and right: tiny loss
1	0.5	−ln 0.5 = 0.693	unsure
1	0.1	−ln 0.1 = 2.303	confident and wrong: big loss
0	0.1	−ln 0.9 = 0.105	confident and right

It is the negative log-likelihood of the data under a Bernoulli model (a single yes/no trial that comes out 1 with probability p), so minimising it is maximum likelihood. It's convex in the weights, so gradient descent finds the global minimum. There's no closed-form solution, so it must be solved iteratively.

5. Gradient. Remarkably, the gradient has the same form as linear regression's:

∇Loss = (1/m) X^T(σ(Xθ) − y) — "features × (prediction − truth)".

Why, in three steps for one example (p = σ(z), z = θ^Tx):

1. dLoss/dp = −y/p + (1 − y)/(1 − p).
2. The sigmoid's derivative is dp/dz = p(1 − p).
3. Multiply: dLoss/dz = −y(1 − p) + (1 − y)p = **p − y**, and dz/dθ_j = x_j, so dLoss/dθ_j = (p − y)x_j. Averaging over examples gives the formula. (No factor 2 here, because there is no square.)

```python
# code/logreg_from_scratch.py (key parts)
def sigmoid(z):
    return 1 / (1 + np.exp(-z))

def fit_logreg_gd(X, y, lr=0.5, epochs=5000):
    Xb = np.c_[np.ones(len(X)), X]
    theta = np.zeros(Xb.shape[1])
    for _ in range(epochs):
        p = sigmoid(Xb @ theta)
        theta -= lr * Xb.T @ (p - y) / len(y)            # gradient of mean log-loss
    return theta


X, y = make_blobs(n_samples=400, centers=[[-1, -0.5], [1, 0.8]], cluster_std=1.1, random_state=0)
# ... stratified split, StandardScaler fitted on train
theta = fit_logreg_gd(X_tr, y_tr)
sk = LogisticRegression(C=np.inf).fit(X_tr, y_tr)        # C=inf -> no penalty (sklearn >= 1.8)
```

Output:

```
sigmoid(-2) = 0.119
sigmoid(+0) = 0.500
sigmoid(+2) = 0.881
y=1, p=0.9: loss = 0.105
y=1, p=0.5: loss = 0.693
y=1, p=0.1: loss = 2.303
y=0, p=0.1: loss = 0.105

from scratch [b, w1, w2]: [0.092 2.454 1.297]
sklearn      [b, w1, w2]: [0.092 2.454 1.298]
test log-loss scratch 0.4048 | sklearn 0.4048
test accuracy scratch 0.850 | sklearn 0.850
w1 = 2.454: +1 std in x1 multiplies the odds of class 1 by e^w1 = 11.64
```

Our 10-line gradient descent matches scikit-learn's L-BFGS solver (a faster optimiser that also uses an estimate of the loss's curvature) to about three decimals.



The probability changes smoothly across the boundary; points near the line get probabilities near 0.5. That's the model being honestly uncertain about overlapping classes.

scikit-learn details (version 1.8+). `LogisticRegression` is L2-regularized by default with `C=1.0`. The old `penalty=` argument is deprecated: use `C=np.inf` for no penalty, `l1_ratio=1` (with `solver="saga"` or `"liblinear"`) for L1, and a value between 0 and 1 for ElasticNet. The default solver is `lbfgs`.

Trade-offs

Strengths	Weaknesses
Fast to train and serve, tiny model	Linear boundary only (needs feature engineering or kernels, tricks that let linear methods draw curves)
Outputs probabilities that are often reasonably calibrated (a predicted 0.7 comes true about 70% of the time)	Sensitive to correlated features and outliers in X
Coefficients interpretable as odds ratios	On perfectly separable data (a straight line splits the classes with no errors), unregularized weights grow without bound
Convex: one global optimum	Usually beaten by gradient boosting (ensembles of decision trees, Chapter 7) on complex tabular data

When not to use it

Strongly non-linear boundaries without good features (use trees/boosting or neural nets); very high-cardinality (very many distinct values) interactions you can't enumerate.

Common mistakes

- Using `LinearRegression` for a 0/1 target — predictions fall outside [0, 1] and the fit is dominated by easy points.
- Forgetting that the default is regularized (C = 1) — compare coefficients across models only with the same C and scaling.
- Assuming 0.5 is the right threshold for imbalanced data (one class much rarer than the other).

Real-world examples

- **Credit scoring** scorecards are traditionally logistic regression, because regulators and loan officers need to read the coefficients.
- **Ad click-through-rate** prediction at Google and Facebook used large-scale logistic regression (Facebook's 2014 paper fed boosted-tree features into a logistic regression).
- Medical risk scores and the final layer of every neural-network binary classifier (a sigmoid on a linear layer).

In the interview

30 seconds: *"Logistic regression computes a linear score $z = w \cdot x + b$, turns it into a probability with the sigmoid, and is trained by minimising log-loss — convex, so gradient descent finds the global optimum. The decision boundary is the hyperplane $w \cdot x + b = 0$. Each coefficient is a change in log-odds, so e^w is an odds ratio."*

- *"Why not MSE for classification?"* — With a sigmoid, MSE is non-convex and gives weak gradients for confidently wrong predictions; log-loss is convex and punishes them hard.
- *"What happens on perfectly separable data?"* — The unregularized loss keeps decreasing as weights grow, so they diverge; regularization keeps them finite.
- *"Is logistic regression's output calibrated?"* — Often roughly, because log-loss is a proper scoring rule (a loss that is lowest only when the predicted probabilities are the true ones), but check with a reliability curve (a plot of predicted probability against how often the event really happened; Chapter 6).

Self-check

1. $\sigma(0)$? → 0.5.
2. Loss for y = 1, p = 0.25? → $-\ln 0.25 = 1.386$.
3. Coefficient w = 0.7: effect on odds? → Multiplied by $e^{0.7} \approx 2.01$ per unit increase.
4. What does the decision boundary look like in 2-D? → A straight line.

TL;DR

Linear score → sigmoid → probability; train with log-loss (convex, gradient = $X^T(p - y)/m$); boundary is $w \cdot x + b = 0$; coefficients are log-odds.

5.9 Multiclass classification: one-vs-rest and softmax

What it is

Two ways to extend logistic regression to K > 2 classes:

1. **One-vs-rest (OvR)** — train K separate binary classifiers ("class k vs everything else"); predict the class whose classifier is most confident.
2. **Softmax (multinomial) regression** — one model with a weight vector per class, producing K scores $z_k = w_k \cdot x + b_k$, turned into probabilities that sum to 1 by the **softmax** function:

$P(y = k \mid x) = e^{z_k} / \Sigma_j e^{z_j}$

Worked example: scores (2, 1, 0.1) → $e^2 = 7.39$, $e^1 = 2.72$, $e^{0.1} = 1.11$, total 11.21 → probabilities **(0.659, 0.242, 0.099)**. The largest score wins, and the probabilities sum to 1.

The loss is **cross-entropy**: $-(1/m) \Sigma_i \ln P(y_i \mid x_i)$ — the negative log-probability of the correct class. With K = 2 it reduces exactly to binary logistic regression. Its gradient again has the form $X^T(P - Y)/m$, with Y the one-hot labels.

```python
# code/multiclass.py (key parts)
def softmax(Z):
    Z = Z - Z.max(axis=1, keepdims=True)                # subtract row max: avoids overflow
    E = np.exp(Z)
    return E / E.sum(axis=1, keepdims=True)


def fit_softmax_gd(X, y, k, lr=0.5, epochs=3000, l2=0.0):
    Xb = np.c_[np.ones(len(X)), X]
    W = np.zeros((Xb.shape[1], k)); Y = np.eye(k)[y]      # one-hot targets
    for _ in range(epochs):
        grad = Xb.T @ (softmax(Xb @ W) - Y) / len(y)
        grad[1:] += l2 * W[1:]
        W -= lr * grad
    return W

softmax_sk = LogisticRegression(C=10).fit(X_tr, y_tr)                  # multinomial by default
ovr = OneVsRestClassifier(LogisticRegression(C=10)).fit(X_tr, y_tr)     # 3 binary models
```

Output:

```
softmax([2, 1, 0.1]) = [[0.659 0.242 0.099]]  sum = 1.0

test accuracy  softmax(sklearn) 0.978 | OvR 0.978 | softmax(scratch) 0.978
one flower, P(setosa, versicolor, virginica):
  softmax sklearn : [[0.    0.001 0.999]]
  softmax scratch : [0.    0.001 0.999]
  OvR raw scores  : [0.    0.175 0.998] (sum 1.174) -> normalized [[0.    0.149 0.851]]
sklearn softmax coef_ shape: (3, 2) (one weight vector per class)
```



Both reach 97.8% accuracy here, but their probabilities differ: the OvR classifiers are trained independently, so their raw scores don't sum to 1 (1.174) and scikit-learn simply rescales them, giving 0.851 for virginica where softmax says 0.999. The regions differ too — OvR's boundaries come from three separate problems.

Trade-offs

	One-vs-rest	Softmax
Models	K binary models	One joint model
Probabilities	Not naturally normalised	Sum to 1, jointly trained — better calibrated
Parallel training / per-class tuning	Easy	No
Use with	Any binary classifier (e.g. SVMs); multi-label problems	Mutually exclusive classes; neural-network output layers

Also: **one-vs-one** trains K(K−1)/2 pairwise classifiers (used internally by `SVC`). For **multi-label** problems (an item can have several labels at once, e.g. photo tags), use independent sigmoids (OvR), not softmax.

Current scikit-learn (1.9 here) has no `multi_class` argument any more: `LogisticRegression` fits the multinomial (softmax) model for K > 2, and you wrap it in `OneVsRestClassifier` if you want OvR.

In the interview

30 seconds: *"For K classes you can train K one-vs-rest binary models, or one softmax model that outputs K scores and normalises them with e^z / Σe^z, trained with cross-entropy. Softmax gives coherent probabilities for mutually exclusive classes and is the output layer of neural classifiers; OvR works with any binary model and suits multi-label problems."*

- *"Why subtract the max in softmax?"* — Numerical stability: e^1000 overflows (is too large for the computer to represent), and subtracting a constant from all scores doesn't change the result.
- *"Softmax with 2 classes?"* — Equivalent to logistic regression on the score difference.

Self-check

1. softmax(0, 0, 0)? → (1/3, 1/3, 1/3).
2. Multi-label tagging: softmax or sigmoids? → Independent sigmoids.
3. How many classifiers does OvR train for 10 classes? → 10 (one-vs-one: 45).

TL;DR

OvR = K binary models; softmax = one model with normalised probabilities and cross-entropy loss. Use softmax for exclusive classes, sigmoids for multi-label.

5.10 Interpreting coefficients

What it is

A linear model's coefficients are its explanation. Reading them correctly depends on units, scaling and correlations.

How it works

- **Raw units:** w_j = change in $\hat{y}$ per 1-unit increase in x_j, **holding all other features fixed**. Change the unit ($m^2 \to km^2$) and the number changes by a factor of a million — the model doesn't.
- **Standardized features:** w_j = change in $\hat{y}$ per 1 standard deviation (the typical spread of the feature) of x_j. Now magnitudes are comparable across features — a rough importance ranking.
- **Logistic regression:** w_j is a change in log-odds; e^{w_j} is the **odds ratio**. $e^w > 1$ raises the odds, < 1 lowers them.
- **Intercept:** the prediction when all features are 0 (with standardized features: at the average feature values).

```
# code/interpret_coefficients.py (key parts)
price = 50 + 3.0 * size - 1.5 * age + rng.normal(0, 20, n)     # $1000s, size in m², age in years
LinearRegression().fit(np.c_[size, age], price)
LinearRegression().fit(np.c_[size / 1e6, age], price)            # size in km²
make_pipeline(StandardScaler(), LinearRegression()).fit(np.c_[size, age], price)

clf = make_pipeline(StandardScaler(), LogisticRegression(C=0.1, max_iter=5000)).fit(cancer.data, cancer.target)

x2 = x1 + rng.normal(0, 0.05, 300)                                 # near-duplicate feature
# fit on 3 bootstrap resamples
```

Output:

```
raw units      : price = 52.6 + 2.98*size_m2 -1.49*age_years
size in km^2   : coef for size = 2984148  (same model, different units -> different number)
standardized   : +1 std of size -> +137.6, +1 std of age -> -20.8  (comparable importance)

breast cancer (target 1 = benign), standardized features, C=0.1:
  worst texture            coef -0.60  odds ratio e^coef = 0.55
  worst radius             coef -0.54  odds ratio e^coef = 0.58
  worst concave points     coef -0.53  odds ratio e^coef = 0.59
  fractal dimension error  coef +0.27  odds ratio e^coef = 1.31
  compactness error        coef +0.27  odds ratio e^coef = 1.31

bootstrap coefficients for two near-duplicate features (true: 1.0 and 1.0):
  resample 0: w1 = +1.07, w2 = +0.95, sum = 2.02
  resample 1: w1 = +2.91, w2 = -0.92, sum = 2.00
  resample 2: w1 = -1.03, w2 = +3.04, sum = 2.01
```

Reading it:

- Each extra m^2 adds about $2,980 and each year of age subtracts about $1,490 (the price unit is $1000s). In raw units, age's coefficient looks half as big as size's; standardized, size matters about 6.6× more (137.6 vs 20.8), because sizes vary much more than ages.
- In the cancer model, one standard deviation more "worst texture" multiplies the odds of *benign* by 0.55 (about halves them).
- With near-duplicate features, individual coefficients swing wildly between resamples (bootstrap resamples: new datasets drawn at random, with replacement, from the original rows) (even flipping sign), while their **sum** stays stable at ≈ 2. Predictions are fine; the individual numbers are

meaningless. Diagnose with correlations or the **variance inflation factor (VIF)**, a score of how much a coefficient's uncertainty is inflated by its correlation with the other features; fix by dropping/combining features or using Ridge.

Common mistakes

- Comparing raw coefficients across features with different units.
- Reading coefficients causally from observational data.
- Interpreting one coefficient of a correlated group in isolation.
- Forgetting that regularization shrinks coefficients (they are biased toward 0).

In the interview

30 seconds: *"A coefficient is the change in prediction per unit of that feature, holding the others constant. Standardize features to compare magnitudes; in logistic regression exponentiate (compute e to the power of the coefficient) to get odds ratios. Coefficients are unstable under multicollinearity and are associations, not causal effects."*

Self-check

1. Logistic coefficient −0.69: effect on odds? → ×e^−0.69 ≈ 0.5, halves the odds.
2. Why are coefficients of correlated features unstable? → Many weight combinations give nearly the same predictions; small data changes flip between them.
3. How to make coefficient magnitudes comparable? → Standardize the features.

TL;DR

Coefficients = effect per unit (or per std if standardized), holding others fixed; exponentiate logistic coefficients for odds ratios; don't trust individual coefficients of correlated features or read them causally.

Chapter TL;DR

- **Workflow:** data → clean → encode (one-hot for nominal) → split (80/20) → fit → evaluate against a baseline → iterate. MSE only means something relative to the target's scale and a baseline.
- **Linear regression:** $\hat{y} = w \cdot x + b$, minimise MSE (convex). **Normal equation** $\theta = (X^T X)^{-1} X^T y$ (use a solver, not an explicit inverse) — exact, $O(d^3)$, no scaling needed. **Gradient descent** $\theta \leftarrow \theta - \eta(2/m)X^T(X\theta - y)$ — scalable and general, needs a learning rate and scaled features.
- **GD variants:** batch (smooth, costly), stochastic (noisy, needs a decaying learning rate), mini-batch (default). Too-large η diverges (for MSE, $\eta < 2/\lambda_{max}$). Unscaled features → elongated loss bowl → many more iterations.
- **Assumptions:** linearity, independent errors, constant variance, roughly normal errors, no strong multicollinearity. Check residual plots (U = missing curvature, funnel = heteroscedasticity).
- **Polynomial regression:** linear model on expanded features; degree controls under/overfitting.
- **Regularization:** Ridge (L2, shrink, stable with correlated features), Lasso (L1, exact zeros, feature selection), ElasticNet (both). Scale first; tune α (or C = 1/strength) by CV.
- **Logistic regression:** $p = \sigma(w \cdot x + b)$, log-loss (convex, gradient $X^T(p - y)/m$), boundary $w \cdot x + b = 0$, coefficients are log-odds (e^w = odds ratio). In sklearn ≥ 1.8, `C=np.inf` means no penalty.
- **Multiclass:** OvR (K binary models) vs softmax ($e^{z_k}/\Sigma e^{z_j}$ + cross-entropy; coherent probabilities).
- **Coefficients:** per-unit effects holding others fixed; standardize to compare; unstable under multicollinearity; associations, not causes.