Chapter 11 — CNNs and Computer Vision

An image is just a grid of numbers — a 224×224 colour photo is 224 × 224 × 3 = 150,528 numbers. Feeding that into the dense networks of Chapter 10 (networks where every neuron is connected to every input value) works badly: far too many weights, and no notion that neighbouring pixels belong together or that a cat is still a cat when it moves ten pixels to the left. **Convolutional neural networks (CNNs)** fix both problems with one idea: slide a small learnable filter across the image and reuse it everywhere. That idea, plus depth, took computer vision from "barely works" to superhuman on some **benchmarks** (standard shared datasets and scoring rules used to compare models) within a decade.

What you'll learn

1. Convolution: kernels, stride, padding, channels, output-size formula — with a worked 3×3 example.
2. Pooling, and how conv + pool + dense layers make a CNN architecture.
3. Receptive field and why stacks of 3×3 convolutions work.
4. The famous architectures: LeNet → AlexNet → VGG → Inception → ResNet (skip connections) → MobileNet/EfficientNet → Vision Transformer.
5. Transfer learning and fine-tuning.
6. Data augmentation for images.
7. Vision tasks beyond classification: object detection (IoU, NMS, the YOLO idea) and segmentation (the U-Net idea).
8. A small PyTorch CNN on scikit-learn's 8×8 digits, trained on CPU in seconds. (**PyTorch** is a popular Python deep-learning library; **scikit-learn** is Python's classic machine-learning library; the **CPU** is the computer's ordinary general-purpose processor.)

Prerequisites: Chapter 10 (neurons, backprop, optimizers, BatchNorm, dropout, PyTorch training loop). All code is in `code/`; outputs are real.

> **Key terms from Chapter 10, in one breath:** **backprop** (backpropagation) works out how much each weight contributed to the error — that number is the weight's **gradient**; an **optimizer** such as **SGD** (stochastic gradient descent, small steps downhill on mini-batches of data) or **Adam** uses gradients to update the weights; **BatchNorm** (BN) rescales each channel's activations to a steady mean and spread so training is stable; **dropout** randomly switches off units during training so the network can't rely on any single one. The **training loop** repeats: predict, measure the loss, backprop, update.

11.1 Convolution

What it is

A **convolutional layer** slides a small grid of weights — a **kernel** or **filter**, typically 3×3 — over the image. At each position it multiplies the kernel element-wise with the patch of pixels underneath and sums the result into a single number. Doing this at every position produces a new grid called a **feature map** (or activation map). A layer has many kernels, each producing its own feature map, each detecting a different pattern.

Analogy: a flashlight with a stencil. You sweep the same stencil across the whole picture; wherever the picture matches the stencil's pattern, the light shines bright.

The problem it solves

Problem with dense layers on images	How convolution fixes it
Huge parameter counts (150k inputs × 1,000 units = 150M weights for one layer)	**Weight sharing**: one 3×3×3 kernel has 27 weights (+1 bias, a learned constant offset) regardless of image size
Ignores spatial structure — pixel order could be shuffled	**Local connectivity**: each output only looks at a small neighbourhood
A pattern learned in one place must be re-learned in every other place	**Translation equivariance**: shift the input, and the feature map shifts the same way — the same detector works everywhere

Parameter comparison from `code/conv_by_hand.py`:

```
Conv2d(3->16, 3x3) params: 448  vs Linear(32*32*3 -> 16) params: 49168
```

$(3 \cdot 3 \cdot 3 + 1) \cdot 16 = 448$ versus $(3{,}072 + 1) \cdot 16 = 49{,}168$ — and the conv layer's count doesn't change with image size.

How it works — worked 3×3 example

Input X (5×5, one channel) and a vertical-edge kernel K:

```
X =  1 2 0 1 3       K =  1 0 -1
     0 1 3 2 1            1 0 -1
     2 1 0 1 0            1 0 -1
     1 0 2 3 1
     0 2 1 0 2
```

1. Place K on the top-left 3×3 patch [[1,2,0],[0,1,3],[2,1,0]]. Multiply element by element and add: left column (1+0+2)·1 + middle column ·0 + right column (0+3+0)·(−1) = 3 − 3 = **0**.
2. Slide one step right and repeat; at the end of the row move one step down.
3. The patch centred on the middle pixel is [[1,3,2],[1,0,1],[0,2,3]]: left column 1+1+0 = 2, right column 2+1+3 = 6, so the output is 2 − 6 = **−4** — a strong response: it's brighter on the right than on the left, a vertical edge.
4. Add the bias (0 here) and, in a real network, apply an activation such as ReLU (rectified linear unit: keeps positive values and turns negatives into 0).

The full output with stride 1 and no padding is 3×3:

```
stride=1 padding=0 -> output (3, 3) (formula 3), matches torch: True
[[ 0.  0. -1.]
 [-2. -4.  3.]
 [ 0. -1.  0.]]
```

Strictly, deep-learning "convolution" is **cross-correlation** — the kernel isn't flipped as in the mathematical definition. Since kernels are learned, the distinction doesn't matter; PyTorch's `F.conv2d` does exactly what the loop below does.

```python
# code/conv_by_hand.py (core)
def conv2d(x, k, stride=1, padding=0):
    x = np.pad(x, padding)
    kh, kw = k.shape
    oh = (x.shape[0] - kh) // stride + 1
    ow = (x.shape[1] - kw) // stride + 1
    out = np.zeros((oh, ow))
    for i in range(oh):
        for j in range(ow):
            patch = x[i * stride:i * stride + kh, j * stride:j * stride + kw]
            out[i, j] = np.sum(patch * k)          # element-wise multiply, then sum
    return out
```

Stride and padding

- **Stride** s: how many pixels the kernel jumps each move. Stride 2 halves the output's height and width — a cheap way to **downsample** (reduce the resolution).
- **Padding** p: extra border (usually zeros) around the input. Without it, every 3×3 conv shrinks the image by 2 pixels and edge pixels are under-used. **"Same" padding** (p = 1 for a 3×3 kernel, p = 2 for 5×5) keeps the size unchanged at stride 1. **"Valid"** means no padding.

Output size formula (per spatial dimension):

out = ⌊(n + 2p − k) / s⌋ + 1

n	k	s	p	out	Check
5	3	1	0	(5 − 3)/1 + 1 = 3	valid conv shrinks by 2
5	3	2	0	⌊2/2⌋ + 1 = 2	stride 2 downsamples
5	3	1	1	(5 + 2 − 3)/1 + 1 = 5	same padding
224	7	2	3	⌊(224 + 6 − 7)/2⌋ + 1 = 112	ResNet's first layer

```
stride=2 padding=0 -> output (2, 2) (formula 2), matches torch: True
[[ 0. -1.]
 [ 0.  0.]]

stride=1 padding=1 -> output (5, 5) (formula 5), matches torch: True
[[-3. -2.  0. -1.  3.]
 [-4.  0.  0. -1.  4.]
 [-2. -2. -4.  3.  6.]
 [-3.  0. -1.  0.  4.]
 [-2. -2. -1.  0.  3.]]
```

Channels

Real images have 3 **channels** (red, green, blue), and hidden feature maps have many (64, 128, 512…). A kernel always spans **all input channels**: a 3×3 kernel on a 64-channel input is really 3×3×64 = 576 weights, producing one output channel. A layer with C_out kernels produces C_out channels.

- Weights in a conv layer: **k × k × C_in × C_out** (+ C_out biases).
- PyTorch **tensor** (a multi-dimensional array of numbers) layout: **N × C × H × W** (batch, channels, height, width — a **batch** is the group of images processed together in one step). `nn.Conv2d(in_channels, out_channels, kernel_size, stride=1, padding=0)`.
- A **1×1 convolution** mixes channels at each pixel without looking at neighbours — used to cheaply change the number of channels (Inception, ResNet **bottlenecks** — layers that temporarily squeeze to fewer channels to save compute).
- A **depthwise-separable convolution** splits a conv into a per-channel k×k spatial conv plus a 1×1 conv that mixes channels (MobileNet, Xception, EfficientNet). Cost per output pixel: standard = $k^2 \cdot C_{in} \cdot C_{out}$; separable = $k^2 \cdot C_{in} + C_{in} \cdot C_{out}$. The ratio is $1/C_{out} + 1/k^2$ — for k = 3, C_in = C_out = 256: 1/256 + 1/9 ≈ 0.115, about 8.7× cheaper.

What do kernels detect?

`code/edge_filters.py` applies classic hand-designed kernels to a digit. A CNN **learns** kernels like these — first-layer filters of trained networks look like edge, colour-blob and stripe detectors.




Figure — A "0" digit and the feature maps from Sobel vertical/horizontal edge detectors (red = positive response, blue = negative), a blur and a sharpen kernel.

Common mistakes

- Mixing up N×C×H×W (PyTorch) and N×H×W×C (TensorFlow/Keras default, NumPy images) — transpose with `permute(0, 3, 1, 2)`.
- Forgetting padding and being surprised when the image shrinks layer after layer.
- Computing the **flatten** size (flattening unrolls a C×H×W feature map into one long vector for a dense layer) by hand wrongly — pass a dummy tensor through the conv part and print its shape, or use `nn.LazyLinear`.

In the interview

30-second answer: "A conv layer slides small learned kernels, each spanning all input channels, across the image and sums the element-wise products into a feature map. Weight sharing makes the parameter count independent of image size, and locality plus sharing give translation equivariance. Output size is ⌊(n + 2p − k)/s⌋ + 1; stride downsamples, padding preserves size; 1×1 convs mix channels cheaply."

- *Q: Output of a 224×224×3 image through `Conv2d(3, 64, 7, stride=2, padding=3)`?* A: 64 × 112 × 112; weights 7·7·3·64 + 64 = 9,472.
- *Q: Is convolution translation invariant (output unchanged when the input shifts)?* A: Equivariant — the feature map shifts with the input; pooling and global pooling add (approximate) invariance.

Self-check

1. 5×5 input, 3×3 kernel, stride 1, padding 0 — output size? → 3×3.
2. Weights in a 3×3 conv from 64 to 64 channels (no bias)? → 3·3·64·64 = 36,864.
3. Why is "convolution" in deep learning really cross-correlation? → The kernel isn't flipped; since it is learned, it makes no difference.

TL;DR

A conv layer slides shared k×k×C_in kernels over the input; out = ⌊(n + 2p − k)/s⌋ + 1; weights = k·k·C_in·C_out. Weight sharing + locality = far fewer parameters and translation equivariance.

11.2 Pooling and the CNN architecture

What it is

A **pooling layer** downsamples each feature map independently by summarising small windows:

- **Max pooling** (most common, 2×2 window, stride 2): keep the largest value — "was the feature present anywhere in this window?"
- **Average pooling**: take the mean.
- **Global average pooling (GAP)**: average each whole feature map to a single number — used at the end of modern CNNs instead of big dense layers.

Pooling has **no learnable parameters**. It shrinks H and W (2×2/2 halves them), cutting compute, growing the receptive field (the patch of the input image a unit can "see" — defined properly below), and adding a little tolerance to small shifts (**local translation invariance**).


Max-pool 2×2 stride 2 of the 5×5 padded-conv output above (the last row and column are dropped because the 2×2 windows don't fit):

```
max-pool 2x2/2 of the padded-conv output (5x5 -> 2x2):
 [[0. 0.]
 [0. 3.]]
avg-pool via torch:
 [[-2.25 -0.5 ]
 [-1.75 -0.5 ]]
```

Top-left window [[−3, −2], [−4, 0]] → max 0, mean −2.25.

Many modern networks replace pooling with **stride-2 convolutions** (learned downsampling) and use pooling only at the very end (GAP).

The standard CNN architecture



1. **Feature extractor ("backbone")**: repeated blocks of conv → normalization (usually BatchNorm) → activation, with periodic downsampling. As you go deeper, spatial size **shrinks** and the number of channels **grows** (e.g. 64 → 128 → 256 → 512): fewer, more abstract, more numerous features.
2. **Classifier ("head")**: flatten or global-average-pool, then one or more dense layers producing class **logits** (raw, unnormalised scores, one per class); **softmax** (turns logits into probabilities that sum to 1) + **cross-entropy** (a loss that is large when the true class gets low probability) for training.

The learned features form a hierarchy (Zeiler & Fergus visualised this in 2013): **edges and colours** → **textures and corners** → **object parts** → **whole objects**.

Receptive field

The **receptive field (RF)** of a unit is the region of the input image that can influence it. A 3×3 conv has RF 3. Stacking layers grows it. Track two numbers per layer — the RF and the **jump** (how many input pixels one step in this layer's output corresponds to, i.e. the product of all strides so far):

RF_new = RF_old + (k − 1) · jump_old, jump_new = jump_old · s

Worked through the VGG pattern below: conv3 → 1 + 2·1 = 3; conv3 → 3 + 2·1 = 5; maxpool 2/2 → 5 + 1·1 = 6, jump becomes 2; conv3 → 6 + 2·2 = 10; conv3 → 10 + 2·2 = 14.

`code/receptive_field.py`:

```
Three 3x3 convs (stride 1) vs one 7x7 conv, on a 32x32 input
layer                  out size   RF  jump
conv3x3                      32    3     1
conv3x3                      32    5     1
conv3x3                      32    7     1
layer                  out size   RF  jump
conv7x7                      32    7     1
weights (C=64 channels in and out, no bias): three 3x3 = 110,592  vs one 7x7 = 200,704

VGG-style block pattern: conv, conv, pool, ... on 224x224
layer                  out size   RF  jump
conv3x3                     224    3     1
conv3x3                     224    5     1
maxpool2                    112    6     2
conv3x3                     112   10     2
conv3x3                     112   14     2
maxpool2                     56   16     4
conv3x3                      56   24     4
conv3x3                      56   32     4
maxpool2                     28   36     8
```

Key insight (VGG, 2014): three stacked 3×3 convs see the same 7×7 region as one 7×7 conv, but use $27C^2$ instead of $49C^2$ weights and add two extra **nonlinearities** (activation functions — they let the network model relationships that aren't straight lines). That's why almost every modern CNN uses 3×3 kernels. Downsampling makes the RF grow much faster ("jump" doubles after each pool), which is how deep layers come to "see" the whole object. (The *effective* receptive field — where influence is actually strong — is smaller and roughly Gaussian-shaped, i.e. a bell curve peaked at the centre.)

Self-check

1. Output size of a 32×32 input after conv(k=5, s=1, p=0)? → 28×28.
2. Parameters of `Conv2d(64, 128, 3)`? → 3·3·64·128 + 128 = 73,856.
3. Why do channel counts grow as spatial size shrinks? → To keep representational capacity (how much information the layer can hold) (and roughly the compute per layer) while features become more abstract and numerous.
4. RF of two 3×3 convs (stride 1)? → 5×5.

TL;DR

Pooling (usually 2×2 max) halves H and W with no parameters. CNN = backbone of conv-BN-ReLU blocks with downsampling + head of GAP and dense layers. Stacked 3×3 convs grow the receptive field cheaply.

11.3 A small CNN on 8×8 digits (PyTorch, CPU)

scikit-learn's `load_digits` has 1,797 grayscale 8×8 images of handwritten digits (pixel values 0–16). It's tiny, so a CNN trains on a laptop CPU in a few seconds.

```python
# code/digits_cnn.py (core)
class SmallCNN(nn.Module):
    def __init__(self):
        super().__init__()
        self.features = nn.Sequential(
            nn.Conv2d(1, 16, kernel_size=3, padding=1),   # 1x8x8  -> 16x8x8
            nn.BatchNorm2d(16), nn.ReLU(),
            nn.MaxPool2d(2),                              # 16x8x8 -> 16x4x4
            nn.Conv2d(16, 32, kernel_size=3, padding=1),  # -> 32x4x4
            nn.BatchNorm2d(32), nn.ReLU(),
            nn.MaxPool2d(2),                              # -> 32x2x2
        )
        self.classifier = nn.Sequential(
            nn.Flatten(),                                 # -> 128
            nn.Dropout(0.3),
            nn.Linear(32 * 2 * 2, 10),                    # 10 class logits
        )
    def forward(self, x):
        return self.classifier(self.features(x))

X = (X / 16.0).reshape(-1, 1, 8, 8).astype(np.float32)   # N x C x H x W, scaled to [0, 1]
# ... stratified 70/30 split, DataLoader(batch_size=64, shuffle=True)
opt = torch.optim.AdamW(model.parameters(), lr=3e-3, weight_decay=1e-3)
sched = torch.optim.lr_scheduler.OneCycleLR(opt, max_lr=3e-3, total_steps=epochs * len(train_dl))
# ... standard loop: forward, cross_entropy, zero_grad, backward, step, sched.step()
```

AdamW is the Adam optimizer with **weight decay** (a small pull of every weight toward zero, which discourages **overfitting** — memorising the training data instead of learning patterns that generalise) applied separately from the gradient step; **OneCycleLR** is a learning-rate schedule (the **learning rate**, LR, is the step size of each weight update) that ramps the step size up and then back down over training. A **stratified** split keeps each class's proportion the same in train and test; a **DataLoader** feeds the data in shuffled batches.

The script trains three models for 40 **epochs** (full passes over the training data) — an **MLP** (multi-layer perceptron: the plain dense network of Chapter 10) with a similar parameter budget, the CNN, and the

CNN with **shift augmentation** (each training image randomly moved up to 1 pixel) — then tests all three on the normal test set and on the test set **shifted 1 pixel right**.

Output:

```
train (1257, 1, 8, 8)  test (540, 1, 8, 8)
MLP                        params= 7210  test accuracy=0.9759
CNN                        params= 6186  test accuracy=0.9907
CNN + shift augmentation   params= 6186  test accuracy=0.9852
MLP                        accuracy on test images shifted 1px right = 0.4722
CNN                        accuracy on test images shifted 1px right = 0.8574
CNN + shift augmentation   accuracy on test images shifted 1px right = 0.9796
misclassified (count, true, predicted): [(2, 8, 1), (2, 3, 9), (1, 9, 7), (1, 9, 1), (1, 8, 9)]
```




Figure — Left: test accuracy per epoch. Middle: the 16 first-layer kernels the CNN learned. Right: confusion matrix (a table counting true class vs predicted class) — nearly everything on the diagonal; the few errors are 8↔1 and 3↔9 type confusions.

What it shows:

- **Fewer parameters, higher accuracy**: the CNN (6.2k parameters) beats the MLP (7.2k) — 99.1% vs 97.6%.
- **Built-in spatial bias**: shift every test image by one pixel and the MLP collapses to 47% (every "pixel feature" moved), while the CNN keeps 86% thanks to shared kernels and pooling.
- **Augmentation buys robustness**: trained with random shifts, the CNN keeps 98% on shifted images — at the cost of half a point on the unshifted test set here (a small, typical trade-off on a tiny dataset).

TL;DR

On tiny 8×8 digits a two-block CNN beats a larger MLP (99.1% vs 97.6%) and is far more robust to shifts; shift augmentation makes it nearly shift-proof.

For real images (28×28 MNIST — a classic handwritten-digit dataset; 32×32 CIFAR-10 — small photos in 10 classes; 224×224 ImageNet — described in §11.4), the same code works with more blocks and channels; you'd load data with `torchvision.datasets` (PyTorch's companion library for images) and run on a **GPU** (graphics processing unit — a chip that does thousands of multiplications in parallel, which is what neural networks need).

Common mistakes

- Forgetting the channel dimension (8×8 images must be reshaped to 1×8×8).
- Evaluating with the model still in `train()` mode (BatchNorm and dropout behave differently). Call `model.eval()` before testing: it turns dropout off and makes BatchNorm use the averages it stored during training.
- Too much downsampling for small images: 8×8 can only be halved three times.

11.4 Famous architectures — a timeline

What it is

A handful of architectures, most of them winners of the **ImageNet Large Scale Visual Recognition Challenge (ILSVRC)** — 1.28 million training images across 1,000 classes — each introduced an idea that is still in use.

Year	Model	Depth / params	Key idea	Result
1998	**LeNet-5** (LeCun et al.)	7 layers, ~60k	Conv → pool → conv → pool → dense; trained with backprop	Read handwritten digits on bank cheques in production
2012	**AlexNet** (Krizhevsky, Sutskever, Hinton)	8 layers, ~60M	ReLU, dropout, heavy augmentation, trained on 2 GPUs	ILSVRC top-5 error (true class not in the model's 5 best guesses) 15.3% vs 26.2% runner-up — started the deep-learning boom
2014	**VGG-16/19** (Simonyan & Zisserman)	16–19 layers, ~138M (VGG-16)	Only 3×3 convs, stacked; very uniform	ILSVRC 2014 runner-up, 7.3% top-5; still a popular feature extractor
2014	**GoogLeNet / Inception** (Szegedy et al.)	22 layers, ~7M	Inception module: parallel 1×1, 3×3, 5×5 convs; 1×1 bottlenecks; GAP instead of big dense layers	ILSVRC 2014 winner, 6.7% top-5
2015	**ResNet** (He et al.)	18–152 layers (ResNet-50 ≈ 25.6M)	**Residual (skip) connections** + BatchNorm	ILSVRC 2015 winner, 3.57% top-5 (ensemble); made 100+ layer nets trainable
2017	**MobileNet** (Howard et al.)	small	Depthwise-separable convs for phones	Efficient on-device vision
2019	**EfficientNet** (Tan & Le)	B0–B7 (5.3M–66M)	**Compound scaling**: grow depth, width and input resolution together with fixed ratios; SiLU (a smooth ReLU-like activation), MBConv (mobile inverted-bottleneck) blocks	B7: 84.3% top-1 ImageNet, 8.4× smaller than the previous best (GPipe)
2020	**Vision Transformer (ViT)** (Dosovitskiy et al.)	86M+ (ViT-Base)	Split the image into 16×16 patches, treat them as tokens (input units), apply a transformer (attention-based network, Chapter 12)	Beats CNNs when pre-trained on very large datasets
2022	**ConvNeXt** (Liu et al.)	ResNet-sized	A ResNet modernised with transformer-era design choices	Matches ViTs, showing CNNs remain competitive

ResNet and skip connections


The problem. Before 2015, making plain CNNs deeper beyond ~20 layers made them *worse* — even on the **training** set. This "degradation" isn't overfitting (that would hurt only the test set, not training accuracy); very deep plain stacks are simply hard to optimise (signals and gradients get distorted through many layers).

The idea. Instead of asking a block to learn a mapping H(x) directly, let it learn the **residual** F(x) = H(x) − x and add the input back:

y = ReLU(x + F(x)), where F = conv → BN → ReLU → conv → BN

If the best thing a block can do is nothing, it just learns F ≈ 0 — easy. And in backprop, $\partial y/\partial x$ (the derivative: how much y changes when x changes slightly) includes an identity term, so gradients have a

direct **highway** back to early layers. When the shapes differ (stride 2 or more channels), the skip path uses a 1×1 conv to match them.




```
# code/resnet_block.py (core)
class ResidualBlock(nn.Module):
    def __init__(self, c):
        super().__init__()
        self.f = nn.Sequential(
            nn.Conv2d(c, c, 3, padding=1, bias=False), nn.BatchNorm2d(c), nn.ReLU(),
            nn.Conv2d(c, c, 3, padding=1, bias=False), nn.BatchNorm2d(c))
    def forward(self, x):
        return torch.relu(x + self.f(x))                # the skip connection
```

Output — gradient norm reaching the first conv, and a 30-conv-layer plain net vs a 30-conv-layer residual net trained on digits for 5 epochs:

```
conv layers  plain |grad|  residual |grad|
          2      2.58e-02         4.78e-02
         10      1.11e-01         1.18e-01
         30      3.54e+00         4.14e-01
         60      3.08e+02         9.41e-01

Training 30-conv-layer nets on digits (SGD+momentum lr 0.05, 5 epochs):
  plain    training accuracy 0.575  training loss 1.121
  residual training accuracy 0.957  training loss 0.159
```

With BatchNorm, the plain net's gradients don't **vanish** (shrink toward zero) here — they become erratic and **explode** (grow uncontrollably large) as depth grows (3×10^2 at 60 layers), while the residual net's stay near 1. Trained with identical settings, the plain net reaches only 58% **training** accuracy (the degradation problem) while the residual net reaches 96%. Skip connections are now everywhere: DenseNet, U-Net, and every transformer block.

EfficientNet in one paragraph

If you have more compute, how should you grow a CNN — deeper, wider (more channels), or with higher-resolution inputs? EfficientNet found that scaling all three together with a fixed ratio (depth × α^φ, width × β^φ, resolution × γ^φ) gives far better accuracy per FLOP (floating-point operation — one multiply or add, the usual unit of compute) than scaling any one. The base network B0 was found by **neural architecture search** (an automated search over many candidate network designs); B1–B7 are compound-scaled versions.

Vision Transformer (brief)

ViT cuts an image into fixed-size patches (e.g. 16×16 pixels → a 224×224 image becomes 14 × 14 = 196 patches), flattens and linearly projects each patch (multiplies it by a learned matrix) into a vector (a "token"), adds **position embeddings** (learned vectors telling the model where each patch came from) and a learnable [CLS] token (an extra token whose final vector is used as the summary of the whole image), and runs a standard transformer encoder (self-attention: Chapter 12). With no built-in locality or translation equivariance, ViTs need much more data (the original used 300M-image pre-training) but scale extremely well. Hybrid and hierarchical designs (Swin Transformer) and modern CNNs (ConvNeXt) now compete closely; for small datasets, a pretrained CNN or pretrained ViT fine-tuned is the practical choice.

Trade-offs

Need	Good choice
Strong, well-understood baseline	ResNet-50 (or ResNet-18 for speed)
Mobile / edge devices (phones, cameras, small embedded chips)	MobileNetV3, EfficientNet-B0
Best accuracy with large pretraining	ViT / Swin / ConvNeXt, EfficientNetV2
Tiny dataset	Any pretrained backbone, fine-tuned

In the interview

30-second answer: "LeNet showed conv-pool stacks work; AlexNet scaled them with ReLU, dropout and GPUs and won ImageNet 2012; VGG showed stacks of 3×3 convs are enough; Inception used parallel branches and 1×1 bottlenecks; ResNet added identity skip connections so 100+ layer networks train — each block learns a residual and gradients flow through the identity path; EfficientNet scales depth, width and resolution together; ViT applies a transformer to image patches and wins with large-scale pretraining."

- *Q: Why do residual connections help?* A: They make the identity easy to represent (F = 0) and give gradients a direct path, fixing the degradation problem of deep plain nets.
- *Q: What is a 1×1 convolution for?* A: Mixing channels and changing channel count cheaply (bottlenecks).
- *Q: Why does ViT need more data than a CNN?* A: It lacks the CNN's built-in inductive biases (assumptions baked into the architecture: locality, weight sharing across positions), so it must learn them from data.

Self-check

1. Which architecture introduced skip connections? → ResNet (2015).
2. What three dimensions does EfficientNet scale? → Depth, width, input resolution.
3. How many patches does ViT make from a 224×224 image with 16×16 patches? → 196.
4. Name two ideas AlexNet popularised. → ReLU activations and dropout (also GPU training and heavy augmentation).

TL;DR

LeNet → AlexNet (ReLU, dropout, GPUs) → VGG (3×3 stacks) → Inception (1×1, multi-branch) → ResNet (skip connections: y = x + F(x)) → MobileNet/EfficientNet (efficiency, compound scaling) → ViT (patches + transformer).

11.5 Transfer learning and fine-tuning

What it is

Transfer learning reuses a model trained on a large **source** task (typically ImageNet classification) as the starting point for your **target** task. The early layers of any vision model learn general features — edges, textures, shapes — that are useful for almost every image problem, so you don't have to learn them again from a few hundred images.

Analogy: hiring an experienced photographer to sort your product photos. They already know how to see; you only teach them your categories.

Why it matters

Training a ResNet-50 from scratch on ImageNet takes days of GPU time and 1.28M labelled images. Fine-tuning a pretrained one on 2,000 of your own images takes minutes and usually gives far better accuracy than training from scratch on those 2,000. It's the default for almost every practical vision project.

How it works — the two strategies

1. **Feature extraction (frozen backbone).** Load pretrained weights, **freeze** the backbone (stop its weights from changing: `requires_grad = False`), replace the final layer with a new head for your classes, and train only the head. Fast, needs little data, low risk of overfitting.
2. **Fine-tuning.** Start from the pretrained weights and also update some or all backbone layers with a **small learning rate** (often 10× smaller than for the head, "discriminative learning rates"), so useful features are adjusted rather than destroyed. A common recipe: train the new head first with the backbone frozen, then unfreeze the top blocks (or all) and continue with a low LR.

Your data	Similar to ImageNet	Very different (X-rays, satellite, spectrograms)
Small	Feature extraction	Feature extraction from earlier layers, or fine-tune gently; augment heavily
Large	Fine-tune all layers	Fine-tune all layers (pretraining still usually helps convergence)

The real code with torchvision (needs a download of weights — not run here):

```
import torch
from torch import nn
from torchvision import models

model = models.resnet18(weights=models.ResNet18_Weights.DEFAULT)   # ImageNet-pretrained
for p in model.parameters():
    p.requires_grad = False                                         # 1) freeze backbone
model.fc = nn.Linear(model.fc.in_features, num_classes)             # new head (trainable)
opt = torch.optim.AdamW(model.fc.parameters(), lr=1e-3)
# ... train a few epochs, then 2) unfreeze and fine-tune with a smaller lr:
for p in model.parameters():
    p.requires_grad = True
opt = torch.optim.AdamW([{"params": model.fc.parameters(), "lr": 1e-3},
                         {"params": [p for n, p in model.named_parameters() if not n.startswith("fc.")], "lr": 1e-
4}])
# Inputs must be preprocessed like the pretraining data: resize/crop to 224 and normalise with
# ImageNet mean (0.485, 0.456, 0.406) and std (0.229, 0.224, 0.225) - the weights object's
# .transforms() gives the exact pipeline.
```

A runnable demonstration (no downloads)

`code/transfer_learning.py` mimics the setting on digits: pretrain a CNN on **clean** digits (half the dataset), then adapt it to the other half **"scanned by a different device"** (Gaussian noise — small random bell-curve jitter — added to every pixel), using only k labelled images per class. Results are averaged over 3 **seeds** (different random starting points), since tiny datasets give noisy results.

```
def make_model(strategy, pretrained):
    bb, head = backbone(), nn.Linear(128, 10)
    model = nn.Sequential(bb, head)
    if strategy == "frozen backbone":                   # pretrained backbone, NEW head
        bb.load_state_dict({k[2:]: v for k, v in pretrained.items() if k.startswith("0.")})
    elif strategy == "fine-tune all":                   # start from the whole source model
        model.load_state_dict(pretrained)
    if strategy == "frozen backbone":
        for p in bb.parameters():
            p.requires_grad = False                     # freeze: no gradients, no updates
        return model, head.parameters()
    if strategy == "fine-tune all":
        return model, [{"params": model.parameters(), "lr": 1e-4}]   # small lr: nudge, don't overwrite
    return model, model.parameters()
```

Output:

```
source model: train acc on clean digits 0.996, acc on noisy target digits with NO adaptation 0.839

labels/class     from scratch  frozen backbone    fine-tune all   (mean test acc over 3 seeds)
           2            0.530            0.650            0.840
           5            0.673            0.766            0.834
          10            0.738            0.779            0.847
          30            0.810            0.824            0.857

trainable params: from scratch / fine-tune = 6090 | frozen backbone = 1290
```

Reading it:

- With **2 labels per class**, from-scratch gets 53%; a frozen pretrained backbone with a new head gets 65%; gently fine-tuning the full pretrained model gets 84%.
- The advantage **shrinks as target data grows** (30 per class: 81% vs 86%) — transfer matters most when labels are scarce.
- **Always measure the pretrained model before adapting it**: here the source model already scores 83.9% on the target with no training. Fine-tuning with a *large* learning rate or a randomly re-initialised head can easily do *worse* than that baseline — which is why fine-tuning uses small learning rates.
- Transfer is not magic: in a variant of this experiment (not included in the script) where the target classes were *different digits* (pretrain on 0–4, adapt to 5–9) on these tiny 8×8 images, pretraining did not help — the features weren't general enough. Real ImageNet backbones, trained on 1,000 diverse classes, transfer far more broadly.

When not to use it

- When your inputs are nothing like natural images *and* you have plenty of data (pretraining may still help convergence, but check).
- When the license of the pretrained weights forbids your use.

Common mistakes

- Forgetting to preprocess inputs exactly like the pretraining data (size, normalisation).
- Fine-tuning everything with a large learning rate on a small dataset — "catastrophic forgetting" (the network overwrites what it learned before) of the useful features.
- Leaving BatchNorm layers updating their running statistics (the averages BN stores for use at prediction time) on tiny batches during fine-tuning (often better kept in eval mode / frozen).

Real-world examples

Most production vision models start from pretrained backbones: medical-imaging classifiers fine-tuned from ImageNet models, retail product recognition, defect detection on factory lines. Detection models (YOLO, Faster R-CNN) use pretrained classification backbones. The same pattern — pretrain big, fine-tune small — is how LLMs (large language models such as GPT or Claude) are adapted (AI Handbook, Chapter 8).

In the interview

30-second answer: "Take a model pretrained on a large dataset like ImageNet, replace its head, and either freeze the backbone and train only the head (feature extraction — small data) or fine-tune some or all layers with a small learning rate (more data or a different domain). Preprocess inputs like the pretraining data. It beats training from scratch whenever labelled data is limited."

- *Q: Which layers transfer best?* A: Early layers (generic edges/textures); later layers are more task-specific, so they're the first to unfreeze.
- *Q: Why a smaller LR for the backbone?* A: To adjust, not overwrite, useful pretrained features.

Self-check

1. What does freezing do in PyTorch? → `requires_grad = False` — no gradients, so the optimizer doesn't change those weights.

2. Small dataset similar to ImageNet — which strategy? → Feature extraction (frozen backbone, new head), maybe light fine-tuning later.
3. Why did transfer help less with 30 labels per class than with 2? → With more target data, a model trained from scratch catches up; pretraining matters most when data is scarce.

TL;DR

Start from pretrained weights; new head; freeze then fine-tune with a small LR; preprocess like the pretraining data; biggest gains when labels are scarce.

11.6 Data augmentation for images

What it is

Generating new training images from existing ones by applying transformations that **don't change the label**: a flipped, slightly rotated or recoloured cat is still a cat. The network sees more variety, so it memorises less and becomes robust to the variations it will meet in the real world.

How it works — common transforms (torchvision.transforms.v2)

`torchvision.transforms.v2` is torchvision's module of ready-made image transformations.

Transform	What it does	Watch out
`RandomResizedCrop(224)`	Random crop of random size/aspect, resized	The standard ImageNet training transform
`RandomHorizontalFlip()`	Mirror left-right	Not for text, digits, or where left/right matters
`RandomRotation(15)`	Small rotations	Large rotations turn 6 into 9
`ColorJitter(0.4, 0.4, 0.4)`	Brightness, contrast, saturation changes	Not if colour is the label (ripe vs unripe fruit)
`RandomErasing()` / Cutout	Blank a random rectangle	Forces use of several parts of the object
`GaussianBlur`, noise	Blur or noise	Mimic camera quality
Mixup / CutMix	Blend two images (or paste a patch) and blend their labels	Strong regularizers (anti-overfitting techniques) for large models
RandAugment / AutoAugment / TrivialAugment	Automatically chosen policies of transforms	Good defaults in modern training recipes

```
from torchvision.transforms import v2 as T   # (torchvision not needed for the rest of this chapter)
train_tf = T.Compose([T.RandomResizedCrop(224), T.RandomHorizontalFlip(), T.ColorJitter(0.2, 0.2, 0.2),
                      T.ToImage(), T.ToDtype(torch.float32, scale=True),
                      T.Normalize(mean=[0.485, 0.456, 0.406], std=[0.229, 0.224, 0.225])])
test_tf = T.Compose([T.Resize(256), T.CenterCrop(224), T.ToImage(), T.ToDtype(torch.float32, scale=True),
                     T.Normalize(mean=[0.485, 0.456, 0.406], std=[0.229, 0.224, 0.225])])
```

Augmentation happens **on the fly** in the training `Dataset`/`DataLoader` (PyTorch's classes for reading examples and grouping them into batches), differently every epoch — only for training data. Validation/test use a fixed **deterministic** (identical every time) resize/crop. **Test-time augmentation (TTA)** — averaging predictions over a few flipped/cropped versions — can add a little accuracy at **inference** (prediction-time, using the trained model) cost.

In §11.3, shift augmentation raised accuracy on shifted digits from 86% to 98%.

For **detection and segmentation**, geometric transforms must be applied to the boxes/masks too (torchvision v2 transforms and the Albumentations library handle this).

Common mistakes

- Augmenting validation/test data randomly.
- Augmentations that change the label (flipping digits, rotating road signs that mean different things when mirrored).
- Forgetting that augmentation slows each epoch (CPU-bound: limited by processor speed, not the GPU) — use `num_workers` in `DataLoader` (extra worker processes that prepare batches in parallel).

In the interview

> **30-second answer:** "Augmentation applies random, label-preserving transforms — crops, flips, colour jitter, small rotations, Mixup/CutMix — to training images on the fly, so the model sees more variety and overfits less. Validation and test use a fixed resize and crop. For detection and segmentation the same geometric transform must be applied to boxes and masks."

Self-check

1. Why not horizontally flip digit images? → Mirrored digits (e.g. a mirrored 2 or 7) aren't valid digits — the label no longer holds.
2. What does Mixup do to the label? → Blends the two one-hot labels (vectors with 1 for the true class and 0 elsewhere) with the same ratio as the images.
3. Is test-time augmentation training or inference? → Inference: average predictions over a few transformed copies.

TL;DR

Random label-preserving transforms on training images only; flips, crops, colour jitter, rotations, Mixup/CutMix; the cheapest regularizer in vision.

11.7 Vision tasks: classification, detection, segmentation

What it is

Task	Question	Output	Typical models
Image classification	What is in this image?	One label (or a label per image)	ResNet, EfficientNet, ViT
Object detection	What objects are where?	A box (x, y, w, h) + class + confidence per object	YOLO, SSD, Faster R-CNN, DETR
Semantic segmentation	Which class is each pixel?	A class per pixel	U-Net, DeepLab, FCN
Instance segmentation	Which object does each pixel belong to?	A mask (per-pixel on/off map) per object	Mask R-CNN, YOLO-seg, SAM (promptable)

Object detection

IoU (Intersection over Union) measures box overlap: area of intersection ÷ area of union. It's used to match predictions to **ground truth** (the correct, human-labelled answer) (e.g. a detection counts as correct if IoU ≥ 0.5) and in NMS.

Worked example (`code/iou_nms.py`): ground truth (50, 50)–(150, 150) and prediction (70, 60)–(170, 160), boxes as (x1, y1)–(x2, y2). Each area = 100 × 100 = 10,000. Intersection = (150 − 70) × (150 − 60) = 80 × 90 = 7,200. Union = 10,000 + 10,000 − 7,200 = 12,800. **IoU = 7,200 / 12,800 = 0.5625.**

NMS (non-maximum suppression) removes duplicate detections of the same object:

1. Sort boxes by confidence.

2. Keep the highest-scoring box; delete every remaining box whose IoU with it exceeds a threshold (e.g. 0.5).
3. Repeat with the next remaining box.

```
def my_nms(boxes, scores, thr):
    order = sorted(range(len(boxes)), key=lambda i: -scores[i])
    keep = []
    while order:
        best = order.pop(0)
        keep.append(best)
        order = [i for i in order if iou(boxes[best], boxes[i]) < thr]   # drop heavy overlaps
    return keep
```

Output:

```
IoU worked example: 0.562
pairwise IoU of the 5 boxes:
[[1.   0.89 0.65 0.   0.  ]
 [0.89 1.   0.69 0.   0.  ]
 [0.65 0.69 1.   0.   0.  ]
 [0.   0.   0.   1.   0.74]
 [0.   0.   0.   0.74 1.  ]]
NMS (IoU threshold 0.5) keeps boxes [0, 3] with scores [0.9, 0.8]
```

Five raw boxes around two objects → two final detections.

Two families of detectors:

- **Two-stage** (R-CNN → Fast R-CNN → **Faster R-CNN**, 2015): a Region Proposal Network (a small network that proposes boxes likely to contain an object) suggests candidate boxes, then a second stage classifies and refines each. Accurate, slower.
- **One-stage** (**YOLO**, SSD, RetinaNet): predict all boxes in a single **forward pass** (one run of the input through the network). Fast enough for real-time video.

The YOLO idea ("You Only Look Once", Redmon et al., 2016): divide the image into an S × S grid. Each grid cell predicts a few bounding boxes (x, y, w, h, and an objectness confidence) and class probabilities for an object whose **centre** falls in that cell — all as one tensor from one CNN pass. Then threshold on confidence and run NMS. The original ran at about 45 frames per second. Later versions (YOLOv3 onward, and today's Ultralytics YOLO releases) added multi-scale predictions, **anchor boxes** (preset box shapes that predictions are expressed as adjustments to) (and later anchor-free heads) and better backbones, and remain the go-to for real-time detection. **DETR** (2020) reframed detection with a transformer that predicts a set of boxes directly, removing NMS. For a full system built on a detector — blurring faces and plates in street imagery, where **recall** (the share of real objects that were found) per person matters more than mAP — see case study 18.7.

Metric: mAP (mean average precision) — area under the precision–recall curve per class, averaged over classes (**precision** is the share of predicted boxes that are correct); PASCAL VOC uses IoU ≥ 0.5, COCO averages over IoU thresholds 0.5 to 0.95 (PASCAL VOC and COCO are the two standard detection benchmark datasets).


Segmentation — the U-Net idea

Segmentation needs a prediction for **every pixel**, so the network must go down to a compact representation (to understand *what*) and back up to full resolution (to say exactly *where*).

U-Net (Ronneberger et al., 2015, for biomedical images):

1. **Encoder (contracting path)**: conv blocks + downsampling — spatial size shrinks, channels grow (like a classifier backbone).
2. **Decoder (expanding path)**: **upsampling** (increasing the resolution) with transposed convolutions (learned upsampling layers — roughly a convolution run in reverse) back to the input resolution.
3. **Skip connections**: at each level, the encoder's feature map is **concatenated** onto the decoder's — giving back the fine spatial detail lost during downsampling.

4. A final 1×1 conv outputs class scores per pixel; train with per-pixel cross-entropy (often plus **Dice loss** — a loss based on how much the predicted and true masks overlap, which copes well when the object covers only a few pixels — for imbalanced masks).



It's shaped like a "U", hence the name. U-Net-style networks also sit at the core of image-generation **diffusion models** (generators that create an image by starting from pure noise and removing it step by step) (e.g. Stable Diffusion v1/v2 use a U-Net denoiser).

Real-world examples

- **Classification**: Google Photos search, product recognition in retail apps, content moderation.
- **Detection**: self-driving perception (cars, pedestrians, signs), warehouse robots, retail shelf auditing, face detection in phone cameras.
- **Segmentation**: medical imaging (tumour and organ outlines), background removal in video calls, satellite land-use maps, portrait mode.

In the interview

30-second answer: "Classification gives one label per image; detection gives boxes plus classes; segmentation gives a label per pixel. Detection uses IoU to match boxes and NMS to remove duplicates; two-stage detectors like Faster R-CNN propose regions then classify them, one-stage detectors like YOLO predict all boxes in one pass over a grid, which makes them real-time. Segmentation uses encoder-decoder networks like U-Net, whose skip connections restore spatial detail. Metrics: accuracy/top-k, mAP at IoU thresholds, and IoU/Dice for masks."

- *Q: Why is NMS needed?* A: Detectors output many overlapping boxes for the same object; NMS keeps the most confident and removes overlaps above an IoU threshold.
- *Q: Semantic vs instance segmentation?* A: Semantic labels pixels by class (all people are "person"); instance separates each object (person 1, person 2).

Self-check

1. IoU of two identical boxes? Of disjoint boxes? → 1 and 0.
2. In YOLO, which grid cell is responsible for an object? → The cell containing the object's centre.
3. What do U-Net's skip connections carry? → High-resolution encoder feature maps, concatenated onto the decoder to recover spatial detail.

TL;DR

Classification → label; detection → boxes (IoU, NMS, YOLO = one pass over a grid, Faster R-CNN = propose then classify); segmentation → per-pixel labels (U-Net = encoder-decoder + skip connections).

11.8 Putting it together — trade-offs, mistakes, interview

When not to use a CNN

- Tabular data — rows and columns like a spreadsheet (use gradient-boosted trees, the decision-tree ensembles of Chapter 7).
- Very small image datasets **without** a pretrained model — collect more data or use classical features.
- When a pretrained ViT/CLIP-style **foundation model** (a large model pretrained on broad data and reused for many tasks; CLIP learned to match images with text captions) with **zero-shot** prompts

(describing the classes in words, with no task-specific training examples) already solves the problem.

Common mistakes (whole chapter)

- Training from scratch when a pretrained backbone is available.
- Wrong tensor layout or normalisation.
- Label-changing augmentations.
- Judging a detector by accuracy instead of mAP.

In the interview — big picture

> **30-second answer:** "CNNs slide shared small kernels over the image, giving far fewer parameters and translation equivariance. Stacked 3×3 convs with downsampling build a hierarchy of features and a growing receptive field; a head of global pooling plus a dense layer classifies. ResNet's skip connections enable very deep networks. In practice I'd start from a pretrained backbone, fine-tune with augmentation, and choose the head by task — classification, YOLO-style detection or U-Net-style segmentation."

Self-check

1. Two properties of convolution that make it suit images? → Weight sharing (few parameters) and local connectivity/translation equivariance.
2. What does global average pooling replace? → The large flattened dense layers at the end of older CNNs.
3. What's the first thing to try for a new 5,000-image classification problem? → Fine-tune a pretrained backbone (e.g. ResNet-50 or EfficientNet) with augmentation.

Chapter TL;DR

- **Convolution**: shared k×k kernels over all input channels; out = ⌊(n + 2p − k)/s⌋ + 1; params = k·k·C_in·C_out + C_out. Stride downsamples; padding preserves size.
- **Pooling**: 2×2 max-pool halves H and W, no parameters; global average pooling before the classifier.
- **Architecture**: conv-BN-ReLU blocks, shrinking space and growing channels, then GAP + dense. Stacked 3×3 convs grow the receptive field cheaply.
- **History**: LeNet → AlexNet (ReLU, dropout, GPU) → VGG → Inception → **ResNet (skip connections)** → MobileNet/EfficientNet → ViT.
- **Our CNN**: 99.1% on 8×8 digits with fewer parameters than an MLP; far more robust to shifts, especially with augmentation.
- **Transfer learning**: pretrained backbone + new head; freeze, then fine-tune with a small LR; biggest gains with few labels.
- **Augmentation**: label-preserving random transforms, training only.
- **Detection**: IoU, NMS, YOLO (one pass, grid), Faster R-CNN (two-stage), mAP. **Segmentation**: U-Net (encoder-decoder + skip connections).

Next: Chapter 12 moves from grids of pixels to sequences — RNNs, LSTMs and attention.