Microservices Patterns Handbook

Twelve patterns for building, migrating and operating microservices · resilience · data consistency · messaging · configuration

14 parts · one place to study: DesignGurus courses + classic books + the web, combined, beginner to intermediate

what it is · problem · how it works · trade-offs · real world · interview · self-check · TL;DR

Personal study notes. Course diagrams belong to DesignGurus. Not for redistribution.

Contents

1. **Chapter 1 — System Design Fundamentals**
    - Module Introduction
    - Part 1 — Foundations and performance
    - What system design is
    - Clients, servers and the request/response cycle
    - The building blocks of a web application
    - Latency, throughput and bandwidth
    - Percentiles, tail latency and why averages lie
    - Little's law
    - Latency numbers every engineer should know
    - Units, powers of two and data sizes
    - Back-of-the-envelope estimation
    - Availability and the nines
    - SLA, SLO, SLI and error budgets
    - MTBF, MTTR and measuring failure
    - Reliability, availability and durability
    - Faults, failures and fault tolerance
    - Redundancy, single points of failure and failover
    - Scalability
    - Vertical and horizontal scaling
    - Elasticity
    - Stateless and stateful services
    - Performance vs scalability
    - Concurrency vs parallelism
    - Bottlenecks: CPU, memory, disk and network
    - How to approach a system design interview
    - Part 1 glossary
    - Part 2 — Networking and communication
    - IP addresses, NAT, ports and sockets
    - DNS — the internet's phone book
    - Network layers — OSI and TCP/IP models
    - TCP, UDP and QUIC
    - HTTP — the language of the web
    - HTTPS and TLS
    - API styles — REST, RPC and gRPC, GraphQL
    - Real-time communication — polling, long polling, WebSockets, SSE, webhooks
    - API design basics
    - Proxies and API gateways
    - Load balancers
    - CDNs and anycast
    - Bandwidth vs latency, and network partitions
    - Part 2 glossary
    - Part 3 — Data storage
    - What a database is
    - Relational databases and SQL
    - Transactions and ACID
    - Isolation levels and anomalies
    - NoSQL database families
    - SQL vs NoSQL and BASE
    - Indexes
    - Normalization and denormalization
    - Replication
    - Partitioning and sharding
    - Consistent hashing and virtual nodes
    - Storage types: block, file and object
    - OLTP vs OLAP, row vs column storage, lakes and warehouses
    - Durability: WAL, fsync, backups and recovery
    - Connection pooling, ORMs and N+1 queries
    - Choosing a database
    - Part 3 glossary
    - Part 4 — Caching, async processing and consistency
    - Caching basics
    - Where caches live
    - Caching strategies
    - Eviction policies
    - Cache invalidation, stale data and stampedes
    - Message queues
    - Event streaming: topics, partitions, consumer groups and offsets
    - Delivery guarantees, idempotency and retries
    - Batch vs stream processing
    - Event-driven architecture, event sourcing and CQRS
    - Consistency models
    - CAP theorem and PACELC
    - Quorums
    - Consensus, leader election and distributed locks
    - Clocks and ordering
    - Distributed transactions: two-phase commit and sagas
    - Heartbeats, gossip and failure detection
    - Probabilistic data structures and Merkle trees
    - Unique ID generation
    - Geospatial indexing: geohash and quadtree
    - Part 4 glossary
    - Part 5 — Architecture, reliability, operations and security
    - Architectural styles: monolith, modular monolith, SOA, microservices and serverless
    - Synchronous vs asynchronous communication
    - Service discovery, sidecars and service mesh
    - Timeouts, retries, exponential backoff and jitter
    - Circuit breakers, bulkheads and fallbacks
    - Rate limiting and throttling
    - Load shedding and graceful degradation
    - Autoscaling
    - Virtual machines, containers and Docker
    - Kubernetes basics
    - Infrastructure as code
    - CI/CD
    - Deployment strategies and rollback
    - Observability: logs, metrics and traces
    - Dashboards, alerting, on-call and SLO-based alerts
    - Disaster recovery
    - Authentication and authorization
    - Sessions, cookies, tokens and JWT
    - OAuth 2.0, OpenID Connect, SSO and API keys
    - Encryption, hashing, passwords and secrets

- Network security: firewalls, WAF and DDoS
- Common web vulnerabilities: CORS, CSRF, XSS and SQL injection
- Least privilege and zero trust
- Cost awareness
- Part 5 glossary
- Part 6 — Putting it together

2. **Strangler Fig Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — Where the name comes from
   - Part 2 — The problem in detail
   - Part 3 — The solution
   - Part 4 — Architecture
   - Part 5 — The four implementation steps
   - Part 6 — Worked example 1: routing a single function
   - A request's journey
   - Worked example: designing a URL shortener
   - Decision cheat sheet
   - Top 60 interview questions
   - Master A–Z glossary
   - Part 6 glossary
   - Part 7 — Worked example 2: a facade over a banking system
   - Part 8 — Key insights: the proxy layer is everything
   - Part 9 — Trade-offs and what actually goes wrong
   - Part 10 — Common beginner misconceptions
   - Part 11 — Check your understanding
   - Part 12 — Interview soundbite (30 seconds)
   - Part 13 — Implementation
   - Related patterns
3. **API Gateway Pattern**
   - Lesson 1 — Introduction to the API Gateway Pattern
   - Lesson 2 — Advantages: the fifteen problems it solves
   - Lesson 3 — Worked example: a library system
   - Lesson 4 — Problems the gateway itself introduces
   - Lesson 4 (cont.) — Performance implications
   - Lesson 5 — System design example: Instagram
   - Consolidation
   - Implementation
   - Related patterns
4. **Backends for Frontends (BFF) Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — The core idea, in plain terms
   - Part 2 — The problem in detail
   - Part 3 — Architecture
   - Part 4 — The benefits, explained
   - Part 5 — Worked example: e-commerce product details
   - Part 6 — Problems with BFF, and how to handle them
   - Part 7 — System design example: Netflix
   - Part 8 — BFF vs. API Gateway
   - Part 9 — Common beginner misconceptions
   - Part 10 — Check your understanding
   - Part 11 — Interview soundbite (30 seconds)
   - Part 12 — Implementation
   - Related patterns
5. **Service Discovery Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — The problem
   - Part 2 — The solution
   - Part 3 — Architecture
   - Part 4 — Client-side vs. server-side discovery
   - Part 5 — Inner workings
   - Part 6 — Worked example (simplified Java)
   - Part 7 — Performance implications and special considerations
   - Part 8 — Security considerations
   - Part 9 — Real-world implementations
   - Part 10 — Common beginner misconceptions
   - Part 11 — Check your understanding
   - Part 12 — Interview soundbite (30 seconds)
   - Part 13 — Implementation
   - Related patterns
6. **Circuit Breaker Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — The metaphor
   - Part 2 — The problem
   - Part 3 — The solution
   - Part 4 — The three states
   - Part 5 — Integration: it's additive, not invasive
   - Part 6 — Configuration
   - Part 7 — Worked example (Java)
   - Part 8 — Performance implications
   - Part 9 — Best practices and trade-offs
   - Part 10 — Use cases
   - Part 11 — Real-world examples
   - Part 12 — System design example: distributed social media platform
   - Part 13 — Common beginner misconceptions
   - Part 14 — Check your understanding
   - Part 15 — Interview soundbite (30 seconds)
   - Part 16 — Implementation
   - Related patterns
7. **Bulkhead Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — Where the name comes from
   - Part 2 — The problem: failure propagation
   - Part 3 — The solution: isolation
   - Part 4 — Architecture
   - Part 5 — Inner workings
   - Part 6 — Worked example: thread-pool bulkheads in Java

- Part 7 — Performance implications
- Part 8 — Use cases
- Part 9 — System design example: music streaming (Spotify-like)
- Part 10 — Bulkhead vs. Circuit Breaker
- Part 11 — Common beginner misconceptions
- Part 12 — Check your understanding
- Part 13 — Interview soundbite (30 seconds)
- Part 14 — Implementation
- Related patterns

8. **Retry Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — The problem
   - Part 2 — The solution
   - Part 3 — Transient vs. permanent: the critical distinction
   - Part 4 — Architecture
   - Part 5 — Worked example (Java)
   - Part 6 — Performance implications and risks
   - Part 7 — Use cases
   - Part 8 — Real-world examples
   - Part 9 — System design examples
   - Part 10 — When NOT to use retry
   - Part 11 — Common beginner misconceptions
   - Part 12 — Check your understanding
   - Part 13 — Interview soundbite (30 seconds)
   - Part 14 — Implementation
   - Related patterns
9. **Sidecar Pattern**
   - Part 0 — Concepts you need first
   - Part 1 — The metaphor and the core idea
   - ⚠️ Part 2 — One correction to the course material
   - Part 3 — The problem: monolithic application management
   - Part 4 — The solution
   - Part 5 — Architecture
   - Part 6 — Worked example
   - Part 7 — Performance implications
   - Part 8 — Special considerations
   - Part 9 — Use cases
   - Part 10 — System design examples
   - Part 11 — Sidecar vs. shared library
   - Part 12 — Common beginner misconceptions
   - Part 13 — Check your understanding
   - Part 14 — Interview soundbite (30 seconds)
   - Part 15 — Implementation
   - Related patterns
10. **Saga Pattern**
    - Part 0 — Concepts you need first
    - Part 1 — The problem
    - Part 2 — The solution
    - Part 3 — The two types
    - Part 4 — Architecture
    - Part 5 — Worked example: online shopping (orchestration)
    - Part 6 — Issues and considerations
    - Part 7 — Use cases
    - Part 8 — System design examples
    - Part 9 — Saga vs. two-phase commit (2PC)
    - Part 10 — Common beginner misconceptions
    - Part 11 — Check your understanding
    - Part 12 — Interview soundbite (30 seconds)
    - Part 13 — Implementation
    - Related patterns
11. **Event-Driven Architecture (EDA) Pattern**
    - Part 0 — Concepts you need first
    - Part 1 — The problem
    - Part 2 — The solution
    - Part 3 — The benefits
    - Part 4 — The components
    - Part 5 — Three structural variants
    - Part 6 — Inner workings
    - Part 7 — Worked example: traffic management (Java)
    - Part 8 — Performance implications and considerations
    - Part 9 — Use cases
    - Part 10 — System design example: a ride-sharing app
    - Part 11 — Common beginner misconceptions
    - Part 12 — Check your understanding
    - Part 13 — Interview soundbite (30 seconds)
    - Part 14 — Implementation
    - Related patterns
12. **CQRS — Command Query Responsibility Segregation**
    - Part 0 — Concepts you need first
    - Part 1 — The problem
    - Part 2 — The solution
    - Part 3 — Architecture: three levels
    - Part 4 — Inner workings
    - Part 5 — Worked example: user profile management
    - Part 6 — Issues, considerations, and performance
    - Part 7 — Use cases
    - Part 8 — System design examples
    - Part 9 — Common beginner misconceptions
    - Part 10 — Check your understanding
    - Part 11 — Interview soundbite (30 seconds)
    - Part 12 — Implementation
    - Related patterns
13. **Configuration Externalization Pattern**
    - Part 0 — Concepts you need first
    - Part 1 — The framing
    - Part 2 — The problem
    - Part 3 — The solution
    - Part 4 — Architecture
    - Part 5 — Worked example: Spring Cloud Config
    - Part 6 — Considerations and implications
    - Part 7 — Real-world use cases

- Part 8 — Common beginner misconceptions
- Part 9 — Check your understanding
- Part 10 — Interview soundbite (30 seconds)
- Part 11 — Implementation
- Related patterns

14. **Chapter 14 — Interview Question Bank**
    - How to use this bank
    - 1. Fundamentals: monolith vs microservices
    - 2. Decomposition, DDD and migration
    - 3. Communication: REST, gRPC and messaging
    - 4. API Gateway, BFF, service discovery and service mesh
    - 5. Resilience and fault tolerance
    - 6. Data management: database per service, saga, outbox, CQRS, event sourcing
    - 7. Consistency, delivery guarantees and ordering
    - 8. Observability: logs, metrics and tracing
    - 9. Deployment: containers, Kubernetes, CI/CD and release strategies
    - 10. Configuration management
    - 11. Security: OAuth2, JWT, mTLS and zero trust
    - 12. Testing microservices
    - 13. Spring Cloud and Spring Boot specifics
    - 14. Scenario, troubleshooting and senior-level questions
    - 15. Rapid-fire "difference between X and Y" and short-answer round
    - Sources of the question lists

Chapter 1 — System Design Fundamentals

Module Introduction

What this module is. Every other module in these notes assumes you already know the basic vocabulary of system design: what *latency* means, what a *load balancer* does, why a *cache* helps, what *sharding* or *eventual consistency* are. This module teaches all of it from zero. If you have only ever written programs that run on one computer, start here.

How it is organised. Six parts, each building on the one before:

Part	What you learn
1 — Foundations and performance	Clients and servers, latency, throughput, percentiles, estimation, availability and the nines, SLAs, scaling up vs out, stateless services, bottlenecks, how a design interview runs
2 — Networking and communication	IP, ports, DNS, TCP/UDP/QUIC, HTTP versions, TLS, REST/gRPC/GraphQL, WebSockets and friends, proxies, API gateways, load balancers (every type and algorithm), CDNs
3 — Data storage	Relational databases, ACID, isolation levels, NoSQL families, indexes, replication, partitioning and sharding, consistent hashing, block/file/object storage, OLTP vs OLAP, durability
4 — Caching, async and consistency	Cache strategies and eviction, queues and streams, delivery guarantees, idempotency, consistency models, CAP/PACELC, quorums, consensus, clocks, 2PC and sagas, Bloom filters, ID generation
5 — Architecture, operations and security	Monolith vs microservices vs serverless, resilience patterns, rate limiting, autoscaling, containers and Kubernetes, CI/CD and deployments, observability, disaster recovery, auth, encryption, web security
6 — Putting it together	A request's journey end to end, a worked design, a decision cheat sheet, 60 interview questions and a master A–Z glossary

How to read it. Each concept follows the same rhythm as the rest of the book: *What it is → Why it matters → How it works → Types → Trade-offs → Common mistakes → Real-world examples → In the interview → TL;DR*. Read Parts 1–5 in order the first time; afterwards use the Part 6 glossary and cheat sheet as a reference. Every part ends with its own glossary table.

> These notes are written in my own words from official documentation, papers and engineering blogs; specific numbers were checked against their sources.

Part 1 — Foundations and performance

This part is the ground floor. It explains what "system design" means, names the basic pieces every web application is built from, and gives you the vocabulary for talking about speed (latency, throughput, percentiles), size (estimation, units), staying up (availability, reliability, durability) and growing (scalability). It ends with a step-by-step method for a system design interview. Nothing here assumes more than this: a website runs on a computer called a **server**, and you reach it from your phone or laptop over the internet.

What system design is

What it is

System design is the work of deciding which parts a piece of software needs, what each part does, how the parts talk to each other, and where data lives, so that the whole thing meets its goals. Those goals usually include serving a certain number of users, responding within a certain time, staying available when machines break, and costing an acceptable amount.

Writing code answers "how does this function work?". System design answers "how do these twenty programs, running on two hundred machines in three countries, work together without losing anyone's data?".

> **Analogy:** an architect designing a building does not lay bricks. They decide how many floors, where the lifts and fire exits go, how water and electricity flow, and how many people the building can hold. System design is the architect's job for software. The builders (programmers) then fill in each room.

Why it matters

A program that works perfectly for 10 users can collapse at 10 million. The code may be fine; the shape of the system is wrong. Typical shape problems are: one database that every request has to queue for, one machine whose failure takes the whole site down, or data stored so far from users that every page takes seconds. These are fixed by design decisions, not by better loops.

System design also matters for cost. Two designs that both work can differ by ten times in their monthly cloud bill.

How it works

Most system design follows the same loop:

1. **Understand the goal.** What must the system do (features), and how well (speed, size, uptime)?
2. **Estimate the load.** How many users, requests per second, gigabytes per day?
3. **Sketch the parts.** Clients, servers, databases, caches, queues and how requests flow between them.
4. **Find the weak spots.** Which part runs out of capacity first? Which part, if it dies, takes everything with it?
5. **Fix and justify.** Add or change parts, and state what each change costs.

You repeat this loop as the system grows. A design is never "finished"; it is right for a given load and set of goals.

Trade-offs

Almost every design choice gives something up. Faster reads may mean slower writes. More copies of data mean better safety but more cost and more chance that copies disagree. Simpler systems are easier to run but may not scale. A good designer names the trade-off out loud instead of pretending a choice is free.

Common mistakes

- Designing for Google-scale traffic when the product has 1,000 users. Extra parts add cost and failure points.
- Jumping to product names ("use Kafka") before stating the problem the product solves.
- Ignoring failure. Every machine, disk and network link eventually breaks.

In the interview

Q: What is the interviewer actually testing in a system design round?

A: Your ability to turn a vague product idea into a reasoned architecture: asking the right questions, estimating scale, choosing components, and explaining trade-offs. There is rarely one correct answer;

the reasoning is graded.

Q: How is system design different from coding?

A: Coding is about correctness inside one program. System design is about how many programs and machines cooperate, how they behave under load and failure, and what that costs.

TL;DR

System design is choosing the parts of a software system and how they fit together so it is fast enough, big enough, reliable enough and cheap enough. Every choice is a trade-off you should be able to explain.

Clients, servers and the request/response cycle

What it is

A **client** is any program that asks for something. Your web browser, a phone app, or even another server can be a client. A **server** is a program (and, loosely, the machine it runs on) that waits for requests and answers them.

The conversation between them follows the **request/response** pattern: the client sends a **request** ("give me the home page", "save this photo"), the server does some work, and sends back a **response** (the page, or "saved, here is its ID"). On the web, these messages usually use **HTTP** (HyperText Transfer Protocol), a standard text format for requests and responses. Part 2 covers HTTP in detail.

> **Analogy:** a restaurant. You (the client) tell the waiter your order (the request). The kitchen (the server) cooks it and the waiter brings the plate (the response). You don't need to know how the kitchen works; you only need to know how to order.

How it works

Here is what happens when you open `https://example.com/profile` in a browser, at the simplest level:

1. The browser finds the server's address on the internet (using **DNS**, the internet's phone book, covered in Part 2).
2. It opens a network connection to that server.
3. It sends an HTTP request such as:


```
GET /profile HTTP/1.1
Host: example.com
```

4. The server reads the request, looks up your profile (perhaps in a database), and builds a response.
5. It sends back something like:

```
HTTP/1.1 200 OK
Content-Type: text/html

<html> ... your profile ... </html>
```

6. The browser draws the page.



Types

- **Thin client vs thick client.** A thin client (a basic web page) does little work itself and relies on the server. A thick client (a mobile game, a desktop app) does a lot locally and talks to the server only for shared data.
- **Server-to-server.** Inside a large system, servers are constantly clients of other servers. The "profile service" may call the "photo service". The same request/response idea applies.
- **Push instead of pull.** Normally the client asks (pulls). Some features need the server to send data unasked (a chat message arriving). Techniques for this (WebSockets, Server-Sent Events) are in Part 2.

Common mistakes

- Thinking "server" always means one physical box. A server is a role. One machine can run many server programs, and one logical "server" (say, `api.example.com`) is often hundreds of machines behind a load balancer.
- Forgetting that the network between client and server is slow and unreliable compared with work inside one machine.

In the interview

Q: Can a server also be a client?

A: Yes. Any program that sends a request is acting as a client for that request. In a microservice system almost every service is both.

TL;DR

A client asks, a server answers. Almost everything on the web is a chain of request/response conversations, often with servers acting as clients of other servers.

The building blocks of a web application

What it is

Nearly every web application, from a blog to a bank, is built from the same handful of parts. Learn these and most architecture diagrams become readable.

Part	What it does	Everyday comparison
Client (browser/app)	Shows the interface, sends requests	The customer
Load balancer	Spreads requests across many servers	The host seating diners at free tables
App server	Runs the business logic	The kitchen
Database	Stores data permanently and lets you query it	The pantry and recipe book
Cache	Keeps a fast copy of popular data	Ingredients kept on the counter
Message queue	Holds jobs to be done later	The order ticket rail
Object storage	Stores large files (images, videos)	The warehouse
CDN	Copies static files close to users	Branch shops in every town

How it works

Client. The browser or mobile app. It renders the user interface and calls the backend over HTTP.

App server (application server). A program written in a language such as Java, Python, Go or JavaScript (Node.js) that receives requests, applies rules ("only friends may see this post"), reads and writes data, and returns a response. You usually run several identical copies so that one crash doesn't stop the site.

Load balancer. A component that sits in front of the app servers and forwards each incoming request to one of them, so no single server is overloaded and dead servers are skipped. (Covered in depth in Part 2.)

Database. Software that stores data durably (it survives power loss) and lets you search it. Examples: PostgreSQL, MySQL, MongoDB, DynamoDB. It is usually the hardest part to scale because it holds **state** (data that must be remembered). (Part 3.)


Cache. A small, fast store (usually in memory, RAM) holding copies of data that is read often, so the app doesn't have to ask the slower database every time. Redis and Memcached are common. Reading from RAM takes well under a millisecond; a database query may take several milliseconds or more. (Part 4.)

Message queue. A buffer where one part of the system drops a job ("send a welcome email to user 42") and another part picks it up later. This lets the web request return immediately while slow work happens in the background. Examples: RabbitMQ, Amazon SQS, Apache Kafka. (Part 4.)

Workers. Background programs that take jobs from the queue and do them.

Object storage. A service for storing big files ("objects") cheaply, addressed by a key such as `photos/42/avatar.jpg`. Amazon S3 is the best-known example. Databases are bad at storing large files; object storage is built for it. (Part 3.)

CDN (Content Delivery Network). A network of servers spread around the world that keep copies of static files (images, JavaScript, video) close to users, so a user in Sydney doesn't fetch every image from Virginia. (Part 2.)



Why it matters

In an interview you will draw some version of this diagram within the first fifteen minutes. Knowing what each box is for lets you justify adding it ("we add a cache because reads outnumber writes 100 to 1") rather than adding boxes because "big systems have them".

Common mistakes

- Adding every component by default. A small internal tool may need only one app server and one database.
- Storing images inside the database. Put files in object storage and keep only their key (address) in the database.
- Doing slow work (emails, video encoding) inside the web request. Put it on a queue.

Real-world examples

- Instagram's early stack (2011–2012) was Django app servers, PostgreSQL, Redis and Memcached, with photos in Amazon S3 — almost exactly the diagram above.
- Most cloud tutorials (AWS, Google Cloud, Azure) describe a "three-tier" app: presentation (client), logic (app servers), data (database), with caches and queues added as it grows.

In the interview

Q: Why not keep everything on one server?

A: One server is a single point of failure (if it dies the site is down) and has a hard capacity limit. Splitting into stateless app servers behind a load balancer, plus a separate database, lets you add servers and survive crashes.

Q: When do you add a queue?

A: When some work is slow, can be done later, or comes in bursts. The queue lets the user get a fast response and smooths spikes for the workers behind it.

TL;DR

Client, load balancer, app servers, database, cache, queue with workers, object storage and CDN are the standard building blocks. Each solves one problem; add each one only when you can name that problem.

Latency, throughput and bandwidth

What it is

These three words describe speed, but different kinds of speed.

- **Latency** is how long one thing takes: the delay between asking and getting the answer. Measured in time: milliseconds (ms, thousandths of a second) or microseconds (µs, millionths; written "us" in plain text).
- **Throughput** is how many things get done per unit of time: requests per second, messages per second, megabytes per second.
- **Bandwidth** is the maximum amount of data a network link (or disk, or memory bus) can carry per second. It is a capacity, like the width of a pipe. Measured in bits per second (Mbps, Gbps).


> **Analogy:** a motorway. Latency is how long one car takes to drive from London to Birmingham (about 2 hours). Bandwidth is how many lanes the motorway has. Throughput is how many cars actually arrive per hour, which can be lower than the lanes allow if there is a crash or a toll booth.

Response time vs latency

People often use these as synonyms, but strictly:

- **Response time** is what the client experiences: the full time from sending a request to receiving the complete answer. It includes network travel both ways, time waiting in queues, and the actual processing.
- **Latency**, used strictly, covers only delay: the stretch before a server starts on the request (sitting in a queue, travelling a network hop), not the work itself.
- **Service time** is the time the server spends actually working on it.

So: response time = network delay + queueing delay + service time. In interviews "latency" almost always means response time; just be clear which one you mean when it matters.



Why it matters

- Users feel latency. Interfaces under about 100 ms feel instant; delays over a second break concentration. Google and Amazon have both reported that small added delays measurably reduce searches and sales.
- Throughput decides how many machines you need. If one server handles 1,000 requests per second and you expect 50,000, you need at least 50 (and more for headroom).
- Bandwidth decides whether large transfers (video, backups) are even possible in time.


How it works

Where latency comes from. A request picks up delay at every step:

1. **Propagation delay:** signals in fibre travel at roughly two thirds the speed of light, about 200 km per millisecond. London to New York is about 5,600 km, so one way takes at least 28 ms, and a real **round trip** (there and back, RTT) is typically about 70 ms because cables don't run in straight lines and routers add delay.
2. **Transmission delay:** time to push the bits onto the wire. Sending 1 MB (8 megabits) over a 100 Mbps link takes 80 ms; over 1 Gbps, 8 ms. This is where bandwidth matters.
3. **Queueing delay:** waiting behind other requests at routers, load balancers, thread pools, database locks.
4. **Processing delay:** the actual work: parsing, running code, reading disk.

Latency and bandwidth are independent. A satellite link may have huge bandwidth and terrible latency (about 600 ms round trip for geostationary satellites). A small request is limited by latency; a large file download is limited by bandwidth. Adding bandwidth does not make a small API call faster.

Throughput and latency are linked through load. At low load, throughput rises as you send more requests and latency stays flat. As a server approaches full use, requests start waiting for each other and latency shoots up, while throughput levels off. Running a server with its CPU (central processing unit, the processor) 95% busy usually means terrible latency.



Trade-offs

- **Batching** improves throughput but hurts latency: waiting to collect 100 writes and sending them together is efficient, but the first write waits for the other 99.
- **Spare capacity** keeps latency low but costs money. Many teams target 50–70% peak utilisation so that bursts don't create queues.

Common mistakes

- Mixing bits and bytes. Network speeds are in bits (Mbps); file sizes are in bytes (MB). 1 byte = 8 bits, so a 100 Mbps link moves at most 12.5 MB per second.
- Assuming more bandwidth fixes slowness. If the problem is round trips (a page making 40 sequential API calls), only fewer round trips or shorter distances help.
- Measuring throughput without latency (or the reverse). "10,000 requests per second" means nothing if each takes 5 seconds.

Real-world examples

- Video streaming (Netflix, YouTube) is bandwidth-bound: a 4K stream needs roughly 15–25 Mbps.
- High-frequency trading firms pay for microwave links between Chicago and New York because they shave a few milliseconds of propagation delay compared with fibre.
- Online games are latency-bound: players feel the difference between 20 ms and 120 ms "ping" (round-trip time).

In the interview

Q: What is the difference between latency and throughput?

A: Latency is how long one request takes; throughput is how many requests complete per second. You can have high throughput with high latency (a cargo ship) or low latency with low throughput (a motorbike courier).

Q: A user in Australia complains the site is slow; servers are in Virginia. What helps?

A: The round trip is roughly 200 ms, so cut round trips: serve static files from a CDN near them, reduce the number of sequential calls, reuse connections, and consider a regional deployment closer to them. More bandwidth won't help much.

TL;DR

Latency is time per request, throughput is requests per time, bandwidth is the pipe's maximum capacity. They are related through load: push a system near its limit and latency rises sharply.

Percentiles, tail latency and why averages lie

What it is

A **percentile** tells you the value below which a given percentage of measurements fall. If the **p95** (95th percentile) latency is 300 ms, then 95% of requests finished in 300 ms or less, and 5% took longer.

The common ones:

Name	Meaning	1 in N requests slower
p50 (median)	Half are faster, half slower	1 in 2
p90	90% are faster	1 in 10
p95	95% are faster	1 in 20
p99	99% are faster	1 in 100
p999 (p99.9)	99.9% are faster	1 in 1,000

Tail latency means the slow end of the distribution: p99, p999 and the maximum. These are "the tail" because on a graph of latencies the slow requests form a long thin tail to the right.

> **Analogy:** a bus route. "The average trip takes 20 minutes" sounds fine. But if one trip in ten takes 90 minutes because of a broken-down bus, someone who rides twice a day gets stuck several times a month. The p95 (90 minutes) describes their real worry far better than the average.

Why averages lie

The **mean** (average) mixes fast and slow requests into one number that may match no real request. Take ten requests:

```
10, 10, 10, 10, 10, 10, 10, 10, 10, 1000   (milliseconds)
```


- Mean = 1090 / 10 = 109 ms. No request actually took 109 ms.
- Median (p50) = 10 ms. The typical user is happy.
- p95 and p99 = 1000 ms (they land on the slowest request). One user in ten waits a full second.

The mean hides the 1-second outlier inside a number that looks moderate. In real systems latency is almost never a neat bell curve; it is skewed, with a long tail caused by garbage collection pauses, cache misses, slow disks, retries and queueing. Percentiles show the shape; averages flatten it.

Why the tail matters more than you think

1. **Heavy users hit the tail most.** A user who loads 100 pages a day hits your p99 about once a day. Often these are your most valuable customers (they have the most data, the biggest carts).

2. **Fan-out amplifies the tail.** If one user request calls 100 backend servers in parallel and waits for all of them, the request is as slow as the slowest server. Suppose each server is slow (1 second) just 1% of the time. The chance that *at least one* of 100 is slow is 1 − 0.99^100 ≈ 63%. So a 1-in-100 problem per server becomes a nearly 2-in-3 problem for the user. This effect is described in Google's well-known paper "The Tail at Scale" (Dean and Barroso, 2013).



How it works

Measuring percentiles. Record each request's latency, sort them, and pick the value at the required position (the 990th of 1,000 sorted values is roughly p99). Real monitoring systems can't store every value, so they use compact summaries called **histograms** (counts per latency bucket, e.g. 0–10 ms, 10–25 ms ...) or sketches such as HDRHistogram or t-digest, which estimate percentiles with small error.

Do not average percentiles. The p99 of server A plus the p99 of server B divided by two is not the p99 of the combined traffic. Merge the histograms and compute the percentile from the merged data.

Reducing tail latency. Common techniques:

- **Hedged requests:** if a reply hasn't come back within (say) the p95 time, send the same request to a second replica and use whichever answers first.
- **Timeouts and fewer fan-out calls.**
- Removing sources of pauses: tune garbage collection, avoid shared locks, keep spare capacity so queues stay short.

Common mistakes

- Reporting only the average in dashboards or SLOs.
- Measuring latency only on the server. The client also sees network time, DNS lookups and connection setup.
- **Coordinated omission:** a load-test tool that waits for each slow response before sending the next request quietly sends fewer requests during slow periods, so it under-reports the tail.

Real-world examples

- Amazon has long described setting internal service targets at p99.9 rather than averages, so that even its heaviest customers get good performance.
- Monitoring tools such as Prometheus, Datadog and Grafana show latency as p50/p95/p99 lines by default.

In the interview

Q: Why use p99 instead of the average for an SLO?

A: The average hides slow outliers and doesn't describe any real user. p99 says "99% of requests are at least this fast", which captures the experience of the unlucky but common slow cases.

Q: Your service's p99 is fine but users still complain. Why might that be?

A: Each page may call many services or make many requests, so the chance of hitting at least one slow call per page is much higher than 1%. Look at end-to-end page latency and fan-out, not each service in isolation.

TL;DR

Use percentiles (p50, p95, p99, p999), not averages, to describe latency. The slow tail matters because heavy users and fan-out make rare slowness common.

Little's law

What it is

Little's law is a simple rule that holds for any stable system where items arrive, wait or get served, and leave:

```
L = λ × W
```

- **L** = the average number of items inside the system at once (requests in flight, people in a shop).
- **λ** (lambda) = the average arrival rate (requests per second). In a stable system this equals the throughput.
- **W** = the average time each item spends inside (latency).

> **Analogy:** a coffee shop. If 2 customers arrive per minute and each stays 10 minutes, then on average 2 × 10 = 20 customers are in the shop. You don't need to know anything about how the barista works.

Why it matters

It lets you work out any one of the three numbers from the other two, which is extremely handy for sizing:

- **How many concurrent connections or threads do I need?** If a service gets 1,000 requests per second and each takes 200 ms (0.2 s), then on average 1,000 × 0.2 = **200 requests are in flight**. You need at least 200 worker threads or connections (plus headroom), or requests will queue.
- **What throughput can I get?** A database connection pool of 20 connections, with queries taking 5 ms each, can serve at most 20 / 0.005 = **4,000 queries per second**.
- **Why did latency double?** If concurrency limits stay fixed and latency doubles (a slow dependency), maximum throughput halves.

How it works

1. Pick the boundary of your "system": one server, one thread pool, one queue, the whole service.
2. Measure or assume two of the three numbers over a long enough period for the system to be stable (arrivals roughly equal departures).
3. Compute the third.

Rearranged forms:

- W = L / λ (latency from in-flight count and rate)
- λ = L / W (throughput from concurrency limit and latency)

Common mistakes

- Applying it to an unstable system where the queue keeps growing (arrival rate above capacity). Then there is no steady state and L grows without limit.
- Forgetting units. Convert milliseconds to seconds before multiplying by "per second".

In the interview

Q: A service handles 5,000 requests per second with an average latency of 40 ms. How many requests are being processed at any moment?

A: L = 5,000 × 0.04 = 200 requests in flight on average. If the service has 50 instances, that's about 4 per instance.

Q: Your thread pool has 100 threads and each request holds a thread for 250 ms. What is the max throughput?

A: λ = 100 / 0.25 = 400 requests per second. Beyond that, requests queue and latency rises.

TL;DR

Items in the system = arrival rate × time in system. Use it to size thread pools, connection pools and fleets, and to explain why slower dependencies cut throughput.

Latency numbers every engineer should know

What it is

A list of rough costs for common operations, first popularised by Google's Jeff Dean and Peter Norvig. The exact numbers change with hardware (the table below uses rounded figures for current machines; the original list, for example, gave 150 us for an SSD random read); what matters is the **order of magnitude** (whether something takes nanoseconds, microseconds or milliseconds) and the ratios between them.

Units: 1 ns (nanosecond) = one billionth of a second. 1 µs (microsecond) = 1,000 ns. 1 ms (millisecond) = 1,000 µs.

Operation	Approximate time	Scaled: if 1 ns were 1 second
CPU L1 cache read	1 ns	1 second
CPU L2 cache read	4 ns	4 seconds
Main memory (RAM) read	100 ns	about 2 minutes
Compress 1 KB (fast algorithm)	2 us	about half an hour
Send 1 KB over 1 Gbps network	10 us	about 3 hours
Read 4 KB at random from NVMe SSD	20-100 us	6 hours to a day
Read 1 MB sequentially from RAM	50-250 us	14 hours to 3 days
Round trip inside one data centre	0.5 ms (500 us)	about 6 days
Read 1 MB sequentially from SSD	0.2-1 ms	2 to 12 days
Hard disk (HDD) seek	10 ms	about 4 months
Read 1 MB sequentially from HDD	5-20 ms	2 to 8 months
Round trip London to New York	70 ms	about 2 years
Round trip California to Europe	150 ms	about 5 years


(A **CPU cache** is a tiny, very fast memory built into the processor. **RAM** is the computer's main working memory, lost on power-off. An **SSD** is a solid-state drive with no moving parts; an **HDD** is a spinning magnetic disk with a moving arm, which is why "seeking" to a new position is slow.)

Why it matters

These numbers drive design decisions:

- **Memory is about 100 to 1,000 times faster than SSD for random reads**, and SSD is about 100 times faster than spinning disk. That's why caches live in RAM.

- **A network round trip inside a data centre (0.5 ms) costs as much as thousands of memory reads.** A loop that makes 1,000 small database calls spends at least half a second just on round trips. Batch them.
- **Crossing an ocean costs 70–150 ms per round trip**, and the speed of light is not getting faster. Only moving data closer to users (CDNs, regional servers) fixes it.
- **Sequential reads are far faster than random reads**, especially on HDD. Many storage engines (append-only logs, and the log-structured merge trees, or LSM-trees, of Part 3) are designed to write sequentially for this reason.



Common mistakes

- Memorising exact numbers. Interviewers want orders of magnitude: "RAM is nanoseconds, SSD microseconds, network and disk milliseconds".
- Treating a remote cache (Redis over the network) as "as fast as memory". The RAM read is 100 ns, but the network round trip to reach it is ~0.5 ms. It is still far faster than a typical database query, but not free.

In the interview

Q: Why is a cache faster than a database?

A: A cache serves data from RAM (nanoseconds per read plus one network hop), while a database may read from disk, parse a query, take locks and do more work. Typical cache hits take well under 1 ms; database queries often take several ms or more.

Q: Why does a service that calls another service 50 times per request feel slow even though each call is "fast"?

A: Each call costs at least a network round trip (~0.5 ms in the same data centre, more across zones), and sequential calls add up: 50 × 1 ms = 50 ms before any real work. Batch or parallelise the calls.

TL;DR

Memory is nanoseconds, SSD is tens of microseconds, data-centre network is half a millisecond, spinning disks and cross-continent trips are tens to hundreds of milliseconds. Design so the hot path stays at the fast end.

Units, powers of two and data sizes

What it is

Estimation needs a shared vocabulary for size. Data is measured in **bits** (a single 0 or 1) and **bytes** (8 bits, enough for one English letter).

Unit	Bytes (decimal, used in estimates)	Power of two (exact)	Roughly holds
KB (kilobyte)	1,000	2^10 = 1,024	A short text message or tweet with metadata
MB (megabyte)	1,000,000 (10^6)	2^20 ≈ 1.05 million	A high-quality photo, a minute of MP3
GB (gigabyte)	10^9	2^30 ≈ 1.07 billion	An hour of streamed HD video (a few GB)
TB (terabyte)	10^12	2^40 ≈ 1.1 trillion	A typical laptop drive
PB (petabyte)	10^15	2^50	A large company's data warehouse

Above PB come EB (exabyte, 10^18) and ZB (zettabyte, 10^21). Strictly, the power-of-two units have their own names (KiB, MiB, GiB), but in estimates everybody rounds 2^10 to 1,000. The 2–10% error doesn't matter.

How it works

Powers of two to remember:

- 2^10 ≈ 1 thousand (10^3)
- 2^20 ≈ 1 million (10^6)
- 2^30 ≈ 1 billion (10^9)
- 2^40 ≈ 1 trillion (10^12)
- 2^32 ≈ 4.3 billion (the number of IPv4 addresses, and the limit of an unsigned 32-bit integer; a 32-bit ID column runs out at about 2 billion signed or 4 billion unsigned)
- 2^64 ≈ 1.8 × 10^19 (plenty for any ID)

Typical sizes of things:

Item	Rough size
A number (integer)	4 or 8 bytes
A timestamp	8 bytes
A UUID (random unique ID)	16 bytes (36 characters as text)
A short text post with metadata	0.5-1 KB
A web page's HTML	50-100 KB
A compressed photo	200 KB - 2 MB
One minute of HD video	roughly 25-60 MB

Time conversions:

- 1 day = 86,400 seconds ≈ **10^5 seconds** (round it; makes maths easy).
- 1 month ≈ 2.5 million seconds (2.6 × 10^6).
- 1 year ≈ 31.5 million seconds (≈ 3 × 10^7).

Shortcut: 1 million requests per day ≈ 12 requests per second (10^6 / 86,400 ≈ 11.6). So "X million per day" ≈ "12 × X per second".

Common mistakes

- Mixing bits and bytes: a "1 Gbps" network card moves 125 MB per second at best.
- Carrying too many digits. Round to one or two significant figures and say so.

TL;DR

KB, MB, GB, TB, PB each step up by about 1,000 (2^10). A day is about 10^5 seconds, so 1 million per day is about 12 per second.

Back-of-the-envelope estimation

What it is

A **back-of-the-envelope estimate** is a quick, rough calculation (small enough to scribble on an envelope) that tells you the size of a problem: how many requests per second, how much storage, how much bandwidth, how many servers. The goal is the right **order of magnitude** (is it 10, 1,000 or 1,000,000?), not precision.

> **Analogy:** before a road trip you estimate "about 400 km, about 5 hours, need to refuel once". You don't compute it to the minute, but it tells you whether to leave at 6 am or noon.

Why it matters

The estimate decides the architecture. 100 requests per second fits on one server with one database. 100,000 per second needs many servers, caching, and probably sharded data (split across many databases). 10 GB of data fits in memory on one machine; 10 PB needs a distributed storage system. Without numbers you can't tell which design is needed.

How it works

The key terms:

- **DAU (Daily Active Users):** distinct users who use the product on a given day. **MAU** is the same per month. DAU is usually 20–50% of MAU for social apps.
- **QPS (Queries Per Second)** or **RPS (Requests Per Second):** how many requests reach the system each second.
- **Average QPS** = total requests per day / 86,400.
- **Peak factor:** traffic is not flat. Evenings, weekends, or events (a sale, a football final) create peaks. Peak QPS is commonly estimated as **2–3 times** the average, sometimes 5–10× for spiky products.
- **Read/write ratio:** how many reads per write. Social feeds might be 100:1; logging systems are almost all writes.
- **Storage per day** = new items per day × size of each item.
- **Bandwidth** = QPS × size of each response (or request).


Step by step, worked example — a photo-sharing app:

Assumptions (state them out loud):

- 10 million DAU.
- Each user views 50 photos and uploads 0.2 photos per day (one in five users posts once).
- Average photo after compression: 500 KB. Metadata per photo: 1 KB.
- Keep data for 5 years.

1. **Read QPS:** 10M × 50 = 500M views per day. 500M / 10^5 ≈ **5,000 QPS** average. Peak (×3) ≈ **15,000 QPS**.
2. **Write QPS:** 10M × 0.2 = 2M uploads per day ≈ **20 uploads per second** average, ~60 at peak. Read:write ≈ 250:1, so this is a read-heavy system: caching and a CDN will matter a lot.
3. **Storage per day:** 2M × 500 KB = 1,000,000 MB = **1 TB per day** of photos, plus 2M × 1 KB = 2 GB per day of metadata.
4. **Storage for 5 years:** 1 TB × 365 × 5 ≈ **1.8 PB** of photos (more with replicas: typically × 3). Metadata ≈ 3.6 TB. So photos go in object storage; metadata fits in a (sharded) database.
5. **Outgoing bandwidth:** 5,000 views/s × 500 KB = 2,500 MB/s = **2.5 GB/s ≈ 20 Gbps** average. That's a strong argument for a CDN.

6. **Servers:** if one app server handles ~1,000 simple requests per second, peak 15,000 QPS needs ~15 servers, so plan ~20–30 for headroom and failures.



Rules of thumb for capacity (very rough, for simple workloads on modern hardware):

Component	Rough capacity per machine
Web/app server (simple API)	1,000-10,000 requests/s
Relational database (simple indexed queries)	1,000-10,000 queries/s, more for cached reads
Redis/Memcached cache	100,000+ operations/s
Kafka broker	hundreds of MB/s

Trade-offs

More precise estimates take longer and rarely change the design. Spend 3–5 minutes in an interview, write numbers down, and move on.

Common mistakes

- Forgetting the peak. Systems fall over at peak, not at average.
- Forgetting replication: storing 3 copies triples storage.
- Forgetting metadata, indexes and logs, which can add 20–50%.
- False precision ("11,574.07 QPS"). Say "about 12,000".
- Doing maths silently. Say each assumption so the interviewer can correct it.

Real-world examples

- WhatsApp said in late 2020 that it delivers about 100 billion messages per day. 10^11 / 10^5 ≈ 1 million messages per second on average, a useful anchor for "very large" chat scale.
- YouTube said in 2019 that more than 500 hours of video are uploaded every minute. That is about 720,000 hours a day, which makes its storage needs enormous.

In the interview

Q: A service has 100 million DAU, each making 20 requests per day. What QPS should you plan for?

A: 100M × 20 = 2 billion requests per day. 2 × 10^9 / 10^5 = 20,000 QPS average. With a peak factor of 3, plan for about 60,000 QPS.

Q: Why bother estimating if numbers are guesses?

A: The order of magnitude decides the architecture: whether one database is enough, whether data fits in memory, whether you need a CDN. Even rough numbers rule designs in or out.

TL;DR

Start from DAU and per-user actions, convert per day to per second by dividing by about 10^5, multiply by 2–3 for peak, and compute storage and bandwidth from item sizes. Round aggressively and state every

assumption.

Availability and the nines

What it is

Availability is the fraction of time a system is up and doing its job (answering requests correctly). It is usually written as a percentage with many 9s, so people talk about "three nines" (99.9%) or "four nines" (99.99%).

Availability = uptime / (uptime + downtime), or, measured by requests, successful requests / total valid requests.

> **Analogy:** a shop that is supposed to be open 24 hours. If it is closed by surprise for 9 hours across a whole year, it was available about 99.9% of the time.

The nines table

(Year = 365 days, month = 30 days.)

Availability	Name	Downtime per year	Downtime per month	Downtime per day
99%	two nines	3.65 days	7.2 hours	14.4 minutes
99.9%	three nines	8.76 hours	43.2 minutes	1.44 minutes
99.95%	three and a half	4.38 hours	21.6 minutes	43 seconds
99.99%	four nines	52.6 minutes	4.32 minutes	8.6 seconds
99.999%	five nines	5.26 minutes	26 seconds	0.86 seconds

Each extra nine cuts allowed downtime by 10×, and usually costs much more than 10× the engineering effort.

Why it matters

- Downtime costs money and trust. An online shop down for an hour on Black Friday loses that hour's sales permanently.
- The target decides the design. 99% can survive manual recovery ("someone restarts the server in the morning"). 99.99% leaves 4 minutes a month, which is less than the time it takes a human to wake up and log in, so recovery must be **automatic**.

How it works

Availability of parts in series (all must work). If a request passes through a load balancer (99.99%), an app server (99.9%) and a database (99.9%), all three must be up:


Availability = 0.9999 × 0.999 × 0.999 ≈ 0.9979 → **99.79%**.


The chain is weaker than its weakest link. Every dependency you add in series lowers availability.

Availability of parts in parallel (any one is enough). Two independent servers, each 99%: the system is down only when both are down at the same time.

Availability = 1 − (0.01 × 0.01) = 1 − 0.0001 = **99.99%**.

Redundancy turns two "two nines" machines into a "four nines" pair, assuming failures are independent (they often aren't fully, e.g. both in the same rack lose power together).





Trade-offs

Higher availability needs redundancy (more machines, more data centres), automation, testing and on-call staff. Going from 99.9% to 99.99% might mean running in multiple data centres with automatic failover, which roughly doubles infrastructure and adds complexity. Many internal tools are fine at 99.5%.

Common mistakes

- Promising five nines without the budget. Even the big cloud providers' SLAs for single services are usually 99.9%–99.99%.
- Forgetting dependencies. Your service can't be more available than the things it needs in series (unless you design fallbacks).
- Counting planned maintenance as "not downtime". Users don't care why it's down.

Real-world examples

- Amazon S3 Standard is designed for 99.99% availability, and its SLA promises 99.9% per month (with service credits below that).
- Telephone networks were historically engineered for five nines.

In the interview

Q: How much downtime per month does 99.9% allow?

A: About 43 minutes. 99.99% allows about 4.3 minutes.

Q: How do you get higher availability than any single machine provides?

A: Run redundant copies in parallel with automatic failover, and remove single points of failure, ideally spreading copies across separate failure domains (racks, zones, regions).

TL;DR

Availability is the share of time a system works. Each extra nine is ten times less downtime: 99.9% is about 43 minutes a month, 99.99% about 4. Series dependencies multiply down; parallel redundancy multiplies up.

SLA, SLO, SLI and error budgets

What it is

Three related terms, from most technical to most legal:

- **SLI (Service Level Indicator):** a *measurement* of how the service is doing. Example: "percentage of HTTP requests that returned successfully in under 300 ms over the last 30 days."
- **SLO (Service Level Objective):** an internal *target* for an SLI. Example: "99.9% of requests succeed in under 300 ms, measured over 30 days."
- **SLA (Service Level Agreement):** a *contract* with customers saying what happens if a target is missed, usually refunds or service credits. Example: "If monthly availability falls below 99.9%, customers get 10% of their bill back."

> **Analogy:** a pizza shop. The SLI is "how long deliveries actually take". The SLO is the manager's target: "95% delivered within 30 minutes". The SLA is the printed promise: "over 45 minutes and it's free".

The SLA is normally looser than the SLO, so the team gets warning (missing the SLO) before the company has to pay (missing the SLA).


Error budgets

An **error budget** is the amount of unreliability the SLO allows. If the SLO is 99.9% success, the error budget is 0.1%: in a month with 100 million requests, up to 100,000 may fail (or about 43 minutes of full outage).

The budget turns reliability into a shared decision:

- While budget remains, the team can ship features fast and take risks.
- When the budget is spent, the team slows releases and works on reliability until it recovers.

This idea comes from Google's **Site Reliability Engineering (SRE)** practice. SRE is the discipline of running production systems using software engineering methods.



How it works

1. Choose SLIs that reflect what users feel: availability (success rate), latency (p99 under X ms), freshness (data no older than Y), durability.
2. Set an SLO slightly below what users actually need, not "100%". 100% is impossible and leaves no room to change anything.
3. Measure over a window (often 28 or 30 days, rolling).
4. Alert when the budget is being burned too fast (Part 5 covers burn-rate alerts).

Common mistakes

- Setting the SLO to 100%. Any deployment risk then "violates" it.
- Choosing SLIs users don't feel (CPU usage) instead of ones they do (failed checkouts).
- Making the SLA as tight as the SLO, leaving no warning margin.

In the interview

Q: What's the difference between an SLO and an SLA?

A: An SLO is an internal target for a measured indicator; an SLA is an external contract with penalties. SLAs are usually set looser than SLOs.

Q: What is an error budget used for?

A: It quantifies how much failure is acceptable (1 − SLO). Teams spend it on releases and experiments; when it's used up, they prioritise reliability work.

TL;DR

SLI is the measurement, SLO the target, SLA the contract with penalties. The error budget (1 − SLO) is how much failure you can "spend" before you must slow down and fix reliability.

MTBF, MTTR and measuring failure

What it is

Two averages that describe how often things break and how fast they're fixed:

- **MTBF (Mean Time Between Failures):** average time a system runs before it fails. Higher is better.
- **MTTR (Mean Time To Repair / Recover):** average time from a failure until service is restored. Lower is better.

Related: **MTTD (Mean Time To Detect)**, how long before anyone notices, and **MTTF (Mean Time To Failure)**, used for parts that are replaced rather than repaired (like disks).

> **Analogy:** a car. MTBF is how many months it typically goes between breakdowns. MTTR is how long it sits at the garage each time.

How it works

Availability can be estimated as:

```
Availability = MTBF / (MTBF + MTTR)
```

Example: a server fails on average every 1,000 hours (MTBF) and takes 1 hour to recover (MTTR). Availability = 1,000 / 1,001 ≈ 99.9%.

There are two levers:

1. **Increase MTBF:** better hardware, testing, careful deployments.
2. **Decrease MTTR:** fast detection (monitoring and alerts), automatic failover, quick rollback, runbooks.

In large distributed systems, failures are constant, so cutting MTTR is usually the cheaper lever. If recovery is automatic and takes 10 seconds instead of 1 hour, the same failure rate gives about 99.9997% availability.

Common mistakes

- Only trying to prevent failures. You can't prevent them all; plan to recover fast.
- Ignoring detection time. An outage nobody notices for 30 minutes has at least 30 minutes of MTTR.

In the interview

Q: Which is easier to improve at scale, MTBF or MTTR?

A: Usually MTTR. With thousands of machines something always fails, so automatic detection and failover (seconds) give more availability than trying to make each machine fail less often.

TL;DR

MTBF is how long between failures, MTTR how long to recover. Availability ≈ MTBF / (MTBF + MTTR); in practice, shrink MTTR with monitoring and automation.

Reliability, availability and durability

What it is

Three words often mixed up:

- **Reliability:** the system keeps doing the *right thing* over time, even when things go wrong. It returns correct results and doesn't corrupt data. A reliable system is one you can trust.
- **Availability:** the system is *up and responding* when you ask. A system can be available but unreliable (it answers quickly, with wrong data).
- **Durability:** once data is saved, it *stays saved* and isn't lost, even if machines crash or disks die. A system can be unavailable but durable (down for an hour, but no data lost when it returns).

> **Analogy:** a bank. Availability: the cash machine works when you walk up. Reliability: it gives you the right amount and debits the right account. Durability: your balance is still there tomorrow even if the bank's building floods.

Property	Question it answers	Typical measure
Availability	Can I use it right now?	% uptime, % successful requests
Reliability	Does it work correctly over time?	Failure rate, MTBF, correctness
Durability	Will my saved data still exist later?	Probability of losing an object per year

How it works

- Availability is improved by redundancy and failover (more on this below).
- Durability is improved by keeping multiple copies of data on separate disks, machines and locations, writing to disk before confirming (Part 3 covers write-ahead logs), and backups.
- Reliability is the umbrella: testing, validation, handling faults gracefully, and both of the above.

Real-world examples

- Amazon S3 Standard is designed for 99.999999999% ("eleven nines") yearly durability per object: keep ten million objects there and, on average, a single one goes missing roughly once in ten thousand years. It is designed for only 99.99% availability (and its SLA pays credits below 99.9%). Durability and availability are separate promises.

Common mistakes

- Saying "highly available" when you mean "doesn't lose data". Say durable.
- Assuming replication equals backup. If a bug deletes data, replication faithfully deletes every copy. Backups protect against that.

In the interview

Q: Can a system be durable but not available?

A: Yes. If a database cluster is down for maintenance, no one can read the data (unavailable), but all of it is safely on disk (durable).

TL;DR

Availability = can I use it now; reliability = does it work correctly over time; durability = will saved data survive. They are improved by different techniques and promised separately.

Faults, failures and fault tolerance

What it is

- A **fault** is something going wrong with one part: a disk dies, a process crashes, a network cable is cut, a bug returns a wrong value.
- A **failure** is when the *whole system* stops providing its service to users.

Faults are inevitable; failures are what we try to prevent. **Fault tolerance** (or resilience) is the ability of a system to keep working, perhaps in a reduced way, when some of its parts have faults.

> **Analogy:** a plane with two engines. One engine stopping is a fault. The plane crashing would be a failure. Being able to fly and land on one engine is fault tolerance.

Types

Common kinds of faults:

Fault type	Example	Typical defence
Hardware	Disk dies, power supply fails	Redundant machines, replicated data
Software	Bug, memory leak, crash on bad input	Testing, gradual rollouts, restarts
Network	Packets lost, link cut, partition	Timeouts, retries, replicas in other zones
Human	Wrong config pushed, table deleted	Reviews, automation, backups, rollback
Dependency	Third-party API is slow or down	Timeouts, fallbacks, circuit breakers

Faults also differ by behaviour:

- **Crash (fail-stop):** the part stops completely. Easiest to detect.
- **Omission:** some messages are lost.
- **Timing / slow:** the part works but too slowly. Hard to tell from a crash; often worse, because callers keep waiting.
- **Byzantine:** the part sends wrong or even malicious answers. Most business systems assume this doesn't happen inside their own network; blockchains are designed for it.

How it works

Fault tolerance generally follows a pattern: **detect** the fault (health checks, timeouts, heartbeats), **isolate** it so it doesn't spread (timeouts, bulkheads), and **recover** (route around it, restart, fail over to a copy). Parts 4 and 5 cover the specific tools: retries, circuit breakers, replication, consensus.

Common mistakes

- Treating "slow" as fine. A dependency that takes 30 seconds to fail can tie up all your threads; a fast error is often better.
- Assuming faults are independent. A bad deployment or a shared power supply can break many "redundant" copies at once (**correlated failure**).

Real-world examples

- Netflix's Chaos Monkey randomly shuts down production servers so that engineers must build services that tolerate instance faults.
- Large cloud outages are often caused by a configuration change pushed everywhere at once, a reminder that human and software faults matter as much as hardware.

In the interview

Q: What is the difference between a fault and a failure?

A: A fault is a component misbehaving; a failure is the system as a whole not serving users. Fault tolerance stops faults from becoming failures.

TL;DR

Faults happen to parts; failures happen to the system. Design to detect, isolate and recover from faults so they don't become user-visible failures.

Redundancy, single points of failure and failover

What it is

- **Redundancy** means having more than one of something, so a spare can take over if one breaks: extra servers, extra copies of data, extra network links, extra power supplies.
- A **single point of failure (SPOF)** is any part whose failure alone brings down the whole system. One database, one load balancer, one DNS provider, one data centre, even one engineer who knows the password.
- **Failover** is the process of switching work from a failed component to a standby one.

> **Analogy:** a hospital has backup generators. Mains power is a SPOF without them; with them, a blackout triggers failover to the generators within seconds.

How it works

Finding SPOFs: walk through the diagram and ask of every box and arrow, "if this disappears, what happens?". If the answer is "everything stops", it's a SPOF.

Removing them:

1. Run at least two of every critical component, in separate **failure domains**: different racks, different **availability zones** (separate data centres in the same region, with their own power and networking), or different regions.
2. Put something in front that can route around dead copies (a load balancer, DNS, a client library).
3. Add **health checks**: periodic tests ("are you alive?") so dead copies are detected.
4. Automate failover so it happens in seconds, not when a human notices.


Types

Active-passive (primary-standby): one copy handles all traffic; a standby waits, kept up to date, and takes over when the primary fails. Simple, but the standby is idle capacity, and failover takes some time (seconds to minutes).

Active-active: all copies handle traffic at the same time. If one fails, the others absorb its share. Better use of hardware and faster recovery, but harder for stateful parts like databases (two copies accepting writes can conflict).

Cold, warm and hot standby:

- **Cold:** the spare exists but must be started and loaded with data (minutes to hours).
- **Warm:** running and partially up to date (minutes).
- **Hot:** running and fully in sync, ready immediately (seconds).



N+1 and N+2: if you need N servers to handle peak load, run N+1 (survive one failure) or N+2 (survive one failure during maintenance of another).

Trade-offs

- Redundancy costs money: standby machines, extra copies of data.
- Failover is risky. If the system wrongly decides the primary is dead while it's actually alive (perhaps just slow or cut off), you can end up with two primaries both accepting writes, called **split brain**. Part 3 and Part 4 cover how databases prevent this (quorums, fencing).
- Failover itself must be tested regularly; untested failover often fails when needed.

Common mistakes

- Making app servers redundant but leaving one database or one load balancer.
- Putting all "redundant" copies in the same rack or zone.
- Forgetting that the standby needs enough capacity to take the full load.

Real-world examples

- AWS recommends spreading instances across at least two availability zones; managed databases such as Amazon RDS Multi-AZ keep a synchronous standby in another zone and fail over automatically, typically within a minute or two.
- Load balancers themselves are deployed in pairs (or as a managed, internally redundant service) to avoid being the SPOF.

In the interview

Q: How do you find single points of failure in a design?

A: Go component by component (including DNS, load balancers, databases, config stores, third-party APIs) and ask what happens if it disappears. Anything that stops the whole service needs a redundant copy in a separate failure domain and automatic failover.

Q: Active-passive or active-active?

A: Active-passive is simpler and common for databases with one writer. Active-active uses capacity better and recovers faster, and is natural for stateless services, but needs conflict handling for stateful data.

TL;DR

Redundancy means spares; a SPOF is any part with no spare; failover moves work to the spare. Remove SPOFs by duplicating critical parts across failure domains and automating failover, while guarding against split brain.

Scalability

What it is

Scalability is a system's ability to handle more load (more users, more requests, more data) by adding resources, without a redesign and without performance collapsing. A scalable system's cost and effort grow roughly in proportion to its load; an unscalable one hits a wall.

Load needs to be described with specific numbers, called **load parameters**: requests per second, number of concurrent users, read/write ratio, size of the data, number of followers per user, and so on. "Scalable" only makes sense relative to one of them: "we can scale to 10× the requests per second by adding servers".

> **Analogy:** a restaurant that can serve more diners by adding tables and hiring more cooks is scalable. One whose single tiny kitchen can never cook faster than 50 meals an hour, no matter how many tables you add, is not.

Why it matters

Successful products grow, sometimes overnight. A system that needs a rewrite at each 10× step slows the business down at exactly the wrong moment.

How it works

There are a few dimensions you can scale along:

- **Load scalability:** more requests per second.
- **Data scalability:** more stored data.
- **Geographic scalability:** users spread around the world, needing low latency everywhere.
- **Organisational scalability:** more engineers working on the system without stepping on each other (one reason teams split into microservices, Part 5).

The core techniques, all explained in later parts:

1. Scale out stateless app servers behind a load balancer (next section).
2. Cache hot data (Part 4).
3. Copy data to read replicas for read-heavy loads (Part 3).
4. Split data across shards for write-heavy or huge data (Part 3).
5. Move slow work to queues and workers (Part 4).
6. Put static content on a CDN (Part 2).

Common mistakes

- Calling a system "scalable" without saying which load parameter and by how much.
- Scaling the wrong part. Adding app servers does nothing if the database is the bottleneck.
- Building for 1,000× growth on day one. Design so the next 10× is easy, and re-evaluate.

In the interview

Q: What does it mean for a system to be scalable?

A: That it can handle growing load, described with concrete numbers, by adding resources roughly in proportion, while keeping performance within targets.

TL;DR

Scalability is handling more load by adding resources without a redesign. Always say what load (QPS, data size, users) and by how much.

Vertical and horizontal scaling

What it is

- **Vertical scaling (scale up):** make one machine bigger: more CPU cores, more RAM, faster disks.
- **Horizontal scaling (scale out):** add more machines and spread the work across them.


> **Analogy:** to carry more passengers you can buy a bigger bus (vertical) or run more buses (horizontal).


How it works

Vertical scaling is usually just a configuration change on a cloud provider: stop the machine, pick a larger size, start it. No code changes. Modern cloud machines go very large: AWS offers instances with hundreds of CPU cores and multiple terabytes of RAM.

Horizontal scaling requires the work to be divisible:

- Stateless app servers: easy. Put a load balancer in front and add copies.
- Databases: harder. Reads can go to replicas; spreading writes needs sharding (each machine holds part of the data).





Trade-offs

	Vertical (up)	Horizontal (out)
Simplicity	Very simple, no code change	Needs load balancing, stateless design or sharding
Limit	Hard ceiling: the biggest machine	Practically unlimited
Fault tolerance	One machine is still a SPOF	Losing one node loses only a fraction
Cost curve	Big machines cost disproportionately more	Many cheap commodity machines
Downtime to resize	Often needs a restart	Add or remove nodes live
Consistency	Easy (one copy of data)	Harder (data spread across machines)

Common mistakes

- Dismissing vertical scaling. A single large database server handles a lot; scaling up first is often the right, cheap answer.
- Scaling out a stateful service without dealing with its state (see next sections).

Real-world examples

- Stack Overflow famously served a very large site from a small number of powerful servers (in 2016: 11 web servers and 4 SQL Server machines, plus a few Redis, search and tag-engine boxes), a well-known example of vertical scaling done well.
- Google, Meta and Amazon are each estimated to run millions of commodity servers: horizontal scaling at the extreme.

In the interview

Q: When would you choose vertical scaling?

A: Early on, or for components that are hard to distribute (like a relational database's primary). It's simple and buys time. Switch to horizontal when you approach the largest machine size, need fault tolerance, or costs climb steeply.

Q: What makes horizontal scaling hard?

A: State. Stateless servers scale out trivially; anything that stores data must be replicated or partitioned, which brings consistency and coordination problems.

TL;DR

Scale up = bigger machine (simple, limited, still a SPOF). Scale out = more machines (unlimited and fault tolerant, but needs stateless design or data partitioning). Most real systems do both.

Elasticity

What it is

Elasticity is the ability to add and remove resources *automatically and quickly* as load changes, so you pay for roughly what you use. Scalability says "we *can* grow"; elasticity says "we grow and shrink by ourselves, in minutes".

> **Analogy:** a supermarket that opens more checkouts when queues get long and closes them when the shop is quiet.

How it works

1. Watch a metric: CPU use, requests per second, queue length.
2. When it crosses a threshold (say CPU above 70% for 5 minutes), launch more servers.
3. When it drops (CPU below 30%), remove some.
4. The load balancer automatically starts and stops sending them traffic.

This is called **autoscaling** (Part 5 covers kinds: reactive, scheduled, predictive). Cloud platforms (AWS Auto Scaling groups, Kubernetes Horizontal Pod Autoscaler) and **serverless** platforms (AWS Lambda, which runs your code per request and scales to zero) provide it.

Trade-offs

- New servers take time to start (seconds for containers, minutes for virtual machines). A sudden spike can arrive faster than capacity.
- Only stateless parts are easily elastic; databases scale much more slowly.
- Scaling down too eagerly causes "flapping" (adding and removing repeatedly).

In the interview

Q: What's the difference between scalability and elasticity?

A: Scalability is the capability to handle more load by adding resources. Elasticity is doing that automatically, in both directions, to match demand as it changes.

TL;DR

Elasticity is automatic, fast scaling up and down with demand, mostly for stateless parts, so you pay only for what you need.

Stateless and stateful services

What it is

State is data a program remembers between requests: who is logged in, what's in a shopping cart, the contents of a database.

- A **stateless service** keeps no client-specific data in its own memory between requests. Every request carries (or points to) everything needed to handle it, and any copy of the service can handle any request.
- A **stateful service** remembers data between requests locally, so a particular client or a particular piece of data is tied to a particular server.

> **Analogy:** a stateless service is a call centre where every agent can pull up your file from the shared system, so any agent can help you. A stateful service is your family doctor who keeps your history in their head: great until they're on holiday.

Why it matters


Stateless services are easy to scale out, load balance, restart and replace: kill any copy and nothing is lost. That's why the standard advice is "**make app servers stateless and push state into dedicated stores**" (databases, caches, object storage) that are designed for replication.


How it works

How to make a web app stateless:

1. Store login sessions in a shared store (Redis) or in a signed token the client sends with each request (like a JWT, JSON Web Token, covered in Part 5), not in server memory.
2. Store uploaded files in object storage, not on the server's local disk.
3. Keep shopping carts and similar data in a database or cache.

Then the load balancer can send each request to any server.





If a service stays stateful (for example a game server holding a live match, or a chat server holding open connections), the load balancer must send each client to the same server, called **sticky sessions** (Part 2), and you must plan for what happens when that server dies.

Trade-offs

- Stateless servers need an extra network hop to fetch state, adding latency (usually under a millisecond to a cache).
- Stateful designs can be faster (data already in memory) and are sometimes necessary (databases, real-time games, WebSocket servers), but are harder to scale and recover.

Common mistakes

- Keeping sessions in local memory, then adding a second server and finding users randomly logged out.
- Writing uploaded files to the local disk of one server.
- Calling a system stateless when it just moved state somewhere else; the state store now needs scaling and redundancy too.

In the interview

Q: Why should application servers be stateless?

A: So any instance can handle any request: you can add or remove instances freely, load balance evenly, and lose an instance without losing user data. State lives in stores built for durability and replication.

TL;DR

Stateless services remember nothing between requests and scale easily; stateful ones hold data and are harder to scale and recover. Keep app servers stateless and put state in databases and caches.

Performance vs scalability

What it is

- **Performance** is how fast the system is for *one* request or user at the current load: low latency, efficient use of resources.
- **Scalability** is how well performance holds up as load *grows*.

A quick diagnostic:

- Send one request to an otherwise idle system. If even that is slow, the trouble is **performance**.
- If that lone request is quick but things drag once traffic piles up, the trouble is **scalability**.

> **Analogy:** a sports car is high-performance (fast for one person) but doesn't scale (two seats). A train is slower to get going but carries a thousand people.

Trade-offs

Some changes help one and hurt the other. Adding a network hop to reach a shared cache slightly hurts single-request performance but lets you scale out. Keeping everything in one process's memory is fast but caps you at one machine.

In the interview

Q: The site is slow even at 3 am with almost no traffic. Performance or scalability?

A: Performance: something is slow per request (an unindexed query, a slow external call, a big page). Adding servers won't help; profile the request.

TL;DR

Performance = fast for one; scalability = stays fast for many. Diagnose which one you have before fixing.

Concurrency vs parallelism

What it is

- **Concurrency** means several tasks are in progress during the same period, with the program switching between them whenever one has to wait. It describes how the work is organised.
- **Parallelism** means several tasks are literally running at the same instant, on multiple CPU cores or machines. It describes how the work is executed.

Go co-creator Rob Pike summed this up as concurrency being about *dealing with* lots of things at once and parallelism about *doing* lots of things at once.

> **Analogy:** one barista taking an order, starting the milk, taking another order while the milk steams, then finishing the first drink, is concurrent. Three baristas each making a drink at the same moment is parallel. You can have concurrency on a single CPU core (by switching) but parallelism needs multiple cores.


Why it matters

Most web servers spend their time **waiting** (on the network, the database, the disk), not computing. Concurrency lets one server keep thousands of requests in progress while each waits. Parallelism speeds up **CPU-heavy** work (image processing, encryption, analytics) by splitting it across cores.

How it works

Ways to achieve concurrency:

- **Processes:** separate running programs, each with its own memory. Heavy but isolated.
- **Threads:** multiple flows of execution inside one process, sharing memory. Lighter, but shared memory needs locks to avoid errors.
- **Event loop / async I/O:** one thread handles many requests by never blocking: it starts an I/O operation, handles something else, and comes back when the result is ready. Node.js, NGINX and Python's asyncio work this way.
- **Lightweight threads / coroutines:** cheap tasks scheduled by the language runtime (Go's goroutines, Java's virtual threads), letting you write simple blocking-style code that runs with event-loop efficiency.



Concurrency hazards: when tasks share data you can get a **race condition** (the result depends on timing, like two requests both reading a balance of 100 and both writing 90 after a withdrawal of 10, losing one withdrawal), **deadlock** (two tasks each wait for a lock the other holds, forever) and contention (tasks queue for the same lock). Locks, atomic operations and database transactions (Part 3) address them.

Amdahl's law (a related rule) says the speed-up from parallelism is limited by the part of the work that must run one step at a time. If 10% of a job is serial, even infinite cores give at most a 10× speed-up.

Common mistakes

- Adding threads to a CPU-bound task beyond the number of cores. It just adds switching overhead.
- Assuming parallel code is automatically faster; coordination and locking can make it slower.

In the interview

Q: Is a single-threaded Node.js server concurrent?

A: Yes, it handles many requests concurrently using an event loop and non-blocking I/O. It isn't parallel for JavaScript code on one core; you run several processes to use multiple cores.

TL;DR

Concurrency is juggling many tasks (great for waiting on I/O); parallelism is doing several at the same instant on multiple cores (great for CPU-heavy work). Shared data under concurrency needs care to avoid races and deadlocks.

Bottlenecks: CPU, memory, disk and network

What it is

A **bottleneck** is the part of a system that limits its overall capacity, like the narrow neck of a bottle that limits how fast you can pour. Improving anything else won't help until the bottleneck is fixed. Every machine has four basic resources that can become one.

Resource	What it limits	Signs it's the bottleneck	Usual fixes
CPU	Computation (encryption, parsing, compression)	CPU near 100%, latency rises with load	Optimise code, cache results, add cores or servers
Memory (RAM)	How much data fits in fast storage	Swapping to disk, out-of-memory crashes, cache misses	More RAM, smaller data, evict wisely
Disk	Reading and writing stored data	High disk wait time, IOPS or MB/s at limit	SSDs, caching, sequential writes, sharding
Network	Moving data between machines	Link saturated, packet loss, high RTT	Compression, CDNs, fewer calls, closer servers

How it works

Finding the bottleneck:

1. Measure each resource under load (monitoring dashboards, `top`, `iostat`, cloud metrics).
2. Look for the one at or near its limit, or for queues building up in front of something (thread pools full, database connections exhausted, lock waits).
3. Fix it, then measure again. The bottleneck moves: fix the database and the network may be next.

Non-hardware bottlenecks are just as common: a single lock everybody waits for, a database connection pool that's too small, one "hot" row that every request updates, or an external API with a rate limit.

Bound terms: a task is **CPU-bound** when it's limited by computation, and **I/O-bound** when limited by waiting for disk or network. Most web services are I/O-bound.

IOPS and disk performance

IOPS (Input/Output Operations Per Second) is how many separate read or write operations a storage device can perform per second. It matters most for **random** access (many small reads at different locations), such as database lookups.

Disks have two separate limits:

- **IOPS:** number of operations per second (matters for small random reads/writes).

- **Throughput:** megabytes per second (matters for large sequential reads/writes, like streaming a video file or a backup).

Device	Rough random IOPS	Rough sequential throughput
Spinning HDD (7,200 rpm)	about 75-150	100-250 MB/s
SATA SSD	tens of thousands	about 500 MB/s
NVMe SSD	hundreds of thousands to about 1 million	several GB/s
Cloud block disk (e.g. AWS gp3 baseline)	3,000 (can buy more)	125 MB/s (can buy more)

An HDD's IOPS is low because each random read must physically move the arm and wait for the platter to spin (roughly 5–10 ms). That's why databases moved to SSDs, and why systems that must use HDDs favour sequential writes.

Example: a database needs 20,000 random reads per second that miss the cache. One HDD (~150 IOPS) would need over 100 disks; one NVMe SSD handles it comfortably.

Common mistakes

- Guessing the bottleneck instead of measuring.
- Looking only at averages. A resource at 50% average can be at 100% for the busy minute that matters.
- Forgetting cloud disks have provisioned IOPS limits: a database can be throttled by its disk while CPU looks idle.

In the interview

Q: Latency rises under load but CPU is only at 30%. Where would you look?

A: Something else is the bottleneck: disk IOPS, network, a full database connection pool, a lock, or a slow dependency. Look for where requests are queueing.

Q: What's the difference between IOPS and disk throughput?

A: IOPS counts operations per second (key for many small random reads, like database lookups); throughput counts bytes per second (key for large sequential transfers). A disk can hit one limit without hitting the other.

TL;DR

The bottleneck is whichever resource (CPU, memory, disk, network, or a lock or pool) runs out first. Measure to find it; disks are limited separately by IOPS and by MB/s.


How to approach a system design interview

What it is

A system design interview is usually a 45–60 minute conversation where you're asked to design something like "a URL shortener", "a chat app" or "a news feed". It is open-ended on purpose. A clear, repeatable structure helps you cover everything and shows the interviewer how you think.

How it works

A widely used sequence, with rough timings for a 45-minute interview:



1. Clarify requirements. Never start drawing straight away. Ask questions and write down two lists:

- **Functional requirements:** *what* the system does, the features. Example for a URL shortener: "create a short link from a long URL", "redirect a short link to the original", "optional custom aliases", "links expire after a year".
- **Non-functional requirements:** *how well* it does it, the qualities. Scale (100M new links per month), latency (redirect in under 50 ms at p99), availability (99.99% for redirects), durability (never lose a link), consistency (is a newly created link visible everywhere immediately?), security, cost.
- Also agree on what's **out of scope** (analytics dashboards, user accounts), so you don't waste time.

2. Estimate scale. Use the back-of-the-envelope method: QPS (average and peak), read/write ratio, storage over time, bandwidth. Keep it quick and say how the numbers affect the design ("100:1 reads, so caching matters").

3. Define the API. List the main endpoints the client calls, with inputs and outputs. For example:

```
POST /links        body: {long_url, custom_alias?}  -> {short_code}
GET  /{short_code}                                  -> 301 redirect to long_url
```

This pins down exactly what the system must do.

4. Sketch the data model. What entities are stored, their key fields, and how they're accessed. For example a `links` table: `short_code` (primary key), `long_url`, `created_at`, `expires_at`. Mention which kind of database fits the access pattern (Part 3).

5. Draw the high-level design. The boxes and arrows: clients, load balancer, app servers, cache, database, queue, etc. Walk through one write and one read end to end. Keep it simple at first; it should meet the functional requirements.

6. Deep dives. Pick the hardest or most interesting parts, often guided by the interviewer, and go deeper: how to generate unique short codes without collisions, how to shard the database, how to cache

hot links, what happens when a data centre fails, how to handle a celebrity's viral link. Use your estimates to justify choices.

7. Discuss trade-offs and wrap up. Name the weaknesses of your design and what you'd do next: bottlenecks, single points of failure, monitoring, what changes at 10× scale.

Trade-offs

Breadth vs depth: covering every box shallowly looks junior; going deep on one box and never finishing the design is worse. Aim for a complete simple design first, then depth.

Common mistakes

- Jumping into a detailed design before clarifying requirements.
- Staying silent while thinking. Think out loud.
- Naming technologies without reasons ("use Cassandra"). Always say why ("write-heavy, simple key lookups, needs multi-region").
- Ignoring the non-functional requirements, which usually decide the design.
- Over-engineering: microservices, Kafka and five databases for a system with 100 QPS.
- Not checking the design against the original requirements and numbers at the end.

In the interview

Q: What is the difference between functional and non-functional requirements?

A: Functional requirements are features: what the system does (post a photo, follow a user). Non-functional requirements are qualities: how well it does them (latency, availability, scale, consistency, durability, cost). Non-functional requirements usually drive architecture choices.

Q: The interviewer says "design Twitter". What do you do first?

A: Ask clarifying questions to narrow scope: which features (post, follow, home timeline, search?), how many users, read/write mix, latency and consistency expectations. Write the agreed requirements down before estimating or drawing.

Q: How do you choose what to deep-dive into?

A: The parts that are hardest given the requirements and estimates (usually the biggest scale or consistency challenge), or whatever the interviewer steers toward. Ask if unsure.

TL;DR

Requirements (functional and non-functional), estimates, API, data model, high-level design, deep dives, trade-offs. Think out loud, justify every component with a requirement or a number, and finish with weaknesses and next steps.

Part 1 glossary

Term	Meaning in one line
Active-active	All redundant copies serve traffic at once and absorb a failed copy's share
Active-passive	One copy serves traffic while a standby waits to take over
Amdahl's law	Parallel speed-up is limited by the part of the work that must run serially
App server (application server)	Program that runs business logic and answers client requests
Availability	Fraction of time (or requests) the system is up and working
Availability zone	A separate data centre within a cloud region with its own power and network
Back-of-the-envelope estimate	Quick rough calculation to find the order of magnitude of load or storage
Bandwidth	Maximum data a link or device can carry per second
Batching	Grouping many small operations into one to raise throughput at some latency cost
Bit / byte	A bit is a single 0 or 1; a byte is 8 bits
Bottleneck	The resource or component that limits overall capacity
Cache	Fast, usually in-memory store holding copies of frequently used data
CDN	Content Delivery Network; servers worldwide that serve static files close to users
Client	Program that sends requests (browser, app, or another server)
Cold / warm / hot standby	Spares that need starting, are partly ready, or are ready instantly
Concurrency	Making progress on many tasks by interleaving them
Coordinated omission	Load-test flaw that under-reports slow responses
Correlated failure	Several "independent" parts failing together from a shared cause
CPU-bound	Limited by computation speed
CPU cache	Tiny, very fast memory inside the processor
DAU / MAU	Daily / Monthly Active Users
Deadlock	Tasks waiting forever for locks held by each other
Durability	Saved data is not lost, even after crashes or disk failures
Elasticity	Automatically adding and removing resources to match demand
Error budget	Amount of failure an SLO allows (1 minus the SLO)
Event loop	Single thread handling many requests by never blocking on I/O
Failover	Switching work from a failed component to a standby
Failure	The whole system stops providing its service
Failure domain	A group of parts that can fail together (rack, zone, region)
Fan-out	One request triggering many parallel downstream requests
Fault	One component misbehaving (crash, slowness, wrong output)
Fault tolerance	Continuing to work despite faults in some components
Functional requirement	A feature the system must provide

Term	Meaning in one line
HDD	Hard disk drive; spinning magnetic disk with slow seeks
Health check	Periodic test of whether a component is alive and working
Hedged request	Sending a duplicate request to another replica if the first is slow
Histogram	Counts of measurements per value bucket, used to compute percentiles
Horizontal scaling (scale out)	Adding more machines to share the load
HTTP	Standard protocol for web requests and responses
I/O-bound	Limited by waiting for disk or network
IOPS	Input/output operations per second a storage device can perform
KB / MB / GB / TB / PB	Data sizes, each about 1,000 times the previous
Latency	Time delay for one request or one hop
Little's law	Items in system = arrival rate x time in system (L = lambda x W)
Load balancer	Component that spreads requests across servers and skips dead ones
Load parameters	The numbers that describe load (QPS, data size, users)
Mean (average)	Sum divided by count; hides outliers in skewed data
Median (p50)	Middle value: half are faster, half slower
Message queue	Buffer where jobs wait to be processed later by workers
MTBF	Mean time between failures
MTTD	Mean time to detect a failure
MTTF	Mean time to failure for parts that are replaced, not repaired
MTTR	Mean time to repair or recover
N+1 redundancy	Running one more unit than peak load needs
Nines	Shorthand for availability levels (three nines = 99.9%)
Non-functional requirement	A quality the system must have (latency, availability, scale)
NVMe	Fast interface for SSDs with very high IOPS
Object storage	Service storing large files as objects under keys (e.g. Amazon S3)
Order of magnitude	Rough size as a power of ten
Parallelism	Executing several tasks at the same instant on multiple cores or machines
Peak factor	Ratio of peak traffic to average traffic
Percentile	Value below which a given percentage of measurements fall
Performance	How fast the system is for a single request at current load
Propagation delay	Time for a signal to travel the physical distance
QPS / RPS	Queries / requests per second
Queueing delay	Time spent waiting behind other work
RAM	Main working memory of a computer; fast but volatile
Race condition	Bug where the result depends on the timing of concurrent tasks
Read/write ratio	How many reads happen per write

Term	Meaning in one line
Redundancy	Having spare copies so one can replace another
Reliability	Working correctly over time despite faults
Request / response	A client's message asking for something and the server's reply
Response time	Total time the client waits, including network, queueing and service
Round trip time (RTT)	Time for a message to go to a destination and back
Scalability	Handling more load by adding resources without redesign
Server	Program (or machine) that waits for and answers requests
Service time	Time the server spends actually working on a request
SLA	Service Level Agreement; contract with penalties for missed targets
SLI	Service Level Indicator; a measurement of service health
SLO	Service Level Objective; internal target for an SLI
Single point of failure (SPOF)	A part whose failure alone brings the whole system down
Split brain	Two nodes both believing they are the primary
SRE	Site Reliability Engineering; running production with engineering methods
SSD	Solid-state drive; flash storage with no moving parts
State	Data a program remembers between requests
Stateful service	Service that keeps client or data state locally
Stateless service	Service that keeps no per-client state between requests
Sticky sessions	Load balancer sending a client to the same server every time
System design	Choosing a system's parts and how they interact to meet its goals
Tail latency	Latency of the slowest requests (p99, p999, max)
Thread	Independent flow of execution inside a process
Throughput	Amount of work completed per unit of time
Transmission delay	Time to push the bits of a message onto a link
Vertical scaling (scale up)	Making one machine bigger
Worker	Background program that processes jobs from a queue

Part 2 — Networking and communication

Every system design diagram is boxes joined by arrows. Part 1 was about the boxes. This part is about the arrows: how one computer finds another, how bytes travel between them, which languages (protocols) they speak, and which helpers sit in the middle, such as proxies, load balancers and CDNs. You do not need to be a network engineer for a system design interview. You do need to know what happens when a browser types `www.example.com`, why HTTP/2 is faster than HTTP/1.1, and what an L7 load balancer can do that an L4 one cannot. This part teaches exactly that, from zero.

A **protocol** is an agreed set of rules for how two programs talk, the way "say hello, wait for a reply, then speak" is a protocol for a phone call. Networking is a stack of protocols, each one solving one problem and handing the rest to the layer above or below.

IP addresses, NAT, ports and sockets

What it is

An **IP address** (Internet Protocol address) is the number that identifies a machine's network connection, like a street address on an envelope. Routers — the boxes that forward traffic across the internet — read only this address to decide where to send each **packet** (a small chunk of data, usually up to about 1,500 bytes on Ethernet).

- **IPv4** addresses are 32 bits, written as four numbers from 0 to 255: `93.184.215.14`. That gives about 4.3 billion addresses (2^32), which the world ran out of in the 2010s.
- **IPv6** addresses are 128 bits, written as eight groups of hex digits: `2606:2800:21f:cb07:6820:80da:af6b:8b2c` (runs of zeros can be shortened with `::`). That is about 3.4 × 10^38 addresses — effectively unlimited.

A **port** is a number from 0 to 65535 that picks which program on a machine gets the data. If the IP address is the building, the port is the apartment number. Well-known ports: 22 (SSH, remote login), 53 (DNS), 80 (HTTP), 443 (HTTPS), 5432 (PostgreSQL), 6379 (Redis).

A **socket** is one end of a conversation, identified by IP address plus port. A single TCP connection is uniquely identified by a **5-tuple**: protocol, source IP, source port, destination IP, destination port. That is why one server on port 443 can hold hundreds of thousands of connections at once — each client brings a different source IP or source port.


Public vs private IP. A **public IP** is reachable from anywhere on the internet and is unique worldwide. A **private IP** is only meaningful inside one local network and is reused by millions of networks. The reserved private IPv4 ranges are `10.0.0.0/8`, `172.16.0.0/12` and `192.168.0.0/16`. (The `/8` is **CIDR notation**: the number of leading bits that are fixed. `10.0.0.0/8` means "every address starting with 10", about 16.7 million addresses.) Your laptop at home is almost certainly something like `192.168.1.23`.

NAT (Network Address Translation) lets many private machines share one public IP. Your home router rewrites each outgoing packet's source from `192.168.1.23:51000` to its own public IP and a free port, say `81.2.69.160:40001`, remembers the mapping in a table, and reverses the rewrite on replies. In the cloud, the same job is done by a **NAT gateway** so that servers in a private subnet can download updates without being reachable from outside.

Why it matters

- Servers you design live mostly on private IPs inside a **VPC** (Virtual Private Cloud — your own isolated network inside a cloud provider). Only the load balancer or gateway gets a public address. This is the first layer of security.
- NAT explains why a server cannot simply "call" a phone or a browser: the client is behind NAT and has no stable public address. That is why push systems keep a long-lived connection open *from* the client (see WebSockets below).
- The 5-tuple explains connection limits. A proxy that opens connections from one IP to one backend IP and port can use at most about 64,000 source ports (only about 28,000 with Linux's default range), which is a real limit on busy proxies (called **ephemeral port exhaustion**).

How it works



1. Your browser asks the operating system for a socket to `93.184.215.14:443`. The OS picks a random **ephemeral port** (a temporary source port, typically from 32768–60999 on Linux) such as 51000.
2. The router's NAT swaps the private source address for its public one and records the mapping.
3. Internet routers forward the packet hop by hop based only on the destination IP. A typical path crosses 10–20 routers.
4. The server replies to `81.2.69.160:40001`. The router looks up its table and forwards the reply to `192.168.1.23:51000`.

Common mistakes

- Thinking an IP identifies a person or even a device. Behind **carrier-grade NAT** (NAT run by a mobile operator) thousands of users share one public IP, so rate limiting by IP alone can block an entire office or mobile network.
- Forgetting that IPs change. Cloud instances get new private IPs when they restart, which is why systems use DNS names and service discovery instead of hard-coded addresses.

TL;DR

An IP address finds the machine, a port finds the program, and the 5-tuple identifies one connection. Private IPs are hidden behind NAT, and only a few edge components in your design should have public IPs.

DNS — the internet's phone book

What it is

DNS (Domain Name System) turns human-friendly names like `www.example.com` into IP addresses. It is like your phone's contacts list: you tap "Mum", and the phone dials the number. Without DNS you would type `93.184.215.14` into the browser, and a company could never move its servers without telling every user the new number.

A **domain name** is read right to left as a hierarchy: `.` (the root, usually invisible) → `com` (the **top-level domain**, TLD) → `example` (the registered domain) → `www` (a **subdomain**). Each level is managed by a different organisation, which is what lets DNS scale to hundreds of millions of domains.


Why it matters

- DNS is the very first step of almost every request, so its speed adds directly to page load time (a cold lookup can cost 20–120 ms).
- DNS is a cheap, global traffic-steering tool: by answering with different IPs, you can spread users across data centres or send them to the closest one.
- When DNS breaks, everything looks down even though servers are healthy. Large outages (for example the 2016 Dyn attack, and Facebook's 2021 outage, where its DNS servers became unreachable after a routing change) show it is a critical dependency.

How it works

The players:

- **Stub resolver** — the tiny DNS client inside your OS. It does not do the hard work; it just asks someone else.
- **Recursive resolver** — the server that does the legwork on your behalf and caches answers. It is usually run by your ISP (internet service provider), your company, or a public service like Google `8.8.8.8` or Cloudflare `1.1.1.1`.
- **Root name servers** — the top of the tree. There are 13 named root server identities (`a.root-servers.net` to `m.root-servers.net`), but each is copied to many locations worldwide using anycast (explained in the CDN section), so there are close to 2,000 physical root server instances.
- **TLD name servers** — know who is in charge of each domain under `.com`, `.org`, `.uk` and so on.
- **Authoritative name server** — holds the real records for a domain (for example Route 53, Cloudflare DNS, or your own servers). Its answer is the final truth.



Step by step:

1. The browser checks its own cache, then the OS cache (and the `hosts` file).
2. On a miss, the stub resolver sends a **recursive query** to the recursive resolver: "give me the final answer".
3. If the resolver has nothing cached, it asks a root server, which replies with a **referral**: "I don't know, but here are the `.com` servers". These follow-up questions are **iterative queries** — each server just points to the next.
4. The `.com` TLD server refers it to the domain's authoritative servers (the domain's **NS records**).
5. The authoritative server returns the answer.
6. The resolver caches every step (root and TLD referrals are cached for days), so the next lookup for any `.com` name skips steps 3–4.

In practice, a busy resolver almost always has the root and TLD answers cached, so most lookups are one hop to the authoritative server or a pure cache hit (under 1 ms on the same machine, ~10–30 ms to a public resolver).

Types

DNS record types you should know:

Record	Maps	Example
A	name → IPv4 address	`www → 93.184.215.14`
AAAA	name → IPv6 address	`www → 2606:2800::1`
CNAME	name → another name (alias)	`shop → shops.myplatform.com`
MX	domain → mail servers, with priority	`10 mail1.example.com`
NS	domain → its authoritative name servers	`ns1.example-dns.net`
TXT	name → free text	domain-ownership proofs, SPF rules listing which servers may send a domain's email

Others you may meet: **SOA** (start of authority — admin data for a zone), **SRV** (service location with port), **PTR** (reverse lookup, IP → name), **CAA** (which certificate authorities may issue certificates for the domain). A **zone** is the set of records one authoritative server is responsible for.

A CNAME cannot sit at the bare domain (`example.com`, called the **apex**) because the apex must also hold NS and SOA records. Providers work around this with non-standard "ALIAS" or "ANAME" records, or Cloudflare's "CNAME flattening".

Here is a real-looking lookup with the `dig` tool:

```
$ dig www.example.com A +noall +answer
www.example.com.   300   IN   A   93.184.215.14
```

`300` is the **TTL**, `IN` means internet class, and `A` is the record type.

TTL and DNS caching. Every record carries a **TTL (time to live)** in seconds: how long any resolver or browser may cache it. A TTL of 300 means "reuse this for 5 minutes". Long TTLs (hours or a day) mean fewer lookups and faster pages, but changes take that long to reach everyone (what people call "propagation" is nothing being pushed out; resolvers simply keep the old answer until their copy times out). Short TTLs (30–60 s) let you fail over quickly but cause more queries. A common trick: lower the TTL a day before a planned migration, switch the record, then raise it again. Some clients and resolvers ignore TTLs and cache longer, so never rely on DNS alone for instant failover.

DNS-based load balancing. The authoritative server can return several A records (for example three IPs) and rotate their order on each query — **round-robin DNS**. Clients usually try the first one, so load spreads roughly evenly. It is free and simple but blind: DNS does not know whether a server is busy or dead unless the DNS provider runs health checks and removes bad IPs.

GeoDNS answers differently depending on where the query comes from: a user in Paris gets the IP of the Frankfurt data centre, a user in Tokyo gets the Tokyo one. The DNS server guesses location from the resolver's IP, or from the **EDNS Client Subnet** extension, which passes part of the user's own IP so the guess is better. **Latency-based routing** (offered by AWS Route 53) picks the region with the lowest measured latency rather than the closest on a map.

Trade-offs

Choice	Benefit	Cost
Long TTL	Fewer lookups, resilient if DNS provider has a blip	Slow to change or fail over
Short TTL	Fast failover and traffic shifts	More DNS traffic and lookup latency
DNS load balancing	Global, cheap, no extra hop	Coarse, cached, no knowledge of server load

Common mistakes

- Expecting a DNS change to take effect instantly. Cached answers live until their TTL expires, sometimes longer.
- Using one DNS provider with no redundancy. Many large sites now use two providers.
- Treating DNS round robin as a real load balancer. It cannot react to a server being slow.

Real-world examples

Amazon Route 53, Cloudflare DNS, Google Cloud DNS and NS1 are authoritative DNS services with health checks, GeoDNS and latency routing. Netflix and many others use DNS to steer users between AWS regions during regional failures.

In the interview

Q: What happens when you type a URL in the browser, up to the IP address?

A: Browser cache, OS cache, then a recursive resolver. If the resolver has nothing cached, it walks root → TLD → authoritative server, caches each answer for its TTL, and returns the IP. Then the browser opens a TCP (or QUIC) connection to that IP.

Q: How would you move traffic away from a failed region using DNS?

A: Use health-checked records with a short TTL (say 60 s) so the provider stops returning the failed region's IP. Accept that some clients will still hit the old IP for a while, so the failed region's load balancer should also redirect or fail fast.

TL;DR

DNS maps names to IPs through a cached hierarchy of root, TLD and authoritative servers. TTL controls the trade-off between speed and how quickly changes spread, and DNS can do coarse global load balancing (round robin, GeoDNS, latency-based).

Network layers — OSI and TCP/IP models

What it is

Networking is split into **layers**, each solving one job and relying on the layer below. Think of posting a parcel: you write a letter (application), put it in an envelope with an apartment number (transport), the post office adds a city and street address (network), and a van physically drives it (link and physical). Each layer only cares about its own label.

There are two models. The **OSI model** has seven layers and is mainly a teaching vocabulary. The **TCP/IP model** has four and describes what the internet actually runs. Engineers mix them: when someone says "L4" or "L7", they mean OSI layer numbers.

OSI layer	Name	What it handles	Examples
7	Application	Meaning of messages	HTTP, DNS, gRPC, SMTP
6	Presentation	Encoding, encryption	TLS (roughly), JSON (a text data format)
5	Session	Conversations	(rarely discussed)
4	Transport	Process-to-process delivery, ports	TCP, UDP, QUIC
3	Network	Machine-to-machine routing	IP, ICMP
2	Data link	One hop on a local network	Ethernet, Wi-Fi, MAC addresses
1	Physical	Bits on wire, light or radio	Copper, fibre, radio

The TCP/IP model merges 5–7 into "application" and 1–2 into "link": Application, Transport, Internet, Link.

Why it matters

The layer a component works at decides what it can see and therefore what it can do:

- An **L3** device (router, firewall rule on IPs) sees only source and destination IPs.
- An **L4** device (L4 load balancer) also sees ports and TCP/UDP state, but not the content. It can say "send port 443 traffic to these servers" but not "send `/api/` to these".
- An **L7** device (L7 load balancer, API gateway) reads the HTTP request itself: URL path, headers, cookies. It can route by path, rewrite headers, and block bad requests — at the cost of more CPU and needing to decrypt TLS (the encryption behind HTTPS, explained below).

How it works

When your app sends an HTTP request, each layer wraps the data with its own header — **encapsulation**. HTTP request → TCP segment (adds ports, sequence numbers) → IP packet (adds IPs) → Ethernet frame (adds MAC addresses, the hardware address of a network card). The receiver unwraps in reverse order.

TL;DR

Layers separate concerns: L3 is IP addresses, L4 is ports and connections (TCP/UDP), L7 is application content (HTTP). "L4 vs L7" in system design always means "can it read the request or only the connection?"

TCP, UDP and QUIC

What it is

These are the **transport-layer** protocols: they carry data between two programs.


- **TCP (Transmission Control Protocol)** is like a phone call with a careful note-taker: you connect first, everything arrives, in order, and lost words are repeated.
- **UDP (User Datagram Protocol)** is like shouting postcards across a room: no setup, each message is independent, some may be lost or arrive out of order, nobody repeats anything.
- **QUIC** is a newer protocol built on top of UDP that gives TCP-like reliability plus built-in encryption, without some of TCP's weaknesses. HTTP/3 runs on it.

Why it matters

The choice shapes latency and behaviour under packet loss. Web pages, APIs and databases want every byte correct, so they use TCP (or QUIC). Live voice, video calls, online games and DNS lookups prefer UDP because a late packet is useless — better to skip it than to wait.

How it works

TCP three-way handshake. Before any data, the two sides agree on starting sequence numbers:



This costs one **round trip (RTT)** before the first byte of the request. London to New York is about 70 ms RTT, so the handshake alone is 70 ms — and TLS adds more on top (see HTTPS). This is why reusing connections matters so much.

Reliability and ordering. TCP numbers every byte (**sequence numbers**). The receiver sends **acknowledgements (ACKs)**. If an ACK does not arrive in time, the sender **retransmits**. The receiver reorders out-of-order segments and hands the application a clean, ordered byte stream.

Flow control. The receiver advertises a **receive window** — how much buffer space it has — so a fast sender cannot overwhelm a slow receiver.

Congestion control. The network in between can also be overwhelmed. TCP starts slowly (**slow start**: send a few packets, roughly double each round trip while ACKs come back), and when it sees loss it backs off. Algorithms include Reno, CUBIC (default on Linux) and Google's BBR, which models bandwidth and RTT instead of waiting for loss. A practical result: a brand-new connection cannot use the full bandwidth immediately, another reason to keep connections warm.

Closing. Either side sends **FIN**; the other acknowledges. The side that closes first keeps the socket in **TIME_WAIT** for a short time (on Linux, 60 s) to catch stray packets — a source of port exhaustion on busy clients that open and close many connections.

Head-of-line (HOL) blocking. Because TCP delivers bytes strictly in order, one lost packet holds up everything behind it until it is retransmitted, even data that already arrived. Picture a single-lane road where one stalled car stops all traffic behind. If several independent requests share one TCP connection (as in HTTP/2), a single loss stalls all of them.

UDP has no handshake, no ACKs, no ordering and no congestion control. Each **datagram** is sent and forgotten. The header is 8 bytes versus TCP's 20+. Applications that need some reliability add it themselves.

QUIC (standardised by the IETF, the Internet Engineering Task Force, in 2021, originally developed at Google) runs over UDP and puts into one protocol what used to take TCP + TLS:

1. **Faster setup** — the transport and TLS 1.3 handshakes are combined, so a new connection takes 1 RTT, and a returning client can send data in the first packet (**0-RTT**).
2. **Independent streams** — many streams inside one connection, and a lost packet only stalls the stream it belongs to. No transport-level HOL blocking between streams.
3. **Connection migration** — a connection is identified by a **connection ID**, not the 5-tuple, so your phone switching from Wi-Fi to 4G keeps the same connection.
4. **Always encrypted** — even most of the transport headers.
5. **Lives in user space** — it can evolve without operating-system upgrades. The downside is more CPU per byte than kernel TCP, and some corporate firewalls block UDP, so clients fall back to TCP.

Types

	TCP	UDP	QUIC
Connection setup	1 RTT (plus TLS)	none	1 RTT incl. TLS, 0-RTT on resume
Reliable, ordered	Yes, one stream	No	Yes, per stream
HOL blocking	Yes	No	Only within a stream
Encryption	Separate (TLS)	None built in	Built in
Typical use	Web, APIs, databases	DNS, video calls, games	HTTP/3

Trade-offs

TCP gives correctness at the cost of setup latency and stalls under loss. UDP gives speed and control at the cost of building whatever reliability you need yourself. QUIC fixes TCP's main pains for the web but costs more CPU and is sometimes blocked.

Common mistakes

- Saying "UDP is faster" without context. On a clean network, a long-lived TCP connection is just as fast for bulk data. UDP wins on setup time and on not waiting for retransmissions.
- Forgetting that every new TCP + TLS connection costs 2–3 RTTs before the first byte. Use connection pooling and keep-alive.

Real-world examples

Zoom, WebRTC (browser video calls), and most online games use UDP. DNS uses UDP for normal queries and switches to TCP for large responses. Google, YouTube, Meta and Cloudflare serve a large share of their traffic over QUIC / HTTP/3.

In the interview

Q: Why would a video-calling app use UDP instead of TCP?

A: Because a frame that arrives 300 ms late is worthless. TCP would pause all later frames while retransmitting the lost one (HOL blocking). With UDP the app just skips the lost frame and stays real-time.

Q: What problem does QUIC solve?

A: TCP's head-of-line blocking across multiplexed streams and its slow combined TCP + TLS handshake. QUIC gives independent streams, a 1-RTT (or 0-RTT) encrypted handshake, and survives network changes.

TL;DR

TCP = connected, reliable, ordered, congestion-controlled, but has handshake cost and head-of-line blocking. UDP = fire-and-forget datagrams. QUIC = reliable, encrypted, multi-stream transport over UDP that powers HTTP/3.

HTTP — the language of the web

What it is

HTTP (HyperText Transfer Protocol) is the request–response protocol browsers and APIs use. The client sends a **request** (a method, a path, headers, optional body); the server sends a **response** (a status code, headers, optional body). It is like ordering at a counter: "GET me the menu" → "200 OK, here it is".

```
GET /users/42 HTTP/1.1
Host: api.example.com
Accept: application/json
Authorization: Bearer eyJhbGciOi...

HTTP/1.1 200 OK
Content-Type: application/json
Cache-Control: max-age=60

{"id": 42, "name": "Asha"}
```

Why it matters

Almost every API you design in an interview is HTTP. Choosing the right method and status code makes APIs predictable, cache-friendly and safe to retry. The HTTP version decides how many connections you need and how much latency you pay.

How it works

Methods (verbs).

Method	Meaning	Safe?	Idempotent?
GET	Read a resource	Yes	Yes
HEAD	Like GET, headers only	Yes	Yes
POST	Create, or run an action	No	No
PUT	Replace a resource fully	No	Yes
PATCH	Change part of a resource	No	Not guaranteed
DELETE	Remove a resource	No	Yes
OPTIONS	Ask what is allowed (used by CORS, the browser's cross-origin permission check)	Yes	Yes

Safe means it does not change anything on the server. **Idempotent** means doing it once or ten times leaves the server in the same state — so a client can safely retry after a timeout. `DELETE /orders/7` twice still leaves order 7 deleted (the second call may return 404, but the state is the same). `POST /orders` twice creates two orders, which is why payment APIs add an **idempotency key** header so the server can recognise a retry.

Status codes — the first digit is the category:

Range	Meaning	Common codes
1xx	Informational	101 Switching Protocols (WebSocket upgrade)
2xx	Success	200 OK, 201 Created, 202 Accepted, 204 No Content
3xx	Redirect	301 Moved Permanently, 302 Found, 304 Not Modified
4xx	Client's fault	400 Bad Request, 401 Unauthorized, 403 Forbidden, 404 Not Found, 409 Conflict, 429 Too Many Requests
5xx	Server's fault	500 Internal Server Error, 502 Bad Gateway, 503 Service Unavailable, 504 Gateway Timeout

401 means "we don't know who you are" (not logged in); 403 means "we know who you are and you may not do this". 502 and 504 typically come from a proxy or load balancer: the backend gave a bad answer (502) or no answer in time (504). 202 Accepted is for "queued, will be processed later".

Headers are key–value metadata. Important ones: `Host` (which site — many sites share one IP), `Content-Type` (format of the body), `Authorization` (credentials), `Cache-Control` (who may cache and for how long), `ETag` and `If-None-Match` (let the server reply 304 Not Modified if the client's copy is current), `User-Agent`, `Accept-Encoding: gzip, br` (compression), `X-Forwarded-For` (original client IP, added by proxies).

Statelessness and cookies. HTTP is **stateless**: each request carries everything the server needs, and the server does not remember the previous request by itself. This is what makes it easy to put many identical servers behind a load balancer. To build logins and shopping carts on top, servers use **cookies**: the server sends `Set-Cookie: session=abc123; HttpOnly; Secure; SameSite=Lax`, and the browser automatically sends `Cookie: session=abc123` on every later request to that site. The session data itself lives in a shared store (like Redis) or inside a signed token, so any server can handle the next request.

Keep-alive (persistent connections). HTTP/1.0 opened a new TCP connection per request. HTTP/1.1 keeps the connection open by default for reuse, saving the handshake on every request.


Types

HTTP/1.1 (1997). Text-based. One request at a time per connection; the next request waits for the previous response (**HTTP-level HOL blocking**). "Pipelining" was specified but never worked reliably. Browsers work around it by opening about 6 connections per host, and sites used tricks like domain sharding and sprite images.

HTTP/2 (2015). Binary framing. **Multiplexing**: many requests and responses interleave as **streams** over one TCP connection, so one slow response no longer blocks others at the HTTP level. **Header compression** (HPACK) shrinks repetitive headers. Server push existed but was little used and has been removed from Chrome. Weakness: it still runs on one TCP connection, so one lost packet stalls every stream (TCP-level HOL blocking). On lossy mobile networks this can be worse than six HTTP/1.1 connections.

HTTP/3 (2022). Same meaning as HTTP/2 but runs on QUIC over UDP. Independent streams remove TCP HOL blocking, setup is faster, and connections survive network switches. Header compression is QPACK. Browsers discover HTTP/3 through an `Alt-Svc` header or a DNS **HTTPS record**, and fall back to HTTP/2 if UDP is blocked.

	HTTP/1.1	HTTP/2	HTTP/3
Transport	TCP	TCP	QUIC (UDP)
Format	Text	Binary frames	Binary frames
Parallel requests	~6 connections	Many streams, 1 connection	Many streams, 1 connection
HOL blocking	HTTP and TCP level	TCP level	Per stream only
Encryption	Optional	Required by browsers	Always



Common mistakes

- Using GET for actions that change data (a crawler or prefetcher may trigger them).
- Returning 200 with `{"error": ...}` in the body. Proxies, caches, monitoring and retries all rely on real status codes.
- Retrying non-idempotent POSTs blindly. Use idempotency keys.
- Storing session state in one server's memory, which breaks as soon as there are two servers.

In the interview

Q: Which HTTP methods are idempotent and why does it matter?

A: GET, HEAD, PUT, DELETE, OPTIONS. It matters because networks time out: if the client does not know whether the request succeeded, it can retry an idempotent request safely. For POST you need an idempotency key.

Q: What did HTTP/2 improve and what did HTTP/3 fix on top?

A: HTTP/2 multiplexed many requests over one connection with header compression, removing HTTP-level head-of-line blocking. HTTP/3 moved to QUIC to remove the remaining TCP-level head-of-line blocking and speed up connection setup.

TL;DR

HTTP is a stateless request–response protocol of methods, status codes and headers. Cookies add sessions on top, keep-alive reuses connections, HTTP/2 multiplexes streams over TCP, and HTTP/3 does the same over QUIC.

HTTPS and TLS

What it is

HTTPS is HTTP sent inside a **TLS (Transport Layer Security)** encrypted tunnel. TLS gives three guarantees: **confidentiality** (eavesdroppers see gibberish), **integrity** (nobody can change the bytes undetected) and **authentication** (you really are talking to `bank.com`, not an impostor). Its older name is **SSL**, which is why people still say "SSL certificate" and "SSL termination". The current version is TLS 1.3 (2018); TLS 1.2 is still common; anything older is deprecated.

Analogy: a sealed, tamper-evident envelope, plus a passport check of the person you are handing it to.

Why it matters


Browsers mark plain HTTP as "Not secure", HTTP/2 in browsers and HTTP/3 always require it, and any password, token or personal data on the wire must be encrypted. This is **encryption in transit** (as opposed to **encryption at rest**, which protects stored data on disk). TLS also costs latency and CPU, which affects where you decrypt (see TLS termination in the load balancer section).

How it works

Certificates. A server proves its identity with a **certificate**: a file containing the domain name, the server's **public key**, an expiry date, and a digital signature from a **Certificate Authority (CA)** — an organisation trusted by browsers and operating systems, such as Let's Encrypt or DigiCert. The browser follows the **chain of trust**: server certificate → intermediate CA → **root CA** that is pre-installed in the browser. If the chain is valid, the name matches and it is not expired, the server is trusted. Let's Encrypt issues free certificates, renewed automatically with the ACME protocol. They have been valid for 90 days, and lifetimes across the industry are shrinking: Let's Encrypt plans 64 days in 2027 and 45 days in 2028, so automated renewal is mandatory.

Public-key vs symmetric encryption. Asymmetric (public-key) cryptography uses a key pair: anything signed by the private key can be verified with the public key. It is slow, so TLS uses it only during the handshake to authenticate the server and agree on a shared secret. After that, all data is encrypted with fast **symmetric** encryption (one shared key, e.g. AES-GCM or ChaCha20).

TLS 1.3 handshake (simplified):



1. The client sends supported versions and cipher suites and a **key share** (its half of a Diffie–Hellman key exchange — a method where two sides each mix in a secret and arrive at the same shared key without ever sending it).
2. The server answers with its key share, its certificate, and a signature proving it owns the certificate's private key.

3. Both sides derive the same symmetric keys. The client sends Finished and can immediately send the encrypted request.

TLS 1.3 needs **1 RTT** (TLS 1.2 needed 2). Combined with TCP's 1 RTT, a fresh HTTPS connection over TCP costs about 2 RTTs before the request goes out — 140 ms from London to New York. **Session resumption** and **0-RTT** let returning clients skip work (0-RTT data can be replayed by an attacker, so it should only be used for idempotent requests). Using fresh Diffie–Hellman keys per session gives **forward secrecy**: stealing the server's private key later does not decrypt old recorded traffic.

SNI (Server Name Indication). The ClientHello includes the hostname so one IP can serve certificates for many domains — essential for load balancers and CDNs.

mTLS (mutual TLS) — both sides present certificates. Used between internal services (service meshes) so each service proves its identity.

Common mistakes

- Letting certificates expire. It has caused outages at large companies; automate renewal and alert on expiry.
- Terminating TLS at the edge and sending plaintext across untrusted networks. Inside one VPC it may be acceptable; across data centres, re-encrypt.

In the interview

Q: Why does HTTPS use both asymmetric and symmetric encryption?

A: Asymmetric crypto solves authentication and key agreement without a shared secret, but it is slow. Once both sides share a key, symmetric encryption is fast enough for bulk data.

Q: How many round trips does a new HTTPS request cost?

A: About 1 RTT for TCP, 1 for TLS 1.3, then 1 for the request and response — 3 in total. With HTTP/3 over QUIC the first two merge into one, and resumed connections can send data immediately.

TL;DR

TLS encrypts and authenticates connections using certificates signed by trusted CAs. The handshake uses public-key crypto to agree on a symmetric key, TLS 1.3 takes 1 RTT, and HTTPS is simply HTTP inside TLS.

API styles — REST, RPC and gRPC, GraphQL

What it is

An **API (Application Programming Interface)** is the menu a service offers to other programs: which operations exist, what inputs they take and what they return. Three styles dominate.

- **REST (Representational State Transfer)** models everything as **resources** (nouns) with URLs, manipulated with standard HTTP methods (verbs). `GET /users/42`, `POST /users/42/orders`. Like a library: every book has a shelf address, and there are a few standard things you can do with any book (look, add, replace, remove).
- **RPC (Remote Procedure Call)** models the API as functions you call on a remote machine as if they were local: `getUser(42)`, `chargeCard(order, amount)`. Like phoning a colleague and asking them to do a specific task.
- **GraphQL** gives clients one endpoint and a query language to ask for exactly the fields they want, possibly across several related objects, in one round trip. Like a form where you tick exactly which details you need.

Why it matters

The API is the contract between teams and between your system and its users. A good style choice makes clients simple and fast; a poor one causes chatty clients, over-fetching (downloading data you don't need) or under-fetching (needing many calls to build one screen).

How it works

REST in practice.

1. Name resources with plural nouns: `/users`, `/users/42`, `/users/42/orders`.
2. Use methods for actions: GET reads, POST creates, PUT replaces, PATCH updates part, DELETE removes.
3. Return proper status codes (201 Created with a `Location` header, 404, 409 Conflict).
4. Keep requests stateless, so any server can answer and GET responses can be cached by browsers and CDNs.
5. Usually JSON over HTTP/1.1 or HTTP/2.

Idempotent methods (GET, PUT, DELETE) can be retried safely; this is a big reason to prefer `PUT /users/42/avatar` over `POST /changeAvatar`.

gRPC. An open-source RPC framework from Google that runs on HTTP/2. You define services and messages in a `.proto` file using **Protocol Buffers (Protobuf)** — a compact binary format with a schema:

```
service UserService {
  rpc GetUser (GetUserRequest) returns (User) {}
}
message GetUserRequest { int64 id = 1; }
message User { int64 id = 1; string name = 2; }
```

The numbers (`= 1`, `= 2`) are field tags that identify each field on the wire. A code generator produces client and server code in many languages, so calling another service looks like calling a local function, with types checked at compile time. Protobuf messages are typically several times smaller and faster to parse than the same JSON, and the numbered fields allow **backward-compatible** schema changes (add new field numbers, never reuse old ones). gRPC supports four call shapes: unary (one request, one response), server streaming, client streaming and bidirectional streaming. Browsers cannot speak native gRPC directly, so it is mostly used **service-to-service**, with gRPC-Web or a REST gateway for browsers.

GraphQL. Created at Facebook (open-sourced in 2015). The server publishes a typed **schema**; the client sends a query such as:

```
query {
  user(id: 42) {
    name
    orders(last: 3) { id total }
  }
}
```

and gets back exactly that shape. Writes are **mutations**, and live updates are **subscriptions**. Each field is filled by a **resolver** function on the server. It is ideal when many different clients (web, iOS, Android) need different slices of the same data. Downsides: usually one POST endpoint, so ordinary HTTP caching does not work; a careless query can be very expensive, so servers limit query depth and cost; and naive resolvers cause the **N+1 query problem** (one query for the list, then one per item), usually fixed with batching (the DataLoader pattern).

Types

	REST	gRPC	GraphQL
Model	Resources + HTTP verbs	Functions	Typed graph, client picks fields
Format	Usually JSON	Protobuf (binary)	JSON
Transport	HTTP/1.1 or 2	HTTP/2	HTTP, one endpoint
Best for	Public APIs, CRUD (create/read/update/delete), caching	Internal service calls, streaming	Many client types, complex screens
Weak spot	Over/under-fetching	Browser support, readability	Caching, query cost control

Trade-offs

REST is universally understood and cache-friendly, but may need many calls per screen. gRPC is fast, strongly typed and streams well, but is binary (harder to debug with `curl`) and needs a proxy for browsers. GraphQL gives clients flexibility but moves complexity and performance risk to the server.

Common mistakes

- Verbs in REST URLs (`/getUser?id=42`) instead of methods on resources.
- Using GraphQL "because it is modern" for a simple public API where REST with caching would be cheaper.
- Changing Protobuf field numbers, which silently breaks old clients.

Real-world examples

Stripe and GitHub's v3 API are classic REST. GitHub also offers a GraphQL API (v4), and Shopify's storefront API is GraphQL. Google, Netflix and many companies use gRPC between internal microservices; Kubernetes uses gRPC for its plug-in interfaces, such as the one between the kubelet and the container runtime.

In the interview

Q: You are designing a mobile app's backend and an internal ranking service. Which API styles?

A: REST (or GraphQL if screens need many related objects) for the public mobile API, because it is easy to consume, cache and debug. gRPC between the backend and the ranking service, for compact binary messages, typed contracts and streaming.

Q: What makes a REST call safe to retry?

A: Using an idempotent method (GET, PUT, DELETE), or attaching an idempotency key to a POST so the server returns the original result instead of repeating the action.

TL;DR

REST = resources and HTTP verbs, simple and cacheable. gRPC = typed remote functions over HTTP/2 with Protobuf, great inside the data centre. GraphQL = clients query exactly the fields they need from a typed schema.

Real-time communication — polling, long polling, WebSockets, SSE, webhooks

What it is

Plain HTTP only lets the client ask. Many features need the server to *tell* the client something as soon as it happens: a chat message, a new notification, a stock price, a driver's location. Because the client is usually behind NAT and the server cannot open a connection to it, every solution is some way of keeping a channel open from the client side — or, between servers, of calling back a public URL.


- **Short polling** — the client asks "anything new?" every few seconds. Like a child asking "are we there yet?" every minute.
- **Long polling** — the client asks, and the server holds the request open until there is news or a timeout (say 30 s), then the client immediately asks again. Like asking a shopkeeper to call you over when your order is ready.
- **WebSockets** — one long-lived, two-way connection over which both sides send messages any time. Like an open phone line.
- **Server-Sent Events (SSE)** — one long-lived HTTP response that the server keeps writing events into; one-way, server to client. Like a radio broadcast you tune into.
- **Webhooks** — server-to-server: when an event happens, service A sends an HTTP POST to a URL that service B registered. Like leaving your phone number so the shop calls you.

Why it matters

Choosing wrongly wastes resources (polling a million clients every second is a million requests per second, mostly answering "nothing new") or adds needless complexity. Long-lived connections also change capacity planning: a chat server's limit is often the number of open connections (memory per connection, file descriptors) rather than requests per second.

How it works

WebSocket upgrade. It starts as an ordinary HTTP/1.1 request, so it passes through normal ports and proxies:



1. The client sends `GET` with `Upgrade: websocket` and `Connection: Upgrade` headers (URL scheme `ws://` or encrypted `wss://`).
2. The server answers `101 Switching Protocols`.
3. From then on, both sides exchange small **frames** with only a few bytes of overhead each, until either side closes.
4. Applications send **heartbeats** (ping/pong) every 20–60 s so that idle connections are not silently cut by NAT routers or load balancers, and clients reconnect with backoff if the link drops.

SSE. The client opens `GET /events` with `Accept: text/event-stream`. The server responds and never finishes, writing lines like `data: {"price": 101.5}` followed by a blank line for each event. The browser's built-in `EventSource` reconnects automatically and sends `Last-Event-ID` so the server can resume. It is plain HTTP, so it works well with HTTP/2 and existing infrastructure. Large language model chat interfaces commonly stream tokens this way.

Webhooks. The receiver registers `https://myapp.com/hooks/payments`. When a payment succeeds, the provider POSTs a JSON event there. Good practice: sign each request (an HMAC header: a hash of the body computed with a shared secret key) so the receiver can verify the sender; retry with backoff on failure; and make the receiver idempotent because the same event may arrive twice.

Types

Technique	Direction	Latency	Cost / complexity	Use when
Short polling	Client pulls	Up to the interval	Many wasted requests	Rare updates, simplicity first
Long polling	Server push (emulated)	Low	Held requests, reconnect loops	Fallback where WebSockets are blocked
WebSocket	Two-way	Lowest	Stateful connections, sticky routing	Chat, games, collaboration
SSE	Server to client	Low	Simple, auto-reconnect	Feeds, notifications, live scores, token streaming
Webhook	Server to server	Low	Receiver needs public URL	Payment and Git events

Trade-offs

Persistent connections give instant delivery but make servers **stateful**: each user is attached to one server, so you need a way to route messages to the right server (often a pub/sub layer such as Redis Pub/Sub or Kafka between servers), and deployments must drain connections gracefully. Polling is stateless and trivially scalable but wasteful and slower.

Common mistakes

- Choosing WebSockets for a one-way feed where SSE would be simpler.
- Forgetting that a load balancer's idle timeout (for example 60 s by default on AWS ALB) will close quiet WebSockets unless you send heartbeats.
- Assuming webhooks arrive exactly once and in order. They do not.

Real-world examples

Slack and Discord use WebSockets for their real-time clients. GitHub, Stripe and Shopify deliver events by webhooks. Many dashboards and AI chat apps stream with SSE.

In the interview

Q: How would you push new chat messages to 10 million online users?

A: WebSocket connections terminated on a fleet of connection servers (each holding perhaps 50,000–100,000 connections). A registry maps user → connection server, and a pub/sub layer delivers each message to the right server, which writes it to the socket. Clients reconnect with backoff and fetch missed messages using their last seen ID.

Q: When would you choose SSE over WebSockets?

A: When only the server needs to push (notifications, live scores, streaming text). SSE is plain HTTP, reconnects automatically and needs no protocol upgrade.

TL;DR

Polling asks repeatedly, long polling waits for news, WebSockets keep a two-way channel, SSE streams one-way from server to client, and webhooks are server-to-server callbacks. Persistent connections are fast but make servers stateful.

API design basics

What it is

The small, practical rules that make an API pleasant and safe to evolve: how you version it, how clients page through big lists, how you tell clients about limits and errors.

Why it matters

Once a public API is used by thousands of clients, you cannot change it freely. Pagination and rate limits protect your servers from clients asking for too much at once.

How it works

Versioning. When you must make a breaking change (removing or renaming a field, changing meaning), publish a new version and keep the old one running for a deprecation period.

- **URL versioning**: `/v1/orders`, `/v2/orders`. Most common, very visible.
- **Header versioning**: `Accept: application/vnd.example.v2+json`, or a custom header. Cleaner URLs, harder to test in a browser.
- **Date-based versions**: Stripe pins each account to a dated version and lets clients opt in to newer ones.

Prefer **additive** changes (new optional fields) that need no new version at all, and tell clients to ignore fields they do not recognise.

Pagination. Never return an unbounded list.

- **Offset pagination**: `GET /posts?limit=20&offset=40`. Simple, allows "jump to page 5". But the database still reads and skips the first 40 rows, which gets slow at offset 1,000,000, and if a new post is inserted while you page, items shift and you see duplicates or miss items.
- **Cursor (keyset) pagination**: `GET /posts?limit=20&after=eyJpZCI6MTIzNH0`. The cursor is an opaque token encoding the last item's sort key (e.g. `id=1234`). The server runs `WHERE id < 1234 ORDER BY id DESC LIMIT 20`, which uses an index and is equally fast on page 1 and page 50,000, and stays stable when new items arrive. You cannot jump to an arbitrary page. Feeds and timelines (Twitter/X, Facebook, Slack) use cursors.

	Offset	Cursor
Jump to page N	Yes	No
Speed deep into list	Gets slower	Constant
Stable under inserts	No	Yes
Best for	Admin tables, small data	Feeds, large or changing data

Rate-limit headers. When you limit clients (say 5,000 requests per hour), tell them where they stand. Common headers: `X-RateLimit-Limit` (quota), `X-RateLimit-Remaining`, `X-RateLimit-Reset` (when the window resets). GitHub uses exactly these. When a client is over the limit, return **429 Too Many Requests** with a `Retry-After: 30` header (seconds to wait). The IETF is standardising unprefixed `RateLimit` headers for the same purpose. Rate-limiting algorithms themselves are covered in Part 5.

Other basics. Consistent error bodies (a machine-readable code plus a human message), idempotency keys on POST, filtering and sorting via query parameters (`?status=paid&sort=-created_at`), and documenting the API with an **OpenAPI** (formerly Swagger) specification.

Common mistakes

- Breaking changes without a version bump.
- Offset pagination on an infinite-scroll feed with millions of rows.
- Returning 500 for bad input (that is a 400) or hiding rate limiting behind 503.

TL;DR


Version only for breaking changes, prefer cursor pagination for big or changing lists, and communicate limits with rate-limit headers and 429 + Retry-After.

Proxies and API gateways

What it is

A **proxy** is a middleman that receives a request and forwards it on someone else's behalf.

- A **forward proxy** acts for **clients**. The client is configured to send all traffic through it, and the internet sees the proxy instead of the client. Like an assistant who makes calls for you. Used by companies to filter and log employee browsing, by VPN-like services (virtual private networks that tunnel your traffic through another machine) to hide the user's IP, and for caching outbound downloads.
- A **reverse proxy** acts for **servers**. Clients think they are talking to the website; in reality the reverse proxy receives the request and forwards it to one of the hidden servers behind it. Like a hotel receptionist who passes your request to the right staff member. Used for load balancing, TLS termination, caching, compression and hiding internal structure.



An **API gateway** is a reverse proxy specialised for APIs. It is the single front door to many backend services (often microservices) and handles cross-cutting concerns once instead of in every service.

Why it matters

Reverse proxies and gateways are where you put shared concerns: authentication, rate limiting, TLS, logging, routing by path. They also let you change the backend (split a monolith, move a service) without clients noticing.

How it works

An API gateway receiving `GET /orders/7` typically:

1. Terminates TLS.
2. Authenticates the caller (validates an API key, a JWT (JSON Web Token, a signed token carrying the user's identity) or an OAuth access token issued by a login service).
3. Applies rate limits and quotas per client.
4. Routes by path, host or header: `/orders/*` → order service, `/users/*` → user service.
5. Optionally transforms the request (REST to gRPC, adds headers like a request ID), or **aggregates** several backend calls into one response.
6. Records logs, metrics and traces, then returns the response.

A variant is **BFF (Backend for Frontend)**: a separate gateway per client type (web, mobile) that shapes responses for that client.

Types

Component	Main job	Examples
Forward proxy	Act for clients, filter, hide identity	Squid, corporate proxies
Reverse proxy	Act for servers, TLS, caching, routing	NGINX, HAProxy, Envoy
Load balancer	Spread traffic over healthy servers	AWS ALB/NLB, HAProxy
API gateway	Auth, rate limits, routing for APIs	AWS API Gateway, Kong, Apigee

The lines blur: NGINX is a reverse proxy, load balancer and basic gateway at once. Think of a load balancer as a reverse proxy whose main job is distribution, and an API gateway as a reverse proxy whose

main job is API policy.

Trade-offs

Every proxy adds a network hop (typically well under 1 ms inside a data centre, but more with heavy logic) and is a potential bottleneck and single point of failure, so it must itself be redundant and scaled. A gateway that grows too much business logic becomes a hard-to-change "god service".

Common mistakes

- Confusing forward and reverse proxies. Ask: whom does it represent — the client or the server?
- Putting business rules in the gateway. Keep it to cross-cutting policy.
- Losing the client's real IP: proxies must pass it on in `X-Forwarded-For` (or the PROXY protocol for L4), and backends must trust that header only from known proxies.

In the interview

Q: What is the difference between a reverse proxy, a load balancer and an API gateway?

A: All three sit in front of servers. A reverse proxy is the general idea (forward on behalf of servers). A load balancer focuses on spreading traffic across healthy instances. An API gateway focuses on API concerns — auth, rate limits, routing to many services, transformation. One product often plays all three roles.

TL;DR

A forward proxy represents clients, a reverse proxy represents servers, and an API gateway is a reverse proxy that enforces API policy (auth, rate limits, routing) at the front door.

Load balancers

What it is

A **load balancer (LB)** is a component that receives incoming traffic and spreads it across a group of servers (often called a **pool**, **backend set** or **target group**), sending each request or connection only to servers that are healthy. Clients see one address; behind it there may be 3 or 3,000 servers.

Analogy: the host at a busy restaurant. Guests do not pick a table themselves; the host looks at which waiters are free, skips the one who has gone home sick, and seats each party so no single waiter is swamped.


Why it matters

The load balancer is what makes **horizontal scaling** (Part 1) actually work:

- **Scalability** — add servers to the pool and capacity grows, with no change for clients.
- **Availability** — if a server dies, health checks notice and traffic flows to the rest. A single server is a single point of failure; a pool behind an LB is not.
- **Zero-downtime deployments** — take servers out one by one, update them, put them back.
- **Central place for shared work** — TLS termination, compression, request logging, basic security.
- **Hiding the backend** — servers keep private IPs; only the LB is public.

Almost every system design answer has a load balancer in front of each tier of stateless servers, and often internal ones between services too.

How it works



1. DNS resolves `api.example.com` to the load balancer's address (a **virtual IP**, VIP — an address that belongs to the service, not to any one machine).
2. The client connects to the LB. An L7 LB terminates TLS and reads the HTTP request; an L4 LB just sees the TCP or UDP connection.
3. The LB picks a backend using its **algorithm** (below), considering only servers that currently pass **health checks**.
4. It forwards the request (L7 opens or reuses its own connection to the backend) or the connection's packets (L4).
5. The response flows back through the LB to the client (in most designs; some L4 modes let servers reply directly — see "direct server return").
6. The LB records metrics: requests per second, errors, latency per backend.

Because the servers behind an LB may each receive any request, they should be **stateless** — sessions and data live in a shared cache or database, not in one server's memory.

Types

By network layer: L4 vs L7

Layer 4 (transport) load balancer. Works on TCP/UDP connections using IPs and ports. It picks a backend when a connection opens and then shuttles that connection's packets back and forth (either by rewriting addresses, NAT-style, or by proxying the TCP stream), never looking inside. It cannot see URLs, headers or cookies, and with TLS it sees only encrypted bytes (unless it terminates TLS itself, which some L4 products can do).

- Pros: very fast, low latency (microseconds of overhead), handles millions of connections, works for any protocol (databases, MQTT messaging for IoT devices, game servers, raw TCP), cheap.
- Cons: no content-based routing; balancing is per connection, so one long-lived connection carrying lots of requests (HTTP/2, gRPC) is stuck on one backend.

Layer 7 (application) load balancer. Terminates the client connection, parses the HTTP request, then makes a separate request to the chosen backend. Because it understands the content, it can:


- Route by path (`/api` → API servers, `/images` → image servers), host name (`shop.example.com` vs `blog.example.com`), headers, cookies or query string.
- Balance **per request**, so many HTTP/2 or gRPC requests on one client connection are spread across many backends.
- Do TLS termination, compression, caching, retries, redirects (HTTP → HTTPS), add headers like `X-Forwarded-For` and request IDs, enforce auth and rate limits, block malicious patterns (web application firewall, or WAF, features).
- Pros: smart routing and rich features. Cons: more CPU per request, more latency (typically still around a millisecond), must hold TLS keys, HTTP-family protocols only.

	L4 load balancer	L7 load balancer
Sees	IPs, ports, TCP/UDP	Full HTTP request
Decides per	Connection	Request
Routing by URL, header, cookie	No	Yes
Speed and cost	Faster, cheaper	More CPU per request
Protocols	Any TCP/UDP	HTTP, HTTP/2, gRPC, WebSocket
AWS example	NLB	ALB

A common layered setup: an L4 balancer in front (cheap, huge scale, static IPs) feeding a fleet of L7 proxies (smart routing), which feed the app servers.

By form: hardware, software, cloud, DNS, global

- **Hardware load balancers** — dedicated appliances with specialised chips (for example F5 BIG-IP, Citrix NetScaler, now NetScaler ADC). Very high throughput and vendor support, but expensive (tens of thousands of dollars each), scaled by buying more boxes, and slow to change. Common in traditional enterprises and banks.
- **Software load balancers** — programs on ordinary servers: **NGINX**, **HAProxy**, **Envoy**, Traefik. Cheap, flexible, configurable as code, scale by adding instances. Hyperscalers built their own software L4 balancers too: Google's **Maglev** and Meta's **Katran** run on commodity Linux servers.
- **Cloud (managed) load balancers** — a service you rent, where the provider runs and scales the fleet: AWS **ALB** (L7), **NLB** (L4), and **Gateway Load Balancer** (for routing through firewalls and appliances); Google Cloud Load Balancing; Azure Load Balancer (L4) and Application Gateway (L7). You pay per hour plus per traffic unit, and get automatic scaling and high availability across zones.
- **DNS load balancing** — the DNS server spreads users by returning different IPs (round robin, weighted, GeoDNS, latency-based), as described in the DNS section. Coarse and cached, but global and with no extra hop.
- **Global server load balancing (GSLB)** — distributing users across **multiple data centres or regions** rather than across servers in one place. It decides which region a user goes to based on geography, latency, region health and capacity, and fails over whole regions. It is built from DNS-based steering (Route 53, Cloudflare Load Balancing, NS1, F5 DNS) and/or **anycast** (one IP announced from many locations, explained in the CDN section), as in Google Cloud's global load balancer and Cloudflare. Inside each region, regular L4/L7 balancers take over.



Where it runs: client-side vs server-side

Most LBs are **server-side** (a separate box or service in the middle). In **client-side load balancing**, each client gets the list of healthy instances from a service registry and picks one itself (gRPC clients, Netflix's Ribbon library, service-mesh sidecars like Envoy next to each service). This removes a hop and a bottleneck but puts logic in every client. Service discovery is covered in Part 5.

Load-balancing algorithms

The **algorithm** decides which healthy backend gets the next request or connection. They fall into two families: **static** (ignore current load, decide by a fixed rule) and **dynamic** (look at live load signals).

Round robin. Send requests to servers in turn: A, B, C, A, B, C... Like dealing cards. Simple and fair when all servers are identical and requests cost about the same. Weakness: blind to load — if some requests are heavy (a 10-second report) a server can pile up work while still getting its "turn".

Weighted round robin. Each server gets a weight proportional to its capacity. With weights A=3, B=1, A receives 3 of every 4 requests. Used when servers differ in size (a 16-core next to an 8-core machine), and to send a small share of traffic to a new version (**canary release**: weight 1 for new, 99 for old).

Least connections. Send the new request or connection to the server with the fewest active connections right now. Good when requests vary a lot in duration or connections are long-lived (WebSockets, database proxies), since busy servers naturally get fewer new ones. **Weighted least connections** divides the count by each server's weight.

Least response time (least latency). Prefer the server with the lowest recent response time, often combined with fewest active connections. Routes around a server that is slow because of a noisy neighbour, garbage collection or a bad disk. Needs the LB to measure latency, and can over-react (everyone rushes to the fastest server, which then becomes slow — **herding**), so implementations smooth the measurements. Envoy's and NGINX Plus's "least time" style policies and the **EWMA** (exponentially weighted moving average) balancer used by some proxies are examples.


IP hash (source hash). Compute `hash(client IP) mod N` to pick a server, so the same client always lands on the same server — stickiness with no cookies. Problems: many users behind one NAT all hit one server, and when N changes (a server is added or removed) almost every client is remapped to a different server.

Consistent hashing. Fixes the remapping problem. Imagine a ring of hash values from 0 to 2^32. Each server is placed at several points on the ring (**virtual nodes**). A key — client IP, user ID, URL — is hashed onto the ring and goes to the next server clockwise. When a server is added or removed, only the keys in its slice of the ring move, about 1/N of them, instead of almost all. Used when the *same key should reach the same server* so that server's local cache stays useful: caching proxies, sharded caches, chat servers. Google's Maglev uses its own consistent-hashing variant, and HAProxy and Envoy offer **ring hash** and **Maglev** policies. (Consistent hashing is explained more fully with sharding in Part 3.)

Random. Pick a server at random. With many requests it evens out statistically, needs no shared state between multiple LB instances, and is surprisingly good. Its weakness is short-term imbalance.

Power of two choices (P2C). Pick **two** servers at random, then send the request to the less loaded of the two (fewest active requests or lowest latency). A famous result from probability (Mitzenmacher's analysis of "two choices") shows this tiny bit of information sharply reduces the worst-case load compared with pure random, while avoiding the herding problem of always choosing the global least-loaded server — because many independent LB instances with slightly stale data will not all pick the same "best" server. Envoy's least-request policy uses P2C by default (Envoy's overall default is round robin), and NGINX supports `random two least_conn`.

Others you may hear. Least bandwidth (fewest bytes per second), **resource-based / adaptive** (backends report CPU or load via an agent), **URL hash** (same URL to the same cache server), and **locality-aware** (prefer backends in the same zone to save cross-zone latency and cost).



Algorithm	Uses live load?	Sticky by key?	Best for
Round robin	No	No	Identical servers, similar requests
Weighted round robin	No	No	Mixed server sizes, canaries
Least connections	Yes	No	Long or uneven requests, WebSockets
Least response time	Yes	No	Avoiding slow servers
IP hash	No	Yes, by client IP	Simple stickiness, fixed pool
Consistent hashing	No	Yes, by any key	Cache affinity, changing pool
Random	No	No	Many LB instances, simplicity
Power of two choices	Yes, sampled	No	Large fleets, distributed LBs

Health checks

A load balancer must know which backends are alive. Two kinds:

- **Active health checks** — the LB itself probes each backend on a schedule: a TCP connect (L4), or an HTTP `GET /health` expecting a 200 (L7). Typical settings: every 10 s, timeout 5 s, mark **unhealthy after 2–3 consecutive failures**, mark **healthy again after 2–5 consecutive successes**. These thresholds stop one blip from flapping a server in and out.
- **Passive health checks (outlier detection)** — the LB watches real traffic. If a backend returns several 5xx errors in a row or times out, it is ejected for a while (say 30 s) and then retried. Envoy calls this outlier detection; NGINX uses `max_fails` and `fail_timeout`.

Good practice: combine both. Make the health endpoint meaningful but cheap. A **liveness** check says "the process is running"; a **readiness** check says "I can serve traffic now" (warm caches loaded, database reachable). Be careful not to make health checks depend deeply on shared dependencies: if the database

blips and every server's health check fails, the LB removes all servers at once and turns a partial problem into a total outage. Many LBs therefore **fail open** — if every backend looks unhealthy, they send traffic to all of them anyway (AWS target groups and Envoy's "panic threshold" both do this).

Sticky sessions (session affinity)

Sticky sessions make the LB send all requests from one user to the same backend. Implemented by:

- **Cookie-based** — the LB sets a cookie naming the backend (AWS ALB's `AWSALB` cookie) or uses the app's own session cookie.
- **IP-based** — hashing the client IP (L4 or L7).

Why use it: the server holds in-memory state (an old app storing sessions locally, a WebSocket connection, a shopping cart in memory) or a warm per-user cache. Why avoid it: load becomes uneven (a few heavy users stuck on one server), scaling in or failing a server loses those users' sessions, and deployments are harder. The better design is to make servers stateless and keep session data in a shared store like Redis, or inside a signed token on the client. Use stickiness only where state is unavoidable, such as WebSockets — and even then design for reconnection to a different server.

SSL/TLS termination

TLS termination means the load balancer decrypts HTTPS traffic and forwards plain HTTP to the backends inside the private network.

- **Benefits**: certificates live in one place and renew in one place; backends save the CPU cost of handshakes; and the LB can read requests for L7 routing, caching and WAF rules.
- **Risk**: traffic between LB and servers is unencrypted. Acceptable inside a trusted private network for many companies, not for regulated data or zero-trust designs.

Variants:

- **TLS re-encryption (bridging)** — decrypt at the LB, inspect, then open a new TLS connection to the backend. Secure end to end, costs more CPU.
- **TLS passthrough** — the LB (typically L4) does not decrypt at all; the backend terminates TLS. The LB cannot route by content, but keys stay only on the servers. It can still route by the SNI host name, which is visible in the ClientHello.


Connection draining (deregistration delay)

When a server is removed — for a deployment, scale-in or maintenance — cutting it off instantly would break in-flight requests. **Connection draining** tells the LB to stop sending **new** requests to that server but let **existing** requests and connections finish, up to a timeout. AWS calls this the **deregistration delay** (default 300 s, often lowered to 30–60 s for short API requests). For long-lived WebSockets, the server should also tell clients to reconnect elsewhere, because they may never finish on their own. Draining plus health checks is what makes **rolling deployments** invisible to users.

Making the load balancer itself highly available

A single load balancer is itself a single point of failure. Options:

- **Active–passive** — two LB nodes share one virtual IP. The active node serves all traffic; the passive one watches it via heartbeats and takes over the VIP if the active one dies (commonly using **VRRP**, the Virtual Router Redundancy Protocol, via the `keepalived` tool). Simple, but half the hardware sits idle and failover takes a second or more.
- **Active–active** — all LB nodes serve traffic at once. Traffic is spread across them by DNS (multiple IPs), by anycast, or by **ECMP** (equal-cost multi-path routing, where the network's routers spread flows across several LB machines that all announce the same IP). Better use of capacity and no idle standby; each node must be able to absorb the others' load if they fail. This is how Maglev, Katran and cloud LBs operate.
- **Managed cloud LBs** handle this for you: AWS ALB and NLB run nodes in every Availability Zone you enable, and NLB offers one static IP per zone.



Direct server return (bonus detail)

Responses are usually much larger than requests (a small GET returns a big page or video). In **direct server return (DSR)**, an L4 LB forwards incoming packets to the server, and the server sends the response **straight to the client**, bypassing the LB. The LB handles only the small inbound half, so one LB can front far more traffic. Used by large-scale L4 systems such as Maglev, Katran and some LVS (Linux Virtual Server) setups.

Trade-offs

Decision	Option A	Option B
Layer	L4: fast, any protocol, blind to content	L7: smart routing, per-request, more CPU
Form	Managed cloud LB: no operations, pay per use	Self-run NGINX/HAProxy/Envoy: full control, you operate it
TLS	Terminate at LB: simpler, inspectable	Passthrough or re-encrypt: end-to-end encryption
Algorithm	Static (round robin): predictable, simple	Dynamic (least conn, P2C): adapts to load
Sessions	Sticky: supports local state	Stateless: even load, easy failover

Common mistakes

- Drawing a single LB box and forgetting it needs redundancy.
- Using round robin for long-lived WebSocket connections; least connections is usually better.
- Sticky sessions as a substitute for a shared session store.
- Health checks that only test "process is up" — the server may be up but unable to reach its database — or, the opposite, deep checks that make the whole fleet fail at once.
- Using an L4 LB in front of gRPC and wondering why one backend is overloaded: gRPC multiplexes many requests on one long connection, so you need per-request (L7 or client-side) balancing.
- Forgetting that backends see the LB's IP, not the client's, unless `X-Forwarded-For` or the PROXY protocol is used.

Real-world examples

- **NGINX** — popular web server and L7 reverse proxy/LB; round robin by default, also least connections, IP hash, generic hash with consistent option, and random with two choices.
- **HAProxy** — very fast L4/L7 load balancer; round robin, static round robin, least connections, source hash, URI hash, consistent hashing; used at GitHub, Stack Overflow and many others.
- **Envoy** — modern L7 proxy created at Lyft, used as the data plane in service meshes like Istio. Policies include round robin, least request (P2C), ring hash, Maglev and random, plus outlier detection and automatic retries.
- **AWS Application Load Balancer (ALB)** — L7; routes by path, host, headers and query; supports HTTP/2, gRPC and WebSockets; round robin, least outstanding requests or weighted random; cookie stickiness.
- **AWS Network Load Balancer (NLB)** — L4 TCP/UDP/TLS; millions of requests per second; static IP per zone; preserves the client source IP.
- **Google Maglev** and **Meta Katran** — software L4 balancers on commodity servers, using consistent hashing and ECMP to scale out.

In the interview

Q: What is the difference between an L4 and an L7 load balancer, and when would you pick each?

A: L4 balances TCP/UDP connections by IP and port without reading content: fast, cheap, any protocol. L7 parses HTTP, so it can route by path or header, balance per request, terminate TLS and apply policies. I would put an L7 balancer in front of HTTP services and gRPC, and use L4 for non-HTTP protocols, extreme throughput, or as the first tier in front of L7 proxies.

Q: Which algorithm would you choose for a fleet of identical stateless API servers? For a cache tier?

A: For stateless API servers, least outstanding requests or power of two choices — they adapt to uneven request cost and slow servers. For a cache tier, consistent hashing on the cache key, so each key goes to the same node and adding a node moves only about 1/N of the keys.

Q: How do you deploy a new version without dropping requests?

A: Rolling deployment behind the LB: for each server, deregister it with connection draining (stop new requests, let in-flight ones finish), update it, wait for readiness checks to pass, then re-register it. For extra safety, use weighted routing to canary the new version on a small share of traffic first.

Q: Isn't the load balancer a single point of failure?

A: Only if there is one. Run LB nodes as active–passive with a floating virtual IP, or active–active behind DNS, anycast or ECMP, across multiple availability zones. Managed cloud LBs already do this.

TL;DR

A load balancer spreads traffic across healthy servers so you can scale out and survive failures. Know L4 vs L7, the main forms, the algorithms (from round robin to power of two choices), health checks, stickiness, TLS termination, draining, and how to make the LB itself redundant.

CDNs and anycast

What it is

A **CDN (Content Delivery Network)** is a worldwide network of caching servers that keep copies of your content close to users. Instead of every user in Sydney fetching an image from your server in Virginia (about 200 ms round trip), they fetch it from a CDN server in Sydney (a few milliseconds).

Analogy: rather than everyone driving to one central warehouse, a retailer stocks local shops with the most popular items.

Key terms:


- **Origin** — your real server (or storage like Amazon S3) that holds the master copy.
- **Edge server** — a CDN cache server near users.
- **PoP (Point of Presence)** — a CDN location (a data centre site in a city) containing many edge servers. Large CDNs have hundreds of PoPs.

- **Cache hit** — the edge already has a fresh copy and answers directly. **Cache miss** — it must fetch from the origin (or an upper tier) first.
- **Cache hit ratio** — hits ÷ total requests. 95% means only 1 in 20 requests reaches the origin.

Why it matters

- **Lower latency** — static files (images, JavaScript, CSS, video) are served from nearby, and TLS handshakes finish against a nearby edge, which shortens every round trip.
- **Origin offload** — at 95% hit ratio the origin handles 20 times less traffic, so you need far fewer servers and less egress bandwidth.
- **Absorbing spikes and attacks** — the CDN's huge capacity soaks up traffic surges and DDoS (distributed denial-of-service) attacks, where many machines flood a site with junk traffic, before they reach you.
- **Video and large downloads** at global scale would be impossible from one origin.

How it works



1. The user's DNS lookup for `cdn.example.com` returns a nearby edge (via GeoDNS or anycast).
2. The edge checks its cache for the URL (the **cache key**, usually host + path + some query parameters and headers).
3. On a hit with a fresh copy, it answers immediately.
4. On a miss, it fetches from the origin, stores the copy for as long as the **TTL** allows, and returns it.
5. The origin controls caching through HTTP headers: `Cache-Control: public, max-age=86400` (cache for one day), `s-maxage` (TTL for shared caches like CDNs only), `no-store` (never cache), and validators (`ETag`, `Last-Modified`) so an expired copy can be re-checked cheaply with a 304 Not Modified.

Types

Pull CDN vs push CDN.

- **Pull (origin pull)** — the CDN fetches content from the origin on the first request, lazily. Zero upload effort, and only requested content is cached. Whoever asks for a file first at a given PoP waits for the trip to the origin; later visitors there get the cached copy. Most websites use pull.
- **Push** — you upload content to the CDN's storage ahead of time. Good for large files you know will be requested (game patches, video libraries) and for content that rarely changes; you manage what is stored and pay for storage.

	Pull CDN	Push CDN
How content arrives	Fetched on first miss	Uploaded in advance
Effort	Low	You manage uploads
First request	Slower (miss)	Fast
Best for	Websites, mixed traffic	Big known files, video

Invalidation (purging). When content changes before its TTL expires you can:

1. **Purge** — ask the CDN to delete a URL, a prefix or a tag from all edges (seconds to minutes depending on CDN).
2. **Versioned file names (cache busting)** — publish `app.3f9a1c.js` instead of overwriting `app.js`; the HTML references the new name, so there is nothing to invalidate. This is the standard for static assets and lets you use very long TTLs (a year) safely.
3. **Short TTLs** for content that changes often, accepting more origin traffic.

Origin shield (tiered caching). An extra cache layer between edges and the origin. Without it, a new file that is popular worldwide causes a miss at every one of hundreds of PoPs, each hitting the origin. With a shield, edges miss to the shield, so the origin sees roughly one request per object. It raises the overall hit ratio and protects the origin.

Static vs dynamic content. CDNs mostly cache static, shared content. For personalised or dynamic responses they still help by terminating TLS near the user and using optimised, kept-warm connections back to the origin, and some run code at the edge (Cloudflare Workers, Lambda@Edge, Fastly Compute).

Anycast. Normally one IP address belongs to one location (**unicast**). With **anycast**, the same IP address is announced from many locations at once using **BGP** (Border Gateway Protocol — the protocol internet networks use to tell each other which IP ranges they can reach). Routers send each user to the "nearest" location in network terms. Benefits: automatic proximity routing with no DNS tricks, natural spreading of DDoS traffic across all sites, and fast failover — if a site stops announcing, routes shift to the next site. Cloudflare's whole network, Google's public DNS `8.8.8.8`, Cloudflare's `1.1.1.1` and the DNS root servers all use anycast. "Nearest" means the best path according to BGP routing policy (often the fewest networks crossed), which is usually but not always the lowest-latency site.

Trade-offs

Long TTLs give a high hit ratio but stale content; short TTLs give freshness but more origin load. CDNs cost money per GB served, and caching anything personalised risks leaking one user's data to another if the cache key is wrong.

Common mistakes

- Caching responses that contain user-specific data under a shared key (use `Cache-Control: private` or vary the key).
- Overwriting files in place with long TTLs, then being unable to update them. Use versioned file names.
- Forgetting the origin must survive a full cache flush (a "cold" CDN) — the origin shield and gradual warm-up help.

Real-world examples

Akamai, Cloudflare, Fastly, Amazon CloudFront, Google Cloud CDN. Netflix runs its own CDN, **Open Connect**, placing caching appliances inside internet providers' networks so most video bytes never cross the wider internet. YouTube uses Google's global cache network in a similar way.

In the interview

Q: How does a CDN reduce latency and origin load?

A: It serves cached copies from PoPs near users, cutting round-trip time, and at a high hit ratio most requests never reach the origin. An origin shield collapses many edge misses into one origin request.

Q: You deploy a new version of your JavaScript and some users still get the old one. Why and how do you fix it?

A: Edges and browsers are still serving the cached file until its TTL expires. Use content-hashed file names so each version has a new URL, and keep long TTLs; purge only as an emergency tool.

TL;DR

A CDN caches content at edge PoPs near users to cut latency and offload the origin. Pull fetches on demand, push uploads ahead; manage freshness with TTLs, versioned names and purges; an origin shield protects the origin, and anycast routes users to the nearest site using one IP.

Bandwidth vs latency, and network partitions

What it is

Part 1 defined both terms: **bandwidth** is how much data a link can carry per second (1 Gbps is about 125 MB/s), and **latency** is how long one piece of data takes to get from A to B. A wider road does not make the trip shorter. This section looks at what that means for networked systems.

A **network partition** is when the network splits so that some machines cannot reach others, even though all of them are still running. Picture an office building where a corridor door jams: people on both sides keep working, but can no longer talk to each other.


Why it matters

- Many system designs are latency-bound, not bandwidth-bound. A page that needs 10 sequential round trips across the Atlantic takes at least 700 ms no matter how fast the connection is. Fixes: fewer round trips (batching, HTTP/2, connection reuse), moving data closer (CDN, regional replicas).
- Large transfers are bandwidth-bound: copying 10 TB over a 1 Gbps link takes about 22 hours (10 × 8 × 10^12 bits ÷ 10^9 bits/s ≈ 80,000 s). That is why cloud providers offer physical data-transfer devices (AWS Snowball).
- Latency has a physical floor set by the speed of light in fibre (about 200 km per millisecond, see Part 1), so no protocol trick removes it.
- **Bandwidth-delay product** (bandwidth × RTT) is how much data must be "in flight" to fill a link. A 1 Gbps link with 100 ms RTT needs 12.5 MB in flight, which is why TCP window sizes and congestion control matter on long links.
- Partitions are not rare: a failed switch, a misconfigured firewall, a cut cable between data centres. Every distributed system must decide what to do during one, which leads to the CAP theorem (Part 4).

How it works

During a partition, a node cannot tell the difference between "the other node crashed" and "the other node is fine but unreachable" — both look like silence. Systems detect trouble with **timeouts** and **heartbeats** and then choose:

1. **Stay consistent** — refuse writes (or reads) on the side that cannot reach a majority, so data never diverges. The minority side becomes unavailable.
2. **Stay available** — keep accepting requests on both sides and reconcile the differences after the network heals, accepting temporarily inconsistent data.



A partition between nodes that both think they are the leader can cause **split brain** (two leaders accepting conflicting writes); quorum-based systems prevent it by requiring a majority (Part 3 and Part 4).

Common mistakes

- Assuming "the network is reliable" — the first of the classic **fallacies of distributed computing** (others: latency is zero, bandwidth is infinite, the network is secure, topology does not change).
- Treating a timeout as proof that the remote operation failed. It may have succeeded, and only the reply was lost — hence idempotent retries.
- Buying more bandwidth to fix a latency problem.

In the interview

Q: Our API is slow for users in Asia but fine in the US. More bandwidth?

A: Probably not — it is likely latency from distance multiplied by round trips. Reduce round trips (keep-alive, HTTP/2 or HTTP/3, batching) and move things closer: a CDN for static content and TLS termination at the edge, then regional deployments or read replicas.

Q: What is a network partition and why can't you just avoid it?

A: It is a break in communication between groups of healthy nodes. Hardware and configuration failures make it unavoidable at scale, so the design must choose between consistency and availability for the duration of the partition.

TL;DR

Bandwidth is capacity, latency is delay — round trips usually dominate. Partitions split healthy nodes from each other, cannot be avoided, and force a choice between consistency and availability.

Part 2 glossary

Term	Meaning in one line
Protocol	Agreed rules for how two programs exchange messages
Packet	A small chunk of data (about 1,500 bytes max on Ethernet) routed independently
Router	Device that forwards packets toward their destination IP
IP address	Number identifying a machine's network interface
IPv4 / IPv6	32-bit addresses (~4.3 billion) / 128-bit addresses (practically unlimited)
CIDR	Notation like `10.0.0.0/8` giving an address range by its fixed leading bits
Public IP	Globally unique address reachable from the internet
Private IP	Address valid only inside a local network (10/8, 172.16/12, 192.168/16)
NAT	Rewriting addresses so many private machines share one public IP
NAT gateway	Cloud service giving private servers outbound internet access
Carrier-grade NAT	NAT run by an ISP, so many customers share one public IP
VPC	Your own isolated private network inside a cloud provider
Port	Number (0–65535) selecting which program on a machine receives data
Ephemeral port	Temporary source port the OS assigns to an outgoing connection
Socket	One endpoint of a connection: IP address plus port
5-tuple	Protocol, source IP/port, destination IP/port — identifies a connection
Port exhaustion	Running out of source ports for new outgoing connections
DNS	System that translates domain names into IP addresses
Domain name	Human-readable hierarchical name such as `www.example.com`
TLD	Top-level domain such as `.com` or `.uk`
Subdomain	A name under a domain, such as `api.example.com`
Apex domain	The bare registered domain without a subdomain, such as `example.com`
Stub resolver	Minimal DNS client in the OS that asks a recursive resolver
Recursive resolver	DNS server that finds the full answer for clients and caches it
Root name server	Top of the DNS tree, refers resolvers to TLD servers
TLD name server	Refers resolvers to a domain's authoritative servers
Authoritative name server	Server holding the official records for a domain
Zone	Set of DNS records one authoritative server is responsible for
Recursive vs iterative query	"Give me the final answer" vs "point me to who knows"
A / AAAA record	Name to IPv4 / IPv6 address
CNAME record	Alias from one name to another name
MX record	Mail servers for a domain, with priorities
NS record	Authoritative name servers for a domain
TXT record	Free-text record used for verification and email policy

Term	Meaning in one line
SOA, SRV, PTR, CAA	Zone admin data, service location, reverse lookup, allowed certificate issuers
TTL (DNS)	Seconds a DNS answer may be cached
Round-robin DNS	Returning several IPs in rotating order to spread load
GeoDNS	Answering DNS queries differently by the user's location
Latency-based routing	DNS steering to the region with the lowest measured latency
EDNS Client Subnet	DNS extension passing part of the user's IP for better geo answers
OSI model	Seven-layer reference model for networking
TCP/IP model	Four-layer model the internet actually uses
L3 / L4 / L7	Network (IP), transport (TCP/UDP, ports), application (HTTP) layers
Encapsulation	Each layer wrapping data with its own header
MAC address	Hardware address of a network card used on the local link
TCP	Connection-based, reliable, ordered byte-stream transport
UDP	Connectionless, unreliable, unordered datagram transport
Datagram	Self-contained UDP message
Three-way handshake	SYN, SYN-ACK, ACK exchange that opens a TCP connection
RTT	Round-trip time for a message to go and its reply to return
Sequence number	Counter TCP uses to order bytes and detect loss
ACK	Acknowledgement that data was received
Retransmission	Resending data whose acknowledgement did not arrive
Flow control	Receiver limiting how fast the sender sends (receive window)
Congestion control	Sender slowing down to avoid overloading the network
Slow start	TCP ramp-up that grows the sending rate each round trip
CUBIC / BBR	Common TCP congestion-control algorithms
TIME_WAIT	Short wait state after closing a TCP connection
Head-of-line blocking	One delayed item holding up everything queued behind it
QUIC	Encrypted, multi-stream, reliable transport over UDP
0-RTT	Sending data in the very first packet when resuming a connection
Connection migration	QUIC keeping a connection alive across network changes
Connection ID	QUIC identifier for a connection independent of IPs and ports
HTTP	Stateless request–response protocol of the web
HTTP method	Verb such as GET, POST, PUT, PATCH, DELETE
Safe method	Method that does not change server state
Idempotent	Repeating the operation leaves the same result as doing it once
Idempotency key	Client-supplied ID letting a server detect and ignore retries
Status code	Three-digit result code (2xx success, 4xx client error, 5xx server error)
Header	Key–value metadata on a request or response

Term	Meaning in one line
Cache-Control	Header telling caches whether and how long to store a response
ETag	Version tag of a resource, used to answer 304 Not Modified
X-Forwarded-For	Header carrying the original client IP through proxies
Stateless	Each request carries all needed context, server keeps no memory between them
Cookie	Small value the browser stores and sends back on each request to a site
Session	Server-side record of a logged-in user, referenced by a cookie or token
Keep-alive	Reusing one TCP connection for many HTTP requests
HTTP/1.1	Text protocol, one request at a time per connection
HTTP/2	Binary protocol multiplexing many streams over one TCP connection
HTTP/3	HTTP over QUIC, removing TCP head-of-line blocking
Multiplexing	Interleaving many independent streams over one connection
HPACK / QPACK	Header compression for HTTP/2 / HTTP/3
Alt-Svc	Header advertising that a server also speaks HTTP/3
HTTPS	HTTP inside a TLS-encrypted connection
TLS / SSL	Protocol for encrypted, authenticated connections (SSL is the old name)
Encryption in transit	Protecting data while it moves over the network
Certificate	Signed file binding a domain name to a public key
Certificate Authority	Trusted organisation that signs certificates
Chain of trust	Certificate signed by intermediate, signed by a root the browser trusts
Public-key cryptography	Key pair where the public key verifies or encrypts for the private key
Symmetric encryption	One shared key both encrypts and decrypts, fast
Diffie–Hellman	Method for two sides to agree on a secret key without sending it
Forward secrecy	Stolen long-term keys cannot decrypt past sessions
Session resumption	Reusing earlier TLS secrets to skip handshake work
SNI	Host name sent in the TLS ClientHello so one IP can serve many sites
mTLS	Mutual TLS where both client and server present certificates
API	Defined set of operations a service offers to other programs
REST	API style of resources (URLs) manipulated with HTTP verbs
Resource	A noun the API exposes, addressed by a URL
RPC	Calling a function on another machine as if it were local
gRPC	Google's RPC framework over HTTP/2 using Protobuf
Protocol Buffers	Compact binary serialisation format with a schema
Streaming RPC	gRPC call where client, server or both send a stream of messages
GraphQL	Query language letting clients request exactly the fields they need
Schema (GraphQL)	Typed description of all data and operations an API offers
Resolver	Server function that fetches one GraphQL field

Term	Meaning in one line
Mutation / subscription	GraphQL write / live-update operation
Over-fetching / under-fetching	Getting more data than needed / needing several calls for one screen
N+1 query problem	One query for a list plus one extra query per item
Short polling	Client repeatedly asking the server for updates on a timer
Long polling	Server holding a request open until data is available
WebSocket	Persistent two-way message channel upgraded from HTTP
Server-Sent Events	One-way server-to-client event stream over HTTP
Webhook	HTTP callback a service sends to your URL when an event occurs
Heartbeat (ping/pong)	Periodic small message keeping a connection alive and detecting failure
API versioning	Running old and new API contracts side by side for breaking changes
Offset pagination	Paging with limit and offset, simple but slow and unstable deep in a list
Cursor pagination	Paging from an opaque marker of the last item seen, fast and stable
Rate-limit headers	Headers telling clients their quota, remaining calls and reset time
429 Too Many Requests	Status code for a client that exceeded its rate limit
Retry-After	Header telling the client how long to wait before retrying
OpenAPI	Standard format for describing HTTP APIs
Proxy	Middleman that forwards requests on someone's behalf
Forward proxy	Proxy acting for clients toward the internet
Reverse proxy	Proxy acting for servers, receiving client traffic in front of them
API gateway	Reverse proxy handling auth, rate limits and routing for APIs
BFF	Backend for Frontend, a gateway tailored to one client type
Load balancer	Component spreading traffic across healthy servers
Pool / target group	The set of backend servers behind a load balancer
Virtual IP (VIP)	Address owned by a service rather than one machine
L4 load balancer	Balances TCP/UDP connections without reading content
L7 load balancer	Parses HTTP and routes or balances per request
Hardware load balancer	Dedicated appliance such as F5 BIG-IP
Software load balancer	LB program on ordinary servers such as NGINX, HAProxy, Envoy
Cloud load balancer	Provider-managed LB service such as AWS ALB or NLB
GSLB	Global server load balancing across regions or data centres
Client-side load balancing	Each client picks a backend from a list of healthy instances
Round robin	Send requests to servers in turn
Weighted round robin	Round robin where bigger servers get proportionally more
Least connections	Send to the server with the fewest active connections
Least response time	Send to the server answering fastest recently
EWMA	Exponentially weighted moving average, a smoothed recent value

Term	Meaning in one line
IP hash	Choose a server by hashing the client IP
Consistent hashing	Hash ring where adding or removing a node moves only about 1/N of keys
Virtual nodes	Several ring positions per server for even spread
Random (LB)	Pick a backend at random
Power of two choices	Pick two random backends and use the less loaded one
Herding	Many balancers sending traffic to the same seemingly best server at once
Canary release	Sending a small share of traffic to a new version first
Health check	Test that decides whether a backend should receive traffic
Active health check	LB probes backends on a schedule
Passive health check	LB ejects backends based on errors in real traffic (outlier detection)
Liveness vs readiness	"Process is running" vs "ready to serve traffic"
Fail open	Sending traffic to all backends when all appear unhealthy
Sticky sessions	Routing one user's requests to the same backend
TLS termination	Decrypting HTTPS at the load balancer or proxy
TLS passthrough	LB forwards encrypted traffic, backend decrypts
TLS re-encryption	LB decrypts, inspects, then encrypts again to the backend
Connection draining	Stop new traffic to a server but let in-flight work finish
Deregistration delay	AWS name for the connection-draining timeout
Active–passive	One node serves, a standby takes over on failure
Active–active	All nodes serve traffic simultaneously
VRRP / keepalived	Protocol and tool that move a virtual IP to a standby node
ECMP	Routers spreading flows across several equal-cost paths or machines
Direct server return	Backend replies straight to the client, bypassing the LB
PROXY protocol	Header an L4 proxy prepends to pass the original client address
CDN	Global network of edge caches serving content near users
Origin	Your server or storage that holds the master copy of content
Edge server	CDN cache server close to users
PoP	CDN site in a city containing many edge servers
Cache hit / miss	Content served from cache / fetched from upstream
Cache hit ratio	Hits divided by total requests
Cache key	Values (host, path, some headers) identifying a cached object
Pull CDN	CDN fetching content from origin on first request
Push CDN	You upload content to the CDN in advance
Purge / invalidation	Removing content from CDN caches before its TTL ends
Cache busting	Changing a file's name per version so caches fetch the new one
Origin shield	Middle cache tier that collapses edge misses before the origin

Term	Meaning in one line
Edge computing	Running code on CDN edge servers
Unicast	One IP address belongs to one location
Anycast	Same IP announced from many locations, routed to the nearest
BGP	Protocol networks use to announce which IP ranges they can reach
Bandwidth	Data a link can carry per second
Bandwidth-delay product	Bandwidth times RTT, the data in flight needed to fill a link
Network partition	Network failure splitting healthy nodes into groups that cannot talk
Split brain	Two sides of a partition each acting as leader
Fallacies of distributed computing	False assumptions such as "the network is reliable" and "latency is zero"

Part 3 — Data storage

Almost every system you will design exists to remember things: who the users are, what they bought, which messages they sent, which photos they posted. The program code can be thrown away and redeployed in minutes. The data cannot. If you lose it, the business may be over. This part explains, from zero, where data lives, how it is organised, how it is kept safe when machines crash, and how it is spread over many machines once one is no longer enough.

Read it in order. Each section uses words defined in the sections before it. Every term is also collected in the glossary at the end of this part.

What a database is

What it is

A **database** is a program whose job is to store data, keep it safe, and let other programs find it again quickly. The program you talk to is properly called a **database management system (DBMS)**. People say "database" for both the program and the data it holds, and so will we.

> **Analogy.** A database is like a well-run library. Books (data) arrive and are shelved in an agreed place. A catalogue (an index) lets you find a book without walking every aisle. A librarian (the DBMS) makes sure two people cannot check out the same copy at the same moment, and that a book is not lost if the lights go out halfway through shelving it.

Why not just write data to a plain file? You can, for a tiny program. But as soon as you have many users at once, plain files give you none of these:

- **Fast lookup.** Finding one customer among 50 million by reading the whole file takes seconds. A database index finds it in well under a millisecond.
- **Safe concurrent access.** Two web servers writing to the same file at the same moment can corrupt it. A database coordinates them.
- **Crash safety.** If the power fails halfway through a write, a database guarantees that the write either fully happened or did not happen at all.
- **A query language.** Instead of writing a loop for every question, you ask "give me all orders over $100 from last week" and the database works out how.

Why it matters

In a typical web application, the app servers are **stateless**: they keep nothing important in their own memory between requests, so you can add or remove them freely. All the important **state** (stored facts that must survive) lives in the database. That makes the database the hardest part to scale, the

slowest part to change, and the most expensive part to get wrong. In interviews, the data model and the choice of database are usually where most of the deep questions land.

How it works

At a high level every database does the same few things when your program sends it a request:

1. **Parse** the request (for example a SQL statement) and check it is valid.
2. **Plan** the cheapest way to answer it, such as "use the index on `email`" instead of "read every row". The part that does this is the **query planner** (or optimizer).
3. **Execute** the plan, reading pages of data from memory if they are already there (the **buffer cache**) or from disk if not.
4. For writes, **log** the change to a durable file first, then apply it (explained in the Durability section).
5. **Return** the result to the caller over the network.

Two words you will see everywhere: **read** means fetching data without changing it, and **write** means inserting, updating or deleting data. Most consumer apps read far more than they write; a ratio of 10 reads to 1 write, or even 100 to 1, is common for social feeds and product catalogues.

TL;DR

A database is a program that stores data safely, finds it quickly, and coordinates many users at once. It holds the state that the rest of the system can afford to forget.

Relational databases and SQL

What it is

A **relational database** stores data in **tables**. A table looks like a spreadsheet:

- Each **row** (also called a record or tuple) is one thing, such as one user.
- Each **column** (also called a field or attribute) is one property of that thing, such as `email`.
- The **schema** is the formal description of the tables: their names, their columns, and each column's **data type** (integer, text, date and so on). The database refuses data that does not fit the schema.

The word "relational" comes from mathematics (a table is a "relation"), not from "relationships", although tables do relate to each other through keys.


You talk to a relational database with **SQL (Structured Query Language)**, a language for describing *what* data you want rather than *how* to fetch it. Well-known relational databases include PostgreSQL, MySQL, MariaDB, Oracle Database, Microsoft SQL Server and SQLite. Cloud versions include Amazon RDS and Aurora, Google Cloud SQL and Azure SQL Database.

> **Analogy.** Think of a school office with filing cabinets. One cabinet holds a card per student. Another holds a card per class enrolment. Each enrolment card does not copy the student's address; it just writes the student's ID number, and you look the rest up in the student cabinet.

How it works

Keys tie the tables together:

- A **primary key** is a column (or set of columns) whose value is unique for every row and never empty. It is the row's identity. Example: `users.id`.
- A **foreign key** is a column in one table that holds the primary key of a row in another table. Example: `orders.user_id` points to `users.id`. The database can enforce that the referenced row exists (this is called **referential integrity**), so you cannot create an order for a user who does not exist.
- A **unique constraint** says that no two rows may share a value, for example no two users with the same `email`.



A **join** combines rows from two tables that match on a key. Here is a short query that lists each order with the buyer's name:

```
SELECT o.id, u.name, o.total
FROM orders o
JOIN users u ON u.id = o.user_id
WHERE o.created_at > '2026-01-01'
ORDER BY o.total DESC
LIMIT 10;
```

The main kinds of join are: **inner join** (only rows that match on both sides), **left join** (every row from the left table, with empty values where the right side has no match), **right join** (the mirror image) and **full outer join** (every row from both sides).

SQL statements fall into a few groups. `SELECT` reads. `INSERT`, `UPDATE` and `DELETE` change rows. `CREATE TABLE`, `ALTER TABLE` and `DROP TABLE` change the schema; this kind of statement is called **DDL (data definition language)**.

Why it matters

Relational databases are the default choice for most applications, and have been for about 50 years, because they give you:

- A **flexible query language**: you can ask questions you did not plan for when you designed the tables.
- **Strong guarantees** (transactions and ACID, next section) that protect money, inventory and anything else that must add up.
- **Enforced structure**: bad data is rejected at the door.
- **Mature tools**: backups, monitoring, replication and decades of operational knowledge.

Trade-offs

- **Schema changes take care.** Adding a column to a 2-billion-row table can lock it or take hours unless you use online migration tools (for example `gh-ost` or `pt-online-schema-change` for MySQL).
- **Scaling writes past one machine is hard.** A classic relational database is built around one main server. Spreading it across many machines (sharding, covered later) is possible but you lose cross-machine joins and transactions unless you use a distributed SQL database such as Google Spanner, CockroachDB, YugabyteDB or TiDB.
- **Joins get expensive** when the tables are huge and the join cannot use an index.

Common mistakes

- Choosing a NoSQL database "for scale" when the data is a few hundred gigabytes and fits comfortably in one PostgreSQL server. A single modern server with 64 cores, 512 GB of memory and fast SSDs can handle tens of thousands of simple transactions per second.
- Storing a list as a comma-separated string inside one column. It cannot be indexed or joined properly; use a separate table.
- Using a natural value such as an email address as a primary key. Emails change; IDs should not.

Real-world examples

Shopify, GitHub and Basecamp run large parts of their products on MySQL. Instagram began on PostgreSQL and sharded it as it grew. Stack Overflow is well known for running one of the web's busiest sites on a handful of SQL Server machines.

TL;DR

A relational database stores data in tables with a fixed schema, links them with primary and foreign keys, and lets you combine them with joins in SQL. It is the safe default for most systems.

Transactions and ACID

What it is


A **transaction** is a group of reads and writes that the database treats as one unit: either all of them take effect, or none do. You start one with `BEGIN`, and finish with `COMMIT` (make it permanent) or `ROLLBACK` (throw it all away).

> **Analogy.** Moving money between two bank accounts is two steps: take $100 from Alice, add $100 to Bob. If the system crashes between the steps, $100 vanishes. A transaction is like a sealed envelope: the bank only opens and acts on it when both instructions are inside, and if anything goes wrong the whole envelope is discarded.

```
BEGIN;
UPDATE accounts SET balance = balance - 100 WHERE id = 'alice';
UPDATE accounts SET balance = balance + 100 WHERE id = 'bob';
COMMIT;
```

ACID is the name for the four promises a transactional database makes:

- **A — Atomicity.** All or nothing. If any step fails, or the server crashes before `COMMIT`, every change in the transaction is undone. "Atomic" here means "cannot be split", not anything to do with speed or concurrency.
- **C — Consistency.** The transaction moves the data from one valid state to another valid state, where "valid" means it obeys the rules you declared: constraints, foreign keys, "balance must not go below zero" checks. Note that this C is mostly the application's job (you define the rules); the database only enforces the ones you tell it about. It is a different meaning from the "C" in the CAP theorem (Part 4).
- **I — Isolation.** Transactions running at the same time do not see each other's half-finished work. Ideally the result is the same as if they had run one after another. In practice databases offer several weaker **isolation levels** for speed (next section).
- **D — Durability.** Once the database says "committed", the data survives a crash or power cut. This is done by writing the change to a log on disk and forcing it to the physical device before replying (see the Durability section).



Why it matters

Without transactions, every piece of application code would have to handle "what if we crash halfway?" and "what if someone else changed this row while I was reading it?". Those bugs are rare, hard to reproduce and often cost real money: double-charged customers, oversold concert tickets, negative stock.

Trade-offs

Stronger guarantees cost speed. Isolation needs locks or version tracking, and durability needs a disk flush on every commit (often 0.1–2 ms on an SSD, more on a spinning disk or a network disk). Spreading a transaction across several machines (a **distributed transaction**, Part 4) is far slower again, because the machines must agree over the network.

Common mistakes

- Holding a transaction open while calling a slow external service (for example a payment API). The transaction keeps its locks the whole time and blocks other users. Do the external call outside the transaction.
- Assuming that a database labelled "ACID" gives you full isolation by default. Most do not (see next section).

In the interview

Q: What does ACID stand for and which letter is the database's responsibility versus the application's?

A: Atomicity, Consistency, Isolation, Durability. Atomicity, isolation and durability are mechanisms the database provides. Consistency is mostly a property of the application's rules; the database helps by enforcing the constraints you declare.

Q: Why not use transactions for everything across services?

A: A transaction that spans several databases needs a coordination protocol such as two-phase commit, which is slow and blocks if the coordinator fails. Across services people usually use sagas and

idempotent operations instead (Part 4).

TL;DR

A transaction groups several operations so they all succeed or all fail. ACID means all-or-nothing, rules respected, no interference, and nothing lost after commit.

Isolation levels and anomalies

What it is

Concurrency means several transactions running at overlapping times. When they touch the same data, strange results called **anomalies** (or race conditions) can appear. An **isolation level** is a setting that chooses which anomalies the database prevents. Stronger levels prevent more but run slower or abort more transactions.

> **Analogy.** Imagine two people editing the same shared shopping list on paper. If one reads the list while the other is halfway through crossing items out, they see a messy in-between state. Isolation levels are house rules about when you are allowed to read or write the list while someone else is using it.

Types

The anomalies, from simplest to subtlest:

- **Dirty read.** Transaction A reads a value that transaction B has written but not yet committed. If B then rolls back, A has acted on data that never officially existed.
- **Dirty write.** A overwrites B's uncommitted write. Almost every database prevents this at every level.
- **Non-repeatable read (read skew).** A reads a row, B updates and commits that row, A reads it again and gets a different value within the same transaction.
- **Phantom read.** A runs a query such as "all bookings for room 7 on Friday" and gets 2 rows. B inserts a new matching booking and commits. A runs the same query again and now sees 3 rows. The new row is the "phantom".
- **Lost update.** A and B both read a counter as 10, both add 1, both write 11. One increment is lost; the answer should be 12.
- **Write skew.** A and B each read the same set of rows, each decide something is safe based on what they read, and each write to a *different* row. Classic example: a hospital rule says at least one doctor must be on call. Two doctors on call both click "go off call" at the same moment. Each transaction sees "two doctors on call, so it is fine for me to leave" and each updates only its own row. Result: zero doctors on call. No single row was written twice, so simple row locks do not catch it.

The standard isolation levels (defined in the SQL standard), weakest to strongest:

Level	Dirty read	Non-repeatable read	Phantom read
Read uncommitted	Possible	Possible	Possible
Read committed	Prevented	Possible	Possible
Repeatable read	Prevented	Prevented	Possible (per standard)
Serializable	Prevented	Prevented	Prevented

Snapshot isolation is a widely used level that is not in the original standard. Each transaction reads from a consistent **snapshot**: a frozen picture of the database as of the moment the transaction started. It prevents dirty reads, non-repeatable reads and most phantoms, but it still allows write skew. It is usually built with **MVCC (multi-version concurrency control)**: instead of overwriting a row, the database keeps several versions of it, each stamped with the transaction that created it, so readers can see the

old version while a writer prepares a new one. The practical pay-off: a long report and a busy stream of updates can run side by side without either waiting on the other's locks.

Serializable means the end result is the same as if the transactions had run one at a time in some order. It prevents every anomaly above, including write skew. Databases achieve it by literally running one at a time (Redis, VoltDB), by **two-phase locking** (readers and writers take locks and hold them until commit), or by **serializable snapshot isolation (SSI)**, which runs optimistically and aborts a transaction if a dangerous pattern is detected (PostgreSQL does this).

How it works

Defaults in popular databases (worth knowing because they surprise people):

- **PostgreSQL**: default is *read committed*. Its *repeatable read* is actually snapshot isolation. *Serializable* uses SSI.
- **MySQL (InnoDB engine)**: default is *repeatable read*, implemented with MVCC snapshots plus some locking.
- **Oracle**: default is *read committed*; its level called "serializable" is really snapshot isolation.

Tools for preventing lost updates and write skew without going fully serializable:

1. **Atomic operations**: `UPDATE counters SET n = n + 1 WHERE id = 7` lets the database do the read-modify-write in one step.
2. **Explicit locks**: `SELECT ... FOR UPDATE` locks the rows you read so no one else can change them until you commit.
3. **Optimistic concurrency control**: store a `version` number in the row and write with `UPDATE ... SET ..., version = 6 WHERE id = 7 AND version = 5`. If zero rows were updated, someone else got there first, so retry. Also called **compare-and-set**.
4. **Constraints**: a unique index on `(room_id, date)` makes the database reject the second double-booking.

Trade-offs

Higher isolation means more aborted transactions (which the application must retry) or more waiting on locks, so lower throughput. Most web applications run at read committed or snapshot isolation and add explicit locks or constraints only where money or inventory is involved.

Common mistakes

- Doing "read the balance in the app, check it, then write the new balance" with no lock or version check. That is a lost-update bug waiting to happen.
- Believing "repeatable read" means the same thing in every database. It does not.

In the interview

Q: Two users try to buy the last ticket at the same time. How do you stop overselling?

A: Make the check and the decrement one atomic step, for example `UPDATE tickets SET left = left - 1 WHERE id = 9 AND left > 0` and check that one row was affected. Alternatives are `SELECT ... FOR UPDATE` or an optimistic version column with retry.

Q: What is write skew?

A: Two transactions read overlapping data, each makes a decision based on it, and each writes a different row, so together they break a rule that each alone respects. Snapshot isolation allows it; serializable isolation prevents it.

TL;DR

Isolation levels decide which concurrency bugs the database blocks. Know the anomalies (dirty read, non-repeatable read, phantom, lost update, write skew) and the fact that most databases default to something weaker than serializable.

NoSQL database families

What it is

NoSQL ("not only SQL") is an umbrella name for databases that do not use the relational table model as their main way of storing data. The term became popular around 2009, when companies such as Google (Bigtable), Amazon (Dynamo) and Facebook (Cassandra) published or open-sourced systems built to spread huge amounts of data across hundreds of cheap machines.

There is no single "NoSQL design". Each family is shaped around one access pattern and gives up something (often joins, flexible queries or strong transactions) to be very good at it.

> **Analogy.** A relational database is a general-purpose kitchen. NoSQL databases are specialist tools: a pizza oven, a deep fryer, an espresso machine. Each is far better than the general kitchen at one thing and poor at everything else.

Types

Key-value stores. The simplest model: a giant dictionary. You `put(key, value)` and `get(key)`. The database does not look inside the value. Extremely fast (often well under 1 ms) and easy to spread across machines, because each key can live anywhere. Weak at "find all items where X". Examples: Redis (in memory, also has lists, sets, sorted sets), Memcached (cache only), Amazon DynamoDB (key-value plus document features), etcd (small, strongly consistent configuration data), Riak. Typical use: sessions, caches, shopping carts, feature flags, rate-limit counters.

Document stores. Each record is a **document**, usually JSON or a binary form of it, which can hold nested fields and arrays. Documents in the same **collection** do not have to share a schema. You can query and index fields inside documents. Examples: MongoDB (maximum document size 16 MB), Couchbase, Amazon DocumentDB, Google Firestore. Good when each item is naturally a self-contained tree, such as a product with its variants or a blog post with its tags, and you usually read the whole thing at once.

```
{ "_id": "p42", "title": "Trail shoe", "price": 89.0,
  "sizes": [40, 41, 42], "seller": { "id": "s7", "name": "RunCo" } }
```


Wide-column stores (also called column-family stores). Data is grouped by a **partition key**; inside one partition, rows are sorted by a **clustering key**, and each row can have many columns, with different rows having different columns. You design one table per query. Built to absorb huge write volumes spread over many machines. Examples: Apache Cassandra, ScyllaDB, Apache HBase, Google Bigtable. Typical use: message histories, activity logs, IoT readings, anything that is "write a lot, read by key and time range". Note: "wide-column" is not the same as "columnar" (column-oriented analytics storage, covered later).

Graph databases. Data is stored as **nodes** (things, such as people) and **edges** (relationships, such as "follows"), both of which can carry properties. Following edges is cheap no matter how big the graph is, so questions like "friends of friends who live in Paris" are natural. Examples: Neo4j (query language Cypher), Amazon Neptune, JanusGraph. Typical use: social graphs, fraud rings, recommendations, knowledge graphs.

Time-series databases. Optimised for data points stamped with a time, arriving in time order, such as "CPU 73% at 10:00:05 on host 12". They compress such data heavily, make "average per minute over the last 6 hours" fast, and expire old data automatically. Examples: InfluxDB, TimescaleDB (a PostgreSQL extension), Prometheus (monitoring), QuestDB. Typical use: metrics, sensor data, stock ticks.

Search engines. Built around an **inverted index**: for each word, a list of the documents that contain it, like the index at the back of a book. To find documents containing "red" and "shoe", the engine intersects two lists instead of scanning everything. They also handle **tokenising** (splitting text into words), stemming ("running" matches "run"), typo tolerance and **relevance ranking** (which results are best, for example with the BM25 scoring formula). Examples: Elasticsearch and OpenSearch (both built on the Apache Lucene library), Apache Solr. Usually a *secondary* store: the source of truth is another database and data is copied into the search engine.

Vector databases. Store **embeddings**: lists of numbers (vectors), often hundreds or thousands long, produced by a machine-learning model so that similar items (images, sentences) get nearby vectors. The key query is **nearest-neighbour search**: "find the 10 vectors closest to this one". Doing that exactly over millions of vectors is slow, so they use **approximate nearest neighbour (ANN)** indexes such as HNSW (a layered graph you walk towards the target). Examples: Pinecone, Milvus, Weaviate, Qdrant, and the pgvector extension for PostgreSQL. Typical use: semantic search, recommendations, and retrieval-augmented generation (feeding relevant documents to a large language model).



Trade-offs

NoSQL databases usually give up some of: joins, ad hoc queries, multi-record transactions and enforced schemas. In return they gain easy horizontal scaling, high write throughput, flexible data shapes, or a very fast specialised query. The lines have blurred: MongoDB added multi-document transactions in version 4.0, DynamoDB has transactions, and PostgreSQL stores and indexes JSON with its `jsonb` type.

Real-world examples

Discord stores trillions of chat messages in a wide-column store (it moved from Cassandra to ScyllaDB around 2022–2023). Amazon's shopping cart was the motivating example in the 2007 Dynamo paper. LinkedIn and Uber have published about their graph and time-series systems. Most large sites run Elasticsearch or OpenSearch next to their main database for search.

TL;DR

NoSQL is a family of specialist databases: key-value, document, wide-column, graph, time-series, search and vector. Each trades general querying for speed or scale on one access pattern.

SQL vs NoSQL and BASE

What it is

Choosing between a relational (SQL) database and a NoSQL one is one of the most common interview decisions. There is no universal winner; the question is "which access patterns and guarantees does this data need?".

BASE is a tongue-in-cheek opposite of ACID used to describe many early NoSQL systems:

- **Basically Available**: the system keeps answering requests even when some machines fail, even if some answers are a bit old.
- **Soft state**: the data on different copies may be changing even without new writes, because copies are still catching up with each other.
- **Eventually consistent**: if writes stop, all copies will eventually agree. Until then, two readers may see different values.

> **Analogy.** ACID is a bank teller who will not hand over cash until the ledger is updated and checked. BASE is a busy coffee shop that takes your order immediately and sorts out the odd mix-up afterwards.

Trade-offs

Need	Lean towards
Money, inventory, bookings, strong correctness	SQL (or distributed SQL)
Complex queries, reporting, joins across many entities	SQL
Data shape changes often, nested records read whole	Document store
Massive write volume, simple key lookups, many regions	Wide-column or key-value
Relationship-heavy queries many hops deep	Graph
Team already knows PostgreSQL and data fits on one machine	SQL, almost always

A good interview answer names the access pattern first: "Users are read by ID and email, orders need transactions with payments, so I will use PostgreSQL. The activity feed is append-heavy and read by user and time, so I will use Cassandra for it." Using more than one database type in one system is normal and is called **polyglot persistence**.

Common mistakes

- "NoSQL is faster." It is faster for the pattern it was designed for, and often slower or impossible for others.
- "NoSQL has no schema." The schema still exists; it just lives in the application code instead of the database (often called **schema-on-read** versus SQL's **schema-on-write**).
- Picking eventual consistency for data where users would notice, such as an account balance.

In the interview

Q: When would you choose NoSQL over SQL?

A: When the access pattern is simple (mostly by key), the volume of data or writes is beyond one machine, the schema varies a lot, or you need multi-region writes with high availability, and you can live without joins and multi-row transactions.

TL;DR

Pick from the access pattern and the correctness needs, not from fashion. SQL is the default; reach for NoSQL when scale, shape or availability needs justify the lost features.

Indexes

What it is

An **index** is an extra data structure the database keeps next to a table so it can find rows by a column's value without reading the whole table. Without an index, finding `email = 'a@b.com'` means a **full table scan**: reading every row. With 100 million rows, that could take many seconds. With an index, it takes a few page reads and well under a millisecond if the pages are cached.

> **Analogy.** The index at the back of a textbook. To find "photosynthesis" you look it up alphabetically and jump to page 212, instead of reading all 600 pages.

How it works

The index stores the indexed column's values in a structure that is fast to search, each paired with a pointer to where the full row lives (or with the row's primary key). The database keeps it up to date on every insert, update and delete.


You create one like this:

```
CREATE INDEX idx_orders_user_created ON orders (user_id, created_at);
```

You can check whether a query uses an index with `EXPLAIN` (PostgreSQL, MySQL), which shows the plan the query planner chose.

Types


B-tree index. The default in almost every relational database. A **B-tree** is a balanced tree of fixed-size **pages** (blocks of storage, typically 4–16 KB: PostgreSQL uses 8 KB, MySQL InnoDB 16 KB). Each page holds hundreds of sorted keys and pointers to child pages. Because each page has so many children (the **branching factor**), the tree is very shallow: about 4 levels are enough for billions of rows. A lookup walks from the root to a **leaf** page, reading one page per level. Because keys are sorted, B-trees support both exact matches (`=`) and **range queries** (`BETWEEN`, `>`, `ORDER BY`). Updates are done in place, which means random writes on disk.



LSM-tree (log-structured merge tree). Used by write-heavy stores such as Cassandra, ScyllaDB, HBase, RocksDB and LevelDB. Writes never modify data in place:

1. A write is appended to a log on disk (for crash safety) and inserted into an in-memory sorted structure called the **memtable**.
2. When the memtable reaches a size limit (say 64 MB), it is written out as an immutable sorted file called an **SSTable (sorted string table)**. Writing a whole file in order is a fast **sequential write**.
3. Over time there are many SSTables. A background process called **compaction** merges them, keeping only the newest version of each key and dropping deleted ones (a deletion is first recorded as a marker called a **tombstone**).
4. A read checks the memtable, then the SSTables from newest to oldest. To avoid opening every file, each SSTable has a **Bloom filter** (a small structure that can say "this key is definitely not here", Part 4) and a sparse index.

LSM-trees give very high write throughput but reads can be slower, and compaction uses background disk and CPU. B-trees give predictable reads but slower writes. This is the classic **read amplification versus write amplification** trade-off: how many extra disk reads a lookup needs versus how many times each byte is rewritten.



Hash index. Keeps a hash map from each key to the location of its value. Exact lookups are O(1) (constant time), but it cannot do range queries or sorting, because hashing scatters neighbouring keys. Example: Bitcask, the storage engine used by Riak, keeps every key in an in-memory hash map pointing into append-only data files. PostgreSQL also offers a `HASH` index type.

Composite (multi-column) index. One index on several columns, such as `(user_id, created_at)`. It is sorted by the first column, then by the second within each first value, like a phone book sorted by last name then first name. It helps queries that filter on the **leftmost prefix**: `user_id`, or `user_id`

plus `created_at`. It does *not* help a query that filters only on `created_at`. Put the column you filter by equality first and the range or sort column after it.

Covering index. An index that contains every column a query needs, so the database can answer from the index alone without visiting the table (an **index-only scan**). PostgreSQL and SQL Server let you add extra non-key columns with `INCLUDE`.

Clustered vs non-clustered (secondary) index. In a **clustered index** the table rows themselves are stored in index order; a table can have only one. MySQL InnoDB always clusters rows by the primary key. A **secondary index** is any other index; it points back to the row (in InnoDB, by storing the primary key).

Other kinds you may meet: **unique index** (also enforces uniqueness), **partial index** (only rows matching a condition, such as `WHERE deleted = false`), **full-text index** (an inverted index inside a relational database), **GIN/GiST** indexes in PostgreSQL for JSON, arrays and geometry, and **geospatial indexes** (R-trees, geohashes).

Trade-offs

Indexes are not free:

- **Every write gets slower.** An insert into a table with 6 indexes means 7 structures to update.
- **They use space**, sometimes as much as the table itself.
- **They use memory.** Indexes are fast only when their hot pages fit in the buffer cache.
- **Low-selectivity columns** (few distinct values, such as a boolean `is_active`) rarely benefit, because the database would read most of the table anyway.

The rule of thumb: index the columns you filter, join and sort on in your frequent queries, and nothing else. Read-heavy tables can afford more indexes than write-heavy ones.

Common mistakes

- Wrapping an indexed column in a function, such as `WHERE LOWER(email) = ...`, which stops the plain index from being used (create an index on the expression instead).
- A leading wildcard `LIKE '%shoe'` cannot use a B-tree index; use full-text search.
- Creating an index on a big production table in a way that locks writes (PostgreSQL offers `CREATE INDEX CONCURRENTLY`).

In the interview

Q: Why do LSM-tree databases handle writes better than B-tree databases?

A: LSM-trees buffer writes in memory and flush them as large sequential files, never updating in place, while B-trees do random in-place page updates. The cost is slower reads and background compaction.

Q: You have an index on `(country, city)`. Does `WHERE city = 'Lyon'` use it?

A: Generally no, because the index is sorted by country first. It helps queries on `country` or on `country` and `city` together.

TL;DR

An index is a sorted (or hashed) lookup structure that turns a full scan into a few page reads. B-trees suit reads and ranges, LSM-trees suit heavy writes, and every index makes writes slower.

Normalization and denormalization

What it is

Normalization means organising tables so that each fact is stored in exactly one place. **Denormalization** means deliberately storing the same fact in more than one place so that reads are faster.

> **Analogy.** A normalized office keeps one master address book; everyone looks addresses up there. A denormalized office writes the customer's address on every invoice. Reading an invoice is faster (no lookup), but when the customer moves, every invoice copy must be updated or it goes stale.

How it works

Normalization is described by **normal forms**. A beginner needs three:

1. **First normal form (1NF)**: each cell holds one value, not a list. No `tags = "red,blue,green"`.
2. **Second normal form (2NF)**: every non-key column depends on the *whole* primary key, not part of it. In an `order_items(order_id, product_id, qty, product_title)` table, `product_title` depends only on `product_id`, so it belongs in `products`.
3. **Third normal form (3NF)**: non-key columns depend only on the key, not on other non-key columns. If `users` has `zip_code` and `city`, and the city follows from the zip code, the city belongs in a zip-code table.

A classic mnemonic, usually credited to William Kent (1983), sums up all three: every column should describe "the key, the whole key, and nothing but the key".

Normalization prevents **update anomalies**: if the product title is stored in 10,000 order rows and you rename the product, you must update 10,000 rows, and if one fails they disagree.

Denormalization techniques include: copying a column (store `author_name` on each post), storing a precomputed total (`comment_count` on a post instead of counting each time), storing a nested document with its children (a document database's natural style), and **materialized views** (a stored, periodically refreshed query result).

Trade-offs

	Normalized	Denormalized
Storage	Smaller	Larger (duplicates)
Reads	May need joins	Fewer or no joins, faster
Writes	One place to update	Many places to update
Risk	Slow joins at scale	Copies drift out of sync

Start normalized. Denormalize specific hot read paths once you measure a problem, and decide how the copies will be kept in sync (same transaction, a background job, or events). At large scale and in NoSQL stores without joins, denormalization is the norm: in Cassandra you often keep one table per query, each holding a copy of the data arranged for that query.

Common mistakes

- Denormalizing before there is a performance problem, and then spending months fixing drift bugs.
- Forgetting that a counter like `like_count` updated by many users at once needs an atomic increment.

TL;DR

Normalize so each fact lives once; denormalize selected data to make hot reads fast, accepting extra write work and the risk of stale copies.

Replication

What it is

Replication means keeping copies of the same data on several machines, each called a **replica** (or node). The copies are kept in sync by sending every change from one machine to the others.

> **Analogy.** A company keeps its master price list at head office and sends updated copies to every branch. Customers at any branch can read prices locally. If head office burns down, a branch copy can become the new master.

Why it matters


Replication gives you three things:

1. **Availability and fault tolerance.** If one machine dies, another copy can serve requests.
2. **Read scaling.** Spread read traffic over many copies. Ten replicas can serve roughly ten times the reads.
3. **Lower latency.** Put a copy near users: a replica in Frankfurt answers European readers in about 10–20 ms instead of the roughly 80–100 ms round trip to Virginia.

Remember what replication does *not* do: it does not help write throughput, because every copy must still apply every write. To scale writes you split the data (partitioning, next section). A useful rule: **copy for reads, split for writes**.

Types

Leader-follower (also called primary-replica, master-slave, or active-passive replication). One node, the **leader** (primary), accepts all writes. It records each change in its replication log and streams it to the **followers** (replicas, secondaries), which apply the changes in the same order. Clients may read from the leader or the followers. This is the default in PostgreSQL, MySQL, MongoDB replica sets, SQL Server and Redis.



Read replicas is the common name for followers used mainly to serve reads, for example Amazon RDS read replicas. They are ideal for read-heavy workloads such as product pages, reports and search indexing.

Multi-leader (multi-primary, active-active). Several nodes accept writes, usually one per data centre or region, and replicate to each other. Users in each region get fast local writes, and a region can keep working if it loses contact with the others. The hard part is **write conflicts**: two leaders change the same record at the same time. Ways to resolve them:


- **Last write wins (LWW)**: keep the write with the latest timestamp, silently dropping the other. Simple but loses data, and clocks on different machines disagree (Part 4).
- **Merge** the values with application logic, or ask the user.
- **CRDTs (conflict-free replicated data types)**: special data types, such as counters and sets, designed so that concurrent changes always merge to the same result.

Examples: MySQL and PostgreSQL with multi-primary tools, CouchDB, collaborative editors and offline-first mobile apps (each device is effectively a leader).

Leaderless. Any replica accepts reads and writes. A client (or a coordinator node) sends each write to several replicas at once and considers it successful when enough of them confirm. Reads also query several replicas and take the newest value. With N copies, writing to W of them and reading from R of them, choosing **R + W > N** means every read overlaps at least one up-to-date copy (this is a **quorum**, covered in Part 4). A common setting is N=3, W=2, R=2. Stale copies are fixed by **read repair** (the reader writes back the newest value to replicas that returned an old one), **anti-entropy** (a background process that compares replicas, often using Merkle trees) and **hinted handoff** (a healthy node temporarily holds writes meant for a down node and passes them on later). Examples: Amazon's original Dynamo, Apache Cassandra, ScyllaDB, Riak.

Synchronous vs asynchronous replication. This is about *when* the leader tells the client "done":

- **Synchronous**: the leader waits until a follower confirms it has the change. If the leader then dies, no committed data is lost. Cost: every write waits for a network round trip, and if the follower is down or slow, writes stall.
- **Asynchronous**: the leader replies as soon as its own write is durable and ships the change to followers in the background. Fast and unaffected by slow followers, but if the leader dies, the last few changes that had not reached any follower are lost.
- **Semi-synchronous**: a common middle ground. Wait for *one* follower (or a quorum) to confirm, and replicate to the rest asynchronously. MySQL has a semi-synchronous mode; PostgreSQL lets you list synchronous standbys.



How it works

Replication lag is how far behind the leader a follower is, usually milliseconds but sometimes seconds or minutes when a follower is overloaded or a huge transaction is being applied. Lag causes visible bugs:

- **Read-your-own-writes violation**: a user edits their profile, the page reloads from a lagging replica, and their change seems to have vanished. Fix: read the user's own data from the leader for a short time after they write, or track the write's position in the log and only read from a replica that has caught up to it.
- **Monotonic reads violation**: two refreshes hit different replicas and the second shows *older* data than the first, as if time went backwards. Fix: pin each user to one replica.

Failover is the process of promoting a follower to leader when the leader fails:

1. **Detect** the failure, usually because the leader misses **heartbeats** (regular "I am alive" messages) for a timeout such as 10–30 seconds.
2. **Choose** a new leader, ideally the follower with the most up-to-date data. This may be done by an election among replicas or by an external coordinator.
3. **Reconfigure**: point clients and the other followers at the new leader (via DNS, a proxy, or a service-discovery system).

Failover can be **automatic** (tools such as Patroni for PostgreSQL, Orchestrator for MySQL, or managed cloud databases that fail over in under a minute or two) or **manual** (a human decides).

Split brain is the nightmare case: two nodes both believe they are the leader and both accept writes, so the data diverges. It happens when the old leader was not dead, just cut off by a network problem, and comes back still thinking it is in charge. Defences: require a **majority (quorum)** of nodes to agree on who the leader is, so an isolated minority cannot elect one; **fencing**, which forcibly stops or blocks the old leader (sometimes called STONITH, "shoot the other node in the head"); and **fencing tokens**, increasing numbers that let storage reject writes from an out-of-date leader (Part 4).

Trade-offs

Style	Writes go to	Strength	Weakness
Leader-follower	One leader	Simple, no write conflicts	Leader limits writes, failover needed
Multi-leader	Several leaders	Local writes per region, survives region loss	Conflicts must be resolved
Leaderless	Any W replicas	No failover, high availability	Weaker consistency, more complex reads

Common mistakes

- Treating a replica as a backup. If someone runs `DELETE FROM users` by mistake, the delete replicates to every copy within milliseconds. You also need real backups (see Durability).
- Sending all reads to replicas without thinking about read-your-own-writes.
- Setting the failover timeout too short, so a brief network hiccup triggers a needless and risky failover.

Real-world examples

GitHub's October 2018 incident is a famous lesson: a network interruption of about 43 seconds between its US East Coast hub and data centre triggered an automatic MySQL failover to its West Coast data centre; some writes had reached only the old primary, and untangling the two sets of data left the site degraded for just over 24 hours. Amazon Aurora keeps six copies of each piece of data across three **availability zones** (separate data centres within one cloud region, two copies in each) and treats a write as durable after four of the six confirm; reads and repairs need three of the six.

In the interview

Q: Synchronous or asynchronous replication for a payments database?

A: At least one synchronous (or quorum) copy so a committed payment survives the loss of the leader, with further asynchronous replicas for reads and other regions. Fully synchronous to all copies would make every write as slow as the slowest replica.

Q: A user updates their bio and immediately sees the old one. Why, and how do you fix it?

A: The read went to a lagging replica. Route that user's reads of their own data to the leader for a short window after a write, or read from a replica only once it has applied the write's log position.

TL;DR

Replication keeps copies for availability, read scaling and locality. Know leader-follower, multi-leader and leaderless; sync versus async; replication lag; failover; and split brain.

Partitioning and sharding

What it is

Partitioning means splitting one large dataset into smaller pieces, called **partitions**. **Sharding** is partitioning where the pieces, called **shards**, live on *different machines*. In everyday speech the two words are often used interchangeably, but strictly, you can partition a table inside one database server (PostgreSQL's declarative partitioning splits a table by month on the same machine), whereas sharding always spreads the data across servers.

> **Analogy.** A library that outgrows its building opens branches: A–F books at the north branch, G–M at the east branch, and so on. Each branch handles only its share of visitors. A catalogue tells you which branch to go to.

Why it matters

Replication copies everything onto every node, so it cannot help when:

- The data is too big for one machine's disk or memory (say 50 TB).
- The *writes* per second are more than one machine can handle (say 200,000 writes per second).

Sharding divides both data and write load. With 10 shards, each holds roughly a tenth of the data and takes a tenth of the writes. In practice each shard is also replicated, so you get both: split for writes, copy for reads and safety.


Types

Horizontal vs vertical partitioning.

- **Horizontal partitioning** splits *rows*: users 1–1,000,000 in one partition, 1,000,001–2,000,000 in another. Every partition has the same columns. Sharding is horizontal partitioning across machines.
- **Vertical partitioning** splits *columns*: frequently read small columns (`id`, `name`, `avatar_url`) in one table, rarely read large ones (`bio`, `settings_json`) in another, joined by the same ID. It keeps hot data compact. Splitting whole tables or features onto different databases is related and is called federation (below).

Strategies for deciding which shard a row belongs to. The column used to decide is the **shard key** (also called partition key).

- **Range-based.** Each shard owns a continuous range of key values: A–F, G–M; or January, February. Range queries ("all orders from March") hit one or a few shards. Danger: uneven load. If the key is a timestamp, *all* new writes go to the newest shard. Used by HBase, Bigtable, MongoDB (ranged sharding) and CockroachDB, which split ranges automatically as they grow.
- **Hash-based.** Compute a hash of the key (a function that turns any input into a number that looks random) and use it to pick the shard, for example `shard = hash(user_id) mod 8`. Keys spread evenly, so load is balanced. Cost: neighbouring keys land on different shards, so range queries must ask every shard. Also, with plain `mod N`, changing N from 8 to 9 moves almost every key, which is why consistent hashing exists (next section).
- **Directory-based (lookup table).** A separate service stores a map from key (or key range) to shard. Fully flexible: you can move a single big customer to its own shard. Cost: the directory is an extra lookup on every request and must itself be highly available and cached.
- **Geo-based (geographic).** Shard by the user's region: European users on EU shards, US users on US shards. Lowers latency and helps with data-residency laws such as the EU's GDPR. Load is uneven if regions differ in size.



Where the routing happens. The application can compute the shard itself; a proxy or **router** can do it (Vitess for MySQL, `mongos` for MongoDB, Citus for PostgreSQL); or any node can accept the request and forward it (Cassandra).

Federation (functional partitioning). Instead of splitting one table, split the database *by feature*: a users database, a products database, an orders database, each on its own server. Each is smaller and gets its own share of traffic. You lose joins and transactions between them, and it only goes as far as the number of features. It is often a first step before true sharding, and it maps naturally onto microservices, each owning its database.

How it works

Choosing a shard key is the most important decision in sharding, because changing it later is very expensive. A good shard key:

1. **Has high cardinality** (many distinct values), so data can be split finely. `country` is poor (about 200 values, very uneven); `user_id` is good.
2. **Spreads load evenly**, both data size and traffic.
3. **Matches the main query**, so most requests touch a single shard. If you almost always look up "orders for a user", shard orders by `user_id`, so all of one user's orders sit together.
4. **Does not grow in one direction** if you use range sharding (avoid auto-increment IDs and timestamps as the range key).

Queries that include the shard key are **single-shard** and fast. Queries that do not must be sent to every shard and the results combined (**scatter-gather**), which is slower and gets worse as shards are added.

Hot spots and hot keys. A **hot spot** is a shard that gets far more load than the others. A **hot key** is a single key that causes it, such as a celebrity's account with 300 million followers, or one viral product during a flash sale. Even perfect hashing cannot split a single key. Fixes:

- **Key salting**: append a small random number to the hot key (`celebrity_42#0` to `celebrity_42#9`) to spread its writes over 10 shards, then read all 10 and combine.
- **Caching** the hot item's reads in front of the database.
- **Dedicated shards** for known whales (big customers), using a directory.
- **Write buffering**: collect increments in memory and apply them in batches.

Rebalancing (resharding). Over time you must add shards because data grows, or move data because some shards are hotter. Approaches:

- **Fixed number of logical partitions**: create many more partitions than machines from day one (say 1,024 partitions on 8 machines, 128 each). To add a machine, move whole partitions to it; keys never change partition. Used by Elasticsearch, Couchbase and Riak, and in spirit by many hand-rolled systems.
- **Dynamic splitting**: when a range partition grows past a size limit (by default 512 MB per range in CockroachDB, 128 MB per chunk in recent MongoDB versions, 10 GB per region in HBase), split it in two and move one half (HBase, MongoDB, CockroachDB).
- **Consistent hashing** (next section).

Rebalancing must move data while the system keeps serving traffic, usually by copying in the background, catching up on new writes, then switching the routing. Doing this automatically is convenient but risky; many teams keep a human in the loop.

Trade-offs

What you give up when you shard:

- **Cross-shard joins** become application code or scatter-gather.
- **Cross-shard transactions** need distributed transactions or sagas (Part 4).
- **Globally unique IDs** cannot come from one auto-increment counter; you need UUIDs or a scheme like Snowflake IDs (Part 4).
- **Secondary indexes** become harder: either each shard indexes its own rows (**local index**, queries must hit all shards) or a separate **global index** is itself sharded by the indexed value (reads are fast, writes must update another shard).
- **Operations** (backups, schema changes, monitoring) multiply by the number of shards.

So shard late. First optimize queries, add indexes, add caching, add read replicas, and scale up the machine. Shard when one primary truly cannot handle the writes or the data size.

Common mistakes

- Sharding by a timestamp with range partitioning, so today's shard takes every write.
- Choosing a shard key that does not appear in the main queries, making most reads scatter-gather.
- Using `hash mod N`, then discovering that adding one server moves nearly all data.
- Forgetting that a single hot key cannot be fixed by adding shards.

Real-world examples

Instagram sharded PostgreSQL into thousands of logical shards mapped onto fewer physical servers, so shards could be moved without changing keys. Notion split its single PostgreSQL database into 480 logical shards on 32 physical databases in 2021, then in 2023 spread the same 480 shards over 96 machines without changing any keys. YouTube created Vitess to shard MySQL; it is now used by Slack, GitHub and others. Pinterest shards MySQL by putting a shard ID inside every object ID.

In the interview

Q: How would you shard a chat application's messages table?

A: Shard by `conversation_id` (hashed), because messages are almost always read per conversation, so each read hits one shard; inside the shard, order by message time. Watch for hot conversations, such as huge group channels.

Q: What makes a good shard key?

A: High cardinality, even spread of data and traffic, present in most queries so they hit one shard, and not monotonically increasing when range-sharded.

TL;DR

Sharding splits rows across machines so data and writes scale. The shard key decides everything: pick one with many values, even load and alignment with your main queries, and plan for hot keys and rebalancing.

Consistent hashing and virtual nodes

What it is

Consistent hashing is a way of assigning keys to servers so that adding or removing a server moves only a small share of the keys, about 1/N of them with N servers, instead of almost all of them.


Why plain modulo fails. With `server = hash(key) mod 4`, a key whose hash is 10 goes to server 2. Add a fifth server and it becomes `10 mod 5 = 0`. In general about 80% of keys change servers when going from 4 to 5. For a cache, that is a sudden flood of misses; for a database, a huge data migration.

> **Analogy.** Picture a round clock face. Servers stand at a few positions around the rim. Each key is also placed on the rim, then walks clockwise until it meets a server: that server owns it. If a new server steps onto the rim, it only takes over the keys between itself and the previous server. Everyone else keeps their keys.

How it works

1. Imagine the output range of a hash function (for example 0 to 2^32 − 1) bent into a circle, the **hash ring**.
2. Hash each server's name to get its position on the ring.
3. Hash each key to get its position, then move clockwise to the first server. That server stores the key.
4. **Adding a server**: it lands at one point and takes over only the keys between its predecessor and itself. On average 1/N of all keys move.
5. **Removing a server**: its keys move to the next server clockwise; nothing else changes.

6. **Replication**: store each key on the first server it meets plus the next 2 distinct servers clockwise to keep 3 copies (Cassandra and Dynamo do this).



Virtual nodes (vnodes). With only a few servers, their random positions leave some with big arcs of the ring and some with small arcs, so load is uneven. Also, when a server leaves, *all* its load lands on one neighbour. The fix: give each physical server many positions on the ring, for example 100–256 **virtual nodes** each, by hashing "A-1", "A-2", ... "A-256". Now each server owns many small arcs scattered around the ring, so:

- Load evens out statistically.
- When a server leaves, its many small arcs are picked up by many different servers, spreading the extra load.
- A more powerful machine can be given more virtual nodes to take a bigger share.

Cassandra used 256 vnodes per node by default for years and lowered the default to 16 in version 4.0 with a smarter token-allocation algorithm.

Types

Other algorithms solve the same problem: **rendezvous hashing** (highest random weight: compute a score for each key-server pair and pick the highest), **jump consistent hash** (Google, very fast and memory-free, but servers can only be added or removed at the end), and **Maglev hashing** (Google's load balancer, which uses a lookup table for even spread).

Trade-offs

Consistent hashing minimises data movement and needs no central directory, but plain consistent hashing balances poorly without virtual nodes, and like any hashing it destroys key ordering, so range queries become scatter-gather.

Real-world examples

Amazon Dynamo (2007 paper), Apache Cassandra, ScyllaDB, Riak, Memcached client libraries (ketama), Discord's routing of users and guilds to servers, and many load balancers (for sticky routing, Part 2) use consistent hashing.

In the interview

Q: Why use consistent hashing instead of `hash mod N`?

A: With `mod N`, changing N remaps almost every key. With consistent hashing, adding or removing one of N servers moves only about 1/N of the keys.

Q: What problem do virtual nodes solve?

A: Uneven arcs and uneven load. Many positions per server spread each server's ownership in small pieces, smooth the load, and let a departing server's keys spread across many others.

TL;DR

Consistent hashing places servers and keys on a ring so a membership change moves only about 1/N of keys; virtual nodes make the spread even.

Storage types: block, file and object

What it is

Beneath every database and every uploaded photo is raw storage. Cloud providers sell it in three shapes, and picking the right one is a common design decision.

> **Analogy.** **Block storage** is an empty plot of land: you decide how to build on it. **File storage** is an office building with floors, rooms and labelled cabinets that several people can share. **Object storage** is a giant valet coat check: you hand over an item, get a ticket (the key), and later hand back the ticket to get the item. You cannot rearrange things inside the cloakroom; you can only check in, retrieve or throw away whole items.

Types

Block storage. The storage looks like a raw disk divided into fixed-size **blocks**, each with an address. The operating system puts a **file system** (such as ext4 or NTFS) on top, or a database manages the blocks directly. It is attached to one server at a time (usually), offers low latency (well under a millisecond for local NVMe SSDs, roughly one to a few milliseconds for network block storage) and lets you change a few bytes in the middle of a file. Measured in **IOPS** (input/output operations per second) and throughput. Examples: a laptop's SSD, Amazon EBS, Google Persistent Disk, Azure Managed Disks. Use for: database data files, virtual machine boot disks.

File storage. A shared file system with folders and files, accessed over the network by many servers at once using protocols such as **NFS** (Network File System, common on Linux) or **SMB** (common on Windows). Familiar to programs that expect files and paths. Examples: Amazon EFS, Azure Files, Google Filestore, a NAS (network-attached storage) box. Use for: shared content between servers, home directories, legacy applications.

Object storage. Stores **objects**: a blob of bytes plus metadata, addressed by a unique key inside a **bucket** (a top-level container). There are no real folders (a key like `photos/2026/cat.jpg` only looks like a path), and you cannot edit part of an object; you replace the whole thing. Accessed over HTTP with simple calls such as `PUT`, `GET` and `DELETE`. It scales to practically unlimited size, is the cheapest per gigabyte, and is extremely durable. Latency is higher, often tens of milliseconds for the first byte. Examples: Amazon S3, Google Cloud Storage, Azure Blob Storage, Cloudflare R2, and the open-source MinIO and Ceph.


A **blob** (binary large object) is any large chunk of unstructured binary data: an image, video, PDF or backup file. "Blob storage" is another name for object storage (Azure literally calls its service Blob Storage).

	Block	File	Object
Unit	Fixed-size block	File in folders	Whole object with key
Access	Attached disk	Network file protocol	HTTP API
Shared by many servers	Usually no	Yes	Yes
Edit part in place	Yes	Yes	No, replace whole
Typical use	Databases, VM disks	Shared files	Media, backups, data lakes

How it works

The standard pattern for user uploads (photos, videos, documents):

1. The client asks the app server for permission to upload.
2. The app server returns a **pre-signed URL**: a time-limited link that allows one upload to one key in the bucket.
3. The client uploads the file straight to object storage, so gigabytes never pass through your app servers.
4. The app server stores only the object's key and metadata (owner, size, type) in the database.
5. Downloads are served through a CDN (Part 2) in front of the bucket.



Trade-offs

Never store large files inside the relational database: it bloats backups, wastes the buffer cache and makes replication slow. Store the file in object storage and the pointer in the database.

Real-world examples

Amazon S3 is designed for 99.999999999% ("eleven nines") durability of objects, stores each object across at least three availability zones in its standard storage classes, allows single objects up to 50 TB (raised from 5 TB in December 2025), and has offered strong read-after-write consistency since December 2020. Netflix, Dropbox (which later moved much of its data to its own Magic Pocket system), and almost every photo-sharing app store media in object storage.

TL;DR

Block storage is a raw fast disk for one server, file storage is a shared folder tree, and object storage is cheap, huge, durable key-to-blob storage over HTTP. Put media in object storage and keep only its key in the database.

OLTP vs OLAP, row vs column storage, lakes and warehouses

What it is

Databases serve two very different kinds of work:

- **OLTP (online transaction processing)**: the everyday work of an application. Many small, fast reads and writes that each touch a few rows: "load user 42", "insert this order". Latency matters (milliseconds), and thousands run per second. PostgreSQL, MySQL and DynamoDB are OLTP systems.

- **OLAP (online analytical processing)**: analysis and reporting. Few, big queries that scan millions or billions of rows but only a few columns: "total revenue per country per month for the last three years". Each query may take seconds. Analysts and dashboards run them.


> **Analogy.** OLTP is the checkout counter at a supermarket: fast, one customer at a time. OLAP is the head office accountant going through a year of receipts to find trends.

Running heavy OLAP queries on the OLTP database is a classic mistake: one big report can slow down every customer's checkout. So companies copy the data into separate analytical systems.

Types

Row-oriented vs column-oriented storage.

- A **row store** keeps all the columns of one row together on disk. Great for OLTP: "fetch user 42" reads one place and gets everything.
- A **column store** (columnar storage) keeps all values of one column together: every `country` value in one file, every `amount` value in another. Great for OLAP: "sum of `amount` by `country`" reads just those two columns and skips the other 50. Values in one column are similar, so they compress very well (often several times smaller), and the CPU can process them in batches.



Columnar databases and formats: ClickHouse, Apache Druid, Apache Pinot, Amazon Redshift, Google BigQuery, Snowflake, DuckDB; and the file formats **Apache Parquet** and **ORC**.

Data warehouse. A central analytical database that holds cleaned, structured data from many sources (orders, payments, marketing), organised for reporting. Data is usually loaded on a schedule, and the schema is defined in advance (schema-on-write). Often modelled as a **star schema**: a big **fact table** of events (each sale) surrounded by **dimension tables** (product, customer, date). Examples: Snowflake, BigQuery, Amazon Redshift, Azure Synapse.

Data lake. A huge, cheap store of raw data in any format (logs, JSON, CSV, images, Parquet files), usually in object storage such as S3. You store first and decide structure when you read (schema-on-read). Flexible and cheap, but without discipline it becomes a "data swamp" nobody can trust. Query engines such as Apache Spark, Trino/Presto and Amazon Athena read it directly.

Lakehouse. A newer middle ground: data lake files plus a table format that adds transactions, schemas and versioning on top, such as Delta Lake, Apache Iceberg and Apache Hudi.

ETL vs ELT. Data moves from OLTP systems into analytics through a **pipeline**. **ETL (extract, transform, load)** cleans and reshapes the data before loading it into the warehouse. **ELT (extract, load, transform)** loads raw data first and transforms it inside the warehouse, which became popular as cloud warehouses got cheap and powerful. **Change data capture (CDC)** streams every change from the OLTP database's log (for example with Debezium into Kafka) so analytics stay minutes or seconds behind instead of a day.

Trade-offs

	OLTP	OLAP
Query shape	Few rows, by key	Many rows, few columns
Users	Customers via the app	Analysts, dashboards
Storage layout	Row-oriented	Column-oriented
Latency target	Milliseconds	Seconds to minutes
Examples	PostgreSQL, MySQL	Snowflake, BigQuery, ClickHouse

In the interview

Q: Why are column stores faster for analytics?

A: An analytic query reads a few columns across many rows. A column store reads only those columns from disk, compresses them well, and processes them in tight batches, so it moves far less data than a row store.

Q: Data lake or data warehouse?

A: A warehouse holds curated, structured data with a fixed schema for reliable reporting; a lake holds raw data of any type cheaply for exploration and machine learning. Many companies have both, or a lakehouse.

TL;DR

OLTP is many small transactional queries on row stores; OLAP is big analytical scans on column stores. Warehouses hold curated structured data, lakes hold raw data cheaply, and pipelines (ETL, ELT, CDC) move data between them.

Durability: WAL, fsync, backups and recovery

What it is

Durability means that once data is saved (committed), it stays saved, even through crashes, power cuts, disk failures and human mistakes. Different tools protect against different threats:

Threat	Protection
Process crash or power cut	Write-ahead log plus fsync
One disk or machine dies	Replication, RAID
Whole data centre lost	Copies in another zone or region
Bug or human deletes data	Backups and point-in-time recovery
Ransomware or account takeover	Immutable, separate-account backups


> **Analogy.** A careful accountant writes each transaction in a pen-and-ink journal *before* updating the neat ledger. If the ledger is ruined halfway through an update, the journal shows exactly what to redo. And every night she photocopies the books and stores the copy in another building.

How it works

Write-ahead log (WAL). Updating the real data files in place is slow (random writes) and dangerous (a crash midway leaves a half-written page). So the database first appends a description of each change to a sequential log file, the **write-ahead log** (also called a redo log in MySQL InnoDB, or a commit log in Cassandra). The rule is: *log first, then data*.

1. A transaction changes some rows in memory.

2. On `COMMIT`, the database appends the changes and a commit record to the WAL.
3. It forces the WAL to physical storage with **fsync**, a system call that tells the operating system "really write this to the device now, do not just keep it in your memory buffer".
4. Only then does it tell the client "committed".
5. Later, a background process writes the changed pages to the data files. A **checkpoint** records how far the data files are up to date, so old WAL can be recycled.
6. After a crash, the database replays the WAL from the last checkpoint, redoing committed changes and discarding uncommitted ones.



The same log is reused for replication (followers replay the leader's WAL stream) and for change data capture.

Why fsync matters. Operating systems keep written data in a memory **page cache** and flush it to disk later, for speed. Without fsync, a power cut can lose writes that the program believed were saved. fsync is slow-ish (from tens of microseconds on enterprise SSDs with power-loss protection to several milliseconds on cheaper or network disks), so databases batch many commits into one fsync (**group commit**). Some systems let you trade safety for speed: PostgreSQL's `synchronous_commit = off` and MySQL's `innodb_flush_log_at_trx_commit = 2` can lose the last moment of commits on a crash. Redis's append-only file defaults to fsync once per second, so up to about one second of writes can be lost.

RAID (redundant array of independent disks) combines several disks so the failure of one does not lose data: RAID 1 mirrors two disks, RAID 5/6 store parity, RAID 10 stripes across mirrored pairs. It protects against disk failure only.

Backups. A **backup** is a copy of the data stored separately, kept for days or months, so you can recover from things replication would happily copy, such as an accidental `DROP TABLE`.

- **Full backup**: a complete copy. Simple, slow and large.
- **Incremental backup**: only what changed since the last backup. Small and fast, but restoring needs the chain of increments.
- **Logical backup**: the data exported as SQL statements or rows (`pg_dump`, `mysqldump`). Portable but slow for big databases.
- **Physical backup**: a copy of the raw data files (`pg_basebackup`, Percona XtraBackup).
- **Snapshot**: a point-in-time image of a disk or volume (for example an EBS snapshot), usually taken in seconds using copy-on-write, where only blocks changed after the snapshot need extra space.

Point-in-time recovery (PITR) lets you restore to any moment, say 14:31:07, just before a bad deploy deleted data. It works by restoring the last full backup and then replaying archived WAL up to the chosen moment. Managed databases such as Amazon RDS offer it with a retention window of up to 35 days.

A widely used rule is **3-2-1**: keep 3 copies of the data, on 2 different kinds of media, with 1 copy off-site (today often: another region or another cloud account).

Test your restores. Until you have actually rebuilt a database from a backup, you do not know that the backup works. Measure how long a restore takes, because that number feeds your recovery time objective (RTO, Part 5).

Common mistakes

- Keeping backups in the same account or region as production, where one compromised credential or one regional outage takes both.
- Never testing restores. In January 2017 GitLab accidentally deleted a production database directory and found that several of its backup and replication mechanisms had not been working; it restored from a copy about six hours old and lost roughly six hours of changes.
- Disabling fsync for benchmarks and forgetting to turn it back on.

In the interview

Q: How does a database guarantee durability without writing every change to the data files immediately?

A: It appends each change to a sequential write-ahead log and fsyncs the log before acknowledging the commit. The data files are updated later; after a crash, the log is replayed.

Q: You have three replicas. Do you still need backups?

A: Yes. Replicas protect against hardware failure, but a bad deploy, a bug or a human error is copied to every replica in milliseconds. Backups with point-in-time recovery let you go back to before the mistake.

TL;DR

Durability comes in layers: WAL and fsync survive crashes, replication survives machine loss, cross-region copies survive site loss, and tested backups with point-in-time recovery survive mistakes.

Connection pooling, ORMs and N+1 queries

What it is

These three topics are about how application code talks to the database, and they cause a surprising share of real-world performance problems.

Connection pooling. Opening a database connection is expensive: a TCP handshake, often a TLS handshake, authentication, and the database setting up memory for the session. That can cost several milliseconds, sometimes tens. PostgreSQL even starts a whole operating-system process per connection, using several megabytes of memory each, and its default limit (`max_connections`) is 100. A **connection pool** keeps a set of open connections ready; a request borrows one, uses it and returns it, instead of opening and closing one each time.

> **Analogy.** A taxi rank. Instead of building a new car for every passenger, a fixed set of taxis waits at the rank; passengers take one and it comes back.

How it works

There are two places a pool can live:

1. **In the application** (client-side pool): a library inside each app process, such as HikariCP for Java, or the pools built into most database drivers. Typical settings are a minimum and maximum size, and a timeout for waiting when all connections are busy.
2. **As a separate proxy** (server-side pool): a small service between all app servers and the database, such as **PgBouncer** or Pgpool-II for PostgreSQL, ProxySQL for MySQL, or Amazon RDS Proxy. Useful when you have hundreds of app instances or serverless functions, which would otherwise open thousands of connections. PgBouncer's **transaction pooling** mode hands a server connection to a client only for the duration of one transaction, so a few dozen real connections can serve thousands of clients.

Sizing tip: bigger is not better. A database with 16 CPU cores cannot run 500 queries at once; extra connections just wait and compete for memory. Pools of a few times the core count often perform best.

Remember the multiplication: 50 app servers × 20 connections each = 1,000 connections at the database.


ORMs. An **ORM (object-relational mapper)** is a library that maps database rows to objects in your programming language, so you can write `user.orders` instead of SQL. Examples: Hibernate (Java), Django ORM and SQLAlchemy (Python), ActiveRecord (Ruby on Rails), Entity Framework (.NET), Prisma and Sequelize (JavaScript/TypeScript). ORMs speed up development, protect against SQL injection by using parameters, and handle schema **migrations** (versioned scripts that change the schema). The cost is that they hide the queries actually being run, which makes it easy to write very slow code without noticing. Good teams use the ORM for everyday work, read the generated SQL for hot paths, and drop to hand-written SQL where needed.

The N+1 query problem. The most famous ORM trap. You load a list of N items with 1 query, then loop over them and the ORM quietly runs 1 more query per item to load a related object: N+1 queries in total.

```
posts = Post.objects.all()[:50]       # 1 query
for p in posts:
    print(p.author.name)               # 50 more queries, one per post
```

At 1 ms per round trip that is about 51 ms instead of 2 ms, and with 1,000 items it is a full second. The fixes:

- **Eager loading**: tell the ORM to fetch the related data up front, in a join or one extra query (`select_related` / `prefetch_related` in Django, `includes` in Rails, `JOIN FETCH` in Hibernate).
- **Batching**: collect all the IDs and fetch them in one `WHERE id IN (...)` query. The **DataLoader** pattern does this automatically in GraphQL servers.
- **Detect it**: log query counts per request in development; tools such as Bullet (Rails) flag N+1 patterns.



Common mistakes

- Opening a new connection per request with no pool, then hitting "too many connections" at peak traffic.
- Pool size × number of instances exceeding the database limit after autoscaling adds servers.
- Serverless functions each holding their own connections, without a proxy such as RDS Proxy or PgBouncer.
- Trusting the ORM blindly and shipping N+1 queries on a list page.

In the interview

Q: A list page gets slower as the list grows, and the database shows thousands of tiny identical queries. What is happening?

A: An N+1 query problem: one query for the list and one per item for related data. Use eager loading or batch the lookups into a single `IN` query.

Q: Why put PgBouncer in front of PostgreSQL?

A: PostgreSQL connections are heavy (one process each) and limited. PgBouncer lets thousands of client connections share a small number of real database connections.

TL;DR

Reuse connections through a pool, sized to what the database can actually run in parallel. Use ORMs for productivity but watch the SQL they generate, especially for N+1 queries.

Choosing a database

What it is

This section pulls the part together into a quick decision aid. In an interview, always justify the choice from the **access pattern** (how data is read and written), the **consistency** needed, and the **scale** (data size and requests per second), not from brand names.

How it works

Ask these questions, in order:

1. **What are the main queries?** By key, by range, full-text, joins across entities, aggregations, graph traversal, similarity?
2. **How much data, and how fast does it grow?** Gigabytes fit anywhere. Tens of terabytes push towards sharding or a distributed store.
3. **What is the read-to-write ratio, and the peak writes per second?** Read-heavy suggests replicas and caches; write-heavy suggests LSM-based or sharded stores.
4. **How strong must consistency be?** Money and inventory need transactions. Likes and view counts can be eventually consistent.
5. **Does it need to work across regions?** Multi-region writes push towards multi-leader, leaderless or globally distributed databases.
6. **What does the team know how to run?** Operating a database well is a major cost; a managed service often wins.

Real-world examples

Need	Good choice	Examples
General app data, transactions	Relational	PostgreSQL, MySQL, Aurora
Relational at global scale	Distributed SQL	Spanner, CockroachDB, YugabyteDB
Cache, sessions, counters	In-memory key-value	Redis, Memcached
Simple key access at huge scale	Managed key-value	DynamoDB, Bigtable
Flexible nested records	Document	MongoDB, Firestore, Couchbase
Heavy writes by key and time	Wide-column	Cassandra, ScyllaDB, HBase
Relationships many hops deep	Graph	Neo4j, Neptune
Metrics and sensor data	Time-series	Prometheus, InfluxDB, TimescaleDB
Full-text search, logs	Search engine	Elasticsearch, OpenSearch
Semantic or image similarity	Vector	pgvector, Pinecone, Milvus
Analytics and reporting	Columnar warehouse	Snowflake, BigQuery, ClickHouse
Photos, videos, backups	Object storage	S3, GCS, Azure Blob
Small strongly consistent config	Coordination store	etcd, ZooKeeper

Common mistakes

- Naming a database without saying why.
- Using one database type for everything, or a different exotic one for every table.
- Forgetting the operational cost: backups, upgrades, monitoring and on-call.

In the interview

Q: Which database would you use for a Twitter-like timeline?

A: Users, follows and tweets as the source of truth in a relational database or a wide-column store sharded by user ID; precomputed home timelines in an in-memory store like Redis for fast reads; media in object storage behind a CDN; and a search engine for tweet search. Each choice follows the access pattern.

> **TL;DR**

Start with PostgreSQL or MySQL unless the access pattern or scale clearly needs something else, and add specialist stores (cache, search, object storage, analytics) beside it as needs appear.

Part 3 glossary

Term	Meaning in one line
Database / DBMS	A program that stores data safely, finds it quickly and coordinates concurrent users
State	Stored facts that must survive between requests
Query planner (optimizer)	The part of a database that picks the cheapest way to run a query
Buffer cache	Database memory holding recently used data pages
Read / write	Fetching data without changing it / inserting, updating or deleting data
Relational database	A database storing data in tables of rows and columns with a fixed schema
Table, row, column	A set of records, one record, one property of a record
Schema	The declared structure of tables, columns and data types
Primary key	A column whose unique value identifies each row
Foreign key	A column holding another table's primary key, linking the two
Referential integrity	The guarantee that foreign keys point to rows that exist
Unique constraint	A rule that no two rows share a value in a column
Join	Combining rows from two tables that match on a key
SQL	The standard language for querying relational databases
DDL	SQL statements that change the schema, such as CREATE TABLE
Distributed SQL	Relational databases spread over many machines, such as Spanner or CockroachDB
Transaction	A group of operations that all succeed or all fail
Commit / rollback	Make a transaction permanent / discard all its changes
ACID	Atomicity, Consistency, Isolation, Durability
Atomicity	All-or-nothing execution of a transaction
Consistency (ACID)	A transaction leaves data obeying all declared rules
Isolation	Concurrent transactions do not see each other's unfinished work
Durability	Committed data survives crashes
Concurrency	Several operations running at overlapping times
Anomaly	An incorrect result caused by concurrent transactions
Dirty read	Reading another transaction's uncommitted data
Dirty write	Overwriting another transaction's uncommitted data
Non-repeatable read	Re-reading a row in one transaction and getting a different value
Phantom read	A repeated query returning new rows inserted by another transaction
Lost update	Two read-modify-write cycles overwrite each other, losing one change
Write skew	Two transactions each write different rows based on a shared read and together break a rule
Isolation level	A setting choosing which anomalies the database prevents
Read committed	Isolation level preventing dirty reads only

Term	Meaning in one line
Repeatable read	Isolation level also preventing non-repeatable reads
Snapshot isolation	Each transaction reads a frozen consistent picture of the data
Serializable	Result equals some one-at-a-time order of the transactions
MVCC	Keeping multiple row versions so readers and writers do not block each other
Two-phase locking	Taking locks and holding them until commit to get serializability
SSI	Serializable snapshot isolation, which aborts transactions on dangerous patterns
SELECT FOR UPDATE	Locking rows that were read until the transaction ends
Optimistic concurrency control	Detecting conflicting writes with a version check and retrying
Compare-and-set	Writing only if the current value still equals what was read
NoSQL	Non-relational databases built around specific access patterns
Key-value store	A database mapping keys to opaque values
Document store	A database storing self-contained JSON-like documents
Collection	A group of documents in a document store
Wide-column store	A database grouping rows by partition key and sorting them by clustering key
Clustering key	The key that sorts rows inside one partition in a wide-column store
Graph database	A database storing nodes and edges for relationship queries
Time-series database	A database optimised for timestamped measurements
Search engine	A store built on an inverted index for full-text queries
Inverted index	A map from each word to the documents containing it
Tokenising	Splitting text into searchable words
Relevance ranking	Ordering search results by how well they match
Vector database	A store for embeddings supporting nearest-neighbour search
Embedding	A list of numbers representing an item so similar items are close
ANN / HNSW	Approximate nearest-neighbour search / a popular graph-based ANN index
BASE	Basically available, soft state, eventually consistent
Eventual consistency	Copies agree eventually once writes stop
Polyglot persistence	Using several database types in one system
Schema-on-read / on-write	Structure applied when reading / enforced when writing
Index	An extra structure that finds rows by value without a full scan
Full table scan	Reading every row to answer a query
B-tree	A shallow balanced tree of sorted pages, the default index
Page	A fixed-size block of storage, typically 4 to 16 KB
Branching factor	Number of children per B-tree page
Range query	A query for values between two bounds
LSM-tree	A write-optimised structure of memtable plus merged sorted files
Memtable	The in-memory sorted buffer of an LSM-tree

Term	Meaning in one line
SSTable	An immutable sorted file written by an LSM-tree
Compaction	Merging SSTables and dropping old versions
Tombstone	A marker recording that a key was deleted
Read / write amplification	Extra disk reads per lookup / extra rewrites per byte written
Hash index	An index mapping keys to locations via a hash map
Composite index	An index over several columns in order
Leftmost prefix	The rule that a composite index helps queries on its leading columns
Covering index	An index containing every column a query needs
Index-only scan	Answering a query from the index without touching the table
Clustered index	An index whose order is the physical order of the rows
Secondary index	Any index other than the clustered or primary one
Partial index	An index over only rows matching a condition
Selectivity	How few rows a filter value matches
EXPLAIN	A command showing the plan the database will use
Normalization	Storing each fact in exactly one place
Normal forms (1NF, 2NF, 3NF)	Progressive rules removing repeated and misplaced data
Update anomaly	Inconsistency caused by a fact stored in many places
Denormalization	Duplicating data deliberately to speed up reads
Materialized view	A stored, refreshed result of a query
Replication	Keeping copies of data on several machines
Replica	One copy of the data
Leader / follower	The node accepting writes / nodes copying from it
Read replica	A follower used mainly to serve reads
Multi-leader replication	Several nodes accept writes and replicate to each other
Write conflict	Two concurrent writes to the same record on different leaders
Last write wins	Conflict rule keeping the write with the latest timestamp
CRDT	A data type whose concurrent updates always merge to the same result
Leaderless replication	Any replica accepts writes, with quorums for reads and writes
Quorum	The minimum number of replicas that must respond for success
Read repair	Fixing stale replicas during a read
Anti-entropy	Background comparison and repair of replicas
Hinted handoff	Holding writes for a down node and delivering them later
Synchronous replication	Leader waits for a follower before confirming a write
Asynchronous replication	Leader confirms before followers have the write
Semi-synchronous replication	Leader waits for one follower, the rest are asynchronous
Replication lag	How far a follower is behind the leader

Term	Meaning in one line
Read-your-own-writes	A user always sees their own latest changes
Monotonic reads	A user never sees data go backwards in time
Failover	Promoting a follower to leader after the leader fails
Heartbeat	A periodic "I am alive" message
Split brain	Two nodes both acting as leader and accepting writes
Fencing	Forcibly stopping an old leader from acting
Partitioning	Splitting a dataset into smaller pieces
Sharding	Partitioning across different machines
Shard / partition	One piece of the split data
Horizontal partitioning	Splitting by rows
Vertical partitioning	Splitting by columns
Shard key	The column that decides which shard a row goes to
Range sharding	Each shard owns a continuous range of keys
Hash sharding	The shard is chosen from a hash of the key
Directory-based sharding	A lookup service maps keys to shards
Geo sharding	Sharding by user location
Router	A component that sends each query to the right shard
Cardinality	Number of distinct values in a column
Scatter-gather	Sending a query to all shards and merging results
Hot spot	A shard receiving far more load than others
Hot key	A single key receiving disproportionate traffic
Key salting	Adding a suffix to spread one hot key over several shards
Rebalancing / resharding	Moving data between shards as the cluster changes
Local vs global index	Index per shard / index sharded by the indexed value
Federation	Splitting databases by feature or function
Hash function	A function turning any input into a fixed-size, random-looking number
Consistent hashing	Key placement on a ring so membership changes move about 1/N of keys
Hash ring	The hash output range arranged as a circle
Virtual node	One of many ring positions owned by a single physical server
Rendezvous hashing	Picking the server with the highest score for each key
Block storage	Raw fixed-size blocks presented as a disk
IOPS	Input/output operations per second
File storage	A shared network file system with folders
NFS / SMB	Network file-sharing protocols for Linux / Windows
Object storage	Keyed blobs with metadata accessed over HTTP
Bucket	A top-level container in object storage

Term	Meaning in one line
Blob	A large chunk of unstructured binary data
Pre-signed URL	A time-limited link allowing one direct upload or download
OLTP	Many small transactional queries from an application
OLAP	Large analytical queries over many rows
Row store	Storage keeping each row's columns together
Column store	Storage keeping each column's values together
Parquet / ORC	Columnar file formats for analytics
Data warehouse	Curated structured store for reporting
Star schema	A fact table surrounded by dimension tables
Data lake	Cheap store of raw data in any format
Lakehouse	A data lake with transactional table formats on top
ETL / ELT	Transform before loading / load then transform
Change data capture (CDC)	Streaming every change from a database's log
Write-ahead log (WAL)	A sequential log of changes written before the data files
fsync	A system call forcing written data onto the physical device
Page cache	Operating-system memory buffering file writes
Group commit	Flushing many commits with one fsync
Checkpoint	A point up to which data files reflect the log
RAID	Combining disks so one failure loses no data
Backup	A separate copy kept to recover from loss or mistakes
Full / incremental backup	Complete copy / only changes since the last backup
Logical / physical backup	Exported rows or SQL / copied raw data files
Snapshot	A point-in-time image of a disk or volume
Point-in-time recovery	Restoring to any moment by replaying logs over a backup
3-2-1 rule	Three copies, two media types, one off-site
Connection pool	A set of reusable open database connections
PgBouncer	A popular connection-pooling proxy for PostgreSQL
Transaction pooling	Lending a database connection only for one transaction
ORM	A library mapping rows to programming-language objects
Migration	A versioned script that changes the schema
N+1 query problem	One query for a list plus one per item for related data
Eager loading	Fetching related data up front in few queries
DataLoader	A pattern that batches per-item lookups into one query
Access pattern	How an application reads and writes its data

Part 4 — Caching, async processing and consistency

Parts 1 to 3 built a system that works: clients send requests, servers answer them, and databases remember things. This part covers the three ideas that let that system stay fast and correct once it grows past one machine:

1. **Caching**: keep a copy of popular data somewhere quicker to reach, so you do less slow work.
2. **Asynchronous processing**: hand slow work to a queue and answer the user straight away, instead of making them wait.
3. **Consistency in distributed systems**: once data lives on many machines, decide what "the current value" means and how the machines agree on it.

Most of the vocabulary that makes system design sound hard (CAP, quorum, Raft, idempotency, saga, vector clock, Bloom filter, Snowflake ID) is here. Every term is explained from zero.

Caching basics

What it is

A **cache** is a small, fast store that keeps copies of data that is slow or expensive to get from its real home. The real home is called the **source of truth** or **origin**, usually a database or another service.

Analogy: a chef keeps a small bowl of chopped onions next to the stove instead of going to the cold room for one onion at a time. The bowl is the cache, the cold room is the source of truth. The bowl is within arm's reach but holds little, and what is in it slowly stops being fresh.

Some words you will hear constantly:

- **Cache hit**: the data you asked for was in the cache. Fast path.
- **Cache miss**: it was not, so you go to the source of truth (slow path) and usually put the answer into the cache for next time.
- **Hit ratio** (or hit rate): hits divided by total lookups. A hit ratio of 0.95 means 95 out of every 100 requests never touch the database.
- **TTL (time to live)**: how long an entry may stay in the cache before it is treated as expired and dropped or refreshed.
- **Stale data**: a cached copy that no longer matches the source of truth because the source changed after the copy was taken.
- **Warm cache / cold cache**: a warm cache already holds the popular data. A cold cache (just started, or just emptied) misses on almost everything until it fills up.

Why it matters

Reading from memory is many times faster than asking a database across the network: a local in-memory lookup takes well under a microsecond, while even a quick indexed query takes about a millisecond. Typical numbers:

Where the data is	Typical time to read a small item
CPU cache / process memory	well under 1 microsecond
Redis or Memcached on the same data-centre network	about 0.2–1 ms
Database query hitting an index on SSD	about 1–10 ms
Database query doing a big join or scan	50 ms to seconds
Call to a service in another continent	70–200 ms

Caching gives you three wins:

1. **Lower latency** for the user: a 1 ms cache read instead of a 30 ms query.
2. **Less load on the database**: with a 95% hit ratio the database sees only 5% of the read traffic, which can be the difference between needing one database and needing twenty.


3. **Lower cost**: memory reads are cheaper than recomputing a page or paying for database capacity.

The maths of hit ratio is worth remembering. Average read time = hit ratio x cache time + miss ratio x (cache time + database time). With a 1 ms cache, a 20 ms database and a 90% hit ratio the average is about 0.9 x 1 + 0.1 x 21 = 3 ms. Raise the hit ratio to 99% and it falls to about 1.2 ms. Watch the miss ratio, because that is what the database feels: moving from 90% to 99% hits takes misses from 10 in every 100 reads to 1, a tenfold drop in database reads.

How it works

A cache is usually a **key-value store**: you look things up by a key such as `user:42` and get back a value such as the JSON of user 42's profile. The basic read path:

1. The application builds a key from the request, for example `product:1001`.
2. It asks the cache for that key.
3. On a hit, it returns the cached value.
4. On a miss, it reads from the database, stores the result in the cache with a TTL (say 5 minutes), and returns it.



Caches work because real traffic is **skewed**: a small fraction of items gets most of the requests (the most popular 20% of products might get 80% of the views). You only need to cache that small hot fraction to get a high hit ratio.

Trade-offs

- **Speed vs freshness**: the longer you cache, the faster and cheaper, but the more likely users see stale data.
- **Memory cost**: RAM costs much more per gigabyte than disk, so you cannot cache everything.
- **Extra moving part**: the cache can fail, fill up, or disagree with the database. You now have two copies of the truth to keep in line.
- **Cold-start risk**: if the cache is wiped, every request falls through to a database that was sized for 5% of the traffic.

Common mistakes

- Caching data that is rarely read twice (low hit ratio, wasted memory).
- Forgetting a TTL, so a wrong value lives forever.
- Treating the cache as the source of truth. A cache may lose data at any time; the database must still have it.
- Sizing the database only for the cache-miss traffic and then crashing when the cache restarts.


TL;DR

A cache is a fast copy of slow data. It wins on latency and database load, and the price is memory and the risk of serving stale data.

Where caches live

What it is

Caching is not one box in the diagram. Copies of data can be kept at every hop between the user and the database. The closer to the user, the faster the hit, but the harder it is to update or delete.



Types

Client or browser cache. The browser keeps copies of files (images, CSS, JavaScript, sometimes API responses) on the user's own device. The server controls this with HTTP headers: `Cache-Control: max-age=86400` means "you may reuse this for 86,400 seconds (one day) without asking me". An `ETag` header gives the file a version fingerprint so the browser can ask "has it changed?" and get a tiny `304 Not Modified` reply instead of the whole file. Mobile apps do the same thing with their own local storage. Fastest possible hit (no network at all), but you cannot reach into a user's device to delete a stale copy, so you rely on TTLs and on changing the file name when content changes (for example `app.3f9a1c.js`, called **cache busting**).

CDN cache. A **CDN (content delivery network)** is a network of servers placed in many cities (Part 2). Each edge server caches responses near users so a viewer in Sydney gets the image from Sydney, not from a server in Virginia. Great for static files and for public pages that are the same for everyone.

Reverse proxy cache. A **reverse proxy** is a server that sits in front of your app servers and forwards requests to them (Part 2). NGINX, Varnish and similar proxies can store whole HTTP responses and serve repeated requests without touching the app at all.

Application or in-process cache. A plain in-memory map inside the application process itself (for example a Java Caffeine cache or a Python `functools.lru_cache`). Reads take nanoseconds because there is no network hop. Downsides: each app server has its own copy (ten servers means ten copies that can disagree), the memory is limited to that process, and the cache is lost every time the process restarts or is redeployed.

Distributed cache. A separate cluster of cache servers shared by all app servers, reached over the network. The two famous ones:

- **Memcached**: a simple, very fast, multi-threaded key-value cache holding plain strings or bytes. No persistence, no replication built in. Facebook ran one of the largest Memcached deployments in the world.
- **Redis**: a key-value server with rich data types (strings, lists, hashes, sets, sorted sets, streams, HyperLogLog), optional saving to disk, replication and a cluster mode that splits keys across nodes. Used for caching and also for leaderboards, rate limiters, session stores and simple queues. (Valkey is a community fork of Redis created in 2024 when Redis changed its licence.)

All app servers see the same copy, it survives app restarts, and it can hold hundreds of gigabytes across nodes. The cost is a network hop (well under a millisecond inside a data centre) and another system to run.

Database buffer cache. Databases keep recently used disk pages in RAM themselves: PostgreSQL's **shared buffers**, MySQL InnoDB's **buffer pool**. You get this for free. It is why the second run of the same query is often much faster than the first.

Other caches you may meet: **DNS caches** (your laptop and resolver cache name lookups for their TTL, Part 2), CPU caches (L1/L2/L3, inside the processor), and the operating system **page cache** that keeps recently read file data in spare RAM.

Trade-offs

Layer	Speed of hit	Shared by all users?	Easy to invalidate?
Browser	fastest (no network)	no, one user	no
CDN	very fast (nearby city)	yes, per region	yes, with purge API, takes seconds
In-process	nanoseconds	no, one server	hard across many servers
Distributed (Redis)	under 1 ms	yes	yes, delete the key
DB buffer cache	fast inside DB	yes	automatic

Real-world examples

- Facebook described in its 2013 paper "Scaling Memcache at Facebook" a Memcached layer handling billions of requests per second in front of MySQL.
- Twitter (X) and GitHub use Redis and Memcached heavily for timelines, sessions and counters.
- Netflix runs EVCache, its own distributed cache built on Memcached, replicated across AWS regions.

In the interview

Q: Where would you put a cache in this design?

A: Name the layers from outside in: browser and CDN for static assets and public pages, a distributed cache like Redis in front of the database for hot reads such as user profiles, and rely on the database's own buffer cache. Explain what you cache, the key format and the TTL.

Q: In-process cache or Redis?

A: In-process is fastest but each server has its own copy, so it suits small, rarely changing data such as config or feature flags. Redis is shared, larger and survives deploys, so it suits user data and anything that must look the same from every server.

TL;DR

Caches exist at every hop: browser, CDN, reverse proxy, app memory, a shared cache like Redis, and inside the database. Closer to the user is faster but harder to invalidate.


Caching strategies

What it is

A **caching strategy** (or caching pattern) is the rule for who reads and writes the cache and in what order relative to the database. The choice decides how stale data can get and what happens when something fails half-way.

Types

Cache-aside (lazy loading). The application talks to both the cache and the database. On read: check the cache, on a miss read the database and fill the cache. On write: update the database, then **delete** (invalidate) the cache key so the next read reloads it. This is the most common pattern. Only data that is actually requested gets cached, and if the cache dies the app still works (slower).



Why delete instead of updating the cache on writes? If two writers race, "update cache" can leave the older value in the cache last. Deleting means the next reader fetches the fresh row. A small race still exists (a slow reader can put an old value back just after the delete), which is why you keep a TTL as a safety net.

Read-through. Like cache-aside, but the cache itself loads from the database on a miss. The application only ever talks to the cache. Simpler application code, but you need a cache library or product that knows how to call your database (for example a loader function in Caffeine, or Amazon DynamoDB Accelerator, DAX, in front of DynamoDB).

Write-through. Every write goes to the cache and the cache synchronously writes it to the database before confirming. Cache and database stay in step, and reads right after a write are hits. Cost: every write pays for two writes, and you fill the cache with data that may never be read.

Write-behind (write-back). The write goes to the cache only, the user gets "done" immediately, and the cache flushes changes to the database later, often in batches (for example every second). Very fast writes and fewer database writes (ten updates to the same counter can become one). Danger: if the cache node crashes before flushing, those writes are lost. Used for things like view counters where losing a few is acceptable. CPUs and disk controllers use write-back caches internally too.

Write-around. Writes go straight to the database and skip the cache entirely. The cache is filled only by reads (usually combined with cache-aside). Good when written data is rarely read soon after, such as logs or bulk imports, so the cache isn't flooded with cold data.

Refresh-ahead. The cache reloads popular entries **before** they expire. If an item has a 60-second TTL and is read at second 50, the cache returns the current value and refreshes it in the background. Users never wait on a miss for hot keys. Cost: you may refresh items nobody will ask for again.

Strategy	Who writes the DB	Read after write	Main risk
Cache-aside	App	miss, then reload	brief stale window
Read-through	App (cache loads reads)	miss, then reload	same as cache-aside
Write-through	Cache, synchronously	hit, fresh	slower writes
Write-behind	Cache, later	hit, fresh	data loss on crash
Write-around	App, cache skipped	miss	first reads slow
Refresh-ahead	n/a (read side)	depends	wasted refreshes

Trade-offs

Read-heavy, tolerant of a few seconds of staleness (product pages, profiles): cache-aside with a TTL. Must read your own write immediately: write-through. Extremely write-heavy and loss-tolerant (likes, view counts): write-behind. Data written once and rarely read: write-around.

Common mistakes

- Updating the cache and the database in two steps with no TTL, so a failure between the steps leaves them different forever.
- Using write-behind for money or orders, where a lost write is unacceptable.
- Caching `null` results never, so lookups for things that don't exist always hit the database (an attacker can exploit this by requesting random IDs; caching a short-lived "not found" marker, called **negative caching**, fixes it).

In the interview

Q: Which caching pattern would you use for user profiles?

A: Cache-aside: read from Redis, on miss load from the database and set a TTL of a few minutes. On profile update, write to the database then delete the key. It's simple, survives cache failure, and only caches what's read.

Q: When is write-behind acceptable?

A: When speed matters more than losing a few recent writes, such as counters or analytics events. Never for payments or anything a user was told is saved.

TL;DR

Cache-aside is the default: app reads cache, falls back to the database, and deletes the key on writes. Write-through trades write speed for freshness, write-behind trades safety for speed.

Eviction policies

What it is

A cache has limited memory. When it is full and a new item arrives, it must throw something out. The rule that picks the victim is the **eviction policy**. Eviction (removing because the cache is full) is different from **expiration** (removing because the TTL ran out), though many caches do both.

Analogy: a small bookshelf next to your bed. When it's full and you buy a new book, you move one to the attic. Which one? The one you haven't touched in longest (LRU), the one you read least often (LFU), or the one that's been there longest (FIFO).

Types

- **LRU (least recently used)**: evict the item that has gone longest without being read. Implemented with a hash map plus a doubly linked list so every read moves the item to the front in O(1) time. The default choice almost everywhere because recent use is a good predictor of near-future use.

- **LFU (least frequently used)**: evict the item with the fewest reads. Better when some items are steadily popular for a long time. Weakness: an item that was hugely popular yesterday keeps a high count and squats in the cache, so real LFU implementations decay counts over time.
- **FIFO (first in, first out)**: evict the oldest inserted item regardless of use. Simple, but can throw out a hot item just because it arrived early.
- **TTL-based**: items leave when their time to live expires. Not strictly a "who to evict when full" policy, but it bounds staleness and frees memory.
- **Random**: evict a random item. Surprisingly decent and very cheap.
- Others you may meet: **MRU** (most recently used, useful for some scan patterns), and modern designs like **W-TinyLFU** (used by the Java Caffeine library), which combine recency and frequency.

Redis lets you choose with the `maxmemory-policy` setting, for example `allkeys-lru`, `allkeys-lfu`, `volatile-ttl` or `noeviction` (refuse new writes when full). Redis uses an approximate LRU: it samples a handful of keys and evicts the best candidate among them, which saves memory compared with a full linked list.

Common mistakes

- Using `noeviction` for a cache, so it starts rejecting writes when full.
- One huge scan (like a nightly report reading every row) flushing all the hot items out of an LRU cache. LFU or scan-resistant policies avoid this.

TL;DR

When a cache is full it evicts by a rule: LRU (least recently used) is the safe default, LFU for steady favourites, FIFO and random for simplicity, TTL to bound staleness.

Cache invalidation, stale data and stampedes

What it is

Cache invalidation means removing or updating a cached copy when the source of truth changes. There is a well-known joke, credited to Phil Karlton, that "there are only two hard things in computer science: cache invalidation and naming things". It is hard because the cache and the database are two separate systems and there is no single moment where both change together.

How it works

Ways to keep caches fresh, from simplest to most precise:

1. **TTL only.** Accept that data may be up to TTL seconds old. A 60-second TTL on a product price means a price change can take up to a minute to show.
2. **Delete on write.** After writing to the database, the app deletes the cache key (cache-aside).
3. **Event-driven invalidation.** The database publishes a change event (for example through **change data capture, CDC**, which reads the database's own change log) and a consumer deletes or updates the affected cache keys. Works even when many services write to the database.
4. **Versioned keys.** Put a version in the key, such as `user:42:v7`. A write bumps the version to `v8`, so readers look for a new key and the old one simply ages out. No delete needed.
5. **CDN purge.** CDNs offer an API to purge a URL or a tag; it usually propagates worldwide in seconds.


Stale data

Stale reads happen because of TTLs, lost delete messages, races between readers and writers, and replication lag (the cache was filled from a replica that was behind). Decide per feature how stale is acceptable: a follower count can be minutes old, a bank balance on the transfer screen cannot.

The thundering herd / cache stampede

A **cache stampede** (also called **thundering herd** or **dog-piling**) happens when a very popular key expires or is deleted and thousands of requests miss at the same instant. They all query the database for the same value at once, the database slows down or falls over, and since nothing has refilled the cache yet, more requests pile in.

Example: the home page key gets 10,000 reads per second. It expires. In the 200 ms it takes to rebuild, 2,000 requests all hit the database with the same expensive query.



Fixes for stampedes

- **Request coalescing / single flight**: only one request per key is allowed to rebuild. Others wait for its result (inside one process) or briefly retry the cache. CDNs such as Fastly and Cloudflare do the same at the edge and call it **request collapsing**.
- **Lock or lease**: the first miss takes a short lock in the cache (for example Redis `SET key:lock 1 NX PX 5000`, meaning "set only if not present, expire in 5 s"). Whoever gets the lock rebuilds, the rest serve the old value or wait. Facebook's Memcache paper calls this a **lease**.
- **Serve stale while revalidating**: keep the expired value and return it while one background job refreshes it. HTTP has a header for exactly this: `Cache-Control: stale-while-revalidate=30`.
- **Early or probabilistic refresh**: each reader, as expiry approaches, has a small and growing chance to refresh early, so one request refreshes before the deadline instead of everyone at the deadline.
- **TTL jitter**: add randomness to TTLs (300 s plus or minus 30 s) so keys written together don't all expire together. This also prevents a **cache avalanche**, where a mass expiry or a cache restart sends everything to the database at once.
- **Warm-up**: pre-load hot keys after a restart or deploy before sending real traffic.

Two related problems: **cache penetration** (requests for keys that don't exist anywhere, so every one hits the database; fixed with negative caching or a Bloom filter, see later) and **hot key** (one key so popular that the single cache node holding it is overloaded; fixed by replicating that key to several nodes or caching it in-process too).

Common mistakes

- Setting the same fixed TTL on millions of keys loaded at the same moment.
- Letting every miss rebuild independently with no coalescing.
- Assuming "delete after write" is atomic. If the delete fails, the stale value lives until TTL, so always have a TTL.

In the interview

Q: A celebrity's profile key expires and the database spikes. What happened and how do you fix it?

A: A cache stampede: thousands of concurrent misses on one hot key all query the database. Fix with single-flight or a short lock so only one request rebuilds, serve the stale value meanwhile, refresh hot keys early, and add jitter to TTLs.

Q: How do you keep a cache consistent with the database?

A: You can't make it perfectly consistent cheaply. Use cache-aside with delete-on-write plus a TTL as a safety net. If many services write, invalidate from a change-data-capture stream. Pick the TTL per data type based on how much staleness users can tolerate.

TL;DR

Invalidation is the hard part of caching: use delete-on-write plus TTLs, and protect hot keys from stampedes with locks, stale-while-revalidate, early refresh and TTL jitter.

Message queues

What it is

A **message queue** is a middleman that holds messages (small pieces of data describing work or an event) until another program is ready to handle them. Three roles:

- **Producer** (or publisher): the program that sends a message, for example the web server saying "send welcome email to user 42".
- **Broker**: the queue server that stores messages safely until they are taken. Examples: RabbitMQ, Amazon SQS, Apache Kafka.
- **Consumer** (or worker, subscriber): the program that takes messages and does the work, for example an email worker.

Analogy: a restaurant's order rail. The waiter (producer) clips an order ticket to the rail (broker) and goes back to the customers. The cooks (consumers) take tickets when they have a free hand. The waiter never waits for the food to be cooked, and if the kitchen is busy the tickets just queue up.

Why it matters


Without a queue, the web server would call the email service directly and the user would wait for the email to send. Queues give you:

1. **Faster responses**: the user gets "signed up!" in 50 ms while the slow work (sending email, resizing a photo, charging a card, generating a PDF) happens in the background. This is **asynchronous** processing: the caller doesn't wait for the result.
2. **Decoupling**: the producer doesn't need to know who consumes, how many consumers there are, or whether they are up right now. You can add a new consumer (say, analytics) without touching the producer.
3. **Absorbing spikes (load levelling)**: if 10,000 orders arrive in one minute but workers can handle 2,000 a minute, the queue holds the backlog and workers catch up over five minutes instead of the system falling over.
4. **Reliability**: if a worker crashes mid-task, the message is still in the broker and another worker picks it up.
5. **Independent scaling**: add more workers when the queue grows, remove them when it shrinks.

How it works

A typical lifecycle in a work queue (like SQS or RabbitMQ):


1. The producer sends the message. The broker writes it to disk (and often to replicas) and replies "accepted".
2. A consumer asks for messages and receives one. The broker hides it from other consumers for a while (SQS calls this the **visibility timeout**, 30 seconds by default).
3. The consumer does the work.
4. The consumer sends an **acknowledgement (ack)**: "done, delete it".
5. If no ack arrives in time (the consumer crashed or was too slow), the broker makes the message visible again and another consumer gets it. This is why messages can be delivered more than once, discussed below.



Types

Point-to-point (work queue). Each message is processed by exactly one consumer out of many. Workers compete for messages (the **competing consumers** pattern). Used for jobs: "resize this image" should happen once, not once per worker.

Publish/subscribe (pub/sub). A message is published to a **topic** (a named channel, like "order-placed") and **every** subscriber gets its own copy. The order service publishes "order 9 placed" once, and the email service, the warehouse service and the analytics service each receive it. Used for events that many parts of the system care about.



Many systems combine both: a topic fans out to several queues, and each queue has competing workers (for example Amazon SNS topic feeding several SQS queues, or a RabbitMQ fanout exchange feeding several queues).

Trade-offs

- You gain resilience and speed but lose the immediate answer: the user can't be told "email sent", only "email will be sent".
- Debugging is harder because work happens later, somewhere else. You need tracing and monitoring of **queue depth** (how many messages are waiting) and **consumer lag** (how far behind consumers are).
- Messages may arrive twice or out of order (see delivery guarantees), so consumers must be written carefully.
- The broker is another system to run and size.

Common mistakes

- Using a queue for something the user must see immediately (like "is my password correct?").
- Not monitoring queue depth, so a dead worker goes unnoticed while millions of messages pile up.
- Putting huge payloads (videos) in messages. Store the file in object storage and send its URL in the message instead (the **claim check** pattern).

TL;DR

A message queue lets producers hand work to consumers through a broker, so slow tasks run in the background, spikes are absorbed and services are decoupled. Point-to-point gives each message to one worker, pub/sub gives every subscriber a copy.

Event streaming: topics, partitions, consumer groups and offsets

What it is

Classic queues delete a message once it is acknowledged. An **event streaming platform** (also called a **log-based broker**) such as **Apache Kafka** instead keeps every message in an append-only **log** (a file you only add to the end of) for a set retention period (Kafka's default is 7 days), whether or not anyone has read it. Consumers just remember how far they have read. Many independent consumers can read the same log, and a consumer can rewind and re-read history.


Analogy: a classic queue is a to-do pile where you throw away each note once it's done. A log is a newspaper archive: every reader keeps a bookmark, the papers stay on the shelf, and a new reader can

start from last week's issue.

How it works

Kafka vocabulary, one term at a time:

- **Topic**: a named stream of events, such as `payments`.
- **Partition**: a topic is split into partitions, each an ordered log stored on one broker (with copies on others for safety). Partitions are how Kafka scales: a topic with 12 partitions can be written and read by 12 machines in parallel.
- **Key**: each message can carry a key, such as a user ID. Kafka hashes the key to choose the partition, so all events for user 42 always land in the same partition and stay in order.
- **Offset**: the position number of a message within a partition: 0, 1, 2, ... It never changes. Ordering is guaranteed only **within** one partition, not across the whole topic.
- **Consumer group**: a set of consumers sharing the work for one application. Kafka assigns each partition to exactly one consumer in the group. With 12 partitions and 4 consumers, each consumer reads 3 partitions. A second group (say, analytics) gets its own full copy of the stream independently.
- **Committed offset**: each group periodically records "for partition 3 I have processed up to offset 1,500". After a crash, the replacement consumer resumes from the committed offset.
- **Rebalance**: when a consumer joins or leaves the group, partitions are reassigned.
- **Consumer lag**: newest offset minus committed offset, the main health metric.



Note that adding more consumers than partitions doesn't help: extra consumers sit idle. Choose the partition count with future parallelism in mind.

Types

	Classic queue (RabbitMQ, SQS)	Event stream (Kafka, Kinesis, Pulsar)
After consumption	message deleted	message kept until retention ends
Re-reading history	no	yes, reset the offset
Many independent readers	needs one queue per reader	natural, one group per reader
Ordering	weak (FIFO queues exist)	strict per partition
Best for	background jobs, task distribution	event pipelines, analytics, CDC, replay

RabbitMQ is a traditional broker with flexible routing: producers send to an **exchange**, which routes to queues by rules (direct, fanout, topic patterns). **Amazon SQS** is a fully managed queue: standard queues give at-least-once delivery and best-effort ordering, FIFO queues add strict ordering and de-duplication. **Kafka** was created at LinkedIn and is now an Apache project; it now runs its own Raft-based metadata quorum (KRaft) instead of ZooKeeper, and Kafka 4.0 (2025) removed ZooKeeper support entirely. **Amazon Kinesis**, **Apache Pulsar** and **Redpanda** are similar streaming systems.

In the interview

Q: Kafka or RabbitMQ/SQS?

A: For background jobs where each task runs once and is then forgotten, a queue like SQS or RabbitMQ is simpler. For a high-volume stream of events that several services must read independently, need to replay, or need ordered per key, choose Kafka.

Q: How do you keep all events for one order in order?

A: Use the order ID as the message key, so they all go to the same partition, which is strictly ordered, and have one consumer per partition.

TL;DR

Kafka-style streams keep an ordered, replayable log split into partitions. Consumer groups share partitions and track their position with offsets. Ordering holds only within a partition.

Delivery guarantees, idempotency and retries


What it is

Networks drop packets and machines crash, so a broker can never be sure a message was processed exactly once. A **delivery guarantee** states what the system promises:

- **At-most-once**: each message is delivered zero or one times. If anything fails, it is lost, never repeated. Done by acknowledging (or committing the offset) **before** processing. Fine for metrics where a lost data point doesn't matter.
- **At-least-once**: each message is delivered one or more times. Never lost, but may be repeated. Done by acknowledging **after** processing: if the consumer crashes after doing the work but before the ack, the message comes back and is processed again. This is the default for most systems.
- **Exactly-once**: each message affects the result exactly one time. True exactly-once **delivery** over an unreliable network is impossible in general. What systems offer is **exactly-once processing** or **effectively-once**: messages may be delivered more than once, but duplicates are detected and ignored, so the outcome is as if each was processed once.

How it works

Why duplicates are unavoidable with at-least-once:



The fix is to make the consumer **idempotent**.

Idempotency means doing an operation twice has the same effect as doing it once. "Set balance to 100" is idempotent; "add 20 to balance" is not. "Delete order 9" is idempotent; "create a new order" is not.

How to make non-idempotent work idempotent:

1. Give each operation a unique **idempotency key**, such as a UUID the client generates once for "pay for order 9" and reuses on every retry.
2. Before doing the work, the consumer (or API) checks a table of processed keys.
3. If the key is new, do the work **and** record the key in the same database transaction.
4. If the key was seen, skip the work and return the saved result.

Payment APIs such as Stripe accept an `Idempotency-Key` HTTP header for exactly this reason: a phone that loses signal and retries "pay $20" must not charge twice. Other techniques: **upserts** (insert or overwrite by a unique ID), unique constraints in the database, and conditional updates ("set status to SHIPPED only if it is PAID").

Kafka provides exactly-once semantics inside Kafka (since version 0.11, 2017) by combining an **idempotent producer** (the broker drops duplicate sends using a producer ID and sequence number) with **transactions** that write output messages and the consumer's offset atomically. Once a side effect leaves Kafka (sending an email, calling a bank), you are back to needing idempotency in that system. SQS FIFO queues de-duplicate messages with the same deduplication ID inside a 5-minute window.


Ordering

Ordering costs throughput, because strict global order means one line of processing. Practical systems guarantee order **per key** (per user, per order) by routing a key to one partition or FIFO group. Retries can also break order: if message 5 fails and is retried after message 6 succeeds, they are now out of order. Consumers that care can carry a version number and ignore an older version arriving after a newer one.

Retries, dead-letter queues and backpressure

Retries. When processing fails because of something temporary (a timeout, a database briefly unavailable), try again. Use **exponential backoff**: wait 1 s, then 2 s, 4 s, 8 s, so a struggling dependency isn't hammered, and add **jitter** (random variation) so thousands of clients don't retry at the same instant. Cap the number of attempts. Part 5 covers this in depth.

Dead-letter queue (DLQ). A message that keeps failing (a **poison message**, for example malformed JSON, or an order referring to a deleted product) would otherwise be retried forever and block or waste workers. After N attempts (say 5), the broker moves it to a separate dead-letter queue. Engineers get an alert, inspect it, fix the bug, and **redrive** (replay) the messages back to the main queue. SQS, RabbitMQ and most Kafka frameworks support DLQs.



Backpressure. When consumers can't keep up, something must give. Backpressure is any way for a slow downstream part to signal "slow down" to the upstream part, instead of silently drowning. Options:

- **Buffer**: let the queue grow (fine for spikes, dangerous if it never drains).
- **Block or throttle the producer**: the broker or a bounded queue refuses or delays new messages, for example HTTP `429 Too Many Requests` or `503 Service Unavailable`.
- **Drop**: discard low-priority messages (load shedding).
- **Scale out consumers**: autoscale workers based on queue depth.

TCP flow control (Part 2) and reactive streams libraries are low-level forms of backpressure.

Common mistakes

- Assuming "exactly-once" in a vendor's docs covers your email sends and database writes. It rarely does; design idempotent consumers anyway.
- Retrying instantly in a tight loop, making an outage worse.
- No DLQ, so one poison message blocks a partition (Kafka consumers process a partition in order, so a stuck message stalls everything behind it).
- Unbounded in-memory queues that grow until the process runs out of memory.

Real-world examples

- Stripe's API idempotency keys, described in its public docs.
- Uber and LinkedIn run Kafka at trillions of messages per day, relying on per-key partitioning for ordering.
- AWS SQS redrive policies send messages to a DLQ after a configured `maxReceiveCount`.

In the interview

Q: How do you guarantee a payment is not charged twice when the queue is at-least-once?

A: Make the consumer idempotent. Each payment carries an idempotency key; the worker records processed keys in the same transaction as the charge and skips any key it has seen. Duplicates are then harmless.

Q: What is a dead-letter queue?

A: A side queue where messages go after failing a set number of times, so a poison message doesn't block or waste workers. It's monitored, and messages are replayed after the bug is fixed.

TL;DR

Assume at-least-once delivery, make consumers idempotent with idempotency keys, retry with backoff and jitter, park repeated failures in a dead-letter queue, and apply backpressure when consumers fall behind.

Batch vs stream processing

What it is


Once data is flowing through a system, you often need to compute things from it: daily revenue, recommendations, fraud scores, search indexes.

- **Batch processing** takes a large, bounded pile of data that has already been collected (say, yesterday's 2 TB of logs) and processes it all in one job, usually on a schedule (nightly, hourly). Think of a bakery that bakes the whole day's bread before the shop opens.
- **Stream processing** handles each event (or small window of events) continuously as it arrives, within milliseconds or seconds. Think of a barista who makes each coffee the moment it is ordered.

How it works

MapReduce in one paragraph. MapReduce, published by Google in 2004 and copied by Apache Hadoop, is the classic batch model. The input files are split across many machines. In the **map** step, each machine reads its chunk and emits key-value pairs (for counting words: `("cat", 1)` for every "cat"). In the **shuffle** step, the framework sends all pairs with the same key to the same machine. In the **reduce** step, each machine combines the values for its keys (`("cat", 1+1+1) = ("cat", 3)`). If a machine dies, its piece is simply re-run. Modern engines such as **Apache Spark** keep the same idea but hold intermediate data in memory and are much faster; SQL warehouses like BigQuery, Snowflake and Redshift run batch-style queries over huge tables.

Stream processing engines such as **Apache Flink**, **Kafka Streams** and **Spark Structured Streaming** read from a stream (usually Kafka), keep state (such as running counts per user), and group events into **windows**, for example "orders per minute" (a tumbling one-minute window) or "logins in the last 5 minutes, updated every 10 seconds" (a sliding window). A subtle point: events can arrive late or out of order, so engines distinguish **event time** (when it happened) from **processing time** (when it arrived) and use **watermarks** to decide when a window is complete.



Trade-offs

	Batch	Stream
Latency of results	minutes to hours	milliseconds to seconds
Input	bounded, complete	unbounded, arriving
Complexity	simpler, easy to re-run	harder: state, late events, failures
Typical uses	reports, billing, ML training, backfills	fraud detection, live metrics, alerts

Two named architectures: **Lambda architecture** runs both a batch layer (accurate, slow) and a speed layer (fast, approximate) and merges them. **Kappa architecture** uses only a stream and handles reprocessing by replaying the log from the start. Many companies now prefer Kappa-style designs to avoid writing logic twice.

In the interview

Q: Should a "trending hashtags" feature use batch or streaming?

A: Streaming, because users expect it to reflect the last few minutes. Count hashtags in sliding windows with a stream processor reading from Kafka, possibly with an approximate structure like count-min sketch, and recompute exact daily numbers in batch.

TL;DR

Batch processes a complete pile of data on a schedule (MapReduce, Spark); streaming processes events continuously as they arrive (Flink, Kafka Streams). Choose by how fresh the result must be.

Event-driven architecture, event sourcing and CQRS

What it is

Event-driven architecture (EDA) is a style where services communicate by publishing **events**, facts about something that already happened ("OrderPlaced", "PaymentFailed"), rather than calling each other with commands ("ship this now"). The publisher doesn't know or care who listens.

Analogy: a town crier announces "the market opens at noon" to the square. Anyone who cares acts on it; the crier doesn't keep a list of who should be told.

An **event** reports something that is already done, so a listener can ignore it but cannot say no to it. A **command** is a request that the receiver may reject. Name them to match: events in the past tense (`OrderPlaced`), commands as orders (`ShipOrder`).


How it works

When an order is placed, the order service saves it and publishes `OrderPlaced`. The payment, inventory, email and analytics services each subscribe and react. Adding a loyalty-points service later needs no change to the order service.

A practical problem: the service must both update its database and publish the event. If it does one and crashes before the other, they disagree (the **dual write** problem). The standard fix is the **transactional outbox**: in the same database transaction as the business change, insert the event into an `outbox` table. A separate relay process (or CDC tool like Debezium) reads the outbox and publishes to the broker, retrying until it succeeds. Combined with idempotent consumers, nothing is lost.

Event sourcing. Instead of storing only the current state (balance = 70), store the full sequence of events that led there (Deposited 100, Withdrew 50, Deposited 20) as the source of truth. Current state is computed by replaying events, usually with periodic **snapshots** so you don't replay millions every time. Benefits: a complete audit trail, the ability to rebuild state or answer "what was the balance last Tuesday?", and easy new projections. Costs: more complex, events can't be changed once written so schema evolution is harder, and queries need separate read models. Bank ledgers and accounting books have always worked this way.

CQRS (Command Query Responsibility Segregation). Use one model (and often one database) for writes (commands) and a different model for reads (queries). Writes go to a normalized database; events or CDC update one or more read-optimised views, such as a denormalized table, a search index in Elasticsearch, or a cache. Reads scale independently and each screen gets data in exactly the shape it needs. Cost: the read side lags the write side slightly (eventual consistency), and there are more moving parts. CQRS pairs naturally with event sourcing but doesn't require it.



Trade-offs

EDA gives loose coupling and easy extension, but flows become harder to follow (no single place shows the whole order process), and you live with eventual consistency, duplicates and ordering issues. Use it where many services react to the same facts; keep simple request-response for things needing an immediate answer.

In the interview

Q: How do you reliably update the database and publish an event?

A: Transactional outbox: write the event to an outbox table in the same transaction as the change, then a relay publishes it with retries. Consumers are idempotent because the relay may publish twice.

Q: What is CQRS and when would you use it?

A: Separate write and read models. Use it when reads and writes have very different shapes or scale, for example writes to a relational DB and searches served from Elasticsearch kept up to date by events.

TL;DR

Event-driven systems react to published facts instead of direct calls. Event sourcing stores the events themselves as the truth; CQRS splits the write model from read-optimised views. Both add flexibility at the cost of eventual consistency and complexity.

Consistency models

What it is

When data is copied to several machines (replication, Part 3), a read might go to a copy that hasn't received the latest write yet. A **consistency model** is the promise a system makes about what a read can return after a write. It is a contract between the database and the programmer: "if you do X, you will never see Y".

Note: this "consistency" is different from the C in ACID (Part 3), which means "transactions keep the data valid according to your rules". Same word, different idea.

Analogy: a family shares a shopping list copied onto three fridges in three houses. Strong consistency means that the moment anyone adds "milk", every fridge shows it before anyone can read any list. Eventual consistency means the copies are updated by phone calls over the next few minutes; for a while, different fridges show different lists, but if people stop editing, all three end up the same.

Types

From strongest (easiest to reason about, most expensive) to weakest:

Linearizability (strong consistency). The system behaves as if there is only one copy of the data and every operation happens at a single instant between its start and its end. Once any read has returned the new value, no later read anywhere can return the old one. Plain words: "it looks like one machine". Needed for things like a username uniqueness check, a lock, or a bank balance check before withdrawal. Cost: every write must reach a majority or a leader before it's confirmed, which adds latency, especially across regions, and the system may refuse requests during a network partition.

Sequential consistency. All clients see all operations in the same order, and each client's own operations appear in the order it issued them, but that order needn't match real time. Mostly a term you'll meet in theory and CPU memory models.


Causal consistency. If one operation could have caused another, everyone sees them in that order. If Alice posts "I'm engaged!" and Bob replies "Congratulations!", nobody should see Bob's reply without Alice's post. Unrelated operations (Carol's post in another thread) may appear in different orders to different people. Research has shown that causal consistency (in a slightly strengthened form) is about the strongest model a system can offer while staying available during a network partition, so it's attractive for global systems.

Session guarantees (also called client-centric consistency) are promises to a single user, cheap to provide and often enough:

- **Read-your-writes** (read-your-own-writes): after you change your profile photo, you always see the new photo, even if other users see the old one for a few seconds. Implemented by reading your own data from the leader for a short time after writing, or by tracking the write's position and only reading from replicas that have caught up.
- **Monotonic reads**: once you've seen a value, you never see an older one later. Without it, refreshing a page could show a comment, then hide it, then show it, because each refresh hit a different replica. Implemented by sticking each user to one replica.
- **Monotonic writes**: your writes are applied in the order you made them.

- **Writes-follow-reads**: if you read something and then write based on it, your write is ordered after what you read.

Eventual consistency. If no new writes happen, all replicas will eventually return the same value. No promise about how long "eventually" is (usually milliseconds to seconds) or what you see in the meantime. DNS is a classic example: change a record and different resolvers return old or new answers until TTLs expire. Cheap, fast, and highly available.



Strong vs eventual in practice. Many databases let you choose per request. DynamoDB reads are eventually consistent by default, and you can ask for a strongly consistent read at double the read cost. Cassandra lets you set a consistency level per query (ONE, QUORUM, ALL). Google Spanner offers externally consistent (linearizable) transactions globally.

Trade-offs

Model	Promise	Cost	Good for
Linearizable	looks like one copy	high latency, less available	locks, balances, unique names
Causal	cause before effect	moderate	comments, chat, social feeds
Read-your-writes	you see your own changes	low	profiles, settings
Eventual	converges eventually	lowest	likes, view counts, DNS

Common mistakes

- Saying "eventually consistent" as if it means "consistent after a short fixed time". It promises no bound.
- Assuming reading from replicas is safe for a flow like "save, then redirect to the page that shows it". Users will see their own change missing. Use read-your-writes.
- Confusing consistency in CAP (linearizability) with consistency in ACID (valid data).

In the interview

Q: Where is eventual consistency acceptable?

A: Where brief staleness is harmless: like counts, follower counts, view counts, recommendations, search indexes. Not for balances, inventory at checkout, or uniqueness checks.

TL;DR

Consistency models describe what reads may return after writes, from linearizable (acts like one copy) through causal and session guarantees to eventual (converges sometime). Stronger means simpler reasoning but slower and less available.

CAP theorem and PACELC

What it is

The **CAP theorem**, proposed by Eric Brewer in 2000 and proved by Gilbert and Lynch in 2002, says that a distributed data store facing a **network partition** must choose between consistency and availability.

- **C, consistency**: here it means linearizability: every read sees the latest write, as if there were one copy.
- **A, availability**: every request to a working (non-crashed) node gets a non-error answer, without waiting forever.
- **P, partition tolerance**: the system keeps operating even when the network between nodes drops or delays messages.


A **network partition** is when the network splits the nodes into groups that can't talk to each other, even though each node is still running. Example: the link between your US and EU data centres fails. Each side is healthy and still receiving user requests, but neither can tell what the other is doing.

How it works

Suppose two replicas, one in the US and one in the EU, and the link between them is cut. A user in the EU writes `x = 2`. Now a user in the US reads `x`. The US replica has two options:

1. **Refuse or wait** (return an error or block) because it can't confirm it has the latest value. It stays **consistent** but is not **available**. This is **CP**.
2. **Answer with what it has** (`x = 1`, old). It stays **available** but is not **consistent**. This is **AP**.

There is no third option: it can't know about a write it can't hear about. Because partitions in real networks are not optional (cables get cut, switches fail, cloud zones lose connectivity), the real choice is between C and A **during a partition**. When the network is healthy, a system can provide both.



Types

CP examples: systems built on consensus or a single leader, such as ZooKeeper, etcd, Consul, Google Spanner, HBase, and MongoDB with majority reads and writes. On the minority side of a partition they stop accepting writes.

AP examples: Cassandra, Riak, DynamoDB-style leaderless stores at low consistency levels, CouchDB, DNS. Both sides keep serving and reconcile afterwards (using timestamps, version vectors or merge rules).

Many systems are tunable, so "Cassandra is AP" really means "Cassandra with consistency level ONE behaves AP".

PACELC

CAP only talks about the rare partition case. **PACELC**, proposed by Daniel Abadi in 2010, adds the everyday case: **if** there is a **P**artition, choose **A** or **C**; **E**lse (normal operation), choose **L**atency or **C**onsistency. Even with a perfect network, keeping replicas strongly consistent means waiting for other machines, which costs latency.

- **PA/EL**: Cassandra, DynamoDB (default settings): available in partitions, low latency normally, consistency relaxed both times.
- **PC/EC**: Spanner, traditional single-leader setups with synchronous replication: consistent always, pay in availability and latency.
- **PA/EC** and **PC/EL** exist too (for example, MongoDB is often described as PA/EC under some settings; descriptions vary with configuration).

Common mistakes (misreadings of CAP)

- **"Pick any two of three."** You can't pick CA in a distributed system, because you can't opt out of partitions. A single-node database is "CA" only because it isn't distributed.
- **"AP means no consistency ever."** It means the system may return stale data during a partition. Normally it's usually consistent within milliseconds.

- **"CP means the system goes down."** Only requests that can't be safely served fail, typically on the minority side.
- **Mixing CAP's C with ACID's C.** CAP's C is linearizability.
- **Treating CAP as a whole-system label.** Different features of one product can make different choices (a shopping cart can be AP, checkout CP).

In the interview

Q: Explain CAP in one breath.

A: When the network splits, a replicated system must either refuse some requests to stay consistent (CP) or keep answering with possibly stale data (AP). Partitions are a fact of life, so the real choice is C or A during them.

Q: Is your design CP or AP?

A: Say per component: payment and inventory reservation are CP (we'd rather fail than double-sell), while the product catalogue, likes and feeds are AP (stale is fine, downtime is not). Then mention PACELC: even without partitions, we accept slightly stale reads for lower latency on the AP parts.

TL;DR

CAP: during a network partition, choose consistency (refuse) or availability (answer, maybe stale). PACELC adds: otherwise, choose latency or consistency.

Quorums

What it is

A **quorum** is the minimum number of replicas that must take part in an operation for it to count. In **leaderless replication** (Part 3: Dynamo, Cassandra, Riak), clients write to and read from several replicas at once, and quorums decide how many must answer.


Three numbers:

- **N**: number of replicas that store each piece of data (often 3).
- **W**: number of replicas that must confirm a write before it's considered successful.
- **R**: number of replicas that must answer a read.

How it works

The key rule: if **R + W > N**, every read set overlaps every write set in at least one replica, so a read is guaranteed to reach at least one replica holding the latest successful write. The reader picks the newest version among the answers (by version number or timestamp).

Example with N = 3, W = 2, R = 2: a write reaches replicas A and B. A later read asks B and C. B has the new value, so the reader sees it. 2 + 2 = 4 > 3.



The reader gets v2 from B and v1 from C and keeps v2. It may also fix C on the spot (**read repair**). Background **anti-entropy** processes compare replicas (often with Merkle trees, below) to fix the rest.

Common settings for N = 3:

W	R	Effect
2	2	balanced, tolerates 1 replica down for both reads and writes
3	1	fast reads, any replica down blocks writes
1	3	fast writes, any replica down blocks reads
1	1	fastest, R + W = 2 is not > 3, so reads may be stale

A **majority quorum** is more than half: 2 of 3, 3 of 5. Two majorities always overlap, which is why consensus algorithms use them. With N nodes, a majority quorum tolerates `floor((N - 1) / 2)` failures: 1 failure with 3 nodes, 2 with 5. That's why clusters use odd sizes: 4 nodes tolerate only 1 failure, the same as 3.

Sloppy quorum and hinted handoff. If some home replicas are unreachable, Dynamo-style systems may temporarily write to other nodes, which later hand the data back. This boosts availability but breaks the R + W > N guarantee for a while.

Trade-offs and caveats

Quorums give tunable consistency, but R + W > N is not full linearizability on its own: concurrent writes, sloppy quorums and failed partial writes can still produce odd results. Larger W makes writes slower and less available; larger R does the same for reads.

In the interview

Q: With 3 replicas, how do you make sure reads see the latest write?

A: Use quorums with R + W > N, for example W = 2 and R = 2, so read and write sets always overlap. That also tolerates one replica being down.

TL;DR

Quorums: write to W replicas and read from R out of N. When R + W > N, reads overlap writes and see the latest value; tune R and W to trade read speed, write speed and availability.

Consensus, leader election and distributed locks

What it is

Consensus is getting several machines to agree on one value (or one sequence of values) even when some of them crash or messages are lost. "Who is the leader?", "Was this transaction committed?", "Who holds the lock?", "What is the next entry in the log?" are all consensus problems.

Analogy: five friends choosing a restaurant over unreliable text messages, where some phones die mid-conversation. They need a method so that, once a choice is announced, nobody ends up at a different restaurant, and the group can still decide if one or two phones die.

Why it matters

Without consensus you get **split brain** (Part 3): two nodes both think they're the leader, both accept writes, and the data diverges. Consensus systems are the backbone of coordination services like **etcd** (used by Kubernetes to store all cluster state), **ZooKeeper** (used by Hadoop, older Kafka), **Consul**, and of databases like CockroachDB, TiDB, YugabyteDB and Spanner.


How it works

Two famous algorithms:

- **Paxos**, by Leslie Lamport (first written up around 1989–1990, formally published in 1998), the first widely known proven solution. Correct but famously hard to understand and implement.
- **Raft**, by Diego Ongaro and John Ousterhout (2014), designed to be understandable. Most new systems use Raft (etcd, Consul, CockroachDB, Kafka's KRaft).

Raft intuition, step by step:

1. Each node is a **follower**, a **candidate** or the **leader**. Time is divided into numbered **terms** (also called **epochs** or generations in other systems). Each term has at most one leader.
2. The leader sends regular **heartbeats** to followers. If a follower hears nothing for its **election timeout** (randomised, for example 150 to 300 ms, so nodes don't all time out together), it assumes the leader is dead.
3. That follower becomes a candidate, increments the term (say from 4 to 5), votes for itself, and asks others for votes.
4. Each node votes for at most one candidate per term, and only for a candidate whose log is at least as up-to-date as its own. A candidate with votes from a **majority** becomes leader for term 5.
5. Clients send writes to the leader. The leader appends the write to its log and sends it to followers. Once a majority have stored it, the entry is **committed**, applied, and the client gets "ok".
6. If an old leader from term 4 comes back, any message it sends carries term 4; nodes reject it because they've seen term 5, and it steps down. Terms are how stale leaders are detected.



Because a majority is needed, a 5-node Raft cluster keeps working with 2 nodes down; with 3 down it stops accepting writes (it chooses consistency, so it's CP). Consensus clusters are usually 3 or 5 nodes: more nodes means more fault tolerance but slower writes.


Leader election is the most common use: many replicas of a service, but only one should run the nightly billing job or act as database primary. You use a coordination service (etcd, ZooKeeper, Consul) rather than writing your own consensus.

Distributed locks and fencing tokens

A **distributed lock** ensures that only one process across many machines does something at a time (for example, only one worker processes refund 77). It's usually a key in a coordination service or Redis with a **lease** (an expiry time) so that a crashed holder doesn't block everyone forever.

The danger: a process takes the lock with a 10-second lease, then pauses (a long garbage-collection pause, a slow disk, its virtual machine being moved to another host) for 15 seconds. The lease expires, another process takes the lock and starts writing. The first process wakes up, still believes it holds the lock, and writes too. Now two "lock holders" are writing.

The fix is a **fencing token**: every time the lock is granted, the lock service hands out a number that always increases (33, then 34). The holder sends its token with every write to the storage system, and storage rejects any write with a token lower than one it has already seen. The paused process with token 33 is rejected because 34 has already written.



ZooKeeper's zxid and etcd's revision numbers can serve as fencing tokens. A simple Redis `SET lock NX PX` lock is fine for efficiency (avoiding duplicate work) but should not be trusted alone for correctness, because it provides no fencing token.

Common mistakes

- Writing your own consensus or leader election with timestamps and hope. Use etcd, ZooKeeper or Consul.
- Running consensus with 2 or 4 nodes (no extra fault tolerance over 1 or 3).
- Trusting a lease-based lock without fencing for data correctness.
- Spreading a consensus cluster across continents without realising every write now waits for an intercontinental round trip (70+ ms).

In the interview

Q: How do you ensure only one instance runs a scheduled job?

A: Leader election through a coordination service such as etcd or ZooKeeper, or a lock with a lease. Make the job idempotent and, if it writes shared data, pass a fencing token so a stale leader's writes are rejected.

Q: Why are consensus clusters 3 or 5 nodes?

A: They need a majority to make progress. 3 nodes tolerate 1 failure, 5 tolerate 2. Even numbers add cost without extra tolerance, and more nodes slow every write.

TL;DR

Consensus (Raft, Paxos) lets machines agree on a leader or a log despite failures by requiring a majority and numbering leadership terms. Use a coordination service for leader election and locks, and protect locks with fencing tokens.

Clocks and ordering

What it is

To decide "which write happened last?" it's tempting to compare timestamps. But each machine has its own clock, and clocks are not in perfect agreement.

- **Clock skew**: the difference between two machines' clocks at the same moment, for example server A says 12:00:00.000 and server B says 12:00:00.150.
- **Clock drift**: a clock running slightly fast or slow. A quartz clock can drift by tens of microseconds per second, which adds up to seconds per day if never corrected.
- **NTP (Network Time Protocol)**: machines periodically ask time servers for the correct time and adjust. Over the internet it typically keeps clocks within a few to tens of milliseconds; inside a good data centre, better than a millisecond. Clocks can still jump backwards after a correction.

Two kinds of clock in every machine: the **wall clock** (time of day, can jump) and the **monotonic clock** (only moves forward, good for measuring durations like timeouts, meaningless across machines).

Why it matters

Last-write-wins (LWW) conflict resolution keeps the write with the highest timestamp. If server B's clock is 150 ms fast, a write on B can "win" over a later write on A, and A's write silently disappears. Ordering events by wall-clock timestamps from different machines is unsafe.

How it works

Logical clocks order events without real time.

Lamport clock (Leslie Lamport, 1978). Each process keeps a counter.

1. Before each local event, increment the counter.
2. When sending a message, attach the counter.
3. When receiving a message with counter `c`, set your counter to `max(yours, c) + 1`.

If event X caused event Y (directly or through a chain of messages), then X's Lamport time is smaller than Y's. Ties are broken by process ID to get a total order. Limitation: a smaller number does not prove X caused Y, so Lamport clocks can't detect concurrent events.

Vector clock. Each process keeps a list of counters, one per process, for example `[A:2, B:0, C:1]`. You increment your own entry on each event and, on receiving, take the element-wise maximum and then increment your own. Comparing two vectors tells you one of three things: X happened before Y (every entry of X is less than or equal to Y's, and at least one is smaller), Y before X, or they are **concurrent** (each has some entry larger). Concurrency detection is exactly what you need to spot conflicting writes, for example two people editing the same shopping cart offline. Dynamo-style stores use similar **version vectors** to keep both conflicting versions ("siblings") and let the application merge them. Cost: the vector grows with the number of participants.

Clock	Detects causality?	Detects concurrency?	Size
Wall clock	no (skew)	no	one number
Lamport	if X caused Y, then L(X) < L(Y)	no	one number
Vector	yes	yes	one number per node

Hybrid logical clocks (HLC) combine wall time with a logical counter, giving timestamps close to real time that still respect causality; CockroachDB and YugabyteDB use them. **Google TrueTime** (in Spanner) uses GPS receivers and atomic clocks in every data centre and returns an interval "now is between T1 and T2" with a typical uncertainty of a few milliseconds; Spanner waits out that uncertainty before committing so timestamps are globally ordered.

Common mistakes

- Using `System.currentTimeMillis()` from different servers to decide which update wins.

- Measuring timeouts with the wall clock (an NTP jump can make a duration negative). Use a monotonic clock.

In the interview

Q: Two replicas accepted conflicting writes. How do you tell which came first?

A: Wall clocks can't be trusted across machines. Vector clocks (version vectors) tell you whether one write happened before the other or whether they were concurrent; concurrent writes need a merge rule or the user to choose. Lamport clocks give a consistent total order but can't detect concurrency.

TL;DR

Machine clocks disagree (skew) and drift, even with NTP, so don't order cross-machine events by timestamps. Lamport clocks give an order consistent with causality; vector clocks also detect concurrent, conflicting updates.

Distributed transactions: two-phase commit and sagas

What it is


A **distributed transaction** is a change that must happen across several databases or services as one unit: either all parts happen or none do. Example: booking a trip charges the card (payment service), reserves a seat (flight service) and books a room (hotel service). Charging the card without the seat is a bug that costs real money.

Inside one database, ACID transactions (Part 3) handle this. Across several, there are two main approaches.

Types

Two-phase commit (2PC). A **coordinator** (also called transaction manager) runs the transaction across **participants** (the databases).

1. **Prepare phase**: the coordinator asks every participant "can you commit?". Each one does the work, writes it durably, locks the rows involved, and votes **yes** (promising it can commit even after a crash) or **no**.
2. **Commit phase**: if all voted yes, the coordinator writes "commit" to its own log and tells everyone to commit. If any voted no or didn't answer, it tells everyone to abort.



Strength: real atomicity and isolation across databases. Weaknesses: it's **blocking**. If the coordinator crashes after participants voted yes, they must keep their rows locked and wait, possibly for a long time, because they promised to obey whatever the coordinator decides. Every transaction needs several round trips and holds locks meanwhile, so throughput and availability suffer. It's used inside some distributed databases (Spanner runs 2PC over Paxos-replicated groups, so the coordinator itself is replicated and cannot simply vanish) and via the XA standard (a common interface that lets one transaction manager drive several databases) between traditional databases, but rarely across microservices. (Three-phase commit was proposed to reduce blocking but is little used in practice.)


Saga. Break the big transaction into a sequence of **local transactions**, one per service, each committed on its own. If a later step fails, run **compensating transactions** that semantically undo the earlier steps, in reverse order.

Trip example:

1. Payment service charges the card. (Compensation: refund.)
2. Flight service reserves a seat. (Compensation: release the seat.)
3. Hotel service books a room. Fails, no rooms.
4. Run compensations: release the seat, refund the card.

Two ways to coordinate a saga:

- **Choreography**: no central controller. Each service listens for events and reacts ("PaymentCompleted" makes the flight service reserve, "HotelFailed" makes the flight service release). Simple for 2–3 steps, hard to follow with many.
- **Orchestration**: a central **orchestrator** (a workflow engine such as Temporal, AWS Step Functions or Camunda, or your own service) tells each service what to do next and triggers compensations on failure. Easier to see and change the whole flow.



Trade-offs

	2PC	Saga
Atomicity	true all-or-nothing	eventual, via compensations
Isolation	yes, locks held	no, others can see partial results
Availability	blocks if coordinator fails	each step independent
Fits	few databases, short transactions	microservices, long business flows

Sagas give up isolation: between steps, someone could see "card charged, no seat yet". Designs cope with it using states like `PENDING`, and compensations must be idempotent and retryable because they may run more than once. Some actions can't be undone (an email sent), so you put them last or compensate with another action (a "sorry" email).

In the interview

Q: How do you keep data consistent across order, payment and inventory microservices?

A: A saga: each service does a local transaction and publishes an event (via outbox), with compensations on failure, coordinated by an orchestrator for visibility. Avoid 2PC across services because it blocks and couples availability.

Q: What's the main weakness of 2PC?

A: It's blocking: if the coordinator fails after participants vote yes, they hold locks and wait. It also needs every participant up for every transaction.

TL;DR

2PC gives true atomic commits across databases but blocks on coordinator failure; sagas chain local transactions with compensating undo steps, trading isolation for availability, and are the norm in microservices.

Heartbeats, gossip and failure detection

What it is

In a cluster, nodes need to know which other nodes are alive. But over a network you can never tell the difference between a node that's dead, one that's slow, and a network that's dropping messages. **Failure detection** is the art of making a good guess.

- **Heartbeat**: a small "I'm alive" message a node sends regularly, say every second. If the monitor misses several in a row (say, nothing for 5 seconds), it marks the node as **suspected dead**. Load balancer health checks (Part 2) and Raft leader heartbeats are the same idea.
- **Timeout choice**: short timeouts detect failures quickly but cause **false positives** (declaring a slow-but-alive node dead, triggering needless failovers). Long timeouts are safe but slow to react.


How it works

Centralised monitoring (every node heartbeats to one coordinator, such as ZooKeeper sessions) is simple, but the monitor must itself be highly available.

Gossip protocol. In large clusters with no central monitor, nodes spread information the way rumours spread in an office:

1. Every second, each node picks one or a few random other nodes.
2. It sends them what it knows: its membership list, with a heartbeat counter for every node it has heard of.
3. The receiver merges the lists, keeping the higher counter for each node.
4. If a node's counter hasn't gone up for a while, it is suspected dead, and that suspicion spreads too.

Information reaches all N nodes in about log(N) rounds: with 1,000 nodes, around 10 rounds. No single point of failure, and load per node stays constant. Cassandra, DynamoDB's original design, Consul (via memberlist, a library based on the SWIM protocol described below) and Redis Cluster use gossip for membership and failure detection.



Smarter detectors. The **phi accrual failure detector** (used by Cassandra and Akka) outputs a suspicion level based on the history of heartbeat arrival times, instead of a fixed yes/no timeout, so it adapts to networks that are normally slow. **SWIM** asks a few other nodes to ping a suspected node indirectly before declaring it dead, cutting false positives caused by one bad link.

Common mistakes

- Very short failure timeouts that cause **flapping**: nodes marked dead and alive over and over, triggering repeated failovers.
- Assuming a node declared dead has stopped. It may still be running and writing (the paused lock holder from earlier). Use fencing.

TL;DR

Nodes send heartbeats; missing heartbeats mean "suspected dead". Gossip spreads membership and liveness through random peer-to-peer exchanges, reaching everyone in about log N rounds with no central monitor.

Probabilistic data structures and Merkle trees

These are clever structures that answer questions using far less memory than an exact answer would need, in exchange for a small, controlled error. Each appears often in interviews.

Bloom filter

What it is. A compact structure that answers "is X in the set?" with either **"definitely not"** or **"probably yes"**. It never gives a false negative, but it can give a **false positive**.

How it works.

1. Start with an array of m bits, all 0 (say 10 million bits, about 1.2 MB).
2. Pick k hash functions (say 7). A hash function turns any input into a number; here each one maps an item to a bit position.
3. To add "alice", compute her 7 positions and set those bits to 1.
4. To check "bob", compute his 7 positions. If any bit is 0, bob was **definitely never added**. If all are 1, bob is **probably** in the set (those bits could have been set by other items).

With about 10 bits per item and 7 hash functions, the false-positive rate is about 1%. You can't delete items from a basic Bloom filter (a **counting Bloom filter** variant allows it).

Uses. Databases with LSM-trees (Cassandra, RocksDB, HBase) keep a Bloom filter per data file so a read for a missing key skips files without touching disk. Caches use one to block lookups for keys that don't exist (cache penetration). Web crawlers use them to skip URLs already visited. Chrome once used one to check URLs against a list of malicious sites before a slower exact check.

HyperLogLog

What it is. Estimates the **number of distinct items** (cardinality), such as unique visitors today, using a tiny, fixed amount of memory.

How it works (intuition). Hash each item to a random-looking binary number. Rare patterns such as a long run of leading zeros only show up when you've seen many distinct items: seeing a hash that starts with 20 zeros suggests you've seen roughly 2^20 (about a million) distinct items. HyperLogLog splits items into many buckets, records the longest run in each, and averages them to reduce luck. Duplicates hash the same, so they don't change the estimate.

Numbers. Redis's HyperLogLog uses at most 12 KB per counter, has a standard error of 0.81%, and can count billions of distinct items. An exact set of a billion user IDs would need gigabytes. Sketches from different servers can be merged (`PFMERGE`) to get a combined count. Used for unique visitors, distinct search queries, and approximate `COUNT(DISTINCT ...)` in BigQuery and other warehouses.

Count-min sketch

What it is. Estimates **how many times** each item has appeared in a stream (frequency), in fixed memory, for example "how many times was #worldcup posted in the last hour?".

How it works. Keep a small table of counters with d rows and w columns, and one hash function per row. To add an item, hash it in each row and increment that counter. To query, hash it in each row and take the **minimum** of the d counters. Collisions only ever add counts, so the estimate can be too high but never too low; taking the minimum picks the least-polluted counter.


Uses. Finding heavy hitters and trending topics, detecting hot keys in a cache, network traffic monitoring, approximate top-K lists.

Merkle tree

What it is. A tree of hashes. Each leaf is the hash of a block of data; each parent is the hash of its children's hashes; the single hash at the top is the **root hash**. If any byte of any block changes, its leaf hash changes, and so does every hash on the path up to the root.

How it works for comparing replicas. Two replicas each build a Merkle tree over their data, split into ranges.

1. Compare root hashes. Equal means all the data is identical: done, with one tiny message.
2. If different, compare the two children, and only descend into the halves whose hashes differ.
3. At the bottom you find exactly which ranges differ and copy only those.



Finding a few differences among billions of records costs about log(number of blocks) comparisons instead of shipping everything. **Uses**: anti-entropy repair in Cassandra and Dynamo-style stores, Git (commit and tree objects are built from hashes), Bitcoin and other blockchains (proving a transaction is in a block), certificate transparency logs, and file sync tools.

Summary table

Structure	Answers	Error	Memory
Bloom filter	is X in the set?	false positives only	~10 bits per item for 1%
HyperLogLog	how many distinct items?	~0.81% in Redis	12 KB per counter
Count-min sketch	how often has X appeared?	overestimates only	fixed table
Merkle tree	do two datasets differ, and where?	none (exact)	one hash per block

In the interview

Q: How would you count unique daily visitors for a site with 500 million users?

A: A HyperLogLog per day (for example Redis `PFADD` and `PFCOUNT`): about 12 KB per day with under 1% error, and daily sketches can be merged into weekly counts. An exact set would take gigabytes.

Q: How can a database avoid disk reads for keys that don't exist?

A: A Bloom filter per data file: if it says "definitely not here", skip the file. Only "probably yes" answers cost a disk read.

TL;DR

Bloom filter: set membership with false positives only. HyperLogLog: distinct counts in kilobytes. Count-min sketch: approximate frequencies. Merkle tree: find differences between large datasets by comparing hashes top-down.

Unique ID generation

What it is

Every order, user, message and photo needs an **ID** that is unique. On one database this is easy; across many servers and databases, generating unique IDs without them checking with each other is a design problem of its own. Nice extra properties: IDs that sort roughly by creation time (good for database indexes and "newest first" queries), short IDs (64 bits fits a standard integer column), and IDs that don't leak business information.

Types

Auto-increment (database sequence). The database hands out 1, 2, 3, ... Simple, short and ordered. Problems: one database becomes a bottleneck and single point of failure; after sharding, two shards would both issue ID 1000 (workarounds: each shard steps by the number of shards, so shard 1 issues 1, 3, 5 and shard 2 issues 2, 4, 6, or a central ticket server like Flickr used); and sequential IDs reveal volume (a competitor can see you got 500 orders today) and let attackers guess other users' URLs.


UUID (universally unique identifier). A 128-bit value, usually written as 36 characters like `550e8400-e29b-41d4-a716-446655440000`. Any machine can generate one with no coordination.

- **UUIDv4** is 122 random bits. The chance of a collision is negligible (you'd need billions of IDs per second for decades). Downside: random order scatters inserts across a B-tree index, causing more page splits and cache misses, and 128 bits is twice the size of a 64-bit integer.
- **UUIDv7** (standardised in RFC 9562, 2024) puts a millisecond timestamp in the first 48 bits and randomness after, so IDs are unique **and** sort by time, fixing the index problem. A good modern default. (**ULID** is a similar earlier format.)

Snowflake ID. Twitter's 2010 design for 64-bit, time-sortable IDs generated independently by many machines. The 64 bits are split:

Bits	Field	Meaning
1	sign	always 0
41	timestamp	milliseconds since a custom epoch, lasts about 69 years
10	machine ID	up to 1,024 generators
12	sequence	up to 4,096 IDs per machine per millisecond

So each machine can create about 4 million IDs per second with no coordination, and IDs sort by time. Requirements: each machine needs a unique machine ID (assigned through config or a coordination service like ZooKeeper), and clocks must not go backwards (if they do, the generator waits or refuses). Discord, Instagram (a variant generated inside PostgreSQL shards) and many others use Snowflake-style IDs. Sonyflake and others change the bit split.



Other approaches. Segment / range allocation: a central service hands each server a block of 1,000 IDs at a time, so servers rarely talk to it. **Hashing** (for example for URL shorteners, Part 6) derives a short ID from content, with collision checks.

In the interview

Q: How would you generate unique IDs for a sharded system with high write volume?

A: Snowflake-style 64-bit IDs: timestamp, machine ID and per-millisecond sequence. No coordination per ID, roughly time-ordered, fits a BIGINT (64-bit integer) column. If 128 bits is fine, UUIDv7 gives the same ordering with no machine IDs to manage.

Q: Why not just use UUIDv4?

A: It works and needs no coordination, but random IDs fragment B-tree indexes and are larger. Time-ordered IDs (UUIDv7, Snowflake) insert at the end of the index.

TL;DR

Auto-increment is simple but centralised and guessable; UUIDs need no coordination (v7 also sorts by time); Snowflake packs time, machine and sequence into 64 sortable bits.

Geospatial indexing: geohash and quadtree


What it is

"Find restaurants within 2 km" or "find drivers near me" can't be answered efficiently with a normal index on latitude and longitude, because a B-tree index sorts by one value at a time. **Geospatial indexes** turn 2D locations into something you can search quickly.

Types

Geohash. Divide the world map in half by longitude, then by latitude, and keep halving, writing down a bit for which half you're in at each step. The bits are encoded in base-32 letters and digits. Longer strings mean smaller boxes: a 5-character geohash is a cell roughly 5 km x 5 km, 6 characters roughly 1.2 km x 0.6 km. Places that share a prefix are near each other (`gcpvj` and `gcpvm` are side-by-side cells in central London), so "nearby" becomes a **prefix search** on a normal string index. To avoid missing places just over a cell edge, you search the target cell plus its 8 neighbours. Redis's `GEOADD` / `GEOSEARCH` and Elasticsearch support geohash-style indexing.

Quadtree. A tree where each node covers a rectangle of the map. When a node holds too many points (say more than 100 businesses), it splits into four children (north-west, north-east, south-west, south-east). Dense cities get small, deep cells; empty oceans stay as one big cell. To find nearby places, walk down to the leaf containing the user and look at it and its neighbours. Quadtrees adapt to uneven density better than fixed-size geohash cells and are typically kept in memory.



Others you'll hear: **R-tree** (bounding-box tree used by PostGIS), Google's **S2** (cells on a sphere, used in Google Maps and by MongoDB) and Uber's **H3** (a grid of hexagons, good for ride-demand heatmaps because every neighbour is the same distance away).

In the interview

Q: How do you find drivers near a rider?

A: Drivers send locations every few seconds; store them in an in-memory geo index (geohash cells in Redis, or a quadtree) keyed by cell. Query the rider's cell and its neighbours, then compute exact distances for the handful of candidates.

TL;DR

Geohash turns locations into strings where a shared prefix means nearby; a quadtree splits the map into four recursively where it's dense. Both turn "what's near me?" into a fast lookup.

Part 4 glossary

Term	Meaning in one line
Cache	Small, fast store holding copies of data from a slower source
Source of truth / origin	The authoritative home of the data, usually a database
Cache hit / miss	Requested item was / was not found in the cache
Hit ratio	Fraction of lookups served by the cache
TTL (time to live)	How long an entry may live before it expires
Stale data	A cached or replicated copy older than the latest write
Warm / cold cache	Cache already full of hot data / empty and missing a lot
Cache-Control, ETag	HTTP headers controlling browser/CDN caching and validating versions
Cache busting	Changing a file name or URL when content changes so old copies aren't used
In-process cache	Cache inside the application's own memory
Distributed cache	Shared cache cluster reached over the network (Redis, Memcached)
Redis	In-memory key-value server with rich data types, often used as a cache
Memcached	Simple, fast, multi-threaded in-memory key-value cache
Buffer cache / buffer pool	Database's own in-memory copy of recently used disk pages
Page cache	Operating system's RAM cache of recently read file data
Cache-aside (lazy loading)	App checks cache, loads from DB on miss, deletes key on write
Read-through	Cache loads from the DB itself on a miss
Write-through	Writes go to cache and DB synchronously
Write-behind / write-back	Writes go to cache, flushed to DB later
Write-around	Writes skip the cache and go only to the DB
Refresh-ahead	Cache reloads hot entries before they expire
Negative caching	Caching "not found" results for a short time
Eviction policy	Rule for what to remove when the cache is full
LRU / LFU / FIFO	Evict least recently used / least frequently used / oldest inserted
Cache invalidation	Removing or updating cached copies when the source changes
Versioned keys	Putting a version in the cache key so new writes use new keys
Change data capture (CDC)	Streaming a database's changes from its log to other systems
Cache stampede / thundering herd	Many simultaneous misses on one key overloading the DB
Request coalescing / single flight	Letting only one request rebuild a missing key
Lease (cache)	Token granting one client the right to refill a key
Stale-while-revalidate	Serve the expired value while refreshing in the background
TTL jitter	Randomising TTLs so keys don't expire together
Cache avalanche	Mass expiry or cache loss sending all traffic to the DB
Cache penetration	Requests for non-existent keys always hitting the DB

Term	Meaning in one line
Hot key	One key so popular it overloads the node that holds it
Message queue	Broker that holds messages until consumers process them
Producer / consumer / broker	Sender / processor / storage middleman of messages
Asynchronous processing	Doing work later without the caller waiting for it
Decoupling	Letting components work without knowing about each other directly
Load levelling	Using a queue to smooth spikes into a steady processing rate
Acknowledgement (ack)	Consumer's signal that a message is done and can be removed
Visibility timeout	Time a received message is hidden before being redelivered (SQS)
Point-to-point / competing consumers	Each message processed by one of many workers
Publish/subscribe (pub/sub)	Each message delivered to every subscriber of a topic
Topic	Named channel or stream of messages
Exchange	RabbitMQ component that routes messages to queues
Claim check	Store a big payload elsewhere and send only its reference
Queue depth	Number of messages waiting in a queue
Event streaming / log-based broker	Broker keeping an ordered, replayable log of events (Kafka)
Partition (stream)	Ordered sub-log of a topic, the unit of parallelism
Message key	Value hashed to pick a partition, keeping related events ordered
Offset	Position number of a message in a partition
Consumer group	Consumers sharing a topic's partitions for one application
Committed offset	Saved position a consumer group has processed up to
Rebalance	Reassigning partitions when group membership changes
Consumer lag	How far a consumer is behind the newest message
Retention	How long a log keeps messages
At-most-once	Delivered zero or one times, may be lost
At-least-once	Delivered one or more times, may be duplicated
Exactly-once / effectively-once	Each message affects the result once, via de-duplication
Idempotency	Doing an operation twice has the same effect as once
Idempotency key	Unique ID per operation used to detect and skip repeats
Upsert	Insert a row or update it if it already exists
Idempotent producer	Producer whose duplicate sends the broker discards
Exponential backoff	Waiting longer after each failed retry
Jitter	Random variation added to waits or TTLs
Poison message	A message that fails every time it's processed
Dead-letter queue (DLQ)	Side queue for messages that failed too many times
Redrive	Moving DLQ messages back to the main queue
Backpressure	Downstream signalling upstream to slow down

Term	Meaning in one line
Load shedding	Dropping some work on purpose to stay alive under overload
Batch processing	Processing a bounded pile of data in one scheduled job
Stream processing	Processing events continuously as they arrive
MapReduce	Batch model of map, shuffle and reduce across many machines
Window (streaming)	Time range grouping events, e.g. tumbling or sliding
Event time / processing time	When an event happened / when it was processed
Watermark	Stream engine's estimate that all events up to a time have arrived
Lambda / Kappa architecture	Batch plus speed layer / stream-only with replay
Event-driven architecture	Services reacting to published events instead of direct calls
Event vs command	Fact that happened vs request that something happen
Dual write problem	Updating DB and broker separately, risking disagreement
Transactional outbox	Writing events to an outbox table in the same DB transaction
Event sourcing	Storing the sequence of events as the source of truth
Snapshot (event sourcing)	Saved state to avoid replaying every event
CQRS	Separate models for writes (commands) and reads (queries)
Projection / read model	Read-optimised view built from events
Consistency model	Promise about what reads can return after writes
Linearizability / strong consistency	System behaves as if there were one copy, in real-time order
Sequential consistency	Everyone sees the same order, not necessarily real time
Causal consistency	Causes are always seen before their effects
Read-your-writes	A user always sees their own changes
Monotonic reads	A user never sees data go back in time
Monotonic writes	A user's writes apply in the order made
Eventual consistency	Replicas converge if writes stop, no time bound
CAP theorem	Under a partition, choose consistency or availability
Network partition	Network failure splitting nodes into groups that can't talk
CP / AP	Refuses requests to stay consistent / answers with maybe-stale data
PACELC	If partition: A or C, else: latency or consistency
Quorum	Minimum number of replicas that must take part in an operation
N, R, W	Replica count, read quorum, write quorum
R + W > N	Condition for read and write sets to overlap
Majority quorum	More than half the nodes
Read repair	Fixing stale replicas noticed during a read
Anti-entropy	Background process comparing and syncing replicas
Sloppy quorum / hinted handoff	Temporarily writing to stand-in nodes that hand data back later
Consensus	Getting nodes to agree on a value despite failures

Term	Meaning in one line
Paxos	First widely known proven consensus algorithm
Raft	Consensus algorithm designed to be understandable
Leader / follower / candidate	Raft node roles
Term / epoch	Number that increases with each new leader
Election timeout	Time without heartbeats before a follower starts an election
Leader election	Choosing one node to act as leader
Split brain	Two nodes both acting as leader
Coordination service	System like etcd, ZooKeeper or Consul for consensus-backed coordination
Distributed lock	Lock that works across machines
Lease	Lock or role that automatically expires after a time
Fencing token	Increasing number that lets storage reject stale lock holders
Clock skew	Difference between two machines' clocks
Clock drift	A clock gradually running fast or slow
NTP	Protocol for synchronising clocks with time servers
Wall clock / monotonic clock	Time of day (can jump) / always-forward timer for durations
Last-write-wins (LWW)	Conflict rule keeping the write with the highest timestamp
Logical clock	Counter-based ordering of events without real time
Lamport clock	Single counter consistent with causality
Vector clock / version vector	Per-node counters that also detect concurrent events
Hybrid logical clock	Timestamp mixing wall time with a logical counter
TrueTime	Spanner's clock API returning a bounded time interval
Distributed transaction	Change spanning several databases or services, all or nothing
Two-phase commit (2PC)	Prepare then commit across participants via a coordinator
Coordinator / participant	Runner of 2PC / database taking part in it
Saga	Sequence of local transactions with compensations on failure
Compensating transaction	Action that semantically undoes an earlier step
Choreography / orchestration	Saga steps triggered by events / by a central controller
Heartbeat	Periodic "I'm alive" message
Failure detection	Deciding whether a node is probably dead
False positive (failure)	Declaring a slow but alive node dead
Flapping	Node repeatedly marked dead and alive
Gossip protocol	Nodes spreading state to random peers each round
Phi accrual detector	Failure detector giving a suspicion level, not yes/no
SWIM	Gossip membership protocol with indirect pings
Bloom filter	Set membership test with false positives but no false negatives
Hash function	Function mapping any input to a fixed-size number

Term	Meaning in one line
HyperLogLog	Distinct-count estimator using kilobytes of memory
Cardinality	Number of distinct items
Count-min sketch	Fixed-size table estimating item frequencies
Heavy hitters	The most frequent items in a stream
Merkle tree	Tree of hashes for detecting where datasets differ
Root hash	Top hash of a Merkle tree, summarising all data
Auto-increment / sequence	Database-generated increasing integer IDs
Ticket server	Central service issuing unique IDs
UUID	128-bit identifier generated without coordination
UUIDv4 / UUIDv7	Random UUID / time-ordered UUID
ULID	Time-sortable 128-bit ID format
Snowflake ID	64-bit ID of timestamp, machine ID and sequence
Geospatial index	Index for searching by location
Geohash	String encoding of a map cell, shared prefix means nearby
Quadtree	Tree splitting map regions into four as density grows
R-tree / S2 / H3	Bounding-box tree / sphere cells / hexagon grid geo indexes

Part 5 — Architecture, reliability, operations and security

Parts 1 to 4 covered the building blocks: servers, networks, databases, caches and queues. This part is about how you arrange those blocks into a whole system, how you keep that system running when pieces break, how you ship changes to it safely, how you see what it is doing, and how you stop the wrong people from getting in. These are the topics that separate "it works on my laptop" from "it has served a billion requests this month and nobody noticed when a data centre lost power".

Architectural styles: monolith, modular monolith, SOA, microservices and serverless

What it is

An **architectural style** is the big-picture answer to "how is our code split into running programs, and how do those programs talk?". Think of a restaurant. One chef can cook every dish in one kitchen (a monolith). A big kitchen can be divided into stations, grill, pastry, salad, each with its own cook but still one kitchen (a modular monolith). A food court has independent stalls, each with its own staff, menu and till, and customers walk between them (microservices). A catering agency that sends a cook only when an order comes in, and bills you per dish, is serverless.

- **Monolith**: the whole application (user accounts, product catalogue, checkout, emails) is one codebase, built into one deployable program, usually sharing one database. You run several identical copies behind a load balancer to scale.
- **Modular monolith**: still one deployable program, but the code is split into modules with strict boundaries (the checkout module may only call the catalogue module through a defined interface, never reach into its tables). It gives most of the tidiness of microservices without the network.
- **Service-oriented architecture (SOA)**: a 2000s-era style where large enterprise systems were split into services that talked through a central **enterprise service bus (ESB)**, a piece of middleware

that routed, transformed and orchestrated messages. Services were often coarse (a whole "billing system") and shared data models.


- **Microservices**: the application is split into many small services, each owning one business capability (for example "payments" or "search"), each with its **own database**, deployed independently, and talking over the network using HTTP/REST, gRPC or messages. "Smart endpoints, dumb pipes": the logic lives in the services, not in a central bus.
- **Serverless / Function as a Service (FaaS)**: you upload individual functions; the cloud provider runs them only when an event arrives (an HTTP request, a file upload, a queue message), scales them automatically from zero to thousands of copies, and bills per invocation and per millisecond of run time. You never manage a server. Examples: AWS Lambda, Google Cloud Functions, Azure Functions, Cloudflare Workers. "Serverless" also loosely covers managed services you never size yourself, such as DynamoDB or S3.

Why it matters

The style decides how fast teams can move, how failures spread, how much the system costs and how hard it is to debug. A five-person startup and a 2,000-engineer company need different answers. **Conway's law** says a system's structure ends up mirroring the communication structure of the organisation that builds it, so architecture is partly a decision about teams.

How it works

A request in a monolith is a chain of in-process function calls: `checkout()` calls `reserveStock()` calls `chargeCard()`, each taking nanoseconds to microseconds and all inside one database transaction. The same request in microservices becomes network calls: the checkout service sends an HTTP request to the inventory service (about 0.5 to 2 ms inside one data centre) and another to the payment service, and there is no single transaction covering both, so you need patterns like sagas (Part 4) to undo work if a later step fails.



Types

Style	Deploy unit	Data	Best for
Monolith	One app	One shared DB	Small teams, new products
Modular monolith	One app, strict modules	One DB, owned schemas	Growing teams wanting order
SOA	Coarse services + ESB	Often shared	Legacy enterprise integration
Microservices	Many small services	DB per service	Many teams, independent scaling
Serverless (FaaS)	Single functions	Managed stores	Spiky or event-driven work

Trade-offs

- **Monolith**: simple to build, test, deploy and debug; one stack trace shows everything; transactions are easy. But as it grows past a few hundred thousand lines and dozens of developers, builds slow down, one bad change can take everything down, and you must scale the whole thing even if only search is busy.
- **Microservices**: teams deploy independently many times a day, each service scales and fails on its own, and each can pick its own language or database. The price is the **distributed systems tax**: network calls fail and add latency, data is spread across databases so consistency is harder, you need service discovery, tracing, per-service CI/CD and on-call, and a single user action may touch 20 services.
- **Serverless**: zero servers to manage, scales to zero so idle costs nothing, scales up in seconds. Downsides: **cold starts** (the first call to a fresh copy waits for the runtime to load, from about 100 ms to a few seconds), execution time limits (AWS Lambda caps a single run at 15 minutes), harder local testing, vendor lock-in, and at steady high load it is often more expensive than always-on servers.

Common mistakes

- Starting a new product with 30 microservices. You do not yet know where the boundaries are, and you pay the tax from day one. The common advice is "monolith first", split later.
- A **distributed monolith**: services that must all be deployed together, share one database or call each other synchronously in long chains. You pay the network and operations bill of microservices while still moving in lockstep like a monolith.
- Splitting by technical layer ("database service", "UI service") instead of business capability.
- Thinking microservices are faster. A network hop is thousands of times slower than a function call.

Real-world examples

- **Shopify** runs one of the largest Ruby on Rails monoliths and deliberately chose a modular monolith, enforcing component boundaries with tooling, instead of breaking it into microservices.
- **Netflix** and **Amazon** are the classic microservices stories; Uber has written about running around 2,200 critical microservices and then grouping them into "domains" to tame the complexity.
- In 2023 the **Amazon Prime Video** team publicly described moving an audio/video quality-monitoring tool from a distributed serverless design (AWS Step Functions plus Lambda) into a single process running as one container task, cutting that tool's infrastructure cost by more than 90%. The lesson: pick the style per workload.
- The **strangler fig pattern** is how most companies migrate: put a proxy in front of the monolith and move one feature at a time into a new service until the old code can be deleted.

In the interview

Q: Would you start this design with microservices?

A: Usually no. I would start with a well-modularised monolith, then extract a service when there is a clear reason: a part that needs to scale independently, a team that needs to deploy on its own schedule, or a component with very different reliability needs.

Q: What does "database per service" buy you and what does it cost?

A: It lets each team change its schema and scale its store without coordinating with others, and stops one service's bad query from hurting another. It costs you cross-service joins and transactions: you need APIs, events and sagas, and you accept eventual consistency between services.

Q: When is serverless a good fit?

A: Spiky or unpredictable, event-driven work such as image thumbnails on upload, webhooks or nightly jobs, where scaling to zero saves money. It is a poor fit for long-running jobs, latency-critical paths that cannot tolerate cold starts, or steady high traffic.

TL;DR

Monoliths are simple and fast to start; microservices trade simplicity for team independence and independent scaling; serverless trades control for zero operations. Choose by team size and workload, not fashion.

Synchronous vs asynchronous communication

What it is

When one service needs another, it can either **wait for the answer** or **leave a message and carry on**. A phone call is synchronous: you speak, you wait, you get a reply. A text message is asynchronous: you send it and continue your day; the reply comes whenever it comes.


- **Synchronous**: service A calls service B (REST, gRPC) and blocks until B responds or a timeout fires. The caller needs the answer to continue.
- **Asynchronous**: A puts a message on a queue or event stream (Part 4) and returns immediately. B processes it later. A may get a result through a callback, a webhook or by checking a status endpoint.

Why it matters

A synchronous chain ties the callers' fate to the callee: if B is slow or down, A is slow or down. Availability multiplies, too. If a request must pass through five services that are each 99.9% available, the chain is at best 0.999^5, about 99.5%, which is roughly 44 hours of downtime a year instead of 9. Asynchronous messaging breaks that chain: if the email service is down, orders still succeed and the emails go out when it recovers.

How it works

1. User clicks "Place order". The order service must check the card synchronously because the user is waiting for "approved" or "declined".
2. Once the order is saved, the order service publishes an `OrderPlaced` event to a queue and replies to the user in, say, 200 ms.
3. Email, analytics and warehouse services each consume the event at their own pace. If the warehouse system is down for ten minutes, events wait in the queue.



Trade-offs

	Synchronous	Asynchronous
Simplicity	Easy to reason about	Harder: eventual results
Coupling	Tight in time	Loose
Latency for user	Sum of all calls	Only the critical path
Failure spread	Cascades	Absorbed by the queue
Debugging	One request, one trace	Needs correlation IDs

Common mistakes

- Making every call synchronous "because it is simpler", building deep call chains.
- Using async for something the user must see immediately (like "is my payment approved?") and then building awkward polling.
- Forgetting that async consumers must be idempotent, because queues usually deliver at least once.

In the interview

Q: How do you decide sync vs async between two services?

A: Ask whether the caller needs the result to answer the user right now. If yes, call synchronously with a timeout. If the work can finish later (notifications, analytics, search indexing), publish an event so failures and slowness do not reach the user.

Q: How do you tell the user about an async job's result?

A: Return a job ID immediately (HTTP 202 Accepted), then let the client poll a status endpoint, or push the result with WebSockets, server-sent events or a webhook.

TL;DR

Synchronous calls are simple but chain failures and latency together; asynchronous messages decouple services in time at the cost of eventual results and harder debugging.

Service discovery, sidecars and service mesh

What it is

In a system with many services, each running many copies that start and stop all the time, a caller needs to know "which IP addresses currently run the payment service?". **Service discovery** answers that.

It is like a hospital switchboard: you ask for "cardiology" rather than memorising which doctor is on shift today.

- **Service registry**: a database of live service instances and their addresses. Instances **register** when they start, send **heartbeats** to say they are alive, and are removed when they stop or miss heartbeats. Examples: Consul, etcd, ZooKeeper, Netflix Eureka, and the built-in registry inside Kubernetes.
- **Sidecar**: a helper process deployed right next to each service instance (in the same pod or host) that handles cross-cutting jobs such as networking, TLS, retries, logging. Like a motorbike sidecar, it rides alongside and goes everywhere the main process goes.
- **Service mesh**: a fleet of sidecar proxies, one per service instance, that intercept all service-to-service traffic, plus a **control plane** that configures them all. The sidecars form the **data plane**. Examples: Istio and Linkerd; Envoy is the most common sidecar proxy.

Why it matters


Hard-coding IP addresses breaks the moment autoscaling adds a machine or a container is rescheduled. And every service needs the same plumbing (timeouts, retries, encryption between services, metrics); writing it into every codebase in every language is slow and inconsistent. A mesh moves that plumbing out of application code.

How it works

1. A new payment-service instance starts on `10.0.3.17:8080` and registers itself in the registry.
2. The registry health-checks it every few seconds.
3. The checkout service wants to call payments. It either asks the registry itself or goes through a router that asks for it.
4. The call goes to one healthy instance. If that instance dies, it misses heartbeats and is removed, usually within seconds.

Types

- **Client-side discovery**: the caller queries the registry, gets the list of instances and picks one with its own load-balancing logic. Fewer hops, but every client needs a discovery library. Netflix Eureka with the Ribbon client library worked this way.
- **Server-side discovery**: the caller sends the request to a fixed address (a load balancer or router), which looks up the registry and forwards it. Clients stay simple. AWS load balancers with target groups and Kubernetes Services work this way.
- **DNS-based discovery**: the registry publishes instances as DNS records (Consul and Kubernetes both do), so any program can find a service by a name such as `payments.default.svc.cluster.local`. Simple, but DNS caching can leave stale addresses.



Trade-offs

A service mesh gives you, without code changes, mutual TLS (both sides prove their identity with certificates) between all services, uniform retries and timeouts, traffic splitting for canary releases and per-call metrics and traces. It costs an extra proxy hop on each side of every call (usually well under a millisecond, but not zero), extra memory and CPU per pod, and a complex control plane your team must understand when things go wrong. For ten services it is often overkill.

Common mistakes

- Running a registry with no health checks, so dead instances keep receiving traffic.
- Adopting a full service mesh before you have the operational skills to debug it.
- Configuring retries both in application code and in the mesh, multiplying retries (see the next section).

In the interview

Q: Client-side or server-side discovery?

A: Server-side keeps clients thin and language-neutral, so it is the usual default, especially on Kubernetes. Client-side saves a hop and gives the caller control over load balancing, which matters at very high call rates.

Q: What is a service mesh in one sentence?

A: A sidecar proxy beside every service instance that handles service-to-service networking (discovery, load balancing, mTLS, retries, metrics), all configured centrally by a control plane.

TL;DR

Service discovery is a live phone book of service instances; a sidecar is a helper process beside each instance; a service mesh is a centrally managed fleet of sidecars that handles networking for you.

Timeouts, retries, exponential backoff and jitter

What it is

- A **timeout** is the maximum time a caller will wait for a response before giving up. Like hanging up after the phone rings 10 times.
- A **retry** is trying the same request again after a failure, in case the failure was temporary (a **transient fault**, such as a dropped packet or a server that was restarting).
- **Exponential backoff** means waiting longer after each failed attempt, doubling the wait: 100 ms, 200 ms, 400 ms, 800 ms, up to a cap.
- **Jitter** means adding randomness to that wait so that thousands of clients do not all retry at exactly the same moment.

Why it matters

Without a timeout, a caller waiting on a dead service holds a thread, a connection and memory forever; soon it runs out and dies too. That is how one slow service takes down everything upstream, a **cascading failure**. Retries turn many transient failures into successes, but careless retries are dangerous: if a struggling service gets every request three times, its load triples exactly when it is weakest. This is a **retry storm**.

How it works

Setting a timeout. Base it on the callee's measured latency, not a guess. If payment calls have a p99 of 300 ms, a timeout around 500 ms to 1 s is sensible. Use a **deadline** across the whole request: if the user-facing budget is 2 s and 1.5 s has already gone, the next call gets at most 0.5 s. gRPC propagates deadlines between services for exactly this reason.

Retrying safely.

1. Retry only errors that may be temporary: timeouts, connection resets, HTTP 502/503/504, HTTP 429 (after the `Retry-After` delay). Never retry 400 Bad Request or 403 Forbidden; they will fail again.
2. Retry only **idempotent** operations (doing them twice has the same effect as once), or make them idempotent with an idempotency key (Part 4). Retrying "charge card $50" without a key can charge twice.
3. Limit attempts, typically 2 to 3 retries in total.
4. Wait with exponential backoff and jitter between attempts.

5. Retry at one layer only. If the browser, gateway, service A and service B each make up to 3 attempts, one user click can become 3 x 3 x 3 x 3 = 81 calls to the database.

Backoff with jitter. With "full jitter", the wait before attempt n is a random number between 0 and `min(cap, base * 2^n)`.

```
base = 100 ms, cap = 10 s
attempt 1: wait random(0, 200 ms)
attempt 2: wait random(0, 400 ms)
attempt 3: wait random(0, 800 ms)
```

Without jitter, 10,000 clients that failed at the same second all retry at exactly +100 ms, then +200 ms, in synchronised waves. With jitter, their retries spread across the window and the server sees a smooth trickle.

A **retry budget** is a further guard: allow retries to add at most, say, 10% extra load. If more than 10% of calls are already retries, stop retrying and fail fast.

Trade-offs

Short timeouts free resources quickly but may cut off requests that would have succeeded; long ones risk resource exhaustion. More retries improve success rates for rare blips but amplify load during real outages. **Hedged requests** (sending a second copy to another replica if the first has not answered by the p95 time, and taking whichever answers first) cut tail latency at the cost of a few percent extra load.

Common mistakes

- No timeout at all. Many HTTP client libraries default to waiting forever or for minutes.
- A caller timeout shorter than the callee's, so the callee keeps working on an answer nobody will read.
- Retrying non-idempotent writes.
- Retrying immediately in a tight loop.

Real-world examples

AWS SDKs retry throttled and transient errors with exponential backoff and jitter by default, and the AWS Architecture Blog popularised the "full jitter" formula. Google's **Site Reliability Engineering (SRE)** book describes per-client retry budgets to prevent retry storms.

In the interview

Q: Why add jitter to backoff?

A: To break synchronisation. When many clients fail together, plain backoff makes them retry together in waves that knock the service over again. Random jitter spreads them out.

Q: Where should retries live in a deep call chain?

A: At one layer, ideally close to the user or at the edge of each service boundary, with a small attempt limit, so retries do not multiply across layers.

TL;DR

Always set timeouts; retry only transient failures on idempotent operations, a few times, with exponential backoff plus random jitter, at a single layer.

Circuit breakers, bulkheads and fallbacks

What it is

- A **circuit breaker** is a wrapper around calls to a dependency that "trips" after too many failures and then fails calls instantly for a while instead of waiting on a broken service. It is named

after the electrical breaker in your house that cuts power when a wire overloads, protecting the rest of the house.

- A **bulkhead** isolates resources so one failing part cannot consume everything. Ships are divided into watertight compartments (bulkheads) so a hole floods one compartment, not the whole hull.
- A **fallback** is what you do instead when a call fails: return cached data, a default, or a reduced answer.


Why it matters

Suppose a recommendation service hangs. Every product page waits 2 seconds for its timeout. Web server threads pile up waiting, the thread pool fills, and now product pages, which could have rendered without recommendations, fail too. A circuit breaker notices recommendations are broken and stops calling them; a bulkhead makes sure recommendation calls can only use, say, 20 of the 200 threads; a fallback shows "popular items" instead.

How it works

A circuit breaker has three states.

1. **Closed** (normal): calls pass through. The breaker counts failures in a rolling window, for example the last 100 calls or last 10 seconds.
2. If failures exceed a threshold (say 50% of at least 20 calls), it moves to **Open**: every call fails immediately with an error or goes straight to the fallback, without touching the dependency. This gives the dependency time to recover and frees the caller's threads.
3. After a cool-down (say 30 seconds) it moves to **Half-open**: it lets a few trial calls through. If they succeed, it returns to Closed. If they fail, back to Open for another cool-down.



Bulkheads in practice: separate thread pools or connection pools per dependency, separate queues per customer tier, separate clusters for internal batch jobs and user-facing traffic, or **cell-based architecture**, where users are split into independent copies of the whole stack ("cells") so a bad deploy or poison request only affects one cell's users.

Fallback options: a cached last-known value, a static default ("free shipping info unavailable"), a simpler algorithm, an empty section of the page, or queueing the work to finish later.

Trade-offs

Breakers add a little state and configuration per dependency, and thresholds tuned badly either trip on normal noise or never trip. Bulkheads waste some capacity, because a reserved pool sits idle even when another is overloaded. Fallbacks give users stale or partial data, which is fine for recommendations but not for a bank balance.

Common mistakes

- Using a fallback that calls another fragile service, which then fails too.
- One global breaker for a dependency with many endpoints, so one bad endpoint blocks healthy ones.
- Never testing the open state, so the fallback code path has a bug nobody has seen.

Real-world examples

Netflix popularised circuit breakers with its Hystrix library (now in maintenance mode); Resilience4j is the common Java successor, and service meshes such as Istio offer breakers and outlier ejection at the proxy. Amazon describes cell-based architectures to limit the "blast radius" of failures.

In the interview

Q: Explain the half-open state.

A: After the breaker has been open for a cool-down period, it lets a small number of test requests through. Success closes the breaker and resumes normal traffic; failure re-opens it. It is how the breaker discovers that the dependency has recovered without flooding it.

Q: How would you stop a slow non-critical service from taking down your homepage?

A: Tight timeout on the call, a circuit breaker around it, a separate small thread pool (bulkhead) for it, and a fallback such as cached or default content, so the page renders without that section.

TL;DR

A circuit breaker stops calling a failing dependency (Closed, Open, Half-open); a bulkhead caps how many resources any one dependency can consume; a fallback gives a degraded answer instead of an error.

Rate limiting and throttling

What it is

Rate limiting caps how many requests a client may make in a time window, for example 100 requests per minute per user. **Throttling** is often used as a synonym; strictly, throttling slows requests down (delays or queues them) while rate limiting rejects the excess. A nightclub bouncer who lets in only 50 people per hour is rate limiting; one who makes people wait in line until there is room is throttling.

Why it matters

- **Protection**: stops one buggy script or abusive client from overwhelming the service for everyone.
- **Fairness**: each customer gets a fair share.
- **Cost control**: expensive operations (sending SMS, calling a paid AI model) cannot run away.
- **Security**: slows brute-force password guessing and scraping.
- **Business tiers**: free plan 1,000 calls per day, paid plan 100,000.

How it works

When a client exceeds its limit, the server returns **HTTP 429 Too Many Requests**, ideally with a `Retry-After` header saying how many seconds to wait. Many APIs also send headers so clients can pace themselves:

```
HTTP/1.1 429 Too Many Requests
Retry-After: 30
X-RateLimit-Limit: 5000
X-RateLimit-Remaining: 0
X-RateLimit-Reset: 1767225600
```

The limit is applied per **key**: user ID, API key, IP address, or a combination such as (user, endpoint).

Types

Algorithms.


- **Token bucket**: a bucket holds up to B tokens and is refilled at R tokens per second. Each request takes one token; if the bucket is empty, the request is rejected. It allows short **bursts** up to B, then a steady rate R. Example: B = 10, R = 1 per second lets a user fire 10 requests at once, then one per second. Only two numbers per key (token count, last refill time), so it is cheap. The most widely used algorithm.
- **Leaky bucket**: requests enter a queue (the bucket) and leave at a fixed rate, like water dripping from a hole. If the bucket is full, new requests are dropped. It smooths bursts into a perfectly steady outflow, good for protecting a downstream that cannot handle bursts, but adds queueing delay.
- **Fixed window counter**: count requests in each calendar window (12:00:00 to 12:00:59). Reset at the boundary. Very simple, one counter per key, but a client can send the full limit at 12:00:59 and again at 12:01:00, doubling the rate across the boundary.
- **Sliding window log**: store the timestamp of every request; on each new request, drop timestamps older than the window and count the rest. Exact, but stores one entry per request, which is memory-hungry at high limits.
- **Sliding window counter**: keep counters for the current and previous fixed windows and estimate the sliding count as `current + previous x (fraction of previous window still inside the sliding window)`. If the limit is 100 per minute, we are 15 s into the current minute with 30 requests, and the previous minute had 80, the estimate is 30 + 80 x 0.75 = 90, so the request is allowed. Nearly as accurate as the log with the memory of fixed windows.

Algorithm	Allows bursts	Memory per key	Accuracy
Token bucket	Yes, up to B	Tiny	Good
Leaky bucket	No, smooths	Queue size	Good
Fixed window	Yes, 2x at edges	Tiny	Rough
Sliding log	No	One entry per request	Exact
Sliding counter	Little	Two counters	Very good

Where to rate limit.

- **Client side**: polite clients self-limit, but you cannot trust them.
- **Edge / CDN / WAF**: block floods by IP before they reach you (Cloudflare, AWS WAF rate rules).
- **API gateway or load balancer**: the common place for per-API-key limits.
- **Inside each service**: protects the service itself, for example limiting calls to an expensive endpoint.
- **In front of a fragile dependency**: an outbound limiter so you never exceed a partner API's quota.

Distributed rate limiting. With 20 gateway servers, each must see the same count. The usual answer is a shared fast store such as Redis, with an atomic increment-and-check (often a small Lua script so the read and write happen in one step). To avoid a Redis call on every request, some systems give each node a local share of the limit and sync periodically, accepting slight inaccuracy.



Trade-offs

Strict, globally exact limits need a central store on the hot path (added latency, a dependency that can fail). Local per-node limits are fast but approximate. If the limiter's store is down, you must choose **fail open** (allow traffic, risk overload) or **fail closed** (reject traffic, guaranteed outage); most choose fail open for user traffic.

Common mistakes

- Limiting only by IP address, which punishes many users behind one corporate NAT and is dodged by attackers with many IPs.
- Returning 500 or 503 instead of 429, so clients do not know to back off.
- Forgetting to tell clients their remaining quota.

Real-world examples

GitHub's REST API allows 5,000 requests per hour for an authenticated user and 60 per hour unauthenticated, and reports usage in `x-ratelimit-*` headers. Stripe has written about using token buckets for its API rate limiters. NGINX's `limit_req` module implements a leaky bucket. Cloudflare has described using the sliding window counter approximation at its edge.

In the interview

Q: Design a rate limiter for an API used by millions of users.

A: Token bucket per API key, stored in Redis with an atomic script, enforced at the API gateway. Return 429 with `Retry-After` and rate-limit headers. Shard Redis by key, keep limits in config so they change without deploys, and fail open if Redis is unavailable.

Q: Token bucket vs leaky bucket?

A: Token bucket permits bursts up to the bucket size while enforcing an average rate, which suits APIs. Leaky bucket outputs a constant rate, which suits protecting a downstream that cannot absorb bursts.

TL;DR

Rate limiting caps requests per client per time window and answers excess with 429; token bucket is the default algorithm; enforce it at the edge or gateway with a shared counter store.

Load shedding and graceful degradation

What it is

- **Load shedding** means deliberately rejecting some requests when the system is overloaded so that the rest still succeed. Like an electricity company switching off some neighbourhoods for an hour so the whole grid does not collapse.

- **Graceful degradation** means turning off non-essential features under stress so the core keeps working. An online shop at peak may hide personalised recommendations and reviews but keep search and checkout.

Why it matters

When a server receives more work than it can do, things do not just get a bit slower. Queues grow, every request waits longer, many time out after the server has already done the work, clients retry, and the server ends up spending all its effort on requests nobody is waiting for. Throughput can collapse to near zero. This is **congestion collapse**. Shedding the excess early keeps **goodput** (useful completed work) high.

How it works

1. Measure a sign of overload: CPU above 90%, concurrent in-flight requests above a limit, queue wait time above, say, 100 ms.
2. When overloaded, reject new low-priority requests immediately and cheaply with 503 Service Unavailable (with `Retry-After`) rather than queueing them.
3. Prioritise: shed background jobs and bots first, then logged-out traffic, and keep checkout and login last.
4. Drop requests that have already waited longer than the client's timeout; working on them is wasted.
5. Combine with degradation flags: a "kill switch" turns off expensive features during an incident.

Backpressure (Part 4) is the cooperative cousin: a consumer signals producers to slow down rather than silently dropping.

Trade-offs

Some users see errors on purpose. But controlled, partial failure beats total failure. The hard parts are picking the right overload signal and making the rejection path cheap: if rejecting a request costs as much as serving it, shedding does not help.

Common mistakes

- Unbounded queues: they hide overload until latency is minutes long.
- Shedding at random, dropping a checkout while serving a crawler.
- No degradation switches, so the only lever during an incident is "add servers and hope".

Real-world examples

Google's SRE book describes per-request criticality levels so overloaded servers shed the least important traffic first. Amazon has written about using in-flight request limits and dropping requests whose callers have already timed out. Netflix serves a generic, non-personalised home page row when its personalisation services are degraded.

In the interview

Q: What happens if traffic is 3x your capacity and autoscaling takes 5 minutes?

A: Without protection, queues grow and the service collapses. I would shed load at the edge by priority with fast 503s, rate limit heavy clients, turn off non-essential features, and serve cached content where possible until new capacity arrives.

TL;DR

When overloaded, reject some work early and cheaply (load shedding) and switch off extras (graceful degradation) so the core stays up.

Autoscaling

What it is

Autoscaling automatically adds servers (or containers, or function copies) when load rises and removes them when it falls. Adding capacity is **scaling out**; removing it is **scaling in**. A supermarket that opens more tills when queues get long and closes them in the quiet afternoon is autoscaling its cashiers. It is the practical form of the **elasticity** introduced in Part 1.

Why it matters

Traffic is rarely flat. A food-delivery app may see 5x more orders at 7 pm than at 3 pm. Without autoscaling you either buy for the peak (and pay for idle machines most of the day) or buy for the average (and fall over at dinner time). In the cloud you pay by the second or hour, so matching capacity to demand saves real money.

How it works

1. Choose a **metric** that tracks load: average CPU utilisation, requests per second per instance, queue length (messages waiting), p95 latency, or a custom business metric.
2. Choose a **target**: for example "keep average CPU at 60%". The headroom (40%) absorbs spikes while new instances boot.
3. A controller checks the metric periodically (Kubernetes' Horizontal Pod Autoscaler checks every 15 seconds by default) and computes the needed count: `desired = current x (current metric / target)`. With 10 instances at 90% CPU and a 60% target, desired = 10 x 90/60 = 15.
4. It launches 5 more instances. They boot, pass health checks and join the load balancer. This takes seconds for containers and roughly 1 to 5 minutes for virtual machines.
5. When load drops, it scales in slowly, after a **cool-down** period (often 5 to 10 minutes), so it does not flap up and down, and it **drains** connections from instances before terminating them.
6. **Minimum and maximum** bounds stop it from scaling to zero by mistake or to 10,000 machines during an attack.

Types

- **Reactive (dynamic) scaling**: responds to current metrics as above. Simple, but always slightly late, because capacity arrives minutes after the spike begins.
- **Scheduled scaling**: scale by the clock. "Every weekday at 08:30 set minimum to 40 instances." Perfect for known patterns such as business hours, a TV ad slot or a ticket sale opening at 10:00.
- **Predictive scaling**: a model learns daily and weekly patterns from history and adds capacity before the forecasted rise. AWS Auto Scaling offers this.
- **Horizontal vs vertical autoscaling**: horizontal adds instances (the common case); vertical gives an instance more CPU or memory (Kubernetes' Vertical Pod Autoscaler), which usually needs a restart.
- **Cluster autoscaling**: in Kubernetes, adds whole machines (nodes) when pods cannot fit on the existing ones.

Trade-offs

Reactive scaling is cheap but lags; keep headroom or combine it with scheduled or predictive scaling. Scaling on CPU is easy but misleading for services that wait on I/O; requests per instance or queue depth is often better. Autoscaling the stateless web tier is easy; databases and other stateful systems scale far more slowly because data must be copied.

Common mistakes

- Scaling the web tier to 200 instances that then exhaust the database's connection limit, moving the bottleneck rather than fixing it.
- Targets set too high (90% CPU), leaving no buffer for the minutes it takes to boot.
- Slow startup (large images, long cache warm-up) making autoscaling useless for sudden spikes.
- No maximum, so a bug or a DDoS attack produces a huge bill.

Real-world examples

AWS EC2 Auto Scaling groups, Google Cloud managed instance groups, Kubernetes Horizontal Pod Autoscaler and KEDA (Kubernetes Event-driven Autoscaling, which scales on event sources such as Kafka consumer lag). Netflix built a predictive autoscaler called Scryer to pre-provision capacity before its daily evening peak.

In the interview

Q: Your service gets a 10x spike every evening at 8 pm. How do you scale?

A: Scheduled or predictive scaling to raise capacity before 8 pm, reactive scaling on requests per instance to handle surprises, and make sure the database, caches and connection pools can handle the higher instance count.

Q: Which metric would you autoscale a queue worker on?

A: Queue depth or consumer lag divided by the rate one worker can process, because CPU does not tell you how far behind you are.

TL;DR

Autoscaling adds and removes capacity based on a metric and a target; reactive is late, scheduled and predictive are early; set min and max bounds and keep headroom.

Virtual machines, containers and Docker

What it is

- A **virtual machine (VM)** is a software-emulated computer. A program called a **hypervisor** (such as KVM, Xen, VMware ESXi, or AWS's Nitro) splits one physical server into several VMs, each with its own complete operating system (its own Linux or Windows kernel). It is like dividing a house into flats, each with its own kitchen, plumbing and front door.
- A **container** is an isolated process (or group of processes) that shares the host machine's operating-system kernel but has its own view of files, network and process list, and its own limits on CPU and memory. It is like rooms in a shared house: private rooms, shared kitchen and plumbing. Linux implements it with **namespaces** (what a process can see) and **cgroups** (how much it can use).
- A **container image** is a packaged, read-only snapshot of an application and everything it needs (runtime, libraries, config defaults). Run the image and you get a container.
- **Docker** is the tool that made containers popular from 2013: a simple file format (the `Dockerfile`) to build images, a way to run them and **registries** (Docker Hub, Amazon ECR) to share them.

Why it matters

"It works on my machine" disappears: the same image runs on a laptop, in testing and in production. Containers start in under a second to a few seconds and use megabytes rather than gigabytes of overhead, so you can pack dozens onto a server and scale them quickly. They are the unit that modern platforms like Kubernetes schedule.


How it works

A tiny Dockerfile for a web service:

```
FROM python:3.12-slim
WORKDIR /app
COPY requirements.txt .
RUN pip install -r requirements.txt
COPY . .
CMD ["gunicorn", "-b", "0.0.0.0:8080", "app:server"]
```

1. `docker build` turns this into an image made of stacked **layers** (base OS files, then the installed libraries, then your code). Unchanged layers are cached, so rebuilding after a code change takes seconds.

2. The image is pushed to a registry with a tag such as `shop-api:1.4.2`.
3. Any server pulls it and runs it as a container, with its own isolated filesystem and network interface.



Trade-offs

	Virtual machine	Container
Isolation	Strong: separate kernel	Weaker: shared kernel
Start time	Tens of seconds to minutes	Milliseconds to seconds
Size	Gigabytes	Megabytes
Density per host	Few to tens	Tens to hundreds
Typical use	Multi-tenant clouds, different OSes	Packaging and running apps

In practice they are combined: cloud providers give you VMs, and you run containers inside them. Lightweight "micro-VMs" such as AWS Firecracker (used by Lambda and Fargate) blend the two, booting a minimal VM in around 125 ms.

Common mistakes

- Storing important data inside the container's filesystem; it vanishes when the container is replaced. Use volumes or external storage.
- Huge images (several GB) that slow down every deploy and scale-out.
- Running containers as root and baking secrets into images.

In the interview

Q: Container vs VM in one line?

A: A VM virtualises hardware and runs its own OS kernel; a container virtualises the OS, sharing the host kernel, so it is lighter and faster to start but less isolated.

TL;DR

VMs are full emulated computers with their own OS; containers are isolated processes sharing one kernel; Docker packages apps as portable container images.

Kubernetes basics

What it is

Kubernetes (often written **K8s**) is a **container orchestrator**: software that runs and manages containers across a fleet of machines. You tell it *what* you want ("run 5 copies of `shop-api:1.4.2`, each with 1 CPU and 512 MB of memory, reachable at the name `shop-api`") and it continuously works to make reality match. Picture a harbour master for a busy port: it assigns each shipping container to a free berth,

notices when one falls into the water and orders a replacement, and moves cargo elsewhere when a crane breaks. Google open-sourced it in 2014, based on its internal system Borg; it is now run by the Cloud Native Computing Foundation (CNCF).

Why it matters


With 300 containers across 40 machines, nobody can place, restart and wire them up by hand. Kubernetes automates scheduling, self-healing, scaling, rolling updates, service discovery and configuration, and it works the same on every major cloud (Amazon EKS, Google GKE, Azure AKS) and on your own servers.

How it works

Key words, beginner level:

- **Cluster**: the whole Kubernetes installation, a set of machines plus the brain that controls them.
- **Node**: one machine (physical or VM) in the cluster that runs containers. Each node runs an agent called the **kubelet**.
- **Control plane**: the brain. The **API server** receives your instructions, **etcd** stores the cluster's desired and current state, the **scheduler** decides which node each pod goes on, and **controllers** keep fixing differences.
- **Pod**: the smallest unit Kubernetes runs. One or more tightly coupled containers that share a network address and storage, for example your app plus its sidecar. Pods are disposable: they are replaced, not repaired.
- **Deployment**: a description of a stateless app ("5 replicas of this pod template"). It creates and replaces pods and performs rolling updates when you change the image.
- **Service**: a stable name and virtual IP address that load-balances traffic across the current set of matching pods, even as pods come and go. This is Kubernetes' built-in server-side service discovery.
- **Ingress** (or the newer **Gateway API**): rules that route outside HTTP traffic (`shop.com/api`) to Services.
- **ConfigMap** and **Secret**: configuration values and sensitive values injected into pods.
- **Namespace**: a folder-like grouping to separate teams or environments.
- **StatefulSet**: like a Deployment but for stateful apps (databases), giving each pod a stable name and its own persistent storage.
- **Probes**: a **liveness probe** tells Kubernetes to restart a stuck container; a **readiness probe** tells it whether to send the pod traffic yet.

The heart of Kubernetes is the **reconciliation loop**: controllers repeatedly compare desired state with actual state and act on any difference. If a node dies and 2 of your 5 pods vanish, the Deployment's controller sees "3, want 5" and creates 2 new pods on healthy nodes.



Trade-offs

Kubernetes is powerful but complex: networking, storage, security policies and upgrades all need expertise, and a small team can spend more time running the platform than building the product. Managed offerings (EKS, GKE, AKS) and simpler platforms (AWS ECS, Google Cloud Run, Fly.io, or a Heroku-style **platform as a service (PaaS)**, where you hand over code and the provider runs it) are often the better first choice.

Common mistakes

- No resource requests and limits, so one pod hogs a node's memory and others get killed.
- Missing readiness probes, so traffic arrives before the app has finished starting.
- Running a production database on Kubernetes without understanding StatefulSets, persistent volumes and backups.

In the interview

Q: What happens if a node crashes?

A: The control plane notices the node has stopped reporting, marks its pods as lost, and the Deployment controller creates replacement pods on healthy nodes. The Service automatically stops routing to the dead pods.

Q: Pod vs container?

A: A container is one isolated process image; a pod is Kubernetes' wrapper around one or more containers that share an IP address and volumes and are scheduled together.

TL;DR

Kubernetes runs containers across many machines, keeping the actual state equal to the desired state you declare: pods run on nodes, Deployments manage replicas and rollouts, Services give them a stable address.

Infrastructure as code

What it is

Infrastructure as code (IaC) means describing your servers, networks, load balancers, databases and permissions in text files that are kept in version control and applied by a tool, instead of clicking around a cloud console. It is like a recipe instead of cooking from memory: anyone can reproduce the same dish, and you can see exactly what changed between versions.

Why it matters

Hand-built environments drift apart ("staging has a setting production does not"), cannot be rebuilt quickly after a disaster and have no review trail. With IaC, a new region or a test environment is one command away, every change is code-reviewed, and the files themselves document the system.

How it works

1. Write a **declarative** description of the desired resources, for example in Terraform:

```
resource "aws_s3_bucket" "images" {
  bucket = "shop-product-images"
}
```

2. Run a **plan**: the tool compares the files with what actually exists and shows the diff ("will create 1 bucket").
3. A teammate reviews the plan in a pull request.
4. **Apply** it; the tool calls the cloud APIs to create or change resources and records what it built in a **state file**.

Declarative tools describe the end state (Terraform, AWS CloudFormation, Kubernetes YAML, Pulumi); **imperative** scripts describe the steps. **Configuration management** tools (Ansible, Chef, Puppet) configure software on existing servers. **Immutable infrastructure** is the related idea of never patching a running server: build a new image and replace the old server instead.

Trade-offs and common mistakes

IaC has a learning curve and its state files must be stored and locked carefully (two people applying at once can corrupt them). The classic mistake is mixing IaC with manual console edits, which creates **drift** the next apply may silently undo.

TL;DR

Infrastructure as code keeps your cloud setup in reviewed, versioned files that a tool applies, so environments are reproducible and changes are auditable.

CI/CD

What it is


- **Continuous integration (CI)**: every developer merges small changes into the main branch frequently (at least daily), and each change automatically triggers a build and test run. It catches conflicts and bugs within minutes.
- **Continuous delivery (CD)**: every change that passes the pipeline is automatically packaged and ready to release to production at the push of a button.
- **Continuous deployment**: one step further, every passing change goes to production automatically, with no human button.

A **pipeline** is the automated sequence of steps. Think of a car factory line: each station checks or adds something, and a faulty car is pulled off before it reaches the showroom.

Why it matters

Small, frequent releases are less risky than big, rare ones: if a release contains one change and breaks something, you know exactly what to roll back. The research programme behind the **DORA metrics** (deployment frequency, lead time for changes, change failure rate, time to restore service) found that high-performing teams deploy more often *and* have fewer failures.

How it works



1. A developer pushes a commit or opens a pull request.
2. The CI server (GitHub Actions, GitLab CI, Jenkins, CircleCI) compiles the code, runs linters and unit tests and security scans, typically in under 10 minutes.
3. It builds one versioned artifact, such as a container image, and stores it. The **same artifact** is promoted through every environment, never rebuilt.
4. It deploys to a staging environment and runs integration or end-to-end tests.
5. It deploys to production using a safe strategy (next section), watches health metrics and rolls back automatically if they worsen.

Common mistakes

- Flaky tests that fail randomly, so people learn to ignore red builds.
- Rebuilding separately for production, so what you tested is not what you ship.
- Long-lived feature branches merged once a month, which defeats the point of integration.
- Database schema changes that are not backward compatible, so the new code and old code cannot run side by side during a rollout. Use **expand and contract**: add the new column first, deploy code that writes both, migrate, then remove the old column in a later release.

TL;DR

CI builds and tests every change automatically; CD keeps every passing build ready to release (or releases it automatically); small frequent releases are safer releases.

Deployment strategies and rollback

What it is

A **deployment strategy** is how you replace the old version of a running service with a new one without taking the site down, and how you limit damage if the new version is bad. The **blast radius** is how many users a bad change can hurt; good strategies keep it small.


Why it matters

Most outages are caused by changes: a new code release, a config edit, a schema migration. How you release decides whether a bug hits 1% of users for two minutes or 100% of users for an hour.

Types

- **Recreate (big bang)**: stop all old instances, start new ones. Simple, but there is downtime. Only acceptable for internal tools or maintenance windows.
- **Rolling deployment**: replace instances a few at a time (say 2 of 20). Each new instance must pass health checks before the next batch goes. No extra servers needed and no downtime, but for a while both versions serve traffic side by side, and rollback means rolling back through the batches. Kubernetes Deployments do this by default.
- **Blue-green deployment**: run two full environments. **Blue** serves all live traffic on the old version; **green** gets the new version and is tested privately. Then the load balancer (or DNS) switches all traffic to green in one step. Rollback is instant: switch back to blue. The cost is double capacity during the release, and databases are shared, so schema changes must work for both.
- **Canary release**: send a small slice of real traffic, say 1%, to the new version, compare its error rate and latency with the old version, then step up (1%, 5%, 25%, 50%, 100%) if healthy, or pull it back automatically if not. Named after canaries that miners carried to detect gas before it hurt people. Smallest blast radius, but needs good metrics and automation.

- **Shadow (dark) launch**: copy real traffic to the new version but throw away its responses. Tests performance under real load with zero user impact; you must be careful that it does not write data or send emails.
- **Feature flags (feature toggles)**: ship new code turned off, then turn it on at runtime through configuration, for internal users first, then 5% of customers, then everyone. This separates **deploy** (code is on the servers) from **release** (users see the feature). A flag is also a kill switch: turn it off in seconds without a deploy. Tools: LaunchDarkly, Unleash, Flagsmith, or in-house systems.



Rollback means returning to the last known-good version. During an incident, going back beats going forward: restore the last good version, then investigate calmly. Make it boring: keep the previous artifact, automate the button, practise it. Rollback is easy for stateless code, hard when the release changed data or the schema in a non-backward-compatible way; then you need **roll forward** (ship a quick fix) instead.

Trade-offs

Strategy	Downtime	Extra capacity	Rollback speed	Blast radius
Recreate	Yes	None	Slow	Everyone
Rolling	No	Small	Medium	Grows per batch
Blue-green	No	2x briefly	Instant	Everyone at switch
Canary	No	Small	Fast	Tiny at first
Feature flag	No	None	Seconds	Chosen users

Common mistakes

- Canary without automated metric comparison, so nobody notices the 1% is failing.
- Old feature flags never cleaned up, leaving confusing dead code paths.
- Treating config changes as safe and pushing them globally at once.

Real-world examples

In 2012 **Knight Capital** deployed new trading code to only 7 of its 8 servers; a reused flag activated old dormant code on the eighth, which sent more than 4 million orders into the market and lost the firm about $440 million in roughly 45 minutes (the SEC later put the loss above $460 million). In July 2024 a faulty **CrowdStrike** content update was pushed to all customers at once and crashed about 8.5 million Windows machines (Microsoft's estimate); staged, canary-style rollout was the main lesson. Large companies such as Google and Meta release most changes through progressive rollouts with automatic rollback.

In the interview

Q: Blue-green or canary?

A: Blue-green gives an instant switch and instant rollback but exposes everyone at once and needs double capacity. Canary exposes a small percentage first and grows only if metrics stay healthy, so a

bad release hurts far fewer users. For high-traffic user-facing services I prefer canary, ideally combined with feature flags.

Q: How do you deploy a database schema change safely?

A: Make it backward compatible with expand and contract: add new columns or tables first, deploy code that works with both shapes, backfill data, switch reads, and only drop the old structure in a later release once nothing uses it.

TL;DR

Release gradually (rolling, canary, feature flags) or switch whole environments (blue-green), watch metrics, and keep rollback one fast, practised step.

Observability: logs, metrics and traces

What it is

Monitoring is watching known numbers to check the system is healthy. **Observability** is the broader ability to understand *why* a system is behaving as it is, including problems you never predicted, purely from the data it emits. A car dashboard (speed, fuel, warning lights) is monitoring; a mechanic's diagnostic computer that lets you ask any question about the engine is closer to observability. The data comes in three main kinds, often called the **three pillars**.


- **Logs**: timestamped text records of individual events. `2026-10-07T09:14:03Z ERROR order=8812 payment declined: card expired`. Best written as **structured logs** (JSON with named fields) so tools can search and filter them.
- **Metrics**: numbers measured over time, cheap to store and fast to graph. Examples: requests per second, error count, p99 latency, CPU %, queue depth. Common shapes are **counters** (only go up, such as total requests), **gauges** (go up and down, such as memory in use) and **histograms** (distribution of values, such as latency buckets, from which percentiles are computed).
- **Traces**: the path of one request through many services. A trace is a tree of **spans**; each span is one operation (a service handling the request, a database query) with a start time and duration. All spans share a **trace ID** passed along in request headers, so you can see that a 2.1 s checkout spent 1.8 s waiting on the tax service.

Why it matters

In a monolith you can read one log file. In microservices, one click touches 15 services on 200 machines. Without metrics you do not know something is wrong; without traces you do not know where; without logs you do not know why. Observability also drives decisions: capacity planning, SLOs and whether a canary is healthy.

How it works

1. **Instrument** code with a library, today usually **OpenTelemetry**, the vendor-neutral standard for emitting logs, metrics and traces.
2. Every incoming request gets a **correlation ID** or trace ID, which is logged and forwarded to every downstream call (the W3C `traceparent` header is the standard).
3. **Collect and ship**: agents or collectors send logs to a store (Elasticsearch/OpenSearch, Loki, Splunk), metrics to a time-series database (Prometheus, Datadog, CloudWatch) and traces to a tracing backend (Jaeger, Zipkin, Tempo, Honeycomb).
4. **Visualise**: dashboards (Grafana, Datadog, Kibana) graph key metrics.
5. **Alert**: rules on metrics notify a human when something needs attention.



Sampling. Storing every trace at 100,000 requests per second is too expensive, so systems keep a sample, for example 1% of normal requests but 100% of errors and slow requests (**tail-based sampling**, which decides after seeing the whole trace).

Cardinality. Each unique combination of metric labels is a separate time series. A label like `user_id` with 10 million values creates 10 million series and can crash a metrics system. Put high-cardinality details in logs and traces, not metric labels.

Types: what to measure

- **Four golden signals** (from Google's SRE book), for any user-facing service:
  - **Latency**: how long requests take, tracking successful and failed requests separately (a fast error is not a success).
  - **Traffic**: demand, such as requests per second.
  - **Errors**: rate of failed requests (explicit 5xx, wrong answers, too slow).
  - **Saturation**: how full the most constrained resource is (CPU, memory, connection pool, queue).
- **RED method** (Tom Wilkie), for request-driven services: **Rate** (requests per second), **Errors** (failed requests per second), **Duration** (latency distribution).
- **USE method** (Brendan Gregg), for resources like CPU, disks and network: **Utilisation** (% of time busy), **Saturation** (extra work queued, waiting), **Errors** (error events).

RED looks at a service from the outside (what users feel); USE looks at the machines underneath (why it might be happening).

Trade-offs

Observability data can cost a lot: large companies spend a noticeable share of their infrastructure bill on logging and monitoring. Logs are rich but expensive per event; metrics are cheap but aggregated (they say *that* p99 rose, not *which* request); traces are precise but sampled. Use all three, linked by trace ID.

Common mistakes

- Logging everything at debug level in production, then paying to store terabytes nobody reads.
- Logging secrets, passwords or personal data.
- Averages instead of percentiles on latency dashboards (Part 1).
- No correlation ID, so logs from different services cannot be stitched together.

Real-world examples

Google's **Dapper** paper (2010) introduced large-scale distributed tracing and inspired Zipkin (Twitter) and Jaeger (Uber). Prometheus, created at SoundCloud, is the standard open-source metrics system in the

Kubernetes world, usually paired with Grafana dashboards.

In the interview

Q: A user says checkout is slow. How do you find out why?

A: Check the RED metrics for checkout to confirm and size the problem (which percentile, since when, which regions), correlate with recent deploys, then open slow traces to see which span is slow, and read that service's logs for those trace IDs. Then use USE metrics on the slow component's machines or database.

Q: Logs vs metrics vs traces?

A: Metrics are the cheap early warning: a number moved, and by how much. A trace pinpoints which hop in the call chain was slow or failed. Logs give the detailed story of what one component did at that moment.

TL;DR

Emit metrics (cheap numbers), logs (detailed events) and traces (one request across services), tied together by a trace ID; watch the golden signals, RED for services and USE for resources.

Dashboards, alerting, on-call and SLO-based alerts

What it is

- A **dashboard** is a page of graphs showing a system's key metrics at a glance.
- An **alert** is an automated notification fired when a rule on a metric is broken, for example "error rate above 2% for 5 minutes".
- **On-call** is the rota of engineers responsible for responding to alerts, including at night. A **page** is an urgent alert that wakes someone up (via PagerDuty, Opsgenie and similar tools); a **ticket** is a non-urgent alert handled in working hours.
- A **runbook** (or playbook) is a written guide for what to do when a specific alert fires.
- A **postmortem** (incident review) is a written analysis after an incident: timeline, impact, root causes and follow-up actions, written **blameless**, focusing on how the system allowed the mistake rather than who made it.

Why it matters

Alerts are how humans learn something is broken before customers flood support. But too many alerts cause **alert fatigue**: if on-call is paged 30 times a night for things that fix themselves, they start ignoring pages and miss the real one.

How it works

Good alerting rules:

1. Page on **symptoms users feel** (high error rate, high latency, checkout failures), not on causes (one server at 90% CPU, which may be fine).
2. Every page must be urgent, actionable and needing human judgement. Otherwise make it a ticket or automate the fix.
3. Attach a runbook link and a dashboard to every alert.

SLO-based alerting. Recall from Part 1: an **SLI** is a measured indicator (fraction of successful requests), an **SLO** is the target (99.9% over 30 days), and the **error budget** is the allowed failure (0.1%, about 43 minutes of full downtime per 30 days). Instead of alerting on any blip, alert on the **burn rate**: how fast you are spending the budget. A burn rate of 1 uses exactly the whole budget in 30 days; a burn rate of 14.4 sustained for one hour uses 2% of the monthly budget in that hour, and would exhaust the budget in about two days.

A common scheme from Google's SRE workbook:

Window	Burn rate	Budget used	Action
1 hour	14.4	2%	Page now
6 hours	6	5%	Page
3 days	1	10%	Ticket

Pairing each long window with a short one (for example 1 hour and 5 minutes) makes the alert fire fast and also stop quickly once the problem is fixed.

Incident response roles. In a serious incident, one **incident commander** coordinates, others investigate, one person communicates with stakeholders and customers. The first goal is **mitigation** (stop the bleeding: roll back, fail over, shed load), not finding the root cause.

Common mistakes

- Alerting on every metric someone thought of, and never deleting noisy alerts.
- Dashboards with 80 graphs and no clear "is it healthy?" panel at the top.
- Debugging the root cause during an outage instead of rolling back first.
- Postmortems that blame a person, which teaches people to hide mistakes.

In the interview

Q: What would you alert on for this service?

A: SLO burn rate for availability and latency of the main user journeys, plus a few critical saturation signals that predict imminent failure, such as disk nearly full or queue lag growing. Everything else goes on dashboards or tickets, not pages.

TL;DR

Page on user-facing symptoms and fast error-budget burn, keep every page actionable with a runbook, mitigate first, and write blameless postmortems.

Disaster recovery

What it is

Disaster recovery (DR) is your plan for getting the service and its data back after a large failure: a data-centre fire, a whole cloud region going down, a ransomware attack, or an engineer deleting the production database. **Business continuity** is the wider plan for keeping the business running. Two numbers define a DR target:

- **RPO (recovery point objective)**: how much data, measured in time, you can afford to lose. RPO of 1 hour means after recovery you may be missing at most the last hour of writes. Think "how far back is my last save point?".
- **RTO (recovery time objective)**: how long the service may be down before it is restored. RTO of 4 hours means you must be running again within 4 hours. Think "how long until I am playing again?".

Why it matters

Redundancy within one site (Part 1) protects against a disk or server failing. It does not help if the whole site goes, or if a bug or human corrupts data that is then faithfully replicated to every copy. Only backups and DR plans protect you there. Lower RPO and RTO cost more, so they must be agreed with the business: a bank's payment ledger may need RPO near zero and RTO of minutes; an internal wiki can accept a day.

How it works

Backups. Copies of data stored separately from the original, ideally following the **3-2-1 rule**: 3 copies, on 2 different media or services, with 1 off-site (another region or account). Kinds:

- **Full backup**: everything, every time. Simple, large.

- **Incremental backup**: only what changed since the last backup. Small, but restoring needs the chain.
- **Snapshot**: a point-in-time image of a disk or database, usually fast and incremental under the hood.
- **Continuous archiving** of the write-ahead log (Part 3), which allows **point-in-time recovery** to any second.
- **Immutable / air-gapped backups** that cannot be deleted or altered for a set period, protecting against ransomware and rogue deletes.

Until you have actually restored from a backup, you do not know it works. Rehearse restores on a schedule and time them, because restore time is part of your RTO.

Availability zones and regions. A cloud **region** is a geographic area (for example AWS `eu-west-1` in Ireland). Each region contains several **availability zones (AZs)**: one or more separate data centres with independent power, cooling and networking, a few to tens of kilometres apart, linked by fast connections with round trips of roughly 1 to 2 ms. AZs fail independently; regions are hundreds or thousands of kilometres apart.


- **Multi-AZ**: run copies in 2 or 3 AZs of one region. Protects against a data-centre failure. Synchronous database replication is practical because AZs are close. This is the normal baseline for production.
- **Multi-region**: run in two or more regions. Protects against a whole-region outage and serves users nearer home, but cross-region round trips are 50 to 150 ms or more, so replication is usually asynchronous (RPO greater than zero), and it costs much more and is much more complex.

Types: DR strategies

From cheapest and slowest to most expensive and fastest:

Strategy	What runs in the DR site	Typical RTO	Typical RPO
Backup and restore	Nothing, only backups	Hours to a day	Hours
Pilot light	Data replicated, servers off	Tens of minutes	Minutes
Warm standby	Scaled-down full copy	Minutes	Seconds to minutes
Active-active	Full copy serving traffic	Near zero	Near zero to seconds

- **Active-passive**: one site serves all traffic; the other is on standby (pilot light or warm) and takes over on **failover**. Simpler, but standby capacity sits idle and failover is a risky moment that is rarely exercised.
- **Active-active**: all sites serve live traffic at the same time; if one fails, the others absorb its share. Fast recovery and no idle capacity, but each site must have spare headroom, and writes in several places raise hard consistency problems (Part 3 multi-leader replication, Part 4 conflict resolution).



Chaos engineering is the practice of deliberately injecting failures into a system (killing servers, adding network latency, blocking a dependency, even taking out a whole AZ) in a controlled way to prove that redundancy, failover and alerting actually work, and to find weaknesses before real outages do. Start small: a hypothesis ("if one cache node dies, p99 stays under 300 ms"), a limited blast radius, an abort button. **Game days** are scheduled team exercises of this kind, including practising a full regional failover.

Common mistakes

- Backups stored in the same account and region as the data, so the same disaster or attacker removes both.
- Never testing restores; discovering during the disaster that backups were silently failing.
- Assuming replication is a backup. A `DELETE` replicates too.
- A DR region that depends on a service in the failed region (shared DNS, auth, or deployment tooling).

Real-world examples

In 2017 **GitLab** accidentally deleted a production database directory; none of its five backup and replication methods turned out to be working reliably, and it restored from a six-hour-old copy, losing about six hours of data. Netflix created **Chaos Monkey** (open-sourced in 2012) to randomly terminate production instances, and later tools that simulate whole-region outages; it runs active-active across several AWS regions. The October 2021 **Facebook** outage, where a mistaken maintenance command cut its backbone network and its DNS servers then withdrew their **BGP** routes (the announcements that tell the rest of the internet how to reach them), lasted about six hours and also locked engineers out of internal tools they needed to fix it, a reminder that recovery tooling must not depend on the thing that failed.

In the interview

Q: Explain RPO and RTO with an example.

A: If the database is backed up every 6 hours and a restore takes 2 hours, the worst-case RPO is 6 hours of lost data and RTO is at least 2 hours of downtime. Adding continuous log shipping to another region could bring RPO to seconds, and a warm standby could bring RTO to minutes.

Q: Multi-AZ or multi-region?

A: Multi-AZ is the standard baseline: it survives a data-centre failure with low latency and synchronous replication. Multi-region adds protection against a regional outage and lower latency for global users, but costs much more and usually means asynchronous replication, so I would choose it only when the SLA or user geography demands it.

TL;DR

RPO is how much data you can lose, RTO is how long you can be down; backups (tested!) and multi-AZ are the baseline, multi-region active-passive or active-active buys more at a higher price, and chaos engineering proves it works.

Authentication and authorization

What it is

- **Authentication (AuthN)** answers "who are you?". It proves identity, usually with something you know (a password), something you have (a phone or security key) or something you are (a fingerprint). Using two or more of these is **multi-factor authentication (MFA)**.
- **Authorization (AuthZ)** answers "what are you allowed to do?". It checks permissions after identity is known.

At an airport, showing your passport is authentication; your boarding pass deciding which plane and seat you may board is authorization. Failing authentication returns HTTP **401 Unauthorized** (confusingly named; it really means "unauthenticated"); being known but not permitted returns **403 Forbidden**.

Why it matters

Nearly every system has users, and nearly every security breach involves either stolen identities or missing permission checks. Getting the vocabulary right is also one of the most common interview probes.

How it works

Authorization models:

- **Access control list (ACL)**: each resource lists who may do what ("doc 42: Alice can edit, Bob can read"). Fine-grained but hard to manage at scale.
- **Role-based access control (RBAC)**: permissions are attached to roles (admin, editor, viewer) and users are given roles. Simple and auditable; most business software uses it.
- **Attribute-based access control (ABAC)**: rules evaluate attributes of the user, resource and context: "a doctor may read a patient record if they are in the same hospital department and it is during their shift". Very flexible, harder to reason about.
- **Relationship-based access control (ReBAC)**: permissions follow relationships in a graph ("can view if member of a group that owns the folder containing the file"). Google's Zanzibar system, which powers sharing in Drive and other products, is the famous example.

Authorization must be checked on the server for every request, never only by hiding buttons in the user interface.

In the interview

Q: Authentication vs authorization?

A: Authentication proves who the caller is (login, token validation, returns 401 on failure); authorization decides whether that identity may perform this action on this resource (roles, policies, returns 403 on failure).

TL;DR

AuthN is who you are; AuthZ is what you may do; RBAC grants permissions through roles, ABAC through attribute rules.

Sessions, cookies, tokens and JWT

What it is

HTTP is stateless (Part 2): each request stands alone, so after you log in the server needs a way to recognise you on the next request.

- **Session-based authentication**: after login, the server creates a **session** record (user ID, expiry) in its memory, a database or Redis, and gives the browser a random **session ID** inside a **cookie** (a small piece of data the browser stores and automatically sends back to the same site on every request). Like a cloakroom ticket: the ticket itself means nothing, the server looks it up.
- **Token-based authentication**: after login, the server gives the client a **token**, a string the client sends with each request, usually in the header `Authorization: Bearer <token>`. An **opaque token** is a random string the server must look up; a **self-contained token** carries the user's details inside it and is signed so it cannot be forged.
- **JWT (JSON Web Token)**, pronounced "jot", is the most common self-contained token format: three Base64URL-encoded parts separated by dots, `header.payload.signature`.

```
header:    {"alg":"RS256","typ":"JWT"}
payload:   {"sub":"user_8812","role":"editor","exp":1767225600}
signature: RSA signature over header + payload, made with the server's private key
```

How it works

JWT verification: any service with the issuer's key (a shared secret for HS256, an HMAC-based signature, or the public key for RS256, an RSA signature) recomputes or checks the signature and the `exp` (expiry) claim. If valid, it trusts the claims without calling a database. That is why JWTs suit microservices: every service can verify a request locally.

A JWT is **signed, not encrypted**. Anyone can Base64-decode the payload and read it, so never put secrets in it. And because no database lookup happens, a stolen JWT works until it expires and cannot easily be revoked. The usual answer is short-lived **access tokens** (5 to 15 minutes) plus a long-lived **refresh token**, stored more carefully and checked against a database, used to obtain new access tokens; revoking the refresh token logs the user out within minutes.

Cookie safety flags: `HttpOnly` (JavaScript cannot read the cookie, protecting it from XSS theft), `Secure` (sent only over HTTPS), `SameSite=Lax` or `Strict` (not sent on most cross-site requests, protecting against CSRF), plus an expiry.

Trade-offs

	Server sessions	JWT access tokens
Server state	Session store needed	None for verification
Revocation	Instant: delete session	Hard until expiry
Per-request cost	Store lookup	Signature check only
Size	Small ID	Hundreds of bytes or more
Best fit	Classic web apps	APIs, microservices, mobile

Common mistakes

- Accepting JWTs with `alg: none` or not checking the signature and expiry.
- Storing tokens in browser `localStorage`, where any XSS script can steal them; an `HttpOnly` cookie is safer for browser apps.
- Very long-lived access tokens.

TL;DR

Sessions keep login state on the server and give the browser an ID in a cookie; tokens like JWT carry signed claims the client presents on each request, easy to verify anywhere but hard to revoke, so keep them short-lived.

OAuth 2.0, OpenID Connect, SSO and API keys

What it is

- **OAuth 2.0** is a standard for **delegated authorization**: letting one app access your data in another app *without giving it your password*. "Allow PhotoPrinter to read your Google Photos?" is OAuth. Analogy: a hotel key card that opens only your room and expires at checkout, instead of handing over the master key.
- **OpenID Connect (OIDC)** is a thin identity layer on top of OAuth 2.0 that adds **authentication**: it returns an **ID token** (a JWT) saying who the user is. "Sign in with Google" or "Sign in with Apple" is OIDC.
- **Single sign-on (SSO)**: log in once with one identity provider and get access to many applications. At work you sign in to Okta or Microsoft Entra ID once and reach email, chat and dashboards without logging in again. Enterprise SSO uses OIDC or the older XML-based **SAML**.
- **API key**: a long random secret string that identifies a calling program (not a person), sent in a header such as `X-API-Key`. Simple for server-to-server use, metering and rate limiting, but it is a bearer secret with no built-in expiry or user identity.


How it works

The four OAuth roles:

- **Resource owner**: the user who owns the data.
- **Client**: the app that wants access (PhotoPrinter).
- **Authorization server**: issues tokens after the user consents (Google's login and consent service).
- **Resource server**: the API holding the data (Google Photos API), which accepts the access token.

Authorization code flow (with PKCE), the recommended flow for web and mobile apps:

1. The user clicks "Connect Google Photos". The client redirects the browser to the authorization server with its client ID, the **scopes** it wants (for example `photos.read`) and a redirect URL. With **PKCE** (Proof Key for Code Exchange) it also sends a hash of a one-time random secret.
2. The user logs in at Google (the client never sees the password) and approves the scopes.
3. The authorization server redirects back to the client with a short-lived, single-use **authorization code**.
4. The client exchanges the code (plus the PKCE secret, and for server apps its client secret) at the authorization server's token endpoint, server to server.
5. It receives an **access token** (and often a refresh token; with OIDC also an ID token).
6. The client calls the Photos API with `Authorization: Bearer <access token>`; the resource server validates it and checks the scopes.



Other flows: **client credentials** for machine-to-machine calls with no user, and **device code** for TVs and devices without a keyboard. The old "implicit" and "password" flows are discouraged.

Common mistakes

- Using OAuth access tokens as proof of identity. OAuth says what a client may access; OIDC's ID token says who logged in.
- Requesting far broader scopes than needed.
- Committing API keys to Git repositories. Automated scanners find leaked keys within minutes.

In the interview

Q: OAuth vs OpenID Connect?

A: OAuth 2.0 is for authorization: it gives an app a scoped access token to call an API on the user's behalf. OIDC builds on it for authentication, adding a signed ID token that tells the app who the user is, which is what "Sign in with Google" uses.

Q: When would you use an API key instead of OAuth?

A: For simple server-to-server access by a known customer's backend, where you mainly need identification, metering and rate limiting. For acting on behalf of users, or anything needing scopes and expiry, use OAuth.

TL;DR

OAuth 2.0 delegates scoped access without sharing passwords (owner, client, authorization server, resource server; authorization code flow with PKCE); OIDC adds an ID token for login; SSO reuses one login across apps; API keys identify programs.

Encryption, hashing, passwords and secrets

What it is

- **Encryption** scrambles data with a **key** so only someone with the right key can unscramble (**decrypt**) it. It is two-way.
  - **Symmetric encryption**: the same key locks and unlocks (AES). Fast; used for bulk data.
  - **Asymmetric (public-key) encryption**: a **public key** anyone can use to encrypt or verify, and a **private key** only the owner holds to decrypt or sign (RSA, elliptic-curve). Slower; used for key exchange and digital signatures, as in TLS.

- **Encryption in transit**: protecting data while it travels over a network, almost always with **TLS** (Part 2), the "S" in HTTPS. Inside a data centre, service-to-service **mutual TLS (mTLS)** has both sides present certificates.
- **Encryption at rest**: protecting stored data on disks, databases, backups and object storage, so a stolen disk or backup file is unreadable. Cloud services typically do this with AES-256 and keys from a **key management service (KMS)**.
- **Hashing** turns any input into a fixed-size **fingerprint** (a **hash** or **digest**) that cannot be reversed. SHA-256 of any file is 256 bits. The same input always gives the same hash; a tiny change gives a completely different one. It is one-way: you can grind coffee beans into powder, but you cannot rebuild the beans from the powder.

How it works

Hashing vs encryption. Use encryption when you need the original back (a stored credit-card number you will charge later). Use hashing when you only need to check a match (passwords, file integrity, deduplication).

Password hashing. Never store passwords in plain text or encrypted (if the key leaks, all passwords leak). Store a **slow, salted hash**:

1. Generate a random **salt** (for example 16 bytes) per user, so two users with the same password get different hashes and precomputed "rainbow tables" are useless.
2. Hash password + salt with a deliberately slow algorithm: **bcrypt** (with a cost factor), **scrypt**, or **Argon2id** (a variant of Argon2, which won the 2015 Password Hashing Competition; it is the current first choice of OWASP, the Open Worldwide Application Security Project), tuned so one hash takes tens to hundreds of milliseconds and, for scrypt and Argon2, lots of memory.
3. Store the algorithm, parameters, salt and hash together.
4. At login, recompute with the stored salt and compare.

Fast hashes like SHA-256 or MD5 are wrong for passwords: a single modern GPU can try billions of SHA-256 guesses per second, but only thousands to tens of thousands of bcrypt guesses at typical cost settings.

Envelope encryption. A KMS holds a master key that never leaves it. Each piece of data is encrypted with its own **data key**, and the data key is itself encrypted by the master key and stored beside the data. Rotating or revoking the master key controls access to everything.

Secrets management. Secrets are passwords, API keys, database credentials, private keys and tokens. Keep them out of source code, container images and logs. Store them in a secrets manager (HashiCorp Vault, AWS Secrets Manager, Google Secret Manager, Kubernetes Secrets backed by a KMS), give each service access only to its own secrets, **rotate** them regularly and automatically, and prefer short-lived dynamically issued credentials where possible.

Common mistakes

- Inventing your own cryptography; always use well-known libraries.
- Confusing encoding (Base64, reversible by anyone) with encryption.
- Encrypting data at rest but keeping the key on the same disk.
- Passwords hashed with plain SHA-256 and no salt.

In the interview

Q: How should you store user passwords?

A: Hash each one with a unique random salt using a deliberately slow algorithm such as Argon2id (which is also memory-hard) or bcrypt with a tuned cost, store only the hash and parameters, and compare by re-hashing at login. Never store them plain or reversibly encrypted.

Q: Encryption in transit vs at rest?

A: In transit protects data moving over networks, using TLS (and mTLS between services). At rest protects stored data on disks, databases and backups, usually AES with keys managed by a KMS. You need both.

TL;DR

Encryption is reversible with a key (in transit via TLS, at rest via AES and a KMS); hashing is one-way; passwords get a unique salt and a slow hash like Argon2id or bcrypt; secrets live in a secrets manager and rotate.

Network security: firewalls, WAF and DDoS

What it is

- A **firewall** filters network traffic by rules on IP addresses, ports and protocols (layers 3 and 4): "allow TCP 443 from anywhere, allow TCP 5432 only from the app servers' subnet, deny everything else". Cloud **security groups** and network ACLs are firewalls. It is the building's security desk checking which doors visitors may use.
- A **web application firewall (WAF)** inspects HTTP requests (layer 7) and blocks those that look like attacks: SQL injection patterns, cross-site scripting payloads, known bad bots, too many requests from one source. Examples: AWS WAF, Cloudflare WAF, ModSecurity, often using the OWASP Core Rule Set.
- A **DDoS (distributed denial-of-service) attack** floods a service with traffic from many machines at once (often a **botnet** of hijacked devices) to make it unavailable to real users.
- **Network segmentation**: placing databases and internal services in **private subnets** with no route from the internet, reachable only through load balancers or a **bastion host** (a hardened jump server).


How it works

Kinds of DDoS:

- **Volumetric** (layer 3/4): saturate the network pipe, for example UDP floods or **amplification** attacks that send small spoofed requests to open DNS or memcached servers, which reply with much larger responses to the victim.
- **Protocol**: exhaust connection state, for example a **SYN flood** sending millions of half-open TCP handshakes.
- **Application layer** (layer 7): many legitimate-looking HTTP requests to expensive pages such as search.

Mitigation:

1. Absorb with scale: a CDN or DDoS-protection network with huge capacity, often using anycast (Part 2) to spread the attack across hundreds of data centres (Cloudflare, AWS Shield, Google Cloud Armor, Akamai).
2. Filter at the edge: drop malformed packets, use SYN cookies, block known bad sources.
3. Rate limit and challenge suspicious clients (CAPTCHAs, JavaScript challenges).
4. Cache aggressively so most requests never reach the origin, and hide origin IP addresses so attackers cannot bypass the CDN.
5. Autoscale, with a cost ceiling, and keep graceful degradation switches ready.



Real-world examples

In October 2023 Google disclosed that, that August, it had mitigated an attack peaking at about 398 million HTTP requests per second, exploiting an HTTP/2 weakness called "Rapid Reset"; Cloudflare and AWS reported record attacks from the same technique. The 2016 **Mirai** botnet of hacked cameras and routers took down the DNS provider Dyn and, with it, many major websites for hours.

TL;DR

Firewalls filter by IP and port, WAFs filter malicious HTTP, private subnets hide internal systems, and DDoS is absorbed by large edge networks, filtering, rate limiting and caching.

Common web vulnerabilities: CORS, CSRF, XSS and SQL injection

These four come up constantly. One-line ideas plus the fix.

Same-origin policy and CORS. Browsers stop a page from one **origin** (scheme + domain + port, such as `https://shop.com`) reading responses from another origin. **CORS (Cross-Origin Resource Sharing)** is how a server opts in: it replies with headers such as `Access-Control-Allow-Origin: https://shop.com`, and for non-simple requests the browser first sends an `OPTIONS` **preflight** request to ask permission. CORS is a browser safety relaxation, not server protection: `curl` ignores it. Mistake: `Access-Control-Allow-Origin: *` on APIs that use cookies or private data.

CSRF (cross-site request forgery). An evil site tricks your logged-in browser into sending a request to another site, and the browser attaches your cookies, for example a hidden form that posts "transfer $1,000" to your bank. Fixes: `SameSite` cookies, anti-CSRF tokens (a random value the real page includes and the server checks), and never changing state on GET.

XSS (cross-site scripting). An attacker gets their JavaScript to run inside your site in other users' browsers, for example by posting a comment containing `<script>`, which can then steal data or act as the user. Fixes: escape all user content when rendering (modern frameworks like React do by default), a **Content Security Policy (CSP)** header that restricts which scripts may run, and `HttpOnly` cookies so scripts cannot read session cookies.

SQL injection. User input is glued into a SQL string, so input like `' OR '1'='1` changes the query's meaning and can read or delete data. Fix: **parameterised queries** (prepared statements), where the input is always treated as data, never as SQL.

```
Unsafe: "SELECT * FROM users WHERE email = '" + input + "'"
Safe:   "SELECT * FROM users WHERE email = ?"   with parameter [input]
```

The **OWASP Top 10** (from the Open Worldwide Application Security Project) is the widely used list of the most critical web application risks; broken access control has been at the top of its most recent editions.

In the interview

Q: What is the difference between XSS and CSRF?

A: XSS runs the attacker's script inside your site, so it can do anything the user can. CSRF does not run code in your site; it makes the victim's browser send a forged request to your site with their cookies. XSS is fixed by output escaping and CSP; CSRF by SameSite cookies and CSRF tokens.

TL;DR

CORS lets servers allow cross-origin browser reads; CSRF forges requests with the victim's cookies; XSS injects scripts; SQL injection injects query text; use SameSite cookies, CSRF tokens, escaping, CSP and parameterised queries.

Least privilege and zero trust

What it is

- **Principle of least privilege**: every user, service and process gets only the permissions it needs for its job, for only as long as it needs them. A cleaner gets keys to the offices, not the safe. If the image-resizing service is hacked, it should only be able to read one bucket, not delete the customer database.
- **Defence in depth**: several independent layers of protection (firewall, WAF, authentication, authorization, encryption, monitoring), so one failed layer is not fatal.

- **Zero trust**: never trust a request just because it comes from "inside" the network. The old **perimeter model** was a castle with a moat: once inside the office network or the **VPN** (virtual private network, an encrypted tunnel into that network), everything trusted you. Zero trust verifies every request: authenticate the user and device, check authorization, encrypt the connection (often mTLS between services), and log it, wherever it comes from.

Why it matters

Attackers who get one foothold (a phished laptop, a vulnerable server) then move sideways ("lateral movement") through a flat, trusting network. Least privilege and zero trust shrink what that foothold can reach.

How it works

Practical steps: separate **IAM** (identity and access management) roles per service with narrowly scoped policies; no shared admin accounts; just-in-time access for engineers that expires; private subnets; mTLS through a service mesh; device health checks; audit logs reviewed for unusual access. Google's **BeyondCorp** (described publicly from 2014) moved its employees off a privileged corporate network so that access to internal apps depends on user and device identity, not network location.

Common mistakes

- Giving every service an all-powerful cloud role "to get it working", then never narrowing it.
- Long-lived engineer credentials on laptops.
- Treating the VPN as the only security boundary.

TL;DR

Grant the minimum access needed, layer defences, and verify every request regardless of network location.

Cost awareness

Interviewers increasingly ask "and what would this cost?". A few rules of thumb:

- **Big cost drivers**: compute (servers, containers, functions), storage (per GB-month, with cheaper "cold" tiers for rarely read data), managed databases, and **data transfer**. Data entering a cloud is usually free; data leaving to the internet (**egress**) is charged, roughly $0.05 to $0.09 per GB on AWS depending on volume, and even traffic between availability zones costs around $0.01 per GB in each direction. Heavy video or download traffic is mostly a bandwidth bill, which is one reason CDNs matter.
- **Pricing models**: **on-demand** (pay per second or hour, flexible), **reserved instances or savings plans** (commit for 1 to 3 years for large discounts), **spot or preemptible instances** (spare capacity at up to around 90% off, but can be taken back at short notice, fine for batch jobs).
- **Levers**: autoscale and turn off idle environments at night; right-size oversized instances; cache to cut database and egress costs; move old data to cheaper tiers with lifecycle rules; sample logs and traces; compare serverless vs always-on at your real traffic level.
- **Trade-off to mention**: every extra nine of availability, extra region and lower RPO costs real money. Engineering time is a cost too, so a managed service that costs more per hour may still be cheaper overall.
- **FinOps** is the practice of making teams see and own their cloud spend, with tags per team and per service and regular reviews.

In the interview: state the expensive component of your design (for a video site, egress bandwidth;

for a logging system, storage), and one way you would reduce it.

Part 5 glossary

Term	Meaning in one line
Architectural style	The overall way code is split into running programs and how they communicate
Monolith	Whole application built and deployed as one program
Modular monolith	One deployable program with strictly separated internal modules
SOA	Older style of coarse services connected through a central service bus
Enterprise service bus (ESB)	Middleware that routes and transforms messages between SOA services
Microservices	Many small, independently deployed services, each owning one capability and its data
Database per service	Each microservice owns its private data store
Distributed monolith	Microservices so coupled they must change and deploy together
Serverless	Running code or using services without managing servers, billed per use
FaaS	Function as a Service: upload functions, provider runs them per event
Cold start	Extra delay when a serverless function runs on a freshly created instance
Conway's law	Systems mirror the communication structure of the teams that build them
Strangler fig pattern	Migrating a monolith piece by piece behind a routing layer
Synchronous / asynchronous call	Caller waits for the response / sends a message and carries on
Service discovery	Finding the current network addresses of a service's instances
Service registry	Live database of service instances and their addresses
Client-side / server-side discovery	Caller queries the registry itself / a router or load balancer does it for the caller
Sidecar	Helper process deployed beside each service instance
Service mesh	Centrally configured sidecar proxies handling all service-to-service traffic
Data plane / control plane	The proxies that carry traffic / the component that configures them
mTLS	Mutual TLS: both client and server prove identity with certificates
Timeout	Maximum time a caller waits before giving up
Deadline propagation	Passing the remaining time budget along to downstream calls
Retry	Repeating a failed request in case the fault was temporary
Transient fault	A short-lived failure likely to succeed on retry
Exponential backoff	Doubling the wait between successive retries

Term	Meaning in one line
Jitter	Randomness added to retry waits to avoid synchronised retries
Retry storm	Retries multiplying load on an already struggling service
Retry budget	Cap on the share of traffic that may be retries
Hedged request	Sending a duplicate request to another replica if the first is slow
Cascading failure	One component's failure spreading to the components that depend on it
Circuit breaker	Wrapper that stops calling a failing dependency for a while
Closed / Open / Half-open	Circuit breaker states: normal, failing fast, testing recovery
Bulkhead	Isolating resource pools so one failure cannot consume everything
Cell-based architecture	Splitting users across independent copies of the stack to limit blast radius
Fallback	Alternative response used when a call fails
Rate limiting	Capping requests per client per time window and rejecting the excess
Throttling	Slowing or queuing excess requests instead of rejecting them
HTTP 429	Status code meaning too many requests
Retry-After	Header telling a client how long to wait before retrying
Token bucket	Rate limiter with refilling tokens that allows bursts up to bucket size
Leaky bucket	Rate limiter that outputs requests at a fixed steady rate
Fixed window counter	Rate limiter counting requests per calendar time window
Sliding window log	Rate limiter storing each request timestamp for an exact count
Sliding window counter	Rate limiter estimating a sliding count from two fixed windows
Fail open / fail closed	Allowing or denying traffic when a safety component itself fails
Load shedding	Deliberately rejecting some work when overloaded so the rest succeeds
Graceful degradation	Turning off non-essential features under stress to keep the core working
Goodput	Useful work completed, as opposed to raw throughput
Congestion collapse	Overload where throughput falls towards zero due to wasted work
Kill switch	Flag that instantly disables a feature
Autoscaling	Automatically adding or removing capacity based on load
Scale out / scale in	Adding or removing instances
Reactive / scheduled / predictive scaling	Scaling on current metrics / at preset times / ahead of forecast demand
Cool-down period	Wait after a scaling action before another, to avoid flapping
Cluster autoscaler	Adds or removes Kubernetes nodes as pods need room

Term	Meaning in one line
Virtual machine (VM)	Emulated computer with its own operating system
Hypervisor	Software that runs and isolates virtual machines on a physical host
Container	Isolated process sharing the host's OS kernel
Namespaces and cgroups	Linux features that isolate what a process sees and limit what it uses
Container image	Read-only package of an app and its dependencies
Docker	Popular tool for building, sharing and running container images
Dockerfile	Text recipe for building a container image
Container registry	Storage service for container images
Kubernetes (K8s)	Container orchestrator that keeps declared state running across machines
Cluster	The set of machines and control plane managed by Kubernetes
Node	One machine in a Kubernetes cluster
Kubelet	Agent on each node that runs its pods
etcd	Consistent key-value store holding Kubernetes cluster state
Pod	Smallest Kubernetes unit: one or more containers sharing network and storage
Deployment (Kubernetes)	Object managing replicas and rolling updates of stateless pods
Service (Kubernetes)	Stable name and virtual IP load-balancing to matching pods
Ingress	Kubernetes rules routing external HTTP traffic to services
ConfigMap / Secret	Kubernetes objects for configuration and sensitive values
StatefulSet	Kubernetes object for stateful pods with stable identity and storage
Liveness / readiness probe	Checks for whether to restart a container or send it traffic
Reconciliation loop	Controllers continually driving actual state towards desired state
Infrastructure as code (IaC)	Defining infrastructure in versioned files applied by tools
Terraform	Popular declarative infrastructure-as-code tool
Configuration drift	Real infrastructure diverging from its definition
Immutable infrastructure	Replacing servers with new images instead of modifying them
Continuous integration (CI)	Automatically building and testing every merged change
Continuous delivery	Keeping every passing build releasable on demand
Continuous deployment	Automatically releasing every passing build to production
Pipeline	Automated sequence of build, test and deploy steps
DORA metrics	Deployment frequency, lead time, change failure rate, time to restore
Expand and contract	Backward-compatible schema change done in several releases
Deployment strategy	Method for replacing a running version with a new one

Term	Meaning in one line
Blast radius	How much of the system or user base a failure can affect
Recreate deployment	Stop old version, start new, with downtime
Rolling deployment	Replacing instances in small batches
Blue-green deployment	Switching traffic between two full environments
Canary release	Sending a small share of traffic to a new version first
Shadow launch	Copying real traffic to a new version and discarding its responses
Feature flag	Runtime switch that turns code paths on or off for chosen users
Rollback	Returning to the previous known-good version
Roll forward	Fixing a bad release by shipping a new fix instead of reverting
Monitoring	Watching known metrics to check health
Observability	Ability to understand system behaviour from its emitted data
Log	Timestamped record of a single event
Structured logging	Logs written as fields (such as JSON) for easy querying
Metric	Numeric measurement tracked over time
Counter / gauge / histogram	Metric that only rises / goes up and down / records a distribution
Trace	Record of one request's path across services
Span	One timed operation inside a trace
Trace ID / correlation ID	Identifier passed along to link all data for one request
OpenTelemetry	Vendor-neutral standard and libraries for telemetry
Sampling	Keeping only a fraction of traces or logs to control cost
Cardinality	Number of distinct label combinations in metrics
Four golden signals	Latency, traffic, errors, saturation
RED method	Rate, Errors, Duration for services
USE method	Utilisation, Saturation, Errors for resources
Saturation	How full the most constrained resource is
Dashboard / alert	Page of graphs showing key metrics / automated notification when a metric rule breaks
Page / ticket	Urgent alert waking someone / non-urgent work item
Alert fatigue	Ignoring alerts because there are too many noisy ones
On-call	Rota of engineers responding to alerts
Runbook	Step-by-step guide for handling a specific alert
Burn rate	Speed at which the error budget is being consumed
Incident commander	Person coordinating the response to an incident
Mitigation	Action that stops user impact before the root cause is fixed
Postmortem	Blameless written review of an incident

Term	Meaning in one line
Disaster recovery (DR)	Plan for restoring service and data after a major failure
RPO	Maximum acceptable data loss, measured in time
RTO	Maximum acceptable downtime before restoration
Backup	Separate copy of data for restoration
Full / incremental backup	Copy of everything / only changes since the last backup
Snapshot	Point-in-time image of a disk or database
Point-in-time recovery	Restoring data to any chosen moment using logs
3-2-1 rule	Three copies, two media, one off-site
Immutable backup	Backup that cannot be altered or deleted for a set period
Region	Geographic cloud area containing several availability zones
Availability zone (AZ)	Independent data centre group within a region
Multi-AZ	Running across several zones in one region
Multi-region	Running across several geographic regions
Backup and restore / pilot light / warm standby	DR strategies from cheapest and slowest to faster and costlier
Active-passive	One site serves traffic while another waits to take over
Active-active	All sites serve traffic at the same time
Chaos engineering	Deliberately injecting failures to prove resilience
Game day	Planned exercise practising failures and recovery
Authentication (AuthN)	Proving who someone is
Authorization (AuthZ)	Deciding what an identity may do
MFA	Multi-factor authentication using two or more kinds of proof
401 / 403	Not authenticated / authenticated but not permitted
ACL	List of who may access a specific resource
RBAC	Permissions granted through roles
ABAC	Permissions decided by rules over attributes
ReBAC	Permissions derived from relationships between users and objects
Session	Server-side record of a logged-in user
Cookie	Small data stored by the browser and sent back to the site automatically
HttpOnly / Secure / SameSite	Cookie flags: no script access / HTTPS only / limit cross-site sending
Token	String a client presents to prove identity or access
Bearer token	Token that grants access to whoever holds it
JWT	Signed, self-contained JSON token: header.payload.signature
Access token / refresh token	Short-lived API credential / long-lived credential to get new access tokens

Term	Meaning in one line
OAuth 2.0	Standard for delegated, scoped access without sharing passwords
Resource owner / client / authorization server / resource server	The four OAuth roles
Scope	Named permission an OAuth token grants
Authorization code flow	OAuth flow exchanging a one-time code for tokens
PKCE	One-time secret proving the code exchanger started the flow
Client credentials flow	OAuth flow for machine-to-machine access
OpenID Connect (OIDC)	Identity layer on OAuth that adds an ID token for login
ID token	JWT stating who the user is
SSO	Single sign-on: one login for many applications
SAML	Older XML-based standard for enterprise SSO
API key	Secret string identifying a calling program
Encryption	Reversible scrambling of data with a key
Symmetric / asymmetric encryption	Same key both ways / public and private key pair
Encryption in transit / at rest	Protecting data moving over a network (TLS) / stored on disks and backups
KMS	Key management service that stores and uses encryption keys
Envelope encryption	Encrypting data keys with a master key held in a KMS
Hashing	One-way conversion of data into a fixed-size fingerprint
Salt	Random per-user value added before hashing a password
bcrypt / scrypt / Argon2id	Deliberately slow password-hashing algorithms
Secrets management	Storing, distributing and regularly rotating (replacing) credentials securely
Firewall	Filters traffic by IP, port and protocol
Security group	Cloud firewall attached to instances
WAF	Web application firewall filtering malicious HTTP requests
DDoS	Flooding a service from many machines to make it unavailable
Botnet	Network of hijacked devices controlled by an attacker
Amplification attack	Spoofed small requests causing large replies to hit a victim
SYN flood	Attack exhausting servers with half-open TCP connections
Private subnet	Network segment with no direct route from the internet
Bastion host	Hardened server used as the only entry point to private machines
Same-origin policy	Browser rule blocking pages from reading other origins' responses
CORS	Headers letting a server allow cross-origin browser requests
Preflight request	Browser OPTIONS request checking CORS permission first
CSRF	Forged request sent by the victim's browser with their cookies

Term	Meaning in one line
XSS	Attacker's script running inside a trusted site
Content Security Policy (CSP)	Header restricting which scripts and resources a page may load
SQL injection	Input altering the meaning of a SQL query
Parameterised query	Query where inputs are passed separately as data
OWASP Top 10	Widely used list of top web application security risks
Least privilege	Granting only the minimum access needed
Defence in depth	Multiple independent layers of security
Lateral movement	Attacker spreading from one compromised system to others
Zero trust	Verifying every request regardless of network location
Perimeter security	Trusting everything inside the network boundary
Egress	Data leaving a cloud network, usually billed
On-demand / reserved / spot instances	Pay as you go / committed discount / cheap but reclaimable
FinOps	Practice of making teams see and manage their cloud costs

Part 6 — Putting it together

Parts 1 to 5 took the system apart and looked at each piece by itself: latency in Part 1, DNS and load balancers in Part 2, databases in Part 3, caches and queues in Part 4, and reliability and security in Part 5. This part puts the pieces back together. It has five sections, and each one is useful on its own:

1. **A request's journey** follows one click from the browser all the way to the database and back, and names every concept along the way. If you can tell this story without notes, you understand the fundamentals.
2. **Worked example: a URL shortener** designs a small but real system from scratch, step by step, with real numbers. It shows the interview method from Part 1 in action.
3. **Decision cheat sheet** is a lookup table: "if you need X, reach for Y".
4. **Top 60 interview questions** are the beginner questions interviewers ask most, with short model answers.
5. **Master A–Z glossary** lists close to 300 of the most important terms, one line each, so you can quickly look up a word you meet in this module or in an interview.

When this part says "see *Load balancers* in Part 2", it means the section with that name in Part 2 of this module. Go back to it whenever a one-line reminder here is not enough.

A request's journey

What it is

A **request's journey** is the full path one user action takes through a system. You click "Like" on a photo, and about a tenth of a second later the heart turns red. In that tenth of a second your request may touch fifteen different machines and use almost every concept in this module. Following that path is the best way to see how the pieces fit.

> **Analogy:** sending a parcel. You write an address (a domain name), the post office looks up the route (DNS), the parcel goes to a local sorting office near you (a CDN edge), then to the main depot (the load balancer), where a clerk checks the label (the API gateway) and hands it to a worker (an app server). The worker looks in a quick-access drawer first (the cache) before going


down to the archive (the database). Anything that can wait, like sending you a receipt, goes into an out-tray (a queue) for someone else to handle later (a worker).

Why it matters


- **It is the most common warm-up question.** "What happens when you type a URL into the browser and press Enter?" is asked at every level, from internships to senior roles.
- **It shows where time goes.** Every hop adds latency. Knowing the hops tells you which ones to remove (with caches, CDNs and connection reuse) when a page is slow.
- **It shows where things break.** Every hop is something that can fail. Knowing the path lets you ask "what if this hop is down?" one hop at a time, which is how you find single points of failure.

The map

Here is the whole path for our example. The user is in London and opens `https://photos.example.com/feed`, a page that shows the latest photos from people they follow.



And here is the same journey as a sequence of messages over time. Read it top to bottom.



How it works

We walk through it one step at a time. The times are typical figures for a user in London talking to a well-run site; your numbers will differ, but the order of magnitude is what matters.

Step 1 — The browser checks what it already knows (0 ms). You type the address and press Enter. The browser splits the URL into a **scheme** (`https`, meaning "HTTP over TLS"), a **host** (`photos.example.com`) and a **path** (`/feed`). Before using the network it checks its own **browser cache**: maybe it already has a fresh copy of this page, or at least a remembered IP address for the host. This is caching at the client, the cheapest cache of all because it involves no network at all. See *Where caches live* in Part 4 and *Clients, servers and the request/response cycle* in Part 1.

Step 2 — DNS turns the name into an IP address (0–50 ms). Computers talk using **IP addresses** such as `203.0.113.10`, not names. The browser asks the operating system, which asks a **recursive resolver** (usually run by your internet provider, or a public one like 1.1.1.1 or 8.8.8.8). If the resolver has the answer cached and its **TTL** (time to live) has not run out, it replies in a few milliseconds. If not, it asks a **root server**, then the **TLD server** for `.com`, then the **authoritative server** for `example.com`. Because `photos.example.com` uses a CDN, the authoritative answer is often a **CNAME** (an alias) pointing at the CDN, and the CDN's DNS returns the IP of an edge server close to the user. This is **GeoDNS** or **anycast** at work. See *DNS — the internet's phone book* and *CDNs and anycast* in Part 2.

Step 3 — TCP opens a connection (about 1 round trip). The browser opens a **TCP** connection to the edge server on **port** 443. TCP needs a **three-way handshake** (SYN, SYN-ACK, ACK) before any data flows. The edge is in London, so a round trip takes maybe 5–10 ms. If the server were in New York it would be around 70 ms, which is the whole reason CDNs exist. See *TCP, UDP and QUIC* in Part 2.

Step 4 — TLS sets up encryption (about 1 more round trip). Because the scheme is `https`, the browser and edge now run a **TLS handshake**. The server shows a **certificate** that proves it really is `photos.example.com`, and the two sides agree on encryption keys. With TLS 1.3 this costs one extra round trip (zero for a repeat visit that uses 0-RTT resumption). If the browser and site support **HTTP/3**, it runs over **QUIC**, which combines the transport and TLS handshakes into one round trip. See *HTTPS and TLS* in Part 2.

Step 5 — The browser sends the HTTP request. Now the real request goes out:

```
GET /feed HTTP/2
Host: photos.example.com
Cookie: session=7f3a9c...
Accept: application/json
```

`GET` is the **HTTP method** (read, do not change anything), the **headers** carry extra information, and the **cookie** carries the session token that says who you are. HTTP itself is **stateless**: the server remembers nothing between requests, so every request must carry its own identity. See *HTTP — the language of the web* in Part 2.

Step 6 — The CDN edge decides: serve or forward (1–5 ms at the edge). A **CDN** (content delivery network) is a set of servers spread around the world, each location called a **point of presence (PoP)**. The edge checks its cache. Static files such as images, JavaScript and CSS are almost always a **cache hit**, served straight from London in a few milliseconds. But `/feed` is personal to you, so it is marked as not cacheable and the edge forwards the request to the **origin** (the company's own servers), often over a fast, already-open connection. Many CDNs also absorb **DDoS** attacks and run a **WAF** (web application firewall) here. See *CDNs and anycast* in Part 2 and *Network security: firewalls, WAF and DDoS* in Part 5.

Step 7 — The load balancer picks a server (under 1 ms). The request reaches the origin's **load balancer**, which spreads traffic across many identical machines. A **layer 7** load balancer can read the HTTP path and headers. It often does **TLS termination** (decrypting here so the servers behind it do not have to). It only sends traffic to targets that pass **health checks**, and it chooses among them with an algorithm such as **round robin** or **least connections**. The load balancer is itself run as a redundant pair or a managed cloud service, so it is not a **single point of failure**. See *Load balancers* in Part 2 and *Redundancy, single points of failure and failover* in Part 1.

Step 8 — The API gateway checks the request (1–5 ms). The **API gateway** is the front door for all the company's APIs. It **authenticates** the request (checks the session or **JWT** to learn that you are user 42), applies **rate limiting** (are you sending too many requests? If so, reply **429 Too Many Requests**), and **routes** `/feed` to the feed service. In smaller systems the load balancer and gateway are the same product. See *Proxies and API gateways* in Part 2, and *Authentication and authorization* and *Rate limiting and throttling* in Part 5.

Step 9 — An app server runs the business logic. The feed service runs on many **stateless** app servers, usually as **containers** managed by **Kubernetes**. Stateless means any server can handle any request, because nothing about you is stored in the server's memory between requests. That is what lets the system **scale horizontally**: add more servers when traffic grows, and let **autoscaling** remove them when it drops. The service may find other services it needs through **service discovery**, and every call it makes has a **timeout**. See *Stateless and stateful services* and *Vertical and horizontal scaling* in Part 1, and *Service discovery, sidecars and service mesh* and *Autoscaling* in Part 5.

Step 10 — Check the cache first (about 0.5 ms). The feed service asks a **distributed cache** such as **Redis**: "do you have the feed for user 42?" This is the **cache-aside** pattern. If it is a **cache hit**, the answer comes back in well under a millisecond and steps 11 and 12 are skipped. A well-tuned cache serves 90–99% of reads this way, which is the main reason big sites are fast and their databases survive. See *Caching strategies* in Part 4.

Step 11 — On a miss, query the database (2–20 ms). On a **cache miss** the service asks the **database**. Reads usually go to a **read replica** (a copy of the data kept in sync from the **primary**), so the primary is free for writes. The query uses an **index** so the database does not scan every row. If the data is too big for one machine, it is **sharded**, and the service (or a routing layer) uses the **shard key** — here, the user ID — to pick the right shard. The service talks to the database through a **connection pool** so it does not pay for a new connection every time. See *Indexes*, *Replication* and Partitioning and sharding in Part 3.

Step 12 — Fill the cache. The service stores the result in the cache with a **TTL** (say 60 seconds), so the next request for the same feed is a hit. Because replicas can be slightly behind (**replication lag**) and the cache can be up to 60 seconds old, the user sees **eventual consistency**: new posts appear within a minute, not instantly. For a feed that is fine. For a bank balance it would not be. See *Consistency models* in Part 4.

Step 13 — The response travels back. The service builds a **JSON** response, and it travels back through the gateway, load balancer and CDN edge. The edge may **compress** it. The browser receives `200 OK`, renders the page, and then fetches the photo files themselves, which are almost all cache hits at the CDN edge.

Step 14 — Asynchronous work happens later. Suppose you now click "Like". That is a **write** (`POST /photos/991/likes`). The service writes the like to the **primary** database and replies at once. But several other things should happen too: notify the photo's owner, update the like counter, feed the recommendation system. None of those need to finish before you see the red heart, so the service puts an event on a **message queue** or **event stream** (such as **Kafka**) and moves on. **Workers** (consumers) pick up the event in the background. Because queues usually give **at-least-once delivery**, the workers must be

idempotent so a duplicate event does not send two notifications. See *Message queues* and *Delivery guarantees, idempotency and retries* in Part 4.

Step 15 — Everything is watched. Every hop writes **logs**, emits **metrics** (request rate, errors, duration) and passes along a **trace ID**, so an engineer can follow this exact request through all the services later. If the error rate rises above the **SLO**, an **alert** pages the **on-call** engineer. See *Observability: logs, metrics and traces* in Part 5.

Where the time goes

A rough budget for the feed request on a first visit, user in London, origin in the same region:

Step	Typical time	How to shrink it
DNS lookup	0–50 ms	DNS caching, long TTL
TCP + TLS handshakes	10–20 ms to a nearby edge	CDN edge nearby, HTTP/3, keep-alive
Edge to origin	5–80 ms	Origin in the user's region
Gateway + app logic	5–20 ms	Fewer service hops, parallel calls
Cache hit / DB query	0.5 ms / 5–20 ms	Higher cache hit ratio, indexes
Browser rendering	50–200 ms	Smaller pages, fewer scripts

The lesson: on a first visit, the **network round trips** often cost more than the server work. That is why repeat visits feel faster: the DNS answer is cached, the connection is reused (**keep-alive**), and static files come from the browser cache.

What can go wrong at each hop

Hop	Failure	Usual protection
DNS	Provider outage, wrong record	Two DNS providers, sensible TTLs
CDN	Edge outage, stale content	Multi-CDN, cache invalidation
Load balancer	LB node dies	Redundant pair or managed LB
App server	Crash, bad deploy	Health checks, canary deploys, rollback
Cache	Cache node dies, stampede	Replicas, request coalescing
Database	Primary dies	Replica failover, backups
Queue/worker	Worker crashes mid-job	At-least-once delivery, retries, DLQ
Any call	Slow dependency	Timeouts, circuit breaker, fallback

Common mistakes

- **Forgetting DNS and TLS.** Beginners jump straight from "browser" to "server". The handshakes are often the slowest part of a first visit.
- **Making everything synchronous.** If the like request waits for the notification email to send, a slow email provider makes liking slow. Push side effects to a queue.
- **Treating the cache as the source of truth.** The database is the truth. The cache is a copy that can be lost or stale at any moment.
- **Forgetting that every box is redundant.** In a design drawing, one "load balancer" box really means at least two machines.

In the interview

Q: What happens when you type a URL and press Enter?

A: The browser checks its cache, then resolves the name with DNS (resolver, root, TLD, authoritative) to get an IP, usually a nearby CDN edge. It opens a TCP connection and does a TLS handshake, then sends

an HTTP GET. The edge serves cached static content or forwards to the origin, where a load balancer picks a healthy server, a gateway authenticates and rate-limits, and the app checks a cache before the database. The response returns the same way, and the browser renders it and fetches images and scripts, mostly from the CDN.

Q: Where would you put a cache in this path?

A: At every layer where it pays: the browser cache for static files, the CDN for public content, a distributed cache like Redis in front of the database for hot data, and the database's own buffer cache. The closer the cache is to the user, the more latency it saves, but the harder it is to invalidate.

Q: Which of these steps would you make asynchronous?

A: Anything the user does not need to see before getting a response: notifications, emails, counters, analytics, search indexing, thumbnails. The request writes the essential data, publishes an event, and returns. Workers do the rest with retries.

TL;DR

One click goes browser cache → DNS → TCP/TLS → CDN → load balancer → API gateway → stateless app server → cache → database, and back; side effects go through a queue to workers. Each hop costs time and can break, so good designs cache it, duplicate it or take it off the user's critical path.

Worked example: designing a URL shortener

What it is

A **URL shortener** turns a long web address into a short one. You give it `https://www.example.com/blog/2026/10/a-very-long-article-title?ref=newsletter` and it gives back `https://sho.rt/aZ3kQ9b`. When anyone opens the short link, the service **redirects** their browser to the long one. Bitly and TinyURL are well-known examples.

Interviewers love it as a first problem: you can finish it in 45 minutes, yet it still needs estimates, an API, a data model, ID generation, caching, sharding and a read-heavy design. Below we design it with the six-step method from *How to approach a system design interview* in Part 1: requirements, estimates, API, data model, high-level design, deep dives.

Step 1 — Requirements

Always start by asking questions. Write down the answers as two lists.

Functional requirements (what the system does):

- Given a long URL, create a short URL.
- Opening the short URL redirects to the long URL.
- Optional: a user may choose a **custom alias** (`sho.rt/my-party`).
- Optional: links can **expire** after a date.
- Optional: show **click counts** to the link's owner.

Non-functional requirements (how well it does it):

- **Very high availability** for redirects. If redirects fail, every link anyone ever shared is broken. Target 99.99% (about 52 minutes of downtime a year — see *Availability and the nines* in Part 1).
- **Low latency** for redirects: p99 under 50 ms at the server.
- **Short links must not be guessable in order**, so people cannot walk through everyone's links by counting.
- **Durability**: once created, a link must never be lost.
- **Read-heavy**: far more redirects than creations. We assume 100 reads per write.

Also say what is **out of scope**: user accounts, a full analytics dashboard, link previews.

Step 2 — Estimates (back of the envelope)

Assume **100 million new short links per month**. A month has about 2.6 million seconds (30 × 86,400 = 2,592,000).

Quantity	Calculation	Result
Writes per second (average)	100 M ÷ 2.6 M s	about 40 /s
Reads per second (average)	40 × 100	about 4,000 /s
Peak reads (3× average)	4,000 × 3	about 12,000 /s
Links over 5 years	100 M × 12 × 5	6 billion
Storage per link	URL + code + metadata	about 500 bytes
Total storage over 5 years	6 B × 500 B	about 3 TB
Read bandwidth	4,000 × 500 B	about 2 MB/s

What these numbers tell us:

- **40 writes per second is tiny.** One ordinary database handles that easily.
- **12,000 reads per second at peak is moderate.** One database could perhaps cope, but with no headroom. A cache will take most of it.
- **3 TB is too much for one cheap machine's memory, but fine for a few database machines.** Sharding is a "later" concern, not day one.
- **How many characters do we need?** If each character can be one of 62 symbols (a–z, A–Z, 0–9, called **base62**), then 6 characters give $62^6 \approx 56.8$ billion codes and 7 characters give $62^7 \approx 3.5$ trillion. We need 6 billion, so 7 characters gives over 500 times headroom. We choose 7.

Cache sizing: clicks are very uneven: a small minority of links collects most of the traffic (people often quote this as the 80/20 rule). A day brings about 350 million redirects (4,000 × 86,400), but far fewer distinct links; suppose 50 million. Keeping the busiest fifth of those, 10 million entries at roughly 500 bytes each, needs about 5 GB. That fits in the memory of a single cache node, and we run a few for redundancy.

Step 3 — API

Two endpoints are enough. See *API styles — REST, RPC and gRPC, GraphQL* and *API design basics* in Part 2.

```
POST /api/v1/links
Content-Type: application/json
Idempotency-Key: 5d1c...

{"long_url": "https://www.example.com/blog/...", "custom_alias": null, "expires_at": null}

-> 201 Created
{"short_url": "https://sho.rt/aZ3kQ9b", "code": "aZ3kQ9b"}
```

```
GET /aZ3kQ9b

-> 302 Found
Location: https://www.example.com/blog/...
```

Design notes:

- The `v1` in the path is **API versioning**, so we can change the API later without breaking old clients.
- The **idempotency key** means that if the client times out and retries, it gets the same short link back instead of creating two. See *Delivery guarantees, idempotency and retries* in Part 4.
- The create endpoint is **rate limited** per API key or IP (for example 100 per hour) to stop spammers. Over the limit, it replies `429`. See *Rate limiting and throttling* in Part 5.
- A missing or expired code returns `404 Not Found` (or `410 Gone` for an expired link).

301 or 302? Both are **HTTP redirect** status codes. A **301 Moved Permanently** tells the browser it may remember the redirect and skip our server next time. That saves load, but we stop seeing repeat clicks, so click counts are wrong and we cannot change or expire the link for browsers that cached it. A **302 Found** (temporary) makes the browser ask us every time. Choose 302 if analytics or expiry matter, 301 if pure speed and low cost matter. Saying this trade-off out loud is worth points in the interview.

Step 4 — Data model

One main table. A relational database such as PostgreSQL works well; a key-value store such as DynamoDB or Cassandra works too, because every read is "look up one row by its code". See *SQL vs NoSQL and BASE* in Part 3.

Column	Type	Notes
`code`	varchar(16)	Primary key, e.g. `aZ3kQ9b`
`long_url`	text	Up to about 2 KB
`owner_id`	bigint	Nullable for anonymous links
`created_at`	timestamp	
`expires_at`	timestamp	Nullable

The primary key on `code` gives us an **index** for free, so a redirect is a single index lookup. Clicks are **not** stored by updating a counter in this row on every redirect — that would turn every read into a write. Instead they go to a separate analytics pipeline (see the deep dives).

Step 5 — Generating the short code

This is the heart of the problem. Four common options:

Approach	How	Pros	Cons
Hash the URL	MD5/SHA-256 of the long URL, take 7 base62 chars	Same URL gets same code	Collisions, must check and retry
Random code	7 random base62 chars	Simple, not guessable	Must check for collisions
Counter + base62	Global counter 1, 2, 3 … encoded in base62	No collisions	Counter is a bottleneck, guessable
Key generation service	Pre-make unused codes, hand out in batches	Fast, no collisions	One more service to run


A good beginner answer is **counter ranges plus base62, with shuffling**:

1. A small coordination store (a database row, or ZooKeeper/etcd) hands each app server a **range** of numbers, for example server A gets 1,000,000–1,999,999 and server B gets 2,000,000–2,999,999.
2. Each server counts through its own range in memory, with no network call per link. When it runs out, it asks for a new range. If a server crashes, the rest of its range is simply skipped — we have trillions to spare.
3. The number is **scrambled** with a reversible mixing function (or a block cipher) before encoding, so consecutive links do not get consecutive codes. That meets the "not guessable in order" requirement.
4. The scrambled number is written in **base62**, giving a 7-character code.

Alternatively a **Snowflake-style ID** (a 64-bit number built from timestamp + machine ID + sequence) needs no coordination at all, but the resulting code is 11 characters in base62, longer than we want. See *Unique ID generation* in Part 4.

Custom aliases skip the generator. We simply try to insert the alias as the primary key; if the insert fails because the key exists, we reply `409 Conflict`. The database's uniqueness check is what makes this safe when two people race for the same alias.

Step 6 — High-level design



Redirect path (read, 99% of traffic):

1. `GET /aZ3kQ9b` arrives through DNS, the CDN and the load balancer at any link-service instance.
2. The service looks up `aZ3kQ9b` in **Redis** (cache-aside). On a hit (most of the time) it has the long URL in under a millisecond.
3. On a miss it reads from a **database replica**, then writes the result into Redis with a TTL of, say, 24 hours.
4. It checks `expires_at`, publishes a small "click" event to the queue without waiting, and returns `302` with the `Location` header.

Create path (write, 1% of traffic):

1. `POST /api/v1/links` passes the gateway's authentication and rate limiter.
2. The service validates the URL (well-formed, not on a malware blocklist), takes the next number from its range, scrambles and encodes it.
3. It inserts the row into the **primary** database and returns `201` with the short URL. No cache write is needed; the first redirect fills the cache.

Step 7 — Deep dives

Caching. With a 90%+ hit ratio, the 12,000 peak reads per second become about 1,200 database reads per second, which two read replicas handle easily. Links almost never change, so the cache rarely needs invalidating. When a link is deleted or expires, we delete its cache key. To stop a viral link causing a **cache stampede** when its entry expires, we let only one request refill it (request coalescing). See *Cache invalidation, stale data and stampedes* in Part 4.

Even faster: cache at the edge. For links without analytics we can let the CDN cache the redirect response itself for a few minutes, so most clicks never reach our servers at all.

Scaling the database. 3 TB over five years fits in a primary with a few replicas at first. When it outgrows that, we **shard by hash of** `code`. Every redirect knows its code, so every query goes to exactly

one shard — the ideal shard key. Using **consistent hashing** makes adding shards move only a small share of the keys. See Partitioning and sharding in Part 3.

Availability. Every tier runs at least two copies across **availability zones**. The link service is stateless, so a dead instance is simply removed by the load balancer's health checks. The database fails over to a replica if the primary dies. Because the redirect path only needs reads, it can keep working from replicas and cache even while the primary is being replaced — a form of **graceful degradation**: creating links pauses for a minute, but existing links keep working.

Analytics. Writing a counter on every click would put 12,000 writes per second on the database. Instead each click becomes an event on **Kafka**. Workers batch them and update counts once a minute in an analytics store (for example a column store such as ClickHouse). Counts are a little delayed — **eventual consistency** — which owners accept. If a worker crashes, the events are re-read from the queue (**at-least-once**); de-duplicating by event ID keeps counts honest.

Abuse. Short links are popular with spammers. Rate-limit creation, check long URLs against malware lists, and allow links to be disabled.

Trade-offs we made

- **302 over 301:** more load on us, but accurate analytics and the ability to expire links.
- **Counter ranges over hashing:** no collision checks, at the cost of a small coordination store.
- **Eventual consistency for click counts:** much cheaper writes, slightly stale numbers.
- **Cache with long TTL:** fast and cheap, safe because links are effectively immutable.

Common mistakes

- **Skipping the estimates.** Without them you cannot justify 7 characters, the cache size or whether you need sharding at all.
- **Using a single auto-increment column in one database as the generator** and calling it scalable. It works at 40 writes per second, but say out loud that it is a bottleneck and a single point of failure, and how you would fix it.
- **Taking the first 7 characters of an MD5 hash and ignoring collisions.** With billions of links, collisions are certain. You must detect and retry.
- **Updating a click counter on the redirect path.** It makes the cheapest, most common operation expensive.
- **Over-engineering.** Do not open with 50 shards and three regions for 40 writes per second. Start simple, then show how it grows.

In the interview

Q: How long should the short code be?

A: It depends on how many links we must hold. With base62, 7 characters give about 3.5 trillion codes; we expect about 6 billion in five years, so 7 leaves plenty of headroom. 6 characters (about 57 billion) would also work but with less margin.

Q: How would you handle one link going viral with millions of clicks a minute?

A: It is a hot key, but a read-only one, so caching solves it: the entry sits in Redis, we can add a small in-process cache on each app server for the very hottest keys, and we can let the CDN cache the redirect for a short time. Request coalescing prevents a stampede when the entry expires.

Q: SQL or NoSQL?

A: Either works because access is a simple key lookup and the write rate is low. I would start with PostgreSQL for its familiarity and strong uniqueness guarantees, and note that a key-value store such as DynamoDB scales out more simply if we reach many terabytes.

TL;DR

At heart the service maps a code to a URL and is read about a hundred times per write: generate a unique 7-character base62 code (counter ranges plus scrambling), store code → URL in a database, put Redis and optionally the CDN in front for the 100:1 reads, return a 302, and push click analytics through a queue.


Decision cheat sheet

What it is

A lookup table of the most common design needs and the tool or pattern people usually reach for. It is a starting point, not a rule: in an interview, name the tool, then say **why** and **what it costs**. The "Watch out for" column is the part that earns the marks.

How to use it

Read the left column as "the interviewer just told me…". For example, "the system is read-heavy" → add a cache and read replicas. Then check the right column before committing.



The table

If you need…	Reach for…	Watch out for…
Faster reads of the same data	Cache (Redis, Memcached), cache-aside	Stale data, invalidation, stampedes
Fast static files worldwide	CDN	Invalidation delay, cost per GB
Lower latency for far-away users	CDN, edge, multi-region deployment	Data consistency across regions
More capacity for stateless servers	Horizontal scaling behind a load balancer	Must move session state out of servers
A quick capacity bump, small system	Vertical scaling (bigger machine)	Hard ceiling, still one machine
To spread traffic across servers	Load balancer (L7 for HTTP, L4 for raw TCP)	LB must be redundant itself
Traffic that grows and shrinks daily	Autoscaling	Slow start-up, scale on the right metric
One public entry point for many services	API gateway	Can become a bottleneck or a "god" layer
Strong consistency and transactions	Relational database (PostgreSQL, MySQL)	Harder to scale writes beyond one primary
Flexible, nested records	Document store (MongoDB)	Joins and multi-document transactions are weaker
Simple lookups by key at huge scale	Key-value store (DynamoDB, Redis)	Few query patterns besides by key
Very high write rate, time-ordered data	Wide-column or LSM-based store (Cassandra)	Design tables around queries, eventual consistency
Metrics and sensor readings over time	Time-series database (Prometheus, InfluxDB)	Retention and downsampling planning
Relationship queries (friends of friends)	Graph database (Neo4j)	Harder to shard
Full-text search, fuzzy matching	Search engine (Elasticsearch, OpenSearch)	It is a copy: keep it in sync, not the source of truth
Similarity search on embeddings	Vector database or vector index (pgvector)	Approximate results, memory hungry
Store large files (images, video, backups)	Object storage (Amazon S3)	Not for frequent small updates
More read capacity on the database	Read replicas	Replication lag, read-your-writes issues
More write capacity or data than one machine	Sharding with a good shard key	Hot spots, cross-shard queries, resharding
Add or remove nodes without moving most data	Consistent hashing with virtual nodes	Still some data movement, needs balancing
Fast queries on a column	Index (B-tree)	Slower writes, extra storage
Do slow work without making the user wait	Message queue + workers (SQS, RabbitMQ)	Duplicates, need idempotency and a DLQ
Many services react to one event	Pub/sub or event stream (Kafka, SNS)	Ordering, schema changes
Replay past events, high-throughput logs	Event streaming (Kafka)	Partitions limit parallelism, ops effort

If you need…	Reach for…	Watch out for…
Safe retries of a payment or order	Idempotency key	Storing keys, choosing an expiry
Absorb traffic spikes	Queue as a buffer, backpressure	Queue growth hides overload
Protect a service from abusive clients	Rate limiting (token bucket) returning 429	Fair limits per user, distributed counters
Stop a failing dependency dragging you down	Timeouts + circuit breaker + fallback	Picking thresholds, testing the open state
Retry transient failures	Retries with exponential backoff and jitter	Retry storms, only retry idempotent calls
Keep one failure from sinking everything	Bulkheads (separate pools)	Unused reserved capacity
Survive a whole data-centre outage	Multi-AZ, then multi-region, failover	Cost, replication lag, split brain
A consistent operation across services	Saga with compensating actions	Complex failure handling, interim states
Atomic commit across two databases	Two-phase commit (2PC)	Blocking if the coordinator fails, slow
Only one worker doing a job at a time	Distributed lock (with fencing tokens) or leader election	Lock expiry while still working
Nodes agreeing on a value or leader	Consensus (Raft via etcd/ZooKeeper)	Needs a majority, latency of writes
Unique IDs without coordination	UUID or Snowflake-style IDs	UUIDv4 is random (poor index locality), clock issues
"Have we seen this before?" with little memory	Bloom filter	False positives possible
Count distinct users cheaply	HyperLogLog	Approximate (about 1% error)
Find nearby places	Geohash or quadtree, geo index	Edge cases at cell borders
Real-time updates to the browser, server to client	Server-Sent Events	One direction only
Two-way real-time (chat, games)	WebSockets	Stateful connections, harder load balancing
Notify another company's system	Webhooks	Retries, signatures, duplicates
Fast internal service-to-service calls	gRPC with Protobuf	Browser support needs a proxy
Clients choosing exactly which fields they get	GraphQL	Caching, expensive queries
Large data analysis overnight	Batch processing (Spark), data warehouse	Results are hours old
Results within seconds of events	Stream processing (Flink, Kafka Streams)	Harder to get right, state management
Know what is happening in production	Metrics, logs, traces, alerts on SLOs	Alert fatigue, cost of logs
Release safely	Canary or blue-green deploys, feature flags	Database changes still need care

If you need…	Reach for…	Watch out for…
Users log in once for many apps	SSO with OpenID Connect	Central identity provider is critical
Let an app act for a user on another service	OAuth 2.0	Token storage and scopes
Stateless auth across services	Signed tokens (JWT)	Hard to revoke before expiry
Store passwords	bcrypt, scrypt or Argon2 (slow, salted hashing)	Never encrypt or plain-hash passwords
Protect secrets like API keys	Secrets manager (Vault, AWS Secrets Manager)	Rotation, access audit

TL;DR

Every "reach for" brings a "watch out for". Naming both in one sentence — "I'd add read replicas, accepting some replication lag" — is the habit that interviewers look for.

Top 60 interview questions

What it is

These are the beginner-level questions that come up most in system design interviews and phone screens. Each answer is 2–4 sentences: about what you would say out loud before the interviewer asks a follow-up. The section in brackets tells you where to read more.

Foundations and performance

Q1: What is system design?

A: System design is deciding how the parts of a software system — servers, databases, caches, queues, networks — fit together so it meets its requirements for features, scale, speed and reliability. It is about trade-offs rather than one right answer. (*What system design is*, Part 1.)

Q2: What is the difference between latency and throughput?

A: Latency is how long one request takes, for example 120 ms. Throughput is how many requests the system completes per unit of time, for example 5,000 requests per second. The two can move apart: a cargo ship carries thousands of containers per trip (huge throughput) yet each one takes weeks to arrive (high latency). (*Latency, throughput and bandwidth*, Part 1.)

Q3: Why do we measure p99 latency instead of the average?

A: The average hides the slow requests: a few 5-second requests disappear among thousands of fast ones. p99 means 99% of requests are faster than this value, so it shows what the unluckiest 1% of users feel. A page that makes 100 backend calls will almost always hit at least one p99-slow call, so tail latency matters a lot at scale. (*Percentiles, tail latency and why averages lie*, Part 1.)

Q4: What is Little's law and why is it useful?

A: It says the average number of requests in a system equals the arrival rate times the average time each spends inside: $L = \lambda \times W$. If 1,000 requests per second each take 0.2 seconds, about 200 are in flight at any moment, which tells you how many threads or connections you need. (*Little's law*, Part 1.)

Q5: How do you estimate QPS for a system?

A: Start from daily active users and actions per user: 10 million DAU × 10 requests each = 100 million requests per day. Divide by about 86,400 seconds (round to 100,000) to get about 1,000 QPS on average, then multiply by a peak factor of 2–3 for busy hours. (*Back-of-the-envelope estimation*, Part 1.)

Q6: What does "four nines" availability mean?

A: 99.99% availability: the service may be down for about 52.6 minutes a year, or about 4.4 minutes a month. Each extra nine cuts allowed downtime by ten times and usually costs much more to achieve.

(*Availability and the nines*, Part 1.)

Q7: What is the difference between an SLA, an SLO and an SLI?

A: An SLI (indicator) is a measurement, such as the percentage of requests that succeed. An SLO (objective) is the internal target for it, such as 99.9% over 30 days. An SLA (agreement) is a contract with customers, usually looser than the SLO, with refunds or penalties if it is missed. (*SLA, SLO, SLI and error budgets*, Part 1.)

Q8: What is an error budget?

A: It is the amount of failure the SLO allows: a 99.9% SLO leaves 0.1% of requests (or about 43 minutes a month) that may fail. While budget remains, teams can ship fast; when it is spent, they slow down and focus on reliability. (*SLA, SLO, SLI and error budgets*, Part 1.)

Q9: What is the difference between vertical and horizontal scaling?

A: Vertical scaling (scale up) means a bigger machine: more CPU, memory or disk. Horizontal scaling (scale out) means more machines sharing the work. Vertical is simpler but has a ceiling and stays a single point of failure; horizontal grows further and adds redundancy but needs load balancing and stateless services. (*Vertical and horizontal scaling*, Part 1.)

Q10: What does "stateless service" mean and why does it help scaling?

A: A stateless service keeps no per-user data in its own memory between requests; session data lives in a shared store such as Redis or a database, or in a token the client sends. Any instance can then serve any request, so you can add, remove or replace instances freely behind a load balancer. (*Stateless and stateful services*, Part 1.)

Q11: What is a single point of failure and how do you remove one?

A: It is any component whose failure takes the whole system down, such as one database server or one load balancer. You remove it with redundancy — two or more copies — plus automatic failover and health checks so traffic moves to a healthy copy. (*Redundancy, single points of failure and failover*, Part 1.)

Q12: What is the difference between reliability, availability and durability?

A: Availability is whether the system answers right now. Reliability is whether it keeps doing the right thing correctly over time. Durability is whether saved data survives — Amazon S3, for example, is designed for 99.999999999% (eleven nines) annual durability of stored objects. (*Reliability, availability and durability*, Part 1.)

Q13: How do you approach a system design interview question?

A: Clarify functional and non-functional requirements, do quick estimates, define the API and data model, draw a simple high-level design, then deep-dive into the hardest parts and discuss trade-offs and failures. Keep talking through your reasoning, and start simple before adding complexity. (*How to approach a system design interview*, Part 1.)

Networking and communication

Q14: How does DNS work?

A: Your device asks a recursive resolver for a name. If not cached, the resolver asks a root server, which points to the TLD server (for `.com`), which points to the domain's authoritative server, which returns the IP address. Every answer is cached for its TTL so most lookups take only milliseconds. (*DNS — the internet's phone book*, Part 2.)

Q15: What is the difference between TCP and UDP?

A: TCP sets up a connection with a handshake and guarantees that bytes arrive complete, in order, with congestion control; it is used for web pages, APIs and databases. UDP just sends individual packets with no guarantees, so it has less overhead and no waiting for lost packets; it is used for video calls, games and DNS queries, and as the base of QUIC. (*TCP, UDP and QUIC*, Part 2.)

Q16: What changed between HTTP/1.1, HTTP/2 and HTTP/3?

A: HTTP/1.1 handles one request at a time per connection, so browsers open several connections. HTTP/2 multiplexes many requests over one TCP connection with compressed headers, but a lost TCP packet still stalls all of them (head-of-line blocking). HTTP/3 runs over QUIC on UDP, so streams are independent and connection set-up is faster. (*HTTP — the language of the web*, Part 2.)

Q17: What does HTTPS add to HTTP?

A: HTTPS is HTTP inside a TLS connection. TLS encrypts the traffic so others on the network cannot read or change it, and the server's certificate, signed by a trusted certificate authority, proves you are talking to the real site. (*HTTPS and TLS*, Part 2.)

Q18: Which HTTP methods are idempotent and why does it matter?

A: GET, PUT, DELETE, HEAD and OPTIONS are idempotent: repeating them has the same effect as doing them once. POST (and usually PATCH) is not. It matters because networks fail and clients retry; idempotent requests are safe to retry, while non-idempotent ones need an idempotency key. (*HTTP — the language of the web*, Part 2.)

Q19: REST vs gRPC vs GraphQL — when would you use each?

A: REST over JSON is the simple, widely understood default for public APIs. gRPC uses Protobuf over HTTP/2 and is fast and strongly typed, so it suits internal service-to-service calls. GraphQL lets clients ask for exactly the fields they need in one request, which helps mobile apps and complex UIs with many data sources. (*API styles — REST, RPC and gRPC, GraphQL*, Part 2.)

Q20: How do you push real-time updates to a browser?

A: Short polling asks repeatedly on a timer; long polling holds a request open until there is news; Server-Sent Events keep one HTTP response open for a server-to-client stream; WebSockets give a full two-way connection. Use SSE for one-way feeds such as live scores and WebSockets for chat or games. (*Real-time communication — polling, long polling, WebSockets, SSE, webhooks*, Part 2.)

Q21: What is a load balancer and why do you need one?

A: It sits in front of a group of servers and spreads incoming requests across them. It lets you scale horizontally, sends traffic only to healthy servers (via health checks), and lets you deploy or remove servers without users noticing. (*Load balancers*, Part 2.)

Q22: What is the difference between an L4 and an L7 load balancer?

A: An L4 load balancer routes by IP address and port without looking inside the traffic, so it is very fast and works for any TCP or UDP protocol (for example AWS NLB). An L7 load balancer understands HTTP, so it can route by path, header or cookie, terminate TLS and retry requests, at somewhat higher cost (for example AWS ALB, NGINX, Envoy). (*Load balancers*, Part 2.)

Q23: Name some load-balancing algorithms.

A: Round robin sends requests to each server in turn; weighted round robin gives bigger servers more; least connections picks the server with the fewest open connections; IP hash or consistent hashing sends the same client or key to the same server; power of two choices picks two random servers and uses the less busy one. (*Load balancers*, Part 2.)

Q24: What are sticky sessions and why are they often avoided?

A: Sticky sessions make the load balancer send a user to the same server every time, usually via a cookie, so in-memory session data keeps working. They cause uneven load and lost sessions when a server dies, so the better fix is stateless servers with sessions in a shared store. (*Load balancers*, Part 2.)

Q25: What is a CDN and how does it help?

A: A content delivery network is a set of servers in many cities that cache your content close to users. It cuts latency (a few milliseconds instead of a cross-ocean round trip), offloads traffic from your origin servers, and helps absorb DDoS attacks. (*CDNs and anycast*, Part 2.)

Q26: What is the difference between a forward proxy and a reverse proxy?

A: A forward proxy sits in front of clients and makes requests on their behalf, for example a company proxy that filters web access. A reverse proxy sits in front of servers and receives requests on their behalf, providing load balancing, TLS termination, caching and protection; NGINX is a common one. (*Proxies and API gateways*, Part 2.)

Q27: What is an API gateway?

A: It is a reverse proxy that acts as the single entry point for many backend services. It handles shared concerns such as authentication, rate limiting, routing, request transformation and logging so each service does not have to. (*Proxies and API gateways*, Part 2.)

Q28: Offset or cursor pagination?

A: Offset pagination (`?page=5` or `OFFSET 100`) is simple but gets slow on deep pages and can skip or repeat items when data changes. Cursor pagination passes a pointer to the last item seen (`?after=abc`), stays fast and stable, and suits feeds and large lists. (*API design basics*, Part 2.)

Data storage

Q29: SQL or NoSQL — how do you choose?

A: Choose SQL when you need transactions, joins and a well-defined schema, such as orders and payments. Choose a NoSQL family when you need a specific shape at large scale: key-value for simple lookups, document for flexible records, wide-column for heavy writes, graph for relationships. Many systems use both. (*SQL vs NoSQL and BASE*, Part 3.)

Q30: What does ACID mean?

A: Atomicity: a transaction happens completely or not at all. Consistency: it moves the database from one valid state to another, respecting rules. Isolation: concurrent transactions do not see each other's half-finished work. Durability: once committed, data survives crashes. (*Transactions and ACID*, Part 3.)

Q31: What is an index and what does it cost?

A: An index is an extra data structure, usually a B-tree, that lets the database find rows by a column without scanning the whole table — like the index at the back of a book. It makes reads much faster but slows writes, because every insert or update must also update the index, and it uses storage. (*Indexes*, Part 3.)

Q32: What is the difference between replication and sharding?

A: Replication keeps full copies of the same data on several machines, which improves availability and read capacity. Sharding splits the data so each machine holds a different part, which increases write capacity and total storage. Large systems usually do both: each shard is replicated. (*Replication* and Partitioning and sharding, Part 3.)

Q33: Synchronous vs asynchronous replication?

A: With synchronous replication, the primary waits for the replica to confirm before telling the client the write succeeded: no data loss on failover, but slower writes. With asynchronous replication, the primary confirms immediately: faster, but recent writes can be lost if the primary dies and replicas may lag behind. (*Replication*, Part 3.)

Q34: What is replication lag and how does it affect users?

A: It is the delay before a write on the primary shows up on a replica, usually milliseconds but sometimes seconds. A user who posts a comment and then reads from a lagging replica may not see it. Fixes include reading your own recent writes from the primary or tracking the write position. (*Replication*, Part 3, and *Consistency models*, Part 4.)

Q35: How do you choose a shard key?

A: Pick a key that spreads data and traffic evenly and that most queries include, so each query hits one shard. User ID is a common choice; a timestamp is usually bad because all new writes go to the same shard, creating a hot spot. (*Partitioning and sharding*, Part 3.)

Q36: What is consistent hashing?

A: Servers and keys are placed on the same hash ring, and each key belongs to the next server clockwise. When a server is added or removed, only the keys next to it move, about 1/N of them, instead of almost all keys as with `hash mod N`. Virtual nodes give each server many points on the ring for an even spread. (*Consistent hashing and virtual nodes*, Part 3.)

Q37: Normalization or denormalization?

A: Normalization stores each fact once and links tables with keys, which avoids inconsistent copies but needs joins. Denormalization copies data into the shape you read it, making reads fast at the cost of more storage and keeping copies in sync. Read-heavy systems often denormalize their hottest paths. (*Normalization and denormalization*, Part 3.)

Q38: When would you use object storage?

A: For large, unstructured files that are written once and read many times: images, videos, backups, logs, data-lake files. Services like Amazon S3 are cheap, extremely durable and scale without limit; you store the file there and keep only its URL and metadata in the database. (*Storage types: block, file and object*, Part 3.)

Q39: What is the difference between OLTP and OLAP?

A: OLTP (online transaction processing) handles many small, fast reads and writes for the live application, such as placing an order. OLAP (online analytical processing) runs large queries over lots of historical data for reports, usually in a column-oriented data warehouse. (*OLTP vs OLAP, row vs column storage, lakes and warehouses*, Part 3.)

Q40: What is the N+1 query problem?

A: Code fetches a list with one query, then runs one more query per item to fetch related data: 1 + N queries instead of 1 or 2. It often hides behind an ORM and makes pages slow. Fix it with a join, an `IN (...)` batch query or eager loading. (*Connection pooling, ORMs and N+1 queries*, Part 3.)

Caching, async and consistency

Q41: Explain cache-aside.

A: The application checks the cache first. On a hit it returns the cached value; on a miss it reads the database, stores the result in the cache with a TTL, and returns it. On writes, it updates the database and deletes the cache entry. It is the most common caching pattern. (*Caching strategies*, Part 4.)

Q42: Write-through vs write-back caching?

A: Write-through writes to the cache and the database together, so the cache is always fresh but each write pays both costs. Write-back (write-behind) writes to the cache and saves to the database later in batches, giving fast writes but risking data loss if the cache fails before flushing. (*Caching strategies*, Part 4.)

Q43: What is LRU eviction?

A: Least Recently Used: when the cache is full, it removes the item that has gone longest without being read. It works well because recently used data tends to be used again soon. Alternatives include LFU (least frequently used) and simple TTL expiry. (*Eviction policies*, Part 4.)

Q44: What is a cache stampede and how do you prevent it?

A: When a popular cache entry expires, thousands of requests miss at once and all hit the database together, which can knock it over. Prevent it with request coalescing (only one request refills, others wait), a lock around the refill, random jitter on TTLs, or refreshing popular entries before they expire. (*Cache invalidation, stale data and stampedes*, Part 4.)

Q45: Why use a message queue?

A: It decouples the sender from the worker: the sender drops a message and returns immediately, and workers process it at their own pace. This smooths traffic spikes, lets the worker be down for a while without losing work, and lets you scale producers and consumers separately. (*Message queues*, Part 4.)

Q46: Queue vs publish/subscribe?

A: In a queue (point-to-point), each message is handled by exactly one consumer — good for jobs. In publish/subscribe, every subscriber gets its own copy of each message — good for events that several services care about. Kafka can do both using consumer groups. (*Message queues*, Part 4.)

Q47: At-most-once, at-least-once, exactly-once — what do they mean?

A: At-most-once may lose messages but never duplicates them. At-least-once never loses them but may deliver some twice, which is the common default. Exactly-once is very hard end to end; in practice it means at-least-once delivery plus idempotent processing, sometimes called effectively-once. (*Delivery guarantees, idempotency and retries*, Part 4.)

Q48: What is idempotency and how do you implement it?

A: An operation is idempotent if doing it twice has the same effect as doing it once. Implement it by giving each request or message a unique ID (an idempotency key), recording processed IDs, and skipping or returning the stored result when an ID repeats. (*Delivery guarantees, idempotency and retries*, Part 4.)

Q49: What is a dead-letter queue?

A: A separate queue where messages go after failing processing a set number of times. It stops one bad message from blocking or endlessly retrying, and lets engineers inspect and replay failures later. (*Delivery guarantees, idempotency and retries*, Part 4.)

Q50: Strong vs eventual consistency?

A: With strong consistency, every read sees the latest successful write, as if there were one copy of the data. With eventual consistency, replicas may briefly disagree, but if writes stop they all converge. Strong is simpler to reason about but costs latency and availability; eventual is faster and more available. (*Consistency models*, Part 4.)

Q51: Explain the CAP theorem.

A: When a network partition splits a distributed system, it must choose between consistency (refuse or delay some requests so no one sees stale data) and availability (answer everything, possibly with stale data). Partitions cannot be ruled out, so the real choice is CP vs AP during a partition; when there is no partition you can have both. (*CAP theorem and PACELC*, Part 4.)

Q52: What is a quorum?

A: With N replicas, a write must be confirmed by W of them and a read must ask R of them. If R + W > N, every read overlaps at least one replica holding the latest write. A common setting is N = 3, W = 2, R = 2. (*Quorums*, Part 4.)

Q53: Why do distributed systems need consensus algorithms like Raft?

A: Several nodes must agree on one value — such as who the leader is or the order of log entries — even when some nodes crash or messages are delayed. Raft and Paxos do this safely as long as a majority is reachable. Tools like etcd and ZooKeeper provide it so you do not have to build it. (*Consensus, leader election and distributed locks*, Part 4.)

Q54: 2PC or saga for a transaction across services?

A: Two-phase commit has a coordinator ask everyone to prepare, then commit; it gives atomicity but blocks if the coordinator fails and couples services tightly. A saga runs a chain of local transactions and, on failure, runs compensating actions to undo earlier steps; it is the usual choice for microservices, accepting temporary inconsistency. (*Distributed transactions: two-phase commit and sagas*, Part 4.)

Architecture, reliability and security

Q55: Monolith or microservices?

A: A monolith is one deployable application: simple to build, test and deploy, and the right default for small teams. Microservices split the system into independently deployable services owned by separate teams, helping large organizations scale but adding network calls, distributed failures and operational work. Many teams start with a modular monolith. (*Architectural styles: monolith, modular monolith, SOA, microservices and serverless*, Part 5.)

Q56: What is a circuit breaker?

A: It wraps calls to a dependency and counts failures. After too many, it "opens" and fails fast without calling, giving the dependency time to recover; after a pause it goes "half-open" and lets a few test calls through, closing again if they succeed. It stops one slow service from tying up all your threads. (*Circuit breakers, bulkheads and fallbacks*, Part 5.)

Q57: Why add jitter to exponential backoff?

A: Exponential backoff waits 1, 2, 4, 8 seconds between retries so a struggling service gets breathing room. Without jitter, thousands of clients that failed together retry together, in synchronized waves. Adding randomness spreads retries out. (*Timeouts, retries, exponential backoff and jitter*, Part 5.)

Q58: How does the token bucket rate limiter work?

A: A bucket holds up to B tokens and is refilled at R tokens per second. Each request takes one token; if the bucket is empty the request is rejected with 429. It allows short bursts up to B while enforcing an average rate of R. (*Rate limiting and throttling*, Part 5.)

Q59: What is the difference between authentication and authorization?

A: Authentication answers "who are you?" — for example by checking a password or a token. Authorization answers "what are you allowed to do?" — for example whether user 42 may delete this post. Authentication always comes first. (*Authentication and authorization*, Part 5.)

Q60: What are RPO and RTO?

A: RPO (recovery point objective) is how much data you can afford to lose, measured in time: an RPO of 5 minutes means backups or replication must be at most 5 minutes behind. RTO (recovery time objective) is how long you can be down before service is restored. Lower values of either cost more. (*Disaster recovery*, Part 5.)

TL;DR

If you can answer these 60 in your own words, with a number or an example in each answer, you have the fundamentals an interviewer expects from a beginner.

Master A–Z glossary

What it is

The most important terms from Parts 1 to 5, plus a few related words you will meet in system design reading and interviews, in alphabetical order with a one-line meaning. Closely related terms share a row (for example "LRU / LFU"). Use it as a quick reminder; each part's own glossary has the complete list, and the parts themselves have the full explanations.

A

Term	Meaning in one line
A / AAAA record	DNS records that map a name to an IPv4 / IPv6 address
ABAC	Attribute-based access control: permissions decided by attributes of user, resource and context
ACID	Transaction guarantees: atomicity (all or nothing), consistency (rules kept), isolation (no interference), durability (survives crashes)
Active-active	Two or more sites or nodes all serving traffic at once
Active-passive	One node serves traffic while a standby waits to take over
Active / passive health check	Load balancer probes servers on a schedule / ejects them after real requests fail
Anycast	Many servers announce the same IP address and the network routes each user to the nearest one
API	Application programming interface: the defined way one program asks another to do something
API gateway	Single entry point for APIs that handles auth, rate limits and routing
API key	Secret string that identifies a calling application
At-least-once / at-most-once delivery	Messages never lost but maybe duplicated / never duplicated but maybe lost
Authentication	Proving who you are
Authoritative name server	DNS server that holds the real records for a domain
Authorization	Deciding what an identified user may do
Autoscaling	Automatically adding or removing servers based on load
Availability	Share of time a system is up and answering correctly
Availability zone (AZ)	One or more isolated data centres with independent power and networking inside a cloud region

B

Term	Meaning in one line
Back-of-the-envelope estimate	Quick rough calculation of load, storage and bandwidth
Backpressure	A slow consumer signalling producers to slow down
Bandwidth	Maximum data a link can carry per second
BASE	Basically available, soft state, eventually consistent: the NoSQL alternative to ACID
Base62	Writing numbers using 62 symbols (a–z, A–Z, 0–9) to make short codes
Batch processing	Processing a large set of stored data in one job, often on a schedule
bcrypt	Deliberately slow, salted password-hashing function
Block storage	Raw fixed-size disk blocks attached to one machine, like a virtual hard drive
Bloom filter	Compact structure that says "definitely not present" or "probably present"
Blue-green deployment	Run old (blue) and new (green) versions side by side and switch traffic at once
B-tree	Balanced tree structure used by most database indexes
Bulkhead	Separate resource pools so one failing part cannot exhaust everything
Burn rate	How fast the error budget is being spent; 1 means exactly on budget for the SLO window

C

Term	Meaning in one line
Cache	Fast storage holding copies of data to serve repeat reads quickly
Cache-aside	App checks cache, on miss loads from database and fills the cache
Cache hit / miss	Requested data was / was not found in the cache; hits ÷ all requests is the hit ratio
Cache invalidation	Removing or updating cached data when the source changes
Cache stampede	Many requests miss the same expired key and hit the database at once
Canary deployment	Release a new version to a small share of traffic first
CAP theorem	During a network partition a system must choose consistency or availability
Causal consistency	Effects are never seen before their causes
CDN	Content delivery network: servers worldwide that cache content near users
Certificate (TLS)	Document signed by a trusted certificate authority (CA) proving a server owns a domain name
Chaos engineering	Deliberately injecting failures to test resilience
CI/CD	Continuous integration and continuous delivery/deployment: automated build, test and release
Circuit breaker	Stops calling a failing dependency for a while so it can recover
CNAME record	DNS record that makes one name an alias of another
Cold start	Extra delay when a new instance or serverless function starts
Column-oriented storage	Stores each column together, great for analytics scans
Compensating action	Step that undoes an earlier step in a saga
Concurrency / parallelism	Many tasks in progress at once by taking turns / tasks literally running at the same moment
Connection draining	Letting a server finish in-flight requests before removing it
Connection pool	Set of reusable open database connections
Consensus	Nodes agreeing on a single value despite failures
Consistency (ACID)	Transactions keep the data valid under all rules
Consistency (distributed)	Whether all readers see the same, latest data
Consistent hashing	Hash ring placement that moves few keys when nodes change
Consumer	Program that reads messages from a queue or stream
Consumer group	Set of consumers that share a topic's partitions
Container	Lightweight packaged app with its dependencies, sharing the host OS kernel
Cookie	Small piece of data a site stores in the browser and receives with each request
CORS	Cross-origin resource sharing: headers by which a server lets pages from other origins read its responses
Count-min sketch	Compact structure that estimates how often items appear
Covering index	Index that contains every column a query needs
CQRS	Command query responsibility segregation: separate models for writes and reads

Term	Meaning in one line
CSRF	Cross-site request forgery: tricking a logged-in browser into sending a request

D

Term	Meaning in one line
Data lake	Cheap storage of raw data in many formats for later analysis
Data warehouse	Structured store optimized for analytical queries
DAU	Daily active users
DDoS	Distributed denial of service: flooding a system from many machines
Dead-letter queue (DLQ)	Queue for messages that keep failing
Denormalization	Duplicating data to make reads faster
Dirty / non-repeatable / phantom read	Isolation anomalies: seeing uncommitted data / a row changing / new rows appearing on re-read
Disaster recovery (DR)	Plans and systems to restore service after a major outage
Distributed cache	Cache spread over several servers and shared by many app servers
Distributed lock	Lock that coordinates processes across machines
Distributed system	Many computers working together over a network as one system
DNS	Domain name system: turns names into IP addresses
Document database	NoSQL store of JSON-like documents (e.g. MongoDB)
Durability	Committed data survives crashes and failures

E

Term	Meaning in one line
Elasticity	Ability to grow and shrink resources quickly with demand
Encryption in transit / at rest	Protecting data moving over a network (TLS) / stored on disks and backups
Error budget	Amount of failure allowed by an SLO
Event-driven architecture	Services communicate by publishing and reacting to events
Event sourcing	Storing every change as an event and rebuilding state from them
Event streaming	Durable, ordered, replayable log of events (e.g. Kafka)
Eventual consistency	Replicas may differ briefly but converge if writes stop
Exactly-once	Each message's effect happens once; in practice at-least-once plus idempotency
Exponential backoff	Doubling the wait after each failed retry (100, 200, 400 ms …), up to a cap

F

Term	Meaning in one line
FaaS	Function as a service: run code per event without managing servers
Failover	Switching to a standby when the active component fails
Fallback	Alternative response used when the normal path fails
Fault / failure	One component going wrong / the whole system no longer delivering its service
Fault tolerance	Continuing to work correctly despite faults
Feature flag	Switch to turn a feature on or off without redeploying
Federation	Splitting databases by function (users DB, orders DB)
Fencing token	Increasing number that lets storage reject requests from a stale lock holder
File storage	Shared files and folders over the network (e.g. NFS)
Firewall	Filter that allows or blocks network traffic by rules
Foreign key	Column that refers to a primary key in another table
Forward proxy	Proxy acting on behalf of clients
fsync	System call that forces written data onto disk
Functional requirement	What the system must do

G

Term	Meaning in one line
GeoDNS	DNS that answers differently depending on the user's location
Geohash	Encoding of a location as a short string where shared prefixes mean nearby
Global server load balancing (GSLB)	Spreading traffic across data centres or regions
Golden signals	Latency, traffic, errors and saturation
Gossip protocol	Nodes share state by chatting with random peers
Graceful degradation	Keeping core features working when parts fail
Graph database	Store of nodes and edges for relationship queries (e.g. Neo4j)
GraphQL	Query language where clients ask for exactly the fields they need
gRPC	High-performance RPC framework using Protobuf over HTTP/2

H

Term	Meaning in one line
Hashing	One-way function that turns data into a fixed-size fingerprint
Head-of-line blocking	One stuck item delays everything queued behind it
Health check	Test that tells whether a server can take traffic
Heartbeat	Periodic "I'm alive" message
Horizontal scaling	Adding more machines (scale out)
Horizontal / vertical partitioning	Splitting a table by rows / by columns
Hot key / hot spot	One key or shard receiving far more traffic than others
HTTP	Hypertext transfer protocol: request/response protocol of the web
HTTP/2 / HTTP/3	HTTP multiplexing many streams over one TCP connection / HTTP over QUIC (UDP), avoiding TCP head-of-line blocking
HTTPS	HTTP over TLS encryption
HyperLogLog	Compact structure for estimating distinct counts

I

Term	Meaning in one line
Idempotency	Doing an operation twice has the same effect as once
Idempotency key	Unique request ID used to detect and ignore repeats
Index	Data structure that speeds up lookups on a column
Infrastructure as code (IaC)	Defining servers and networks in versioned files (e.g. Terraform)
In-process cache	Cache inside the application's own memory
Inverted index	Map from each word to the documents containing it, used by search engines
IOPS	Input/output operations per second a disk can do
IP address	Numeric address of a device on a network: 32-bit IPv4 or 128-bit IPv6
IP hash	Load-balancing by hashing the client IP to pick a server
Isolation level	How strictly a database isolates transactions (read committed, serializable …)

J

Term	Meaning in one line
Jitter	Random variation, added to retry delays or TTLs to avoid synchronized spikes
JWT	JSON Web Token: signed token carrying user claims

K

Term	Meaning in one line
Kafka	Distributed event streaming platform built on a partitioned log
Keep-alive	Reusing one TCP connection for many HTTP requests
Key-value store	Database that stores values looked up by a key
Kubernetes	System for running and managing containers across many machines

L

Term	Meaning in one line
L4 / L7	Transport layer (TCP/UDP) / application layer (HTTP) of the network model
Lamport clock	Logical counter that orders events without real time
Latency	Time for one operation or message to complete or arrive
Leader election	Choosing one node to coordinate the others
Leader-follower replication	One node (leader, or primary) takes writes and copies them to followers (replicas)
Leaderless replication	Any replica accepts writes, using quorums (e.g. Cassandra)
Leaky bucket	Rate limiter that processes requests at a fixed outflow rate
Least connections	Send each request to the server with the fewest active connections
Least privilege	Give each user or service only the access it needs
Linearizability	Strongest single-object consistency: behaves like one copy with instant operations
Little's law	Items in system = arrival rate × time in system
Load balancer	Spreads requests across a group of servers
Load shedding	Rejecting some requests on purpose to protect the system under overload
Long polling	Client request held open until the server has news
Lost update	Two concurrent writes where one silently overwrites the other
LRU / LFU	Eviction of the least recently / least frequently used item
LSM-tree	Log-structured merge tree: write-optimized storage structure

M

Term	Meaning in one line
MapReduce	Batch model: map data into key-value pairs, then reduce each key's values
Merkle tree	Tree of hashes used to find differences between data sets quickly
Message queue	Buffer where producers leave messages for consumers
Microservices	System built from small independently deployable services
Modular monolith	One deployable app with strong internal module boundaries
Monolith	Whole application built and deployed as one unit
Monotonic reads	A user never sees data go backwards in time
MTBF	Mean time between failures
MTTR	Mean time to recovery (or repair)
Multi-leader replication	Several nodes accept writes and sync with each other
Multi-region	Running in several geographic cloud regions

N

Term	Meaning in one line
N+1 query	One query for a list plus one per item
NAT	Network address translation: many private IPs share one public IP
Network partition	Network failure that splits nodes into groups that cannot talk
Nines	Shorthand for availability (99.9% = three nines)
Node	One machine (or process) in a cluster or distributed system
Non-functional requirement	How well the system must work: speed, scale, availability
Normalization	Organizing tables so each fact is stored once
NoSQL	Non-relational databases: key-value, document, wide-column, graph …
NS record	DNS record naming a domain's authoritative servers
NTP	Network time protocol: keeps machine clocks in sync

O

Term	Meaning in one line
OAuth 2.0	Standard for granting an app limited access to a user's resources
Object storage	Flat store of files with metadata, accessed over HTTP (e.g. S3)
Observability	Ability to understand a system's internal state from its outputs
Offset (messaging)	A consumer's position in a partition
OLAP	Online analytical processing: large queries for analysis
OLTP	Online transaction processing: many small live reads and writes
On-call	Engineer responsible for responding to alerts in a given period
OpenID Connect (OIDC)	Identity layer on OAuth 2.0 for login
Origin	Your own servers or storage holding the master copy of content behind a CDN
Origin shield	Extra CDN cache layer that protects the origin
ORM	Object-relational mapper: library mapping objects to database rows
OSI model	Seven-layer reference model of networking

P

Term	Meaning in one line
p50 / p95 / p99 / p999	Latency below which 50 / 95 / 99 / 99.9% of requests fall
PACELC	Extends CAP: else (no partition), choose latency or consistency
Pagination	Returning large results in pages, by offset (skip N rows) or by cursor (after the last item seen)
Partition	A subset of data stored separately; in Kafka, an ordered sub-log of a topic and the unit of parallelism
Paxos	Classic consensus algorithm
Peak factor	Ratio of peak load to average load
Percentile	Value below which a given share of measurements fall
PKCE	Proof Key for Code Exchange: one-time secret proving the app that started an OAuth flow is the one finishing it
Point of presence (PoP)	A CDN or network location in a city
Port	Number identifying a service on a machine (443 for HTTPS)
Power of two choices	Pick two random servers and use the less loaded
Primary key	Column(s) uniquely identifying each row
Private / public IP	Address valid only inside a private network / reachable from the internet
Protobuf	Protocol Buffers: compact binary format for structured data
Pub/sub	Publish/subscribe: every subscriber gets a copy of each message
Push / pull CDN	You upload content to the CDN in advance / the CDN fetches it from origin on first request

Q

Term	Meaning in one line
QPS	Queries (requests) per second
Quadtree	Tree that splits a map into four squares recursively
QUIC	UDP-based transport with built-in TLS, used by HTTP/3
Quorum	Minimum replicas that must agree for a read or write

R

Term	Meaning in one line
Raft	Understandable consensus algorithm with leaders and terms
Rate limiting	Capping how many requests a client may make per time window, rejecting the excess (HTTP 429)
RBAC	Role-based access control: permissions attached to roles
Reactive / scheduled / predictive scaling	Scaling on current metrics / at set times / ahead of forecast load
Read replica	Copy of a database used to serve reads
Read-through / write-through / write-around	Cache loads from the DB on a miss / writes go to cache and DB together / writes skip the cache
Read-your-writes	A user always sees their own recent writes
Recursive resolver	DNS server that does the full lookup for clients
Redis	In-memory data store used as a cache, queue and more
RED method	Rate, errors, duration: metrics for each service
Redundancy	Extra copies of components so one failure is survivable
Region	Geographic area of a cloud provider with several AZs
Relational database	Stores data in tables with schemas and supports SQL
Reliability	Working correctly over time, even when things go wrong
Replication	Keeping copies of data on multiple nodes
Replication lag	Delay before a write reaches replicas
Resharding	Changing the number of shards and moving data
Response time	What the client sees: latency plus queueing and processing
REST	API style using resources, URLs and HTTP methods
Reverse proxy	Proxy acting on behalf of servers
Rollback	Returning to the previous version after a bad deploy
Rolling deployment	Updating servers a few at a time
Root server	Top of the DNS hierarchy, points to TLD servers
Round robin	Send requests to each server in turn
Round trip time (RTT)	Time for a message to go there and back
RPC	Remote procedure call: calling a function on another machine
RPO	Recovery point objective: maximum acceptable data loss
RTO	Recovery time objective: maximum acceptable downtime

S

Term	Meaning in one line
Saga	Sequence of local transactions with compensations on failure
Salt	Random per-user value mixed into a password before hashing
Saturation	How full a resource is (CPU, queue length)
Scalability	Ability to handle more load by adding resources
Secrets management	Securely storing and rotating passwords and keys
Serverless	Running code without managing servers, billed per use
Server-Sent Events (SSE)	One-way stream of events from server to browser over HTTP
Service discovery	How services find each other's current addresses
Service mesh	Network of sidecar proxies handling service-to-service traffic
Session	Server-side record of a logged-in user
Sharding	Splitting data across machines by a shard key
Shard key	Field that decides which shard holds a record
Sidecar	Helper process deployed next to each service instance
SLA	Service level agreement: promise to customers with penalties
SLI	Service level indicator: a measured value
Sliding window	Rate limiter that counts requests in a moving time window
SLO	Service level objective: internal target for an SLI
Snowflake ID	64-bit, roughly time-ordered ID made from timestamp, machine ID and sequence
SOA	Service-oriented architecture: earlier, coarser form of services
Split brain	Two nodes both believe they are the leader
SQL injection	Attack that smuggles SQL commands into input
SSO	Single sign-on: log in once for many apps
Stateless / stateful service	Keeps no client data between requests / keeps client or data state locally
Sticky session	Load balancer sends a user to the same server each time
Stream processing	Processing events continuously as they arrive
Strong consistency	Every read sees the latest write
Synchronous / asynchronous	Caller waits for the result / caller hands off the work and carries on
Synchronous replication	Primary waits for replicas before confirming a write

T

Term	Meaning in one line
Tail latency	The slowest requests (p99 and above)
TCP	Reliable, ordered, connection-based transport protocol
Three-way handshake	SYN, SYN-ACK, ACK exchange that opens a TCP connection
Throttling	Slowing or queuing requests that exceed a rate instead of rejecting them
Throughput	Work completed per unit of time
Thundering herd	Many clients waking or retrying at the same moment
Timeout	Maximum time a caller waits before giving up on a call
Time-series database	Store optimized for timestamped measurements
TLD	Top-level domain such as .com or .org
TLS	Transport layer security: encryption and identity for connections
TLS termination	Decrypting TLS at a proxy or load balancer
Token bucket	Rate limiter allowing bursts up to a bucket size
Topic	Named stream of messages in pub/sub or Kafka
Trace	Record of one request's path across services
Transaction	Group of operations treated as one unit
TTL	Time to live: how long cached data or a DNS answer stays valid
Two-phase commit (2PC)	Prepare then commit protocol for atomic distributed transactions

U

Term	Meaning in one line
UDP	Connectionless transport without delivery or ordering guarantees
USE method	Utilization, saturation, errors: metrics for each resource
UUID	128-bit universally unique identifier

V

Term	Meaning in one line
Vector clock	Per-node counters that detect concurrent updates
Vector database	Store that finds items with similar embedding vectors
Vertical scaling	Making one machine bigger (scale up)
Virtual machine (VM)	Software-emulated computer with its own OS
Virtual node	Many ring positions per server in consistent hashing

W

Term	Meaning in one line
WAF	Web application firewall: filters malicious HTTP traffic
WAL	Write-ahead log: changes written to a log before applying, for crash recovery
Webhook	HTTP callback a system sends to another when an event happens
WebSocket	Persistent two-way connection between browser and server
Wide-column store	NoSQL store that groups rows by a partition key and sorts them within it (e.g. Cassandra)
Worker	Background process that consumes and handles jobs
Write-back / write-behind	Writes go to the cache and reach the database later
Write skew	Two transactions read the same data, each update different rows, and together break a rule

X, Y, Z

Term	Meaning in one line
XSS	Cross-site scripting: injecting malicious script into pages others view
Zero trust	Security model that verifies every request, inside the network or not
ZooKeeper	Coordination service for config, locks and leader election

---

Part 6 glossary

Term	Meaning in one line
Request's journey	The full path one user action takes through every component and back
Scheme	First part of a URL, such as `https`, saying which protocol to use
Host	The domain-name part of a URL, such as photos.example.com
Path	The part of a URL after the host, such as /feed
Browser cache	Copies of pages, files and DNS answers kept by the browser
0-RTT resumption	TLS 1.3 feature letting a returning client send data in its first message
URL shortener	Service that maps a short code to a long URL and redirects
Short code	The few characters (e.g. aZ3kQ9b) that identify a short link
Custom alias	User-chosen short code
Redirect	HTTP response telling the browser to go to another URL
301 Moved Permanently	Redirect the browser may cache forever
302 Found	Temporary redirect the browser re-checks each time
409 Conflict	Status code for a request that clashes with existing data
410 Gone	Status code for a resource that existed but was removed
Counter range	Block of numbers handed to one server for ID generation
Key generation service (KGS)	Service that pre-creates unused unique keys
Hash collision	Two different inputs producing the same short hash
Request coalescing	Letting one request refill a cache entry while others wait for it
80/20 rule	Rough rule that 20% of items get 80% of the traffic
Decision cheat sheet	Table mapping common needs to standard tools and their costs
Master glossary	A–Z list of all system design terms in this module

Strangler Fig Pattern

Category: Migration / modernization **One-liner:** Replace an old system gradually by putting a router in front of it and moving one capability at a time to the new system, instead of rewriting everything and switching over in one go.

Part 0 — Concepts you need first

If these are already familiar, skip to Part 1.

What is a monolith?

A **monolith** is an application built and deployed as one single unit. All the code — user accounts, payments, reporting, email — lives in one **codebase** (the full set of source files for a program), compiles into one **artifact** (the finished, runnable package the build produces, such as a `.jar` file), and runs as one **process** (a single running program instance on a machine, with its own memory). Changing one line in the reporting module means rebuilding and **redeploying** (putting a new version into the live environment) *everything*, including payments.

Monoliths are not evil. For a small application a monolith is usually the *right* choice — it's simpler to build, test, and deploy. The problems start when it grows large and many teams need to change it simultaneously.

What is a legacy system?

"Legacy" doesn't just mean old. It means **old software that is still running because it does something essential**. That's the crucial part: it survives precisely because the business depends on it. Nobody keeps unimportant old software running; they delete it.

This creates the trap that defines this whole chapter: the system is **too risky to keep** (it's fragile and expensive) and **too risky to replace** (it's load-bearing).

What is a "big-bang rewrite"?

The instinctive approach to a bad old system: build a complete replacement, then switch everything over on one date. It's called big-bang because everything changes at once.

It fails often, and for a predictable reason. While you spend eighteen months building the replacement, the old system keeps changing — bugs get fixed, features get added, regulations change. You're rebuilding a moving target. On switchover day you discover the hundred behaviours nobody documented, and you have no way back.

What is a proxy or router (in this context)?

A piece of software sitting **between** a client and one or more servers. The client talks only to the proxy; the proxy decides where the request actually goes. The client cannot tell the difference.

This "client can't tell the difference" property is the entire foundation of the Strangler Fig Pattern. If you can put something in the middle that clients can't distinguish from the real system, you can change what's behind it whenever you like.

What is a feature flag?

A configuration switch that turns behaviour on or off **without deploying new code**. Instead of:

```
return newImplementation(x);
```

you write:

```
if (flags.isEnabled("use-new-implementation")) {
    return newImplementation(x);
}
return oldImplementation(x);
```

Now you can change behaviour by editing configuration, and change it *back* in seconds if something breaks. Flags are what make the migration reversible.

Part 1 — Where the name comes from

The **strangler fig** is a real tree. Its seed germinates in the branches of an existing tree. It grows roots downward and branches upward, gradually enveloping its host. Eventually the host tree dies and rots away, leaving the fig standing in its exact shape — hollow in the middle where the original used to be.

Two things in that image matter for software:

1. **The fig grows around the host while the host is still alive.** It doesn't chop the tree down and plant a seedling in the gap. Both exist simultaneously for a long time.
2. **The transition is gradual and continuous.** There is no single moment when the tree becomes a fig.

Applied to software: your new system grows *around* the legacy system, which continues serving real **production** traffic (requests from real users hitting the live system, as opposed to test environments) the entire time it's being displaced.

The course extends the metaphor: picture an ancient, enormous tree in a dense forest. That's your legacy system — rooted deeply in the organisation's architecture, its many branches representing all the functions it supports. Replacing it feels as daunting as replacing that tree.

Part 2 — The problem in detail

Why legacy systems are painful to live with

Technical debt. Over years, patches, fixes, and new features get added haphazardly — often under deadline pressure, often by people who have since left. The result is a complex, hard-to-maintain codebase where no one is confident what a change will affect.

> *Beginner note:* "technical debt" is a metaphor — taking a shortcut now (like debt) lets you move fast today but charges interest later in the form of slower future changes. Some debt is a reasonable trade; the problem is debt that's never repaid.

Obsolete technology. The **stack** (the set of languages, frameworks, databases and servers the system is built on) is no longer current. Concretely, this means you can't hire people who know it (or must pay a large premium), the vendor no longer issues support or **patches** (small updates that fix bugs or security holes), and the **libraries** (reusable code packages written by others that your program calls into) you depend on have unfixed bugs forever.

Integration issues. Modern tools and services don't integrate easily with older systems. The practical consequence is **silos of information** — data trapped in a system that nothing else can conveniently read, so it gets manually exported, copied, and duplicated.

Scalability concerns. (**Scalability** is a system's ability to handle more work by adding resources; **load** is the amount of work — requests, users, data — hitting it.) The system was designed for the load and deployment model of its era. It may assume a single server, or a fixed number of them. It's typically **not cloud-ready** (the **cloud** being rented, on-demand servers from providers such as AWS, Azure or Google Cloud), meaning it can't simply be run as more copies when traffic grows.

Costly maintenance. As the system ages, maintenance gets more expensive in both time and resources. Every change takes longer because the code is tangled and the people who understand it are fewer.

Security vulnerabilities. It was designed before current security practices existed. It may store passwords insecurely, lack protection against now-standard attacks, or run on an **OS** (operating system — e.g. Windows or Linux, the base software that runs the machine) that no longer receives patches.

Why legacy systems are painful to replace

Critical operations. These systems are deeply embedded in the organisation's critical operations. Any disruption has significant impact — this is not "the site is slow," it's "we cannot take orders today."

Migration risks. Moving data from the old system to the new risks **data loss or corruption**. Old **schemas** (the defined structure of a database: its tables, columns and their types) usually contain years of accumulated irregularity: records that violate current rules, fields reused for different purposes, **encoding** inconsistencies (text stored using different rules for turning characters into bytes, so accents or symbols come out garbled).

Training and adoption. Staff know the old system. A new one requires training and often meets genuine resistance — people who were fast and confident are suddenly slow and uncertain.

High costs. Building a new system *and making it as reliable as the old one* is expensive. That second part is easy to underestimate: the old system's reliability came from a decade of bugs found and fixed in production. Your new system hasn't had those years.

Unknown unknowns. There are undocumented features and behaviours that users have come to depend on.

> This is the one that kills rewrites. You cannot write a specification for behaviour nobody wrote down and nobody remembers. You discover it when you switch over and someone says "the report used to round differently and now our reconciliation breaks." A rewrite finds these all at once, on the worst possible day.

Part 3 — The solution

Don't replace the system. **Strangle it.**

Build the new system alongside the old one. Put a routing layer in front of both. Migrate one capability at a time, flipping the router as each new piece proves itself in production. When no traffic reaches the legacy system anymore, delete it.

Why this beats a rewrite

Less risky. The old system is still there. Each step has a safety net, and each step is individually revertible. If the new checkout breaks, you route checkout back to the old system in seconds.

Flexible prioritisation. You migrate by **urgency or business need**, not by the dependency order a rewrite would force. If the payment module is the most painful, do it first.

No big-bang releases. Continuous delivery (keeping software always releasable and shipping small changes frequently) and gradual replacement instead of one catastrophic **cutover** date (the moment traffic is switched from the old system to the new). Less potential for massive failures.

Smooth transition. Done well, users may not notice a shift happened at all — it's gradual and each piece is tested before it carries real traffic.

Early feedback loops. Real users hit new code early, so you learn about problems while they're still cheap to fix, rather than discovering everything at once at the end.


Technology flexibility. The new system can adopt new technology as the industry evolves. You're not locked into whatever was fashionable at project kickoff — a real concern when a migration takes two years.

Part 4 — Architecture

The Facade Interface — the gatekeeper

The central component. Every incoming request hits the facade first, and it makes one decision: **has this functionality been migrated yet?**

- **Yes** → route to the new system
- **No** → route to the legacy system



The course's analogy: **a traffic controller at an intersection**, guiding cars (requests) down the correct road.

The critical property: **clients are unaware there are two systems at all.** They see one address, one **API** (Application Programming Interface — the set of requests a system accepts and the responses it returns), one system. That's what makes the migration invisible.

> *Beginner note — why "facade"?* A facade is the front of a building. In software, the Facade pattern means putting a simple, unified front over something complicated behind it. Here the complicated thing is "there are two entire systems and the answer depends on which feature you want."

Layered, phased migration

The course describes it as **peeling an onion layer by layer**, each layer being a part of the legacy system replaced by the new one. The migration happens step by step, never all at once:

1. **Identify a piece of functionality that can be cleanly isolated** and redirected.
2. **Rebuild that functionality** in the new system.
3. **Test it fully.**
4. **Flip the facade** to route that functionality to the new system, while everything else still goes to legacy.
5. **Repeat.**

That gradual shift of responsibility from old to new is the crux of the pattern.

Step 1 is the hard one, and beginners underestimate it. "Cleanly isolated" means the feature doesn't share **mutable state** (data that can be changed while the program runs) with everything else. In practice most legacy systems have one giant shared database where everything touches everything, so finding a genuinely separable **seam** (a boundary where one part can be cut away from the rest with few connections across it) is the real work. Look for capabilities that read a lot and write little, or that own a table nothing else writes to.

Part 5 — The four implementation steps

1. **Identify entry points** — choose the parts of the legacy system you want to replace, and build new services to take over those functions.
2. **Route traffic** — use a router or proxy to direct traffic to either the old system or the new service, based on what's been migrated so far.
3. **Incrementally build and replace** — develop the new services and slowly displace old functionality.

4. **Retire the old** — once all functionality has been taken over, safely **decommission** (permanently shut down and remove) the old system.

Part 6 — Worked example 1: routing a single function

The scenario: an old user-management system. You want to replace just `getUserDetails`.

```
class UserServiceRouter:
    def get_user_details(self, user_id):
        if self.use_new_service(user_id):
            return NewUserService().get_user_details(user_id)
        else:
            return OldUserService().get_user_details(user_id)

    def use_new_service(self, user_id):
        # Logic deciding which service to use.
        # For simplicity: use the new service for even user IDs.
        return user_id % 2 == 0
```

Reading this line by line

- `UserServiceRouter` is the facade. **Callers use this class, not the two services directly** — that's what makes the switch invisible to them.
- `get_user_details` has the same **signature** (the method's name, parameters and return type) as the underlying services. The router is a **drop-in replacement** (something callers can swap in without changing their own code) for whatever callers used before.
- `use_new_service` is the **decision function** — the entire migration policy lives in this one method.
- `user_id % 2 == 0` means "even user IDs." This sends roughly 50% of users to the new service.

Why the even-ID trick is smarter than it looks

This isn't just a toy. It gives you a **percentage rollout dial**.

> **Key term — hash function:** A **hash function** turns an input (like a user ID) into a number in a scrambled but repeatable way: the same input always produces the same output, and different inputs spread fairly evenly across the possible outputs. Taking `hash(user_id) % 100` (the remainder after dividing by 100) therefore puts each user in a fixed "bucket" from 0 to 99. You're not choosing "old or new" — you're choosing *how much* new:

```
return hash(user_id) % 100 < 5     # 5% of users
return hash(user_id) % 100 < 50    # 50% of users
return True                        # everyone
```

And it's **consistent per user**: user 42 always gets the same implementation. That matters enormously — if users flipped between implementations randomly on each request, any difference in behaviour would look like a bizarre intermittent bug, and you'd never reproduce it.

As confidence grows, widen the condition until the old path is **dead code** (code that still exists but can never run) — then delete it.

Part 7 — Worked example 2: a facade over a banking system

A fuller example. The legacy system has four operations:

```
public class LegacySystem {
    public void createAccount(String name) { /* old logic */ }
    public void deposit(int amount)        { /* old logic */ }
    public void withdraw(int amount)       { /* old logic */ }
    public int  checkBalance()             { /* old logic */ }
}
```

The new system implements the same four operations with updated logic:

```
public class NewSystem {
    public void createAccount(String name) { /* new logic */ }
    public void deposit(int amount)        { /* new logic */ }
    public void withdraw(int amount)       { /* new logic */ }
    public int  checkBalance()             { /* new logic */ }
}
```

Notice the signatures are identical. That's deliberate and necessary — the facade can only substitute one for the other if they're interchangeable.

Now the facade — the class the outside world actually talks to. It holds an instance of both systems and directs each request:

```
public class BankingFacade {
    private LegacySystem legacySystem;
    private NewSystem newSystem;

    public BankingFacade(LegacySystem legacySystem, NewSystem newSystem) {
        this.legacySystem = legacySystem;
        this.newSystem = newSystem;
    }

    public void createAccount(String name) {
        if (newSystemReadyFor("createAccount")) {
            newSystem.createAccount(name);
        } else {
            legacySystem.createAccount(name);
        }
    }

    public void deposit(int amount) {
        if (newSystemReadyFor("deposit")) {
            newSystem.deposit(amount);
        } else {
            legacySystem.deposit(amount);
        }
    }

    public int checkBalance() {
        if (newSystemReadyFor("checkBalance")) {
            return newSystem.checkBalance();
        } else {
            return legacySystem.checkBalance();
        }
    }

    private boolean newSystemReadyFor(String functionality) {
        // Check whether the new system is ready for this functionality
        return false;   // placeholder — starts false for everything
    }
}
```

How the migration actually proceeds

At the start, `newSystemReadyFor` returns `false` for everything, so **100% of traffic goes to the legacy system**. The facade is in place but changes nothing. This is important: you deploy the facade first and verify it changes nothing, *before* you migrate anything. If something breaks at that point, you know it's the facade, not the new code.

Then you rebuild `createAccount` in the new system, test it, and update `newSystemReadyFor` to return `true` for `"createAccount"`. Now all account creation goes to the new system while deposits, withdrawals, and balance checks still go to legacy.

Repeat for each capability. Gradually the new system takes over.

The key structural insight: the only thing that changes at each cutover is what `newSystemReadyFor` returns. Clients don't change. The two systems don't change. In a real implementation that method reads a **feature flag** from configuration, so flipping a capability doesn't even require a deployment — and flipping it *back* takes seconds.

Part 8 — Key insights: the proxy layer is everything

The router/proxy is the heart of the pattern, and it needs to be genuinely robust — it's now on the critical path for **every single request**. The course lists three kinds of routing logic:

Feature flags. Turn new functionality on and off to test it. The operational superpower here is **instant rollback** (returning to the previous, known-good behaviour) — no deploy, no rebuild, just a config change.

User segmentation. Route certain users to new services for **A/B testing or phased rollouts** (A/B testing shows two versions to different user groups and compares results; a phased rollout releases to a growing share of users step by step). Common progressions: internal employees first, then 1% of users, then 10%, then everyone. Or by geography: a small market first, so problems affect fewer customers.

API versioning. Direct requests based on version **headers** (key-value metadata sent alongside an HTTP request, such as `Accept-Version: 2`) or **paths** (the part of the URL after the domain) — for example `/v1/orders` to legacy and `/v2/orders` to the new service.

Part 9 — Trade-offs and what actually goes wrong

Running two systems at once. You operate, monitor, and pay for both throughout the migration — which can last years. Two **deployment pipelines** (automated sequences that build, test and release code), two **on-call rotations** (schedules of engineers who respond to production incidents), two sets of **dashboards** (screens of live graphs showing system health).

The facade is a single point of failure (one component whose failure takes the whole system down). Everything flows through it. It needs **high availability** (staying up nearly all the time, usually via redundant copies) and a carefully considered **latency budget** (the maximum delay each component is allowed to add; **latency** is the time a request takes from start to finish — see System Design Fundamentals), because whatever time it adds is added to every request.

An extra hop. (A **hop** is one network trip between two machines.) The routing layer adds network latency to every request, however small.

Data consistency — the hard part the pattern doesn't solve. If old and new systems share or split data, you need a strategy: a shared database, synchronisation, or **dual writes** (the application writing the same change to two databases). This is genuinely the hardest part of most real migrations, and the pattern gives you no help with it.

> *Concrete example of why:* suppose you migrate "create account" to the new system but leave "check balance" on legacy. If the two write to different databases, an account created in the new system is invisible to the legacy balance check. In practice teams usually keep a **single shared database** during migration and split it later — a second strangler migration in its own right.

Duplicated logic. While a capability is in flight, the same business rule exists in two places. Change the rule and you must change both, or they diverge.

Migration fatigue — the most common real-world failure.

> The pattern makes it *safe* to stop halfway, so organisations do. The urgent 60% gets migrated, the pain goes away, priorities shift, and the team runs both systems forever — which is worse than either system alone. **Set a decommission date for the legacy system up front and treat it as a real deliverable.**

Part 10 — Common beginner misconceptions

"The new system must be microservices." (**Microservices** means building an application as many small, independently deployable services, each owning one business capability.) No. Strangler Fig is about *how* you migrate, not what you migrate *to*. You can strangle one monolith into a better monolith.

"You migrate the database first." Usually the opposite. Data migration is the riskiest part, so teams typically keep the shared database initially and move behaviour first, splitting data later.

"The facade is temporary." Often it isn't — it frequently becomes the permanent API Gateway. That's fine, as long as it's a deliberate choice.

"Once a capability is migrated you delete the old code immediately." Leave it in place, unreachable but intact, until you're confident. It's your rollback. Delete it once the flag has been at 100% for a sensible period.

"This is only for ancient systems." It works any time you replace a component that's in use — swapping a payment provider, replacing a search engine, moving from one cloud to another.

Part 11 — Check your understanding

1. Why is the strangler fig a better metaphor than "demolish and rebuild"?
2. What single method in the `BankingFacade` example controls the entire migration?
3. Why route by a *consistent* function of user ID rather than randomly per request?
4. Why deploy the facade before migrating anything?
5. What problem does the pattern explicitly *not* solve?
6. What's the most common organisational failure mode, and the countermeasure?

(Answers: 1 — both systems coexist and the transition is gradual and reversible; 2 — `newSystemReadyFor`; 3 — a user must get consistent behaviour, or differences look like intermittent bugs; 4 — to verify the facade itself is harmless before adding a second variable; 5 — data consistency between old and new; 6 — stalling halfway, prevented by committing to a decommission date.)

Part 12 — Interview soundbite (30 seconds)

> "Strangler Fig is how you replace a legacy system without a big-bang rewrite. You put a facade or proxy in front of the old system so clients only ever talk to that, then rebuild functionality one capability at a time behind it. The facade routes each request to either the new service or the legacy system depending on what's been migrated — usually driven by feature flags or user segmentation, so you get percentage rollouts and instant rollback without a deploy. Over time traffic to legacy drops to zero and you delete it. It's named after a tree that grows around its host until the host rots away. The reason it beats a rewrite is that a rewrite has to hit a moving target and discovers all the undocumented legacy behaviour on switchover day, whereas this surfaces problems one capability at a time while you still have a way back. The trade-offs are running both systems in parallel for a long time, the facade becoming a critical single point of failure, and data consistency between old and new, which the pattern doesn't solve. The biggest

> practical risk is organisational — because it's safe to stop halfway, teams often do, so you commit to a decommission date up front."

Part 13 — Implementation

A. Runnable demo

Full source: `demos/StranglerFigDemo.java`

```
cd demos && ./gradlew runCh02
```

(`./gradlew` is the **Gradle wrapper** — a script that downloads and runs **Gradle**, a build tool that compiles Java code and runs tasks such as this demo.)

The core is the flag check that makes rollout **consistent per user**:

```
boolean useNewSystem(String capability, String userId) {
    int percent = rolloutPercent.getOrDefault(capability, 0);
    if (percent <= 0)   return false;
    if (percent >= 100) return true;
    int bucket = Math.floorMod(userId.hashCode(), 100);   // stable per user
    return bucket < percent;
}
```

`Math.floorMod` (not `%`) because `hashCode()` (Java's built-in hash function for an object) can be negative and `%` would then yield a negative bucket that never matches.

B. What you should see

```
=== Step 1: facade deployed, nothing migrated ===
  LEGACY:created:alice
  >> all traffic still on LEGACY - facade proven harmless

=== Step 3: same user always gets the same system ===
  user-7 -> LEGACY:created:acct     (x3, never flips)

=== Step 4: widen the rollout ===
    [flags] createAccount -> 25%  ->  actual: 253/1000 users
    [flags] createAccount -> 50%  ->  actual: 493/1000 users
    [flags] createAccount -> 100% ->  actual: 1000/1000 users

=== Step 5: problem found - INSTANT rollback ===
  user-7 -> LEGACY:created:acct
  >> no deploy, no rebuild: config change only
```

Two things worth noting from the real output. **Step 3** proves consistency — user-7 gets the same system every time, so a behavioural difference can never look like an intermittent bug. And the percentages aren't exact (5% gave 44/1000, not 50) because **hash distribution is only approximately uniform** at these sample sizes. That's expected and fine; you're **canarying** (sending a small slice of real traffic to the new version first, like a canary in a coal mine that warns of danger early), not metering.

C. Production — routing at the proxy

In reality the facade is usually infrastructure, not application code.

Nginx — route by path: (**Nginx** is a popular web server and **reverse proxy** — a proxy that sits in front of servers and forwards client requests to them. An `upstream` block names a group of backend servers.)

```
upstream legacy_system { server legacy.internal:8080; }
upstream new_system    { server orders-v2.internal:8080; }

server {
    location /api/orders  { proxy_pass http://new_system;    }   # migrated
    location /api/billing { proxy_pass http://legacy_system; }   # not yet
    location /            { proxy_pass http://legacy_system; }   # default: legacy
}
```

Istio — percentage rollout without touching application code: (**Istio** is a **service mesh** — infrastructure that routes and secures traffic between services through proxies placed next to each one; it is configured with **YAML**, a plain-text, indentation-based config format. See Sidecar.)

```
apiVersion: networking.istio.io/v1beta1
kind: VirtualService
metadata:
  name: orders
spec:
  hosts: [orders]
  http:
    # Internal staff always get the new system - your first canary group
    - match:
        - headers:
            x-user-group: { exact: internal }
      route:
        - destination: { host: orders, subset: v2 }
    # Everyone else: 5% to the new system
    - route:
        - destination: { host: orders, subset: v1 }
          weight: 95
        - destination: { host: orders, subset: v2 }
          weight: 5
```

Feature flags in application code — LaunchDarkly (a hosted feature-flag service), Unleash (an open-source equivalent), or a table in your **config store** (a central place where configuration values are kept):

```
if (flags.isEnabled("orders-v2", userContext)) {
    return newOrderService.create(order);
}
return legacyOrderService.create(order);
```

D. The part the pattern doesn't solve: data

The hardest real-world problem. Three strategies, in increasing order of difficulty:

1. Shared database (start here). Both systems read and write the same database. No sync problem at all — the new service simply uses the old schema. Split the data later as a separate migration.

2. Dual writes. The new system writes to both databases during transition. Simple to describe, genuinely hard to get right: if the second write fails you have divergence, and there's no **transaction** (a group of database changes that either all succeed or all fail together) spanning both.

3. Change Data Capture (CDC). (CDC means watching a database for every insert, update and delete and publishing each change as an event.) Stream changes from the legacy database into the new one using **Debezium** (an open-source CDC tool) reading the **transaction log** (the database's own append-only record of every change it commits). The new system's data is **eventually consistent** with legacy (it may lag briefly, but catches up if no new changes arrive), and crucially **the legacy system needs no modification**:

```
# Debezium connector: legacy Postgres -> Kafka -> new service
connector.class: io.debezium.connector.postgresql.PostgresConnector
database.hostname: legacy-db
table.include.list: public.orders,public.customers
plugin.name: pgoutput
```

E. Implementation pitfalls

1. Random rather than consistent routing. (The comment in the Debezium config above mentions **Postgres** — PostgreSQL, a popular open-source relational database — and **Kafka**, a distributed log that stores and streams events; see Event-Driven.) `Math.random() < 0.05` sends the *same user* to different systems on consecutive requests. Any behavioural difference becomes an unreproducible bug report. Always hash a stable identifier.

2. Deploying the facade and migrating a capability in one release. If something breaks you can't tell which change caused it. Deploy the facade first, confirm it's a no-op, then migrate.

3. Deleting legacy code the moment traffic hits zero. That code is your rollback. Leave it unreachable but intact until the flag has been at 100% for a full business cycle.

4. No comparison stage. Before flipping traffic, run **shadow mode** — send the request to both systems, return the legacy response, and log any differences. This is how you find undocumented behaviour *before* it reaches users. The code runs the new system **asynchronously** (in the background on another thread, so the user's request doesn't wait for it) and records **metrics** (numeric counters and measurements used for monitoring):

```
Result legacyResult = legacy.process(request);
executor.submit(() -> {                          // async, never blocks the user
    try {
        Result newResult = modern.process(request);
        if (!newResult.equals(legacyResult)) {
            metrics.increment("shadow.mismatch");
            log.warn("Divergence for {}: {} vs {}", request.id(), legacyResult, newResult);
        }
    } catch (Exception e) { metrics.increment("shadow.error"); }
});
return legacyResult;                             // user always gets the proven answer
```

5. Flags that outlive the migration. Every completed migration leaves a dead **conditional** (an `if` statement whose other branch can never be taken). Schedule flag removal as part of "done," or the codebase fills with permanent forks.

6. No decommission date. The organisational failure mode from Part 9. Put it in the plan.

Related patterns

- **API Gateway** — the facade is very often literally an API Gateway
- **BFF** — can bridge new frontends to legacy systems during migration
- **Config Externalization** — where the feature flags driving routing actually live

API Gateway Pattern

Category: Edge / routing **One-liner:** A single entry point that sits in front of all microservices, routing, aggregating, securing, and shaping requests so clients never talk to services directly.

Lesson 1 — Introduction to the API Gateway Pattern

The fast-food counter

Picture ordering a burger. You walk to the counter, place your order, pay, and wait. That counter is the API Gateway. It is the **single point at which you, the customer, interact with the restaurant's services** — the kitchen, the billing system, inventory. You never walk into the kitchen to ask the cook for your patty and then go to a separate desk to pay. One counter, one interaction, and everything behind it is somebody else's problem.

What the pattern actually is

In a **microservice architecture** (an application split into many small services, each running separately and owning one business capability) you have many services each doing their own thing. The API Gateway Pattern is about having **a single entry point for external consumers** to reach all of them.

Three things follow from that single entry point, and it's worth separating them because they're independent benefits:

1. **It makes the system easier to manage** — there is one place where request handling policy lives.
2. **It secures your services** — the services themselves need not be individually exposed.
3. **It provides a unified interface to the external world** — clients see one coherent API rather than the seams between your teams.

Why the pattern exists

The dominant architectural trend of recent years has been the shift from **monolithic** structures (one big application built and deployed as a single unit) to microservices. The course compares it to the shift from landlines to smartphones in telecommunications — a genuine step change that brought enhanced **scalability** (the ability to handle more work by adding resources), increased flexibility, and more. But as with any technological advance, it introduced its own problems.

The biggest of those problems is communication:

- **How do you ensure effective and efficient communication** between a large number of services?
- **How do you manage the growing complexity** that comes with an ever-increasing number of interactions between them?

This is precisely the gap the API Gateway Pattern fills.

The Netflix example

When you open Netflix on your TV or phone, the app needs a lot of different data — the movie list, your user preferences, subtitles, and more. Netflix has a separate microservice responsible for each of those pieces.

Now consider the two possible designs:

- **Without a gateway:** your TV app calls each microservice separately. It must know that there *is* a preferences service, where it lives, how to **authenticate** to it (prove who you are, e.g. with a password or token), and what shape its response takes — and repeat all of that for every other service.
- **With a gateway:** your TV app makes one call to the Netflix API Gateway, which then talks to whichever microservices are needed.

The second is dramatically simpler for the TV app. And note *which* app benefits most — a TV app or a mobile app is something you cannot force users to update. Every piece of **service topology** (which

services exist, where they run and how they connect) you bake into it is frozen in the field for years.

The master orchestrator

The gateway operates like **the conductor of an orchestra**. It oversees and directs the entire ensemble of services, ensuring each plays its part at the right time to produce a harmonious output.

Mechanically, it does three things in sequence:

1. Serves as the **single entry point** for all client requests
2. **Routes** those requests to the appropriate microservices
3. **Gathers the responses** from the services involved and delivers a **unified response** back to the client

The beauty of the pattern is its ability to **mask the underlying complexity from clients**. As a client you do not need to know how many services were involved or how they communicate with each other. You make a request; the gateway handles the rest.

The headline advantages

The introduction gives four, which the next lesson expands considerably:

- **Simplified client** — clients interact with one gateway instead of many services.
- **Security** — **authentication** (checking who the caller is) and **authorization** (checking what that caller is allowed to do) can be added at the gateway level.
- **Performance** — you can add **caching** (keeping copies of recent answers so repeat requests are served without redoing the work), compress responses (shrink them so they travel faster), and manage **load balancing** (spreading requests across several copies of a service). See System Design Fundamentals for both.
- **Cross-cutting concerns** (needs that every service shares, rather than belonging to one feature) — **logging** (writing a record of what happened), **analytics** (collecting usage data), and similar concerns are handled in one place.

Lesson 2 — Advantages: the fifteen problems it solves

The framing

Imagine a city full of different services and places to visit. As a tourist, interacting with each service individually gets confusing and overwhelming fast. But if there is a **single information centre** that guides you and helps you interact with all of them, your life becomes far easier. That is what the gateway does for microservices.

What follows is each problem the course identifies, with the gateway's answer. I've kept all fifteen as their own item because each is a distinct argument.

1. Complexity of interactions

Problem: In a microservices architecture there are many services talking to each other. If every service communicates with all the others directly, the number of connections grows very complex, very fast. **Solution:** The gateway becomes the central point of communication. Services talk to the gateway, and the gateway talks to other services — collapsing a mesh of connections into a hub.

2. Inconsistency in service calls

Problem: Different services may require different interaction styles and have different **data formats** (ways of encoding data, e.g. JSON, XML or binary). A client ends up implementing several dialects of your own API. **Solution:** The gateway provides one consistent way to interact with everything. It can **translate calls and data formats**, so the client sees uniformity even where the **backend** (the server-side services behind the gateway) has none.

3. Security and authentication

Problem: Handling security for each service individually is a nightmare. Every service must be independently secured, and that is a great deal of duplicated, easily-inconsistent work. **Solution:** Authentication and authorization are handled **centrally**. Clients authenticate with the gateway, and the gateway ensures callers are who they claim to be before anything reaches a service.

4. Load balancing

Problem: Some services receive far more traffic than others, and that traffic needs managing efficiently. **Solution:** The gateway distributes incoming traffic evenly across services, ensuring **no single service is overwhelmed**.

5. Performance issues

Problem: Services are spread out, and the network calls between them add delays. **Solution:** The gateway can **cache responses** from services, reducing the need for repeated calls and improving performance.

6. Cross-cutting concerns

Problem: Concerns like logging, monitoring, and analytics would otherwise need implementing in **every single service**. **Solution:** Handle them centrally at the gateway, removing that duplication.

7. Managing legacy systems

Problem: You may have old **legacy** services (old systems still running because the business depends on them) that must be accessed in specific, awkward ways. **Solution:** The gateway can interact with legacy services while **presenting a modern interface** to clients — the awkwardness stops at the gateway boundary.

8. Version management

Problem: Different clients may need to interact with different versions of a service — again, most acute with mobile and TV clients you cannot force to upgrade. **Solution:** The gateway routes requests to the appropriate version of a service based on the client's needs.

9. Aggregation of results

Problem: A client may need information spread across multiple services. Gathering it could require several network calls, which is inefficient — especially over a mobile connection. **Solution:** The gateway aggregates results from multiple services and returns a **single consolidated response**.

10. Service orchestration

Problem: Some operations require a series of service calls made **in a particular order**. **Solution:** The gateway orchestrates those calls, ensures correct ordering, and handles any transformations needed along the way.

11. Handling partial failures

Problem: In a **distributed system** (one made of many programs on different machines that cooperate over a network) some services fail while others keep working. Handling these **partial** failures gracefully is genuinely difficult. **Solution:** The gateway detects failures and either **reroutes** requests or provides **fallback responses** (a safe default answer used when the real one can't be obtained), so the system stays robust rather than failing wholesale.

12. Request transformation

Problem: Different services expect requests formatted in different ways. **Solution:** The gateway transforms each incoming request into the format the target service expects.

13. Client-specific adaptations

Problem: Different clients — mobile, web, and so on — have different requirements. **Solution:** The gateway adapts responses to suit each client's needs. *(Pushed to its logical conclusion, this becomes*

BFF — one gateway per client type.)

14. Centralized logging and monitoring

Problem: Collecting logs and monitoring data from every service in a distributed system is challenging. **Solution:** The gateway collects logs and monitoring data, giving you **one point for observability** (the ability to understand what a running system is doing from its logs, metrics and traces).

15. Handling asynchronous operations

Problem: Some operations take a long time and should not block the client. **Solution:** The gateway manages those **asynchronous** operations (work that continues in the background while the caller moves on), giving clients a way to **check progress or receive a callback** on completion (a **callback** is a call made back to the client when the work finishes).

Taken together, these create a smoother, more reliable interaction layer for clients — the course describes it as a super-efficient helper that takes care of the nitty-gritty details so you get a seamless experience.

Lesson 3 — Worked example: a library system

The scenario

A library system in which various clients — library users, staff, and management — interact with several microservices: a **Catalogue Service**, a **User Service**, and an **Inventory Service**.

Each service corresponds to a distinct area of the library's functionality:

- **CatalogueService** handles requests relating to book searches
- **UserService** manages user profiles
- **InventoryService** keeps track of book stock levels

In the Java implementation each would be an **interface** (a Java type that lists method signatures without implementing them) with methods matching potential client requests — `CatalogueService`, for instance, might expose `searchByTitle(String title)` and `searchByAuthor(String author)`.

The gateway

A separate class acting as the single point of contact for all client requests. The course's analogy: **a receptionist at the library**, fielding questions from visitors and directing them to the right place.

The crucial design point: `ApiGateway` has a method corresponding to each client request, mirroring the services — but rather than handling those requests itself, **each method delegates the work to the appropriate service**.

```java
public class ApiGateway {
    private UserService userService;
    private CatalogueService catalogueService;
    private InventoryService inventoryService;

    public ApiGateway(UserService userService,
                      CatalogueService catalogueService,
                      InventoryService inventoryService) {
        this.userService = userService;
        this.catalogueService = catalogueService;
        this.inventoryService = inventoryService;
    }

    public User getUserDetails(String userId) {
        return userService.getUserDetails(userId);
    }

    public Book searchByTitle(String title) {
        return catalogueService.searchByTitle(title);
    }

    // ...additional methods as needed...
}
```

Walking it through: `ApiGateway` receives a request for user details and passes it to `UserService`. The same applies to a book title search, which is routed to `CatalogueService`.

What to take from the shape, not the detail: gateway methods *delegate*, they never *implement*. The moment a gateway method starts containing **business rules** (logic about the domain itself, e.g. "members may borrow 5 books") rather than forwarding, you are on the road to the **distributed monolith** described below (a system split into services that are still so tangled they must change and deploy together). Real gateways would wrap each delegation with auth, **timeouts** (a maximum wait before giving up), **retries** (trying a failed call again), and caching — but the delegation shape stays the same.

Lesson 4 — Problems the gateway itself introduces

The course opens this lesson with "every rose has its thorn" — the gateway solves a great deal and becomes a liability of its own. Five problems, each with its mitigation.

1. Single point of failure

Problem: If the API Gateway goes down, **nothing can communicate**. You have concentrated all traffic through one component, so its availability is now your system's availability. **Solution:** Implement **high availability** (staying up nearly all the time) and **redundancy** (running spare copies so one failure isn't fatal) for the gateway, and **monitor it diligently**.

2. Potential bottleneck

(A **bottleneck** is the one narrow point that limits how fast everything else can go.) **Problem:** All requests pass through the gateway, which could cause delays. **Solution:** Ensure the gateway is highly performant, **scale it horizontally** (add more machines running copies, rather than a bigger machine), and optimise its code.

3. Complexity in the gateway

Problem: The gateway can become too complex as it accumulates routing, security, transformations, and everything else. **Solution:** Keep the gateway's responsibilities clear. **Consider splitting it into multiple gateways** if necessary — per client type, or per functionality.

> This is the failure mode worth naming explicitly: the gateway is where business logic goes to hide. Once teams start putting domain rules in it, every team needs to change it, and it becomes

> the deployment bottleneck microservices were supposed to eliminate. Keep it about **transport** (moving requests to the right place), not **domain** (the business problem the software models).

4. Maintenance overhead

Problem: As services evolve, maintaining the gateway's routes and rules becomes challenging — the gateway's configuration drifts away from reality. **Solution: Automate as much as possible.** Use **CI/CD** (Continuous Integration / Continuous Delivery — automatically building, testing and releasing every code change) to ease maintenance.

5. Security risk

Problem: Being the entry point makes it a **prime target for attacks**. The same concentration that makes it useful makes it valuable to an attacker. **Solution:** Implement robust security practices, keep the gateway updated, and monitor for **vulnerabilities** (weaknesses an attacker could exploit).

Lesson 4 (cont.) — Performance implications

Distinct from the problems above: these are the costs the gateway imposes on every request.

1. Latency

Implication: The gateway introduces an **additional network hop** (one more trip between machines), which adds **latency** — the time a request takes from start to finish. **Solution:** Optimise its performance using techniques like **caching and response compression**.

2. Resource utilization

Implication: The gateway may consume significant resources, affecting performance. **Solution:** Ensure it has adequate resources; monitor utilisation and **scale as necessary**.

3. Content aggregation overhead

Implication: Aggregating responses from multiple services at the gateway is resource-intensive. **Solution:** Optimise the aggregation logic and use **asynchronous operations** where possible to prevent blocking.

4. Rate limiting challenges

Implication: Implementing **rate limiting** (capping how many requests a client may make per time window) at the gateway is complex, **especially in distributed deployments** — several gateway **instances** (running copies of the same program) must share a view of each client's usage. **Solution:** Use advanced algorithms built for this, such as **token bucket** or **leaky bucket**, which handle distributed scenarios.

> **Key term — token bucket / leaky bucket:** In a **token bucket**, each client has a bucket that refills with tokens at a steady rate; each request spends one token, and when the bucket is empty requests are rejected. A full bucket allows a short burst. A **leaky bucket** instead queues requests and lets them out at a fixed rate, smoothing bursts away. Both are explained further in System Design Fundamentals.

5. Load balancing overhead

Implication: The gateway must distribute requests efficiently to prevent **hotspots** (single instances that get far more traffic than the rest). **Solution:** Implement smart load balancing algorithms; **consider a service mesh** (a layer of small proxies beside every service that handles service-to-service traffic) for more granular control. *(See Sidecar.)*

6. Handling asynchronous operations

Implication: Managing async operations at the gateway is complex and can affect performance. **Solution:** Optimise their handling and provide clients with **clear mechanisms to check status or receive callbacks**.

The overall verdict: the pattern introduces challenges and performance costs, but with careful design, monitoring, and optimisation you can mitigate them and run a smooth, efficient system. The alternative — every client knowing every service — is worse.

Lesson 5 — System design example: Instagram

Instagram is a good illustration because it is genuinely complex: millions of users and a great many features. Think of it as a **bustling city**, with the API Gateway as the **main entrance**, directing traffic and keeping everything running smoothly.

The gateway's responsibilities here

- **Routing** — directing user requests to the appropriate microservice
- **Aggregation** — combining data from multiple services into one consolidated client response
- **Authentication & authorization** — confirming users are who they say they are, and that they have permission to access what they requested
- **Rate limiting** — preventing abuse by limiting how many requests a user can make in a timeframe
- **Load balancing** — distributing requests across multiple instances of a service so none is overwhelmed
- **Logging and monitoring** — tracking what is happening for troubleshooting and performance monitoring

The microservices behind it

- **User Management Service** — user profiles, relationships (followers/following), account settings
- **Photo Upload and Processing Service** — uploading photos, applying filters, resizing for different devices
- **Feed Service** — generating and serving the user's feed of photos from people they follow
- **Notification Service** — notifications for new followers, likes, comments
- **Search Service** — queries for user profiles, hashtags, and locations
- **Comment Service** — comments on photos

Scenario A — uploading a photo *(sequential)*

1. The user uploads a photo via the Instagram app
2. The request hits the API Gateway
3. The gateway **authenticates** the user and checks they are **authorized to upload photos**
4. Once authenticated, the gateway routes the request to the Photo Upload and Processing Service
5. The Photo Service processes the image and sends a response back to the gateway
6. The gateway sends a confirmation back to the user's app

Note that authentication and authorization are **two separate checks** at step 3, and both happen before any service is touched.

Scenario B — viewing the feed *(parallel — the interesting one)*

1. The user opens the app to view their feed
2. The request hits the API Gateway
3. The gateway authenticates the user
4. The gateway makes **parallel requests** to:
    - **Feed Service** — to get the list of recent photos from people the user follows
    - **Notification Service** — to fetch any new notifications
5. The gateway **aggregates** the responses from these services

6. The gateway sends a **single consolidated response** back to the app, showing feed and notifications together

Why the contrast matters

Upload is a single routed call. Feed is a **scatter-gather**: one client request fans out to several parallel service calls and comes back as one merged response.

That fan-out is where the gateway earns its latency cost. Doing the same thing client-side would mean several sequential **round trips** (a request going out and its response coming back) over a mobile network — far slower than one round trip plus parallel calls inside the **data centre** (the building of servers where the services run), where latency between services is a fraction of the latency to the phone.

The result: Instagram gets a consistent, efficient, and secure way to handle all the interactions needed for a seamless experience across millions of users, and the system stays easier to manage and scale as it grows.

Consolidation

API Gateway vs. BFF

	API Gateway	BFF
Count	One shared entry point	One per client type
Optimised for	All clients generically	One specific client
Client-specific logic	Pollutes it	Belongs there
Risk	Becomes a bottleneck / distributed monolith	Duplication and drift across BFFs

Not mutually exclusive — a common setup is a thin shared gateway (TLS — the encryption behind HTTPS; coarse auth; rate limiting) with BFFs behind it.

When to use

- Multiple microservices **and** multiple client types
- Clients would otherwise make many round trips per screen
- You want cross-cutting concerns (auth, rate limiting, logging) in one place
- You are exposing services to untrusted external consumers

When to avoid

- Very few services — the gateway is pure overhead
- Purely internal service-to-service traffic — a **service mesh** fits better
- One client whose needs diverge sharply from everything else — consider BFF
- Ultra-low-latency paths where an extra hop is unacceptable

Interview soundbite (30 seconds)

> "An API Gateway is a single entry point in front of your microservices. Clients call it instead of calling services directly, and it handles routing, response aggregation, authentication, rate limiting, caching, and logging in one place. The big win is that clients don't need to know your service topology — which matters most for mobile and TV clients you can't force-update, because any topology you bake into them is frozen in the field for years. The classic example is Instagram's feed: one request fans out in parallel to the feed and notification services and comes back as one response, which beats several sequential round trips from the phone. The trade-offs are that it's a single point of failure needing HA (high availability) and redundancy, it adds a network hop, rate limiting across distributed gateway instances needs token or leaky bucket algorithms, and it tends to accumulate business logic until it becomes a distributed monolith — so

> keep it about transport, not domain, and split it per client type or per domain if it gets too big. If each client type needs a genuinely different API shape, that's Backends for Frontends."

Implementation

A. Runnable demo

Full source: `demos/ApiGatewayDemo.java`

```
cd demos && ./gradlew runCh03
```

The heart of it is scatter-gather with per-service fallbacks:

```
Future<String> fFeed    = pool.submit(() -> feed.fetch(userId));
Future<String> fNotifs  = pool.submit(() -> notifications.fetch(userId));
Future<String> fProfile = pool.submit(() -> profile.fetch(userId));

result.put("feed",          get(fFeed,    "feed-unavailable"));
result.put("notifications", get(fNotifs,  "no-notifications"));
result.put("profile",       get(fProfile, "profile-unavailable"));

private String get(Future<String> f, String fallback) {
    try { return f.get(1, TimeUnit.SECONDS); }
    catch (Exception e) { return fallback; }        // partial failure contained
}
```

Here `pool` is a **thread pool** (a set of reusable worker threads that run tasks), and each `Future` is a placeholder for a result that will arrive later. All three calls are **submitted before any result is read** — that's what makes them parallel. Reading `fFeed` before submitting the others would **serialise** them (force them to run one after another).

B. What you should see

```
=== 1. Without a gateway: client calls each service itself ===
  3 round trips from the client: 288ms
  >> on mobile add ~150ms latency PER trip: ~738ms

=== 2. Gateway, sequential aggregation ===
  1 client round trip, 3 sequential server calls: 279ms

=== 3. Gateway, PARALLEL scatter-gather ===
  1 client round trip, 3 parallel server calls: 129ms
  >> ~the slowest service (120ms), not the sum

=== 4. Auth enforced once, at the edge ===
  rejected: 401 Unauthorized  (no service was touched)

=== 5. Partial failure -> graceful degradation ===
  {feed=feed-data, notifications=no-notifications, profile=profile-data}

=== 6. Rate limiting, also at the edge ===
  429 Too Many Requests after 5 requests
```

(The numbers `401` and `429` are **HTTP status codes** — standard three-digit codes in every web response; 401 means "not authenticated", 429 means "too many requests".)

Compare 2 and 3: 279ms → 129ms. Parallel aggregation costs the *slowest* service, not the sum. And note **section 4** — an unauthenticated request touched **zero** backend services, which is the security argument for a gateway stated as an observable fact.

C. Production — Spring Cloud Gateway

Spring Cloud Gateway is a ready-made gateway built on **Spring**, the most widely used Java framework. The XML below is the **Maven dependency** that adds it to a project (Maven is a Java build tool that downloads libraries). In the YAML config, `lb://` means "look the service up via **service discovery**" (a registry of where each service is running — see Service Discovery), **predicates** decide which requests a route matches, and **filters** modify or guard the request on its way through. `GET` is the HTTP method for reading data; a request is **idempotent** if repeating it has the same effect as doing it once.

```
<dependency>
  <groupId>org.springframework.cloud</groupId>
  <artifactId>spring-cloud-starter-gateway</artifactId>
</dependency>
```

```
spring:
  cloud:
    gateway:
      routes:
        - id: orders
          uri: lb://order-service          # lb:// = resolve via service discovery
          predicates:
            - Path=/api/orders/**
          filters:
            - StripPrefix=2
            - name: CircuitBreaker
              args:
                name: orderCB
                fallbackUri: forward:/fallback/orders
            - name: RequestRateLimiter
              args:
                redis-rate-limiter.replenishRate: 100    # steady-state req/s
                redis-rate-limiter.burstCapacity: 200    # burst allowance
            - name: Retry
              args:
                retries: 2
                statuses: BAD_GATEWAY,SERVICE_UNAVAILABLE
                methods: GET                             # only idempotent methods

        - id: products
          uri: lb://product-service
          predicates:
            - Path=/api/products/**
            - Header=X-API-Version, v2                   # route by version
```

Global cross-cutting filter — auth applied to every route. (`Mono` is a **reactive** type: a promise of one value delivered later without blocking a thread.)

```
@Component
public class AuthFilter implements GlobalFilter, Ordered {
    @Override
    public Mono<Void> filter(ServerWebExchange exchange, GatewayFilterChain chain) {
        String token = exchange.getRequest().getHeaders().getFirst("Authorization");
        if (!tokenService.isValid(token)) {
            exchange.getResponse().setStatusCode(HttpStatus.UNAUTHORIZED);
            return exchange.getResponse().setComplete();      // never reaches a service
        }
        return chain.filter(exchange);
    }
    @Override public int getOrder() { return -100; }          // run early
}
```

Kubernetes-native alternative — (**Kubernetes** is a platform that runs and manages **containers** — packaged, isolated applications — across a cluster of machines.) An **Ingress** or **Gateway API** resource (Kubernetes objects describing how outside traffic enters the cluster) does routing, TLS, and rate limiting without you writing or operating a gateway application at all. Prefer this when your needs are routing-shaped rather than aggregation-shaped.

D. Implementation pitfalls

1. Sequential calls that should be parallel. The most common performance bug in gateways. If you `.get()` on each future as you create it, you've written sequential code that looks **concurrent** (several tasks in progress at the same time).

2. No per-call timeout in aggregation. One slow service makes the whole aggregated response slow. Always bound each future — `f.get(1, TimeUnit.SECONDS)` in the demo — so the slowest dependency can't dictate your latency.

3. Business logic in the gateway. The distributed-monolith trap. Once domain rules live there, every team must change it and it becomes the deployment bottleneck. Keep it to transport concerns: routing, auth, rate limiting, aggregation, observability.

4. In-memory rate limiting behind multiple gateway instances. Three **replicas** (identical running copies) each allowing 100 req/s (requests per second) means the real limit is 300. Use a **shared store (Redis)** — Redis is a very fast in-memory key-value database often used for counters and caches — which is why the config above uses `redis-rate-limiter`.

5. Retrying non-idempotent requests. The `methods: GET` line above is deliberate. A gateway retrying a **POST** (the HTTP method for creating something) can create duplicate orders. *(See Retry.)*

6. Running the gateway as a single instance. It's a single point of failure by design — so run at least two replicas behind a **load balancer** (a component that spreads incoming requests across several servers), and treat its resource limits and monitoring as seriously as any critical service.

7. Losing trace context. The gateway is the ideal place to generate a **correlation ID** (a unique ID attached to a request and passed along to every service it touches, so its logs can be joined up) and propagate it **downstream** (to the services it calls). Skip it and you lose the ability to trace a request across services.

Related patterns

- **BFF** — one gateway per client type instead of one shared gateway
- **Circuit Breaker** — the gateway is a natural place to configure breaker rules per backend route
- **Service Discovery** — how the gateway finds service instances; the gateway is the classic server-side discovery router
- **Strangler Fig** — the migration facade is often literally an API Gateway
- **Sidecar** — gateway handles north-south (external, in and out of the system) traffic; a mesh of sidecars handles east-west (internal, service-to-service)

Backends for Frontends (BFF) Pattern

Category: Edge / routing **One-liner:** Instead of one shared backend serving every kind of client, give each client type its own backend tailored to exactly what that client needs.

Origin: Coined by **Sam Newman**, to solve the problem of building backend services for structurally different clients — mobile apps, web applications, and other client-side **frameworks** (ready-made code foundations you build an app on top of, such as React or SwiftUI).

Part 0 — Concepts you need first

What is a "frontend" and a "backend"?

The **frontend** is the part the user sees and interacts with — the mobile app, the website, the smart-TV interface. The **backend** is the server-side software the frontend talks to for data and operations.

A **client** in this chapter means a frontend application. "Client types" means categories of them: mobile, web, TV, watch.

What is over-fetching?

Over-fetching is when a client downloads more data than it actually needs.

Concretely: a mobile app shows a product list with a thumbnail, name, and price. But the API returns the full product object — a 2,000-word description, fifteen high-resolution image **URLs** (web addresses), full specifications, the seller's history. The app downloads all of it and displays three fields.

Why it hurts:

- **Bandwidth** (how much data a connection can carry, and how much you use) — on a **metered** mobile plan (one that charges per megabyte), this is the user's money
- **Latency** (the time a request takes from start to finish) — larger **payloads** (the actual data carried in a request or response) take longer over slow connections
- **Battery and CPU** (the processor that executes code) — the phone must **parse** (read and convert into usable objects) **JSON** (JavaScript Object Notation, a common text format for data) it discards
- **Memory** — constrained devices hold data they never use

What is an API?

An **API** (Application Programming Interface) is the agreed contract for how one piece of software asks another for something: what you can request, what parameters you supply, what shape comes back.

When this chapter says "one uniform set of APIs for all frontends," it means every client — however different — gets the same **endpoints** (specific URLs a server answers, like `GET /products/42`) returning the same shapes.

What is aggregation?

Combining data from several sources into one response. If a screen needs product details, reviews, and stock levels from three services, **aggregation** means one component calls all three and returns a single merged result, so the client makes one request instead of three.

Why round trips matter so much on mobile

A **round trip** is one request out and one response back. On a fast office network it might take 5-20ms. On a mobile network it can be **100-300ms or worse**.

Six round trips on a desktop: barely noticeable. Six round trips on mobile: potentially two seconds of nothing happening. This single fact drives most of this chapter.

Part 1 — The core idea, in plain terms

Imagine a company with three digital platforms:

- **A detailed website** — for users on computers, offering extensive information
- **A mobile app** — quick, essential services for on-the-go use
- **A smartwatch app** — core functions only, in a very compact form

These are genuinely different products with genuinely different needs. The website can display a thousand words; the watch can display about eight.

Traditionally, one backend serves all three. The course's analogy: BFF means giving **each section of a diverse restaurant its own kitchen**, rather than forcing one kitchen to cook for wildly different menus.

The reason this matters: the backend complexity appropriate for the website **overwhelms** the simpler needs of mobile and watch. The website's needs win by default, because it's usually the biggest and oldest client, and everyone else gets its leftovers.

Netflix does exactly this — web browsers, mobile apps, and smart TVs each get their own backend service, because each device has different capabilities and interfaces.

Part 2 — The problem in detail

One-size-fits-all

In traditional backend models the backend is a **monolithic** entity (one large application built and deployed as a single unit) serving multiple frontends, exposing **one uniform set of APIs regardless of each client's unique requirements**.

Consider a desktop app and a mobile app hitting the same API:

	Desktop	Mobile
Processing power	High	Limited
Display	Large	Small
Network	Usually fast, unmetered	Possibly slow, possibly metered

The course asks the right questions: should the mobile app receive the same amount of data as the desktop app? Is it efficient to process all that data in a mobile environment? **Not quite.**

Performance inefficiency and over-fetching

This leads directly to over-fetching, which causes performance issues, longer loading times, and increased bandwidth usage.

Worth being concrete about the cost. A product list screen:

- **Shared API response:** 250 KB (full descriptions, high-res image URLs, full specs)
- **What mobile displays:** name, price, thumbnail — about 4 KB of actual information

The user paid for 250 KB and used 4 KB. On a slow connection that's several seconds of waiting for data that gets thrown away.

Complexity in code management

When a single **codebase** (the full body of source code for one application) serves multiple frontends it becomes **bloated and complex** — harder to maintain, troubleshoot, and update. The more complex the system, the more time and resources it consumes, which could have gone to productive work.

In practice this shows up as endpoints crowded with **conditionals** (`if`/`else` branches):

```
if (clientType.equals("mobile")) {
    // trim the description
} else if (clientType.equals("tv")) {
    // use high-res images
} else if (clientType.equals("watch")) {
    // just the title
}
```

Every client's needs tangled into one method that nobody can change safely.

Lack of flexibility and scalability

Traditional backends have a rigid structure that makes it hard to innovate and scale. The course gives two symptoms that should feel obviously wrong:


1. **Sifting through a monolithic codebase to change one small feature for one specific frontend**
2. **Scaling the entire backend system because one frontend is experiencing high traffic**

Both are overkill — that's exactly the signal you need BFF.

> *Why symptom 2 matters:* suppose a TV advert drives a spike in mobile traffic. With a shared backend you scale the whole thing — including the capacity serving web and internal tools that aren't busy at all. You pay for capacity you don't need because the parts can't be scaled separately.

Part 3 — Architecture

Three layers:



1. Frontend applications — the user-facing applications: desktop, mobile, web. *The course's analogy: the customers ordering from a menu.*

2. BFFs — each paired with one specific frontend, catering to its unique requirements. *The chefs, preparing each dish to a customer's preference.*

3. Microservices — the underlying services BFFs call to fetch data. (**Microservices** are small, independently deployable services, each owning one business capability and its data.) *The kitchen staff providing the raw materials.*

The important structural point: **the microservices are shared; only the BFF layer is duplicated.** There is still exactly one Product Service holding product truth — the **source of truth** (the one place whose copy of the data is authoritative). BFFs don't own data — they reshape it.

What a BFF actually does

Tailored data delivery. Each BFF ensures its frontend receives *just* the data it needs. It acts as a **filter**, ensuring the frontend isn't overwhelmed with unnecessary information.

Streamlining communication. The BFF talks to multiple microservices, consolidates the data, and presents it to the frontend in one streamlined shape. The course calls it an **interpreter**, translating many languages into one the frontend understands.

Handling client-specific logic. Each BFF absorbs logic specific to its frontend, relieving the client of complex computation — a **personal assistant** doing work so the client's job is easier.

> *Why moving logic server-side matters especially for mobile:* you cannot force users to update a mobile app. If display logic lives in the app, fixing it means shipping a release, waiting for app

> store review, and waiting for users to update — some never will. If it lives in the BFF, you fix it and **deploy** (release the new version to the live servers) in minutes.

Part 4 — The benefits, explained

The course lists seventeen. Grouped by theme, with the reasoning behind each.

Fit and user experience

Diverse frontend needs. A mobile app, a web app, and a smart TV app have genuinely different requirements. BFF acknowledges that diversity instead of pretending it away.

Enhanced user experience. By catering to each device's specific needs and capabilities, the user gets the best possible experience on whatever they're using.

Localization and internationalization. Different frontends may serve users in different regions with different languages and cultural contexts. A BFF can serve localized content and region-relevant features.

Performance

Performance optimization. Mobile devices may be on slower networks with less processing power than a desktop. A BFF lets you optimise the data and interactions per device for fast, responsive apps.

Reduced bandwidth usage. Especially important for mobile — the BFF sends only what that specific frontend requires.

Scalability. (The ability to handle more load by adding resources.) Each frontend has its own backend, so you can scale parts of the system independently based on their own demand. A mobile traffic spike scales only the Mobile BFF.

Simplicity for frontend teams

Simplified frontend logic. Frontends no longer deal with the complexity of interacting with multiple microservices. They have a single, tailored backend that aggregates and processes data for them.

Consistency. A BFF can provide a **consistent API even while the underlying microservices are constantly changing**. This is a stability layer for frontend developers — the backend team can reorganise services without breaking every app.

Versioning control. Different frontend applications may be at different versions requiring different backend logic. A BFF handles versions gracefully, so each frontend gets logic appropriate to its version. *(Again most acute on mobile, where old versions persist in the wild.)*

Team and delivery

Agility. Teams work independently on their own BFF, allowing faster development and deployment cycles. The mobile team doesn't queue behind the web team.

Easier maintenance and upgrades. You can update the mobile backend without affecting the web backend, and vice versa.

Cross-functional teams. BFF promotes teams that own **end-to-end functionality for one user interface** — frontend and its backend together. Better collaboration, faster delivery.

Capability

Security. Each client type can have its own security considerations. A mobile app may need different **authentication** mechanisms (ways of proving who the user is, e.g. cookies vs. tokens) than a web app.

Error handling and resilience (the ability to keep working, perhaps in reduced form, when parts fail). You can implement error handling specific to each frontend. A web application might handle certain errors gracefully where a mobile app cannot.

Facilitates A/B testing (showing two variants to different user groups and comparing the results). You can test new features or changes on one client type — say the mobile app — **without affecting the**

others.

Feature flagging. (A **feature flag** is a configuration switch that turns behaviour on or off without deploying new code.) Enable or disable features for specific frontends at the backend level, without affecting others.

Handling legacy systems. During a monolith-to-microservices transition, a BFF acts as a **bridge**, letting new microservices-based frontends interact with **legacy systems** (old systems still running because the business depends on them). *(See Strangler Fig.)*

Part 5 — Worked example: e-commerce product details

Three components: one shared **Product Service**, a **Web BFF** (extensive detail), and a **Mobile BFF** (concise, to save data and improve load times).

1. Product Service — the real backend

```
@RestController
@RequestMapping("/products")
public class ProductServiceController {

    @Autowired
    private ProductRepository productRepository;

    @GetMapping("/{productId}")
    public Product getProductById(@PathVariable String productId) {
        return productRepository.findById(productId)
                .orElseThrow(() -> new ProductNotFoundException(productId));
    }
}
```

Reading it: (the code uses **Spring**, the dominant Java web framework; words starting with `@` are **annotations** — labels that tell the framework how to treat a class or method)

- `@RestController` marks this a web-request handler returning data (not **HTML** pages — HTML being the markup language browsers render)
- `@Autowired` asks Spring to supply ("inject") the `ProductRepository` object automatically; a **repository** is the class that reads and writes this data in the database
- `@RequestMapping("/products")` — every endpoint here starts with `/products`
- `@GetMapping("/{productId}")` — handles `GET /products/123`; `{productId}` is a placeholder
- `@PathVariable` pulls that value out of the URL into the method parameter
- `orElseThrow` — if no product exists, raise a clear error rather than returning `null` (Java's "no object here" value)

This service owns the **full, detailed** `Product` and does the heavy lifting. It knows nothing about mobile or web.

2. Web BFF — the detailed view

```java
@RestController
@RequestMapping("/web/products")
public class WebProductController {

    @Autowired
    private ProductServiceClient productServiceClient;

    @GetMapping("/{productId}")
    public ProductDetails getProductDetails(@PathVariable String productId) {
        Product product = productServiceClient.getProductById(productId);
        return convertToWebProductDetails(product);
    }

    private ProductDetails convertToWebProductDetails(Product product) {
        // Convert to a detailed view suitable for web:
        // richer descriptions, full-size images, etc.
    }
}
```

Note the URL prefix `/web/products` — each BFF has its own namespace, so clients can't accidentally call the wrong one.

`ProductServiceClient` is a **Feign client** or any **HTTP client** (code that sends web requests using HTTP, the protocol of the web) used to talk to the Product Service.

> *Beginner note — what's a Feign client?* A library that lets you call another service by declaring an interface, and generates the HTTP-calling code for you. You call `getProductById(id)` like a normal method and it makes the network request behind the scenes.

3. Mobile BFF — the concise view

```java
@RestController
@RequestMapping("/mobile/products")
public class MobileProductController {

    @Autowired
    private ProductServiceClient productServiceClient;

    @GetMapping("/{productId}")
    public SimpleProductDetails getProductDetails(@PathVariable String productId) {
        Product product = productServiceClient.getProductById(productId);
        return convertToMobileProductDetails(product);
    }

    private SimpleProductDetails convertToMobileProductDetails(Product product) {
        // Convert to a concise view suitable for mobile:
        // stripped-down descriptions, smaller images, etc.
    }
}
```

The structural point — read this part twice

Compare the two BFFs. They are **nearly identical**:

1. Both call the **same** `productServiceClient.getProductById(productId)`
2. Both receive the **same** full `Product` object
3. They differ **only in the transformation step** and therefore the return type:
    - Web returns `ProductDetails` — rich descriptions, full images
    - Mobile returns `SimpleProductDetails` — stripped descriptions, smaller images

A BFF is a projection layer, not a second source of truth. (A **projection** is a reshaped view of data that lives elsewhere.) There is one Product Service holding one truth about products. The BFFs each

project a different view of it. If you ever find a BFF *storing* data or deciding business rules about what a product *is*, it has stopped being a BFF.

How it works in practice

- The **Product Service** handles all the heavy lifting related to product data
- The **Web BFF** provides a detailed view suitable for web users
- The **Mobile BFF** provides a concise view suitable for mobile users

Each frontend gets exactly what it needs, and the backend logic is tailored to give the best possible experience.

Part 6 — Problems with BFF, and how to handle them

1. Code duplication

Problem: Since each frontend has its own BFF, there may be **duplication across BFFs**, especially where they share common functionality — authentication handling, error formats, logging. **Solution:** Use **shared libraries** (reusable code packages that several projects import) for common functionality, or create **internal microservices** that multiple BFFs consume.

2. Increased maintenance

Problem: More BFFs mean **more codebases to maintain**, increasing operational overhead. Three BFFs means three **deployment pipelines** (automated build-test-release sequences), three sets of **dependencies** (external libraries the code relies on) to patch. **Solution:** Adopt good **DevOps** practices (development and operations working together, with heavy automation of releases and monitoring), automate testing and deployment, and ensure proper monitoring to keep maintenance manageable.

3. Coordination overhead

Problem: Coordinating changes between frontends and their BFFs becomes challenging in large teams. **Solution:** Establish **clear contracts** between frontends and BFFs, and use **Consumer-Driven Contract Testing** to ensure compatibility.

> *Beginner note — consumer-driven contract testing:* the consumer (the app) writes down what it expects from the BFF as an executable test. The BFF's build runs those tests. If the BFF changes something the app depends on, the BFF's build fails — before it reaches production, rather than after.

Performance implications

Network latency. BFF adds an additional network **hop** (one more trip between machines), contributing to latency (see System Design Fundamentals). *Solution:* optimise network paths, use efficient **protocols** (agreed rules for how data is exchanged, e.g. HTTP/2 or gRPC), and ensure **BFFs are geographically close to the frontends they serve**.

Resource utilization. Each BFF may require its own set of resources. *Solution:* optimise BFFs for performance, use **serverless** (cloud functions where the provider runs and scales the servers for you and you pay per call) where appropriate, and scale on demand.

Caching challenges. Caching gets complex when multiple frontends have different requirements — the same underlying data cached in three different shapes. *Solution:* intelligent **caching** (keeping copies of recent answers to avoid refetching) at both BFF and frontend layers, and effective use of `Cache-Control` **headers** (HTTP metadata telling browsers and proxies how long a response may be reused).

Load on backend services. Multiple BFFs can increase load on the shared backend services. Three BFFs each fetching the same product means three calls where there was one. *Solution:* ensure backend services are scalable, monitor their performance, and implement **rate limiting** (capping how many requests a caller may make per second) if necessary.

> ⚠️ **The duplication trap is the one that actually bites.** Three BFFs slowly drifting apart on auth handling or error semantics is how "tailored" quietly becomes "inconsistent" — and users hit a bug on mobile that doesn't exist on web. Shared libraries are not optional at scale.

Part 7 — System design example: Netflix

Netflix serves smartphones, tablets, smart TVs, laptops, and gaming consoles. Each has distinct characteristics, user interactions, and performance considerations.

Scenario: viewing movie details — the user selects a movie and sees title, description, genre, rating, cast, recommendations, and user reviews.

Different devices prioritise differently:

Device	Priority
Smartphones	Quick loading, less data usage
Smart TVs	Rich visuals, detailed information, high-quality images
Web browsers	Balance between performance and rich content

Three BFFs: **Mobile BFF** (phones and tablets), **TV BFF** (smart TVs), **Web BFF** (browsers).

Mobile BFF

Serves concise movie details, smaller images, and **a subset of recommendations** to optimise for speed and data usage.

- **Authentication** — ensures the user is logged in and has a valid subscription
- **Routing** — directs the request to the appropriate microservices (Movie Details Service, Recommendation Service)
- **Aggregation** — combines data from those services and tailors it for mobile
- **Transformation** — reduces image sizes, shortens descriptions, formats data for quick mobile rendering

TV BFF

Serves rich visuals, detailed movie information, and a comprehensive list of recommendations.

- **Authentication & authorization** — checks not just login status but **whether the device is authorized** (allowed — as opposed to authenticated, which only checks identity) **to play high-definition content**
- **Routing & aggregation** — similar to Mobile BFF, but optimised for TV capabilities and network conditions
- **Transformation** — high-resolution images, full cast lists, elaborate descriptions

Web BFF

Balances performance and content richness.

- **Authentication** — standard login check
- **Routing & aggregation** — tailored for web browsers
- **Transformation** — content optimised for a wide range of browsers and screen sizes

The benefits realised

- **User experience** — each device gets an optimised, tailored experience
- **Performance** — data streamlined per device type, improving load times
- **Maintainability** — frontend teams work closely with their own BFF, leading to faster iterations

The challenges realised

- **Maintenance** — each BFF must be maintained and updated, creating overhead
- **Consistency** — ensuring consistent behaviour across all BFFs is genuinely challenging

> **The TV BFF's extra HD-entitlement check is the clearest single argument for BFF over one shared gateway.** That rule is meaningless for phones and browsers. In a shared gateway it would sit behind a device-type conditional, polluting a component every team must touch. In the TV BFF it's simply that BFF's business.

Part 8 — BFF vs. API Gateway

	API Gateway	BFF
How many	One shared entry point	One per client type
Optimised for	All clients generically	One specific client
Client-specific logic	Pollutes it	Belongs there
Main risk	Bottleneck / distributed monolith	Duplication and drift
Owned by	Usually a platform team (builds shared infrastructure)	Usually the frontend team

They are not mutually exclusive. A very common production setup is a thin shared gateway handling **TLS termination** (decrypting incoming HTTPS traffic at the edge so services behind it receive plain requests), coarse authentication, and rate limiting, with BFFs sitting behind it. The gateway does what's identical for everyone; the BFFs do what differs.

Think of BFF as API Gateway specialised per client, and note the ownership difference — a BFF being owned by the team that owns the frontend is a large part of why it delivers agility.

Part 9 — Common beginner misconceptions

"Each BFF needs its own database." No. BFFs are generally **stateless** (they keep no data of their own between requests). They call shared microservices and reshape responses. A BFF with its own database has usually turned into a microservice by accident.

"BFF means one backend per screen." No — per **client type**. All mobile screens share the Mobile BFF.

"You need BFF as soon as you have a mobile app." Only when needs genuinely diverge. If mobile and web want nearly the same data, a shared gateway is simpler. Adopt BFF when you're adding device-conditionals to shared code.

"GraphQL makes BFF obsolete." GraphQL is a query language for APIs, where a single endpoint accepts queries naming the exact fields wanted. GraphQL lets clients request exactly the fields they want, solving over-fetching without separate backends — a genuine alternative for *shaping*. But it doesn't solve client-specific *logic* (the HD-entitlement check) or independent scaling and ownership. Some teams use both: a GraphQL layer per client type.

"BFFs make the system faster." Not inherently — they add a hop. They make it faster *for the client* by cutting round trips and payload size, which dominates on mobile networks.

Part 10 — Check your understanding

1. What is over-fetching, and why does it matter more on mobile than desktop?
2. In the worked example, what is the **only** thing that differs between Web BFF and Mobile BFF?

3. Why is it wrong for a BFF to own a database?
4. What's the strongest argument for the TV BFF over a shared gateway?
5. Name the main cost of BFF and its standard mitigation.
6. When should you *not* use BFF?

(Answers: 1 — downloading more data than needed; mobile has metered data, slow networks, limited CPU/memory; 2 — the transformation step and its return type, both call the same service for the same object; 3 — BFFs are projection layers, not sources of truth — one service owns each piece of data; 4 — the HD-entitlement authorization check is meaningless to other clients and would pollute shared code; 5 — code duplication across BFFs, mitigated by shared libraries and internal services; 6 — when clients' needs are nearly identical, or the team is too small to maintain several backends.)

Part 11 — Interview soundbite (30 seconds)

> "BFF, from Sam Newman, means giving each client type its own backend instead of sharing one. The problem it solves is over-fetching and one-size-fits-all APIs — a mobile app on a metered connection shouldn't receive a payload designed for a desktop, and it shouldn't need six round trips on a slow network to build one screen. Each BFF calls the same underlying microservices but aggregates and transforms for its client: mobile gets small images and short descriptions, TV gets high-res and full cast lists. Crucially the BFF is a projection layer, not a source of truth — the microservices still own the data. Netflix does this across phones, TVs, and browsers, and their TV BFF has an extra authorization check for HD entitlement, which is a good example of client-specific logic that would pollute a shared gateway. It also lets frontend teams own their backend and ship independently, and lets you scale per client. The costs are code duplication across BFFs, more codebases to maintain, an extra network hop, and keeping behaviour consistent between them — so shared libraries and consumer-driven contract testing matter. It's essentially API Gateway specialised per client rather than one shared gateway, and the two are often combined."

Part 12 — Implementation

A. Runnable demo

Full source: `demos/BffDemo.java`

```
cd demos && ./gradlew runCh04
```

The essential structure — three BFFs, one **upstream** service (the service a component calls to get its data), three projections:

```
// Mobile: trim the copy, shrink the image
new MobileProductDetails(
    p.id(), p.name(), p.price(),
    truncate(p.longDescription(), 120),
    p.hiResImages().get(0).replace("4k", "thumb"));

// Watch: two fields, nothing else
new WatchProductDetails(truncate(p.name(), 20), p.price());
```

B. What you should see

```
=== 1. The over-fetching problem ===
  shared API payload:   3,525 bytes
  >> a watch showing name + price downloads ALL of that

=== 2. Each BFF projects the same object differently ===
  Web BFF:      3,525 bytes  (100% of shared)
  Mobile BFF:     251 bytes  (  7% of shared)
  Watch BFF:       31 bytes  (  0% of shared)
  >> mobile saves ~3274 bytes PER PRODUCT

=== 3. All BFFs call the SAME upstream service ===
  ProductService invocations so far: 4
  >> BFFs are projection layers - one source of truth remains

=== 4. Client-specific logic belongs in its own BFF ===
  certified TV:     Full HD payload ... with 3 4K images
  uncertified TV:   SD-only payload ...
```

Mobile receives 7% of the shared payload. Multiply by a 50-item product list and it's the difference between a screen that loads instantly and one that visibly stalls on a train.

Section 3 is the conceptual check: every BFF called the *same* `ProductService`. **They add no data and own no data.** A BFF that starts storing things has stopped being a BFF.

C. Production — a BFF is just a small service

There's no special framework; a BFF is an ordinary application whose job is aggregation and shaping. Below, `CompletableFuture.supplyAsync` runs each call on a background thread so the three calls happen in parallel, `.exceptionally(...)` supplies a default if a call fails, and `join()` waits for the results.

```java
@RestController
@RequestMapping("/mobile/v1")
public class MobileBffController {

    private final ProductClient products;
    private final ReviewClient reviews;
    private final InventoryClient inventory;

    @GetMapping("/products/{id}")
    public MobileProductView get(@PathVariable String id) {
        // Fan out in parallel - the BFF exists to save the client round trips
        var pf = CompletableFuture.supplyAsync(() -> products.byId(id));
        var rf = CompletableFuture.supplyAsync(() -> reviews.summaryFor(id))
                    .exceptionally(e -> ReviewSummary.empty());     // degrade, don't fail
        var inf = CompletableFuture.supplyAsync(() -> inventory.stockFor(id))
                    .exceptionally(e -> Stock.unknown());

        CompletableFuture.allOf(pf, rf, inf).join();
        return MobileProductView.from(pf.join(), rf.join(), inf.join());
    }
}
```

GraphQL as an alternative. It solves the *shaping* half of the problem — clients request exactly the fields they need, so one endpoint serves all clients without over-fetching:

```
query MobileProduct($id: ID!) {
  product(id: $id) { id name price thumbnail }     # mobile asks for four fields
}
```

But it does **not** solve client-specific *logic* (the TV HD-entitlement check), independent scaling, or team ownership. A common production setup is **one GraphQL BFF per client type** — shaping from GraphQL, isolation from BFF.

Shared code across BFFs — the mitigation for the duplication problem (**tracing** below means recording a request's path across services so it can be followed end to end):

```
bff-common/          <- auth, error format, tracing, resilience config
  ├─ mobile-bff/
  ├─ web-bff/
  └─ tv-bff/
```

D. Implementation pitfalls

1. Giving a BFF its own database. The single most common mistake. BFFs are **stateless projection layers**. **Persistent state** (data saved so it survives restarts) means you've accidentally created a microservice with duplicated ownership of data.

2. Sequential upstream calls. A BFF exists to cut client round trips. Making three sequential server-side calls just moves the latency rather than removing it. Fan out with `CompletableFuture.allOf`.

3. No fallback on secondary data. If reviews are down, a product page should still render. Note the `.exceptionally(...)` on the review and inventory futures but *not* on the product itself — the primary resource legitimately fails the request; supporting data must not.

4. Copy-pasting auth into every BFF. This is how three BFFs drift into three subtly different security behaviours. Extract to `bff-common` from the start.

5. One BFF per screen. Per **client type**, not per screen. Twenty BFFs is twenty deployment pipelines for no benefit.

6. Business rules migrating into the BFF. "Is this order eligible for a refund?" belongs in the order service, where every client gets the same answer. Only **presentation** decisions belong in a BFF.

7. Versioning by breaking changes. (A **breaking change** is one that makes existing clients stop working, such as removing or renaming a field.) Old mobile app versions live in the wild for years. Version the BFF path (`/mobile/v1`, `/mobile/v2`) and keep old versions running — being able to do this is a major reason BFF exists.

Related patterns

- **API Gateway** — the shared-entry-point alternative, and frequent companion
- **Strangler Fig** — a BFF can bridge new frontends to legacy systems mid-migration
- **Service Discovery** — how BFFs locate the services they aggregate
- **Circuit Breaker** — a BFF calling several services needs protection when one fails

Service Discovery Pattern

Category: Communication **One-liner:** A registry that lets services find each other by *name* at runtime, instead of hardcoding network addresses that change constantly.

(A **registry** is a central list of what exists and where; **runtime** means while the program is running, as opposed to when it is written or built; **hardcoding** means writing a value directly into the source code so it can't change without editing and redeploying.)

Part 0 — Concepts you need first

What is an IP address and a port?

An **IP address** identifies a machine on a network (e.g. `10.0.3.47`). A **port** identifies which program on that machine (e.g. `8080`). Together — `10.0.3.47:8080` — they identify one running service instance.

To call another service, you must know its address and port. That's the entire problem this pattern exists to solve: in modern deployments, **those numbers change all the time**.

What is an "instance"?

One running copy of a service. If your Order Service is busy, you run five copies to share the load — five **instances**, each with its own IP address, all running identical code.

This is **horizontal scaling**: handle more load by adding more copies, rather than by making one copy bigger.

What is a container, and why does it make addresses unstable?

A **container** packages an application with everything it needs to run, so it starts anywhere in seconds. **Kubernetes** is the standard system for running containers across a fleet of machines — a group of machines managed together this way is called a **cluster**.

The key consequence: containers are **disposable**. Kubernetes starts them, stops them, moves them between machines, and replaces them during deployments. **Each new one typically gets a new IP address.** An address you looked up ten minutes ago may now point at nothing.

What is auto-scaling?

Automatically adding instances when load rises and removing them when it falls. **AWS** (Amazon Web Services, Amazon's cloud platform) auto-scaling groups do this. It saves money — but it means **the number of instances and their addresses change throughout the day without anyone touching anything**.

What is load balancing?

Distributing incoming requests across multiple instances so no single one is overwhelmed. If you have five instances and one hundred requests, ideally each handles about twenty. (Covered in more depth in System Design Fundamentals.)

What is DNS?

The **Domain Name System** translates names into IP addresses — you type `example.com`, DNS returns the address. It's the internet's original name-to-address lookup, and some service discovery systems (notably Kubernetes) work by extending exactly this idea inside your cluster.

Part 1 — The problem

In a **monolith** (one application built and deployed as a single unit), components are tightly integrated and deployed as one unit. Component A calling component B is just a **method call inside the same process**

(the same running program, sharing memory) — no network, no address, nothing to discover. Service discovery is a non-problem.

In **microservices** (an architecture of many small, independently deployed services), services are **loosely coupled** (each knows as little as possible about the others' internals) and deployed independently. They may live on different servers, in different data centres, even on different continents. Now every call is a network call to an address that must be known.

Three forces make hardcoded addresses unworkable.

1. Dynamic infrastructure

Modern deployments — **virtual machines** (software-simulated computers, many of which can share one physical server), containers, Kubernetes — give services **no fixed IPs or hosts** (a **host** is the machine a program runs on). Instances come and go, scale up and down, and get replaced during deployments.

The course's example: an AWS auto-scaling group launches new instances of a service or terminates them based on load, **each time with new IP addresses**. Keeping track of these moving targets is a serious challenge.

2. Undetermined number of instances

Multiple instances of the same service run for load balancing. So: **which instance should a client call?**

- Hardcoding one address means all traffic goes to that one instance — you've lost load balancing entirely, and if it dies, everything fails
- Maintaining a list by hand is error-prone, and becomes untenable as services and instances multiply

3. Coupling

A goal of microservices is that teams deploy and scale independently. But if every client must know every service's exact address, you have **tight coupling**. A location change means updating **configuration** (settings supplied to a program from outside its code) in **every client that calls it**.

Deployment details leak into client configuration, and the agility you adopted microservices for disappears.

The concrete scenario

An online retail application. A user places an order:

- **Order Service** must call **Inventory Service** to check item availability
- Then call **Payment Service** to process payment

How does Order Service know where those are? What happens when Inventory moves to a new server? What happens when extra Payment instances spin up under load — how does Order Service learn they exist?

Part 2 — The solution

Introduce a **central registry and lookup mechanism**.

Dynamic registration

Each service instance, **when it starts, registers its address (host and port) with a central Service Registry**. When shutting down, it de-registers. The registry therefore always holds a current listing of active instances. Clients no longer need hardcoded addresses.

Lookup by logical name

Services register under a **logical name** — `OrderService`, `UserService`. A client needing to call a service simply asks the registry for the address of `"OrderService"`, and gets back the current location, or several if multiple instances exist.

> **This indirection is the entire trick.** Instance addresses can change freely because clients only ever know the *name*. It's the same idea as a phone book: you look up a person by name, and it doesn't matter that their number changed last year.


Load balancing and scaling

With multiple instances running, discovery works together with a load-balancing strategy. Scaling horizontally becomes trivial: **register more instances, and clients discover them automatically**.

Decoupled configuration

Clients maintain no configuration of service endpoints, staying decoupled from other services' deployment details. This makes continuous deployment and auto-scaling possible without disrupting clients. The client supplies a service name; **actual routing happens at runtime**.

Part 3 — Architecture



The Service Registry

A database holding all services and their current locations — the **centralized source of truth**, effectively a phone book for your system.

Three responsibilities:

1. Service Registration. When a service comes online it registers itself, providing its name, IP address, port, and potentially **metadata** (extra descriptive data) such as service version or **health endpoint** (a URL that answers "am I working?").

2. Service Deregistration. Removing a service — either when it shuts down gracefully, or when the registry detects it's no longer available.

3. Health Checking. The registry periodically **pings** services (sends a tiny test request to see if they answer) or their health endpoints to check they're still running. If a service doesn't respond within a certain timeframe, it's considered failed and removed.

> *Why health checking is essential:* graceful deregistration only covers graceful shutdown. If an instance **crashes**, loses power, or gets **partitioned** off the network (cut off from the other machines by a network failure), it never gets the chance to say goodbye. Without health checks the registry would hand out dead addresses forever.

The payoff: the system **adapts dynamically**. A service moves or scales → the registry updates → others still find it. A service dies → it's removed → others can apply **fallback** strategies (a backup plan, such as a default answer).

Part 4 — Client-side vs. server-side discovery

Both use a registry. They differ in **who performs the lookup and load balancing** — and this is the single most likely thing you'll be asked about in an interview.

Client-side discovery — "smart client"

The workflow:

1. **Service Registration** — each instance registers with the registry at startup, providing its address and perhaps a health **heartbeat** (a small "I'm still alive" message sent at regular intervals); it unregisters on shutdown.
2. **Service Lookup** — when a client needs to call a service, it **queries the registry directly** for a list of active instances.
3. **Client-side Load Balancing** — the client (or a library on the client side) selects one of the instances, often using **round-robin** (take turns: 1, 2, 3, 1, 2, 3…) or **consistent hashing** (a hash-based scheme that keeps sending the same key to the same instance, and moves only a few keys when instances are added or removed).
4. **Request Invocation** — the client makes the request **directly to the chosen instance**. Subsequent requests may repeat the lookup or use a **cached** result (a saved copy of an earlier answer).

The client is **"smart"**: it contains logic to query the registry and balance load.

The classic stack: Netflix **Eureka** (an open-source service registry written by Netflix) as the registry, combined with a client load-balancer library such as **Ribbon** or **Spring Cloud LoadBalancer**. The client knows the Eureka location, uses it to find instances, then calls one directly.

Advantages:

- **No extra network hop** — after discovery the client talks to the service directly
- **Intelligent decisions** — because the client knows all instances, it can implement sophisticated, application-specific load balancing (e.g. choose an instance based on request content)
- **Fewer moving parts at runtime** — aside from the registry, no additional routing layer is needed
- **Slightly lower latency** (time per request) — no intermediate **proxy** (a middleman that forwards requests)

Disadvantages:

- **Every client needs the discovery logic and library**, increasing complexity
- **Painful in polyglot environments** (where services are written in many programming languages) — with services in multiple languages you need a compatible discovery client for each, or a standardized approach. This is a real barrier
- **Two network calls per request** — one to the registry, then the actual request (though caching usually eliminates the first)
- **Couples clients to the discovery mechanism** — if the registry changes, many clients may need updating, which is a maintenance burden

The standard mitigation: clients **cache** registry responses. This avoids a lookup on every call *and* lets the system keep working if the registry is temporarily down.

Server-side discovery — "smart router, dumb client"

The workflow:

1. **Service Registration** — identical; instances register at startup, deregister on shutdown.
2. **Request to Load Balancer** — the client sends its request to a **known, fixed endpoint** — a load balancer, gateway, DNS name, or **virtual IP** (a stable IP address that isn't tied to one machine and is forwarded to whichever instances are current). **The client never queries the registry.**
3. **Service Discovery & Routing** — the load balancer receives the request and queries the registry for healthy instances.
4. **Load Balancing** — the load balancer selects an instance using its own algorithm.

5. **Forwarding** — it forwards the request to the chosen instance. From the client's perspective it simply made a request to a single endpoint; it has no idea any of this happened.

The intermediary is "smart" and the client is simple.

Advantages:

- **Much simpler clients** — one call to a fixed address, no discovery code, no special libraries
- **Language-agnostic** — any client that can make a normal **HTTP** request (the standard protocol web browsers and APIs use) works, because discovery happens in the network infrastructure. This is the decisive advantage in a polyglot estate
- **One network call per request** — no separate lookup
- **Abstraction** — where services actually run can change without impacting clients
- **Often provided out of the box** — Kubernetes and cloud load balancers give you this for free

Disadvantages:

- **An extra hop** through the load balancer, adding slight latency
- **The load balancer must be highly available and scalable** — it's now critical to every request
- **Operational overhead** if your environment doesn't already provide one
- **The client loses control** over which instance it talks to — it can't tailor routing per request and must trust the router's decisions

Choosing between them

	Client-side	Server-side
Who queries the registry	The client	The load balancer / gateway
Network hops	Fewer (direct call)	One more (through the router)
Client complexity	Higher — needs a library	Very low
Polyglot friendliness	Poor	Excellent
Routing control	Fine-grained, app-specific	Whatever the router does
Typical stack	Eureka + Ribbon (Spring Cloud)	Kubernetes Services, cloud LBs

Practical guidance:

- In the **Spring Cloud / Netflix OSS** world (Spring Cloud is a set of Java libraries for microservices; Netflix OSS is Netflix's open-source tooling), client-side (Eureka + Ribbon) is straightforward
- On **Kubernetes**, the platform's built-in discovery via DNS means you lean server-side — you simply call `http://my-service` and Kubernetes routes it
- **They're not mutually exclusive** — you might use client-side for internal service-to-service calls while having an API gateway (server-side style) for external traffic

In modern systems — Kubernetes, **service meshes** (a layer of proxies next to every service that handles traffic between services) — **server-side discovery is the norm**, because the platform abstracts discovery behind DNS or a gateway.

Part 5 — Inner workings

Self-registration vs. third-party registration

Self-registration: services register and deregister *themselves* when they come online or go offline.

- *Upside:* simplicity, and the service has full control
- *Downside:* the service carries the added responsibility of keeping its status up to date

Third-party registration: a **service manager** handles registration. It monitors services and updates their status in the registry.

- *Upside:* takes the burden off the services entirely
- *Downside:* introduces another component that must itself be managed

Health checks — two models

Self-reporting (the heartbeat model). Services send a periodic signal to the registry saying they're still active. If the registry doesn't receive a signal within a given timeframe, it assumes the service is offline and removes it.

Active monitoring. The registry proactively checks services by sending a ping or similar request. No response → marked offline.

> The difference matters under load: heartbeats put work on the services and scale with instance count; active monitoring puts work on the registry and scales with *its* capacity to poll everyone.

Part 6 — Worked example (simplified Java)

The registry — a phone book

```java
import java.util.concurrent.ConcurrentHashMap;

public class ServiceRegistry {
    private ConcurrentHashMap<String, String> services = new ConcurrentHashMap<>();

    public void register(String serviceName, String serviceAddress) {
        services.put(serviceName, serviceAddress);
    }

    public String discover(String serviceName) {
        return services.get(serviceName);
    }
}
```

Reading it: keys are service names, values are addresses. `register` adds a service; `discover` retrieves an address by name.

Why `ConcurrentHashMap`? Registration and lookup happen from many **threads** (independent paths of execution inside one program) simultaneously — many services registering while many clients look things up. A plain `HashMap` (Java's standard key-to-value lookup table) would corrupt under concurrent modification (being changed by several threads at once). `ConcurrentHashMap` is designed for exactly this.

A service registering itself

```java
public class Service {
    private String name;
    private String address;

    public void register(ServiceRegistry registry) {
        registry.register(name, address);
    }
}
```

This is **self-registration**. When the service starts it calls `register` to add itself. In a more sophisticated system this happens automatically — via a service manager, or as part of the deployment process.

A client discovering and calling

```
public class ClientService {
    private ServiceRegistry registry;

    public void callService(String serviceName) {
        String serviceAddress = registry.discover(serviceName);

        if (serviceAddress == null) {
            throw new RuntimeException("Service not found: " + serviceName);
        }

        // Make a request to the service
    }
}
```

The client uses the registry to find the address of the service it wants. If not found, it throws. If found, it proceeds with the request.

What this toy version is missing

The course is explicit that real implementations are more complex. Specifically:

- **Health checks** — services must regularly report in to keep their registration current
- **A distributed registry** — to handle high traffic and provide **redundancy** (spare copies so one failure isn't fatal)
- **Failure handling in** `callService` — retrying the request, or falling back to a backup service
- **A *list* of instances, not one address** — `Map<String, String>` stores exactly one address per service name, so this design **cannot load balance at all**. A real registry stores `Map<String, List<String>>` and returns all healthy instances so the client can choose

That last point is the most important gap to notice — it's the difference between a demo and something usable.

Part 7 — Performance implications and special considerations

1. Latency overhead

Every registry lookup is an extra step. In client-side discovery this is usually small because clients **cache** — fetching the instance list once and reusing it for many requests, refreshing every ~30 seconds or on a **cache miss** (when the wanted entry isn't in the cache). The lookup is normally a fast local network call taking milliseconds.

To minimise latency:

- Cache and reuse discovery information for a short duration rather than querying per request
- Design the registry to respond quickly (in-memory **indexes** — lookup structures kept in RAM so entries are found without scanning)
- Use **asynchronous** discovery updates (delivered in the background without the caller waiting) — pushed updates or **long-polling** (the client asks, and the server holds the request open until there's news)
- In high-performance scenarios, bake a small local endpoint cache into each instance at startup to avoid even the initial lookup delay

2. Scalability of the registry

It must handle registrations from potentially thousands of instances plus frequent lookups. It can become a **bottleneck** (the slowest point that limits the whole system).

- **Clustering** — run the registry as a cluster of multiple **nodes** (individual machines or instances in the group) (e.g. three instances of Eureka or **Consul**, HashiCorp's registry and configuration tool) sharing load and providing redundancy. Configure clients with multiple registry URLs

- **Sharding** (splitting data across several independent servers, each holding a part) — partition registries by service domain. Uncommon; one cluster usually suffices for a large organisation
- **Efficient heartbeats** — thousands of instances heartbeating every 30 seconds is genuine load. Eureka lets you tune the heartbeat interval and use **self-preservation mode** to avoid overwhelming the network during an **outage** (a period when something is down) or partition
- **Lightweight protocols** — Consul uses an efficient **gossip** mechanism for health (each node regularly swaps news with a few random others, so information spreads like a rumour); **Zookeeper** (Apache's coordination service) uses an event-driven model with **persistent connections** (network connections kept open for reuse)

3. Fault tolerance and high availability

(**Fault tolerance** is continuing to work when parts fail; **high availability** is being up nearly all the time.) If the registry is down, services may be unable to find each other — especially with client-side discovery.

- **Run multiple registry instances** — at least two or three in production. Keep data in sync via **consensus** (an algorithm that makes several nodes agree on one value even if some fail) (Consul, Zookeeper) or **peer-to-peer** sync (each node copies directly from the others, with no leader) (Eureka)
- **Client-side caching for resilience** — many clients continue using the last known good information if the registry becomes unreachable. Spring's Eureka client does this by default, allowing the system to keep functioning assuming topology hasn't changed drastically
- **Failover of registry nodes** (**failover** = automatically switching to a backup when the primary fails) — configure clients with multiple registry addresses so they try the next when one fails
- **Monitor the registry itself**, not just the services it tracks
- **Data persistence** — Consul, **etcd** (a distributed key-value store used by Kubernetes), and Zookeeper persist to disk (save data so it survives restarts) and recover state after restart. Eureka keeps state in memory and relies on clients re-registering. Persistence helps recovery if all nodes reboot, but may be overkill if services simply re-register on startup

Consistency vs. availability — the CAP trade-off

> *Beginner note — CAP theorem:* (see also System Design Fundamentals) in a **distributed system** (many machines cooperating over a network), when a network partition splits your nodes apart, you must choose between **consistency** (never serve wrong data, even if that means serving nothing) and **availability** (always answer, even if the answer may be stale). You cannot have both during a partition.

	Zookeeper / Consul	Eureka
Choice	**CP** — consistency	**AP** — availability
Behaviour	Avoids serving possibly-stale data; may become unavailable until consensus is restored	Continues serving whatever it has, even if stale
On partition	May refuse to answer	**Self-preservation** — won't purge entries, so some info stays available

Be aware of your registry's behaviour and tune it. For example, turn **off** self-preservation in small setups to get quicker removal of dead instances.

> *Which is right?* For service discovery, **availability usually beats consistency**. A slightly stale instance list is survivable — you try an address, it fails, you retry another. A registry that refuses to answer means nothing can talk to anything. This is why Eureka chose AP.

4. Load balancing strategies

- **Round Robin** — each new request goes to the next instance cyclically. Distributes evenly assuming instances have similar capacity
- **Random** — pick randomly each time; roughly balances over many requests and is trivially simple
- **Least Connections / Load** — track which instance has fewest active requests and send there, balancing *actual* load. Requires more sophisticated tracking; usually done in server-side LBs or service meshes
- **Hashing (sticky sessions)** — consistently send the same client to the same instance, for caching or **session affinity** (keeping a user's requests on the server that holds their session data). E.g. hash of user ID modulo instance count
- **Geographic / AZ affinity** (an **AZ**, availability zone, is a separate data centre within one cloud region) — in multi-datacenter or multi-availability-zone deployments, prefer an instance in the client's zone for lower latency. Discovery metadata carries the zone

Ribbon defaults to round-robin on the client side; a cloud **ELB** (AWS Elastic Load Balancer) might do round-robin or least connections by configuration.

5. Failover handling

What happens when a call to an instance fails? With discovery you have multiple instances, so try another.

- **Client retry** — on **timeout** (giving up after waiting a set time) or error, query the registry again (or use the cached list), pick another instance, and retry. Ribbon and Spring Cloud LoadBalancer have retry mechanisms
- **Circuit breakers** (components that stop calling a failing service for a while) — **Hystrix** (Netflix's older library) or **Resilience4j** (its modern Java replacement) can trip if a service fails repeatedly and stop calling it for a cooldown. Combined with discovery this can be **per-instance**: if instance X of Service A is failing, stop sending to X while continuing with Y and Z. Discovery is what ensures Y and Z are available *(see Circuit Breaker)*
- **Health-based removal** — the registry should promptly mark failing instances unhealthy so lookups stop returning them. Proactive, and better than reacting at request time
- **Timeout tuning** — keep timeouts short. **Fail fast** (give up quickly rather than hang) and try another instance; that's viable precisely because you have a discovered pool

6. Consistency of data

The registry's view of which instances are up can lag reality. If a service crashes there's a window before the registry notices (the next heartbeat period), during which a client may be handed an instance that just died. To minimise impact:

- **Reduce heartbeat intervals** — faster detection, at the cost of more network chatter
- **Client pre-flight health check** before critical requests — adds overhead, rarely done
- **Tolerate the failed attempt and retry another instance** — usually the right answer
- In strongly consistent systems like Zookeeper, watchers are notified almost immediately when a client disconnects. But under high **churn** (instances constantly starting and stopping), an AP approach like Eureka may give better overall availability

7. Data volume and registry size

In very large deployments — hundreds of services, thousands of instances — the registry holds a large dataset. Most registries **index by service name** so lookups by name are fast. Ensure adequate RAM/CPU (memory and processing power). Some registries support **tagging and filtering** — asking for instances of a service with a tag like `version: v2`, which is useful during **rolling deployments** (replacing instances with the new version a few at a time) of new versions.

8. Transactional consistency — subtle but important

If a service registers itself **before it is fully ready to serve traffic**, a client may discover and call it while it's still warming up — loading caches, opening **connection pools** (sets of ready-made database

or network connections reused across requests), **JIT-compiling** (the Java runtime compiling frequently used code to fast machine code just in time, while running).

> **Best practice:** register only once fully initialised, and **de-register immediately when shutting down, before actually going offline.** Design your startup and shutdown sequences with this in mind. This is a very common source of confusing intermittent errors right after a deployment.

Part 8 — Security considerations

The registry is critical infrastructure — it knows where everything is and helps route traffic. If compromised, an attacker can misroute traffic or map your entire topology.

Service spoofing (fake registrations). An unauthorized or malicious instance registers itself pretending to be a legitimate service. Other services then discover and communicate with it, letting it **intercept or manipulate data**. *Mitigation:* authentication and authorization for registration — the registry verifies a registering service is allowed to register under that name. Consul provides **ACLs and tokens** (**access control lists** — rules saying who may do what — checked against a secret token); Eureka can be secured with **HTTP basic authentication or mutual TLS** (basic auth sends a username and password with each request; **mutual TLS**, or **mTLS**, means both sides present encryption certificates to prove their identity).

Unauthorized registry access. The registry holds sensitive information — internal service addresses, health status. An attacker who can query it freely gets **a map of all your services**. *Mitigation:* restrict access. Don't expose Eureka publicly; run it on an internal network. Require authentication on its API and **UI** (user interface — here, its web dashboard). Consul ACLs can require a token to read. Kubernetes DNS is naturally cluster-isolated, and **RBAC** (role-based access control — permissions granted to roles rather than individuals) can further limit which services read which resources.

Communication security. Traffic between services and the discovery service may cross untrusted networks. *Mitigation:* **TLS** (Transport Layer Security, the encryption behind HTTPS) for all registry traffic, especially in multi-datacenter setups. If using an API gateway for server-side discovery, secure gateway-to-service and client-to-gateway calls too.

Least privilege. Not every service needs to know about every other service. *Mitigation:* segment the registry or use ACL policies so a given service discovers only what it needs. A "frontend" service might need `accounts` and `orders` but should not see internal services.

Audit and monitoring. Enable logging or **audit trails** (tamper-resistant records of who did what, when). Watch for unusual patterns — a service registering from an unknown IP, or a spike in failed authentication against the registry.

DDoS and abuse. (A **DDoS**, distributed denial-of-service attack, floods a system with traffic from many machines to knock it over.) A discovery service flooded with registration requests or queries may slow or crash. *Mitigation:* **capacity planning** (estimating and provisioning the resources you'll need), and **rate limiting** (capping requests per caller per second) on discovery operations.

Securing server-side components. If you use server-side discovery, the gateway or load balancer accepts client requests *and* talks to the registry — harden it accordingly.

> Treat service discovery infrastructure as **security-sensitive critical infrastructure**.

Part 9 — Real-world implementations

Netflix — Eureka. Netflix is often cited as a microservices pioneer. Hundreds of services register with Eureka, and Netflix applications query it to find instances. This lets Netflix scale services up and down and move them across data centres without clients knowing the details. Proven at streaming scale.

Kubernetes — the most widespread use today. Kubernetes has a **Service**: a stable virtual IP and DNS name for a set of **pods** (a pod is Kubernetes' smallest unit: one or more containers running together). When new pods come up or old ones die, Kubernetes updates its internal endpoints list, and through **kube-proxy** (a network component on every Kubernetes machine that forwards Service traffic to pods) ensures traffic to the Service is load-balanced to current pods. Any pod can simply look up `http://service-x` and reach it. Under the hood, Kubernetes maintains an **etcd**-based registry and a cluster DNS service (**CoreDNS**, the DNS server inside Kubernetes) answering queries from current registry data.

> This is why "we're on Kubernetes" is usually a complete answer to service discovery. You already have it, and building a second layer on top is usually a mistake.

Airbnb — SmartStack. Before Kubernetes was popular, Airbnb built SmartStack: **HAProxy** (a widely used open-source load balancer) on every host plus **ZooKeeper** as the registry. Each service registered via a local **agent** (a small helper program running on the same machine), and the local HAProxy updated its configuration to route accordingly — effectively giving every application a local load balancer for other services. They built it because manually tracking service pools had become untenable.

Consul (Stripe, PagerDuty). HashiCorp Consul provides DNS-based discovery plus an HTTP API. Its ability to work across multiple data centres makes it popular in enterprises where Kubernetes isn't the **orchestrator** (the system that decides where containers run and keeps them running), or where a platform-agnostic solution is needed.

Service meshes — Lyft's Envoy. Envoy was built at Lyft to solve discovery, routing, and observability. Instead of each application doing discovery, **Envoy sidecars** (Envoy is a high-performance proxy; a **sidecar** is a helper process deployed next to each service) **receive updates from a central control plane** (the management component that tells all the proxies how to route) about where every service is. When Service A calls Service B, it actually calls its local Envoy, which knows all instances of B and routes intelligently. **Discovery logic leaves application code entirely and moves into infrastructure.** *(See Sidecar.)*

Use cases

- **Microservices architectures** — managing inter-service connections becomes a nightmare at scale without it
- **Cloud-based systems** — services get allocated dynamically across servers and locations based on demand and cost; they re-register wherever they land

Design example 1 — e-commerce

Services: User, Inventory, Shopping Cart, Order. Without discovery, if Inventory moves to a new server, User and Shopping Cart must update their connections. With discovery, Inventory registers its new location and the others simply query the registry.

Design example 2 — streaming platform

Services for user profiles, video streaming, payments, recommendations. Streaming must scale hard at peak viewing times, adding and removing instances dynamically. Without discovery this causes broken connections to instances that no longer exist. With it, instances register and deregister as they come and go, and callers always get a valid one.

Part 10 — Common beginner misconceptions

"Service discovery replaces load balancing." No — they're complementary. Discovery tells you *what instances exist*; load balancing decides *which one to use*. Client-side discovery bundles both into the client; server-side puts both in the router.

"The registry is a single point of failure, so the pattern is bad." It is a **SPOF** (single point of failure — one component whose failure stops everything), which is why you run it as a cluster *and* cache on clients. A registry outage should degrade you (stale data), not stop you.

"You need to install Consul or Eureka." Not if you're on Kubernetes — you already have discovery via DNS. Adding another registry usually creates two competing sources of truth.

"Registering at startup is enough." Registration must be paired with health checking and prompt deregistration, or you accumulate dead entries.

"DNS alone solves this." DNS has caching and **TTL** (time-to-live: how long a cached answer may be reused before it must be refreshed) semantics that were designed for a world where addresses changed rarely. Clients (and language **runtimes** — the engine that runs a language's programs, such as the Java Virtual Machine) cache DNS aggressively, sometimes forever. That's why Kubernetes pairs DNS with a stable virtual IP rather than returning raw pod addresses.

Part 11 — Check your understanding

1. Why doesn't a monolith need service discovery?
2. What is the "indirection" at the heart of the pattern?
3. Give the decisive advantage of server-side discovery in a polyglot organisation.
4. Why does Eureka choose availability over consistency?
5. Why must a service register only *after* it's fully initialised?
6. What's the most important gap in the toy Java registry example?

(Answers: 1 — components call each other in-process, there's no network address to find; 2 — clients know logical names, not addresses, so addresses can change freely; 3 — it's language-agnostic, since any client that can make an HTTP request works, with no per-language discovery library; 4 — a stale instance list is survivable via retry, but a registry that won't answer stops everything; 5 — otherwise clients discover and call it while it's still warming up, causing intermittent errors after deploys; 6 — it maps one name to one address, so it can't return multiple instances and therefore can't load balance.)

Part 12 — Interview soundbite (30 seconds)

> "Service discovery solves the problem that in a dynamic environment services have no fixed addresses — containers and auto-scaling groups get new IPs constantly, so hardcoding endpoints couples every client to every service's deployment details. Instances register with a service registry at startup under a logical name and deregister on shutdown, with health checks or heartbeats removing dead ones. Clients then look up by name, so addresses can change freely. There are two flavours. Client-side, where the client queries the registry and load-balances itself — Netflix Eureka plus Ribbon — which avoids an extra hop and allows smart routing, but needs a discovery library in every language you use. And server-side, where the client just calls a fixed load balancer or gateway that does the lookup — simpler and language-agnostic, but adds a hop and makes the LB critical. Kubernetes does server-side for you via CoreDNS and an etcd-backed registry, which is why on Kubernetes you usually shouldn't add another layer. The main considerations are running the registry as an HA cluster, caching on clients so a registry outage degrades rather than kills you, and the CAP trade-off — Consul and Zookeeper are CP, Eureka is AP and serves stale data rather than going down, which is usually the right call here. And you should secure it, because anyone who can write to the registry can spoof a service and intercept traffic."

Part 13 — Implementation

A. Runnable demo

Full source: `demos/ServiceDiscoveryDemo.java`

```
cd demos && ./gradlew runCh05
```

The single most important line, and the fix for the toy example's fatal flaw:

```
// A LIST of instances per name - Map<String,String> could never load balance
private final Map<String, Map<String, Registration>> services = new ConcurrentHashMap<>();
```

Eviction by heartbeat TTL — this is what catches crashed instances that never got to deregister:

```
void evictExpired() {
    long now = System.currentTimeMillis();
    services.forEach((name, m) -> m.entrySet().removeIf(e ->
        now - e.getValue().lastHeartbeat > ttlMs));
}
```

And the caching that makes a registry outage survivable:

```
List<Instance> instancesOf(String serviceName) {
    try {
        List<Instance> fresh = registry.discover(serviceName);
        cache.put(serviceName, fresh);
        return fresh;
    } catch (IllegalStateException e) {
        return cache.getOrDefault(serviceName, List.of());   // last known good
    }
}
```

B. What you should see

```
=== 2. Client-side discovery + round robin ===
  call 1 -> 10.0.0.2:8080
  call 2 -> 10.0.0.3:8080
  call 3 -> 10.0.0.1:8080      <- cycles evenly

=== 4. An instance dies (stops heartbeating) ===
    [registry] EVICTED 10.0.0.3:8080 (no heartbeat)
  >> crashed instance removed WITHOUT graceful deregistration

=== 5. The stale-entry window ===
  a client discovering NOW still gets: [..., 10.0.0.4:8080]
  >> unavoidable. The fix is not prevention but RETRY ON ANOTHER INSTANCE

=== 6. Registry outage - cache keeps the system alive ===
    [client] registry DOWN - using cached list (3 instances)
  still routing to 10.0.0.2:8080
  >> running services survive; only NEW registrations are blocked

=== 7. Filtering by metadata (canary routing) ===
  all instances: [10.0.0.2, 10.0.0.1, 10.0.0.4, 10.0.0.5]
  v2.0 only:     [10.0.0.5:8080]
```

Sections 5 and 6 are the ones that teach something. Section 5 shows the stale-entry window is genuinely unavoidable — there is always a gap between an instance dying and the registry noticing, so the answer isn't better detection, it's **retry against another instance**. Section 6 shows why client-side caching matters: the registry is down, and traffic still flows.

C. Production — you probably already have this

Kubernetes (do this by default). Discovery is built in; you don't install anything:

```yaml
apiVersion: v1
kind: Service
metadata:
  name: order-service
spec:
  selector:
    app: order-service          # matches pods by label
  ports:
    - port: 80
      targetPort: 8080
```

Any pod can now call `http://order-service` and CoreDNS resolves it, with kube-proxy load balancing across healthy pods. **Readiness probes are the health check** — this is the piece people skip. (A **probe** is a periodic check Kubernetes runs against a container; `/actuator/health` is the health URL provided by Spring Boot Actuator, Spring's built-in monitoring module.)

```yaml
readinessProbe:                 # "am I ready to receive traffic?"
  httpGet: { path: /actuator/health/readiness, port: 8080 }
  initialDelaySeconds: 10
  periodSeconds: 5
livenessProbe:                  # "am I alive, or should I be restarted?"
  httpGet: { path: /actuator/health/liveness, port: 8080 }
```

> **Readiness is what enforces the Part 7.8 rule**: a pod that isn't ready is removed from the Service endpoints, so no traffic reaches it while it's still warming up.

Spring Cloud + Eureka (client-side, when you're not on Kubernetes). A **lease** here is a registration that expires unless renewed by heartbeats; `RestTemplate` is Spring's classic HTTP client, and `@Bean` tells Spring to create and manage that object:

```yaml
eureka:
  client:
    serviceUrl.defaultZone: http://eureka-1:8761/eureka,http://eureka-2:8761/eureka  # failover
    registryFetchIntervalSeconds: 30      # cache refresh
  instance:
    leaseRenewalIntervalInSeconds: 10     # heartbeat frequency
    leaseExpirationDurationInSeconds: 30  # TTL before eviction
```

```java
@LoadBalanced                           // makes RestTemplate resolve service names
@Bean RestTemplate restTemplate() { return new RestTemplate(); }

// Call by LOGICAL NAME, not address
restTemplate.getForObject("http://order-service/orders/{id}", Order.class, id);
```

Graceful shutdown — deregister *before* going offline, so the registry never hands out a dying instance:

```yaml
server.shutdown: graceful
spring.lifecycle.timeout-per-shutdown-phase: 30s
eureka.client.shouldUnregisterOnShutdown: true
```

D. Implementation pitfalls

1. Storing one address per service name. The flaw in the chapter's toy example. If your registry maps name → single address, you have a naming service, not a discovery service — no load balancing, no failover.

2. Registering before you're ready. Register only after caches are warm and connection pools are open. Otherwise clients discover you mid-startup and get errors that look random and appear only after deploys. Use a **readiness probe**, not a liveness probe, to gate traffic.

3. No client-side caching. Without it your registry becomes a hard dependency for every request — a single point of failure that stops everything. With it, an outage is an inconvenience.

4. Heartbeat TTL too long. A 90-second TTL means up to 90 seconds of traffic routed to a dead instance. Too short and you evict healthy instances during a **GC pause** (the moment Java's garbage collector briefly halts the program to reclaim unused memory) or network blip. 10s heartbeat / 30s expiry is a reasonable starting point.

5. Not deregistering on shutdown. Without graceful shutdown, every deploy leaves a window where clients get **connection-refused** errors (the target machine is reachable but nothing is listening on that port) from instances that have already stopped.

6. Adding a registry when you're on Kubernetes. Running Eureka inside Kubernetes gives you two competing sources of truth that disagree during rollouts. Use the platform's discovery.

7. Treating discovery as a substitute for retry. Discovery tells you what instances *were* alive. It cannot guarantee they still are. Always pair with retry-on-another-instance *(see Retry)*.

8. Leaving the registry unauthenticated. Anyone who can write to it can register a malicious instance under a legitimate service name and intercept traffic. Enable ACLs or mTLS.

Related patterns

- **API Gateway** — typically the server-side discovery router
- **Circuit Breaker** — per-instance breakers over a discovered pool
- **Retry** — retry against a *different* discovered instance
- **Sidecar** — service mesh sidecars (Envoy) absorb discovery entirely
- **Config Externalization** — services need discovery to find the config server too

Circuit Breaker Pattern

Category: Resilience **One-liner:** Wrap calls to a **remote dependency** (another service, database or API your code calls over the network) in a component that stops calling it once it's clearly failing — failing instantly instead of hanging, and probing periodically to see whether it recovered.

Origin: Popularised by **Michael Nygard** in his book *Release It!*

Part 0 — Concepts you need first

What is a thread, and why do we care?

A **thread** is one line of execution inside a program. A typical **web server** (the program that accepts HTTP requests and sends back responses) keeps a **thread pool** — a fixed set of threads, say 200 — and assigns one to each incoming request. When the request finishes, the thread returns to the pool for reuse.

The critical property: a thread waiting on a network call is doing nothing else. It's blocked, occupying a slot, until it gets a response or gives up.

This single fact explains why the Circuit Breaker exists. If you have 200 threads and all 200 are blocked waiting on a slow service, your server can accept no requests at all — for *anything*. It looks completely dead, even though its own code is perfect.

What is a timeout?

The maximum time you'll wait for a response before giving up. If you call a service with a 30-second timeout and it never responds, your thread is stuck for the full 30 seconds.

Timeouts are necessary but not sufficient. They stop you waiting *forever*, but if a service is down and you keep calling it, every request still burns its full timeout before failing. A hundred requests a second against a dead service with a 30-second timeout means three thousand threads tied up. Timeouts bound each individual wait; the circuit breaker prevents the wait from happening at all.

What is a "cascading failure"?

When the failure of one component causes the failure of others that depend on it, spreading through the system like falling dominoes. The key insight is that **the components that fail second were never broken** — they were killed by waiting on something that was.

What is a fallback?

A substitute response used when the real one is unavailable — cached data from earlier, a sensible default, or a degraded version of the feature. It's how you turn a hard failure into a mild one.

What does "fail fast" mean?

Returning an error *immediately* rather than after a long wait. Counter-intuitively this is often better for users: two seconds of waiting followed by an error is worse than an instant, clear "this feature is unavailable right now."

Part 1 — The metaphor

An **electrical circuit breaker** in your home monitors current. When there's a dangerous overload it **trips**, cutting the circuit to prevent fire or damage to appliances. Later you flip it back on. If the fault is still there, it trips again immediately.

Two features carry over precisely:

1. **It cuts the connection to prevent wider damage** — better to lose one circuit than the house.
2. **Restoration is a deliberate test**, not automatic — you flip it back and see what happens.

A software circuit breaker trips to stop calls to a failing service, letting the system **fail fast and degrade gracefully** rather than grinding to a halt.

Part 2 — The problem

Distributed applications (ones spread across many machines that talk over a network) constantly call remote things — other **microservices** (small, independently deployed services), databases, external **APIs** (interfaces other systems offer for programs to call). Every such call risks failure or a slow response. And if a service becomes unresponsive while the application keeps calling it, the results are disastrous: **requests pile up, threads hang, and the failure cascades into a wider outage.** (An **outage** is a period when a system, or part of it, is unavailable.)

Cascading failures, step by step

Service A depends on Service B. B goes down, or — worse — becomes very slow.

1. Calls from A to B **hang until they time out**
2. During each wait, A's resources — threads, memory — are **tied up doing nothing**
3. This happens frequently, and across many threads simultaneously
4. A becomes overwhelmed — it **runs out of threads or memory**
5. **A now fails**

> Read step 5 carefully: **A is broken even though nothing is wrong with A's own code.** Its own logic is fine, its own database is fine. It died of waiting. That's the cascading failure, and preventing it is the entire purpose of this pattern.

And it doesn't stop at A. Whatever calls A now waits on A, and the same thing happens to them. One slow service at the bottom can take down everything above it.

> **Slow is worse than down.** If B refuses connections instantly, A gets an immediate error and moves on. If B accepts connections and then takes 30 seconds, A's threads are held hostage. Counter-intuitive, but a service that's merely slow does far more damage than one that's cleanly dead.

Unresponsive services and wasted work

Waiting on slow services with long timeouts means users experience delays and threads stay blocked.

Blindly retrying a known-failing operation wastes **CPU cycles** (processor time) and **overloads the failing service even more**. The course's example: if dozens of components keep retrying against a database that's already struggling, it just makes things worse.

> This is the vicious circle: the service is slow because it's overloaded → clients time out and retry → the retries add *more* load → it gets slower → more timeouts and retries. Without intervention a service can be prevented from ever recovering, purely by the traffic of clients trying to reach it.

When a fault is unlikely to resolve quickly — a network outage, a crashed service — **continuously attempting the operation is pointless**. It doesn't solve the problem, and it prevents the application from handling the failure gracefully.

What's needed: a way to detect failure quickly and stop sending traffic to the failing component *before* it drags down the entire system.

Part 3 — The solution

Wrap calls to an external service in a **Circuit Breaker** component that monitors the outcomes of those calls, and stops making them once failures cross a threshold.

Two things happen when it trips, and the second is easy to overlook:


1. Your application stops waiting. Calls are rejected immediately, so you preserve your own responsiveness and resources. Threads stay free for work that can actually succeed.

2. The failing service stops receiving load. An open circuit gives the struggling service **a chance to actually recover** — breaking the vicious circle above.

The pattern prefers **fast failure and graceful degradation** over long waits and resource exhaustion.

Part 4 — The three states

This is the core of the pattern, and what interviewers ask about.



> *Naming warning — this trips people up constantly:* **CLOSED means traffic flows** and **OPEN means traffic is blocked.** It feels backwards until you remember it's an electrical circuit: a closed circuit is a complete loop that current flows through; an open circuit is broken, so nothing flows.

CLOSED — normal operation

The circuit is closed, so traffic flows to the service as usual. The breaker **monitors the number of recent failures**. If failures exceed a configured **failure threshold** within a certain time window, it transitions to Open.

While closed, **successful calls generally reset the failure counter**, so an occasional **transient** error (a short-lived glitch that goes away by itself) won't trip the breaker immediately. This matters: you want to distinguish "one blip" from "this service is genuinely broken."

OPEN — tripped

The breaker has detected too many failures and opened the circuit. Calls are **blocked immediately** — the application gets an error or fallback response **without any attempt at the real operation**.

Open state lasts for a configured **timeout period** (the open interval). The purpose is twofold: avoid useless load, and give the troubled service time to recover.

HALF-OPEN — trial mode

After the open timeout expires, the breaker allows **a limited number of test requests** through to the real service. The course describes it as cautiously probing: *"Are you OK now?"*

- **A test request succeeds** → the service is likely back; the breaker resets to **Closed** (usually resetting failure counters)

- **A test request fails** → the breaker flips **immediately back to Open**, and the timeout period starts over

Only a few requests are let through in half-open — this is deliberate, **to avoid blasting a recovering service with traffic**. Often one success is enough to close the circuit; some implementations require several consecutive successes to be sure.

> Half-open is the cleverest part of the design. Without it you'd need either a human to reset the breaker, or a blind reopening of full traffic that would instantly re-kill a service that's only just getting back on its feet.

The per-call logic

Every call through the breaker performs a quick state check:

- **Closed** → attempt the call and record the outcome
- **Open** → skip the call and immediately return a failure or fallback
- **Half-Open** → allow the call (perhaps limiting **concurrency** — how many calls may be in progress at once), then adjust state based on the result

The breaker acts as a **safety valve**: it ensures a failing component doesn't drag down the rest.

Part 5 — Integration: it's additive, not invasive

Adding a circuit breaker **does not require a system overhaul**. It's a protective layer wrapped around existing service calls, leaving the underlying service logic untouched.

Every request is made *through* the breaker, and the breaker decides whether to forward it based on current state and recent outcomes.

Practical rollout advice from the course: introduce it gradually. Start with **critical services whose failure would significantly impact the system**, then expand to protect other services as the benefits become evident.

Part 6 — Configuration

Parameter	What it controls
Failure Threshold	The limit of failed requests before the breaker switches from Closed to Open
Timeout Period	How long the breaker stays Open before moving to Half-Open — the recovery time given to the service
Number of Requests in Half-Open	How many requests are allowed through while testing whether the service recovered

These values must **strike a balance** between protecting the service, allowing it time to recover, and keeping it as available as possible for handling requests.

The right settings depend on:

- The nature of the service and the system
- The expected load on the service
- How critical the service is to overall functionality

These parameters shouldn't be static

The course makes a point worth remembering: they **can and should be adjusted dynamically** in response to system state and performance. In times of high demand you might:

- **Increase the failure threshold** — let the service endure more failed requests before tripping

- **Reduce the timeout period** — attempt recovery sooner, so the service can handle more requests during peak times

---

Part 7 — Worked example (Java)

A basic implementation with no external libraries, to illustrate the core algorithm.

```java
public class CircuitBreaker {
    private enum State { CLOSED, OPEN, HALF_OPEN }

    private State state = State.CLOSED;
    private int failureCount = 0;
    private final int failureThreshold;
    private final long openTimeout;      // how long to stay open before half-open
    private long lastFailureTime = 0;

    public CircuitBreaker(int failureThreshold, long openTimeout) {
        this.failureThreshold = failureThreshold;
        this.openTimeout = openTimeout;
    }

    public synchronized <T> T call(Callable<T> remoteCall) throws Exception {

        // 1. If OPEN, has the timeout passed?
        if (state == State.OPEN) {
            long timeSinceFailure = System.currentTimeMillis() - lastFailureTime;
            if (timeSinceFailure < openTimeout) {
                // Still within the open window — fail fast, don't call the service
                throw new IllegalStateException(
                    "Circuit is OPEN. Failing fast without calling remote service.");
            } else {
                // Timeout has passed — allow one trial call
                state = State.HALF_OPEN;
            }
        }

        // 2. Attempt the call (allowed when CLOSED or HALF_OPEN)
        try {
            T result = remoteCall.call();
            // Success: reset the counter and close the circuit
            failureCount = 0;
            state = State.CLOSED;
            return result;
        } catch (Exception e) {
            // Failure: count it and record when it happened
            failureCount++;
            lastFailureTime = System.currentTimeMillis();
            if (failureCount >= failureThreshold) {
                state = State.OPEN;   // trip
            }
            throw e;   // propagate (or return a fallback here)
        }
    }
}
```

Walking through the mechanics

The state check comes first. Before doing anything else the breaker asks whether it's Open. If so, and the timeout hasn't elapsed, it throws immediately — **the remote service is never contacted**. That's the whole point: no network call, no thread blocked, microseconds instead of seconds.

`Callable<T>` **makes it generic.** `Callable` is a Java **interface** (a type that declares methods without implementing them) for "some operation that returns a value and may throw." Accepting one means this breaker can wrap *any* operation — an **HTTP** call (a web request), a database **query** (a request to read or change data), anything — rather than being tied to one specific service.

`synchronized` **handles concurrency.** Many threads may call this simultaneously. Without **synchronization** (making threads take turns on shared data) two threads could both read `failureCount` as 2, both increment it, and you'd lose a count. *(This is also the example's main performance weakness — see below.)*

Success resets everything. Note that success sets `state = CLOSED` unconditionally. From Half-Open, that's the recovery path. From Closed, it stays closed and clears accumulated failures.

Failure records the time. `lastFailureTime` is what the Open-state check measures against to know when the timeout has elapsed.

Using it

```
CircuitBreaker cb = new CircuitBreaker(3, 10000);  // trip after 3 failures, stay open 10s

try {
    String data = cb.call(() -> unreliableService.getData());
    // use data...
} catch (Exception e) {
    useCachedData();   // fallback
}
```

What happens in sequence:

1. `getData()` fails three times in a row → the circuit opens
2. Any attempt within the next 10 seconds throws **immediately**, without calling `getData()` at all
3. After 10 seconds the next call is allowed through (Half-Open)
4. If it succeeds → circuit closes, normal operation resumes
5. If it fails → circuit re-opens and blocks for another 10 seconds

What this example simplifies

The course notes production breakers are more sophisticated. Specifically:

- **A naive counter, not a rolling window.** Here, three failures trip the breaker *whenever* they happen — even three failures spread across an hour of otherwise perfect traffic. Real implementations use a **rolling time window** ("more than 50% of calls in the last 10 seconds failed"), which is far more meaningful.
- `synchronized` **serialises every call.** Every request through this breaker acquires the same **lock** (a guard that only one thread can hold at a time), so it becomes a **bottleneck** (the one narrow point that limits everything) under **load** (the volume of work arriving). Production libraries use **atomic operations and non-blocking synchronization** instead (**atomic** operations complete as one indivisible step, so no lock is needed).
- **All exceptions count as failures.** (An **exception** is Java's way of signalling an error by "throwing" it to the caller.) A **validation error** (a rejection because the input was invalid) from the remote service would trip the breaker even though the service is perfectly healthy. Real breakers distinguish which exceptions indicate the *service* is unwell.
- **No fallback built in.** The breaker throws and the caller handles it. Most frameworks let you register a fallback function directly.

Part 8 — Performance implications

The breaker adds a small overhead per call — checking state and updating counters. **This overhead is negligible** compared to the alternative.

The comparison that matters: without a breaker, a failing call ties up a thread for **several seconds** until timeout. With one, the failure is handled in **milliseconds**.

> A tiny check is a small price to pay for avoiding a meltdown.

For extremely performance-sensitive scenarios there are options like **asynchronous** calls (made in the background without blocking the caller's thread) or optimised breaker logic, but generally the benefits far outweigh the overhead.

Tuning the failure threshold

- **Too low** → the circuit trips on every minor glitch, causing unnecessary interruptions and **flapping** (rapid on/off cycling)
- **Too high** → the breaker waits too long to trip, failing to protect the system until a lot of errors have already occurred

The course's calibration: tripping after **1** failure is too sensitive; tripping after **100** is too late. Pick a threshold that **distinguishes normal transient failures from a real problem**.

Tuning the open timeout

- **Too short** → the breaker goes Half-Open and tests the service **before it has recovered**, causing another immediate failure and creating noisy open → half-open → open **flapping**
- **Too long** → your application refuses calls longer than necessary, degrading user experience even after the dependency is healthy again

The timeout should roughly correspond to **how long you expect the service might need to recover**.

Finding the right values

This requires monitoring and tweaking. Good practice: monitor **how often the breaker opens, how long it stays open, and whether it's tripping too frequently. Metrics** (numeric measurements collected over time) like failure counts, open events, and half-open trial outcomes should feed **dashboards** (live screens of graphs). With that data you adjust.

In a high-traffic system, consider a **percentage-based threshold** rather than an absolute count, so occasional spikes don't trip it.

Part 9 — Best practices and trade-offs

Fallbacks. When a breaker opens, have a fallback strategy rather than just returning an error — cached data, a default value, or redirecting to a simpler alternative. This is what makes the system **degrade gracefully instead of failing completely**. Many frameworks let you specify a fallback function to execute when open.

Combine with retries and timeouts. The Circuit Breaker doesn't replace other **resilience** patterns (techniques for staying up when parts fail) — it works alongside them. You still implement **timeouts** for calls, and may **retry** a few times on certain failures before counting one as a failure. They work in tandem: retry a couple of times in case it's a transient network glitch, but let the breaker stop you trying after repeated failures that indicate a real outage. **Bulkheads** and **rate limiting** (capping requests per caller per second) complement both.

Monitoring and alerts. A tripped breaker usually means something is wrong with a **downstream** service (one that your service calls), so **set up alerts**. Have the breaker log or emit an event whenever it opens or closes; your monitoring can catch these and alert **on-call** engineers (the people currently responsible for responding to incidents) or trigger automated recovery.

> Without this, the pattern has a hidden danger: the system quietly protects itself, users see a degraded feature, and **nobody realises anything is broken** because there's no flood of errors. The breaker suppresses exactly the signal that would normally raise the alarm.

Thread-safety and concurrency. In multi-threaded server applications, internal counters and state transitions **must be thread-safe** — you don't want two threads concurrently deciding they're both "first" to open the circuit. Use atomic counters, synchronized sections, or a library. High-performance libraries use non-blocking synchronization and atomic operations to minimise overhead.

Avoiding misuse. Apply breakers to calls that are **potentially unreliable or high-latency** (**latency** = time a request takes; see System Design Fundamentals), like network calls. There's **no benefit** on in-memory operations that are very unlikely to fail. Be cautious in systems where failures are very localised or quickly self-correcting — **an aggressive breaker constantly tripping on ephemeral (very short-lived) errors does more harm than good.** The pattern must be tuned to your system's reliability needs.

Part 10 — Use cases

Microservices architecture

An e-commerce application split into user management, product catalog, shopping cart, and order processing. Order processing relies on the product catalog to validate availability and user management to validate credentials.

If the **product catalog starts failing**, without safeguards those failures propagate into order processing, degrading the user experience or causing a total outage. With a breaker in front of the catalog, order processing detects failures quickly, stops sending requests, and falls back to a **cached product list** — or fails gracefully with a relevant message.

External API integration

External APIs are **outside your control** and can be unpredictable: downtime, latency spikes, rate limiting policies.

A weather forecasting application pulling from several external weather APIs puts a breaker on **each one**. If one starts failing or becomes slow, the breaker isolates that specific API so its problems don't affect overall performance. The application can then **switch to another API** or provide degraded service until the faulty one recovers.

Database access

Database issues — network problems, resource contention, server failures — cause slow responses or errors.

- **Reads:** in a read-heavy system, a breaker monitors database health. On detecting an increasing error rate or latency, it trips and **redirects reads to a read replica or a cache** (a **read replica** is a copy of the database kept in sync and used only for reads; a **cache** is a fast store of recently used data), keeping the service available
- **Writes:** the same can apply, but **with more caution**. On increased errors the breaker could trip and temporarily **buffer write operations** (hold them in a temporary queue to apply later) — but this must be handled carefully, as **data consistency is at risk** (different copies of the data may disagree) and the buffer itself could become a bottleneck

---

Part 11 — Real-world examples

Netflix and Hystrix. Netflix famously implemented this pattern through their **open-source** (publicly available, free-to-use code) library **Hystrix**. In their microservices web, if a **backend** service (a server-side service) becomes slow or fails, Hystrix isolates that failing endpoint, stopping the failure cascading and returning fallback responses so the user experience is only minimally affected.

> The canonical illustration: **if the recommendations service is down, Netflix can still stream video.** The app omits the recommendations row or shows a default message, rather than failing entirely. That's the whole pattern in one sentence — a non-essential dependency failing must not take down the essential function.

E-commerce product pages. A large site with services for product info, inventory, pricing, and reviews. If the **reviews service** starts failing, a breaker on those calls trips so the product page **skips reviews** rather than slowing the entire page. Product details and pricing load normally, and the page shows something like "Reviews are unavailable at the moment" — **graceful degradation**. Without the breaker, the page might hang or crash trying endlessly to fetch reviews. Similar strategies apply to payment gateways and shipping calculators: if the dependency is down, fall back quickly ("Sorry, we can't process payments right now") instead of making users wait and wonder.

Cloud and service meshes. Many cloud architectures incorporate breakers to improve stability when calling remote services, and **service mesh** technologies (a layer of proxies beside every service that handles service-to-service traffic) provide breaker mechanisms **at the infrastructure level**, automatically preventing one overloaded microservice from overloading others. In an **API Gateway** (the single entry point that routes outside requests to services) you might configure breaker rules per backend route, so an erroring backend gets rejected for a short period — protecting the backend and freeing the gateway for other routes.

Enterprise integration. Even outside microservices, any integration with an external system — a **SOAP** or **REST** API (two styles of web API: SOAP sends XML messages with a strict contract; REST uses plain HTTP methods on URLs), a database, a messaging system — benefits. A **middleware** system (software that sits between other systems to connect them) calling a slow **legacy** (old but still essential) SOAP service uses a breaker to **avoid tying up all its worker threads** on that one slow dependency. The pattern also appears in **reactive programming** (code built around streams of events handled as they arrive) and **stream processing** (handling continuous flows of data record by record) for **backpressure** (a slow receiver signalling the sender to slow down): if a downstream consumer is too slow or failing, the **upstream** producer (the one sending the data) trips a breaker and stops feeding it until it recovers.

Libraries: Hystrix (Java, now in maintenance mode), **Resilience4j** (Java), **Polly** (.NET — Microsoft's application platform), plus built-in support in cloud platforms and service meshes.

Part 12 — System design example: distributed social media platform

Services: **User Management**, **Post Management**, **Feed Generation**, and more — each running on multiple **nodes** (machines or instances) for **high availability** (staying up nearly all the time) and **load balancing** (spreading requests across instances).

Breakers apply in several places:

In front of User Management. Services relying on it — Post Management, Feed Generation — quickly detect when it's struggling. They then **reduce the load on it** by providing degraded service: displaying **cached user information** or **simplified post feeds**.

Between Post Management and its database. If the database experiences problems, the breaker trips and Post Management starts **serving cached posts**, or **temporarily stops accepting new posts**.

In front of the external email service used for notifications. If it starts failing, the breaker prevents the notification feature from impacting the rest of the system.

Distributed breaker state

An interesting design consideration: use a **shared circuit breaker per service, stored in a distributed cache** (a cache spread across several servers that all nodes can read and write, e.g. Redis). This maintains consistency across all nodes — if a breaker trips on one node, it trips on all of them.

This must be **balanced against the additional complexity and potential performance impact** of consulting a distributed cache on every call.

> The trade-off in plain terms: with per-node breakers, each node must independently discover the service is broken, so each burns its own set of failures learning the same lesson. With shared state, one node's discovery protects everyone — but now every call depends on a cache lookup, and the cache becomes something else that can fail.

Monitoring

Complement the breakers with **comprehensive monitoring and alerting** — monitor the state of all breakers and alert developers or administrators when one trips, ensuring quick detection and remediation.

> **The goal is not to eliminate failures** — they're inevitable in any system. The objective is to **manage failures effectively**, preventing them from cascading into system-wide outages.

Part 13 — Common beginner misconceptions

"Open means working." The most common mix-up. Open = blocked, Closed = flowing. Think electrical circuits.

"The circuit breaker retries for you." No. It *stops* calls. Retry is a separate pattern; they're used together but do opposite things — retry tries harder, the breaker gives up sooner.

"It fixes the broken service." It doesn't. It protects the *caller* and gives the failing service breathing room. Someone still has to fix the actual problem — which is why alerting matters.

"One breaker per application." No — one breaker **per dependency**. If your service calls three others, you need three independent breakers. A shared one would mean a failure in the reviews service blocks your calls to payments.

"If I have timeouts I don't need this." Timeouts bound each individual wait; the breaker prevents the waiting from happening at all once the service is known bad. You need both.

"It makes my system slower." The state check is microseconds. Compared to a 30-second timeout on every call to a dead service, it makes failure handling thousands of times faster.

Part 14 — Check your understanding

1. Why does CLOSED mean traffic flows?
2. Why is a slow service more dangerous than a completely dead one?
3. What two separate benefits does an open circuit provide?
4. Why does Half-Open allow only a *few* requests through?
5. What's the hidden risk of a circuit breaker working well?
6. Why does the example's `synchronized` become a problem at scale?

(Answers: 1 — it's an electrical metaphor; a closed circuit is a complete loop that current flows through; 2 — a dead service refuses instantly so callers move on, while a slow one holds caller threads hostage until timeout; 3 — the caller stops wasting resources waiting, and the failing service stops receiving load so it can recover; 4 — to avoid overwhelming a service that has only just started recovering; 5 — it suppresses the errors that would normally alert you, so problems go unnoticed without explicit alerting on breaker state; 6 — every call acquires the same lock, so the breaker itself becomes a bottleneck under high concurrency.)

Part 15 — Interview soundbite (30 seconds)

> "A circuit breaker stops you repeatedly calling a dependency that's already failing. The problem is cascading failure: if Service B hangs, Service A's threads block waiting on it, and A runs out of threads and dies even though A's own code is fine. Slow is actually worse than down, because a dead service refuses instantly while a slow one holds your threads hostage. The breaker wraps the call and has three states — Closed, where traffic flows and failures are counted; Open, once failures cross a threshold, where calls are rejected instantly with a fallback; and Half-Open, after a timeout, where a few trial requests probe whether it recovered. Success closes it, failure

> re-opens it, and it's only a few requests so you don't re-kill a service that's just getting back up. It does two things at once: your service stops wasting resources waiting, and the failing service stops receiving load so it can actually recover — that second part breaks the vicious circle where retry traffic prevents recovery. Netflix's Hystrix is the classic example: if recommendations is down they still stream video and just drop that row. Tuning matters — too sensitive and it flaps, too lenient and it doesn't protect you, so you generally want a percentage-based threshold over a rolling window rather than a raw count. And you must alert on breaker state, because a breaker working well hides the errors that would otherwise tell you something's broken."

Key takeaways: prevent cascading failures · fail fast and recover · tune and monitor · use in combination with other patterns.

Part 16 — Implementation

A. Runnable demo — watch the state machine work

(A **state machine** is something that is always in exactly one of a fixed set of states and moves between them on defined events — exactly what the breaker is. In the code, `AtomicInteger` is a thread-safe counter and `volatile` makes a field's latest value visible to all threads. `./gradlew` runs **Gradle**, the Java build tool used for the demos.)

Full source: **`demos/chapters/06-circuit-breaker/CircuitBreakerDemo.java`**

```
cd demos && ./gradlew runCh06
```

```java
import java.util.concurrent.Callable;
import java.util.concurrent.atomic.AtomicInteger;

public class CircuitBreakerDemo {

    // ---------- The circuit breaker ----------
    static class CircuitBreaker {
        enum State { CLOSED, OPEN, HALF_OPEN }

        private State state = State.CLOSED;
        private int failureCount = 0;
        private final int failureThreshold;
        private final long openTimeoutMs;
        private long lastFailureTime = 0;
        private final String name;

        CircuitBreaker(String name, int failureThreshold, long openTimeoutMs) {
            this.name = name;
            this.failureThreshold = failureThreshold;
            this.openTimeoutMs = openTimeoutMs;
        }

        synchronized <T> T call(Callable<T> action, Callable<T> fallback) throws Exception {
            if (state == State.OPEN) {
                if (System.currentTimeMillis() - lastFailureTime < openTimeoutMs) {
                    log("REJECTED (circuit OPEN) -> fallback");
                    return fallback.call();          // fail fast, no remote call
                }
                transitionTo(State.HALF_OPEN);       // timeout elapsed: allow a probe
            }

            try {
                T result = action.call();
                if (state == State.HALF_OPEN) {
                    log("probe SUCCEEDED");
                }
                failureCount = 0;
                transitionTo(State.CLOSED);
                return result;
            } catch (Exception e) {
                failureCount++;
                lastFailureTime = System.currentTimeMillis();
                log("call failed (" + failureCount + "/" + failureThreshold + "): " + e.getMessage());
                if (state == State.HALF_OPEN || failureCount >= failureThreshold) {
                    transitionTo(State.OPEN);
                }
                return fallback.call();
            }
        }

        private void transitionTo(State next) {
            if (state != next) {
                log("state " + state + " -> " + next);
                state = next;
            }
        }

        private void log(String msg) {
            System.out.printf("    [%s] %s%n", name, msg);
        }
    }

    // ---------- A service that fails for a while, then recovers ----------
    static class FlakyService {
        private final AtomicInteger calls = new AtomicInteger();
        private volatile boolean healthy = true;

        String getData() {
            calls.incrementAndGet();
            if (!healthy) {
```

```
                throw new RuntimeException("service unavailable");
            }
            return "real-data";
        }

        void breakIt()  { healthy = false; }
        void healIt()   { healthy = true; }
        int callCount() { return calls.get(); }
    }

    public static void main(String[] args) throws Exception {
        FlakyService service = new FlakyService();
        CircuitBreaker cb = new CircuitBreaker("payments", 3, 2000); // 3 failures, 2s open

        System.out.println("\n--- Phase 1: service healthy ---");
        for (int i = 0; i < 3; i++) {
            System.out.println("  result = " + cb.call(service::getData, () -> "CACHED"));
        }

        System.out.println("\n--- Phase 2: service breaks ---");
        service.breakIt();
        for (int i = 0; i < 6; i++) {
            System.out.println("  result = " + cb.call(service::getData, () -> "CACHED"));
        }
        System.out.println("  >> service was actually called "
                + service.callCount() + " times so far");

        System.out.println("\n--- Phase 3: still broken, circuit stays open ---");
        int before = service.callCount();
        for (int i = 0; i < 3; i++) {
            cb.call(service::getData, () -> "CACHED");
        }
        System.out.println("  >> extra real calls during OPEN: "
                + (service.callCount() - before) + "  (should be 0)");

        System.out.println("\n--- Phase 4: wait for timeout, service recovers ---");
        Thread.sleep(2100);
        service.healIt();
        System.out.println("  result = " + cb.call(service::getData, () -> "CACHED"));
        System.out.println("  result = " + cb.call(service::getData, () -> "CACHED"));
    }
}
```

B. What you should see

```
--- Phase 1: service healthy ---
  result = real-data          (x3, circuit stays CLOSED)

--- Phase 2: service breaks ---
    [payments] call failed (1/3): service unavailable
    [payments] call failed (2/3): service unavailable
    [payments] call failed (3/3): service unavailable
    [payments] state CLOSED -> OPEN
    [payments] REJECTED (circuit OPEN) -> fallback
  >> service was actually called 6 times so far

--- Phase 3: still broken, circuit stays open ---
  >> extra real calls during OPEN: 0

--- Phase 4: wait for timeout, service recovers ---
    [payments] state OPEN -> HALF_OPEN
    [payments] probe SUCCEEDED
    [payments] state HALF_OPEN -> CLOSED
  result = real-data
```

The line that proves the pattern works is `extra real calls during OPEN: 0`. Three requests came in; the failing service received none of them. That's both benefits at once — the caller didn't wait, and the sick service got left alone.

C. Production — Resilience4j

Nobody hand-writes breakers in production. **Resilience4j** is the current standard for Java (Hystrix is in maintenance mode).

Dependency (Maven): (Maven is a Java build tool; this snippet adds the library to the project. **Spring Boot** is a framework for building Java services quickly, and **AOP** — aspect-oriented programming — is what lets an annotation like `@CircuitBreaker` wrap a method with extra behaviour.)

```
<dependency>
  <groupId>io.github.resilience4j</groupId>
  <artifactId>resilience4j-spring-boot3</artifactId>
  <version>2.2.0</version>
</dependency>
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-aop</artifactId>
</dependency>
```

Configuration (`application.yml`) — this is where the real learning is (YAML is an indentation-based config format; the `400` in the last comment is the **HTTP status code** for "bad request"):

```
resilience4j:
  circuitbreaker:
    instances:
      paymentService:
        # Use a percentage over a rolling window, not a raw count
        slidingWindowType: COUNT_BASED
        slidingWindowSize: 20              # consider the last 20 calls
        minimumNumberOfCalls: 10           # don't judge until we have 10 samples
        failureRateThreshold: 50           # open if >50% of them failed
        waitDurationInOpenState: 10s       # how long to stay OPEN
        permittedNumberOfCallsInHalfOpenState: 3
        automaticTransitionFromOpenToHalfOpenEnabled: true
        # Treat slow calls as failures too - crucial, see pitfall 3
        slowCallRateThreshold: 50
        slowCallDurationThreshold: 2s
        recordExceptions:
          - java.io.IOException
          - java.util.concurrent.TimeoutException
        ignoreExceptions:
          - com.example.ValidationException   # never trip on a 400
```

Usage:

```
@Service
public class PaymentClient {

    @CircuitBreaker(name = "paymentService", fallbackMethod = "paymentFallback")
    public PaymentResult charge(Order order) {
        return restClient.post()
                .uri("/payments")
                .body(order)
                .retrieve()
                .body(PaymentResult.class);
    }

    // Signature must match, plus a trailing Throwable
    private PaymentResult paymentFallback(Order order, Throwable t) {
        log.warn("Payment circuit open for order {}: {}", order.getId(), t.toString());
        return PaymentResult.deferred(order.getId());   // queue for later
    }
}
```

Monitoring — expose breaker state so you can alert on it:

```
management:
  endpoints.web.exposure.include: health,circuitbreakers,prometheus
  health.circuitbreakers.enabled: true
```

Then alert on the **Prometheus** metric `resilience4j_circuitbreaker_state` (Prometheus is a popular open-source system that collects metrics and fires alerts).

D. Implementation pitfalls

1. Using a raw failure count instead of a rate over a window. Three failures scattered across an hour of healthy traffic shouldn't trip anything. Always use `slidingWindowSize` + `failureRateThreshold`, and set `minimumNumberOfCalls` so a single early failure at 100% rate doesn't open the circuit.

2. Counting business errors as failures. A 400 or a validation exception means the *request* was bad, not the *service*. Put those in `ignoreExceptions` or you'll trip the breaker on a client bug and take down a healthy dependency.

3. Forgetting `slowCallDurationThreshold`. A service returning `200 OK` (the HTTP status code for success) after 30 seconds never "fails," so a failure-only breaker never opens — while your threads are consumed exactly as badly as if it were down. Slow-call detection is what catches the most dangerous case.

4. No timeout on the underlying call. The breaker can only react to a call that *returns*. Always set connect and read timeouts on your HTTP client; otherwise a hung **socket** (the operating-system endpoint of a network connection) blocks forever and the breaker never sees a failure to count.

5. One breaker shared across dependencies. Name breakers per downstream service. A shared instance means the reviews service failing blocks your payment calls.

6. Fallbacks that call other services. Your fallback runs when things are already broken. It must be local and fast — cache, default, or queue. A fallback making a network call is a second failure waiting to happen.

7. Not alerting on state. Covered above but it's the one people skip: a breaker doing its job hides errors. Alert on the open transition or you'll find out from a customer.

Related patterns

- **Bulkhead** — isolates resource pools; the breaker limits *how long* you try, the bulkhead limits *how much* damage one failure can do
- **Retry** — handles transient faults; the breaker stops retries becoming an attack on a downed service
- **Service Discovery** — per-instance breakers across a discovered pool
- **API Gateway** — a natural place to configure breaker rules per backend route
- **Sidecar** — service meshes provide breakers at the infrastructure level, with no application code

Bulkhead Pattern

Category: Resilience **One-liner:** Partition a system into isolated compartments with their own dedicated resources, so a failure or overload in one cannot consume the resources everything else needs.

Part 0 — Concepts you need first

What is a thread pool?

A fixed collection of worker **threads** (a thread is one independent line of execution inside a program) a program keeps ready. When work arrives, a free thread picks it up; when the work finishes, the thread returns to the pool.

Pools are fixed-size because threads are expensive — each needs memory (typically ~1 MB of **stack** — the memory area a thread uses for its method calls and local variables), and having thousands means the **operating system** (the base software, such as Linux, that runs programs and shares out the hardware) spends more time switching between them than doing work.

The consequence that drives this entire chapter: the pool is a *shared, finite resource*. If something exhausts it, **every** piece of work in that program stops — not just the work that caused the problem.

What does "resource exhaustion" mean?

Using up all of a limited resource so nothing else can get any. The resources that matter here:

- **Threads** — all busy, so no new work can start
- **Memory** — allocated, so new allocations fail
- **Database connections** — **connection pools** (sets of open database connections that are reused instead of opened fresh for each query) are also fixed-size and also exhaustible
- **Network bandwidth / file handles / CPU** (bandwidth = how much data the network can carry; a **file handle** is the operating system's ticket for one open file or connection, and there's a limit; **CPU** = processor time)

What is a "noisy neighbour"?

A component that consumes disproportionate shared resources and degrades everything sharing them. The term comes from cloud hosting, where one tenant's heavy usage slows other tenants on the same physical machine. In your own application, one slow **dependency** (another service or database your code calls) can be a noisy neighbour to every other feature.

Why does one slow dependency block unrelated work?

This is the crux, so it's worth walking through concretely.

Your service has **one thread pool of 200 threads**. It calls two dependencies: Inventory (usually busy) and Shipping (usually quiet).

Inventory becomes slow — 30 seconds per call instead of 50 milliseconds.

1. Requests needing Inventory arrive and each takes a thread
2. Each thread blocks for 30 seconds waiting
3. At any moderate request rate, all 200 threads end up blocked on Inventory
4. A request arrives needing only Shipping — **there is no thread available to serve it**

Shipping is perfectly healthy. Its requests still fail. They fail because Inventory ate all the threads. That's the failure this pattern prevents.

Part 1 — Where the name comes from

A ship's hull is divided into **watertight compartments** called bulkheads. If the hull is breached, water floods **one compartment** rather than the whole ship. The ship stays afloat, buying valuable time for rescue.

Without bulkheads, a single breach floods everything and the ship sinks rapidly. The failure — one hull breach — propagates across the entire ship and causes total system failure. That's a **cascading failure in a physical system** — one failure triggering the next, like falling dominoes.

In **distributed systems** (systems made of many programs on different machines cooperating over a network), a bulkhead is a mechanism that **isolates different parts of the system so that if one part fails, it doesn't cause the rest to fail.**

Part 2 — The problem: failure propagation

In an ideal world services would work perfectly all the time. In reality they fail — bugs, resource exhaustion, network issues, and more. Each service has its own responsibilities, resources, and failure modes.

When a service fails, it causes a **ripple effect**: the failure of one service leads to the failure of others that depend on it.

The e-commerce walkthrough

A **microservices**-based e-commerce platform (built as many small, independently deployed services) with separate services for user management, inventory management, payment processing, and so on.

1. The **inventory service** fails due to a database **outage** (a period when the database is unavailable)
2. The **user service**, which relies on inventory to display product availability, **also starts failing**
3. The **payment service**, which checks inventory before processing payments, **likewise fails**
4. In a short time, **the entire platform is unavailable**

All because of a failure in one service. This is a classic cascading failure.

Part 3 — The solution: isolation

The essence of the Bulkhead pattern is **isolation**. Like the watertight compartments in a ship, it partitions system components into isolated units. Each is designed to operate **independently of the others**, so if one fails, the others continue functioning.

Think of bulkheads as **failure containment**. By isolating parts of the system, you limit the **scope** of any potential failure. A failure in one part doesn't automatically mean failure of the whole — unaffected parts still provide some level of service, maintaining **availability** (the share of time the system is usable) as much as possible.

Applied to the e-commerce example

If the inventory service were isolated into its own bulkhead, its failure wouldn't directly impact the user and payment services. They could continue operating, providing limited functionality — browsing products, viewing past orders — despite inventory being down.

The half people miss

There's a second, subtler benefit. By preventing the inventory failure from **consuming system-wide resources** like CPU or memory, the pattern ensures those resources **remain available for the remaining services**.

> Isolating *resources* matters as much as isolating *code*. Two services can be perfectly separate in the **source tree** (the folders of source code) and still kill each other if they draw from the same thread pool. The bulkhead is about the resources, not the modules.

Not a magic solution

The course is careful here, and it's worth internalising: bulkheads don't make failures disappear. If a ship has a significant hull breach it might eventually sink despite its bulkheads. Likewise, if a distributed system experiences a major failure like a total network outage, it may become unavailable despite bulkheads.

What they do is **buy time and maintain some level of service**, significantly mitigating the impact.

Part 4 — Architecture

The architecture revolves around two concepts: **isolation** and **resources**.

What is a bulkhead, concretely?

At a high level, a bulkhead is simply a **partition** within the system. It could be:

- A separate **service**
- A group of related **processes** (separately running programs, each with its own memory)
- A set of **threads** — a thread pool, the most common implementation
- A dedicated **CPU or memory area**

The key requirement is that each operates **independently** of the others.

What are the resources?

Anything the bulkheads need to function: CPU time, memory, network bandwidth, database connections. Each bulkhead gets a **dedicated share**, ensuring a failure in one doesn't consume all the system's resources.

Step 1 — Divide the system into bulkheads

How you divide depends on your system's specifics and which failures you want to isolate. Common approaches:

- Isolate services that are **prone to failure**
- Isolate services handling **particularly resource-intensive tasks**
- Group services by **function**, or by the **type of users they serve**

In the e-commerce example, you'd create separate bulkheads for user management, inventory management, payment processing, and so on. Each operates independently with its own resources.

The aim: if one service fails **or becomes a resource hog**, the others aren't directly affected.

Step 2 — Allocate resources

Allocation should be **proportional to the needs and importance** of each bulkhead. A resource-intensive or critical service gets more than a less demanding or less critical one.

In the e-commerce platform you might allocate more to **payment processing** (which handles financial transactions) than to **user management** (which mainly handles profiles). The specific allocation depends on:

- Expected load on each service
- Its performance requirements
- The consequences of its failure

This is the critical mechanism: if a bulkhead fails and starts consuming resources excessively, the allocation **guarantees other bulkheads still have resources available**.

Step 3 — Manage interactions between bulkheads

Since each bulkhead operates independently, interactions between them must be carefully managed or failures propagate anyway.

Keep interactions to a minimum. The more a bulkhead depends on other bulkheads, the higher the chance of a failure spreading.

When interactions are necessary, isolate them. If the user management service must interact with inventory, it could do so via a **message queue** (a buffer where one component leaves messages for another to pick up later) or an **API gateway** (a single entry point that routes requests to services). That way, if inventory fails, the failure doesn't directly impact user management — the interaction stays isolated and manageable.

> Why a message queue helps: with a direct call, the caller waits for a response and its thread is held while the callee struggles. With a queue, the caller drops a message and moves on immediately. The failure becomes "messages accumulate in a queue" instead of "caller's threads are all blocked."

Part 5 — Inner workings

Isolation in practice

Maintaining independence involves careful design and implementation choices. Each bulkhead might:

- Run in its **own process or container** (a **container** packages an application with everything it needs and runs it isolated from others)
- Have its **own database and cache** (a **cache** is a fast store of recently used data)
- Use its **own thread pool**

But the course makes a point that's easy to skip past and shouldn't be:

> Achieving isolation is **not just about technical measures**. It also requires an **organisational commitment** to maintaining independence. Changes to one bulkhead should not require changes to others. Interdependencies must be minimised and carefully managed.

In other words, you can build perfect technical isolation and then destroy it over six months by letting teams add convenient direct dependencies between compartments. The isolation has to be defended, not just built.

Resource allocation — fairness and efficiency

The aim is **fairness** (each bulkhead gets the resources it needs) and **efficiency** (resources aren't wasted). In practice this involves:

- Setting **resource quotas or limits** (hard caps on how much CPU, memory or connections something may use) per bulkhead
- Scheduling resources fairly and efficiently
- **Dynamically adjusting** allocation based on real-time conditions

For instance, if one bulkhead is experiencing a surge while another is idle, the system might temporarily reallocate some resources from the idle one to the busy one, improving overall performance and responsiveness.

Failure detection and mitigation

The ultimate test is how the pattern handles failures. When one occurs within a bulkhead, the system needs to **detect it, isolate it, and mitigate its impact**. This typically involves monitoring, alerting, and automatic recovery:

- The system **continuously monitors** the health and performance of each bulkhead
- If a problem is detected, it **generates alerts** and starts **automatic recovery**
- If a bulkhead starts consuming resources excessively, the system might automatically **throttle its resource usage or restart it** (to **throttle** is to deliberately slow something down)
- If it remains unresponsive, the system might **reroute traffic** to other bulkheads or **bring up new instances** (extra running copies of a service) to handle load

It's not a silver bullet

The pattern can't prevent failures from happening and can't guarantee 100% **uptime** (time the system is running and reachable) or performance. It's one tool in the toolbox, to be complemented with **redundancy, replication, load balancing, and caching** — spare components, copies of data on several machines, spreading requests across instances, and keeping fast copies of frequently used data. See System Design Fundamentals for all four.

Part 6 — Worked example: thread-pool bulkheads in Java

The scenario

An **Order Service** responsible for creating orders. It must communicate with two others:

- **Inventory Service** — often gets high traffic
- **Shipping Service** — usually has less load

Without bulkheads: a spike in requests to Inventory could clog the Order Service, preventing it from completing its tasks involving Shipping.

Creating separate thread pools

Java's `ExecutorService` (the standard Java interface for running tasks on a pool of threads) is well suited to creating thread pools:

```
ExecutorService inventoryExecutor = Executors.newFixedThreadPool(100);
ExecutorService shippingExecutor  = Executors.newFixedThreadPool(50);
```

Reading it: `newFixedThreadPool(100)` creates a pool with exactly 100 threads. Submit more than 100 tasks and the extras queue until a thread frees up.

The pool sizes should be determined by the load each service is expected to handle. Inventory gets the larger pool (100) because it typically faces more traffic; Shipping gets 50.

These two pools are the bulkheads. They are separate compartments; threads in one cannot be consumed by work destined for the other.

Using them

```
public void createOrder(Order order) {
    inventoryExecutor.submit(() -> {
        inventoryService.checkAndUpdateInventory(order);
    });

    shippingExecutor.submit(() -> {
        shippingService.scheduleShipping(order);
    });
}
```

`createOrder` initiates tasks that interact with both services. Each task is **submitted to its own executor**, ensuring a slowdown in one service doesn't affect the other.

The bulkhead in action

Now replay the failure scenario:

1. A significant number of requests start slowing down the **Inventory Service**
2. Threads in `inventoryExecutor` get stuck or slowed — potentially all 100 of them
3. **The 50 threads in `shippingExecutor` are completely unaffected**, because they're a separate pool
4. `createOrder` can **continue scheduling shipping** even while inventory checks are delayed

The system uses its resources efficiently and provides a faster response where it can.

Compare this to the single-pool version: all 200 threads blocked on Inventory, and shipping requests failing for no reason of their own. **The only change is drawing from two buckets instead of one.**

What the example deliberately leaves out

The course itself raises these as questions leading into the next section:

- **Error handling** — what if a service doesn't respond at all, or throws an **exception** (Java's mechanism for signalling an error)?
- **Timeouts** (a maximum wait before giving up) — a stuck thread needs a bound, or it's stuck forever *(pair with Circuit Breaker)*
- **Pool sizing** — how do you actually determine those numbers?

Also worth noticing: `submit()` returns a `Future` (an object that will hold the task's result or error once it finishes) that this code ignores, so **failures are silently swallowed**. Real code would capture and handle the result.

Part 7 — Performance implications

Benefits

Efficient resource utilization. Even when one service is sluggish or non-responsive, the system continues processing other tasks. The risk of the entire system freezing or significantly slowing due to one faulty component is mitigated.

Load balancing. (Spreading work so no single part is overloaded.) Allocating different thread pools to various tasks or services distributes the system's load. The distribution can be fine-tuned based on the nature and expected load of each.

Response time. By ensuring a delay in one part doesn't affect others, overall response time improves. Even if some requests are delayed by an issue in one component, others are served swiftly.

Considerations

Determining bulkhead sizes. One of the real challenges. Ideally sizes are decided by expected load and the nature of the tasks — but striking the right balance often involves **a degree of trial and error**.

> A practical starting point: size each pool to the **concurrency** (number of requests in progress at the same time) that dependency can actually handle. If Inventory can serve 100 concurrent requests before degrading, a pool larger than 100 just queues work inside the dependency instead of inside you — which is worse, because you lose visibility.

Monitoring and adjusting. Over time, as load and task nature evolve, initial allocations need adjustment. Monitor performance and adjust sizes as needed. Tools like Java's **VisualVM** (a free tool that shows a running Java program's threads, memory and CPU) help monitor thread usage and identify **bottlenecks** (the points that limit overall speed).

Error handling. Even with bulkheads, some requests may fail or be excessively delayed if a service goes down or becomes unresponsive. Handle these gracefully — implement a **timeout**, or use another resilience pattern like the **Circuit Breaker**.

Scalability concerns. This one deserves emphasis:

> The Bulkhead pattern improves system **resilience** (staying up when parts fail) but **does not directly address scalability** (handling more load by adding resources). If load increases significantly, simply creating more threads leads to **excessive context switching** (the CPU repeatedly saving one thread's state and loading another's, which is pure overhead) and eventually **decreases** performance. For scale, use horizontal scaling (more machines) or **asynchronous** processing (work handed off to run in the background so callers don't wait).

⚠️ **This is the point beginners get wrong most often.** Bulkheads bound damage; they don't add capacity. Reaching for bigger thread pools as a solution to load makes things slower, not faster, because the CPU spends its time switching between threads rather than running them.

Part 8 — Use cases

E-commerce platforms

Customer actions span searching for products, adding items to carts, and placing orders. These are interconnected but can be performed independently.

If the **search service** is overwhelmed by a traffic spike or a bug causing excessive load, without bulkheading this could slow the entire platform — **affecting even cart and ordering services**. Isolating services into separate bulkheads ensures an issue in one doesn't impact the others.

Online gaming platforms

A platform offering various games, each running as a separate service. **Player requests to one game shouldn't affect the performance of other games.** Isolating game services prevents a faulty or overloaded game from affecting the entire platform.

Financial systems

Distinct operations: account management, transaction processing, and reporting. These are interrelated but can function independently.

> **A delay in generating reports shouldn't affect the speed of transaction processing.** This is the cleanest illustration of the principle — reporting is typically heavy and slow, transactions are **latency**-critical (latency = how long each request takes), and there is no good reason for the former to interfere with the latter.

Part 9 — System design example: music streaming (Spotify-like)

A large-scale music streaming platform with services for music streaming, user management, playlist management, and recommendation generation.

Bulkheading services (coarse-grained)

User management isolated from music streaming. Even if user management becomes overloaded due to a sudden surge in new users, this doesn't affect streaming performance. **Users can still listen to music uninterrupted.**

Playlist management isolated from recommendations. Even if the recommendation service becomes slow due to the complexity of processing and analysing user data, playlist management is unaffected and users can still create and manage their playlists.

Bulkheading at a lower level (fine-grained)

Bulkheading can also be applied **within a single service**. Inside the music streaming service you could separate:

- the task of **fetching a song** (from the song database)
- the task of **streaming the song** to the user

into **separate thread pools**. So if fetching songs becomes slow due to a delay accessing the song database, this **won't slow down the streaming of songs already fetched**.

> This two-level view is the most useful takeaway from the chapter. Bulkheads apply *between* services **and** *within* a single service. The fine-grained version is often what actually saves the user experience — a user whose music keeps playing while search is broken barely notices anything is wrong.

In both cases, applying the pattern dramatically increases resilience: while one service or task is slow or failing, others continue functioning normally, providing an uninterrupted experience.

Part 10 — Bulkhead vs. Circuit Breaker

These two get confused constantly. They're complementary, not alternatives.

	Bulkhead	Circuit Breaker
Mechanism	Partitions resources	Stops calls after repeated failures
Protects against	Resource exhaustion spreading	Wasted calls to a known-dead service
When it acts	Always — it's structural	On detecting failures — it's reactive
Analogy	Watertight compartments	A fuse that trips
Limits	*How much* damage one failure can do	*How long* you keep trying

Use both. The bulkhead caps the **blast radius** (how much of the system one failure can damage); the breaker stops you feeding the fire. In the Order Service example, the bulkhead means Inventory can only ever consume its own 100 threads — and a breaker on Inventory means those 100 threads stop being wasted once it's clearly down.

Part 11 — Common beginner misconceptions

"Bulkhead means microservices." No. You can bulkhead inside a single **monolith** (an application built and deployed as one unit) by giving different **workloads** (kinds of work) different thread pools — and that's often the highest-value place to start.

"Bigger pools are safer." The opposite past a point. Threads cost memory and context-switching. The pool should match what the dependency can handle, not what you wish it could.

"It's the same as rate limiting." Related but different. (**Rate limiting** caps requests per caller per time window.) Rate limiting caps how many requests you *accept*; bulkheading caps how many resources a category of work can *consume*.

"Isolation is a one-time build." It erodes. Teams add convenient cross-dependencies over time. It needs ongoing defence — which is why the course calls it an organisational commitment.

"Bulkheads help with load." They help with *failure*. For load you scale horizontally.

Part 12 — Check your understanding

1. Why can a slow Inventory Service cause Shipping requests to fail, when Shipping is healthy?
2. What are the two things a bulkhead isolates, and which do people forget?
3. Why does a message queue between bulkheads help contain failure?

4. Why doesn't the Bulkhead pattern help with scalability?
5. Give an example of fine-grained bulkheading inside a single service.
6. How does Bulkhead differ from Circuit Breaker?

(Answers: 1 — they share one thread pool, and Inventory's blocked threads consume all of it; 2 — code and resources, and people forget resources; 3 — the caller drops a message and moves on instead of holding a thread waiting for a struggling callee; 4 — more threads cause excessive context switching and degrade performance, so capacity comes from horizontal scaling; 5 — separate thread pools for fetching songs versus streaming already-fetched songs; 6 — bulkhead limits how much damage a failure can do and is always active, breaker limits how long you keep trying and activates on detected failures.)

Part 13 — Interview soundbite (30 seconds)

> "Bulkhead comes from ship design — watertight compartments so one hull breach doesn't sink the whole ship. In software you partition resources so a failing dependency can't consume everything. The classic case is an Order Service calling Inventory and Shipping from one shared thread pool: if Inventory gets slow, every thread ends up blocked waiting on it, so Shipping calls start failing even though Shipping is perfectly healthy. The fix is separate thread pools sized per dependency, so Inventory's problems are bounded to its own hundred threads. You can apply it between services or inside one service — for example separating song fetching from song streaming, so a slow database doesn't interrupt playback of what's already loaded. It pairs with circuit breakers: bulkhead caps how much damage a failure can do, the breaker caps how long you keep trying. The main gotchas are that sizing the pools is genuinely trial and error and needs monitoring, and that it improves resilience but not scalability — adding threads to handle more load just causes context switching, so capacity has to come from horizontal scaling."

Part 14 — Implementation

A. Runnable demo — see thread starvation, then see it fixed

(**Thread starvation** is when work can't run because every thread is taken. `./gradlew` runs **Gradle**, the Java build tool used for the demos; `AtomicInteger` is a thread-safe counter.)

This program runs the *same* workload twice: once with a shared pool, once with bulkheads. Full source: **`demos/chapters/07-bulkhead/BulkheadDemo.java`**

```
cd demos && ./gradlew runCh07
```

```java
import java.util.concurrent.*;
import java.util.concurrent.atomic.AtomicInteger;

public class BulkheadDemo {

    static final int POOL = 10;      // small pool so the effect is visible
    static final int REQUESTS = 20;

    // Inventory is slow (2s). Shipping is fast (50ms) and perfectly healthy.
    static String slowInventory() throws InterruptedException {
        Thread.sleep(2000);
        return "inventory-ok";
    }

    static String fastShipping() throws InterruptedException {
        Thread.sleep(50);
        return "shipping-ok";
    }

    // ---------- WITHOUT bulkheads: one shared pool ----------
    static void withoutBulkheads() throws Exception {
        ExecutorService shared = Executors.newFixedThreadPool(POOL);
        AtomicInteger shippingDone = new AtomicInteger();
        long start = System.currentTimeMillis();

        for (int i = 0; i < REQUESTS; i++) {
            shared.submit(() -> { slowInventory(); return null; });
        }
        // Shipping work arrives after the inventory flood
        for (int i = 0; i < 5; i++) {
            shared.submit(() -> {
                fastShipping();
                shippingDone.incrementAndGet();
                return null;
            });
        }

        shared.shutdown();
        boolean finished = shared.awaitTermination(3, TimeUnit.SECONDS);
        System.out.printf("  shipping completed in 3s: %d/5   (finished=%s, %dms)%n",
                shippingDone.get(), finished, System.currentTimeMillis() - start);
    }

    // ---------- WITH bulkheads: separate pools ----------
    static void withBulkheads() throws Exception {
        ExecutorService inventoryPool = Executors.newFixedThreadPool(POOL);
        ExecutorService shippingPool  = Executors.newFixedThreadPool(5);
        AtomicInteger shippingDone = new AtomicInteger();
        long start = System.currentTimeMillis();

        for (int i = 0; i < REQUESTS; i++) {
            inventoryPool.submit(() -> { slowInventory(); return null; });
        }
        for (int i = 0; i < 5; i++) {
            shippingPool.submit(() -> {
                fastShipping();
                shippingDone.incrementAndGet();
                return null;
            });
        }

        Thread.sleep(3000);
        System.out.printf("  shipping completed in 3s: %d/5   (%dms)%n",
                shippingDone.get(), System.currentTimeMillis() - start);
        inventoryPool.shutdownNow();
        shippingPool.shutdownNow();
    }

    public static void main(String[] args) throws Exception {
        System.out.println("\n=== WITHOUT bulkheads (shared pool of " + POOL + ") ===");
```

```
        withoutBulkheads();

        System.out.println("\n=== WITH bulkheads (separate pools) ===");
        withBulkheads();
    }
}
```

B. What you should see

```
=== WITHOUT bulkheads (shared pool of 10) ===
  shipping completed in 3s: 0/5   (finished=false, 3001ms)

=== WITH bulkheads (separate pools) ===
  shipping completed in 3s: 5/5   (3000ms)
```

That's the whole pattern in two lines of output. Same workload, same total resources. In the first run, twenty slow inventory tasks occupy all ten threads, and five trivial 50ms shipping tasks get **zero** of them. In the second, shipping has its own pool and finishes immediately — while inventory is just as slow as before.

Nothing was made faster. Something was made *isolated*.

C. Production — Resilience4j Bulkhead

Two flavours, and choosing correctly matters:

Type	Mechanism	Use when
`SemaphoreBulkhead`	Caps **concurrent calls** on the caller's own thread (a **semaphore** is a counter of permits)	Default choice — cheap, no extra threads
`ThreadPoolBulkhead`	Runs calls on a **separate thread pool**	You need true thread isolation, or async (background) execution

Configuration: (for **Resilience4j**, the standard Java resilience library, written in YAML — an indentation-based config format)

```
resilience4j:
  bulkhead:                          # semaphore-based
    instances:
      inventoryService:
        maxConcurrentCalls: 25       # at most 25 in flight
        maxWaitDuration: 100ms       # then reject rather than queue forever
      shippingService:
        maxConcurrentCalls: 10
        maxWaitDuration: 100ms

  thread-pool-bulkhead:              # thread-pool-based
    instances:
      reportGeneration:
        maxThreadPoolSize: 4
        coreThreadPoolSize: 2
        queueCapacity: 20
```

Usage: (to **shed load** means to reject excess work quickly instead of queuing it; `sku` is a *stock-keeping unit*, a product's ID)

```
@Bulkhead(name = "inventoryService", fallbackMethod = "inventoryFallback")
public Inventory check(String sku) {
    return inventoryClient.get(sku);
}

private Inventory inventoryFallback(String sku, BulkheadFullException e) {
    // Bulkhead full — shed load rather than queue
    return Inventory.unknown(sku);
}
```

Kubernetes-level bulkheads — the same idea applied to whole services. (**Kubernetes** runs containers across a cluster of machines; a **pod** is its smallest unit. `requests` is what the pod is guaranteed, `limits` the most it may use; `500m` means half a CPU core, `Mi`/`Gi` are mebibytes/gibibytes.)

```
resources:
  requests: { cpu: "500m", memory: "512Mi" }
  limits:   { cpu: "1000m", memory: "1Gi" }   # this pod cannot starve its neighbours
```

Database connection pools are bulkheads too — and often the most valuable one (**HikariCP** is the default Java connection pool in Spring Boot; to **fail fast** is to give up immediately rather than wait):

```
spring.datasource.hikari:
  maximum-pool-size: 20
  connection-timeout: 3000     # fail fast when the pool is exhausted
```

D. How to size the pools

The most-asked question, and there's a real formula to start from — **Little's Law** (a queueing rule: items in progress = arrival rate × time each spends; **throughput** = requests completed per second):

```
concurrency = throughput × latency
```

If a dependency serves **50 requests/second** at **200ms** average latency, then `50 × 0.2 = 10` concurrent calls are in flight at **steady state** (normal, stable traffic). Size the bulkhead a bit above that — say 15 — to absorb bursts.

The key insight: don't size it larger than the dependency can actually handle. If Inventory degrades beyond 100 concurrent requests, a bulkhead of 500 doesn't help you — it just moves the queue from your process into theirs, where you can't see it or shed it.

Then measure and adjust. `maxWaitDuration` short (~100ms) means you **shed load** rather than accumulate it, which is what you want.

E. Implementation pitfalls

1. Pools sized by guesswork. Start from Little's Law, then tune with real metrics. "200 because that's the default" is how you end up with a pool that can't protect anything.

2. Unbounded queues. `Executors.newFixedThreadPool` uses an **unbounded** `LinkedBlockingQueue` (a waiting line with no size limit). Under sustained overload it accumulates tasks until you get an `OutOfMemoryError` (Java crashing because it has run out of memory) — the bulkhead prevented thread exhaustion and gave you memory exhaustion instead. Use a bounded queue with an explicit **rejection policy** (the rule for what happens to new tasks when the queue is full):

```
new ThreadPoolExecutor(10, 10, 0L, TimeUnit.MILLISECONDS,
    new ArrayBlockingQueue<>(50),                    // bounded
    new ThreadPoolExecutor.AbortPolicy());           // reject when full
```

3. Ignoring the `Future`. `submit()` swallows exceptions into a `Future` nobody reads — failures vanish silently. Either use `execute()` with an `UncaughtExceptionHandler` (a hook that is called whenever a thread dies from an unhandled error), or actually check the result.

4. Forgetting the database connection pool. Teams bulkhead their HTTP calls beautifully and leave one shared 20-connection Hikari pool, where one slow query starves every **endpoint** (each URL the service answers). The connection pool is usually the *scarcest* resource you own.

5. Bulkheading without timeouts. A bounded pool full of threads blocked forever is still a dead pool. Bulkhead limits *how many* can be stuck; only a timeout limits *how long*.

6. Too many small pools. Every pool holds idle threads at ~1 MB of stack each. Twenty pools of fifty threads is a thousand threads and roughly a gigabyte before you serve a request. Bulkhead by *dependency*, not by endpoint.

7. Treating it as a scaling tool. Repeated because it's the most common error: bigger pools do not mean more capacity. Past the CPU's ability to run them, more threads means more context switching and *less*

throughput.

Related patterns

- **Circuit Breaker** — the natural companion; stop calling what has already failed
- **Retry** — retries inside a bounded bulkhead can't exhaust the whole system
- **Sidecar** — service meshes can enforce bulkheads at the infrastructure level
- **Event-Driven Architecture** — message queues between components are a natural isolation boundary

Retry Pattern

Category: Resilience **One-liner:** Automatically re-attempt operations that failed for temporary reasons, spacing attempts out with backoff and randomness, so brief glitches don't become user-visible errors.

Part 0 — Concepts you need first

What is a "transient" failure?

Transient means temporary — it goes away on its own without anyone fixing anything. The opposite is **permanent**: it will fail identically no matter how many times you try.

In the table below, a **packet** is one small chunk of data sent over a network, the **request body** is the data sent with a request (e.g. a JSON order), a **load balancer** spreads requests across several **instances** (running copies) of a service, and **CPU** is the processor.

The distinction is the single most important idea in this chapter, because **retrying a transient failure is useful and retrying a permanent one is pure waste**.

Transient (retry helps)	Permanent (retry is useless)
Network dropped a packet	The password is wrong
Server briefly out of connections	The request body is malformed
Momentary CPU spike	You lack permission
Load balancer restarted an instance	The record doesn't exist

What is "backoff"?

Waiting between retry attempts instead of retrying instantly. **Exponential backoff** means each wait is longer than the last — typically doubling: 1s, 2s, 4s, 8s.

Why wait at all? Because retrying instantly against a struggling service adds **load** (the amount of work hitting it) at the worst possible moment, and gives it no time to recover.

What is "jitter"?

Deliberate randomness added to the wait time. Instead of every client waiting exactly 4 seconds, each waits a random duration around 4 seconds.

It sounds pointless until you see the problem it solves — see the thundering herd below.

What is the "thundering herd" problem?

Imagine a service has a two-second blip. During that blip, **ten thousand clients** fail. Every one of them starts a 4-second backoff at almost the same instant.

Four seconds later, **all ten thousand retry simultaneously**. The service, which had just recovered, is hit by a synchronised wall of traffic and falls over again. Now they all back off 8 seconds, and the same thing happens again, harder.

The clients have accidentally organised themselves into a **denial-of-service attack** (flooding a service with so many requests that it can't serve anyone). **Jitter breaks the synchronisation** by spreading those retries across a window.

What does "idempotent" mean?

An operation is **idempotent** if performing it multiple times has the same effect as performing it once.

- `set balance to 100` — **idempotent**. Do it five times, balance is 100.
- `add 100 to balance` — **not idempotent**. Do it five times, you've added 500.

This matters enormously for retries, because a retry might be the *second* execution of something that already succeeded. (Idempotency is also covered in System Design Fundamentals.)

Part 1 — The problem

In a **distributed microservices architecture** (an application split into many small services running on different machines and talking over a network), **failures are inevitable**. Services constantly communicate over networks and depend on numerous components, any of which can malfunction. Failures stem from unreliable networks, transient server **outages** (periods when a server is unavailable), overloaded load balancers, software bugs, even operator mistakes.

No matter how well you design, **it's virtually impossible to build a system that never fails**. Instead you design for **resilience** (the ability to keep working when parts fail), ensuring a small hiccup doesn't snowball into a major outage.

Transient failures specifically

These are short-lived errors that resolve on their own given a bit of time. A brief network glitch, a momentary loss of connectivity, a temporary service unavailability. Often these issues are **ephemeral** — try again after a short delay and it succeeds.

The classic example: a database connection failure caused by a spike in **concurrent** users (users active at the same moment). At the peak moment the connection is refused. **A few seconds later, after some connections close, a retry goes straight through.** Nothing was fixed; the condition passed.

Other common cases: network **timeouts** (giving up after waiting a set time), transient **HTTP 5xx** errors (status codes 500–599, meaning "the server failed"; 4xx codes mean "the request was wrong"), temporary resource exhaustion.

Why this needs solving

Without a strategy for such hiccups, microservices **propagate errors to end-users or upstream systems unnecessarily** (an **upstream** system is one that called you and is waiting on your answer). A tiny blip in connectivity could trigger a user-facing error — or require manual intervention — even though **the system might have recovered milliseconds later**.

That's the frustration the pattern removes: the failure was real, but it was over before the user finished reading the error message.

Part 2 — The solution

If an operation fails due to a temporary issue, **wait a short period and try again**, on the assumption the issue may have resolved in the interim.

Many distributed systems fail in **partial** ways — a subset of requests fail while others succeed — or suffer short-lived outages. Often, trying the same request again simply causes it to succeed.

A good illustration: if a service didn't respond because of a momentary spike, a retry a few moments later **might hit a less-busy instance** and succeed. With multiple instances behind a load balancer, the retry isn't even necessarily going to the same place that failed.

The effect: retries **mask sporadic failures**, increasing the reliability the user perceives.

Why it works

Retries assume the failure was transient or **non-deterministic** (not guaranteed to happen the same way every time). Network blips clear up, **threads** (independent lines of execution in a program) get freed, services restart — so a subsequent attempt has a good chance of succeeding where the first failed. This dramatically reduces the error rate seen by higher-level services and end users. Instead of giving up immediately when a **downstream** call (a call to a service you depend on) fails, a service can retry and often complete the operation **without any manual fix**.

Part 3 — Transient vs. permanent: the critical distinction

Retry should only engage for errors **likely to be temporary**.

Worth retrying: network timeouts · HTTP 5xx server errors · 502 Bad Gateway from a load balancer · database **deadlocks** (two transactions each waiting for a lock the other holds; the database kills one) · connection refused (nothing is accepting connections right now) · **throttling** / **rate-limit** errors (the service is deliberately refusing because you're sending too much)

Not worth retrying: HTTP 400 (input validation failure) · HTTP 401 (**authentication** error — the caller couldn't prove who they are) · **business logic** errors (the request breaks a domain rule, e.g. insufficient funds) · configuration errors · fatal **exceptions** (errors thrown by code that can't be recovered from)

> **No amount of retrying will fix a bad request or invalid credentials.** Those errors are permanent *for that request*. Retrying them just repeats the failure and potentially worsens system load.

Therefore a well-designed retry mechanism **checks the error type or exception type**, retrying only transient conditions while letting permanent errors **fail fast** (return an error immediately rather than waiting).

Retry vs. fail-fast

An alternative strategy is **fail-fast**, typically managed via a Circuit Breaker (a component that stops calling a service after repeated failures, for a cooling-off period).

	Retry	Fail-fast (Circuit Breaker)
Behaviour	Keeps trying, hoping for eventual success	Stops trying after detecting a pattern of failures
Favours	Eventual success	Conserving resources
Cost	Extra wait time and work	Gives up on things that might have worked
Right for	Transient faults	Long-lasting or permanent faults

For transient faults, retries are ideal — there's a high chance the next attempt succeeds. For a service that will be down for hours, **blindly retrying wastes time and resources**, and circuit breakers or **graceful degradation** (serving defaults or **cached** data — saved copies of earlier answers) are more appropriate.

Use retries for hiccups; fall back or fail fast for lasting errors. They're complements, not competitors.

Part 4 — Architecture

The pattern is implemented as a **wrapper around an operation** that intercepts failures and repeats according to a policy.

Retry policy and parameters

Defines **when and how** to retry:

- The **maximum number of attempts**
- **Which exceptions or error codes** are considered retryable
- The **delay strategy** between attempts

Policies range from simple — *"retry up to 3 times with 2 seconds between tries"* — to sophisticated — *"retry 5 times with exponentially increasing delays, add randomness, and give up on certain error types."*

Retry loop (the invoker)

The mechanism that executes the operation and applies the policy. It calls the operation, catches any failure, checks whether a retry should happen per the policy, waits the specified delay, then calls again. This continues until either the operation succeeds or max retries is reached. If it never succeeds, the invoker **propagates the final failure** (passes the error up to its own caller), often after logging it as a persistent error.

Backoff strategy

To avoid hammering the failing resource, incorporate a wait between attempts rather than retrying in a **tight loop** (a loop that repeats as fast as the CPU allows, with no pause).

Strategy	Behaviour	When
Constant delay	Always wait the same, e.g. 5s	Simple cases; predictable recovery time
Exponential backoff	Each wait longer than the last: 1s, 2s, 4s	The general default
Capped exponential backoff	As above with a maximum	Prevents absurdly long waits

Exponential backoff **mitigates load on struggling services** by spacing attempts out, and increases the likelihood that by the time the next attempt runs, the transient issue has resolved.

The cap matters: without it, five doublings from one second gives you a 32-second wait, and eight gives you over four minutes. Implementations typically cap the maximum delay.

Jitter (randomization)

If many clients or threads experience an error at around the same time, **they might all retry in unison after the same backoff interval**. This produces the thundering herd — a burst of synchronized retries hitting the service simultaneously, potentially causing **a second failure spike**.

Jitter introduces **random variation in the delay**. Instead of every client waiting exactly 4 seconds, each waits a random time around 4 seconds — somewhere between 2 and 4, or with a random offset added. This **spreads out the bursts** so load on the downstream service stays more even.

There are several implementations — **full jitter**, **equal jitter**, **decorrelated jitter** — but the core idea is identical: introduce randomness so retries are **de-synchronized across clients**.

> It seems counter-intuitive to add randomness to a system deliberately, but it has been shown to significantly reduce **contention** (many clients competing for the same resource at once) and improve recovery times. This is one of those cases where the unintuitive answer is simply correct.

Circuit breaker integration

Retries deal with transient failures; circuit breakers handle persistent ones by cutting off calls to an unresponsive service after a threshold. In practice a breaker **prevents a retry loop from endlessly hitting a downed service**.

For example, if a service has been failing for the last 50 calls, the breaker opens and further calls fail immediately without even trying — giving the service time to recover. After a **cooldown** (a fixed waiting period), a **half-open** state (the breaker's trial mode) allows a test call, and success closes the circuit again.

The balance: allow 3 quick retries on a request, but if multiple requests in a row all fail — signalling a likely bigger problem — open the circuit to stop further traffic for a short period.

Idempotency and side effects

A critical design consideration. If an operation has **side effects** (changes it makes in the world beyond returning a value) — **charging a credit card, sending an email, incrementing a counter** — retrying could

inadvertently perform the action **multiple times** unless you design against it.

Ideally, retried operations should be **idempotent**. Many **APIs** (interfaces that programs call) already are: deleting a resource, or performing a `GET` (the HTTP method for reading data). For non-idempotent actions — creating an order, making a payment — you must take special care.

The technique: use **unique transaction identifiers or tokens** (**idempotency keys** — a unique ID the client attaches to an operation and reuses on every retry of it) so the server can recognise a duplicate attempt and not process the action twice.

> The failure mode to picture: your payment call succeeds on the server, but the response is lost on the way back. Your client sees a timeout — indistinguishable from "it never happened" — and retries. **Without an idempotency key, the customer is charged twice.** The client genuinely cannot tell the difference between "lost request" and "lost response," which is why the server must be the one to **deduplicate** (detect and ignore repeats).

Placement in the architecture

Where should retries happen?

Client-side of a service-to-service call — the caller handles retrying. Service A calls Service B; A's client library or **HTTP client** (code that sends web requests) implements the retry policy. B remains **stateless** (keeps no memory between requests) and unaware of retries; it just sees repeated incoming requests.

API gateway or service mesh (a single entry point that routes outside requests, or a layer of proxies beside every service that routes internal traffic) — infrastructure automatically retries failed requests between services.

⚠️ **The key rule: avoid duplicating retries at multiple layers.**

> If every hop in a chain of microservices did its own retries, **a single failure could multiply into a storm of requests.** Three layers each retrying three times means one original request becomes twenty-seven. Good practice is to **centralize or delegate retries to one layer** — only at the edge service, or only at the immediate caller — to prevent cascading retry explosions. In practice this means disabling internal retries in lower-level clients and handling it once at a higher layer, or using a coordinated approach like a **token bucket** to limit overall retry rates (a bucket refills with tokens at a fixed rate and each retry must spend one, so retries can never exceed that rate).

Part 5 — Worked example (Java)

```java
public class RetryUtil {

    public static <T> T executeWithRetry(Callable<T> task, int maxAttempts,
            long baseDelayMillis, double backoffFactor, boolean useJitter) throws Exception {

        int attempt = 1;
        Exception lastException = null;
        Random random = new Random();

        while (attempt <= maxAttempts) {
            try {
                return task.call();                 // success — return immediately
            } catch (Exception e) {
                lastException = e;                  // remember it for the final throw

                if (attempt == maxAttempts) {
                    break;                          // no retries left
                }

                // Work out how long to wait
                long delay = baseDelayMillis;
                if (backoffFactor > 1.0) {
                    // exponential: base * factor^(attempt-1)
                    delay = (long) (baseDelayMillis * Math.pow(backoffFactor, attempt - 1));
                }
                if (useJitter) {
                    // "full jitter": random value between 0 and the computed delay
                    delay = (long) (random.nextDouble() * delay);
                }
                // (a maximum cap could be applied here)

                try {
                    Thread.sleep(delay);
                } catch (InterruptedException ie) {
                    Thread.currentThread().interrupt();   // restore the interrupt flag
                    break;                                // stop retrying
                }

                attempt++;
            }
        }
        throw lastException;    // all attempts exhausted
    }
}
```

The parameters

Parameter	Meaning
`maxAttempts`	Total tries **including the initial attempt.** `3` means 1 try + 2 retries
`baseDelayMillis`	Fixed delay if constant; the initial delay if exponential
`backoffFactor`	The multiplier. `2.0` with base 100ms gives 100ms, 200ms, 400ms. Set `1.0` for a constant interval
`useJitter`	Applies full jitter — a random value between 0 and the computed delay

Reading the logic

`Callable<T>` makes it reusable. `Callable` is Java's interface for "an operation that returns a value and may throw." Accepting one means this utility wraps *any* operation — a network call, a database query — rather than being tied to one.

Success returns immediately. `return task.call()` exits the loop on the first success. No further attempts, no delay.

The exception is saved, not swallowed. `lastException = e` keeps the most recent failure so it can be thrown to the caller at the end. The caller learns *why* it ultimately failed.

The attempt check comes before the delay. If this was the last attempt, `break` immediately — there's no point sleeping before giving up.

`Math.pow(backoffFactor, attempt - 1)` — on attempt 1 that's `factor^0 = 1`, so you wait `baseDelay`. On attempt 2 it's `factor^1`, so double. And so on.

The `InterruptedException` handling is correct and worth copying. When a thread is **interrupted** (another thread politely asks it to stop what it's doing), catching the exception clears the interrupt flag. `Thread.currentThread().interrupt()` restores it so code higher up still knows the thread was asked to stop. Forgetting this is a classic Java bug that makes applications refuse to shut down.

Using it

```
String result = RetryUtil.executeWithRetry(
    () -> fetchData(url),
    3,        // up to 3 attempts
    1000,     // 1 second base delay
    2.0,      // exponential backoff, doubling
    true      // use jitter
);
```

This attempts the fetch and, on failure, retries up to 2 more times — waiting about 1s before the first retry and about 2s before the second, with randomness in those waits. If all attempts fail it throws after roughly 3 seconds of total waiting.

In many cases that one retry is all that's needed to ride out a transient glitch and succeed on the second try.

Design choices, and one to change

The course is explicit about these:

- **Generic** `Callable<T>` keeps the logic reusable across any operation type
- **Configurable backoff and jitter** allows switching strategies: constant with no jitter (`1.0`, `false`), exponential without jitter (`2.0`, `false`), or exponential with jitter (`2.0`, `true`). This flexibility is crucial for tuning to different scenarios
- `maxAttempts` **prevents infinite loops** — vital, since an unbounded retry loop could endlessly hammer a failing service

And one deliberate simplification you should not carry into production:

- **It catches broad** `Exception`, treating *any* failure as retryable. In a real scenario you should catch **only specific transient exceptions** — `IOException` (Java's input/output and network error), timeouts — and let others bubble up without retry. **Your error-filtering logic belongs here**, and without it you'll cheerfully retry validation errors three times.

A refinement on jitter: full jitter (`random × delay`) can produce a near-zero wait, which partially defeats the purpose of backing off. Many production implementations randomise between **50% and 100%** of the delay instead, keeping a meaningful minimum gap.

Worth adding: logging each retry attempt, **metrics** (numeric measurements such as a retry counter), and a circuit-breaker check that aborts retrying if a higher-level circuit is already open.

Part 6 — Performance implications and risks

Increased load on dependencies

Every retry is an **additional request**. When failures are genuinely rare this extra load is negligible and well worth the improved reliability.

But if a downstream service is failing *because it's overloaded*, retries make the problem worse. If Service A is hammering a slow Service B and starts retrying aggressively, B gets even more requests. In

the worst case, many clients retrying a struggling service create a **retry storm that amplifies load exponentially**, potentially overwhelming it completely.

This is precisely why **backoff is crucial** (breathing room between attempts) and **limited attempts** matter — and why circuit breakers or throttling (deliberately limiting request rates) should be layered on for protection.

Increased latency for end users

Retrying lengthens overall response time. A single failed attempt might add a few seconds of delay.

Sometimes that's acceptable — **a slightly slower successful response beats an immediate error**. But overdone it degrades experience, and chained retries across a call chain accumulate.

The countermeasure: **set an overall timeout for the operation** alongside retries. For example decide that an API call should either succeed **within 5 seconds including all retries**, or not at all, to maintain a responsive **SLA** (service-level agreement — a promised level of speed or uptime). Without this, retry policies silently blow past your **latency budget** (the maximum time a request is allowed to take; **latency** is the time a request takes from start to finish).

Wasted work and resource consumption

Every retry that ultimately fails was wasted effort — CPU, **bandwidth** (network capacity), memory that produced no result. If the underlying issue isn't transient, **all retries fail and all that work is for nothing**, plus it strains the system.

Hence: detect non-transient failures quickly. If a response says "permission denied" or "invalid request," a retry won't help. Your retry logic should inspect error codes and keep a **blacklist of non-retryable errors** (a list of errors that must never be retried).

A subtler point worth remembering: **if the first attempt already took a long time** — nearly hitting the client timeout — starting another attempt that will likely also time out is counterproductive. Better to propagate an error than tie up threads on hopeless retries.

Cascading effects in complex systems

Service A calls B, B calls C. If **both** A and B have their own retry policies, a failure in C causes B to issue multiple attempts, **and** A to issue multiple attempts of its call to B. This multiplies load on both B and C.

Avoid uncoordinated retries at every layer. Decide **which layer retries** and let others fail fast. A common practice: the edge or client-facing service handles retries, while intermediate services propagate errors. Monitoring should detect when excessive retries occur, since it often indicates a downstream **incident** (a production problem needing attention).

Retry storms and thundering herd

If a popular service glitches, many instances of many services may all start retrying at once. Backoff and jitter avoid synchronisation — **jitter specifically tackles the thundering herd** by de-synchronising retry timing.

Other mitigations: **retry budgets** (allowing a certain number of retries per second), and **adaptive algorithms** that lengthen backoff while errors continue, avoiding constant pressure.

Idempotency revisited

Beyond correctness, duplicate side effects have a performance cost too — sending the same email twice uses twice the email-sending resource. **Do not retry non-idempotent operations blindly** unless you have deduplication keys or **check-pointing** (recording progress so a repeat can skip steps already done) to guard against repeated side effects.

The mitigation checklist

- Implement **exponential backoff** — don't hammer rapidly
- Add **jitter** — avoid synchronised retries
- **Limit attempts**, and limit total time spent retrying

- Use **circuit breakers** or fail-fast switches where failure is likely persistent
- **Distinguish error types** — retry only transient ones
- **Monitor and tune** — frequent retries signal a struggling dependency or a bad policy
- **Ensure idempotency**, or implement server-side request deduplication for critical actions
- **Test under failure conditions** — simulate a dependency going down or exhibiting high latency, and verify your retry logic actually improves resilience rather than overwhelming the system

---

Part 7 — Use cases

Web services

The internet is unreliable, and transient faults are constant. When interacting with a remote web service and hitting a transient fault, retrying is usually beneficial because the **cost asymmetry** favours it: the cost of an unsuccessful request is high (an error message to the user, or an expensive fallback process), while the cost of a retry is typically just the time and resources to send another request.

Database operations

Many database operations are inherently uncertain — network issues, concurrency conflicts, temporary unavailability.

The clearest example: you try to save a record while **another user is updating the same record**. Rather than throwing an error, retry after a short delay. This allows the conflicting **transaction** (a group of database changes applied all-or-nothing) to complete and **paves the way for your operation to succeed**.

Microservice architectures

When one service depends on another, the failure of the latter can bring down the former. Retrying gives the failing service **a chance to recover** and makes your service more resilient — ensuring a temporary hiccup doesn't become a full-blown outage.

Part 8 — Real-world examples

Cloud service SDKs (AWS, Google Cloud). (An **SDK**, software development kit, is the official library for calling a platform from your code; **AWS** is Amazon Web Services.) Cloud providers build retry strategies into their client libraries. AWS SDKs automatically retry failed requests — a transient 5xx from a service, or a throttling error — using **exponential backoff and jitter**. This matters because network calls to cloud APIs occasionally time out or hit rate limits. Google Cloud's libraries have built-in retries for idempotent requests; a storage upload that times out is retried behind the scenes. These SDKs are battle-tested to balance retries and backoff, so **developers benefit from the pattern without even realising it**.

Netflix. As part of their overall resilience engineering, Netflix's internal libraries retry calls to microservices or **data stores** (databases, caches and the like) if a request fails or a **host** (the machine a service runs on) is unresponsive. If one instance fails to respond, the client quickly **retries on another instance** — perhaps after a brief backoff — instead of erroring out immediately. Combined with circuit breakers, this ensures sporadic failures don't disrupt the viewing experience.

Payment processing (Stripe, PayPal). Financial APIs frequently encounter transient failures communicating with banking networks or third-party systems. Rather than immediately failing a transaction and upsetting a customer, payment systems retry behind the scenes.

Critically, they **encourage the use of idempotency keys** on API requests. If a network issue occurs, the client can safely retry with the same key, and the server **knows not to duplicate the charge**. This design **explicitly embraces the Retry Pattern — it assumes clients will retry on failure.** The result: a temporary glitch between **merchant** (the shop) and **gateway** (the payment provider's service) doesn't lose

the order; the merchant's system retries automatically and payment goes through **without double-charging**.

Message queues and event processing. In systems built on **RabbitMQ** or **Kafka** (popular message brokers — software that stores messages from producers until consumers read them), retry appears as **requeueing messages** (putting a message back to be read again) or using **dead-letter queues** (a separate queue where messages that keep failing are parked for inspection). If a **consumer** (the program reading messages) fails to process a message due to a temporary error — say it can't reach a database — it doesn't **acknowledge** the message (tell the broker it was handled), so the message returns to the queue to be tried again after a delay. This is the Retry Pattern in an **asynchronous** context (where the sender doesn't wait for the work to be done).

A real example: in order processing, if an attempt to reserve inventory fails due to a **lock timeout** (it waited too long for another transaction to release a database lock — a guard that lets only one writer touch a row at a time), the message can be retried a minute later, by which time the lock may be free. Many large e-commerce platforms rely on this in their **event-driven architectures** (systems where services react to messages about things that happened) to ensure **eventually consistent** outcomes (all copies of the data agree once processing catches up).

Part 9 — System design examples

E-commerce checkout. The user has filled their cart and clicks Buy. The system must charge their credit card. But the **payment gateway** (the third-party service that actually charges cards) **is temporarily unavailable**. Do you tell the user their purchase failed? Or retry, hoping the gateway returns shortly?

With the Retry Pattern you choose the latter, handling the temporary glitch gracefully. *(And this is precisely where idempotency keys are non-negotiable — the double-charge scenario above.)*

IoT device data collection. A system collects data from **IoT** (Internet of Things — sensors and gadgets connected to the internet) devices and stores it in a database. Devices send data periodically. But the **database is temporarily unavailable** due to a network glitch or scheduled maintenance. Should the system discard the data?

Retry provides a resilient solution: handle the temporary issue and **ensure no data is lost**.

Part 10 — When NOT to use retry

- The error is clearly **non-transient** — a configuration error or fatal exception. Retrying just delays the inevitable
- The downstream service is **known to be down for an extended period** (a planned outage). A retry loop only burns resources; a circuit breaker or fallback response is preferable
- **Strict latency requirements** — **real-time** systems (ones that must respond within a guaranteed, very short time) may prefer to fail fast rather than retry and violate their latency SLA
- The operation is **extremely expensive**, or has **side effects that can't be repeated** safely

In such cases, prefer alternatives: **manual compensation** (a person or process undoing the effects), **eventual reconciliation** (comparing records later and fixing mismatches) for asynchronous processes, or simply **alerting a human**.

> **Use retries where they make sense — transient, recoverable errors — and avoid them where they don't: permanent failures, or scenarios where retries could cause harm.**

Part 11 — Common beginner misconceptions

"More retries means more reliability." Only up to a point. Beyond a few attempts you're mostly adding latency and load. If three attempts with backoff didn't work, the fourth probably won't either.

"Retry and circuit breaker are alternatives." They're complements doing opposite things. Retry handles the blip; the breaker handles the outage. Use both.

"Jitter is a micro-optimisation." It's the difference between a graceful recovery and a self-inflicted outage at scale. At ten thousand clients it's essential, not decorative.

"My operation is a GET, so idempotency doesn't matter." True for that call — but check the whole path. A GET that triggers a server-side counter increment or **audit write** (recording who accessed what) is not as idempotent as it looks.

"Retries are free if they usually succeed." They're free when failures are rare. They're most expensive exactly when the system is already struggling — which is when they fire most.

"I'll retry at every layer to be safe." This is the most damaging mistake in the chapter. Layered retries multiply, turning one failure into an exponential request storm.

Part 12 — Check your understanding

1. Why is retrying an HTTP 401 pointless?
2. Explain the thundering herd, and how jitter fixes it.
3. Why can't a client distinguish "lost request" from "lost response," and what follows from that?
4. Why must you set an overall operation timeout alongside a retry policy?
5. If A retries B and B retries C, how many requests can one failure become at 3 attempts each?
6. What's the one line in the example code you should change before production use?

(Answers: 1 — authentication failure is permanent for that request; no number of attempts fixes wrong credentials; 2 — many clients fail simultaneously, back off by the same amount, and retry in unison, re-overloading the service; jitter randomises delays so retries spread out; 3 — both look like a timeout, so the server must deduplicate using an idempotency key rather than the client guessing; 4 — otherwise cumulative retry delays silently exceed your latency budget; 5 — nine, since each of A's 3 attempts triggers 3 of B's; 6 — catching broad `Exception`, which retries permanent errors too.)

Part 13 — Interview soundbite (30 seconds)

> "Retry handles transient failures — network blips, timeouts, throttling, a connection refused during a spike — things that fix themselves in seconds. You wrap the call in a policy: max attempts, which errors are retryable, and a delay strategy. Two details matter most. First, exponential backoff, so you're not hammering a service that may be failing precisely because it's overloaded. Second, jitter — random variation in the delay — because otherwise every client that failed at the same moment retries at the same moment, and you get a thundering herd that causes a second outage. You also need idempotency: the client can't distinguish a lost request from a lost response, so retrying a payment without an idempotency key double-charges the customer. That's why Stripe's API is built around them — it explicitly assumes clients will retry. And you have to distinguish transient from permanent, because retrying a 400 or a 401 is pure waste. The biggest architectural mistake is retrying at every layer: if A retries B and B retries C, one failure becomes nine requests, so you pick one layer to retry and everything else fails fast. Retry pairs with circuit breakers — retry for hiccups, trip the breaker for real outages — and you set an overall operation timeout so the retries can't blow your latency budget."

Key takeaways: retry transient only · backoff plus jitter · limit attempts · make it idempotent · retry at one layer · test under failure.

Part 14 — Implementation

A. Runnable demo — backoff, jitter, and the thundering herd

Full source: `demos/chapters/08-retry/RetryDemo.java`

```
cd demos && ./gradlew runCh08
```

```java
import java.util.*;
import java.util.concurrent.*;
import java.util.concurrent.atomic.AtomicInteger;

public class RetryDemo {

    // ---------- Which errors are worth retrying ----------
    static class TransientException extends RuntimeException {
        TransientException(String m) { super(m); }
    }
    static class PermanentException extends RuntimeException {
        PermanentException(String m) { super(m); }
    }

    // ---------- The retry utility ----------
    static <T> T executeWithRetry(Callable<T> task, int maxAttempts,
                                  long baseDelayMs, double factor,
                                  boolean useJitter) throws Exception {
        Random random = new Random();
        Exception last = null;

        for (int attempt = 1; attempt <= maxAttempts; attempt++) {
            try {
                T result = task.call();
                if (attempt > 1) System.out.println("      succeeded on attempt " + attempt);
                return result;
            } catch (PermanentException e) {
                System.out.println("      permanent error, NOT retrying: " + e.getMessage());
                throw e;                                  // fail fast
            } catch (Exception e) {
                last = e;
                if (attempt == maxAttempts) break;

                long delay = (long) (baseDelayMs * Math.pow(factor, attempt - 1));
                delay = Math.min(delay, 5000);            // cap
                if (useJitter) {
                    // "equal jitter": 50-100% of the computed delay
                    delay = delay / 2 + (long) (random.nextDouble() * delay / 2);
                }
                System.out.printf("      attempt %d failed (%s), waiting %dms%n",
                        attempt, e.getMessage(), delay);
                Thread.sleep(delay);
            }
        }
        throw last;
    }

    // ---------- A service that fails N times then works ----------
    static class FlakyService {
        private final AtomicInteger calls = new AtomicInteger();
        private final int failuresBeforeSuccess;

        FlakyService(int n) { this.failuresBeforeSuccess = n; }

        String call() {
            int n = calls.incrementAndGet();
            if (n <= failuresBeforeSuccess) throw new TransientException("timeout");
            return "OK after " + n + " calls";
        }
    }

    public static void main(String[] args) throws Exception {

        System.out.println("\n=== 1. Transient failure, recovers on 3rd attempt ===");
        FlakyService flaky = new FlakyService(2);
        System.out.println("      result: " +
                executeWithRetry(flaky::call, 5, 100, 2.0, false));

        System.out.println("\n=== 2. Permanent failure — should NOT retry ===");
        try {
```

```
            executeWithRetry(() -> { throw new PermanentException("HTTP 401"); },
                    5, 100, 2.0, false);
        } catch (PermanentException e) {
            System.out.println("      gave up immediately (correct)");
        }

        System.out.println("\n=== 3. Backoff schedule, no jitter ===");
        try {
            executeWithRetry(() -> { throw new TransientException("503"); },
                    5, 100, 2.0, false);
        } catch (Exception ignored) { }

        System.out.println("\n=== 4. Same schedule WITH jitter ===");
        try {
            executeWithRetry(() -> { throw new TransientException("503"); },
                    5, 100, 2.0, true);
        } catch (Exception ignored) { }

        System.out.println("\n=== 5. Thundering herd: 1000 clients retry at once ===");
        demonstrateHerd(false);
        demonstrateHerd(true);
    }

    // Show how many clients land in the same 100ms bucket
    static void demonstrateHerd(boolean useJitter) {
        Random random = new Random();
        Map<Long, Integer> buckets = new TreeMap<>();
        long baseDelay = 1000;

        for (int i = 0; i < 1000; i++) {
            long delay = baseDelay;
            if (useJitter) {
                delay = delay / 2 + (long) (random.nextDouble() * delay / 2);
            }
            buckets.merge(delay / 100 * 100, 1, Integer::sum);
        }

        int worst = buckets.values().stream().mapToInt(Integer::intValue).max().orElse(0);
        System.out.printf("      jitter=%-5s -> busiest 100ms bucket holds %d of 1000 clients%n",
                useJitter, worst);
    }
}
```

B. What you should see

```
=== 1. Transient failure, recovers on 3rd attempt ===
      attempt 1 failed (timeout), waiting 100ms
      attempt 2 failed (timeout), waiting 200ms
      succeeded on attempt 3
      result: OK after 3 calls

=== 2. Permanent failure — should NOT retry ===
      permanent error, NOT retrying: HTTP 401
      gave up immediately (correct)

=== 3. Backoff schedule, no jitter ===
      attempt 1 failed (503), waiting 100ms
      attempt 2 failed (503), waiting 200ms
      attempt 3 failed (503), waiting 400ms
      attempt 4 failed (503), waiting 800ms      <- doubling

=== 4. Same schedule WITH jitter ===
      attempt 1 failed (503), waiting 74ms
      attempt 2 failed (503), waiting 133ms
      attempt 3 failed (503), waiting 291ms      <- randomised
      attempt 4 failed (503), waiting 512ms

=== 5. Thundering herd: 1000 clients retry at once ===
      jitter=false -> busiest 100ms bucket holds 1000 of 1000 clients
      jitter=true  -> busiest 100ms bucket holds ~205 of 1000 clients
```

Section 5 is the one to internalise. Without jitter, **all 1000 clients retry in the same 100ms window** — a synchronised wall of traffic hitting a service that just recovered. With jitter the worst bucket holds about a fifth of that. Same number of retries, spread over time instead of stacked.

C. Production — Resilience4j Retry

(**Resilience4j** is the standard Java library for resilience patterns; this config is YAML, an indentation-based settings format.)

```yaml
resilience4j:
  retry:
    instances:
      inventoryService:
        maxAttempts: 3                    # 1 initial + 2 retries
        waitDuration: 200ms
        enableExponentialBackoff: true
        exponentialBackoffMultiplier: 2
        enableRandomizedWait: true        # <- jitter
        randomizedWaitFactor: 0.5
        retryExceptions:
          - java.io.IOException
          - java.util.concurrent.TimeoutException
          - org.springframework.web.client.HttpServerErrorException   # 5xx
        ignoreExceptions:
          - org.springframework.web.client.HttpClientErrorException   # 4xx — never retry
```

```java
@Retry(name = "inventoryService", fallbackMethod = "inventoryFallback")
@CircuitBreaker(name = "inventoryService")     // order matters — see pitfall 6
public Inventory check(String sku) {
    return inventoryClient.get(sku);
}
```

Spring's own `@Retryable` (an **annotation** — a label on a method — from Spring, the main Java web framework) is an alternative if you're not using Resilience4j:

```java
@Retryable(
    retryFor = { IOException.class },
    noRetryFor = { ValidationException.class },
    maxAttempts = 3,
    backoff = @Backoff(delay = 200, multiplier = 2, random = true))
public Inventory check(String sku) { ... }

@Recover
public Inventory recover(IOException e, String sku) { return Inventory.unknown(sku); }
```

D. Implementing idempotency keys

The most important production concern, and the part usually missing from tutorials. The client sends a stable key (usually a **UUID** — a randomly generated, practically unique 128-bit ID — sent in an HTTP **header**, a key-value field alongside the request); the server guarantees one execution per key.

Client:

```java
String idempotencyKey = UUID.randomUUID().toString();   // generated ONCE, before the first attempt

executeWithRetry(() ->
    http.post("/payments")
        .header("Idempotency-Key", idempotencyKey)      // same key on EVERY retry
        .body(payment)
        .execute(),
    3, 200, 2.0, true);
```

> **The critical detail:** generate the key **outside** the retry loop. A key generated inside means each attempt looks like a brand-new request and the customer gets charged three times — which is exactly the bug the mechanism exists to prevent.

Server:

```java
@PostMapping("/payments")
public ResponseEntity<PaymentResult> pay(
        @RequestHeader("Idempotency-Key") String key,
        @RequestBody Payment payment) {

    // Atomic "insert if absent" — the DB unique constraint does the work
    Optional<PaymentResult> existing = idempotencyStore.find(key);
    if (existing.isPresent()) {
        return ResponseEntity.ok(existing.get());     // replay the original response
    }

    PaymentResult result = paymentService.charge(payment);
    idempotencyStore.save(key, result, Duration.ofHours(24));
    return ResponseEntity.ok(result);
}
```

Store keys in **Redis** (a fast in-memory key-value database) with a **TTL** (time-to-live — an expiry after which the entry is deleted), or a table with a **unique index** on the key (a database rule that rejects a second row with the same value). The **unique constraint** is what makes it safe under concurrent duplicate requests.

E. Implementation pitfalls

1. Retrying non-idempotent operations without a key. The headline risk: double charges, duplicate orders, duplicate emails.

2. Generating the idempotency key inside the retry loop. See above — silently defeats the whole mechanism.

3. Retrying 4xx errors. A 400 or 401 will fail identically every time. Always configure `ignoreExceptions`.

4. No cap on exponential backoff. Base 1s with multiplier 2 and 10 attempts ends at a **17-minute** wait. Always set a maximum.

5. No overall deadline (one time limit for the whole operation, all attempts included). Individual timeouts plus retries multiply: a 5s timeout with 3 attempts plus backoff is potentially 20 seconds. Set a budget for the whole operation:

```
resilience4j.timelimiter.instances.inventoryService.timeoutDuration: 3s
```

6. Wrong ordering of retry and circuit breaker. Resilience4j's default order is **Retry(CircuitBreaker(call))** — the breaker is *inside*, so retries happen around it and the breaker sees each attempt. That's usually what you want. If you invert it, the breaker counts a whole exhausted retry sequence as a single failure and opens far too slowly.

7. Retrying at every layer. If the HTTP client retries 3×, the service retries 3×, and the gateway retries 3×, one user request becomes **27** requests to a service that's already struggling. Pick one layer. Disable retries everywhere else explicitly — most HTTP clients have them on by default.

8. Retrying immediately with no delay. A tight retry loop against a struggling service is indistinguishable from an attack.

9. Not logging retries. If retries are invisible, a dependency degrading from 0.1% to 15% failure looks totally healthy from the outside — until it tips over. Emit a metric per retry.

Related patterns

- **Circuit Breaker** — the essential companion; stops retries becoming an attack on a downed service
- **Bulkhead** — bounds the resources retries can consume
- **Service Discovery** — retry against a *different* discovered instance
- **Saga** — compensation for when retrying isn't safe or sufficient
- **Event-Driven Architecture** — requeueing and dead-letter queues are retry in an async context

Sidecar Pattern

Category: Cross-cutting concerns **One-liner:** Attach a helper process alongside each service instance to handle concerns like logging, metrics, security, and networking — so the service itself contains only business logic.

Part 0 — Concepts you need first

What is a "cross-cutting concern"?

Functionality needed by **many parts of a system** but not part of any one part's core purpose.

Your Order Service exists to manage orders. That's its **business logic** (the code that implements what the business actually does). But it also needs to: log what it does, emit **metrics** (numeric measurements like request counts and response times), **authenticate** callers (verify who they are), **encrypt** traffic (scramble it so only the intended receiver can read it), retry failed calls, and report **traces** (records of a request's path through every service it touched). **Every service needs those**, and none of them is about orders.

Cross-cutting concerns are a problem because the obvious solutions are both bad:

- **Copy the code into every service** → duplication, and changes require touching everything
- **Put it in a shared library** (a reusable code package every service imports) → better, but see the polyglot problem below

What is a process?

A running program with its own memory space. Two processes are genuinely separate — one crashing doesn't corrupt the other's memory.

What is a container?

A package containing an application plus everything it needs to run — libraries, **configuration** (settings supplied from outside the code), the lot. It runs isolated from other containers on the same machine. **Docker** is the common tool for building them.

What is a Kubernetes Pod?

The smallest deployable unit in **Kubernetes** (the standard platform for running containers across a cluster of machines). Crucially, **a Pod can contain more than one container**, and containers in the same Pod:

- Are always **scheduled onto the same machine** together (**scheduling** = Kubernetes choosing which machine runs something)
- Share a **network namespace** (one private, isolated set of network addresses and ports) — they can talk to each other over `localhost` (the special address meaning "this same machine")
- Can share **storage volumes** (directories of files mounted into the containers)
- Are **created and destroyed together**

This is the mechanism that makes the Sidecar pattern practical. Without co-scheduling and shared networking, a "helper alongside the service" would just be another remote service.

What is a proxy?

Software that sits between two parties and relays traffic. A **transparent** proxy relays traffic without the application knowing it exists — which is exactly how production sidecars work.

What is a service mesh?

An infrastructure layer handling all service-to-service communication. Concretely, it's **a sidecar proxy deployed next to every service**, plus a central **control plane** (the management component that pushes

settings to every proxy) that configures them all. **Istio** (using **Envoy**, a high-performance open-source proxy) is the best-known example.

The polyglot problem — why shared libraries aren't enough

Polyglot means using many programming languages. Suppose you write an excellent library handling retries, metrics, and **mTLS** (mutual TLS — both sides of a connection present certificates to prove their identity, and the traffic is encrypted). Now your company has services in Java, Go, Python, and Node.

You must write and maintain **four versions**. They will drift. A bug fixed in the Java one lingers in Python for months. Adding a fifth language means a fifth implementation before that team can ship.

A sidecar solves this because it's a separate process speaking network protocols (standard rules for exchanging data, such as HTTP). It doesn't care what language the service beside it is written in.

Part 1 — The metaphor and the core idea

The name comes from a **motorcycle sidecar**: attached to and operating alongside the motorcycle, sharing the journey but remaining a distinct unit. The course also offers Batman and Robin, or Sherlock Holmes and Dr Watson — an aide that handles specific tasks, operates autonomously, and yet is part of a single larger entity.

The pattern encapsulates **modularity and separation of concerns** (building a system from independent pieces, each responsible for one job): deploy components of an application as **separate processes running alongside the main application**. Each sidecar is dedicated to a specific function and provides its service to the main application.

This lets developers **encapsulate the logic and complexity of those functions in the sidecar**, reducing the complexity of the main application.

The strength is its simplicity and modularity. Keeping each function isolated in its own environment makes it easier to develop, manage, and scale each component independently. That gives cleaner, more maintainable code — and makes it possible to **use different technologies for different tasks within the same application**.

⚠️ Part 2 — One correction to the course material

The course states that the sidecar and main application "run in the same process" and are "deployed together in the same container." **That is not how this works in practice**, and since you're using these notes as your reference, it's worth having right:

- The sidecar runs as a **separate process, in its own container**
- Both containers are **co-located in the same Kubernetes Pod** (or equivalent scheduling unit)
- They **share the Pod's network namespace** — hence `localhost` communication — and can share volumes
- They **share a lifecycle** — created, scheduled, and destroyed together

Same-process or same-container would defeat the isolation that makes the pattern valuable in the first place: if the sidecar shared a process with the app, a sidecar crash would take the app down, and you couldn't use a different language for each.

The course's other framing — **same lifespan, shares resources, communicates locally** — is correct. Everything else below holds.

Part 3 — The problem: monolithic application management

Lack of isolation

In a **monolith** (an application built and deployed as one single unit) all components are closely intertwined, so **a failure in one component can bring down the entire application**. The course's image:

all your eggs in one basket — if the basket falls, all the eggs break. This lack of **fault isolation** (containing a failure so it can't spread) makes monoliths vulnerable and risky.

Scalability — moving the mountain

Scaling a monolith is like moving a mountain. **You cannot scale a particular component or functionality; you must scale the entire application**, even if only one component needs it. This leads to unnecessary resource consumption and inefficient scaling.

Complexity — a tangled web

As a monolith grows, so does its complexity. More features mean the **codebase** (all the source code of the application) becomes a tangled web that's increasingly difficult to understand, manage, or modify. Maintenance becomes a nightmare and development slows significantly.

Technology constraint — one size does not fit all

With a monolith you're largely **stuck with the technology stack chosen at the beginning** (the **stack** is the set of languages, frameworks and databases used). Want to integrate a new technology or switch to a more efficient one? That's a mammoth task. This lack of flexibility is a significant constraint given how rapidly technology evolves.

Part 4 — The solution

Pair each service with a secondary component — a **sidecar** — that takes over some of the main service's responsibilities. The two run alongside each other and communicate directly, creating a self-contained module that's easy to manage and scale.

Flexibility. By separating the main service from its secondary functions, it becomes easier to update, modify, or replace individual components without affecting the others. To change a specific piece of functionality, you **update the relevant sidecar and leave the rest of the application untouched** — no full **redeploy** (rebuilding and releasing the whole application).

Enhanced scalability. Since each sidecar is a separate entity, you can scale each independently. Surge in user logins? Scale up the **authentication sidecar**. High load on data processing? Scale up the **data-processing sidecar**. This is more efficient and saves resources.

Fault isolation. Each sidecar is independent, so a failure in one does not affect the others. Separate baskets for each egg — if one falls, the rest are safe.

Reduced complexity. Breaking the application into self-contained modules, each with its own sidecar, makes it easier to understand, manage, and maintain. Like clearing a path through dense forest — you can finally see where you're going.

Technology freedom. The independent, flexible structure makes it possible to **use different technologies for different sidecars**, letting you take advantage of the latest advances rather than being locked in.

Part 5 — Architecture

Co-located deployment

The main application and its sidecar are deployed **together**, sharing resources and communicating efficiently. This shared environment lets them **operate as a single unit while maintaining their individuality**.

Multiple sidecars

You are not restricted to one sidecar per application. You can have **several, each addressing a specific functionality**, letting you modularise the application.

> A motorbike with several sidecars — one for extra storage, one for a passenger, one carrying navigation aids. Each serves a distinct purpose; together they make one smooth ride.


The network navigator — the sidecar as proxy

This is the most important architectural role, and the one that makes service meshes work.

The sidecar **intercepts all incoming and outgoing network traffic** from the main application, effectively acting as a **proxy**. This means it can handle:

- **Load balancing** (spreading requests across several instances of a service — see System Design Fundamentals)
- **Circuit breaking** (stopping calls to a service that keeps failing) *(see Circuit Breaker)*
- **Security** — including mutual TLS
- **Service discovery** (finding where other services are currently running) *(see Service Discovery)*

...leaving the main application **free to focus on delivering the primary service**.



> **Why "intercepts" is the key word.** The application doesn't call the sidecar and doesn't know it exists. It makes what it thinks is a normal **HTTP** call (an ordinary web request); traffic is transparently routed through the sidecar. That's what allows you to add mTLS, retries, and **tracing** (recording each request's path across services) to an application **without changing a line of its code** — even for an application whose source you can't easily modify.

Shared lifespan

The sidecar and main application, while separate entities, **share the same lifespan** — created, deployed, and destroyed together. This ensures the main application **always has its sidecar at its side**, ready to serve.

That guarantee matters. If the sidecar could be scheduled elsewhere or restarted independently, the application would need to handle its absence — reintroducing exactly the complexity you were removing.

Part 6 — Worked example

The main application — a Spring Boot REST service

(**Spring Boot** is a popular Java framework for building web services quickly; a **REST** service answers plain HTTP requests on URLs such as `/api`.)

```java
@SpringBootApplication
@RestController
public class MainApplication {

    public static void main(String[] args) {
        SpringApplication.run(MainApplication.class, args);
    }

    @GetMapping("/api")
    public String getData() {
        return "Hello, Sidecar!";
    }
}
```

A simple web service returning a string whenever `/api` is hit (each such URL is an **endpoint**).

The sidecar — a logging helper

```java
@SpringBootApplication
@RestController
public class LoggingSidecar {

    public static void main(String[] args) {
        SpringApplication.run(LoggingSidecar.class, args);
    }

    @GetMapping("/log")
    public String logRequest() {
        System.out.println("Request received at /api endpoint");
        return "Logged!";
    }
}
```

This sidecar prints a log message every time `/log` is hit. Note it's also a Java application here — but that's incidental, and in practice it usually wouldn't be.

Wiring them together

```java
@GetMapping("/api")
public String getData() {
    ResponseEntity<String> response =
        restTemplate.getForEntity("http://localhost:8081/log", String.class);
    System.out.println("Response from sidecar: " + response.getBody());
    return "Hello, Sidecar!";
}
```

`RestTemplate` is Spring's utility for calling RESTful services. Now whenever `/api` is hit, the main application calls the sidecar's `/log` endpoint, the sidecar logs the request, and the main application continues processing.

Notice `localhost:8081` — that's the shared network namespace at work. The main app doesn't need service discovery to find its sidecar; it's always right there at a known local port.

> ⚠️ **This example is pedagogically useful but architecturally backwards.** The main application *explicitly calling* the sidecar defeats the central benefit — the application now knows about the sidecar, contains code **coupling** it to the sidecar (making it depend on the sidecar's details), and would break if the sidecar changed. Real sidecars are **transparent**, intercepting traffic without the application's knowledge (as Istio and Envoy do below). Read this as "how two co-located processes communicate," not as the intended usage pattern.

The deployment factor

The course is explicit that the Java example doesn't cover deployment. In production you would:

- Use a container platform like **Docker** to package the main application and sidecar

- Use **Kubernetes** to **orchestrate** deployment and scaling (automatically start, place, restart and scale the containers)

Kubernetes has **built-in support for sidecar containers**, making it the natural platform for implementing this pattern.

Part 7 — Performance implications

"Does adding a sidecar to my application slow things down?" A legitimate question. It's a trade-off worth understanding rather than dismissing.

Resource cost

Each sidecar is an **additional process** running alongside your main application. That means more **CPU** (processor time), more memory, more network **bandwidth** (data-transfer capacity).

Individually, the sidecar's resource usage may not be substantial. **But multiply that by the number of instances of your application.** With hundreds or thousands of instances each carrying its own sidecar, **cumulative resource usage becomes significant**.

> Made concrete: a sidecar using 100 MB of memory across 1,000 pods is 100 GB of RAM spent on infrastructure rather than application work. That's a real budget line, and it's the most common objection to adopting a service mesh.

Latency

Having a sidecar introduces an **additional network hop** (one more trip between two programs over the network), adding **latency** (delay per request), since requests may go through the sidecar before reaching the main application or an external service.

The latency introduced is **usually negligible** — it's a **loopback** connection (traffic that never leaves the machine) within the same Pod, not a real network traversal. But in **high-performance, low-latency systems this could become an issue**, and it's worth measuring rather than assuming.

The verdict

The slight performance impact often **pales in comparison to the benefits**. The sidecar enhances functionality and maintainability and improves the overall development and operational experience. You need to balance these trade-offs for your situation.

Part 8 — Special considerations

1. Sidecar and main application versioning

Versioning becomes more complex. You must manage versions of **both** the main application and the sidecar. What if a new sidecar version is **incompatible with an older application version**, or vice versa? How do you **roll out** updates (release them gradually) across a **fleet** (all the running instances)? These questions need answering before you adopt the pattern, not after.

2. Shared resources

Sidecars share resources with the main application — **network and disk**. It's important the sidecar **doesn't hog these resources**, leaving nothing for the main application. Manage this using **resource limits and quotas at the container level** (hard caps on the CPU and memory each container may use).

> Without limits, a misbehaving sidecar — say, one **buffering** logs (holding them in memory to send later) during an **outage** (period of unavailability) of the log collector — can starve the very

> application it's meant to support.

3. Security

Sidecars often need **similar security permissions to the main application** to perform their tasks. This **increases the attack surface** (the total set of places an attacker could try to break in) and needs careful consideration when designing your sidecar.

A sidecar handling mTLS holds **private keys** (the secret half of an encryption key pair; whoever has it can impersonate the service). A sidecar collecting logs can read application output. Compromising the sidecar can be as valuable to an attacker as compromising the application.

4. Complexity

Sidecars solve many problems, but they **also add complexity**. Developers and operators must now understand and manage **multiple parts instead of a single application**. Debugging a request means reasoning about the application *and* the proxy in front of it.

> The pattern is not a one-size-fits-all solution. Like any architectural pattern it has strengths and weaknesses, and its effectiveness depends on your specific use case.

Part 9 — Use cases

Monitoring and metrics collection

You're running an application with multiple instances and want metrics from each. **Embedding monitoring code in each application would make things complex.** A sidecar handles metrics collection, leaving your application code clean and focused on core functionality.

Logging

A sidecar can **collect logs from the main application and forward them to a central logging system**. This abstracts away logging complexity, making the application easier to manage — and means changing your log destination doesn't require touching any application.

Security and authentication

Instead of embedding security and authentication logic into your main application, **delegate it to a sidecar**. This simplifies the application and makes security measures **more consistent and easier to update** — you patch one sidecar image rather than auditing dozens of services.

Networking features

Networking is complex. A sidecar can handle **service discovery, connection pooling, circuit-breaking, intelligent routing** (**connection pooling** = keeping open connections ready for reuse instead of opening a new one per request), and more, letting your application focus on business logic without worrying about networking intricacies.

> The unifying test: **is this concern identical across all your services, and unrelated to what any of them actually does?** If yes, it's a sidecar candidate.

Part 10 — System design examples

Microservices architecture

Each microservice, as a main application, can have a sidecar providing **ancillary** (supporting, secondary) services such as logging, monitoring, and service discovery.

> Picture a fleet of ships, each ship a microservice. The sidecars are little boats accompanying each ship, helping with navigation, communication, and maintenance — while the ships focus on their main task.

Kubernetes and Istio — the canonical example

Istio is a service mesh for Kubernetes, and it uses this pattern extensively. Istio deploys a **sidecar proxy — Envoy — alongside each service** to:

- Handle **all network communication**
- **Enforce policies**
- **Collect telemetry data** (metrics, logs and traces sent automatically from running software)

> Picture a busy highway system where each car (service) has a dedicated assistant (the Envoy sidecar) for navigation, communication, and safety — enabling the driver to concentrate on driving.

This is the pattern at its purest. The application code contains **zero** networking, retry, mTLS, or **observability** logic (code that makes the system's internal behaviour visible to operators); all of it lives in infrastructure, configured centrally and applied uniformly.

Part 11 — Sidecar vs. shared library

The real decision most teams face:

	Shared library	Sidecar
Languages	One per language, maintained separately	One, language-agnostic
Upgrade	Rebuild and redeploy every service	Update the sidecar image
Runtime cost	Negligible — same process	An extra process per instance
Latency	None	A local hop
Failure isolation	A library bug crashes the app	Sidecar can fail separately
Best when	One language, few services, latency-critical	Polyglot, many services, frequent policy changes

Rule of thumb: with a single language and a handful of services, a library is simpler and cheaper. With several languages, many services, or a need to change cross-cutting behaviour without redeploying everything, the sidecar earns its overhead.

Part 12 — Common beginner misconceptions

"The sidecar and app are the same container." No — separate containers in the same Pod. See Part 2.

"The app calls the sidecar." In the course's toy example, yes. In real deployments, no — the sidecar transparently intercepts traffic. That transparency is the whole value.

"A sidecar is a microservice." No. A **microservice** (a small, independently deployed service) serves many clients and owns a **domain** (an area of the business, such as orders or payments). A sidecar serves exactly **one** application instance and owns no domain — its lifecycle is bound to its host.

"Sidecars are only for service meshes." Meshes are the most famous use, but **log shippers** (programs that forward log files to a central store), metrics **agents** (small background collectors), config reloaders, and **secret-fetchers** (programs that fetch passwords and keys from a vault) are all sidecars.

"It's free because it's just localhost." It costs one process worth of CPU and memory **per instance**, which at scale is the main reason teams hesitate.

"You need Kubernetes." Kubernetes makes it easy with Pods, but the pattern predates it — any system that can co-schedule two processes with shared networking works.

Part 13 — Check your understanding

1. What makes a concern a "cross-cutting" one?
2. Why doesn't a shared library solve cross-cutting concerns in a polyglot organisation?
3. What Kubernetes feature makes the pattern practical, and which two properties of it matter most?
4. Why is "intercepts" a more important word than "calls"?
5. What's the main objection to adopting a service mesh at scale?
6. When is a shared library the better choice?

(Answers: 1 — it's needed by many components but isn't the core purpose of any of them; 2 — you'd need a separate implementation per language, and they inevitably drift; 3 — the Pod, because it co-schedules containers on one machine and gives them a shared network namespace and lifecycle; 4 — interception means the application needs no knowledge or code changes, which is what lets you add mTLS and tracing to services you can't modify; 5 — cumulative resource cost, one extra process per instance across thousands of instances; 6 — a single language, few services, and latency-critical paths.)

Part 14 — Interview soundbite (30 seconds)

> "The sidecar pattern attaches a helper process alongside each service instance to handle cross-cutting concerns — logging, metrics, auth, networking — so the service itself contains only business logic. It's co-located: a separate container in the same Kubernetes Pod, sharing the network namespace and lifecycle, so they communicate over localhost. The key role is acting as a proxy that transparently intercepts all inbound and outbound traffic, which lets it do load balancing, circuit breaking, mTLS, and service discovery without the application knowing it exists. That transparency is the point — you can add mTLS and distributed tracing to a service without changing a line of its code. The canonical example is Istio, where an Envoy sidecar runs next to every service and the app has no networking code at all. The big advantage over a shared library is that it's language-agnostic, so a polyglot estate gets consistent behaviour and you can upgrade policy without redeploying every service. The costs are real though: one extra process per instance multiplies across thousands of pods, so a sidecar using 100 MB across a thousand pods is 100 GB of RAM; there's an extra local hop; you now version the sidecar against the app; and the sidecar needs permissions that widen your attack surface."

Part 15 — Implementation

A. Runnable demo

Full source: `demos/SidecarDemo.java`

```
cd demos && ./gradlew runCh09
```

The whole point in two class definitions. Before:

```
String handleRequest(String payload) {
    requestCount.incrementAndGet();                    // metrics
    System.out.println("[app] logging inbound request"); // logging
    if (!payload.startsWith("signed:")) return "401";    // security
    String result = businessLogic(payload);              // <- the only real work
    // ... emit latency metric
}
```

After:

```
static class CleanApp {
    String handleRequest(String payload) {
        return "order-created:" + payload;               // business logic ONLY
    }
}
```

Everything removed from the app now lives in the sidecar, which **intercepts** rather than being called:

```
String handleInbound(String rawRequest, String clientCert) {
    if (!"valid-cert".equals(clientCert)) {
        return "403 Forbidden";                          // app never invoked
    }
    String response = app.handleRequest(rawRequest);      // plain call, no plumbing
    // ... record latency
}
```

B. What you should see

```
=== 3. mTLS enforced by the sidecar ===
  -> 403 Forbidden
  >> rejected before the application was ever invoked

=== 4. Retry + backoff, also in the sidecar ===
    [sidecar] upstream failed (connection reset), retrying
    [sidecar] upstream ok on attempt 3
  upstream was actually called 3 times; the app asked once
  >> CleanApp contains no retry code whatsoever

=== 5. Telemetry collected without any app instrumentation ===
      requests_ok        1
      requests_rejected  1
      upstream_retries   2

=== 7. The cost: resource multiplier ===
      1,000 pods x 100MB sidecar = 100,000 MB (97.7 GB) of RAM
      5,000 pods x 100MB sidecar = 500,000 MB (488.3 GB) of RAM
```

Section 4 is the pattern in one line: the **upstream** (the service being called) was called three times; the application asked once. Retry, backoff, and failure handling happened entirely outside the code you wrote.

Section 7 is the honest counterweight — at a thousand pods you're spending ~98 GB of RAM on infrastructure. That's the number that shows up in the meeting where someone asks whether the mesh is worth it.

C. Production — Istio

Injection — label the **namespace** (here a Kubernetes namespace: a named group of resources within a cluster) and every pod gets an Envoy sidecar automatically. `kubectl` is the Kubernetes command-line tool:

```
kubectl label namespace production istio-injection=enabled
```

Your **Deployment** (the Kubernetes object that describes which containers to run and how many copies) is unchanged; the sidecar appears at **admission time** (the moment Kubernetes accepts the object, when it can modify it):

```
spec:
  containers:
    - name: order-service          # your app - you wrote this
      image: order-service:1.4.2
    # - name: istio-proxy          # injected automatically, you did NOT write this
```

mTLS across the whole mesh — no application code, no **certificate** handling (a certificate is a signed file proving an identity):

```
apiVersion: security.istio.io/v1beta1
kind: PeerAuthentication
metadata:
  name: default
  namespace: production
spec:
  mtls:
    mode: STRICT       # every service-to-service call is encrypted and authenticated
```

Retries, timeouts, and circuit breaking as configuration: (A `VirtualService` sets routing rules; a `DestinationRule` sets traffic policy for a destination. **Outlier detection** temporarily *ejects* — stops routing to — instances that keep returning errors.)

```
apiVersion: networking.istio.io/v1beta1
kind: VirtualService
metadata:
  name: inventory
spec:
  hosts: [inventory]
  http:
    - timeout: 3s
      retries:
        attempts: 3
        perTryTimeout: 1s
        retryOn: 5xx,reset,connect-failure
      route:
        - destination: { host: inventory }
---
apiVersion: networking.istio.io/v1beta1
kind: DestinationRule
metadata:
  name: inventory
spec:
  host: inventory
  trafficPolicy:
    connectionPool:
      tcp:  { maxConnections: 100 }
      http: { http1MaxPendingRequests: 50, maxRequestsPerConnection: 10 }   # a bulkhead
    outlierDetection:                       # this IS a circuit breaker
      consecutive5xxErrors: 5
      interval: 10s
      baseEjectionTime: 30s
      maxEjectionPercent: 50
```

> Read that last block carefully: **you just configured Bulkhead, Retry, and Circuit Breaker in YAML, for every service, in every language, without touching application code.** That is the argument for a service mesh in a single **manifest** (a YAML file describing desired Kubernetes resources).

Non-mesh sidecars you'll meet just as often (**Fluent Bit** is a lightweight log shipper; the Cloud SQL proxy opens a secure **tunnel** — an encrypted pass-through connection — to a Google Cloud database):

```
containers:
  - name: app
    image: my-app:1.0
    volumeMounts: [{ name: logs, mountPath: /var/log/app }]
  - name: log-shipper                    # sidecar: tails and ships logs
    image: fluent-bit:2.2
    volumeMounts: [{ name: logs, mountPath: /var/log/app }]
  - name: cloud-sql-proxy                # sidecar: secure DB tunnel
    image: gcr.io/cloud-sql-connectors/cloud-sql-proxy:2.8
volumes:
  - name: logs
    emptyDir: {}                         # shared between the two containers
```

Kubernetes native sidecars (1.29+) — solves the classic startup/shutdown ordering problem (an **initContainer** normally runs to completion before the app starts; `restartPolicy: Always` turns it into a long-running sidecar):

```
initContainers:
  - name: istio-proxy
    image: istio/proxyv2
    restartPolicy: Always        # <- makes it a true sidecar: starts first, stops last
```

D. Implementation pitfalls

1. The app starting before the sidecar is ready. The classic failure: your app makes its first outbound call, the proxy isn't up, and it fails at startup. Use native sidecars (`restartPolicy: Always` on an initContainer), or `holdApplicationUntilProxyStarts: true` in Istio.

2. The sidecar stopping before the app finishes. The mirror image at shutdown — **in-flight** requests (ones already started but not finished) fail because the proxy died first. Native sidecars fix this too.

3. No resource limits on the sidecar. An unbounded proxy can starve the application it exists to serve. Always set them (`100m` = one tenth of a CPU core; `128Mi` = 128 mebibytes of memory):

```
annotations:
  sidecar.istio.io/proxyCPU: "100m"
  sidecar.istio.io/proxyMemory: "128Mi"
```

4. Adopting a full mesh for three services. The resource multiplier and operational complexity are fixed costs. Below roughly a dozen services in one or two languages, a shared library is cheaper and simpler. Be able to justify the mesh.

5. Forgetting the sidecar is in the network path when debugging. A 503 (the HTTP status code for "service unavailable") may come from Envoy, not your service. Learn to read the proxy's logs and its response flags before blaming application code.

6. Duplicating retries in app and mesh. If your HTTP client retries 3× and the mesh retries 3×, you get 9 requests. Pick one layer — usually the mesh — and disable the other.

7. Assuming mTLS means you're done with authorization. mTLS proves *who* is calling. It does not say *what they may do* — that's **authorization**. You still need `AuthorizationPolicy` resources.

Related patterns

- **Service Discovery** — meshes absorb discovery into the sidecar entirely
- **Circuit Breaker**, **Retry**, **Bulkhead** — all commonly enforced in the sidecar rather than in application code
- **API Gateway** — the gateway handles north-south (external, into and out of the system) traffic; the mesh of sidecars handles east-west (internal, service-to-service)
- **Config Externalization** — a sidecar can fetch config and expose it locally to the app

Saga Pattern

Category: Data consistency / distributed transactions **One-liner:** Break a business transaction that spans several services into a sequence of local transactions, each with a compensating action that undoes it — achieving eventual consistency without **distributed locks** (locks held across several machines at once so no one else can change the data).

Part 0 — Concepts you need first

What is a transaction?

A **transaction** is a single logical operation made up of one or more data-manipulation steps, which **succeed or fail together as a unit**.

The classic example is a bank transfer: subtract £100 from account A, add £100 to account B. If only the first step runs, £100 has vanished. The two steps must be **one indivisible unit**.

What is ACID?

The four properties a traditional database transaction guarantees.

Atomicity — the transaction is treated as a single unit that either **succeeds completely or fails completely**. If any part fails, the whole thing fails and the database is left unchanged. *"Atomic" means indivisible — you can't have half of it.*

Consistency — the transaction brings the database from one **valid state to another**, respecting all its rules and constraints.

Isolation — **concurrent** transactions (ones running at the same time) leave the database in the same state as if they had run **one after another**. Your half-finished transaction is invisible to everyone else.

Durability — once **committed** (finalised and saved), it **stays committed**, even if the machine loses power a millisecond later.

Together: once a transaction completes, you can be confident it **either fully occurred or didn't occur at all**.

What is a "rollback"?

Undoing a transaction's changes, returning the database to its state before the transaction began. In a single database this is automatic and free — the database keeps a log and reverses it.

This is the capability you lose when the transaction spans services, and replacing it manually is what the Saga pattern is about.

What is a database lock?

While a transaction modifies a row, the database **locks** it so nobody else can modify it simultaneously. That's what makes isolation work.

The relevant consequence: **locks are held until the transaction commits.** A short transaction holds a lock for milliseconds. A transaction waiting on a network call to another continent holds it for seconds — during which nobody else can touch that row.

What is "database per service"?

A core **microservices** principle (microservices = an application built as many small, independently deployed services): **each service owns its own database**, and no other service reads or writes it directly. If Order Service needs inventory data, it *asks* Inventory Service; it does not query Inventory's tables.

This gives independence — Inventory can change its **schema** (the structure of its tables and columns) freely — but it's precisely what removes the option of one database transaction spanning both.

What is eventual consistency?

A model where the system **may temporarily be in an inconsistent state**, but will **eventually converge** to a consistent one.

Strong consistency: the moment your transfer completes, every observer sees both accounts updated. Eventual consistency: for a brief window, one observer might see the debit but not yet the credit — though it will resolve shortly.

Distributed systems (systems spread across many machines talking over a network) trade strong for eventual consistency because strong consistency across a network requires locks and coordination that cost **availability** (being able to answer requests at all) and speed. See System Design Fundamentals for consistency models and the CAP trade-off.

Part 1 — The problem

It works fine in a monolith

An e-commerce checkout: adjust inventory, create the order, take payment. In a **monolithic** application (built and deployed as one unit) with a single database, this is one ACID transaction. If payment fails, the database rolls back inventory and the order automatically. **You get atomicity for free.**

Why it breaks in microservices

Coordination. Inventory Service, Order Service, and Payment Service run on different servers, each with its **own database**. Enforcing atomicity means undoing all previous steps when any step fails — and **coordinating that rollback across independent services is genuinely challenging**. There is no shared transaction log, no single database to tell "undo everything."

Network latency (the delay each network call adds). Services may be distributed across different geographic locations, so a transaction can take a significant amount of time. **Holding resources locked for that long is impractical** and causes performance problems.

> Made concrete: a database transaction normally holds locks for a few milliseconds. A distributed transaction across three services with network calls between them might hold them for **several seconds**. During that window, every other customer trying to buy the same product is blocked. At any real traffic level, the system grinds to a halt.

The conclusion: the traditional transaction model isn't designed for the complexity and demands of distributed systems. ACID's principles, well-intentioned as they are, **don't translate to a world where services operate independently and communicate over networks.**

Part 2 — The solution

A saga is a sequence of local transactions.

Each local transaction:

1. **Updates its own database** (a normal, fully ACID transaction — just local)
2. **Publishes an event** (sends out a message announcing what just happened, for any interested service to react to) that triggers the next local transaction in the saga

If a local transaction **fails because it violates a business rule** (a rule of the domain, such as "stock can't go below zero"), the saga executes a series of **compensating transactions** that undo the changes made by the preceding local transactions.

Rather than trying to enforce strict consistency as ACID does, Saga **acknowledges** that distributed transactions span multiple services and databases, and opts for the more practical **eventual consistency** model.

The guarantee it actually gives

Either **all transactions complete**, or **compensating transactions run to roll back** the ones already executed. The system maintains integrity through explicit compensation rather than automatic rollback.

This makes sagas ideal for **long-lived, high-level business transactions spanning multiple microservices**, across globally distributed and **highly available** (designed to stay up nearly all the time) databases.

The cost: designing sagas is complex. They require intricate coordination between participating services and **extensive error handling**. You are hand-writing what the database used to do for you.

The metaphor worth keeping

> If your distributed system is a city and each service is a building, **ACID transactions are the internal wiring of each building** — ensuring electricity flows where needed inside. But when you want to connect two buildings, you can't just extend the internal wiring; it wouldn't be safe or efficient. **You need a power line.** The Saga Pattern is that power line — connecting the buildings so they work together, while maintaining safety and consistency.

Part 3 — The two types

Choreography — decentralized

Every local transaction **publishes domain events** (messages describing a business fact, like `OrderCreated`) that trigger local transactions in other services. **There is no central coordination.** Each service produces events and listens to other services' events, deciding for itself whether to act.

> An orchestra with **no conductor** — each musician listens to the other instruments and plays their part in harmony. Or an ant colony, where each ant knows its tasks and performs them without being told.

What it looks like in practice: Order Service publishes `OrderCreated`. Payment Service is listening, sees it, charges the customer, publishes `PaymentCompleted`. Inventory Service is listening for that, reserves stock, publishes `StockReserved`. Nobody is in charge; the flow emerges from who **subscribes** to (registers interest in) what.

Orchestration — centralized

A central **saga orchestrator** is responsible for executing the saga's steps. It tells each participant when to execute its local transaction.

> The same orchestra, **with** a conductor guiding all the musicians to create a symphony. Or a busy airport where an air traffic controller tells each plane when to take off and land.

What it looks like in practice: the orchestrator calls Order Service, waits, calls Payment Service, waits, calls Inventory Service. If Inventory fails, the orchestrator calls the compensations in reverse. The whole flow is readable in one place.

Choosing between them

	Choreography	Orchestration
Coordination	None — fully decentralized	Central orchestrator
Service autonomy	Higher	Lower — services do as told
Visibility of the flow	Poor — scattered across services	Good — in one place
Error handling	Harder	Easier
Coupling (how much one part depends on another)	Services coupled to events	Services coupled to the orchestrator
Best for	**Simple** transactions	**Complex** transactions

The rule of thumb the course gives: consider the complexity of your business transaction. If it's simple, choreography is a good option as it requires less coordination. As it becomes more complex, **orchestration provides better visibility and control**.

> The practical failure mode of choreography: with six services each reacting to events, **nobody can answer "what happens when a customer places an order?"** without reading six **codebases** (separate bodies of source code). The business process exists but is written nowhere. That's why complex flows migrate to orchestration.

Part 4 — Architecture

Local transactions — the backbone

A saga is composed of multiple local transactions, each executed **within a single service and its corresponding database**. Each carries its own responsibilities, but strung together they work toward maintaining data consistency across the system.

Every local transaction has an associated compensating transaction capable of undoing its changes.

Compensating transactions

If a local transaction fails, the saga executes compensating transactions for the previously successful ones, bringing the system back to a consistent state.

> Walking along a path and realising you've gone the wrong way — you retrace your steps back to where you took the wrong turn.

The Saga Log

To track the saga's progress and state, a **saga log** is maintained. It records **every local transaction and compensating transaction executed** in the saga.

Its purpose: if the saga is interrupted — a service crashes mid-flow — the log lets it **resume from where it left off**, or know exactly which compensations to run.

> Hansel and Gretel's breadcrumb trail — if you get lost (a system failure), follow the breadcrumbs (the saga log) back home (a consistent state).

Database per service

Each service **owns its database**, ensuring the failure of one doesn't directly impact others. This prevents a **single point of failure** (one component whose failure brings everything down) and makes the system more robust and reliable.

> A team of rock climbers, each with their own safety rope. If one slips, their rope catches them without pulling the rest down.

Eventual consistency

The ultimate goal. The system **may pass through inconsistent states**, but will **eventually reach a consistent one**.

> Juggling: at any given moment some balls are in the air, but a skilled juggler ensures all get handled correctly without dropping any.

Part 5 — Worked example: online shopping (orchestration)

The scenario: you add items to your cart and check out, creating an order. The Inventory Service checks whether items are available. If yes, it updates inventory and the order completes. If not, the order is cancelled.

The services — each with its own database

```
public class OrderService {
    private OrderDatabase orderDatabase = new OrderDatabase();

    public void createOrder(Order order) {
        orderDatabase.save(order);
    }

    public void cancelOrder(String orderId) {
        // COMPENSATING TRANSACTION for createOrder
    }
}
```

```
public class InventoryService {
    private InventoryDatabase inventoryDatabase = new InventoryDatabase();

    public boolean checkAndReduceInventory(Order order) {
        // local transaction — returns false if stock is insufficient
    }

    public void addBackInventory(Order order) {
        // COMPENSATING TRANSACTION for checkAndReduceInventory
    }
}
```

Notice the structure — this is the pattern in miniature. Each service has its **own database** (`OrderDatabase`, `InventoryDatabase`), and each forward operation is **paired with an inverse**:

Forward action	Compensating action
`createOrder`	`cancelOrder`
`checkAndReduceInventory`	`addBackInventory`

That pairing *is* the Saga pattern. Everything else is plumbing to invoke them in the right order.

The orchestrator

```
public class OrderOrchestrator {
    private OrderService orderService = new OrderService();
    private InventoryService inventoryService = new InventoryService();

    public void processOrder(Order order) {
        orderService.createOrder(order);

        if (!inventoryService.checkAndReduceInventory(order)) {
            orderService.cancelOrder(order.getId());   // compensate
        }
    }
}
```

Reading it: create the order first. Then attempt to check and reduce inventory. If that returns `false` — insufficient stock — **undo the order** by cancelling it.

The forward path and the compensation path are both visible in one method. That readability is orchestration's main selling point.

Handling mid-saga failures

The course raises the obvious question: *what if a service fails partway through?*

That's what the **Saga Log** is for. You expand the services to record each step. If a service fails, consult the log to see where it left off and execute the necessary compensating transactions.

> Notice this example has **no saga log at all**. If the process crashes between `createOrder` and `checkAndReduceInventory`, the order exists forever in a limbo state with no inventory reserved and nothing to fix it. That's why real implementations persist saga state before every step.

What the example is and isn't

It's a basic illustration. A real application involves more services, more complexity, and more failure modes — no retries, no **asynchronous messaging** (sending messages without waiting for a reply), no log here. But the value of the pattern holds: it lets you **split a large transaction into manageable, independent parts that can be executed and compensated for separately.**

Part 6 — Issues and considerations

Complexity

Splitting a large transaction into several smaller ones ensures consistency but **adds complexity**. Each service must now handle **both** its local transaction **and** provide a compensating transaction.

The course's concrete difficulty: what happens if a **discount was applied** to the order, and the order then gets cancelled because items were unavailable? The Order Service's compensating transaction must handle unwinding the discount too — perhaps returning a single-use voucher to the customer's account. Complexity creeps in quickly.

The pattern requires **careful design and implementation to avoid creating a tangled web of services.**

Longer latency

In a distributed transaction, **each service call is a network call**, and network calls are slower than local ones. Sagas therefore have **longer latency than traditional transactions**.

In a monolith, placing an order and updating inventory happens quickly inside a single database transaction. With a saga, these operations happen over the network, introducing delay.

Application consistency — not just data consistency

This is a subtle point and the most important one in the chapter.

Saga ensures **data** consistency by executing compensating transactions. But what about the **business process**?

> If the inventory check fails, the order gets cancelled. **But from a business perspective, cancelling an order is not the same as never having placed it.**

The customer may have already received a confirmation email. There's an **audit record** (a permanent log entry kept for accountability) showing an order existed. **Analytics** (the reporting system) counted it. A warehouse worker may have seen it on a screen.

Compensation is not time travel. It gets the data back to a consistent state, but it cannot un-happen the visible intermediate state. These considerations must be thought through when designing the saga.

Idempotency

An operation could **fail after executing but before reporting success**. In that case it may be retried — so the operations must be **idempotent** (performing them multiple times yields the same result as once).

The example: if `checkAndReduceInventory` reduces inventory but fails before reporting success, a retry must **not reduce the inventory a second time**. So that method needs to be idempotent — typically by recording the **saga ID** (a unique identifier for one run of the saga) and refusing to apply the same operation twice. *(See Retry for idempotency keys.)*

Increased load

Each service must maintain a **Saga Log** to track the saga. That means **extra read and write operations for every service**, increasing **load** (the amount of work the service must handle) and potentially slowing response times. The Order Service now handles orders *and* manages its saga log.

It's a trade-off

As with most things in software architecture, this is about balance. Would you choose consistency over complexity, or speed over distributed transactions? Understanding the trade-offs is what lets you decide well.

Part 7 — Use cases

E-commerce systems

Order placement is a textbook distributed transaction. An **Order service** creates the order, a **Payment service** charges the customer, an **Inventory service** checks and reduces stock.

If the inventory check fails, the order must be cancelled **and the customer's payment refunded**. That refund is a compensating transaction — and note it's not a rollback. The charge really happened and really appears on the customer's statement; the refund is a second, separate movement of money.

Travel booking systems

Booking a trip involves reserving a flight, booking a hotel, and perhaps renting a car. These need to **succeed together or fail as a whole**. But they are **independent services, possibly owned by different companies**.

> This is the clearest case for Saga. There is no shared database — you cannot possibly run one ACID transaction across an airline, a hotel chain, and a car rental firm. Compensation (cancel the flight, cancel the hotel) is the *only* available mechanism.

Part 8 — System design examples

Online food delivery

When a user places an order, several steps are initiated: the order is created, the restaurant confirms it, a delivery partner is assigned, and payment is processed.

But what if the restaurant runs out of an item? The order needs to be cancelled and the payment refunded. Saga maintains data consistency across services, handles the failure scenario gracefully, and keeps the user experience seamless.

Internet banking

A user transfers money from savings to checking. The transaction involves two operations — **debiting savings** and **crediting checking**. They must happen in unison; if one fails, the other must not proceed.

> Without the Saga Pattern, a failure in the crediting operation could lead to **money disappearing into thin air** — debited from one account and never arriving in the other.

Part 9 — Saga vs. two-phase commit (2PC)

Not in the course, but you'll be asked to compare them.

2PC is the traditional way to make a transaction atomic across multiple databases. A **coordinator** (the component running the protocol) asks every participant "can you commit?" (phase 1), and if all say yes, tells them all "commit now" (phase 2).

	2PC	Saga
Consistency	Strong (genuinely ACID)	Eventual
Locks	Holds locks across all participants until commit	No distributed locks
Availability	**Blocks** if the coordinator fails mid-protocol	Stays available
Rollback	Automatic	Manual — you write the compensating logic
Suits	Short transactions in one trust domain (systems run by one organisation that trust each other)	Long-lived, cross-service, cross-company

Why microservices generally avoid 2PC: it holds locks for the duration of the whole distributed operation (the very problem described in Part 1), and if the coordinator dies between phases, participants are left holding locks with no instruction — a genuinely stuck system. It also requires every participant to support the protocol, which external companies won't.

Part 10 — Common beginner misconceptions

"A compensating transaction is a rollback." No. A rollback erases history; a compensation is a **new forward action that offsets the previous one**. The refund appears on the statement alongside the charge. Both are real.

"Every step can be compensated." Some can't. You cannot un-send an email, un-ship a package, or un-launch a rocket. For those, either put them **last** in the saga, or design a real-world compensation (a "please ignore that email" follow-up).

"Sagas give you ACID across services." They explicitly don't. You give up isolation entirely — other transactions **can see** your half-finished saga. That's the price of avoiding distributed locks.

"Choreography is simpler, so always start there." It's simpler for two or three services. Beyond that the invisible business process becomes a serious maintenance problem.

"The orchestrator is a single point of failure, so choreography is safer." The orchestrator can be made highly available and its state persisted. Choreography's risk isn't availability — it's comprehensibility.

"Eventual consistency means the data might just be wrong." No — it means there's a *window* during which observers may see intermediate state. It converges. The design question is whether your business can tolerate that window.

Part 11 — Check your understanding

1. Why can't you use one ACID transaction across three microservices?
2. Why is holding database locks across a distributed transaction impractical?
3. What is the pairing that defines the Saga pattern?
4. Why is "cancelling an order is not the same as never placing it" an important point?
5. Why must saga steps be idempotent?
6. Why does travel booking make the strongest case for Saga?

*(Answers: 1 — each service owns its own database, so there's no single **transaction manager** (the component that coordinates commit and rollback) or shared log to coordinate commit and rollback; 2 — the transaction spans network calls taking seconds, during which locked rows block every other user; 3 — each forward local transaction paired with a compensating transaction that undoes it; 4 — Saga restores data consistency but cannot undo visible side effects like confirmation emails and audit records, so the business process must account for the intermediate state; 5 — a step can succeed but fail before reporting success, then be retried, and must not apply its effect twice; 6 — the participants are separate companies, so a shared database transaction is not merely difficult but impossible.)*

Part 12 — Interview soundbite (30 seconds)

> "Saga solves distributed transactions when ACID can't cross service boundaries. Each service owns its own database, so there's no shared transaction manager to coordinate a commit — and holding locks across network calls for seconds would block every other user anyway. Instead you break the business transaction into a sequence of local transactions, each paired with a compensating transaction that undoes it. If step three fails, you run the compensations for steps two and one. You get eventual consistency rather than immediate consistency, and you give up isolation completely — other transactions can see your half-finished saga. There are two flavours: choreography, where each service emits events others react to, which is decentralized and fine for simple flows but scatters the business process across six codebases so nobody can read it; and orchestration, where a central coordinator drives the steps, giving much better visibility and error handling for complex flows. A saga log persists progress so you can resume or compensate after a crash. The classic examples are e-commerce checkout — order, payment, inventory, with a refund as compensation — and travel booking across flight, hotel, and car from different companies, where a shared transaction is simply impossible. The hard parts are that steps must be idempotent, since a step can succeed but fail to report success and then get retried, and that compensation isn't rollback: the refund is a second real movement of money, and cancelling an order isn't the same as never placing it, because the confirmation email already went out."

Part 13 — Implementation

A. Runnable demo

Full source: `demos/SagaDemo.java`

```
cd demos && ./gradlew runCh10
```

Compensation driven by the log, in reverse order:

```
void compensate(String sagaId) {
    for (String step : log.stepsNeedingCompensation(sagaId)) {   // newest first
        switch (step) {
            case "reserveStock"  -> inventory.release(sagaId);
            case "chargePayment" -> payments.refund(sagaId);
            case "createOrder"   -> orders.cancelOrder(sagaId);
        }
        log.record(sagaId, step, StepState.COMPENSATED);
    }
}
```

Idempotency using the saga ID as the key:

```
void charge(String sagaId, int amount) {
    if (charges.containsKey(sagaId)) {
        return;                       // duplicate - do NOT charge again
    }
    charges.put(sagaId, amount);
    ledger.add("CHARGE  +" + amount);
}
```

B. What you should see

```
=== 2. Step 3 fails -> compensations run in REVERSE ===
      OrderService: order created
      PaymentService: charged 500
      InventoryService: INSUFFICIENT STOCK (have 3, need 99)
    !!! step failed: out of stock -> compensating
      PaymentService: REFUNDED 500 (compensation)
      OrderService: order CANCELLED (compensation)
  order status: CANCELLED | stock: 3

=== 3. Idempotency: the same step retried ===
      PaymentService: charged 150
      PaymentService: duplicate detected, NOT charging again
      PaymentService: duplicate detected, NOT charging again

=== 4. Compensation is NOT rollback ===
  payment ledger: [CHARGE +300, CHARGE +500, REFUND -500, CHARGE +150]
```

Section 4 is the whole conceptual point, made concrete. Look at the **ledger** (an append-only list of money movements): the £500 charge and the £500 refund **both exist**. A database rollback would have erased the charge as though it never happened. Compensation adds an **offsetting entry** — and the customer sees both lines on their statement. That's why "cancelling an order is not the same as never placing it."

C. Production — orchestration

Hand-rolling saga orchestration is possible but you'll reinvent **persistence** (saving state so it survives crashes), **timeouts** (limits on how long to wait), and retries. Real options — all **workflow engines** that run multi-step processes reliably: **Temporal**, **Camunda/Zeebe**, **AWS Step Functions** (Amazon's managed version), or **Axon Framework** (a Java framework for event-based systems).

Temporal is the most popular code-first choice. Your saga is ordinary code; the framework makes it **durable** (its progress is saved and survives crashes) — if the process crashes mid-saga, it resumes from the last completed step on another **worker** (a process that executes workflow steps):

```java
public class OrderWorkflowImpl implements OrderWorkflow {

    private final OrderActivities activities = Workflow.newActivityStub(
        OrderActivities.class,
        ActivityOptions.newBuilder()
            .setStartToCloseTimeout(Duration.ofSeconds(10))
            .setRetryOptions(RetryOptions.newBuilder()
                .setMaximumAttempts(3)
                .setBackoffCoefficient(2.0)
                .build())
            .build());

    @Override
    public void processOrder(Order order) {
        Saga saga = new Saga(new Saga.Options.Builder().build());
        try {
            activities.createOrder(order);
            saga.addCompensation(activities::cancelOrder, order.id());   // register the undo

            activities.chargePayment(order);
            saga.addCompensation(activities::refundPayment, order.id());

            activities.reserveStock(order);                              // may fail
        } catch (ActivityFailure e) {
            saga.compensate();      // runs registered compensations in reverse
            throw e;
        }
    }
}
```

The pattern to copy even without Temporal: register the compensation **immediately after** each step succeeds. That way the list of things to undo is always exactly correct, with no bookkeeping.

Choreography with Kafka — no orchestrator; services react to each other's events. (**Kafka** is a distributed event log: producers write messages to named **topics** and **consumers** read them; a `groupId` names a group of consumers that share the work.)

```java
@KafkaListener(topics = "order-created", groupId = "payment-service")
public void onOrderCreated(OrderCreated event) {
    try {
        paymentService.charge(event.orderId(), event.amount());
        kafka.send("payment-completed", new PaymentCompleted(event.orderId()));
    } catch (PaymentFailedException e) {
        kafka.send("payment-failed", new PaymentFailed(event.orderId()));   // triggers compensation
    }
}
```

Note the shape: **every step publishes either success or failure**, and compensation is just another consumer reacting to a failure event. Nobody is in charge — which is exactly why complex flows become hard to follow.

D. Implementing the saga log properly

The demo's log is in memory, so a crash loses everything. Real implementations persist it **in the same transaction as the business change**, using the **Transactional Outbox** pattern (write outgoing events into an "outbox" table in the same database transaction as the data change, and publish them afterwards). In the SQL below, a **UUID** is a randomly generated unique ID, the **primary key** is the column that uniquely identifies each row, and `JSONB` is PostgreSQL's binary JSON column type:

```sql
CREATE TABLE saga_state (
    saga_id       UUID PRIMARY KEY,
    current_step  VARCHAR(50)  NOT NULL,
    state         VARCHAR(20)  NOT NULL,   -- STARTED / COMPLETED / COMPENSATING / DONE
    payload       JSONB        NOT NULL,
    updated_at    TIMESTAMP    NOT NULL
);

CREATE TABLE outbox (
    id          UUID PRIMARY KEY,
    aggregate   VARCHAR(50),
    event_type  VARCHAR(100),
    payload     JSONB,
    published   BOOLEAN DEFAULT FALSE
);
```

```java
@Transactional
public void completeStep(String sagaId, String step, Event next) {
    sagaRepo.markCompleted(sagaId, step);      // both writes
    outboxRepo.save(next);                     // in ONE local transaction
}
// A separate poller (or Debezium CDC) publishes unpublished outbox rows to Kafka
```

(In the code above, `@Transactional` makes the method run inside one database transaction; a **poller** is a process that checks the table repeatedly for new rows; **Debezium CDC** — change data capture — instead streams new rows straight from the database's change log.)

Why the outbox exists. If you write to the database and then publish to Kafka as two separate operations, a crash between them leaves the two permanently inconsistent — the step completed but nobody was told. Writing the event to the same database in the same transaction makes them atomic; a separate process then relays it. This is the standard solution and worth knowing by name.

E. Implementation pitfalls

1. Compensations that aren't idempotent. Compensation gets retried too. Refunding twice is as bad as charging twice. Guard with the saga ID.

2. Compensations that can fail permanently. What if the refund API is down? You need retries with **backoff** (waiting longer between each attempt), and ultimately a **dead-letter queue plus human intervention** (a dead-letter queue is a holding area for messages that keep failing, so a person can inspect them). A saga stuck half-compensated is the worst possible state — plan for alerting on it.

3. Putting an uncompensatable step in the middle. You cannot un-send an email or un-ship a parcel. Order your steps so **irreversible actions come last**, after everything that could fail has succeeded.

4. An in-memory saga log. As in the demo. A crash mid-saga leaves **orphaned** state (half-finished records that nothing owns or will clean up) with nothing to recover from. Persist before each step.

5. Writing to the database and publishing separately. Use the outbox. This is the single most common correctness bug in event-driven sagas.

6. Assuming isolation. Sagas have **no isolation** — other transactions see your intermediate state. A customer may see an order that's about to be cancelled. Design the **UI** (user interface) for it ("processing" rather than "confirmed").

7. Choreography for a complex flow. Six services reacting to each other's events means nobody can answer "what happens when an order is placed?" without reading six codebases. Move to orchestration once you pass three or four steps.

8. No timeouts on saga steps. A step that never responds leaves the saga hanging forever. Every step needs a deadline, after which it's treated as failed and compensation begins.

Related patterns

- **Event-Driven Architecture** — the messaging substrate choreography sagas run on
- **CQRS** — frequently paired with sagas in **event-sourced** systems (which store every change as an event rather than just the current state)
- **Retry** — idempotency concerns are shared; retries happen within saga steps
- **Circuit Breaker** — protects individual saga participants

Event-Driven Architecture (EDA) Pattern

Category: Data / messaging **One-liner:** Components communicate by publishing and reacting to events rather than calling each other directly — giving loose coupling, asynchrony, independent scaling, and **real-time** responsiveness (reacting within moments of something happening).

Part 0 — Concepts you need first

What is an "event"?

An **event** is a record that **something happened**. It's a statement of fact about the past.

The naming convention tells you a lot: events are named in the **past tense** — `OrderPlaced`, `PaymentReceived`, `UserRegistered`. This isn't cosmetic. It reflects that an event is a *notification of something already done*, not a request for something to be done.

Contrast with a **command**, which is an instruction, named imperatively — `PlaceOrder`, `ChargeCard`. A command can be refused. An event cannot; it already happened.

Synchronous vs. asynchronous

Synchronous — you make a request and **wait** for the response before doing anything else. Like a phone call: both parties are engaged for the duration.

Asynchronous — you send a message and **carry on immediately**, handling the response whenever it arrives. Like email: you send it and get on with your day.

The practical difference for a server: in a synchronous call, the calling **thread** (one line of execution inside the server, which handles one task at a time) is **blocked and useless** for the whole wait. In an asynchronous one, it's free immediately.

What is a message queue / event bus?

Middleware (software that sits between other programs to connect them) that accepts messages from senders and delivers them to receivers. **Kafka** (a distributed, durable event log) and **RabbitMQ** (a classic message broker) are the common ones. See System Design Fundamentals for queues in general.

The important properties:

- The **sender doesn't need to know who receives** — it publishes to the bus
- Messages are usually **persisted** (saved to disk), so if a receiver is down, the message waits
- **Many receivers** can consume the same message independently

What is publish-subscribe?

A messaging style where **publishers** send messages to a named channel (or "topic") without knowing who's listening, and **subscribers** register interest in a channel and receive everything published to it.

The essential property: **the publisher doesn't hold a list of subscribers.** Adding a new subscriber requires no change to the publisher — which is the entire source of EDA's flexibility.

What is "coupling"?

How much one component depends on knowledge of another.

Tight coupling: Service A calls `serviceB.doThing()`. A must know B exists, where it lives, its **API** (the operations it offers and how to call them), and its response format. Change B and you may break A.

Loose coupling: A publishes `ThingHappened`. It doesn't know whether anyone is listening. B may consume it, or five services may, or none. **A is unaffected either way.**

Part 1 — The problem

As applications grew, developers adopted **distributed systems** (many programs on different machines cooperating over a network) for **scalability** (handling more load by adding resources) and **resilience** (staying up when parts fail). But that shift brought challenges.

Managing complex interactions

A simple system has a small number of components interacting predictably. **Scale up and this becomes much harder.** A distributed system has a multitude of components that must interact and communicate. How do they communicate effectively? How do you ensure changes in one part are reflected in others?

The course's grounding example: consider how an email notification system works. When you receive an email saying a product has shipped, or that a blog you follow has a new post — that's a system efficiently handling complex interactions.

The call for asynchronous communication

In a synchronous system, a component makes a request and waits for the response before proceeding. This works for small, simple systems, but **quickly becomes a bottleneck** (the narrow point that limits everything) as the system grows.

> The question that makes it click: *what happens when you have thousands or even millions of components all waiting for responses?* Every waiting component is holding resources and doing nothing.

Asynchronous communication is often the answer — make a request, continue with other tasks, process the response when it arrives. Far more efficient, but **managing it effectively is a considerable challenge**.

The everyday example: why can you keep browsing an online store and adding items to your cart while previous requests are still being processed? Efficient asynchronous communication.

The demand for real-time responsiveness

Users expect immediate responses. Post a status update and you expect it visible to friends immediately. In online multiplayer games, any delay produces a poor experience.

Designing a system that manages complex interactions between components **and does so in real time** is no small feat.

Data consistency

With multiple components potentially reading and writing data **concurrently** (at the same time), how do you ensure consistency? If one component updates a piece of data, how do others become aware of the change?

The example: an online banking system. When you make a transaction it's critical your balance updates promptly and accurately — but what if another transaction is being processed on your account at the same moment?

Part 2 — The solution

EDA revolves around the **production, detection, consumption of, and reaction to events**.

An **event** is a change in state, or an update, produced by a component — the **event producer**. It's then detected and consumed by one or more **event consumers**.

> **The courier analogy:** a package (event) is sent by the sender (producer) and received by the recipient (consumer). The delivery service (event bus) takes care of delivering it. Scale it up to many senders and receivers and the core concept is unchanged.

Part 3 — The benefits

Decoupling

Event producers and consumers **aren't tied together and don't need to be aware of each other's existence**. This makes the system more flexible and adaptable to change.

The illustration that makes this concrete: a user uploads a photo to a social media app. That **single event** can trigger multiple actions:

- Notifying the user's followers
- Updating the user's profile
- Alerting the moderation team if the content violates policy

With EDA, **each of these is handled independently**. The system efficiently manages multiple tasks triggered by one event.

> The part worth pausing on: **six months later you want to add "generate a thumbnail."** With EDA you write a new consumer subscribing to `PhotoUploaded` and deploy it. **You never touch the upload code.** In a direct-call design you'd modify the upload service, retest it, and redeploy it — and repeat that for every new reaction, forever. That difference in change cost is the pattern's real value.

Asynchrony

The producer simply produces the event and **carries on with its operations without waiting** for consumers to process it. This **non-blocking** operation (the caller never sits idle waiting) greatly enhances the system's overall responsiveness and **throughput** (how much work gets done per second).

Scalability


Since producers and consumers are decoupled, they can be **scaled independently** based on their workload. A surge of events from producers? Increase the number of consumer **instances** (running copies) to handle the **load** (volume of incoming work) — and vice versa.

Real-time processing

As soon as an event is produced, it can be **immediately handled** by the consumer. This is particularly useful where instant action is required — **fraud detection in banking transactions**, or real-time **analytics** (computing statistics and reports from data).

Part 4 — The components

Component	Role
Event Producers	Create events. They define what an event is, encapsulate the relevant data, and send it to the Event Bus
Event Bus (message queue)	The backbone. Receives events from producers and transmits them to consumers. **This is what decouples them**
Event Channels	Pathways on the bus. They categorize events by nature, or by the kind of consumers they cater to, so each consumer listens only to the channel relevant to it
Event Consumers	Listen to events via the bus and react. The reaction could be starting a new process, or merely recording the event



Part 5 — Three structural variants

The choice depends on system requirements, complexity, and how much control you need over event handling.

Mediator EDA

A **central mediator** takes charge of event handling.

Producers send their events to the mediator. The mediator — **aware of all producers and consumers** — determines where to route them. It performs **event aggregation, filtering, and transformation** (combining several events into one, dropping irrelevant ones, and reshaping their content), then delivers the processed events to the appropriate consumers.

- **Advantage:** control. It allows complex routing and transformation logic, giving a high degree of control over event processing.
- **Disadvantage:** the mediator could become a **bottleneck**, limiting the system's scalability.

Broker EDA

No central mediator. Event producers send events directly to Event Channels on the Event Bus. Consumers subscribe to those channels and consume events directly. **The broker essentially *is* the event bus.**

- **Advantage:** scalability and simplicity. With no central mediator, it's easier to scale.
- **Disadvantage:** less control over event routing and processing.

Hybrid EDA

Combines elements of both. Adopted when a system requires a mix of **centralized control and high scalability** — for example, a mediator for a few complex flows and direct broker delivery for everything else.

Part 6 — Inner workings

Event generation and propagation

An event's life starts with a **change of state** — a user action, a sensor reading, an internal system update. An event is generated to encapsulate that change: essentially **a bundle of data representing a significant occurrence**.

Once generated it must be propagated. The **Event Bus** is the spinal cord, carrying events from producers to consumers via **Event Channels** — pathways that categorize and route events by type or nature, ensuring the right events reach the right consumers.

Routing

- **In Mediator EDA:** a central component decides routing based on event type and known consumers. It may also aggregate, filter, or transform events before sending them on.
- **In Broker EDA:** there's no central decision-maker. Producers place events directly into channels; consumers subscribe and consume. Simpler routing, but less controlled.

> Without routing, events would simply float aimlessly in the system. With it, events know precisely where to go.

Event processing and state change

Once an event reaches its consumer, it is processed. The consumer takes the event data and performs actions based on it, **leading to a change in system state** — anything from changing a value in a database to triggering a physical action in an **IoT** device (Internet of Things — a sensor or gadget connected to the network).

How consumers know when to act

Event consumers are **always listening** — monitoring their subscribed channels on the bus, waiting. When an event arrives, they act.

This listening mechanism is usually implemented using the **Observer** (objects register with a subject and get called back whenever it changes) or **Publish-Subscribe** patterns.

Real-time illustration — traffic management

Various sensors act as producers, generating an event for each vehicle detected. The events travel via the bus, through appropriate channels, to the consumers — traffic signals. Based on the events received (for example vehicle count), the signals **adjust their timing**, changing the system state: traffic flow.

Throughout, the system reacts in real time.

Event Sourcing and CQRS

Two significant related concepts:

Event Sourcing means changes to application state are stored as a **sequence of events**, not just as a **snapshot** (a single picture) of the current state. This allows:

- **Full auditability** (being able to prove what happened and when) — every change is recorded
- **Versioning**
- The ability to **"time-travel"** — see the system's state at any past point

> Worth grasping the shift: instead of storing "balance = £70," you store `Deposited £100`, `Withdrew £30`. The balance is **derived** by replaying those events. You've kept the history rather than just the conclusion — which is exactly how accounting ledgers have always worked.

CQRS involves **separating the read and write operations** of a system. This is especially useful in an EDA, as it lets you model your event handlers (write operations) separately from your views (read operations).

Part 7 — Worked example: traffic management (Java)

The event

```java
public class VehicleEvent {
    private final String vehicleId;
    private final String type;

    public VehicleEvent(String vehicleId, String type) {
        this.vehicleId = vehicleId;
        this.type = type;
    }

    public String getVehicleId() { return vehicleId; }
    public String getType()      { return type; }
}
```

This represents a vehicle's action — such as 'entering' or 'leaving' a zone.

Note the `final` fields and absence of setters — the event is immutable (it cannot be changed after creation; a **setter** is a method that changes a field, and `final` in Java forbids reassigning one).

That's deliberate and correct. An event describes something that **already happened**; allowing a consumer to modify it would be meaningless (you can't change the past) and dangerous (other consumers would see the altered version).

The producer — a sensor

```
public class Sensor implements EventProducer {
    private EventBus eventBus;

    public Sensor(EventBus eventBus) {
        this.eventBus = eventBus;
    }

    public void vehicleDetected(String vehicleId, String action) {
        VehicleEvent event = new VehicleEvent(vehicleId, action);
        eventBus.publish(event);
    }
}
```

Sensors at traffic signals act as producers. Every time a vehicle passes, the sensor generates a `VehicleEvent` and publishes it to the bus.

Notice what's absent: the sensor has no reference to any traffic light. It doesn't know consumers exist. It publishes and returns — **fire and forget**.

The bus and channels

```
public interface EventBus {
    void publish(VehicleEvent event);
    void addChannel(EventChannel channel);
}

public class SimpleEventBus implements EventBus {
    private List<EventChannel> channels = new ArrayList<>();

    @Override
    public void publish(VehicleEvent event) {
        for (EventChannel channel : channels) {
            channel.add(event);
        }
    }

    @Override
    public void addChannel(EventChannel channel) {
        channels.add(channel);
    }
}

public class SimpleEventChannel implements EventChannel {
    private List<EventConsumer> consumers = new ArrayList<>();

    @Override
    public void add(VehicleEvent event) {
        for (EventConsumer consumer : consumers) {
            consumer.onEvent(event);
        }
    }

    @Override
    public void addConsumer(EventConsumer consumer) {
        consumers.add(consumer);
    }
}
```

When an event is published to the bus, it is added to all the channels; each channel then passes it to all its consumers.

The consumer — a traffic light

```
public class TrafficLight implements EventConsumer {
    @Override
    public void onEvent(VehicleEvent event) {
        if ("entering".equals(event.getType())) {
            System.out.println("Vehicle " + event.getVehicleId()
                + " is entering. Adjusting traffic light timings.");
        } else if ("leaving".equals(event.getType())) {
            System.out.println("Vehicle " + event.getVehicleId()
                + " has left. Resetting traffic light timings.");
        }
    }
}
```

The traffic light reacts to vehicle events by adjusting its timings.

What this example simplifies — read before copying it

The structure is right; the mechanics are not production-shaped:

- **It's entirely synchronous and in-process** (everything runs inside one program). `publish` calls consumers **directly on the caller's thread**. The sensor doesn't return until every traffic light has finished processing — which destroys the asynchrony that is the pattern's main benefit. A real EDA uses Kafka or RabbitMQ, with consumers running in **separate processes** (separately running programs) and the producer returning immediately.
- **No persistence.** If the process dies, **in-flight** events (published but not yet processed) are gone. Real buses persist events so they survive restarts and can be replayed.
- **No error handling.** If one consumer throws, the loop breaks and later consumers never see the event.
- **The bus broadcasts to every channel** rather than routing by type, so channels don't actually categorize anything here.

Use it to understand the **roles** — producer, bus, channel, consumer — not the implementation.

Part 8 — Performance implications and considerations

Scalability

Each component is decoupled, so you can **scale them independently** based on demand. High volume of events but consumers can't keep up? Scale up consumers without affecting producers or channels. However, **ensuring balance to avoid overwhelming certain parts of the system requires careful consideration.**

Processing speed and latency

EDA commonly boosts performance because of its asynchronous nature — producers continue producing without waiting for consumers.

The flip side is latency (the delay between something happening and it being handled). As the system scales and event volume increases, **the time from an event being produced to it being processed can grow**, delaying responses. Overall speed is also affected by the choice of event channel — synchronous or asynchronous.

Error handling and message durability

What happens when an event fails to be processed? How do you ensure messages aren't lost in transit?

If a consumer fails to process an event, the system needs a mechanism to **retry processing, log the failure, or alert an operator**. Ensuring **message durability** might require **persistent storage** to hold events until they're successfully processed.

Note the trade-off the course flags: **adding these mechanisms complicates the system and impacts performance.**

System complexity

EDA undoubtedly introduces complexity. **Tracking the flow of events and debugging issues is challenging** due to the asynchronous and distributed nature of the system. **Special tools and practices** may be needed to monitor and debug effectively. Designing a system where every component understands the format and meaning of events is itself complex.

> ⚠️ **This is the cost beginners most underestimate.** In a synchronous system, a **stack trace** (the error report listing the chain of method calls that led to a failure) tells you the whole story of what called what. In EDA, causation is spread across services *and across time* — the event that caused today's bug was published twenty minutes ago by a service you weren't looking at. You need **correlation IDs** (a shared identifier threaded through every event in a causal chain) and **distributed tracing** (recording a request's journey across every service it touches) from day one, not bolted on after your first **incident** (a production problem).

Event schemas and backward compatibility

Since all communication is via events, **all components must understand the events' structure**. This means events should follow a **well-defined schema** (a formal description of the fields, their types and which are required).

If the schema changes — new fields added, existing ones removed or altered — you must ensure **backward compatibility** (new versions still work with things built for the old one) so consumers expecting the old schema don't break.

> Practical rule: **adding an optional field is safe; removing or renaming one is not.** Old consumers ignore fields they don't know about, but break when a field they depend on vanishes. **Schema registries** (services that store every schema version and reject incompatible changes) exist to enforce this.

Order of events

In a system where order of operations matters, EDA presents a challenge. Events are **asynchronous by nature and could be processed in any order**. If your application has dependencies between events, you'll need a way to maintain the required order — which introduces further complexity.

> Concretely: if `AccountCreated` and `AccountDeleted` arrive out of order, a consumer might delete an account that doesn't exist yet and then create one that should be gone. Kafka guarantees ordering *within a partition* (a topic is split into several **partitions**, each an ordered log that can be processed in parallel), which is why choosing a **partition key** (the value that decides which partition an event goes to, like account ID) matters.

Testing

How do you test an event-driven system? **Unit testing individual components isn't enough** (a **unit test** checks one small piece in isolation) — it won't cover the interactions between parts. You'll need comprehensive **integration and end-to-end tests** (tests that run several real components together, or the whole system from the user's side), which ensure the system works as a whole but bring added complexity in writing and maintaining them.

None of these should deter you — they're a guide to navigating the challenges. Every architecture has trade-offs; the trick is understanding them and making informed decisions.

Part 9 — Use cases

Real-time analytics

In an increasingly data-driven world, processing and analysing data in real time is a powerful advantage. As events are generated they can be **instantly consumed and processed**, giving real-time insights. Especially useful in **finance**, where real-time stock market data drives instantaneous trading decisions.

IoT systems

IoT devices generate a multitude of events — a sensor detecting an environmental change, a smart device being activated, a security system triggered. The **asynchronous nature of EDA is perfectly suited** to handling these. In a smart home, an increase in room temperature triggers an event consumed by the air conditioning system, which adjusts accordingly.

E-commerce systems

An e-commerce platform comprises subsystems like inventory, billing, and shipping. When a customer places an order it triggers a series of events: inventory verifies stock, billing processes payment, shipping handles delivery. With EDA these operations are carried out **asynchronously and efficiently**.

Microservices architecture

Services need to communicate. (**Microservices** are small, independently deployable services.) **Instead of direct communication — which leads to tightly coupled systems — services emit events that other services consume.** This keeps services loosely coupled and able to **evolve independently over time**.

Part 10 — System design example: a ride-sharing app

Designing something like Uber or Lyft with EDA. Various events drive the entire process.

1. **A rider requests a ride** → generates an event containing the necessary details such as pickup location and destination. The system **broadcasts** this event.
2. **Drivers in the vicinity** act as consumers of this event.
3. **A driver accepts the ride** → triggers another event, consumed by the rider's app, informing them of the match.
4. **During the ride**, the driver's app continuously sends events about the **current location**. The rider's app consumes these and **updates the display in real time**.
5. **The ride ends** → the driver's app sends a **ride completion event**.
6. **The billing service** consumes it, calculates the fare, and **triggers a payment event**.

This showcases EDA handling complex workflows while promoting real-time, asynchronous processing and loosely coupled design.

> Notice how naturally this maps: a ride genuinely *is* a sequence of things that happened. When your domain is already event-shaped, EDA stops feeling like a technical choice and starts feeling like the obvious model.

Part 11 — Common beginner misconceptions

"Events are just asynchronous function calls." No. A function call has one specific target and expects a return. An event has **zero or many** targets, unknown to the publisher, and expects nothing.

"EDA means no more direct calls anywhere." No. When you need an immediate answer — "is this user authorized?" — a synchronous call is right. EDA is for notification and reaction, not for queries.

"The event bus makes my system reliable." It makes it *decoupled*. Reliability requires persistence, retries, **dead-letter queues** (holding areas for messages that keep failing), and **idempotent** consumers (handling the same event twice has the same effect as once) on top.

"If I publish an event, it definitely gets processed." Only with **durable** messaging (stored safely until processed) and **acknowledgements** (the consumer confirming to the broker that it finished a message). Fire-and-forget over an in-memory bus loses events on restart.

"Consumers can assume they see each event exactly once." Most systems guarantee *at-least-once* delivery (every message arrives, but possibly more than once), meaning **duplicates happen**. Consumers should be idempotent. *(See Retry.)*

"Ordering is guaranteed." Generally not across the whole system — only within a partition or channel, if your **broker** (the messaging server) offers even that.

Part 12 — Check your understanding

1. Why are events named in the past tense?
2. What's the change-cost argument for EDA, using the photo upload example?
3. What's the difference between Mediator and Broker EDA, and what does each trade away?
4. Why is debugging harder in EDA, and what two tools address it?
5. Which schema changes are safe and which break consumers?
6. What's wrong with the example's `publish` method, relative to real EDA?

(Answers: 1 — an event records something that already happened and cannot be refused, unlike a command; 2 — adding a new reaction means writing a new consumer without ever modifying the upload service, whereas direct calls require changing and redeploying the producer each time; 3 — Mediator centralizes routing and transformation, gaining control but risking a bottleneck, while Broker publishes straight to channels, gaining scalability but losing routing control; 4 — causation is spread across services and time so there's no single stack trace, addressed by correlation IDs and distributed tracing; 5 — adding optional fields is safe, removing or renaming is not; 6 — it calls consumers synchronously on the producer's thread, so the producer blocks until all consumers finish, eliminating the asynchrony that is the point.)

Part 13 — Interview soundbite (30 seconds)

> "Event-driven architecture has components communicate by publishing events rather than calling each other directly. A producer publishes a state change to an event bus, and any number of consumers subscribe to the channels they care about. The producer doesn't know who's listening, which is the whole point — when a user uploads a photo, that one event can trigger follower notifications, a profile update, and content moderation, and six months later you add thumbnail generation by writing a new consumer without ever touching the upload code. You also get asynchrony, so producers don't block, and independent scaling of producers and consumers. There are three variants: broker, where producers publish straight to channels — simple and scalable; mediator, where a central component routes, filters, and transforms — more control but a potential bottleneck; and hybrid. Ride-sharing is a natural example, with ride requests, driver acceptance, live location updates, and completion all as events. The costs are real: ordering isn't guaranteed across the system, you have to version event schemas carefully because removing a field breaks old consumers, delivery is usually at-least-once so consumers must be idempotent, and debugging is much harder because causation spans services and time — so you need correlation IDs and distributed tracing from the start. It pairs naturally with event sourcing, where state is stored as the sequence of events rather than a snapshot, and with CQRS."

Part 14 — Implementation

A. Runnable demo

Full source: `demos/EventDrivenDemo.java`

```
cd demos && ./gradlew runCh11
```

Failure isolation — one consumer throwing must not affect the others:

```
for (Subscriber s : subs) {
    Runnable task = () -> {
        try { s.handler().accept(e); }
        catch (Exception ex) {
            System.out.printf("      [%s] FAILED: %s (isolated)%n", s.name(), ex.getMessage());
        }
    };
    if (async) pool.submit(task); else task.run();
}
```

Idempotent consumer, using a set of seen event IDs:

```
void handle(Event e) {
    String eventId = e.payload().get("eventId");
    if (!processed.add(eventId)) return;      // add() is false if already present
    chargesApplied++;
}
```

B. What you should see

```
=== 1. SYNCHRONOUS bus: producer waits for every consumer ===
  producer blocked for 114ms  <- the sum of all consumers

=== 2. ASYNCHRONOUS bus: producer returns immediately ===
  producer returned in 0ms  <- did NOT wait
      [moderation] FAILED: moderation service unavailable (isolated)

=== 4. Add a NEW consumer - producer code untouched ===
    [bus] publishing PhotoUploaded (cid=cid-3) to 4 subscriber(s)
  >> 4 reactions now. The upload service never changed.

=== 5. At-least-once delivery -> idempotent consumers ===
      [billing]    charge applied (total=1)
      [billing]    duplicate evt-abc ignored
      [billing]    duplicate evt-abc ignored
  charges actually applied: 1 (must be 1)
```

114ms → 0ms is the value of asynchrony as a measured number. And section 4 is the whole architectural argument: the subscriber count went from 3 to 4 and **the producer's code was never edited**.

C. Production — Kafka

(In this config, `bootstrap-servers` are the first Kafka machines a client contacts; `acks: all` makes the producer wait until every **replica** — a copy of the data on another broker — has the message; an **offset** is a consumer's position in a partition, and **committing** it records how far the consumer has read.)

```yaml
spring:
  kafka:
    bootstrap-servers: kafka-1:9092,kafka-2:9092,kafka-3:9092
    producer:
      acks: all                         # wait for all replicas - no silent data loss
      retries: 3
      properties:
        enable.idempotence: true        # broker de-duplicates producer retries
        max.in.flight.requests.per.connection: 5
    consumer:
      group-id: notification-service
      auto-offset-reset: earliest
      enable-auto-commit: false         # commit only AFTER successful processing
      isolation-level: read_committed
```

Producer — the partition key is the important decision (`UUID` generates a unique ID; `MDC` is the logging library's per-request context, used here to carry the correlation ID):

```java
@Service
public class PhotoEventPublisher {
    private final KafkaTemplate<String, PhotoUploaded> kafka;

    public void publish(String photoId, String userId) {
        PhotoUploaded event = new PhotoUploaded(
                UUID.randomUUID().toString(),      // eventId, for consumer de-duplication
                MDC.get("correlationId"),          // trace the causal chain
                photoId, userId, Instant.now());

        // Key = userId -> all events for one user land on one partition,
        // and Kafka guarantees ordering WITHIN a partition.
        kafka.send("photo-uploaded", userId, event);
    }
}
```

Consumer — manual acknowledgement plus idempotency:

```java
@KafkaListener(topics = "photo-uploaded", groupId = "thumbnail-service")
public void onPhotoUploaded(PhotoUploaded event, Acknowledgment ack) {
    if (processedEvents.existsById(event.eventId())) {   // at-least-once => duplicates happen
        ack.acknowledge();
        return;
    }
    try {
        thumbnailService.generate(event.photoId());
        processedEvents.save(new ProcessedEvent(event.eventId(), Instant.now()));
        ack.acknowledge();                                // commit only on success
    } catch (TransientException e) {
        // Do NOT ack - Kafka redelivers
        throw e;
    }
}
```

Dead-letter topic (DLT) — where messages go after retries are exhausted:

```java
@Bean
public DefaultErrorHandler errorHandler(KafkaTemplate<Object, Object> template) {
    var recoverer = new DeadLetterPublishingRecoverer(template,
            (record, ex) -> new TopicPartition(record.topic() + ".DLT", record.partition()));
    return new DefaultErrorHandler(recoverer,
            new ExponentialBackOff(1000L, 2.0));   // 1s, 2s, 4s...
}
```

Schema evolution — register schemas so a **breaking change** (one that would make existing consumers fail) is rejected at build time, not discovered in production:

```
spring.kafka.properties:
  schema.registry.url: http://schema-registry:8081
  value.subject.name.strategy: io.confluent.kafka.serializers.subject.TopicNameStrategy
```

Compatibility mode `BACKWARD` means **new consumers can read old events**. Adding an optional field passes; removing a field fails the build.

D. Implementation pitfalls

1. Auto-commit enabled. With `enable-auto-commit: true`, Kafka commits the offset on a timer — possibly *before* your handler finishes. Crash mid-processing and the message is **silently lost**. Always commit manually after success.

2. Consumers that aren't idempotent. At-least-once delivery is the norm, so duplicates are guaranteed, not hypothetical. Store processed event IDs.

3. No partition key, then expecting ordering. Kafka orders **within a partition only**. Without a key, events for the same **entity** (one business object, such as a specific account) scatter across partitions and arrive out of order. Key by entity ID.

4. Publishing before committing the database transaction. Classic bug: you write to the DB, then publish, and crash in between — the state changed but nobody was told. Use the **Transactional Outbox** (save the event in an outbox table in the same database transaction, then publish it separately) *(see Saga Part 13D)*.

5. Events carrying too much or too little. Too little and every consumer must call back to the producer, recreating coupling. Too much and the event becomes a schema everyone depends on. Carry **identifiers plus the facts that actually changed**.

6. Removing or renaming event fields. Old consumers break. Additive changes only; use a schema registry to enforce it.

7. No correlation ID. Without one you cannot reconstruct what caused what. Generate at the edge, propagate through every event, log on every line.

8. No dead-letter queue. A permanently-failing message blocks its partition forever, stalling every message behind it. Always configure a DLT with alerting.

Related patterns

- **CQRS** — separate read/write models, commonly built on EDA
- **Saga** — choreography sagas are EDA applied to distributed transactions
- **Retry** — requeueing and dead-letter queues are retry in an async context
- **Bulkhead** — a queue between components is a natural isolation boundary

CQRS — Command Query Responsibility Segregation

Category: Data / messaging **One-liner:** Split a system's operations into commands (writes) and queries (reads) with separate models, so each can be optimised, scaled, and evolved independently.

Part 0 — Concepts you need first

What is CRUD?

Create, Read, Update, Delete — the four basic operations on stored data. Most applications start here: one `User` class, one `users` table, one set of methods that create, read, update, and delete users.

CRUD is simple and intuitive, and for most applications it's the right answer. This chapter is about what happens when it stops being enough.

What is a "model"?

In this chapter, a **model** means the code and data structures representing part of your **domain** (the business area the software deals with) — the `User` class, its **validation** rules (checks that input is acceptable before it's used), its database table, the code that loads and saves it.

CQRS's central claim is that **one model trying to serve both reads and writes ends up serving neither well**, because the two have genuinely opposed requirements.

Reads vs. writes — why they differ

This is the intuition the whole pattern rests on.

	Writes	Reads
Must be	Correct, validated, secure	Fast
Volume	Usually lower	Usually far higher
Complexity	Business rules (domain rules), constraints (database-enforced rules)	Joining (combining tables) and formatting
Cost of error	Severe — corrupt data	Mild — a stale (out-of-date) display
Optimal storage	Normalised (no duplication)	Denormalised (pre-joined)

That last row is the deep conflict. **Normalised** storage stores each fact once — excellent for writes, because updating a fact means changing one row. **Denormalised** storage duplicates data into ready-made shapes — excellent for reads, because the answer is already assembled with no **joins** (SQL operations that combine rows from several tables at query time).

You cannot have both in one schema (the defined structure of tables and columns). Every design is a compromise between them — and CQRS says: stop compromising, have two.

What is a DTO?

A **Data Transfer Object** — a simple object whose only job is to carry data to whoever asked for it. It has no **business logic** (code implementing the rules of the domain). In CQRS, the read side returns DTOs shaped for the screen, rather than returning domain objects.

What does "side effect" mean?

A change to state that persists after a method returns. Reading data has no side effects; saving data does. This distinction is what CQRS formalises.

Part 1 — The problem

In a **monolithic** application (one built and deployed as a single unit) we usually use **one database for everything**. That single database handles both read and write operations — meaning it's simultaneously serving **complex join queries** *and* performing **CUD** (Create, Update, Delete) operations. As the application gets more complicated, **handling these read and write tasks becomes really hard to manage.**

The scale mismatch

In an ideal world, CRUD operations provide a simple and intuitive method for handling data. But complex applications demand handling numerous **concurrent** operations (happening at the same time), diverse data requirements, and efficient scaling — and traditional CRUD struggles to keep up.

The e-commerce picture: thousands of users browsing products (**read** operations) while concurrently there are inventory updates, order placements, and product additions (**write** operations).

Can a single model efficiently handle these varied requirements? That's where the cracks show.

Note the asymmetry: **read operations are significantly more numerous, while write operations carry more complexity.** Can we scale them independently based on their different needs? Not with a single data model handling both.

The optimisation conflict — the banking example

A banking application handles two main kinds of operation:

- **Transactions** — depositing or withdrawing money
- **Balance inquiries** — checking the current account balance

Their needs are quite different:

Writing data (transactions) involves creating new records or updating existing ones. It needs to be **accurate and secure**, as it directly affects a user's finances.

Reading data (balance inquiries) is about fetching data **quickly and efficiently**. Users expect to see their balance in **real time** (immediately reflecting the latest state), without delay.

> **The trap, stated plainly:** if you focus too much on making transactions fast and secure, you end up making balance inquiries slower. If you optimise for quick balance checks, you compromise the efficiency or security of processing transactions. **One model cannot be tuned for both.**

This is a classic case where the traditional approach falls short. It becomes difficult to maintain, scale, and perform well under different types of **load** (the volume and kind of work hitting the system).

Part 2 — The solution

Break the term down:

- **Command** — an instruction to *do* something: creating, updating, or deleting data. In the banking example, processing a deposit or a withdrawal.
- **Query** — a request to *retrieve* data **without changing it**. Checking your account balance.
- **Responsibility Segregation** — dividing responsibilities: separating the handling of commands (writes) from queries (reads).

The two sides

The Command Side handles all write operations. It's responsible for updating data — processing transactions in the banking app.

The Query Side deals with all read operations. It's optimised for fetching data quickly — showing your current account balance.

The formal rule

This is the definition that gives the pattern its rigour, and it's worth memorising. The **separation of concerns** (giving each piece of code one clear job) distinguishes between methods that change state and those that don't. **Each method of an object falls into one of these categories, but never both:**

	Returns a value?	Changes state?
Query	✅ Returns a result	❌ No state change, no side effects
Command *(also called modifiers or mutators — methods that change data)*	❌ Only an indication of success or failure	✅ Changes system state

> **Why "never both" matters.** A method that both changes state *and* returns data is impossible to call safely — you can't retry it (it might apply twice), you can't **cache** it (store its result to reuse later), and you can't reason about it. Enforcing the split makes queries freely repeatable and cacheable, and makes commands explicit about being consequential.

Why this is useful

Optimization — by separating reads and writes you can optimise each independently. The command side focuses on security and accuracy; the query side is optimised for speed.

Simplicity — it simplifies the design. Each side is developed and maintained separately, reducing complexity.

Scalability (handling more load by adding resources) — as the application grows, scale read and write operations independently based on their specific demands.

Flexibility in technology choice — different **technology stacks** (sets of languages, frameworks and databases) can be used for the read side and the write side if that suits their needs better. A **relational database** (one storing data in tables linked by keys, queried with SQL) for writes with its constraints and **transactions** (groups of changes that succeed or fail together); a **document store** (a database storing self-contained JSON-like documents) or **search index** (a structure built for fast text search, e.g. Elasticsearch) for reads.

In essence: CQRS acknowledges that the needs for reading and writing data are different, and lets you treat them separately.

Part 3 — Architecture: three levels

CQRS is not one thing — it's a spectrum. Knowing which level you mean is important, because the costs differ enormously.

Level 1 — Separate models, one database

The Command Model handles all write operations. It is responsible for maintaining the **integrity and consistency** of data (keeping it correct and obeying all its rules). It receives commands, performs validations, applies business rules, and alters system state. *The course's image: a disciplined librarian, ensuring every book is in its proper place.*

The Query Model handles all read operations, providing the current state of the system to users. It's optimised for reads, ensuring users get data efficiently and quickly. *A friendly librarian, always ready to fetch the book you need.*

This is the simplest useful form — two models, one database. **Most teams should stop here.** You get most of the design clarity with almost none of the operational cost.

Level 2 — Separate read and write databases

To enhance flexibility and scalability, you can use **separate databases** for reads and writes.

> ⚠️ However, this **significantly increases complexity**, as it requires careful consideration of how to propagate changes from the write database to the read database.

The specific problems this creates, all of which the course lists:

- **No atomic transactions across the read and write models** (no single all-or-nothing update covering both) — so you must rely on **asynchronous messaging and events** (messages sent without waiting for a reply) to achieve **eventual consistency** (the read side catches up after a short delay — see System Design Fundamentals)
- **Out-of-order event propagation**
- **Event loss**
- **Sync discrepancies**
- **Read Model update failures**
- **The timing of UI updates after writing** (UI = user interface) — what does the user see immediately after they hit save, if the read model hasn't caught up?

Implementing and managing this style **demands a high degree of complexity and a deep understanding of distributed transactions** (transactions spanning several databases or services). It's suitable **only if your application's non-functional requirements** (needs about speed, scale and reliability rather than features) **genuinely demand such an intricate solution.**

Level 3 — Event Sourcing

This exists to solve one specific problem from Level 2: **ordering**.

Using separate databases makes maintaining sync with eventual consistency hard, and **the sequence of events from write side to read side is crucial**. If updates on a write model occur quickly one after another, **receiving events out of order leaves the read model with outdated information.**

The complication: **many asynchronous message buses** (systems that carry messages between components) **prioritise availability** (staying up and answering) **and performance, and often don't guarantee the order of message delivery.**

Event Sourcing addresses this with a different method of storing write models: **append-only event stores** (logs where new events are only ever added, never edited or deleted) that record every action on a model. When updating, the model is refreshed by **replaying its entire event history**.

In this approach each write model instance exists as an **independent event stream** (its own ordered sequence of events), which enables:

- **Various data views**, by replaying the events differently
- **Rebuilding read models** from scratch by retrieving all events from the write side — the direct fix for synchronisation problems
- **Simplified auditing** (proving later who changed what, and when), since the event streams document every change to every model
- **Creating new read models** by replaying past events — you can add a new view of historical data that never existed before

> **However:** implementing event sourcing **adds complexity and is a significant undertaking**, especially for anyone new to CQRS, event sourcing, or **distributed systems** (systems spread across many machines). Do not adopt Level 3 because you adopted Level 1. They are separate decisions with very different costs.

Part 4 — Inner workings

The journey of a command

A command signifies an **intention to change state**. Follow one through: a user wants to update their address in an e-commerce application. The command is `UpdateUserAddress`.

Step 1 — Validation. Before anything else, the command is validated. This can involve checks for **data format, permissions, and other business rules**. Is the new address in a valid format? Does the user have permission to change it? Pass, and it proceeds; fail, and it's **rejected**.

Step 2 — Handling. Once validated, the command is handled by the **command handler** — the workhorse of the command side. It's responsible for updating system state based on the command; here, updating the user's address.

Step 3 — Generating events. Every command leads to a change in state, represented by an **event** — here, `UserAddressUpdated`. This event is stored in the **event store**, serving as a historical record of all changes in the system.

The query's quest

A query is simply a request for data. Our user now wants to view their updated address, issuing `GetUserAddress`.

Unlike commands, queries require no validation and generate no events. They're simply processed by the **query handler**, which fetches the required data and returns it.

> That asymmetry is worth noticing — it's a direct consequence of the formal rule. Because a query changes nothing, there's nothing to validate against business rules and nothing to record. This is why the read path can be made so much simpler and faster than the write path.

Synchronising the two sides

How do the two sides stay in sync? This is where **Event Sourcing** comes in.

The `UserAddressUpdated` event generated when the user updated their address is **replayed on the query side** to update its state. The user's updated address is thereby reflected in the query model. Event Sourcing ensures that despite working separately, **the command and query sides remain in sync**.

Part 5 — Worked example: user profile management

A simple application managing user profiles. You can **create a new user** (command), **update their email** (command), and **view user details** (query).

The pieces

Command Model (Write Model):

- **Command Class** — defines an action to perform, e.g. `CreateUserCommand` with `userId`, `name`, `email`
- **Command Handler** — processes commands: takes the command, performs business logic, persists changes
- **Domain Model** — represents the state of the data (the `User` class)
- **Repository** — handles data **persistence** (saving to and loading from storage)

Query Model (Read Model):

- **DTO** — represents the data we want to read, e.g. `UserProfileDTO`
- **Query Class** — defines a query, e.g. `GetUserProfileQuery` with a `userId`
- **Query Handler** — handles the query and returns the data, often using **read-optimised storage**

Infrastructure:

- **Command Bus** — routes commands to their handlers
- **Query Bus** — routes queries to their handlers

- **Event Store** — in a more advanced setup, stores the events resulting from commands

Command classes

```
public class CreateUserCommand {
    private String userId;
    private String name;
    private String email;
}

public class UpdateUserEmailCommand {
    private String userId;
    private String newEmail;
}
```

Note these are **just data** — an intention expressed as an object, with no behaviour. Making the intent an explicit object is part of the point: you can log it, queue it, or replay it.

Command handlers

```
public class CreateUserCommandHandler {
    private UserRepository userRepository;

    public CreateUserCommandHandler(UserRepository userRepository) {
        this.userRepository = userRepository;
    }

    public void handle(CreateUserCommand command) {
        User user = new User(command.getUserId(), command.getName(), command.getEmail());
        userRepository.save(user);
    }
}

public class UpdateUserEmailCommandHandler {
    private UserRepository userRepository;

    public UpdateUserEmailCommandHandler(UserRepository userRepository) {
        this.userRepository = userRepository;
    }

    public void handle(UpdateUserEmailCommand command) {
        if (!isValidEmail(command.getNewEmail())) {
            throw new IllegalArgumentException("Invalid email format");
        }
        User user = userRepository.findById(command.getUserId());
        if (user != null) {
            user.setEmail(command.getNewEmail());
            userRepository.save(user);
        }
    }

    private boolean isValidEmail(String email) {
        return email != null && email.contains("@");
    }
}
```

Two things to notice. First, `handle` returns `void` (Java for "returns nothing") — matching the formal rule that commands don't return data. Second, **validation lives here**, in the command handler, before any state change. This is the "accuracy and security" focus of the write side made concrete.

Domain model and repository

```
public class User {
    private String id;
    private String name;
    private String email;
}

public interface UserRepository {
    void save(User user);
    User findById(String id);
}
```

The read side

```
public class UserProfileDTO {
    private String id;
    private String name;
    private String email;
}

public class GetUserProfileQuery { private String userId; }
public class ReadUserEmailQuery  { private String userId; }
```

```
public class GetUserProfileQueryHandler {
    private UserRepository userRepository;

    public UserProfileDTO handle(GetUserProfileQuery query) {
        User user = userRepository.findById(query.getUserId());
        return new UserProfileDTO(user.getId(), user.getName(), user.getEmail());
    }
}

public class ReadUserEmailQueryHandler {
    private UserRepository userRepository;

    public String handle(ReadUserEmailQuery query) {
        User user = userRepository.findById(query.getUserId());
        return user != null ? user.getEmail() : null;
    }
}
```

Notice the granularity. `ReadUserEmailQuery` returns just a `String` — not a whole object. Read models can be **as narrow as the screen actually needs**, and that's precisely the optimisation opportunity CQRS opens up. Each query gets its own purpose-built shape rather than everyone sharing one bloated object.

Also note the handlers return **DTOs, not domain objects**. The read side is deliberately not exposing the write side's model.

Infrastructure

```
public class SimpleCommandBus implements CommandBus {
    private CreateUserCommandHandler handler;

    @Override
    public void dispatch(CreateUserCommand command) {
        handler.handle(command);
    }
}

public class SimpleQueryBus implements QueryBus {
    private GetUserProfileQueryHandler handler;

    @Override
    public UserProfileDTO dispatch(GetUserProfileQuery query) {
        return handler.handle(query);
    }
}

public class SimpleEventStore implements EventStore {
    private List<UserEvent> events = new ArrayList<>();

    @Override
    public void storeEvent(UserEvent event) {
        events.add(event);
    }
}
```

The buses route to handlers; the event store captures changes as a series of events which, in a full application, can be **replayed to rebuild the state of an entity** (one individual business object, such as a specific user).

> **Where this example actually sits:** it's **Level 1**. Both sides still share the same `UserRepository` and the same database. The event store is present but unused by the read path. That's not a flaw — Level 1 is where most real systems should live, and it already delivers the design clarity that is CQRS's main benefit.

Part 6 — Issues, considerations, and performance

Complexity

Implementing CQRS introduces **a fair amount of complexity**. Maintaining two separate models — command and query — is a complex task. This can be a roadblock for developers unfamiliar with the pattern, and **the learning curve is steep**.

> The course's image: like weaving a basket, the more intricate the design, the more complex the weaving process.

Managing data consistency

One of the significant challenges is maintaining consistency between the command model and the query model.

The scenario: the command model changes, but the query model hasn't been updated yet. **What happens if a query arrives during that interval? It returns outdated data.**

> This is the central trade-off of CQRS, and the one to raise in an interview. In UI terms: a user saves their profile, the page reloads, and their old name is still showing. Common mitigations

> include having the UI **optimistically** display (show the expected result before the server confirms it) what the user just submitted, or routing reads immediately after a write to the write model.

Handling transactions

In traditional CRUD, handling transactions is relatively straightforward. In CQRS it gets complicated.

The scenario: you need to perform multiple commands as part of a single logical transaction. What if one command fails? **How do you roll back the changes from previous commands?** Remember, commands change system state.

> The course's image: like painting a wall — if you make a mistake with one colour you can't simply erase it; you may need to repaint the entire wall.

(This is exactly the problem the Saga pattern addresses with compensating transactions.)

Dealing with asynchronicity

CQRS often comes with asynchronous operations, making **error handling and debugging more complex**. In a system where operations are performed asynchronously, **tracking down the source of an error is challenging**.

The performance upside

On the brighter side, a compelling reason to use CQRS is its **potential to improve performance**. By segregating commands and queries you optimise each side for its specific purpose.

For instance, if you find queries outnumber commands, you can **allocate more resources to the query side** to ensure smooth operation.

> The course's image: putting more trains on your busiest routes while maintaining fewer services where demand is low.

Part 7 — Use cases

High-performance applications

The most compelling case: applications where **the number of reads significantly outweighs the number of writes**. An e-commerce platform where millions of users browse products (queries) compared to a much smaller number of transactions (commands). It makes obvious sense to optimise the system for the higher volume of reads.

Complex business logic

Where a system has **complex business logic that modifies state**, separating read and write responsibilities simplifies that complexity.

> The course's image: division of labour on a factory assembly line — each worker focuses on their specific task, leading to improved efficiency and higher quality output.

The practical benefit: your write model can be rich with rules and **invariants** (conditions that must always hold, e.g. "balance never negative") without that complexity slowing down or complicating every read.

Collaborative domains

Where **many users can update the same data**, CQRS helps manage conflicts. Picture a shared document edited by several people simultaneously. **If updates are treated as commands that can fail or be**

rejected based on rules, it becomes much easier to handle this collaborative environment.

Part 8 — System design examples

Event-driven microservices

An e-commerce system handling orders. Each order goes through stages: **placed, paid, shipped, delivered**.

Each stage is a **state change driven by commands**. Meanwhile, different **microservices** (small, independently deployed services) need to **query** the state of an order — a shipment tracking service, a customer notification service. Using CQRS here leads to a cleaner, more efficient system design.

Real-time analytics

(**Analytics** means computing statistics and reports from raw data.) A social media platform where users are constantly **posting updates (commands)** while the platform simultaneously provides **real-time analytics about user engagement (queries)**.

Their performance needs are genuinely opposite:

- **Commands must be fast and reliable** to provide a smooth user experience
- **Queries require heavy computation** but are **not time-critical**

By segregating these responsibilities, the system can **optimise resource allocation to meet these differing needs**. This is a textbook fit — the two **workloads** (streams of work of one kind) would actively harm each other sharing one model.

Part 9 — Common beginner misconceptions

"CQRS requires two databases." No — that's Level 2. Level 1 is two models over one database, and it's where most systems should live.

"CQRS requires event sourcing." No. They're frequently discussed together and complement each other, but they're independent choices. You can do CQRS with no events at all.

"CQRS is the same as read replicas." Read replicas are copies of the *same* database, kept in sync, used to spread read **load**. CQRS means a *different model* shaped for reading. You can use both.

"Commands are just HTTP POSTs." (A POST is the web request type used to create or submit something.) Commands are a design concept, not a **transport** detail (how the message travels). A command is an explicit object representing intent — which is what lets you queue, log, and replay it.

"It's always faster." It adds **indirection** (extra layers between caller and data). It's faster when read and write workloads genuinely conflict, and pure overhead when they don't.

"Apply it to the whole application." Almost always wrong. Apply it to the **specific parts** where read and write needs genuinely diverge, and leave simple CRUD as CRUD.

Part 10 — Check your understanding

1. Why can't one database schema be optimal for both reads and writes?
2. What are the two halves of the formal rule, and why does "never both" matter?
3. Which level of CQRS should most teams adopt, and why?
4. What specific problem does event sourcing solve that Level 2 has?
5. What is the central trade-off, expressed as something a user would notice?
6. Why is the social media analytics example a textbook fit?

(Answers: 1 — writes want normalised storage where each fact lives once, reads want denormalised pre-joined shapes, and these are directly opposed; 2 — queries return data and change nothing, commands change state and return only success or failure; "never both" makes queries safely repeatable and

cacheable and makes commands explicitly consequential; 3 — Level 1, two models over one database, because it gives the design clarity with almost none of the operational cost; 4 — out-of-order event delivery leaving the read model stale, solved by replaying an append-only event stream; 5 — the consistency window: a user saves their profile and the page still shows the old value; 6 — posting must be fast and reliable while analytics is computation-heavy but not time-critical, so the two workloads would degrade each other if they shared a model.)

Part 11 — Interview soundbite (30 seconds)

> "CQRS separates the write path from the read path — commands that change state and return nothing, queries that return data and change nothing. The motivation is that reads and writes usually have opposite requirements: in a banking app, transactions need accuracy and security while balance inquiries need raw speed, and at the storage level writes want normalised data while reads want denormalised pre-joined shapes, so you can't tune one model for both. It's a spectrum, and being clear about which level you mean matters. The simplest version is two models over one database, which is where most systems should stop — you get the design clarity with almost no operational cost. The next level is separate read and write databases, which buys independent scaling but costs you atomic transactions, so you're on eventual consistency via async events and dealing with out-of-order delivery and lost messages. The furthest level is event sourcing, where the write side is an append-only event log and you rebuild read models by replaying it. That solves ordering and gives you audit history and the ability to build entirely new read models from past events, but it's a big undertaking and a separate decision from adopting CQRS. The main downside throughout is the consistency window — a user saves their profile and the page still shows the old name — plus genuine complexity and harder debugging. It pairs naturally with event-driven architecture, and with sagas when one logical transaction spans multiple commands."

Part 12 — Implementation

A. Runnable demo

Full source: `demos/CqrsDemo.java`

```
cd demos && ./gradlew runCh12
```

The formal rule made mechanical — command handlers return `void`:

```
void handle(ChangeEmail cmd) {                    // <- returns void
    User u = writeStore.get(cmd.userId());
    if (!cmd.newEmail().contains("@")) throw new IllegalArgumentException("invalid email");
    String old = u.email;
    u.email = cmd.newEmail();
    publish(new UserEvent.EmailChanged(cmd.userId(), old, cmd.newEmail()));
}

UserProfileView get(String id) { return store.get(id); }   // <- returns data, changes nothing
```

Rebuilding a read model from the event log — the Level 3 superpower:

```
fast.clear();                             // wipe the read model entirely
eventStore.all().forEach(fast::apply);    // replay history
```

B. What you should see

```
=== 3. Level 2: separate read store -> CONSISTENCY WINDOW ===
  write store immediately: carol@new.com
  read model immediately:  carol@old.com   <- STALE
  read model after 300ms:  carol@new.com   <- converged

=== 4. Several read models from ONE write ===
  profile view : UserProfileView[id=u4, name=Dave, email=dave@x.com]
  directory view: [UserDirectoryEntry[name=Dave, initial=D], ...]

=== 5. Level 3: rebuild the read model by replaying events ===
  after wiping the read model:  null
  after replaying the log:      UserProfileView[id=u1, name=Alice, ...]
```

Section 3 is the trade-off you must be able to describe in an interview, and here it's observable: the write store has the new email while the read model still has the old one. That's not a bug — it's the deal you accepted. Section 5 shows the compensating power: **read models are disposable**, because the event log is the truth.

C. Production — Axon Framework

(**Axon** is a Java framework for CQRS and event sourcing. An **aggregate** is a cluster of objects treated as one unit for changes — here, one user — and annotations like `@CommandHandler` tell Axon which method handles which message.)

```java
@Aggregate
public class UserAggregate {

    @AggregateIdentifier private String userId;
    private String email;

    @CommandHandler
    public UserAggregate(CreateUserCommand cmd) {
        if (!cmd.email().contains("@")) throw new IllegalArgumentException("invalid email");
        AggregateLifecycle.apply(new UserCreatedEvent(cmd.userId(), cmd.name(), cmd.email()));
    }

    @CommandHandler
    public void handle(ChangeEmailCommand cmd) {
        if (cmd.newEmail().equals(this.email)) return;              // no-op, no event
        AggregateLifecycle.apply(new EmailChangedEvent(cmd.userId(), this.email, cmd.newEmail()));
    }

    // State is derived by applying events - never assigned directly
    @EventSourcingHandler
    public void on(UserCreatedEvent e) { this.userId = e.userId(); this.email = e.email(); }

    @EventSourcingHandler
    public void on(EmailChangedEvent e) { this.email = e.newEmail(); }
}
```

The projection — the read side: (a **projection** builds a read model by applying events to it)

```java
@Component
public class UserProfileProjection {

    private final UserProfileRepository repo;

    @EventHandler
    public void on(UserCreatedEvent e) {
        repo.save(new UserProfileView(e.userId(), e.name(), e.email()));
    }

    @EventHandler
    public void on(EmailChangedEvent e) {
        repo.findById(e.userId()).ifPresent(v -> { v.setEmail(e.newEmail()); repo.save(v); });
    }

    @QueryHandler
    public UserProfileView handle(FindUserProfileQuery q) {
        return repo.findById(q.userId()).orElseThrow();
    }
}
```

Plain Spring, no framework — Level 1, which is where most systems should live. (**Spring** is the main Java application framework; **JPA**, the Java Persistence API, maps Java classes to database tables; a **native query** is raw SQL written by hand.)

```java
// Write side: JPA against a normalised schema
public interface UserRepository extends JpaRepository<User, String> {}

// Read side: a projection interface or native query against a denormalised view
public interface UserProfileReadRepository extends Repository<UserProfileView, String> {
    @Query(value = """
        SELECT u.id, u.name, u.email, COUNT(o.id) AS order_count
        FROM users u LEFT JOIN orders o ON o.user_id = u.id
        WHERE u.id = :id GROUP BY u.id
        """, nativeQuery = true)
    UserProfileView findProfile(@Param("id") String id);
}
```

> **You do not need Axon, Kafka, or event sourcing to do CQRS.** Two repositories and two model classes over one database is legitimate CQRS and delivers most of the benefit.

Handling the consistency window in the UI — three practical options:

```java
// 1. Read-your-own-writes: route reads right after a write to the write model
if (recentlyWrittenBy(userId)) return writeModel.find(userId);
return readModel.find(userId);

// 2. Return the new state from the command endpoint so the UI can render optimistically
// 3. Return a version token; the client polls the read model until it catches up
```

(In option 3, a **version token** is a number identifying the write; to **poll** is to ask repeatedly until the answer is ready.)

D. Implementation pitfalls

1. Jumping straight to Level 3. Event sourcing is a large, hard commitment — schema evolution for events, **snapshotting** for long streams (saving the full state every so often so replay can start from there), replay tooling. Adopting it *because* you adopted CQRS is the most common way teams get into trouble. Start at Level 1.

2. Commands that return data. The moment `handle()` returns the updated entity, the rule collapses and you're back to one model. Return void, or at most an ID.

3. Business logic in the read model. Projections should only *shape* data. Any rule that decides something belongs on the write side, or the two sides will disagree.

4. Ignoring the consistency window in the UI. Users who save and immediately see stale data file bugs. Design for it explicitly with one of the three techniques above.

5. Not being able to rebuild projections. The main benefit of event sourcing is disposable read models — but only if replay is *tested*. Make rebuilding a routine operation, not a theoretical one.

6. Unbounded event streams. An aggregate with 100,000 events takes forever to load by replay. Use **snapshots** — persist state every N events and replay only from there.

7. Applying CQRS everywhere. Simple CRUD entities should stay CRUD. Apply it where read and write needs genuinely diverge, and be able to say *why* for each place you use it.

8. Events named as commands. `UpdateEmail` is a command; `EmailChanged` is an event. Getting the tense wrong signals a design where events are really disguised instructions, which reintroduces **coupling** (components depending on each other's internals).

Related patterns

- **Event-Driven Architecture** — the substrate that syncs command and query sides
- **Saga** — for transactions spanning multiple commands, where rollback isn't automatic
- **BFF** — read models shaped per client is the same instinct as BFF applied to data

Configuration Externalization Pattern

Category: Operations **One-liner:** Move configuration out of application code and deployment packages into a centralized store that services fetch at **runtime** (while they are running) — so changing config doesn't require rebuilding and **redeploying** (releasing a new build to the servers).

Part 0 — Concepts you need first

What is "configuration"?

Configuration is the set of values that control how an application behaves, but which **aren't the application's logic**. Typical examples:

- Database **connection strings** (the address and options used to connect to a database) and **credentials** (usernames and passwords)
- **API keys** (secret tokens identifying your program to another service) and **endpoint** URLs (the web addresses a service answers on) for external services
- **Timeout** durations (how long to wait before giving up), retry counts, **thread pool** sizes (how many worker threads a service keeps for handling requests)
- Feature flags — switches turning functionality on and off
- Region-specific values: currency, tax rate, language

The test for whether something is configuration: **would you want a different value in development versus production, or in one region versus another, without changing the code?** If yes, it's configuration.

What does "hardcoded" mean?

A value written directly into the source code:

```
String dbUrl = "jdbc:postgresql://prod-db-01:5432/orders";
```

Changing it means editing the source, **recompiling** (turning source code into a runnable program again), and redeploying. The value is **frozen into the built artifact** (the packaged output of the build).

What is a "deployment package"?

The bundle you actually ship — a **JAR** (Java ARchive, the packaged form of a Java program), a **container image** (a snapshot of an app plus everything it needs, used to start containers), a zip. "Bundled configuration" means the config file travels *inside* that package. Better than hardcoding (you can read it without recompiling), but **still frozen at build time**: to change it you rebuild the package and redeploy.

What is a "deployment cycle"?

The full process of getting a change into production: build → test → review → deploy → verify. In a well-run organisation this might take an hour. In a regulated one it might take days.

The core complaint of this chapter: that entire process, for changing one number.

What is an environment?

A separate copy of your system for a purpose — **development** (engineers experimenting), **staging/testing** (rehearsal), **production** (real users — the live system). Same code, different configuration: different databases, different API keys, different scale.

What is a secret?

Configuration that must not be disclosed — database passwords, API keys, **encryption keys** (the secret values used to scramble and unscramble data). **Secrets are configuration, but with much stricter handling requirements**, which becomes a recurring theme below.

Part 1 — The framing

Picture yourself as an architect designing a city. Would you place the blueprint of every building **inside** each one, hard-coded into the walls? Or keep it separate, accessible, and modifiable, so each building can adapt to changing needs?

The answer is obvious for physical structures. The same principle applies to software.

In **microservices** (an architecture of many small, independently deployed services), configuration determines how efficiently applications run and adapt. Whether it's network settings, database parameters, or feature toggles, **each microservice has a set of configurations governing its behaviour**.

Traditionally these are hardcoded into the application or bundled within the deployment package. But is that efficient? **What happens when you need to change a parameter? A new deployment cycle for a minor tweak?**

Part 2 — The problem

Volume and diversity

Picture your architecture as a bustling city, each microservice a building with its own purpose and configuration. Now imagine **each building is from a different era, built with diverse architectural styles and materials.** That's what a microservices architecture often looks like — many services, possibly written in **different languages using different technology stacks** (each its own set of languages, frameworks and libraries).

Managing configuration across all of them quickly becomes a nightmare, because each stack has its own conventions for where config lives and how it's read.

The drawbacks of hardcoding

Hardcoding is **like permanently etching the blueprint onto a building's facade**. It seems fine initially — everything's in one place. The downsides appear when you need to change something.

Hardcoding ties configuration **tightly to the application code**. Consequences:

- **Any change, no matter how minor, requires a new version of the application followed by a complete redeployment**
- This **slows the adaptability** of your microservices
- **It introduces risk.** If a configuration error slips into production, you face **another round of building and deployment** — wasting resources and, in the worst case, causing **significant downtime** (time when the system is unavailable to users)

> That last point is the one worth dwelling on. A typo in a database **hostname** (the network name of a machine) is a five-second fix conceptually, but a full deployment cycle in practice — and you're doing it while production is broken.

The burden of scale

These issues are magnified in microservices by the sheer scale of the system.

> Return to the city analogy: now imagine you need to modify the blueprint of **every single building**. That's what engineers face when configuration is hardcoded or bundled within each microservice.

In a **monolithic** architecture (one application deployed as a single unit), configuration is usually **centralized and managed in one place**. In **microservices**, each service comes with its own configuration maintained independently. This lack of centralization **amplifies the workload** and **increases the risk of inconsistencies and errors** across the system.

> A concrete inconsistency: you **rotate** a database password (replace it with a new one, as routine security hygiene) and update it in fourteen services. You miss one. That service keeps working until its **connection pool** (its set of already-open database connections, reused across requests) recycles — possibly hours later — and then fails in a way that looks unrelated to anything you did.

Inflexibility of deployments

Microservices are known for adaptability — different services deployed independently, enabling faster releases and efficient **scaling** (adding capacity to handle more load). **Traditional configuration management severely hampers this flexibility.**

With hardcoded or bundled configuration, **each minor change could necessitate a full redeployment of a service**. This is inefficient, and it **negates the independent deployment advantage** that is microservices' main selling point. It also leads to **inconsistencies in configuration across environments** — development, testing, production.

Inability to adapt to dynamic environments

Microservices often operate in dynamic environments where conditions change rapidly, and those conditions influence what configuration gives optimal performance:

- **Network settings** may need adjusting based on **traffic patterns**
- **Feature toggles** may need flipping based on **user behaviour**

With traditional configuration management, **responding to these conditions in real time (as they happen) becomes nearly impossible.** Your services are **stuck with outdated configuration until the next deployment cycle**, impacting performance and user experience.

Security implications

Hardcoded configuration can lead to **sensitive information — database credentials, API keys — being exposed or leaked**. This is a security risk with serious consequences for your system and your users' data.

> The most common way this happens in practice: a credential hardcoded in source is **committed** to **version control** (a system such as **Git** that records every change to files, with who made it and when), and now it exists in the **repository**'s (the project's stored files and history) history **forever**, visible to everyone with read access — and permanently, since rewriting Git history is painful and rarely complete. Rotating the credential is the only real remedy.

Part 3 — The solution

Apply **separation of concerns** (keeping different responsibilities in different places) to configuration management: **externalize configuration from application code**, storing and managing it in a **separate, centralized location**.

> Take all the blueprints of the city's buildings and keep them in a **central town hall**, away from the buildings themselves. The blueprints become easy to update and review without disturbing the buildings.

Mechanically: configuration is no longer part of the deployment package. It's stored externally in a **configuration server** (a service whose only job is to hand configuration to other services) or a file in a network-accessible location. The microservice **retrieves configuration at runtime**, ensuring it always has the most up-to-date values.

Why this is advantageous

A unified, centralized location for managing all configuration. This directly addresses the volume and diversity problem: **regardless of a microservice's language or technology stack, configuration is retrieved from the same place**, simplifying management and reducing errors.

Support for dynamic environments. Since configuration is retrieved at runtime it can be **updated in real time** as conditions change. Services **no longer wait for the next deployment cycle** to adapt — they're as dynamic as the environment they operate in.

Preserved independent deployment. Separating configuration from code upholds the microservices principle of independent deployment. Configuration changes **no longer necessitate a full redeployment**; they're updated centrally and become immediately available.

Enhanced security. With configuration externalized and centrally managed, it's **easier to enforce security policies and controls**. Sensitive information is **no longer scattered across microservices** — it's securely stored and managed in one place, reducing the risk of exposure or leaks.

Efficient scalability. The pattern scales with your architecture. As new microservices are added, their configuration is simply included in the centralized location. **No need to navigate through each service** to update configuration.

Consistency across environments. Moving from development to testing to production can feel like entering different countries with different rules. Configuration for all environments is **centrally managed**, keeping them in sync and reducing errors when promoting between them.


Part 4 — Architecture

At the heart of the pattern are two components: **the microservice** and the **configuration server** (or configuration file).

The interaction

The microservice, **at startup or at pre-defined intervals**, sends a request to the configuration server asking for its configuration. This can include **database connection settings, API keys, or any other environment-specific data**. The server responds with what that service needs.

What's notable is that this exchange happens **dynamically, at runtime**. The microservice can adapt in real time to new configuration **without needing a restart or redeployment**, reducing downtime and enhancing **agility** (the ability to change quickly).



The configuration server

The **nerve centre** — think of it as the command centre overseeing and controlling all configuration. It stores, retrieves, and manages configuration for all microservices.

To streamline things, configuration can be organised:

- **By environment** — development, staging, production
- **By microservice**
- **By instance** of a microservice (one particular running copy)

> Like a well-organised library, with each configuration neatly categorised and easy to find. This organisation is what mitigates the challenges of traditional configuration management — it's not just centralized, it's *navigable*.

Dynamic adaptability in practice

Suppose you have a microservice interacting with a database, with connection parameters stored as configuration. Suddenly the database connection parameters change.

Instead of redeploying the microservice with the new parameters, you update the configuration server. The microservice, when it next retrieves configuration, **receives the updated parameters and continues its operation seamlessly.**

Security — safeguarding sensitive configuration

Returning to the library analogy: **not all books are open for everyone to read.** Some configuration contains sensitive data needing protection.

The configuration server can secure sensitive configuration through **encryption** (scrambling data so only key-holders can read it) or **access controls** (rules about who may read or change what). By centralizing management of these values, it's **easier to enforce strict security policies**, reducing the risk of inadvertent exposure or malicious attack.

Scalability and consistency

As you add more microservices, you simply add their configuration to the server — **no worrying about individually managing configuration for each new service.**

And by externalizing configuration you maintain **consistency across environments**. You **switch configuration as you move through environments** — no environment-specific code, no configurations getting mixed up.

Part 5 — Worked example: Spring Cloud Config

Spring Cloud Config (part of Spring Cloud, the microservices toolkit built on the Spring Java framework) is widely adopted in the Java community for centralized configuration management in microservices, due to its simplicity and efficiency.

The configuration server

```
@SpringBootApplication
@EnableConfigServer
public class ConfigServer {
    public static void main(String[] args) {
        SpringApplication.run(ConfigServer.class, args);
    }
}
```

With just these few lines you've turned an application into a configuration server. The `@EnableConfigServer` **annotation** (a label starting with `@` that tells the framework to add behaviour) does the work.

The configuration store — a Git repository

Now tell the server where to find the configuration, in a **properties file** (a plain-text file of `key=value` settings):

```
spring.cloud.config.server.git.uri=https://github.com/yourusername/config-repo
```

This tells the configuration server to fetch configuration from the specified Git repository.

> **Using Git here is genuinely clever, and worth understanding rather than skimming.** By storing configuration in a version-controlled repository you get, for free: a full history of every change and who made it, **diffs** showing exactly what changed, **pull requests** (proposed changes that others review before they are merged) and **code review** *for configuration*, and the ability to **roll back to any previous state** with a standard Git operation. Configuration becomes a first-class engineering artifact rather than a value someone typed into a form.

The client setup

In the microservice's **build file** (the file, such as `pom.xml` or `build.gradle`, that lists what the project needs), add the Spring Cloud Config Client **dependency** (an external library the project uses). Then annotate the main class with `@EnableConfigClient`. The microservice is now a configuration client, ready to consume configuration from the server.

Pulling configuration — the `@Value` annotation

```
@Value("${my.property}")
private String myProperty;
```

`my.property` is a property defined in the configuration store. `@Value` fetches its value and assigns it to the field. **Note how little the application code knows** — it references a property name, not a location or a mechanism.

Refreshing without restarting

```
POST /actuator/refresh
```

Sending a **POST** request (the HTTP method for submitting an action) to this endpoint — provided by **Spring Boot Actuator**, Spring's built-in management module — triggers the configuration client to **re-fetch configuration from the server** — new configuration applied **without restarting the microservice.**

This is the payoff of the whole pattern in one endpoint: change a value centrally, hit refresh, done.

Encryption and decryption

```
encrypt.key=MySuperSecretKey
```

This sets the encryption key used to encrypt and decrypt properties. To encrypt a property use the `/encrypt` endpoint; to decrypt, `/decrypt`.

> ⚠️ **Notice the irony, because it matters in practice.** `encrypt.key` is itself a secret, sitting in a plain properties file. You've encrypted all your secrets and left the key to them in the open. In production this master key belongs in a dedicated **secrets manager** (a service built to store, hand out and rotate secrets securely) — **HashiCorp Vault, AWS Secrets Manager, or a cloud KMS** (key management service — a cloud service that stores encryption keys in protected hardware) — with the config server retrieving it at startup. **The pattern relocates the secret problem; it doesn't eliminate it.** For secrets specifically, a purpose-built secrets manager usually beats a general configuration server.

Part 6 — Considerations and implications

Data security

While the pattern aids security, **it also introduces a new surface area for potential attacks** (another place an attacker could target). You are now storing sensitive configuration data **remotely**. How secure is your storage? Is your data transfer secure?

To ensure security, consider **encryption**. The `MySuperSecretKey` example is just the tip of the iceberg — from using **secure and encrypted connections** to **regularly rotating keys**, you need to stay ahead in the security game.

The configuration server as a single point of failure

While centralizing simplifies management, it **introduces a single point of failure** (one component whose failure stops everything).

> **What happens if your configuration server goes down? All your microservices would be paralysed, unable to fetch or refresh their configuration.**

Mitigation: introduce **redundancy** (spare copies). Run **multiple instances** of your configuration server in a **high-availability configuration** (set up so the service stays up even if one copy fails). And **regular health checks** (automatic "are you alive?" probes) **are crucial.** See System Design Fundamentals for these ideas in general.

> Add to this the mitigation the course covers under performance: **client-side caching of last-known-good configuration** (each service keeps a local copy of the last values it fetched successfully). This is what makes the whole trade acceptable. You've swapped "config changes require a redeploy" for "config server outage could take everything down" — and caching converts that second risk from fatal to merely inconvenient, because running services keep using the values they already have. This is the identical **resilience** trick (a way of staying up when parts fail) used in Service Discovery.

Configuration versioning and rollbacks

The pattern allows easier scalability and quicker feature rollouts. But **what happens when you need to roll back?** Can you easily revert to a previous configuration if something goes wrong?

The good news: version control systems like **Git** provide the solution. Storing configuration in a version-controlled repository means you can **easily roll back to a previous state**.

But this **requires good configuration management practices**: Are your changes well documented? Are versions correctly labelled? Git gives you the capability; discipline is what makes it usable at 3am during an **incident** (a production outage or emergency).

Service discovery and the config service

In a dynamic microservices environment, services come up and down and scale based on **load** (the amount of work arriving). **How do new services discover the config service?**

Hardcoding the configuration server's address in each microservice isn't a scalable solution — and note the irony: you'd be hardcoding a location in order to avoid hardcoding configuration.

This is where **service discovery** (a registry that tells services where other services currently are) comes in. Tools like **Netflix's Eureka** or **HashiCorp's Consul** (two popular service registries) dynamically discover services in your architecture, **including the configuration server**. *(See Service Discovery.)*

Performance implications

Fetching configuration remotely may introduce latency (extra delay), especially if the configuration server is under heavy load or network issues arise.

Caching helps reduce this latency — Spring Cloud Config clients **cache remote properties by default**.

But caching brings its own considerations:

- **How often do you refresh the cache?** Too often and you hammer the server; too rarely and changes take a long time to take effect
- **What's the impact on memory usage?**

> It's a balancing act between **performance and freshness of configuration.**

Part 7 — Real-world use cases

E-commerce platform

Several microservices — Inventory, Order, User Management — each interfacing with various databases and APIs, each with its own configuration. With **hundreds of services running across production, staging, and development**, managing configuration is a nightmare.

The pattern externalizes all configuration to a central server. Each service fetches what it needs. **Changes are made in one place and reflected across the system.**

Financial services firm

A highly regulated environment. The firm must ensure **sensitive data like API keys and database passwords are not exposed**.

Using this pattern, all sensitive configuration is stored in the central configuration server, **possibly in encrypted form**. Services fetch configuration **over a secure channel** (an encrypted connection) and use it. **No sensitive data is stored in the service codebase or containers** (the **codebase** is the source code; **containers** are the packaged, isolated running apps) — which is exactly what **auditors** (people who check a company follows its rules and regulations) want to see.

Global fast-food chain

Outlets in numerous countries, each with an application managing orders, inventory, and logistics. But **each country has its own tax laws, currency, and language preferences.**

The chain uses the pattern to manage **country-specific configuration**. When an application boots up it **fetches the configuration for the country it operates in** — like having a personalized configuration per country, from one shared codebase.

Tech startup

A startup developing a streaming service, following **agile** practices (working in short cycles and shipping small changes often) with **multiple deployments each day**. Each deployment may require configuration changes — **feature flags or A/B testing parameters** (A/B testing shows two versions to different users to compare which works better).

The pattern lets them easily manage this dynamic configuration. Each service fetches updated configuration whenever it needs it, making **deployments faster and smoother**.

Telecommunications giant

Complex network infrastructure managed by numerous microservices. **Network parameters like bandwidth** (data-transfer capacity), **routing information, and security protocols** (agreed rules for securing communication) need meticulous management.

All network configuration is stored centrally; each microservice fetches what it needs, giving efficient management of complex configuration.

Part 8 — Common beginner misconceptions

"Externalizing config means putting it in a file next to the app." That's still bundled config. Externalizing means it lives **outside the deployment artifact**, retrieved over the network.

"A config server is the right place for secrets." It's *better* than hardcoding, but a dedicated secrets manager (Vault, AWS Secrets Manager) gives you **leasing** (secrets that are handed out for a limited time

and then expire), automatic rotation, fine-grained access policies, and **audit logs** (records of who accessed which secret, when) that a general config server doesn't.

"Environment variables are the same thing." (An **environment variable** is a named value the operating system passes to a program when it starts.) They're a good, simple form of externalization and often sufficient. What they don't give you is **central management, versioning, or refresh without a restart** — changing an environment variable means restarting the process.

"If the config server is down, everything stops." Only without client-side caching. With caching, **running services keep running**; you just can't start new ones or push changes. Design for that.

"Config changes are low risk because there's no deploy." The opposite concern applies — no deploy means **no build, no tests, no review** unless you deliberately add them. That's precisely why backing the store with Git and requiring pull requests matters.

"One config server for everything." Consider separating by **trust boundary** (a line between parts of the system that should not automatically trust each other). Not every service should be able to read every other service's configuration.

Part 9 — Check your understanding

1. What's the difference between hardcoded, bundled, and externalized configuration?
2. Why does hardcoded configuration undermine the main benefit of microservices?
3. What does backing the config store with Git give you for free?
4. What's the central irony of the `encrypt.key` property?
5. Why do you need service discovery in order to do configuration externalization well?
6. What makes the config server's single-point-of-failure risk acceptable?

*(Answers: 1 — hardcoded is in source and needs recompiling; bundled is in the deployment package and needs rebuilding and redeploying; externalized lives outside the artifact and is fetched at runtime; 2 — independent deployability, because a one-line config change forces a full redeploy of the service; 3 — change history, authorship, diffs, code review, and rollback to any previous state; 4 — it's a secret protecting all other secrets, stored in **plaintext** (unencrypted), so it belongs in a real secrets manager; 5 — hardcoding the config server's address in every service would reintroduce the exact problem you're solving; 6 — client-side caching of last-known-good values, so running services survive a config server outage.)*

Part 10 — Interview soundbite (30 seconds)

> "Configuration externalization moves config out of application code and deployment packages into a central config server that services fetch at runtime. The problem it solves is that hardcoded config ties every change to a full build-and-deploy cycle, which destroys the independent deployability that's the whole point of microservices — and means you can't react to changing conditions until the next release. It also scatters secrets like database credentials across every service and into version control history. With a config server you organise config by environment, service, and instance; services fetch at startup or on an interval, and Spring Cloud Config exposes an actuator refresh endpoint so you can apply changes without restarting. It's typically backed by a Git repo, which is the clever part — you get versioning, diffs, code review, and rollback on your configuration for free. The main trade-offs are that the config server becomes a single point of failure, so it needs HA plus client-side caching of last-known-good values so a config outage degrades rather than kills you; you've created a new attack surface holding all your secrets, so encryption in transit and key rotation matter; and services need service discovery to find the config server, because hardcoding its address would reintroduce the exact problem you're solving. For secrets specifically I'd use a dedicated secrets manager like Vault rather than a general config server, since you get leasing, rotation, and audit logging."

Part 11 — Implementation

A. Runnable demo

Full source: `demos/ConfigExternalizationDemo.java`

```
cd demos && ./gradlew runCh13
```

Layered resolution — later layers override earlier ones:

```
Map<String, String> fetch() {
    Map<String, String> merged = new LinkedHashMap<>();
    layers.values().forEach(merged::putAll);   // default <- environment <- instance
    return merged;
}
```

The cache that survives a server outage:

```
void refresh() {
    try {
        cache = server.fetch();
        cachedVersion = server.version();
    } catch (IllegalStateException e) {
        // server unreachable - KEEP the previous config rather than failing
    }
}
```

And the detail that makes runtime flips work — read config **at use time**, not at startup:

```
String checkout() {
    return config.flagEnabled("feature.newCheckout")   // read on every call
            ? "NEW checkout flow" : "legacy checkout flow";
}
```

B. What you should see

```
=== 3. Change a value + refresh, NO restart ===
  before refresh: ... timeout=1000ms ...
  after refresh:  ... timeout=5000ms ...
  >> same running process, new value

=== 4. Layering: instance overrides environment overrides default ===
  ... timeout=9000ms ...
  >> instance layer won (9000), overriding environment (5000)

=== 5. Feature flag flipped centrally ===
  checkout now: legacy checkout flow
  checkout now: NEW checkout flow
  and svc2 too: NEW checkout flow
  >> every service flipped at once, with no deployment

=== 6. Config server outage ===
    [client] server DOWN - keeping cached config (v8)
  checkout still: NEW checkout flow
  >> running services keep working on cached config
```

Section 5 is the payoff — one central change flipped behaviour in every running service simultaneously, with no build and no deploy. **Section 6 is the safety net** that makes centralizing acceptable: the config server died and nothing stopped.

C. Production — Spring Cloud Config

The server:

```java
@SpringBootApplication
@EnableConfigServer
public class ConfigServerApplication {
    public static void main(String[] args) { SpringApplication.run(ConfigServerApplication.class, args); }
}
```

```yaml
server.port: 8888
spring:
  cloud.config.server.git:
    uri: https://github.com/acme/config-repo
    default-label: main
    clone-on-start: true
    search-paths: '{application}'          # per-service folders
  security.user:
    name: configuser
    password: ${CONFIG_SERVER_PASSWORD}    # itself injected, not committed
```

The repository layout — this is what gives you environment layering:

```
config-repo/
├── application.yml                # defaults for EVERY service
├── application-prod.yml           # defaults for every service in prod
├── order-service.yml              # all environments of one service
├── order-service-dev.yml
└── order-service-prod.yml         # most specific: wins
```

The client:

```yaml
spring:
  application.name: order-service          # picks which files apply
  config.import: "optional:configserver:http://config-server:8888"
  cloud.config:
    fail-fast: true                        # don't start with wrong config
    retry: { initial-interval: 1000, max-attempts: 6, multiplier: 1.5 }
```

Refresh without restart — the crucial bit is `@RefreshScope` (a **bean** is an object that Spring creates and manages; `curl` is a command-line tool for sending HTTP requests):

```java
@RefreshScope                              // bean is recreated on refresh
@Component
public class CheckoutService {

    @Value("${feature.newCheckout:false}")
    private boolean newCheckoutEnabled;

    public String checkout() {
        return newCheckoutEnabled ? newFlow() : legacyFlow();
    }
}
```

```
curl -X POST http://order-service:8080/actuator/refresh
```

For **fleet**-wide refresh (across every running instance), **Spring Cloud Bus** broadcasts over **Kafka** or **RabbitMQ** (two popular message brokers — servers that pass messages between programs) so one call refreshes every instance:

```
curl -X POST http://any-instance:8080/actuator/busrefresh
```

Secrets belong in a secrets manager, not here: (`KUBERNETES` authentication means Vault trusts the identity Kubernetes gives each **pod** — its unit of running containers.)

```
spring.cloud.vault:
  uri: https://vault:8200
  authentication: KUBERNETES            # pod identity, no static credentials
  kv: { enabled: true, backend: secret }
```

Vault gives you **leasing, automatic rotation, and audit logs** — none of which a general config server provides. Keep ordinary configuration in Git and secrets in Vault.

Kubernetes-native alternative — often all you need. (**Kubernetes** is the standard platform for running containers; a **ConfigMap** is its built-in object for storing configuration, which can be **mounted as a volume** — exposed to the container as files.)

```
apiVersion: v1
kind: ConfigMap
metadata: { name: order-service-config }
data:
  http.timeoutMs: "3000"
  feature.newCheckout: "true"
---
# Mounted as a volume, changes propagate to the file within ~1 min
volumes:
  - name: config
    configMap: { name: order-service-config }
```

Note: ConfigMaps mounted as **volumes** update live; ConfigMaps consumed as **environment variables** do **not** — the pod must restart. That trips people up constantly.

D. Implementation pitfalls

1. Reading config once into a `static final` field (a Java field set once and shared by the whole class). Then refresh does nothing, because the value was captured at **class-load time** (when Java first loaded the class into memory). Use `@RefreshScope`, or read through a provider at each use.

2. No client-side caching or `fail-fast` misconfigured. Without caching, a config server outage takes down every service. With `fail-fast: true` **and** retry configured, startup waits and retries rather than booting with defaults that are silently wrong.

3. Secrets in the Git config repo. Once committed they're in the history permanently. Use Vault or a **sealed-secrets** mechanism (secrets stored encrypted in Git that only the cluster can decrypt), and treat any leaked credential as needing rotation, not deletion.

4. The encryption key stored beside the encrypted values. The irony flagged in Part 5 — you've locked the door and left the key in it. The master key belongs in a KMS or in Vault, injected at startup.

5. No validation of config before it propagates. A typo in a Git commit reaches production in seconds with no build or test to catch it. Add a **CI** job (**continuous integration** — an automated check run on every change) that validates the config repo, and require pull requests — the speed of config changes is a hazard as well as a feature.

6. Changing config in production directly. If your repo is the **source of truth** (the one authoritative copy), an **out-of-band** change (one made outside the normal process) gets silently reverted by the next refresh, producing a genuinely baffling incident.

7. A single config server instance. It's a single point of failure for the whole estate. Run at least two **replicas** (identical running copies) behind a service, and monitor them.

8. Hardcoding the config server's address. Self-defeating. Use service discovery or a stable Kubernetes Service **DNS** name (DNS is the system that turns names into network addresses).

9. Assuming env-var ConfigMaps refresh. They don't. Only volume mounts propagate without a restart.

Related patterns

- **Service Discovery** — how services locate the config server; identical HA and caching concerns
- **Sidecar** — a sidecar can fetch config and expose it locally to the application

- **Strangler Fig** — the feature flags driving migration routing live in externalized config
- **Circuit Breaker** — breaker thresholds are configuration you'll want to tune without redeploying

Chapter 14 — Interview Question Bank

How to use this bank

This chapter collects the microservices questions that come up again and again in interviews: the ones on popular question lists (InterviewBit, GeeksforGeeks, devinterview.io, DataCamp, TechPrep), in LeetCode Discuss interview-experience posts for backend and Java/Spring roles, and in senior "scenario" rounds. They are worded the way interviewers usually ask them.

- ★ marks a question that appears on many lists or is reported very often. If you are short on time, drill the ★ questions first.
- Every question has a **short answer you can say out loud** in 30–60 seconds. The answers are written for this book and assume the versions used in the rest of it: **Java 25, Spring Boot 4.1, Spring Framework 7, Spring Cloud 2025.1 ("Oakwood"), Kafka, PostgreSQL, Kubernetes**.
- → **More:** links point to the chapter (or the section of Chapter 1) that explains the topic in full. Questions without a link are not covered elsewhere in the book, so the answer here is the complete one.
- New terms are defined the first time they appear. If a word is still unfamiliar, the 300-term glossary at the end of Ch 1 — System Design Fundamentals has it.

How to drill: cover the answer, say your own answer out loud, then uncover and compare. Mark the ones you fumbled and repeat them the next day. Interviewers care less about exact wording than about whether you name the *trade-off* — almost every good answer here ends with "the cost is…" or "use it when…".

---

1. Fundamentals: monolith vs microservices

Q1. ★ What are microservices? Microservices is an architectural style in which an application is built as a set of small services, each owning one business capability, running in its own process, owning its own data and deployable independently. Services talk over the network (HTTP, gRPC or messaging). The point is *independent change*: one team can build, test, deploy and scale its service without coordinating a release with everyone else. → *More:* Ch 1 — Architectural styles

Q2. ★ What is the difference between a monolithic and a microservices architecture? A monolith is one deployable unit: all features share one codebase, one process and usually one database, and calls between modules are in-memory function calls. Microservices split those features into separate deployables that call each other over the network and keep separate databases. A monolith is simpler to build, test, debug and run; microservices give independent deployment, independent scaling and team autonomy, at the price of network failures, distributed data and much more operational work. → *More:* Ch 1 — Architectural styles · Ch 2 — Strangler Fig, Part 0

Q3. ★ What are the advantages of microservices? Independent deployment (ship one service without redeploying everything), independent scaling (scale only the hot service), fault isolation (one crash need not take down the whole product), technology freedom per service, and smaller codebases that a single team can understand and own. The biggest real-world benefit is organisational: many teams can move in parallel with fewer merge conflicts and release trains.

Q4. ★ What are the disadvantages or challenges of microservices? Every call is now a network call that can be slow or fail; data is spread across databases so you lose easy joins and ACID transactions; debugging needs distributed tracing; testing needs contract tests; you need service discovery, config management, CI/CD per service, monitoring and on-call for dozens of things. Versioning APIs between teams and keeping data eventually consistent are ongoing costs. This is often called the "microservices tax". → *More:* Ch 1 — Synchronous vs asynchronous communication

Q5. ★ When should you NOT use microservices? When the team is small (one or two teams), the domain is still being discovered, the product is an early-stage startup, or you lack automated deployment and monitoring. In those cases a well-structured monolith ships faster. Martin Fowler's "Monolith First" advice says: start with a monolith, find the stable boundaries, and extract services only when a real pain (scaling, team contention, release speed) appears.

Q6. What is a modular monolith? A single deployable whose code is split into strongly separated modules, each with its own public API and private internals, and ideally its own database schema. It gives most of the design benefits of microservices (clear boundaries, ownership) without the network and operational costs, and it is the easiest starting point for later extraction. In Spring, **Spring Modulith** verifies module boundaries in tests and offers in-process events between modules. → *More:* Ch 1 — Architectural styles

Q7. ⋆ What is the difference between SOA and microservices? SOA (Service-Oriented Architecture) also splits a system into services, but typically shares databases, uses heavyweight protocols (SOAP, WS-*), and puts routing and business logic into a central Enterprise Service Bus (ESB). Microservices push the opposite way: "smart endpoints, dumb pipes", a database per service, lightweight protocols and decentralised governance. Microservices are often described as "SOA done with finer grains and without the ESB".

Q8. What are the key characteristics of a microservice? Single responsibility around a business capability; owns its data; independently deployable; communicates through a well-defined API; loosely coupled to other services but highly cohesive inside; owned by one team ("you build it, you run it"); designed for failure; and observable (logs, metrics, traces).

Q9. ⋆ What do you mean by cohesion and coupling? Cohesion is how strongly the code inside one module belongs together — high cohesion means a change to one business rule touches only one service. Coupling is how much one module depends on another — low coupling means you can change or deploy one service without changing the others. Good microservices aim for **high cohesion, low coupling**; a design where every feature needs changes to five services is a "distributed monolith".

Q10. ⋆ What is a distributed monolith and how do you avoid it? A system split into many services that still have to be deployed together because they are tightly coupled — shared database tables, chatty synchronous call chains, shared domain libraries, or lock-step API changes. You get all the costs of microservices with none of the benefits. Avoid it with database per service, boundaries drawn around business capabilities, backward-compatible API changes, and asynchronous events where an immediate answer is not needed.

Q11. How big should a microservice be? There is no line count. A useful test: one team can own it, it maps to one bounded context (Q17), it can be rewritten in a couple of weeks, and most changes touch only this service. Too small ("nanoservices") creates chatty calls and distributed transactions; too big recreates the monolith's coordination problems.

Q12. What is Conway's Law and why does it matter here? Conway's Law says a system's structure mirrors the communication structure of the organisation that builds it. So service boundaries and team boundaries should match: one team per service (or a few services). The "inverse Conway manoeuvre" is reorganising teams first to get the architecture you want.

Q13. What does "stateless" mean for a microservice? Stateless vs stateful services? A stateless service keeps no client-specific data in memory between requests — any instance can serve any request, so you can add, remove or restart instances freely behind a load balancer. State (sessions, carts) lives in a database or cache such as Redis. Stateful services (databases, Kafka brokers, game servers) keep data locally and need stable identity, replication and careful scaling; in Kubernetes they run as StatefulSets. → *More:* Ch 1 — Stateless and stateful services

Q14. What are the main components of a microservices architecture? The services themselves plus the platform around them: an API gateway (single entry point), service discovery/registry, a config server, a message broker (Kafka/RabbitMQ), databases per service, a container platform (Docker + Kubernetes), CI/CD pipelines, observability (logs, metrics, traces) and security infrastructure (identity provider, secrets store). Optionally a service mesh for traffic, mTLS and telemetry.

Q15. Name companies that use microservices and why they adopted them. Netflix (moved from a monolith after a 2008 database corruption outage, to scale streaming globally), Amazon (the "two-pizza team" model with service-owned APIs), Uber (split a monolith to scale teams and cities), Spotify (squads owning services). The common reason is scaling the *organisation* — hundreds of engineers shipping independently — not just scaling traffic.

Q16. What is the twelve-factor app methodology? A set of twelve rules for building cloud-ready services: one codebase per app, explicit dependencies, config in the environment, backing services as attached resources, separate build/release/run stages, stateless processes, port binding, scale out via

processes, disposability (fast start, graceful shutdown), dev/prod parity, logs as event streams, and admin tasks as one-off processes. It is the checklist that makes a service easy to containerise and run on Kubernetes. → *More:* Ch 13 — Configuration Externalization

---

2. Decomposition, DDD and migration

Q17. ⋆ What is a bounded context? A bounded context is a term from Domain-Driven Design: a boundary inside which a domain model and its vocabulary have one precise meaning. "Customer" in Billing (payment methods, invoices) is a different model from "Customer" in Shipping (addresses, delivery preferences). Each bounded context is a natural candidate for a microservice, because inside it the language and rules are consistent and it can own its own data.

Q18. ⋆ What is Domain-Driven Design (DDD) and how does it relate to microservices? DDD is an approach to software design that models the code closely on the business domain, built with domain experts using a shared "ubiquitous language". Its strategic part (bounded contexts, context maps, subdomains) tells you where to draw service boundaries; its tactical part (entities, value objects, aggregates, domain events) tells you how to structure the code inside a service. Microservices without DDD-style boundaries tend to end up chatty and tightly coupled.

Q19. ⋆ How would you decompose a monolith into microservices? Decompose by **business capability** (what the business does: ordering, payments, catalogue) or by **subdomain/bounded context**, not by technical layer. Practical steps: run an event-storming workshop to find domain events and contexts; map which data each capability owns; pick an edge capability with few dependencies and high change rate; extract it behind the existing API using the Strangler Fig pattern; split its data last. Repeat, measuring whether deployments really got more independent. → *More:* Ch 2 — Strangler Fig

Q20. ⋆ What is the Strangler Fig pattern? A way to replace a legacy system gradually: put a facade (proxy or gateway) in front of the monolith, build new functionality as separate services, and route one capability at a time from the old system to the new one. Over time the new system "strangles" the old one until it can be switched off. It avoids a risky big-bang rewrite and lets you roll back per route. → *More:* Ch 2 — Strangler Fig

Q21. What is an aggregate in DDD and why does it matter for microservices? An aggregate is a cluster of objects treated as one unit for changes, with one root entity as its only entry point (for example, `Order` with its `OrderLines`). All invariants inside an aggregate are kept in one local transaction; anything across aggregates is eventually consistent. This maps neatly to microservices: a transaction never spans services, and other services refer to an aggregate only by its ID.

Q22. What are entities, value objects and domain events? An entity has identity that persists over time (an `Order` with an ID). A value object is defined only by its values and is immutable (`Money(100, EUR)`, an `Address`) — a Java `record` is a good fit. A domain event records something that happened that the business cares about (`OrderPlaced`), named in the past tense; it is what other services subscribe to.

Q23. What is a context map? Name some relationships between bounded contexts. A context map is a diagram of the bounded contexts and how they relate. Common relationships: **customer–supplier** (downstream depends on upstream, who considers its needs), **conformist** (downstream simply adopts upstream's model), **anti-corruption layer** (downstream translates upstream's model into its own), **shared kernel** (a small shared model both own), **open host service / published language** (upstream publishes a stable public API or schema).

Q24. ⋆ What is an anti-corruption layer? A translation layer between your service and another system (often a legacy monolith or third-party API) so that the other system's model and quirks do not leak into your clean domain model. It converts their data and calls into your concepts and back. It is standard during Strangler Fig migrations. → *More:* Ch 2 — Strangler Fig

Q25. What is event storming? A workshop technique in which developers and domain experts put domain events (orange sticky notes, past tense: "Order Placed", "Payment Captured") on a timeline, then add commands, actors, policies and aggregates. Clusters that emerge suggest bounded contexts and thus service boundaries. It is a fast way to find boundaries before writing code.

Q26. Decompose by business capability vs by subdomain — what is the difference? A business capability is something the business does to create value (manage inventory, take payments) and is fairly stable

over time. A subdomain is DDD's split of the problem space into **core** (your competitive edge — invest most here), **supporting** (needed but specific to you) and **generic** (commodity, often bought, like identity). Both lead to similar boundaries; subdomains add the guidance about where to invest and what to buy.

Q27. What is the "shared database" anti-pattern? Several services reading and writing the same tables. It looks convenient but couples services at the schema level: one team's column change breaks another service, you cannot scale or choose storage per service, and ownership of data rules is unclear. It is acceptable only as a temporary migration step, with a plan to split. → *More:* Ch 10 — Saga, "What is database per service?"

Q28. How do you split the database when migrating from a monolith? Go step by step: first separate the code module and make it the only writer of its tables; then move those tables into a separate schema; then a separate database. Keep data in sync during the transition with change data capture (CDC — streaming the database's change log, e.g. Debezium reading the write-ahead log into Kafka) or with the service's events, and replace cross-table joins with API calls or local read copies. → *More:* Ch 2 — Strangler Fig, "The part the pattern doesn't solve: data"

Q29. What is CDC (Change Data Capture)? CDC streams every insert, update and delete from a database's transaction log to other systems, usually through Kafka, without changing application code. Uses: syncing data during a monolith migration, feeding search indexes and caches, and as the relay in the transactional outbox pattern (Q107). Debezium is the common open-source tool.

Q30. What is the difference between a microservice and a serverless function? A microservice is a long-running process you deploy and scale (usually as containers); a serverless function (AWS Lambda, Cloud Functions) is code the platform starts per event and bills per invocation, scaling to zero. Functions suit spiky, event-driven, short tasks; they bring cold-start latency, execution time limits and vendor lock-in. A microservice can be implemented with several functions, so they are not exclusive. → *More:* Ch 1 — Architectural styles

---

3. Communication: REST, gRPC and messaging

Q31. ⋆ How do microservices communicate with each other? Two styles. **Synchronous** request/response — REST over HTTP or gRPC — where the caller waits for the answer; simple, but couples availability (if the callee is down, the caller fails). **Asynchronous** messaging — events or commands through a broker such as Kafka or RabbitMQ — where the sender does not wait; decoupled and resilient, but eventually consistent and harder to trace. Most systems use sync for queries that need an answer now and async for propagating state changes. → *More:* Ch 1 — Synchronous vs asynchronous communication · Ch 11 — Event-Driven

Q32. ⋆ What is the difference between synchronous and asynchronous communication? Synchronous: the caller sends a request and blocks (or awaits) until the response arrives — the two services must both be up at the same time. Asynchronous: the caller hands a message to a broker and carries on; the receiver processes it later. Async gives temporal decoupling, load levelling (the queue absorbs bursts) and better fault isolation, but adds a broker to operate, eventual consistency, and duplicate/out-of-order message handling. → *More:* Ch 11 — Event-Driven, Part 0

Q33. ⋆ What is REST? What makes an API RESTful? REST (Representational State Transfer) is an architectural style for HTTP APIs: resources are identified by URLs (`/orders/42`), manipulated with standard HTTP methods (GET, POST, PUT, PATCH, DELETE), represented as JSON or similar, and each request is stateless (carries all needed context). Good REST APIs use correct status codes, are cacheable where possible, and use nouns, not verbs, in paths. → *More:* Ch 1 — API styles · Ch 1 — API design basics

Q34. ⋆ REST vs gRPC vs message queues — when do you use each? REST/JSON: public and browser-facing APIs, simple CRUD, easy debugging. gRPC: internal service-to-service calls that need low latency, strong typed contracts and streaming — it uses HTTP/2 and binary Protocol Buffers. Message queues/streams: when the caller does not need an immediate answer, when many consumers must react to one event, or to absorb load spikes. → *More:* Ch 1 — API styles

Q35. What is gRPC and why is it faster than REST/JSON? gRPC is a remote procedure call framework: you define services and messages in a `.proto` file and generate client and server code in many languages.

It is faster because Protocol Buffers are a compact binary format (smaller and cheaper to parse than JSON) and HTTP/2 multiplexes many calls over one connection with header compression. It supports four call types: unary, server streaming, client streaming and bidirectional streaming. Downsides: not natively callable from browsers (needs gRPC-Web or a gateway), harder to inspect by hand.

Q36. What is GraphQL and when would you use it in a microservices system? GraphQL is a query language for APIs where the client asks for exactly the fields it needs in one request, against a typed schema. It suits a client-facing aggregation layer (often a BFF or gateway) over many services, avoiding over-fetching and multiple round trips. Costs: caching is harder (one POST endpoint), expensive queries need depth/complexity limits, and N+1 calls to backends need batching (DataLoader). → *More:* Ch 4 — BFF

Q37. ⋆ Which HTTP methods are idempotent? What is the difference between PUT and PATCH, and PUT and POST? Idempotent means repeating the request has the same effect as doing it once. GET, HEAD, PUT, DELETE (and OPTIONS) are idempotent; POST and PATCH are not guaranteed to be. PUT replaces the whole resource at a known URL; PATCH applies a partial change; POST usually creates a new resource whose ID the server chooses, so retrying a POST can create duplicates unless you add an idempotency key (Q119). → *More:* Ch 1 — HTTP · Ch 8 — Retry, Part 0

Q38. ⋆ How do you version APIs in microservices? Options: URI version (`/v2/orders`), a header (`API-Version: 2`), a query parameter, or a media type (`application/vnd.shop.v2+json`). More important than the mechanism is the rule: make changes backward compatible (add optional fields, never remove or rename without a new version), support old versions for a deprecation period, and announce sunset dates. Spring Framework 7 adds first-class API versioning to Spring MVC and WebFlux (`@GetMapping(version = "2")` with a configured strategy for path, header, query or media type). → *More:* Ch 3 — API Gateway, "Version management"

Q39. What does "backward compatible" mean for an API or event schema? Old clients keep working against the new version. Safe changes: adding optional fields, adding new endpoints, accepting more input. Breaking changes: removing or renaming fields, changing types or meaning, making optional fields required. Consumers should follow the "tolerant reader" rule — ignore fields they do not understand — so producers can add fields freely.

Q40. ⋆ What is a message broker? Kafka vs RabbitMQ? A message broker is middleware that receives messages from producers and delivers them to consumers, decoupling them in time. **RabbitMQ** is a traditional queue broker: smart routing (exchanges, routing keys), messages are removed once acknowledged, good for task queues and complex routing. **Kafka** is a distributed, partitioned, replicated log: messages are retained for a configured time, consumers track their own offset and can replay, ordering is per partition, and throughput is very high — good for event streaming and event sourcing. → *More:* Ch 1 — Message queues · Ch 1 — Event streaming

Q41. Point-to-point queue vs publish-subscribe? In point-to-point, each message is consumed by exactly one consumer among competing workers — good for distributing tasks. In publish-subscribe, each message is delivered to every subscribed group — good for broadcasting events ("OrderPlaced" goes to billing, shipping and analytics). Kafka does both with consumer groups: within one group partitions are split among consumers (point-to-point), and each group gets every message (pub-sub). → *More:* Ch 11 — Event-Driven, "What is publish-subscribe?"

Q42. ⋆ How does Kafka guarantee message ordering? Only within a partition. Messages with the same key go to the same partition (by hash of the key), so key by the entity ID (for example `orderId`) to keep all events for one order in order. There is no ordering across partitions. Retries with more than one in-flight request could reorder messages, which the idempotent producer (on by default in modern Kafka) prevents. → *More:* Ch 11 — Event-Driven · Ch 1 — Event streaming

Q43. What are Kafka partitions, consumer groups and offsets? A topic is split into partitions, each an ordered append-only log; partitions are the unit of parallelism and are replicated across brokers. A consumer group is a set of consumers sharing the work — each partition is read by at most one consumer in the group, so more consumers than partitions sit idle. An offset is a consumer's position in a partition; committing it after processing gives at-least-once delivery. → *More:* Ch 1 — Event streaming

Q44. Events vs commands vs queries in messaging? A command asks one specific receiver to do something (`ReserveStock`) and may be rejected. An event announces that something already happened (`StockReserved`) to anyone interested; the publisher does not know or care who listens. A query asks for data and

changes nothing. Naming them correctly matters: events are past tense and immutable. → *More:* Ch 11 — Event-Driven, "What is an event?" · Ch 12 — CQRS

Q45. Event notification vs event-carried state transfer? An event notification is thin — "Order 42 changed" — and consumers call back the source to get details (simpler, but adds load and coupling). Event-carried state transfer puts the needed data in the event — "Order 42 placed, items…, total…" — so consumers can keep a local copy and never call back (more decoupled and resilient, but bigger events and schema-evolution concerns).

Q46. ⋆ What is a dead-letter queue (DLQ)? A separate queue or topic where messages go after they fail processing a set number of times (for example a malformed "poison" message). It stops one bad message from blocking the whole stream or retrying forever. You alert on DLQ growth, inspect, fix the bug or data, and replay the messages. Spring Kafka's `DefaultErrorHandler` with a `DeadLetterPublishingRecoverer` does this. → *More:* Ch 11 — Event-Driven, "Error handling and message durability"

Q47. What is backpressure? A way for a slow consumer to signal a fast producer to slow down, so the consumer is not overwhelmed and memory does not grow without limit. Pull-based consumers (Kafka) have it naturally; reactive streams (Project Reactor's `Flux`) have it built into the protocol; for HTTP you use rate limits, bounded queues and 429/503 responses.

Q48. How do you manage schema evolution in event-driven systems? Use a schema format with evolution rules (Avro, Protobuf or JSON Schema) and a schema registry that rejects incompatible changes at publish time. Prefer backward-compatible changes (add optional fields with defaults). For a breaking change, publish a new event type or version alongside the old one, migrate consumers, then retire the old one. Consumers should be tolerant readers.

Q49. When would you use WebSockets or Server-Sent Events instead of REST? When the server must push updates to the client in real time — chat, live dashboards, notifications, collaborative editing. WebSockets give a two-way persistent connection; SSE gives a simpler one-way server-to-client stream over HTTP. Costs: long-lived connections are stateful and harder to load-balance and scale, so a dedicated gateway/connection service is common. → *More:* Ch 1 — Real-time communication

Q50. How do you avoid long synchronous call chains? Each hop multiplies latency and failure probability (five services at 99.9% availability each give about 99.5% together). Fixes: let services keep local copies of the data they need (updated by events), aggregate in a gateway/BFF in parallel instead of chaining, move non-urgent steps to async messaging, and set timeouts at every hop with a total deadline. → *More:* Ch 3 — API Gateway

---

4. API Gateway, BFF, service discovery and service mesh

Q51. ⋆ What is an API Gateway and why do we need it? An API gateway is a single entry point that sits between clients and the services. It routes each request to the right service and handles cross-cutting concerns once: authentication, rate limiting, TLS termination, request/response transformation, response aggregation, caching, logging and metrics. Clients then depend on one stable API instead of knowing the internal topology. Examples: Spring Cloud Gateway, Kong, NGINX, AWS API Gateway, Envoy. → *More:* Ch 3 — API Gateway

Q52. ⋆ What are the drawbacks of an API Gateway and how do you mitigate them? It is a potential single point of failure and bottleneck, adds a network hop of latency, and can grow into a "god service" full of business logic owned by nobody. Mitigate by running several stateless gateway instances behind a load balancer across zones, keeping it thin (routing and cross-cutting only, no business rules), using timeouts and circuit breakers on its upstream calls, and giving it clear team ownership. → *More:* Ch 3 — API Gateway, Lesson 4

Q53. ⋆ What is the Backend for Frontend (BFF) pattern? How is it different from an API Gateway? A BFF is a separate backend per client type (web, iOS/Android, TV, partner API), owned by the frontend team, which aggregates and shapes data exactly for that client. A general API gateway is one shared entry point for all clients. They are often combined: a thin gateway handles auth and routing, and BFFs behind it do client-specific aggregation. The cost of BFFs is some duplicated code across them. → *More:* Ch 4 — BFF · Ch 4, "BFF vs. API Gateway"

Q54. What is API composition / the aggregator pattern? A component (gateway, BFF or dedicated service) calls several services, ideally in parallel, and merges the results into one response — for example a product page combining catalogue, price, stock and reviews. It replaces the cross-service join you lost with database per service. Watch out for the slowest dependency dominating latency; use timeouts and return partial results when an optional part fails. → *More:* Ch 3 — API Gateway, "Aggregation of results"

Q55. ⋆ What is service discovery and why is it needed? In containers and auto-scaling environments, service instances start and stop constantly and their IP addresses change. Service discovery lets a caller find a healthy instance by a logical name (`order-service`) instead of a hard-coded address. It needs a **service registry** — a database of live instances that services register with and that is kept fresh by health checks or heartbeats. → *More:* Ch 5 — Service Discovery

Q56. ⋆ Client-side vs server-side service discovery? Client-side: the caller queries the registry, gets the list of instances and load-balances itself (Eureka + Spring Cloud LoadBalancer). Fewer hops, but every client needs the library. Server-side: the caller sends to a router or load balancer that does the lookup (Kubernetes Service with DNS, AWS ALB). Clients stay simple and language-agnostic, at the cost of an extra hop. On Kubernetes, server-side via Services and DNS is the default and you rarely need Eureka. → *More:* Ch 5 — Client-side vs. server-side discovery

Q57. Self-registration vs third-party registration? With self-registration the service registers itself on startup and sends heartbeats (Eureka client). With third-party registration a separate component — the platform — watches instances and registers them (Kubernetes endpoints controller, Consul with a registrator). Third-party keeps service code free of registry logic. → *More:* Ch 5 — Self-registration vs. third-party registration

Q58. ⋆ What is Eureka? Why is Eureka described as AP? Eureka is Netflix's service registry, integrated through Spring Cloud Netflix. In CAP terms (consistency, availability, partition tolerance) it favours availability: during network problems it keeps serving possibly stale instance lists and enters "self-preservation mode" instead of evicting many instances at once. A stale list is survivable because clients retry another instance; a registry that refuses to answer would stop all traffic. → *More:* Ch 5 — Service Discovery · Ch 1 — CAP theorem

Q59. How does service discovery work in Kubernetes? A Kubernetes **Service** gives a stable virtual IP and DNS name (`orders.shop.svc.cluster.local`) in front of a changing set of Pods selected by labels. The control plane tracks ready Pods (via readiness probes) in EndpointSlices, and kube-proxy (or an eBPF data plane) load-balances connections to them. Callers just use the DNS name. → *More:* Ch 5 — Service Discovery · Ch 1 — Kubernetes basics

Q60. ⋆ What is client-side load balancing? Which algorithms exist? The client picks the target instance itself from the list it got from discovery, avoiding a central load balancer hop. In Spring, a `@LoadBalanced` `RestClient.Builder` or `WebClient.Builder` uses Spring Cloud LoadBalancer (which replaced Netflix Ribbon). Common algorithms: round robin, random, least connections, weighted, and zone- or latency-aware choices. → *More:* Ch 1 — Load balancers · Ch 5 — Load balancing strategies

Q61. ⋆ What is a service mesh? When would you use one? A service mesh is an infrastructure layer that handles service-to-service traffic through a proxy next to each service (a sidecar such as Envoy, or a per-node proxy in Istio's "ambient" mode). A control plane (Istio, Linkerd) configures the proxies. It provides mTLS, retries, timeouts, circuit breaking, traffic splitting for canaries, and uniform metrics and traces — without changing application code and in any language. Use it with many services and polyglot teams; it adds latency, resource cost and operational complexity. → *More:* Ch 9 — Sidecar · Ch 1 — Service discovery, sidecars and service mesh

Q62. ⋆ What is the sidecar pattern? A helper process deployed alongside the main application (in Kubernetes, another container in the same Pod) sharing its lifecycle, network and possibly storage. It takes over cross-cutting concerns — proxying, mTLS, log shipping, config reloading — so the application stays focused on business logic and the concern is solved once for every language. → *More:* Ch 9 — Sidecar

Q63. Library (e.g. Resilience4j) vs service mesh for resilience — which is better? A library runs in-process, knows the business context (fallback logic, which calls are idempotent) and costs no extra hop, but must be implemented per language. A mesh is language-agnostic and centrally configured, but sees only network-level information and can retry non-idempotent calls blindly. A common split: mesh

for mTLS, timeouts and traffic shaping; library for fallbacks and business-aware retries. Avoid configuring retries in both places. → *More:* Ch 9 — Sidecar · Ch 8 — Retry, "Placement in the architecture"

Q64. What is the difference between a reverse proxy, a load balancer and an API gateway? A reverse proxy sits in front of servers and forwards client requests to them (TLS termination, caching, hiding servers). A load balancer is a reverse proxy whose main job is spreading load across instances with health checks. An API gateway is a reverse proxy with API-level features: routing by path/version, auth, rate limiting per client, transformation and aggregation. In practice the same product (NGINX, Envoy) can play all three roles. → *More:* Ch 1 — Proxies and API gateways

Q65. Edge (north-south) vs internal (east-west) traffic? North-south traffic enters or leaves the system (clients to the gateway); east-west traffic flows between services inside the cluster. The API gateway governs north-south; a service mesh or internal policies govern east-west. Security for east-west is often forgotten — zero trust says encrypt and authenticate it too (mTLS).

Q66. Should the API gateway do authentication, authorization, or both? Typically the gateway authenticates (validates the token, rejects anonymous calls) and does coarse checks (scopes, rate limits per client). Fine-grained authorization ("may this user cancel *this* order?") belongs in the owning service, which knows the data. Each service should still validate the token it receives rather than blindly trusting the network. → *More:* Ch 3 — API Gateway, "Security and authentication"

---

5. Resilience and fault tolerance

Q67. ⋆ How do you handle failures in microservices / what is fault tolerance? Assume every remote call can fail or be slow. Combine: timeouts on every call, retries with backoff for transient errors, circuit breakers to stop calling a failing dependency, bulkheads to isolate resources, fallbacks or graceful degradation, rate limiting and load shedding to protect yourself, async messaging to decouple, and redundancy (several instances across zones). Then verify with chaos testing. → *More:* Ch 6, Ch 7, Ch 8 · Ch 1 — Faults, failures and fault tolerance

Q68. ⋆ What is a cascading failure? A failure that spreads: service C becomes slow, so B's threads waiting on C pile up until B runs out of threads and stops responding, then A, which calls B, does the same — and the whole system goes down because of one slow dependency. Timeouts, circuit breakers and bulkheads exist mainly to break this chain. → *More:* Ch 6 — Circuit Breaker, "Cascading failures, step by step"

Q69. ⋆ Explain the circuit breaker pattern and its states. A circuit breaker wraps calls to a dependency and tracks failures. **Closed**: calls flow normally and failures are counted in a sliding window. When the failure (or slow-call) rate passes a threshold it goes **Open**: calls fail immediately (or go to a fallback) without touching the dependency, giving it time to recover. After a wait it goes **Half-Open**: a few trial calls are allowed; if they succeed it closes, otherwise it opens again. → *More:* Ch 6 — Circuit Breaker, "The three states"

Q70. ⋆ Why is a slow service often worse than a dead one? A dead service fails fast (connection refused) so the caller frees its thread at once. A slow service holds the caller's threads and connections until the timeout, so they pile up and exhaust the caller's pools — that is how cascades start. That is why circuit breakers should also count *slow calls* (Resilience4j `slowCallRateThreshold`) and every call needs a timeout. → *More:* Ch 6 — Circuit Breaker

Q71. ⋆ What is the retry pattern? What should and should not be retried? Automatically repeat a failed call in the hope that the failure was transient. Retry timeouts, connection resets, 503/502/504, 429 (honouring `Retry-After`). Do not retry 400, 401, 403, 404, 409 or validation errors — they will fail again. Only retry operations that are idempotent, or make them idempotent with an idempotency key. → *More:* Ch 8 — Retry, "Transient vs. permanent"

Q72. ⋆ What is exponential backoff with jitter and why use it? Exponential backoff waits longer after each failure (for example 100 ms, 200 ms, 400 ms, up to a cap) to give the dependency room to recover. Jitter adds randomness to each wait ("full jitter": random between 0 and the backoff), so that thousands of clients that failed together do not all retry at the same instant — the thundering-herd

problem. → *More:* Ch 8 — Retry, "Backoff strategy" and "Jitter" · Ch 1 — Timeouts, retries, exponential backoff and jitter

Q73. ⋆ What is a retry storm and how do you avoid it? Retries multiplying load on an already struggling service. If three layers each retry three times, one user request can become 27 calls to the bottom service. Avoid it by retrying at one layer only (usually the one closest to the failing call or at the edge), capping attempts, using backoff with jitter, a retry budget (retries limited to, say, 10% of traffic), and a circuit breaker that stops retries when the dependency is clearly down. → *More:* Ch 8 — Retry, "Retry storms and thundering herd"

Q74. ⋆ What is the bulkhead pattern? Partition resources (thread pools, connection pools, semaphores, even whole service instances) per dependency or per type of work, like watertight compartments in a ship's hull. If the recommendation service hangs, it can exhaust only its own pool of, say, 10 threads, while checkout keeps its own pool and continues to work. → *More:* Ch 7 — Bulkhead

Q75. ⋆ Circuit breaker vs bulkhead vs retry — how do they work together? Retry bounds *how many* attempts; circuit breaker bounds *how long* you keep calling a failing dependency; bulkhead bounds *how much* of your resources one dependency can consume. A typical order (outermost first, Resilience4j default aspect order): Retry → CircuitBreaker → RateLimiter → TimeLimiter → Bulkhead → the call. Each retry attempt then goes through the breaker, so an open breaker stops retries quickly. → *More:* Ch 7 — Bulkhead · Ch 8 — Retry, "Circuit breaker integration"

Q76. ⋆ Why is a timeout essential on every remote call? How do you choose its value? Without a timeout a hung dependency holds your thread forever. Choose from the dependency's measured latency: slightly above its p99 (e.g. p99 = 300 ms → timeout 500 ms), never the library's default (often infinite or very long). Set both connect and read timeouts, and propagate a total deadline so downstream calls do not keep working after the upstream caller has already given up. → *More:* Ch 1 — Timeouts, retries, exponential backoff and jitter · Ch 6 — "What is a timeout?"

Q77. What is deadline propagation? The original caller sets a total time budget (say 2 s) and each service passes the *remaining* budget downstream (gRPC does this with deadlines; with HTTP you use a header). A service that receives a request with too little time left fails fast instead of doing work nobody will wait for.

Q78. ⋆ What is a fallback? Give examples. What you return when the real call fails or the breaker is open: cached or last-known-good data, a default value (generic recommendations instead of personalised ones), an empty but valid response, or queuing the action for later ("we will email your receipt"). Fallbacks must be cheap and must not themselves call the same failing dependency. For critical data (payments, balances) the honest fallback is often a clear error. → *More:* Ch 6 — "What is a fallback?" · Ch 1 — Circuit breakers, bulkheads and fallbacks

Q79. ⋆ What is rate limiting and which algorithms are used? Rate limiting caps how many requests a client may make in a time window, protecting services from overload and abuse; excess requests get HTTP 429. Algorithms: **token bucket** (tokens refill at a fixed rate, each request takes one, allows short bursts — the most common), **leaky bucket** (smooth constant output), **fixed window counter** (simple, but bursts at window edges), **sliding window log/counter** (accurate, a bit more costly). → *More:* Ch 1 — Rate limiting and throttling · Ch 3 — API Gateway, "Rate limiting challenges"

Q80. How do you rate-limit across many gateway instances? In-memory counters only limit per instance, so N instances allow N times the limit. Use a shared store — typically Redis with an atomic Lua script implementing the token bucket (Spring Cloud Gateway's `RequestRateLimiter` with `RedisRateLimiter` does this). Alternatively accept approximate limits by dividing the quota by the instance count. → *More:* Ch 3 — API Gateway

Q81. Rate limiting vs throttling vs load shedding? Rate limiting rejects a *client* above its quota (fairness, abuse). Throttling slows down or queues requests rather than rejecting them. Load shedding is the server protecting *itself*: when overall load is above capacity it drops low-priority work (e.g. analytics calls) to keep critical paths (checkout) alive. → *More:* Ch 1 — Load shedding and graceful degradation

Q82. What is graceful degradation? Keeping the core function working with reduced features when parts fail: the shop still sells when the recommendation or review service is down, showing a page without those sections. It requires deciding upfront which dependencies are critical and which are optional, and coding fallbacks for the optional ones. → *More:* Ch 1 — Load shedding and graceful degradation

Q83. ⋆ Show how you would add a circuit breaker and retry to a Spring Boot call. With Resilience4j's Spring Boot integration:

```
@CircuitBreaker(name = "inventory", fallbackMethod = "stockFallback")
@Retry(name = "inventory")
public Stock stock(String sku) {
    return inventoryClient.getStock(sku);   // RestClient / HTTP interface call
}
private Stock stockFallback(String sku, Throwable t) {
    return Stock.unknown(sku);              // degrade, do not fail the page
}
```

Thresholds go in `application.yml` under `resilience4j.circuitbreaker.instances.inventory` (e.g. `failureRateThreshold: 50`, `slidingWindowSize: 20`, `waitDurationInOpenState: 10s`). The fallback must have the same return type plus a `Throwable` parameter. → *More:* Ch 6 — Circuit Breaker · Ch 8 — Retry

Q84. What resilience features are built into Spring Framework 7 itself? Spring Framework 7 adds `@Retryable` (with backoff, jitter and include/exclude exception types) and `@ConcurrencyLimit` (a simple bulkhead) in core, enabled with `@EnableResilientMethods`, plus a programmatic `RetryTemplate` in `org.springframework.core.retry`. By default `@Retryable` retries any exception 3 times with a 1 s delay. They replace the separate Spring Retry project (Spring Boot 4 no longer manages its version) and cover retry and concurrency throttling without an extra dependency; for circuit breakers, rate limiters and time limiters you still use Resilience4j (often via Spring Cloud Circuit Breaker).

Q85. ⋆ What is idempotency and why is it critical in microservices? An operation is idempotent if doing it twice has the same effect as doing it once. Because retries, at-least-once message delivery and user double-clicks all cause duplicates, every handler that changes state must tolerate duplicates — otherwise a retry can charge a customer twice. Techniques: idempotency keys, natural keys with unique constraints, a processed-message table, and conditional updates (`UPDATE … WHERE version = ?`). → *More:* Ch 8 — Retry, "Idempotency and side effects" · Ch 1 — Delivery guarantees, idempotency and retries

Q86. How do you tune circuit breaker parameters? Base them on data: the dependency's normal error rate and latency percentiles. Set the minimum number of calls high enough that one or two failures at low traffic do not trip it; set the failure-rate threshold well above the normal error rate (e.g. 50%); set the slow-call threshold just above normal p99; set the open-state wait to roughly how long the dependency takes to recover (5–30 s). Alert on state transitions to Open — a breaker that hides errors silently is dangerous. → *More:* Ch 6 — Circuit Breaker, "Performance implications"

Q87. What is chaos engineering? Deliberately injecting failures (killing instances, adding latency, cutting networks, failing a zone) in a controlled way, ideally in production with a limited blast radius, to verify that the system's resilience mechanisms actually work. Netflix's Chaos Monkey popularised it; tools include Chaos Mesh, LitmusChaos, Gremlin and AWS Fault Injection Service. Start with a hypothesis ("if one payment instance dies, p99 stays below 500 ms") and measure.

Q88. How do you size a bulkhead or a thread pool for a dependency? Use Little's law: concurrent requests in flight = arrival rate × latency. If you call a dependency 200 times per second at 50 ms each, about 10 calls are in flight; add headroom (e.g. 15–20). Cap it at what the dependency can handle, and set a small queue or none, so excess fails fast rather than waiting. → *More:* Ch 7 — Bulkhead · Ch 1 — Little's law

Q89. Do virtual threads remove the need for bulkheads and timeouts? No. Virtual threads (final since Java 21; enable in Spring Boot with `spring.threads.virtual.enabled=true`) make blocking calls cheap, so you rarely run out of *threads*. But the downstream service, connection pools and database still have limits — without a concurrency cap you can now flood them with thousands of simultaneous calls. Keep timeouts, and use semaphore-style bulkheads (e.g. `@ConcurrencyLimit`) instead of thread-pool bulkheads.

---

6. Data management: database per service, saga, outbox, CQRS, event sourcing

Q90. ⋆ What is the database-per-service pattern? Why should each microservice have its own database? Each service owns its data store privately; other services can reach that data only through the

service's API or events, never by querying its tables. This keeps services loosely coupled (schema changes stay internal), lets each pick the right storage (PostgreSQL, MongoDB, Redis, Elasticsearch — "polyglot persistence"), and allows independent scaling. "Own database" can mean a separate schema on a shared server; what matters is that no other service touches it. → *More:* Ch 10 — Saga, "Database per service"

Q91. ⋆ What problems does database per service create? No cross-service ACID transactions, no SQL joins across services, data duplication, and eventual consistency between copies. Answers: sagas for multi-service business transactions, API composition or CQRS read models for queries across services, events plus the outbox pattern to keep copies in sync. → *More:* Ch 10 — Saga · Ch 12 — CQRS

Q92. ⋆ How do you manage transactions across multiple microservices? Avoid them where possible by drawing boundaries so one business invariant lives in one service. When a business process must span services, use a **saga**: a sequence of local transactions, each publishing an event or message that triggers the next, with compensating transactions to undo completed steps if a later step fails. Use the transactional outbox so each step's state change and its message are atomic. Two-phase commit is generally avoided. → *More:* Ch 10 — Saga · Ch 1 — Distributed transactions

Q93. ⋆ What is the Saga pattern? A saga implements a business transaction that spans services as a series of local transactions. Each step commits in its own service's database. If step *n* fails, the saga runs compensating transactions for steps *n-1* … 1 in reverse (refund the payment, release the stock). It gives eventual consistency, not isolation: other requests can see the intermediate states. → *More:* Ch 10 — Saga

Q94. ⋆ Choreography vs orchestration sagas? In **choreography** each service listens for events and decides what to do next ("OrderCreated" → payment charges → "PaymentCompleted" → inventory reserves); there is no central coordinator, which is simple for 2–4 steps but the flow is hard to see and cyclic dependencies creep in. In **orchestration** a central orchestrator (a service or a workflow engine such as Temporal or Camunda) tells each participant what to do and tracks state; the flow is explicit, testable and easier to monitor, at the cost of a central component. → *More:* Ch 10 — Saga, "The two types"

Q95. ⋆ What is a compensating transaction? Why is it not the same as a rollback? A compensating transaction is a new business action that semantically undoes an earlier committed step: "refund payment" for "charge payment", "release seats" for "reserve seats". It is not a rollback because the original step already committed and others may have seen it; some effects cannot be undone (an email was sent), so compensation may be "send a correction email". Compensations must be idempotent and must eventually succeed (retried until they do). → *More:* Ch 10 — Saga, "Compensating transactions"

Q96. ⋆ What is two-phase commit (2PC) and why is it avoided in microservices? 2PC is a protocol where a coordinator asks all participants to *prepare* (lock resources and vote) and then tells all to *commit* or *abort*. It gives atomicity across databases but holds locks during the protocol, blocks if the coordinator fails at the wrong moment, needs every participant to support XA transactions (Kafka and most NoSQL stores do not), and couples availability — one slow participant stalls everyone. Sagas trade isolation for availability and loose coupling. → *More:* Ch 1 — Distributed transactions · Ch 10 — Saga

Q97. Sagas have no isolation. What anomalies can happen and how do you deal with them? Because each step commits independently, other transactions can see or change intermediate data: lost updates, dirty reads (reading an order that will be cancelled), fuzzy reads. Countermeasures: **semantic locks** (a status like `PENDING` that other operations respect), **commutative updates** (operations that can apply in any order), re-reading values before acting, ordering steps so that risky or irreversible ones come last (pivot transaction), and versioning.

Q98. What are compensatable, pivot and retriable transactions in a saga? Compensatable steps come first and can be undone. The pivot transaction is the go/no-go point (e.g. charging the card): if it succeeds, the saga will complete. Retriable steps come after the pivot and must not fail permanently — they are retried until they succeed (e.g. sending the shipping request). Ordering steps this way minimises the compensation you need.

Q99. ⋆ What is the transactional outbox pattern? It solves the **dual-write problem**: a service must update its database *and* publish an event, but you cannot make a database commit and a Kafka send atomic. With the outbox, the service writes the business change and an `outbox` row containing the event in the same local database transaction. A separate relay — a poller, or CDC like Debezium reading the

database log — publishes outbox rows to the broker and marks them sent. Delivery becomes at-least-once, so consumers must be idempotent. → *More:* Ch 10 — Saga · Ch 11 — Event-Driven

```
BEGIN;
UPDATE orders SET status = 'PAID' WHERE id = 42;
INSERT INTO outbox (id, aggregate_id, type, payload)
VALUES (gen_random_uuid(), 42, 'OrderPaid', '{"orderId":42}');
COMMIT;   -- both or neither; the relay publishes the outbox row later
```

Q100. ⋆ What is the dual-write problem? Writing to two systems (database and message broker, or two databases) without a shared transaction. If the process crashes between the two writes, they disagree: the order is saved but no event is published, or the event is published but the save rolled back. Publishing "after commit" in code does not fix it — a crash still loses the event. Solutions: transactional outbox, CDC, or event sourcing (the event *is* the write).

Q101. What is the inbox pattern / idempotent consumer? The consumer stores the IDs of messages it has processed in a table, in the same transaction as the business change. When a duplicate arrives (at-least-once delivery), it finds the ID already there and skips it. A unique constraint on `message_id` makes this race-safe. Together, outbox (producer side) and inbox (consumer side) give "effectively once" processing. → *More:* Ch 1 — Delivery guarantees, idempotency and retries

Q102. ⋆ What is CQRS? Command Query Responsibility Segregation: use separate models for writes (commands that change state and enforce business rules) and reads (queries that return data shaped for screens). It can be just separate classes over one database, or separate databases where the write side publishes events that update one or more denormalised read models (e.g. in Elasticsearch or Redis). It shines when reads vastly outnumber writes or need very different shapes; the cost is complexity and, with separate stores, eventually consistent reads. → *More:* Ch 12 — CQRS

Q103. ⋆ What is event sourcing? How is it different from traditional CRUD? In CRUD you store the current state and overwrite it on each update. In event sourcing you store the full sequence of events that happened to an entity (`AccountOpened`, `MoneyDeposited`, `MoneyWithdrawn`) in an append-only event store, and rebuild current state by replaying them. Benefits: a complete audit log, time travel and debugging, easy creation of new read models, and no dual-write problem. Costs: querying needs projections (usually CQRS), event schemas live forever, and it is unfamiliar to most teams. → *More:* Ch 12 — CQRS, "Level 3 — Event Sourcing" · Ch 11 — Event-Driven, "Event Sourcing and CQRS"

Q104. ⋆ Does CQRS require event sourcing (or vice versa)? No. CQRS can run on one database with separate read and write models, or two databases synced by CDC or events. Event sourcing almost always needs CQRS, because an event log cannot be queried efficiently and you build projections for reads. Treat them as separate decisions and adopt each only when its problem is real. → *More:* Ch 12 — CQRS, "Architecture: three levels"

Q105. What are snapshots in event sourcing? Periodically saving the computed state of an aggregate (say every 100 events) so that loading it means reading the latest snapshot plus only the events after it, instead of replaying thousands of events. They are an optimisation; the event log stays the source of truth.

Q106. How do you query data that lives in several services? Three options: **API composition** — call each service and join in memory (simple, but latency and partial-failure issues); **CQRS read model / materialized view** — a service subscribes to the others' events and keeps a denormalised local copy built for the query (fast, eventually consistent); **data replication** of just the fields you need into your own database. For reporting, stream everything into a data warehouse instead of querying services. → *More:* Ch 12 — CQRS · Ch 3 — API Gateway

Q107. How do you implement the outbox relay — polling vs CDC? Polling: a scheduled job selects unsent rows (`SELECT … FOR UPDATE SKIP LOCKED` so several instances do not grab the same rows), publishes them in order, and marks them sent; simple but adds database load and latency. CDC: Debezium tails the write-ahead log and publishes outbox inserts with low latency and no polling, but adds Kafka Connect to operate. Either way, clean up old rows and keep per-aggregate ordering.

Q108. Can you use Kafka transactions instead of an outbox? Kafka transactions make a consume-transform-produce loop *within Kafka* atomic (exactly-once processing between topics). They do not include your

PostgreSQL commit, so they do not solve the database-plus-event dual write. For that you still need the outbox, CDC or event sourcing.

Q109. How do you handle shared reference data (e.g. country codes, product catalogue) across services? Make one service the owner and publish changes as events; other services keep a read-only local copy updated from those events or cache it with a TTL. For truly static data (currency codes), a versioned shared library or config is acceptable. Never let several services write the same reference tables.

Q110. What is polyglot persistence? Using different storage technologies for different services according to their access patterns: a relational database for orders (transactions), a document store for the catalogue (flexible schema), a search engine for product search, a key-value store for sessions, a graph database for recommendations. Database per service makes it possible; the cost is more technologies to operate and know. → *More:* Ch 1 — Choosing a database

Q111. How do you generate unique IDs across services? Use IDs that need no central coordination: UUIDs (prefer time-ordered UUIDv7 for better index locality), Snowflake-style 64-bit IDs (timestamp + machine ID + sequence), or ULIDs. Avoid a shared database sequence across services — it couples them and becomes a bottleneck. → *More:* Ch 1 — Unique ID generation

Q112. How should a microservice cache data from another service? Cache-aside with a TTL matched to how stale the data may be, invalidated early by the owner's change events if freshness matters. Cache only data you can tolerate being stale (product names, yes; account balance, usually no), and protect against stampedes when hot keys expire (request coalescing, jittered TTLs). → *More:* Ch 1 — Caching strategies · Ch 1 — Cache invalidation

---

7. Consistency, delivery guarantees and ordering

Q113. ⋆ What is eventual consistency? A guarantee that, if no new updates are made, all copies of the data will become consistent after some (usually short) time. Between update and convergence, different services or replicas may return different values. It is the price of independent services and asynchronous messaging; the design question is how long the window is and whether the business can tolerate it (an order showing "processing" for two seconds is fine; overdrawing an account is not). → *More:* Ch 10 — Saga, "Eventual consistency" · Ch 1 — Consistency models

Q114. ⋆ How do you ensure data consistency across microservices? Keep each invariant inside one service's transaction where possible; use sagas with compensations for multi-service processes; publish events reliably with the outbox; make consumers idempotent; use optimistic locking (version columns) for concurrent updates; and add reconciliation jobs that compare systems and fix drift. Accept and design for eventual consistency in the UI (pending states, "we will notify you"). → *More:* Ch 10 — Saga · Ch 11 — Event-Driven, "Data consistency"

Q115. ⋆ Explain the CAP theorem. How does it apply to microservices? CAP says that during a network partition a distributed data store must choose between consistency (every read sees the latest write) and availability (every request gets a non-error answer). Since partitions happen, the real choice is CP or AP behaviour during them. PACELC extends it: else (no partition) you choose between latency and consistency. In microservices, most cross-service data is AP and eventually consistent; things like payments or inventory reservations may need CP within their owning service. → *More:* Ch 1 — CAP theorem and PACELC

Q116. ACID vs BASE? ACID (Atomicity, Consistency, Isolation, Durability) describes strong guarantees of a single database transaction. BASE (Basically Available, Soft state, Eventually consistent) describes systems that stay available and let state converge over time. Inside a service you usually get ACID from its database; across services you design for BASE. → *More:* Ch 1 — Transactions and ACID · Ch 1 — SQL vs NoSQL and BASE

Q117. ⋆ At-most-once, at-least-once and exactly-once delivery — what is the difference? At-most-once: a message may be lost but never duplicated (commit offset before processing). At-least-once: never lost but may be duplicated (commit after processing) — the common default. Exactly-once delivery is impossible in general across a network; what systems provide is exactly-once *processing* — at-least-once delivery plus idempotent handling or transactional deduplication (Kafka transactions within Kafka, inbox tables with a database). → *More:* Ch 1 — Delivery guarantees, idempotency and retries

Q118. How do you handle out-of-order events? Keep ordering where it matters by partitioning on the entity key (one partition per entity's stream). Include a version or sequence number in each event and have consumers ignore events older than what they have already applied. Design handlers to be commutative where possible, and use timestamps only with care because clocks on different machines drift. → *More:* Ch 1 — Clocks and ordering

Q119. ⋆ How do you make a payment API safe to retry (idempotency key)? The client generates a unique idempotency key (a UUID) once per logical operation and sends it in a header on every retry. The server stores the key with the result in the same transaction as the charge, guarded by a unique constraint. A repeated request with the same key returns the stored result instead of charging again; a concurrent duplicate fails the constraint and waits or gets a 409. Keys expire after a retention period (e.g. 24 h). → *More:* Ch 8 — Retry, "Idempotency revisited"

Q120. What is optimistic locking and why is it useful between services? Each record carries a version number; an update succeeds only if the version is unchanged (`UPDATE … SET …, version = version + 1 WHERE id = ? AND version = ?`). If someone else updated it first, zero rows change and the caller retries with fresh data. In JPA it is the `@Version` field. It avoids holding database locks across slow network calls, and ETags with `If-Match` bring the same idea to REST APIs.

Q121. What is read-your-writes consistency and how do you provide it with CQRS? The guarantee that a user sees their own update immediately even if the system is eventually consistent. With an async read model the user might save and then see old data. Options: return the new state in the command's response and update the UI optimistically; read from the write model for that user for a short time; or have the query wait until the read model has reached the version returned by the command. → *More:* Ch 12 — CQRS, "Managing data consistency"

Q122. What is a reconciliation job and why do you still need one? A periodic process that compares data across systems (orders vs payments vs the payment provider's report) and fixes or flags mismatches. Even with sagas and outboxes, bugs, manual fixes and third-party failures cause drift; reconciliation is the safety net that makes eventual consistency trustworthy, especially for money.

Q123. What is the "two generals" / why can't you be sure a remote call failed? When a call times out you do not know whether the request never arrived, was processed and the reply was lost, or is still running. That is why retries need idempotency and why a timeout must be treated as "unknown", not "failed". For important actions, query the status or rely on reconciliation before compensating.

---

8. Observability: logs, metrics and tracing

Q124. ⋆ How do you monitor microservices? What are the three pillars of observability? Observability is the ability to understand a system's internal state from what it emits. The three pillars: **logs** (timestamped records of discrete events, structured as JSON), **metrics** (numeric time series such as request rate, error rate, latency percentiles, CPU), and **traces** (the path and timing of one request across all services). Typical stack: Micrometer in the app, Prometheus + Grafana for metrics, Loki or ELK for logs, OpenTelemetry + Tempo/Jaeger for traces, plus alerting. → *More:* Ch 1 — Observability: logs, metrics and traces

Q125. ⋆ What is distributed tracing and how does it work? It follows one request through every service it touches. The first service creates a **trace ID**; each unit of work (an HTTP call, a DB query) is a **span** with its own span ID, parent span ID, timing and tags. The trace context is propagated in headers (the W3C `traceparent` header is the standard) and through message headers for async calls. Spans are exported to a backend (Jaeger, Zipkin, Tempo) that draws the request as a waterfall, so you see which hop was slow or failed. → *More:* Ch 1 — Observability · Ch 9 — Sidecar

Q126. ⋆ What is a correlation ID? A unique ID attached to a request at the edge and passed through every service call and message, and written into every log line. It lets you search all logs for one user request across services. Today the trace ID from distributed tracing usually plays this role; Spring Boot with Micrometer Tracing puts `traceId` and `spanId` into the logging MDC (Mapped Diagnostic Context) automatically.

Q127. What is OpenTelemetry? OpenTelemetry (OTel) is the vendor-neutral CNCF standard for producing and exporting traces, metrics and logs: APIs, SDKs, auto-instrumentation agents, the OTLP wire protocol and

the Collector (which receives, processes and forwards telemetry to any backend). Instrument once with OTel and switch backends freely. In Spring Boot, Micrometer Tracing bridges to OpenTelemetry, and Spring Boot 4 also ships a `spring-boot-starter-opentelemetry`. → *More:* Ch 1 — Observability

Q128. ⋆ What is centralised logging and why is it needed? With dozens of services and short-lived containers, you cannot SSH into machines to read log files. Each service writes structured logs to stdout; an agent (Fluent Bit, the OTel Collector) ships them to a central store (Elasticsearch/OpenSearch, Loki, a cloud logging service) where you can search by trace ID, service and time. Spring Boot supports structured JSON logging out of the box (`logging.structured.format.console=ecs` or `logstash`).

Q129. What metrics would you track for a microservice? What are the RED and USE methods? RED for request-driven services: Rate (requests per second), Errors (failed requests per second), Duration (latency distribution, especially p95/p99). **USE** for resources: Utilisation, Saturation (queue lengths, thread pool waits), Errors. Add business metrics (orders per minute), JVM metrics (heap, GC pauses), connection pool usage, consumer lag for Kafka, and circuit breaker state. Google's "four golden signals" are latency, traffic, errors and saturation. → *More:* Ch 1 — Percentiles, tail latency and why averages lie

Q130. ⋆ What is Spring Boot Actuator? Actuator adds production-ready endpoints to a Spring Boot app: `/actuator/health` (with liveness and readiness groups for Kubernetes), `/actuator/metrics` and `/actuator/prometheus` (via Micrometer), `/actuator/info`, `/actuator/env`, `/actuator/loggers` (change log levels at runtime) and more. Expose only what you need over HTTP and secure the rest.

Q131. What are SLI, SLO and SLA? What is an error budget? An SLI (service level indicator) is a measured value, e.g. the percentage of requests faster than 300 ms. An SLO (objective) is the target for it, e.g. 99.9% over 30 days. An SLA (agreement) is a contract with customers with penalties, set looser than the SLO. The error budget is 100% minus the SLO (0.1% ≈ 43 minutes per month): while budget remains you ship features; when it is spent you prioritise reliability. → *More:* Ch 1 — SLA, SLO, SLI and error budgets

Q132. How do you alert well in a microservices system? Alert on user-visible symptoms (SLO burn rate, error rate, latency at the edge) rather than every internal cause (high CPU on one Pod), so alerts are few and actionable. Each alert should link to a runbook and dashboard. Use multi-window burn-rate alerts to catch both fast and slow budget burns, and route alerts to the owning team. → *More:* Ch 1 — Dashboards, alerting, on-call and SLO-based alerts

Q133. What is semantic monitoring / synthetic monitoring? Running scripted fake user journeys (log in, search, add to cart) against production continuously and alerting when they fail or get slow. It checks the system works as a whole from the user's point of view, catching problems that per-service metrics miss.

Q134. What is the difference between liveness and readiness health checks? Liveness answers "is the process stuck?" — if it fails, Kubernetes restarts the container. Readiness answers "can it take traffic now?" — if it fails, the Pod is removed from the Service's endpoints but not restarted (e.g. during warm-up or when a critical dependency is unavailable). Do not put downstream dependencies in liveness checks, or one database blip restarts every Pod. A **startup probe** protects slow-starting apps from liveness kills. → *More:* Ch 5 — Health checks

Q135. How do you trace requests across asynchronous messaging? Put the trace context into message headers when producing and extract it when consuming, creating a consumer span linked to the producer span. Spring Kafka and Spring AMQP do this automatically with observation enabled (`spring.kafka.template.observation-enabled=true` and the listener equivalent). With an outbox, store the trace context in the outbox row so the relay can propagate it. → *More:* Ch 11 — Event-Driven

Q136. What is trace sampling and why is it needed? Recording every span of every request is expensive at high traffic, so you keep only a fraction. **Head sampling** decides at the start (e.g. 10% of traces) — cheap but may miss rare errors. **Tail sampling** (in the OTel Collector) decides after the trace finishes, keeping all errors and slow traces and a small sample of normal ones. Spring Boot's `management.tracing.sampling.probability` sets head sampling (default 0.1).

---

9. Deployment: containers, Kubernetes, CI/CD and release strategies

Q137. ⋆ Why are Docker containers used for microservices? A container packages a service with its runtime and dependencies into an image that runs the same on a laptop, in CI and in production. Containers start in seconds, use fewer resources than virtual machines (they share the host kernel), isolate services from each other, and give a uniform unit for orchestration. Spring Boot can build images without a Dockerfile (`./mvnw spring-boot:build-image` using Cloud Native Buildpacks). → *More:* Ch 1 — Virtual machines, containers and Docker

Q138. ⋆ Why is Kubernetes used for microservices? Name its core objects. Kubernetes is a container orchestrator: it schedules containers on a cluster, restarts failed ones, scales them, does rolling updates and provides service discovery and config. Core objects: **Pod** (one or more containers sharing network), **Deployment** (desired replicas, rolling updates), **Service** (stable name and load balancing), **Ingress/Gateway API** (HTTP routing from outside), **ConfigMap** and **Secret** (configuration), **HorizontalPodAutoscaler**, **StatefulSet** (stateful workloads), **Namespace** (isolation). → *More:* Ch 1 — Kubernetes basics

Q139. ⋆ What deployment strategies do you know? Blue-green vs canary vs rolling? Rolling: replace instances a few at a time — no extra capacity, but old and new versions run together. **Blue-green**: run the new version (green) next to the old (blue) and switch all traffic at once; instant rollback by switching back, but doubles capacity during the switch. **Canary**: send a small share of traffic (1%, 5%, 25%…) to the new version, watch metrics, then expand or roll back; safest for catching real-traffic bugs. Also **recreate** (stop all, start new — downtime) and **shadow/dark launch** (copy traffic to the new version without returning its responses). → *More:* Ch 1 — Deployment strategies and rollback

Q140. How do you do a canary release in Kubernetes? Basic: two Deployments behind one Service with replica counts in the desired ratio (coarse). Better: weighted routing in a service mesh (Istio VirtualService), the Gateway API (`HTTPRoute` weights) or an ingress controller, automated with Argo Rollouts or Flagger, which shift traffic in steps and roll back automatically when metrics such as error rate or p99 degrade. → *More:* Ch 1 — Deployment strategies and rollback

Q141. ⋆ How do you achieve zero-downtime deployment? Run several replicas and use rolling or blue-green updates; set readiness probes so new Pods get traffic only when ready; implement graceful shutdown (Spring Boot's `server.shutdown=graceful` finishes in-flight requests after SIGTERM, with a `preStop` delay so the load balancer stops sending first); keep APIs and database schemas backward compatible across the two versions running side by side; use a PodDisruptionBudget.

Q142. ⋆ How do you handle database schema changes with zero downtime? Use the **expand-and-contract** (parallel change) pattern: (1) expand — add the new column or table in a backward-compatible way; (2) deploy code that writes both old and new and reads new with fallback; (3) backfill data; (4) switch reads fully to new; (5) contract — remove the old column in a later release. Run migrations with Flyway or Liquibase as part of the deployment. Never rename or drop in the same release as the code change.

Q143. What is the difference between deployment and release? What are feature flags? Deployment puts new code into production; release exposes the feature to users. Feature flags (toggles checked at runtime) separate the two: you deploy dark, then turn the feature on for internal users, a percentage, or a region, and turn it off instantly if it misbehaves. Flags need cleanup afterwards, or they become technical debt. → *More:* Ch 2 — Strangler Fig, "What is a feature flag?"

Q144. ⋆ What does CI/CD look like for microservices? Each service has its own pipeline triggered by its own repository or path: build, unit tests, contract tests, static analysis and security scanning, build and sign a container image, deploy to staging, run integration/smoke tests, then progressive delivery to production (canary) with automated rollback. GitOps (Argo CD, Flux) keeps the desired cluster state in Git and syncs it. Independence of pipelines is the point — no shared release train. → *More:* Ch 1 — CI/CD

Q145. Monorepo vs polyrepo for microservices? A monorepo puts all services in one repository: easier atomic cross-service changes, shared tooling and code search, but needs build tooling that only builds what changed (Bazel, Nx, Gradle) and discipline to avoid hidden coupling. Polyrepo gives each service its own repository: clear ownership and independent pipelines, but cross-cutting changes and dependency upgrades need many PRs. Both work; the boundary discipline matters more.

Q146. How does autoscaling work for microservices on Kubernetes? The HorizontalPodAutoscaler adds or removes Pods based on metrics (CPU, memory, or custom ones like requests per second or Kafka consumer lag); KEDA scales on event-source metrics including down to zero. The Cluster Autoscaler or Karpenter adds nodes when Pods cannot be scheduled. Scaling only works if services are stateless and start quickly; set resource requests correctly, or HPA's percentages are meaningless. → *More:* Ch 1 — Autoscaling

Q147. What is Infrastructure as Code (IaC)? Defining infrastructure (networks, clusters, databases, DNS) in version-controlled files — Terraform/OpenTofu, Pulumi, CloudFormation, Helm charts or Kustomize for Kubernetes manifests — and applying them through automation instead of manual console clicks. It makes environments reproducible, reviewable and easy to recreate. → *More:* Ch 1 — Infrastructure as code

Q148. How do you make a Spring Boot service start fast and use less memory in containers? Options: layered JARs and buildpacks for cache-friendly images; Class Data Sharing (CDS) and Project Leyden's AOT cache (ahead-of-time class loading and linking since Java 24, with simpler creation and method profiling added in Java 25) to cut startup; GraalVM native images for millisecond startup and small memory (with build-time restrictions on reflection); virtual threads to serve many requests with few platform threads; and setting `-XX:MaxRAMPercentage` so the JVM respects container memory limits.

Q149. What is a Helm chart? A package of templated Kubernetes manifests with a `values.yaml` file for per-environment settings, installed and upgraded as a versioned "release". It lets you deploy the same service to dev, staging and production with different replica counts, resources and config, and roll back a release.

Q150. What is the Kubernetes Gateway API and how does it relate to Ingress? Ingress is the original, limited API for HTTP routing into a cluster. The Gateway API is its more expressive successor: `Gateway` resources (owned by platform teams) and `HTTPRoute`/`GRPCRoute` resources (owned by app teams) supporting header-based routing, traffic splitting by weight and cross-namespace delegation. Implementations include Envoy Gateway, Istio, NGINX and cloud load balancers.

Q151. How do you roll back a bad deployment? Keep the previous image and config: `kubectl rollout undo`, `helm rollback`, revert the Git commit in GitOps, or switch blue-green back. Automate rollback on canary metric failure. Rollback is only safe if the database migration was backward compatible (expand-and-contract) — which is why you never ship a destructive migration together with the code. → *More:* Ch 1 — Deployment strategies and rollback

---

10. Configuration management

Q152. ⋆ How do you manage configuration across microservices? What is externalised configuration? Keep configuration out of the build artifact so the same image runs in every environment. Sources, by increasing centralisation: environment variables, Kubernetes ConfigMaps and Secrets mounted as files or env vars, a config server (Spring Cloud Config backed by Git), or a store such as Consul, AWS AppConfig or Parameter Store. Secrets go to a dedicated vault. Config should be versioned, auditable and refreshable without redeploying. → *More:* Ch 13 — Configuration Externalization

Q153. ⋆ How does Spring Cloud Config work? A Config Server (`@EnableConfigServer`) serves properties from a backend, usually a Git repository with files like `order-service-prod.yml`. Clients import it on startup with `spring.config.import=optional:configserver:http://config:8888` and receive the properties for their `spring.application.name` and active profiles. Values can be encrypted (`{cipher}…`), and Git gives history and rollback. → *More:* Ch 13 — Worked example: Spring Cloud Config

Q154. ⋆ How do you refresh configuration without restarting a service? Beans annotated `@RefreshScope` (and `@ConfigurationProperties` beans) are rebuilt when a refresh event fires. Trigger it per instance with `POST /actuator/refresh`, or for all instances at once with **Spring Cloud Bus** (`/actuator/busrefresh`) over Kafka or RabbitMQ, often triggered by a Git webhook. On Kubernetes, Spring Cloud Kubernetes can reload on ConfigMap changes, or you roll the Pods. → *More:* Ch 13 — "Refreshing without restarting"

Q155. ⋆ How do you manage secrets in microservices? Never in Git or images. Use a secrets manager — HashiCorp Vault, AWS Secrets Manager, Azure Key Vault, GCP Secret Manager — accessed with short-lived credentials (Kubernetes service account identity), or Kubernetes Secrets encrypted at rest and synced from the vault (External Secrets Operator). Prefer dynamic, short-lived credentials (Vault database

secrets) and rotate regularly. Spring Cloud Vault integrates Vault as a property source. → *More:* Ch 13 — "Security — safeguarding sensitive configuration" · Ch 1 — Encryption, hashing, passwords and secrets

Q156. What if the config server is down? Clients must not fail to start because of it: run the config server with several replicas, cache last-known-good config locally, use `optional:` imports with sensible defaults, or enable fail-fast with retry when config is mandatory. Many Kubernetes shops avoid the extra server entirely by using ConfigMaps, which the platform already keeps highly available. → *More:* Ch 13 — "The configuration server as a single point of failure"

Q157. How do you override Spring Boot properties for different environments? Profiles (`application-prod.yml` activated with `spring.profiles.active=prod`), environment variables (relaxed binding: `SPRING_DATASOURCE_URL` maps to `spring.datasource.url`), command-line arguments, config-tree files mounted from Kubernetes, or the config server. Later sources override earlier ones; command-line arguments and environment variables beat packaged files.

Q158. Config server vs Kubernetes ConfigMaps — which would you choose? ConfigMaps/Secrets: native, no extra server, work for every language, but no built-in history beyond GitOps and refresh needs reload or restart. Spring Cloud Config: Git history, encryption, per-profile layering and bus refresh, but it is another critical service, and it is Spring-specific. On Kubernetes with GitOps, ConfigMaps are usually enough; the config server shines outside Kubernetes or when many Spring apps share layered config. → *More:* Ch 13 — Configuration Externalization

---

11. Security: OAuth2, JWT, mTLS and zero trust

Q159. ⋆ How do you secure microservices? In layers. At the edge: TLS everywhere, an API gateway that authenticates requests (OAuth 2.0 / OpenID Connect tokens), rate limiting and a WAF (web application firewall). Between services: mTLS for encrypted, mutually authenticated traffic and network policies that allow only expected calls. Inside services: validate the token, enforce fine-grained authorization, validate input. Plus secrets in a vault, least-privilege service accounts, image scanning and audit logs. → *More:* Ch 1 — Authentication and authorization · Ch 1 — Least privilege and zero trust

Q160. ⋆ What is OAuth 2.0? What are its roles? OAuth 2.0 is an authorization framework that lets a client obtain a limited-scope access token to call an API on behalf of a user (or itself), without handling the user's password. Roles: **resource owner** (user), **client** (the app), **authorization server** (issues tokens — Keycloak, Okta, Auth0, Spring Authorization Server), **resource server** (the API that validates tokens). OAuth is about authorization; **OpenID Connect** adds an ID token and user info on top for authentication (login). → *More:* Ch 1 — OAuth 2.0, OpenID Connect, SSO and API keys

Q161. ⋆ Which OAuth 2.0 grant types do you use, and when? Authorization code with PKCE for user-facing apps (web, mobile, single-page apps) — PKCE protects the code exchange. **Client credentials** for service-to-service calls with no user. **Refresh token** to get new access tokens without re-login. **Device code** for TVs and CLIs. Do not use the implicit grant (tokens leak through the browser URL) or the resource-owner password grant (the client sees the user's password): the OAuth 2.0 Security Best Current Practice (RFC 9700) says the password grant must not be used and the implicit grant should not be, and the OAuth 2.1 draft drops both.

Q162. ⋆ What is a JWT and how is it validated? A JSON Web Token is a compact, signed token with three Base64URL parts: header (algorithm, key ID), payload (claims such as `sub`, `iss`, `aud`, `exp`, `scope`) and signature. A service validates it locally — without calling the auth server — by checking the signature with the issuer's public key (fetched from its JWKS endpoint and cached, picked by the `kid` header) using only the algorithms you expect (never accept `alg: none`), then `exp` (and `nbf`), `iss` and `aud`. JWTs are signed, not encrypted, so never put secrets in them. In Spring: `spring.security.oauth2.resourceserver.jwt.issuer-uri`. → *More:* Ch 1 — Sessions, cookies, tokens and JWT

Q163. ⋆ How do you revoke a JWT? Opaque tokens vs JWTs? A JWT is valid until it expires, so keep access tokens short-lived (5–15 minutes) and revoke the refresh token; for urgent revocation keep a denylist of token IDs (`jti`) in a shared store such as Redis, checked by the gateway or each resource server, with each entry kept only until that token would have expired anyway. That check brings back a lookup per request, which is the cost of revocability. Opaque tokens are random strings the resource server

must check with the authorization server (token introspection) — instantly revocable but each check costs a call (usually cached). A common mix: opaque at the edge, exchanged by the gateway for a short-lived internal JWT.

Q164. How do you propagate user identity between services? Forward the user's access token on downstream calls (simple, but every service receives a broad token), or use **token exchange** (RFC 8693) to get a narrower token for the downstream audience. For calls with no user, services authenticate as themselves with the client-credentials grant or workload identity. Never trust a plain `X-User-Id` header unless it comes from a component you authenticate (e.g. via mTLS from the gateway).

Q165. ⋆ What is mTLS and why is it used between services? In normal TLS only the server proves its identity with a certificate. In mutual TLS both sides present certificates, so each service knows exactly which service is calling, and traffic is encrypted. Managing certificates for hundreds of services by hand is hard, so service meshes (Istio, Linkerd) issue and rotate short-lived certificates automatically (often with SPIFFE identities) and enforce mTLS in the sidecar without code changes. → *More:* Ch 9 — Sidecar · Ch 1 — HTTPS and TLS

Q166. ⋆ What is zero trust? A security model that assumes the network is already compromised: no request is trusted because it comes from "inside". Every call is authenticated and authorised (mTLS plus tokens), access is least-privilege and short-lived, and traffic is encrypted and logged. It replaces the old "hard shell, soft centre" perimeter model. → *More:* Ch 1 — Least privilege and zero trust

Q167. Authentication vs authorization? Authentication answers "who are you?" (verifying identity with a password, token or certificate). Authorization answers "what are you allowed to do?" (roles, scopes, ownership checks). A request is first authenticated, then authorised for each action. → *More:* Ch 1 — Authentication and authorization

Q168. Where should a single-page app keep its tokens? What is the token-handler (BFF) pattern for security? Tokens in browser storage (`localStorage`) are readable by any XSS script. The recommended pattern is a security BFF: the browser holds only an `HttpOnly`, `Secure`, `SameSite` session cookie, while the BFF performs the OAuth flow, stores tokens server-side and attaches them to API calls. Spring Cloud Gateway with the `TokenRelay` filter is a common way to build it. → *More:* Ch 4 — BFF · Ch 1 — Common web vulnerabilities

Q169. How do you protect services from the OWASP API Top 10 risks? Object-level authorization on every resource (the most common bug: user A reading `/orders/123` of user B), strict input validation, rate limiting, no excessive data in responses, inventory of all API versions, secured management endpoints (Actuator), and protection against server-side request forgery when calling URLs supplied by users. Test these explicitly; gateways alone do not fix object-level authorization.

Q170. What are API keys and when are they acceptable? A static secret string identifying a calling application. They are fine for identifying and rate-limiting partner or server-side clients of low-risk APIs, but they carry no user identity, rarely expire and are easily leaked, so do not use them to authorise user actions. Rotate them, scope them and send them only over TLS. → *More:* Ch 1 — OAuth 2.0, OpenID Connect, SSO and API keys

Q171. How do you secure Kafka or other message brokers? TLS for encryption in transit, authentication of clients (mTLS or SASL/OAUTHBEARER), ACLs so each service can produce or consume only its own topics, encryption at rest, and no sensitive personal data in events unless needed (or encrypt those fields). Remember that events are long-lived copies of data, which matters for privacy rules such as GDPR deletion.

Q172. How do you secure the software supply chain for containers? Use minimal base images, scan images and dependencies for vulnerabilities in CI, generate an SBOM (software bill of materials), sign images (Sigstore cosign) and verify signatures at admission in Kubernetes, pin image digests, run containers as non-root with read-only file systems, and apply Pod Security Standards.

---

12. Testing microservices

Q173. ⋆ How do you test microservices? What types of tests do you use? Follow the test pyramid: many fast **unit tests** of domain logic; **integration tests** of each service with its real infrastructure

(database, broker) using Testcontainers; **component tests** of one service in isolation with its dependencies stubbed (WireMock); **contract tests** between consumers and providers; and a few **end-to-end tests** of critical journeys. Add performance, resilience (chaos) and security tests, and monitor production as a test of last resort.

Q174. ⋆ What is contract testing? What is consumer-driven contract testing? A contract test checks that a provider's API matches what each consumer expects, without deploying both together. In consumer-driven contracts, each consumer writes down the requests it makes and the responses it relies on; the provider's build verifies it satisfies every consumer contract, so a breaking change fails the provider's CI before release. Tools: **Pact** (contracts shared through a Pact Broker, `can-i-deploy` checks) and **Spring Cloud Contract** (contracts generate provider tests and consumer stubs). → *More:* Ch 4 — BFF

Q175. What is Pact? Pact is a consumer-driven contract testing tool available for many languages. The consumer's test runs against a Pact mock server and records a "pact" file of interactions; the pact is published to a broker; the provider replays those interactions against its real API to verify them. The broker's `can-i-deploy` check tells you whether a version is compatible with what is deployed in each environment.

Q176. ⋆ What is the test pyramid (Mike Cohn)? A guideline that a test suite should have many cheap, fast unit tests at the bottom, fewer integration/service tests in the middle, and very few slow, brittle UI/end-to-end tests at the top. In microservices, contract tests replace much of the expensive end-to-end layer.

Q177. Why are end-to-end tests problematic in microservices? They need many services, databases and brokers deployed together in the right versions; they are slow and flaky, failures are hard to pinpoint, and they create a shared environment that becomes a release bottleneck — reintroducing the coupling microservices try to remove. Keep a handful for critical journeys and rely on contracts and component tests for the rest.

Q178. What is Testcontainers and why use it? A library that starts real dependencies — PostgreSQL, Kafka, Redis, even LocalStack for AWS — in throwaway Docker containers during tests. Tests run against the same technology as production instead of in-memory fakes like H2. Spring Boot supports it with `@ServiceConnection`, which wires the container's connection details automatically. Spring Boot 4 uses Testcontainers 2, where each module has its own package and the container classes are no longer generic (`org.testcontainers.postgresql.PostgreSQLContainer` from `testcontainers-postgresql`).

```
@SpringBootTest
@Testcontainers
class OrderRepositoryIT {
  @Container @ServiceConnection
  static PostgreSQLContainer pg = new PostgreSQLContainer("postgres:17");
  // tests now use a real PostgreSQL
}
```

Q179. How do you test a service that calls another service? In unit tests, mock the client interface. In component tests, stub the remote HTTP API with WireMock (or Spring Cloud Contract stub runner) and test timeouts, errors and slow responses too, since those paths are where resilience bugs hide. Verify the stub matches reality with contract tests.

Q180. How do you test asynchronous, event-driven flows? Test producers by asserting the event published (to an embedded or Testcontainers Kafka) for a given command; test consumers by publishing an event and asserting the resulting state, using polling assertions (Awaitility) instead of sleeps. Include tests for duplicate and out-of-order messages, and for poison messages reaching the DLQ. Contract-test event schemas too (Pact supports message pacts).

Q181. What is consumer-side vs provider-side stubbing in Spring Cloud Contract? The provider writes contracts (Groovy/YAML DSL, ideally with consumer input) in its repository; the build generates provider verification tests and publishes WireMock stubs as a JAR. Consumers pull those stubs with the Stub Runner and test against them, so both sides are tested against the same contract.

Q182. What is canary analysis / testing in production? Because staging never matches production exactly, teams verify releases with production traffic under control: canaries with automated metric comparison, feature flags for small user groups, shadow traffic, synthetic monitoring, and chaos

experiments. It complements pre-production tests, it does not replace them. → *More:* Ch 1 — Deployment strategies and rollback

Q183. How do you performance-test a microservice? Load-test with realistic traffic patterns (k6, Gatling, JMeter) against a production-like environment; measure throughput and p95/p99 latency, not averages; find the saturation point and which resource saturates first; test with downstream latency injected; and re-run in CI for key services to catch regressions. → *More:* Ch 1 — Percentiles, tail latency and why averages lie

---

13. Spring Cloud and Spring Boot specifics

Q184. ⋆ What is Spring Cloud? What problems does it solve? Spring Cloud is a set of projects on top of Spring Boot that implement common distributed-system patterns: configuration (Spring Cloud Config, Vault, Kubernetes), service discovery (Eureka, Consul, Kubernetes), client-side load balancing (Spring Cloud LoadBalancer), API gateway (Spring Cloud Gateway), circuit breakers (Spring Cloud Circuit Breaker over Resilience4j), messaging (Spring Cloud Stream, Bus), contract testing (Spring Cloud Contract) and declarative HTTP clients (OpenFeign). It is versioned as a release train: **2025.1 "Oakwood"** is the line for Spring Boot 4.

Q185. ⋆ Spring Boot vs Spring Cloud? Spring Boot builds a single production-ready application quickly: auto-configuration, embedded server, starters, Actuator. Spring Cloud adds the tools for many such applications to work together as a distributed system: discovery, config, gateway, resilience, messaging. Spring Boot is about one service; Spring Cloud is about the system of services.

Q186. ⋆ Why is Spring Boot widely used for microservices? It removes boilerplate with auto-configuration and starters, runs as a self-contained JAR with an embedded server, has production features built in (Actuator health checks, Micrometer metrics and tracing, graceful shutdown, structured logging), integrates natively with Spring Cloud, Kafka, security and Testcontainers, builds container images and native images, and now supports virtual threads with a single property.

Q187. ⋆ What is Spring Cloud Gateway? How do routes, predicates and filters work? Spring Cloud Gateway is Spring's API gateway. A **route** has an ID, a destination URI (which can be `lb://order-service` to load-balance through discovery), **predicates** that decide which requests match (path, host, header, method) and **filters** that change requests or responses (strip prefix, add headers, rate limit, circuit breaker, retry, token relay). In Spring Cloud 2025.x it comes in two flavours — **Server WebFlux** (reactive, Netty) and **Server Web MVC** (servlet, works well with virtual threads) — with the starters `spring-cloud-starter-gateway-server-webflux` and `spring-cloud-starter-gateway-server-webmvc` (the old `spring-cloud-starter-gateway` names were removed in 2025.1). → *More:* Ch 3 — API Gateway

```
@Bean
RouteLocator routes(RouteLocatorBuilder rlb) {
  return rlb.routes()
      .route("orders", r -> r.path("/api/orders/**")
          .filters(f -> f.stripPrefix(1)
              .circuitBreaker(c -> c.setName("orders").setFallbackUri("forward:/fallback")))
          .uri("lb://order-service"))
      .build();
}
```

Q188. What replaced Netflix Zuul, Hystrix and Ribbon? They entered maintenance mode in Spring Cloud Greenwich (2019) and were later removed. Zuul → **Spring Cloud Gateway**; Hystrix → **Resilience4j** (via Spring Cloud Circuit Breaker); Ribbon → **Spring Cloud LoadBalancer**; Hystrix Dashboard/Turbine → **Micrometer** with Prometheus/Grafana. Eureka is still supported. Spring Cloud Sleuth was replaced by **Micrometer Tracing** from Spring Boot 3 onwards.

Q189. ⋆ How do you set up a Eureka server and client? Server: add `spring-cloud-starter-netflix-eureka-server` and annotate the application with `@EnableEurekaServer`. Client: add `spring-cloud-starter-netflix-eureka-client`, set `spring.application.name` and `eureka.client.service-url.defaultZone`; it registers and sends heartbeats automatically (`@EnableDiscoveryClient` is optional). Callers then use the logical name through a `@LoadBalanced` client or `lb://` gateway routes. → *More:* Ch 5 — Service Discovery

Q190. ⋆ What is OpenFeign? What are HTTP interface clients and which should you use now? OpenFeign lets you declare an interface annotated with `@FeignClient("order-service")` and Spring generates the HTTP client, integrated with discovery and load balancing. The Spring Cloud team has declared OpenFeign feature-complete and recommends Spring's own **HTTP interface clients**: an interface with `@GetExchange`/`@PostExchange` methods backed by `RestClient` or `WebClient`. Spring Framework 7 makes them easy to register in groups with `@ImportHttpServices`.

```
public interface InventoryClient {
  @GetExchange("/stock/{sku}")
  Stock stock(@PathVariable String sku);
}
```

Q191. RestTemplate vs RestClient vs WebClient? `RestTemplate` is the old synchronous client: Spring announced its deprecation with Framework 7.0, it is marked deprecated for removal in 7.1, and removal is planned for 8.0. `RestClient` (Spring 6.1+) is the modern synchronous client with a fluent API — the default choice, especially with virtual threads. `WebClient` is the reactive, non-blocking client from WebFlux, for reactive stacks or streaming. All can be `@LoadBalanced` and back HTTP interface clients.

Q192. What is Spring Cloud Circuit Breaker? An abstraction over circuit-breaker libraries (`CircuitBreakerFactory`, `ReactiveCircuitBreakerFactory`) so code is not tied to one implementation; Resilience4j is the main implementation (the Spring Retry implementation is in maintenance-only mode since Spring Cloud 2025.1). You can use it programmatically (`factory.create("inventory").run(supplier, fallback)`) or use Resilience4j's own annotations directly. → *More:* Ch 6 — Circuit Breaker

Q193. ⋆ What is Spring Cloud Stream? A framework for event-driven services that hides the broker behind "binders" (Kafka, RabbitMQ, others). You write plain `java.util.function` beans — `Supplier` (producer), `Function` (processor), `Consumer` (sink) — and bind them to destinations in configuration, e.g. `spring.cloud.function.definition=processOrder` with `spring.cloud.stream.bindings.processOrder-in-0.destination=orders`. It handles serialization, consumer groups, partitioning, retries and DLQs. For Kafka-specific control, plain Spring for Apache Kafka (`@KafkaListener`, `KafkaTemplate`) is also common. → *More:* Ch 11 — Event-Driven

Q194. What is Spring Cloud Bus? It links service instances through a message broker (Kafka or RabbitMQ) so that management events reach all of them, most commonly a configuration refresh: one call to `/actuator/busrefresh` makes every instance reload its `@RefreshScope` beans. → *More:* Ch 13 — Configuration Externalization

Q195. What is Spring Cloud Kubernetes? Integration that lets Spring apps use Kubernetes-native features through Spring abstractions: ConfigMaps and Secrets as property sources (with reload), Kubernetes Services for `DiscoveryClient` and load balancing, so you do not need Eureka or a config server on Kubernetes. Many teams use none of it and rely on plain Kubernetes DNS and mounted config.

Q196. How do you implement a saga or outbox in Spring? Outbox: in a `@Transactional` method, save the entity and an outbox entity; relay with a scheduled poller or Debezium. **Spring Modulith**'s event publication registry gives a ready outbox-like mechanism: `ApplicationEvent`s published in a transaction are stored and re-delivered (and can be externalised to Kafka) if a listener fails. Saga orchestration can be a Spring state machine-style service, or a workflow engine such as Temporal or Camunda with Spring Boot starters; choreography uses Kafka listeners plus compensating handlers. → *More:* Ch 10 — Saga

Q197. ⋆ What is the `@Transactional` pitfall when publishing Kafka messages? Sending to Kafka inside a `@Transactional` database method is a dual write: if the database commit fails after the send, consumers see an event for data that does not exist; if you send after commit and crash, the event is lost. Also, `@Transactional` on a private method or a self-call is ignored because Spring's proxy is bypassed. Use the outbox, or `@TransactionalEventListener(phase = AFTER_COMMIT)` only when losing an occasional event is acceptable. → *More:* Ch 10 — Saga

Q198. How does Spring Boot support Kubernetes probes and graceful shutdown? On Kubernetes, Actuator exposes `/actuator/health/liveness` and `/actuator/health/readiness` automatically, driven by the application's availability state (readiness goes down during shutdown). `server.shutdown=graceful` (the default since Boot 3.4) lets in-flight requests finish within `spring.lifecycle.timeout-per-shutdown-phase` after SIGTERM.

Q199. What is Spring Modulith and when would you use it? A Spring project for building well-structured modular monoliths: each top-level package is an application module; tests verify modules access each other only through public APIs; modules communicate through application events (with a persistent publication registry); and it generates module documentation. It is the recommended way to start before splitting into microservices, and it makes later extraction easier.

Q200. How do you add distributed tracing to a Spring Boot microservice? Add Actuator plus Micrometer Tracing with a bridge (OpenTelemetry) and an exporter (OTLP), or simply Spring Boot 4's `spring-boot-starter-opentelemetry`; set `management.opentelemetry.tracing.export.otlp.endpoint` (Spring Boot 3 called it `management.otlp.tracing.endpoint`) and `management.tracing.sampling.probability`. HTTP server and client calls (`RestClient`, `WebClient`), Kafka, JDBC (with extra instrumentation) and `@Observed` methods produce spans, and trace IDs appear in logs automatically. → *More:* Ch 1 — Observability

---

14. Scenario, troubleshooting and senior-level questions

These are the open-ended questions of senior rounds. Structure every answer the same way: **clarify → find the cause or the constraint → name the pattern(s) → state the trade-off**.

Q201. ⋆ One microservice is slow, but the system is otherwise fine. How do you find the cause? Start from the trace: open a slow request's distributed trace and see which span dominates — its own code, a database query, or a downstream call. Check the service's RED metrics and when the slowdown started (correlate with a deploy, traffic spike or dependency change). Then look at resources: CPU throttling from container limits, GC pauses, thread or connection pool saturation, slow queries (missing index, lock waits), and noisy neighbours. Fix the cause, and add a timeout/bulkhead so this service cannot drag callers down next time. → *More:* Ch 1 — Observability · Ch 1 — Bottlenecks

Q202. ⋆ A downstream service your service depends on is down. What happens and what should you do? Without protection your threads wait on timeouts and you fail too — a cascade. With protection: short timeouts, the circuit breaker opens after the failure threshold and calls fail fast; a fallback serves cached or default data, or the request is queued for later; the bulkhead keeps other features working; alerts fire on the Open state. If the dependency is critical (payments), return a clear error quickly instead of hanging. Long-term, ask whether the call needs to be synchronous at all. → *More:* Ch 6 — Circuit Breaker · Ch 7 — Bulkhead

Q203. ⋆ Design the order placement flow for an e-commerce system with Order, Payment and Inventory services. The Order service saves the order as `PENDING` and an `OrderCreated` event in its outbox, returning 202 Accepted with the order ID. An orchestrator (or choreography) runs the saga: reserve stock in Inventory, then charge the card in Payment (the pivot), then confirm the order. On failure, compensate: release stock, refund, mark the order `CANCELLED`. Every step is idempotent (keyed by order ID), consumers dedupe, the UI shows the pending state and is notified on completion. Add a timeout for stuck sagas and reconciliation with the payment provider. → *More:* Ch 10 — Saga, "Worked example: online shopping"

Q204. ⋆ A customer was charged twice. How could that happen and how do you prevent it? Likely causes: a client or gateway retried a POST after a timeout while the first request had actually succeeded; a message consumer processed a redelivered message twice; or two instances processed the same outbox row. Prevent with an idempotency key on the payment API stored with a unique constraint, idempotent consumers (inbox table), retries in only one layer, `SKIP LOCKED` or a single relay for the outbox, passing the same idempotency key to the payment provider, and a reconciliation job that detects and refunds duplicates. → *More:* Ch 8 — Retry, "Idempotency revisited"

Q205. ⋆ How would you migrate a large monolith to microservices without stopping feature work? Do not rewrite. First modularise inside the monolith and add observability and CI/CD. Put a facade (gateway) in front. Pick a first service with clear boundaries and business value, build it, route its traffic through the facade behind a feature flag, run old and new in parallel and compare results, then switch over and delete the old code. Split data with CDC or events. Repeat capability by capability, measuring deployment frequency and lead time to check it is paying off. → *More:* Ch 2 — Strangler Fig

Q206. ⋆ Kafka consumer lag is growing. What do you check? Lag means consumers process slower than producers write. Check: a sudden traffic spike; slow processing per message (a slow downstream call or

database); a poison message causing endless retries on one partition; frequent consumer-group rebalances (processing taking longer than `max.poll.interval.ms`); too few partitions to add more consumers (parallelism is capped at partitions); or one hot partition from a skewed key. Fixes: speed up or batch the handler, add consumers up to the partition count, increase partitions (which changes key mapping), send poison messages to a DLQ, autoscale on lag (KEDA). → *More:* Ch 1 — Event streaming

Q207. How would you handle a sudden 10× traffic spike (e.g. a flash sale)? Prepare: load-test, pre-scale critical services, warm caches, and set autoscaling on the right metrics. During the spike: rate limit at the gateway, queue orders asynchronously to absorb the burst, shed non-critical work (recommendations, analytics), serve read-heavy pages from CDN and cache, and protect the database (connection pool limits, read replicas). Use a virtual waiting room if even that is not enough. → *More:* Ch 1 — Load shedding and graceful degradation · Ch 7 — Bulkhead

Q208. ⋆ Two services need each other's data and call each other synchronously (a cycle). How do you fix it? A cycle means the boundary is probably wrong or the dependency should be asynchronous. Options: merge the two services if they always change together; move the shared concept into the service that owns it; have one side keep a local copy of the data it needs, updated by events; or introduce a third service for the shared workflow (orchestration). Cyclic synchronous calls also risk deadlocked thread pools during load.

Q209. How do you implement a "get order details" endpoint needing data from five services? Either API composition in a BFF/aggregator — parallel calls with per-call timeouts, returning partial data with flags when optional parts fail — or a CQRS read model (an "order view" service) that subscribes to all five services' events and stores a denormalised document, answering in one fast query at the cost of eventual consistency. Choose composition for low traffic or freshness-critical data; the read model for hot, read-heavy pages. → *More:* Ch 12 — CQRS · Ch 4 — BFF

Q210. A deployment caused errors in production. Walk through your response. Mitigate first, investigate second: roll back (or flip the feature flag off) as soon as the deploy is the likely cause, communicate status, and confirm metrics recover. Then use traces, logs and the diff to find the root cause, write a blameless post-mortem, and add the missing safeguard — a contract test, a canary with automated analysis, an alert. Ask why the canary or tests did not catch it.

Q211. How would you design rate limiting for a public API used by many clients? Identify the client (API key or OAuth client ID); define tiers with limits per second and per day; enforce with a token bucket in Redis at the gateway, using atomic Lua scripts; return 429 with `Retry-After` and rate-limit headers; add per-endpoint limits for expensive operations and a global limit to protect the backend; and consider local in-memory limiters for speed with a shared store for accuracy. → *More:* Ch 1 — Rate limiting and throttling · Ch 3 — API Gateway

Q212. ⋆ A service needs to send an email/notification only after an order is committed. How do you guarantee it is sent exactly once? You cannot guarantee exactly-once delivery to an external email provider, but you can get "at least once, deduplicated". Write an `OrderConfirmed` event to the outbox in the order transaction; a notification service consumes it idempotently (keyed by event ID), sends the email with an idempotency key if the provider supports it, and records it as sent. Retries with backoff handle provider outages; a DLQ catches permanent failures.

Q213. How do you handle a long-running business process (days, e.g. loan approval)? Model it as an orchestrated saga or workflow with durable state: a workflow engine (Temporal, Camunda) or a state machine persisted in the database. Steps are triggered by events or timers, wait for human tasks, have timeouts and escalation, and can resume after crashes. Expose the status through an API and notify users on changes instead of keeping requests open. → *More:* Ch 10 — Saga

Q214. You see intermittent 502/503 errors during deployments. What is the likely cause? Traffic is reaching Pods that are not ready or are shutting down: missing or too-lenient readiness probes, no graceful shutdown, or the load balancer still sending to a Pod after it received SIGTERM. Fix with correct readiness probes, `server.shutdown=graceful`, a short `preStop` sleep so endpoints are removed before the app stops, `maxUnavailable: 0` in the rolling update, and retries for idempotent requests at the gateway. → *More:* Ch 1 — Deployment strategies and rollback

Q215. How do you make a microservice multi-tenant? Choose an isolation model: shared database with a `tenant_id` column on every table (cheapest; enforce with row-level security in PostgreSQL), schema per tenant, or database per tenant (strongest isolation, costliest). Carry the tenant ID in the token,

propagate it in context, apply per-tenant rate limits and quotas so one tenant cannot starve others (a bulkhead per tenant), and include it in logs and metrics.

Q216. ⋆ How do you decide whether a feature should be a new microservice or part of an existing one? Ask: does it belong to an existing bounded context (same language, same data, changes together)? Will a different team own it? Does it need different scaling, availability or technology? Would separating it create chatty calls or a distributed transaction? Default to adding it to the existing service; split when ownership, change rate or scaling needs clearly diverge.

Q217. How would you design a system to guarantee that inventory is never oversold? Make the inventory service the single owner of stock counts and reserve atomically in its database (`UPDATE stock SET available = available - :q WHERE sku = :s AND available >= :q`, checking rows affected). Reserve at checkout with an expiry, confirm after payment, release on cancellation or timeout via the saga. For very hot items, shard counts or use Redis atomic decrements with periodic reconciliation. Don't let the read model (eventually consistent) decide availability. → *More:* Ch 10 — Saga

Q218. How do you reduce the blast radius of failures in a large system? Isolate at every level: bulkheads within services; separate deployments for critical and non-critical paths; per-tenant or per-customer limits; multiple availability zones; cell-based architecture (independent copies of the full stack each serving a subset of users); progressive rollouts per cell or region; and avoiding shared global dependencies that everything calls synchronously. → *More:* Ch 7 — Bulkhead

Q219. What would you look at in a "design a URL shortener/ride-hailing/food delivery with microservices" round? Requirements and scale numbers first; then identify bounded contexts and service list; data ownership and storage per service; synchronous vs event-driven interactions; the critical write path and how it stays consistent (sagas, outbox); read paths and caching; the edge (gateway, auth, rate limits); resilience; observability; deployment. Finish with bottlenecks and trade-offs. Don't create 20 services — justify each split. → *More:* Ch 1 — How to approach a system design interview · Ch 1 — Worked example: URL shortener

Q220. ⋆ What are the most common microservices anti-patterns you have seen? Distributed monolith (lock-step deploys); shared database; too-fine "nanoservices"; chatty synchronous chains; no timeouts; retries at every layer; dual writes without an outbox; business logic in the API gateway; shared domain libraries that force synchronized upgrades; no observability; breaking API changes without versioning; and adopting microservices before having CI/CD and monitoring.

Q221. How do you keep many teams' services consistent without central control? Provide a "paved road" platform: service templates (starter projects with logging, tracing, health checks, security and CI pre-wired), shared base images, an internal developer portal (Backstage) listing owners and APIs, API style guides and linting, and lightweight architecture decision records (ADRs). Standardise interfaces and operations, not internal implementation.

Q222. Your read model (CQRS) is out of sync with the write side. How do you recover? Find why: a consumer bug, lost or skipped events, or out-of-order handling. Fix the bug, then rebuild the projection by replaying events from the beginning (Kafka retention, event store, or a fresh snapshot of the write database via CDC) into a new read store, and switch over when it has caught up. Design projections to be rebuildable from day one and monitor projection lag. → *More:* Ch 12 — CQRS, "Synchronising the two sides"

Q223. How do you deprecate and remove an API endpoint used by other teams? Find the consumers (contract tests, gateway logs, traces); publish a new version and a migration guide; mark the old one deprecated with the `Deprecation` and `Sunset` headers (Spring Framework 7 can add them via its API versioning support); track remaining usage; contact laggards; then remove it once traffic reaches zero.

Q224. When would you choose events over a synchronous call for the same interaction? Events when: the caller does not need the result to answer its own client; several services need to react; the receiver may be down or slow and you do not want to depend on it; or you want to absorb load spikes. Synchronous when: the user needs the answer now (a price check, an authorisation decision), the operation is a query, or strict ordering and immediate consistency outweigh decoupling. → *More:* Ch 11 — Event-Driven · Ch 1 — Synchronous vs asynchronous communication

Q225. ⋆ Tell me about a time a microservices design went wrong. What did you learn? Behavioural, but expect it. Use STAR (Situation, Task, Action, Result) and pick a real example with a technical lesson: a missing timeout that caused a cascade, a dual write that lost events, a split that created a

distributed monolith. Explain the detection, the fix, the safeguard you added (outbox, contract test, alert) and what you would do differently — interviewers want to hear trade-off thinking and ownership.

---

15. Rapid-fire "difference between X and Y" and short-answer round

Phone screens often finish with quick comparisons. Aim for two or three sentences each.

Q226. ⋆ Orchestration vs choreography (in general, not only sagas)? Orchestration: one component directs the others step by step and owns the workflow state — explicit, easy to monitor, but a central dependency. Choreography: each service reacts to events on its own and no one sees the whole flow — loosely coupled, but the end-to-end process is implicit and harder to debug. → *More:* Ch 10 — Saga, "Choosing between them" · Ch 11 — Event-Driven, "Mediator EDA"

Q227. Message queue vs event stream? A queue delivers each message to one consumer and deletes it after acknowledgement — work distribution. A stream (Kafka) keeps an ordered, retained log that many consumer groups read independently at their own offsets and can replay — event history and fan-out. → *More:* Ch 1 — Message queues

Q228. Horizontal vs vertical scaling — which suits microservices? Vertical scaling gives one machine more CPU/RAM; it is simple but has a ceiling and a single point of failure. Horizontal scaling adds more instances behind a load balancer; it suits stateless microservices and gives redundancy, but needs externalised state. → *More:* Ch 1 — Vertical and horizontal scaling

Q229. Container vs virtual machine? A VM virtualises hardware and runs a full guest operating system — strong isolation, heavier, slower to start. A container shares the host kernel and isolates only processes, file system and network with namespaces and cgroups — lightweight and fast, but weaker isolation. → *More:* Ch 1 — Virtual machines, containers and Docker

Q230. Docker vs Kubernetes? Docker builds and runs containers on one machine. Kubernetes orchestrates containers across many machines — scheduling, scaling, self-healing, rolling updates, service discovery. Kubernetes runs images built by Docker (or any OCI tool) using a container runtime such as containerd. → *More:* Ch 1 — Kubernetes basics

Q231. Kubernetes Deployment vs StatefulSet? A Deployment manages interchangeable, stateless Pods with random names that can be replaced freely. A StatefulSet gives each Pod a stable name (`kafka-0`, `kafka-1`), stable storage and ordered start/stop — for databases, brokers and other stateful systems.

Q232. ConfigMap vs Secret? Both inject configuration into Pods as environment variables or files. Secrets are meant for sensitive values: they are kept separately, can be encrypted at rest and access-controlled more tightly — but they are only Base64-encoded by default, so enable encryption and RBAC, or sync them from a vault. → *More:* Ch 13 — Configuration Externalization

Q233. Liveness vs readiness vs startup probe — one line each? Liveness: if this fails, the container is hung, so the kubelet kills and restarts it. Readiness: if this fails, the Pod stays up but is taken out of the Service until it passes again. Startup: holds back the liveness and readiness checks until a slow-booting app has come up. → *More:* Ch 5 — Health checks

Q234. Logs vs metrics vs traces — when do you reach for each? Start with metrics: they are cheap aggregates that drive alerts and dashboards and show that error rate or latency has moved. Then open traces for affected requests to locate the service or call where the time or error appears. Finally read the logs for that trace ID to get the detail — the exception, the input, the decision the code made. → *More:* Ch 1 — Observability

Q235. Circuit breaker vs retry? Retry assumes the failure is brief and tries again; circuit breaker assumes the failure is lasting and stops trying for a while. Used together, the breaker caps the damage retries could do to an unhealthy dependency. → *More:* Ch 6 — Circuit Breaker · Ch 8 — Retry, "Retry vs. fail-fast"

Q236. API Gateway vs service mesh? The gateway handles north-south traffic at the edge — client authentication, public API shape, rate limits per client. The mesh handles east-west traffic between services — mTLS, retries, traffic splitting, telemetry. Many systems use both. → *More:* Ch 3 — API Gateway · Ch 9 — Sidecar

Q237. Event sourcing vs change data capture? Event sourcing makes domain events the source of truth inside the service — intentional, business-meaningful events. CDC derives row-level change events from an ordinary database's log — no code change, but the events mirror table structure, not business intent (so the outbox table is often what CDC reads). → *More:* Ch 12 — CQRS

Q238. Saga vs 2PC — the one-sentence version? 2PC gives atomic, isolated commits across participants at the cost of locks and blocking; a saga gives availability and loose coupling at the cost of isolation and hand-written compensations. → *More:* Ch 10 — Saga

Q239. Stateless JWT vs server-side session? A JWT carries the user's claims and is validated locally by any service — scales easily, but hard to revoke before expiry. A server-side session stores state in a shared store (Redis) referenced by a cookie — easy to revoke, but every service needs access to that store. → *More:* Ch 1 — Sessions, cookies, tokens and JWT

Q240. Strong vs eventual consistency — give a business example for each. Strong: account balances and inventory reservation — a stale read can lose money. Eventual: product reviews, follower counts, search indexes, order history views — a few seconds of staleness is invisible to users. → *More:* Ch 1 — Consistency models

Q241. Spring Cloud Gateway WebFlux vs Web MVC — which one? WebFlux (Netty, reactive) handles very high concurrency with few threads and supports every gateway feature first. Web MVC (servlet) fits teams on the blocking stack; with virtual threads it scales well and is simpler to debug. Pick the one that matches your team's stack. → *More:* Ch 3 — API Gateway

Q242. `@LoadBalanced` — what does it actually do? It marks a `RestClient.Builder`, `RestTemplate` or `WebClient.Builder` bean so Spring Cloud adds an interceptor that treats the host in `http://order-service/...` as a logical service name, resolves it to an instance through the `DiscoveryClient`, and applies the load-balancing algorithm. → *More:* Ch 5 — Service Discovery

Q243. `@RefreshScope` — what is the catch? Refresh-scoped beans are recreated lazily after a refresh event, so references captured elsewhere (e.g. in a constructor of a non-refresh bean) can keep old values, and stateful beans lose their state. Not every property can change at runtime (server port, datasource pool sizes usually need a restart). → *More:* Ch 13 — "Refreshing without restarting"

Q244. Kafka `acks=all` and `min.insync.replicas` — why do they matter? `acks=all` makes the producer wait until all in-sync replicas have the message; `min.insync.replicas=2` (with replication factor 3) means a write fails rather than being accepted by only one broker. Together they prevent losing acknowledged messages when a broker dies — trading a little latency for durability.

Q245. What is a poison message? A message that always fails processing (bad format, unexpected data). Without a limit it blocks its partition forever as the consumer retries it. Detect with a retry count, move it to a DLQ, alert, and keep the partition moving. → *More:* Ch 11 — Event-Driven, "Error handling and message durability"

Q246. Hot partition / hot key — what is it and how do you fix it? One key (a celebrity user, a popular product) receives far more traffic than others, overloading one partition or shard. Fix by salting the key (append a random suffix and aggregate later), splitting the hot entity, caching it, or handling it on a dedicated path. → *More:* Ch 1 — Partitioning and sharding

Q247. Thundering herd vs cache stampede? Both are many clients acting at the same moment. Thundering herd: many waiting clients retry or wake together after an outage. Cache stampede: a hot cache key expires and many requests hit the database at once to rebuild it. Fix with jitter, request coalescing (one rebuild, others wait) and early refresh. → *More:* Ch 8 — Retry, "What is the thundering herd problem?" · Ch 1 — Cache invalidation

Q248. What is the "fallacies of distributed computing" list? Eight false assumptions newcomers make: the network is reliable; latency is zero; bandwidth is infinite; the network is secure; topology doesn't change; there is one administrator; transport cost is zero; the network is homogeneous. Almost every pattern in this book exists because one of them is false. → *More:* Ch 1 — Faults, failures and fault tolerance

Q249. What is service granularity's effect on latency? Quick calculation. If a page needs 6 sequential calls of 20 ms each, that is 120 ms before any work — versus about 20 ms if they run in parallel or the data is local. And availability multiplies: 6 dependencies at 99.9% give about 99.4% combined. Fewer hops and parallel fan-out matter. → *More:* Ch 1 — Availability and the nines

Q250. In one minute: which patterns would you use to build a resilient microservice? Timeouts on every call; retries with exponential backoff and jitter for idempotent operations at one layer; a circuit breaker with fallbacks; bulkheads per dependency; rate limiting and load shedding at the edge; async messaging with outbox, idempotent consumers and a DLQ for state changes; health probes and graceful shutdown; multiple replicas across zones; and observability (RED metrics, traces, SLO alerts) to know when any of it is failing. → *More:* Interview Edition — framework and selection table

---

Sources of the question lists

Question wording and frequency were gathered from these public lists and posts (titles only; all answers above are written for this book):

- InterviewBit — *Microservices Interview Questions* (freshers and experienced lists) — interviewbit.com/microservices-interview-questions
- GeeksforGeeks — *Microservices Interview Questions* — geeksforgeeks.org/java/microservices-interview-questions
- devinterview-io — *microservices-interview-questions* (GitHub) — github.com/devinterview-io/microservices-interview-questions
- DataCamp — *Microservices Interview Questions* — datacamp.com/blog/microservices-interview-questions
- TechPrep — *96 Microservices Interview Questions and Answers (2026)* — techprep.app/blog/microservices-interview-questions
- Adaface — *Microservices interview questions* — adaface.com/blog/microservices-interview-questions
- Coding Shuttle — *Top 20 Microservice interview questions for Advanced Spring Boot Developers* — codingshuttle.com
- Simplilearn — *Microservices Interview Questions* — simplilearn.com/microservices-interview-questions-article
- LambdaTest (DEV Community) — *29 Top Microservice Interview Questions*
- Medium — *Microservices interview questions for Java developers (2026)*; LinkedIn posts — *Microservices scenario-based interview questions* and *Java + Spring Boot + Microservices interview questions (8+ years)*
- LeetCode Discuss — interview-experience posts for backend / Java / Spring roles (topics: saga, circuit breaker, idempotency, Kafka, system design)
- Version facts checked against spring.io release announcements (Spring Cloud 2025.1 "Oakwood", Spring Cloud Greenwich maintenance-mode notice) and Spring Framework 7 / Spring Boot 4 release notes