Chapter 5 — Spring MVC and REST APIs

Spring MVC is Spring's web framework for the classic, thread-per-request Servlet stack (one thread handles a request from start to end, waiting during I/O; the Servlet API is the standard Java web-server API, implemented by Tomcat and Jetty). Almost every Boot service exposing an HTTP/JSON API is built on it. This chapter builds a small **book catalogue API** to explain the request flow, mappings, input, validation, status codes and error bodies, content negotiation, Framework 7 API versioning, CORS (§5.10), uploads, pagination, OpenAPI docs (§5.12) and filters/interceptors (§5.11).

Code: `code/mvc-rest/` (the book API) and `code/api-versioning/` — Spring Boot 4.1.1, Framework 7.0, Java 25. All behaviour is proved with `@WebMvcTest` + `MockMvcTester` tests (only the web layer, fake requests in memory); output is real. Testing in depth is Chapter 12; the reactive alternative (WebFlux) is Chapter 13; calling other APIs is Chapter 6.

The project's single web dependency is the Boot 4 starter:

```
<!-- Spring MVC + embedded Tomcat + Jackson 3 (was spring-boot-starter-web before Boot 4) -->
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-webmvc</artifactId>
</dependency>
```

5.1 REST in one page

What it is

REST (Representational State Transfer) is an architectural style for HTTP APIs. In practice a "REST API" means:

- The API exposes **resources** (things) at **URLs**: `/api/books`, `/api/books/3`.
- Clients act on them with standard **HTTP methods**.
- Data travels as **representations** (usually JSON) whose format is agreed with headers (`Content-Type`, `Accept`). An HTTP **header** is a `Name: value` line of metadata sent before the body of a request or response.
- Each request carries everything needed to handle it (**stateless** server — it keeps no memory of earlier requests from that client).
- Results are signalled with **HTTP status codes**.

Methods

Method	Meaning	Safe? (no change)	Idempotent? (repeat = same effect)	Typical response
`GET /books`	list/search	yes	yes	`200` + body
`GET /books/3`	read one	yes	yes	`200`, or `404`
`POST /books`	create (server picks the id)	no	**no** — two POSTs create two books	`201 Created` + `Location` header
`PUT /books/3`	replace the whole resource	no	yes	`200` + body, or `204`
`PATCH /books/3`	partial update	no	not necessarily	`200` / `204`
`DELETE /books/3`	delete	no	yes	`204 No Content`, then `404`

Idempotency matters for retries: a client may safely retry a timed-out `PUT` or `DELETE`, but not a `POST` without an idempotency key (a unique id sent with the request so the server can spot and ignore a duplicate; see System Design Fundamentals) (see Chapter 6).

Status codes you will actually use

Code	Name	When
200	OK	success with a body
201	Created	a POST created something; add `Location`
204	No Content	success, nothing to return (DELETE)
400	Bad Request	malformed JSON, invalid fields, bad parameter types
401	Unauthorized	not authenticated (Chapter 10)
403	Forbidden	authenticated but not allowed; also a rejected CORS request
404	Not Found	no such resource / URL
405	Method Not Allowed	URL exists, method doesn't (response has `Allow`)
406	Not Acceptable	cannot produce any format the client accepts
409	Conflict	state conflict, e.g. duplicate or version clash
413	Content Too Large	upload too big
415	Unsupported Media Type	request body format not supported
422	Unprocessable Content	some teams use it for semantic validation errors (Spring uses 400 by default)
500	Internal Server Error	unexpected bug
503	Service Unavailable	overloaded / dependency down


5.2 How a request flows: the `DispatcherServlet`

What it is

Spring MVC is built around one servlet (a class the web server calls to handle HTTP requests), the **`DispatcherServlet`** — a **front controller**: every request enters through it, and it delegates each step to pluggable components.

Boot registers the `DispatcherServlet` at `/` automatically and starts an embedded **Tomcat 11** (Jakarta Servlet 6.1).

How it works



1. **Servlet filters** run first (security, request ids, compression). They are outside Spring MVC and don't know which controller method will run.
2. The `DispatcherServlet` asks its **`HandlerMapping`s** which handler matches. For annotated controllers, `RequestMappingHandlerMapping` compares path, HTTP method, `consumes` / `produces`, params, headers and — in Framework 7 — the **API version**.
3. **`HandlerInterceptor.preHandle`** runs for the chosen handler.
4. A **`HandlerAdapter`** invokes the method. Before that, **`HandlerMethodArgumentResolver`s** build each argument: `@PathVariable` from the URL, `@RequestParam` from the query string (the `?page=1&size=2` part of a URL), `@RequestBody` via an **`HttpMessageConverter`** (Jackson for JSON), plus validation.
5. The return value is handled by a **`HandlerMethodReturnValueHandler`**: for `@ResponseBody` / `@RestController` it picks an `HttpMessageConverter` based on the `Accept` header (content negotiation) and writes the body.
6. If anything throws, **`HandlerExceptionResolver`s** turn the exception into a response (`@ExceptionHandler` methods, `@ResponseStatus`, Spring's defaults).
7. `postHandle` / `afterCompletion` interceptor callbacks, then filters unwind.

For server-rendered HTML (Thymeleaf, a template engine that fills HTML templates with data), step 5 instead returns a view name that a `ViewResolver` renders; this book focuses on JSON APIs.

5.3 Controllers and request mappings

What it is

A **controller** is a bean whose methods handle requests. `@RestController` = `@Controller` + `@ResponseBody`: every method's return value is written straight into the response body (as JSON), not treated as a view name.

```java
@RestController                          // = @Controller + @ResponseBody on every method
@RequestMapping("/api/books")            // common path prefix for the class
public class BookController {

    private final BookRepository repo;

    public BookController(BookRepository repo) { this.repo = repo; }

    @GetMapping
    public PageResponse<Book> list(@RequestParam(defaultValue = "0") @Min(0) int page,
                                   @RequestParam(defaultValue = "2") @Min(1) @Max(50) int size,
                                   @RequestParam(required = false) String author) { ... }

    @GetMapping("/{id:\\d+}")      // regex: only digits, so "/export" never lands here
    public Book get(@PathVariable long id,
                    @RequestHeader(name = "X-Client", defaultValue = "unknown") String client) {
        return repo.findById(id).orElseThrow(() -> new BookNotFoundException(id));
    }

    @PostMapping
    public ResponseEntity<Book> create(
            @Validated({BookRequest.OnCreate.class, Default.class}) @RequestBody BookRequest request) { ... }

    @PutMapping("/{id:\\d+}")
    public Book update(@PathVariable long id, @Validated @RequestBody BookRequest request) { ... }

    @DeleteMapping("/{id:\\d+}")
    @ResponseStatus(HttpStatus.NO_CONTENT)
    public void delete(@PathVariable long id) { ... }
}
```

Mapping annotations

Annotation	Same as
`@GetMapping`	`@RequestMapping(method = GET)`
`@PostMapping` , `@PutMapping` , `@PatchMapping` , `@DeleteMapping`	the other methods
`@RequestMapping` on the class	prefix + shared settings for all methods

Useful attributes (all mapping annotations):

Attribute	Narrows the match to requests ...	Example
`path` / `value`	with this URL pattern	`"/{id}"`
`consumes`	whose `Content-Type` matches	`consumes = "application/json"`
`produces`	whose `Accept` allows this type	`produces = "text/csv"`
`params`	having / lacking a parameter	`params = "format=short"`
`headers`	having a header value	`headers = "X-Beta=true"`
`version` (Framework 7)	with a matching API version	`version = "1.1+"`

Path patterns

Spring MVC matches with `PathPattern` (the default since Framework 6 / Boot 3):

Pattern	Matches
`/books/{id}`	one segment captured as `id`
`/books/{id:\d+}`	only if the segment matches the regex (`\d+` = one or more digits; in Java source `"{id:\\d+}"`)
`/files/**`	anything below `/files/`
`/files/{*path}`	the rest of the path, captured (must be at the end)
`/books/*.csv`	`*` = any characters within one segment

Two version-specific facts:

- **Trailing slashes** no longer match by default (since Framework 6.0): `/api/books/` is *not* `/api/books`.
- When several patterns match, the **most specific** wins (fewer wildcards — `*` / `**` placeholders that match anything — or variables, longer literal text).

A real pitfall caught by the tests

The first version of this controller mapped `@GetMapping("/{id}")`. A request `GET /api/books/export` with `Accept: application/xml` could not be served by the two `/export` methods (they produce JSON and CSV only), so Spring fell back to the next matching pattern — `/{id}` with `id = "export"` — and answered **400 "Failed to convert 'id'"** instead of **406 Not Acceptable**. Constraining the variable with a regex, `/{id:\d+}`, removed the ambiguity. Use regex constraints (or distinct paths) when literal sub-paths share a level with variables.

5.4 Reading input and writing output

Method arguments

Annotation / type	Source	Notes
`@PathVariable long id`	URL segment `{id}`	type conversion is automatic; failure → 400
`@RequestParam int page`	query string / form field	`required` defaults to `true` (missing → 400 `MissingServletRequestParameterException`); `defaultValue` makes it optional; `Optional<T>` also works
`@RequestParam Map<String,String>`	all query params	
`@RequestHeader("X-Client") String c`	request header	`defaultValue`, `required` as above
`@CookieValue`	cookie (small named value the browser stores and sends back on every request)	
`@RequestBody BookRequest r`	body, via `HttpMessageConverter`	JSON → record/class with Jackson
`@RequestPart MultipartFile f`	part of a `multipart/form-data` (the body format browsers use to upload files) body	section 5.10
`@ModelAttribute` / no annotation on a class	query params / form fields bound to an object's properties	handy for search filters
`HttpServletRequest`, `Principal` (the logged-in user), `Locale` (the client's language/region), `UriComponentsBuilder`	framework-provided	

Names: with `@PathVariable long id` Spring uses the parameter name `id`. That needs the `-parameters` compiler flag, which `spring-boot-starter-parent` enables; outside Boot's parent, write `@PathVariable("id")`.

Return values

Return type	Result
any object / record / `List`	`200` + body serialised (turned into JSON text) by a message converter
`void` + `@ResponseStatus(NO_CONTENT)`	`204`, no body
`ResponseEntity<T>`	full control: status, headers, body
`ProblemDetail` / `ErrorResponse`	RFC 9457 error body (section 5.7)
`String` in a `@RestController`	written as text (`text/plain` or what `produces` says)
`CompletableFuture<T>`, `Callable<T>`, `DeferredResult<T>`, `SseEmitter`, `StreamingResponseBody`	async/streaming responses (SSE — Server-Sent Events, a one-way stream of messages from server to browser — is covered in Chapter 13)

`ResponseEntity` for 201 + `Location` — `ResponseEntity.created(uri).body(saved)`

```
@PostMapping
public ResponseEntity<Book> create(
        @Validated({BookRequest.OnCreate.class, Default.class}) @RequestBody BookRequest request) {
    Book saved = repo.save(request);
    URI location = ServletUriComponentsBuilder.fromCurrentRequest()
            .path("/{id}").buildAndExpand(saved.id()).toUri();
    return ResponseEntity.created(location).body(saved);
}
```

`ServletUriComponentsBuilder.fromCurrentRequest()` starts from the URL the client used, so the `Location` is correct behind different hosts (if you run behind a proxy — e.g. a load balancer that receives the client's request and forwards it to your app — set `server.forward-headers-strategy=framework` so `X-Forwarded-*` headers, which carry the client's original host and protocol, are honoured).

The tests

The tests use `MockMvcTester` (Framework 6.2+), the AssertJ-style front end for MockMvc: it calls the `DispatcherServlet` in-process with mock request/response objects — no network, no Tomcat.

```
@WebMvcTest                         // web slice: controllers, advice, filters, WebMvcConfigurers, Jackson
@Import(BookRepository.class)       // @Repository beans are not part of the slice, so add ours
class BookApiTest {
    @Autowired MockMvcTester mvc;

    @Test
    void createReturns201WithLocation() throws Exception {
        MvcTestResult r = mvc.post().uri("/api/books")
                .contentType(MediaType.APPLICATION_JSON)
                .content("""
                        {"title":"Release It! 2nd ed","author":"Michael T. Nygard",
                         "isbn":"9781680502398","year":2018}""")
                .exchange();
        show("POST /api/books", r);
        System.out.println("  Location = " + r.getResponse().getHeader("Location"));
        assertThat(r).hasStatus(201).hasHeader("Location", "http://localhost/api/books/6");
    }
    // list, get, update, delete tests ...
}
```

Output (all CRUD — Create, Read, Update, Delete — tests):

```
GET /api/books?page=1&size=2 -> 200 {"content":[{"id":3,"title":"Refactoring","author":"Martin
Fowler","isbn":"9780134757599","published_year":2018,"addedOn":"2026-01-15"},{"id":4,"title":"Domain-Driven
Design","author":"Eric Evans","isbn":"9780321125217","published_year":2003,"addedOn":"2026-01-
15"}],"page":1,"size":2,"totalElements":5,"totalPages":3}
GET /api/books/2 -> 200 {"id":2,"title":"Effective Java","author":"Joshua
Bloch","isbn":"9780134685991","published_year":2018,"addedOn":"2026-01-15"}
  X-Request-Id = req-15
  X-Handler    = BookController#get
POST /api/books -> 201 {"id":6,"title":"Release It! 2nd ed","author":"Michael T.
Nygard","isbn":"9781680502398","published_year":2018,"addedOn":"2026-01-15"}
  Location = http://localhost/api/books/6
PUT /api/books/1 -> 200 {"id":1,"title":"Clean Code (2nd ed)","author":"Robert C.
Martin","isbn":"9780132350884","published_year":2025,"addedOn":"2026-01-15"}
DELETE /api/books/1 -> 204
GET /api/books/1 after delete -> 404
```

(`X-Request-Id` and `X-Handler` come from the filter and interceptor in section 5.11. The number in `req-15` is a counter shared by all tests in the cached context, so it depends on test order and may differ in your run.)

Pagination

`list` returns one **page** plus the numbers a client needs to build page links:

```
public record PageResponse<T>(List<T> content, int page, int size, long totalElements, int totalPages) {}
```

- Use **zero-based** (first page is `0`) `page` and a bounded `size` (`@Max(50)`) so nobody can request a million rows.
- Return a **stable DTO** (Data Transfer Object: a simple class/record shaped for the API) like this one rather than serialising Spring Data's `Page` implementation directly — its JSON shape is not a stable API (Spring Data now warns about it and offers `@EnableSpringDataWebSupport(pageSerializationMode = VIA_DTO)`). With Spring Data you would accept a `Pageable` argument (`?page=1&size=2&sort=title,asc`) — see Chapter 8.
- For very large or fast-changing data, **keyset (cursor) pagination** (`?after=lastSeenId` — "give me the rows after the last one I saw") is faster and more stable than `OFFSET` (SQL's "skip the first N rows", which still has to read them) — see the SQL book, Indexes and query performance.

5.5 JSON with Jackson 3

What it is

Jackson is the JSON library behind Spring MVC's JSON converter. **Spring Boot 4 uses Jackson 3** by default (Boot 4.1.1 manages 3.1.x) — a new major version with new Maven coordinates, so Jackson 2 code and configuration need small changes.

What changed from Jackson 2

Topic	Jackson 2 (Boot 3)	Jackson 3 (Boot 4)
Maven group / Java package	`com.fasterxml.jackson.*`	`tools.jackson.*`
Annotations (`@JsonProperty`, `@JsonIgnore`, ...)	`com.fasterxml.jackson.annotation`	**unchanged**: still `com.fasterxml.jackson.annotation`
Java baseline	Java 8	Java 17
Main mapper	`ObjectMapper` (mutable)	`JsonMapper` (a format-specific `ObjectMapper`), **immutable**, built with `JsonMapper.builder()`
Exceptions	checked (must be declared or caught) `JsonProcessingException`	unchecked (extends `RuntimeException`) `JacksonException` (`DatabindException`, `StreamReadException`, ...)
`java.time`, `Optional`, parameter names	separate modules (`jsr310`, `jdk8`, ...)	built in
Dates	timestamps by default (Boot turned this off)	ISO strings by default (`WRITE_DATES_AS_TIMESTAMPS` disabled)
Unknown JSON properties	fail by default (Boot turned this off)	ignored by default
Property order	declaration order	alphabetical by default, but creator (constructor/record) properties first
Renamed types	`JsonSerializer`, `JsonDeserializer`, `SerializerProvider`, `Module`	`ValueSerializer`, `ValueDeserializer`, `SerializationContext`, `JacksonModule`

Spring Boot 4 changes that follow from it:

Boot 3	Boot 4
`Jackson2ObjectMapperBuilderCustomizer`	`JsonMapperBuilderCustomizer`
`@JsonComponent` , `@JsonMixin`	`@JacksonComponent` , `@JacksonMixin`
`spring.jackson.read.*` / `spring.jackson.write.*`	`spring.jackson.json.read.*` / `spring.jackson.json.write.*`
define an `ObjectMapper` bean to customise	define/customise a `JsonMapper` bean
—	deprecated `spring-boot-jackson2` module to keep Jackson 2 while migrating
`HttpMessageConverters` bean	deprecated; use `ServerHttpMessageConvertersCustomizer` / `ClientHttpMessageConvertersCustomizer`

Example

The API record uses an annotation from the unchanged annotations package:

```
import com.fasterxml.jackson.annotation.JsonProperty;
import java.time.LocalDate;

public record Book(
        Long id,
        String title,
        String author,
        String isbn,
        @JsonProperty("published_year") int year,   // rename one JSON field
        LocalDate addedOn) {
}
```

The test injects Boot's `JsonMapper`:

```
@SpringBootTest
class JacksonTest {
    @Autowired JsonMapper mapper;   // Jackson 3 (package tools.jackson), configured by Boot 4

    @Test
    void serializeAndDeserializeARecord() {
        Book b = new Book(7L, "Effective Java", "Joshua Bloch", "9780134685991", 2018, LocalDate.of(2026, 1, 15));
        String json = mapper.writeValueAsString(b);          // no checked exception in Jackson 3
        System.out.println("mapper class: " + mapper.getClass().getName());
        System.out.println("JSON: " + json);

        Book back = mapper.readValue("""
                {"id":8,"title":"T","author":"A","isbn":"1","published_year":2001,
                 "addedOn":"2026-02-01","somethingNew":true}""", Book.class);
        System.out.println("read back (unknown field ignored): " + back);
    }

    @Test
    void jacksonExceptionsAreUnchecked() {
        assertThatThrownBy(() -> mapper.readValue("{not json", Book.class))
                .isInstanceOf(JacksonException.class)
                .isInstanceOf(RuntimeException.class) ... ;
    }
}
```

Output:

```
mapper class: tools.jackson.databind.json.JsonMapper
JSON: {"id":7,"title":"Effective Java","author":"Joshua
Bloch","isbn":"9780134685991","published_year":2018,"addedOn":"2026-01-15"}
read back (unknown field ignored): Book[id=8, title=T, author=A, isbn=1, year=2001, addedOn=2026-02-01]
bad JSON -> StreamReadException (a RuntimeException: true)
```

Notice: `LocalDate` became `"2026-01-15"` with no extra module; the record kept its declaration order (record components are creator properties, which are sorted first); the unknown `somethingNew` was ignored. In the error responses later in this chapter, `ProblemDetail`'s fields *do* appear alphabetically (`detail, instance, status, title, type`) — that is Jackson 3's new default ordering for regular properties.

Customising

```
@Bean
JsonMapperBuilderCustomizer jsonCustomizer() {
    return builder -> builder.enable(SerializationFeature.INDENT_OUTPUT);   // tools.jackson.databind
}
```

or with properties, e.g. `spring.jackson.serialization.indent-output=true`, `spring.jackson.default-property-inclusion=non_null`. (`spring.jackson.json.read.*` / `json.write.*` hold the JSON-format-specific `JsonReadFeature` / `JsonWriteFeature` switches.)

Common mistakes

- Mixing Jackson 2 and 3 imports (`com.fasterxml.jackson.databind.ObjectMapper` vs `tools.jackson.databind...`): Spring MVC uses the Jackson 3 mapper, so a Jackson 2 `ObjectMapper` bean you define is simply not used for HTTP. (Some libraries, e.g. springdoc's swagger-core, still bring Jackson 2 for their own use — that is fine.)
- Exposing JPA entities directly as JSON → lazy-loading errors (related data loaded on first access, after the session closed), infinite recursion (two objects pointing at each other), leaking columns. Use DTOs/records (Chapter 8).
- Relying on field order in clients — JSON objects are unordered by definition.

5.6 Validation

What it is

Jakarta Bean Validation (the standard Java API for validation rules; Hibernate Validator is the implementation; add `spring-boot-starter-validation`) lets you declare rules as annotations on fields/record components and parameters. Spring MVC runs them before your method executes, so the controller only ever sees valid input.

```
public record BookRequest(
        @NotBlank @Size(max = 100) String title,
        @NotBlank String author,
        // required only when creating (group OnCreate); an update may leave it out
        @NotBlank(groups = OnCreate.class)
        @Pattern(regexp = "\\d{13}", message = "must be 13 digits") String isbn,
        @Min(1450) @Max(2100) int year) {

    /** Validation group marker: rules that apply only on create. */
    public interface OnCreate {}
}
```

Common constraints: `@NotNull`, `@NotBlank` (not null and not only whitespace), `@NotEmpty`, `@Size`, `@Min` / `@Max`, `@Positive`, `@Email`, `@Pattern`, `@Past` / `@Future`, `@Valid` (cascade into a nested object or list elements). Custom constraints: an annotation + a `ConstraintValidator`.

Three ways validation is triggered

Where	How to trigger	Failure exception	Default status
`@RequestBody` / `@ModelAttribute` object	`@Valid` or `@Validated` on the parameter	`MethodArgumentNotValidException`	400
Constraints directly on `@RequestParam`, `@PathVariable`, `@RequestHeader` (e.g. `@Max(50) int size`)	automatic — **built-in method validation** since Framework 6.1, no `@Validated` needed	`HandlerMethodValidationException`	400
Any Spring bean method (services)	`@Validated` on the **class** + constraints on parameters	`ConstraintViolationException` (AOP proxy, see Chapter 4)	500 unless you handle it

Do **not** put `@Validated` on the controller class in Framework 6.1+: it switches that controller to the AOP-based validation of the third row, and you get `ConstraintViolationException` instead of the web-aware exceptions.

Validation groups

A **group** is a marker interface (an empty interface used as a label) that labels constraints so different subsets can be validated in different situations. Constraints without `groups` belong to `jakarta.validation.groups.Default`. `@Valid` (Jakarta) has no groups attribute; Spring's `@Validated({...})` does:

```
@PostMapping                    // create: Default rules + OnCreate rules (isbn required)
public ResponseEntity<Book> create(
        @Validated({BookRequest.OnCreate.class, Default.class}) @RequestBody BookRequest request) { ... }

@PutMapping("/{id:\\d+}")       // update: only Default rules (isbn optional)
public Book update(@PathVariable long id, @Validated @RequestBody BookRequest request) { ... }
```

Test output (the same body without `isbn`):

```
POST without isbn -> 400 errors={"isbn":"must not be blank"}
PUT  without isbn -> 200
```

Invalid body and invalid query parameter:

```
POST invalid book -> 400 application/problem+json
   {"detail":"Request body has 3 invalid field(s)","instance":"/api/books","status":400,"title":"Bad
Request","errors":{"isbn":"must be 13 digits","title":"must not be blank","year":"must be greater than or equal to
1450"}}
GET /api/books?size=500 -> 400 application/problem+json
   {"detail":"Validation failure","instance":"/api/books","status":400,"title":"Bad Request","errors":
{"size":"must be less than or equal to 50"}}
```

The `errors` maps are added by the exception handler in the next section.

Common mistakes

- Forgetting `@Valid` / `@Validated` on `@RequestBody` → annotations on the record are ignored.
- Forgetting `@Valid` on a nested field (`@Valid Address address`) → nested object not validated.
- Missing `spring-boot-starter-validation` → no validator on the classpath, constraints silently ignored.
- `@NotNull` on a primitive `int` is pointless (never null); use `Integer` if "missing" must be detected.
- Validating only in the UI → every API must validate its own input.

5.7 Error handling and Problem Details (RFC 9457)

The problem it solves

Without a plan, errors leak as stack traces, HTML error pages, or a different JSON shape per endpoint. Clients need **one predictable error format**. **RFC 9457 "Problem Details for HTTP APIs"** (July 2023, replacing RFC 7807) defines it: media type (the format label used in `Content-Type`) `application/problem+json` with members

Member	Meaning
`type`	URI (a string that identifies a resource; URLs are one kind) identifying the problem type (default `about:blank`)
`title`	short human summary of the type
`status`	HTTP status code
`detail`	explanation of this occurrence
`instance`	URI of this occurrence (Spring fills the request path)
extensions	any extra members, e.g. `bookId`, `errors`

Spring's model: `ProblemDetail` (the body), `ErrorResponse` (an exception that carries a `ProblemDetail`; all Spring MVC exceptions implement it), `ErrorResponseException` (a base class for your own).

How it works

1. Controller code throws.
2. `ExceptionHandlerExceptionResolver` looks for an `@ExceptionHandler` for that type — first in the controller, then in **`@ControllerAdvice`** / **`@RestControllerAdvice`** beans (global handlers).
3. Otherwise `ResponseStatusExceptionResolver` (for `@ResponseStatus` or `ResponseStatusException`) and `DefaultHandlerExceptionResolver` (Spring MVC's own exceptions) set a status.
4. Anything still unhandled goes to the servlet container's (the web server, here Tomcat) error page, which Boot maps to **`/error`** → `BasicErrorController`, producing Boot's JSON (`timestamp`, `status`, `error`, `path`).

The cleanest setup: one `@RestControllerAdvice` that **extends** **`ResponseEntityExceptionHandler`**. The base class already maps every Spring MVC exception (400, 404, 405, 406, 413, 415, 500 ...) to a `ProblemDetail`; you add handlers for your own exceptions and override the hooks you want to enrich.

```java
@RestControllerAdvice
public class ApiExceptionHandler extends ResponseEntityExceptionHandler {

    @ExceptionHandler(BookNotFoundException.class)
    public ProblemDetail bookNotFound(BookNotFoundException ex) {
        ProblemDetail pd = ProblemDetail.forStatusAndDetail(HttpStatus.NOT_FOUND, ex.getMessage());
        pd.setTitle("Book not found");
        pd.setType(URI.create("https://api.example.com/problems/book-not-found"));
        pd.setProperty("bookId", ex.bookId());          // extra member in the JSON
        return pd;
    }

    // Customise the built-in 400 for @Valid/@Validated @RequestBody failures: add field errors
    @Override
    protected ResponseEntity<Object> handleMethodArgumentNotValid(
            MethodArgumentNotValidException ex, HttpHeaders headers, HttpStatusCode status, WebRequest request) {
        ProblemDetail pd = ex.getBody();                // already a ProblemDetail (status 400)
        Map<String, String> errors = new TreeMap<>();
        ex.getBindingResult().getFieldErrors()
                .forEach(fe -> errors.put(fe.getField(), fe.getDefaultMessage()));
        pd.setDetail("Request body has " + errors.size() + " invalid field(s)");
        pd.setProperty("errors", errors);
        return ResponseEntity.status(status).headers(headers).body(pd);
    }

    // Customise the built-in 400 for constraint violations on @RequestParam/@PathVariable/... (Framework 6.1+)
    @Override
    protected ResponseEntity<Object> handleHandlerMethodValidationException(
            HandlerMethodValidationException ex, HttpHeaders headers, HttpStatusCode status, WebRequest request) {
        ProblemDetail pd = ex.getBody();
        Map<String, String> errors = new TreeMap<>();
        ex.getParameterValidationResults().forEach(result -> result.getResolvableErrors().forEach(err ->
                errors.put(result.getMethodParameter().getParameterName(), err.getDefaultMessage())));
        pd.setProperty("errors", errors);
        return ResponseEntity.status(status).headers(headers).body(pd);
    }
}
```

Test output — our own exception and several framework errors, all in the same format:

```
GET /api/books/99 -> 404 application/problem+json
   {"detail":"Book 99 does not exist","instance":"/api/books/99","status":404,"title":"Book not
found","type":"https://api.example.com/problems/book-not-found","bookId":99}
GET /api/books?page=abc -> 400 application/problem+json
   {"detail":"Failed to convert 'page' with value: 'abc'","instance":"/api/books","status":400,"title":"Bad
Request"}
PATCH /api/books/1 -> 405 application/problem+json
   {"detail":"Method 'PATCH' is not supported.","instance":"/api/books/1","status":405,"title":"Method Not
Allowed"}
POST text/plain -> 415 application/problem+json
   {"detail":"Content-Type 'text/plain;charset=UTF-8' is not
supported.","instance":"/api/books","status":415,"title":"Unsupported Media Type"}
POST broken JSON -> 400 application/problem+json
   {"detail":"Failed to read request","instance":"/api/books","status":400,"title":"Bad Request"}
```

The 405 response also carries an `Allow` header listing the supported methods, and the 415 an `Accept` header listing supported body types. Note the generic `detail` for broken JSON: Spring deliberately does not echo parser internals back to clients.

Other options

Option	Use when
`spring.mvc.problemdetails.enabled=true`	you have **no** advice of your own and just want Problem Details for Spring MVC's exceptions (Boot registers a `ResponseEntityExceptionHandler` for you; default `false`)
`@ResponseStatus(HttpStatus.NOT_FOUND)` on an exception class	quick and simple, but no custom body
`throw new ResponseStatusException(HttpStatus.CONFLICT, "...")`	one-off errors without a custom class
extend `ErrorResponseException`	your exception carries its own `ProblemDetail` (status, type, extra properties)
`@ExceptionHandler` inside one controller	an error specific to that controller
`@RestControllerAdvice(basePackages = ...)` / `assignableTypes`	different handlers for different API areas

Common mistakes

- **Catching exceptions in controllers** and returning `200` with an `"error"` field — breaks HTTP semantics, caching and client retries.
- **Leaking internals** (`ex.getMessage()` from a SQL exception, stack traces) in `detail`. Log them server-side; return a safe message.
- **A generic `@ExceptionHandler(Exception.class)` returning 400** — bugs are 500s. Keep a catch-all that returns 500 and logs.
- Two advices handling the same exception without `@Order` — which wins is undefined.

In the interview

> **30-second answer:** "A single `@RestControllerAdvice` extending `ResponseEntityExceptionHandler`, so every Spring MVC exception already produces an RFC 9457 `ProblemDetail` (`application/problem+json`). I add `@ExceptionHandler`s for domain exceptions — e.g. `NotFound` → 404 with a `type` URI and extra properties — and override `handleMethodArgumentNotValid` to include field errors. Unexpected exceptions become 500s with a safe message, logged with a correlation id (an id on every log line of one request)."

- *What's RFC 9457?* → Problem Details for HTTP APIs; it obsoletes RFC 7807; fields `type`, `title`, `status`, `detail`, `instance` plus extensions.
- *Order of lookup?* → `@ExceptionHandler` in the controller, then in `@ControllerAdvice` beans, then `@ResponseStatus` / `ResponseStatusException`, then Spring defaults, finally Boot's `/error`.

5.8 Content negotiation

What it is

Content negotiation is how client and server agree on a representation. The client sends `Accept: text/csv` (what it wants back) and `Content-Type` (what it is sending). Spring matches `Accept` against each method's `produces` and the available `HttpMessageConverter`s; `Content-Type` against `consumes`.

```java
@GetMapping(value = "/export", produces = MediaType.APPLICATION_JSON_VALUE)
public List<Book> exportJson() { return repo.findAll(null); }

@GetMapping(value = "/export", produces = "text/csv")
public String exportCsv() {
    return repo.findAll(null).stream()
            .map(b -> b.id() + "," + b.title() + "," + b.year())
            .collect(Collectors.joining("\n", "id,title,year\n", "\n"));
}
```

Output:

```
Accept: text/csv -> text/csv;charset=UTF-8
   id,title,year
   1,Clean Code,2008
   2,Effective Java,2018
Accept: application/json -> application/json starts [{"id":1,"title":"Clean Code","author":"...
Accept: application/xml -> 406
```

- No `Accept` header (or `*/*`) → the first producible type wins.
- XML would need a converter: add `tools.jackson.dataformat:jackson-dataformat-xml` (Jackson 3) and Boot registers it automatically.
- Query-parameter negotiation (`?format=csv`) can be turned on with `spring.mvc.contentnegotiation.favor-parameter=true` (parameter name `format`, changeable with `spring.mvc.contentnegotiation.parameter-name`). Negotiation by path extension (`/books.json`) was deprecated in Framework 5.3 and is not available with the modern `PathPattern` matching.

5.9 API versioning (Framework 7)

What it is

API versioning lets old clients keep the old contract while new clients use a new one. Before Framework 7 every team invented its own scheme (`/v1/...` prefixes, custom header conditions); **Spring Framework 7.0 made it first-class**: a version is resolved from each request, parsed, validated, and used as one more mapping condition, with support on the client side (`RestClient`, `WebClient`, HTTP interfaces — Chapter 6) and in tests.

How it works

1. A **resolver** reads the version from the request: header, query parameter, path segment, or media-type parameter.
2. A **parser** turns it into a comparable version (default: semantic versioning `major.minor.patch` — major for breaking changes, minor for new features, patch for fixes — so `1.1` = `1.1.0`).
3. The version is **validated**: if missing and no default → 400 `MissingApiVersionException`; if not supported → 400 `InvalidApiVersionException`.
4. Mappings with a `version` attribute are matched: `"1.0"` = exactly that version; `"1.1+"` = a **baseline** — 1.1 and higher, until a more specific mapping for a higher version exists. Mappings without `version` match any version.
5. An optional **deprecation handler** adds standard `Deprecation` (RFC 9745), `Sunset` (RFC 8594) and `Link` headers to responses for deprecated versions.

Configuration

In Boot 4 via properties (or `WebMvcConfigurer.configureApiVersioning(ApiVersionConfigurer)` in plain Spring):

```
# Framework 7 API versioning, configured through Boot 4 properties
spring.mvc.apiversion.use.header=X-API-Version
spring.mvc.apiversion.default=1.0
# versions used in @GetMapping(version=...) are detected automatically; list extra ones here
spring.mvc.apiversion.supported=1.2
```

Property	Meaning
`spring.mvc.apiversion.use.header` / `.use.query-parameter` / `.use.path-segment` / `.use.media-type-parameter`	where the version comes from
`spring.mvc.apiversion.default`	version assumed when a request has none
`spring.mvc.apiversion.required`	reject requests without a version
`spring.mvc.apiversion.supported`	extra supported versions
`spring.mvc.apiversion.detect-supported`	detect supported versions from mappings

Beans of type `ApiVersionResolver`, `ApiVersionParser` and `ApiVersionDeprecationHandler` are picked up by Boot's MVC auto-configuration for full control. Our deprecation handler:

```
@Bean
ApiVersionDeprecationHandler deprecationHandler() {
    var handler = new StandardApiVersionDeprecationHandler();
    handler.configureVersion("1.0")
            .setDeprecationDate(ZonedDateTime.of(2026, 6, 1, 0, 0, 0, 0, ZoneOffset.UTC))
            .setSunsetDate(ZonedDateTime.of(2027, 1, 1, 0, 0, 0, 0, ZoneOffset.UTC))
            .setDeprecationLink(URI.create("https://api.example.com/docs/migrate-to-v2"));
    return handler;
}
```

The controller:

```
@RestController
@RequestMapping("/api/greeting")
public class GreetingController {
    public record GreetingV1(String message) {}
    public record GreetingV1_1(String message, String language) {}
    public record GreetingV2(String text, String lang) {}

    @GetMapping(version = "1.0")            // exactly version 1.0
    public GreetingV1 v1()     { return new GreetingV1("Hello"); }

    @GetMapping(version = "1.1+")           // baseline: 1.1 and every later version...
    public GreetingV1_1 v1_1() { return new GreetingV1_1("Hello", "en"); }

    @GetMapping(version = "2.0")            // ...until a more specific mapping takes over
    public GreetingV2 v2()     { return new GreetingV2("Hello", "en"); }
}
```

Output of `ApiVersioningTest`:

```
X-API-Version: none -> 200 {"message":"Hello"}
X-API-Version: 1.0  -> 200 {"message":"Hello"}
X-API-Version: 1.1  -> 200 {"message":"Hello","language":"en"}
X-API-Version: 1.2  -> 200 {"message":"Hello","language":"en"}
X-API-Version: 2.0  -> 200 {"text":"Hello","lang":"en"}
X-API-Version: 3.0  -> 400
Deprecation: @1780272000
Sunset: Fri, 1 Jan 2027 00:00:00 GMT
Link: <https://api.example.com/docs/migrate-to-v2>; rel="deprecation"; type="text/html"
```

- No header → default `1.0`. `1.2` has no exact mapping, so the `1.1+` baseline serves it (1.2 is supported because we listed it). `3.0` is unsupported → 400.
- `Deprecation: @1780272000` is the RFC 9745 format: `@` + Unix seconds (seconds since 1 Jan 1970 UTC; here 2026-06-01T00:00Z).

Trade-offs: where to put the version

Strategy	Example	Pros	Cons
Path segment	`/api/v2/books`	visible, easy to test in a browser, cache-friendly	"the same resource" has several URLs
Header	`X-API-Version: 2.0`	clean URLs	invisible in logs/links unless you add it; needs `Vary` (a header telling caches which request headers change the response) for caches
Query parameter	`?version=2.0`	easy to try	mixes with filters, easy to drop
Media type parameter	`Accept: application/json;version=2.0`	"pure" HTTP content negotiation	least discoverable, harder tooling

Whatever you choose, prefer **additive, backwards-compatible changes** (new optional fields that old clients can ignore) and bump the version only for breaking changes (changes that make existing clients fail).

5.10 CORS and file upload

CORS

What it is

Browsers enforce the **same-origin policy** (an *origin* is scheme + host + port, e.g. `https://shop.example.com`): JavaScript on `https://shop.example.com` may not read responses from `https://api.example.com` unless the API opts in with **CORS** (Cross-Origin Resource Sharing) headers. For "non-simple" requests (e.g. JSON `POST`, custom headers) the browser first sends a **preflight** `OPTIONS` request asking permission.

CORS protects **users' browsers**, not your server: `curl` and server-to-server calls ignore it. It is not authentication.

How to configure

Globally (preferred):

```
@Override
public void addCorsMappings(CorsRegistry registry) {
    registry.addMapping("/api/**")
            .allowedOrigins("https://shop.example.com")   // the browser app's origin
            .allowedMethods("GET", "POST", "PUT", "DELETE")
            .maxAge(3600);                                // preflight may be cached 1 h
}
```

or per controller/method with `@CrossOrigin(origins = "...")`. With Spring Security, also enable `http.cors(...)` so the security filter chain lets preflights through (Chapter 10).

Test output (preflights from an allowed and an unknown origin):

```
preflight from shop.example.com -> 200 Allow-Origin=https://shop.example.com Allow-Methods=GET,POST,PUT,DELETE
Max-Age=3600
preflight from evil.example.net -> 403 Allow-Origin=null
```

Common mistakes

- `allowedOrigins("*")` together with `allowCredentials(true)` — not allowed by the CORS spec (Spring rejects it); use explicit origins or `allowedOriginPatterns`.
- Configuring CORS in MVC but not in Spring Security → preflight gets 401/403 from security first.

File upload

Multipart (`multipart/form-data`) requests carry files plus form fields. Boot configures multipart support; limits:

```
spring.servlet.multipart.max-file-size=1MB       # default 1MB
spring.servlet.multipart.max-request-size=2MB    # default 10MB
```

```
@PostMapping("/api/uploads")
public UploadResult upload(@RequestPart("file") MultipartFile file,
                           @RequestParam(defaultValue = "") String note) throws IOException {
    String text = new String(file.getBytes(), StandardCharsets.UTF_8);
    return new UploadResult(file.getOriginalFilename(), file.getSize(),
            file.getContentType(), (int) text.lines().count(), note);
}
```

Output:

```
POST /api/uploads -> 200 {"fileName":"books.csv","bytes":36,"contentType":"text/csv","lines":3,"note":"weekly import"}
```

- Exceeding the limit in a running server raises `MaxUploadSizeExceededException`, which `ResponseEntityExceptionHandler` maps to **413**. (MockMvc does not parse real multipart streams, so the limit is not exercised by this test.)
- **Security:** never trust `getOriginalFilename()` as a path (path traversal: `../../etc/passwd`); generate your own storage names, check type and size, and stream large files (`file.getInputStream()` / `transferTo`) rather than loading them into memory. Large files usually go straight to object storage (a file store such as Amazon S3) via pre-signed URLs (temporary upload links signed by your server) instead of through your API.

5.11 Filters vs interceptors (vs AOP)

What it is

Three places to put code that runs around requests:

	Servlet `Filter`	Spring MVC `HandlerInterceptor`	AOP aspect (Ch. 4)
Runs	before/after the `DispatcherServlet`, for every request (also static files, errors)	inside the `DispatcherServlet`, only for requests mapped to a handler	around bean method calls
Knows the controller method?	no	yes (`HandlerMethod`)	yes (join point)
Can wrap/replace request & response objects	yes	no	no
Typical use	security (Spring Security is a filter chain), request ids/MDC (Mapped Diagnostic Context: per-thread values added to every log line), compression, CORS	per-endpoint auth checks, locale, audit, timing by handler	business-level cross-cutting concerns
Register	`@Component` implementing `Filter` (often `OncePerRequestFilter`) or `FilterRegistrationBean`	`WebMvcConfigurer.addInterceptors`	`@Aspect` `@Component`

The chapter's filter adds a correlation id to every response:

```
@Component
@Order(Ordered.HIGHEST_PRECEDENCE)
public class RequestIdFilter extends OncePerRequestFilter {
    private final AtomicLong counter = new AtomicLong();

    @Override
    protected void doFilterInternal(HttpServletRequest req, HttpServletResponse res, FilterChain chain)
            throws ServletException, IOException {
        String id = req.getHeader("X-Request-Id");
        if (id == null) id = "req-" + counter.incrementAndGet();
        res.setHeader("X-Request-Id", id);   // echo it so clients and logs can correlate
        chain.doFilter(req, res);            // continue to the next filter / the DispatcherServlet
    }
}
```

The interceptor records which controller method was chosen — something a filter cannot know:

```
public class HandlerNameInterceptor implements HandlerInterceptor {
    @Override
    public boolean preHandle(HttpServletRequest req, HttpServletResponse res, Object handler) {
        if (handler instanceof HandlerMethod hm) {
            res.setHeader("X-Handler", hm.getBeanType().getSimpleName() + "#" + hm.getMethod().getName());
        }
        return true;                         // false would stop the request here
    }
}
```

registered with `registry.addInterceptor(new HandlerNameInterceptor()).addPathPatterns("/api/**")`. The earlier output showed both headers: `X-Request-Id = req-15`, `X-Handler = BookController#get`.

Interceptor callbacks: `preHandle` (before the method; return `false` to stop), `postHandle` (after the method, **before** the response is written for views — for `@ResponseBody` methods the body is already written, so headers added here are too late), `afterCompletion` (always, even on exceptions — use for cleanup/metrics).

`@WebMvcTest` includes `Filter` beans, `WebMvcConfigurer`s and interceptors, which is why the tests see both headers.

5.12 Documenting the API: OpenAPI with springdoc

What it is

OpenAPI (formerly Swagger) is a machine-readable description of an HTTP API: paths, parameters, bodies, responses. Tools generate client SDKs (ready-made client libraries), contract tests (tests that check the real service matches the published description) and interactive docs from it. **springdoc-openapi** generates the document from your Spring MVC controllers at runtime. Its **3.x** line targets **Spring Boot 4** (2.x is for Boot 3); this project uses 3.1.1.

```
<dependency>
  <groupId>org.springdoc</groupId>
  <artifactId>springdoc-openapi-starter-webmvc-api</artifactId>   <!-- -ui adds Swagger UI -->
  <version>3.1.1</version>
</dependency>
```

- `/v3/api-docs` serves the JSON document (`/v3/api-docs.yaml` for YAML).
- With `springdoc-openapi-starter-webmvc-ui`, Swagger UI appears at `/swagger-ui.html`.
- It reads your mappings, parameter annotations and Bean Validation constraints (`@Max(50)` becomes `maximum: 50`). Add detail with `io.swagger.v3.oas.annotations` (`@Operation`, `@ApiResponse`, `@Schema`).

The test fetches the document:

```
@SpringBootTest                 // full context: springdoc is not part of the @WebMvcTest slice
@AutoConfigureMockMvc           // Boot 4: @SpringBootTest no longer adds MockMvc on its own
class OpenApiTest { ... mvc.get().uri("/v3/api-docs") ... }
```

Output:

```
openapi: 3.1.0
  /api/books/{id} [get, put, delete]
  /api/uploads [post]
  /api/books [get, post]
  /api/books/export [get]
```

springdoc logs a warning that `/v3/api-docs` is enabled by default — in production either secure it or set `springdoc.api-docs.enabled=false` (and `springdoc.swagger-ui.enabled=false`).

Code-first vs design-first: springdoc is *code-first* (document generated from code). Many API-platform teams go *design-first*: write the OpenAPI file, review it, then generate server interfaces/clients with `openapi-generator`. Both are fine; the key is that the published spec is tested against the real service.

HATEOAS in brief

HATEOAS (Hypermedia as the Engine of Application State) means responses include **links** to related actions (`"_links": {"self": ..., "next": ...}`), so clients navigate the API like a website instead of hard-coding URLs. **Spring HATEOAS** (`spring-boot-starter-hateoas`) provides `EntityModel`, `CollectionModel`, `PagedModel` and `linkTo(methodOn(...))` builders, rendering HAL JSON (a common JSON convention for embedding links). It is valuable for long-lived public APIs; most internal JSON APIs skip it and rely on OpenAPI documentation instead.

5.13 Putting it together: design checklist and mistakes

Area	Do
URLs	plural nouns (`/books` , `/books/{id}`), no verbs; nested only for true ownership (`/orders/{id}/items`)
Methods & codes	follow section 5.1; `201 + Location` on create, `204` on delete
DTOs	separate request/response records; never expose entities
Validation	Bean Validation on every input; groups for create vs update
Errors	one `@RestControllerAdvice` , RFC 9457 `ProblemDetail` , no internals
Lists	always paginate, cap `size` , stable JSON shape
Versioning	pick one strategy; Framework 7 `version` attribute; deprecate with headers
Security	authentication/authorization (Ch. 10), CORS explicit origins, upload limits
Docs	OpenAPI published and tested
Observability (logs, metrics, traces)	request id filter, metrics per endpoint (Ch. 15)
Threads	Spring MVC is thread-per-request; with `spring.threads.virtual.enabled=true` Tomcat uses virtual threads (cheap JVM-managed threads), giving high concurrency without reactive code (Ch. 13)

Functional endpoints. Besides annotated controllers, Spring MVC offers `RouterFunction` / `HandlerFunction` ("WebMvc.fn"): routes are declared as code (`route().GET("/api/books/{id}", handler::get).build()`). Same `DispatcherServlet` , same converters; choose it if you prefer explicit routing over annotations. It also supports API versioning.

5.14 In the interview

Q: Walk me through what happens when a request hits a Spring MVC app. Filters → `DispatcherServlet` → `HandlerMapping` finds the controller method (path, method, consumes/produces, version) → interceptors' `preHandle` → `HandlerAdapter` resolves arguments (message converters for bodies, conversion, validation) → method runs → return value written by a message converter chosen by `Accept` → exceptions go to `HandlerExceptionResolver` s (`@ExceptionHandler` /advice) → `afterCompletion` → filters.

- *Filter vs interceptor?* → Filter: servlet level, every request, can wrap request/response, doesn't know the handler. Interceptor: MVC level, knows the `HandlerMethod` , only mapped requests.
- *`@Controller` vs `@RestController` ?* → The latter adds `@ResponseBody` .

Q: How do you validate input and report errors? → Bean Validation annotations on DTOs + `@Valid` / `@Validated` (groups via `@Validated`); constraints on parameters are validated automatically since 6.1; a global `@RestControllerAdvice` extending `ResponseEntityExceptionHandler` returns RFC 9457 `ProblemDetail` s with field errors.

Q: PUT vs PATCH vs POST? Which are idempotent? → POST creates (not idempotent); PUT replaces (idempotent); PATCH partially updates (not necessarily idempotent); GET/DELETE idempotent.

Q: How would you version an API in Spring Boot 4? → Framework 7 API versioning: configure a resolver (`spring.mvc.apiversion.use.header=X-API-Version` or path segment), set default/supported versions, use `@GetMapping(version = "1.1+")` baselines, add a deprecation handler that sends `Deprecation` / `Sunset` / `Link` headers; clients use `ApiVersionInserter` .

Q: What changed with JSON in Boot 4? → Jackson 3: `tools.jackson` packages (annotations unchanged), immutable `JsonMapper` , unchecked exceptions, java.time built in, ISO dates by default; Boot's customizer is `JsonMapperBuilderCustomizer` , `@JsonComponent` → `@JacksonComponent` , JSON read/write properties moved under `spring.jackson.json.*` .

Q: What is CORS and does it secure my API? → A browser mechanism that lets a page from one origin read responses from another if the server allows it via headers and preflight. It doesn't secure the API against non-browser clients — you still need authentication and authorization.

5.15 Chapter TL;DR

- `spring-boot-starter-webmvc` (Boot 4 name) gives Spring MVC on embedded Tomcat with Jackson 3.
- Request flow: **filters** → `DispatcherServlet` → **HandlerMapping** → **interceptors** → **argument resolution (converters + validation)** → **controller** → **message converter (by `Accept`)** → **exception resolvers**.
- `@RestController` + `@GetMapping/@PostMapping/...`; `@PathVariable`, `@RequestParam`, `@RequestHeader`, `@RequestBody`; `ResponseEntity.created(uri)` for 201; `@ResponseStatus(NO_CONTENT)` for 204. Constrain path variables (`{id:\d+}`) to avoid ambiguous matches.
- **Jackson 3**: `tools.jackson.*`, annotations unchanged, immutable `JsonMapper`, unchecked `JacksonException`, java.time built in.
- **Validation**: `@Valid` / `@Validated` on bodies (groups via `@Validated`), parameter constraints validated automatically (6.1+), don't put `@Validated` on controllers.
- **Errors**: one `@RestControllerAdvice extends ResponseEntityExceptionHandler`, returning **RFC 9457** `ProblemDetail` (`application/problem+json`).
- **Content negotiation** via `Accept` + `produces`; 406 if impossible. Paginate with a bounded `size` and a stable DTO.
- **API versioning** (Framework 7): `spring.mvc.apiversion.*`, `version = "1.0"` / `"1.1+"`, 400 for unsupported versions, `Deprecation` / `Sunset` headers.
- **CORS** in `addCorsMappings` (+ Spring Security); **uploads** with `MultipartFile` and size limits; **filters** vs **interceptors**; **springdoc 3.x** for OpenAPI on Boot 4.
- Next: Chapter 6 — REST clients and HTTP interfaces.