Chapter 11 — Spring Security 2: Tokens and OAuth2

Chapter 10 authenticated people with a password and a session cookie — fine for one browser and one server. Modern systems add a mobile app, a **single-page app** (SPA: loads one page, then updates it with JavaScript), many **microservices** (small, separately deployed services forming one system), partner backends, and an **identity provider** (IdP: the system owning user accounts and checking logins — Keycloak, Okta, Entra ID, Google). They must prove identity **without sharing passwords or sessions**: with **tokens**, handed out via **OAuth 2.0** with **OpenID Connect** on top. Signing keys are generated locally, so **no external IdP is needed** to run anything.

All code lives in `code/` — three Spring Boot **4.1.1** projects plus one plain-JDK project (Spring Security **7.1.1**, Java 25). Output blocks are real `mvn -q -B -ntp verify` output (log lines trimmed as `...`; timestamps and random values change per run).

Project	Shows
`jwt-resource-server`	local RSA key, `/token` endpoint with `NimbusJwtEncoder`, a JWT-protected API, every validation failure, `jwt()` tests
`resource-server-variants`	opaque tokens with an introspector, multi-tenant JWTs (two issuers, two keys)
`oauth2-login-client`	OAuth2/OIDC login configuration. The redirect to the provider, `state` / `nonce` /PKCE, and `oidcLogin()` tests
`crypto-basics`	plain JDK: Base64 vs SHA-256 vs AES-GCM vs Ed25519 signatures, an X25519 key exchange, and TOTP checked against the RFC 6238 test vectors (§11.18)

Prerequisites. Filter chain, 401 vs 403, authorities, CSRF: Chapter 10. Browser storage, cookies and XSS: JavaScript handbook Chapter 14. Gateways and BFFs as patterns: API Gateway, Backend for Frontend.

11.1 From sessions to tokens: bearer tokens and JWT

What it is

A **bearer token** grants access to whoever *bears* (holds) it, like a cinema ticket: the server checks only that the ticket is valid. It travels in an HTTP header:

```
GET /api/messages HTTP/1.1
Authorization: Bearer eyJraWQiOiJkZW1vLWtleS0xIiwidH...
```

A **JWT (JSON Web Token, RFC 7519)** is the most common format (an RFC is a numbered internet-standard document): three **Base64URL**-encoded parts (URL-safe, reversible by anyone) joined by dots, `header.payload.signature`. A token from our `/token` endpoint, decoded:

```
token (3 base64url parts) : eyJraWQiOiJkZW1vLWtleS0xIiwidH... length=670
header  : {"kid":"demo-key-1","typ":"JWT","alg":"RS256"}
payload : {"sub":"bob","aud":"notes-api","scope":"messages.read messages.write","roles":
["ADMIN"],"iss":"https://auth.demo.test","exp":<epoch>,"iat":<epoch>,"jti":"<uuid>"}
```

Part	Contains	Notes
Header	`alg` (signature algorithm), `kid` (key id), `typ`	tells the receiver *how* to verify
Payload	**claims**: statements about the subject	readable by anyone, since it is only encoded, not encrypted
Signature	signature over `header.payload`	proves who issued it and that nothing changed

The registered claims you will meet everywhere:

Claim	Meaning	Checked by Spring by default?
`iss` (issuer)	who created the token	yes, if you configure an issuer
`sub` (subject)	who the token is about (user or client id)	becomes `Authentication#getName()`
`aud` (audience)	which API(s) the token is meant for	no, you add it (property `audiences` or a validator)
`exp` / `nbf` / `iat`	expires at / not before / issued at (epoch seconds: since 1 Jan 1970 UTC)	`exp` and `nbf` yes, with 60 s clock skew (allowed gap between server clocks)
`jti`	unique token id	no, useful for revocation lists
`scope` / `scp`	granted OAuth scopes (space-separated string or list)	mapped to `SCOPE_x` authorities

Signing: symmetric vs asymmetric

	HMAC (`HS256` , a hash keyed with a shared secret)	RSA / EC (`RS256` , `ES256` , `PS256` ; public-key algorithms, EC = elliptic curve)
Keys	one shared secret signs *and* verifies	the **private** key signs, the **public** key verifies
Who can mint tokens	everybody who can verify	only the key owner
Fits	one service issuing tokens to itself	an identity provider and many APIs (the normal case)

Resource servers download the issuer's public keys as a **JWK Set** (JSON Web Key Set, JWKS) from a URL such as `https://idp.example.com/.well-known/jwks.json`; the header's `kid` names the key, which is how keys **rotate** (§11.13).

JWS vs JWE. A signed JWT is a **JWS** (JSON Web Signature); an *encrypted* JWT is a **JWE**, rare in APIs. Never put secrets or personal data you would not show the user into a normal JWT — any holder can decode the payload; the signature protects integrity, not confidentiality.

Why tokens

- **No server-side session.** Any instance verifies the signature locally, so APIs **scale horizontally** without a shared session store.
- **Many parties.** The IdP issues, APIs only verify and never see passwords.
- **Delegation.** A token carries *limited* rights (scopes), e.g. "read calendar" but not "delete account".

Trade-offs

- **Revocation is hard.** A self-contained JWT stays valid until `exp`, even after logout or a password change. Keep access tokens short-lived (minutes) with refresh tokens (§11.11), or use **opaque tokens** (§11.7).
- **Size.** Our small token is 670 bytes, sent on every request.

- **Theft = access.** Always HTTPS (System Design Fundamentals), short lifetimes, safe storage (§11.12).

TL;DR

A JWT is `header.payload.signature`: claims readable, signature proves origin and integrity. Use asymmetric keys (APIs hold only the public key, so a compromised API cannot mint tokens), short lifetimes, and verify `exp`, `iss` and `aud`.

11.2 OAuth 2.0 and OpenID Connect in one picture

What it is

OAuth 2.0 (RFC 6749) is a framework for **delegated authorization**: letting an application act on a user's behalf *without receiving the user's password*. Like a hotel key card: reception (authorization server) checks your passport once and issues a card (access token) opening *your* room (scopes) until checkout (expiry); doors (APIs) only check the card.

OpenID Connect (OIDC) is a thin layer on top of OAuth 2.0 that adds **authentication**: an **ID token** (always a JWT) telling the client *who logged in*, a standard `userinfo` endpoint, and discovery metadata at `/.well-known/openid-configuration`.

OAuth role	Who it is	Spring module
Resource owner	the user	—
Client	the app that wants access (web app, SPA backend, mobile app, service)	`spring-security-oauth2-client` (`oauth2Login`, `oauth2Client`)
Authorization server (identity provider, IdP)	issues tokens: Keycloak, Okta, Entra ID, Auth0, Google, Spring Authorization Server	`spring-security-oauth2-authorization-server` (§11.14)
Resource server	the API that accepts tokens	`spring-security-oauth2-resource-server` (`oauth2ResourceServer`)

The tokens

Token	For whom	Format	Lifetime
Access token	the resource server (API)	JWT or opaque	short: 5–60 minutes
Refresh token	the authorization server only, to get new access tokens	usually opaque	hours to weeks, and can be revoked
ID token (OIDC)	the client, to learn who logged in	always a JWT	short, used once at login

Never send an ID token to an API as an access token, nor use an access token to "log a user in" to the client — different audiences.

Grant types (how a client gets a token)

Grant	Used by	Status
Authorization code + PKCE	any app with a user: server web apps, SPAs (via BFF), mobile	the standard (§11.9)
Client credentials	service-to-service, no user involved	standard (§11.10)
Refresh token	a client renewing an access token	standard (§11.11)
Device code (RFC 8628)	TVs, CLIs without a browser	standard
Token exchange (RFC 8693)	a service swapping a token for one aimed at another API	growing
Implicit	old SPAs (token in the URL fragment)	**deprecated**, left out of OAuth 2.1
Resource owner password	app collects the user's password	**deprecated**. Spring Security 7 **removed** its client support

The **OAuth 2.1** draft consolidates these best practices: PKCE for every authorization-code client, no implicit and no password grant, exact redirect-URI matching.

Scopes vs roles

A **scope** (`messages.read`) limits what *the client* may do on the user's behalf (the user consented to it); a **role** is what *the user* may do in your system. A token can carry both; Spring maps scopes to `SCOPE_x` authorities by default (§11.5).

TL;DR

OAuth 2.0 = delegated authorization with access tokens. OIDC adds login with ID tokens. Use authorization code + PKCE for users and client credentials for services. Implicit and password grants are obsolete.

11.3 A JWT resource server in Spring

What it is

A **resource server** is an API that accepts access tokens. With `spring-boot-starter-security-oauth2-resource-server` (Boot 4's name; the old `spring-boot-starter-oauth2-resource-server` is deprecated), one DSL call adds a `BearerTokenAuthenticationFilter` to the filter chain:

```
http.oauth2ResourceServer(rs -> rs.jwt(Customizer.withDefaults()));
```

With a real identity provider, one property is usually all you need:

```
# Spring reads https://idp.example.com/.well-known/openid-configuration (or oauth-authorization-server)
# to find the JWK Set URL, and validates that iss equals this value
spring.security.oauth2.resourceserver.jwt.issuer-uri=https://idp.example.com/realms/demo
# optional extras
spring.security.oauth2.resourceserver.jwt.audiences=notes-api
spring.security.oauth2.resourceserver.jwt.jws-algorithms=RS256
# alternatives: jwk-set-uri=... (no discovery) or public-key-location=classpath:key.pub (static key)
```

Without an IdP, we declare the `JwtDecoder` bean ourselves with a locally generated RSA key pair. A `JwtDecoder` bean always takes precedence over the properties.


```java
@Bean
KeyPair signingKeys() throws Exception {                        // demo only: new keys at each start
    KeyPairGenerator gen = KeyPairGenerator.getInstance("RSA");
    gen.initialize(2048);
    return gen.generateKeyPair();
}

@Bean
JwtDecoder jwtDecoder(KeyPair keys, @Value("${demo.jwt.issuer}") String issuer,
                      @Value("${demo.jwt.audience}") String audience) {
    NimbusJwtDecoder decoder = NimbusJwtDecoder.withPublicKey((RSAPublicKey) keys.getPublic()).build();
    OAuth2TokenValidator<Jwt> audienceCheck =
            new JwtClaimValidator<List<String>>("aud", aud -> aud != null && aud.contains(audience));
    decoder.setJwtValidator(new DelegatingOAuth2TokenValidator<>(
            JwtValidators.createDefaultWithIssuer(issuer), audienceCheck));
    return decoder;
}
```

The API chain:

```java
@Bean @Order(2)
SecurityFilterChain api(HttpSecurity http, JwtAuthenticationConverter converter) throws Exception {
    http.authorizeHttpRequests(a -> a
            .requestMatchers(HttpMethod.GET, "/api/messages").hasAuthority("SCOPE_messages.read")
            .requestMatchers(HttpMethod.POST, "/api/messages").hasAuthority("SCOPE_messages.write")
            .requestMatchers("/api/admin/**").hasRole("ADMIN")
            .anyRequest().authenticated())
        .oauth2ResourceServer(rs -> rs.jwt(jwt -> jwt.jwtAuthenticationConverter(converter)))
        .csrf(c -> c.disable())                // no cookies -> no CSRF risk
        .sessionManagement(s -> s.sessionCreationPolicy(SessionCreationPolicy.STATELESS));
    return http.build();
}
```

How it works



1. `BearerTokenAuthenticationFilter` takes the token from `Authorization: Bearer ...` (form parameters and query strings are off by default — tokens in URLs leak into logs).
2. `JwtAuthenticationProvider` calls the **`JwtDecoder`** : Nimbus (the JWT library underneath) parses it, rejects algorithms not configured (the classic `alg: none` trick fails here), and **verifies the signature**.
3. **Validators** run: `JwtTimestampValidator` (`exp` / `nbf` , 60 s skew), the issuer validator if configured, your own (audience), and in Spring Security 7 a `JwtTypeValidator` accepting `typ` = `JWT` or none (now in all `JwtValidators.createDefault...()`).

4. A `JwtAuthenticationConverter` maps claims to authorities (§11.5) and builds a `JwtAuthenticationToken`; controllers can take `@AuthenticationPrincipal Jwt jwt`.
5. Any failure → **401** with `WWW-Authenticate: Bearer error="invalid_token"` (RFC 6750). Valid token without the needed authority → **403** `error="insufficient_scope"`.

Proved: status codes with real tokens

Nothing is mocked: the test obtains real tokens from `/token` and calls the API:

```
no token                            401 WWW-Authenticate: Bearer resource_metadata="http://localhost/.well-known/oauth-protected-resource"
alice GET (messages.read)           200 ["welcome"]
alice POST (needs messages.write)   403 WWW-Authenticate: Bearer error="insufficient_scope", error_description="The request requires higher privileges than provided by the access token.", error_uri="https://tools.ietf.org/html/rfc6750#section-3.1"
bob POST                            201 added by bob
bob GET admin (roles=[ADMIN])       200 audit log for bob
garbage token                       401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: Malformed token", error_uri="https://tools.ietf.org/html/rfc6750#section-3.1", resource_metadata="http://localhost/.well-known/oauth-protected-resource"
```

`resource_metadata` points to the **OAuth 2.0 Protected Resource Metadata** document (RFC 9728) the resource server publishes, so a client knowing nothing about the API can discover which authorization server to ask:

```
GET /.well-known/oauth-protected-resource -> 200 {"resource":"http://localhost","bearer_methods_supported":["header"],"tls_client_certificate_bound_access_tokens":true}
```

With a real issuer it also lists `authorization_servers`; customise via `oauth2ResourceServer(rs -> rs.protectedResourceMetadata(...))`. The Model Context Protocol (MCP: how AI assistants call external tools) authorization spec relies on this discovery.

Proved: every validation rule

The test mints tokens with deliberate defects:

```
String expiredLongAgo = mint(encoder, c -> c.issuedAt(now.minusSeconds(3600)).expiresAt(now.minusSeconds(600)));
String expiredJustNow = mint(encoder, c -> c.issuedAt(now.minusSeconds(600)).expiresAt(now.minusSeconds(30)));
String wrongIssuer    = mint(encoder, c -> c.issuer("https://evil.test"));
String wrongAudience  = mint(encoder, c -> c.audience(List.of("billing-api")));
String otherKey       = mint(attacker, c -> {});              // attacker's own RSA key pair
// valid token, payload swapped for one with more scopes, original signature kept
String tampered = parts[0] + "." + forgedPayload + "." + parts[2];
```

Output (the `error_uri` and `resource_metadata` parameters are trimmed as `...`):

```
valid                               200 ["welcome","hi"]
expired 10 min ago                  401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: Jwt expired at 2026-09-28T23:19:21Z", ...
expired 30 s ago (clock skew 60 s) 200 ["welcome","hi"]
wrong issuer                        401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: The iss claim is not valid", ...
wrong audience                      401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: The aud claim is not valid", ...
signed with another key             401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: Signed JWT rejected: Invalid signature", ...
payload edited after signing        401 WWW-Authenticate: Bearer error="invalid_token", error_description="An error occurred while attempting to decode the Jwt: Signed JWT rejected: Invalid signature", ...
```

- A token that expired **30 s ago still passes** — 60 s clock skew. Remember this when testing expiry.
- **Changing one payload character breaks the signature** — why readable claims can be trusted.
- **Audience matters.** A `billing-api` token from the *same* trusted issuer is refused; without an audience check, every API would accept any token from your IdP.

Common mistakes

- **Skipping the audience check** — set `spring.security.oauth2.resourceserver.jwt.audiences` or add a validator.
- **Replacing** the validators: `decoder.setJwtValidator(audienceCheck)` alone drops the expiry check! Combine with `JwtValidators.createDefault...()`.
- Session-based policy (`IF_REQUIRED`) on the resource server, so a session cookie becomes a second way in. Use `STATELESS` and disable CSRF only on the token chain.
- Logging full tokens — log `jti` or `sub`.

TL;DR

`oauth2ResourceServer(jwt)` + `issuer-uri` (or your own `JwtDecoder`). Spring verifies the signature, `exp` / `nbf` (60 s skew), `iss`, `typ`, and your `aud` rule. Bad or missing token → 401 `invalid_token`. Missing authority → 403 `insufficient_scope`.

11.4 Minting tokens with `NimbusJwtEncoder`

What it is

`JwtEncoder` signs claims into a JWT. Spring Security 7 added builder methods to **`NimbusJwtEncoder`**, so creating one from a key pair or secret is a one-liner (previously a hand-built Nimbus `JWKSource`):

```
@Bean
JwtEncoder jwtEncoder(KeyPair keys) {
    return NimbusJwtEncoder.withKeyPair((RSAPublicKey) keys.getPublic(), (RSAPrivateKey) keys.getPrivate())
            .jwkPostProcessor(jwk -> jwk.keyID("demo-key-1"))   // becomes "kid" in the header
            .build();
}
// also: withKeyPair(ECPublicKey, ECPrivateKey) for ES256, withSecretKey(SecretKey) for HS256
```

Our `/token` endpoint (HTTP Basic, its own chain `@Order(1)`) turns the user's authorities into claims:

```
@PostMapping("/token")
TokenResponse token(Authentication auth) {
    Instant now = Instant.now();
    Duration ttl = Duration.ofMinutes(15);
    List<String> authorities = auth.getAuthorities().stream().map(GrantedAuthority::getAuthority)
            .filter(a -> !a.startsWith("FACTOR_")).toList();          // drop Security 7 MFA factors
    String scope = String.join(" ", authorities.stream().filter(a -> !a.startsWith("ROLE_")).toList());
    List<String> roles = authorities.stream().filter(a -> a.startsWith("ROLE_")).map(a ->
a.substring(5)).toList();
    JwtClaimsSet claims = JwtClaimsSet.builder()
            .issuer(issuer).audience(List.of(audience)).subject(auth.getName())
            .issuedAt(now).expiresAt(now.plus(ttl)).id(UUID.randomUUID().toString())
            .claim("scope", scope).claim("roles", roles)
            .build();
    JwsHeader header = JwsHeader.with(SignatureAlgorithm.RS256).type("JWT").build();
    String jwt = encoder.encode(JwtEncoderParameters.from(header, claims)).getTokenValue();
    return new TokenResponse(jwt, "Bearer", ttl.toSeconds());
}
```

The `FACTOR_` filter drops Spring Security 7's `FACTOR_PASSWORD` (10.4): it says *how* the user logged in and doesn't belong in a scope.

When to issue your own tokens — and when not

Situation	Self-issued JWT (JwtEncoder)	Real authorization server
tests, demos, this book	ideal: no infrastructure	overkill
one internal service issuing short tokens to its own clients	acceptable	better long-term
users from several apps, SSO (single sign-on), social login, MFA, consent, refresh-token rotation, revocation	**no**, you would be re-writing an IdP (password storage, lockout, key rotation, revocation — forever)	**yes**: Keycloak, a cloud IdP, or Spring Authorization Server (§11.14)

TL;DR

`NimbusJwtEncoder.withKeyPair(...)` / `withSecretKey(...)` + `JwtClaimsSet` + `JwsHeader` = a signed token in a few lines. Tests and demos yes; real users need an authorization server.

11.5 Mapping claims to authorities

What it is

Authorization rules need **authorities**. By default `JwtAuthenticationConverter` uses `JwtGrantedAuthoritiesConverter`: reads `scope` (or `scp`), splits on spaces, prefixes `SCOPE_` (`"messages.read messages.write"` → `SCOPE_messages.read`, `SCOPE_messages.write`). Nothing else becomes an authority unless you say so.

IdPs put roles in different places (Keycloak `realm_access.roles`, Entra ID `roles`, Okta `groups`). Our token has `roles`, so the project combines two converters:

```
public class ScopeAndRoleAuthorities implements Converter<Jwt, Collection<GrantedAuthority>> {
    private final JwtGrantedAuthoritiesConverter scopes = new JwtGrantedAuthoritiesConverter(); // scope/scp -> SCOPE_
    private final JwtGrantedAuthoritiesConverter roles = new JwtGrantedAuthoritiesConverter();

    public ScopeAndRoleAuthorities() {
        roles.setAuthoritiesClaimName("roles");
        roles.setAuthorityPrefix("ROLE_");
    }

    @Override
    public Collection<GrantedAuthority> convert(Jwt jwt) {
        Collection<GrantedAuthority> all = new ArrayList<>(scopes.convert(jwt));
        all.addAll(roles.convert(jwt));
        return all;
    }
}

@Bean
JwtAuthenticationConverter jwtAuthenticationConverter(ScopeAndRoleAuthorities authorities) {
    JwtAuthenticationConverter converter = new JwtAuthenticationConverter();
    converter.setJwtGrantedAuthoritiesConverter(authorities);
    converter.setPrincipalClaimName("sub");                // Authentication#getName() = sub claim
    return converter;
}
```

So `roles: ["ADMIN"]` became `ROLE_ADMIN` and `bob GET admin` returned 200. If one claim is enough, Boot properties configure the default converter without code:

```
spring.security.oauth2.resourceserver.jwt.authorities-claim-name=roles
spring.security.oauth2.resourceserver.jwt.authority-prefix=ROLE_
spring.security.oauth2.resourceserver.jwt.principal-claim-name=preferred_username
```

Common mistakes

- `hasRole("messages.read")` / `hasAuthority("messages.read")` for a scope — the authority is `SCOPE_messages.read`.
- Nested claims (`realm_access.roles`): `JwtGrantedAuthoritiesConverter` reads top-level claims only — write a converter walking the map.
- `sub` for display: often an opaque id. Show `preferred_username` or `email`, but key data by `sub` (+ `iss`).

TL;DR

Default: `scope` → `SCOPE_x`. Anything else (roles, groups) needs a custom converter or the Boot `authorities-claim-name` / `authority-prefix` properties.

11.6 Testing token security

Two ways to test

Approach	How	Proves
Real tokens	mint with `JwtEncoder` (or call `/token`), send `Authorization: Bearer ...`	decoder, validators, converter *and* rules. Everything in §11.3 was tested this way
`jwt()` post-processor	`mvc.get().uri(..).with(jwt()...)`	only the **rules**: decoding and validation are skipped, a ready-made `JwtAuthenticationToken` is placed in the context

Use real tokens for a handful of decoder tests (issuer, audience, expiry), `jwt()` for the many rule tests (faster, no keys).

The `jwt()` pitfall — proved

```
var plain = mvc.get().uri("/api/messages").with(jwt());                  // sub=user, scope=read
var explicit = mvc.post().uri("/api/messages").contentType(MediaType.TEXT_PLAIN).content("x")
        .with(jwt().jwt(j -> j.subject("carol")).authorities(new SimpleGrantedAuthority("SCOPE_messages.write")));
var scopeClaim = mvc.get().uri("/api/messages").with(jwt().jwt(j -> j.claim("scope", "messages.read")));
// PITFALL: jwt() does not use your JwtAuthenticationConverter unless you pass it in
var rolesIgnored = mvc.get().uri("/api/admin/audit").with(jwt().jwt(j -> j.claim("roles", List.of("ADMIN"))));
var rolesMapped  = mvc.get().uri("/api/admin/audit")
        .with(jwt().jwt(j -> j.claim("roles", List.of("ADMIN"))).authorities(appConverter));
```

Output:

```
jwt() default, GET messages             -> 403
jwt() SCOPE_messages.write, POST        -> 201 added by carol
jwt() scope claim messages.read, GET    -> 200
jwt() roles=[ADMIN], default converter  -> 403
jwt() roles=[ADMIN], app converter      -> 200
```

1. `jwt()` alone gives subject `user`, scope `read` → `SCOPE_read`, not `SCOPE_messages.read` → 403.
2. `.authorities(...)` sets authorities directly, whatever the claims say.
3. Claims are mapped with the **default** `JwtGrantedAuthoritiesConverter`, so `scope` works…
4. …but your custom `roles` mapping is **not applied**: 403 although a real IdP token would get 200. Pass `.authorities(converter)`, or test that path with a real token.

Siblings: `opaqueToken()` (§11.7), `oauth2Login()` / `oidcLogin()` (§11.9), `oauth2Client()`. `@WithMockUser` tests URL rules too, but the principal is then not a `Jwt`, so `@AuthenticationPrincipal Jwt` parameters receive `null`.

TL;DR

Real locally signed tokens for the decoder; `jwt()` for rules — with your authorities converter, or you test a different mapping from production.

11.7 Opaque tokens and introspection

What it is

An **opaque token** is a random string with no readable content (`tok-alice-7f3a`). The resource server asks the authorization server's **introspection endpoint** (RFC 7662) "is it active, and for whom?" on every request (cache answers if you add it):

```
POST /oauth2/introspect   token=tok-alice-7f3a   (client authenticates with its own id/secret)
-> {"active": true, "sub": "alice", "scope": "notes.read", "exp": 1790000000, ...}
```

```
spring.security.oauth2.resourceserver.opaquetoken.introspection-uri=https://idp.example.com/oauth2/introspect
spring.security.oauth2.resourceserver.opaquetoken.client-id=notes-api
spring.security.oauth2.resourceserver.opaquetoken.client-secret=${INTROSPECTION_SECRET}
```

These properties make Boot create an `OpaqueTokenIntrospector` (classic: `SpringOpaqueTokenIntrospector`; Spring Security 7.1 adds `RestClientOpaqueTokenIntrospector`). To stay offline, our project supplies one answering from a map in the real endpoint's shape:

```
class FakeIntrospector implements OpaqueTokenIntrospector {
    private final Map<String, Map<String, Object>> activeTokens = Map.of(
            "tok-alice-7f3a", Map.of("active", true, "sub", "alice", "scope", "notes.read", "exp",
Instant.now().plusSeconds(600)),
            "tok-bob-91c2", Map.of("active", true, "sub", "bob", "scope", "notes.read notes.write", "exp",
Instant.now().plusSeconds(600)));

    @Override
    public OAuth2AuthenticatedPrincipal introspect(String token) {
        Map<String, Object> claims = activeTokens.get(token);
        if (claims == null) throw new BadOpaqueTokenException("Provided token isn't active"); // {"active":false}
        List<GrantedAuthority> authorities = Arrays.stream(((String) claims.get("scope")).split(" "))
                .map(s -> (GrantedAuthority) new SimpleGrantedAuthority("SCOPE_" + s)).toList();
        return new OAuth2IntrospectionAuthenticatedPrincipal((String) claims.get("sub"), claims, authorities);
    }
}

// chain for /opaque/**
http.securityMatcher("/opaque/**")
    .authorizeHttpRequests(a -> a
        .requestMatchers("/opaque/notes/write").hasAuthority("SCOPE_notes.write")
        .anyRequest().hasAuthority("SCOPE_notes.read"))
    .oauth2ResourceServer(rs -> rs.opaqueToken(o -> o.introspector(introspector)));
```

Output:

```
alice GET   -> 200 notes for alice (scope=notes.read)
alice write -> 403
bob write   -> 200 written by bob
inactive    -> 401 Bearer error="invalid_token", error_description="Provided token isn't active", ...
opaqueToken() -> 200 notes for carol (scope=notes.read)
```

The principal is an `OAuth2AuthenticatedPrincipal` (not a `Jwt`); the last line uses the `opaqueToken()` test post-processor.

JWT vs opaque

	JWT (self-contained)	Opaque + introspection
Validation	local, just a signature check	network call to the IdP per request (or per cache period)
Revocation	only when it expires (or via a deny-list)	**immediate**: the IdP answers `active: false`
Latency / IdP load	minimal	higher, and the IdP must be highly available
Privacy	claims readable by any holder	nothing readable
Typical use	APIs inside your platform	high-risk operations, tokens handed to third parties

A common hybrid is **opaque outside, JWT inside** ("phantom token"): the **API gateway** (single entry point routing to all services) introspects the opaque token and forwards a short-lived JWT internally.

TL;DR

Opaque tokens are checked with the IdP (RFC 7662): instant revocation and privacy, paid in latency and IdP load. `oauth2ResourceServer(rs -> rs.opaqueToken(...))`.

11.8 Multi-tenancy: several issuers in one API

What it is

A **multi-tenant** API serves several customers ("tenants"), each with its *own* IdP or **realm** (Keycloak: a separate set of users, clients and keys), hence its own issuer and keys. The API must verify each token with **that tenant's keys** and reject untrusted issuers.

`JwtIssuerAuthenticationManagerResolver` reads `iss` *without trusting it yet*, looks up an `AuthenticationManager` for that issuer, and lets it verify the signature with that issuer's keys:

```
Map<String, AuthenticationManager> managers = new ConcurrentHashMap<>();
JwtIssuerAuthenticationManagerResolver resolver = new JwtIssuerAuthenticationManagerResolver(issuer -> {
    if (!keys.isTrusted(issuer)) return null;         // unknown issuer -> 401
    return managers.computeIfAbsent(issuer, iss -> {
        NimbusJwtDecoder decoder = NimbusJwtDecoder.withPublicKey(keys.publicKey(iss)).build();
        decoder.setJwtValidator(JwtValidators.createDefaultWithIssuer(iss));
        return new ProviderManager(new JwtAuthenticationProvider(decoder));
    });
});
http.securityMatcher("/tenant/**")
    .authorizeHttpRequests(a -> a.anyRequest().authenticated())
    .oauth2ResourceServer(rs -> rs.authenticationManagerResolver(resolver));
```

Output:

```
tenant A token            -> 200 ann from https://idp.tenant-a.test
tenant B token            -> 200 ben from https://idp.tenant-b.test
B-signed, iss = tenant A  -> 401
untrusted issuer          -> 401
```

The third line matters: a token **signed by tenant B's key claiming tenant A** is rejected, because it was verified with A's key. With real IdPs publishing discovery metadata, one line suffices: `JwtIssuerAuthenticationManagerResolver.fromTrustedIssuers("https://idp.tenant-a.test", "https://idp.tenant-b.test")` (discovers each JWK Set on first use).

Common mistakes

- Building a decoder for **any** `iss` the token names (no allow-list) — an attacker runs their own IdP and names it.
- Forgetting tenant isolation *after* authentication — queries must still filter by tenant.

TL;DR


Several issuers → `JwtIssuerAuthenticationManagerResolver` with an allow-list. The `iss` claim chooses the keys, and the signature must match that issuer's key.

11.9 OAuth2 login: "Sign in with ..."

What it is

OAuth2 login lets users sign in to *your web app* with an IdP account (Google, GitHub, Keycloak, Entra ID). Your app is the **client** and never sees the password: it receives an **authorization code** (short-lived, single-use), exchanges it for tokens *server-side*, and creates a normal browser session. This is the **authorization-code flow**; with OIDC it also yields an ID token.

How it works



The protective parameters:

Parameter	Protects against	How
`state`	CSRF on the callback: an attacker making your browser finish *their* login	random value stored in the session and compared on return
`nonce` (OIDC; "number used once")	**replay** (an attacker re-sending a captured valid message) of an old ID token	random value that must come back inside the ID token
PKCE (`code_challenge` + `code_verifier`, RFC 7636)	a stolen authorization code	the app sends `SHA-256(verifier)` first; only the verifier's holder can redeem the code
exact `redirect_uri`	codes sent to an attacker's site	the IdP only redirects to pre-registered URIs
code exchange on the **back channel**	tokens exposed to the browser	tokens travel server-to-server, and the browser only gets a session cookie

Configuration

With a real OIDC provider, Boot needs just the client credentials and the issuer:

```
spring.security.oauth2.client.registration.demo-idp.client-id=notes-web
spring.security.oauth2.client.registration.demo-idp.client-secret=${DEMO_IDP_SECRET}
spring.security.oauth2.client.registration.demo-idp.scope=openid,profile,email
spring.security.oauth2.client.provider.demo-idp.issuer-uri=https://idp.example.test
```

Boot has provider defaults for `google`, `github`, `facebook` and `okta` (registration id is enough). Our project spells out every endpoint instead of `issuer-uri`, so it starts offline:

```
spring.security.oauth2.client.registration.demo-idp.authorization-grant-type=authorization_code
spring.security.oauth2.client.registration.demo-idp.redirect-uri={baseUrl}/login/oauth2/code/{registrationId}
spring.security.oauth2.client.provider.demo-idp.authorization-uri=https://idp.example.test/oauth2/authorize
spring.security.oauth2.client.provider.demo-idp.token-uri=https://idp.example.test/oauth2/token
spring.security.oauth2.client.provider.demo-idp.jwk-set-uri=https://idp.example.test/oauth2/jwks
spring.security.oauth2.client.provider.demo-idp.user-info-uri=https://idp.example.test/userinfo
spring.security.oauth2.client.provider.demo-idp.user-name-attribute=sub
```

```
http.authorizeHttpRequests(a -> a.requestMatchers("/", "/public/**").permitAll().anyRequest().authenticated())
    .oauth2Login(Customizer.withDefaults())
    .logout(Customizer.withDefaults());

@GetMapping("/profile")
String profile(@AuthenticationPrincipal OidcUser user) {
    return "hello " + user.getFullName() + " <" + user.getEmail() + ">, sub=" + user.getSubject()
            + ", issuer=" + user.getIssuer();
}
```

What we can run without an IdP

Steps 1–4 (everything before the browser leaves our app) and the callback's `state` check run for real; the IdP sign-in and code exchange cannot run without an IdP, so `oidcLogin()` simulates a finished login:

```
1. GET /profile (anonymous)       -> 302 /oauth2/authorization/demo-idp
2. GET /oauth2/authorization/demo-idp -> 302 to https://idp.example.test/oauth2/authorize
     client_id=notes-web
     code_challenge=<random>
     code_challenge_method=S256
     nonce=<random>
     redirect_uri=http://localhost/login/oauth2/code/demo-idp
     response_type=code
     scope=openid%20profile%20email
     state=<random>
   session attribute saved: true
3. callback with forged state      -> 302 /login?error
oidcLogin() GET /profile -> 200 hello Jane Doe <jane@example.com>, sub=248289761001,
issuer=https://idp.example.test
```

- The request has `state`, `nonce` **and PKCE** (`S256`) although this client has a secret: Spring Security 7 uses PKCE for **confidential clients** too (server-side clients that can keep a secret; browser/mobile apps are *public* clients). For an old IdP that can't handle it: `.clientSettings(ClientRegistration.ClientSettings.builder().requireProofKey(false).build())`.
- A callback with a `state` never issued to this session is refused (`/login?error`) — the login flow's CSRF protection.
- After a real login the principal is an `OidcUser` (ID-token claims + userinfo); tokens are stored server-side as an `OAuth2AuthorizedClient`, the browser holds only the session cookie. OAuth2 login is **session-based**: keep CSRF on.

OAuth2 vs OIDC login

With the `openid` scope Spring does **OIDC** login (validates the ID token, builds an `OidcUser`). Without it (e.g. GitHub, plain OAuth2) it calls the user-info endpoint and builds an `OAuth2User`. Mapping external users to *your* accounts (first login = sign-up, linking by verified e-mail, local roles) is your job: a custom `OidcUserService` / `OAuth2UserService`, or a listener for the login success event.

TL;DR

`oauth2Login()` + a client registration = "Sign in with X" via authorization code, `state`, `nonce` and PKCE. Tokens stay on the server, and the browser gets a session. Test with `oidcLogin()` / `oauth2Login()`.

11.10 Calling other services: client credentials and token relay

What it is

Calling *another* protected API has two cases:

Case	Whose token?	Grant
a nightly job calls the reports API	the **service's own** identity	**client credentials**: client id + secret (or private-key JWT / mTLS, mutual TLS) → access token
a user's request fans out to **downstream** APIs	the **user's** identity	**token relay**: forward the user's token, or better, exchange it (RFC 8693) for one aimed at the downstream API

How it looks in Spring (not run: needs a token endpoint)

Configure a registration and let `OAuth2AuthorizedClientManager` fetch, cache and renew tokens:

```
spring.security.oauth2.client.registration.reports.provider=demo-idp
spring.security.oauth2.client.registration.reports.client-id=nightly-job
spring.security.oauth2.client.registration.reports.client-secret=${REPORTS_SECRET}
spring.security.oauth2.client.registration.reports.authorization-grant-type=client_credentials
spring.security.oauth2.client.registration.reports.scope=reports.read
```

```java
// RestClient (Chapter 6) with an interceptor that adds "Authorization: Bearer <token>"
@Bean
RestClient reportsClient(RestClient.Builder builder, OAuth2AuthorizedClientManager manager) {
    return builder.baseUrl("https://reports.internal")
            .requestInterceptor(new OAuth2ClientHttpRequestInterceptor(manager))
            .build();
}

String csv = reportsClient.get().uri("/daily")
        .attributes(clientRegistrationId("reports"))   // which registration's token to use
        .retrieve().body(String.class);
```

With **HTTP interfaces** (Chapter 6), Spring Security 7 allows `@ClientRegistrationId` on the whole interface; register an `OAuth2RestClientHttpServiceGroupConfigurer` bean so the clients get the interceptor:

```java
@HttpExchange("/reports")
@ClientRegistrationId("reports")           // type-level support is new in Spring Security 7
interface ReportsApi {
    @GetExchange("/daily") String daily();
}

@Bean
OAuth2RestClientHttpServiceGroupConfigurer securityConfigurer(OAuth2AuthorizedClientManager manager) {
    return OAuth2RestClientHttpServiceGroupConfigurer.from(manager);
}
```

The **interceptor** asks the manager for a token on each outgoing request; the manager returns the cached one while valid and requests or refreshes when needed — you never parse expiry yourself.

Token relay. In a resource server the incoming token is `JwtAuthenticationToken#getToken().getTokenValue()`; an interceptor can copy it to outgoing calls. In **Spring Cloud Gateway** the `TokenRelay` filter does this for logged-in users (Chapter 16). Forwarding one token everywhere means every service accepts the same audience; **token exchange** (Spring Security OAuth2 client since 6.3) gets a narrower token per downstream API.

TL;DR

Services call APIs with **client credentials**, via `OAuth2AuthorizedClientManager` + `OAuth2ClientHttpRequestInterceptor` on `RestClient` (or `@ClientRegistrationId` on HTTP interfaces). User context flows by token relay or, better, token exchange.

11.11 Refresh tokens, lifetimes, revocation and logout

What it is

Users shouldn't log in every 10 minutes. A **refresh token** is a long-lived credential the client sends **only to the authorization server** to get a new access token without user interaction.

Practice	Why
access token 5–15 min, refresh token hours/days	a stolen access token is soon useless
refresh-token rotation: every use returns a *new* refresh token and invalidates the old one	a stolen refresh token used twice is detected, and the IdP revokes the whole family
bind refresh tokens to the client (secret, DPoP — proof of holding a private key — or mTLS)	a stolen token alone is not enough
never give refresh tokens to browser JavaScript	XSS could steal a long-lived credential (§11.12)

In Spring the resource server never sees refresh tokens; the client-side `OAuth2AuthorizedClientManager` (behind `oauth2Login` and the interceptor) refreshes expired access tokens automatically.

Revocation and logout

- **Revoking** (RFC 7009) tells the IdP a token is dead: opaque tokens stop at once; JWTs work until `exp` unless APIs check a `jti` deny-list (rarely worth it with short lifetimes).
- **Logging out** of your app (`POST /logout`) ends *your* session, not the IdP's — the next "Sign in with ..." logs straight back in. For single logout use **OIDC RP-initiated logout** (RP = relying party, the app relying on the IdP) to also redirect to the IdP's `end_session_endpoint`:

```
http.logout(l -> l.logoutSuccessHandler(new
OidcClientInitiatedLogoutSuccessHandler(clientRegistrationRepository)));
```

OIDC back-channel logout (`http.oidcLogout(...)`) lets the IdP call your app to end sessions when the user logs out elsewhere.

TL;DR

Short access tokens + rotating refresh tokens, handled by the client-side `OAuth2AuthorizedClientManager`. Revocation is instant only for opaque tokens. Use OIDC RP-initiated logout to end the IdP session too.

11.12 Where should a browser keep tokens? The BFF pattern

The problem it solves

SPA tokens in `localStorage` / `sessionStorage` are readable by **any script on the page**, so one XSS bug leaks them (JS 14.3, JS 14.10). In-memory storage is lost on reload and still reachable by injected script.

The recommended answer: Backend for Frontend (BFF)



1. The SPA talks only to its **BFF** on the same site, with an `HttpOnly` session cookie JavaScript cannot read.
2. The BFF is a confidential OAuth2 client (`oauth2Login`, §11.9) keeping and refreshing tokens server-side.
3. It forwards API calls with the bearer token (token relay, §11.10); Spring Cloud Gateway with `TokenRelay` is a common BFF.
4. The SPA now uses cookies, so **CSRF protection is required** — `csrf.spa()` (10.8).

The IETF draft *OAuth 2.0 for Browser-Based Applications* recommends this as the most secure option. See also the BFF pattern notes.

Where tokens live	XSS steals tokens?	CSRF risk	Complexity
`localStorage`	**yes**	no	low
JS memory only	harder, still possible while the page runs	no	low, but lost on reload
BFF (`HttpOnly` cookie session)	no, the tokens never reach the browser	yes, so use CSRF tokens	an extra backend

TL;DR

No long-lived tokens in browser JavaScript: a BFF keeps them server-side; the browser gets an `HttpOnly` session cookie plus CSRF protection.

11.13 Storing keys and secrets

Passwords: 10.5. Token systems add more secrets:

Secret	Where it lives	Rules
JWT signing private key	the authorization server only: vault, KMS (key management service) or HSM (hardware security module)	never in Git or a resource server; resource servers get *public* keys from the JWKS URL
Client secret	environment variable / secret manager, injected as `${...}`	rotate it; prefer `private_key_jwt` or mTLS for high-value clients
Refresh tokens stored by a BFF	server-side session or database, encrypted at rest	never sent to the browser
HMAC secret (if you use HS256)	secret manager	at least 256 bits of randomness. Everyone who can verify can also forge

Key rotation without downtime:

1. Publish the *new* public key in the JWKS next to the old one (a different `kid`).
2. Wait longer than the verifiers' JWKS cache time. `NimbusJwtDecoder` caches the JWK Set and re-fetches it when it meets an unknown `kid`.
3. Start signing with the new key.
4. Remove the old key after the longest token lifetime has passed.

Our demo generates a fresh key pair per start: tokens die on restart and several instances would disagree — fine for tests, wrong for production.

11.14 Spring Authorization Server

If you need your own IdP, **Spring Authorization Server** implements OAuth 2.1 and OpenID Connect 1.0: authorization code + PKCE, client credentials, refresh tokens, device authorization, token exchange, introspection, revocation, JWKS and discovery endpoints, dynamic client registration. Since **Spring Security 7.0 it ships inside Spring Security** (module `spring-security-oauth2-authorization-server`); Boot 4 provides `spring-boot-starter-security-oauth2-authorization-server`, configured under `spring.security.oauth2.authorizationserver.*`. PKCE is required by default for authorization-code clients.

Choose it to keep the IdP in your Spring codebase, customised in Java; choose Keycloak or a cloud IdP for an off-the-shelf product with admin UI, federation and user management. Either way *your APIs* look the same (resource servers with an `issuer-uri`). It needs a user store, persistent client/authorization storage (JDBC) and key management, so it is beyond this chapter's runnable examples.

11.15 Rate limiting and brute-force protection

Spring Security does **not** include **rate limiting** (capping requests per client per time window). Yet login and token endpoints are what attackers hammer: password guessing, **credential stuffing** (pairs leaked from other sites), and making you pay for slow bcrypt/Argon2 checks (10.5). Layers:

Layer	Tool	Limits
edge	API gateway / WAF (web application firewall) / CDN, Spring Cloud Gateway `RequestRateLimiter` (Redis, token bucket)	requests per IP / client / API key
application	Bucket4j (token bucket, local or distributed via Redis/JCache) in a servlet filter	per user or per endpoint rules
login logic	count failures per account *and* per IP (listen to `AuthenticationFailureBadCredentialsEvent`), add delays, CAPTCHA or MFA after N failures	brute force on one account
identity provider	Keycloak/cloud IdPs have brute-force detection built in	when login happens at the IdP

Avoid hard **account lockout** — it lets anyone lock out any user; prefer progressive delays and step-up checks (an extra factor only when something looks risky). Framework 7's `@ConcurrencyLimit` (Chapter 4) caps *concurrent* executions, not requests per second — not a rate limiter. Algorithms: System Design Patterns — Rate Limiting.

11.16 Common mistakes (whole chapter)

Mistake	Consequence	Fix
no audience check	tokens for *other* APIs accepted	`jwt.audiences` property or `JwtClaimValidator("aud", ...)`
custom validator *replacing* defaults	expired tokens accepted	combine with `JwtValidators.createDefaultWithIssuer(...)`
`hasAuthority("messages.read")`	always 403	scopes are `SCOPE_messages.read`
`jwt()` tests without your converter	tests disagree with production	`.authorities(yourConverter)` or real tokens
long-lived JWT access tokens	stolen token valid for days	minutes + refresh tokens, or opaque tokens
tokens in `localStorage`	XSS = account takeover	BFF with `HttpOnly` cookie
accepting any `iss` in multi-tenant setups	attacker-run IdP accepted	allow-list of issuers
CSRF disabled on the BFF / OAuth2-login app	CSRF on a cookie session	keep CSRF on (`csrf.spa()`)
ID token sent to APIs	wrong audience, identity confusion	send the **access** token
rolling your own token server for real users	endless security work	use an authorization server
private key in `application.properties` / Git	anyone can mint tokens	vault/KMS, JWKS for public keys

11.17 In the interview

"How does a Spring resource server validate a JWT?" "`BearerTokenAuthenticationFilter` extracts the token from the `Authorization` header. `JwtAuthenticationProvider` calls the `JwtDecoder`, which Nimbus backs with the issuer's JWK Set found via `issuer-uri` discovery. It checks the algorithm, picks the key by `kid`, and verifies the signature. Then validators check `exp` and `nbf` with 60 seconds of skew, `iss`, `typ`,

and the audience I configure. `JwtAuthenticationConverter` maps `scope` to `SCOPE_` authorities, plus any role claims I map. A failure returns 401 `invalid_token`, and a missing authority returns 403 `insufficient_scope`."

Follow-ups:

- *JWT or opaque token?* → JWT for fast local validation inside the platform; opaque for instant revocation or hidden claims, at the cost of introspection.
- *Why PKCE if the client has a secret?* → It binds the code to the party that started the flow, so a stolen code is useless. OAuth 2.1 requires it for all clients; Spring Security 7 sends it by default.
- *Logout with stateless tokens?* → Short access tokens, revoke the refresh token, end the local session, OIDC RP-initiated logout for the IdP session.
- *Tokens in an SPA?* → Preferably none: a BFF with an `HttpOnly` cookie and CSRF protection.
- *Service-to-service auth?* → Client credentials via `OAuth2AuthorizedClientManager` + `OAuth2ClientHttpRequestInterceptor`, or mTLS in a mesh; relay or exchange the user's token when user context matters.
- *What is `state` for?* → CSRF protection of the login callback: ties the response to the session that started the flow.

11.18 Security fundamentals beyond Spring

What it is

Everything above rests on a few cryptographic building blocks — hashes, symmetric and asymmetric keys, signatures, key exchange — which Spring hides behind `PasswordEncoder`, `JwtDecoder` and `https://` URLs. Each is shown with the plain JDK in `code/crypto-basics`, followed by the protocols built from them: TLS, SSH keys, one-time codes, passkeys, single sign-on.

Analogy: a **hash** is a fingerprint (identifies, cannot be turned back); **symmetric encryption** a padlock both sides hold keys to; **asymmetric encryption** a mailbox anyone can post into but only the owner opens; a **signature** a wax seal only one ring makes but anyone can check.

Encoding vs hashing vs encryption vs tokenisation

	Purpose	Key?	Reversible?	Example	Wrong use
Encoding	change representation so bytes survive a channel	no	yes, by anyone	Base64, URL encoding, UTF-8	"hiding" a password in Base64
Hashing	fixed-size fingerprint; detect change; store passwords	no (HMAC adds one)	**no**	SHA-256, BLAKE3; for passwords bcrypt/Argon2 (10.5)	fast SHA-256 for passwords (GPU-crackable)
Encryption	confidentiality: only key holders can read	yes	yes, with the key	AES-GCM, ChaCha20-Poly1305, RSA-OAEP	encrypting passwords (then someone can decrypt them)
Tokenisation	replace sensitive data with a random stand-in; the real value lives in a secured vault	vault lookup	only via the vault	card number → `tok_8f3a…` in payment systems	—

An **HMAC** (hash-based message authentication code) is a hash mixed with a secret key: only key holders can compute or check it. HS256 JWTs and TOTP codes (below) are HMACs.

Symmetric vs asymmetric encryption

	Symmetric	Asymmetric (public-key)
Keys	one shared secret key	a key pair: **public** (share freely) + **private** (never leaves the owner)
Speed	very fast (AES has CPU instructions)	100–1000× slower; small data only
Problem	how do both sides get the key safely?	who does this public key really belong to?
Algorithms	AES-GCM, ChaCha20-Poly1305	RSA, elliptic curves (ECDH/X25519 for key exchange, ECDSA/Ed25519 for signatures)

Real systems are **hybrid**: asymmetric crypto agrees or protects a random symmetric key; bulk data goes through AES (Advanced Encryption Standard). **Authenticated encryption** modes (GCM, Poly1305) add a tag, so tampering makes decryption fail rather than return garbage (the demo proves it).


Digital signatures and certificates

A **digital signature** is computed with the private key over a hash of the message; anyone with the public key verifies that (1) that key's holder signed it and (2) not one bit changed — how an RS256/ES256 JWT is trusted (§11.1).

A **certificate** (X.509) is a signed statement "this public key belongs to `api.example.com`", signed by a **certificate authority (CA)** that browsers and OSes trust. Browsers and the JDK ship trusted root CAs; the server sends its certificate plus intermediates, and the client checks the **chain** up to a trusted root, the name, and the validity dates.

The TLS 1.3 handshake

HTML book §1.4 says what TLS gives (confidentiality, integrity, server authentication). Here is how, in one round trip (RFC 8446):



Key ideas: the **key exchange** (ECDHE) gives both sides a secret nobody on the wire can compute; the `CertificateVerify` **signature** proves the server owns the certificate's private key; keys are **ephemeral**, so recording traffic now and stealing the server key later reveals nothing (**forward secrecy** — the long-term key only signs). **mTLS** adds a client certificate so the server authenticates the client too — common between services (§11.10). Spring Boot configures TLS with SSL bundles (`server.ssl.bundle`), though it is usually terminated at a load balancer or Kubernetes ingress (System Design Fundamentals).

SSH keys

SSH logs you into servers and Git hosts. `ssh-keygen -t ed25519` creates a key pair; the **public** key goes in the server's `~/.ssh/authorized_keys` (or GitHub settings). On login the server sends a challenge, the client **signs** it with the private key, the server verifies — no password crosses the wire. On first connect SSH shows the **server's** host-key fingerprint; accepting stores it in `known_hosts`, and a later mismatch warns of a possible **man-in-the-middle** (an attacker between you and the server). Protect the private key with a passphrase and `ssh-agent`; never copy it between machines.

TOTP: the six digits in an authenticator app

TOTP (time-based one-time password, RFC 6238) builds on **HOTP** (RFC 4226):

1. At enrolment the server generates a random secret and shows it as a QR code (`otpauth://totp/...?secret=BASE32...`); the app stores it. Both sides now share a secret.
2. Every 30 seconds both compute `counter = floor(unixTime / 30)`, then `HMAC-SHA1(secret, counter)`.
3. **Dynamic truncation**: the last 4 bits of the HMAC pick an offset; 31 bits from there, `mod 10^6`, give six digits.
4. The server accepts the current step and usually ±1 step for clock drift, and should remember used codes against replay.

`Totp.java` implements it in 30 lines; `TotpTest` checks every RFC 6238 Appendix B test vector (SHA-1, SHA-256 and SHA-512) and the RFC 4226 HOTP vectors.

```
byte[] h = mac.doFinal(ByteBuffer.allocate(8).putLong(counter).array()); // HMAC(secret, 8-byte counter)
int offset = h[h.length - 1] & 0x0f;                                     // dynamic truncation
int binary = ((h[offset] & 0x7f) << 24) | ((h[offset + 1] & 0xff) << 16)
           | ((h[offset + 2] & 0xff) << 8) | (h[offset + 3] & 0xff);
return String.format("%0" + digits + "d", binary % (int) Math.pow(10, digits));
```

TOTP is phishable (a fake look-alike site can ask for the code and replay it within 30 s) and relies on a server-stored shared secret — what passkeys fix.

Passkeys (WebAuthn / FIDO2)

A **passkey** is a key pair created by your device (phone, laptop, security key) **for one website**. Registration: the browser's WebAuthn API asks the device's **authenticator** to create a key pair scoped to the site's domain (the **relying party ID**); the site stores only the public key (plus a credential ID). Login: the site sends a random challenge; the authenticator checks you (fingerprint, face, PIN), **signs** the challenge together with the **origin** (scheme + domain + port), and the site verifies with the stored public key.

Stronger than passwords + TOTP: nothing secret on the server (a leak yields only public keys), and the signature covers the origin, so a look-alike phishing domain gets a useless signature. Synced passkeys (iCloud Keychain, Google Password Manager) survive losing a phone. Spring Security supports them since 6.4: `http.webAuthn(w -> w.rpName("Shop").rpId("shop.example.com").allowedOrigins("https://shop.example.com"))` (module `spring-security-webauthn` in 7.x), recording a `FACTOR_WEBAUTHN` authority for multi-factor rules (10.4).

Single sign-on: SAML vs OpenID Connect

SSO means logging in once at an identity provider (IdP) and being let into many applications (service providers / relying parties) without new passwords.

	SAML 2.0 (2005)	OpenID Connect (2014, on OAuth 2.0)
Token	signed **XML assertion**	signed **JWT** ID token (§11.2)
Transport	browser POSTs/redirects the assertion to the app	authorization-code flow + PKCE, back-channel token call
Fits	enterprise web apps, older corporate IdPs (AD FS)	web, SPA/BFF, mobile, APIs; also gives access tokens
Spring	`saml2Login()` (`spring-security-saml2-service-provider`)	`oauth2Login()` (§11.9)

Both rely on the IdP **signing** a statement about the user, verified with its published key or certificate. Pick OIDC for new systems; add SAML when an enterprise customer's IdP only speaks SAML (Keycloak, Okta and Entra ID speak both and can bridge).

Seeing it: `code/crypto-basics`

Plain JDK 25, no Spring. `mvn -q -B -ntp verify` runs 13 JUnit tests (RFC vectors, AES-GCM tamper detection, signatures, X25519 agreement); `java -cp target/classes handbook.security.CryptoBasicsDemo` prints:

```
encode  Base64      : cGF5IGJvYiAxMDA=  -> decodes back to: pay bob 100
hash    SHA-256     : aa843d8373c66e26...  ('pay bob 900' -> 70ef8a2487a6d483...)
encrypt AES-256-GCM : 27 bytes (11 plaintext + 16 auth tag) -> decrypts to: pay bob 100
encrypt tampered    : AEADBadTagException (integrity check failed)
sign    Ed25519     : 64-byte signature; verify original = true, verify 'pay bob 900' = false
ECDHE   X25519      : both sides derived the same 32-byte secret = true (e4582f7aff4d...)
ECDHE   record      : server decrypts client's record: GET /
TOTP    t=59          : counter=1         code=94287082
TOTP    t=1111111109  : counter=37037036  code=07081804
TOTP    t=1234567890  : counter=41152263  code=89005924
TOTP    t=2000000000  : counter=66666666  code=69279037
TOTP    6-digit app : 921300 valid 25 s later = true, valid 5 min later = false
```

The four `TOTP t=` codes are exactly the SHA-1 column of RFC 6238 Appendix B. Keys and the X25519 secret are random on every run.

Common mistakes

- Calling Base64 "encryption" — it is encoding.
- Hashing passwords with plain SHA-256 or MD5 — use bcrypt, Argon2, PBKDF2.
- Reusing an AES-GCM IV (initialisation vector: a per-message nonce) with the same key — breaks confidentiality and integrity; use a random 12-byte IV per message.
- Rolling your own crypto or protocol — use the JDK, TLS and vetted libraries; your job is parameters and key management.
- Disabling certificate checks ("trust all") to pass a test — removes TLS's *authentication* half in production too.
- Comparing codes or MACs with `equals` — use constant-time `MessageDigest.isEqual` to avoid timing leaks.

In the interview

> **30-second answer — how HTTPS works:** "TLS 1.3 does an ephemeral Diffie-Hellman key exchange (two parties agreeing a shared secret over an open network) in the first round trip, so both derive the same session keys without sending them. The server proves its identity by signing the handshake with its certificate's private key; the client checks the chain up to a trusted CA and the hostname. Then data is encrypted and integrity-protected with a fast symmetric cipher such as AES-GCM. Ephemeral keys give forward secrecy."

- *Hashing vs encryption?* → Hashing is one-way and keyless (fingerprints, passwords); encryption is reversible with a key (confidentiality).

- *Why both symmetric and asymmetric?* → Asymmetric solves key distribution and identity but is slow; symmetric is fast. TLS uses the first to set up the second.
- *Authenticator app offline?* → Shared secret + current time → HMAC → truncation (TOTP); ±1 step tolerates clock drift.
- *Why are passkeys phishing-resistant?* → The signature is bound to the site's origin and the server holds only a public key.
- *SAML vs OIDC?* → Both SSO via an IdP-signed statement; SAML: XML assertions via browser POST; OIDC: JWT ID tokens over OAuth 2.0, suits mobile and APIs.
- *What protects a JWT's claims from change, and what would hide them?* → A signature (JWS) / encryption (JWE).

TL;DR

Encoding is keyless and reversible, hashing one-way, encryption keyed, tokenisation a vault reference. Symmetric = one fast shared key; asymmetric = public/private pair for key exchange and signatures; TLS 1.3 combines them (ECDHE + certificate signature + AES-GCM). SSH and passkeys sign a challenge; TOTP = HMAC(secret, time/30) truncated to six digits. SSO: SAML (XML) or OIDC (JWT) — prefer OIDC.

Sources: RFC 6238 (TOTP), RFC 4226 (HOTP), RFC 8446 (TLS 1.3), RFC 4251/4252 (SSH), RFC 7748 (X25519), RFC 8032 (Ed25519), NIST SP 800-38D (GCM), W3C Web Authentication Level 2, OASIS SAML 2.0 Core, OpenID Connect Core 1.0, Spring Security reference (Passkeys, SAML 2.0 Login), JDK 25 `java.security` / `javax.crypto` API docs.

Chapter 11 TL;DR

- **Tokens**: JWT = `header.payload.signature`; claims readable, signature makes them trustworthy. Prefer asymmetric keys (RS256/ES256) published as a JWKS.
- **OAuth 2.0/OIDC**: authorization code + PKCE for users, client credentials for services, refresh tokens for renewal. Implicit and password grants are gone (Spring Security 7 removed password-grant support).
- **Resource server**: `oauth2ResourceServer(jwt)` + `issuer-uri`; validates signature, `exp` / `nbf` (60 s skew), `iss`, `typ`, your `aud`. 401 `invalid_token` vs 403 `insufficient_scope`; publishes RFC 9728 metadata.
- **Authorities**: `scope` → `SCOPE_x`; map role claims with a converter or Boot properties.
- **Testing**: real tokens from a local `NimbusJwtEncoder` for decoder rules; `jwt()` / `opaqueToken()` / `oidcLogin()` for access rules — pass your converter to `jwt()`.
- **Variants**: opaque tokens via introspection (instant revocation); multi-tenant via `JwtIssuerAuthenticationManagerResolver` with an issuer allow-list.
- **Clients**: `oauth2Login` (state, nonce, PKCE, tokens server-side); `OAuth2AuthorizedClientManager` + `RestClient` interceptor or `@ClientRegistrationId` HTTP interfaces; token relay or exchange.
- **Browsers**: BFF + `HttpOnly` cookie + CSRF; no tokens in `localStorage`.
- **Operations**: keys in a vault, rotated via `kid`; Spring Authorization Server (inside Spring Security 7) if you must run an IdP; rate limiting at the edge.
- **Fundamentals** (§11.18): encoding ≠ hashing ≠ encryption; TLS 1.3 = asymmetric key exchange + signatures + AES-GCM; SSH keys and passkeys sign a challenge; TOTP = HMAC(secret, time/30) truncated; SSO via SAML or OIDC.

Next: Chapter 12 — Testing Spring apps covers the test slices used here in depth.