Chapter 6 — REST Clients and HTTP Interfaces

Chapter 5 built an API. Real services also **call** APIs: a payment provider, another team's microservice (a small, independently deployed service that owns one business area), a search engine. Calling over the network brings problems a local call never has — slowness, timeouts, partial failures (some calls fail while others work), error bodies, versioning, retries. This chapter covers Spring's HTTP clients and how to use them safely.

Code: `code/rest-clients/` — Spring Boot 4.1.1, Framework 7.0, Java 25. To make the tests hit a *real* HTTP server without the internet, the project also contains a small "remote" catalog API (`CatalogServerController`) that the test starts on a free local port; imagine it belongs to another team. All output shown is real.

```
<!-- RestClient.Builder, RestTemplateBuilder, HTTP service client auto-configuration (Boot 4 starter) -->
<dependency>
  <groupId>org.springframework.boot</groupId>
  <artifactId>spring-boot-starter-restclient</artifactId>
</dependency>
```

(An app that already has `spring-boot-starter-webmvc` for its own endpoints still adds `spring-boot-starter-restclient` for the client side — Boot 4's starters are modular.)


6.1 Choosing a client

What they are

Client	Style	Since	Status (Framework 7)	Use for
`RestClient`	synchronous (the calling thread waits for the response), **fluent** (calls chained with dots: `get().uri(...).retrieve()`) API	Framework 6.1 (2023)	the recommended blocking client	new code in Spring MVC / non-reactive apps
`RestTemplate`	synchronous, template methods (`getForObject`, `exchange`, ...)	Spring 3.0 (2009)	**deprecation announced**: intent to deprecate in 7.0, planned `@Deprecated` in 7.1 (Nov 2026), removal in 8.0	existing code only; migrate to `RestClient`
`WebClient`	non-blocking, reactive (the thread is freed while waiting; results arrive later as `Mono` = 0–1 value or `Flux` = 0–N values)	Framework 5.0	recommended reactive client	WebFlux apps, streaming, reactive pipelines (Chapter 13)
HTTP interface (`@HttpExchange`)	**declarative** (you describe *what* to call, not *how*): an annotated Java interface, Spring generates the implementation	Framework 6.0; Boot auto-config in 4.0	recommended for calling well-defined APIs	typed clients for other services; runs on `RestClient` or `WebClient`

Why `RestClient` replaced `RestTemplate`: the same underlying machinery (request factories, message converters, interceptors) but a modern fluent API instead of dozens of overloaded methods (methods with the same name but different parameter lists), and one place for all new features (API versioning, `requiredBody`, status handlers). The Spring team's plan (spring.io blog, "The state of HTTP clients in Spring", September 2025) keeps `RestTemplate` working through the 7.x line — so no panic, but no new code on it.

Do you need `WebClient` in a Spring MVC app? Not any more. Before `RestClient`, people pulled in WebFlux just to use `WebClient` and called `.block()`. With `RestClient` — and **virtual threads** (lightweight threads managed by the JVM, so millions can wait at once) making blocking calls cheap (Java book 15.4) — the blocking client is the simpler choice for MVC apps.



6.2 `RestClient` basics

How it works

1. Get a **builder**. In Boot, inject `RestClient.Builder` — a **prototype** bean (fresh per injection point, so configuring one doesn't affect others) pre-configured with Boot's message converters (Jackson 3), the chosen HTTP library, timeouts from `spring.http.clients.*`, and (with Micrometer) observability — metrics and traces per call. (Outside Boot: `RestClient.builder()` or `RestClient.create("https://...")`.)
2. Set shared settings (`baseUrl`, `defaultHeader`, `defaultStatusHandler`, `requestInterceptor`, `requestFactory`) and `build()`. A `RestClient` is **immutable and thread-safe** — build it once (e.g. in a constructor) and reuse it.
3. Per call: choose the method (`get()`, `post()`, `put()`, `patch()`, `delete()`, `method(...)`), the `uri(...)`, headers, body.
4. Finish with **`retrieve()`** (then `body(...)`, `toEntity(...)`, `toBodilessEntity()`) or **`exchange(...)`**.

Example: body, entity and generic lists

```
RestClient rest = builder.baseUrl(baseUrl()).build();

BookDto book = rest.get().uri("/catalog/books/{id}", 1).retrieve().body(BookDto.class);

ResponseEntity<List<BookDto>> entity = rest.get()
        .uri(b -> b.path("/catalog/books").queryParam("author", "Martin Fowler").build())
        .retrieve()
        .toEntity(new ParameterizedTypeReference<List<BookDto>>() {});
```

Output:

```
body(BookDto.class) -> BookDto[id=1, title=Release It!, author=Michael T. Nygard]
toEntity(List) -> 200 OK 2 books
```

What each part does:

- `uri("/catalog/books/{id}", 1)` — a **URI template**; variables are URL-encoded for you (spaces → `%20` etc.). Never build URLs by string concatenation with user input.
- `uri(b -> b.path(...).queryParam("author", "Martin Fowler").build())` — the `UriBuilder` form for query parameters (the space is encoded).
- `body(BookDto.class)` — deserialises the JSON body into your record. Your DTO only needs the fields you use; unknown fields are ignored (Jackson 3 default).
- `ParameterizedTypeReference<List<BookDto>>` — Java erases generics at runtime, so `List.class` would give a list of maps; the anonymous subclass (`{}`) captures the full type. Same with `body(new ParameterizedTypeReference<List<BookDto>>() {})`.
- `toEntity(...)` returns `ResponseEntity<T>`: status + headers + body. `toBodilessEntity()` when you only care about the status.
- `requiredBody(...)` (Framework 7.0.4+) is like `body(...)` but throws if the body is empty instead of returning `null`.

A hand-written client class

Wrap the calls in a small class so the rest of your code talks in domain terms (books, orders — not HTTP) (`CatalogClient.java`):

```
@Component
public class CatalogClient {

    private final RestClient rest;

    public CatalogClient(RestClient.Builder builder, @Value("${catalog.base-url}") String baseUrl) {
        this.rest = builder                                    // Boot's pre-configured, prototype builder
                .baseUrl(baseUrl)
                .defaultHeader("X-Client", "catalog-client")
                .defaultStatusHandler(status -> status.is5xxServerError(), (request, response) -> {
                    throw new CatalogUnavailableException(
                            "catalog answered " + response.getStatusCode().value() + " for " +
request.getURI().getPath());
                })
                .build();
    }

    /** 404 becomes Optional.empty(); 5xx becomes CatalogUnavailableException (default status handler). */
    public Optional<BookDto> findBook(long id) {
        try {
            return Optional.ofNullable(rest.get()
                    .uri("/catalog/books/{id}", id)            // URI template: id is encoded for us
                    .retrieve()                                // status handlers apply to retrieve()
                    .body(BookDto.class));
        } catch (HttpClientErrorException.NotFound e) {
            return Optional.empty();
        }
    }

    /** exchange(): full control over the raw response - status handlers are NOT applied. */
    public String describe(long id) {
        return rest.get()
                .uri("/catalog/books/{id}", id)
                .exchange((request, response) -> {
                    if (response.getStatusCode().isError()) {
                        return "status " + response.getStatusCode().value();
                    }
                    BookDto b = response.bodyTo(BookDto.class);
                    return b.title() + " by " + b.author();
                });
    }

    public ResponseEntity<BookDto> create(String title, String author) {
        return rest.post()
                .uri("/catalog/books")
                .body(new BookDto(null, title, author))      // serialised to JSON by Jackson
                .retrieve()
                .toEntity(BookDto.class);                     // status + headers + body
    }
}
```

Output:

```
findBook(2)   -> Optional[BookDto[id=2, title=Refactoring, author=Martin Fowler]]
findBook(999) -> Optional.empty
describe(1)   -> Release It! by Michael T. Nygard
describe(999) -> status 404
create        -> 201 CREATED Location=/catalog/books/102 body=BookDto[id=102, title=Designing Data-Intensive
Applications, author=Martin Kleppmann]
```

`retrieve()` vs `exchange()`

	`retrieve()`	`exchange((req, res) -> ...)`
Error statuses	turned into exceptions (default or your status handlers)	**you** inspect the status; **status handlers are not applied**
Body handling	`body`, `toEntity`, `toBodilessEntity`	`res.bodyTo(...)`, `res.getHeaders()`, anything
Use when	almost always	different body types per status, streaming, very custom handling


A lesson from writing this chapter: the first version of `findBook` used `exchange()` and treated 404 specially, assuming the 5xx `defaultStatusHandler` would still fire. It does not — `exchange()` bypasses status handlers — so a 503 silently became `Optional.empty()`. The `@RestClientTest` in section 6.8 caught it. If you use `exchange()`, handle **every** status yourself.

More request features (quick reference)

Need	**`RestClient` call**
Header on one request	`.header("X-Tenant", "acme")`, `.headers(h -> h.setBearerAuth(token))`
Accept / content type	`.accept(MediaType.APPLICATION_JSON)`, `.contentType(MediaType.APPLICATION_JSON)`
Form post (`application/x-www-form-urlencoded`)	`.contentType(APPLICATION_FORM_URLENCODED).body(multiValueMap)`
Multipart upload	`.body(new MultipartBodyBuilder().part("file", resource).build())` with `contentType(MULTIPART_FORM_DATA)`
Download a large file	`.exchange((req, res) -> { res.getBody().transferTo(out); return null; })` — stream, don't buffer
Plain text	`.retrieve().body(String.class)`
Per-request attributes for interceptors/observations	`.attribute("name", value)`

6.3 Error handling

Spring's client exception hierarchy



Exception	Meaning	Retry?
`HttpClientErrorException` (4xx) with nested types `.NotFound`, `.BadRequest`, `.Conflict`, `.TooManyRequests`, ...	the **request** was wrong or not allowed	no (except 429 "too many requests" after waiting the `Retry-After` header's delay, and 408 "request timeout")
`HttpServerErrorException` (5xx) with `.InternalServerError`, `.BadGateway`, `.ServiceUnavailable`, `.GatewayTimeout`	the server failed	often yes (transient), if the operation is idempotent (doing it twice = doing it once — see System Design Fundamentals)
`ResourceAccessException`	network I/O problem: connection refused, **timeout** (cause e.g. `HttpTimeoutException` for the JDK client), DNS	often yes
`UnknownContentTypeException`	no converter for the response type	no — a bug or contract change

All are **unchecked** (`RestClientException extends RuntimeException`). `RestClientResponseException` gives you `getStatusCode()`, `getResponseHeaders()`, `getResponseBodyAsString()`, and **`getResponseBodyAs(Class)`** — which can decode an RFC 9457 error body directly:

```
assertThatThrownBy(() -> rest.get().uri("/catalog/books/{id}", 999).retrieve().body(BookDto.class))
        .isInstanceOf(HttpClientErrorException.NotFound.class)
        .satisfies(e -> {
            var ex = (HttpClientErrorException) e;
            ProblemDetail pd = ex.getResponseBodyAs(ProblemDetail.class);   // read the error body
            System.out.println("404 -> " + ex.getClass().getSimpleName()
                    + ", problem title='" + pd.getTitle() + "', detail='" + pd.getDetail() + "'");
        });
```

Output:

```
404 -> NotFound, problem title='Book not found', detail='No book 999'
```

Mapping to your own exceptions

Callers of `CatalogClient` should not need to know it uses HTTP. Translate at the edge:

- **Per request:** `.retrieve().onStatus(HttpStatusCode::is4xxClientError, (req, res) -> { throw new ... })`.

- **For every request of a client:** `builder.defaultStatusHandler(predicate, handler)` — used above to turn any 5xx into `CatalogUnavailableException`:

```
503 -> CatalogUnavailableException: catalog answered 503 for /catalog/flaky
```

- **Expected "not found":** return `Optional.empty()` (as `findBook` does) instead of throwing.

Common mistakes

- Catching `Exception` around a client call and returning `null` — hides outages; log and translate instead.
- Logging full response bodies of errors — may contain personal data or secrets.
- Treating every 4xx as retryable — a 400 will fail the same way every time.
- Forgetting that **no timeout = wait forever**-ish (next section).

6.4 Timeouts and the underlying HTTP library

What it is

`RestClient` does not open sockets itself; it delegates to a **`ClientHttpRequestFactory`** wrapping a real HTTP library. Two timeouts matter:

- **Connect timeout** — how long to wait for the TCP + TLS (`https` encryption) connection to be established.
- **Read timeout** — how long to wait for response data once connected.

Why it matters: without timeouts, a slow downstream service makes your request threads pile up waiting until your service also stops answering — a **cascading failure** (one failure spreading to the services that depend on it). Every remote call needs a timeout shorter than your own callers' timeout. See also Circuit breaker and Bulkhead.

Which library does Boot pick?

Boot 4 detects, in this order, the first one on the classpath:

Priority	Library	Factory	Add dependency
1	Apache HttpClient 5	`HttpComponentsClientHttpRequestFactory`	`org.apache.httpcomponents.client5:httpclient5`
2	Jetty HttpClient	`JettyClientHttpRequestFactory`	`org.eclipse.jetty:jetty-client`
3	Reactor Netty	`ReactorClientHttpRequestFactory`	`io.projectreactor.netty:reactor-netty-http`
4	JDK `java.net.http.HttpClient`	`JdkClientHttpRequestFactory`	nothing (built in)
5	`HttpURLConnection`	`SimpleClientHttpRequestFactory`	nothing

This project has none of the first three, so it uses the **JDK HttpClient**. Force a choice with `spring.http.clients.imperative.factory=jdk|http-components|jetty|reactor|simple`. (For `WebClient` the equivalent is `spring.http.clients.reactive.connector`.)

Configuring timeouts

Globally, for every auto-configured client (Boot 4 property names — the Boot 3.x `spring.http.client.*` names are deprecated):

```
spring.http.clients.connect-timeout=1s
spring.http.clients.read-timeout=3s
spring.http.clients.redirects=dont-follow     # or follow / follow-when-possible
```

Per client, in code, with Boot's `ClientHttpRequestFactoryBuilder` and `HttpClientSettings`:

```
var factory = ClientHttpRequestFactoryBuilder.jdk()
        .build(HttpClientSettings.defaults()
                .withConnectTimeout(Duration.ofSeconds(1))
                .withReadTimeout(Duration.ofMillis(300)));
RestClient rest = builder.baseUrl(baseUrl()).requestFactory(factory).build();
rest.get().uri("/catalog/slow").retrieve().body(String.class);   // server needs 1.5 s
```

Output:

```
slow endpoint -> ResourceAccessException caused by HttpTimeoutException after ~300 ms
```

For HTTP service groups (section 6.6) the timeouts can be set per group: `spring.http.serviceclient.<group>.read-timeout=2s`.

Choosing values: measure the downstream's latency (p99 = the time 99% of calls stay under) and set the read timeout a bit above it; keep the total (timeout × attempts + back-off waits) below what *your* caller will wait. Connection **pooling** (reusing open connections; Apache/Jetty/Netty pool by default, the JDK client keeps connections alive) avoids TCP/TLS setup on every call.

6.5 Interceptors

A `ClientHttpRequestInterceptor` wraps every request a client sends — the client-side twin of a servlet filter. Uses: auth headers (tokens), correlation ids (one id carried through all calls of a request so logs can be joined), logging, metrics.

```
RestClient rest = builder.baseUrl(baseUrl())
        .requestInterceptor((request, body, execution) -> {
            request.getHeaders().add("X-Trace-Id", "trace-42");          // add a header
            var response = execution.execute(request, body);            // do the call
            log.add(request.getMethod() + " " + request.getURI().getPath() + " -> " + response.getStatusCode().value());
            return response;
        })
        .build();
```

Output:

```
interceptor: GET /catalog/books/1 -> 200
interceptor: GET /catalog/books/3 -> 200
```

- You rarely need interceptors for **tracing**: when Micrometer observability is set up (Actuator, Chapter 15), Boot instruments the auto-configured builder to record `http.client.requests` metrics and propagate trace headers to the next service. This only works if you build from the injected builder — `RestClient.create()` skips it.
- For OAuth2 bearer tokens (`Authorization: Bearer ...`), Spring Security provides `OAuth2ClientHttpRequestInterceptor` (Chapter 11).
- Don't read the response body in an interceptor unless you buffer it (`BufferingClientHttpRequestFactory`); a body can normally be read only once.
- To customise **all** builders Boot creates, declare a `RestClientCustomizer` bean.

6.6 HTTP service interfaces (`@HttpExchange`)

What it is

An **HTTP service interface** is a Java interface whose methods are annotated with the HTTP method, path and parameters. Spring generates a **proxy** that implements it by turning each call into an HTTP request (the same proxy idea as Chapter 4). It is Spring's built-in answer to Feign-style declarative clients (OpenFeign is a popular library doing the same) — no extra library.

```java
@HttpExchange("/catalog")
public interface CatalogApi {

    @GetExchange("/books/{id}")
    BookDto get(@PathVariable long id);

    @GetExchange("/books/{id}")
    ResponseEntity<BookDto> getEntity(@PathVariable long id);   // status + headers too

    @GetExchange("/books")
    List<BookDto> byAuthor(@RequestParam String author);

    @PostExchange("/books")
    ResponseEntity<BookDto> create(@RequestBody BookDto book);

    @GetExchange(url = "/greeting", version = "2.0")   // Framework 7: API version per method
    String greetingV2();
}
```

Annotation	Purpose
`@HttpExchange` (type)	shared URL prefix, content type, accept, headers, version
`@GetExchange`, `@PostExchange`, `@PutExchange`, `@PatchExchange`, `@DeleteExchange`	method + path
`@PathVariable`, `@RequestParam`, `@RequestHeader`, `@RequestBody`, `@RequestPart`, `@CookieValue`	the same annotations as server controllers, now describing the request to send
`URI` parameter	override the full URL dynamically

Return types: a body type (`BookDto`, `List<BookDto>`), `ResponseEntity<T>`, `ResponseEntity<Void>`, `HttpHeaders`, `void`; on `WebClient`, also `Mono<T>`/`Flux<T>`. Errors surface as the same `HttpClientErrorException`/`HttpServerErrorException` as `RestClient`.

Boot 4 auto-configuration: `@ImportHttpServices`

Before Framework 7 / Boot 4 you created each proxy yourself. Now you declare **groups** of interfaces; each group gets its own `RestClient` configured from properties:

```java
@SpringBootApplication
@EnableResilientMethods                                    // for @Retryable (Framework 7)
@ImportHttpServices(group = "catalog", types = CatalogApi.class)   // creates a CatalogApi bean
public class ClientsApplication { ... }
```

```properties
# Boot 4: HTTP service client group "catalog" (the @HttpExchange interface)
spring.http.serviceclient.catalog.base-url=http://localhost:8080
spring.http.serviceclient.catalog.read-timeout=2s
spring.http.serviceclient.catalog.default-header.X-Client=handbook-ch06
# the group's RestClient sends the API version (from @GetExchange(version=...)) in this header
spring.http.serviceclient.catalog.apiversion.insert.header=X-API-Version
```

- `types = ...` lists interfaces; `basePackages`/`basePackageClasses` scans a package instead. Repeat the annotation for several groups (one per remote service).
- `clientType = WEB_CLIENT` makes a group use `WebClient`.
- For configuration beyond properties, declare a `RestClientHttpServiceGroupConfigurer` bean: `groups -> groups.filterByName("catalog").forEachClient((group, builder) -> builder.requestInterceptor(...))`.

Then inject and call it like any bean (`HttpInterfaceTest.java`):

```java
@Autowired CatalogApi catalogApi;     // generated by @ImportHttpServices + Boot auto-config

BookDto one = catalogApi.get(1);
ResponseEntity<BookDto> e = catalogApi.getEntity(2);
ResponseEntity<BookDto> created = catalogApi.create(new BookDto(null, "Accelerate", "Nicole Forsgren"));
String v2 = catalogApi.greetingV2();
```

Output:

```
bean class     -> $ProxyN
get(1)         -> BookDto[id=1, title=Release It!, author=Michael T. Nygard]
byAuthor(...)  -> [BookDto[id=2, title=Refactoring, author=Martin Fowler], BookDto[id=3, title=Patterns of Enterprise
Application Architecture, author=Martin Fowler]]
getEntity(2)   -> 200 OK server saw X-Client=handbook-ch06
create(...)    -> 201 CREATED BookDto[id=101, title=Accelerate, author=Nicole Forsgren]
greetingV2()   -> v2: hello
get(999)       -> NotFound
```

The bean is a JDK dynamic proxy (`$Proxy...`). `X-Client=handbook-ch06` shows the per-group `default-header` property reached the server, and `greetingV2()` shows the method's `version = "2.0"` was sent in the `X-API-Version` header configured for the group.

What Boot does for you, by hand

```
RestClient restClient = RestClient.builder().baseUrl(baseUrl()).build();
HttpServiceProxyFactory factory = HttpServiceProxyFactory
        .builderFor(RestClientAdapter.create(restClient)).build();
CatalogApi manual = factory.createClient(CatalogApi.class);
```

```
manual proxy get(3) -> Patterns of Enterprise Application Architecture
```

(`WebClientAdapter` does the same on `WebClient`.) Useful in plain Spring, in tests, or in libraries.

Trade-offs

	HTTP interface	Hand-written `RestClient` class	OpenFeign (Spring Cloud)
Boilerplate	minimal	more	minimal
Custom per-call logic (fallbacks, `Optional` on 404)	needs a wrapper or default methods	natural	via fallbacks (alternative answers on failure)
Dependencies	none beyond Spring	none	Spring Cloud OpenFeign (maintenance mode — bug fixes only; Spring recommends HTTP interfaces)
Config per remote service	`spring.http.serviceclient.<group>.*` (Boot 4)	your own properties	`spring.cloud.openfeign.client.config.*`
Can share the interface with the server?	technically, but couples client and server release cycles	—	same caveat

Common approach: an HTTP interface for the raw calls + a thin service class on top for domain translation (`Optional`, own exceptions, retries).

6.7 Client-side API versioning and retries

API versioning (Framework 7)

When the server versions its API (Chapter 5, section 5.9), the client must send the version. Framework 7 adds this to every client: an `ApiVersionInserter` decides *how* (header, query param, path segment, media-type parameter), `defaultApiVersion` sets the usual version, and each request can override it with `.apiVersion(...)`:

```
RestClient rest = builder.baseUrl(baseUrl())
        .apiVersionInserter(ApiVersionInserter.useHeader("X-API-Version"))  // how to send it
        .defaultApiVersion("1.0")                                           // unless overridden
        .build();
String v1 = rest.get().uri("/catalog/greeting").retrieve().body(String.class);
String v2 = rest.get().uri("/catalog/greeting").apiVersion("2.0").retrieve().body(String.class);
```

Output:

```
default version -> v1: hello
apiVersion(2.0) -> v2: hello
```

HTTP interfaces put the version on the method (`@GetExchange(version = "2.0")`) and configure the inserter per group (`spring.http.serviceclient.<group>.apiversion.insert.header=...`), as shown in 6.6. Server-side version properties (`spring.mvc.apiversion.*`) are **not** applied to clients; configure them separately.

Retries

What it is

A **retry** repeats a failed call hoping the failure was transient. Framework 7's `@Retryable` (Chapter 4, section 4.7) makes this one annotation:

```
@Service
public class StockService {
    private final RestClient rest;

    public StockService(RestClient.Builder builder, @Value("${catalog.base-url}") String baseUrl) {
        this.rest = builder.baseUrl(baseUrl).build();
    }

    @Retryable(includes = org.springframework.web.client.HttpServerErrorException.class,
               maxRetries = 3, delay = 20, multiplier = 2, jitter = 5)
    public String checkStock() {
        return rest.get().uri("/catalog/flaky").retrieve().body(String.class);
    }
}
```

With `maxRetries = 3` there are at most 4 HTTP calls. The `/catalog/flaky` endpoint answers 503 twice, then 200:

```
checkStock() -> ok on call 3
```

Rules for safe retries

1. **Only transient failures:** 5xx (especially 502/503/504), timeouts/`ResourceAccessException`, 429 (respect `Retry-After`). Never 400/401/403/404/409/422.
2. **Only idempotent operations** — GET, PUT, DELETE — or POSTs protected by an **idempotency key** header that the server uses to de-duplicate (the way payment APIs such as Stripe do).
3. **Exponential back-off + jitter** (growing waits plus a small random amount) so thousands of clients don't hammer a recovering service in sync.
4. **Bound the total time**: attempts × read timeout + delays must fit your own deadline (`@Retryable(timeout = ...)` since 7.0.2 caps the total).
5. **Retry in one layer only**, and combine with a **circuit breaker** (stops calling a failing service for a while; e.g. Resilience4j) so a dead dependency is not retried forever — see Chapter 16 and Retry pattern.
6. `@Retryable` is proxy-based: it must be on a Spring bean method called from **another** bean.

6.8 Testing clients

Option 1 — `@RestClientTest` + `MockRestServiceServer` (fast, no network)

`@RestClientTest` is a **test slice**: it starts only the listed components, Jackson and the `RestClient.Builder`/`RestTemplateBuilder` auto-configuration, and binds a `MockRestServiceServer` to the builder. Requests never leave the JVM; the mock checks each request against expectations and returns canned responses; `server.verify()` checks every expected request was made. Boot 4 dependency: `spring-boot-starter-restclient-test`.

```java
@RestClientTest(components = CatalogClient.class, properties = "catalog.base-url=http://catalog.test")
class CatalogClientMockServerTest {

    @Autowired CatalogClient client;
    @Autowired MockRestServiceServer server;   // intercepts requests; no network at all

    @Test
    void foundNotFoundAndUnavailable() {
        server.expect(requestTo("http://catalog.test/catalog/books/1"))
              .andExpect(method(HttpMethod.GET))
              .andExpect(header("X-Client", "catalog-client"))
              .andRespond(withSuccess("""
                     {"id":1,"title":"Release It!","author":"Michael T. Nygard","pages":376}""",
                     MediaType.APPLICATION_JSON));
        server.expect(requestTo("http://catalog.test/catalog/books/2"))
              .andRespond(withStatus(HttpStatus.NOT_FOUND));
        server.expect(requestTo("http://catalog.test/catalog/books/3"))
              .andRespond(withStatus(HttpStatus.SERVICE_UNAVAILABLE));

        System.out.println("mock 200 -> " + client.findBook(1));
        System.out.println("mock 404 -> " + client.findBook(2));
        assertThatThrownBy(() -> client.findBook(3))
                .isInstanceOf(CatalogUnavailableException.class)
                .satisfies(e -> System.out.println("mock 503 -> " + e.getMessage()));
        server.verify();                          // every expected request really happened
    }
}
```

Output:

```
mock 200 -> Optional[BookDto[id=1, title=Release It!, author=Michael T. Nygard]]
mock 404 -> Optional.empty
mock 503 -> catalog answered 503 for /catalog/books/3
```

The unknown `pages` field was ignored. By default expectations must occur **in order**; `MockRestServiceServer.bindTo(builder).ignoreExpectOrder(true)` relaxes that. `withException(new SocketTimeoutException())` simulates I/O failures.

Option 2 — a real HTTP server

Mocks can't catch problems in the real HTTP layer (timeouts, headers, encoding, the version header). This chapter's other tests start the app on a real port with a local "remote" controller:

```java
@SpringBootTest(webEnvironment = SpringBootTest.WebEnvironment.DEFINED_PORT)
abstract class LiveServerTest {

    static final int PORT = freePort();

    @DynamicPropertySource
    static void urls(DynamicPropertyRegistry registry) {
        String base = "http://localhost:" + PORT;
        registry.add("server.port", () -> PORT);
        registry.add("catalog.base-url", () -> base);
        registry.add("spring.http.serviceclient.catalog.base-url", () -> base);
    }
    ...
}
```

The port is picked **before** the context starts so the client base URLs can be set as properties (with `RANDOM_PORT` the port is only known after the clients were created). In real projects the "remote" side is usually a **WireMock** stub server (often via Testcontainers) or a Spring Cloud Contract stub (generated from an agreed API contract) — see Chapter 12.

For testing **your own** endpoints over HTTP, Boot 4 offers **`RestTestClient`** (`@AutoConfigureRestTestClient`), the `RestClient`-based successor of `TestRestTemplate` (which now needs `@AutoConfigureTestRestTemplate` and the `spring-boot-resttestclient` module).

6.9 `RestTemplate` and `WebClient` in brief

`RestTemplate` (legacy)

```
RestTemplate template = restTemplateBuilder.rootUri(baseUrl()).build();
BookDto viaTemplate = template.getForObject("/catalog/books/{id}", BookDto.class, 2);

RestClient wrapped = RestClient.create(template);     // migration step: reuse its config
BookDto viaWrapped = wrapped.get().uri("/catalog/books/{id}", 2).retrieve().body(BookDto.class);
```

```
RestTemplate  -> BookDto[id=2, title=Refactoring, author=Martin Fowler]
RestClient.create(template) -> BookDto[id=2, title=Refactoring, author=Martin Fowler]
```

Boot auto-configures a `RestTemplateBuilder` (not a `RestTemplate`). Migration map:

`RestTemplate`	`RestClient`
`getForObject(url, T.class, vars)`	`get().uri(url, vars).retrieve().body(T.class)`
`getForEntity(...)`	`get().uri(...).retrieve().toEntity(T.class)`
`postForEntity(url, body, T.class)`	`post().uri(url).body(body).retrieve().toEntity(T.class)`
`exchange(url, method, entity, T.class)`	`method(m).uri(url).headers(...).body(...).retrieve().toEntity(T.class)`
`setErrorHandler(...)`	`defaultStatusHandler(...)`
interceptors / request factory	reused as-is (`requestInterceptor`, `requestFactory`)

Steps: (1) wrap existing templates with `RestClient.create(restTemplate)` or `RestClient.builder(restTemplate)` so configuration is reused; (2) rewrite call sites; (3) move shared config to a `RestClientCustomizer` / builder; (4) remove the templates.

`WebClient` (reactive) — not run here

```
WebClient web = webClientBuilder.baseUrl("https://catalog.example.com").build();
Mono<BookDto> book = web.get().uri("/catalog/books/{id}", 1)
        .retrieve()
        .bodyToMono(BookDto.class)
        .timeout(Duration.ofSeconds(2));
```

Same shape as `RestClient`, but returns `Mono`/`Flux` and never blocks a thread. Use it in WebFlux apps or for streaming; don't call `.block()` inside a reactive pipeline. Full coverage in Chapter 13.

6.10 Common mistakes, real-world examples, interview

Common mistakes

Mistake	Consequence	Fix
New `RestClient` per request	loses connection pooling, slower, more sockets	build once, reuse
`RestClient.create()` in a Boot app	no Boot converters/timeouts/observability	inject `RestClient.Builder`
No timeouts	thread pile-up, cascading failure	`spring.http.clients.*-timeout` or per-group/per-client settings
String-concatenated URLs	broken encoding, injection (attacker text changing the URL's meaning)	URI templates / `UriBuilder`
Using `exchange()` and expecting status handlers	errors silently treated as success	handle statuses yourself or use `retrieve()`
Retrying POSTs / 4xx	duplicate orders, wasted calls	retry only idempotent + transient
Leaking `HttpClientErrorException` into business code	HTTP details spread everywhere	translate at the client edge
Mock-only tests	real HTTP issues missed	add a test against a real/stub server

Real-world examples

- **Payment integration**: a `PaymentsApi` HTTP interface for the provider, read timeout ~5 s, retries only for GETs and for POSTs carrying an `Idempotency-Key`, errors mapped to `PaymentDeclined` vs `PaymentProviderUnavailable`.
- **Microservice calls** inside a company: one `@ImportHttpServices` group per downstream service (`inventory`, `pricing`, `shipping`) each with its own base URL and timeouts from config, tracing headers propagated automatically.
- **Third-party APIs with versions** (e.g. APIs that version by header or date): a default API version on the client, bumped deliberately after testing.

In the interview

Q: Which HTTP client would you use in a new Spring Boot 4 MVC service, and why? 30-second answer: "`RestClient` — or an `@HttpExchange` interface backed by it. It's the modern synchronous client: fluent, uses Boot's auto-configured converters, HTTP library, timeouts and observability. `RestTemplate` is being deprecated (formally in 7.1, removal in 8.0), and `WebClient` is for reactive stacks. With virtual threads, blocking calls are cheap enough that I don't need reactive just for concurrency."

- *How do HTTP interfaces get implemented?* → `HttpServiceProxyFactory` creates a JDK dynamic proxy; in Boot 4 `@ImportHttpServices` registers groups and `spring.http.serviceclient.<group>.*` configures each group's client.
- *How do you handle errors?* → `retrieve()` throws `HttpClientErrorException`/`HttpServerErrorException` (with nested per-status types) and `ResourceAccessException` for I/O/timeouts; I map them to domain exceptions with `onStatus`/`defaultStatusHandler` and read `ProblemDetail` bodies with `getResponseBodyAs`.
- *What timeouts do you set?* → Connect and read timeouts on every client (`spring.http.clients.connect-timeout/read-timeout` or per group), sized from downstream p99 and my own SLA (the response time/availability promised to my callers).

Q: How do you make remote calls resilient? → Timeouts, retries with exponential back-off + jitter only for idempotent/transient failures (`@Retryable` in Framework 7), circuit breaker + bulkhead (Resilience4j / `@ConcurrencyLimit`), fallbacks where acceptable, and idempotency keys for writes.

Q: How do you test a REST client? → `@RestClientTest` + `MockRestServiceServer` for fast request/response contract checks; plus an integration test against a real stub server (WireMock) or the provider's contract stubs for the HTTP layer.

6.11 Chapter TL;DR

- **Clients:** `RestClient` (sync, recommended) · HTTP interfaces `@HttpExchange` (declarative, on `RestClient` or `WebClient`) · `WebClient` (reactive) · `RestTemplate` (legacy; deprecated from 7.1, removed in 8.0).
- **Boot 4:** add `spring-boot-starter-restclient`; inject the **prototype** `RestClient.Builder`; build once, reuse (thread-safe).
- **Calls:** `get().uri(template, vars).retrieve().body(T)` / `toEntity(T)` / `toBodilessEntity()`; `ParameterizedTypeReference` for generics; `exchange()` for raw control (**status handlers not applied**).
- **Errors:** 4xx → `HttpClientErrorException.*`, 5xx → `HttpServerErrorException.*`, I/O/timeouts → `ResourceAccessException`; `getResponseBodyAs(ProblemDetail.class)`; translate with `onStatus`/`defaultStatusHandler`.
- **Timeouts:** `spring.http.clients.connect-timeout`/`read-timeout` (Boot 4 names), per group `spring.http.serviceclient.<g>.read-timeout`, or `ClientHttpRequestFactoryBuilder` + `HttpClientSettings`. Library order: Apache → Jetty → Reactor Netty → JDK → simple.
- **HTTP interfaces in Boot 4:** `@ImportHttpServices(group = "...", types = ...)` + `spring.http.serviceclient.<group>.base-url/default-header/apiversion.*`; customise with `RestClientHttpServiceGroupConfigurer`.
- **Versioning (Framework 7):** `ApiVersionInserter.useHeader(...)` + `defaultApiVersion(...)`, per-request `.apiVersion(...)`, `@GetExchange(version = ...)`.
- **Retries:** `@Retryable` for transient + idempotent calls only, with back-off, jitter and a total budget; add a circuit breaker.
- **Tests:** `@RestClientTest` + `MockRestServiceServer`; real/stub server tests for the HTTP layer; `RestTestClient` for your own endpoints.
- Next: Chapter 7 — Data access with JDBC and transactions.