Chapter 4 — Images, Media and Embeds

Photos, logos, charts, podcasts, videos, maps and payment widgets (self-contained interactive components, often from another company) are "media": non-text content, usually in its own file. HTML's elements for them — `<img>`, `<picture>`, `<figure>`, `<audio>`, `<video>`, `<track>`, `<iframe>` (a window showing another page), `<svg>` (vector drawings) and `<canvas>` (a JavaScript drawing surface) — each carry accessibility, performance and security rules beginners miss.

Media is also most of a page's weight (download size): images are typically the largest share of bytes, and the biggest image above the fold (visible without scrolling) often decides how fast the page *feels* — the **Largest Contentful Paint** (LCP, Chapter 14). So this chapter is as much about "which file is downloaded, and when" as about markup.

In this chapter: 4.1 `<img>` · 4.2 Image formats (with real file sizes) · 4.3 Responsive images: `srcset`, `sizes`, `<picture>` · 4.4 Loading hints · 4.5 `<figure>` · 4.6 Audio and video, WebVTT captions · 4.7 `<iframe>` and `sandbox` · 4.8 SVG basics · 4.9 `<canvas>` · 4.10 Choosing the right element.

How the examples work. Every example is a real file in `code/`, with no network access: pictures, the audio beep and the video were generated by `code/make_assets.py` (Python + Pillow, an image library) and `code/make_video.mjs` (headless Chrome records an animated canvas). Screenshots are headless Chrome at 900 CSS px wide and device pixel ratio 2 (a "Retina"-style high-density screen; terms defined in §4.3). `format_sizes.mjs` and `srcset_pick.mjs` print the outputs shown.

4.1 The `<img>` element

What it is

`<img>` embeds a picture. It is a **void element** (no closing tag or content) and a **replaced element**: its box is replaced by an external resource (the image file) whose content CSS cannot style from inside.

Why it matters

- Images carry meaning (a chart, a product). Screen-reader users, people whose images failed on a slow connection, and search engines get only the `alt` text.
- Images without known dimensions make the page jump as they load (**layout shift**), hurting the Core Web Vital **CLS** (Core Web Vitals = Google's three headline page-experience metrics; CLS, Cumulative Layout Shift, scores how much content jumps).

How it works

Attribute	Required?	What it does
`src`	yes	Image URL (relative `media/a.jpg` or absolute `https://…`).
`alt`	yes, in practice	Text alternative: shown on failure, read by screen readers, indexed by search. `alt=""` = decorative.
`width`, `height`	strongly recommended	Intrinsic (natural) size in CSS pixels, **no units** (`width="800"`). Lets the browser reserve space before the file arrives.
`srcset`, `sizes`	optional	Candidate files for different screens (4.3).
`loading`, `decoding`, `fetchpriority`	optional	Loading hints (4.4).

1. The parser meets `<img>` and (unless lazy) starts downloading immediately — even before CSS is ready; the **preload scanner** (a fast look-ahead over raw HTML) finds images early.
2. From `width` / `height` the browser derives the **aspect ratio** (width ÷ height; its built-in stylesheet effectively applies `aspect-ratio: auto <width> / <height>`), so it reserves a correctly shaped box even when CSS makes the image fluid.

3. Bytes arrive, are decoded (decompressed to raw pixels) and painted into the box.
4. On failure the browser shows a broken-image indicator plus the `alt` text.

Standard CSS so images shrink with their container but never stretch:

```
img { max-width: 100%; height: auto; }   /* fluid width, height follows the aspect ratio */
```

`height: auto` matters: without it the HTML `height="533"` keeps the image 533 px tall while the width shrinks, squashing it. The attributes don't stop an image being responsive — CSS overrides the displayed size; the attributes still supply the ratio.

```
<!-- code/01_img_basics.html (excerpt) -->
<figure>
  <img src="media/hills-800.jpg" alt="Two green hills under a blue sky with a yellow sun"
       width="800" height="533">
  <figcaption>Figure 1 — JPEG, 800x533. width/height reserve the space before it loads.</figcaption>
</figure>
<img src="media/logo.png" alt="HC" width="80" height="80">
<img src="media/logo.svg" alt="" width="80" height="80">   <!-- decorative duplicate -->

<!-- three images whose file is missing -->
<img src="media/does-not-exist.jpg" alt="Sales chart: revenue up 12% in Q3" width="200" height="120">
<img src="media/does-not-exist.jpg" alt="image123.jpg" width="200" height="120">
<img src="media/does-not-exist.jpg" width="200" height="120">
```




Figure 4.1 — When the file is missing, only the first broken image still communicates anything.

Writing alt text — a decision list

The full decision list is in §3.5. The essentials: describe the *information*, not the pixels (`alt="Revenue rose 12% in Q3"`, not `"bar chart"`); for a linked/button image describe the action or destination (magnifier in a search button → `alt="Search"`; a logo linking home → `alt="Acme home"`); decorative or repeating nearby text → `alt=""` (empty, not missing — missing makes many screen readers read the file name), or better, put decoration in CSS `background-image`; complex images get a short alt plus full text nearby; never start with "image of".

Common mistakes

- Omitting `width` / `height` → content jumps when the image loads.
- Units in the attributes (`width="800px"`) — they take plain integers.
- CSS `width` without `height: auto` → distorted images.

- Keyword-stuffed or file-name alt text.
- A 4000-px camera photo in a 300-px slot (fixed by 4.3).

In the interview

> **30-second answer:** "`<img>` is a void, replaced element. `src` and `alt` are required in practice; `alt` conveys the image's purpose and is empty for decoration. Always set `width` and `height` so the browser knows the aspect ratio and reserves space, preventing layout shift, and use `max-width: 100%; height: auto` for fluid images."

- *`alt=""` vs no alt?* → Empty says "decorative, skip it"; missing is an error, and assistive tech may read the URL.
- *CSS background image or `<img>`?* → `<img>` for content (alt, indexable, responsive via srcset); backgrounds for decoration.

4.2 Image formats — JPEG, PNG, GIF, WebP, AVIF, SVG

What it is

Raster formats store a grid of pixels (JPEG, PNG, GIF, WebP, AVIF). **Vector** formats store drawing instructions ("circle here, radius 40"), so they scale without blur (SVG). **Lossy compression** discards detail the eye is unlikely to notice for much smaller files (JPEG, lossy WebP, AVIF); **lossless** keeps every pixel exactly (PNG, GIF, lossless WebP/AVIF).

Comparison table

Format	Type	Compression	Transparency	Animation	Best for	Browser support
JPEG (`.jpg`)	raster	lossy	no	no	photos, as the one universal format	everywhere
PNG	raster	lossless	yes (alpha channel: per-pixel see-through level)	no (APNG, animated PNG, exists)	screenshots, UI, logos with transparency, sharp text	everywhere
GIF	raster	lossless, 256 colours max	1-bit (on/off)	yes	legacy animations — prefer video or WebP/AVIF	everywhere
WebP	raster	lossy or lossless	yes	yes	general JPEG/PNG replacement	all modern browsers (Safari since 2020)
AVIF	raster	lossy or lossless	yes	yes	smallest photo files; HDR (high dynamic range)/wide colour	Baseline 2024 (widely available since July 2026)
SVG	vector	text (XML, a tag-based format like HTML)	yes	yes (CSS/SMIL, SVG's own animation tags)	icons, logos, illustrations, simple charts	everywhere

("Baseline" = works in current Chrome, Edge, Firefox and Safari — §1.1.)

Real numbers

`make_assets.py` saved the same 800×533 picture in four formats (JPEG q80, WebP q80, AVIF q60, optimised PNG) — once as a flat graphic, once with photo-like grain. `code/format_sizes.mjs` prints the sizes:

```
hills-800  (flat graphic)
  png       8.8 KB    100% of PNG
  jpg      19.1 KB    216% of PNG
  webp      7.4 KB     84% of PNG
  avif      4.3 KB     48% of PNG
photo-800  (photo-like grain)
  png     508.2 KB    100% of PNG
  jpg     106.8 KB     21% of PNG
  webp    106.3 KB     21% of PNG
  avif     73.7 KB     14% of PNG
```




Figure 4.2 — Visually identical at this size; the byte counts are not.

1. **Content decides the winner.** For a flat graphic, lossless PNG (8.8 KB) beats JPEG (19.1 KB): lossless compression is very efficient on large same-colour areas, while JPEG (which compresses in 8×8-pixel blocks) wastes bytes on blocky artefacts around sharp edges. For a photo, PNG is 5× bigger than JPEG.
2. **AVIF was smallest in both cases**; WebP roughly equal or better than the older format. Savings vary per image and quality — measure your own.
3. Vector-like artwork as SVG is often smaller still and sharp at any size (4.8).

How to choose (quick rules)

1. Icon, logo, flat illustration → **SVG**.
2. Photo → **AVIF** (or WebP) with a **JPEG** fallback via `<picture>` (4.3).
3. Screenshot or graphic needing transparency / exact pixels → **PNG** or lossless WebP.
4. Short animation → a muted, looping `<video>` (MP4/WebM) is usually far smaller than a GIF (or animated WebP/AVIF).

Common mistakes

- Photos as PNG "for quality" — huge files, no visible benefit.
- Logos as JPEG — fuzzy edges, no transparency.
- AVIF with no fallback when old devices matter.
- Re-compressing a JPEG repeatedly (quality degrades each time).

Real-world examples

Image CDNs (content delivery networks that store copies worldwide and convert images on the fly — Cloudinary, imgix, Cloudflare Images, Next.js `<Image>`; System Design Fundamentals) read the browser's `Accept` header (the file types it understands) and serve AVIF or WebP when supported, else JPEG.

4.3 Responsive images — `srcset`, `sizes` and `<picture>`

The problem it solves

A 360-px phone doesn't need the 1600-px hero (top-of-page banner) a desktop does — but a phone with three physical pixels per CSS pixel *does* need more pixels than its CSS width suggests. One `src` can't fit everyone. Three needs:

1. **Resolution switching** — same picture, different sizes; the browser downloads the smallest file that's still sharp (`srcset` + `sizes` on `<img>`).
2. **Art direction** — a *different crop or picture* per layout (wide landscape on desktop, tight square on phones); you decide (`<picture>` + `<source media>`).
3. **Format switching** — AVIF/WebP where supported, JPEG elsewhere (`<picture>` + `<source type>`).

- **CSS pixel** — the unit CSS lengths use; roughly one pixel of a traditional 96-dpi screen.
- **Device pixel ratio (DPR)** — physical pixels per CSS pixel (`window.devicePixelRatio`): 1 on older monitors, 2 on Retina laptops, often 3 on phones.

How it works — density descriptors (`x`)

For a **fixed display size**, list files by density:

```
<img srcset="media/hills-400.jpg 1x, media/hills-800.jpg 2x"
     src="media/hills-400.jpg" alt="Hills at sunrise" width="200" height="133">
```

DPR 1 takes `1x`; DPR 2+ takes `2x`; `src` is the fallback for very old browsers.

How it works — width descriptors (`w`) + `sizes`

For a size that **changes with the layout**, give each file's real pixel width with `w`, and the displayed width with `sizes`:

```
<img srcset="hills-400.jpg 400w, hills-800.jpg 800w, hills-1600.jpg 1600w"
     sizes="(max-width: 600px) 100vw, (max-width: 1000px) 50vw, 400px"
     src="hills-800.jpg" alt="Hills at sunrise" width="800" height="533">
```

1. **Evaluate** `sizes` left to right: each entry is `(media condition) length` (a media condition tests the screen, e.g. `(max-width: 600px)` = viewport at most 600 px wide); the first match wins; the last, condition-less entry is the default. Result: the **slot width** in CSS px (`vw` = 1 % of the **viewport**, the visible window area).
2. **Why `sizes`?** The browser picks the image while still downloading the HTML, *before* CSS and layout exist — waiting would delay every image. `sizes` is your promise about the layout; without it, a `w` srcset assumes `100vw`.
3. **Each candidate's density** = file width ÷ slot width (`800w` in a 400-px slot = 2x).
4. **Pick** a candidate with density ≥ DPR — typically the smallest sharp-enough one. The spec lets browsers deviate (e.g. reuse a larger cached file, or save data on a slow connection).

`code/srcset_pick.mjs` models this rule (first matching `sizes` entry → slot; smallest candidate with `w / slot ≥ dpr`, else the largest):

```
sizes = "(max-width: 600px) 100vw, (max-width: 1000px) 50vw, 400px"
viewport  dpr  slot(CSS px)  needs(px)  chosen
     360  1x           360        360  hills-400.jpg
     360  2x           360        720  hills-800.jpg
     360  3x           360       1080  hills-1600.jpg
     768  1x           384        384  hills-400.jpg
     768  2x           384        768  hills-800.jpg
     768  3x           384       1152  hills-1600.jpg
    1280  1x           400        400  hills-400.jpg
    1280  2x           400        800  hills-800.jpg
    1280  3x           400       1200  hills-1600.jpg
```

The biggest file goes to the DPR-3 *phone*, not the desktop — physical pixels, not screen size, decide.

How it works — `<picture>`

`<picture>` wraps any number of `<source>`s and one `<img>`. The browser walks sources **in order** and uses the **first** whose `media` matches and whose `type` it supports; else the `<img>`. The `<img>` is always required: it's what is displayed, and it carries `alt`, `width`, `height`, `loading` for all sources. (An art-directed crop of a different shape can carry its own `width`/`height` on the `<source>`.)

```
<!-- code/03_responsive_images.html (excerpt) -->
<picture>
  <!-- art direction: narrow screens get a square crop -->
  <source media="(max-width: 600px)" srcset="media/hills-square-600.jpg">
  <!-- format switching: best format the browser can decode -->
  <source type="image/avif" srcset="media/hills-800.avif">
  <source type="image/webp" srcset="media/hills-800.webp">
  <img src="media/hills-800.jpg" alt="Hills at sunrise" width="800" height="533">
</picture>
```

The demo prints `img.currentSrc` — the file actually chosen (also visible in DevTools' Network panel):




Figure 4.3 — 900 px wide, DPR 2. A: slot 300 px × 2 = 600 px needed → the 800w file. B: DPR 2 → the `2x` file. C: no media match, AVIF supported → AVIF.




Figure 4.4 — At 420 px only `<picture>` (C) changed crop, because `(max-width: 600px)` now matches; A and B still pick by density.

Trade-offs

Need	Use	Who decides?
Fixed-size image, sharp on high-DPR screens	`srcset` with `1x, 2x`	browser
Fluid image, many screen sizes	`srcset` with `w` + `sizes`	browser
Different crop/composition per layout	`<picture>` + `<source media>`	you
Modern format with fallback	`<picture>` + `<source type>`	browser (by support)

Common mistakes

- `w` **descriptors without** `sizes` — assumed 100vw, so far-too-big files for small slots.
- `sizes` that lie (`sizes="100vw"` for a sidebar thumbnail).
- `alt` on `<source>` — it belongs on the `<img>`.
- `<picture>` just for resolution switching — plain `srcset` lets the browser choose smarter.
- Mixing `x` and `w` in one `srcset` (invalid).

When not to use it

Icons and SVGs don't need `srcset` (vectors are always sharp). For background images use CSS `image-set()` (Chapter 10).

In the interview

30-second answer: "`srcset` lists candidate files: `x` descriptors for fixed-size images, `w` descriptors plus `sizes` for fluid ones. `sizes` gives the display width before CSS loads; the browser divides each file's width by it to get density and picks one dense enough for the device pixel ratio. `<picture>` is for when *I* control the choice — art direction with `media`, format fallbacks with `type`; its `<img>` child is mandatory and carries alt and dimensions. If two sources match, the first wins."

Self-check

1. Viewport 768 px, DPR 2, `sizes="(max-width: 1000px) 50vw, 400px"` — slot and needed pixels? → 384 CSS px; 768 device px → the 800w file.

4.4 Loading hints — `loading`, `decoding`, `fetchpriority`

What they are

Hints that change *when* and *how urgently* an image is fetched or decoded — the page works without them, loads faster with them.

Attribute	Values	Effect
`loading`	`eager` (default), `lazy`	`lazy` defers fetching until near the viewport. Also works on `<iframe>`.
`fetchpriority`	`high`, `low`, `auto` (default)	Raises/lowers download priority relative to other images. Baseline since Oct 2024.
`decoding`	`sync`, `async`, `auto` (default)	Whether decoding may happen off the main rendering step (not holding up drawing the rest). Rarely needed.

Native lazy loading for images and iframes has been Baseline since December 2023 (Firefox 121 was last, for iframes; images worked everywhere earlier) — no JS library needed for the basic case.

How it works

1. Browsers check each lazy element's distance to the viewport with a generous margin (a screen or more), so images normally arrive before the user scrolls to them.
2. Lazy images do **not** delay the window `load` event (they may never be fetched).
3. Lazy loading happens only with JavaScript enabled — a privacy measure, since otherwise image requests would reveal scroll position even with JS off.
4. `fetchpriority="high"` moves an image up the download queue — for the one image that is the page's LCP element (e.g. the main product photo).

```
<!-- code/04_lazy_loading.html (excerpt) -->
<img id="hero" src="media/hills-400.jpg" alt="Hero: hills at sunrise" width="400" height="267"
     fetchpriority="high">                                  <!-- above the fold -->
<img id="lazy1" class="far" src="media/photo-800.jpg" alt="Grainy hills"
     width="400" height="267" loading="lazy">               <!-- 3000 px lower -->
<img id="lazy2" src="media/hills-1600.jpg" alt="Large hills"
     width="400" height="267" loading="lazy">
<script>
  addEventListener('load', () => {
    report.textContent = 'after the load event:\n' + [...document.images]
      .map(i => `${i.id.padEnd(6)} ${(i.getAttribute('loading') || '(none)').padEnd(6)} ${i.naturalWidth ?
'LOADED' : 'not loaded yet'}`)
      .join('\n');
  });
</script>
```




Figure 4.5 — At `load`, only the hero was downloaded; the two lazy images (~660 KB) were never fetched.

Common mistakes

- **Lazy-loading the hero / LCP image** — it waits for layout, delaying the most important paint. Never lazy-load above the fold.
- Lazy images without `width`/`height` — they start 0×0, the page jumps, and the browser misjudges which are near the viewport.
- `fetchpriority="high"` on many images: if everything is high, nothing is.

4.5 `<figure>` and `<figcaption>`

What it is

`<figure>` groups **self-contained content referenced from the main text** — image, diagram, code listing, quotation, table — and `<figcaption>` (first or last child) captions it; the caption becomes the figure's accessible name. Test: could it move to an appendix with the text saying "see Figure 3"? Then it's a figure. (Example markup in §4.1.)

Caption vs alt

The **alt** *replaces* the image for people who can't see it; the **caption** *adds* context for everyone. Don't copy one into the other (a screen reader reads it twice). If the caption fully describes the image, a short alt is fine.

Common mistakes

- Wrapping *every* image in `<figure>` (decorative images and icons aren't figures).
- A `<p>` or `<div class="caption">` instead of `<figcaption>` — the association is lost for assistive technology.

4.6 Audio and video — `<audio>`, `<video>`, `<source>`, `<track>`

What it is

`<audio>` and `<video>` play media natively — no plugins (add-ons like the old Flash player). Both are **media elements** sharing one JavaScript API: `play()`, `pause()`, `currentTime`, `volume`, events like `play`, `ended`, `timeupdate`.

How it works

1. The browser reads `<source>` children **in order** and picks the first whose `type` (MIME type such as `video/webm`, optionally with codecs — the compression methods inside) it can play. (Safari 17.4+ may pick the best supported one instead.) Or use one `src` attribute.
2. Other content inside the element (e.g. a download link) is **fallback** for browsers without the element at all — *not* for unsupported formats.
3. `<track>` attaches timed text files in **WebVTT** (`.vtt`, first line `WEBVTT`) — captions, subtitles, descriptions, chapters.
4. Without `controls` there is no UI; you'd build your own with the JS API.

Attribute	Element	Meaning
`controls`	both	Built-in play/pause/volume/seek UI.
`autoplay`	both	Try to start immediately. Browsers block autoplay **with sound**; muted autoplay is generally allowed.
`muted`	both	Start muted (needed for autoplay).
`loop`	both	Restart at the end.
`preload`	both	`none` (nothing until play), `metadata` (duration/dimensions only), `auto` (may download all).
`poster`	video	Image shown before playback.
`playsinline`	video	On iPhone, play in the page instead of full-screen.
`width` / `height`	video	Reserve space (like `<img>`).

`<track>` attributes: `kind` (`subtitles` default, `captions`, `descriptions`, `chapters`, `metadata`), `src`, `srclang`, `label` (shown in the captions menu), `default`.

Captions vs subtitles. *Subtitles* translate dialogue for hearing viewers who don't know the language. *Captions* serve viewers who can't hear: dialogue **and** meaningful sounds ("[door slams]").

```
WEBVTT

00:00:00.000 --> 00:00:01.400
The sun rises on the left.

00:00:01.400 --> 00:00:03.000
[soft wind] It drifts to the right.
```

```
<!-- code/05_audio_video.html (excerpt) -->
<audio controls preload="metadata">
  <source src="media/tone.wav" type="audio/wav">
  <p>Your browser cannot play this audio. <a href="media/tone.wav">Download the WAV</a>.</p>
</audio>

<video controls preload="none" poster="media/poster.jpg" width="640" height="360">
  <source src="media/clip.webm" type="video/webm">
  <track kind="captions" src="media/captions.vtt" srclang="en" label="English" default>
  <p>Your browser cannot play this video. <a href="media/clip.webm">Download it</a>.</p>
</video>
```

A second demo video is seeked to 2.0 s by script and shows the matching cue. Gotcha: browsers refuse `<track>` files on `file://` pages (text tracks must be same-origin or served with CORS — headers by which a server lets other origins read its files), so the demo adds the same cues (timed caption lines) with the TextTrack API — `video.addTextTrack('captions', 'English', 'en').addCue(new VTTCue(1.4, 3.0, '…'))`. Over `http://` the `<track>` works as written.




Figure 4.6 — Native controls, a poster before playback, and a caption cue at t = 2 s.

Formats in practice

A **container** (MP4, WebM) wraps separately compressed video and audio streams, each with its own **codec** (coder–decoder).

Container	Typical codecs	Support
MP4	H.264 video + AAC audio	every browser — the safest single choice
WebM	VP9 or AV1 video + Opus audio	Chrome, Edge, Firefox, Safari (14.1+ on macOS, 17.4+ on iOS)
MP4	AV1 or HEVC (H.265)	varies by browser and hardware — always provide a fallback
MP3 / AAC / Opus / WAV	audio	MP3 and AAC everywhere; WAV is uncompressed (large)

List the smallest well-supported format first, MP4/H.264 last as the universal fallback, and always declare `type` so the browser skips formats without downloading them.

Accessibility and UX checklist

- Captions for every video with speech (WCAG 2.2 SC 1.2.2); a transcript for audio-only (1.2.1).
- No autoplay with sound; anything moving for more than 5 seconds must be pausable (2.2.2).
- `poster` and dimensions on `<video>` so the page doesn't jump.
- Big sites stream with **adaptive bitrate** (HLS or DASH switch quality with bandwidth) via Media Source Extensions (an API letting JS feed video data into `<video>` piece by piece) — `<video src="file.mp4">` downloads one fixed-quality file. YouTube and Netflix work this way.

Common mistakes

- `autoplay` without `muted` (and `playsinline` on iOS) — browser autoplay policies block it.
- Expecting the fallback paragraph for an unsupported *format*.
- A 50 MB unoptimised "background video"; `preload="auto"` on a page of many videos.

Real-world examples

Social feeds replace GIFs with `<video autoplay muted loop playsinline>` — the MP4 is typically a fraction of the GIF size.

In the interview

> **30-second answer:** "`<video>` / `<audio>` with `controls`, multiple `<source>`s with `type` so the browser picks a playable format, and `<track kind="captions">` with WebVTT for accessibility. Autoplay only works muted; add `playsinline` for iOS. For large video, use adaptive streaming (HLS/DASH), not one big file."

4.7 Embedding other pages — `<iframe>`

What it is

An `<iframe>` (inline frame) shows **another complete HTML document** in a rectangle of your page, with its own DOM, CSS, JS and **browsing context** (its own document, history, scripts). If it's from another **origin** (scheme + host + port), the **same-origin policy** stops the two pages reading each other's data.

Uses: YouTube/Vimeo players, maps, payment fields (Stripe, Adyen host card inputs in iframes so card numbers never touch your page), social posts, ads, code playgrounds.

Why it matters

You're putting someone else's code in your page — and iframes are how attackers do **clickjacking**: loading *your* site invisibly inside theirs to trick users into clicking. Both directions need controls.

How it works — key attributes

Attribute	Purpose
`src`	URL of the embedded document.
`srcdoc`	Inline HTML instead of `src` (previews, sandboxed user content).
`title`	**Required for accessibility**: announced so users know what the frame contains.
`width`, `height`	Size (default 300×150).
`loading="lazy"`	Defer off-screen frames — a big win for video and map embeds.
`sandbox`	Extra restrictions (below).
`allow`	Permissions policy: which powerful features the frame may use, e.g. `allow="fullscreen; camera; geolocation"`.
`referrerpolicy`	How much of your URL to send as `Referer`, e.g. `no-referrer`.

`sandbox`. An empty `sandbox` turns *everything* off — scripts, forms, pop-ups, plugins, top-level navigation (changing the whole tab's address) — and gives the content a unique **opaque origin** (so it can't read its real origin's cookies/storage). Add back only what's needed: `allow-scripts`, `allow-forms`, `allow-popups`, `allow-same-origin`, `allow-modals`, `allow-downloads`, `allow-top-navigation-by-user-activation`.

> Warning: `allow-scripts` + `allow-same-origin` on a document from **your own origin** lets its script reach into the parent and remove the sandbox — the sandbox becomes meaningless. Use that pair only for content from a different origin.

The demo loads one small document (via `srcdoc`) into three frames; its script writes "allowed" if it ran, then tries to read the parent's title:

```
<!-- code/06_iframe.html (excerpt) -->
<iframe class="widget" title="Widget without sandbox"></iframe>
<iframe class="widget" sandbox title="Widget, fully sandboxed"></iframe>
<iframe class="widget" sandbox="allow-scripts" title="Widget, scripts only"></iframe>

<!-- inside each frame -->
<script>
  document.querySelector('#js span').textContent = 'allowed (set by JS)';
  let parentTitle;
  try { parentTitle = window.parent.document.title; }
  catch (e) { parentTitle = 'blocked (' + e.name + ')'; }
</script>
```




Figure 4.7 — `srcdoc` content shares the parent's origin, so unsandboxed it reads the parent. `sandbox` blocks scripts; `allow-scripts` lets them run in an opaque origin (no `allow-same-origin`), so touching the parent throws `SecurityError`.

The other direction: stopping others from framing *you*

Your server decides who may embed your pages via HTTP response headers:

- `Content-Security-Policy: frame-ancestors 'self'` (modern; can list allowed sites), or
- the older `X-Frame-Options: DENY` / `SAMEORIGIN`.

Banks and login pages send these against clickjacking — which is why some sites show an error inside an iframe.

`<embed>` and `<object>`

Old elements for plugin content (Flash, Java applets — both gone). Today mostly used for PDFs, where an `<iframe>` or plain link is usually better. Don't use them for new work.

Common mistakes

- No `title`.
- Heavy third-party embeds (video, maps, chat) loaded eagerly — each can pull megabytes of script. Use `loading="lazy"` or a "click to load" placeholder (**facade**).
- `sandbox="allow-scripts allow-same-origin"` on same-origin untrusted content.
- Iframes for your own page layout (a 1990s pattern) — breaks URLs, history, accessibility.

In the interview

> **30-second answer:** "An iframe embeds another document with its own browsing context; cross-origin frames are isolated by the same-origin policy. I always add a `title`, lazy-load off-screen embeds, restrict untrusted content with `sandbox` plus only the needed tokens, and use `allow` for permissions. To stop my site being framed — clickjacking — I send `Content-Security-Policy: frame-ancestors`."

- *Why do payment providers use iframes?* → The card field lives on their origin, so the merchant page (and any malicious script on it) can't read the card number — which also shrinks the merchant's PCI DSS scope (the card industry's security standard; less card data touched, fewer rules apply).

4.8 SVG basics

What it is

SVG (Scalable Vector Graphics) is an XML language for 2-D vector drawings: shapes, not pixels, so razor-sharp at any zoom and tiny for icons and logos. Use it **inline** (part of the DOM — CSS and JS can style and animate each shape), as a file via `<img src="x.svg">`, or in CSS (`background-image: url(x.svg)`).

How it works

1. **Coordinates.** `viewBox="minX minY width height"` defines internal coordinates: `viewBox="0 0 200 120"` → x 0→200, y 0→120, **y pointing down**. `width`/`height` (or CSS) set the displayed size; the viewBox scales to fit (preserving aspect ratio by default).
2. **Shapes.** `<rect x y width height rx>`, `<circle cx cy r>`, `<ellipse>`, `<line x1 y1 x2 y2>`, `<polyline>`/`<polygon points="x,y x,y …">`, `<text>`.
3. **Paths.** `<path d="…">`: `M x y` move, `L` line, `H`/`V` horizontal/vertical line, `C` cubic Bézier (a smooth curve shaped by two "pull" points), `Q` quadratic (one pull point), `T` smooth quadratic continuation, `A` arc, `Z` close. Upper-case = absolute, lower-case = relative.
4. **Painting.** `fill`, `stroke`, `stroke-width` — also CSS properties.
5. **Reuse.** Define once with `<symbol id="…" viewBox="…">`, place copies with `<use href="#id"/>`.

6. **`currentColor`.** `fill` / `stroke="currentColor"` takes the surrounding text colour, so one icon works on a green button and a red one (set CSS `color` on each).

```svg
<!-- code/07_svg.html (excerpt) -->
<svg width="200" height="120" viewBox="0 0 200 120" role="img" aria-labelledby="t1">
  <title id="t1">Basic SVG shapes</title>
  <rect x="10" y="10" width="60" height="40" rx="6" fill="#6c5ce7"/>
  <circle cx="110" cy="30" r="20" fill="#fdcb6e" stroke="#e17055" stroke-width="4"/>
  <line x1="150" y1="10" x2="190" y2="50" stroke="#2d3436" stroke-width="3"/>
  <polygon points="10,110 40,70 70,110" fill="#00b894"/>
  <path d="M90 80 Q 120 40 150 80 T 190 80" fill="none" stroke="#0984e3" stroke-width="3"/>
</svg>

<!-- same viewBox, half the display size: still sharp -->
<svg width="100" height="60" viewBox="0 0 200 120" aria-hidden="true">…</svg>

<!-- icon sprite + currentColor -->
<svg width="0" height="0" style="position:absolute">
  <symbol id="check" viewBox="0 0 24 24">
    <path d="M4 12l5 5L20 6" fill="none" stroke="currentColor" stroke-width="3"/></symbol>
</svg>
<button><svg class="icon" aria-hidden="true"><use href="#check"/></svg>Save</button>

<img src="media/logo.svg" alt="HC logo" width="60" height="60">
```




Figure 4.8 — Shapes and a path; the same drawing scaled down; one icon coloured per button via `currentColor`; an SVG file as `<img>`.

Inline SVG vs `<img src="x.svg">`

	Inline `<svg>`	`<img src="x.svg">` / CSS background
Style parts with page CSS / animate with JS	yes	no (a closed image)
`currentColor` follows the text colour	yes	no
Cached separately	no (part of the HTML)	yes
Scripts inside the SVG run	yes — never inline untrusted SVG	no (scripts and external resources disabled)
Accessibility	`role="img"` + `<title>` / `aria-label`, or `aria-hidden="true"` if decorative	`alt` like any image

Common mistakes

- No `viewBox` → the drawing gets cropped instead of scaling.
- Icon-only buttons whose icon is neither hidden nor accompanied by text → no accessible name.
- Inlining user-uploaded SVG — it can contain `<script>` (an **XSS**, cross-site scripting, risk). Serve it through `<img>` or sanitise it.
- Design-tool exports full of editor metadata — run them through an optimiser such as SVGO.

4.9 `<canvas>` — an introduction

What it is

`<canvas>` is a blank bitmap that JavaScript paints via a drawing API — the 2D context (`getContext('2d')`) or WebGL/WebGPU (GPU-accelerated, for 3-D). Afterwards it holds only **pixels**, not shapes: there's no DOM node for "bar 3", so to change something you redraw.

How it works

1. The `width` / `height` **attributes** size the drawing buffer (default 300×150). CSS sizes only stretch it on screen, blurring it.
2. On high-DPR screens, make the buffer `devicePixelRatio` times bigger, keep the CSS size, and `ctx.scale(dpr, dpr)` to keep drawing in CSS-pixel coordinates — one canvas pixel per physical pixel.
3. Draw with `fillRect`, `strokeRect`, `beginPath/moveTo/lineTo/arc/fill/stroke`, `fillText`, `drawImage`, after setting `fillStyle`, `strokeStyle`, `font`, `textAlign`.
4. Animate by clearing and redrawing in `requestAnimationFrame` (calls your code just before each screen refresh) — how `make_video.mjs` drew the 4.6 clip.

```
<!-- code/08_canvas.html (excerpt) -->
<canvas id="chart" width="420" height="220" role="img"
        aria-label="Bar chart of visits: Mon 12, Tue 19, Wed 7, Thu 15, Fri 22">
  Visits: Mon 12, Tue 19, Wed 7, Thu 15, Fri 22.
</canvas>
<script>
  const data = { Mon: 12, Tue: 19, Wed: 7, Thu: 15, Fri: 22 };
  const canvas = document.getElementById('chart');
  const dpr = window.devicePixelRatio || 1;                // sharp on high-DPI screens
  canvas.style.width = canvas.width + 'px'; canvas.style.height = canvas.height + 'px';
  canvas.width *= dpr; canvas.height *= dpr;
  const ctx = canvas.getContext('2d');
  ctx.scale(dpr, dpr);

  const max = Math.max(...Object.values(data)), barW = 50, gap = 25, base = 190;
  ctx.font = '13px system-ui'; ctx.textAlign = 'center';
  Object.entries(data).forEach(([day, v], i) => {
    const x = 30 + i * (barW + gap), h = (v / max) * 150;
    ctx.fillStyle = '#6c5ce7'; ctx.fillRect(x, base - h, barW, h);
    ctx.fillStyle = '#222';
    ctx.fillText(v, x + barW / 2, base - h - 6);
    ctx.fillText(day, x + barW / 2, base + 18);
  });
  ctx.beginPath(); ctx.moveTo(20, base); ctx.lineTo(410, base); ctx.stroke();
</script>
```




Figure 4.9 — Painted with the 2D context. The fallback text and `aria-label` give assistive technology the data it cannot "see".


Canvas vs SVG

	SVG	Canvas
Model	retained (browser keeps every shape as a DOM node)	immediate (draw and forget; only pixels remain)
Scales without blur	yes	no — redraw at the new size
Events per shape (click a bar)	native	you do hit-testing (which shape is under the pointer)
Accessibility	text and titles are real content	none built in — add fallback text / `aria-label` / a data table
Performance sweet spot	up to a few thousand elements	many thousands of objects, pixel effects, games, real-time charts
Examples	icons, logos, D3 charts, a clickable 50-region map	games, image editors, Figma-style editors, big-data plots

Common mistakes

- Sizing with CSS only → blurry, stretched drawing.
- No fallback/accessible text for meaningful drawings.
- Text-heavy UI on canvas that would be simpler and more accessible as HTML.

4.10 Choosing the right element



Chapter interview round-up

1. **How do you make images responsive?** CSS `max-width:100%; height:auto`; `srcset` (`x` or `w` + `sizes`); `<picture>` for art direction/format fallback; `width`/`height` against layout shift.
2. **How do you improve image loading performance?** Right format (AVIF/WebP), right size (srcset), compression, lazy-load below the fold, `fetchpriority="high"` for the LCP image, dimensions to avoid CLS, a CDN.
3. **When is `alt=""` correct?** Decorative images and images whose information is already in adjacent text.
4. **How would you embed an untrusted HTML snippet?** An iframe with `sandbox` (no `allow-same-origin`), possibly via `srcdoc`, or sanitise it.
5. **SVG vs PNG for a logo?** SVG: sharp at any size, usually smaller, styleable; PNG only if too complex for vectors.
6. **Canvas vs SVG for a chart?** SVG for typical dashboards (accessible, per-element interaction); canvas for tens of thousands of points or real-time updates.

Chapter TL;DR

- `<img src alt width height>`: meaningful alt, empty alt for decoration, dimensions prevent layout shift, fluid via `max-width:100%; height:auto`.
- Formats: SVG for vectors; AVIF/WebP (JPEG fallback) for photos; PNG for pixel-exact graphics; video instead of GIF. Measure — content type changes the winner.
- `srcset` + honest `sizes` lets the browser choose by device pixels; `<picture>` lets *you* choose by layout (`media`) or format (`type`); `currentSrc` shows the winner.
- `loading="lazy"` below the fold, never on the hero; `fetchpriority="high"` for the LCP image.
- `<figure>`/`<figcaption>` for referenced, self-contained content; alt and caption complement, not duplicate.
- `<video>`/`<audio>` with `controls`, ordered `<source type>`s, WebVTT `<track>` captions; autoplay only when muted; stream big video adaptively.
- `<iframe>`: `title`, `loading="lazy"`, minimal `sandbox` tokens, `allow`; defend your own pages with `frame-ancestors`.
- SVG: `viewBox`, shapes and paths, `symbol`/`use`, `currentColor`; never inline untrusted SVG.
- `<canvas>`: script-painted pixels, buffer = attributes × `devicePixelRatio`, provide accessible fallback.

Next: Chapter 5 — Tables and Forms.