Chapter 7 — Core APIs: Strings, Numbers, Dates and Randomness

Almost every Java class you write will touch a handful of library types: `String` and `StringBuilder` for text, `Math` and the wrapper classes (`Integer`, `Double` …) for numbers, `BigDecimal` for money, `java.time` for dates, and `Random` for simulations and tests. These live in `java.lang`, `java.math`, `java.time`, `java.text` and `java.util`, and they are part of every JDK — no dependencies needed.

This chapter teaches each API the way you'll actually use it: what it is, how it behaves, the handful of methods that matter, and the mistakes that cause real bugs (comparing strings with `==`, the `Integer` cache, `new BigDecimal(0.1)`, `YYYY` in date patterns, daylight-saving gaps). Chapter 2 §2.12 already introduced `String` basics and text blocks, and §2.11 explained why `0.1 + 0.2 != 0.3`; here we go deeper instead of repeating.

What you'll learn

§	Topic	You'll be able to…
7.1	String immutability and the pool	explain why `String` is immutable, how the pool and `intern` work, and when `==` "works" by accident
7.2	The `String` API	pick the right method for searching, splitting, comparing and transforming text; handle Unicode correctly
7.3	`StringBuilder`, `StringJoiner`	build text efficiently and know when `+` is fine
7.4	Formatting text and numbers	use `format` / `formatted` / `printf` specifiers, locales, `NumberFormat`, `DecimalFormat`, `HexFormat`
7.5	`Math`	round, divide, clamp and detect overflow correctly
7.6	Wrapper classes and autoboxing	avoid the `Integer` cache, null-unboxing and `remove(int)` traps
7.7	`BigInteger` and `BigDecimal`	do exact arithmetic and money with the right rounding
7.8	The `java.time` model	choose between `LocalDate`, `ZonedDateTime`, `Instant`, `Duration`, `Period`
7.9	Local dates and times	create, adjust, compare and measure calendar values
7.10	Zones, instants and DST	convert between zones and survive daylight-saving changes
7.11	Formatting and parsing dates	write safe patterns (and avoid `YYYY`)
7.12	Random numbers	pick between `Random`, `ThreadLocalRandom`, `SecureRandom` and `RandomGenerator`

All runnable code is in `code/` (package `ch07.*`), compiled with `javac --release 25` and run on JDK 26; every "Output:" block below is pasted from a real run.

> **Exam depth.** Tricky `String` / `StringBuilder` method-chain puzzles, `Math` return types and date-time arithmetic questions are drilled in OCP Chapter 4 — Core APIs. Number and date formatting with locales and resource bundles: OCP Chapter 11 — Exceptions and localization (sections 5–8).

7.1 Strings: immutability, the pool and memory

What it is

A `String` is an object that holds a fixed sequence of characters. **Immutable** means that once a `String` object is created, nothing can change its contents: every method that looks like it modifies a string (`toUpperCase`, `replace`, `concat`, `strip` …) actually returns a **new** `String`.

Analogy: a printed page. You can photocopy it and write on the copy, but the original page never changes — anyone else holding the original still sees the same text.


Why it matters

Immutability is a deliberate design choice with several pay-offs:

Benefit	Why immutability enables it
Safe sharing	Many variables (and threads) can point to one `String` with no risk that one of them changes it — no locking needed.
Safe `HashMap` keys	A key's hash code can't change after insertion, so lookups keep working. `String` even caches its `hashCode` after the first call.
Security	A file path or class name checked by security code can't be altered afterwards by the caller.
The string pool	Identical literals can share one object only because nobody can modify it.

How it works — the string pool

1. Every string **literal** in your source code (`"hello"`) is stored once in the **string pool** (also called the *intern pool*), a table the JVM keeps on the heap (it moved from PermGen to the main heap in Java 7).
2. Two identical literals anywhere in the program refer to the **same** pooled object.
3. **Compile-time constant expressions** — literals joined with `+`, or `final` variables initialised with constants — are folded by the compiler into one literal, so they are pooled too.
4. Strings computed **at run time** (concatenating a non-final variable, reading input, `new String(...)`) are ordinary new heap objects, not pooled.
5. `s.intern()` returns the pooled copy of `s`'s contents, adding it to the pool if necessary.



`code/ch07/strings/StringPool.java`:

```java
String a = "hello";                    // literal -> string pool
String b = "hello";                    // same pooled object
String c = new String("hello");        // always a new heap object
String d = c.intern();                 // pooled copy
String e = "hel" + "lo";               // constant expression, folded at compile time
String part = "hel";
String f = part + "lo";                // computed at run time -> new object
final String constPart = "hel";
String g = constPart + "lo";           // final + literal initialiser = constant -> pooled
```

Output:

```
a == b: true
a == c: false, a.equals(c): true
a == c.intern(): true
a == "hel" + "lo": true
a == part + "lo": false
a == constPart + "lo": true
s=java, upper=JAVA, same object? false
"x".equals(null)=false, Objects.equals(null,null)=true
```

The lesson: `==` compares *references* (same object?), `equals` compares *contents*. Because of the pool, `==` sometimes *appears* to work on strings – then fails on the first string that came from user input or a database. Always use `equals` (or `Objects.equals(a, b)` when either side may be `null`, or put the literal first: `"yes".equals(answer)`).

How strings are stored (Java 9+)

Since Java 9 (**compact strings**, JEP 254) a `String` stores its characters in a `byte[]`: one byte per character when every character fits in Latin-1, otherwise two bytes per character (UTF-16). This roughly halves memory for mostly-ASCII text and is invisible to your code. Also since Java 9 (JEP 280), `a + b + c` is compiled to an optimised `invokedynamic` call, so a *single* concatenation expression is already efficient – only concatenation *inside loops* needs `StringBuilder` (§7.3).

Common mistakes

- Calling a "modifying" method and ignoring the result: `s.trim();` does nothing useful – write `s = s.trim();`.
- Comparing with `==` (see above), including `switch`-like `if (cmd == "quit")` chains.
- Calling `intern()` everywhere "to save memory" – the pool is a shared table; modern JVMs already deduplicate where it pays (G1 has an optional string-deduplication flag). Intern only with measurements.

In the interview

30-second answer: "`String` is immutable and final. That makes it thread-safe, lets it cache its hash code so it's a good map key, keeps security checks valid, and allows the JVM to pool identical literals. Literals and compile-time constants are pooled, runtime strings aren't, so `==` is unreliable – I always compare with `equals`."

- *Follow-up: How many objects does `new String("hi")` create?* → Up to two: the pooled literal `"hi"` (if it isn't already in the pool from class loading) and the new heap `String`.
- *Follow-up: Why is `String` final?* → So no subclass can break its immutability guarantees (e.g., a mutable "String" passed to security code).
- *Follow-up: Where is the pool?* → On the heap since Java 7, so pooled strings are garbage-collected like other objects when unreachable.

Self-check

1. `String s = "a"; s.concat("b");` – what is `s`? → `"a"`; `concat` returned a new string that was discarded.
2. Is `"ab" == "a" + "b"` true? → Yes: a constant expression, folded at compile time.

3. Safest way to compare a possibly-null `input` to `"yes"`? → `"yes".equals(input)`.

TL;DR

Strings never change; methods return new strings. Literals and constants are pooled, so `==` may coincidentally be `true` — never rely on it; use `equals`.

7.2 The `String` API toolkit

What it is

`String` has around 100 methods. You need about 30. This section groups them by job, shows them in one program, and flags the ones with surprising behaviour. Indexes are **0-based** and ranges are **half-open**: `substring(begin, end)` includes `begin` and excludes `end`, so its length is `end - begin`.

The methods, by purpose

Job	Methods (Java version if newer than 8)	Notes
Size & emptiness	`length()`, `isEmpty()`, `isBlank()` (11)	`isBlank` is true for `""` and whitespace-only strings
Read characters	`charAt(i)`, `toCharArray()`, `chars()` (9), `codePointAt(i)`, `codePoints()` (9)	`charAt` returns a UTF-16 unit, see Unicode below
Search	`indexOf`, `lastIndexOf`, `contains`, `startsWith`, `endsWith`, `indexOf(ch/str, begin, end)` (21)	`indexOf` returns **-1** when not found
Extract	`substring(begin)`, `substring(begin, end)`, `subSequence`	throws `StringIndexOutOfBoundsException` for bad indexes
Whitespace	`trim()`, `strip()` (11), `stripLeading()`, `stripTrailing()` (11), `stripIndent()` (15)	`trim` removes chars ≤ U+0020; `strip` uses Unicode `Character.isWhitespace` — prefer `strip`
Case	`toUpperCase()`, `toLowerCase()`, with `Locale` overloads	use `toLowerCase(Locale.ROOT)` for identifiers (see mistakes)
Replace	`replace(char, char)`, `replace(CharSequence, CharSequence)`, `replaceAll(regex, repl)`, `replaceFirst(regex, repl)`	`replace` is **literal**, `replaceAll` is **regex**
Compare	`equals`, `equalsIgnoreCase`, `compareTo`, `compareToIgnoreCase`, `contentEquals`, `regionMatches`, `matches(regex)`	`compareTo` < 0, 0, > 0 — not necessarily -1/1
Split & join	`split(regex)`, `split(regex, limit)`, `splitWithDelimiters` (21), `String.join`, `lines()` (11)	`split` takes a **regex**
Build new text	`concat`, `repeat` (11), `indent` (12), `formatted` (15), `transform` (12), `String.valueOf(x)`, `String.format`	`valueOf(null object)` → `"null"`
Other	`hashCode`, `intern`, `translateEscapes` (15)	

Code

`code/ch07/strings/StringApi.java` (key parts):

```
String s = "  Hello, Java World  ";
String t = s.strip();                                  // "Hello, Java World"
t.indexOf('o'); t.lastIndexOf('o'); t.indexOf("Kotlin");          // 4, 13, -1
t.substring(7); t.substring(7, 11);                               // "Java World", "Java"
t.replace('o', '0'); t.replaceAll("[aeiou]", "*");                // literal vs regex
"apple".compareTo("banana"); "Z".compareTo("a");                  // -1, -7
"a,b,,c,,".split(",");  "a,b,,c,,".split(",", -1);                // trailing empties dropped vs kept
"1.2.3".split(".");     "1.2.3".split("\\.");                     // regex dot matches everything!
"a+b-c".splitWithDelimiters("[+-]", 0);                           // Java 21
"education".chars().filter(c -> "aeiou".indexOf(c) >= 0).count(); // count vowels
String emoji = "I ❤ Jäva 😀";                  // heart, a-umlaut, grinning face
emoji.length(); emoji.codePointCount(0, emoji.length());
```

Output:

```
length=21 isEmpty=false isBlank("  ")=true
strip -> [Hello, Java World] charAt(7)=J
indexOf('o')=4 lastIndexOf('o')=13 indexOf("Java")=7 indexOf("Kotlin")=-1
contains=true startsWith=true endsWith=true
substring(7)=Java World substring(7, 11)=Java
replace=Hell0, Java W0rld | replaceAll=H*ll*, J*v* W*rld
upper=HELLO, JAVA WORLD lower=hello, java world
repeat=ababab join=a-b-c joinList=usr/local/bin
equals=false equalsIgnoreCase=true compareTo("apple","banana")=-1 compareTo("b","a")=1 compareTo("Z","a")=-7
compareToIgnoreCase=25
split(",")=[a, b, , c]
split(",", -1)=[a, b, , c, , ]
split("\\s+")=[one, two, three]
split(".") on 1.2.3 -> 0 parts; split("\\.") -> [1, 2, 3]
splitWithDelimiters=[a, +, b, -, c]
palindrome(level)=true toCharArray=[a, b, c] vowels=5
lines=[a, b, c] indent=[  x\n]
formatted=Ada is 36 valueOf(3.5)=3.5 valueOf(char[])=hi
I ❤ Jäva 😀 length=11 codePoints=10 charAt(9) is high surrogate? true
```

What to notice:

- `compareTo` compares character by character and returns the *difference* of the first differing characters (`'Z'` is 90, `'a'` is 97, so -7), or the length difference if one string is a prefix of the other. It is **case-sensitive and uppercase sorts before lowercase** – `"Zebra"` comes before `"apple"`. For human-facing sorting use `String.CASE_INSENSITIVE_ORDER` or a locale-aware `java.text.Collator`.
- `split` **takes a regular expression.** `.` means "any character", so `"1.2.3".split(".")` splits at every character and – because trailing empty strings are removed – returns an empty array. Escape (`"\\."`) or use `Pattern.quote(".")`. Likewise `|`, `+`, `*`, `?`, `(`, `[`, `$`, `^` and `\` are special.
- `split` **drops trailing empty strings** unless you pass a negative limit (`split(",", -1)`) – important when parsing CSV-like lines where the last fields may be empty.
- `replace` **vs** `replaceAll`: both replace *all* occurrences; the difference is literal vs regex. `replaceAll("$", "")` doesn't remove dollar signs; `replace("$", "")` does.

Unicode: `length()` is not "number of characters"

Java `char` is a 16-bit **UTF-16 code unit**. Most characters fit in one `char`, but characters outside the Basic Multilingual Plane – many emoji, some CJK and historic scripts – need **two** `char`s, called a **surrogate pair**. A **code point** is the actual Unicode character number.

In the output above, the string has 10 visible characters but `length()` is 11, because 😀 takes two `char`s. Consequences:

- `charAt`, `substring` and `reverse` by index can cut a surrogate pair in half. (`StringBuilder.reverse` is surrogate-aware; manual loops usually aren't.)
- To iterate real characters use `s.codePoints()`; to count them, `s.codePointCount(0, s.length())`.

- Even code points aren't "what the user sees": a flag or a family emoji is several code points. For user-perceived characters (grapheme clusters) use `java.text.BreakIterator`.

Common mistakes

Mistake	Fix
`"TITLE".toLowerCase()` in Turkish locale gives `"tıtle"` (dotless ı)	Use `toLowerCase(Locale.ROOT)` for keys, protocols, file extensions
`split(".")`, `` `split(" ``	`")` ``
Forgetting `-1` limit when trailing fields may be empty	`line.split(",", -1)`
`s.substring(0, 10)` on a shorter string	Check `length()` first, or `s.substring(0, Math.min(10, s.length()))`
Using `trim` on text with Unicode spaces (e.g. non-breaking or ideographic spaces)	`strip()`
Building a string in a loop with `+=`	`StringBuilder` (§7.3)

Real-world examples

- Log parsing: `line.split("\\s+", 4)` – limit the split so the free-text message stays in one piece.
- Normalising user input: `email.strip().toLowerCase(Locale.ROOT)` before looking up an account.
- `startsWith("https://")`, `endsWith(".json")` for quick routing checks.

Self-check

1. `"banana".indexOf("an", 2)`? → 3.
2. `"a:b:".split(":").length`? → 2 (trailing empty string removed).
3. Why can `length()` exceed the number of emoji-containing characters you see? → It counts UTF-16 units; supplementary characters use two.
4. Literal replacement of `.` with `-` in `"1.2.3"`? → `replace(".", "-")` (not `replaceAll`).

TL;DR

Know the half-open ranges, that `indexOf` returns -1, that `split`/`replaceAll`/`matches` take regexes, that `compareTo` is case-sensitive, and that `length()` counts UTF-16 units. Prefer `strip`, `isBlank`, `repeat`, `lines` (Java 11+).

7.3 `StringBuilder`, `StringBuffer` and `StringJoiner`

What it is

A `StringBuilder` is a *mutable* sequence of characters: you can append, insert, delete and replace in place, then call `toString()` once at the end. It's the tool for building text step by step.

Analogy: a `String` is a printed page; a `StringBuilder` is a whiteboard you keep editing, then photograph (`toString()`) when finished.

Why it matters

Because strings are immutable, `result += piece` inside a loop creates a brand-new `String` each iteration and copies all the previous characters into it. For n pieces that's $O(n^2)$ character copying. A `StringBuilder` grows an internal buffer (default capacity 16, roughly doubling when full), so appending is amortised $O(1)$ and the whole build is $O(n)$.

When is `+` fine? For a single expression like `"Hello, " + name + "!"` – the compiler already produces efficient code (§7.1). Use `StringBuilder` when you concatenate **in a loop** or across many statements.

How it works

1. Create: `new StringBuilder()`, `new StringBuilder("start")`, or `new StringBuilder(expectedCapacity)`.
2. Mutate with methods that **return the same builder** (so they chain): `append`, `insert`, `delete`, `deleteCharAt`, `replace`, `reverse`, `repeat` (21). `setCharAt` and `setLength` return `void`.
3. Read with `length()`, `charAt`, `indexOf`, `substring` (returns a `String`, doesn't change the builder).
4. Finish with `toString()`.

`code/ch07/strings/BuilderDemo.java` (key parts):

```
StringBuilder sb = new StringBuilder("Java");
sb.append(' ').append(25).append(" LTS");          // methods return this -> chaining
sb.insert(0, ">> ");
sb.replace(3, 7, "JAVA");                          // replace [3, 7) with "JAVA"
sb.delete(0, 3);
sb.deleteCharAt(sb.length() - 1).setCharAt(0, 'j');
new StringBuilder("stressed").reverse();
new StringBuilder().repeat("=-", 5).repeat('!', 2);    // Java 21

StringBuilder x = new StringBuilder("abc"), y = new StringBuilder("abc");
x.equals(y);                                       // false! identity comparison

StringBuilder csv = new StringBuilder();
for (int i = 1; i <= 5; i++) {
    if (!csv.isEmpty()) csv.append(',');
    csv.append(i * i);
}
StringJoiner joiner = new StringJoiner(", ", "[", "]");
```

Output:

```
append:  Java 25 LTS (length 11)
insert:  >> Java 25 LTS
replace: >> JAVA 25 LTS
delete:  JAVA 25 LTS
deleteCharAt+setCharAt: jAVA 25 LT
reverse: desserts
indexOf("25")=5 charAt(1)=A
repeat (21): =-=-=-=-=-!!
x.equals(y)=false x.toString().equals(y.toString())=true x.compareTo(y)=0 "abc".contentEquals(x)=true
loop: 1,4,9,16,25
StringJoiner: [Java, Kotlin, Scala]
capacity=1000 length=0
```

Trade-offs

	`String` + `+`	`StringBuilder`	`StringBuffer`	`StringJoiner` / `String.join` / `Collectors.joining`
Mutable	No	Yes	Yes	builds internally
Thread-safe	Yes (immutable)	No	Yes (every method `synchronized`)	No
Use for	one-off expressions	loops, incremental building	legacy code only	joining a sequence with delimiter/prefix/suffix

`StringBuffer` is the Java 1.0 version of `StringBuilder` (added in Java 5). Its locking is almost never what you want — sharing one half-built string between threads is rarely a sensible design — so use `StringBuilder`.

Common mistakes

- `sb1.equals(sb2)` — `StringBuilder` does **not** override `equals` / `hashCode`, so this is identity. Compare `sb1.toString().equals(sb2.toString())`, `sb1.compareTo(sb2) == 0` (Java 11), or `"abc".contentEquals(sb)`.

- Using a `StringBuilder` as a `HashMap` key or in a `HashSet` (same reason, and it's mutable).
- `sb.append(a + b + c)` in a loop – the inner `+` builds a temporary string; write `.append(a).append(b).append(c)`.
- Sharing one `StringBuilder` between threads.
- `new StringBuilder('x')` – a `char` is widened to `int` and treated as the **capacity**, giving an empty builder. Use `new StringBuilder("x")`.

In the interview

> **30-second answer:** "Strings are immutable, so repeated `+=` in a loop copies everything each time – $O(n^2)$. `StringBuilder` is a growable mutable buffer with amortised O(1) appends. `StringBuffer` is the same but synchronized, which is legacy. A single `+` expression is fine; the compiler optimises it."

- *Follow-up: Does `StringBuilder` override `equals`?* → No; compare via `toString()` or `compareTo`.
- *Follow-up: Default capacity?* → 16 characters (or 16 + initial string length); it grows automatically.

Self-check

1. `new StringBuilder("abc").reverse().insert(1, "-")`? → `"c-ba"`.
2. Does `sb.substring(1)` change `sb`? → No, it returns a `String`.
3. Why not `StringBuffer`? → Unneeded synchronisation; `StringBuilder` is the modern default.

TL;DR

Loop-building text → `StringBuilder`; joining a list → `String.join` / `StringJoiner` / `Collectors.joining`; one-line concatenation → `+`. `StringBuilder` has no value-based `equals`.

7.4 Formatting text and numbers

What it is

Formatting turns values into text with a controlled layout: width, alignment, decimal places, thousands separators, currency symbols. Java's main tool is the `java.util.Formatter` mini-language used by `String.format(...)`, `"...".formatted(...)` (Java 15) and `System.out.printf(...)`. For locale-aware business formatting there's `java.text.NumberFormat` / `DecimalFormat`, and for bytes `java.util.HexFormat` (Java 17).

How it works – format specifiers

A specifier has the shape `%[argument_index$][flags][width][.precision]conversion`:

Part	Examples	Meaning
conversion	`s` string, `d` integer, `f` fixed decimal, `e` scientific, `x` / `X` hex, `o` octal, `c` char, `b` boolean, `n` line separator, `%%` literal %	what kind of value
width	`%10s`, `%8d`	minimum characters; right-aligned by default
flags	`-` left-align, `0` zero-pad, `,` grouping separators, `+` always show sign, `(` negatives in parentheses	layout tweaks
precision	`%.2f` (2 decimals), `%.2s` (max 2 chars)	decimals for numbers, max length for strings
argument index	`%2$s`	use the 2nd argument (lets you reuse or reorder)

`code/ch07/format/Formatting.java` (key parts):

```
String.format("|%s|%10s|%-10s|%.2s|", name, name, name, name);
String.format("|%d|%8d|%-8d|%08d|%,d|%+d|", 42, 42, 42, 42, 1234567, 42);
String.format("|%f|%.2f|%10.3f|%-10.1f|%e|", price, price, price, price, 12345.678);
String.format("|%x|%X|%o|%c|%b|%%|", 255, 255, 8, 'J', null);
String.format("|%2$s %1$s|%s|", "world", "hello");
"%s bought %d items for $%.2f".formatted(name, 3, 9.5);             // Java 15
String.format(Locale.US, "US: %,.2f", 1234567.891);
String.format(Locale.GERMANY, "DE: %,.2f", 1234567.891);
NumberFormat.getCurrencyInstance(Locale.US).format(new BigDecimal("1234.5"));
NumberFormat.getPercentInstance(Locale.US).format(0.256);
NumberFormat.getCompactNumberInstance(Locale.US, NumberFormat.Style.SHORT).format(1_250_000); // Java 12
new DecimalFormat("#,##0.00", DecimalFormatSymbols.getInstance(Locale.US)).format(1234.5);
HexFormat.ofDelimiter(":").withUpperCase().formatHex(new byte[]{10, -1, 127});        // Java 17
```

Output:

```
|Ada|       Ada|Ada       |Ad|
|42|      42|42      |00000042|1,234,567|+42|
|3.141590|3.14|     3.142|3.1       |1.234568e+04|
|ff|FF|10|J|false|%|
|hello world|world|
Ada bought 3 items for $9.50
printf with %n line ending
US: 1,234,567.89
DE: 1.234.567,89
currency=$1,234.50 percent=26% compact=1M
DecimalFormat: 1,234.50 0.50 -7.00
HexFormat: 0A:FF:7F
```

What to notice:

- `%f` defaults to **6** decimals; `%.2f` **rounds** (HALF_UP) rather than truncates.
- `%b` prints `false` for `null`, and `true` for *any* other non-Boolean object — it is not a "truthiness" check.
- In `|%2$s %1$s|%s|` the plain `%s` after indexed ones takes the *first* ordinary argument, `"world"` — mixing styles is confusing; pick one.
- `%n` produces the platform line separator (`\n` on macOS/Linux, `\r\n` on Windows); prefer it in `printf`.
- Wrong specifier for the type throws at run time: `String.format("%d", 3.5)` → `IllegalFormatConversionException`. Missing arguments → `MissingFormatArgumentException`.
- **Locale matters.** `String.format` uses the JVM's default locale, so a server running in Germany prints `1.234.567,89`. For machine-readable output (CSV, JSON, logs parsed by tools) pass `Locale.ROOT` or `Locale.US` explicitly. `Locale.of("de", "DE")` (Java 19) replaces the deprecated `new Locale(...)` constructors.
- `DecimalFormat` patterns: `0` = digit, always shown; `#` = digit, hidden if zero; `,` grouping; `.` decimal point; `%` multiply by 100. `DecimalFormat` is **not thread-safe** — create one per use or per thread. (`DateTimeFormatter` from §7.11, in contrast, is immutable and thread-safe.)
- Compact number formatting rounds to a whole unit by default (`1.25M` → `1M`); `setMinimumFractionDigits(1)` keeps one decimal. Its rounding mode is `HALF_EVEN`, so 1,250,000 then prints `1.2M` while 1,260,000 prints `1.3M`.

When not to use it

- Money *arithmetic* — format only at the edge; compute with `BigDecimal` or `long` cents (§7.7).
- Building SQL or HTML by formatting user input — use prepared statements / templating that escapes.
- Hot logging paths — use your logger's placeholders (`log.info("user {} logged in", id)`), which skip formatting when the level is disabled.

Self-check

1. `String.format("%05.1f", 3.14159)`? → `"003.1"` (width 5 includes the dot).
2. `String.format("%-5s|", "ab")`? → `"ab   |"`.

3. Why pass a `Locale` to `format` in a CSV exporter? → So decimal separators don't change with the server's locale.

TL;DR

`%[index$][flags][width][.precision]conv`. `%s %d %.2f %,d %08d %-10s %x %n`. Be explicit about `Locale` for machine output; use `NumberFormat` for currency/percent/compact, `HexFormat` for bytes.

7.5 Math

What it is

`java.lang.Math` is a utility class of `static` methods for arithmetic and trigonometry on primitives. You never create it (`Math` has a private constructor). Everything below is `double`-based unless noted, and the `*Exact` methods throw on overflow instead of wrapping silently.

The methods you'll use

Group	Methods	Return type & behaviour
Absolute, min, max	`abs`, `min`, `max`	same type as the arguments (after promotion)
Powers & roots	`pow(a, b)`, `sqrt`, `cbrt`, `hypot(x, y)`, `exp`, `log`, `log10`	`double`
Rounding	`round` → `long` (or `int` for `float`), `floor` / `ceil` / `rint` → `double`	`round` = nearest integer, ties toward +∞ (`-2.5` → `-2`); `rint` = ties to **even**
Integer division	`floorDiv`, `floorMod` (8), `ceilDiv`, `ceilMod` (18)	round toward −∞ / +∞ instead of toward 0
Limiting	`clamp(value, min, max)` (21)	keeps a value inside a range
Overflow-safe	`addExact`, `subtractExact`, `multiplyExact`, `incrementExact`, `negateExact`, `toIntExact` (8), `absExact` (15), `divideExact` (18), `powExact` (25)	throw `ArithmeticException` on overflow
Trig & angles	`sin`, `cos`, `tan`, `atan2`, `toRadians`, `toDegrees`, constants `PI`, `E`	radians
Misc	`signum`, `random()`	`random()` returns a `double` in [0.0, 1.0)

`code/ch07/math/MathDemo.java` output:

```
abs(-7)=7 max(3,9)=9 min(2.5,-1)=-1.0
pow(2,10)=1024.0 sqrt(144)=12.0 cbrt(27)=3.0 hypot(3,4)=5.0
round(2.5)=3 round(-2.5)=-2 rint(2.5)=2.0 floor(-1.1)=-2.0 ceil(-1.1)=-1.0
7/2=3 -7/2=-3 floorDiv(-7,2)=-4 ceilDiv(7,2)=4 floorMod(-7,3)=2
clamp(150,0,100)=100 clamp(-3.5,0.0,1.0)=0.0
signum(-4.2)=-1.0 log10(1000)=3.0 exp(1)=2.7182818284590455
PI=3.141592653589793 sin(PI/2)=1.0 toDegrees(PI)=180.0
multiplyExact overflow -> ArithmeticException: integer overflow
pages=6 (same as (items + perPage - 1) / perPage = 6)
Math.random() in [0,1)? true
```

What to notice:

- `min(2.5, -1)` printed `-1.0`: the `int` was promoted to `double` first (Chapter 2 §2.7).

- `pow` always returns `double` – `(int) Math.pow(10, 2)` is fine for small values, but for big integer powers use `BigInteger.pow` or `Math.powExact` (Java 25) to avoid rounding and overflow.
- `/` on integers truncates toward zero (`-7/2 = -3`); `floorDiv` rounds toward negative infinity (`-4`). Use `floorMod` for "wrap-around" indexes (clock arithmetic, circular buffers), because `%` keeps the dividend's sign.
- **Paging:** `Math.ceilDiv(items, perPage)` (Java 18) replaces the classic `(items + perPage - 1) / perPage` trick, which can overflow for huge values.
- `Math.abs(Integer.MIN_VALUE)` is still negative – see Chapter 2 §2.10; `absExact` throws instead.
- `StrictMath` gives bit-for-bit identical results on every platform; since Java 17 (JEP 306) all floating-point arithmetic is strict anyway, and `Math` may still use faster intrinsics for functions like `sin`.

Self-check

1. Type of `Math.round(2.7)` ? → `long` (3). `Math.round(2.7f)` ? → `int` .
2. `Math.floorMod(-1, 7)` ? → 6.
3. How do you detect that `a * b` overflowed an `int` ? → `Math.multiplyExact(a, b)` throws `ArithmeticException` .

TL;DR

`round` → `long` , half up; `floor` / `ceil` / `rint` → `double` . `floorDiv` / `floorMod` / `ceilDiv` for correct negative and paging arithmetic, `clamp` (21) for ranges, `*Exact` for overflow detection.

7.6 Wrapper classes and autoboxing

What it is


Each primitive has a **wrapper class** – an immutable object holding one value: `byte→Byte` , `short→Short` , `int→Integer` , `long→Long` , `float→Float` , `double→Double` , `char→Character` , `boolean→Boolean` . You need them wherever Java requires an *object*: collections (`List<Integer>` , not `List<int>`), generics (Chapter 9), and fields that may be "absent" (`null`).

Autoboxing (Java 5) is the compiler automatically converting a primitive to its wrapper (`Integer x = 5;` becomes `Integer.valueOf(5)`); **unboxing** is the reverse (`int y = x;` becomes `x.intValue()`).

Analogy: a primitive is a coin; a wrapper is the coin in a small labelled envelope. Collections only accept envelopes; Java puts coins in and takes them out for you – but an empty envelope (`null`) has no coin to take out.

How it works

1. **Boxing** calls `valueOf` . For `Integer` , `Short` , `Byte` , `Long` (–128 to 127), `Character` (0 to 127) and `Boolean` , `valueOf` returns **cached, shared objects**. The Java Language Specification (§5.1.7) guarantees this for boxed `int` , `short` and `byte` values in –128…127, `char` values up to 127, and `true` / `false` ; the `Long` cache is a JDK implementation choice. `Integer` 's upper bound can be raised with `-XX:AutoBoxCacheMax=<n>` . `Float` and `Double` have no cache.
2. **Unboxing** calls `xxxValue()` – which throws `NullPointerException` if the reference is `null` .
3. **Arithmetic and** `<` / `>` on wrappers unbox first. `==` **between two wrappers compares references**, not values. `==` between a wrapper and a primitive unboxes the wrapper.
4. The `new Integer(5)` style constructors have been deprecated since Java 9 – always use `valueOf` (or just autobox).



`code/ch07/wrappers/WrappersDemo.java` (key parts):

```
Integer a = 127, b = 127, c = 128, d = 128;
(a == b); (c == d); c.equals(d);                  // true, false, true

Long big = 42L;
big.equals(42);                                   // false: 42 boxes to Integer, a different class
big == 42;                                        // true: big is unboxed, numeric comparison

Map<String, Integer> stock = new HashMap<>();
int apples = stock.get("apples");                 // get returns null -> NPE while unboxing

List<Integer> list = new ArrayList<>(List.of(10, 20, 30));
list.remove(1);                                   // remove(int index)  -> [10, 30]
list.remove(Integer.valueOf(10));                 // remove(Object o)   -> [30]

Integer maybe = null;
Integer result = true ? maybe : 0;                // mixed boxed/primitive ternary unboxes -> NPE

Long total = 0L;
for (long i = 0; i < 1_000; i++) total += i;      // unbox, add, re-box: 1,000 allocations
```

Output:

```
boxed then unboxed: 5
127 == 127: true, 128 == 128: false, 128 equals 128: true
parseInt=42 valueOf=42 parseInt("ff",16)=255 toBinaryString(10)=1010 Double.parseDouble("1e3")=1000.0
Boolean.parseBoolean("YES")=false
NumberFormatException: For input string: "4 2"
Integer.MAX_VALUE=2147483647 Integer.compare(3,7)=-1 Integer.sum(2,3)=5 Integer.bitCount(255)=8
Character.isDigit('7')=true Character.toUpperCase('q')=Q Character.getNumericValue('9')=9
Long(42).equals(Integer 42): false, big == 42: true
NPE: Cannot invoke "java.lang.Integer.intValue()" because the return value of "java.util.Map.get(Object)" is
null
safe: 0
after remove(1) and remove(Integer.valueOf(10)): [30]
ternary unboxing NPE
total=499500
```

Parsing and converting

You have	You want	Use
`String`	`int`	`Integer.parseInt(s)` (radix overload: `parseInt("ff", 16)`)
`String`	`Integer`	`Integer.valueOf(s)`
`int`	`String`	`String.valueOf(i)`, `Integer.toString(i)`, `Integer.toBinaryString/HexString`
`String`	`boolean`	`Boolean.parseBoolean(s)` – `true` only for `"true"` (any case); everything else, including `"YES"`, is `false`
`double`	`int`	cast `(int) d` (truncates) or `Math.round`

Invalid numeric text throws the unchecked `NumberFormatException`. The parse methods don't trim: `" 42"` fails. Since the parser is strict, validate or catch at the boundary where text enters your program.

Handy statics: `Integer.MAX_VALUE` / `MIN_VALUE`, `Integer.compare(a, b)` (use this instead of `a - b` in comparators, which can overflow), `Integer.sum/max/min` (useful as method references), `Character.isDigit/isLetter/isWhitespace/toUpperCase`, `Character.getNumericValue`.

Trade-offs – primitive vs wrapper

	`int`	`Integer`
Memory	4 bytes	object header + value (typically 16 bytes) + reference
Can be `null`	No (default 0)	Yes – useful for "unknown", dangerous when unboxed
Collections/generics	Not allowed	Required
`==`	compares values	compares references
Speed in hot loops	fast	boxing allocates (except cached values)

When not to use wrappers

- Local variables, counters, loop indexes, arithmetic – use primitives. The `Long total` loop above allocates on every iteration (*Effective Java*, Item 61: prefer primitives to boxed primitives).
- Large numeric arrays/collections in performance-sensitive code – prefer `int[]` or primitive streams (`IntStream`) over `List<Integer>`.

Common mistakes

1. `==` on wrappers – works for small cached values in tests, fails in production at 128. Use `equals` or unbox.
2. `Long.equals(Integer)` is always false – the classes differ. Watch `map.get(42)` on a `Map<Long, …>` (it returns `null`; use `42L`).
3. Unboxing `null`: from `Map.get`, from a nullable database column, or in a ternary mixing `Integer` and `int`.
4. `List<Integer>.remove(1)` removes by **index**; use `remove(Integer.valueOf(1))` for the value.
5. Synchronising on a wrapper (`synchronized (count)`) – cached instances are shared JVM-wide; `javac` warns about synchronising on these *value-based* classes.

In the interview

> **30-second answer:** "Wrappers let primitives live in collections and generics. Autoboxing calls `valueOf`, which caches −128 to 127, so `==` on two `Integer`s is true for 127 and false for 128 – always use `equals`. Unboxing `null` throws an NPE, which bites with `Map.get` and mixed ternaries. I use primitives for arithmetic and wrappers only where an object or null is needed."

- *Follow-up: Is `Integer i1 = 1000, i2 = 1000; i1 == i2` guaranteed false?* → Not guaranteed – the cache upper bound is configurable, but by default it's false. The point is it's *reference* comparison, so never rely on

it.

- *Follow-up:* `new Integer(5) == new Integer(5)`*?* → Always false (two objects); the constructor is deprecated anyway.

Self-check

1. `Integer x = null; int y = x;` → ? → `NullPointerException`.
2. `Short s = 100; s.equals(100)`? → `false` – `100` boxes to `Integer`.
3. `Boolean.parseBoolean("True")`? → `true` (case-insensitive).

TL;DR

Autoboxing = `valueOf`, unboxing = `xxxValue()`. Cache −128…127 makes `==` lie; use `equals`. Null unboxing → NPE. `remove(int)` vs `remove(Object)`. Primitives for math, wrappers for collections.

7.7 `BigInteger` and `BigDecimal`

What it is

Two immutable classes in `java.math` for numbers that primitives can't represent exactly:

- `BigInteger` – whole numbers of *any* size (limited only by memory). Use when values exceed `long` (about 9.2×10^{18}): factorials, cryptography, exact combinatorics.
- `BigDecimal` – exact *decimal* numbers: an arbitrary-precision integer **unscaled value** plus a **scale** (the number of digits after the decimal point). `12.30` is unscaled `1230`, scale `2`. Use for money and anything that must match human decimal arithmetic.

Analogy: `double` is a ruler with fine but binary tick marks – 0.1 falls between two ticks. `BigDecimal` is counting coins: exact, but slower.

How it works

1. Both are **immutable**: `a.add(b)` returns a new object – assign the result (`total = total.add(x);`). There are no operators; you call `add`, `subtract`, `multiply`, `divide`, `pow`, `negate`, `abs`, `compareTo`.
2. **Create `BigDecimal` from a `String`** (`new BigDecimal("0.10")`) or `BigDecimal.valueOf(double)` (which goes through `Double.toString`, giving the short decimal you expect). `new BigDecimal(0.1)` copies the double's exact binary value – 55 digits of noise.
3. **Division** must say how to round when the result doesn't terminate: `divide(divisor, scale, RoundingMode)` or `divide(divisor, MathContext)`. Plain `divide(divisor)` throws `ArithmeticException` for 10/3.
4. **Rounding** is explicit: `setScale(2, RoundingMode.HALF_EVEN)`. Modes: `UP` / `DOWN` (away from / toward zero), `CEILING` / `FLOOR` (toward +∞ / −∞), `HALF_UP` (school rounding), `HALF_DOWN`, `HALF_EVEN` (**banker's rounding**: ties go to the even neighbour, which avoids systematic upward bias over many operations), `UNNECESSARY` (throws if rounding would be needed).
5. **`equals` compares value *and* scale** (`2.0` ≠ `2.00`); **`compareTo` compares value only**. Use `compareTo(...) == 0` for numeric equality.

`code/ch07/big/BigNumbers.java` (key parts):

```
BigInteger f = BigInteger.ONE;
for (int i = 2; i <= 30; i++) f = f.multiply(BigInteger.valueOf(i));      // 30!
BigInteger.TWO.pow(100);
BigInteger.valueOf(3).modPow(BigInteger.valueOf(200), BigInteger.valueOf(1000));
f.longValueExact();                                        // throws: doesn't fit

new BigDecimal("0.1").add(new BigDecimal("0.2"));          // 0.3 exactly
new BigDecimal(0.1);                                       // the double's binary value
new BigDecimal("2.0").equals(new BigDecimal("2.00"));      // false (scale differs)
ten.divide(three);                                         // ArithmeticException
ten.divide(three, 4, RoundingMode.HALF_UP);                // 3.3333

BigDecimal price = new BigDecimal("19.99");
BigDecimal subtotal = price.multiply(BigDecimal.valueOf(3));
BigDecimal tax = subtotal.multiply(new BigDecimal("0.0825")).setScale(2, RoundingMode.HALF_EVEN);
```

Output:

```
30! = 265252859812191058636308480000000 (108 bits)
2^100 = 1267650600228229401496703205376
gcd(84,36)=12 3^200 mod 1000=1 isProbablePrime(97)=true sqrt(10^20)=10000000000
30!.longValueExact(): BigInteger out of long range
double 0.1+0.2=0.30000000000000004 BigDecimal=0.3
new BigDecimal(0.1)=0.1000000000000000055511151231257827021181583404541015625
BigDecimal.valueOf(0.1)=0.1
2.0 equals 2.00? false, compareTo == 0? true, scales 1 vs 2, stripTrailingZeros equal? true
10/3: Non-terminating decimal expansion; no exact representable decimal result.
10/3 scale 4 HALF_UP=3.3333 MathContext.DECIMAL64=3.333333333333333
2.345 -> HALF_UP 2.35, HALF_EVEN 2.34, DOWN 2.34, FLOOR 2.34
2.355 -> HALF_UP 2.36, HALF_EVEN 2.36, DOWN 2.35, FLOOR 2.35
-2.345 -> HALF_UP -2.35, HALF_EVEN -2.34, DOWN -2.34, FLOOR -2.35
subtotal=59.97 tax=4.95 total=64.92
share=33.33 leftover cent(s)=0.01 (divideAndRemainder: 33.00 r 1.00)
```

Read the rounding rows: for `2.345`, the tie goes *up* with `HALF_UP` (2.35) but to the *even* digit with `HALF_EVEN` (2.34); for `2.355` both give 2.36 because 6 is even. `FLOOR` differs from `DOWN` only for negatives.

The last line shows a classic money problem: $100.00 split three ways is 33.33 each with **one cent left over**. Real systems allocate the remainder explicitly (e.g., the first account gets 33.34) rather than letting it vanish.

Trade-offs

	`double`	`long` cents	`BigDecimal`
Exact decimals	No	Yes (fixed 2 places)	Yes (any scale)
Speed	Fastest (hardware)	Fast	Much slower, allocates
Range	Huge, approximate	$\pm 9.2 \times 10^{16}$ dollars	Unlimited
Good for	Science, graphics, statistics	Payments in one currency, high throughput	Finance, tax, currency conversion, accounting

Common mistakes

- `new BigDecimal(0.1)` → use the `String` constructor or `valueOf`.
- `total.add(x);` without assignment (immutable!).
- `equals` for numeric comparison; also, `HashSet` / `HashMap` use `equals`, so `2.0` and `2.00` are different keys, while a `TreeSet` (uses `compareTo`) treats them as one. Normalise with `stripTrailingZeros()` or a fixed `setScale` before using as keys.
- Unbounded `divide` → `ArithmeticException`; always pass a scale/rounding or a `MathContext`.

- Rounding too early (per line item) vs. at the end — follow your domain's (often legal) rules; tax is frequently rounded per invoice line.
- Using `BigInteger` / `BigDecimal` in tight numeric loops where `long` suffices.

Real-world examples

- Payment platforms store amounts as integer minor units (cents) *or* `DECIMAL(19,4)` columns mapped to `BigDecimal` — see the SQL handbook's data types chapter for `NUMERIC` in PostgreSQL.
- RSA keys and `KeyPairGenerator` internals use `BigInteger.modPow` and `isProbablePrime`.

In the interview

> **30-second answer:** "For money I use `BigDecimal` built from strings, or long minor units. Doubles are binary fractions, so 0.1 isn't representable. `BigDecimal` is immutable, needs an explicit scale and `RoundingMode` for division — usually `HALF_EVEN` for finance — and I compare with `compareTo` because `equals` also checks scale."

- *Follow-up: Why is `new BigDecimal("1.0").equals(new BigDecimal("1.00"))` false?* → `equals` includes scale; `compareTo` returns 0.
- *Follow-up: What's banker's rounding?* → `HALF_EVEN`: ties round to the even neighbour, eliminating the upward bias of always rounding .5 up.

Self-check

1. `BigDecimal.valueOf(1.10).scale()`? → 1 (`Double.toString(1.10)` is `"1.1"`).
2. What does `divide` without rounding do for 1/3? → Throws `ArithmeticException`.
3. `new BigDecimal("-1.5").setScale(0, RoundingMode.HALF_EVEN)`? → `-2`.

TL;DR

`BigInteger` for huge integers, `BigDecimal` for exact decimals. Build from `String`, assign every result, give `divide` a scale + `RoundingMode`, compare with `compareTo`, and prefer `HALF_EVEN` for money.


7.8 The `java.time` model

What it is

`java.time` (JSR 310, **Java 8**, designed by the author of the Joda-Time library) is Java's date-and-time API. It replaced `java.util.Date`, `Calendar` and `SimpleDateFormat`, which were mutable, not thread-safe, used 0-based months, and mixed up "a point in time" with "a date on a calendar". All `java.time` types are **immutable** and **thread-safe**.

The key idea: **different questions need different types.** "What's the user's birthday?" has no time zone. "When did this payment happen?" is an exact moment. "What time does the 9:00 meeting start in Tokyo?" needs a zone.

Type	Holds	Example	Use for
`LocalDate`	year-month-day	`2025-09-16`	birthdays, holidays, due dates
`LocalTime`	hour-minute-second-nanos	`09:30`	opening hours, alarm times
`LocalDateTime`	date + time, **no zone**	`2025-09-16T09:30`	a wall-clock time whose zone is implied elsewhere
`ZonedDateTime`	date + time + zone (`ZoneId`) with DST rules	`2026-03-20T09:00-04:00[America/New_York]`	scheduling in a region, displaying to users
`OffsetDateTime`	date + time + fixed offset	`2026-03-20T09:00-04:00`	APIs, databases (`timestamp with time zone` values), logs
`Instant`	a point on the UTC timeline (seconds + nanos since 1970-01-01T00:00Z)	`2025-09-16T05:20:00Z`	event timestamps, storing "when", measuring machine time
`Duration`	an amount of **time** (seconds + nanos)	`PT2H15M30S`	timeouts, elapsed time
`Period`	an amount of **calendar** time (years, months, days)	`P1Y2M3D`	ages, subscriptions, "add one month"
`ZoneId` / `ZoneOffset`	region like `Europe/London` / fixed `+05:30`		converting between zones
Also	`Year` , `YearMonth` , `MonthDay` , `DayOfWeek` , `Month` (enums), `Clock`		



How to choose

1. Storing *when something happened* (logs, orders, audit) → `Instant` (store in UTC; convert for display).
2. A date with no time (birthday, invoice date) → `LocalDate`. Don't store it as midnight UTC – that shifts the day for users west of Greenwich.
3. A future appointment in a place → store `LocalDateTime` + `ZoneId` (not an `Instant`): if the government changes DST rules before the meeting, the meeting should still be at 9:00 local.
4. Machine elapsed time → `System.nanoTime()` or `Duration.between(instantA, instantB)`; calendar arithmetic → `Period`.

Common API conventions

Prefix	Meaning	Example
`of`	create from parts	`LocalDate.of(2025, 9, 16)`
`now`	current value (optionally from a `Clock` or zone)	`LocalDate.now(clock)`
`parse`	from text	`LocalDate.parse("2025-09-16")`
`get`	read a field	`getDayOfWeek()`
`with`	copy with one field changed	`withDayOfMonth(1)`
`plus` / `minus`	copy shifted by an amount	`plusMonths(1)`
`to` / `at`	convert to another type	`toLocalDate()`, `atZone(zone)`
`is`	query	`isBefore`, `isLeapYear`

Months are **1-based** (`Month.JANUARY` = 1), unlike `Calendar`.

Legacy interop

You'll meet `Date` in older libraries. Convert at the boundary: `Date.from(instant)`, `date.toInstant()`, `GregorianCalendar.from(zdt)`, `java.sql.Timestamp.from(instant)`. With JDBC 4.2+ drivers you can read and write `LocalDate`, `LocalDateTime`, `OffsetDateTime` directly with `getObject(col, LocalDate.class)`.

7.9 Local dates, times, adjusters and `Period`

How it works

1. **Create**: `LocalDate.of(2025, Month.SEPTEMBER, 16)`, `LocalTime.of(9, 30)`, `LocalDateTime.of(date, time)`, `LocalDate.parse("2023-09-19")`. Invalid values throw `DateTimeException` immediately.
2. **Read**: `getYear`, `getMonth` / `getMonthValue`, `getDayOfMonth`, `getDayOfWeek`, `getDayOfYear`, `isLeapYear`, `lengthOfMonth`.
3. **Adjust** (always returns a new object): `plusDays/Weeks/Months/Years`, `minus…`, `withDayOfMonth`, and `TemporalAdjusters` for rules like "last day of month" or "next Friday".
4. **Compare**: `isBefore`, `isAfter`, `isEqual`, `equals`, `compareTo`.
5. **Measure**: `Period.between(a, b)` gives years + months + days; `ChronoUnit.DAYS.between(a, b)` gives a single total.

`code/ch07/time/LocalDates.java` (key parts):

```
LocalDate release = LocalDate.of(2025, Month.SEPTEMBER, 16);     // Java 25 GA date
LocalDate d = LocalDate.of(2024, 1, 31);
d.plusDays(1);                                                   // result ignored -> d unchanged
d.plusMonths(1);                                                 // 2024-02-29
release.with(TemporalAdjusters.lastDayOfMonth());
release.with(TemporalAdjusters.next(DayOfWeek.FRIDAY));
Period gap = Period.between(LocalDate.of(2023, 9, 19), release);
ChronoUnit.DAYS.between(LocalDate.of(2023, 9, 19), release);
Period.between(LocalDate.of(1990, 2, 28), LocalDate.of(2026, 2, 27)).getYears();   // age
LocalDate.of(2026, 3, 2).datesUntil(LocalDate.of(2026, 3, 9))                     // Java 9
         .filter(x -> x.getDayOfWeek().getValue() <= 5) ...
LocalDate.of(2025, 2, 29);                                       // DateTimeException
```

Output:

```
date=2025-09-16 time=09:30 dateTime=2025-09-16T09:30
dayOfWeek=TUESDAY dayOfYear=259 month=SEPTEMBER monthValue=9 leapYear=false lengthOfMonth=30
d after ignored plusDays: 2024-01-31
2024-01-31 plusMonths(1)=2024-02-29 (clamped to month end, leap year)
2025-01-31 plusMonths(1)=2025-02-28
withDayOfMonth(1)=2025-09-01 lastDayOfMonth=2025-09-30 nextFriday=2025-09-19
isBefore=true isAfter=false equals=true
Period between Java 21 and 25 GA: P1Y11M28D = 1y 11m 28d; total days=728 total months=23
age on 2026-02-27 = 35
weekdays in week of 2026-03-02: 2 3 4 5 6
YearMonth 2028-02 has 29 days
DateTimeException: Invalid date 'February 29' as '2025' is not a leap year
```

What to notice:

- **Month arithmetic clamps** to the last valid day: Jan 31 + 1 month = Feb 28 (or 29). So `d.plusMonths(1).minusMonths(1)` may not return `d`. Billing systems must decide what "monthly on the 31st" means.
- **`Period` vs total units:** `P1Y11M28D` is not "728 days expressed differently" — months have different lengths. Use `Period` for human display ("1 year, 11 months"), `ChronoUnit.X.between` for a single count.
- The age calculation gives 35 on the day *before* the 36th birthday — `Period.between` handles this correctly; subtracting years does not.
- `datesUntil` (Java 9) streams dates with the end **exclusive**, like most Java ranges.

Common mistakes

- Ignoring return values (`date.plusDays(1);`) — the object is immutable.
- Using `LocalDateTime` for timestamps of events: it has no zone, so it can't identify an instant. Use `Instant` or `OffsetDateTime`.
- Calling `LocalDate.now()` directly inside business logic — tests become date-dependent. Inject a `Clock` (§7.10).

Self-check

1. `LocalDate.of(2024, 3, 31).minusMonths(1)`? → `2024-02-29`.
2. Days in the half-open range from 2026-03-02 to 2026-03-09? → 7.
3. Which gives "3 months" between Jan 15 and Apr 15: `Period` or `ChronoUnit.DAYS`? → `Period` (`P3M`); `DAYS` gives 90.

7.10 Zones, instants, `Duration` and daylight saving

What it is

A **time zone** (`ZoneId`, e.g. `America/New_York`) is a region's set of rules: its offset from UTC and when that offset changes (**daylight saving time**, DST). An **offset** (`ZoneOffset`, e.g. `-04:00`) is just a fixed number of hours/minutes. Zone rules come from the IANA time-zone database, shipped with the JDK and updated in JDK updates when governments change rules.

How it works

1. `instant.atZone(zone)` shows one moment as local time in a zone. The same `Instant` is 01:20 in New York, 10:50 in Kolkata, 14:20 in Tokyo.
2. `zdt.withZoneSameInstant(otherZone)` converts a meeting to another zone (same moment, different clock reading). `withZoneSameLocal` keeps the clock reading and changes the moment — rarely what you want.
3. **DST gap** (spring forward): local times that don't exist are shifted forward by the gap length. **DST overlap** (fall back): local times that occur twice default to the earlier offset (`withLaterOffsetAtOverlap()` picks the other).

4. **`Duration` is exact time; `Period` is calendar time.** Across a DST change, `plus(Period.ofDays(1))` keeps the same local clock time (a "day" of 23 hours), while `plus(Duration.ofDays(1))` adds exactly 24 hours.
5. A `Clock` is the source of "now". Production uses `Clock.systemUTC()` or `systemDefaultZone()`; tests pass `Clock.fixed(...)`.

`code/ch07/time/ZonesAndInstants.java` (key parts):

```
Instant t = Instant.ofEpochSecond(1_758_000_000L);
t.atZone(ZoneId.of("America/New_York")); // and Asia/Kolkata, Asia/Tokyo
ZonedDateTime call = ZonedDateTime.of(LocalDateTime.of(2026, 3, 20, 9, 0), ny);
call.withZoneSameInstant(kolkata).toLocalTime();
ZonedDateTime gap = ZonedDateTime.of(LocalDateTime.of(2026, 3, 8, 2, 30), ny);     // doesn't exist
ZonedDateTime before = ZonedDateTime.of(LocalDateTime.of(2026, 3, 7, 12, 0), ny);
before.plus(Period.ofDays(1));  before.plus(Duration.ofDays(1));
Duration.between(before, before.plusDays(1)).toHours();
Clock fixed = Clock.fixed(Instant.parse("2026-01-01T00:00:00Z"), ZoneOffset.UTC);
LocalDate.now(fixed);
```

Output:

```
epoch=1970-01-01T00:00:00Z t=2025-09-16T05:20:00Z t.toEpochMilli()=1758000000000
NY:      2025-09-16T01:20-04:00[America/New_York]
Kolkata: 2025-09-16T10:50+05:30[Asia/Kolkata]
Tokyo:   2025-09-16T14:20+09:00[Asia/Tokyo]
9:00 NY call in Kolkata: 18:30; withZoneSameLocal keeps 09:00 but changes the instant: 2026-03-
20T09:00+05:30[Asia/Kolkata]
02:30 in the gap becomes: 2026-03-08T03:30-04:00[America/New_York]
plus(Period.ofDays(1)) = 2026-03-08T12:00-04:00[America/New_York]
plus(Duration.ofDays(1)) = 2026-03-08T13:00-04:00[America/New_York]
hours between noon and noon next day: 23
Duration PT2H15M30S = 2h 15m 30s; Period.of(1,2,3)=P1Y2M3D Period.ofWeeks(2)=P14D
OffsetDateTime=2026-03-20T09:00-04:00 toInstant=2026-03-20T13:00:00Z
LocalDate.now(fixedClock)=2026-01-01 Instant.now(fixedClock)=2026-01-01T00:00:00Z
Date.from(t).getTime()==t.toEpochMilli(): true, back to Instant: 2025-09-16T05:20:00Z
```

In 2026, US clocks spring forward on Sunday 8 March at 02:00, so 02:30 doesn't exist and becomes 03:30 EDT; the "day" from Saturday noon to Sunday noon is 23 hours long. Note also the Kolkata offset is `+05:30` – offsets aren't always whole hours. `Period.ofWeeks(2)` is stored as 14 days (`P14D`).

Trade-offs – which "now"?

Need	Use
Timestamp to store/send	`Instant.now(clock)`
Measuring how long code took	`System.nanoTime()` (monotonic; `Instant.now()` can jump if the system clock is adjusted)
Today's date for a user	`LocalDate.now(clock.withZone(userZone))` – "today" depends on the zone
Testable business logic	Inject `Clock`; in tests use `Clock.fixed` or `Clock.offset`

Common mistakes

- Using the server's default zone (`ZoneId.systemDefault()`) implicitly – servers are often UTC while users aren't. Pass zones explicitly.
- Abbreviations like `"EST"` / `"IST"` – ambiguous (IST is India, Ireland and Israel). Use region IDs (`Asia/Kolkata`).
- Adding `Duration.ofDays(1)` when you mean "same time tomorrow".
- Storing future local events as `Instant` (breaks when DST rules change) or past events as `LocalDateTime` (loses the moment).

In the interview

> **30-second answer:** "I store moments as `Instant` in UTC and convert to `ZonedDateTime` with the user's `ZoneId` only for display. Dates without time are `LocalDate`. `Duration` is exact seconds, `Period` is calendar units, and they differ across DST. All java.time types are immutable and thread-safe, and I inject a `Clock` so time-dependent code is testable."

- *Follow-up: Difference between `ZonedDateTime` and `OffsetDateTime`?* → Zoned knows the region's DST rules; Offset has only a fixed offset – better for serialising a moment unambiguously.
- *Follow-up: Why was `SimpleDateFormat` a problem?* → Mutable and not thread-safe; sharing one in a static field corrupted results under load. `DateTimeFormatter` is immutable.

Self-check

1. Same `Instant`, two zones – equal instants? → Yes; only the local representation differs.
2. How many hours between 2026-11-01T00:00 and 2026-11-02T00:00 in New York? → 25 (fall-back day).
3. Why inject a `Clock`? → To control "now" in tests and avoid hidden dependence on the system clock/zone.

TL;DR

`Instant` for moments, `LocalDate` for dates, `ZonedDateTime` for local times in a region. Convert with `atZone` / `withZoneSameInstant`. DST: gaps shift forward, overlaps pick the earlier offset. `Duration` ≠ `Period`. Inject `Clock`.

7.11 Formatting and parsing dates

How it works

1. Every `java.time` type's `toString()` prints **ISO-8601** (`2025-12-29T14:05:09`), and `parse(text)` reads it back – ideal for JSON, logs and databases.
2. `DateTimeFormatter` has predefined formatters (`ISO_LOCAL_DATE`, `ISO_OFFSET_DATE_TIME`, `BASIC_ISO_DATE`, `RFC_1123_DATE_TIME` …), localized styles (`ofLocalizedDate(FormatStyle.MEDIUM)`), and custom patterns (`ofPattern("dd MMM uuuu")`).
3. Format with `value.format(formatter)`; parse with `LocalDate.parse(text, formatter)`. Bad text throws `DateTimeParseException`.
4. `DateTimeFormatter` is **immutable and thread-safe**, so store it in a `static final` field.

Pattern letters you need

Letter	Meaning	Example (2025-12-29 14:05:09)
`uuuu` / `yyyy`	year / year-of-era	2025
`YYYY`	**week-based year** – almost never what you want	2026 (!)
`MM` / `MMM` / `MMMM`	month number / short / full name	12 / Dec / December
`dd`	day of month	29
`D`	day of year	363
`EEE` / `EEEE`	day name short / full	Mon / Monday
`HH` / `hh` + `a`	hour 0–23 / hour 1–12 + AM/PM	14 / 02 PM
`mm`	**minute** (not month)	05
`ss`, `SSS`	second, fraction	09, 000
`VV`, `z`, `XXX`	zone ID, zone name, offset	Europe/London, GMT, Z
`'text'`	literal text	`'T'`

`code/ch07/time/DateFormatting.java` output:

```
toString (ISO-8601): 2025-12-29T14:05:09
ISO_LOCAL_DATE: 2025-12-29
BASIC_ISO_DATE: 20251229
custom: 29 Dec 2025, 02:05 PM
EEEE d MMMM (fr): lundi 29 décembre
MEDIUM (US): Dec 29, 2025
yyyy-MM-dd: 2025-12-29   YYYY-MM-dd: 2026-12-29
MM=12 mm=05
parsed=2026-03-08 SUNDAY
DateTimeParseException: Text '2026-13-01' could not be parsed: Invalid value for MonthOfYear (valid values 1 - 12): 13
ISO_OFFSET_DATE_TIME: 2025-12-29T14:05:09Z | zone pattern: 14:05 Europe/London (GMT)
```

The `YYYY` bug: 29 December 2025 is a Monday in the week that contains 1 January 2026, so in the US week definition it belongs to *week-based year* 2026. `YYYY-MM-dd` therefore prints `2026-12-29` – a date a year in the future. This has caused real production outages (expired certificates, broken booking systems) during the last days of December. Use `uuuu` (or `yyyy`) – never `YYYY` unless you're printing ISO week numbers with `ww`.

`uuuu` vs `yyyy`: `u` is the proleptic year (can be zero/negative), `y` is year-of-era (needs an era `G` with `ResolverStyle.STRICT`). With the default (smart) resolver both work for modern dates; use `uuuu` if you switch to strict parsing.

Common mistakes

- `MM` vs `mm`, `HH` vs `hh`, `YYYY` vs `yyyy`, `DD` (day of year) vs `dd`.
- Parsing month/day names without a `Locale` – `ofPattern("MMM", Locale.US)`, otherwise the JVM default locale decides whether "Dec" or "déc." is expected.
- Formatting a `LocalDate` with a pattern containing time fields → `UnsupportedTemporalTypeException`.
- Rolling your own ISO format instead of `toString()` / `parse()` or `ISO_*` constants.

Self-check

1. Pattern for `08/03/2026` meaning 3 August? → `MM/dd/uuuu`.
2. Why store formatters in `static final` fields? → They're immutable and thread-safe, and building one parses the pattern.
3. What's wrong with `ofPattern("YYYY-MM-dd")`? → Week-based year; wrong in late December/early January.

TL;DR

ISO `toString` / `parse` for machines; `DateTimeFormatter.ofPattern(..., Locale)` for humans. `uuuu` / `yyyy` for year, `MM` month, `mm` minute, `HH` 24-hour. Never `YYYY`.

7.12 Random numbers

What it is

A **pseudo-random number generator** (PRNG) produces a sequence of numbers that looks random but is fully determined by a starting value, the **seed**. Same seed → same sequence, which is great for reproducible tests and simulations and terrible for security.

The options

Class	Since	Thread-safe?	Use for
`Math.random()`	1.0	yes (one shared generator)	quick scripts; a `double` in [0, 1)
`java.util.Random`	1.0	yes, but contended across threads	seeded, reproducible sequences
`ThreadLocalRandom.current()`	7	per-thread instance, no contention	general randomness in concurrent code
`SplittableRandom`	8	no — split per task	parallel computations (e.g. Fork/Join)
`SecureRandom`	1.1	yes	**security**: tokens, passwords, keys, session IDs
`RandomGenerator` interface + `RandomGeneratorFactory`	17 (JEP 356)	depends on algorithm	choosing modern algorithms (LXM family) by name

Java 17 made all of these implement a common `java.util.random.RandomGenerator` interface, which also added `nextInt(origin, bound)` and `nextLong(origin, bound)` to every generator. `Random.from(RandomGenerator)` (Java 19) adapts a new-style generator for APIs that still want a `Random`.

`code/ch07/random/RandomDemo.java` (key parts):

```
Random r1 = new Random(42), r2 = new Random(42);          // same seed -> same sequence
r1.nextInt(100);                                          // [0, 100)
new Random(7).nextInt(1, 7);                              // dice: [1, 7), Java 17
Collections.shuffle(deck, new Random(1));                 // reproducible shuffle
new Random(3).ints(5, 0, 10).boxed().toList();            // stream of 5 ints in [0, 10)
RandomGeneratorFactory.of("L64X128MixRandom").create(42L);
ThreadLocalRandom.current().nextInt(1, 7);
new SecureRandom().nextBytes(token);
```

Output:

```
seed 42 twice: 30/30 63/63 48/48 84/84 70/70
nextInt(1,7) dice: 5 3 4 | nextBoolean=false | nextDouble in [0,1)? true
nextGaussian (mean 0, sd 1): 0.5840
shuffle with seed 1: [C, D, B, E, A]
ints stream: [4, 0, 0, 1, 8]
L64X128MixRandom seeded: 98 1
default algorithm: L32X64MixRandom
ThreadLocalRandom roll in 1..6? true
SecureRandom token bytes: 16
```

The seeded lines are identical on every run and every JVM (the `Random` algorithm is specified). The default `RandomGenerator` algorithm is an implementation detail – don't rely on it being `L32X64MixRandom` forever.

Common mistakes

- `Math.abs(random.nextInt()) % n` – biased, and `Math.abs(Integer.MIN_VALUE)` is negative. Use `nextInt(n)` or `nextInt(origin, bound)`.
- `(int) (Math.random() * 6) + 1` works, but `ThreadLocalRandom.current().nextInt(1, 7)` states the range clearly.
- Creating `new Random()` inside a loop – wasteful; keep one.
- Using `Random` or `Math.random` for passwords, reset tokens or session IDs – predictable. Use `SecureRandom`.
- Forgetting that bounds are **exclusive** at the top: `nextInt(1, 6)` never returns 6.

Self-check

1. Two `Random(99)` objects – same first `nextInt()`? → Yes, same seed, same sequence.
2. Which class for generating an API key? → `SecureRandom`.
3. Range of `nextInt(10, 20)`? → 10 to 19.

TL;DR

Seeded `Random` for reproducible tests; `ThreadLocalRandom` in concurrent code; `SecureRandom` for anything security-related; upper bounds are exclusive.

Chapter TL;DR

Topic	Remember
`String`	Immutable, pooled literals, compare with `equals`; methods return new strings
`String` API	0-based, half-open ranges; `indexOf` → -1; `split` / `replaceAll` use regex; `length()` counts UTF-16 units; prefer `strip` / `isBlank`
`StringBuilder`	Mutable, chainable, for loops; no value `equals`; `StringBuffer` is legacy
Formatting	`%[i$][flags][width][.prec]conv`; explicit `Locale` for machine output; `NumberFormat`, `DecimalFormat` (not thread-safe), `HexFormat` (17)
`Math`	`round` → long, half up; `floorDiv` / `floorMod` / `ceilDiv` (18); `clamp` (21); `*Exact` throws on overflow
Wrappers	Autobox = `valueOf`; cache –128…127 makes `==` unreliable; null unboxing → NPE; `remove(int)` vs `remove(Object)`
`BigDecimal`	Build from `String`; assign results; `divide` needs scale + `RoundingMode`; `compareTo` not `equals`; `HALF_EVEN` for money
`java.time`	Immutable, thread-safe; `Instant` = moment, `LocalDate` = date, `ZonedDateTime` = local time in a region; `Duration` ≠ `Period` across DST; inject `Clock`
Date patterns	`uuuu-MM-dd HH:mm`; never `YYYY`; pass a `Locale` for names
Random	Seeded `Random` for tests, `ThreadLocalRandom` for concurrency, `SecureRandom` for security

Where next: what happens when these APIs fail – `NumberFormatException`, `DateTimeParseException`, `ArithmeticException` – and how to design your own error handling: Chapter 8 – Exceptions. Collections of these values: Chapter 10. Exam traps: OCP Chapter 4 – Core APIs and OCP Chapter 11 for localization.