

# FreeBSD package management system

Vsevolod Stakhov  
vsevolod@FreeBSD.org



FreeBSD

pkgSrcCon July 01, 2017

# What is pkg

Pkg (previously pkgng) is the binary package management system written for FreeBSD but ported for other BSD and Linux platforms.

- ▶ **Binary packages** management

# What is pkg

Pkg (previously pkgng) is the binary package management system written for FreeBSD but ported for other BSD and Linux platforms.

- ▶ **Binary packages** management
- ▶ Replaces old `pkg_*` tools

# What is pkg

Pkg (previously pkgng) is the binary package management system written for FreeBSD but ported for other BSD and Linux platforms.

- ▶ **Binary packages** management
- ▶ Replaces old `pkg_*` tools
- ▶ Uses central *sqlite3* based storage



# What is pkg

Pkg (previously pkgng) is the binary package management system written for FreeBSD but ported for other BSD and Linux platforms.

- ▶ **Binary packages** management
- ▶ Replaces old `pkg_*` tools
- ▶ Uses central *sqlite3* based storage
- ▶ Provides the comprehensive toolset for **binary packages** management

# Pkg development goals

The main goal of pkg is to simplify system management tasks.

- ▶ Easy install, remove and upgrade of binary packages

# Pkg development goals

The main goal of pkg is to simplify system management tasks.

- ▶ Easy install, remove and upgrade of binary packages
- ▶ Integration with the **ports** (easily adopted for other source management systems, e.g. pkgsrc)

# Pkg development goals

The main goal of pkg is to simplify system management tasks.

- ▶ Easy install, remove and upgrade of binary packages
- ▶ Integration with the **ports** (easily adopted for other source management systems, e.g. pkgsrc)
- ▶ Automatic **resolving** of dependencies and conflicts





# Pkg development goals

The main goal of pkg is to simplify system management tasks.


- ▶ Easy install, remove and upgrade of binary packages
- ▶ Integration with the **ports** (easily adopted for other source management systems, e.g. pkgsrc)
- ▶ Automatic **resolving** of dependencies and conflicts
- ▶ Encourage users to install software from **binary packages**

# Pkg development goals

The main goal of pkg is to simplify system management tasks.

- ▶ Easy install, remove and upgrade of binary packages
- ▶ Integration with the **ports** (easily adopted for other source management systems, e.g. pkgsrc)
- ▶ Automatic **resolving** of dependencies and conflicts
- ▶ Encourage users to install software from **binary packages**
- ▶ ...but do not prevent users from building custom packages using the **ports**

# Ports management using pkg




# Unique pkg features

- ▶ Dependencies and conflicts solver that can automatically resolve complex upgrade or install scenarios

# Unique pkg features

- ▶ Dependencies and conflicts solver that can automatically resolve complex upgrade or install scenarios
- ▶ Improved security by **sandboxing** (Capsicum) untrusted operations:




Sandboxing:

- ▶ **archives** extracting

# Unique pkg features

- ▶ Dependencies and conflicts solver that can automatically resolve complex upgrade or install scenarios
- ▶ Improved security by **sandboxing** (Capsicum) untrusted operations:




Sandboxing:

- ▶ **archives** extracting
- ▶ **vulnxml** parsing

# Unique pkg features

- ▶ Dependencies and conflicts solver that can automatically resolve complex upgrade or install scenarios
- ▶ Improved security by **sandboxing** (Capsicum) untrusted operations:




## Sandboxing:

- ▶ **archives** extracting
- ▶ **vulnxml** parsing
- ▶ repositories **signatures** checking and public keys extracting

# Unique pkg features

- ▶ Dependencies and conflicts solver that can automatically resolve complex upgrade or install scenarios
- ▶ Improved security by **sandboxing** (Capsicum) untrusted operations:




## Sandboxing:

- ▶ **archives** extracting
- ▶ **vulnxml** parsing
- ▶ repositories **signatures** checking and public keys extracting
- ▶ Concurrent **locking** system





# Pkg architecture



# The problems of the old solver in pkg

- ▶ Absence of conflicts resolving



# The problems of the old solver in pkg

- ▶ Absence of conflicts resolving
- ▶ No **alternatives** support (plain dependencies only)




# The problems of the old solver in pkg

- ▶ Absence of conflicts resolving
- ▶ No **alternatives** support (plain dependencies only)
- ▶ Can perform merely a **single task**: either install or upgrade or remove

# Tasks to solve

- ▶ Ports renaming:


- ▶ simple: racket-textual  $\rightarrow$  racket-minimal
- ▶ splitting/merging:



# Tasks to solve

- ▶ Ports renaming:

- ▶ simple: `racket-textual` → `racket-minimal`
- ▶ splitting/merging:




- ▶ Ports reorganising:

- ▶ files **moving**

# Tasks to solve

- ▶ Ports renaming:

- ▶ simple: `racket-textual` → `racket-minimal`
- ▶ splitting/merging:




- ▶ Ports reorganising:

- ▶ files **moving**
- ▶ **dependencies** change

# Tasks to solve

- ▶ Ports renaming:

- ▶ simple: racket-textual  $\rightarrow$  racket-minimal
- ▶ splitting/merging:



- ▶ Ports reorganising:

- ▶ files **moving**
- ▶ **dependencies** change
- ▶ adding or removing new **conflicts**



# Tasks to solve

There are another issues to be resolved:

- ▶ Find conflicts using files list

# Tasks to solve

There are another issues to be resolved:

- ▶ Find conflicts using files list
- ▶ Set jobs priorities using the following rules:

# Tasks to solve

There are another issues to be resolved:

- ▶ Find conflicts using files list
- ▶ Set jobs priorities using the following rules:
  - ▶ install **dependencies** first

# Tasks to solve

There are another issues to be resolved:

- ▶ Find conflicts using files list
- ▶ Set jobs priorities using the following rules:
  - ▶ install **dependencies** first
  - ▶ check for **reverse dependencies** and increase priority



# Tasks to solve

There are another issues to be resolved:

- ▶ Find conflicts using files list
- ▶ Set jobs priorities using the following rules:
  - ▶ install **dependencies** first
  - ▶ check for **reverse dependencies** and increase priority
  - ▶ deal with **conflicts** using the same priority



# Tasks to solve






There are another issues to be resolved:

- ▶ Find conflicts using files list
- ▶ Set jobs priorities using the following rules:
  - ▶ install **dependencies** first
  - ▶ check for **reverse dependencies** and increase priority
  - ▶ deal with **conflicts** using the same priority
  - ▶ packages removing **reverses** the priority order



# Existing systems

There are many examples of solvers used in different package management systems, for example:

- ▶  Zypper/SUSE - uses libsolv as the base
- ▶  Yum/RedHat - migrating to libsolv
- ▶  OpenBSD/pkg\_add - uses internal solver
- ▶  Apt/Debian - uses internal solver
- ▶  Pacman/Archlinux - uses internal solver

# External solvers

To interact with an external solver we have chosen the CUDF format used in the Mancoosi research project

<http://mancoosi.org>:

```
^^Ipackage: devel/libblah
```

```
^^Iversion: 1
```

```
^^Idepends: x11/libfoo
```

```
^^Ipackage: security/blah
```

```
^^Iversion: 2
```

```
^^Idepends: devel/libblah
```

```
^^Iconflicts: security/blah-devel
```

```
^^I
```



# Interaction with external solver

There are some limitations and incompatibilities with CUDF.

- ▶ CUDF supports plain integers as versions and we need to convert versions twice



# Interaction with external solver

There are some limitations and incompatibilities with CUDF.

- ▶ CUDF supports plain integers as versions and we need to convert versions twice
- ▶ There is no support of options in CUDF packages formulas

# Interaction with external solver

There are some limitations and incompatibilities with CUDF.

- ▶ CUDF supports plain integers as versions and we need to convert versions twice
- ▶ There is no support of options in CUDF packages formulas
- ▶ External solvers are often too complicated and large

# We need an internal solver!

## Alternatives:

- ▶ Write own logic of dependencies and conflicts resolution?

# We need an internal solver!

## Alternatives:

- ▶ Write own logic of dependencies and conflicts resolution?
- ▶ Use some existing solution?

# We need an internal solver!

## Alternatives:

- ▶ Write own logic of dependencies and conflicts resolution?
- ▶ Use some existing solution?
- ▶ Use some known algorithm?

# We need an internal solver!

## Alternatives:

- ▶ Write own logic of dependencies and conflicts resolution?
- ▶ Use some existing solution?
- ▶ Use some known algorithm?


## Use SAT solver for packages management

$$\overbrace{(x_1 \parallel \neg x_2 \parallel x_3) \& (x_3 \parallel \neg x_1) \& (x_2)}^{\text{SAT expression}}$$

Clause

# Packages universe

We convert all packages involved to a packages universe of the following structure:





# Making a SAT problem

- ▶ Assign a **variable** to each package: package A  $\rightarrow a_1$ ,  
package B  $\rightarrow b_1$

# Making a SAT problem

- ▶ Assign a **variable** to each package: package A  $\rightarrow a_1$ , package B  $\rightarrow b_1$
- ▶ Interpret a request as a set of **unary clauses**:
  - ▶ Install/Upgrade package A  $\rightarrow (a_1)$
  - ▶ Delete package B  $\rightarrow (\neg b_1)$

# Making a SAT problem

- ▶ Assign a **variable** to each package: package A  $\rightarrow a_1$ , package B  $\rightarrow b_1$
- ▶ Interpret a request as a set of **unary clauses**:
  - ▶ Install/Upgrade package A  $\rightarrow (a_1)$
  - ▶ Delete package B  $\rightarrow (\neg b_1)$
- ▶ Convert dependencies and conflicts to **disjuncted clauses**

# Converting dependencies and conflicts

- ▶ If package A depends on package B (versions  $B_1$  and  $B_2$ ), then we can either have package A not installed or any of B installed:

$$(\neg A \parallel B_1 \parallel B_2)$$

# Converting dependencies and conflicts

- ▶ If package A depends on package B (versions  $B_1$  and  $B_2$ ), then we can either have package A not installed or any of B installed:

$$(\neg A \parallel B_1 \parallel B_2)$$

- ▶ If we have a conflict between versions of B ( $B_1$ ,  $B_2$  and  $B_3$ ) then we ensure that merely one version is installed:

$$\underbrace{(\neg B_1 \parallel \neg B_2) \& (\neg B_1 \parallel \neg B_3) \& (\neg B_2 \parallel \neg B_3)}_{\text{Conflicts chain}}$$

# The solving of SAT problem

Some rules to follow to speed up SAT problem solving.

- ▶ Trivial propagation - solve **unary** clauses

# The solving of SAT problem

Some rules to follow to speed up SAT problem solving.

- ▶ Trivial propagation - solve **unary** clauses
- ▶ **Unit propagation** - solve clauses with only a single unsolved variable



# The solving of SAT problem

Some rules to follow to speed up SAT problem solving.

- ▶ Trivial propagation - solve **unary** clauses
- ▶ **Unit propagation** - solve clauses with only a single unsolved variable
- ▶ **DPLL** algorithm backtracking (conflict driven resolution is used now)





# The solving of SAT problem

Some rules to follow to speed up SAT problem solving.

- ▶ Trivial propagation - solve **unary** clauses
- ▶ **Unit propagation** - solve clauses with only a single unsolved variable
- ▶ **DPLL** algorithm backtracking (conflict driven resolution is used now)
- ▶ **Package specific** assumptions.

# SAT problem propagation

- ▶ Trivial propagation - direct install or delete rules

$$(\neg A \parallel B) \& \underbrace{(A)}_{\text{true}} \& \underbrace{(\neg C)}_{\text{false}} \& (\neg A \parallel \neg D)$$



# SAT problem propagation

- ▶ Trivial propagation - direct install or delete rules

$$(\neg A \parallel B) \& \underbrace{(A)}_{\text{true}} \& \underbrace{(\neg C)}_{\text{false}} \& (\neg A \parallel \neg D)$$

- ▶ Unit propagation - simple depends and conflicts


$$\overbrace{(\neg A \parallel B)}^{\text{Dependency}} \& \underbrace{(A)}_{\text{true}} \& \underbrace{(\neg C)}_{\text{false}} \& \overbrace{(\neg A \parallel \neg D)}^{\text{Conflict}}$$

$B \rightarrow \text{true}$   $D \rightarrow \text{false}$




# DPLL algorithm

DPLL is proved to be one of the efficient algorithms to solve SAT problem (not the fastest but more simple than alternatives).




# DPLL algorithm

DPLL is proved to be one of the efficient algorithms to solve SAT problem (not the fastest but more simple than alternatives).



# DPLL algorithm

DPLL is proved to be one of the efficient algorithms to solve SAT problem (not the fastest but more simple than alternatives).



# Package specific assumptions

Pure SAT solvers cannot deal with package management as they do not consider several packages peculiarities:

# Package specific assumptions

Pure SAT solvers cannot deal with package management as they do not consider several packages peculiarities:

- ▶ Try to keep **installed** packages (if no direct conflicts)



# Package specific assumptions

Pure SAT solvers cannot deal with package management as they do not consider several packages peculiarities:

- ▶ Try to keep **installed** packages (if no direct conflicts)
- ▶ Do not install packages if they are not **needed** (but try to upgrade if a user has requested upgrade)

# Package specific assumptions

Pure SAT solvers cannot deal with package management as they do not consider several packages peculiarities:

- ▶ Try to keep **installed** packages (if no direct conflicts)
- ▶ Do not install packages if they are not **needed** (but try to upgrade if a user has requested upgrade)
- ▶ Additional logic when dealing with **multi-repo**

# Solvers and Pkg

- ▶ Pkg may pass the formed universe to an external CUDF solver:

# Solvers and Pkg

- ▶ Pkg may pass the formed universe to an external CUDF solver:
  - ▶ convert **versions**
  - ▶ format request
  - ▶ parse output


# Solvers and Pkg

- ▶ Pkg may pass the formed universe to an external CUDF solver:
  - ▶ convert **versions**
  - ▶ format request
  - ▶ parse output
- ▶ Alternatively the internal SAT solver may be used:
  - ▶ convert the universe to **SAT** problem
  - ▶ formulate request
  - ▶ ???
  - ▶ **PROFIT**



# New dependencies formulae


$$libblah \geq 1.0 + option_1, +option_2 || libfoo! = 1.1$$



# New dependencies formulae

$libblah \geq 1.0 + option_1, + option_2 || libfoo! = 1.1$


- Can depend on normal packages and **virtual packages** (provides)



# New dependencies formulae

$libblah \geq 1.0 + option_1, + option_2 || libfoo! = 1.1$

- ▶ Can depend on normal packages and **virtual packages** (provides)
- ▶ Easy to define the **concrete** dependency versions






# New dependencies formulae

$libblah \geq 1.0 + option_1, + option_2 || libfoo! = 1.1$

- ▶ Can depend on normal packages and **virtual packages** (provides)
- ▶ Easy to define the **concrete** dependency versions
- ▶ **Alternative** dependencies



# Packages format

- Uses **xz** format:


# Packages format

- ▶ Uses **xz** format:
- ▶ ▶ **Terribly** slow
- ▶ XZ format is too **complicated**
- ▶ No place to put **signature**


# Packages format

- ▶ Uses **xz** format:
- ▶
  - ▶ **Terribly** slow
  - ▶ XZ format is too **complicated**
  - ▶ No place to put **signature**
- ▶ Metadata is compressed together with payload (**slow index**)

# Signatures now



# New format proposal



Ed25519 via asignify

For faster index

Plain tar + zstd compression

# New format proposal

- ▶ Uses **zstd** compression: very fast and good compression rate (faster and better than gz)

# New format proposal

- ▶ Uses **zstd** compression: very fast and good compression rate (faster and better than gz)
- ▶ Fast **index**, allow to build repos rapidly



# New format proposal

- ▶ Uses **zstd** compression: very fast and good compression rate (faster and better than gz)
- ▶ Fast **index**, allow to build repos rapidly
- ▶ Has place for dedicated signature

# New format proposal

- ▶ Uses **zstd** compression: very fast and good compression rate (faster and better than gz)
- ▶ Fast **index**, allow to build repos rapidly
- ▶ Has place for dedicated signature
- ▶ Extendable

# New format proposal

- ▶ Uses **zstd** compression: very fast and good compression rate (faster and better than gz)
- ▶ Fast **index**, allow to build repos rapidly
- ▶ Has place for dedicated signature
- ▶ Extendable
- ▶ No direct support of libarchive (yet)



FreeBSD

**Questions?**

[vsevolod@FreeBSD.org](mailto:vsevolod@FreeBSD.org)



FreeBSD