

# B343-C40-AAJ3

Blade Server - AMD EPYC™ 4005 & Ryzen™ 9000 - 3U 10-Node UP



### Key Features

- 3U 10-node front access server system
- Single AMD EPYC™ 4005 & Ryzen™ 9000 Series Processors per node
- Dual Channel DDR5 ECC/Non-ECC UDIMM, 4 x DIMMs per node
- 2 x 25Gb/s LAN ports via Broadcom® BCM57502 per node
- 2 x 2.5" Gen5 NVMe/SATA internal bays per node
- 1 x M.2 slot with PCIe Gen3 x1 interface per node
- 1 x FHHL PCIe Gen5 x16 slot per node
- 3 x OCP NIC 3.0 PCIe Gen4 slots for multi-host NICs
- 2+2 2000W 80 PLUS Titanium redundant power supplies

### Applications

Networks Server, Servers for Hybrid/Private Cloud...

### Specification

|             |                                                                                                                                                                               |                       |                                                                                                                                               |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| Dimensions  | 3U 10-Node - Front access (W447 x H132 x D770 mm)                                                                                                                             | PCIe Expansion Slots  | 1 x FHHL PCIe Gen5 x16 per node<br>3 x OCP NIC 3.0 PCIe Gen4, for multi-host NICs                                                             |
| Motherboard | MC43-BL0                                                                                                                                                                      | I/O Ports             | <b>Front:</b><br>2 x USB 3.2 Gen1, 1 x Mini-DP, 2 x SFP28, 1 x MLAN<br><b>Rear:</b><br>2 x CMC ports                                          |
| CPU         | AMD EPYC™ 4005 Series Processors<br>AMD Ryzen™ 9000 Series Processors<br>Single processor per node, TDP up to 170W                                                            | Backplane Board       | PCIe Gen5 x4 or SATA 6Gb/s                                                                                                                    |
| Socket      | 10 x AM5                                                                                                                                                                      | TPM                   | 1 x TPM header (SPI) per node, Optional TPM2.0 kit: CTM010                                                                                    |
| Chipset     | AMD B650E                                                                                                                                                                     | Power Supply          | 2+2 2000W 80 PLUS Titanium redundant power supplies<br>AC Input: 100-240V                                                                     |
| Memory      | Dual-channel DDR5 ECC/Non-ECC UDIMM, 4 x DIMMs per node<br>Up to 5600 MT/s (1DPC), 3600 MT/s (2DPC)                                                                           | System Management     | ASPEED® AST2600 Baseboard Management Controller<br>ASPEED® AST2620 Chassis Management Controller<br>GIGABYTE Management Console web interface |
| LAN         | <b>Front:</b><br>2 x 25Gb/s LAN (1 x Broadcom® BCM57502) per node, Support NCSI<br>1 x 10/100/1000 Mbps Management LAN per node<br><b>Rear:</b><br>2 x Chassis Management LAN | System Fans           | 5 x 80x80x80mm                                                                                                                                |
| Video       | Integrated in ASPEED® AST2600<br>- 1 x Mini-DP per node                                                                                                                       | Operating Properties  | Operating: 10°C to 30°C, 8% to 80% (non-condensing)<br>Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)                              |
| Storage     | <b>Internal:</b><br>2 x 2.5" Gen5 NVMe/SATA per node<br><b>Internal M.2:</b><br>1 x M.2 (2280/22110) per node, PCIe Gen3 x1                                                   | Packaging Content     | 1 x B343-C40-AAJ3<br>10 x CPU heatsinks<br>1 x Mini-DP to D-Sub cable<br>1 x L-shape Rail kit                                                 |
| RAID        | SATA RAID 0/1                                                                                                                                                                 | Ordering Part Numbers | 6NB343C40MR000AAJ3*                                                                                                                           |



Learn more at: <https://www.gigabyte.com/Enterprise>  
\* All specifications are subject to change without notice. Please visit our website for the latest information.  
\* All trademarks and logos are the properties of their respective holders.  
© 2025 Giga Computing Technology Co., Ltd. All rights reserved.  
Last updated: Dec 10, 2025

Designed by

