

E143-E30-AAG1

Edge Server - 1U UP 2-Bay Gen5 NVMe/SATA/SAS-4 Titanium



Key Features

- Single AMD EPYC™ 8004 Series Processors
- 6-Channel DDR5 RDIMM, 12 x DIMMs
- Dual ROM Architecture
- 1 x 1Gb/s LAN port via Intel® I210-AT
- 2 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 1 x M.2 slot with PCIe Gen3 x4 interface
- 2 x FHHL PCIe Gen5 x16 slots
- 2 x OCP NIC 3.0 PCIe Gen5 x16 slots
- 1+1 800W 80 PLUS Titanium redundant power supplies

Applications

Networks Server, Servers for Hybrid/Private Cloud, Edge Server...

Specification

Dimensions	1U (W438 x H43.5 x D520 mm)	PCIe Expansion Slots	2 x FHHL PCIe Gen5 x16 2 x OCP NIC 3.0 PCIe Gen5 x16, Support NCSI
Motherboard	ME33-DC0	I/O Ports	Front: 1 x USB 3.2 Gen1 Rear: 2 x USB 3.2 Gen1, 1 x Mini-DP, 1 x RJ45, 1 x MLAN
CPU	AMD EPYC™ 8004 Series Processors Single processor, cTDP up to 225W	Backplane Board	PCIe Gen5 x4 or SATA 6Gb/s or SAS-4 24Gb/s
OS Compatibility	OS Support List	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Socket	1 x LGA 4844 (Socket SP6)	Power Supply	1+1 800W 80 PLUS Titanium redundant power supplies AC Input: 100-240V
Chipset	System on Chip	System Management	ASPEED® AST2600 Baseboard Management Controller GIGABYTE Management Console web interface
Memory	6-Channel DDR5 RDIMM, 12 x DIMMs Up to 4800 MT/s (1DPC), 3600 MT/s (2DPC)	System Fans	5 x 40x40x56mm
LAN	1 x 1Gb/s LAN (1 x Intel® I210-AT), Supports NCSI 1 x 10/100/1000 Mbps Management LAN	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x Mini-DP	Packaging Content	1 x E143-E30-AAG1 1 x CPU heatsink 1 x Mini-DP to D-Sub cable
Storage	Front hot-swap: 2 x 2.5" Gen5 NVMe/SATA/SAS-4 ^[1] Internal M.2: 1 x M.2 (2280/22110), PCIe Gen3 x4 ^[1] SAS card is required to support SAS drives.	Ordering Part Numbers	6NE143E30DR000AAG1*
RAID	Require RAID add-in cards	Optional Parts	- 2-Section Rail kit (385-480mm): 25HB2-3A0204-K0R (MOQ: 500) - 2-Section Rail kit (660-840mm): 25HB2-3A0203-K0R

