

G294-S43-AAP2

HPC/AI Server - Intel® Xeon® 6700/6500 - 2U DP 16 x PCIe Gen5 GPUs



Key Features

- Supports up to 16 x Single slot Gen5 GPUs
- Dual Intel® Xeon® 6700/6500-Series Processors
- 8-Channel DDR5 RDIMM / MRDIMM, 24 x DIMMs
- 2 x 10 Gb/s LAN ports via Intel® X710-AT2
- 8 x 2.5" Gen5 NVMe/SATA/SAS-4 hot-swap bays
- 16 x FHFL PCIe Gen5 x16 for GPUs
- 2 x LP PCIe Gen5 x16
- Dual 3000 W 80 PLUS Titanium redundant power supply

Applications

AI Platform, AI Inference Server, Visual Computing...

Specification

Dimensions	2U (W448 x H87.5 x D962 mm, depth incl. 112 mm rear fans)	Storage	Front hot-swap: 8 x 2.5" Gen5 NVMe/SATA/SAS-4 ^{[1][2]}
Motherboard	MS44-G20		^[1] SAS card is required to support SAS drives. ^[2] Optional M.2 storage kit available for SATA support without requiring a PCIe storage card.
CPU	Intel® Xeon® 6 Processors - Intel® Xeon® 6700-Series Processors - Intel® Xeon® 6500-Series Processors Dual processor, TDP up to 250 W - At 30°C ambient, TDP up to 300 W - At 25°C ambient, TDP up to 350 W	PCIe Expansion Slots	16 x FHFL PCIe Gen5 x16, for GPUs 2 x LP PCIe Gen5 x16
OS Compatibility	OS Support List	I/O Ports	Rear: 2 x USB 3.2 Gen1, 1 x VGA, 2 x RJ45, 1 x MLAN
Socket	2 x LGA 4710 (Socket E2)	TPM	1 x TPM header (SPI), Optional TPM 2.0 kit: CTM012 1 x PRoT connector (only enabled on RoT SKU)
Chipset	System on Chip	Power Supply	Dual 3000 W 80 PLUS Titanium redundant power supply AC Input: 100-240 V *The system power supply requires C19 power cord.
Memory	8-Channel DDR5 RDIMM/MRDIMM, 24 x DIMMs ^[1] [RDIMM] Up to 6400 MT/s (1DPC), 5200 MT/s (2DPC) [MRDIMM] Up to 8000 MT/s ^[2] ^[1] Intel® Xeon® 6700E-Series Processors only support up to 16 x DIMMs. ^[2] MRDIMMs are supported only on select Intel® Xeon® 6 processors with P-cores and only in a 1DPC configuration.	System Fans	8 x 80x80x80mm
LAN	2 x 10 Gb/s LAN (1 x Intel® X710-AT2), Support NCSI 1 x 10/100/1000 Mb/s Management LAN	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Video	Integrated in ASPEED® AST2600 - 1 x VGA port	Packaging Content	1 x G294-S43-AAP2 2 x CPU heatsinks 4 x Carriers 1 x L-shape Rail kit
		Ordering Part Numbers	6NG294S43DR000AAP2*



Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.

* All trademarks and logos are the properties of their respective holders.

© 2026 Giga Computing Technology Co., Ltd. All rights reserved.

Last updated: Apr 24, 2026

Designed by

