

S452-Z30

Storage Server - 4U UP 42-Bay Gen3 NVMe/SATA/SAS

AMD
EPYCWindows
Server
2022
Certified

Key Features

- Single AMD EPYC™ 7003/7002 Series Processors
- 8-Channel DDR4 RDIMM/LRDIMM, 16 x DIMMs
- 2 x 1Gb/s LAN ports via Intel® I350-AM2
- 36 x 3.5"/2.5" SATA/SAS hot-swap bays
- 4 x 2.5" Gen3 NVMe/SATA hot-swap bays on the rear side
- 2 x 2.5" SATA hot-swap bays on the rear side
- SAS expander with 12Gb/s transfer speed
- 2 x M.2 slots with PCIe Gen3 x4 interface
- 4 x LP PCIe Gen4 x16 and x8 slots
- 2 x LP PCIe Gen3 x16 and x8 slots
- 1+1 1200W 80 PLUS Platinum redundant power supplies (-A00)
- 1+1 1300W 80 PLUS Platinum redundant power supplies (-A01/-B0x)
- 1+1 1300W 80 PLUS Titanium redundant power supplies (-ATx)

Applications

Storage Server...

Specification

Dimensions	4U (W482.6 x H177 x D625 mm)	PCIe Expansion Slots	4 x LP PCIe Gen4 x16 and x8 2 x LP PCIe Gen3 x16 and x8
Motherboard	MZ32-AR0	I/O Ports	Front: 2 x USB 3.0 Rear: 3 x USB 3.0, 1 x VGA, 2 x RJ45, 1 x MLAN
CPU	AMD EPYC™ 7003 Series Processors AMD EPYC™ 7002 Series Processors Single processor, cTDP up to 180W	Backplane Board	Front - CBPD400: SATA 6Gb/s or SAS 12Gb/s Rear - CBPD0C0: SATA 6Gb/s or SAS 12Gb/s Rear - CBP2021: SATA 6Gb/s Rear - COBPU43: PCIe Gen3 x4 or SATA 6Gb/s
Socket	1 x LGA 4094 (Socket SP3)	TPM	1 x TPM header (SPI), Optional TPM2.0 kit: CTM010
Chipset	System on Chip	Power Supply	1+1 1200W 80 PLUS Platinum redundant power supplies (-A00) 1+1 1300W 80 PLUS Platinum redundant power supplies (-A01/-B0x) 1+1 1300W 80 PLUS Titanium redundant power supplies (-ATx) AC Input: 100-240V
Memory	8-Channel DDR4 RDIMM/LRDIMM, 16 x DIMMs Up to 3200/2933 MT/s	System Management	ASPEED® AST2500 Baseboard Management Controller GIGABYTE Management Console web interface
LAN	2 x 1Gb/s LAN (1 x Intel® I350-AM2), Support NCSI 1 x 10/100/1000 Mbps Management LAN	System Fans	8 x 80x80x38mm
Video	Integrated in ASPEED® AST2500 - 1 x VGA port	Operating Properties	Operating: 10°C to 35°C, 8% to 80% (non-condensing) Non-operating: -40°C to 60°C, 20% to 95% (non-condensing)
Storage	Front hot-swap: 24 x 3.5"/2.5" SATA/SAS ^[1] Rear hot-swap: 12 x 3.5"/2.5" SATA/SAS ^[1] 4 x 2.5" Gen3 NVMe/SATA ^[2] 2 x 2.5" SATA ^[2] Internal M.2: 2 x M.2 (2242/2260/2280), PCIe Gen3 x4 ^[1] Storage card is required to enable SATA and SAS drives. - Broadcom SAS35x48 expander - Bandwidth: SATA 6Gb/s or SAS 12Gb/s per port ^[2] Rear side 2.5" bays only support Solid State Drives due to thermal consideration.	Packaging Content	1 x S452-Z30 1 x CPU heatsink 1 x 3-Section Rail kit
RAID	Require RAID add-in cards	Ordering Part Numbers	6NS452Z30MR-00-A*/B*

Learn more at: <https://www.gigabyte.com/Enterprise>

* All specifications are subject to change without notice. Please visit our website for the latest information.
* All trademarks and logos are the properties of their respective holders.

© 2025 Giga Computing Technology Co., Ltd. All rights reserved.

Designed by

