

X14SRA-T

Key Features

- Intel® Xeon® 600 Processors for Workstation, Single Socket E2 (LGA 4710-2), Up to 86 Cores, Up to 350W TDP
- Intel® W890
- Up to 1TB of DDR5 ECC RDIMM, 6400 MT/s (1DPC) or 5200 MT/s (2DPC)
- Up to 2TB DDR5 ECC 3DS RDIMM, 6400 MT/s (1DPC) or 5200 MT/s (2DPC)
- Up to 256GB of DDR5 ECC MRDIMM, 8000MT/s (1DPC)
- 2 PCIe 5.0 x16 Slots, Metal Armor Protection
- 2 PCIe 5.0 x8 Slots, Open Rear
- 2 M.2 Slots (2 PCIe 5.0 x4 from CPU, Support M-Key 2280/22110)
- 1 MCIO Connector to Support 2 U.2 Ports (PCIe 5.0 x4 from CPU) via cable for NVMe 2.5" SSD drives, Intel® Virtual RAID (VROC) 0 &1 (VROC Key Is Required)
- 1 10Gb Marvell® AQC113 LAN Port
- 1 1Gb Intel® I219LM LAN Port, Intel® VPro® Feature
- 1 on board TPM2.0 (can not support TPM 1.2)
- Overclocking supported on CPU and memory

X14SRA-F

Key Features

- Intel® Xeon® 600 Processor for Workstation, Single Socket E2 (LGA 4710-2), Up to 86 Cores, Up to 350W TDP
- Intel® W890
- Up to 1TB of DDR5 ECC RDIMM, 6400 MT/s (1DPC) or 5200 MT/s (2DPC)
- Up to 2TB DDR5 ECC 3DS RDIMM, 6400 MT/s (1DPC) or 5200 MT/s (2DPC)
- Up to 256GB of DDR5 ECC MRDIMM, 8000MT/s (1DPC)
- 2 PCIe 5.0 x16 Slots with Metal Armor Protection
- 2 PCIe 5.0 x8 Slots, Open Rear
- 2 M.2 Slots (2 PCIe 5.0 x4 from CPU; Support 2280/22110), M-Key
- 1 MCIO Connector to Support 2 U.2 Ports (PCIe 5.0 x4 from CPU) via cable for NVMe 2.5" SSD drives, Intel® Virtual RAID (VROC) 0 &1 (VROC Key Is Required)
- 1 1Gb Intel® I210AT LAN Port, IPMI share LAN
- 1 1Gb Intel® I219LM LAN Port, Intel® VPro® Feature
- 1 on board TPM2.0 (can not support TPM 1.2)
- Overclocking supported on CPU and memory
- OpenBMC

X14SPN-H

Key Features

- 2 USB3.2 type-A connectors and 4 USB2.0 headers
- Dual M.2 2242/2280 M-key slots for storage, up to PCIe Gen5x4
- Triple LAN RJ45 connectors. 2 Intel i226IT 2.5GbE with POE, and 1 Intel i219LM GbE
- Dual DDR5 5600/6400MHz SO/CSO-DIMM, up to 128GB, IB ECC
- Intel® Core™ Ultra X7 Processor 368H, up to 16 Core, 25W
- 2 COM (RS-232/422/485), Audio, 8 bits GPIO, SMBus connector and TPM2.0
- Dual M.2 expansion slots. 1 E-key, and 1 B-key with nano SIM
- Dual HDMI2.1. 1 HDMI2.1, and 1 HDMI2.1 TMDS (4K60Hz)
- One eDP1.4 and One MIPI D-PHY connector for embedded application
- 12~36V DC power input

X14SDW-72C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6776P-B, CPU TDP 325W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 1TB ECC RDIMM DDR5-6400MT/s in 8 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-64CM-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6756P-B, CPU TDP 325W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 1TB ECC RDIMM DDR5-6400MT/s in 8 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDW-42C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6726P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-40C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6716P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-36CE-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6556P-B, CPU TDP 215W, Intel Quick Assist Technology, Intel vRAN Accelerator, extended working temperature
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 25GbE SFP28 with Intel SoC1 1GbE RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-36C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6553P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 25GbE SFP28 with Intel SoC, 1 1GbE RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-42C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6726P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-36CE-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6556P-B, CPU TDP 215W, Intel Quick Assist Technology, Intel vRAN Accelerator, extended working temperature
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-36C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6553P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16
- M.2 Interface: 1 PCIe 4.0 x4 M.2 2280 M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-32C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6546P-B, CPU TDP 195W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-20C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6516P-B, CPU TDP 145W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-4800MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDI-36C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6553P-B, CPU TDP 235W, Intel® QuickAssist Technology, Intel® Media Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 1 PCIe 5.0 x16 (slot 6), 1 PCIe 5.0 x16 (slot 3) or 2 PCIe 5.0 x8 (slot 3 & 4), 1 PCIe 4.0 x8 (slot 2), 1 PCIe 4.0 x2 (slot 1, physical x4)
- 1 PCIe 4.0 x4 & 1 PCIe 4.0 x2 M.2 2280/22110 M-key
- Dual 100G QSFP28 with Intel SoC 1G RJ45 with Intel® Ethernet Controller i210IT
- Onboard TPM2.0 & Header support

X14SBW-TF

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB ECC RDIMM DDR5-6400MT/s and up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 4 PCIe 5.0 X8 via MCIO connectors
- 1 PCIe 5.0 x8 (WIO-R),2 PCIe 5.0 x16 (WIO-L),M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 2280, 22110, M-Key)
- Dual LAN with 10GBase-T with Intel®X550
- 4 USB 3.2 Gen1(2 rear, 2 via header), 8 SATA3 (via SlimSAS x8)
- Onboard TPM9672: TCG2.0, FIPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SBW-F

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB ECC RDIMM DDR5-6400MT/s and up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 4 PCIe 5.0 X8 via MCIO connectors
- 1 PCIe 5.0 x8 (WIO-R),2 PCIe 5.0 x16 (WIO-L),M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 2280, 22110, M-Key)
- Dual LAN with 1GbE with Intel®I210
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 8 SATA3 (via SlimSAS x8)
- Onboard TPM9672: TCG2.0, FIPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SBT-GAP

Key Features

- Intel® Xeon® 6900-series processors with P-cores, Single Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W TDP
- 12 DIMM slots supporting up to 3TB
- 1 PCIe 5.0 x8 via customized 124-pin slim cool edge connector(for front I/O module)
- 8 PCIe 5.0 x8 via MCIO connectors to support AIOM, storage devices or PCIe expansion slots
- I/O: 1 COM, TPM header
- 1 PCIe 5.0 x8 GENZ 2C connector to support 2x M.2 (2280,22110) via proprietary M.2 adapter

X14SBT-G

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- 16 DIMM slots support RDIMM / MRDIMM(1DPC)
- 1 PCIe 5.0 x8 via customized 124-pin slim cool edge connector(for front I/O module)
- 2 PCIe 5.0 x16 via Molex Impleplus connectors
- 4 PCIe 5.0 X8 via MCIO connectors
- M.2 Interface: 2 PCIe5.0 x4 (Form Factor: 2280, 22110, M-Key)
- I/O: 1 COM, TPM header

X14SBSC

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 512GB MRDIMM with speeds up to 8000 MT/s (1DPC) or 4TB of RDIMM (3DS) with speeds up to 6400 MT/s (1DPC) or 5200 MT/s (2DPC) in 16 DIMM slots
- 1 PCIe 5.0 x8,3 PCIe 5.0 x16,M.2 Interface: 2 PCIe 4.0 x2 via SAS3808n (Form Factor: 2280, 22110, M-Key)
- I/O: 1 COM, TPM header, 1 VGA
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SBM-TP4F

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB ECC RDIMM DDR5-6400MT/s or up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 4 PCIe 5.0 X8 via MCIO connectors
- 1 PCIe 5.0 x8,2 PCIe 5.0 x16,M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 2280, 22110, M-Key)
- Quad LAN with 2x 10GBase-T and 2x 10G SFP+ with Intel® X710-TM4
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 2 SATA3 ports

X14SBM-TF

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB ECC RDIMM DDR5-6400MT/s or up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 4 PCIe 5.0 X8 via MCIO connectors
- 1 PCIe 5.0 x8,2 PCIe 5.0 x16,M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 2280, 22110, M-Key)
- Dual LAN with 10GBase-T with Intel® X710-AT2
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 2 SATA3 ports
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SBI-TF

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP up to 350W
- Up to 2TB ECC RDIMM DDR5-6400MT/s and up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 6 PCIe 5.0 x8 via MCIO connectors (JNVME3-6 are enabled with the specific CPU** installed)
- 3 PCIe 5.0 x16 (SLOT6 is enabled with the specific CPU** installed), 3 PCIe 5.0 x8,M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 22110, M-Key)
- Dual LAN with 10GBase-T with Intel®X550
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 4 SATA3 (via SlimSAS x4)
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification
- **Specific CPUs: Intel® Xeon® 6781P, 6761P, 6741P, 6731P, 6521P

X14SBI-F

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP up to 350W
- Up to 2TB ECC RDIMM DDR5-6400MT/s and up to 512GB MRDIMM DDR5-8000MT/s in 8 DIMM slots
- 6 PCIe 5.0 x8 via MCIO connectors (JNVME3–6 are enabled with the specific CPU** installed)
- 3 PCIe 5.0 x16 (SLOT6 is enabled with the specific CPU** installed), 3 PCIe 5.0 x8,M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 22110, M-Key)
- Dual LAN with 1GbE with Intel®I210
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 4 SATA3 (via SlimSAS x4)
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification
- **Specific CPUs: Intel® Xeon® 6781P, 6761P, 6741P, 6731P, 6521P

X14SBHM

Key Features

- Intel® Xeon® 6700/6500-seires processors with P-cores or Intel® Xeon® 6700-series processor with E-cores , Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 512GB MRDIMM with speeds up to 8000 MT/s (1DPC) or 4TB of RDIMM(3DS) with speeds up to 6400 MT/s (1DPC) or 5200 MT/s (2DPC) in 16 DIMM slots
- 2 PCIe 5.0 x16 M-XIO 1 PCIe 5.0 x16 AIOM M.2 Interface: 2 PCIe 5.0 x2 M-PIC M.2 Form Factor: 2280, 22110 M.2 Key: M-Key
- AIOM for LAN
- I/O: 1 DC-SCM

X14SBH-AP

Key Features

- Intel® Xeon® 6900 series processors with P-cores, Single Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W TDP
- Up to 3TB ECC RDIMM, DDR5-8800MT/s (1DPC) in 12 DIMM slots
- 5 PCIe 5.0 x8 via MCIO connectors
- 2 PCIe 5.0 x16 4C; 1 PCIe 5.0 x16 AIOM
- M.2 Interface: 2 PCIe 5.0 x2; M.2 Form Factor: 2280, 22110, 25110; M.2 Key: M-Key
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification
- AIOM for LAN

X14SBH

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP up to 350W
- Up to 512GB MRDIMM with speeds up to 8000 MT/s (1DPC) or 4TB of RDIMM(3DS) with speeds up to 6400 MT/s (1DPC) or 5200 MT/s (2DPC) in 16 DIMM slots
- 10 PCIe 5.0 x8 via MCIO connectors
- 2 PCIe 5.0 x16 4C 1 PCIe 5.0 x16 AIOM M.2 Interface: 2 PCIe 5.0 x2 (Form Factor: 2280, 22110, 25110, M-Key)
- AIOM for LAN
- Onboard TPM9672: TCG2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SBGM

Key Features

- Intel® Xeon® 6700 series processors with P-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB ECC RDIMM DDR5-6400MT/s and up to 512GB MRDIMM DDR5-8000MT/s in 16 DIMM slots
- 16 PCIe 5.0 x8 MCIO M.2 Interface: 2 PCIe 5.0 x2 M.2 Form Factor: 2280, 22110 M.2 Key: M-Key

X14SAZ-TLN4F

Key Features

- Intel Core Ultra 9/7/5 Series 2 Processor, CPU TDP supports Up to 125W TDP
- Intel® W880
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO port M.2 Interface: 1 PCIe 5.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 2 HDMI 2.1 port)
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 12V DC power input
- Onboard TPM9672: TCG 2.0, FIPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SAZ-F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, CPU TDP supports Up to 125W TDP
- Intel® W880
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO port M.2 Interface: 1 PCIe 5.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 2 HDMI 2.1 port)
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 12V DC power input
- Onboard TPM9672: TCG 2.0, FIPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SAV-TLN4F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 125W TDP
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4), 1 MCIO x8 port, 1 MCIO x4 port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 B-Key 3052 (PCIe 4.0 x1/USB 3)
- Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports via cable; RAID 0,1,5,10
- Supports 12V DC power input

X14SAV-LVDS

Key Features

- Intel® Core® Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 65W
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4) 1 PCIe 4.0 x4 MCIO port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 E-Key 2230 (PCIe 4.0 x1/USB 2.0)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 24 bit LVDS, 2 DP 2.1 ports, 2 HDMI 2.1 ports)
- Supports 12V - 24V DC power input
- Both onboard TPM chip SLB9672: TCG2.0, FIPs 140-2 Level 2 and pin header

X14SAV-F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 125W TDP
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4), 1 MCIO x8 port, 1 MCIO x4 port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 B-Key 3052 (PCIe 4.0 x1/USB 3)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports via cable; RAID 0,1,5,10
- Supports 12V DC power input

X14SAE-F

Key Features

- Intel® Core™ Ultra 200S Plus Processors (Ultra 7/5) and Core™ Ultra 9/7/5 Series Processors, Single Socket LGA-1851(Intel® V1 Socket) supported, CPU TDP supports Up to 125W TDP
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz (2SPC CUDIMM only), in 4 DIMM slots
- 2 M.2 slots (1 PCIe 4.0 x4 from PCH; support 2280/22110, and 1 PCIe5.0 x4 from CPU, support 2280); M.2 Key: M-Key
- 2 PCIe 5.0 x16 slots (16/NA or 8/8), 1 PCIe 4.0 x4 slot
- Single 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller
- Single 1 Gigabit LAN with Intel® Ethernet i219LM LAN controller [AMT/vPro]
- Single 1 Gigabit dedicated LAN with Realtek RTL8211F controller
- Intel® W880 Controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports Thunderbolt 4
- 1 VGA, 1 HDMI 2.1*, 1 DP 2.1**, 1 Thunderbolt™ 4.0 Type-C**Supports data rates of up to 10 Gbps **Supports data rates of up to 10 Gbps
- Onboard TPM2.0

X14SAE

Key Features

- Intel® Core™ Ultra 200S Plus Processors (Ultra 7/5) and Core™ Ultra 9/7/5 Series Processors, Single Socket LGA-1851(Intel® V1 Socket) supported, CPU TDP supports Up to 125W TDP
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz (2SPC CUDIMM only), in 4 DIMM slots
- 2 M.2 slots (1 PCIe 4.0 x4 from PCH; support 2280/22110, and 1 PCIe5.0 x4 from CPU, support 2280); M.2 Key: M-Key
- 2 PCIe 5.0 x16 slots(16/NA or 8/8), 1 PCIe 4.0 x4 slot
- Single 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller
- Single 1 Gigabit LAN with Intel® Ethernet i219LM LAN controller [AMT/vPro]
- 1 HDMI 2.1*, 1 DP 2.1**, 1 Thunderbolt™ 4.0 Type-C**Supports data rates of up to 10 Gbps **Supports data rates of up to 10 Gbps
- Intel® W880 Controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports Thunderbolt 4
- Onboard TPM2.0

X14QBH+

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores, Quad Socket LGA-4710 (Socket E2) supported, CPU 150W to 350W TDP)
- Up to 16TB ECC RDIMM, DDR5-6400MT/s in 64 DIMM slots
- 1 x DP port, 1 x COM Port, 2 x USB 3.0 Ports, and 1 x BMC Gbe LAN Port via AOM-218H2-IO - I/O board
- 32 x PCIe 5.0 x8 via MCIO Connectors
- 2 x PCIe 5.0 x16 via AIOM Connectors
- AST2600 BMC, TPM 2.0 (HW Root of Trust)

X14DBT-FLAP

Key Features

- Intel® Xeon® 6900 series processors with P-cores, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 6400MT/s in 24 DIMM slots
- Support DDR5-MRDIMM 8800MT/s in 24 DIMM slots
- One PCIe 5.0 x16 interface via 2 MCIO connectors
- up to two M.2 22x110mm form factor
- One PCIe 5.0x16 Riser cards supporting high speed interface
- Two PCIe 5.0x4 NVMe E1.S Storage ports via MCIO connector
- One PCIe 5.0x16 to AIOM slot
- Direct Cold Plate Cooling technology over CPU and VRM chips, and DIMM

X14DBT-FAP

Key Features

- Intel® Xeon® 6 processors, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports up to 500W
- Support DDR5 6400MT/s in 24 DIMM slots
- Support DDR5-MRDIMM 8800MT/s in 24 DIMM slots
- One PCIe 5.0 x16 interface via 2 MCIO connectors
- up to two M.2 22x110mm form factor
- One PCIe 5.0x16 Riser cards supporting high speed interface
- Two PCIe 5.0x4 NVMe E1.S Storage ports via MCIO connector
- One PCIe 5.0x16 to AIOM slot
- Direct Cold Plate Cooling technology over CPU chips

X14DBT-B

Key Features

- Intel® Xeon® 6700/6500-series processors with P-cores or E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Supports single CPU opeartion
- total 16 DDR5 (up to 6400MT/s) DIMM slots
- Support DDR5-MRDIMM 8000MT/s in 16 DIMM slots
- two PCIe 5.0x16 Riser cards supporting high speed interface
- PCIe 5.0 NVMe and SAS storages with optional RAID
- up to four M.2 22x110 with optional RAID
- support CXL 1.0, 1.1, 2.0 Type-3 Memory
- PCIe 5.0x16 to AIOM slot

X14DBM-SP

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Supports Single CPU Operation
- Support DDR5 RDIMM 5200MT/s in 32 DIMM slots (2DPC. Using 6400MT/s DIMM)
- Support DDR5 RDIMM 6400MT/s in 16 DIMM slots (1DPC. Using 6400MT/s DIMM)
- Support DDR5 MRDIMM 8000MT/s in 16 DIMM slots(1DPC. Using 8800MT/s MRDIMM & P-core CPU)
- 8 NVMe ports PCIe 5.0 x8 via 8 MCIO connectors
- M.2 Interface: 2 PCIe5.0 x2 M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Modular design. 32 DIMM, AIOM, up to 24 drives support.

X14DBM-APL

Key Features

- Intel® Xeon® 6 processors, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports up to 500W
- Supports Single CPU Operation
- Support DDR5-RDIMM 6400MT/s in 24 DIMM slots
- Support DDR5-MRDIMM 8800MT/s in 24 DIMM slots
- 8 NVMe ports PCIe 5.0 x8 via 8 MCIO connectors
- M.2 Interface: 2 PCIe5.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Modular design. 24 DIMM, AIOM, up to 24 drives support.

X14DBM-AP

Key Features

- Intel® Xeon® 6 processors, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports up to 500W
- Supports Single CPU Operation
- Support DDR5-RDIMM 6400MT/s in 24 DIMM slots
- Support DDR5-MRDIMM 8800MT/s in 24 DIMM slots
- 8 NVMe ports PCIe 5.0 x8 via 8 MCIO connectors
- M.2 Interface: 2 PCIe5.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Modular design. 24 DIMM, AIOM, up to 24 drives support.

X14DBI-T

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Dual Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Total up to 4TB ECC RDIMM DDR5-6400MT/s in 16 DIMM slots
- Support CXL 2.0
- 4 PCIe 5.0 x16
- 2 PCIe 5.0 x8
- 3 PCIe 5.0 x8 via MCIO connectors
- M.2 Interface: 2 PCIe 5.0 x4M.2 Form Factor: 2280, 22110
- Dual LAN with 10GBase-T with Broadcom® BCM57416
- 6 USB 3.2 Gen1 (4 rear and 2 via header)
- 10 SATA3 ports

X14DBI

Key Features

- Intel® Xeon® 6500/6700-series processors with E-cores and P-cores, Dual Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Total up to 4TB ECC RDIMM DDR5-6400MT/s in 16 DIMM slots
- Support CXL 2.0
- 4 PCIe 5.0 x16
- 2 PCIe 5.0 x8
- 3 PCIe 5.0 x8 via MCIO connectors
- M.2 Interface: 2 PCIe 5.0 x4M.2 Form Factor: 2280, 22110
- Dual LAN with 1GBase-T with Broadcom® BCM5720
- 6 USB 3.2 Gen1 (4 rear and 2 via header)
- 10 SATA3 ports

X14DBHM

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Support 5200MT/s DDR5 RDIMM/LRDIMM in 32 DIMM slots (2DPC)
- Support 6400MT/s DDR5 RDIMM/LRDIMM in 16 DIMM slots (1DPC)
- Support 8000MT/s DDR5 MRDIMM in 16 DIMM slots (1DPC)
- 8 PCIe 5.0 x8 via MCIO connectors
- 4 Multi-Trak PCIe 5.0 x16
- 1 Multi-Trak PCIe 5.0 x8
- M.2 Interface: 2 PCIe5.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- 2 AIOM PCIe 5.0 x16 slots
- I/O: 1 DC-SCM

X14DBG-XAP

Key Features

- Support Single CPU Operation
- Intel® Xeon® 6900 series processors with P-cores, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 6400MT/s in 24 DIMM slots
- M.2 Interface: 2 PCIe5.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Support up to 16 Single-Width PCIe Gen5 x8 cards or 8 Double-Width PCIe Gen5 x16 cards
- Modular design. 24 DIMM, AIOM, up to 24 drives support.

X14DBG-SP

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores or 6700 series processors with E-cores, Dual Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W
- Support DDR5 6000MT/s in 32 DIMM slots
- Support DDR5 6400MT/s in 16 DIMM slots
- 18 PCIe 5.0 x8 MCIO connectors
- 1 PCIe 5.0 x8 slot for IO riser card
- 2 M.2 PCIe5.0 x4
- 1 AIOM slot

X14DBG-MAP

Key Features

- 6th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 with up to speeds of 6400MT/s (RDIMM) or 8800MT/s (MRDIMM) in 24 DIMM slots
- 1 PCIe 5.0 x8 slot for IO riser card
- 22 PCIe 5.0 x8 MCIO connectors
- M.2 Interface: 2 PCIe5.0 x2_x000D_ M.2 Form Factor: 2280_x000D_ M.2 Key: M-Key
- 1 DC-SCM slot for modular BMC
- NVIDIA MGX

X14DBG-LC+

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores. LGA-4710 (Socket E2) CPU TDP supports Up to 350W TDP
- Support DDR5 RDIMM 5200MT/s in 32 DIMM slots (2DPC)
- Support DDR5 MRDIMM 8000MT/s in 16 DIMM slots (1DPC)
- M.2 Interface: 2 PCIe5.0 x4M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- 4 MCIO Connectors PCIe 5.0 x8 (NVMe)
- 4 MCIO Connectors PCIe 5.0 x16 (Bluefield)
- 1 MCIO Connectors PCIe 5.0 x4 (NVMe M.2 RAID controller)
- 16 MCIO Connectors PCIe 5.0 x16 (Networking, GPU direct)
- 8 EXAMAX PCIe 5.0 x16 (GPU)
- Networking options provided via Intel X710 via. AOM-GP805-IO
- Support Nvidia HGX Blackwell B200

X14DBG-LC

Key Features

- Intel® Xeon® 6700/6500 series processors with P-cores. LGA-4710 (Socket E2) CPU TDP supports Up to 350W TDP
- Support 8TB DDR5 RDIMM in 32 DIMM slots (2DPC)
- M.2 Interface: 2 PCIe 5.0 x4 M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- 4 MCIO Connectors PCIe 5.0 x8 (NVMe)
- 4 MCIO Connectors PCIe 5.0 x16 (Bluefield)
- Networking options provided via Intel X710 via. LOM
- Support Nvidia HGX Blackwell B300

X14DBG-GD

Key Features

- Intel® Xeon® 6900 series processors with P-cores, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 8800MT/s in 24 DIMM slots
- M.2 Interface: 2 PCIe5.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Modular design. 24 DIMM, AIOM, up to 24 drives support.
- Support Intel Habana Gaudi 3 GPU

X14DBG-DAP

Key Features

- Intel® Xeon® 6900-series processors with P-cores, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports up to 500W
- Support DDR5 with up to speeds of 6400MT/s (RDIMM) or 8800MT/s (MRDIMM) in 24 DIMM slots
- M.2 Interface: 2 PCIe5.0 x4M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- 5 MCIO Connectors PCIe 5.0 x8 (NVMe)
- 2 MCIO Connectors PCIe 5.0 x16 (Bluefield)
- 1 MCIO Connectors PCIe 5.0 x4 (NVMe M.2 RAID controller)
- 8 EXAMAX PCIe 5.0 x16 (Networking, GPU direct)
- 8 EXAMAX PCIe 5.0 x16 (GPU)
- Networking options provided via Intel X710 via. AOM-DP805-IO
- Support Nvidia HGX Blackwell

X14DBG-AP

Key Features

- Intel® Xeon® 6900 series processors with P-cores, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 6400MT/s in 24 DIMM slots
- 20 PCIe 5.0 x8 MCIO connectors
- 1 PCIe 5.0 x8 slot for IO riser card
- 2 M.2 PCIe5.0 x4
- 1 AIOM slot

X13SWA-TF

Key Features

- Intel® Xeon® W-3400 series, W-2400 series, W-3500 series, W-2500 series processors, Up to 60 CPU cores and a thermal design power (TDP) of up to 385W.
- Intel® W790
- Up to 4TB(W-3400/ W-3500)/2TB(W-2400/ W-2500) 3DS ECC RDIMM, 1TB(W-3400)/512GB(W-2400) ECC RDIMM; DDR5-4800MT/s(1DPC)/ 4400MT/s(2DPC), in 16 DIMM slots
- M.2 Interface: 4 PCIe 5.0 x4 (Software RAID 0,1,5,10); M.2 Form Factor: 2280/22110; M.2 Key: M-Socket (w/o heat sink)
- 2 U.2 PCIe 3.0 for NVMe 2.5" SSD drives (U.2-1, U.2-2; Software RAID 0,1)
- Xeon® W-3400/ W-3500 Series Processors: 6 PCIe 5.0 x16 Slots, support up to 6 Single Width/4 Double Width/2 Triple Width GPU cardsXeon® W-2400/ W-2500 Series Processors:3 PCIe 5.0 x16 Slots, support up to 3 Single Width/3 Double Width/2 Triple Width GPU cards (slot 3/5/7)
- 1GbE LAN port with Intel® Ethernet Controller I210-AT10GbE LAN with Marvell AQC113C
- 8 SATA 3 (6Gb, RAID 0, 1, 5, 10)
- IPMI Supported
- Overclocking Supported (optional)

X13SRN-H-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-H

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfcie: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-E-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfcie: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-E

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfcie: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRA-TF

Key Features

- Intel® Xeon® W-3400 series, W-2400 series, W-3500 series, W-2500 series processors, Single Socket Socket E (LGA-4677) supported, Up to 60 CPU cores and a thermal design power (TDP) of up to 385W.
- Intel® W790
- Up to 2TB RDIMM 3DS, 512GB ECC RDIMM; DDR5-4800MT/s (1DPC)/4400MT/s (2DPC), in 8 DIMM slots
- 3 PCIe 5.0 x16 Slots, support up to 3 Single-Width, 2 Double-Width, or 2 Triple-Width GPU cards; 1 PCIe 4.0 x4 Slots
- M.2 Interface: 2 PCIe 5.0 x4 (Software RAID 0,1); M.2 Form Factor: 2280/22110; M.2 Key: M-Socket (w/o heat sink)
- 1GbE LAN port with Intel® Ethernet Controller I210-AT10GbE LAN with Marvell AQC113
- 6 SATA 3 (6Gb, RAID 0, 1, 5, 10)
- IPMI Supported
- Overclocking Supported (optional)

X13SEW-TF

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket V0) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 1 PCIe 5.0 x8 (in x16)1 PCIe 5.0 x32 M.2 Interface: 1 PCIe 3.0 x2 M.2 Form Factor: 2280, 22110 M.2 Key: M-Key
- 10 NVMe ports PCIe 5.0 x8 via 5 MCIO connectors
- Dual LAN with 10GBase-T with Intel® X550
- 2 SuperDOM with built-in power
- I/O: 1 VGA, 2 COM, 1 TPM header
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 3 USB 2.0 (2 rear, 1 via Type-A)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports

X13SEW-F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket V0) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 1 PCIe 5.0 x8 (in x16)1 PCIe 5.0 x32 M.2 Interface: 1 PCIe 3.0 x2 M.2 Form Factor: 2280, 22110 M.2 Key: M-Key
- 10 NVMe ports PCIe 5.0 x8 via 5 MCIO connectors
- Dual LAN with 1GbE with Intel® I210
- 2 SuperDOM with built-in power
- I/O: 1 VGA, 2 COM, 1 TPM header
- 4 USB 3.2 Gen1 (2 rear, 2 via header), 3 USB 2.0 (2 rear, 1 via Type-A)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports

X13SEVR-SP13F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 225W TDP
- Intel C741® Chipset
- Up to 2TB ECC RDIMM/RDIMM 3DS, DDR5-5600MT/s in 8 DIMM slots
- 2 PCIe 5.0 x8 MCIO connector, support riser card: RSC-S-68G5 for FHHL PCIe card
- IEEE1588 v2 & Synchronous Ethernet supportDPLL/OCXO designUp to 8 hours hold-over
- 12 SFP28 for 25GbE Ethernet and 1 IPMI shared LAN with Intel® Ethernet Controller E810-CAM11 RJ45 for Gigabit Ethernet and IPMI shared LAN with Intel® Ethernet Controller I210-ATNote that only port10 support E810 NC-SI function
- M.2 Interface: 1 PCIe 4.0 x4, M.2 Form Factor: 2280
- 1 COM header;1 VGA header; 2 USB 3.2 Gen1 Ports
- 4 SMA for 1PPS & 10MHz (two Input two Output)1x SMA for GNSS input with onboard GNSS module

X13SET-PT

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 300W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 1 PCIe 5.0 x16 Left Riser Slot
- 1 PCIe 5.0 x16 Right Riser Slot
- 1 PCIe 5.0 x16 Proprietary Storage adapter Slot
- Dual LAN with 10G SFP+_x000D_
- M.2 Interface: 2 PCIe 5.0x4M.2 Form Factor: 2280,22110M.2 Key: M-Key
- Intel® C741 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA, 1 COM, TPM header

X13SET-GC

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) or DDR5-4400MT/s (2DPC) in 16 DIMM slots
- 1 PCIe 5.0 x8 via customized 124-pin slim cool edge connector(for front I/O module)
- 2 PCIe 5.0 x16 via Molex Impleplus connectors
- 4 PCIe 5.0 X8 via MCIO connectors
- Boardcom 3808 controller for 6 SAS3 drives
- I/O: 1 COM, TPM header
- M.2 Interface: 2 PCIe 3.0x4&SATAM.2 Form Factor: 2280M.2 Key: M-Key

X13SET-G

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) or DDR5-4400MT/s (2DPC) in 16 DIMM slots
- 1 PCIe 5.0 x8 via customized 124-pin slim cool edge connector(for front I/O module)
- 2 PCIe 5.0 x16 via Molex Impleplus connectors
- 4 PCIe 5.0 X8 via MCIO connectors
- I/O: 1 COM, TPM header
- M.2 Interface: 2 PCIe 3.0x4&SATAM.2 Form Factor: 2280M.2 Key: M-Key

X13SEM-TF

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 8 NVMe ports PCIe 5.0 x4 via 4 MCIO connectors
- 1 PCIe 5.0 x8,2 PCIe 5.0 x16,4 PCIe 5.0 x8 MCIO connectorsM.2 Interface: 2 PCIe 4.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X550
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports or 2 PCIe 3.0 x4 NVMe + 2 SATA3 ports; RAID (SATA) 0,1,5,10

X13SEM-F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 8 NVMe ports PCIe 5.0 x4 via 4 MCIO connectors
- 1 PCIe 5.0 x8,2 PCIe 5.0 x16,4 PCIe 5.0 x8 MCIO connectors M.2 Interface: 2 PCIe 4.0 x2M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- Dual LAN with 1GbE with Intel® I350
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports or 2 PCIe 3.0 x4 NVMe + 2 SATA3 ports; RAID (SATA) 0,1,5,10

X13SEI-TF

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E), CPU TDP supports up to 350W TDP
- Intel® C741 Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 2 MCIO (PCIe5.0 x8) connectors for 4 NVMe SSDs
- 2 PCIe 5.0 x16; 3 PCIe 5.0 x8
- M.2 Interface: 2 PCIe 5.0 x4 (Form Factor: 2280/22110, M-Key)
- Dual LAN with 10GbE with Intel® X550
- 4 USB 3.2 Gen1 (2 rear, 1 Type-A, 1 via header), 2 USB 2.0 (2 rear)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports

X13SEI-F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E), CPU TDP supports up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 2 MCIO (PCIe5.0 x8) connectors for 4 NVMe SSDs
- 2 PCIe 5.0 x16; 3 PCIe 5.0 x8
- M.2 Interface: 2 PCIe 5.0 x4 (Form Factor: 2280/22110, M-Key)
- Dual LAN with 1GbE with Intel® I210
- 4 USB 3.2 Gen1 (2 rear, 1 Type-A, 1 via header), 2 USB 2.0 (2 rear)
- Intel® C741 controller for 10 SATA3 (6 Gbps) ports

X13SEFR-A

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) or DDR5-4400MT/s (2DPC) in 16 DIMM slots
- 1 PCIe 5.0 x16
- 1 PCIe 5.0 x16 AIOM slot
- 5 PCIe 5.0 x8 via MCIO connectors
- AIOM for LAN
- I/O: 1 VGA, 1 COM, TPM header
- M.2 Interface: 2 PCIe 3.0x2&SATAM.2 Form Factor: 2280,22110M.2 Key: M-Key

X13SEED-SF

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB ECC RDIMM/RDIMM 3DS, DDR5-5600MT/s in 8 DIMM slots
- 1 PCIe 5.0 x16 Right Riser Slot, support LP PCIe card2 PCIe 5.0 x16 Left Riser Slot, support FHHL PCIe card
- M.2 Interface: 2 PCIe 5.0 x4, M.2 Form Factor: 2280/22110
- 1 VGA Port; 2 USB 2.0 Ports; 1 Serial Port via KVM Connector.
- 1 SFP for Gigabit Ethernet and IPMI shared LAN with Intel® Ethernet Controller I210-IS

X13SEED-F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB ECC RDIMM/RDIMM 3DS, DDR5-5600MT/s in 8 DIMM slots
- 1 PCIe 5.0 x16 Right Riser Slot, support LP PCIe card2 PCIe 5.0 x16 Left Riser Slot, support FHHL PCIe card
- M.2 Interface: 2 PCIe 5.0 x4, M.2 Form Factor: 2280/22110
- 1 VGA Port; 2 USB 2.0 Ports; 1 Serial Port via KVM Connector.
- 1 RJ45 for Gigabit Ethernet and IPMI shared LAN with Intel® Ethernet Controller I210-AT

X13SEDW-F

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) or DDR5-4400MT/s (2DPC) in 16 DIMM slots
- 2 PCIe 5.0 x16 4C 1 PCIe 5.0 x8 AIOM 1 PCIe 5.0 x0 AIOM M.2 Interface: 2 PCIe 3.0 x2 M.2 Form Factor: 2280, 22110 M.2 Key: M-Key
- 8 MCIO PCIe 5.0 x4 connectors 1 MCIO PCIe 5.0 x8 connectors
- AIOM for LAN
- I/O: 1 VGA, 1 COM, 1 TPM header, 1 NC-SI header
- Intel® C741 controller for 12 SATA3 (6 Gbps) ports

X13SEB-TF

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 2TB 3DS ECC RDIMM, DDR5-5600MT/s (1DPC) in 8 DIMM slots
- 2 PCIe 5.0 x8 2 PCIe 5.0 x16 M.2 Interface: 2 PCIe 3.0 x4 M.2 Form Factor: 2280, 22110 M.2 Key: M-Key
- Dual LAN with 10GbE with Intel® X710
- 2 USB 3.0 (2 rear)
- I/O: 1 VGA, 1 TPM header

X13SCW-F

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C266 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 (Left Riser Slot); 1 PCIe 4.0 x4 (in x16, Right Riser slot)
- M.2 Interface: 2 PCIe 4.0 x4 (Form Factor: 2280/22110, M-Key)
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- 3 USB 3.2 Gen2 ports (2 rear + 1 Type A); 2 USB 3.2 Gen1 ports (via heaader); 4 USB 2.0 ports (2 rear + 2 via header)

X13SCL-IF

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C262 controller for 6 SATA3 (6 Gbps) ports ; RAID 0,1,5,10
- Up to 64GB ECC Unbuffered DIMM, DDR5-4800MHz, in 2 DIMM slots
- 1 PCIe 5.0 x16 2 SlimSAS (2 PCIe 4.0x4 or 1 PCIe 4.0x4 & 4 SATA)
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280 M.2 Key: M-Key
- 4 USB 3.2 Gen1 ports (2 rear + 2 via header) 2 USB 2.0 ports (2 rear)

X13SCL-F

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C262 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x81 PCIe 5.0 x8 (in x16)2 PCIe 4.0 x4 (in x8)
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- 4 USB 3.2 Gen1 ports (2 rear + 2 via header)6 USB 2.0 ports (2 rear+ 4 via header) 1 USB 3.2 Gen1 Type-A header

X13SCH-SYS

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C266 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16; 2 PCIe 4.0 x4 (in x8)
- I/O: 1 VGA, 2 COM, 1 TPM header
- M.2 Interface: 2 PCIe 4.0 x4 (Form Factor: 2280/22110, M-Key)
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- 5 USB 3.2 Gen1 ports (2 rear + 1 Type A + 2 via header); 6 USB 2.0 ports (2 rear + 4 via header)

X13SCH-LN4F

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C266 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16; 2 PCIe 4.0 x4 (in x8)
- I/O: 1 VGA, 2 COM, 1 TPM header
- M.2 Interface: 2 PCIe 4.0 x4 (Form Factor: 2280/22110, M-Key)
- 5 USB 3.2 Gen1 ports (2 rear + 1 Type A + 2 via header); 6 USB 2.0 ports (2 rear + 4 via header)
- Quad LAN with Intel® i210 Gigabit Ethernet Controller

X13SCH-F

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C266 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16; 2 PCIe 4.0 x4 (in x8)
- I/O: 1 VGA, 2 COM, 1 TPM header
- M.2 Interface: 2 PCIe 4.0 x4 (Form Factor: 2280/22110, M-Key)
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- 5 USB 3.2 Gen1 ports (2 rear + 1 Type A + 2 via header); 6 USB 2.0 ports (2 rear + 4 via header)

X13SCD-F

Key Features

- Intel® Xeon® 6300-series Processor, E-2400 Series Processor, Pentium® Processor, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Up to 128GB ECC Unbuffered DIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 4.0 x8 (Micro Low Profile) + 1 PCIe 5.0 x8 (Low Profile, Open End)
- 1 VGA Port;2 USB 2.0 Ports; 1 Serial Port via KVM Connector
- M.2 Interface: 2x SATA3/PCIe 4.0 x4, M.2 Form Factor: 2242/2280, 22110 for one slot only
- 1 Dedicated IPMI LAN via Backplane to the Centralized Management Port

X13SAZ-Q

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® Q670E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 1 PCIe 4.0 x4 OCulink port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP++ ports, 1 HDMI 2.0b port, 1 DVI - D port)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAZ-F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 1 PCIe 4.0 x4 OCulink port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 1 HDMI 2.0b port, 1 DVI - D port)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAW-TLN4F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 M.2 M-Key 2280 (PCIe 3.0 x4) 1 M.2 M-Key 2280/22110 (PCIe 4.0 x4)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226 LAN controller, Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 Independent Display Ports (2 DP1.4)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAW-F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 M.2 M-Key 2280 (PCIe 3.0 x4) 1 M.2 M-Key 2280/22110 (PCIe 4.0 x4)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226 LAN controller
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 Independent Display Ports (2 DP1.4)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-PS

Key Features

- 13th/12th Gen Intel® Core™ processors , Intel® Celeron® processors, SoC, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP
- Up to 64GB Unbuffered non-ECC SODIMM, DDR5-4800MHz, in 2 SODIMM slots
- 1 PCIe 4.0 x4 slot
1 M.2 M-Key 2280 (PCIe 4.0 x4)
1 M.2 E-Key 2230 (PCIe 3.0 x1/USB2.0)
1 M.2 B-Key 3052 (PCIe 3.0 x2/USB3.0/USB2.0)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 DP ports, 1 HDMI port, 2 TYPE C support DP/USB3.0)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-LVDS

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP (**bios v5.0 or above)
- Up to 64GB Unbuffered non-ECC SODIMM, DDR4-3200MHz, in 2 SODIMM slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8) 1 M.2 M-Key 2280 (PCIe 4.0 x4) 1 M.2 E-Key 2230 (PCIe 3.0 x1/USB)
- Single 1 Gigabit LAN with Intel® Ethernet i210-AT LAN controller Single 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 5 SATA3 (1 header, 4 via Oculink) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP ports, 1 HDMI 2.0b port, 1 HDMI 1.4a port, LVDS)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-D5LVDS

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP (**bios v5.0 or above)
- Up to 64GB Unbuffered non-ECC SODIMM, DDR5-5600MHz, in 2 SODIMM slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8) 1 M.2 M-Key 2280 (PCIe 4.0 x4) 1 M.2 E-Key 2230 (PCIe 3.0 x1/USB)
- Single 1 Gigabit LAN with Intel® Ethernet i210-AT LAN controller Single 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 5 SATA3 (1 header, 4 via Oculink) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP ports, 1 HDMI 2.0b port, 1 HDMI 1.4a port, LVDS)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAQ

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP (**bios v5.x or above)
- Intel® Q670E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slot, 1 PCIe 3.0 x4 slot, 1 PCIe 3.0 x2 slot, 1 PCIe 4.0 NVMe x4 SlimSAS port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 VGA port, 1 DP 1.4a port, 1 HDMI 2.0b port, 1 DVI - D port)
- Onboard TPM2.0

X13SAN-L-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-L

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-H-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-H

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-E-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-E

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-C-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcie: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-C

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcie: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAE-F

Key Features

- 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3 Processors, Single Socket LGA-1700 supported, Up to 150W TDP
- Intel® W680
- 192GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MT/s, 4 DIMM Slots
- 2 PCIe 5.0 x16 slots (16/NA or 8/8), 2 PCIe 3.0 x41 5V PCI 32bit
- M.2 Interface: 3 PCIe 4.0 x4 (RAID 0, 1, 5)M.2 Form Factor: 2280M.2 Key: M-Key
- Single LAN with Intel® Ethernet I225-LMSingle LAN with Intel® PHY I219LM LAN controller for AMT/vPro
- 8 SATA3 (6 Gb, RAID 0, 1, 5, 10)
- 1 DP 1.4a, 1 HDMI 2.0b, 1 VGA, 1 DVI-D, 1 Dedicated IPMI LAN Port
- IPMI Supported

X13SAE

Key Features

- 14th/13th/12th Gen Intel® Core™ i9/i7/i5/i3 Processors, Single Socket LGA-1700 supported, Up to 150W TDP
- Intel® W680
- 192GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MT/s, 4 DIMM Slots
- 2 PCIe 5.0 x16 slots (16/NA or 8/8), 2 PCIe 3.0 x41 5V PCI 32bit
- M.2 Interface: 3 PCIe 4.0 x4 (RAID 0, 1, 5)M.2 Form Factor: 2280M.2 Key: M-Key
- Single LAN with Intel® Ethernet i225VSingle LAN with Intel® PHY I219LM LAN controller for AMT/vPro
- 8 SATA3 (6 Gb, RAID 0, 1, 5, 10)
- 1 DP 1.4a, 1 HDMI 2.0b, 1 DVI-D

X13QEH+

Key Features

- 4th Gen Intel® Xeon® Scalable processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 16TB 3DS RDIMM/RDIMM DDR5 (288-pin) ECC memory with speeds up to 4800Mhz in 64 DIMMs. Up to 16TB PMem 300 Series Memory
- 2 PCIe 5.0 x 16 via Riser Card
- 1 PCIe 5.0 x16 and 1 PCIe 5.0 x8 via Riser Card
- 17 MCIO PCIe 5.0 x8 connectors for 24 NVMe SSDs via Riser Card
- 2 Nvme PCIe 3.0 x4/SATA 2.0 Hybrid M.2 ports
- 8 SATA 3.0 or 24 NVMe SSDs via Riser Card
- 1 MP

X13OEI-CPU

Key Features

- 4th Gen Intel® Xeon® Scalable processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP (4 CPU module in one 8 Way System)
- Intel C741® Chipset (On PCH Module)
- Up to 8TB 3DS RDIMM/RDIMM DDR5 (288-pin) ECC memory with speeds up to 4800MHs (max.) in 32 DIMMs. Up to 8TB PMem 300 Series Memory
- PCI Slot Located on PCIe Module
- USB & Display Port on PCH Module

X13DSF-A

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports CXL
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 2 GenZ x16 slot PCIe 5.0
- 2 AIOM connectors PCIe 5.0 x16
- 2 M.2
- 24 NVMe ports PCIe 5.0 x4 via 12 MCIO connectors
- 2 USB 3.0
- 4 SATA via SlimSAS

X13DGU

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 12 PCIe 5.0 MCIO x8
- Dual LAN with Intel X710 10GbE
- 1 VGA port
- 2 hybrid M.2
- 2 USB 3.0

X13DET-B

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Supports CXL 1.0, 1.1
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s in 16 DIMM slots
- 2 PCIe 5.0 x16 slots supported by CPU1 (Slot1, Slot2)
- 1 PCIe 5.0 x16 slots supported by CPU2 (SXB1) for NVMe, SATA, SAS storage card(s)
- 1 PCIe 5.0 x8 for 2 NVMe M.2 connections on AOC supported by CPU1 (SXB5)
- 2 PCIe 5.0 x8 slots supported by CPU1 (SXB3, SXB4) for SAS 3.0, NVMe storage card(s)
- 3 PCIe 5.0 x8 connector supported by CPU1 and CPU2 (NS1, NS2, NS3) for NVMe storage card(s)
- 2 SATA headers support 12 SATA 3.0 connections
- UID/BMC Reset Switch and UID_LED/BMC LED Indicator
- Support for TPM (JTPM1)

X13DEM

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM and CXL
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 4 PCIe 5.0 x16
- 2 AIOM OCP 3.0 superset
- 8 NVMe ports PCIe 5.0 x8 via 8 MCIO connectors
- 2 M.2
- 1 VGA
- 2 USB 2.0 and 2 USB 3.0

X13DEI-T

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Supports CXL
- Intel® C741 Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s in 16 DIMM slots
- 4 PCIe 5.0 x16
- 2 PCIe 5.0 x8
- Broadcom BCM57416 Dual ports 10G LAN
- 6 USB3.0 and 3 USB2.0
- 2 SATA DOM ports
- 2 M.2
- 6 NVMe ports PCIe 5.0 x4 via 3 MCIO connectors
- 8 SATA3.0 ports

X13DEI

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Supports CXL
- Intel® C741 Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s in 16 DIMM slots
- 4 PCIe 5.0 x16
- 2 PCIe 5.0 x8
- Broadcom BCM5720 Dual ports 1G LAN
- 6 USB3.0 and 3 USB2.0
- 2 SATA DOM ports
- 2 M.2
- 6 NVMe ports PCIe 5.0 x4 via 3 MCIO connectors
- 8 SATA3.0 ports

X13DEH

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM and CXL
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 20 PCIe 5.0 MCIO x8
- 2 M.2
- 1 Sideband to I/O module via SlimSAS x8
- 1 SATA3 port via SlimSAS-LP x8
- 1 USB 2.0 header

X13DEG-R

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel® C741 Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 18 PCIe 5.0 MCIO x8 (8 for GPU Module; 8 for Riser Card; 2 for NVMe)
- Dual LAN with Intel X710 10GbE
- 2 PCIe 3.0 x4 Hybrid M.2
- 1 VGA via AOM Card
- 4 SATA3 port s via SlimSAS-LP x4
- 2 USB 3.0 via AOM Card + 1 USB 3.0 onboard

X13DEG-QT

Key Features

- Support CXL
- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Intel® C741 Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots
- Intel® X550-AT2 Dual ports 10G LAN
- 2 SATA DOM ports
- 8 NVMe ports PCIe 5.0 x4 via 4 MCIO connectors
- 7 PCIe 5.0 x16
- 2 M.2 (2280/22110)
- HD Audio 7.1 channel header
- 8 SATA 3.0 ports via 2 SlimSAS connectors
- 7 USB 3.0 ports

X13DEG-PVC

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 12 PCIe 5.0 MCIO x8

X13DEG-OAD

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 12 PCIe 5.0 MCIO x8

X13DEG-OA

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM and CXL
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 20 PCIe 5.0 MCIO x8
- Networking options provided via Ultra RiserDual LAN with 10GbE LAN via Intel® X710
- 8 SATA 3.0

X13DEG-MA

Key Features

- Support HBM
- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 12 PCIe 5.0 MCIO x8

X13DEG-M

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 12 PCIe 5.0 MCIO x8

X13DEG-D

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Sockets LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 10x PCIe 5.0 x16 connections

X13DDW-A

Key Features

- Support CXL
- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s in 16 DIMM slots
- 4 PCI-E 5.0 x16
- 2 AIOM OCP 3.0 superset
- 2 M.2
- 1 VGA
- 8 NVMe ports PCI-E 5.0 x4 via 8 MCIO connectors
- 2 USB 2.0 header and 2 USB 3.2 Gen1

X13DAI-T

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) , CPU TDP supports up to 350W TDP
- Supports CXL
- Intel® C741 Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s(1DPC) in 16 DIMM slots
- Broadcom BCM57416 Dual ports 10G LAN
- 2 SATA DOM ports
- 2 M.2
- 4 NVMe ports PCIe 5.0 x4 via 2 MCIO connectors
- 5 PCIe 5.0 x16
- 1 PCIe 5.0 x8
- 8 SATA 3.0 ports(C741, RAID 0, 1, 5, 10)
- HD Audio 7.1 channel
- 1 USB 3.1 Gen 2, 6 USB 3.0

X12STN-L-WOHS

Key Features

- Intel® 11th Generation Core™ i3-1115GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-L

Key Features

- Intel® 11th Generation Core™ i3-1115GRE Processor
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Intel® UHD Graphics for 11th Gen with 48EU capable of 4K60 resolution
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-H-WOHS

Key Features

- Intel® 11th Generation Core™ i7-1185GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-H

Key Features

- Intel® 11th Generation Core™ i7-1185GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-E-WOHS

Key Features

- Intel® 11th Generation Core™ i5-1145GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-E

Key Features

- Intel® 11th Generation Core™ i5-1145GRE Processor
- Up to 80 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-C-WOHS

Key Features

- Intel® Celeron® 6305E Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-C

Key Features

- Intel® Celeron® 6305E Processor
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Intel® UHD Graphics with 48 EU capable of 4K60 resolution
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STE-F

Key Features

- Intel® Pentium®, Intel® Xeon® E-2300 Series Processor,Single Socket LGA-1200 (Socket H5) supported,CPU TDP supports Up to 95W TDP.
- Intel® C256.
- Up to 128GB ECC/non-ECC Unbuffered VLP DIMM, DDR4-3200MHz, in 4 DIMM slots.
- 1 PCI-E 4.0 x8 (Micro Low Profile)
1 PCI-E 4.0 x8 for Add-On-Module (AOM).
- Intel® C256 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10.
- M.2 Interface: 1 SATA/PCI-E 3.0 x4,M.2 Form Factor: 2280/22110.
- 1 LAN port;Realtek RTL8211FS PHY for dedicated IPMI.
- 1 VGA Port;2 USB 2.0 Ports; 1 Serial Port via KVM Connector.

X12STD-F

Key Features

- Intel® Pentium®, Intel® Xeon® E-2300 Series Processor, Single Socket LGA-1200 (Socket H5) supported,CPU TDP supports Up to 95W TDP.
- Intel® C256.
- Up to 128GB ECC/non-ECC Unbuffered DIMM, DDR4-3200MHz, in 4 DIMM slots.
- 1 PCI-E 4.0 x8 (Micro Low Profile)
1 PCI-E 4.0 x8 (Low Profile).
- 1 LAN port;Realtek RTL8211FS PHY for dedicated IPMI.
- Intel® C256 controller for 2 SATA3 (6 Gbps) ports; RAID 0,1,5,10.
- 1 VGA Port;2 USB 2.0 Ports; 1 Serial Port via KVM Connector.
- M.2 Interface: 2 SATA/PCI-E 3.0 x4,M.2 Form Factor: 2280/22110.

X12SPZ-SPLN6F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 OCuLink Connector (4 SATA/PCIe 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCIe 3.0 x4)
- 1 PCIe 4.0 NVMe x8 SlimSAS Internal Port
1 PCIe 4.0 NVMe x4 SlimSAS Internal Port
- 2 PCIe 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Broadcom BCM57414
- 4 USB 3.2 Gen 1 (2 Rear, 2 via Header),
4 USB 2.0 (Headers)
- Supports 12V DC power input

X12SPZ-LN4F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 OcuLink Connector (4 SATA/PCIe 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCIe 3.0 x4)
- 1 PCIe 4.0 NVMe x8 SlimSAS Internal Port
1 PCIe 4.0 NVMe x4 SlimSAS Internal Port
- 2 PCIe 4.0 x16
- 4 USB 3.2 Gen 1 (2 Rear, 2 via Header),
4 USB 2.0 (Headers)
- Quad 1G RJ45 with Intel® I350-AM4
- Supports 12V DC power input

X12SPW-TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x32 Left Riser Slot,
4 PCI-E 4.0 NVMe x4 Internal Port(s)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X12SPW-F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x32 Left Riser Slot,
4 PCI-E 4.0 NVMe x4 Internal Port(s)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- Dual LAN with 1GbE with Intel® I210
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X12SPT-PT

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x16 Left Riser Slot,
1 PCI-E 4.0 x16 Right Riser Slot,

1 PCI-E 4.0 x8 Proprietary Storage adapter Slot
- Dual LAN with 10G SFP+
- Intel® C621A controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12SPT-GC

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 16 DIMM slots
- 1x PCI-E 4.0 x8 4C connector (for front I/O module), 4x PCI-E 4.0 x8 MCIO connectors
- LSI 3808 controller for 6 SAS3 ports
- M.2 Interface: 2 PCI-E 3.0 x4&SATA,M.2 Form Factor: 2280

X12SPT-G

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 16 DIMM slots
- 1x PCI-E 4.0 x8 4C connector (for front I/O module), 4x PCI-E 4.0 x8 MCIO connectors
- Intel® C621A controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- M.2 Interface: 2 PCI-E 3.0 x4&SATA,M.2 Form Factor: 2280

X12SPO-NTF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory, in 8 DIMM slots
- 1 PCI-E 4.0 x16,
5 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 2 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 10x NVMe drives via SlimSAS connectors

X12SPO-F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory, in 8 DIMM slots
- 1 PCI-E 4.0 x16,
2 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 2 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® i350 Gigabit Ethernet Controller
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 4x NVMe drives via SlimSAS connectors

X12SPM-TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SPM-LN6TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Quad LAN with 1GbE with Intel® I350-AM4
Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SPM-LN4F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Quad LAN with 1GbE with Intel® I350-AM4
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SPL-LN4F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory, in 8 DIMM slots
- 2 PCI-E 4.0 x8,
1 PCI-E 4.0 x16,
1 PCI-E 4.0 x8 (in x16 slot)
3 PCI-E 3.0 x8
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Quad LAN with Intel® i210 Gigabit Ethernet Controller
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10

X12SPL-F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory, in 8 DIMM slots
- 2 PCI-E 4.0 x8,
1 PCI-E 4.0 x16,
1 PCI-E 4.0 x8 (in x16 slot)
3 PCI-E 3.0 x8
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10

X12SPi-TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8,
1 PCI-E 4.0 x8 (in x16 slot),
1 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10

X12SPG-NF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 3 PCI-E 4.0 x16 Proprietary Slots
2 PCI-E 4.0 NVMe x4
M.2 Interface: 2 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
1 PCI-E 4.0 x8 AIOM
- Single LAN with Realtek RTL8211F PHY
(dedicated IPMI)
- Intel® C621A controller for 2 SATA3 (6 Gbps) ports; RAID 0,1

X12SPED-F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x16 (LP)
2 PCI-E 4.0 x16 (FHHL)
- 1 RJ-45 GbE dedicated IPMI LAN with Intel® Ethernet Controller I210-AT
- M.2 Interface: 2 PCI-E 4.0 x4, M.2 Form Factor: 2280/22110
- 1 VGA Port; 2 USB 2.0 Ports; 1 Serial Port via KVM Connector.

X12SPA-TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Intel® Xeon® W-3300 Processor
Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Marvell AQc113
Single LAN with Realtek RTL8211F PHY (dedicated IPMI)
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots
- 4 PCI-E 4.0 x16,
3 PCI-E 4.0 x8 (in x16 slot)
M.2 Interface: 4 PCI-E 4.0 x4
M.2 Form Factor: 2260/2280/22110
M.2 Key: M-Key
M.2 support to RAID 0,1, 5, 10, VROC key is required for RAID.
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port,
VGA connector is dedicated for IPMI.

X12SDV-8CE-SP4F

Key Features

- Intel® Xeon® Processor D-1732TE, CPU TDP 52W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Dual 1G RJ45 with Intel® i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-8C-SPT8F

Key Features

- Intel® Xeon® Processor D-2733NT, CPU TDP 80W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® i350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-8C-SPT4F

Key Features

- Intel® Xeon® Processor D-1736NT, CPU TDP 67W, Intel Quick Assist Technology
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2667MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-8C-SP6F

Key Features

- Intel® Xeon® Processor D-1736NT, CPU TDP 67W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-4C-SPT8F

Key Features

- Intel® Xeon® Processor D-2712T, CPU TDP 65W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-4C-SPT4F

Key Features

- Intel® Xeon® Processor D-1718T, CPU TDP 46W
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-4C-SP6F

Key Features

- Intel® Xeon® Processor D-1718T, CPU TDP 46W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-20C-SPT8F

Key Features

- Intel® Xeon® Processor D-2796NT, CPU TDP 120W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for up to 6 SATA3 (6 Gbps) ports
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-16C-SPT8F

Key Features

- Intel® Xeon® Processor D-2775TE, CPU TDP 100W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-14C-SPT8F

Key Features

- Intel® Xeon® Processor D-2766NT, CPU TDP 97W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for up to 6 SATA3 (6 Gbps) ports
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-10CR-SP6F

Key Features

- Intel® Xeon® Processor D-1844NT, CPU TDP 55W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-10C-SPT4F

Key Features

- Intel® Xeon® Processor D-1749NT, CPU TDP 90W, Intel Quick Assist Technology
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2667MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-10C-SP6F

Key Features

- Intel® Xeon® Processor D-1747NTE, CPU TDP 80W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SCZ-TLN4F

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Intel® W480E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCZ-QF

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 125W TDP
- Intel® Q470E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® Q470E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCZ-F

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Intel® W480E
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCV-W

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 65W TDP
- Single LAN with Intel® Ethernet i225LM
Single LAN with Intel® Ethernet i225V
- Intel® W480E
- Up to 64GB DDR4 ECC/non-ECC SO-DIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 PCIe 3.0 x16 slots (16/NA or 8/8)
1 M.2 M-Key PCIe 3.0 x4, 2280
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 HDMI port, 1 DP (DisplayPort) port

X12SCV-LVDS

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 65W TDP
- Intel® W480E
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 64GB DDR4 ECC/non-ECC SO-DIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 PCIe 3.0 x16 slots (16/NA or 8/8)
1 M.2 M-Key PCIe 3.0 x4, 2242/2280
1 M.2 E-Key CNVi/PCIe 3.0 x1/USB, 2230
- Intel® W480E controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 2 HDMI ports, 1 DP (DisplayPort) port, 1 LVDS port,
3 Independent Displays thru HDMI 2.0a/HDMI1.4/DP/LVDS

X12SCQ

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® Q470 controller for 6 RAID 0,1,5,10
- Intel® Q470E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16 (in x16 slot),
1 PCIe 3.0 x8,
2 PCIe 3.0 x4
M.2 Interface: 1 PCIe 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2280
M.2 Key: M-Key
- 1 VGA port, 1 HDMI port, 1 DP (DisplayPort) port, 1 DVI - D port

X12SCA-F

Key Features

- 10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Intel® W480/ W480E
- Single LAN with Intel® PHY I219LM LAN controller
for AMT/vPro
Single LAN with Intel® Ethernet i225LM
- 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4,
2 PCI-E 3.0 x16 slots (16/NA or 8/8)
1 - 5V PCI 32bit

M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® W480 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DP (DisplayPort) port, 1 HDMI port, 1 DVI - D port, 1 VGA port,
VGA port is dedicated for IPMI

X12SAE

Key Features

- 10th Gen Intel® Corei9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, Up to 125W TDP
- Intel® W480/ W480E
- Single LAN with Intel® PHY I219LM LAN controller
for AMT/vPro
Single LAN with Intel® Ethernet i225V
- 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4,
2 PCI-E 3.0 x16 slots (16/NA or 8/8),
1 PCI-E 3.0 x1
1 - 5V PCI 32bit

M.2 Interface: 2 PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® W480 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DP (DisplayPort) port, 1 HDMI port, 1 DVI - D port

X12QCH+

Key Features

- 3rd Generation Intel® Xeon® Scalable processors
Quad Socket LGA-4189 (Socket P+) supported, CPU TDP support Up to 250W TDP, 6 UPI up to 10.4 GT/s
- Intel® C621A
- Up to 12TB 3DS ECC LRDIMM/ RDIMM, DDR4-3200MHz; Up to 18TB 3DS ECC DDR4-3200:LRDIMM/RDIMM/Intel® DCPMM , in 48 DIMM slots
- 3 PCI-E 3.0 x32 Left Riser Slot,
3 PCI-E 3.0 x32 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
U.2 Interface: 8 PCI-E 3.0 x4 and 8 PCI-E 3.0 x4 and 8 PCI-E 3.0 x4 and 8 PCI-E 3.0 x4
1 PCI-E 3.0 x32 Left Riser Slot, Riser card PN: RSC-D2-668G4
1 PCI-E 3.0 x32 Right Riser Slot, Riser card PN: RSC-D2R-668G4
- Quad LAN with
2x 10G BaseT with Intel® X710-TM4; 2x 10G SFP+ with Intel® X710-TM4,
(Optional) AIOM up to 100G QSFP 28
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12DSC-A6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 16 DIMM slots
- 3 PCI-E 4.0 x16
M.2 Form Factor: 22110
- AIOM slot

X12DSC-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 16 DIMM slots
- 3 PCI-E 4.0 x16
M.2 Form Factor: 22110
- AIOM slot
- Dual LAN with 10GBase-T with Intel® X550
- 1 VGA (Rear/Internal) port

X12DPU-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 32 DIMM slots
- 1 PCI-E 4.0 x32 Right Riser Slot,
1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x40 Ultra Riser Slot,
1 NVMe x4 Internal Port(s)
- Intel® C621A controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Networking options provided via Ultra Riser
- 1 VGA D-Sub Connector port

X12DPT-PT6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz (OC), in 16 DIMM slots
- 1 PCI-E 4.0 x16 Left Riser Slot,
1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x8 Right Riser Slot
- 1 PCI-E 4.0 x8 Proprietary Storage adapter Slot
- Dual LAN with 10Gbase-T
- Intel® C621A controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12DPT-B6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 20 DIMM slots
- 1 PCI-E 4.0 x16 Left Riser Slot,
1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x8 connector for SMC add-on cards
1 PCI-E 4.0 x8 Proprietary Storage Slot,
1 PCI-E 4.0 x16 AIOM Networking Slot,
1 PCI-E 4.0 x8 M.2 Slot
M.2 Form Factor: 2260/2280/22110
1 PCI-E 4.0 x16
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port
- Single LAN with
Networking options provided via AIOM module

X12DPL-NT6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots
- 4 PCI-E 4.0 x16,
1 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110, 2280
M.2 Key: M-Key
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12DPL-i6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 185W TDP, 2 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 2TB RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz, in 8 DIMM slots
- 4 PCI-E 4.0 x16
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110, 2280
M.2 Key: M-Key
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12DPi-NT6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 18 DIMM slotsP1-DIMMB2 and P2-DIMMB2 are reserved for Intel Optane Persistent Memory 200 series only.
- 2 PCI-E 4.0 x8,
4 PCI-E 4.0 x16,
2 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 1 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 VGA (1 rear bezel, 1 front panel) ports

X12DPi-N6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 18 DIMM slotsP1-DIMMB2 and P2-DIMMB2 are reserved for Intel Optane Persistent Memory 200 Series only.
- 2 PCI-E 4.0 x8,
4 PCI-E 4.0 x16,
2 PCI-E 4.0 NVMe x8 Internal Port(s)
M.2 Interface: 1 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® i350 Gigabit Ethernet Controller
- Intel® C621A controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 VGA (1 rear bezel, 1 front panel) ports

X12DPG-U6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors.
Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8GB Unbuffered ECC Intel® Optane™ Persistent Memory, DDR4-2933MHz, in 32 DIMM slots
- 8 PCI-E 4.0 x16
M.2 Interface: 2 PCI-E 4.0 x4, RAID 0 & 1
M.2 Form Factor: 2280/22110
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X12DPG-QT6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® Node Manager, IPMI2.0, KVM with dedicated LAN, NMI, SPM, SSM, SUM, SuperDoctor® 5, Watchdog
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 6TB Intel® Optane™ Persistent Memory 200 Series, in 16 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 6 PCI-E 4.0 x16,
1 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- HD Audio with optical S/PDIF
- 5 USB 3.0 ports, 4 USB 2.0 ports
- Integrated IPMI 2.0 and KVM with Dedicated LAN

X12DPG-QBT6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® Node Manager, IPMI2.0, KVM with dedicated LAN, NMI, SPM, SSM, SUM, SuperDoctor® 5, Watchdog
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 6TB Intel® Optane™ Persistent Memory 200 Series, in 16 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode.
- 6 PCI-E 4.0 x16,
1 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
- Dual LAN with Broadcom BCM57416 10GBase-T
- HD Audio with optical S/PDIF
- 5 USB 3.0 ports, 4 USB 2.0 ports
- Integrated IPMI 2.0 and KVM with Dedicated LAN

X12DPG-OA6-GD2

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8GB Unbuffered ECC Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 32 DIMM slots
- 16 PCIe 4.0 x8
M.2 Interface: 2 PCIe 3.0 x4
M.2 Form Factor: 2280/22110
1 PCIe 4.0 x16
- Networking options provided via Ultra RiserDual LAN with 1GbE LAN via Intel® i350-AM2
- 1 VGA port

X12DPG-OA6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8GB Unbuffered ECC Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 32 DIMM slots
- 16 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
1 PCI-E 4.0 x16
- Networking options provided via Ultra RiserDual LAN with 1GbE LAN via Intel® i350-AM2
- 1 VGA port

X12DPG-AR

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4GB Unbuffered ECC Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 16 DIMM slots
- 6 PCI-E 4.0 x16
2 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110
- Flexible networking options
- 1 VGA port

X12DPFR-AN6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 205W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 16 DIMM slots
- 1 PCI-E 4.0 x16 Right Riser Slot,
1 PCI-E 4.0 x8 connector for SMC add-on cards,
3 PCI-E 4.0 NVMe x8 Internal Port(s)
1 PCI-E 4.0 x16, OCP 3.0 compliant
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port
- Single LAN with
Networking options provided via AIOM module

X12DPD-A6M25

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 16 DIMM slots
- 3 PCI-E 4.0 x16 (in x16 slot),
8 PCI-E 3.0 NVMe x4
M.2 Interface: 2 PCI-E 3.0 x2, RAID 0 & 1
M.2 Form Factor: 2242/2280
M.2 Key: M-Key
1 PCI-E 4.0 x16, AIOM superset of OCP 3.0 Ethernet
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN
- Intel® C621A controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X12DHM-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 32 DIMM slots
- 5 PCI-E 4.0 x16,
8 PCI-E 4.0 NVMe x4
M.2 Interface: 2 SATA/PCI-E 3.0 x2, RAID 0 & 1
M.2 Form Factor: 2280/22110
1 PCI-E 4.0 x16, AIOM (OCP3.0 Compliant)
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X12DGU

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 8GB Unbuffered ECC Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz, in 32 DIMM slots
- 25 PCI-E 4.0 x8
M.2 Interface: 1 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110
1 PCI-E 4.0 x16
- Dual LAN with 2x 10Gbase-T with Intel ® Ethernet Controller X710
- 1 VGA port

X12DGQ-R

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory 200 Series, DDR4-3200MHz (OC), in 16 DIMM slots
- 1 PCI-Express 4.0 x32 riser supporting x16/x16,
4 PCI-Express 4.0 x16 slots,
1 PCI-Express 4.0 x4 M.2 slot
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
1 PCI-Express 4.0 x8 SlimSAS ports supporting two NVME drives
- Intel® C621A controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X12DGO-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz, in 32 DIMM slots
- 3 PCI-E 4.0 x16
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2280/22110
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X12DDW-A6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB RDIMM, DDR4-3200MHz; Up to 4TB LRDIMM, DDR4-3200MHz
DDR4-3200MHz (OC), in 16 DIMM slots
- 1 PCI-E 4.0 x16 Left Riser Slot,
1 PCI-E 4.0 x16 Right Riser Slot,
2 PCI-E 4.0 x16 Center Right Hand Slot,
8 PCI-E 4.0 NVMe Internal Port(s)
M.2 Interface: 2 PCI-E 2.0 x1
M.2 Form Factor: 2260/2280
M.2 Key: M-Key
2 PCI-E 4.0 x16, AIOM slots Superset of OCP 3.0 Expansion
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- AIOM for LAN
- 1 VGA D-Sub Connector port

X12DAI-N6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP, 3 UPI up to 11.2 GT/s
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 4TB Intel® Optane™ Persistent Memory, DDR4-3200MHz, in 16 DIMM slots;
- 5 PCI-E 4.0 x16,
1 PCI-E 4.0 x8,
4 PCI-E 4.0 NVMe x4 Internal Port(s)
M.2 Interface: 2 PCI-E 4.0 x4, RAID 0 & 1
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Dual LAN with Intel® i210 Gigabit Ethernet Controller
- Intel® C621A controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X11SWN-L-WOHS

Key Features

- Intel® 8th Generation Core™ i3-8145UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-L

Key Features

- Intel® 8th Generation Core™ i3-8145UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-H-WOHS

Key Features

- Intel® 8th Generation Core™ i7-8665UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-H

Key Features

- Intel® 8th Generation Core™ i7-8665UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-E-WOHS

Key Features

- Intel® 8th Generation Core™ i5-8365UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-E

Key Features

- Intel® 8th Generation Core™ i5-8365UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-C-WOHS

Key Features

- Intel® Celeron® 4305UE Processor
- Dual Channel DDR4 2133MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-C

Key Features

- Intel® Celeron® 4305UE Processor
- Dual Channel DDR4 2133MHz SO-DIMM, up to 64GB
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Intel UHD Graphics 610 with 4K and 24 EU for Vision Solution
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SSN-L-WOHS

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-L-VDC

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0

X11SSN-L-001

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-L

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-H-WOHS

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-H-VDC

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0
- Supports on board TPM 2.0

X11SSN-H-001

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-H

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E-WOHS

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E-VDC

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0
- Supports on board TPM 2.0

X11SSN-E-001

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SPW-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots:
1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x32 Left Riser slot
- 10 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X11SPW-CTF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots:
1 PCI-E 3.0 x8 (in x16), 1 PCI-E 3.0 x32 Left Riser slot
- 4 SAS3 (12Gbps) via Broadcom® 3008; RAID 0, 1, 10
- 10 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X11SPM-TPF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C622
- 2 10G SFP+
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- I/O: 1 VGA, 2 COM, 1 TPM header
- Supports 12V DC power input

X11SPM-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X11SPM-F

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C621 Chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C621
- 2 GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X11SPL-F

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Single Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 165W TDP
- Intel® C621 Chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots: , 2 PCI-E 3.0 x8 (in x16) , , 4 PCI-E 3.0 x8 , , 1 PCI-E 3.0 x4 (in x8)
- 8 SATA3 (6Gbps) ports
- 2 GbE LAN ports
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 8 USB 2.0 (2 rear, 6 via headers)
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X11SPI-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots: , 1 PCI-E 3.0 x16 , , 1 PCI-E 3.0 x16 (x16 || x8) , , 1 PCI-E 3.0 x8 (x0 || x8) , , 1 PCI-E 3.0 x8 , , 1 PCI-E 3.0 x4 (in x8)
- 10 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)

X11SPH-nCTPF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Single Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 205W TDP
- Intel® C622 chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280
Key: M-Key
- 2x Port NVMe PCI-E 3.0 x4 via OCuLink
- Expansion slots: , 1 PCI-E 3.0 x16 (x16 || x8) , , 1 PCI-E 3.0 x8 (x0 || x8) , , 1 PCI-E 3.0 x8 , , 1 PCI-E 3.0 x4 (in x8)
- 2 10G SFP+
- 10 SATA3 (6Gbps) via C622
- 8 SAS3 (12Gbps) via Broadcom® 3008; RAID 0, 1, 10
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 8 USB 2.0 (2 rear, 6 via headers)

X11SPH-nCTF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C622 chipset
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4 and SATA
Form Factor: 2280
Key: M-Key
- 2x Port NVMe PCI-E 3.0 x4 via OCuLink
- Expansion slots: , 1 PCI-E 3.0 x16 (x16 || x8) , , 1 PCI-E 3.0 x8 (x0 || x8) , , 1 PCI-E 3.0 x8 , , 1 PCI-E 3.0 x4 (in x8)
- 10 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- 8 SAS3 (12Gbps) via Broadcom® 3008; RAID 0, 1, 10
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 8 USB 2.0 (2 rear, 6 via headers)

X11SPG-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP
- Intel® C621 Chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots
- 2x M.2 NGFF connectors, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2280
Key: M-Key
- 3 PCI-E 3.0 x16
- 6 SATA (6Gbps)
- 2 10GbE LAN ports
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 4 USB 2.0 (2 rear, 2 via headers)
- I/O: 1 VGA, 1 COM, TPM header
- 2 SuperDOM with built-in power

X11SPA-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors
Single Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 205W TDP
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz
Up to 3TB Intel® Optane™ Persistent Memory, DDR4-2666MHz, in 12 DIMM slots
- 4 PCI-E 3.0 x16,
3 PCI-E 3.0 x8 (in x16 slot),
PCI-Ex16 Slot#1 shares with M.2, Slot#2 shares with Slot#3(NA/16,8/8), Slot#4 shares with Slot#5(NA/16,8/8), Slot#6 shares with Slot#7(NA/16,8/8)

M.2 Interface: 4 PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
M.2 support RAID 0,1(up to RAID 5, 10), VROC key is required for Raid.
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Aquantia® AQC107 10G Ethernet Controller
Single LAN with Realtek RTL8211E PHY (dedicated IPMI)
- Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port,
VGA connector is dedicated for IPMI.

X11SPA-T

Key Features

- Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Xeon-W32xx series processors
Single Socket LGA-3647 (Socket P) supported, CPU TDP up to 205W
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz
Up to 3TB Intel® Optane™ Persistent Memory, DDR4-2666MHz
Xeon-W32xx supports up to 2TB 3DS ECC RDIMM/LRDIMM, Xeon-W32xx supports up to 1TB 3DS RDIMM/LRDIMM
Xeon-W32xx series processors don't support DCPMM
- 4 PCIe 3.0 x16,
3 PCIe 3.0 x8 (in x16 slot),
PCIe x16 Slot#1 shares with M.2, Slot#2 shares with Slot#3(NA/16,8/8), Slot#4 shares with Slot#5(NA/16,8/8), Slot#6 shares with Slot#7(NA/16,8/8)

(16/NA/16/NA/16/NA/16 or 16/8/8/8/8/8/8)
M.2 Interface: 4 PCIe 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key
M.2 support RAID 0,1(up to RAID 5, 10), VROC key is required for Raid.
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Aquantia® AQC107 10G Ethernet Controller
Single LAN with Realtek RTL8211E PHY (dedicated IPMI)
- 1 VGA port,
VGA connector is dedicated for IPMI.

X11SDC-8C

Key Features

- Intel® Xeon® Processor D-2146NT, 8-Core, 16 Threads, 80W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SDC-4C

Key Features

- Intel® Xeon® Processor D-2123IT, 4-Core, 8 Threads, 60W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SDC-16C

Key Features

- Intel® Xeon® Processor D-2183IT, 16-Core, 32 Threads, 100W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SCZ-Q

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor.
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
2 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® Q370 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DVI - I port, 2 DP (DisplayPort) ports,
3 Independent Displays

X11SCZ-F

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor.
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
2 PCI-E 3.0 x4 (in x8 slot)
1 M.2 M-Key SATA/PCI-E 3.0 x4, 2280/22110
- Intel® C246 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 1 DVI - I port, 2 DP (DisplayPort) ports,
3 Independent Displays

X11SCW-F

Key Features

- 8th/9th Generation Intel® Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Dual LAN with Intel® Ethernet Controller I210-AT
- Intel® C246
- Up to 128GB Unbuffered ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
1 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: 1 SATA/PCI-E 3.0 x4 and 1 PCI-E 3.0 x4
M.2 Form Factor: 2260/2280/22110
M.2 Key: M-Key
- 4 USB 3.1 Gen2 (2 header, 2 rear), 1 USB 3.1 Gen1 Type A, 6 USB 2.0
- Intel® C246 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11SCV-Q

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 65W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 64GB Unbuffered non-ECC SO-DIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 M.2 M-Key PCI-E 3.0 x4, 2242/2280
1 M.2 E-Key CNVi/PCI-E 3.0 x1, 2230
- Intel® Q370 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
X11SCV-Q: Q370 controller for 5SATA3 ports;RAID 0,1,5,10
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
3 Independent Displays, HDMI 2.0

X11SCV-L

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 65W TDP
- Intel® H310
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 M.2 E-Key PCI-E 2.0 x1, 2230
- Intel® H310 controller for 4 SATA3 (6 Gbps) ports;
Only I-SATA0 - I-SATA3
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
2 Independent Displays

X11SCQ-L

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Intel® H310
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Up to 32GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 PCI-E 2.0 x4
1 PCI-E 2.0 x1
- Intel® H310 controller for 4 SATA3 (6 Gbps) ports;
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
2 Independent Displays

X11SCQ

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 64GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
1 PCI-E 3.0 x1,
2 PCI-E 3.0 x4
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2242/2280/22110
M.2 Key: M-Key
- Intel® Q370 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
3 Independent Displays

X11SCM-LN8F

Key Features

- 8th/9th Generation Intel® Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- 8 LAN with Intel® Ethernet Controller I210-AT
- Intel® C246
- Up to 128GB Unbuffered ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16
M.2 Interface: 1 SATA/PCI-E 3.0 x4 and 1 PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® C246 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA, 1 COM, 1 TPM
- 5x USB 3.0 ports, 4x USB 2.0 ports
- 2 SuperDOM with built-in power

X11SCM-F

Key Features

- 8th/9th Generation Intel® Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Dual LAN with Intel® Ethernet Controller I210-AT
- Intel® C246
- Up to 128GB Unbuffered ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16
M.2 Interface: 1 SATA/PCI-E 3.0 x4 and 1 PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® C246 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA, 1 COM, 1 TPM
- 5x USB 3.0 ports, 4x USB 2.0 ports
- 2 SuperDOM with built-in power

X11SCL-LN4F

Key Features

- 8th/9th Generation Intel® Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor., Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Quad LAN with Intel® Ethernet Controller I210-AT
- Intel® C242
- Up to 128GB Unbuffered ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® C242 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA, 1 COM, 1 TPM
- 5x USB 3.0 ports, 4x USB 2.0 ports
- 2 SuperDOM with built-in power

X11SCL-iF

Key Features

- 8th/9th Generation Intel® Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C242 chipset
- Up to 64GB DDR4 2666MHz ECC UDIMM; 2 DIMM slots
- M.2 Interface: 1 SATA/PCI-E 3.0 x4
Form Factor: 2280
Key: M-Key
- 4 SATA3 (6Gbps); RAID 0, 1, 5, 10
- M.2 NGFF connector
- Dual GbE LAN with Intel® i210-AT
- Support up to 6 Cores

X11SCL-F

Key Features

- 8th/9th Generation Intel® Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C242 chipset
- Up to 128GB DDR4 2666MHz ECC UDIMM; 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x8 (in x16), , 2 PCI-E 3.0 x4 (in x8)
- 6 SATA3 (6Gbps) ports; , RAID 0, 1, 5, 10
- M.2 NGFF connector
- Dual GbE LAN with Intel® i210-AT
- Support up to 6 Cores
- I/O: 1 VGA, 2 COM, 2 SuperDOM, and TPM header

X11SCH-LN4F

Key Features

- 8th/9th Generation Intel® Core™i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C246 chipset
- Up to 128GB DDR4 2666MHz ECC UDIMM; 4 DIMM slots
- 2x M.2 NGFF connectors, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots: 1 PCI-E 3.0 x8 (in x16) and 1 PCI-E 3.0 x8 slots
- Quad GbE LAN ports via Intel® i210
- 2 USB 3.1 Gen 2 (rear); 3 USB 3.1 Gen 1 (1 Type A, 2 via header(s)); 6 USB 2.0 (2 rear, 4 via header(s))
- 8 SATA3 (6Gbps) via C246; RAID 0, 1, 5, 10
- I/O: 1 VGA, 2 COM, 1 TPM header
- 2 SuperDOM with built-in power

X11SCH-F

Key Features

- 8th/9th Generation Intel® Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor, Single Socket LGA-1151 (Socket H4) supported, CPU TDP supports Up to 95W TDP
- Intel® C246 chipset
- Up to 128GB DDR4 2666MHz ECC UDIMM; 4 DIMM slots
- 2x M.2 NGFF connectors, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2280, 22110
Key: M-Key
- Expansion slots: 1 PCI-E 3.0 x8 (in x16) and 1 PCI-E 3.0 x8 slots
- Dual GbE LAN ports via Intel® i210
- 2 USB 3.1 Gen 2 (rear); 3 USB 3.1 Gen 1 (1 Type A, 2 via header(s)); 6 USB 2.0 (2 rear, 4 via header(s))
- 8 SATA3 (6Gbps) via C246; RAID 0, 1, 5, 10
- I/O: 1 VGA, 2 COM, TPM header
- 2 SuperDOM with built-in power

X11SCE-F

Key Features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E-2100, E-2200, Intel® 8th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C246 chipset
- Up to 128GB Unbuffered ECC UDIMM DDR4 2400MHz; 4 DIMM slot
- 1 M.2 PCI-E 3.0 x4 Form Factor: 2280/22110
- 4 SATA 3.0 (RAID 0, 1, 5, 10) or 2 U.2 NVMe drives
- 1 VGA, 2 USB 2.0, 1 COM via KVM dongle

X11SCD-F

Key Features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E-2100, E-2200, Intel® 8th Gen. Core™ i3 series, Intel® Celeron® and Intel® Pentium®
- Intel® C246 chipset
- Up to 128GB Unbuffered ECC UDIMM DDR4 2666 MHz; 4 DIMM slot
- 1 M.2 M-key SATA/PCI-E 3.0 x4 2242/2280, 1 M.2 M-key SATA/PCI-E 3.0 x4 2242/2280/22110
- 2 SATA (6Gbps)
- 1 VGA, 2 USB 2.0, 1 COM via KVM dongle

X11SBA-LN4F

Key Features

- Up to 8GB 1600MHz DDR3 Non-ECC SO-DIMM in 2 sockets
- Intel® Pentium™ Processor N3710., Single Socket FCBGA1170 supported, CPU TDP support 6W
- 1 PCI-E 2.0 x1 (in x8),, 1 Mini-PCIe (mSATA support)
- Quad GbE LAN with Intel® i210-AT
- IPMI 2.0 with dedicated Port and KVM
- I/O: 1 SATA DOM, 2 COM, TPM 1.2 header, ALC 888S HD Audio
- 2 USB 3.0 ports (2 rear), 7 USB 2.0 (2 rear, 4 via header(s), 1 Type A)
- 1 HDMI, 1 DP, Intel HD Graphics,, VGA port for BMC
- System-on-Chip
- Supports 12V DC power input

X11SBA-F

Key Features

- Up to 8GB 1600MHz DDR3 Non-ECC SO-DIMM in 2 sockets
- Intel® Pentium™ Processor N3710., Single Socket FCBGA1170 supported, CPU TDP support 6W
- 1 PCI-E 2.0 x1 (in x8),, 1 Mini-PCIe (mSATA support)
- Dual GbE LAN with Intel® i210-AT
- IPMI 2.0 with dedicated Port and KVM
- I/O: 1 SATA DOM, 2 COM, TPM 1.2 header, ALC 888S HD Audio
- 2 USB 3.0 ports (2 rear), 7 USB 2.0 (2 rear, 4 via header(s), 1 Type A)
- 1 HDMI, 1 DP, Intel HD Graphics,, VGA port for BMC
- System-on-Chip
- Supports 12V DC power input

X11SAN-WOHS

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

X11SAN

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

X11SAA

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), 1 Mini-PCIe (mSATA support) and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 1 SATA DOM, 3 COM, TPM header and Audio Header
- 2 USB 3.0 ports (2 rear), 8 USB 2.0 (2 rear, 5 via header(s), 1 Type A)
- 1 HDMI, 1 DP, 1 VGA, Intel HD Graphic 3 independent displays
- 4 SATA 3.0 (RAID 0, 1, 10)
- 1 M.2 M-key with SATA

X11QPL

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 12TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 12TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 12TB 3DS ECC DCPMM, DDR4-2666MHz, in 48 DIMM slots
- 5 PCI-E 3.0 x8,
2 PCI-E 3.0 x16
M.2 Interface: 2 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key,
8 PCI-E 3.0 NVMe x4 External Port(s)
- Single LAN with GbE from C621
- Intel® C621 controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 1 VGA port

X11QPH+

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Quad Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 12TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 12TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 12TB 3DS ECC DCPMM, DDR4-2666MHz, in 48 DIMM slots
- 1 PCI-E 3.0 x32 Left Riser._x000D_ _x000D_ 1 PCI-E 3.0 x40 Ultra Riser._x000D_ _x000D_ 1 PCI-E 3.0 x8 in x16 slot rear Middle Riser. _x000D_ _x000D_ 1 PCI-E 3.0 x32 for 2U (or x48+x8 for 4U) on front for NVMe card support. _x000D_ _x000D_ 1 PCI-E 3.0 (x32 for 2U or x48 for 4U) on front for NVMe card support.
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Networking options provided via Ultra Riser
- 1 VGA port

X110Pi-CPU

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors
Octal Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz
Or 3TB DCPMM, DDR4-2666MHz, in 12 DIMM slotsMaximum System Capacity (8 CPU modules, 96 DIMM slots);
Up to 24TB ECC DDR4 @ 2933 MHz RDIMM/LRDIMM;
,Up to 24TB Intel® Optane™ DC Persistent Memory;
, Up to 36TB combined memory (DDR4and Optane DCPMM).
- 2 PCI-E 3.0 x16
M.2 Interface: 2 SATA/PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2260/2280/22110
(M.2 slots on PCH board)
U.2 Interface: 4 PCI-E 3.0 x4,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Quad LAN with Intel® X550 10GBase-T Ethernet Controller
(on PCH board)
- Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
(on Storage board)
- 1 VGA D-Sub Connector port,
(on PCH board)

X11DSN-TSQ

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C627
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 Left Riser Slot
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X557
- Intel® PCH SATA controller for
- 1 VGA D-Sub Connector port

X11DSN-TS

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C624
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 Left Riser Slot
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X557
- Intel® PCH SATA controller for
- 1 VGA D-Sub Connector port

X11DSF-E

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C627
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 1 PCI-E 3.0 x32 Left Riser Slot,
2 PCI-E 3.0 x4 (Low Profile),
4 PCI-E 3.0 x16
- Intel® C627 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10GBase-T with Intel® X550
- 1 VGA D-Sub Connector port

X11DSC+

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® Node Manager, IPMI (Intelligent Platform Management Interface) v2.0 with KVM support, KVM with dedicated LAN, NMI, SPM, SSM, SUM, SuperDoctor® 5, Watchdog
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 24 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 4 PCI-E 3.0 NVMe x4 Internal Port(s)
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 PCI-E 3.0 x8+x8 for SAS3 Add-On-Module
- Intel® C621 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Networking options provide via SIOM or AOC NIC

X11DSC

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors
Dual Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 205W TDP, 3 UPI up to 10.4 GT/s
CPU1: Skylake-SP CPU supported
CPU2: Skylake-SP CPU supported
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, DDR4-2666MHz, in 16 DIMM slots
- 2 PCI-E 3.0 x16 Or 1 PCI-E 3.0 x8
M.2 Interface: 2 PCI-E 3.0 x2
M.2 Form Factor: 22110
- Networking options provided via Ultra RiserDual LAN with Intel® X550 10GBase-T Ethernet Controller

X11DPX-T

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 2 PCI-E 3.0 x16,
8 PCI-E 3.0 x8,
1 PCI-E 3.0 x4 (in x8 slot) Or 4 PCI-E 3.0 x16 and 4 PCI-E 3.0 x8 and 1 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- 1 VGA D-Sub Connector port

X11DPU-ZE+

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x32 Left Riser Slot,
1 PCI-E 3.0 x8 Right Riser Slot,
1 PCI-E 3.0 x40 Far Right Riser Slot,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; SATA3 (6 Gbps) RAID 0,1,5,10
- Networking options provided via Ultra Riser
- 1 VGA port

X11DPU-Z+

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x32 Left Riser Slot,
1 PCI-E 3.0 x8 Right Riser Slot,
1 PCI-E 3.0 x40 Far Right Riser Slot,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; SATA3 (6 Gbps) RAID 0,1,5,10
- Networking options provided via Ultra Riser
- 1 VGA port

X11DPU-XLL

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots
- 1 PCI-E 3.0 x32 Left Riser Slot,
1 PCI-E 3.0 x8 Center Right Riser Slot,
1 PCI-E 3.0 x40 Far Right Riser Slot,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Networking options provided via Ultra Riser
- 1 VGA port

X11DPU-V

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x32 Left Riser Slot
1 PCI-E 3.0 x8 Right Riser Slot
1 PCI-E 3.0 x40 Ultra Riser Slot
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 VGA D-Sub Connector ports
- Networking options provided via Ultra Riser

X11DPU

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x32 Left Riser Slot
1 PCI-E 3.0 x8 Right Riser Slot
1 PCI-E 3.0 x40 Ultra Riser Slot
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 VGA D-Sub Connector ports

X11DPT-PS

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slotsUp to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 1 PCI-E 3.0 x16 Right Riser Slot,
1 PCI-E 3.0 x24 riser,
1 PCI-E 3.0 x16 connector for SMC add-on cards,
1 PCI-E 3.0 x8 connector for SMC add-on cards
PCI-E 3.0 x16 SIOM LAN Networking slot
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPT-L

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 140W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 1 PCI-E 3.0 x16
- Dual LAN with 1GbE with Marvell® 88E1512
- Intel® C621 controller for 2 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

X11DPT-BH

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz Or 6TB DCPMM, DDR4-2666MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot
1 PCI-E 3.0 x24 Proprietary Slot (for Supermicro storage add-on card),
x000D 1 PCI-E 3.0 x16 SIOM LAN Networking Slot,
x000D 1 PCI-E 3.0 x8 Proprietary Slot (For M.2 add-on card)
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking option provided via SIOM module
- 1 VGA port

X11DPT-B

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz Or 6TB DCPMM, DDR4-2666MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot
1 PCI-E 3.0 x24 Proprietary Slot (for Supermicro storage add-on card),
x000D 1 PCI-E 3.0 x16 SIOM LAN Networking Slot,
x000D 1 PCI-E 3.0 x8 Proprietary Slot (For M.2 add-on card)
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPS-RE

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C627
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 (Low Profile),
4 PCI-E 3.0 x16
M.2 Interface: 2 PCI-E 3.0 x2
M.2 Form Factor: 2260/2280/22110
M.2 Key: M-Key
*2 SATA Hybrid ports, RAID 0 & 1
- Dual LAN with 10GBase-T with Intel® X550
- 1 VGA D-Sub Connector port

X11DPL-I

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 140W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 2TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-2933MHz, in 8 DIMM slots
- 2 PCI-E 3.0 x16,
3 PCI-E 3.0 x8,
1 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280
M.2 Key: M-Key
- Dual LAN with 1GbE with Intel® X722 + Marvell 88E1512
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DPI-NT

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB Intel® PMem, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 4 PCI-E 3.0 x16,
2 PCI-E 3.0 x8,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280, 22110
M.2 Key: M-Key
- Dual LAN with 10GBase-T with Intel® X722 + X557
- Intel® C622 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DPI-N

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB Intel® PMem, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 4 PCI-E 3.0 x16,
2 PCI-E 3.0 x8,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280, 22110
M.2 Key: M-Key
- Dual LAN with 1GbE LAN with Intel® X722
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DPH-Tq

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C627
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16,
3 PCI-E 3.0 x8
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key (RAID 0,1 support)
- Intel® C627 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10GBase-T with Intel® X722 + X557
- 1 VGA port

X11DPH-T

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16,
4 PCI-E 3.0 x8
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key (RAID 0,1 support)
- Intel® C622 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10GBase-T with Intel® X722 + X557
- 1 VGA port

X11DPH-i

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 3 PCI-E 3.0 x16,
4 PCI-E 3.0 x8
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2242/2260/2280/22110
M.2 Key: M-Key (RAID 0,1 support)
- Dual LAN with 1GbE with Intel® X722 + Marvell 88E1512
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DPG-SN

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16,
1 PCI-E 3.0 x8,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Networking options provide via SIOM or AOC NIC
- 1 VGA port

X11DPG-QT

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Intel® Node Manager, IPMI2.0, KVM with dedicated LAN, NMI, SPM, SSM, SUM, SuperDoctor® 5, Watchdog
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 6 PCI-E 3.0 x16,
1 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
- HD Audio with optical S/PDIF
- 5 USB 3.0 ports, 4 USB 2.0 ports
- Integrated IPMI 2.0 and KVM with Dedicated LAN

X11DPG-OT-CPU

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C622
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slotsUp to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x24 slots to PCI-E board
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C622 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10Gbase-T
from C622
- 1 VGA port

X11DPG-HGX2

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors,
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® C621 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10GBase-T with Intel® X540 10GbE Controller
- 1 VGA D-Sub Connector port

X11DPFR-SN

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 12 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot,
1 PCI-E 3.0 x16 connector for SMC add-on cards
1 PCI-E 3.0 x16 SIOM LAN Networking Slot
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280, 22110
M.2 Key: M-Key,
4 NVMe Internal Port(s)
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPFR-S

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 12 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 1 PCI-E 3.0 x24 Left Riser Slot,
1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 connector for SMC add-on cards
1 PCI-E 3.0 x16 SIOM LAN Networking Slot
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280, 22110
M.2 Key: M-Key
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPFF-SNR

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 12 DIMM slots
- 1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2260/2280/22110
U.2 Interface: 4 PCI-E 3.0 x4,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPFF-SN

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz
Or 2TB DCPMM, DDR4-2666MHz, in 12 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only);
- 1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2260/2280/22110
M.2 Key: M-Key
U.2 Interface: 4 PCI-E 3.0 x4,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Single LAN with
Networking options provided via SIOM module
- 1 VGA port

X11DPD-M25

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 1 PCI-E 3.0 x16 (Low Profile),
1 PCI-E 3.0 x8 Right Riser Slot,
2 PCI-E 3.0 x8 Proprietary Slot,
1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x16 for Add-On-Module (AOM)
M.2 Interface: 1 PCI-E 3.0 x4 and 1 PCI-E 3.0 x1
M.2 Form Factor: 2280
M.2 Key: M-Key
U.2 Interface: 2 PCI-E 3.0 x4,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
- Dual LAN with SoC
Mellanox CONNECTX-4 LX EN 25GbE
- Intel® C621 controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DPD-L

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors
Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots;
Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 1 PCI-E 3.0 x16 (HBA Add-On-Module),
1 PCI-E 3.0 x16 Left Riser Slot,
1 PCI-E 3.0 x24 Right Riser Slot,
1 PCI-E 3.0 x16 (Low Profile)
M.2 Interface: 1 PCI-E 3.0 x4 and 1 PCI-E 3.0 x1
M.2 Form Factor: 2280
M.2 Key: M-Key
U.2 Interface: 2 PCI-E 3.0 x4,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
- Intel® C621 controller for 12 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DGQ

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16,
1 PCI-E 3.0 x32 Riser Slot
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2242, 2260, 2280
M.2 Key: M-Key
M.2 type: SATA and NVMe
- Dual LAN with 10GBase-T with Intel® X540 10GbE Controller
- Intel® C621 controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10

X11DGO-T

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 3 UPI up to 10.4 GT/s
- Intel® C621
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots (2933MHz in two DIMMs per channel supported on Rev 1.10 MB only)_x000D_ ;
Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16
4 PCI-E 3.0 x16 to midplane
M.2 Interface: 2 PCI-E 3.0 x4
M.2 Form Factor: 2260/2280/22110
M.2 Key: M-Key
M.2 Type: NVMe
- Dual LAN with Intel® X540 10GBase-T Ethernet Controller
- Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DDW-NT

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C622
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 1 PCI-E 3.0 x32 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot,
1 PCI-E 3.0 x16 for Add-On-Module (AOM)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110
M.2 Key: M-Key
U.2 Interface: PCI-E 3.0 x4,
4 PCI-E 3.0 NVMe x4 Internal Port(s)
- Dual LAN with 10Gbase-T
from C622
- Intel® C622 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DDW-L

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 3TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 3TB 3DS ECC LRDIMM, DDR4-2933MHz, in 12 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 1 PCI-E 3.0 x32 Left Riser Slot,
1 PCI-E 3.0 x16 Right Riser Slot,
1 PCI-E 3.0 x16 for Add-On-Module (AOM)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110
M.2 Key: M-Key
- Dual LAN with GbE from C621
- Intel® C621 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DAi-N

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 4 PCI-E 3.0 x16,
2 PCI-E 3.0 x8,
2 PCI-E 3.0 NVMe x4 Internal Port(s)
M.2 Interface: PCI-E 3.0 x4
M.2 Form Factor: 2260, 2280, 22110
M.2 Key: M-Key
- Dual LAN with GbE from C621
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA port

X11DAC

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, Dual Socket LGA-3647 (Socket P) supported, CPU TDP supports Up to 205W TDP, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots
- 3 PCI-E 3.0 x16 (in x16 slot),
3 PCI-E 3.0 x8
- Dual LAN with GbE from C621
- Intel® C621 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port

R13SPD

Key Features

- AmpereOne™ up to 192-cores, up to 400W TDP, 128 lanes of PCIe Gen 5,5964-Pin Flip Chip Land Grid Array (FCLGA)
- Up to 16x ECC RDIMM DDR5-4800 MTs,up to 8TB/socket
- 3 x PCIe 5.0 x16 PCIe slot
- 6 x PCIe 5.0 x8 Mcio connector
- 2x 10Gb or 1x 25Gb SFP28 Broadcom BCM 57414
- 1 x AIOM (OCP3.0 Compliant)
- M.2 Interface: 1 PCIe 5.0 x4M.2 Form Factor: 2280/22110M.2 Key: M-Key
- 1 x Aspeed 2600

R12SPD-A

Key Features

- Ampere® Altra® up to 80-cores, Ampere® Altra® Max up to 128-cores, up to 250W TDP, 128 lanes of PCIe Gen 4,4926-Pin Flip Chip Land Grid Array (FCLGA)
- Up to 16x ECC RDIMM/LRDIMM DDR4-3200 MTs,up to 4TB/socket
- 3 x PCIe 4.0 x16 PCIe slot -Altra® Max; 2 x PCIe 4.0 x16, 1 x PCIe 4.0 x8 PCIe slot -Altra®
- 6 x PCIe 4.0 x8 SlimSAS connector
- 2 x 10Gb SFP+ or 1 x 25Gb SFP28, Mellanox ConnectX®-4 Lx EN
- M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280/22110M.2 Key: M-Key
- 1 x AIOM (OCP3.0 Compliant)
- 1 x Aspeed 2600

H14SST-GE

Key Features

- AMD EPYC™ 9005 series Processors
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- 8 PCIe 5.0 x8 MCIO connector, 1 PCIe 5.0/SATA3 x8 MCIO hybrid port connector
- M.2 Interface: 2 PCIe 5.0 x4 with SATA support. Form factor: 2280/22110
- 2 USB 3.0 (Front I/O board)
- NCSI Support for riser slot

H14SST-G

Key Features

- AMD EPYC™ 9005/9004 Series Processors
- Support up to DDR5 16 DIMM slots (2DPC), speed up to 5200MT/s (Please check System Memory Section for detail)
- 4 PCIe 5.0 x8 MCIO connector, 1 PCIe 5.0/SATA3 x8 MCIO hybrid port connector
- M.2 Interface: 2 PCIe 5.0 x4 with SATA support. Form factor: 2280/22110
- 2 USB 3.0 (Front I/O board)
- NCSI Support for riser slot

H14SSL-NT

Key Features

- AMD EPYC™ 9005/9004 Series Processors
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- 3 PCIe 5.0 x16, 2 PCIe 5.0 x8
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- ASPEED AST2600 BMC graphics
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 4.0 x4, M.2 Form Factor: 2280, 22110

H14SSL-N

Key Features

- AMD EPYC™ 9005/9004 Series Processors
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- 3 PCIe 5.0 x16, 2 PCIe 5.0 x8
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- ASPEED AST2600 BMC graphics
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 4.0 x4, M.2 Form Factor: 2280, 22110

H14SSF

Key Features

- Single AMD EPYC™ 9005/9004 Series Processors Socket SP5
- 12 DDR5 DIMM slots (1DPC), up to 6400MT/s speed (Please check System Memory Section for details)
- 2 onboard M.2 NVMe slots for OS boot with RAID 0/1
- 4 PCIe 5.0 x16 via ExaMax connectors
- 3 PCIe 5.0 x16 for AOCs via Riser Card
- 1 PCIe 5.0 x16 for AOC or 4 PCIe x4 E1.S
- 2 10GBASE-T Ports
- On-board ASPEED AST2600 supports open BMC
- 2 USB3.0 ports, 1 IPMI GE LAN port and 1 VGA port
- Supports ROT and 1 TPM2.0 Header

H14SRV-HLN4F

Key Features

- AMD EPYC™ 4005 up to 16 Cores processor, single socket LGA-1718 (socket AM5), up to 65W
- Up to 192GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 (16/NA or 8/8)
- Quad 1Gbit LAN ports (I350-AM4); 1 dedicated Realtek 1Gbit LAN for IPMI
- BMC, Flex-ATX form factor
- 4 USB 3.2 gen2(2 gen2 & 1gen1 Type A in rear, 1 USB Type C Alt DP/USB3.2)
- 1 HDMI 2.1 port, 1 mini DP port (from AST2600)
- M.2 Interface: 2 PCIe 5.0 x4 (2280/22110, M-Key)
- Supports 12V DC power input

H14SHM

Key Features

- AMD EPYC™ 9005/9004 Series Processors
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- AIOM for LAN
- 10 PCIe 5.0 x8 MCIO connectors
- I/O: 1 DC-SCM
- 2 PCIe 5.0 x16 M-XIO 1 PCIe 5.0 x16 AIOM
- M.2 Interface: 2 PCIe 3.0 x2 M-PIC (via an optional M.2 adapter card, M.2 Form Factor: 2280, 22110, M.2 Key: M-Key)

H14DST-FL

Key Features

- Dual AMD EPYC™ 9005 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- Flexible networking with up to 1 OCP 3.0 compatible AIOM slots
- Optional 1 PCIe 5.0 x16 FHHL slot + 1 PCIe 5.0 x16 LP slot
- Optional 2 E1.S Slots + Optional 2 M.2 NVME drive Slots

H14DST-F

Key Features

- Dual AMD EPYC™ 9005 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- Flexible networking with up to 1 OCP 3.0 compatible AIOM slots
- Optional 1 PCIe 5.0 x16 FHHL slot + 1 PCIe 5.0 x16 LP slot
- Optional 2 E1.S Slots + Optional 2 M.2 NVME drive Slots

H14DSH

Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- 32 SATA3 Hybrid via MCIO, 1 AIOM slot
- 2 PCIe 5.0 x16 slot via Riser
- 14 PCIe 5.0 x8 MCIO connectors
- 2 M.2 PCIe 3.0 x4 slots (M-key 2280/22110)
- 4 USB 3.0 ports (2 rear via I/O board + 2 via header)
- ASPEED AST2600 BMC graphics via I/O board

H14DSG-OM

Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- ASPEED AST2600 BMC graphics via I/O board
- 12 PCIe 5.0 x8 MCIO connectors
- 1 PCIe 3.0 x4 MCIO connector
- 2 SlimSAS x4
- 1 USB 3.0, 1 USB 2.0 and mini display port via I/O board
- M.2 Interface: 2 PCIe 3.0 x4; M.2 Form Factor: 22110 via M.2 I/O board
- 1 VGA Header

H14DSG-OD

Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400MT/s (Please check System Memory Section for detail)
- ASPEED AST2600 BMC graphics via I/O board
- 6 PCIe 5.0 x8 MCIO connectors; 2 SATA3 / PCIe 5.0 Hybrid x8 MCIO connectors
- 2 USB 3.0 ports via I/O board
- M.2 Interface: 2 PCIe 3.0 x4; M.2 Form Factor: 22110 via M.2 I/O board

H14DSG-O-CPU

Key Features

- Dual AMD EPYC™ 9005/9004 Series Processors
- Up to 6400MT/s ECC DDR5 RDIMM memory
- 20 PCIe 5.0 x8 MCIO connectors
- 2 SATA3, 1AIOM slot
- M.2 Interface: 1 PCIe 3.0 x4 (2280, 22110)
- 2 USB 3.0 via I/O board

H13SVW-NT-OS2

Key Features

- AMD EPYC™ 8004 series Processors
- System on Chip
- Up to 768GB ECC RDIMM, DDR5-4800MHz in 6 DIMM slots
- 2 PCIe 5.0 x16 via Riser Slot 1 PCIe 5.0 x 16 via Riser Slot
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 3 PCIe 5.0 x8 MCIO connectors
- 8 SATA3 / PCIe 5.0 Hybrid via 2 PCIe 5.0 x8 MCIO
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4 M.2 Form Factor: 2280, 22110

H13SVW-NT-OS1

Key Features

- AMD EPYC™ 8004 series Processors
- System on Chip
- Up to 768GB ECC RDIMM, DDR5-4800MHz in 6 DIMM slots
- 2 PCIe 5.0 x16 via Riser Slot 1 PCIe 5.0 x 16 via Riser Slot
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 3 PCIe 5.0 x8 MCIO connectors
- 8 SATA3 / PCIe 5.0 Hybrid via 2 PCIe 5.0 x8 MCIO
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4 ; M.2 Form Factor: 2280, 22110

H13SVW-NT

Key Features

- AMD EPYC™ 8004 series Processors
- System on Chip
- Up to 768GB ECC RDIMM, DDR5-4800MHz in 6 DIMM slots
- 2 PCIe 5.0 x16 via Riser Slot 1 PCIe 5.0 x 16 via Riser Slot
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 3 PCIe 5.0 x8 MCIO connectors
- 8 SATA3 / PCIe 5.0 Hybrid via 2 PCIe 5.0 x8 MCIO
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4 M.2 Form Factor: 2280, 22110

H13SVW-N

Key Features

- AMD EPYC™ 8004 series Processors
- System on Chip
- Up to 768GB ECC RDIMM, DDR5-4800MHz in 6 DIMM slots
- 2 PCIe 5.0 x16 via Riser Slot ; 1 PCIe 5.0 x 16 via Riser Slot
- 2x 1GBase-T LAN Ports via Broadcom BCM5720L
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 3 PCIe 5.0 x8 MCIO connectors
- 8 SATA3 / PCIe 5.0 Hybrid via 2 PCIe 5.0 x8 MCIO
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4M.2 Form Factor: 2280, 22110

H13SSW

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6400 MT/s (Please check System Memory Section for detail)
- 2 PCIe 5.0 x16 via riser slot; 8 PCIe 5.0 x8 via MCIO
- PCIe 5.0 x16 AIOM / OCP3.0 networking slot
- M.2 Interface: 2 PCIe 3.0 x2 (2280/22110)
- 16 SATA3 Hybrid via 2 PCIe 5.0 x8 MCIO
- 2 USB 3.0 from rear I/O + 2 USB2.0 via Header
- ASPEED AST2600 BMC graphics

H13SST-GC

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- LSI 3808 controller for 6 SAS3 ports
- AMD FCH controller for 8 SATA3 (6 Gbps) ports;
- 1 PCIe 4.0 x8 4C connector (for front I/O module), 5 PCIe 5.0 x8 MCIO connectors
- M.2 Interface: 2 SATA/PCIe 4.0 x4, M.2 Form Factor: 2280

H13SST-G

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- AMD FCH controller for 8 SATA3 (6 Gbps) ports;
- 1x PCIe 4.0 x8 4C connector (for front I/O module), 5x PCIe 5.0 x8 MCIO connectors
- M.2 Interface: 2 SATA/PCIe 4.0 x4, M.2 Form Factor: 2280

H13SSL-NT

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- 3 PCIe 5.0 x16; 2 PCIe 5.0 x8
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- ASPEED AST2600 BMC graphics
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4 M.2 Form Factor: 2280, 22110

H13SSL-N

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 12 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- 3 PCIe 5.0 x16 ; 2 PCIe 5.0 x8
- 2x 1GBase-T LAN Ports via with Broadcom BCM5720L
- Up to 6 USB 3.0 ports(4 rear + 2 via header)
- 8 SATA3
- ASPEED AST2600 BMC graphics
- 6 PWM 4-pin Fans with tachometer status monitoring
- M.2 Interface: 2 PCIe 5.0 x4 M.2 Form Factor: 2280, 22110

H13SSH-E

Key Features

- AMD EPYC™ 9004/9005 Series Processors
- System on Chip
- Support up to DDR5 24 DIMM slots (2DPC), speed up to 5200MT/s (Please check System Memory Section for detail)
- 24 NVMe (PCIe 5.0 x8)
- 2 PCIe 5.0 x16 Molex Impel plus connector
- M.2 Interface: 1 PCIe 3.0 x4, 1 PCIe 3.0 x2; M.2 (22110)
- 4 USB 3.0 ports (2 rear via riser + 2 via header)

H13SSH

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 24 DIMM slots (2DPC), speed up to 5200MT/s (Please check System Memory Section for detail)
- 2 PCIe 5.0 x16 Molex Impel plus connector
- 24 NVMe (PCIe 5.0 x8), 32 SATA 3.0 Hybrid ports
- 4 USB 3.0 ports (2 rear via riser + 2 via header)
- M.2 Interface: 1 PCIe 3.0 x4, 1 PCIe 3.0 x2; M.2 (22110)

H13SSF

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- System on Chip
- Support up to DDR5 24 DIMM slots (2DPC), speed up to 5200MT/s (Please check System Memory Section for detail)
- 2 PCIe 5.0 x16 via Riser Slot8 PCIe 5.0 x8 via MCIO2 PCIe 5.0 x16 AIOM/ OCP3.0 Networking SlotM.2 Interface: 1 PCIe 3.0 x4, 1 PCIe 3.0 x2M.2 Form Factor: 2280/22110
- ASPEED AST2600 BMC graphics
- 2 SATA3 via SlimSAS connector
- 2 USB 3.0 from Rear IO+ 2 USB3.0 via Header

H13SRH

Key Features

- AMD Ryzen™ Threadripper™ PRO 9000WX and 7000 WX-Series Processor. Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported
- AMD WRX90
- Up to 2TB of memory with speeds of 6400+MT/s (1DPC) with overclocking support**Max. capacity up to 8TB *Currently the largest capacity on the market is 256GB/per DIMM**Memory addressing up to 1TB/channel is subject to AMD Infrastructure Roadmap for Socket sTR5 Processors
- 9 PCIe 5.0 x8 MCIO connectors for 8 NVMe/SATA drives, Riser Card and 2nd AIOM2 PCIe 5.0 x16 for Riser Card
- M.2 Interface: 2 PCIe 4.0 x4 (RAID 0, 1)M.2 Form Factor: 2280/22110M.2 Key: M-Socket
- Onboard TPM2.0
- Overclocking supported on CPU and RDIMM

H13SRE-F

Key Features

- AMD EPYC™ 4005, 4004 series processors, or Ryzen™ 9000 & 7000 series processor, single socket LGA-1718 (Socket AM5) supported, APU TDP supports up to 170W TDP
- Up to 192GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x4 (Micro Low Profile);1 PCIe 5.0 x16
- 2 PCIe Gen5 x2 NVMe SSD / 2 SATA3 SSD
- M.2 Interface: PCIe 5.0 x2 (2280/22110)
- 1 VGA port; 2 USB 2.0 ports; 1 serial port via KVM connector
- 1 LAN port; Realtek RTL8211FS PHY for dedicated IPMI

H13SRD-F

Key Features

- AMD EPYC™ 4005, 4004 series or Ryzen™ 9000 & 7000 series desktop processor, single socket LGA-1718 (socket AM5), up to 170W
- Up to 192GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x8 (Micro Low Profile)1 PCIe 5.0 x8 (Low Profile, Open End)
- 1 VGA port; 2 USB 2.0 ports; 1 serial port via KVM connector
- 1 LAN port; Realtek RTL8211FS PHY for dedicated IPMI
- M.2 Interface:PCIe 5.0 x2 (2280/22110)

H13SRA-TF

Key Features

- AMD Ryzen™ Threadripper™ PRO 9000/7000 WX-Series and Ryzen™ Threadripper™ 9000/7000 Series Processors
- Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported
- AMD TRX50
- Up to 1TB of memory with speeds of 6400+MT/s (1DPC) with overclocking support
- M.2 Interface: 2 PCIe 4.0 x4 (RAID 0, 1)M.2 Form Factor: 2280/22110M.2 Key: M-Socket
- 2 PCIe 5.0 x16, support 2 triple/dual/single-width GPU cards2 PCIe 5.0 x8, open rear
- Dual 10Gb LAN with Broadcom BCM57416
- 1 MCIO connector (PCIe Gen4 x8) to support 2 U.2 ports via cable for NVMe 2.5" SSD drives (RAID 0,1)
- 1 Dedicated LAN for IPMI
- Overclocking supported on CPU and RDIMM

H13SRA-F

Key Features

- AMD Ryzen™ Threadripper™ PRO 9000/7000 WX-Series and Ryzen™ Threadripper™ 9000/7000 Series Processors
- Single socket sTR5, LGA-4844, Up to 350W TDP, Overclocking supported
- AMD TRX50
- Up to 1TB of memory with speeds of 6400+MT/s (1DPC) with overclocking support
- M.2 Interface: 2 PCIe 4.0 x4 (RAID 0, 1)M.2 Form Factor: 2280/22110M.2 Key: M-Socket
- 2 PCIe 5.0 x16, support 2 triple/dual/single-width GPU cards2 PCIe 5.0 x8, open rear
- Dual 1Gb LAN with Broadcom BCM5720
- 1 MCIO connector (PCIe Gen4 x8) to support 2 U.2 ports via cable for NVMe 2.5" SSD drives (RAID 0,1)
- 1 Dedicated LAN for IPMI
- Overclocking supported on CPU and RDIMM

H13SAE-MF

Key Features

- AMD EPYC™ 4005, 4004 series or Ryzen™ 9000 & 8700G* (system only) & 7000 series desktop processor, single socket LGA-1718 (socket AM5), up to 170W
- Up to 192GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 4 DIMM slots
- 2 PCIe 5.0 x16 (16/NA or 8/8), support up to 2 GPU cards (mechanical is up to 1 triple-width GPU card or 2 double-width GPU cards); 1 PCIe 4.0 x4
- Dual 1Gbit LAN ports (i210 AT); 1 dedicated Realtek 1Gbit LAN for IPMI
- Micro-ATX form factor
- 1 USB 3.2 Gen2x2 port (type C, 20Gb, rear); 5 USB 3.2 Gen2 ports (2 Type C, rear, support DP 1.4 Alt mode)
- 1 HDMI 2.0 port, 1 DP 1.4a port
- M.2 Interface: 2 PCIe 5.0 x4 (RAID 0 & 1) (2280/22110, M-Key)

H13QSH

Key Features

- Quad AMD Instinct™ MI300 Series Processors (MI300A, AMD Socket SH5)
- Up to GENOA 96 cores / 192 threads, 912 GPU cores, Max. cTDP 760W
- Up to 512GB HBM3 memory, bandwidth 5.3TB/s
- 16 PCIe 5.0 x8 MCIO connectors
- 4 PCIe 5.0 x4,x4 MCIO connectors
- 2 OCP NIC 3.0 compatible AIOM networking slots
- 2 M.2 PCIe 4.0 x4 (2280/22110)

H13DSH

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6400 MT/s (Please check System Memory Section for detail)
- 10 PCIe 5.0 x8 MCIO connectors
- 32 SATA3 Hybrid via MCIO, 1 AIOM slot
- 4 USB 3.0 ports (2 rear via I/O board + 2 via header)
- ASPEED AST2600 BMC graphics via I/O board

H13DSG-OM

Key Features

- AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 6000 MT/s (Please check System Memory Section for detail)
- 6 PCIe 5.0 x8 MCIO connectors; 2 SATA3 / PCIe 5.0 Hybrid x8 MCIO connectors
- 2 USB 3.0 ports via I/O board
- ASPEED AST2600 BMC graphics
- M.2 Interface: 2 PCIe 3.0 x4; M.2 Form Factor: 2280, 22110

H13DSG-O-CPU-D

Key Features

- Dual AMD EPYC™ 9004 Series Processors
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 4800 MT/s (Please check System Memory Section for detail)
- 20 PCIe 5.0 x8 MCIO to PCIe board
- 2 USB 3.0 ports via I/O board
- Integrated IPMI 2.0 + KVM with dedicated LAN
- 2x 4-pin PWM Fans & Speed control
- ASPEED AST2600 BMC graphics via I/O board
- 2 SATA3, 4 NVMe

H13DSG-O-CPU

Key Features

- Dual AMD EPYC™ 9004/9005* Series Processors (*AMD EPYC™ 9005 series drop-in support requires board revision 2.x)
- Support up to DDR5 24 DIMM slots (1DPC), speed up to 5200 MT/s (Please check System Memory Section for detail)
- 20 PCIe 5.0 x8 MCIO to PCIe board
- 2 USB 3.0 ports via I/O board
- 2 SATA3, 4 NVMe, 1 AIOM slot
- ASPEED AST2600 BMC graphics via I/O board

H12SSW-NTR

Key Features

- Single AMD EPYC™ 7003/7002 Series Processor (7003 Series Processor drop-in support requires BIOS version 2.0 or newer)
- 4TB Registered ECC DDR4 3200MHz SDRAM in 16 DIMMs
- Expansion slots:, 1 PCI-E 4.0 x32 Left Riser Slot, 1 PCI-E 4.0 x16 Right Riser Slot, M.2 Interface: 2 PCI-E 4.0 x2, M.2 Form Factor: 2280, 22110, M.2 Key: M-key
- 2x 10GBase-T LAN Ports via Broadcom BCM57416
- 12 native NVMe via SlimSAS,, 4 NVMe or 16 SATA3 ports via SlimSAS,, 2 M.2,, 2 SATA3
- 6x 4-pin PWM Fans & Speed control
- Up to 7 USB 3.0 ports
- ASPEED AST2500 BMC graphics

H12SSW-NTL

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x2
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
M.2-C1 can support PCI-E x4, when only install 1pcs M.2
- 2 Broadcom BCM57416 10GBase-T,
1 Realtek RTL8211F PHY (dedicated IPMI)
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports; Hybrid use from Four(4) internal NVMe ports by BIOS option.
SATA3 (6 Gbps)2 SATA3 (6 Gbps) ports; Asmedia ASM1061

H12SSW-NT

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x2
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
M.2-C1 can support PCI-E x4, when only install 1pcs M.2
- 2 Broadcom BCM57416 10GBase-T,
1 Realtek RTL8211F PHY (dedicated IPMI)
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports; Hybrid use from Four(4) internal NVMe ports by BIOS option.
SATA3 (6 Gbps)2 SATA3 (6 Gbps) ports; Asmedia ASM1061

H12SSW-iNR

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
8-channel memory bus
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
M.2 Interface: 2 PCI-E 3.0 x2
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 2 Broadcom BCM5720 1GBase-T,
1 Realtek RTL8211F PHY (dedicated IPMI)
- SATA3 (6 Gbps)2 SATA3 (6 Gbps) ports; Asmedia ASM1061

H12SSW-iNL

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x2
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
M.2-C1 can support PCI-E x4, when only install 1pcs M.2
- 2 Broadcom BCM5720 1GBase-T,
1 Realtek RTL8211F PHY (dedicated IPMI)
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports; Hybrid use from Four(4) internal NVMe ports by BIOS option.
SATA3 (6 Gbps)2 SATA3 (6 Gbps) ports; Asmedia ASM1061

H12SSW-iN

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
M.2 Interface: 2 SATA/PCI-E 3.0 x2
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
M.2-C1 can support PCI-E x4, when only install 1pcs M.2
- 2 Broadcom BCM5720 1GBase-T,
1 Realtek RTL8211F PHY (dedicated IPMI)
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports; Hybrid use from Four(4) internal NVMe ports by BIOS option.
SATA3 (6 Gbps)2 SATA3 (6 Gbps) ports; Asmedia ASM1061

H12SSW-AN6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
8-channel memory bus
- 1 PCI-E 4.0 x16 for Left riser card support
1 PCI-E 4.0 x16 for Right riser card support
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
2 PCI-E 4.0 x16 slots (16/NA/NA or 8/8/NA or 8/4/4) for AIOM networking
- SATA3 (6 Gbps)8 SATA3 (6 Gbps) ports; 8 SATA3 via 1x Slim SASx8
SATA3 (6 Gbps)8 SATA3 (6 Gbps) ports; 8 SATA3 via 2x Slim SASx4
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12SST-PS

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x16 for Left riser card support
1 PCI-E 4.0 x16 for Right riser card support
1 PCI-E 4.0 x16 SIOM LAN Networking Slot
1 PCI-E 4.0 x24 Proprietary Slot (for Supermicro storage add-on card)
M.2 Interface: 4 SATA/PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280, 2260, 2242
M.2 Key: M-Key
- SATA3 (6 Gbps)6 SATA3 (6 Gbps) ports;
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12SSL-NT

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16
2 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
M.2 Key: M-Key
- 2 Broadcom BCM57416 10GBase-T

H12SSL-i

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16
2 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
M.2 Key: M-Key
- 2 Broadcom BCM5720 1GBase-T

H12SSL-CT

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16
2 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
M.2 Key: M-Key
- Broadcom 3008 SAS3 (12 Gbps) controller for 8 SAS3 (12 Gbps) ports; RAID 0,1,10
- 2 Broadcom BCM57416 10GBase-T

H12SSL-C

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 5 PCI-E 4.0 x16
2 PCI-E 4.0 x8
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
M.2 Key: M-Key
- Broadcom 3008 SAS3 (12 Gbps) controller for 8 SAS3 (12 Gbps) ports; RAID 0,1,10
- 2 Broadcom BCM5720 1GBase-T

H12SSG-ANP6

Key Features

- AMD Ryzen™ Threadripper™ PRO 3000/5000 Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 3 PCI-E 4.0 x16
9 PCI-E 4.0 x8 SlimSAS
2 PCI-E 4.0 x4 SlimSAS
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110
M.2 Key: M-Key
1 PCI-E 4.0 x16 PCI-E 4.0 AOM Slot for AIOM networking
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12SSG-AN6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 3 PCI-E 4.0 x16
9 PCI-E 4.0 x8 SlimSAS
2 PCI-E 4.0 x4 SlimSAS
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110
M.2 Key: M-Key
1 PCI-E 4.0 x16 PCI-E 4.0 AOM Slot for AIOM networking
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12SSFR-AN6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 2 TB ECC Registered, DDR4-3200MHz SDRAM in 8 DIMMs
- 1 PCI-E 4.0 x16 for Right riser card support
1 PCI-E 4.0 x8 Left Hand Riser
M.2 Interface: 4 SATA/PCI-E 4.0 x4
M.2 Form Factor: 22110
1 PCI-E 4.0 x16 for AIOM networking, AIOM

H12SSFF-AN6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
- 1 PCI-E 4.0 x16 for Right riser card support
1 PCI-E 4.0 x16 for Left riser card support
M.2 Interface: 2 SATA/PCI-E 4.0 x4
M.2 Form Factor: 22110
1 PCI-E 4.0 x16 PCI-E 4.0 AOM Slot for AIOM networking

H12DSU-iNR

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 8 TB ECC Registered, DDR4-3200MHz SDRAM in 32 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
1 PCI-E 4.0 x40 Far Right Riser Slot
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports;
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12DSU-iN

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 8 TB ECC Registered, DDR4-3200MHz SDRAM in 32 DIMMs
- 1 PCI-E 4.0 x32 Left Riser Slot
1 PCI-E 4.0 x16 Right Riser Slot
1 PCI-E 4.0 x40 Far Right Riser Slot
- SATA3 (6 Gbps)16 SATA3 (6 Gbps) ports;
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12DST-B

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
- 1 PCI-E 4.0 x16 for Left riser card support
1 PCI-E 4.0 x16 for Right riser card support
1 PCI-E 4.0 x16 SIOM LAN Networking Slot
1 PCI-E 4.0 x24 Proprietary Slot (for Supermicro storage add-on card)
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 22110, 2280
M.2 Key: M-Key
- SATA3 (6 Gbps)6 SATA3 (6 Gbps) ports;
- 1 Realtek RTL8211F PHY (dedicated IPMI)

H12DSi-NT6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
- 3 PCI-E 4.0 x16
3 PCI-E 4.0 x8
M.2 Interface: 1 SATA/PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
- 2 Broadcom BCM57416 10GBase-T
- SATA3 (6 Gbps)10 SATA3 (6 Gbps) ports;

H12DSi-N6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 4 TB ECC Registered, DDR4-3200MHz SDRAM in 16 DIMMs
- 3 PCI-E 4.0 x16
3 PCI-E 4.0 x8
M.2 Interface: 1 SATA/PCI-E 4.0 x4
M.2 Form Factor: 22110, 2280
- 2 Broadcom BCM5720 1GBase-T
- SATA3 (6 Gbps)10 SATA3 (6 Gbps) ports;

H12DSG-Q-CPU6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 8 TB ECC Registered, DDR4-3200MHz SDRAM in 32 DIMMs
- 19 PCI-E 4.0 x8 SlimSAS
1 PCI-E 4.0 x4 SlimSAS

H12DSG-O-CPU

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 20 PCI-E 4.0 x8 SlimSAS to PCI-E board
1 PCI-E 4.0 x16 for AIOM networking
- Marvell 88SE9230 controller SATA3 (6 Gbps) controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 8 TB ECC Registered, DDR4-3200MHz

H12DGQ-NT6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 8 TB ECC Registered, DDR4-3200MHz SDRAM in 32 DIMMs
- 8 PCI-E 4.0 x16 via SlimSAS x8 from PLX for GPU
8 PCI-E 4.0 x16 via SlimSAS x8 from PLX for Riser
2 PCI-E 4.0 x16 vis SlimSAS x8 from CPU for Riser or AIOM
- 12 SATA3 (6Gbps) ports via 3 SlimSAS x4 ports ; 10 NVMe ports via 5 SlimSAS x8 ports
- 1 Realtek RTL8211F PHY (dedicated IPMI)
- ASPEED AST2600 BMC graphics

H12DGO-6

Key Features

- AMD EPYC™ 7002 series (Rome) Processors, AMD EPYC™ 7003 series (Milan) Processors
- System on Chip
- 8 TB ECC Registered, DDR4-3200MHz SDRAM in 32 DIMMs
- 4 PCI-E 4.0 x8 SlimSAS
1 PCI-E 4.0 x4 SlimSAS
M.2 Interface: 2 PCI-E 4.0 x4
M.2 Form Factor: 22110
M.2 Key: M-Key

G2DMH-GI

Key Features

- Dual NVIDIA GH200 Grace Hopper™ Superchip with GPU memory 144GB HBM3e
- Intel ARRIA 10 GX FPGA
- 8x PCIe 5.0 x8 M-XIO
- DC-SCM support
- 2x NVMe Gen.5 M.2

G1SMP

Key Features

- NVIDIA Grace™ CPU Superchip, up to 144 Arm v9 cores
- 480GB/960GB LPDDR5X with ECC (Embedded in Nvidia C2 Superchip)
- Broadcom PEX89144
- Intel Cyclone 10 GX FPGA
- 16x NVMe ports PCIe5.0 x 4 via 8x MCIO
- 4x PCIe5.0 x16 interfaces via 8x MCIO
- 2x NVMe Gen5 M.2 (Form Factor 22110, M-Key)
- ASPEED AST2600 BMC Module with Nvidia Open BMC software
- Supports: Redfish, IPMI tool, SAA for L6 and L10 production.
- No supporting: SCC,SSM, SUM, SDO, TAS, IPMI Utilities.

G1SMH-G

Key Features

- NVIDIA GH200 Grace Hopper™ Superchip
- Intel Cyclone 10 GX FPGA
- 6x PCIe 5.0 x8 M-XIO
- DC-SCM support
- 2x NVMe Gen.5 M.2

G1SMH

Key Features

- NVIDIA Grace™ CPU Superchip
- Intel Cyclone 10 GX FPGA
- 14x PCIe 5.0 x8 M-XIO
- 2x NVMe Gen.5 M.2
- DC-SCM support

G1SBC

Key Features

- Single processor(s) NVIDIA Grace™ CPU C1
- 240GB on-board memory with ECC LPDDR5X
- Intel Cyclone 10 GX FPGA
- 3x PCIe 5.0 x16
- 2x NVMe Gen.5 M.2
- DC-SCM support

CARAM5-M

Key Features

- AMD EPYC™ 4004/4005 Series or Ryzen™ 7000/9000 Series Processors, LGA-1718 (AM5 Socket), Up to 170W TDP
- AMD B850 chipset
- 2 DDR5 5600MT/s Non-ECC UDIMM, Up to 96GB
- 1 PCIe 5.0 x16 attached to CPU, 1 PCIe 4.0 x4 attached to B850
- M.2 Interface: 1 PCIe 5.0 x4, 1 PCIe 4.0 x4 (RAID 0 &1)
- M.2 Form Factor: 2280/22110
- M.2 Key: M-key
- 1 HDMI 2.1, 2 USB 4.0 Type-C (DP 2.0 Alt Mode)
- Single 5G LAN with Realtek® Ethernet RTL8126
- Wi-Fi 7 + Bluetooth® 5.4

C9Z890-MW

Key Features

- Intel® Core™ Ultra 9/7/5 and Core™ Ultra 7/5 Plus Processors, LGA 1851 (Intel® V1 Socket), TDP up to 125W
- Intel® Z890
- Up to 256GB non-ECC UDIMM4 DDR5 5600+MT/s (OC), Supports Intel Extreme Memory Profile (XMP) memory module
- 1 PCIe 5.0 x16 Slot1 PCIe 4.0 x4 Slot 1 PCIe 4.0 x1 Slot
- M.2 Interface: 1 PCIe 5.0 x4; 1 PCIe 4.0 x4, RAID 0 &1M.2 Form Factor: 2280/22110M.2 Key: M-Key
- Single LAN with Intel® Ethernet I219-VWi-Fi 7 + Bluetooth® 5.4
- 1 HDMI 2.1*, 1 DP 2.1**, 1 Thunderbolt™ 4.0 Type-C® *Supports data rates of up to 8Gbps (8K@60Hz) **Supports data rates of up to 10 Gbps

C9Z790-CGW

Key Features

- 14th (up to 8+16 cores)/13th (up to 8+16 cores)/12th (up to 8+8 cores) Gen Intel® Core™ i9/i7/i5/i3, Pentium® and Celeron® Processors, LGA 1700 (Intel® V0 Socket), TDP up to 150W
- Intel® Z790
- Up to 192GB non-ECC UDIMM4 DDR5 4400MT/s, 5000+MT/s (OC)
- 2 PCIe 5.0 x16 Slots (16/NA or 8/8) with Armor protection (only available for discrete graphics or storage cards)2 PCIe 3.0 x1 Slot
- M.2 Interface: 1 PCIe 4.0 x4, 2 PCIe 3.0 x4, RAID 0,1,5M.2 Form Factor: 2260/2280/22110M.2 Key: M-Key
- Single LAN with Intel® single Ethernet PHY i219V + Single LAN with Marvell AQCC113
- 1 HDMI 2.1 port, 1 DP 1.4b port
- 1 Wi-Fi 6E (1.3Gbps) + Bluetooth 5.4 (C9Z790-CGW only)
- Overclocking Supported (optional)

C9Z790-CG

Key Features

- 14th (up to 8+16 cores)/13th (up to 8+16 cores)/12th (up to 8+8 cores) Gen Intel® Core™ i9/i7/i5/i3, Pentium® and Celeron® Processors, LGA 1700 (Intel® V0 Socket), TDP up to 150W
- Intel® Z790
- Up to 192GB non-ECC UDIMM4 DDR5 4400MT/s, 5000+MT/s (OC)
- 2 PCIe 5.0 x16 Slots (16/NA or 8/8) with Armor protection (only available for discrete graphics or storage cards)2 PCIe 3.0 x1 Slot
- Single LAN with Intel® single Ethernet PHY i219V + Single LAN with Marvell AQCC113
- M.2 Interface: 1 PCIe 4.0 x4, 2 PCIe 3.0 x4, RAID 0,1,5
- M.2 Form Factor: 2260/2280/22110
- M.2 Key: M-Key
- 1 HDMI 2.1 port, 1 DP 1.4b port

C9Q870-M

Key Features

- Intel® Core™ Ultra 9/7/5 and Core™ Ultra 7/5 Plus Processors, LGA 1851 (Intel® V1 Socket), TDP up to 125W
- Intel® Q870
- Up to 256GB non-ECC UDIMM4 DDR5 5600MT/s
- 1 PCIe 5.0 x16 Slot1 PCIe 4.0 x4 Slot 1 PCIe 4.0 x1 Slot
- M.2 Interface: 1 PCIe 5.0 x4; 1 PCIe 4.0 x4, RAID 0 &1M.2 Form Factor: 2280/22110M.2 Key: M-Key
- Single LAN with Intel® Ethernet I219-LMSupports Intel® vPro
- 1 HDMI 2.1*, 1 DP 2.1**, 1 Thunderbolt™ 4.0 Type-C® *Supports data rates of up to 8Gbps (8K@60Hz) **Supports data rates of up to 10 Gbps

C9B860-MW

Key Features

- Intel® Core™ Ultra 9/7/5 and Core™ Ultra 7/5 Plus Processors, LGA 1851 (Intel® V1 Socket), TDP up to 125W
- Intel® B860
- Up to 256GB non-ECC UDIMM4 DDR5 5600+MT/s (OC), Supports Intel Extreme Memory Profile (XMP) memory module
- 1 PCIe 5.0 x16 Slot1 PCIe 4.0 x4 Slot 1 PCIe 4.0 x1 Slot
- M.2 Interface: 1 PCIe 5.0 x4; 1 PCIe 4.0 x4, RAID 0 &1M.2 Form Factor: 2280/22110M.2 Key: M-Key
- Single LAN with Intel® Ethernet I219-V
- 1 HDMI 2.1*, 1 DP 2.1**, 1 Thunderbolt™ 4.0 Type-C® *Supports data rates of up to 8Gbps (8K@60Hz) **Supports data rates of up to 10 Gbps
- Intel® Wi-Fi 7 and Bluetooth® 5.4

C7C232-CB-ML

Key Features

- Single socket H4 (LGA 1151) supports Intel® Xeon® processor E3-1200 v5/v6, Intel® 6th/7th Gen. Core™ i7/i5/i3 series, Intel® Celeron® and Intel® Pentium®

BH4SRG

Key Features

- AMD EPYC™ 4005/4004 series processors, single socket LGA-1718 (Socket AM5) supported, APU TDP supports up to 170W TDP
- Up to 192GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 4 DIMM slots
- 2 PCIe 5.0 x8 MCIO connectors for GPU / 2x U.2 NVME riser
- 1 PCIe 5.0 x4 and 1 PCIe 5.0 x2 M.2 slots for 22110/2280 M.2 drives
- Onboard Broadcom BCM57414 Dual-Port 10GbE Base-KR PCIe 3.0 x4 to back panel
- Power distribution board to support extra GPU in 6U AMD Microblade

BH4SR2-25G

Key Features

- AMD EPYC™ 4005/4004 series processors, Dual nodes with LGA-1718 (Socket AM5), APU TDP supports up to 110W TDP per node
- Up to 128GB ECC/non-ECC unbuffered DIMM, DDR5-5600MHz, in 2 DIMM slots per node
- 2x E1.S connectors and 1x M.2 slots for 22110/2280 M.2 drives per node
- Onboard Broadcom BCM57414 Dual-Port 25GbE Base-KR PCIe 3.0 x8 to back panel

B4SC1-CPU

Key Features

- Intel® Xeon® 6300-series/E-2400 Series Processors, Single Socket LGA-1700 (Socket V0) supported, CPU TDP supports Up to 95W TDP
- Intel® C266 Chipset
- Up to 128GB DDR5 ECC UDIMM in 4 DIMM slots. Supports up to 4400MT/s (1DPC), 4000MT/s (2DPC)
- 1 PCIe 4.0 x8 for AIOM Add-On-Module
- Dual LAN with Broadcom BCM57414 Dual-Port 10G Base-KR PCIe Gen 3 via AOM-BPNIO-MSH2
- Dual 1GbE LAN ports with Intel i350 via AOM-BPNIO-MS
- M.2 Interface: 1 SATA3/NVMe (PCIe 4.0 from PCH) M.2 Form Factor: 2280/22110 M.2 Key: M-Key

B4SA1-CPU

Key Features

- 12th/13th Gen Intel® Core™ i5/i7/i9 Processors
- Single Socket LGA-1700, CPU TDP up to 125W
- Intel® W680 Chipset
- Up to 128GB DDR5 ECC UDIMM in 4 DIMM slots. Supports up to 4400MT/s (1DPC)
- 1 PCIe 4.0 x8 for AIOM Add-On-Module
- Dual LAN with Broadcom BCM57414 Dual-Port 10G Base-KR PCIe Gen 3 via AOM-BPNIO-MSH2
- Dual 1GbE LAN ports with Intel i350 via AOM-BPNIO-MS
- M.2 Interface: 1 SATA3/NVMe (PCIe 4.0 from PCH) M.2 Form Factor: 2280/22110 M.2 Key: M-Key

B3ST1-CPU-001

Key Features

- Intel® Xeon® E-2300 Rocket Lake Processor
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 95W TDP
- Intel® C256
- Up to 128GB of ECC and Non-ECC VLP UDIMM DDR4, in 4 DIMM Slots
- Dual LAN with
Broadcom BCM57414 Dual-Port 10G Base-KR PCIe Gen 3 via AOM-BPNIO-MSH2
- 1 PCI-E 4.0 x8 for Add-On-Module (AOM)

2x U.2 SATA 3.0 PCI-E x4 Gen 4 via AOM-BPNIO-MSH2
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
2x M.2 PCI-E 2280/22110 (1x onboard and 1x via AOM-BPNIO-MSH2)
- Intel® C256 controller for 2 SATA3 (6 Gbps) ports; RAID 0,1,5,10

B3SD1-20C-25G

Key Features

- U.2 Interface: 1 PCIe 4.0 x4 via HDD Backplane
- Intel® Xeon® Processor D-2796NT, CPU TDP 120W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB DDR4 ECC LRDIMM in 2 DIMM slots, 2933MT/s
- 1 PCI-E 4.0 x4
M.2 Interface: 1 PCI-E 4.0 x4
M.2 Form Factor: 2280
M.2 Key: M-Key
- Dual LAN with SoC
Two(2)25GbE Ethernet ports from KR interface to BP

B14SBE-CPU-AP

Key Features

- Intel® Xeon® 6900-series processors with P-cores, Single Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W TDP
- Up to 1.5TB DDR5 ECC RDIMM or 3TB RDIMM (3DS) with speeds of up to 6400MT/s (1DPC) or up to 3TB MRDIMM (1DPC) DDR5-8800MT/s in 12 DIMM slots
- 6x PCIe 5.0 x8 MCIO connectors for GPU Riser/NVMe/AIOM add on module
- Power distribution board to support extra GPU in 6/8U blade1x Blade Power Connector1x 12pin+4S 12VHPWR Connector2x Side Band Connectors for Motherboard Control
- EDSFF Interface: EDSFF 1C swich to M.2, Up to 2x PCIe 5.0 x2 via adaptor card, RAID 0 & 1M.2 Form Factor: 2280M.2 Key: M-Key
- Onboard Intel® Columbiaville Ethernet Controller E810-XXVAM2

B14SBE-CPU-25G

Key Features

- Intel® Xeon® 6700/6500-series processors with P-cores or E-cores, Single Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 2TB DDR5 ECC RDIMM or 4TB RDIMM (3DS) with speeds of up to 6400MT/s (1DPC) or DDR5-5200MT/s (2DPC) or up to 512GB MRDIMM (1DPC) DDR5-8000MT/s in 16 DIMM slots
- 5x PCIe 5.0 x8 MCIO connectors for GPU Riser/NVMe/AIOM add on module
- Onboard Intel® Columbiaville Ethernet Controller E810-XXVAM2
- M.2 Interface: 1x PCIe 5.0 x4 M.2 Form Factor: 2280, 22110M.2 Key: M-Key

B14DBT

Key Features

- Intel® Xeon® 6700/6500-series processors with P-cores or E-cores, dual Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 1TB MRDIMM with speeds up to 8000 MT/s (1DPC) or 4TB of RDIMM(3DS) with speeds up to 6400 MT/s (1DPC)
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16 AIOM connector
- 1 PCIe 4.0 x16 Mezzanine connector
- M.2 Interface: 1 PCIe 5.0 x4 M.2 Form Factor: 2280 M.2 Key: M-Key
- Dual 25G LAN with Intel®E810
- Onboard TPM2.0

B14DBE-AP

Key Features

- 6th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-7529 (Socket BR) supported, CPU TDP supports Up to 500W
- Support DDR5 with up to speeds of 6400MT/s (RDIMM) or 8800MT/s (MRDIMM) in 24 DIMM slots
- 1 PCIe 5.0 x16 AIOM slot
- M.2 Interface: 2 PCIe5.0 x4M.2 Form Factor: 2280, 22110M.2 Key: M-Key
- 7 PCIe 5.0 x8 MCIO connectors
- 1 PCIe 5.0 x16 riser card slot

B14DBE

Key Features

- Intel® Xeon® 6700/6500-series processors with P-cores or E-cores, dual Socket LGA-4710 (Socket E2) supported, CPU TDP supports Up to 350W TDP
- Up to 1TB MRDIMM with speeds up to 8000 MT/s (1DPC) or 8TB of RDIMM(3DS) with speeds up to 6400 MT/s (1DPC) or 5200 MT/s (2DPC) in 32 DIMM slots
- 1 PCIe 4.0 x16 Mezzanine connector
- 6 PCIe 5.0 x8 via MCIO connectors
- Dual 25G LAN with Intel®E810
- Onboard TPM2.0
- 1 PCIe 5.0 x8 E1.S connector for dual M.2 support via adapter card

B13SEG

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 270W (air-cooled) or 350W (liquid-cooled)
- Intel C741® Chipset
- Up to 2TB ECC RDIMM/LR/3DS RDIMM DDR5-5600MT/s in 8 DIMM slots
- 4x PCIe 5.0 x8 MCIO connectors for GPU Riser/E1S/NVMe/AIOM add on module
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN
- Dual M.2 M-Key 2280 PCIe 5.0 Connector
- Mezzanine PCIe 5.0 x16 connector for Mezzanine Daughter Card

B13SEE-CPU-25G

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Single Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Intel C741® Chipset
- Up to 4TB ECC R/LR/3DSLR, DDR5-5600MT/s (1DPC) or DDR5-4400MT/s (2DPC) in 16 DIMM slots Supports Intel® Optane™ Persistent Memory (PMem) 300 series
- 4x PCIe 5.0 x8 MCIO connectors for GPU Riser/E1S/NVMe/AIOM add on module
- Onboard Intel® Columbiaville Ethernet Controller E810-XXVAM2
- M.2 Interface: 1x PCIe 3.0 M.2 Form Factor: 2280, 22110M.2 Key: M-Key

B13DET

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors, Dual Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM and CXL
- Intel C741® Chipset
- Up to 4TB 3DS ECC RDIMM, DDR5-5600MT/s in 16 DIMM slots
- 3 SATA3 Ports or 2 NVME + 1 SATA3 ports
- 1 M.2
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN

B13DEE

Key Features

- 5th/4th Gen Intel® Xeon® Scalable processors and Intel® Xeon® Max series processors, Dual Socket LGA-4677 (Socket E) supported, CPU TDP supports Up to 350W TDP
- Supports HBM and CXL
- Intel C741® Chipset
- Up to 8TB 3DS ECC RDIMM, DDR5-5600MT/s in 32 DIMM slots
- 3 SATA3/NVMe HDDs/SSDs or 3 SAS3 HDDs
- 4 PCIe 5.0 X8 via MCIO connectors
- Dual LAN with 25GbE Intel® Ethernet Controller E810-XXVAM2

B12SPE-CPU-25G

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, in 16 DIMM slots
- M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Key: M-Key
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN

B12DPT-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 4TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-3200MHz, in 16 DIMM slots
- M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Key: M-Key
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN

B12DPE-6

Key Features

- 3rd Gen Intel® Xeon® Scalable processors
Dual Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 8TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 8TB 3DS ECC LRDIMM, DDR4-3200MHz, in 32 DIMM slots
- Dual LAN with 25GbE with Mellanox ConnectX-4 Lx EN

A4SAP-L

Key Features

- Intel® processor N97 (12W, 4C)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)

A4SAP-H

Key Features

- Intel® processor N97 (7W, 4C)
- Extension I/O (1 DP/HDMI, 2 PCI-E x1, 2 USB2.0, LPC, SATA, SMBus, Power)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)

A4SAP-E

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature support from -40°C to 65°C

A4SAN-L-WOHS

Key Features

- Intel® processor N97 (12W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2242/3052/2280
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays

A4SAN-L

Key Features

- Intel® processor N97 (12W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays

A4SAN-H-WOHS

Key Features

- Intel® Atom® Processor x7835RE (12W, 8C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 85°C

A4SAN-H

Key Features

- Intel® Atom® Processor x7835RE (12W, 8C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 70°C (by optional heatsink)

A4SAN-E-WOHS

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 85°C

A4SAN-E

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 75°C (by optional heatsink)

A3SSV-8C-SPLN10F

Key Features

- Intel Atom Processor P5322, , Single Socket FCBGA-2106 supported, , CPU TDP support 55 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2400MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SSV-24C-SPLN10F

Key Features

- Intel Atom Processor P5362, , Single Socket FCBGA-2106 supported, , CPU TDP support 83 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2933MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SSV-16C-SPLN10F

Key Features

- Intel Atom Processor P5342, , Single Socket FCBGA-2106 supported, , CPU TDP support 71 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2667MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SEV-4C-LN4

Key Features

- Intel® Atom® Processor x6425E
Single Socket FCBGA-1493 supported, CPU TDP supports Up to 12W TDP
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-3200MHz, in 2 DIMM slots
- 1 PCI-E 3.0 X2 (in x8 slot)
1 M.2 B-Key SATA/PCI-E 3.0 x2/USB 3.0, 3042/2280
1 M.2 E-Key PCI-E 3.0 x1/USB 2.0, 2230
- Single LAN with Intel® Ethernet Controller I210IT
ONLY i210 support PXE
3 LAN with 1GbE with Marvell® 88E1512
- 1 DP (DisplayPort) port, 1 HDMI port, 1 VGA port or 1 eDP (Embedded DisplayPort) port, Supports 3 independent displays
- System on Chip

A3SEV-2C-LN4

Key Features

- Intel® Atom® Processor x6211E.
Socket FCBGA-1493 supported, CPU TDP supports Up to 6W TDP
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-3200MHz, in 2 DIMM slots
- 1 PCI-E 3.0 X2 (in x8 slot)
1 M.2 B-Key SATA/PCI-E 3.0 x2/USB 3.0, 3042/2280
1 M.2 E-Key PCI-E 3.0 x1/USB 2.0, 2230
- Single LAN with Intel® Ethernet Controller I210IT
ONLY i210 support PXE
3 LAN with 1GbE with Marvell® 88E1512
- 1 DP (DisplayPort) port, 1 HDMI port, 1 VGA port or 1 eDP (Embedded DisplayPort) port, Supports 3 independent displays
- System on Chip

A2SDV-8C-TLN5F

Key Features

- Intel Atom Processor C3708, , Single Socket FCBGA1310 supported, , CPU TDP support 17W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-8C-LN8F

Key Features

- Intel® Atom® Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 5 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-8C-LN10PF

Key Features

- Intel® Atom® Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 5 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports , 2x 1GbE SFP LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-4C-LN8F

Key Features

- Intel® Atom® Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x2 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 3 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-4C-LN10PF

Key Features

- Intel® Atom® Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 up to x2 (Slot 6 or 7 option)* , Flexible I/O - software configurable in BIOS
- Up to 3 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS
- 8x 1GbE RJ45 LAN ports , 2x 1GbE SFP LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-16C-TLN5F

Key Features

- Intel Atom Processor C3958, , Single Socket FCBGA1310 supported, , CPU TDP support 31W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-12C+-TLN5F

Key Features

- Intel Atom Processor C3858, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDi-TP8F

Key Features

- Intel® Atom® Processor C3858.
Single Socket FCBGA-1310 supported, CPU TDP support Up to 25W TDP
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT, 2 10Gb SFP+
Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port

A2SDi-LN4F

Key Features

- Intel® Atom® Processor C3850., Single Socket FCBGA1310 supported, CPU TDP support 25W
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port
- Supports 12V DC power input

A2SDi-H-TP4F

Key Features

- Intel® Atom® Processor C3958., Single Socket FCBGA1310 supported, CPU TDP support 31W
- Up to 256GB Registered ECC RDIMM, DDR4-2400MHz
Up to 64GB Unbuffered ECC/non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
M.2 Interface: PCI-E 3.0 x2 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT and 2 10Gb SFP+
- SoC controller for 12 SATA3 (6 Gbps) ports;
4 SATA3 ports, 2 MiniSAS HD ports
- System on Chip
- 1 VGA port

A2SDi-H-TF

Key Features

- Intel® Atom® Processor C3758., Single Socket FCBGA1310 supported, CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC RDIMM, DDR4-2400MHz
Up to 64GB Unbuffered ECC/non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
M.2 Interface: PCI-E 3.0 x2 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Dual LAN with Intel® C3000 SoC
2 10GBaseT
- SoC controller for 12 SATA3 (6 Gbps) ports;
4 SATA3 ports, 2 MiniSAS HD ports
- Support 12V DC power
- System on Chip
- 1 VGA port

A2SDi-8C-HLN4F

Key Features

- Intel Atom Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-8C+-HLN4F

Key Features

- Intel Atom Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-4C-HLN4F

Key Features

- Intel Atom Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- Expansion slots: , 1 PCI-E 3.0 up to x4 (in x4 slot)* , Flexible I/O - software configurable in BIOS setup
- Up to 8 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS setup
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-2C-HLN4F

Key Features

- Intel Atom Processor C3338, , Single Socket FCBGA1310 supported, , CPU TDP support 9W
- Up to 128GB Registered ECC DDR4-1866MHz, , Up to 32GB Unbuffered ECC/Non-ECC DDR4-1866MHz; in 2 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 up to x4 (in x4 slot)* , Flexible I/O - software configurable in BIOS setup
- Up to 8 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS setup
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDI-16C-TP8F

Key Features

- Intel® Atom® Processor C3958., Single Socket FCBGA-1310 supported, CPU TDP support 31W TDP
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT, 2 10Gb SFP+
Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port

A2SDi-16C-HLN4F

Key Features

- Intel Atom Processor C3955, , Single Socket FCBGA1310 supported, , CPU TDP support 32W
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-16C+-HLN4F

Key Features

- Intel Atom Processor C3955, , Single Socket FCBGA1310 supported, , CPU TDP support 32W
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-12C-HLN4F

Key Features

- Intel Atom Processor C3858, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SAV-L

Key Features

- Intel® Atom processor E3940 (9W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 4 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 1 HDMI, 1 DP, 1 VGA or 1 eDP, Intel HD Graphic 3 independent displays
- 12V DC Input and ATX Power Source
- 1 M.2 M-key with SATA

A2SAV-2C-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 4 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 1 HDMI, 1 DP, 1 VGA or 1 eDP, Intel HD Graphic 3 independent displays
- 12V DC Input and ATX Power Source
- 1 M.2 M-key with SATA

A2SAV

Key Features

- Intel® Atom processor E3940 (9W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), 1 Mini-PCIe (mSATA support) and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 7 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 12V DC Input and ATX Power Source
- 1 HDMI, 1 DP, 1 VGA, Intel HD Graphic 3 independent displays
- 4 SATA 3.0 (RAID 0, 1, 10)
- 1 M.2 M-key with SATA

A2SAP-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E, 1 SATA 3.0
- Dual Gigabit Ethernet LAN ports via Intel® i210AT
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Supports 12V DC power input

A2SAP-H

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Dual LAN with Intel® Ethernet Controller I210-IT
- Extension I/O (1 DP/HDMI, 2 PCI-E x1, 2 USB2.0, LPC, SATA, SMBus, Power)
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature suppot from -30°C to 75°C
- Supports 12V DC power input

A2SAP-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature suppot from -30°C to 75°C
- Supports 12V DC power input

A2SAN-LN4-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Quad LAN with Intel® Ethernet Controller I210-IT
- 2 USB 3.0 ports, 2 USB 2.0 ports, 1 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 3 M.2 B-Key 2242/3042 with nano SIM slot, 1 M.2 E-Key 2230
- Supports 12V DC power input

A2SAN-LN4-C

Key Features

- Intel® Celeron® Processor J3455 (10W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Quad LAN with Intel® Ethernet Controller I211-AT
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports, 2 USB 2.0 ports, 1 SATA 3.0, SMBus
- 3 M.2 B-Key 2242/3042 with nano SIM slot, 1 M.2 E-Key 2230
- Supports 12V DC power input

A2SAN-L-WOHS

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature suppot from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature suppot from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-H-WOHS

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB3.0, 4 USB2.0, 6 COM ports, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-H

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-E-WOHS

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input