

CSE-LB16AC2-R504W

Key Features

- Optimized for WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 10 x 2.5"(tool-less) hot-swap SAS3/SATA drive bay
- SAS or enterprise SATA HDD only recommended
- 1U SAS/SATA Backplane with SES2 support
- 1U 500W Redundant power supply Platinum level, 24Pin output
- 2x full-height & full-length expansion slot(s) 1x low-profile expansion slot
- 3 x 40x56mm counter-rotation PWM fan(s)
- Support Service Tag for system information
- OEM Only, MOQ Applies

CSE-LB16AC10-R860AW

Key Features

- 1U Optimized for CloudDC motherboard with S-AIOM support, support MB size up to 12.3" x 13.4"
- 10 x 2.5"(tool-less) hot-swap SAS3/SATA drive bay
- SAS or enterprise SATA HDD only recommended
- 1U 10-Slot SFF Backplane Supports SAS3/SATA3/NVMe
- 1U 860W Redundant power supply Platinum level, 24Pin output
- 2x full-height & full-length expansion slot(s) 2x AIOM expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s) by default, 2 x as optional
- Support Service Tag for system information

CSE-LB13AC2-R860AW

Key Features

- 1U Optimized for CloudDC motherboard with S-AIOM support, support MB size up to 12.3" x 13.4"
- 8 x 2.5"(tool-less) hot-swap SAS3/SATA drive bay
- SAS or enterprise SATA HDD only recommended
- 1U SAS/SATA Backplane with SES2 support
- 1U 860W Redundant power supply Platinum level, 24Pin output
- 2x full-height & full-length expansion slot(s) 2x S-AIOM expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s) by default, 2 x as optional
- Support optional 1x Slim SATA DVD or 1x 2.5" HDD with DVD dummy tray kit
- Support Service Tag for system information

CSE-LA15TQC-R860AW

Key Features

- 1U Optimized for CloudDC motherboard with S-AIOM support, support MB size up to 12.3" x 13.4"
- 4 x 3.5"(tool-less) or 2.5"(screw) hot-swap SAS3/SATA drive bay
- SAS or enterprise SATA HDD only recommended
- 1U SAS/SATA Backplane with SES2 support
- 1U 860W Redundant power supply Platinum level, 24Pin output
- 2x full-height & full-length expansion slot(s) 2x S-AIOM expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s) by default, 2x as optional
- Support Service Tag for system information

CSE-LA15TQC-R504W

Key Features

- Optimized for WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 4 x 3.5"(tool-less) or 2.5"(screw) hot-swap SAS3/SATA drive bay
- SAS or enterprise SATA HDD only recommended
- 1U SAS/SATA Backplane with SES2 support
- 1U 500W Redundant power supply Platinum level, 24Pin output
- 2x full-height & full-length expansion slot(s) 1x low-profile expansion slot
- 3 x 40x56mm counter-rotation PWM fan(s)
- Support Service Tag for system information
- OEM Only, MOQ Applies

CSE-815TQC4-R504WB3

Key Features

- 1U Chassis, Support proprietary WIO MB size 8"x13" and up to 12.3"x13"
- 4 x 3.5" hot-swap SAS3/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 4-port 1U SAS3 12Gbps Hybrid backplane, support up to 4x 3.5-inch SAS3/SATA3/NVMe Storage Devices
- 1U 500W/600W redundant single output 80PLUS Platinum
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-815TQC4-605WB2

Key Features

- 1U chassis, Support WIO/Proprietary motherboard size up to 12.3" x 13"
- 4 x 3.5" hot-swap SAS3/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 4-port 1U SAS3 12Gbps Hybrid backplane, support up to 4x 3.5-inch SAS3/SATA3/NVMe Storage Devices
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling



815TQC-R706WB2

Key Features

- Optimized for X11 WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-R706WB

Key Features

- Optimized for WIO (W series) motherboards
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-R706CB

Key Features

- 1U Chassis for motherboard support size: (12" x 13")
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 1 full-height & full-length expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-R504WB2

Key Features

- Optimized for X11 WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 500W Redundant Single Output power supply W/PMbus 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 3 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-R504WB

Key Features

- Optimized for WIO (W series) motherboards
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 500W Redundant Single Output power supply W/PMbus 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 3 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-R504CB

Key Features

- 1U Chassis for motherboard support size: (12" x 13")
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 500W Redundant Single Output power supply W/PMbus 54.5mm width
- 1 full-height & full-length expansion slot(s)
- 3 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-605WB

Key Features

- 1U chassis, support Proprietary motherboard size 12.3" x 13", Proprietary 8.15" x 13.05"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQC-605CB

Key Features

- 1U Chassis for motherboard support size: (13.68" x 13")
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 1 full-height & full-length expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-815TQ-R706WB

Key Features

- 700W/750W redundant Platinum Level (PWS-706) or Gold level (PWS-704) high-efficiency power supplies
- 4x 3.5" Hot-swap SAS/ SATA Drive Bays
- 1x Slim DVD-ROM Drive (optional)
- 4x 4cm Counter-rotating PWM fans
- 2x Full-height I/O Expansion slots &
1x Low-profile I/O Expansion slot
- Power Switch, Reset, UID Button & 5 LED Indicators
- Optimize for WIO (W series) MB
- Full SES2 support is available with SAS motherboards and other compatible components

CSE-815TQ-R654CB

Key Features

- 1U chassis support for motherboard size ATX 12" x 10", E-ATX 12" x 13"
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 650W -48VDC input Redundant power supply, 54.5mm width
- 1 full-height & full-length expansion slot(s) (Riser Card Required)
- 4 x 4cm heavy duty counter-rotating with optimal fan(s) speed control

CSE-815TQ-R500WB

Key Features

- 1U chassis, Optimized for WIO (W series) motherboards, Support max. motherboard size: E-ATX 12" x 13"
- 1x Full-height & Full-length, 1x Full-height & Half-length, 1x Low-profile expansion slot(s)
- 4x 3.5" Hot-swap SAS/SATA Drive Bays
- 1x Slim DVD-ROM Drive (optional)
- Power Switch, Reset, UID Button & LED Indicators
- 3x 4cm Counter-rotating PWM Fans
- 500W Redundant High-efficiency Platinum Level(94%+)Power Supply

CSE-815TQ-R500CB

Key Features

- 1U chassis support for motherboard size ATX 12" x 10", E-ATX 12" x 13"
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 500W Redundant Single Output power supply W/PMBus 54.5mm width
- 1 full-height & full-length expansion slot(s) (Riser Card Required)
- 3 x 4cm counter-rotating PWM fan(s)
Optional 2 x fan for PCI card cooling

CSE-815TQ-600WB

Key Features

- 1U Chassis support for max. motherboard size E-ATX 13.68" x 13" - optimized for WIO motherboard
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 2 full height expansion slot(s) (Riser Card Required), 1 low-profile expansion slot(s) (Riser Card Required)
- 4 x 4cm heavy duty counter-rotating with optimal fan(s) speed control
Optional 2 x fans for AOC cooling

CSE-815TQ-600CB

Key Features

- 1U chassis support for motherboard size 13.68" x 13" and ATX 12" x 10", E-ATX 12" x 13"
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 1 full-height & full-length expansion slot(s) (Riser Card Required)
- 4 x 4cm heavy duty counter-rotating with optimal fan(s) speed control
Optional 2 x fan for PCI card cooling

CSE-815BTQC-R860W

Key Features

- Optimized for X13 WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U Redundant 860W Single Output Power Supply Platinum level, 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-813MTQ-600CB

Key Features

- 1U chassis supports for maximum motherboard sizes - ATX 12" x 10" and Micro-ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 600/680W Multi-output 80PLUS gold power supply, 24pin output
- 1 full-height & half-length expansion slot(s) (Riser Card Required)
- 4 x 4cm high performance PWM fan(s)
Optional 1 x fan for PCI card cooling

 813MFTQC-R407CB

Key Features

- 1U chassis, support motherboard size ATX 12" x 10" and Micro ATX 9.6" x 9.6".
- 4 x 3.5" hot-swap SAS/SATA
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)

CSE-813MFTQC-505CB

Key Features

- 1U Chassis for motherboard support size: (12" x 10") (9.6" x 9.6")
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 500W Multi-output power supply w/ PMbus, 80Plus Platinum
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x 40x28mm PWM fan(s)

CSE-813MFTQC-350CB2

Key Features

- 1U Chassis for motherboard support size: (12" x 10") (9.6" x 9.6")
- 4 x 3.5" hot-swap SAS/SATA
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 350W Multi-output power supply Platinum level
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x 40x28mm PWM fan(s)

CSE-813MFTQC-350CB

Key Features

- 1U Chassis for motherboard support size: (12" x 10") (9.6" x 9.6")
- 4 x 3.5" hot-swap SAS/SATA
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 350W Multi-output power supply Platinum level
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x 40x28mm PWM fan(s)

CSE-813MFTQ-R606CB

Key Features

- 1U chassis, support motherboard sizes: ATX 12" x 10" and Micro ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 4-port 1U TQ backplane (W/ enclosure management), support up to 4x 3.5-inch SAS/SATA HDD
- 1U 600W Redundant Single Output Power Supply w/PMBus, short depth, W54.5xL220xH40
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-813MF2TQC4-R407CB

Key Features

- 1U chassis, support motherboard sizes: ATX 12" x 10" and Micro ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS3/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 4-port 1U SAS3 12Gbps Hybrid backplane, support up to 4x 3.5-inch SAS3/SATA3/NVMe Storage Devices
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-813MF2TQC-R804CB

Key Features

- 1U chassis, support motherboard sizes: ATX 12" x 10" and Micro ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS/SATA
SAS or enterprise SATA HDD only recommended
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 800W 1U redundant power supply
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-813MF2TQC-R407RCB

Key Features

- 1U chassis, support motherboard sizes: Proprietary Micro ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS3/SATA drive bay
SAS or enterprise SATA HDD only recommended
- Support up to 4x3.5"SAS3/SATA Storage Devices
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 1 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-813MF2TQC-505CB

Key Features

- 1U Chassis for motherboard support size: (12" x 10") (9.6" x 9.6")
- 4 x 3.5" hot-swap SAS/SATA drive bay with SES2
- 1U 4-Port 12Gbps Backplane Support 4x3.5
- 1U 500W Multi-output power supply w/ PMbus, 80Plus Platinum
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x 40x28mm PWM fan(s)

CSE-813MF2TQC-350RCB

Key Features

- 1U chassis, support motherboard sizes: Proprietary Micro ATX 9.6" x 9.6"
- 4 x 3.5" hot-swap SAS3/SATA drive bay
SAS or enterprise SATA HDD only recommended
- Support up to 4x3.5"SAS3/SATA Storage Devices
- 1U 350W Multi-output power supply Platinum level
- 1 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-515M-R804

Key Features

- Front I/O short depth resource optimized chassis
- Support Proprietary WIO MB size up to 8"x10"
- 800W Redundant AC power supplies Platinum Level Certified
- 2x 2.5" Internal Drive Bays
- Up to 2x Full-height AOC expansion slot
- Up to 5x 40x56mm high-efficiency fans, hot-swappable
- Support Service Tag for system information

CSE-515M-R601

Key Features

- Front I/O short depth resource optimized chassis
- Support Proprietary WIO MB size up to 8"x10"
- 600W Redundant DC power supplies Platinum Level Certified
- 2x 2.5" Internal Drive Bays
- Up to 2x Full-height AOC expansion slot
- Up to 5x 40x56mm high-efficiency fans, hot-swappable
- Support Service Tag for system information

CSE-515B-R601W

Key Features

- Short depth front I/O with front redundant power supply resource optimized chassis, chassis length 16.9 inches
- Support WIO MB, max MB size 12.3" x 13" and Proprietary MB 8" x 13"
- 1U 600W Redundant power supply DC48V input with PMBUS
- 2x 2.5" Internal Drive Bays
- 2x Full-height and 1x Low-profile AOC expansion slot
- 4x 40x40x56mm high-efficiency fans
(2x more optional; 6x fans maximum)

CSE-515-R407

Key Features

- Support STD and WIO MB size up to 12"x13"
- Up to 2 x 2.5" fixed with bracket
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- Up to , 2 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-515-505

Key Features

- Support STD and WIO MB size up 12"x13"
- Optional Up to 4 x 2.5" fixed with bracket, Up to 1 x 3.5" fixed drive bay
SAS or enterprise SATA HDD only recommended
- 1U 500W Multi-output power supply w/ PMbus, 80Plus Platinum
- Up to , 2 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-515-350

Key Features

- Support STD and WIO MB size up to 12"x13"
- Optional Up to 4 x 2.5" fixed with bracket, Up to 1 x 3.5" fixed drive bay
- 1U 350W Multi-output power supply Platinum level
- Up to , 2 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-514-R407W

Key Features

- Support WIO MB, max MB size 12.3" x 13" and Proprietary MB 8" x 13"
- Up to 2 x 2.5" fixed with bracket
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 2 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-514-R407C

Key Features

- Support STD MB, size up to E. ATX 12" x 13".
- 2 x 2.5" fixed with bracket
SAS or enterprise SATA HDD only recommended
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 1 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-514-505

Key Features

- Support STD and WIO MB, size up to 12" x 13"
- Optional Up to 4 x 2.5" fixed with bracket, Up to 1 x 3.5" fixed drive bay
- 1U 500W Multi-output power supply w/ PMbus, 80Plus Platinum
- Up to , 2 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-514-407C-1P

Key Features

- Support STD MB
- Up to 2 x 2.5" fixed with bracket
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- Up to , 1 full height expansion slot(s)
- 4 x 40x56mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-502L-200B

Key Features

- Mini 1U Chassis, Optimized for Intel Atom Platforms
- 200W Low Noise Power Supply
- 1x 3.5" Internal Drive Bay
- OR 2x 2.5" Internal Drive Bay (Optional)
- OR 1x Full-height, Half-length PCI Expansion Slot (Optional)
- OR 1x 2.5" Internal Drive & 1x FH, HL PCI (optional)
- Power Switch, Reset Button & 5 LED Indicators

CSE-116BAC10-R860W

Key Features

- Optimized for X13 WIO (W series) motherboards, support MB size up to 12.3" x 13.4"
- 10 x 2.5" hot-swap SAS3/SATA drive bay
- 10-port 1U SAS3 12Gbps Hybrid backplane, support up to 10x 2.5-inch NVMe storage devices, 4 of them are SAS3/SATA3 drives compatible.
- 1U Redundant 860W Single Output Power Supply Platinum level, 54.5mm width
- 2 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)

CSE-116AC2-R706WB2

Key Features

- 1U chassis for motherboard support size of E-ATX 12"x13", 13.38"x 13.4".
Optimized for X11 WIO (W series) motherboards
- 10 x 2.5" hot-swap SAS/SATA drive bay
- 10-port 1U SAS3 12Gbps Hybrid backplane, support up to 8x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-116AC2-R706WB

Key Features

- 1U chassis for motherboard support size of E-ATX 12"x13", 13.38"x 13.4".
Optimized for WIO (W series) motherboards
- 10 x 2.5" hot-swap SAS/SATA drive bay
- 10-port 1U SAS3 12Gbps Hybrid backplane, support up to 8x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full-height & full-length expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-116AC10-R860CB-N10

Key Features

- 23.5" Depth 1U Rackmount Chassis - supports for maximum motherboard sizes of 12" x 13"
- 10 x 2.5" NVMe/SAS hybrid drive bay
SAS or enterprise SATA HDD only recommended
- 1U 10-Slot SFF Hybrid Backplane Supports 10xSAS3/SATA3/NVMe4 Storage Devices with 1x(2x4) + 2x(1x4) + 1x(2x2) Power Connectors
- 800W/860W 1U redundant power supply
- 1 full-height & full-length expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-116AC10-R706WB3

Key Features

- 1U Chassis, Support proprietary WIO MB size 8"x13" and up to 12.3"x13"
- 10 x 2.5" hot-swap SAS3/SATA drive bay
- 10-port 1U SAS3 12Gbps Hybrid backplane, support up to 10x 2.5-inch NVMe storage devices, 4 of them are SAS3/SATA3 drives compatible.
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113TQ-R500CB

Key Features

- 1U rackmount chassis, support for motherboard size: 12" x 13" E-ATX
- 8 x 2.5" hot-swap SAS/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U TQ (W/ AMI 9072) backplane, support up to 8x 2.5-inch SAS/SATA HDD/SSD
- 1U 500W Redundant Single Output power supply W/PMbus 54.5mm width
- 1 full-height & full-length expansion slot(s) (Riser Card Required)
- 3 x 4cm counter-rotating PWM fan(s)
Optional 3 x fan for PCI card cooling

CSE-113TQ-600WB

Key Features

- 1U rackmount chassis, support for motherboard size: 12" x 13" E-ATX and 13.68" x 13"
- 8 x 2.5" hot-swap SAS/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U TQ (W/ AMI 9072) backplane, support up to 8x 2.5-inch SAS/SATA HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 2 full height expansion slot(s) (Riser Card Required), 1 low-profile expansion slot(s) (Riser Card Required)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fan for PCI card cooling

CSE-113TQ-600CB

Key Features

- 1U rackmount chassis, support for motherboard size: 12" x 13" E-ATX and 13.68" x 13"
- 8 x 2.5" hot-swap SAS/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U TQ (W/ AMI 9072) backplane, support up to 8x 2.5-inch SAS/SATA HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 1 full-height & full-length expansion slot(s) (Riser Card Required)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fan for PCI card cooling

CSE-113MTQ-600CB

Key Features

- 1U Rackmount Chassis, supports maximum motherboard sizes: 13.68" x 10.5"
- 8 x 2.5" hot-swap SAS/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U TQ (W/ AMI 9072) backplane, support up to 8x 2.5-inch SAS/SATA HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113MFAC2-R804CB

Key Features

- 1U Chassis, support motherboard size: ATX 12" x 10"
- 8 x 2.5" hot-swap SAS/SATA drive bay
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 800W 1U redundant power supply
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113MFAC2-R606CB

Key Features

- 1U Chassis, support motherboard size: ATX 12" x 10"
- 8 x 2.5" hot-swap SAS/SATA drive bay
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U 600W Redundant Single Output Power Supply w/PMBus, short depth, W54.5xL220xH40
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113MFAC2-R407RCB

Key Features

- 1U Chassis, support motherboard size: Proprietary Micro ATX 9.6" x 9.6"
- 8 x 2.5" hot-swap SAS/SATA drive bay
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U 400W Redundant Power Supply Platinum with PMBUS, W54.5xL220xH40mm
- 1 full height expansion slot(s) , 1 low-profile expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113MFAC2-605CB

Key Features

- •1U Chassis for motherboard support size: ATX 12" x 10"
- 8 x 2.5" hot-swap SAS/SATA drive bay
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 1 full height expansion slot(s)
- 4 x 40x28mm PWM fan(s)
Optional 2 x fans for AOC cooling

CSE-113AC2-R706WB2

Key Features

- 1U rackmount chassis, support for motherboard size: 12" x 13" E-ATX
Optimized for X11 WIO (W series) motherboards
- 8 x 2.5" hot-swap SAS/SATA drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U Redundant 700/750W Single Output Power Supply Platinum level, 54.5mm width
- 2 full height expansion slot(s) (Riser Card Required), 1 low-profile expansion slot(s) (Riser Card Required)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fan for PCI card cooling

CSE-113AC2-605WB

Key Features

- 1U rackmount chassis, support for motherboard size: 12" x 13" E-ATX and 13.68" x 13"
- 8 x 2.5" hot-swap SAS3/SATA3 (2 NVMe Ports) drive bay
SAS or enterprise SATA HDD only recommended
- 8-port 1U SAS3 12Gbps Hybrid backplane, support up to 6x 2.5-inch SAS3/SATA3 HDD/SSD and 2x SAS3/SATA3/NVMe Storage Devices
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 2 full height expansion slot(s) (Riser Card Required), 1 low-profile expansion slot(s) (Riser Card Required)
- 4 x 40x56mm counter-rotation PWM fan(s)
Optional 2 x fan for PCI card cooling

CSE-LA26E1C4-R609LP

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68".
Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12x 3.5" (tool-less) or 2.5" (screw) hot-swap SAS3/SATA drive bay with SES3
Optional rear 2x 2.5" hot-swap drive bay kit
- 12-port 2U SAS3 12Gbps single-expander backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
- 600W / 650W 1U Redundant Power Supply
- 7x low-profile expansion slot(s)
- 3x 8cm high-performance PWM fan(s)
- Support service tag for system information
- OEM Only, MOQ Applies

CSE-LA26AC12-R920LP1

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12x 3.5" (tool-less) or 2.5" (screw) hot-swap SAS3/SATA drive bay with SES3
Optional rear 2x 2.5" hot-swap drive bay kit
- 12-port LFF Backplane Supports 12 x SAS3/SATA3/NVMe4 Storage Device
- 920W 1U Redundant Power Supply
- 7x low-profile expansion slot(s)
- 3x 8cm high-performance PWM fan(s)
- Support service tag for system information
- Comes with standard 2U package with 2-layer carton and SMC logo

CSE-LA26AC12-R1K23AW

Key Features

- 2U chassis support Proprietary MBD X12DDW
- 12x 3.5" (tool-less) or 2.5" (screw) hot-swap SAS3/SATA drive bay with SES3
Optional rear 2x 2.5" hot-swap drive bay kit
- Supports 12 x SAS3/SATA3/NVMe4 Storage Device
- Support 1200W Titanium Redundant Power Supply
- Support 6x FH and 2x SIOM expansion slot(s)
- 3x 8cm high-performance PWM fan(s)
- Support service tag for system information

CSE-LA26AC12-R1K03LP1

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12x 3.5" (tool-less) or 2.5" (screw) hot-swap SAS3/SATA drive bay with SES3
Optional rear 2x 2.5" hot-swap drive bay kit
- 12-port LFF Backplane Supports 12 x SAS3/SATA3/NVMe4 Storage Device
- 1000W 1U Redundant Power Supply
- 7x low-profile expansion slot(s)
- 3x 8cm high-performance PWM fan(s)
- Support service tag for system information
- Comes with standard 2U package with 2-layer carton and SMC logo

CSE-LA25TQC-R609LP

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 8x 3.5"(tool-less) or 2.5"(screw) hot-swap SAS3/SATA drive bay
Optional 2x 3.5" fixed drive bay,
Optional rear 2x 2.5" hot-swap drive bay kit
- 2U 8-Slot 12G Backplane for 8x 3.5" SAS3/SATA HDD/SSD
- 600W / 650W 1U Redundant Power Supply
- 7 low-profile expansion slot(s)
- 3x 80mm heavy duty fan(s) with PWM fan(s) speed control
- Support Service Tag for system information.
- OEM Only, MOQ Applies

CSE-829HE1C4-R1K62LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13.4", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 16 x 3.5" hot-swap SAS3/SATA drive bay, optional 2 x 2.5" hot-swap SAS3/SATA drive bay
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices,HF,RoHS/REACH
4-port internal SAS3 12Gbps backplane, support up to 4x 3.5-inch SAS3/SATA3 HDD/SSD
- 7 low-profile expansion slot(s)
- 4 x 80x38mm hot-swap cooling fan(s)

CSE-829HE1C4-R1K02LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13.4", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 16 x 3.5" hot-swap SAS3/SATA drive bay, optional 2 x 2.5" hot-swap SAS/SATA drive bay
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices,HF,RoHS/REACH 4-port internal SAS3 12Gbps backplane, support up to 4x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800/1000W Redundant Single Output Power Supply Titanium Level, CRPS 203mm length
- 7 low-profile expansion slot(s)
- 4 x 80x38mm hot-swap cooling fan(s)

CSE-829HAC12-R1K62LPB

Key Features

- 12x NVMe/ SAS3 Hybrid Drive Bays Provide Ultimate Flexibility
- Additional 4x 3.5" Hot-swap SAS3/ SATA3 HDD Bays with Rear 2x 2.5" SAS3/SATA3 HDD option
- Enhanced cooling design w/ 4x 8cm 13.5K RPM high-performance fans
- Redundant 1600W Titanium Level (96%+) high-efficiency supplies
- Optional cable management arm for hot-swap access
- 7x Low-profile, Half-length I/O expansion slots

CSE-829BTQ-R920WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 16.5" motherboards
- 10 x 3.5" hot-swap SAS/SATA
- 10-port 2U CSE-829 TQ (W/ AMI 9072 SGPIO support) backplane, support up to 10x 3.5-inch SAS/SATA HDD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMBus
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 4 x 80mm 9500 RPM fan(s)
Optional 3 x fans for 100% cooling redundancy

CSE-826SE1C-R1K02JBOD2

Key Features

- Simply Double High Density JBOD Storage Enclosure
- Extreme High Density Storage Chassis support 24x (12 front + 12 middle) 3.5" SAS/SATA 12Gb/s Hot-Swap Bays
- Single Expander Backplane Boards support SAS/SATA HDDs with 12Gb/s throughput
- 4x Mini-SAS HD ports for Internal/External Cascading
- 1000W (1+1) Redundant High-efficiency Titanium Level power supplies with PMBus
- Optimize cooling with 4x 8cm Hot-Swap fans
- JBOD Power Control Board with IPMI for remote monitor and power on-off; Internal Connection Cables Included
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-826BE2C-R920WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68". Support up to 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps dual-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 920W Redundant Platinum Super Quiet power supply W/PMBus
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BE2C-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3
- 12-port 2U SAS3 12Gbps dual-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BE2C-R802JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 800W (1+1) 96% efficient Titanium level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-826BE2C-R609JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-826BE1C4-R1K23WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68". Support up to 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices, HF, RoHS/REACH
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-826BE1C4-R1K23LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices,HF,RoHS/REACH
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BE1C-R920WB

Key Features

- 2U chassis - supports for maximum motherboard sizes: 13.68" x 13"; E-ATX 12" x 13", ATX 12" x 10". Support up to 12" x 13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps single-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- WIO Slots (4x Full-height, Full-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BE1C-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps single-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BE1C-R802JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 or SATA3 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 800W (1+1) 96% efficient Titanium level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-826BE1C-R609JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 12 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 or SATA3 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-826BAC4-R920WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68".
Support up to 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD
- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-826BAC4-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68".
Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD
- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-826BAC4-R1K23WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68".
Support up to 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD
- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-826BAC4-R1K23LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
8x SAS3 12Gbps and 4x Hybrid (NVMe/SAS3) 3.5" HDD
- 12-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-826BAC12-R802LPB

Key Features

- 800W high-efficiency AC-DC Redundant power supplies
- Direct attached Storage Rackmount chassis
- Support 12x SAS3/SATA3/NVMe4 storage devices
- 3 high-performance fans with adjustable air shroud

CSE-826BAC12-R1K23LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68" with rear 2.5" HDD option installed
- 12 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
12x SAS3/SATA3/NVMe4 storage devices
- 2U 12-Slot LFF Backplane Supports 12 x SAS3/SATA3/NVMe4 Storage Devices with 1x(2x4) + 4x(1x4) power connectors, co-lay with BPN-SAS3-LA26A-N12,HF,RoHS
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-826BA-R920WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards; max. motherboard size - 12" x 13", 13" x 13.68". Support up to 12"x13" MB with rear 2.5" HDD option installed.
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES2 and Mini-i-Pass (SFF 8087) connectivity
- 12-port 2U SAS 6Gbps direct-attached backplane, support up to 12x 3.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm fan cooling module for 826B/216B

CSE-826BA-R920LPB

Key Features

- 2U chassis - supports for maximum motherboard sizes: 13.68" x 13"; E-ATX 12" x 13", ATX 12" x 10". Supports up to 12" x 13" MB with rear 2.5" HDD option installed.
- 12 x 3.5" hot-swap SAS/SATA drive bay with SES2 and Mini-i-Pass (SFF 8087) connectivity
- 12-port 2U SAS 6Gbps direct-attached backplane, support up to 12x 3.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5x 6cm hot-swap cooling fans

CSE-825TQC-R802WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 13" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 3 x 80mm Hot-swap PWM Fans

CSE-825TQC-R802LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium
- 7 low-profile expansion slot(s)
- 3 x 80mm Hot-swap PWM Fans

CSE-825TQC-R1K03WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 13" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 3 x 80mm heavy duty fan(s) with PWM fan(s) speed control

CSE-825TQC-R1K03LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 80mm heavy duty fan(s) with PWM fan(s) speed control

CSE-825TQC-600WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 13" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-825TQC-600LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, 2 x 3.5" fixed drive bay
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 7 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-825TQ-600WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 13" motherboards
- 8 x 3.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards, 2 x 3.5" fixed drive bay
- 8-port 2U TQ (W/ AMI 9072) backplane, support up to 8x 3.5-inch SAS/SATA HDD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-825TQ-600LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards, 2 x 3.5" fixed drive bay
- 8-port 2U TQ (W/ AMI 9072) backplane, support up to 8x 3.5-inch SAS/SATA HDD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 7 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-825TQ-563LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards, 2 x 3.5" fixed drive bay
- 8-port 2U TQ (W/ AMI 9072) backplane, support up to 8x 3.5-inch SAS/SATA HDD
- 1U 560W/600W Multi-output power supply Gold level, 24Pin output
- 7 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-825MBTQC-R802WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO, 12.8" x 13.4" motherboards
- 3 x 3.5" hot-swap SAS/SATA drive bay with SGPIO, optional 2 x 2.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards
- 3-port SC825M SAS3 12Gbps TQ backplane, support up to 3x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMBus, Titanium
- 4 full height expansion slot(s) (Riser Card Required), 3 low-profile expansion slot(s) (Riser Card Required)
- 4 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control
Optional 1 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control

CSE-825MBTQC-R802LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - EE-ATX 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 3 x 3.5" hot-swap SAS/SATA drive bay with SGPIO, optional 2 x 2.5" hot-swap SAS/SATA drive bay w/ full SES-II support on SAS motherboards
- 3-port SC825M SAS3 12Gbps TQ backplane, support up to 3x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMBus, Titanium
- 7 low-profile expansion slot(s)
- 4 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control
Optional 1 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control

CSE-825BTQC-R609WB

Key Features

- SAS3(12 Gbps) HDD support
- 8x 3.5" Hot-swap SAS3/ SATA Drive Bays & 2x Fixed 3.5" Drive Bays & optional 2x rear 2.5" HDD kit available
- 600W Redundant Power Supplies Platinum Level (94%)
- Adjustable Air Shroud with Enhanced cooling design
- 4x FH and 3x LP Slots for PCI expansion
- Power button, Power switch & 6 LED Indicators

CSE-825BTQC-R1K23LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 3.5" hot-swap SAS3/SATA drive bay, optional 2 x 3.5" fixed drive bay, optional 2 x 2.5" hot-swap HDD bay for server chassis
- 8-port 2U SAS3 12Gbps TQ backplane, support up to 8x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 80mm heavy duty fan(s) with PWM fan(s) speed control

CSE-825B2TQC-R920W

Key Features

- Optimized for X13 WIO (W series) motherboards
- 8x 3.5" Hot-swap SAS3 / SATA Drive Bays & 2x Fixed 3.5" Drive Bays & optional 2x rear 2.5" HDD kit available
- SAS3 (12 Gbps) HDD support 4x Hybrid Device
- 1U Redundant 920W Single Output Power Supply Platinum Level
- 4x FH and 3x LP Slots for PCI expansion
- Power button, Power switch & 6 LED Indicators
- 3x 80mm heavy duty fan(s) with PWM fan(s) speed control

CSE-823MTQC-R802WB

Key Features

- 2U chassis - supports for maximum motherboard sizes: SMC Proprietary WIO, 12.8" x 13.4" motherboards
- 3 x 3.5" hot-swap SAS/SATA drive bay with SGPIO
- 3-port SC825M SAS3 12Gbps TQ backplane, support up to 3x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium
- 4 full height expansion slot(s) (Riser Card Required), 3 low-profile expansion slot(s) (Riser Card Required)
- 4 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control
Optional 2 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control

CSE-823MTQC-R802LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - EE-ATX 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 3 x 3.5" hot-swap SAS/SATA drive bay with SGPIO
- 3-port SC825M SAS3 12Gbps TQ backplane, support up to 3x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800W Redundant Power Supply 76mm width, W/PMbus, Titanium
- 7 low-profile expansion slot(s)
- 4 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control
Optional 2 x 4cm high-performance counter-rotating PWM fan(s) with optimal fan(s) speed control

CSE-523L-505B

Key Features

- 2U Chassis - supports for maximum motherboard sizes of 12" x 10" ATX
- 2 x 3.5" fixed drive bay, optional Up to 4 x 2.5" fixed drive bay
- 1U 500W Multi-output power supply w/ PMbus, 80Plus Platinum
- 7 low-profile expansion slot(s)
- 2 x 8cm hot-swap exhaust fan(s) & air shroud

CSE-219A-R920WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 16.5", motherboards
- 16 x 2.5" hot-swap SAS2/SATA drive bay, 1 x 5.25" drive bay
- 16-port 2U SAS 6Gbps direct-attached backplane, support up to 16x 2.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 4 full-height & full-length expansion slot(s) , 3 low-profile expansion slot(s)
- 4 x 80mm high-performance fan(s)
Optional 3 x fans for 100% cooling redundancy

CSE-216BE2C-R920WB

Key Features

- 2U Chassis for motherboard support size: (ATX 12" x 10") (E. ATX 12" x 13") (E.E. ATX 13.68" x 13")
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps dual-expander backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)

CSE-216BE2C-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68".
Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps dual-expander backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-216BE2C-R609JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 24 x 2.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-216BE1C4-R1K23LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68".
Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps single-expander backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x NVMe/SAS3/SATA3 storage devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-216BE1C-R920WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68".
Support up to 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps single-expander backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- WIO Slots (4x Full-height, Half-length + 3x Low-profile)
- 3 x 8cm high-performance PWM fan(s)

CSE-216BE1C-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps single-expander backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-216BE1C-R609JBOD

Key Features

- 2U Storage JBOD Chassis with capacity 24 x 2.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 or SATA3 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 3 x 80mm high efficient hot-swappable fans for best system cooling
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-216BAC4-R1K23LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap SAS/SATA drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps hybrid backplane, support up to 20x 2.5-inch SAS3/SATA3 HDD/SSD and 4x SAS3/SATA3/NVMe Storage Devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-216BAC-R920LPB

Key Features

- 2U chassis support max. motherboard size - ATX 12" x 10", E-ATX 12" x 13", EE-ATX 13" x 13.68". Support up to ATX 12"x13" MB with rear 2.5" HDD option installed
- 24 x 2.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
- 24-port 2U SAS3 12Gbps direct-attached backplane, support up to 24x 2.5-inch SAS3/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm 4pin high performance fan(s)

CSE-216BA-R920WB

Key Features

- 2U chassis support for SMC Proprietary WIO motherboards max. motherboard size - 12" x 13", 13" x 13.68". Support up to 12"x13" MB with rear 2.5" HDD option installed.
- 24 x 2.5" hot-swap drive bay
- 24-port 2U SAS 6Gbps direct-attached backplane, support up to 24x 2.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 4 full-height & half-length expansion slot(s) , 3 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)
Optional 5 x 6cm fan cooling module for 826B/216B

CSE-216BA-R920LPB

Key Features

- 2U chassis support for max. motherboard size - 13" x 13.68", E-ATX and ATX.
Support up to 12"x13" MB with rear 2.5" HDD option installed.
- 24 x 2.5" hot-swap SAS/SATA drive bay
- 24-port 2U SAS 6Gbps direct-attached backplane, support up to 24x 2.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 low-profile expansion slot(s)
- 3 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)
Optional 5 x 6cm fan cooling module for 826B/216B

CSE-213XAC-R1K05LP

Key Features

- 2U rackmount chassis - supports for maximum motherboard sizes: 15.2" x 13.2"
- 16 x 2.5" hot-swap SAS3/SATA drive bay
- 16-port 2U SAS3 12Gbps direct-attached backplane, support up to 16x 2.5-inch SAS3/SATA3 HDD/SSD
- 1U 800/1000W Redundant Power Supply 38mm Width
- 11 low-profile expansion slot(s)
- 4 x 8cm high-performance PWM fan(s)

CSE-213LT-600LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 8 x 2.5" hot-swap SAS/SATA drive bay, 1 x 5.25" drive bay
- 8-port 2U TQ backplane (W/O AMI9071/72 enclosure management), support up to 8x 2.5-inch SAS/SATA HDD/SSD
- 1U 600W platinum efficiency multiple output power supply w/PMBus
- 7 low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-213BAC8-R1K23WB

Key Features

- 2U chassis supports for maximum motherboard sizes - SMC Proprietary WIO , 13.68" x 13" motherboards
- 16 x 2.5" hot-swap SAS3/SATA drive bay, 1 x 5.25" drive bay, optional 2 x 2.5" hot-swap SAS/SATA drive bay
- 16-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 2.5-inch SAS3/SATA3 HDD/SSD and 8x SAS3/SATA3/NVMe Storage Devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 4x full-height & full-length expansion slot(s) and 3x low-profile expansion slot(s)
- 3 x 8cm high-performance PWM fan(s)

CSE-213BAC8-R1K23LPB

Key Features

- 2U chassis supports for maximum motherboard sizes - 13.68" x 13", E-ATX 12" x 13", ATX 12" x 10" motherboards
- 16 x 2.5" hot-swap SAS3/SATA drive bay, 1 x 5.25" drive bay, optional 2 x 2.5" hot-swap SAS3/SATA drive bay
- 16-port 2U SAS3 12Gbps hybrid backplane, support up to 8x 2.5-inch SAS3/SATA3 HDD/SSD and 8x SAS3/SATA3/NVMe Storage Devices
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7x Low profile I/O Expansion Slot
- 3 x 8cm high-performance PWM fan(s)

CSE-836BE2C-R609JBOD

Key Features

- 3U Storage JBOD Chassis with capacity 16 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-836BE2C-R1K03JBOD

Key Features

- 3U Storage JBOD Chassis with capacity 16 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1000W (1+1) 96% efficient Titanium level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-836BE2C-R1K03B

Key Features

- 3U chassis - supports for maximum motherboard sizes: 13.68" x 13" E-ATX and ATX
- 16 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
- 16-port 3U SAS3 12Gbps dual-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus
- 7 full-height & full-length expansion slot(s)
- 3 x 8cm hot-swap redundant PWM cooling fan(s)
2 x 8cm hot-swap exhaust fan(s) & air shroud

CSE-836BE1C-R609JBOD

Key Features

- 3U Storage JBOD Chassis with capacity 16 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-836BE1C-R1K23B

Key Features

- 3U chassis - supports for maximum motherboard sizes: 13.68" x 13" E-ATX and ATX
- 16 x 3.5" hot-swap SAS/SATA drive bay with SES2, optional 2 x 2.5" hot-swap drive bay
- 16-port 3U SAS3 12Gbps single-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 full-height & full-length expansion slot(s)
- 3 x 8cm hot-swap redundant PWM cooling fan(s)
2 x 8cm hot-swap exhaust fan(s) & air shroud

CSE-836BE1C-R1K03JBOD

Key Features

- 3U Storage JBOD Chassis with capacity 16 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1000W (1+1) 96% efficient Titanium level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-836BE1C-R1K03B

Key Features

- 3U chassis - supports for maximum motherboard sizes: 13.68" x 13" E-ATX and ATX
- 16 x 3.5" hot-swap SAS/SATA drive bay with SES2, optional 2 x 2.5" hot-swap drive bay
- 16-port 3U SAS3 12Gbps single-expander backplane, support up to 16x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 800/1000W Redundant Titanium Single Output Power Supply W/PMbus
- 7 full-height & full-length expansion slot(s)
- 3 x 8cm hot-swap redundant PWM cooling fan(s)
2 x 8cm hot-swap exhaust fan(s) & air shroud

CSE-836BA-R920B

Key Features

- Optimized chassis cooling with redundant cooling fans and adjustable air shroud
- 16x 3.5" hot-swap drive bays supporting SAS2 or SATA3 HDDs with 6Gbps throughput
- Redundant (1+1) 920W Platinum Level (94%) high efficiency power supplies
- Direct Attached SAS2 (6Gbps) backplane
- Up to 20 hot-swap drives with optional slim floppy/DVD sizes and rear 2.5" drive bays

CSE-835TQC-R802B

Key Features

- 800W Redundant High-efficiency Titanium Level Power Supplies
- 8x 3.5" Hot-swap SAS3/SATA3 drive bays, space to support 2x 5.25" Drive Bays & 1x Slim DVD
- Optional hot-swap Slim HDD/SSD drive Kit and Mobile Racks for additional storage
- 7x Full-height, Full-length Expansion Slots
- Five Fans (3 middle, 2 rear) & Adjustable Air Shroud for 100% Cooling Redundancy
- 3U 8-Port Backplane Supports 8 x 3.5" SAS3/SATA3 HDD/SSD with 2x mini SAS HD connectors

CSE-835TQC-R1K03B

Key Features

- 1000W Redundant High-efficiency Titanium Level Power Supplies
- 8x 3.5" Hot-swap SAS3/SATA3 drive bays, space to support 2x 5.25" Drive Bays & 1x Slim DVD
- Optional hot-swap Slim HDD/SSD drive Kit and Mobile Racks for additional storage
- 7x Full-height, Full-length Expansion Slots
- Five Fans (3 middle, 2 rear) & Adjustable Air Shroud for 100% Cooling Redundancy
- 3U 8-Port Backplane Supports 8 x 3.5" SAS3/SATA3 HDD/SSD with 2x mini SAS HD connectors

CSE-835TQ-R921B

Key Features

- 3U chassis support for motherboard size - E-ATX and ATX.
- 8 x 3.5" hot-swap SAS/SATA, 2 x 5.25" drive bay
- SAS833/835 BACK PANEL WITH AMI MG9072
- 1U 920W Redundant Platinum Super Quiet power supply W/PMbus
- 7 full-height & full-length expansion slot(s)
- 3 x 80mm Hot-swap PWM Fans
2 x 80mm rear hot-swap exhaust PWM fan(s)

CSE-947SE2C-R1K66JBOD

Key Features

- Dual-Path Storage Enclosure
- Support two canister controllers; 1+1 redundant for Dual-Path Enclosure
- Support 60 3.5" Top Loading SAS3 12 Gb/s Hot-Swappable HDDs
- 6x SAS3.0 IO ports (MiniSAS HD) per node
- Dedicated IPMI RJ45 management port
- Redfish OOB management protocol support
- SCSI Enclosure Services SES-4 support
- Hot-swappable Tool-less Modular Design for Easy Service and Easy Maintenance
- Redundant Platinum 1600W power supply

CSE-947SE1C-R1K66JBOD

Key Features

- Single-Path Storage Enclosure
- Support single canister controllers
- Support 60x 3.5" Top Loading SAS3 12 Gb/s Hot-Swappable HDDs
- 6x SAS3.0 IO ports (MiniSAS HD) per node
- Dedicated IPMI RJ45 management port
- Redfish OOB management protocol support
- SCSI Enclosure Services SES-4 support
- Hot-swappable Tool-less Modular Design for Easy Service and Easy Maintenance
- Redundant Platinum 1600W power supply

CSE-947SE1C-R1K63JBOD

Key Features

- Single-Path Storage Enclosure
- Support single canister controllers
- Support 60 3.5" Top Loading SAS3 12 Gb/s Hot-Swappable HDDs
- 6x SAS3.0 IO ports (MiniSAS HD) per node
- Dedicated IPMI RJ45 management port
- Redfish OOB management protocol support
- SCSI Enclosure Services SES-4 support
- Hot-swappable Tool-less Modular Design for Easy Service and Easy Maintenance
- Redundant Titanium 1600W power supply

CSE-947HE2C-R2K05JBOD

Key Features

- Dual-Path Storage Enclosure for High Availability Applications
- Support two canister controllers; 1+1 redundant for Dual-Path Enclosure
- Support 90 3.5"/2.5" Top Loading SAS3 12Gb/s Hot-Swappable HDDs
- 6x SAS3.0 IO ports (MiniSAS HD/SFF-8644) per node
- Dedicated IPMI RJ45 management port
- Redfish OOB management protocol support
- SCSI Enclosure Services SES-4 support
- Hot-swappable Tool-less Modular Design for Easy Service and Easy Maintenance
- Redundant Titanium 2000W power supply

CSE-947HE1C-R2K05JBOD

Key Features

- Single-Path Storage Enclosure
- Single canister controllers with field serviceable tray
- Support 90 3.5"/2.5" Top Loading SATA 6Gb/s / SAS3 12Gb/s Hot-Swappable HDDs
- 6x SAS3.0 IO ports (MiniSAS HD/SFF-8644)
- Dedicated IPMI RJ45 management port
- Redfish OOB management protocol support
- SCSI Enclosure Services SES-4 support
- Hot-swappable Tool-less Modular Design for Easy Service and Easy Maintenance
- Redundant Titanium 2000W power supply

CSE-946SE1C-R1K63JBOD

Key Features

- Ultra High Density and High Capacity Storage Chassis support 60 x 3.5" Top Loading SAS/SATA 12Gb/s Hot Swapping HDD/SSD Bays
- Tool-less HDD tray with HDD LED indicator
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1600W (1+1) Redundant High-efficiency Titanium Level Power Supplies
- Optimized cooling w/ 5x 80x38mm rear hot-swap fans
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-946LE1C-R1K66JBOD

Key Features

- Extreme High Density and High Capacity Storage Chassis support 45 x 3.5" Top Loading SAS/SATA 12Gb/s Hot Swapping HDD/SSD Bays
- Tool-less HDD tray with HDD LED indicator
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1600W (1+1) Redundant High-efficiency Platinum Level Power Supplies
- Optimized cooling w/ 5x 80x38mm rear hot-swap fans
- Support front LCD panel for system status & error info (Option)
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9300-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9380-8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-847E2C-R1K23JBOD

Key Features

- Double-sided High Density JBOD Storage Enclosure
- 44x (24 front + 20 rear) 3.5" hot-swap SAS drive bays supporting SAS3/2 HDDs with 12Gbps throughput
- Redundant 1200W Titanium Level (1+1) power supplies with PMBus
- 7x 8cm (middle) hot-swap redundant cooling fans
- SAS3 (12Gbps) backplane with dual expanders supports SAS3 drives for load balancing and redundancy
- JBOD Power Control Board with IPMI for remote monitor and power on-off
- 8x External mini SAS HD (SFF 8644) connectivity and IPMI RJ45 port
- Palletized packaging for easy shipping and handling
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-847E1C-R1K23JBOD

Key Features

- Double-sided High Density JBOD Storage Enclosure
- 44x (24 front + 20 rear) 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Redundant 1200W Titanium Level (1+1) power supplies with PMBus
- 7x 8cm (middle) hot-swap redundant cooling fans
- SAS3 (12Gbps) backplane with single expander supports SAS3/SATA3 drives for capacity expansion
- JBOD Power Control Board with IPMI for remote monitor and power on-off
- 4x External mini SAS HD (SFF 8644) connectivity and IPMI RJ45 port
- Palletized packaging for easy shipping and handling
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-847BE2C-R1K23WB

Key Features

- High Storage Capacity with Full Height Expansion Slot
- 4U chassis support for SMCI Proprietary WIO motherboards; max. motherboard size - 12" x 13", 13" x 13.68"
* Support up to 12"x13" MB with rear 2.5" HDD option installed
- 36 x 3.5" hot-swap drive bay, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps dual-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
24-port 4U SAS3 12Gbps dual-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- WIO Slots (4x Full-height, Full-length + 3x Low-profile)
- 7 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-847BE2C-R1K23LPB

Key Features

- 4U Chassis for motherboard support size: (12" x 10") (13.68" x 13") (9.6" x 9.6")
- 36 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps dual-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
24-port 4U SAS3 12Gbps dual-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD (secondary expander port only connects to dual-port SAS devices, single-port SATA will not have this redundancy feature)
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 7 x 80mm high-performance fan(s)

CSE-847BE1C4-R1K23LPB4

Key Features

- 4U Chassis for motherboard support size: (12" x 10") (13.68" x 13") (9.6" x 9.6")
- 36 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices,HF,RoHS/REACH
24-port 4U SAS3 12Gbps single-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 7 x 80mm high-performance fan(s)

CSE-847BE1C4-R1K23LPB

Key Features

- 4U Chassis for motherboard support size: (12" x 10") (13.68" x 13") (9.6" x 9.6")
- 36 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-Port 2U Backplane with Expander support up to 8 x 3.5" SAS3/SATA3 HDD/SDD and 4 x SAS3/SATA3/NVMe Storage Devices,HF,RoHS/REACH
24-port 4U SAS3 12Gbps single-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 7 x 80mm high-performance fan(s)

CSE-847BE1C12-R1K68LPB4

Key Features

- 36x (24 front + 12 rear) 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Optional rear 2.5" removable HDD
- Redundant 1600W Titanium Level (1+1) power supplies with PMBus
- 7x low-profile expansion slots; 7x 8cm (middle) hot-swap 13.5Krpm cooling fans and adjustable air shroud
- E1C12: Single SAS3 (12Gbps) expander plus 12 x NVMe backplane(Front:8/ Rear:4)
- Mini SAS HD (SFF 8643) connectivity on backplane
- Palletized packaging for easy shipping and handling

CSE-847BE1C-R1K23WB

Key Features

- High Storage Capacity with Full Height Expansion Slot
- 4U chassis support for SMCI Proprietary WIO motherboards; max. motherboard size - 12" x 13", 13" x 13.68"
* Support up to 12"x13" MB with rear 2.5" HDD option installed
- 36 x 3.5" hot-swap SAS/SATA drive bay with SES3, optional 2 x 2.5" hot-swap drive bay
- 12-port 2U SAS3 12Gbps single-expander backplane, support up to 12x 3.5-inch SAS3/SATA3 HDD/SSD
24-port 4U SAS3 12Gbps single-expander backplane, support up to 24x 3.5-inch SAS3/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- WIO Slots (4x Full-height, Full-length + 3x Low-profile)
- 7 x 8cm (7000 RPM) hot-swap PWM cooling fan(s)

CSE-847BA-R1K23LPB

Key Features

- 4U chassis - supports for maximum motherboard sizes: 13.68" x 13", E-ATX, ATX motherboards
- 36 x 3.5" hot-swap HDD bays for server chassis
- 12-port 2U SAS 6Gbps direct-attached backplane, support up to 12x 3.5-inch SAS2/SATA3 HDD/SSD
24-port 4U SAS 6Gbps direct-attached backplane, support up to 24x 3.5-inch SAS2/SATA3 HDD/SSD
- 1U 1200W/1000W Titanium Power Supply W/PMbus W76xL336xH40mm
- 7 low-profile expansion slot(s)
- 7 x 8cm hot-swap redundant PWM cooling fan(s)

CSE-846XE2C-R1K23B

Key Features

- 100% cooling redundancy, 24x 3.5" Hot-swap SAS3 Drive Bays
- Redundant 1200W Titanium Level high efficiency power supply & 5 hot-plug redundant cooling fans w/adjustable air shroud
- Dual SAS3 (12Gbps) expander backplane
- Mini SAS HD (SFF 8643) connectivity;
- Support up to 13 FH FL expansion slots
- High Availability PS, Storage Capacity, and numerous I/O slots

CSE-846XE1C-R1K23B

Key Features

- 100% cooling redundancy, 24x 3.5" Hot-swap SAS2/SATA3 Drive Bays
- Redundant 1200W Titanium Level high efficiency power supply & 5 hot-plug redundant cooling fans w/adjustable air shroud
- Single SAS3 (12Gbps) expander backplane
- Mini SAS HD (SFF8643) connectivity;
- Support two 1000W BBP
- Support up to 13 FH FL expansion slots
- High Availability PS, Storage Capacity, and numerous I/O slots

CSE-846XA-R1K23B

Key Features

- 100% cooling redundancy, 24x 3.5" Hot-swap SAS2/SATA3 Drive Bays w/ Direct Attached HDD backplane
- Redundant 1200W Titanium Level high efficiency power supply & 5 hot-plug redundant cooling fans w/adjustable air shroud
- Mini-i-Pass (SFF 8087) connectivity;
- Support two 1000W BBP
- Support up to 13 FH FL expansion slots
- High Availability PS, Storage Capacity, and numerous I/O slots

CSE-846BE2C-R609JBOD

Key Features

- 4U Storage JBOD Chassis with capacity 24 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High density Archive Storage Applications:
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-846BE2C-R1K23B

Key Features

- Optimized chassis cooling with redundant cooling fans and adjustable air shroud
- 24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Redundant 1200W Titanium Level power supply
- E2C: Dual SAS3 (12Gbps) expander backplane
- Mini SAS HD (SFF 8643) connectivity on backplane

CSE-846BE2C-R1K03JBOD

Key Features

- 4U Storage JBOD Chassis with capacity 24 x 3.5" hot-swappable HDDs bays
- Dual Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 8 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1000W (1+1) 96% efficient Titanium level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications:
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-846BE1C8-R1K23B4

Key Features

- Optimized chassis cooling with redundant cooling fans and adjustable air shroud
- 24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Redundant 1200W Titanium Level power supply
- E1C8: Single SAS3 (12Gbps) expander plus 8 x NVMe backplane
- Mini SAS HD (SFF 8643) connectivity on backplane
- Palletized packaging for easy shipping and handling

CSE-846BE1C-R609JBOD

Key Features

- 4U Storage JBOD Chassis with capacity 24 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 600W (1+1) 94% efficient Platinum level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-846BE1C-R1K23B

Key Features

- Optimized chassis cooling with redundant cooling fans and adjustable air shroud
- 24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Redundant 1200W Titanium Level power supply
- E1C: Single SAS3 (12Gbps) expander backplane
- Mini SAS HD (SFF 8643) connectivity on backplane

CSE-846BE1C-R1K03JBOD

Key Features

- 4U Storage JBOD Chassis with capacity 24 x 3.5" hot-swappable HDDs bays
- Single Expander Backplane Boards support SAS3/2 HDDs with 12Gb/s throughput
- 4 x Mini-SAS HD ports for Internal / External Cascading Expander Combination for high performance, high availability or high redundancy requirements
- 1x IPMI port for Remote System Power on/off and system monitoring
- Support NTP for time synchronization & RTC battery backup
- 1000W (1+1) 96% efficient Titanium level power supplies
- 5 hot-plug redundant cooling fans
- Ideal for Cloud backup, data Replication or High desnsity Archive Storage Applications
- Qualified SAS HBA / controller:
AOC-SAS3-9500-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9500-16E - 12Gb/s 4-external ports SAS3 HBA
AOC-SAS3-9580-8I8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-846BA-R920B

Key Features

- High Efficiency Power
High Storage Capacity
- 4U chassis support for max. motherboard size - 13.68" x 13" E-ATX, 12" x 10" ATX and 9.6" x 9.6" Micro-ATX
- 24 x 3.5" hot-swap drive bay
- 24-port 4U SAS 6Gbps direct-attached backplane, support up to 24x 3.5-inch SAS2/SATA3 HDD/SSD
- 1U 920W Redundant Platinum Level Power Supply
- 7 full-height & full-length expansion slot(s)
- 3 x 8cm hot-swap redundant PWM cooling fan(s)
2 x 8cm hot-swap exhaust fan(s) & air shroud

CSE-846BA-R1K23B

Key Features

- High Efficiency Power
High Storage Capacity
- High density 4U Storage Chassis
- 2.1200W Redundant Power Supplies
Titanium Level (95%)
- 24x 3.5" Hot-swap SAS Drive Bays w/ SES2 (dual-channel) and optional 2x 2.5" Hot-swap SAS Drive Bays on rear side of Chassis
- Mini-I-Pass (SFF 8087) connectivity
- 100% Cooling Redundancy
- Power Switch, Reset Switch & 6 LED Indicators

CSE-842XTQC-R862B

Key Features

- 5x 3.5" SAS3 / SATA3 Hot-swap HDD Bays
- 1x Slim DVD-ROM Drive Bay
- Dual-channel Air Duct design
- Front intake Cooling Fan and Optional
Front Bezel with Removable Air Filter

CSE-842XTQC-R804B

Key Features

- 800W Redundant Power Supplies Platinum Level (94%)
- 5x 3.5" SAS3 / SATA3 Hot-swap HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 1x Slim DVD-ROM Drive Bay
- 7x Full-height, Full-length and 4x Full-height, Half-length Expansion Slots
- Dual-channel Air Duct design
- 2x Front USB 3.0 Ports & 1x COM Port
- Front intake Cooling Fan and Optional Front Bezel with Removable Air Filter
- Power Switch, Reset Switch & 6x LED Indicators

CSE-842XTQ-R606B

Key Features

- 600W Redundant Power Supplies Platinum Level (94%)
- 5x 3.5" Hot-swap HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 1x Slim DVD-ROM Drive Bay
- 7x Full-height, Full-length and 4x Full-height, Half-length Expansion Slots
- Dual-channel Air Duct design
- 2x Front USB 2.0 Ports & 1x COM Port
- Front intake Cooling Fan and Optional Front Bezel with Removable Air Filter
- Power Switch, Reset Switch & 6x LED Indicators

CSE-842TQC-1K26B

Key Features

- 1200W Platinum Level Certified High-Efficiency Power Supply
- 5x SAS3 3.5" HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 1x Slim DVD-ROM Drive Bay
- 5.7x Full-height, Full-length Tool-less Expansion SlotsDual channel Air Duct design
- 7x Full-height, Full-length Tool-less Expansion Slots
- Dual channel Air Duct design
- 2x Front USB 3.0 Ports & 1x Com port
- Optional Front Bezel with Removable Air Filter
- Power Switch, Reset Switch & 6x LED Indicators

CSE-747BTQ-R2K04B

Key Features

- 8x 3.5" SAS/SATA Backplane for Hot-Swappable Drives (Support SES2)
- 11x Full-Height, Full-Length Expansion Slots Optimized for 4x Double Width GPU Solution
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- (2x) Rear Additional 80mm PWM Fans & (4x) Middle Lower 92mm PWM Fans
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes – E-ATX 15.2" x 13.2"/ ATX/Micro ATX
- 2000W Redundant Titanium Level Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5" Hot-Swappable HDD Drives

CSE-745BTQ-R920B

Key Features

- 8x 3.5"/2.5" SAS/SATA Backplane for Hot-Swappable Drives
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 3x Middle 8cm (6100 rpm) PWM Fans & 2x 8cm (6100 rpm) PWM Fans
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes E-ATX 13.68" x 13" ATX/Micro ATX
- 920W Redundant Platinum Level Certified High-Efficiency Class-B Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5"/2.5" Hot-Swappable HDD Drives

CSE-745BAC-R1K23B-SQ

Key Features

- 8x 3.5"/2.5" SAS/SATA Backplane for Hot-Swappable Drives
- Whisper-Quiet (<27dB)
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 2x 8cm (2800 rpm) PWM Fans & 1x 9cm (2400 rpm) PWM Fans
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes: E-ATX 13.68" x 13"/ATX/Micro ATX
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5/2.5" Hot-Swappable HDD Drives

CSE-745BAC-R1K23B

Key Features

- 8x 3.5"/ 2.5" SAS3/SATA3 Backplane for Hot-Swappable Drives
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 3x Middle 8cm (9400 rpm) PWM Fans & 2x 8cm (9400 rpm) PWM Fans
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes - E-ATX 13.68" x 13"/ATX/Micro ATX
- 1200W (1 + 1) Redundant Titanium Level Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5"/2.5" Hot-Swappable HDD Drives

CSE-743TQ-903B-SQ

Key Features

- 8x 3.5"/2.5" SAS/SATA Backplane for Hot-Swappable Drives
- Whisper-Quiet (<28dB)
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 2x 8cm PWM Fans & 1x 9cm Rear PWM Fan
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes: E-ATX 12" x 13"/ATX/Micro ATX
- 903W 80-Plus Gold Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5"/2.5" Hot-Swappable HDD Drives

CSE-743AC-668B

Key Features

- 8x 3.5" SAS3/SATA3 Backplane for Hot-Swappable Drives
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 4x Middle 8cm (5000 rpm) PWM Fan
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes – E-ATX 12" x 13"/ATX/Micro ATX
- 668W Platinum Level Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5" Hot-Swappable HDD Drives

CSE-743AC-1K26B-SQ

Key Features

- 8x 3.5"/2.5" SAS3/SATA3 Backplane for Hot-Swappable Drives
- Whisper-Quiet (<27dB)
- Front HDD Door Lock & Side Panel Intrusion Switch
- Front I/O Ports: 2x USB 3.0
- 2x 8cm PWM Fans & 1x 9cm Rear PWM Fan
- 4U / Full Tower Chassis Supports max. Motherboard, Sizes – E-ATX 12" x 13"/ATX/Micro ATX
- 1200W Platinum Level Certified High-Efficiency Power Supply
- 3x 5.25" External HDD Drive Bays & 8x 3.5"/2.5" Hot-Swappable HDD Drives

CSE-417BE1C-R1K23JBOD

Key Features

- Extremely high-density 4U storage server chassis (saves 2U space)
- Maximum drives per enclosure: 72x (48 front + 24 rear) 2.5" hot-swap HDD bays for server chassis
- SAS3 (12Gbps) single expander backplane
- 1200W Titanium Level (1+1) redundant power supplies with PMBus
- Optimized thermal solution with 100% redundant cooling design
- Qualified SAS HBA / controller:
AOC-SAS3-9300-8E - 12Gb/s 2-external ports SAS3 HBA
AOC-SAS3-9380-8E - 12Gb/s 2-external ports SAS3 RAID Controller

CSE-GS7A-2000B

Key Features

- 5U / Full Tower Chassis supports motherboard sizes – E-ATX/ATX/Micro ATX
- 8x Full-Height, Full-Length Expansion Slots
- Front I/O Ports: 2xUSB2.0 2x USB 3.0 1xType C Line out jack & Microphone jack
- PS2 2000W Multi-output PLATINUM power supply
- Kensington Lock Security
- 2x 5.25" Tool-less device installation
- Internal removable 4x3.5"HDD tool-less trays and external 2x2.5"HDD tool-less trays
- Front bezel and chassis bottom side with dust filter
- LED lighting bar
- 2x120mm PWM fans in front side 1x120mm PWM fan in rear side
- Optional side cover with glass
- Optional CPU liquid cooling module

CSE-GS5B-000R

Key Features

- Black interior paints throughout the chassis - best for DIY gamer.
- Black anodized brushed aluminum fascia front panel with two USB 3.0 ports
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives
- Tool-less 5.25" device installation with trays to support 3.5" and 2.5" drives
- Cable management holes with rubber grommets for clean builds
- Removable magnetic dust filter
- One click front grille access
- Large motherboard tray cut-out for CPU cooler back-plates
- 3x 120mm PWM fans included

CSE-GS5A-754K

Key Features

- Black anodized brushed aluminum fascia front panel with two USB 3.0 ports
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives
- Sound-dampened side panels
- Tool-less 5.25" device installation with trays to support 3.5" and 2.5" drives
- Cable management holes with rubber grommets for clean builds
- Removable magnetic dust filter
- 3x 120mm PWM fans included
- 750W 80PLUS Gold Fully-Modular Power Supply

CSE-GS50-000R

Key Features

- Black anodized brushed aluminum fascia front panel with two USB 3.0 ports
- Removable 3.5" and 2.5" HDD/SSD cages with tool-less trays for up to 10 drives
- Tool-less 5.25" device installation with trays to support 3.5" and 2.5" drives
- Cable management holes with rubber grommets for clean builds
- Removable magnetic dust filter
- One click front grille access
- Large motherboard tray cut-out for CPU cooler back-plates
- 3x 120mm PWM fans included

CSE-GS3A-1K01B

Key Features

- Mid-tower chassis supports motherboard sizes – ATX/Micro ATX
- 7x Full-Height, Full-Length Expansion Slots
- Front I/O Ports: 1xUSB3.2 GEN2X2 type-c/2xUSB 3.2 Gen1xtype-a/1xCombo audio Jack
- PS2 1000W Multi-output Power supply with full modular cable with one set 12VHPWR cable(600W)
- 2x 3.5" HDD Tool-less tray and 6 pcs 2.5"HDD mounting location
- Removable magnetic dust filter in top side of chassis
- Support CPU 360 AIO liquid cooling installation
- 3x120mm PWM fans in front side 1x120mm PWM fan in rear side
- Support GPU length max is 390mm
- Dual-opening side cover supports rear cable management

CSE-735D4-668B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Security
- Front I/O Ports: 2x USB 3.0 1xType C Line out jack & Microphone jack
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 668W Platinum Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays
- Security door for M14&M28 Mobile Racks

CSE-733TQ-668B

Key Features

- 4x 3.5" SAS/SATA Backplane for Hot-Swappable Drives (Support SGPIO)
- Front HDD Door Lock
- Front I/O Ports: 2x USB 2.0
- 1x 12cm Rear (4000 rpm) PWM Fan & 1x 9cm Front (4200 rpm) PWM Fan
- Mid-Tower Chassis Supports max. Motherboard, Sizes – E-ATX 12" x 13"/ATX/Micro ATX
- 668W Platinum Level Certified High-Efficiency Power Supply
- 2x 5.25" External HDD Drive Bays & 4x 3.5" HDD Drive Bays

CSE-732I-R600B

Key Features

- 90° Rotatable HDD Cage
- Kensington Lock Security
- Front I/O Ports: 2x USB 3.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes ⅘ E-ATX/ATX/Micro ATX
- 600W Redundant Power supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732I-668B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Security
- Front I/O Ports: 2x USB 3.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 668W Platinum Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732D4-903B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 3.0 & 2x USB 2.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 900W Gold Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732D4-668B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 3.0 & 2x USB 2.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 668W Platinum Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732D3-903B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 3.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 900W Gold Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732D3-1K26B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 3.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 1200W Platinum Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-732D2-903B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2x USB 2.0
- 1x Optional Front 12cm (1850 RPM) PWM Fan
- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes – E-ATX/ATX/Micro ATX
- 900W Gold Level Certified High-Efficiency Power Supply
- 1x Rear 12cm (1850 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-731I-404B

Key Features

- 90° Rotatable HDD Cage
- Whisper-Quiet (<25dB)
- Kensington Lock Support
- Front I/O Supports 2x USB 3.0
- 1x Optional Front Intake 8cm (2800 RPM) PWM Fan
- Mini-Tower Chassis Supports Micro-ATX Motherboard, Size 9.6" x 9.6"
- 400W Gold Level Certified High-Efficiency Power Supply
- 1x Rear 9cm (2050 RPM) PWM Fan
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays

CSE-721TQ-350B2

Key Features

- Compact Mini-Tower: D 11"x W 8.27"x H 9.45"
- Support wide range of Mini-ITX (6.75"x 6.75") motherboards
- 4 3.5" Hot-Swap SATA3/SAS2 drive bays, 2 internal 2.5" SATA drive bays, and 1 slim DVD-ROM drive bay
- 2 USB3.1 Gen1 ports(front), chassis intrusion switch, Kensington Lock supported
- 1 low-profile expansion slot for add-on cards
- 350W 80 PLUS Gold-certified High-efficiency power supply

CSE-721TQ-350B

Key Features

- Compact Mini-Tower: D 11"x W 8.27"x H 9.45"
- Support wide range of Mini-ITX (6.75"x 6.75") motherboards
- 4 3.5" Hot-Swap SATA3/SAS2 drive bays, 2 internal 2.5" SATA drive bays, and 1 slim DVD-ROM drive bay
- 2 USB2.0 ports(front), chassis intrusion switch, Kensington Lock supported
- 1 low-profile expansion slot for add-on cards
- 350W 80 PLUS Gold-certified High-efficiency power supply

CSE-513BTQC-350WB

Key Features

- 15" Mini 1U chassis support for maximum proprietary WIO motherboard size - 12" x 13" E-ATX
- 2 x Full-height & Half-length expansion slot(s)
- 2 x 2.5" hot-swap drive bay, Up to optional 4 x 2.5" fixed Internal Drive with bracket
- Power Switch, UID Button & LED Indicators
- 4 x 40mm x28mm PWM fan(s)
- 1U 350W Multi-output Power Supply Platinum Level

CSE-513BTQC-350B

Key Features

- 15" Mini 1U chassis support for maximum motherboard size - 12" x 13" E-ATX
- 1x Full-height & Half-length expansion slot(s)
- 2 x 2.5" hot-swap drive bay, optional 4 x 2.5" fixed Internal Drive with bracket
- Power Switch, UID Button & LED Indicators
- 4 x 40mm x28mm PWM fan(s)
- 1U 350W Multi-output Power Supply Platinum Level

CSE-512F-600LB

Key Features

- 14.5" Mini 1U chassis - supports for maximum motherboard sizes: ATX 12" x 10"
- 1 x 3.5" fixed drive bay
SAS or enterprise SATA HDD only recommended
- 1U 600/680W Multi-output 80PLUS gold power supply, 24pin output
- 1 full-height & half-length expansion slot(s) (Riser Card Required)
- 3 x 4cm counter-rotating PWM fan(s)

CSE-512F-600B

Key Features

- 14.5" Mini 1U chassis, supports maximum motherboard sizes: ATX 12" x 10"
- 1x Full-height & half-length expansion slot
- 1x 3.5" Fixed Internal Drive Bay
- 1x Slim DVD ROM (optional)
- 2x Front USB Ports
- Power Switch, Reset, and LED Indicators
- 3x Counter-rotating PWM Fans
- 600/680W 1U Multi-output 80PLUS Gold Level Power Supply, 24pin output

CSE-512F-350B1

Key Features

- 14.5" Mini 1U chassis, supports maximum motherboard sizes: ATX 12" x 10"
- 1x Full-height & half-length expansion slot
- 2x 3.5" Fixed Internal Drive Bay
- 1x Slim DVD ROM (optional)
- Power Switch, Reset, and LED Indicators
- 2x Counter-rotating Fans
- 350W Platinum Level High-efficiency Power Supply

CSE-512-203B

Key Features

- 14" Mini 1U chassis, supports maximum motherboard sizes: ATX 12" x 9.6"
- 1x Full-height & half-length expansion slot
- 1x 3.5" Fixed Internal Drive Bay
- 1x Slim DVD ROM (option)
- 2x Front USB Ports
- Power Switch, Reset, and LED Indicators
- 1x 10cm Blower Fan
- 200W Multi-output 80PLUS Gold Level Power Supply w/20pin output

CSE-510T-203B

Key Features

- Extra Compact Size
- 200W High-efficiency Power Supply Gold Level Certified
- Low noise level
- 2x 2.5" hot-swap SAS/SATA HDD Bays
- 1x Low-profile PCI expansion slot
- 3x 8500 RPM Cooling Fan
- Power Switch, Reset Button & 5 LED Indicators

CSE-510-203B

Key Features

- COMPACT SIZE
- 200W High-efficiency Power Supply Gold Level Certified
- 1x 3.5" Internal Drive Bay
- OR Up to 4x 2.5" Internal Drive Bays (Optional)
- OR 1x Full-height, Half-length PCI-Expansion Slot (Optional)
- OR up to 2x 2.5" (with single retention bracket) and 1x FH, HL PCI-E
- 2x 8500 RPM Cooling Fan
- Power Switch, Reset Button & 5 LED Indicators

CSE-506TQC-R301

Key Features

- Mini 1U Chassis
- 300W Redundant High-efficiency Power Supply with Gold Level Certified
- Rear I/O Ports
- Support 2x 2.5" Hotswappable HDD/SSD + 1 Low-Profile PCIe Card
- OR 1x 2.5" Internal Drive Bay + 1 Full-Height, Half-Length PCIe Card
- OR 4x 2.5" Internal Drive Bay + 1 Low-Profile PCIe Card
- OR 1x 3.5" Internal Drive Bay only when using Mini-ITX MB
- Support Intrusion Switch Feature
- Optional Thermal Sensor Feature
- 10.Power Switch, Reset Button 6x LED Indicators

CSE-505-203B

Key Features

- 9.8" depth small form factor 1U, 200W Gold level power supply
- Optimized for Mini-ITX (6.75"x 6.75") Motherboard
- Front I/O Ports
- 1x 3.5" Internal Drive Bay with 1x Half-height, Half-length PCI-E
- OR 2x 3.5" Internal Drive Bay
- OR 2x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI (need HDD bracket)
- OR 4x 2.5" Internal Drive Bay(need HDD bracket)
- Power Switch, Reset Button and 5x LED Indicators

CSE-504-203B

Key Features

- Mini 1U Chassis
- 200W High-efficiency Power Supply Gold Level Certified
- Rear I/O Ports
- 1x 3.5" Internal Drive Bay with 1x Full-height, Half-length PCI
- OR 2x 3.5" Internal Drive Bay
- OR 2x 2.5" Internal Drive Bay with 1x Full-height, Half-length PCI
- OR 4x 2.5" Internal Drive Bay
- Power Switch, Reset Button and 5x LED Indicators

CSE-503L-200B

Key Features

- Mini 1U Chassis optimized for Intel® Atom™ Platform
- 200W Low Noise Power Supply
- Front I/O Ports
- 1x 3.5" Internal Drive Bay
- OR 2x 2.5" Internal Drive Bay (opt.)
- OR 1x Full-height, Half-length PCI (opt.)
- OR 1x 2.5" Internal Drive & 1x FH, HL PCI-E
- Power Switch, Reset Button & 5 LED Indicators

CSE-M35TQB

Key Features

- 5x 3.5" Hot-swap SAS/SATA HDDs
- Fan Failure LED and Alarm
- Overheat LED
- Drive Activity & Fail LED
- 3x 5.25" Drive Bay Enclosure
- 9cm Cooling Fan

CSE-M35T-1B

Key Features

- 5x 3.5" Hot-swap SATA HDDs
- Fan Failure LED and Alarm
- Overheat LED
- Drive Activity LED
- 3x 5.25" Drive Bay Enclosure
- 9cm Cooling Fan

CSE-M28SACB-OEM

Key Features

- 8x 2.5" Hot-swap SAS3/SATA3 HDDs
- Overheat LED indication
- Drive Activity/Failure LED
- Occupy 2x 5.25" Drive Bay Enclosure
- 2x mini-SAS HD Connectors, up to 12Gbs support

CSE-M28SACB

Key Features

- 8x 2.5" Hot-swap SAS3/SATA3 HDDs
- Overheat LED indication
- Drive Activity/Failure LED
- Occupy 2x 5.25" Drive Bay Enclosure
- 2x mini-SAS HD Connectors, up to 12Gbs support
- 4cm Cooling Fan 12.5K RPM 16 CFM

CSE-M28SAB-OEM

Key Features

- 8x 2.5" Hot-swap SAS2/SATA3 HDDs
- Overheat LED indication
- Drive Activity/Failure LED
- Occupy 2x 5.25" Drive Bay Enclosure
- 2x direct attached iPass connectors, up to 6Gbs support

CSE-M28SAB

Key Features

- 8x 2.5" Hot-swap SAS2/SATA3 HDDs
- Overheat LED indication
- Drive Activity/Failure LED
- Occupy 2x 5.25" Drive Bay Enclosure
- 2x direct attached iPass connectors, up to 6Gbs support
- 4cm Cooling Fan 12.5K RPM 16 CFM

MCP-220-84610-0N

Key Features

- 12G Rear 2.5"x2 Drive Kit
- Hot-swappable SAS3/SATA3 Drives
- Drive Activity and Status(Fail) LED Support
- Tool-less HDD Trays
- SGPIO and 6G data cables are included
- Optional 12G cable CBL-SAST-0699 (internal mini SAS HD to 4 SAS/SATA) available

MCP-220-83608-0N

Key Features

- 12G Rear 2.5"x2 Drive Kit
- Hot-swappable SAS3/SATA3 Drives
- Drive Activity and Status(Fail) LED Support
- Tool-less HDD Trays
- SGPIO, Power extension Y-cable and 6G data cables are included
- Optional 12G cable CBL-SAST-0699 (internal mini SAS HD to 4 SAS/SATA) available

MCP-220-82616-0N

Key Features

- 12G Rear 2.5"x2 Drive Kit
- Hot-swappable SAS3/SATA3 Drives
- Drive Activity and Status(Fail) LED Support
- Tool-less HDD Trays
- SGPIO, Power extension Y-cable and 6G data cables are included
- Optional 12G cable CBL-SAST-0699 (internal mini SAS HD to 4 SAS/SATA) available

MCP-220-81506-0N

Key Features

- 12G 2.5" Slim DVD Size Drive Kit
- 1x 2.5" Hot-swappable SAS3/SATA3 Slim HDD (up to 9.5mm)
- Drive Activity and Status(Fail) LED Support
- SGPIO and 6G data cables are included
- Optional 12G cable CBL-SAST-0699 (internal mini SAS HD to 4 SAS/SATA) available

MCP-220-81504-0N

Key Features

- 12G 2.5" Slim Floppy Size Drive Kit
- 1x 2.5" Hot-swappable SAS3/SATA3 Slim HDD (up to 9.5mm)
- Drive Activity and Status(Fail) LED Support
- SGPIO and 6G data cables are included
- Optional 12G cable CBL-SAST-0699 (internal mini SAS HD to 4 SAS/SATA) available