

X14SPN-H

Key Features

- 2 USB3.2 type-A connectors and 4 USB2.0 headers
- Dual M.2 2242/2280 M-key slots for storage, up to PCIe Gen5x4
- Triple LAN RJ45 connectors. 2 Intel i226IT 2.5GbE with POE, and 1 Intel i219LM GbE
- Dual DDR5 5600/6400MHz SO/CSO-DIMM, up to 128GB, IB ECC
- Intel® Core™ Ultra X7 Processor 368H, up to 16 Core, 25W
- 2 COM (RS-232/422/485), Audio, 8 bits GPIO, SMBus connector and TPM2.0
- Dual M.2 expansion slots. 1 E-key, and 1 B-key with nano SIM
- Dual HDMI2.1. 1 HDMI2.1, and 1 HDMI2.1 TMDS (4K60Hz)
- One eDP1.4 and One MIPI D-PHY connector for embedded application
- 12~36V DC power input

X14SDW-72C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6776P-B, CPU TDP 325W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 1TB ECC RDIMM DDR5-6400MT/s in 8 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-64CM-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6756P-B, CPU TDP 325W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 1TB ECC RDIMM DDR5-6400MT/s in 8 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDW-42C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6726P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-40C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6716P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 SFP28 for 25GbE Ethernet with Intel SoC, 1 RJ45 for Gigabit Ethernet with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-36CE-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6556P-B, CPU TDP 215W, Intel Quick Assist Technology, Intel vRAN Accelerator, extended working temperature
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 25GbE SFP28 with Intel SoC 1 GbE RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0
- IEEE1588 v2 & Synchronous Ethernet support, timing module with DPLL/OCXO design up to 8 hours hold-over
- 2 SMA for 1PPS (1 Input 1 Output), 1 SMA for GNSS input with GNSS add-on module

X14SDW-36C-SP9F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6553P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x16 via Riser slot
- 1 PCIe 4.0 x8 via MCIO connector
- 8 25GbE SFP28 with Intel SoC, 1 GbE RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-42C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6726P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16, M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280 M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-36CE-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6556P-B, CPU TDP 215W, Intel Quick Assist Technology, Intel vRAN Accelerator, extended working temperature
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-36C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6553P-B, CPU TDP 235W, Intel Quick Assist Technology, Intel Media Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16
- M.2 Interface: 1 PCIe 4.0 x4 M.2 2280 M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-32C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6546P-B, CPU TDP 195W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-6400MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC 1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SDV-20C-SP3F

Key Features

- System on Chip
- Intel® Xeon® 6 SoC 6516P-B, CPU TDP 145W, Intel Quick Assist Technology, Intel vRAN Accelerator
- Up to 512GB ECC RDIMM DDR5-4800MT/s in 4 DIMM slots
- 2 PCIe 5.0 x8 via MCIO connectors
- 1 PCIe 5.0 x16,M.2 Interface: 1 PCIe 4.0 x4M.2 Form Factor: 2280M.2 Key: M-Key
- Dual 100G QSFP28 with Intel SoC1G RJ-45 with Intel® Ethernet Controller i210IT
- 12V DC or ATX Power Input
- Onboard TPM2.0

X14SAZ-TLN4F

Key Features

- Intel Core Ultra 9/7/5 Series 2 Processor, CPU TDP supports Up to 125W TDP
- Intel® W880
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO port M.2 Interface: 1 PCIe 5.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 2 HDMI 2.1 port)
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 12V DC power input
- Onboard TPM9672: TCG 2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SAZ-F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, CPU TDP supports Up to 125W TDP
- Intel® W880
- Up to 256GB Unbuffered ECC/non-ECC UDIMM/CUDIMM, DDR5-5600MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO port M.2 Interface: 1 PCIe 5.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 2 HDMI 2.1 port)
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Supports 12V DC power input
- Onboard TPM9672: TCG 2.0, FiPs 140-2 Level 2, Intel TXT and Microsoft Windows certification

X14SAV-TLN4F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 125W TDP
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4), 1 MCIO x8 port, 1 MCIO x4 port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 B-Key 3052 (PCIe 4.0 x1/USB 3)
- Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports via cable; RAID 0,1,5,10
- Supports 12V DC power input

X14SAV-LVDS

Key Features

- Intel® Core® Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 65W
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4) 1 PCIe 4.0 x4 MCIO port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 E-Key 2230 (PCIe 4.0 x1/USB 2.0)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 24 bit LVDS, 2 DP 2.1 ports, 2 HDMI 2.1 ports)
- Supports 12V - 24V DC power input
- Both onboard TPM chip SLB9672: TCG2.0, FiPs 140-2 Level 2 and pin header

X14SAV-F

Key Features

- Intel® Core™ Ultra 9/7/5 Series 2 Processor, Single Socket LGA-1851 supported, CPU TDP supports Up to 125W TDP
- Up to 96GB Unbuffered ECC/non-ECC CSODIMM/SODIMM, clocked DIMM support up to 6400MT/s (with Core Ultra 9/7), in 2 slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8 or 8/4/4), 1 MCIO x8 port, 1 MCIO x4 port 1 M.2 M-Key 2280 (PCIe 5.0 x4) 1 M.2 B-Key 3052 (PCIe 4.0 x1/USB 3)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® W880 Controller for 4 SATA3 (6 Gbps) ports via cable; RAID 0,1,5,10
- Supports 12V DC power input

X13SRN-H-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-H

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-E-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SRN-E

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAZ-Q

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® Q670E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 1 PCIe 4.0 x4 OCulink port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP++ ports, 1 HDMI 2.0b port, 1 DVI - D port)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAZ-F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 2 PCIe 4.0 x4 slots, 1 PCIe 4.0 x4 OCulink port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 VGA port, 2 DP++ ports, 1 HDMI 2.0b port, 1 DVI - D port)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAW-TLN4F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO 1 M.2 M-Key 2280 (PCIe 3.0 x4) 1 M.2 M-Key 2280/22110 (PCIe 4.0 x4)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226 LAN controller, Dual 10 Gigabit LAN with Intel® Ethernet X550-AT2 LAN controller
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 Independent Display Ports (2 DP1.4)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAW-F

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP. (**bios v5.x or above)
- Intel® R680E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slots, 2 PCIe 4.0 x4 MCIO 1 M.2 M-Key 2280 (PCIe 3.0 x4) 1 M.2 M-Key 2280/22110 (PCIe 4.0 x4)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i226 LAN controller
- Intel® R680E Controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 2 Independent Display Ports (2 DP1.4)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-PS

Key Features

- 13th/12th Gen Intel® Core™ processors , Intel® Celeron® processors, SoC, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP
- Up to 64GB Unbuffered non-ECC SODIMM, DDR5-4800MHz, in 2 SODIMM slots
- 1 PCIe 4.0 x4 slot
 - 1 M.2 M-Key 2280 (PCIe 4.0 x4)
 - 1 M.2 E-Key 2230 (PCIe 3.0 x1/USB2.0)
 - 1 M.2 B-Key 3052 (PCIe 3.0 x2/USB3.0/USB2.0)
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- 4 Independent Displays (1 DP ports, 1 HDMI port, 2 TYPE C support DP/USB3.0)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-LVDS

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP (**bios v5.0 or above)
- Up to 64GB Unbuffered non-ECC SODIMM, DDR4-3200MHz, in 2 SODIMM slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8) 1 M.2 M-Key 2280 (PCIe 4.0 x4) 1 M.2 E-Key 2230 (PCIe 3.0 x1/USB)
- Single 1 Gigabit LAN with Intel® Ethernet i210-AT LAN controller Single 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 5 SATA3 (1 header, 4 via Oculink) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP ports, 1 HDMI 2.0b port, 1 HDMI 1.4a port, LVDS)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAV-D5LVDS

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 65W TDP (**bios v5.0 or above)
- Up to 64GB Unbuffered non-ECC SODIMM, DDR5-5600MHz, in 2 SODIMM slots
- 1 PCIe 5.0 x16 slot (16/NA or 8/8) 1 M.2 M-Key 2280 (PCIe 4.0 x4) 1 M.2 E-Key 2230 (PCIe 3.0 x1/USB)
- Single 1 Gigabit LAN with Intel® Ethernet i210-AT LAN controller Single 2.5 Gigabit LAN with Intel® Ethernet i226LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 5 SATA3 (1 header, 4 via Oculink) ports; RAID 0,1,5,10
- 4 Independent Displays (2 DP ports, 1 HDMI 2.0b port, 1 HDMI 1.4a port, LVDS)
- Supports 12V DC power input
- Onboard TPM2.0

X13SAQ

Key Features

- Intel® Core Processors Series 2 & 14th/13th/12th Gen Core i Processor, Single Socket LGA-1700 supported, CPU TDP supports Up to 125W TDP (**bios v5.x or above)
- Intel® Q670E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR5-4400MHz, in 4 DIMM slots
- 1 PCIe 5.0 x16 slot, 1 PCIe 4.0 x4 slot, 1 PCIe 3.0 x4 slot, 1 PCIe 3.0 x2 slot, 1 PCIe 4.0 NVMe x4 SlimSAS port M.2 Interface: 1 PCIe 4.0 x4 M.2 Form Factor: 2280/22110 M.2 Key: M-Key
- Dual 2.5 Gigabit LAN with Intel® Ethernet i225LM LAN controller [AMT/vPro]
- Intel® Q670E Controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 4 Independent Displays (1 VGA port, 1 DP 1.4a port, 1 HDMI 2.0b port, 1 DVI - D port)
- Onboard TPM2.0

X13SAN-L-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-L

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-H-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-H

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfce: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-E-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfcse: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-E

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- Next gen interfcse: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-C-WOHS

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcse: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X13SAN-C

Key Features

- First performance hybrid architecture from Intel
- 4 independent display with 4K resolution
- Fast AI hardware acceleration
- Up to 64 EU with Intel® UHD graphics capable of 4K60 resolution
- Next gen interfcse: DDR5-4800 MHz and PCIe Gen4 x4 by SlimSAS and M.2
- High speed connectivity through dual 2.5GbE
- 100% wide temp grade design and components applied
- 12-24V wide range power with RVP and TVS
- Rich I/O and expansion: 4 COM, 9 USB, audio with AMP, triple M.2
- Hailo-8™ powerful and efficient Edge AI solution integration ready

X12STN-L-WOHS

Key Features

- Intel® 11th Generation Core™ i3-1115GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-L

Key Features

- Intel® 11th Generation Core™ i3-1115GRE Processor
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Intel® UHD Graphics for 11th Gen with 48EU capable of 4K60 resolution
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-H-WOHS

Key Features

- Intel® 11th Generation Core™ i7-1185GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-H

Key Features

- Intel® 11th Generation Core™ i7-1185GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-E-WOHS

Key Features

- Intel® 11th Generation Core™ i5-1145GRE Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-E

Key Features

- Intel® 11th Generation Core™ i5-1145GRE Processor
- Up to 80 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-C-WOHS

Key Features

- Intel® Celeron® 6305E Processor
- Up to 96 EU with Intel® Iris® Xe graphics capable of 4K60 resolution
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- Without heatsink for customers flexible thermal design
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12STN-C

Key Features

- Intel® Celeron® 6305E Processor
- High-speed connectivity through dual 2.5GbE, 4 USB3.1 gen2, PCIe 4.0 expansion
- Intel® UHD Graphics with 48 EU capable of 4K60 resolution
- Hailo-8™ powerful and efficient Edge AI solution integration ready
- 12-24V (10% tolerance) wide range power input support
- Accelerated AI inferencing and computer vision in parallel without extra hardware
- Rich I/O and expansion: 4 COM, 8 USB, audio with AMP, triple M.2
- 4 display support(HDMI2.0b/1.4b, DP1.4 and 48-bit LVDS)
- 100% wide temp grade design and components applied

X12SPZ-SPLN6F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 OCuLink Connector (4 SATA/PCIe 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCIe 3.0 x4)
- 1 PCIe 4.0 NVMe x8 SlimSAS Internal Port
1 PCIe 4.0 NVMe x4 SlimSAS Internal Port
- 2 PCIe 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Broadcom BCM57414
- 4 USB 3.2 Gen 1 (2 Rear, 2 via Header),
4 USB 2.0 (Headers)
- Supports 12V DC power input

X12SPZ-LN4F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 OCuLink Connector (4 SATA/PCIe 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCIe 3.0 x4)
- 1 PCIe 4.0 NVMe x8 SlimSAS Internal Port
1 PCIe 4.0 NVMe x4 SlimSAS Internal Port
- 2 PCIe 4.0 x16
- 4 USB 3.2 Gen 1 (2 Rear, 2 via Header),
4 USB 2.0 (Headers)
- Quad 1G RJ45 with Intel® I350-AM4
- Supports 12V DC power input

X12SPM-TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SPM-LN6TF

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Quad LAN with 1GbE with Intel® I350-AM4
Dual LAN with 10GBase-T with Intel® X550
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SPM-LN4F

Key Features

- 3rd Gen Intel® Xeon® Scalable processors, Single Socket LGA-4189 (Socket P+) supported, CPU TDP supports Up to 270W TDP
- Intel® C621A
- Up to 2TB 3DS ECC RDIMM, DDR4-3200MHz; Up to 2TB 3DS ECC LRDIMM, DDR4-3200MHz
Up to 2TB Intel® Optane™ Persistent Memory 200 Series, in 8 DIMM slots
- 1 PCI-E 4.0 x8,
2 PCI-E 4.0 x16,
2 PCI-E 4.0 x8 SlimSAS connectors
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280, 22110
M.2 Key: M-Key
- 4x NVMe port PCI-E 4.0 x4 via SlimSAS connector
- Quad LAN with 1GbE with Intel® I350-AM4
- Intel® C621A controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 5 USB 3.2 Gen1 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X12SDV-8CE-SP4F

Key Features

- Intel® Xeon® Processor D-1732TE, CPU TDP 52W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Dual 1G RJ45 with Intel® i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-8C-SPT8F

Key Features

- Intel® Xeon® Processor D-2733NT, CPU TDP 80W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-8C-SPT4F

Key Features

- Intel® Xeon® Processor D-1736NT, CPU TDP 67W, Intel Quick Assist Technology
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2667MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-8C-SP6F

Key Features

- Intel® Xeon® Processor D-1736NT, CPU TDP 67W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-4C-SPT8F

Key Features

- Intel® Xeon® Processor D-2712T, CPU TDP 65W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-4C-SPT4F

Key Features

- Intel® Xeon® Processor D-1718T, CPU TDP 46W
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-4C-SP6F

Key Features

- Intel® Xeon® Processor D-1718T, CPU TDP 46W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-20C-SPT8F

Key Features

- Intel® Xeon® Processor D-2796NT, CPU TDP 120W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for up to 6 SATA3 (6 Gbps) ports
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-16C-SPT8F

Key Features

- Intel® Xeon® Processor D-2775TE, CPU TDP 100W
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-14C-SPT8F

Key Features

- Intel® Xeon® Processor D-2766NT, CPU TDP 97W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz; Up to 512GB LRDIMM LRDIMM, DDR4-2667MHz, in 4 DIMM slots
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
1 M.2 M-Key 2242/2280 (SATA/PCI-E 3.0 x4)
- 2 PCI-E 4.0 NVMe x8 SlimSAS Internal Port
- 1 PCI-E 4.0 x16
- Quad 1G RJ45 with Intel® I350-AM4
Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- SoC controller for up to 6 SATA3 (6 Gbps) ports
- 12V DC or ATX Power Input (Use at least 5Vsb/4A PSU)

X12SDV-10CR-SP6F

Key Features

- Intel® Xeon® Processor D-1844NT, CPU TDP 55W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2667MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SDV-10C-SPT4F

Key Features

- Intel® Xeon® Processor D-1749NT, CPU TDP 90W, Intel Quick Assist Technology
- System on Chip
- Up to 128GB Registered ECC RDIMM, DDR4-2667MHz, in 2 DIMM slots
- 1 M.2 M-Key 2280 (SATA/PCI-E 4.0 x4)
- 1 OCuLink Connector (4 SATA/PCI-E 3.0 x4)
- 1 PCI-E 4.0 x8
- Dual 25G SFP28 with Intel SoC
Dual 10Gbase-T RJ-45 with Intel® Ethernet Controller X550-AT2
- 12V DC or ATX Power Input

X12SDV-10C-SP6F

Key Features

- Intel® Xeon® Processor D-1747NTE, CPU TDP 80W, Intel Quick Assist Technology
- System on Chip
- Up to 256GB Registered ECC RDIMM, DDR4-2933MHz, in 4 DIMM slots
- 2 PCI-E 3.0 NVMe x4 SlimSAS Internal Port (4 SATA/PCI-E 3.0 x4)
- 1 M.2 M-Key 2280 (SATA/PCI-E 3.0 x4)
1 M.2 B-Key 2280/3042/3052 (USB/SATA/PCI-E 3.0 x2)
1 M.2 E-Key 2230 (PCI-E 3.0 x1)
- 1 PCI-E 4.0 x16 or 2 PCI-E 4.0 x8
- Quad 1G RJ45 with Intel® I350-AM2 and i210-IT
Dual 25G SFP28 with Intel SoC
- SoC controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 12V DC or ATX Power Input

X12SCZ-TLN4F

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Intel® W480E
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Dual LAN with Intel® X550 10GBase-T Ethernet Controller
Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCZ-QF

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1200 (Socket H5) supported, CPU TDP support Up to 125W TDP
- Intel® Q470E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® Q470E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCZ-F

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Intel® W480E
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16,
1 PCIe 3.0 x4 (in x8 slot),
1 PCIe 3.0 x4
1 M.2 M-Key SATA/PCIe 3.0 x4, 2280/22110
1 M.2 E-Key CNVi/PCIe 3.0 x1, 2230
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 2 DP++(Dual-Mode DisplayPort) ports, 1 DVI - D port

X12SCV-W

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 65W TDP
- Single LAN with Intel® Ethernet i225LM
Single LAN with Intel® Ethernet i225V
- Intel® W480E
- Up to 64GB DDR4 ECC/non-ECC SO-DIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 PCIe 3.0 x16 slots (16/NA or 8/8)
1 M.2 M-Key PCIe 3.0 x4, 2280
- Intel® W480E controller for 4 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 HDMI port, 1 DP (DisplayPort) port

X12SCV-LVDS

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3 Processor, Intel® Xeon® W-1200 Processors
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 65W TDP
- Intel® W480E
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 64GB DDR4 ECC/non-ECC SO-DIMM, DDR4-2933MHz, in 2 DIMM slots
- 1 PCIe 3.0 x16 slots (16/NA or 8/8)
1 M.2 M-Key PCIe 3.0 x4, 2242/2280
1 M.2 E-Key CNVi/PCIe 3.0 x1/USB, 2230
- Intel® W480E controller for 2 SATA3 (6 Gbps) ports; RAID 0,1
- 2 HDMI ports, 1 DP (DisplayPort) port, 1 LVDS port,
3 Independent Displays thru HDMI 2.0a/HDMI1.4/DP/LVDS

X12SCQ

Key Features

- 11th/10th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 125W TDP
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Intel® Q470 controller for 6 RAID 0,1,5,10
- Intel® Q470E
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2933MHz, in 4 DIMM slots
- 1 PCIe 3.0 x16 (in x16 slot),
1 PCIe 3.0 x8,
2 PCIe 3.0 x4
M.2 Interface: 1 PCIe 3.0 x4, RAID 0 & 1
M.2 Form Factor: 2242/2280
M.2 Key: M-Key
- 1 VGA port, 1 HDMI port, 1 DP (DisplayPort) port, 1 DVI - D port

X11SWN-L-WOHS

Key Features

- Intel® 8th Generation Core™ i3-8145UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-L

Key Features

- Intel® 8th Generation Core™ i3-8145UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-H-WOHS

Key Features

- Intel® 8th Generation Core™ i7-8665UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-H

Key Features

- Intel® 8th Generation Core™ i7-8665UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-E-WOHS

Key Features

- Intel® 8th Generation Core™ i5-8365UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-E

Key Features

- Intel® 8th Generation Core™ i5-8365UE Processor
- Dual Channel DDR4 2400MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-C-WOHS

Key Features

- Intel® Celeron® 4305UE Processor
- Dual Channel DDR4 2133MHz SO-DIMM, up to 64GB
- Intel UHD Graphics 620 with 4K and 24 EU for Vision Solution
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Without heatsink for customer's flexible thermal design
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SWN-C

Key Features

- Intel® Celeron® 4305UE Processor
- Dual Channel DDR4 2133MHz SO-DIMM, up to 64GB
- Small form factor with rich I/O: 2 GbE, 8 USB and 6 COM
- Intel UHD Graphics 610 with 4K and 24 EU for Vision Solution
- 12-24V wide range power input with RVP and TVS
- Rich expansion: 3 x M.2 (B/E/M key) for NVMe/SATA/Wifi/BT/LTE
- 3 display support(DP++, HDMI and 48-bit LVDS)

X11SSN-L-WOHS

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-L-VDC

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0

X11SSN-L-001

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-L

Key Features

- 7th Generation Intel® Core™ i3-7100U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)

X11SSN-H-WOHS

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-H-VDC

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0
- Supports on board TPM 2.0

X11SSN-H-001

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-H

Key Features

- 7th Generation Intel® Core™ i7-7600U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E-WOHS

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E-VDC

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support 12V DC Power Input (Vertical Type Connector)
- Support HDMI 2.0
- Supports on board TPM 2.0

X11SSN-E-001

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SSN-E

Key Features

- 7th Generation Intel® Core™ i5-7300U Processor
- Up to 32GB Unbuffered Non-ECC SO-DIMM, DDR4 2133MHz; 2 DIMM slots
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 DP, 1 LVDS, Intel HD Graphics 3 independent displays
- Dual GbE LAN w/ Intel i219LM + i210IT
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Support HDMI 2.0
- Support 12V DC power input (R/A Type Connector)
- Supports on board TPM 2.0

X11SPM-TPF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C622
- 2 10G SFP+
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- I/O: 1 VGA, 2 COM, 1 TPM header
- Supports 12V DC power input

X11SPM-TF

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C622 chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C622
- 2 10GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X11SPM-F

Key Features

- 2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors, , Single Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 165W TDP
- Intel® C621 Chipset
- Up to 1.5TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 1.5TB 3DS ECC LRDIMM, DDR4-2933MHz, in 6 DIMM slots; Up to 1TB Intel Optane DC Persistent Memory in memory mode (Cascade Lake Only)
- M.2 NGFF connector, M.2 Interface: PCI-E 3.0 x4
Form Factor: 2242, 2280
Key: M-Key
- Expansion slots: 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8 (in x8)
- 12 SATA3 (6Gbps) via C621
- 2 GbE LAN ports
- I/O: 1 VGA, 2 COM, TPM header
- 5 USB 3.0 (2 rear, 1 Type-A, 2 via header), 6 USB 2.0 (2 rear, 4 via headers)
- Supports 12V DC power input

X11SDC-8C

Key Features

- Intel® Xeon® Processor D-2146NT, 8-Core, 16 Threads, 80W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SDC-4C

Key Features

- Intel® Xeon® Processor D-2123IT, 4-Core, 8 Threads, 60W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SDC-16C

Key Features

- Intel® Xeon® Processor D-2183IT, 16-Core, 32 Threads, 100W
- Up to 256GB Registered ECC RDIMM or 512GB ECC LRDIMM, DDR4-2400MHz in 4 DIMM slots
- Up to 44 PCI-E Gen3 lanes (x16, x8, x4, x1) to Carrier Board
- Single 1G BASE-T port (Intel i210IT) to Carrier Board
- Quad 10G BASE-KR ports (SoC) to Carrier Board
- System on Chip

X11SCZ-Q

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor.
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 128GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
2 PCI-E 3.0 x4 (in x8 slot)
M.2 Interface: 1 SATA/PCI-E 3.0 x4
M.2 Form Factor: 2280/22110
M.2 Key: M-Key
- Intel® Q370 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DVI - I port, 2 DP (DisplayPort) ports,
3 Independent Displays

X11SCZ-F

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor, Intel® Xeon® E-2100 Processor, Intel® Xeon® E-2200 Processor.
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® C246
- Up to 128GB Unbuffered ECC/non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
2 PCI-E 3.0 x4 (in x8 slot)
1 M.2 M-Key SATA/PCI-E 3.0 x4, 2280/22110
- Intel® C246 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 VGA D-Sub Connector port, 1 DVI - I port, 2 DP (DisplayPort) ports,
3 Independent Displays

X11SCV-Q

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 65W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 64GB Unbuffered non-ECC SO-DIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 M.2 M-Key PCI-E 3.0 x4, 2242/2280
1 M.2 E-Key CNVi/PCI-E 3.0 x1, 2230
- Intel® Q370 controller for 5 SATA3 (6 Gbps) ports; RAID 0,1,5,10
X11SCV-Q: Q370 controller for 5SATA3 ports;RAID 0,1,5,10
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
3 Independent Displays, HDMI 2.0

X11SCV-L

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 65W TDP
- Intel® H310
- Single LAN with Intel® PHY I219LM LAN controller
Single LAN with Intel® Ethernet Controller I210-AT
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 M.2 E-Key PCI-E 2.0 x1, 2230
- Intel® H310 controller for 4 SATA3 (6 Gbps) ports;
Only I-SATA0 - I-SATA3
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
2 Independent Displays

X11SCQ-L

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Intel® H310
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Up to 32GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 2 DIMM slots
- 1 PCI-E 3.0 x16
1 PCI-E 2.0 x4
1 PCI-E 2.0 x1
- Intel® H310 controller for 4 SATA3 (6 Gbps) ports;
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
2 Independent Displays

X11SCQ

Key Features

- 8th/9th Generation Intel® Core™ i9/Core™ i7/Core™ i5/Core™ i3/Pentium®/Celeron® Processor
Single Socket LGA-1151 (Socket H4) supported, CPU TDP support Up to 95W TDP
- Single LAN with Intel® Ethernet Controller I210-AT
Single LAN with Intel® PHY I219LM LAN controller
- Intel® Q370
- Up to 64GB Unbuffered non-ECC UDIMM, DDR4-2666MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x16,
1 PCI-E 3.0 x1,
2 PCI-E 3.0 x4
M.2 Interface: 1 PCI-E 3.0 x4
M.2 Form Factor: 2242/2280/22110
M.2 Key: M-Key
- Intel® Q370 controller for 6 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 1 DVI - D port, 1 HDMI port, 1 DP (DisplayPort) port, 1 eDP (Embedded DisplayPort) port,
3 Independent Displays

X11SAN-WOHS

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

X11SAN

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

X11SAA

Key Features

- Intel® Pentium™ Processor N4200 (6W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), 1 Mini-PCIe (mSATA support) and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 1 SATA DOM, 3 COM, TPM header and Audio Header
- 2 USB 3.0 ports (2 rear), 8 USB 2.0 (2 rear, 5 via header(s), 1 Type A)
- 1 HDMI, 1 DP, 1 VGA, Intel HD Graphic 3 independent displays
- 4 SATA 3.0 (RAID 0, 1, 10)
- 1 M.2 M-key with SATA

A4SAP-L

Key Features

- Intel® processor N97 (12W, 4C)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)

A4SAP-H

Key Features

- Intel® processor N97 (7W, 4C)
- Extension I/O (1 DP/HDMI, 2 PCI-E x1, 2 USB2.0, LPC, SATA, SMBus, Power)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)

A4SAP-E

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- 1 M.2 B-Key 2242/3042, 1 M.2 E-Key 2230
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Supports 12V DC power input
- 2 USB 3.2 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature support from -40°C to 65°C

A4SAN-L-WOHS

Key Features

- Intel® processor N97 (12W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2242/3052/2280
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays

A4SAN-L

Key Features

- Intel® processor N97 (12W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays

A4SAN-H-WOHS

Key Features

- Intel® Atom® Processor x7835RE (12W, 8C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 85°C

A4SAN-H

Key Features

- Intel® Atom® Processor x7835RE (12W, 8C)
- DDR5 4800 MHz, SODIMM x 1, Up to 16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 70°C (by optional heatsink)

A4SAN-E-WOHS

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 85°C

A4SAN-E

Key Features

- Intel® Atom® Processor x7433RE (9W, 4C)
- DDR5 4800 MHz, SODIMM x 1, Up to16GB, In-Band ECC supported
- M.2 M-Key 2242/2280, M.2 E-key 2230, M.2 B-key 2240/3052/2280
- Dual 2.5GbE, M.2 B-key w/ nano SIM & 5G module supported
- 9-36V wide range power with RVP and TVS
- 4 USB3.2, 2 USB2.0, 4COM ports, audio with AMP, SMBus/I2C, 8bit GPIO
- 2 HDMI, 1 48bit LVDS, Intel HD Graphics 3 independent displays
- Wide temperature support from -40°C to 75°C (by optional heatsink)

A3SSV-8C-SPLN10F

Key Features

- Intel Atom Processor P5322, , Single Socket FCBGA-2106 supported, , CPU TDP support 55 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2400MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SSV-24C-SPLN10F

Key Features

- Intel Atom Processor P5362, , Single Socket FCBGA-2106 supported, , CPU TDP support 83 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2933MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SSV-16C-SPLN10F

Key Features

- Intel Atom Processor P5342, , Single Socket FCBGA-2106 supported, , CPU TDP support 71 W
- System on Chip
- Intel Quick Assist Technology
- Up to 256GB ECC RDIMM DDR4-2667MHz, in 4 DIMM slots
- 2x 25G SFP28 ports and 8 GbE RJ45 LAN ports
- Linux support only (RHEL 8.3 and kernel version 4.18.0 or higher)
- I/O: 1 VGA, 2 COM, TPM 2.0 onboard and header both
- Up to 6 SATA 2.0 ports
- Expansion slots: , 1 PCI-E 3.0 x8 , 1 PCI-E 3.0 x4
- M.2 Interface: , 1x M.2 B-Key 2242/3042/2280 w/PCIe 2.0 x2/SATA 2.0/USB 3.0 , 1x M.2 M-Key 2242/2280/22110 w/PCIe 2.0 x4/SATA 2.0/USB 2.0 , 1x M.2 E-Key 2230 w/PCIe 2.0 x1/USB 2.0
- 2 USB 3.0 (Type-A on rear) , 2 USB 2.0 (via headers)
- Supports 12V DC power input

A3SEV-4C-LN4

Key Features

- Intel® Atom® Processor x6425E
Single Socket FCBGA-1493 supported, CPU TDP supports Up to 12W TDP
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-3200MHz, in 2 DIMM slots
- 1 PCI-E 3.0 X2 (in x8 slot)
1 M.2 B-Key SATA/PCI-E 3.0 x2/USB 3.0, 3042/2280
1 M.2 E-Key PCI-E 3.0 x1/USB 2.0, 2230
- Single LAN with Intel® Ethernet Controller I210IT
ONLY i210 support PXE
3 LAN with 1GbE with Marvell® 88E1512
- 1 DP (DisplayPort) port, 1 HDMI port, 1 VGA port or 1 eDP (Embedded DisplayPort) port, Supports 3 independent displays
- System on Chip

A3SEV-2C-LN4

Key Features

- Intel® Atom® Processor x6211E.
Socket FCBGA-1493 supported, CPU TDP supports Up to 6W TDP
- Up to 32GB Unbuffered non-ECC SO-DIMM, DDR4-3200MHz, in 2 DIMM slots
- 1 PCI-E 3.0 X2 (in x8 slot)
1 M.2 B-Key SATA/PCI-E 3.0 x2/USB 3.0, 3042/2280
1 M.2 E-Key PCI-E 3.0 x1/USB 2.0, 2230
- Single LAN with Intel® Ethernet Controller I210IT
ONLY i210 support PXE
3 LAN with 1GbE with Marvell® 88E1512
- 1 DP (DisplayPort) port, 1 HDMI port, 1 VGA port or 1 eDP (Embedded DisplayPort) port, Supports 3 independent displays
- System on Chip

A2SDV-8C-TLN5F

Key Features

- Intel Atom Processor C3708, , Single Socket FCBGA1310 supported, , CPU TDP support 17W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-8C-LN8F

Key Features

- Intel® Atom® Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 5 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-8C-LN10PF

Key Features

- Intel® Atom® Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 5 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports , 2x 1GbE SFP LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-4C-LN8F

Key Features

- Intel® Atom® Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x2 (Slot 6 or 7 option)
- M.2 Interfaces: , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- 3 SATA3 (6 Gbps) ports
- 8x 1GbE RJ45 LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-4C-LN10PF

Key Features

- Intel® Atom® Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 up to x2 (Slot 6 or 7 option)* , Flexible I/O - software configurable in BIOS
- Up to 3 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS
- 8x 1GbE RJ45 LAN ports , 2x 1GbE SFP LAN ports
- 3 USB 3.0 (2 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 1 COM (1 via header), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-16C-TLN5F

Key Features

- Intel Atom Processor C3958, , Single Socket FCBGA1310 supported, , CPU TDP support 31W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDV-12C+-TLN5F

Key Features

- Intel Atom Processor C3858, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- M.2 Interfaces: , 1 M-Key 2242/80 supports PCI-E 3.0 x2/SATA , 1 B-Key 3042/2280 supports PCI-E 3.0 x2/SATA/USB
- Expansion slots: , 1 PCI-E 3.0 x8 (Slot 6 or 7 option)
- 2 SATA3 (6 Gbps) ports
- 4x 10GbE LAN ports, , 1x 1GbE LAN port (IPMI shared LAN)
- 5 USB 3.0 (4 rear, Type-A) , 2 USB 2.0 (2 via headers)
- I/O: 1 VGA, 2 COM (1 via header, 1 rear RJ45), TPM header
- System on Chip
- Supports 12V DC power input

A2SDi-TP8F

Key Features

- Intel® Atom® Processor C3858.
Single Socket FCBGA-1310 supported, CPU TDP support Up to 25W TDP
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT, 2 10Gb SFP+
Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port

A2SDi-LN4F

Key Features

- Intel® Atom® Processor C3850., Single Socket FCBGA1310 supported, CPU TDP support 25W
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port
- Supports 12V DC power input

A2SDi-H-TP4F

Key Features

- Intel® Atom® Processor C3958., Single Socket FCBGA1310 supported, CPU TDP support 31W
- Up to 256GB Registered ECC RDIMM, DDR4-2400MHz
Up to 64GB Unbuffered ECC/non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
M.2 Interface: PCI-E 3.0 x2 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT and 2 10Gb SFP+
- SoC controller for 12 SATA3 (6 Gbps) ports;
4 SATA3 ports, 2 MiniSAS HD ports
- System on Chip
- 1 VGA port

A2SDi-H-TF

Key Features

- Intel® Atom® Processor C3758., Single Socket FCBGA1310 supported, CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC RDIMM, DDR4-2400MHz
Up to 64GB Unbuffered ECC/non-ECC UDIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
M.2 Interface: PCI-E 3.0 x2 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Dual LAN with Intel® C3000 SoC
2 10GBaseT
- SoC controller for 12 SATA3 (6 Gbps) ports;
4 SATA3 ports, 2 MiniSAS HD ports
- Support 12V DC power
- System on Chip
- 1 VGA port

A2SDi-8C-HLN4F

Key Features

- Intel Atom Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-8C+-HLN4F

Key Features

- Intel Atom Processor C3758, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-4C-HLN4F

Key Features

- Intel Atom Processor C3558, , Single Socket FCBGA1310 supported, , CPU TDP support 16W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2133MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2133MHz; in 4 DIMM slots
- M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- Expansion slots: , 1 PCI-E 3.0 up to x4 (in x4 slot)* , Flexible I/O - software configurable in BIOS setup
- Up to 8 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS setup
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-2C-HLN4F

Key Features

- Intel Atom Processor C3338, , Single Socket FCBGA1310 supported, , CPU TDP support 9W
- Up to 128GB Registered ECC DDR4-1866MHz, , Up to 32GB Unbuffered ECC/Non-ECC DDR4-1866MHz; in 2 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 up to x4 (in x4 slot)* , Flexible I/O - software configurable in BIOS setup
- Up to 8 SATA3 (6 Gbps) ports via SoC* , Flexible I/O - software configurable in BIOS setup
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDI-16C-TP8F

Key Features

- Intel® Atom® Processor C3958., Single Socket FCBGA-1310 supported, CPU TDP support 31W TDP
- Up to 64GB Unbuffered ECC/non-ECC SO-DIMM, DDR4-2400MHz, in 4 DIMM slots
- 1 PCI-E 3.0 x4
1 miniPCI-E with mSATA supports (half card only)
M.2 Interface: PCI-E 3.0 x4 and SATA
M.2 Form Factor: 2242, 2280
M.2 Key: M-Key
- Quad LAN with Intel® C3000 SoC
2 10GBaseT, 2 10Gb SFP+
Quad LAN with Intel® Ethernet Controller I350-AM4
1GbE
- SoC controller for 4 SATA3 (6 Gbps) ports;
- System on Chip
- 1 VGA port

A2SDi-16C-HLN4F

Key Features

- Intel Atom Processor C3955, , Single Socket FCBGA1310 supported, , CPU TDP support 32W
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-16C+-HLN4F

Key Features

- Intel Atom Processor C3955, , Single Socket FCBGA1310 supported, , CPU TDP support 32W
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SDi-12C-HLN4F

Key Features

- Intel Atom Processor C3858, , Single Socket FCBGA1310 supported, , CPU TDP support 25W
- Intel Quick Assist Technology
- Up to 256GB Registered ECC DDR4-2400MHz, , Up to 64GB Unbuffered ECC/Non-ECC DDR4-2400MHz; in 4 DIMM slots
- Expansion slots: , 1 PCI-E 3.0 x4, , M.2 Interface: PCI-E 3.0 x2 and SATA , M.2 Form Factor: 2242, 2280 , M.2 Key: M-Key
- 12 SATA3 (6 Gbps) ports
- 4 GbE LAN ports
- 1 USB 3.0 (Type-A) , 4 USB 2.0 (2 rear, 2 via headers)
- System on Chip
- I/O: 1 VGA, 1 COM, TPM header
- Supports 12V DC power input

A2SAV-L

Key Features

- Intel® Atom processor E3940 (9W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 4 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 1 HDMI, 1 DP, 1 VGA or 1 eDP, Intel HD Graphic 3 independent displays
- 12V DC Input and ATX Power Source
- 1 M.2 M-key with SATA

A2SAV-2C-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 4 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 1 HDMI, 1 DP, 1 VGA or 1 eDP, Intel HD Graphic 3 independent displays
- 12V DC Input and ATX Power Source
- 1 M.2 M-key with SATA

A2SAV

Key Features

- Intel® Atom processor E3940 (9W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 PCI-E 2.0 x2 (in x8), 1 Mini-PCIe (mSATA support) and 2 SATA 3.0
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- 2 USB 3.0 ports, 7 USB 2.0 ports, 3 COM ports, and 1 DOM connector
- 12V DC Input and ATX Power Source
- 1 HDMI, 1 DP, 1 VGA, Intel HD Graphic 3 independent displays
- 4 SATA 3.0 (RAID 0, 1, 10)
- 1 M.2 M-key with SATA

A2SAP-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E, 1 SATA 3.0
- Dual Gigabit Ethernet LAN ports via Intel® i210AT
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Supports 12V DC power input

A2SAP-H

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Dual LAN with Intel® Ethernet Controller I210-IT
- Extension I/O (1 DP/HDMI, 2 PCI-E x1, 2 USB2.0, LPC, SATA, SMBus, Power)
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature suppot from -30°C to 75°C
- Supports 12V DC power input

A2SAP-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2242/3042, 1 Half size Mini-PCI-E, 1 SATA 3.0
- 1 HDMI, 1 48-bit LVDS, Intel® HD Graphic 2 independent displays
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports (rear), 2 USB 2.0 ports (via headers), 2 COM ports (via headers)
- Wide temperature suppot from -30°C to 75°C
- Supports 12V DC power input

A2SAN-LN4-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Quad LAN with Intel® Ethernet Controller I210-IT
- 2 USB 3.0 ports, 2 USB 2.0 ports, 1 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 3 M.2 B-Key 2242/3042 with nano SIM slot, 1 M.2 E-Key 2230
- Supports 12V DC power input

A2SAN-LN4-C

Key Features

- Intel® Celeron® Processor J3455 (10W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Quad LAN with Intel® Ethernet Controller I211-AT
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- 2 USB 3.0 ports, 2 USB 2.0 ports, 1 SATA 3.0, SMBus
- 3 M.2 B-Key 2242/3042 with nano SIM slot, 1 M.2 E-Key 2230
- Supports 12V DC power input

A2SAN-L-WOHS

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-L

Key Features

- Intel® Atom processor E3930 (6.5W, 2C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-H-WOHS

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB3.0, 4 USB2.0, 6 COM ports, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-H

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 1 USB 3.1 Gen2 Type-C port, 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Dual GbE LAN with Intel® i210-AT
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-E-WOHS

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input

A2SAN-E

Key Features

- Intel® Atom processor E3940 (9.5W, 4C)
- Up to 8GB 1866MHz DDR3L Non-ECC SO-DIMM in 1 socket
- Dual LAN with Intel® Ethernet Controller I210-IT
- 1 M.2 B-Key 2280, 1 Full size Mini-PCI-E, 1 SATA 3.0
- 2 USB 3.0 ports, 4 USB 2.0 ports, 4 COM ports, 1 SATA 3.0, 8-bit GPIO, SMBus
- Intel® Goldmont microarchitecture 14nm System-on-Chip
- Wide temperature support from -30°C to 75°C
- Supports on board TPM 2.0
- 1 HDMI, 1 VGA, 1 48-bit LVDS, Intel® HD Graphic 3 independent displays
- Supports 12V DC power input