

SSE-T7132S - 400Gb Ethernet Switch

Specifications

High-performance SONiC Open Networking 400GbE and 200GbE switch Software Features

Supermicro's next generation 400Gbps Open Networking Switch designed to provide high density and superior performance to data datacenter demands.

The Super Micro Computer SSE-T7132 is professional datacenter robust 50 Gbps PAM4 SERDES lowers the cost per bit and enable such as 200 GbE and 400 GbE while maintaining backward compatibility 10/25G NRZ.

SSE-T7132SR delivers exceptional forwarding performance for networking applications such as High Performance Computing computing and most of the data center applications. With the a single SKU over various network layers such as Data Center Spine DCI applications, SSE-T7132 provides easy of management and to users.

With 1U rack size occupancy and high port density 400G/200G/ achieves minimalistic setup in the rack. SSE-T7132 comes in standard reverse airflow models that can operate at variety of speeds such as QSFP56-DD or 64 x200Gbps QSFP56 or 128x100Gbps QSFP28 using cables. Switch comes with dual and redundant power supplies FRU capable. The included rail kit facilitates rack-mounting installation.

With emerging SONiC OS support on SSE-T7132 switch provide to applications such as large-scale enterprises, service providers computing. Supermicro provides user friendly enhancements to the various data center applications.

Machine learning (ML) and artificial intelligence (AI) applications faster CPUs, and flash storage are driving the next generation of networks based on 400G Ethernet. Evolution to the next generation systems that deliver optimized performance for ML/AI and additional and increased scale of modern cloud environments. Line rate proven layer 2 and layer 3 features with up to 128 ports of 100G 200GE or 32 ports of 400G along with break through power efficient FLASHLIGHT analytics



Operating System / NOS

**The SSE-T7132 series switch comes with preloaded SONiC OS.
No additional licensing is required.**

Download

Datasheet

Standard ToR Ethernet Switches [[Download \(/datasheet/datasheet_S](#)

Firmware

- Firmware Upgrade [[Download](#)

(<https://www.supermicro.com/en/support/resources/download/SSE-T7132SR/NetworkSwitch>).]

Manuals

SONiC Configuration Guide [[Download \(/about/policies/disclaimer_url=/manuals/network/Supermicro_Datacenter_SONiC_Configuration_Guide.pdf\)](#)]
[[View \(/support/manuals/product/switch/datacenter-sonic\)](#)]
User's Manual [[Download \(/manuals/other/MNL-2588.pdf\)](#)]
BMC User's Manual [[Download \(/manuals/network/SSE-T7132_BMC_User_Manual.pdf\)](#)]

Specifications

Key Switch Specs

Form Factor: 1 RU
Capacity: 25.6Tbps
Interfaces Speeds: 10, 25, 40, 50, 100, 200 & 400GbE
Supported default Configurations: 32x400GbE,
28x400G+4x100G, 24x400G+8x100G,
32x100G,
72x25G+8x100G+6x400G,
Operating System: SONiC OS

Key Advantages

DC Optimized Silicon for AI Industry leading Latency
Power Efficient
FLASHLIGHT Analytics

OS Features

MAC addresses per system: up to 44K
IPv4 Host: up to 192K
IPv4 LPM: up to 288K
IPv6 Host: up to 94K
IPv6 LPM ($\leq$ /64): up to 44K
IPv6 LPM ($>$ /64): up to 128K
IPv4 Multicast: up to 47K
IPv6 Multicast: up to 54K

*The values mentioned are max per attribute and overall value. The attribute will depend upon the profile selected at the boot time.

Key Capabilities and Advantages

Up to 12.8T performance
Up to 128x 100GbE, 64x 200GbE or 32x 400GbE
70MB Buffer for Superior Network
Quality
RoCEv2/RDMA support for best QoS
2x+ lower latency, largest on-chip buffers
FLASHLIGHT™ telemetry. Pinpoint any network delays, detect congestion and correlate network events all in hardware with no impact to performance. Accelerating issue resolution and automation and self-healing autonomous networks
Line-Rate Programmability
Standards & Software based
No impact to throughput or latency

Hardware Features

Layers 2

VLAN
VLAN Trunking
MAC Aging

Layers 3

BGP/BGP MP
BGP Graceful Restart
IPv6
Basic VRF
ECMP
L3 RIF counters
Mgmt VRF
VRF

Port

LLDP
LAG
LACP Fallback
MTU Settings
Static Port Breakout
Sub-port support

Management and Monitoring

SNMP
Syslog
Everflow
OOM
TCPDump
Critical Resource Monitoring
Mirroring
TACACS+
Sensor transceiver monitoring
sFlow
BDC/HDC with remote & local collectors

QoS

CoPP
COS
PFC
PFC Watermark
PFC WD
Asymmetric PFC
ECN
RDMA
WRED

ACL

ACL permit/deny
IPv6 ACL
Dynamic ACL upgrade
ACL Statistics

Utilities

Interface Ports

- 32x QSFP-DD Ports
- 1x RJ45 Serial Console
- 1x RJ45 100/1000BASE-T Management
- 1x USB Type A Storage

- Fast Reload
- Warm Reload
- DHCP Relay Agent
- NTP
- Transparent QoS Settings
- ZTP
- Python 2/3 support

Onboard CPU Engine

- Intel Quad Core CPU
- 16GB DDR4 DRAM
- 16MB SPI Flash
- 128GB SSD

Safety

Physical and Environmental

- 1RU, Mountable in either 19” or 21” racks
- Dimensions: (WxDxH) 433 x 600 x 44 mm (17.1 x 23.6 x 1.73
- Weight: (Switch Unit) 11.52kg
- Front-to-Rear and Rear-to-Front airflow versions available
- 2x Redundant, Load Sharing, Hot Swappable PSUs
- Input Voltage: 100 to 240V AC at 5-60Hz
- 1300W Maximum Power (with Pluggable Optic)
- Hot Swappable 6+1 Redundant Fan Modules

EU:

IEC 60950-1:2005,
IEC 60950-1:2005/AMD1:2009,
IEC 60950-1:2005/AMD2:2013,
EN 60950-1:2006 including
A11:2009/A1:2010/A12:2011/A2:2013

CSA / cUL:

CAN/CSA C22.2 No. 62368-1:19
ANSI/UL 62368-1, 3rd Ed.

CE / UKCA:

EN 55032:2015+A11:2020 Class A, BS EN
55032:2015+A11:2020 Class A
EN 300 386 V2.1.1(2016-07) Class A,
EN IEC 61000-3-2:2019, BS EN IEC 61000-3-2:2019,
EN 61000-3-3:2013+A1:2019, BS EN 61000-3-
3:2013+A1:2019,
EN 55035:2017+A11:2020, BS EN
55035:2017+A11:2020,
EN 300 386 V2.1.1(2016-07)

(IEC 61000-4-2 Edition 2.0 2008-12, IEC 61000-4-3
Edition 3.2 2010-04, IEC 61000-4-4 Edition 3.0 2012-
04, IEC 61000-4-5 Edition 3.1 2017-08, IEC 61000-4-6
Edition 4.0 2013-10, IEC 61000-4-8 Edition 2.0 2009-
09, IEC 61000-4-11 Edition 3.0 2020-01)

ICES:

ICES-003 Issue 7, Class A

FCC:

FCC Part 15 Subpart B

CB:

CB 242716-80161384
IEC 62368-1:2014
EN 62368-1:2014+A11:2017

Japan (VCCI):

VCCI 32-1

AUS/NZS:

AS/NZS CISPR 32:2015 AMD 1:2020

EU:

- CISPR 32
- EN 55032
- BS EN 55032
- CISPR 35
- EN 55035
- BS EN 55035
- EN6100-3-2
- BS EN 6100-3-2
- EN6100-3-3
- BS EN 6100-3-3
- EN 300 386

North America:

- 47CFR Part 15(CFR 47) Class A
- ICES003 issue7 Class A

Japan (VCCI):

- VCCI CISPR 32-1

Aus/Nz (ACMA):

- AS/NZS CISPR 32

Taiwan (BSMI):

- CNS 15936

Korean (KCC):

- KN32 Class A
- KN35

China (CCC):

- GB9254.1

Environmental

EU (RoHS)

EU (REACH)

Parts List

Certain products may not be available in your region
