

SSE-SN3420 - 25Gb/100Gb Ethernet Switch

Specifications

High-performance Open Networking 25GbE/100G Leaf/Aggregation switch

Supermicro introduces the Spectrum-2 based Open Networking 25G Switch SSE-SN3420 series that is designed to provide high density 25G as well as 100G ports in a compact 1U form factor.

SSE-SN3420 is an ideal choice for Top-of-Rack network Switch that delivers exceptional processing capacity of 3.5Bpps, suitable for leaf-spine architecture data center deployments.

With a total of 4.8Tb/s throughput, SSE-SN3420 switch comes with dual and redundant power supplies and FANs. The included rail kit facilitates rack-mounting installations.

SSE-SN3420 is ready with pre-installed Cumulus Linux OS for open networking incorporating a true Linux distribution with extensive networking features plus hardware acceleration of routing and switching functions. By using many of the same tools employed for servers, Cumulus Linux enables affordable scalability with clear CapEx savings and even greater OpEx savings; it unleashes rapid innovation via custom, open source or commercial Linux tools and applications.



Compliance

Safety

CB, CE, cTUVus, CU

EMC

CE, ICES, FCC, RCM, VCCI

ROHS

RoHS compliant

Relative Humidity

5% to 85%

Operating Altitude

0-3050m

Download

Features

- 1U ToR 25Gbps/100Gbps Ethernet Switch
- Open Networking - ONIE installed
- Cumulus Linux Ready (Pre-Installed and License activated)
- Data Center Friendly
 - Dual Redundant Hot-swappable power supplies
 - Regular and Reverse Air-Flow Models

- Powerful Spectrum-2 Switch Chip
 - 4.8Tbps Switching Capacity
 - Non-blocking

- Versatile Dual Core Processor
 - 8GB DRAM
 - 32GB SSD

Specifications

Physical Ports:

- 48x SFP28 and 12x QSFP28 Ethernet ports
- RJ-45 Gigabit Ethernet management port
- RJ-45 serial console
- USB port

Data Forwarding:

- Full Duplex 4.8Tbps Switching Capacity
- Spectrum-2 Switch Chip
- Non-blocking, wire-speed Layer 3 Routing

Power:

- 1+1 hot-swappable power supplies and N+1 hot-swappable fans
- AC Input: 100-127/200-240 V, 50/60 Hz
- Frequency: 50-60Hz
- Input range: 100-264 AC
- Input current 2.9-4.5A

Physical/Environmental:

- Weight: Net weight: 8.5kg (18.73b)
- Regular and Reverse Airflow Models
- Size: 1.72" x 16.84" x 22" (44mm x 428mm x 432mm)
- Temperature: Operating 0°C to 40°C (32°F to 104°F)
- Humidity: Operating: 5% to 85% (non-condensing)

General:

- Open Networking
- 1U form factor for flexible installation
- Mounting Rails (included)

Datasheet

Spectrum-2 based Top-of-Rack Ethernet switches [[Download \(/datasheet/datasheet_SSE-SN3000.pdf\)](#),]

Operating System / NOS & Support

The SSE-SN3420 switch comes with preloaded Cumulus Linux OS.

Mandatory Software Service & Support SKUs sold separately; can be found under parts list below.

Parts List

Certain products may not be available in your region
