

SSE-SN3700C - 100Gb Ethernet Switch

Specifications

High-performance Open Networking 100G spine switch

Supermicro introduces the Spectrum-2 based Open Networking 32 port 100G spine Switch SSE-SN3700C series that is designed to provide high density 10G/25G leaf as well in a compact 1U form factor.

With a total of 6.4Tb/s throughput, SSE-SN3700C switch comes with dual and redundant power supplies and FANs. The included rail kit facilitates rack-mounting installations. SN3700C allows for maximum flexibility, with ports spanning from 1GbE to 100GbE and port density that enables full rack connectivity to any server at any speed, and a variety of blocking ratios. SN3700C ports are fully splittable to up to 128X 10/25GbE ports.

SSE-SN3700C is ready with pre-installed Cumulus Linux OS for open networking incorporating a true Linux distribution with extensive networking features plus hardware acceleration of routing and switching functions. By using many of the same tools employed for servers, Cumulus Linux enables affordable scalability with clear CapEx savings and even greater OpEx savings; it unleashes rapid innovation via custom, open source or commercial Linux tools and applications.



CUMULUS 

Compliance

Safety

CB, CE, cTUVus, CU

EMC

CE, ICES, FCC, RCM, VCCI

ROHS

RoHS compliant

Relative Humidity

5% to 85%

Operating Altitude

0-3050m

Download

Features

1U ToR 100Gbps/25Gbps Ethernet Switch
Open Networking - ONIE installed
Cumulus Linux Ready (Pre-Installed and License activated)
Data Center Friendly
Dual Redundant Hot-swappable power supplies
Regular and Reverse Air-Flow Models

Powerful Spectrum-2 Switch Chip
6.4Tbps Switching Capacity
Non-blocking

Versatile Dual Core Processor
8GB DRAM
32GB SSD

Specifications

Physical Ports:

32x QSFP28 Ethernet ports
RJ-45 Gigabit Ethernet management port
RJ-45 serial console
USB port

Data Forwarding:

Full Duplex 6.4Tbps Switching Capacity
Spectrum-2 Switch Chip
Non-blocking, wire-speed Layer 3 Routing

Power:

1+1 hot-swappable power supplies and N+1 hot-swappable fans
AC Input: 100-127/200-240 V, 50/60 Hz
Frequency: 50-60Hz
Input range: 100-264 AC
Input current 2.9-4.5A

Physical/Environmental:

Weight: Net weight: 11.1kg (24.5lb)
Regular and Reverse Airflow Models
Size: 1.72" x 16.84" x 22" (44mm x 428mm x 559mm)
Temperature: Operating 0°C to 40°C (32°F to 104°F)
Humidity: Operating: 5% to 85% (non-condensing)

General:

Open Networking
1U form factor for flexible installation
Mounting Rails (included)

Datasheet

Spectrum-2 based Top-of-Rack Ethernet switches [[Download \(/datasheet/datasheet_SSE-SN3000.pdf\)](#),]

Operating System / NOS & Support

The SSE-SN3700C switch comes with preloaded Cumulus Linux OS.

Mandatory Software Service & Support SKUs sold separately; can be found under parts list below.

Parts List

Certain products may not be available in your region
