



More details here

# GPU SuperServer AS -5126GS-TNRT2

DP AMD 5U System with 10 PCIe GPUs via PLX switch

## Key Applications

AI / Deep Learning, 3D Rendering Farm, Visualization / Simulation, High Performance Computing, Multimedia/Digital Content creation,

## Key Features

- Dual processor(s) AMD EPYC™ 9005/9004 Series Processors up to 500W with air cooling;
- Supports up to 24 DIMM slots, 6400 MT/s 6TB DDR5 in 1DPC (Please check System Memory Section for detail);
- Total of 13 PCIe 5.0 x16 FHFL slots;
- Supports up to 10 double-width PCIe GPU accelerator cards (8 double-width GPU is recommended, other 5 slots reserved for Networking scale out);
- Flexible networking with AIOM support;
- Dual front hot-swap 2.5" SATA + 8 front hot-swap 2.5" NVMe drive bays;
- Total of 6x 2700W Redundant (3+3 or 4+2) Titanium Level power supplies 3+3 under 8100 Watt, 4+2 under 10,800 Watt (Power supply redundancy based on configuration and application load);



|                          |                                                                                                                                                                                                                                                                            |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Form Factor              | 5U Rackmount<br>Enclosure: 438 x 222.5 x 786.1mm (17.2" x 8.75" x 31")<br>Package: 720 x 440 x 1080mm (28.34" x 17.32" x 42.51")                                                                                                                                           |
| Processor                | Dual processor(s)<br>AMD EPYC™ 9005/9004 Series Processors<br>Up to 192C/384T                                                                                                                                                                                              |
| GPU                      | Max GPU Count: Up to 10 double-width GPUs<br>Supported GPU: NVIDIA PCIe: H100 NVL, H200 NVL (141GB), L40S, NVIDIA RTX PRO™ 6000 Blackwell Server Edition<br>CPU-GPU Interconnect: PCIe 5.0 x16 Switch Dual-Root<br>GPU-GPU Interconnect: NVIDIA® NVLink™ Bridge (optional) |
| System Memory            | Slot Count: 24 DIMM slots<br>Max Memory (1DPC): Up to 6TB 6400MT/s ECC DDR5 RDIMM (AMD EPYC™ 9005 Series Processor)<br>Max Memory (1DPC): Up to 6TB 4800MT/s ECC DDR5 RDIMM (AMD EPYC™ 9004 Series Processor)                                                              |
| Drive Bays Configuration | Default: Total 10 bays <ul style="list-style-type: none"> <li>• 2 front hot-swap 2.5" SATA drive bays</li> <li>• 8 front hot-swap 2.5" NVMe drive bays</li> </ul> M.2: 1 M.2 PCIe 3.0 x4 NVMe slot (M-key)                                                                 |
| Expansion Slots          | Default <ul style="list-style-type: none"> <li>• 13 PCIe 5.0 x16 FHFL slots</li> </ul> Option A <ul style="list-style-type: none"> <li>• 11 PCIe 5.0 x16 FHFL slots</li> </ul>                                                                                             |
| On-Board Devices         | SATA: SATA (6Gbps)<br>Network Connectivity: 2 RJ45 10GbE                                                                                                                                                                                                                   |
| Input / Output           | LAN: 1 RJ45 1 GbE Dedicated BMC LAN port<br>2 RJ45 10 GBASE-T LAN ports<br>USB: 2 ports(rear)<br>Video: 1 VGA port                                                                                                                                                         |



|                       |                                                                                                                                                                                                                                                                                                                            |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System Cooling        | Fans: Up to 10 heavy duty fans with optimal fan speed control                                                                                                                                                                                                                                                              |
| Power Supply          | 6x 2700W Redundant (4 + 2) Titanium Level (96%) power supplies                                                                                                                                                                                                                                                             |
| System BIOS           | BIOS Type: AMI 64MB SPI Flash EEPROM                                                                                                                                                                                                                                                                                       |
| Management            | SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!                                                                                                                  |
| PC Health Monitoring  | CPU: 7 +1 Phase-switching voltage regulator<br>Monitors for CPU Cores, Chipset Voltages, Memory<br>FAN: Fans with tachometer monitoring<br>Pulse Width Modulated (PWM) fan connectors<br>Status monitor for speed control<br>Temperature: Monitoring for CPU and chassis environment<br>Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 100 lbs (45.3 kg)<br>Net Weight: 65.5 lbs (29.7 kg)<br>Available Color: Black Front & Silver Body                                                                                                                                                                                                    |
| Operating Environment | Operating Temperature: 10°C to 35°C (50°F to 95°F)<br>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)<br>Operating Relative Humidity: 8% to 90% (non-condensing)<br>Non-operating Relative Humidity: 5% to 95% (non-condensing)                                                                                  |
| Motherboard           | <a href="#">Super H14DSG-O-CPU</a>                                                                                                                                                                                                                                                                                         |
| Chassis               | CSE-528G2TS-R000NDP                                                                                                                                                                                                                                                                                                        |