

GPU A+ Server AS -4124GO-NART

DP AMD System with NVIDIA HGX A100 8-GPU

Key Applications



HPC, AI / Deep Learning,

Key Features

- Supports NVIDIA® HGX™ A100 8-GPU
Highest GPU communication using NVIDIA® NVLINK™ v3.0 + NVIDIA® NVSwitch™
NICs for GPUDirect RDMA (1:1 GPU Ratio)
Supports HGX A100 8-GPU 40GB (HBM2) or 80GB (HBM2e);
- Dual AMD EPYC™ 7003/7002 Series Processors
(The latest AMD EPYC™ 7003 Series Processor with AMD 3D V-Cache™ Technology requires BIOS version 2.3 or newer);
- 8TB Registered ECC DDR4 3200MHz SDRAM in 32 DIMMs;
- 8 PCIe 4.0 x16 via PCIe switch;
1 PCIe 4.0 x 16 LP and 1 PCIe 4.0 x8 LP via CPUs; AIOM Support;
- 6 Hot-swap 2.5" NVMe drive bays
(4 via PCIe switch, 2 via CPU)
Up to 10 U.2 NVMe 2.5" drives available with an optional 4 drive bays at rear of system;



Form Factor	4U Rackmount Enclosure: 446 x 174 x 900mm (17.6" x 6.9" x 35.4") Package: 695 x 750 x 1140mm (27.4" x 29.5" x 44.9")
Processor	Dual Socket SP3 AMD EPYC™ 7002/7003 Series Processors
GPU	Max GPU Count: 8 onboard GPUs Supported GPU: NVIDIA SXM: HGX A100 8-GPU (80GB)
System Memory	Slot Count: 32 DIMM slots
Drive Bays Configuration	Default: Total 6 bays • 6 front hot-swap 2.5" NVMe drive bays Option A: Total 10 bays • 6 front hot-swap 2.5" NVMe drive bays • 4 rear hot-swap 2.5" NVMe* drive bays (*NVMe support may require additional storage controller and/or cables, please see the optional parts list for details)
Expansion Slots	Default • 1 PCIe 4.0 x16 (in x16) LP slot • 1 PCIe 4.0 x8 (in x8) LP slot • 8 PCIe 4.0 x16 (in x16) via PCIe switch slots
On-Board Devices	SATA: SATA (6Gbps) Network Connectivity: Ethernet IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 ports(front) Video: 1 VGA port(Front)



System Cooling	Fans: Up to 4 hot-swap 11.5K RPM heavy duty Fan(s)
Power Supply	4x 2200W Redundant (3 + 1) Platinum Level (94%) power supplies
System BIOS	BIOS Type: AMI 256MB SPI Flash ROM
Management	Supermicro Server Manager (SSM); Supermicro Power Manager (SPM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); KVM with dedicated LAN ; IPMI 2.0; Watch Dog
PC Health Monitoring	CPU: 4+1 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory FAN: Fans with tachometer monitoring Pulse Width Modulated (PWM) fan connectors Status monitor for speed control Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 225 lbs (102.1 kg) Net Weight: 166 lbs (75.3 kg) Available Color: Black Front & Silver Body
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super H12DGO-6
Chassis	CSE-438G