

CloudDC A+ Server AS -2014CS-TR

2U CloudDC with 4 PCI-E 4.0 x16 slots + 2 PCIe 4.0 AIOM

Key Applications

Cloud Computing, content Delivery Network (CDN), Deep Learning Inferencing,
Financial Services, Private Cloud, Networking Security Appliance,

Key Features

- Single AMD EPYC™ 7002/7003 Series Processor
(The latest AMD EPYC™ 7003 Series Processor with AMD 3D V-Cache™ Technology requires BIOS version 2.3 or newer);
- 16 DIMMs; up to 4TB 3DS ECC DDR4-3200MHz RDIMM/LRDIMM;
- 4 PCIe 4.0 x16 FH, 10.5" L slots
2 AIOM slots for flexible networking (1 x8 AIOM slot + 1 x16 AIOM slot);
- 12 Hot-swap 3.5" SATA3/SAS3/NVMe drive bays
12 SATA3 by default
or 8 SATA3 + 4NVMe via optional cables
or 12 SAS3 via optional SAS kit
Optional dual 2.5" peripheral drive bays via rear drive bay kits
M.2 Interface: 2 PCIe 4.0 x4
M.2 Form Factor: 2242, 2260, 2280, 22110
M.2 Key: M-key;




Form Factor	2U Rackmount Enclosure: 437 x 89 x 648mm (17.2" x 3.5" x 25.5") Package: 679 x 296 x 876mm (26.7" x 11.4" x 34.5")
Processor	Single Socket SP3 AMD EPYC™ 7002/7003 Series Processors
GPU	Max GPU Count: Up to 2 double-width or 4 single-width GPUs Supported GPU: NVIDIA PCIe: A10, A100, A16, A2, A40, RTX A4000, RTX A5000, RTX A6000, T4 AMD PCIe: Instinct™ MI100, Instinct™ MI210
System Memory	Slot Count: 16 DIMM slots Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM/LRDIMM
Drive Bays Configuration	Default: Total 12 bays • 12 front hot-swap 3.5" SATA drive bays Option A: Total 12 bays • 8 front hot-swap 3.5" SATA drive bays • 4 front hot-swap 3.5"/2.5" NVMe* drive bays Option B: Total 12 bays • 12 front hot-swap 3.5" SAS* drive bays (*NVMe/SAS support may require additional storage controller and/or cables, please see the optional parts list for details)
Expansion Slots	PCI-Express (PCIe) Configuration: Default • 4 PCIe 4.0 x16 FH/10.5"L slots • 2 PCIe 4.0 x16 AIOM slots (OCP 3.0 compatible) M.2: 2 M.2 PCIe 4.0 x4 slots (M-key 2242/2260/2280/22110)
On-Board Devices	SATA: SATA (6Gbps) Network Connectivity: Ethernet IPMI: Support for Intelligent Platform Management Interface v.2.0 IPMI 2.0 with virtual media over LAN and KVM-over-LAN support
Input / Output	LAN: 1 RJ45 1 GbE Dedicated BMC LAN port USB: 2 USB 3.0 ports(rear) Video: 1 VGA port Serial: 1 COM port(rear)



Slot	Description
0 - 11	3.5" Hot-Swap SATA3/SAS3/NVMe** Drive Bays

*SAS3 support requires additional parts in optional parts list
 **NVMe support requires additional cables parts in optional parts list for slots 0 ~ 3



Drive Bay	Description
12 - 15	Optional 2.5" Hot-Swap SATA3/SAS3 Drive Bays***

Slot	Description	Slot	Description
1	PCI-E 4.0 x16 Slot (FH, 10.5")	1	PCI-E 4.0 x16 Slot (FH, 10.5")
2	PCI-E 4.0 x16 Slot (FH, 10.5")	2	PCI-E 4.0 x16 Slot (FH, 10.5")
3	PCI-E 4.0 x16 Slot (FHH), (Optional)**	3	PCI-E 4.0 x16 Slot (FHH), (Optional)**
4	PCI-E 4.0 x16 AOM Slot	4	PCI-E 4.0 x8 AOM Slot (NCSI)

* Contact support for configurations requiring optional PCIe slots to be enabled
 ** Full redundancy based on configuration and application load
 *** Requires additional parts in optional parts list

System Cooling	Fans: Up to 3 middle cooling 80x80x38mm Fan(s)
Power Supply	2x 920W Redundant (1 + 1) Platinum Level (94%) power supplies
System BIOS	BIOS Type: AMI 256MB SPI Flash EEPROM
Management	Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); KVM with dedicated LAN ; IPMI 2.0; Watch Dog; OOB Management Package (SFT-OOB-LIC)
PC Health Monitoring	CPU: 4+1 Phase-switching voltage regulator Monitors for CPU Cores, Chipset Voltages, Memory FAN: 3 fans with tachometer status monitoring, Status monitoring for speed control Pulse Width Modulated (PWM) fan connectors Temperature: Monitoring for CPU and chassis environment Thermal Control for fan connectors
Dimensions and Weight	Weight: Gross Weight: 59 lbs (26.76 kg) Net Weight: 33 lbs (15 kg) Available Color: Black front & sliver body
Operating Environment	RoHS Compliant Operating Temperature: 10°C to 35°C (50°F to 95°F) Non-operating Temperature: -40°C to 60°C (-40°F to 140°F) Operating Relative Humidity: 8% to 90% (Non-Condensing) Non-operating Relative Humidity: 5% to 95% (Non-Condensing)
Motherboard	Super H12SSW-AN6
Chassis	CSE-LA26TS-R1K23AWP1