



More details here

# Twin SuperServer SYS-220TP-HTTR

2U 4-node TwinPro with 6 2.5" SATA drives per node and dual 10GbE

## Key Applications

High Performance Computing, Hyper-Converged Infrastructure, Big Data / Big Science,


## Key Features

- Four **hot-pluggable** systems (nodes) in a 2U form factor. Each node supports the following;;
- Dual Socket P+ (LGA-4189) 3rd Generation Intel® Xeon® Scalable Processors;
- Intel® C621A Chipset;
- 16 DIMMs, Up to 4TB 3DS ECC DDR4-3200 LRDIMM/RDIMM;
- 2 PCIe 4.0 x16 (LP), 1 PCIe 4.0 x8 (with M.2 adapter installed for support 2 NVME up to 22x80 mm);
- Intel® X710 Dual port 10GBase-T LAN onboard;
- 6x 2.5" hot-swap SATA drive bays;
- 4 heavy duty 8cm PWM fans with optimal fan speed control (Per System);
- Two 2200W redundant power supplies with PMBus;
- SATA (6Gbps); 6 slots per node; RAID 0, 1, 5, 10 support. ASPEED AST2600 BMC, 2 USB, VGA. RoT;




|                          |                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Form Factor              | 2U Rackmount<br>Enclosure: 438 x 88 x 730mm (17.25" x 3.47" x 28.75")<br>Package: 622 x 254 x 1143mm (24.5" x 10" x 45")              |
| Processor                | Dual Socket P+ (LGA-4189)<br>3rd Gen Intel® Xeon® Scalable processors<br>Up to 32C/64T; Up to 48MB Cache per CPU                      |
| System Memory            | Slot Count: 16 DIMM slots<br>Max Memory (2DPC): Up to 4TB 3200MT/s ECC DDR4 RDIMM                                                     |
| Drive Bays Configuration | Default: Total 6 bays <ul style="list-style-type: none"> <li>• 6 front hot-swap 2.5" SATA drive bays</li> </ul>                       |
| Expansion Slots          | Default <ul style="list-style-type: none"> <li>• 2 PCIe 4.0 x16 LP slots</li> </ul>                                                   |
| On-Board Devices         | SATA: SATA (6Gbps)<br>Network Connectivity: 2 RJ45 10GBASE-T with Intel® X710-AT2                                                     |
| Input / Output           | LAN: 1 RJ45 1 GbE Dedicated BMC LAN port<br>USB: 2 USB 3.0 ports(rear)<br>Video: 1 VGA port<br>DOM: 2 SuperDOM (Disk on Module) ports |

(Front View – System)



(Rear View – System)



|                       |                                                                                                                                                                                                                                                                                                                         |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| System Cooling        | Fans: Up to 4x 8cm heavy duty fans with optimal fan speed control<br>Air Shroud: 4 Air Shrouds                                                                                                                                                                                                                          |
| Power Supply          | 1x 2200W Redundant Titanium Level (96%) power supply                                                                                                                                                                                                                                                                    |
| System BIOS           | BIOS Type: AMI 32MB SPI Flash EEPROM                                                                                                                                                                                                                                                                                    |
| Management            | SuperCloud Composer®; Supermicro Server Manager (SSM); Supermicro Update Manager (SUM); Supermicro SuperDoctor® 5 (SD5); Super Diagnostics Offline (SDO); Supermicro Thin-Agent Service (TAS); SuperServer Automation Assistant (SAA) New!                                                                              |
| PC Health Monitoring  | CPU: 5 Phase-switching voltage regulator<br>Monitors for CPU Cores, Chipset Voltages, Memory<br>FAN: Fans with tachometer monitoring<br>Pulse Width Modulated (PWM) fan connectors<br>Status monitor for speed control<br>Temperature: Monitoring for CPU and chassis environment<br>Thermal Control for fan connectors |
| Dimensions and Weight | Weight: Gross Weight: 90 lbs (40.9 kg)<br>Net Weight: 72 lbs (32.7 kg)<br>Available Color: Black front & silver body                                                                                                                                                                                                    |
| Operating Environment | Operating Temperature: 10°C to 35°C (50°F to 95°F)<br>Non-operating Temperature: -40°C to 60°C (-40°F to 140°F)<br>Operating Relative Humidity: 8% to 90% (non-condensing)<br>Non-operating Relative Humidity: 5% to 95% (non-condensing)                                                                               |
| Motherboard           | <a href="#">Super X12DPT-PT6</a>                                                                                                                                                                                                                                                                                        |
| Chassis               | CSV-217HQ+-R2K20BP4                                                                                                                                                                                                                                                                                                     |