



Model Number	AIB-MX11/12 AIB-MX21/22	AIB-MX13 AIB-MX23	AIB-MO22 AIB-MO32	AIB-MN32 AIB-MN42	AIB-SO21 AIB-SO31	AIB-SN31 AIB-SN41
Module Compatibility	NVIDIA Jetson AGX Orin 32GB NVIDIA Jetson AGX Orin 64GB	NVIDIA Jetson AGX Orin 32GB NVIDIA Jetson AGX Orin 64GB	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB
AI Performance	200 TOPS 275 TOPS	200 TOPS 275 TOPS	20 TOPS 40 TOPS	70 TOPS 100 TOPS	20 TOPS 40 TOPS	70 TOPS 100 TOPS
Storage	64GB eMMC 5.1	64GB eMMC 5.1	1 x M.2 M-Key 2242 (NVMe 128GB built-in)		1 x M.2 M-Key 2242 (NVMe 128GB built-in)	
Display	1 x HDMI 2.0 Type A	1 x HDMI 2.0 Type A	1 x HDMI 2.0 Type A		1 x HDMI 2.0 Type A	
TPM	TPM v2.0 (optional)	TPM v2.0 (optional)	–		–	
RTC	With super capacitor, battery (optional)		With super capacitor, battery (optional)		With super capacitor, battery (optional)	
Audio	Line-out / Line-in / Mic (optional with daughter board)		Line-out / Line-in / Mic (optional with daughter board)		Line-out / Line-in / Mic (optional with daughter board)	
Camera Input	1 x 16-Lane MIPI Expansion Connector (120-Pin)	1 x 16-Lane MIPI Expansion Connector	1 x 8-Lane MIPI Expansion Connector (120-Pin)		2 x 4-Lane MIPI CSI-2 22-Pin Connector	
LAN	1 x RJ-45 GbE port, 1 x RJ-45 10GbE port	1 x RJ-45 GbE port, 1 x RJ-45 10GbE port	2 x RJ-45 GbE Ports		1 x RJ-45 GbE Port	
PoE Interface	2 or 4 x RJ-45 GbE PSE (IEEE 802.3af compliant, Power Output 15W/Port)*		Not supported		Not supported	
USB	2 x USB 3.2 Gen1 Type A, 1 x OTG Type-C, 1 x USB 3.2 Gen2 Type-C	2 x USB 3.2 Gen1 Type A, 1 x OTG Type-C, 1 x USB 3.2 Gen2 Type-C	2 x USB 3.2 Gen2 Type A (supports up to 10Gbps shared) 1 x OTG Type-C		2 x USB 3.2 Gen2 Type A (supports up to 10Gbps shared) 1 x OTG Type-C	
I/O Interfaces	2 x UART, 1 x UART (Debug only) 1 x RS-232, 1 x CAN 2.0b (isolation; support CAN FD), 2 x I ² C, 1 x I ² S, 1 x SPI, 5 x GPIO, 2 x 3VDC/0.5A, 3 x 5VDC/0.5A, 1 x 12VDC/0.5A, 1 x USB 2.0, 1 x microSD Card Slot	2 x I ² C, 1 x SPI, 1 x SPI, 1 x I ² C, 2 x 3VDC/0.5A, 3 x 5VDC/0.5A, 1 x 12VDC/0.5A, 1 x USB 2.0, 1 x microSD Card Slot	5 x GPIO, 1 x SPI, 1 x I ² C, 2 x 3VDC/0.5A, 3 x 5VDC/0.5A, 1 x 12VDC/0.5A, 1 x USB 2.0, 1 x microSD Card Slot	1 x UART (Debug Only), 1 x RS-232, 1 x CAN (isolation; support CAN FD), 1 x RS-422/485 (2-in-1), 1 x RS-422/485 (2-in-1), 2 x CAN 2.0b (isolation; support CAN FD)	5 x GPIO, 1 x I ² C, 1 x I ² S, 1 x RS-232, 1 x RS-422/485, 1 x CAN (isolation; support CAN FD)	5 x GPIO, 1 x I ² C, 1 x I ² S, 1 x RS-232, 1 x RS-422/485, 1 x UART (Debug Only), 1 x CAN (isolation; support CAN FD)
Expansion	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in) 1 x microSD Card Slot	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2280 (supports NVMe, PCIe x4 Gen4) 1 x microSD Card Slot	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2280 (supports NVMe, PCIe x2 Gen3) 1 x microSD Card Slot
MISC. Function	1 x Power / 1 x Recovery / 1 x Reset Button	1 x Power / 1 x Recovery / 1 x Reset Button	1 x Recovery / 1 x Reset Button		1 x Power / 1 x Recovery / 1 x Reset Button	
Power Consumption	Idle: 10.5 W/Full Loading: 111* W Idle: 12 W/Full Loading: 132* W	Idle: 6.655 W/Full Loading: 52.25* W Idle: 6.9 W/Full Loading: 72.25* W	Idle: 7 W Full Loading: 28.6* W	Idle: 7.3 W Full Loading: 39* W	Idle: 5.4 W Full Loading: 27.08* W	Idle: 5.7 W Full Loading: 37.5* W
Power Input / Connector	DC-in 9 to 36 VDC / 4-Pin DC Jack Power Connector	DC-in 9 to 36 VDC / 4-Pin DC Jack Power Connector	DC-in 12 to 24 VDC / 4-Pin DC Jack Power Connector		DC-in 12 to 24VDC / 2-Pin Terminal Block	
Dimension (W x D x H)	176 x 132 x 57.32 mm (6.93 x 5.19 x 2.26")	131 x 120 x 62.9 mm (5.16 x 4.72 x 2.47 in)	120 x 100 x 57.54 mm (4.73 x 3.94 x 2.27 in)		87.4 x 67.4 x 28.45 mm (3.43 x 2.65 x 1.12 in)	
Net Weight	0.980 kg (2.161 lb) w/ Fansink	0.701 kg (1.54 lb) w/ Fansink	0.195 kg (0.43 lb)		0.144 kg (0.32 lb) w/ Fansink	
Vibration	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis		1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	
Shock	10 G, IEC 60068-2-27, half sine, 11 ms duration	10 G, IEC 60068-2-27, half sine, 11 ms duration	10 G, IEC 60068-2-27, half sine, 11 ms duration		10 G, IEC 60068-2-27, half sine, 11 ms duration	
Temperature	Operating Temp. : -25°C ~ +80°C Storage Temp. : -40°C ~ +85°C	Operating Temp. : -25°C ~ +80°C Storage Temp. : -40°C ~ +85°C	Operating Temp. : -25°C ~ +80°C Storage Temp. : -40°C ~ +85°C		Operating Temp. : -25°C ~ +80°C Storage Temp. : -40°C ~ +85°C	
Humidity	95% @ 40°C (104°F) (non-condensing)	95% @ 40°C (104°F) (non-condensing)	95% @ 40°C (104°F) (non-condensing)		95% @ 40°C (104°F) (non-condensing)	
Software Support	Linux (Support Jetpack 5.0 above)	Linux (Support Jetpack 5.0 above)	Linux (Support Jetpack 5.0 above)		Linux (Support Jetpack 5.0 above)	
Certification	CE / FCC Class A / UKCA	CE / FCC Class A / UKCA	CE / FCC Class A / UKCA		CE / FCC Class A / UKCA	



Model Number	AIE-PN33-2PSE / AIE-PN33-4PSE	AIE-PN43-2PSE / AIE-PN43-4PSE	AIE-PO23-6USB / AIE-PO33-6USB	AIE-PN33-6USB / AIE-PN43-6USB
Module Compatibility	NVIDIA Jetson Orin NX 8GB	NVIDIA Jetson Orin NX 16GB	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB
AI Performance	70 TOPS	100 TOPS	20/40 TOPS	70/100 TOPS
Storage	1 x M.2 NVMe M-Key 2242 (128GB built-in)		1 x M.2 NVMe M-Key 2242 (128GB built-in)	
Display	1 x HDMI 2.0 Type A		1 x HDMI 2.0 Type A	
TPM	Not supported		Not supported	
RTC	Not supported		Not supported	
Audio	Not supported		Not supported	
LAN	2 x RJ-45 GbE Ports		2 x RJ-45 GbE Ports	
PoE Interface	2/4 x RJ-45 GbE PSE (IEEE 802.3af compliant, Power Output 15W per Port)	2/4 x RJ-45 GbE PSE (IEEE 802.3af compliant, Power Output 15W per Port)	Not supported	
USB	2 x USB 3.2 Gen2 Type A (supports up to 10Gbps shared) 1 x OTG Type-C		2 x USB 3.2 Gen2 Type A (support up to 10 Gbps shared) 4 x USB 3.2 Gen1 Type A 1 x OTG Type-C	
I/O Interfaces	5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 1 x RS-422/485, 1 x CAN (isolation; support CAN FD)		5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 1 x RS-422/485, 1 x CAN (isolation; support CAN FD)	5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 1 x RS-422/485, 1 x CAN (isolation; support CAN FD)
Expansion	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in)
MISC. Function	1 x Power / 1 x Recovery / 1 x Reset Button		1 x Power / 1 x Recovery / 1 x Reset Button	
Power Consumption	Idle: 6.413 W Full Loading: 89.13* W	Idle: 6.413 W Full Loading: 89.13* W	Idle: 6.413 W Full Loading: 47.13* W	Idle: 6.413 W Full Loading: 47.13* W
Power Input / Connector	DC-in 12-24VDC / 4-Pin DC Jack Power Connector		DC-in 12-24VDC / 4-Pin DC Jack Power Connector	
Dimension (W x D x H)	270 x 195 x 80 mm (10.63 x 7.67 x 3.15 in)		270 x 195 x 80 mm (10.63 x 7.67 x 3.15 in)	
Mounting	Wall Mount (optional) / Din Rail (optional)		Wall Mount (optional) / Din Rail (optional)	
Net Weight	TBC kg (TBC lb)		TBC kg (TBC lb)	
Vibration	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis		1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	
Shock	10 G, IEC 60068-2-27, half sine, 11 ms duration		10 G, IEC 60068-2-27, half sine, 11 ms duration	
Temperature	Operating Temp. : -25°C ~ +55°C (13°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (40°F ~ +185°F)		Operating Temp. : -25°C ~ +55°C (13°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (40°F ~ +185°F)	
Humidity	95% @ 40°C (104°F) (non-condensing)		95% @ 40°C (104°F) (non-condensing)	
Software Support	Linux (Support Jetpack 5.0 above)		Linux (Support Jetpack 5.0 above)	
Certification	CE / FCC Class A / UKCA		CE / FCC Class A / UKCA	



Model Number	AIE-PO23-3M / AIE-PO33-3M	AIE-PN33-3M / AIE-PN43-3M	AIE-PX11/AIE-PX12	AIE-PX21/AIE-PX22
Module Compatibility	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB	NVIDIA Jetson AGX Orin 32GB	NVIDIA Jetson AGX Orin 64GB
AI Performance	20/40 TOPS	70/100 TOPS	200 TOPS	275 TOPS
Storage	1 x M.2 NVMe M-Key 2242 (128GB built-in)		64GB eMMC 5.1	
Display	1 x HDMI 2.0 Type A		1 x HDMI 2.0 Type A	
TPM	Not supported		TPM v2.0 (optional)	
RTC	Not supported		Not supported	
Audio	Not supported		Not supported	
LAN	2 x RJ-45 GbE Ports		1 x RJ-45 GbE, 1 x RJ-45 10GbE	
PoE Interface	Not supported		2/4 x RJ-45 GbE PSE (IEEE 802.3af compliant, Power Output 15W/Port)*	2/4 x RJ-45 GbE PSE (IEEE 802.3af compliant, Power Output 15W/Port)*
USB	2 x USB 3.2 Gen2 Type A (support up to 10 Gbps shared) 1 x OTG Type-C		2 x USB 3.2 Gen1 Type A, 1 x USB 2.0 (DB-15), 1 x OTG Type-C, 1 x USB 3.2 Gen2 Type-C	
I/O Interfaces	5 x GPIO, 1 x SPI, 5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 1 x RS-422/485, 1 x CAN (isolation; support CAN FD)		2 x I ² C, 1 x SPI, 5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 2 x CAN 2.0b (isolation; support CAN FD) 1 x microSD Card Slot, 1 x CoS (optional)	2 x I ² C, 1 x SPI, 5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 2 x CAN 2.0b (isolation; support CAN FD) 1 x microSD Card Slot, 1 x CoS (optional)
Expansion	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in) 2 x M.2 M-Key 2280 (PCIe) 1 x microSD Card Slot	1 x M.2 B-Key 3042/3052 (LTE/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in) 2 x M.2 M-Key 2280 (PCIe) 1 x microSD Card Slot	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in) 1 x microSD Card Slot	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in) 1 x microSD Card Slot
MISC. Function	1 x Power / 1 x Recovery / 1 x Reset Button		1 x Power / 1 x Recovery / 1 x Reset Button	
Power Consumption	Idle: 6.413 W Full Loading: 43.13* W	Idle: 6.413 W Full Loading: 43.13* W	Idle: 7.5 W Full Loading: 109* W	Idle: 8 W Full Loading: 130* W
Power Input / Connector	DC-in 12-24VDC / 4-Pin DC Jack Power Connector		DC-in 9 to 36 VDC / 4-Pin DC Jack Power Connector	
Dimension (W x D x H)	270 x 195 x 80 mm (10.63 x 7.67 x 3.15 in)		270 x 195 x 80 mm (10.63 x 7.67 x 3.15 in)	
Mounting	Wall Mount (optional) / Din Rail (optional)		Wall Mount (optional) / Din Rail (optional)	
Net Weight	TBC kg (TBC lb)		4.3 kg (9.48 lb)	
Vibration	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis		1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	
Shock	10 G, IEC 60068-2-27, half sine, 11 ms duration		10 G, IEC 60068-2-27, half sine, 11 ms duration	
Temperature	Operating Temp. : -25°C ~ +55°C (13°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (40°F ~ +185°F)		Operating Temp. : -25°C ~ +55°C (13°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (40°F ~ +185°F)	
Humidity	95% @ 40°C (104°F) (non-condensing)		95% @ 40°C (104°F) (non-condensing)	
Software Support	Linux (Support Jetpack 5.0 above)		Linux (Support Jetpack 5.0 above)	
Certification	CE / FCC Class A / UKCA		CE / FCC Class A / UKCA	



Model Number	AIE-PX13	AIE-PX23	AIE-PO22 AIE-PO32	AIE-PN32 AIE-PN42	AIE-CO21 AIE-CO31	AIE-CN31 AIE-CN41
Module Compatibility	NVIDIA Jetson AGX Orin 32GB	NVIDIA Jetson AGX Orin 64GB	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB	NVIDIA Jetson Orin Nano 4GB/8GB	NVIDIA Jetson Orin NX 8GB/16GB
AI Performance	200 TOPS	275 TOPS	20 TOPS 40 TOPS	70 TOPS 100 TOPS	20 TOPS 40 TOPS	70 TOPS 100 TOPS
Storage	64GB eMMC 5.1		1 x M.2 M-Key 2242 (NVMe 128GB built-in)		1 x M.2 M-Key 2242 (128GB built-in)	
Display	1 x HDMI 2.0 Type A		1 x HDMI 2.0 Type A		1 x HDMI 2.0 Type A	
TPM	Not supported		Not supported		Not supported	
RTC	Not supported		Not supported		With super capacitor, battery (optional)	
Audio	Line-out/Line-in/Mic (optional with daughter board)		Not supported		Not supported	
LAN	1 x RJ-45 GbE, 1 x RJ-45 10GbE		2 x RJ-45 GbE Ports		1 x RJ-45 GbE Port	
PoE Interface	Not supported		Not supported		Not supported	
USB	2 x USB 3.2 Gen1 Type A, 1 x USB 2.0 (DB-15), 1 x OTG Type-C, 1 x USB 3.2 Gen2 Type-C		2 x USB 3.2 Gen2 Type A (supports up to 10Gbps shared) 1 x OTG Type-C		2 x USB 3.2 Gen2 Type A (supports up to 10Gbps shared) 1 x OTG Type-C	
I/O Interfaces	2 x I ² C, 1 x SPI, 5 x GPIO, 2 x UART 1 x RS-232, 1 x RS-422/485 (2-in-1) 2 x CAN 2.0b (isolation; support CAN FD) 1 x microSD Card Slot		5 x GPIO, 1 x UART, 1 x I ² C, 1 x RS-232, 1 x RS-422/485 (2-in-1), 1 x CAN (isolation; support CAN FD), 1 x microSD Card Slot		5 x GPIO, 1 x UART, 1 x I ² C, 1 x CAN (isolation; support CAN FD)	
Expansion	1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2280 (supports NVMe; PCIe x4 Gen4) 1 x microSD Card Slot		1 x M.2 B-Key 3042/3052 (LTE/4G/5G) 1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in; PCIe x4 Gen3)		1 x M.2 E-Key 2230 (WiFi/BT) 1 x M.2 M-Key 2242 (NVMe 128GB built-in; PCIe x4 Gen3)	
MISC. Function	1 x Power / 1 x Recovery / 1 x Reset Button		1 x Power / 1 x Recovery / 1 x Reset Button		1 x Power / 1 x Recovery / 1 x Reset Button 1 x CAN 2.0b with isolation	
Power Consumption	Idle: 5.5 W Full Loading: 51.08* W	Idle: 5.9 W Full Loading: 71* W	Idle: 5.5 W Full Loading: 25.95* W	Idle: 6.4 W Full Loading: 35.45* W	Idle: 3.4 W Full Loading: 25.08* W	Idle: 3.7 W Full Loading: 35.5* W
Power Input / Connector	DC-in 9 to 36 VDC / 4-Pin DC Jack Power Connector		DC-in 12 to 24VDC / 4-Pin DC Jack Power Connector		DC-in 12 to 24 VDC / 2-Pin Terminal Block	
Dimension W x D x H)	270 x 195 x 80 mm (10.63 x 7.67 x 3.15 in)		137.6 x 125 x 71.5 mm (5.41 x 4.92 x 2.81 in)		130 x 90.2 x 72 mm (5.11 x 3.55 x 2.83 in)	
Mounting	Wall Mount (optional) / Din Rail (optional)		Wall Mount (optional) / Din Rail (optional)		Wall Mount (optional) / Din Rail (optional)	
Net Weight	4.2 kg (9.7 lb)		1.36 kg (3 lb)		0.927 kg (2.044 lb)	
Vibration	1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis		1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis		1 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis	
Shock	10 G, IEC 60068-2-27, half sine, 11 ms duration		10 G, IEC 60068-2-27, half sine, 11 ms duration		10 G, IEC 60068-2-27, half sine, 11 ms duration	
Temperature	Operating Temp. : -25°C ~ +55°C (+131°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (+40°F ~ +185°F)		Operating Temp. : -25°C ~ +55°C (+131°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (+40°F ~ +185°F)		Operating Temp. : -25°C ~ +55°C (+131°F ~ +131°F) with 0.5 m/s air flow Storage Temp. : -40°C ~ +85°C (+40°F ~ +185°F)	
Humidity	95% @ 40°C (104°F) (non-condensing)		95% @ 40°C (104°F) (non-condensing)		95% @ 40°C (104°F) (non-condensing)	
Software Support	Linux (Support Jetpack 5.0 above)		Linux (Support Jetpack 5.0 above)		Linux (Support Jetpack 5.0 above)	
Certification	CE / FCC Class A / UKCA		CE / FCC Class A / UKCA		CE / FCC Class A / UKCA	