

GCMS Parameter Table Layouts

4 November 2025



Contents

GCMS Parameter Table Layouts.....	7
Chapter 1: About IPM Mastercard Parameter Extract.....	10
IPM MPE definitions.....	13
Using the CurrentParm.txt file.....	13
Annotation of data element attributes.....	13
Applying the IPM MPE updates.....	15
Applying an inactive IPM MPE update record.....	15
Applying an active IPM MPE update record.....	17
Header and trailer records for the IPM MPE update file.....	18
Header and trailer records for the IPM MPE full file replacement.....	20
Mastercard reserved tables.....	22
Empty table processing.....	22
Expanding the IPM MPE file.....	22
Expand table IP0040T1 records.....	23
Expand table IP0041T1 records.....	23
Build table IP0090T1 default agreements.....	23
Build table IP0091T1 default agreements.....	24
IPM MPE compressed table layouts.....	25
Table IP0036T1: Default Business Service.....	25
Table IP0040T1: Issuer Account Range.....	27
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	38
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	40
IPM MPE non-compressed table layouts.....	41
Table IP0000T1: keys.....	41
Table IP0001T1: Run Control Options.....	43
Table IP0002T1: Valid Run Option Overrides.....	44
Table IP0003T1: Run Control Errors.....	45
Table IP0006T1: Data Element Attributes.....	46
Table IP0007T1: Data Element Subfield Attributes.....	48
Table IP0008T1: PDS Attributes.....	49
Table IP0009T1: PDS Subfield Attributes.....	51
Table IP0011T1: Expanded MTI/Function/Reason Code.....	52
Table IP0012T1: Life Cycle Time Frame.....	54
Table IP0015T1: IPM Error Messages.....	56
Table IP0016T1: Brand Product.....	57
Table IP0017T1: Currency Codes.....	59

Table IP0018T1: Mastercard Product Graduation Parameters.....	60
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters.....	62
Table IP0020T1: PAN Mapping Product Code Pairs.....	65
Table IP0023T1: MDS Routing Member ID.....	67
Table IP0025T1: Message Reason Codes.....	68
Table IP0026T1: Parameter Print Controls.....	68
Table IP0027T1: Run Control Default Override Values.....	70
Table IP0028T1: Country Codes.....	71
Table IP0029T1: Edit Override Table.....	74
Table IP0030T1: Interchange Amount Restriction	74
Table IP0031T1: Addendum Data.....	75
Table IP0033T1: IPM Module Names and Version Numbers.....	78
Table IP0034T1: Processing Code Group.....	79
Table IP0035T1: Settlement Service Selection BIN Data.....	80
Table IP0036T1: Default Business Service.....	81
Table IP0037T1: Selection Criteria Data.....	82
Table IP0039T1: Selection Criteria Account Range.....	85
Table IP0040T1: Issuer Account Range.....	86
Table IP0041T1: Acquirer Reference ID.....	97
Table IP0045T1: Cash Disbursement Fee.....	98
Table IP0048T1: Settlement Service.....	99
Table IP0050T1: Settlement Service Selection Criteria.....	101
Table IP0052T1: Interchange Fee Group.....	102
Table IP0053T1: Interchange Fee Type.....	106
Table IP0054T1: Retrieval Fee.....	108
Table IP0056T1: Member Business Service Arrangements.....	109
Table IP0057T1: Interchange Override Fee Group.....	111
Table IP0058T1: QPS and Contactless Chargeback Protection Amounts.....	113
Table IP0059T1: Timeliness Code.....	114
Table IP0060T1: Timeliness Holiday.....	116
Table IP0064T1: Transaction Function Group Code Table.....	118
Table IP0069T1: Global Currency.....	118
Table IP0070T1: Common Area	119
Table IP0071T1: Chip Liability Shift Country Exclusions.....	120
Table IP0072T1: Expanded Member ID Master.....	120
Table IP0074T1: IFC Gaming.....	125
Table IP0075T1: Acceptor Business Codes (MCCs).....	126
Table IP0076T1: Mastercard Assigned IDs.....	129
Table IP0087T1: Masked Business Services and Interchange Rate Designators.....	130
Table IP0088T1: Masked Business Services.....	131
Table IP0089T1: Business Service Switches.....	133

Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	133
Table IP0092T1: Transaction Functions Requiring Business Service Processing.....	135
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	136
Table IP0093T1: Intracountry Business Service Override.....	137
Table IP0094T1: Geographic Restrictions for Card Program Identifier Business Service Arrangement, and IRD.....	138
Table IP0095T1: Acceptor Business Program Restrictions.....	140
Table IP0096T1: Card Program Identifier and Product Restrictions.....	141
Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement.....	142
Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement.....	143
Table IP0099T1: Transaction Currency Qualification.....	146
Table IP0105T1: New Product Code Mapping.....	147
Table IP0106T1: Issuer Participation Activation/Deactivation.....	148
Table IP0128T1: Tiered Debit U.S. and Territories.....	149
Table IP0132T1: Anonymous Prepaid Countries.....	149
Table IP0137T1: Brazil Flex Mapping.....	150
Table IP0138T1: Authentication Enforcement.....	151
Table IP0142T1: Business Service Selection Enforcement.....	153
Table IP0144T1: Processing Code and Transaction Type Indicator.....	154
Table IP0304T1: Transaction Type Identifier and AB Code.....	155
Tables IP1100T1: Mandatory and Not Allowed Field Edits.....	156
Table IP1102T1: Mandatory Field Edits for Elements Used in the Selection Process.....	157
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier.....	158
Tables IP7XXXT1 through IP9XXXT1: reserved tables.....	167
Chapter 2: About optimized current parameter file layouts.....	168
File structure comparison.....	171
Annotation of data element attributes.....	176
IPM optimized current parameters file layouts.....	177
Table IP0000T1: keys.....	177
Table IP0001T1: Run Control Options.....	179
Table IP0002T1: Valid Run Option Overrides.....	181
Table IP0003T1: Run Control Errors.....	182
Table IP0005T1: KSDS Optimized Keys.....	183
Table IP0006T1: Data Element Attributes.....	183
Table IP0006T2: Data Element Attribute Overrides.....	185
Table IP0007T1: Data Element Subfield Attributes.....	187
Table IP0008T1: PDS Attributes.....	189

Table IP0009T1: PDS Subfield Attributes.....	191
Table IP0010T1: RRDS Optimized Keys	192
Table IP0011T1: Expanded MTI/Function/Reason Code.....	193
Table IP0012T1: Life Cycle Time Frame.....	195
Table IP0015T1: IPM Error Messages.....	198
Table IP0016T1: Brand Product.....	199
Table IP0017T1: Currency Codes.....	202
Table IP0018T1: Mastercard Product Graduation Parameters.....	202
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters.....	204
Table IP0020T1: PAN Mapping Product Code Pairs.....	208
Table IP0023T1: MDS Routing Member ID.....	211
Table IP0025T1: Message Reason Codes.....	211
Table IP0026T1: Parameter Print Controls.....	212
Table IP0027T1: Run Control Default Override Values.....	214
Table IP0028T1: Country Codes.....	215
Table IP0029T1: Edit Override Table.....	218
Table IP0030T1: Interchange Amount Restriction	219
Table IP0031T1: Addendum Data.....	220
Table IP0033T1: IPM Module Names and Version Numbers.....	223
Table IP0034T1: Processing Code Group	225
Table IP0035T1: Settlement Service Selection BIN Data.....	225
Table IP0037T1: Selection Criteria Data.....	226
Table IP0039T1: Selection Criteria Account Range	228
Table IP0040T1: Issuer Account Range	229
Table IP0041T1: Acquirer Reference ID.....	242
Table IP0045T1: Cash Disbursement.....	243
Table IP0048T1: Settlement Service	244
Table IP0050T1: Settlement Service Selection Criteria.....	246
Table IP0052T1: Interchange Fee Group	247
Table IP0053T1: Interchange Fee Type.....	250
Table IP0054T1: Retrieval Fee	255
Table IP0056T1: Member Business Service Arrangements	256
Table IP0057T1: Interchange Override Fee Group.....	257
Table IP0058T1: QPS and Contactless Chargeback Protection Amounts.....	259
Table IP0059T1: Timeliness Code	260
Table IP0060T1: Timeliness Holiday	262
Table IP0064T1: Transaction Function Group Codes.....	264
Table IP0069T1: Global Currency.....	265
Table IP0070T1: Common Area.....	266
Table IP0071T1: Chip Liability Shift Country Exclusions.....	267
Table IP0072T1: Expanded Member ID Master.....	268
Table IP0074T1: IFC Gaming	273

Table IP0075T1: Acceptor Business Codes (MCCs).....	274
Table IP0076T1: Mastercard Assigned IDs.....	277
Table IP0087T1: Masked Business Services and Interchange Rate Designators.....	278
Table IP0088T1: Masked Business Services.....	280
Table IP0089T1: Business Service Switches.....	281
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	282
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	284
Table IP0092T1: Transaction Functions Requiring Business Service Processing.....	285
Table IP0093T1: Intracountry Business Service Override.....	286
Table IP0094T1: Geographic Restrictions for Card Program Identifier and Business Service Arrangement/IRD.....	287
Table IP0095T1: Acceptor Business Program Restrictions for Card Program Identifier and Business Service Arrangement, and IRD.....	289
Table IP0096T1: Product Restrictions for Card Program Identifier and Business Service Arrangement, and IRD.....	290
Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement.....	291
Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement.....	293
Table IP0099T1: Transaction Currency Qualification.....	295
Table IP0105T1: New Product Code Mapping.....	296
Table IP0106T1: Issuer Participation Activation/Deactivation.....	297
Table IP0128T1: Tiered Debit U.S. and Territories.....	298
Table IP0132T1: Anonymous Prepaid Countries.....	299
Table IP0137T1: Brazil Flex Mapping.....	300
Table IP0138T1: Authentication Enforcement.....	301
Table IP0142T1: Business Service Selection Enforcement.....	303
Table IP0144T1: Processing Code and Transaction Type Indicator.....	304
Table IP0304T1: Transaction Type Identifier and AB Code.....	305
Table IP0970T1: key for IP0097T1 (Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement).....	306
Tables IP1100T1 and IP1100T2: mandatory field edits.....	307
Table IP2000T1 and IP2000T2: valid values/ranges	309
Table IP4090T1: Account Range ID.....	318
Table IP4191T1: BIN Pointer.....	322
Table IP5200T1: key for IP0052T1 (Interchange Fee Group).....	323
Table IP5300T1: key for IP0053T1 (Interchange Fee Type).....	324
Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements).....	325
Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group).....	326

Notices.....	328
--------------	-----

GCMS Parameter Table Layouts

This document contains technical information and specifications for customers to understand the system functionality and to process transactions through the Dual Message Clearing System.

Audience

This document is for acquirers, issuers, processors, and Network Enablement Partners.

Product

Clearing, using the Integrated Product Messages (IPM) format, moves transaction information from the customer to the Dual Message Clearing System, or from the Dual Message Clearing System to the customer.

Offline clearing is the practice of sending transaction information in a clearing file after a previous authorization, if applicable. The IPM format provides the vehicle for delivery of these messages. The sending customer places messages into a clearing file and sends this transaction data for clearing to the Dual Message Clearing System seven days a week, 24 hours a day.

Table 1: Details

Metadata	Value
Audience	Acquirer, Issuer, Network Enablement Partner, Processor
Product	Dual Message Clearing System
Region	Global
Type	Technical specification guide
Publish Date	4 November 2025

Table 2: Summary of changes

Description of Change	Source	Where to look
Routine document maintenance	N/A	Throughout

Description of Change	Source	Where to look
Enhancements for future growth:	<i>GLB 11362.3 25.Q4 IPM</i>	Table IP0144T1: Processing Code and Transaction Type Indicator
Added new Table IP0144T1: Processing Code and Transaction Type Indicator for non-compressed and optimized table layouts	<i>Mastercard Parameter Extract Table Updates, Release 25.Q4</i>	Table IP0144T1: Processing Code and Transaction Type Indicator
Removed Table IP2212T1: Payment Type and IRD Validation for non-compressed and optimized table layouts		Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier
Expanded Table IP0072T1: Expanded Member ID Master for non-compressed and optimized table layouts		Table IP2000T1 and IP2000T2: valid values/ranges
- Modifying the layout for the optimized versions of: - Table IP0010T1: RRDS Optimized Keys: Relative record number, Record count fields - Table IP4090T1: Account Range ID: Table IP0040T1 relative record number, Table IP0040T1 data length, Table IP0049T1 relative record number, Table IP0049T1 data length, Table IP0051T1 relative record number, Table IP0051T1 data length, Table IP0090T1 relative record number, Table IP0090T1 data length, Table IP0093T1 relative record number, Table IP0093T1 data length fields - Table IP419T1: BIN Pointer: Table 0041T1 relative record number, Table IP0041T1 data length, Table IP0043T1 relative record number, Table IP0043T1 data length, Table IP009T1		Table IP0072T1: Expanded Member ID Master
		Table IP0072T1: Expanded Member ID Master
		Table IP0010T1: RRDS Optimized Keys
		Table IP4090T1: Account Range ID
		Table IP4191T1: BIN Pointer
		Table IP5200T1: key for IP0052T1 (Interchange Fee Group)
		Table IP5300T1: key for IP0053T1 (Interchange Fee Type)
		Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements)
		Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group)

Description of Change	Source	Where to look
- relative record number, Table IP009T1 data length fields – Table IP5200T1: key for IP0052T1 (Interchange Fee Group): Relative record number, ICA entry length fields – Table IP5300T1: key for IP0053T1 (Interchange Fee Type): Relative record number start, Relative record number end fields – Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements): Relative record number, ICA entry length fields – Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group): Relative record number start, Relative record number end fields • Optimized layout for Table IP0010T1: RRDS Optimized Keys: Record count field		
Added:	<i>AP/EUR/LAC/MEA 11242</i>	Table IP0028T1: Country Codes
• Mastercard Transaction Calculator Indicator row and updated Filler row for Table IP0028T1: Issuer Account Range for non-compressed and optimized table layouts.	<i>Introducing Mastercard One Credential, Release 25.Q4</i>	Table IP0028T1: Country Codes
• Mastercard One Credential Participation Indicator row and updated Filler row for Table IP0040T1: Issuer Account Range for compressed, non-compressed, and optimized table layouts.	<i>US 11423 Introducing Mastercard One Credential, Release 25.Q4</i>	Table IP0040T1: Issuer Account Range
		Table IP0040T1: Issuer Account Range

Chapter 1 About IPM Mastercard Parameter Extract

This section provides the layout of the parameters used in the IPM Mastercard Parameter Extract (MPE).

IPM MPE definitions.....	13
Using the CurrentParm.txt file.....	13
Annotation of data element attributes.....	13
Applying the IPM MPE updates.....	15
Applying an inactive IPM MPE update record.....	15
Applying an active IPM MPE update record.....	17
Header and trailer records for the IPM MPE update file.....	18
Header and trailer records for the IPM MPE full file replacement.....	20
Mastercard reserved tables.....	22
Empty table processing.....	22
Expanding the IPM MPE file.....	22
Expand table IP0040T1 records.....	23
Expand table IP0041T1 records.....	23
Build table IP0090T1 default agreements.....	23
Build table IP0091T1 default agreements.....	24
IPM MPE compressed table layouts.....	25
Table IP0036T1: Default Business Service.....	25
Table IP0040T1: Issuer Account Range.....	27
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	38
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	40
IPM MPE non-compressed table layouts.....	41
Table IP0000T1: keys.....	41
Table IP0001T1: Run Control Options.....	43
Table IP0002T1: Valid Run Option Overrides.....	44
Table IP0003T1: Run Control Errors.....	45
Table IP0006T1: Data Element Attributes.....	46
Table IP0007T1: Data Element Subfield Attributes.....	48
Table IP0008T1: PDS Attributes.....	49
Table IP0009T1: PDS Subfield Attributes.....	51
Table IP0011T1: Expanded MTI/Function/Reason Code.....	52
Table IP0012T1: Life Cycle Time Frame.....	54

Table IP0015T1: IPM Error Messages.....	56
Table IP0016T1: Brand Product.....	57
Table IP0017T1: Currency Codes.....	59
Table IP0018T1: Mastercard Product Graduation Parameters.....	60
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters.....	62
Table IP0020T1: PAN Mapping Product Code Pairs.....	65
Table IP0023T1: MDS Routing Member ID.....	67
Table IP0025T1: Message Reason Codes.....	68
Table IP0026T1: Parameter Print Controls.....	68
Table IP0027T1: Run Control Default Override Values.....	70
Table IP0028T1: Country Codes.....	71
Table IP0029T1: Edit Override Table.....	74
Table IP0030T1: Interchange Amount Restriction	74
Table IP0031T1: Addendum Data.....	75
Table IP0033T1: IPM Module Names and Version Numbers.....	78
Table IP0034T1: Processing Code Group.....	79
Table IP0035T1: Settlement Service Selection BIN Data.....	80
Table IP0036T1: Default Business Service.....	81
Table IP0037T1: Selection Criteria Data.....	82
Table IP0039T1: Selection Criteria Account Range.....	85
Table IP0040T1: Issuer Account Range.....	86
Table IP0041T1: Acquirer Reference ID.....	97
Table IP0045T1: Cash Disbursement Fee.....	98
Table IP0048T1: Settlement Service.....	99
Table IP0050T1: Settlement Service Selection Criteria.....	101
Table IP0052T1: Interchange Fee Group.....	102
Table IP0053T1: Interchange Fee Type.....	106
Table IP0054T1: Retrieval Fee.....	108
Table IP0056T1: Member Business Service Arrangements.....	109
Table IP0057T1: Interchange Override Fee Group.....	111
Table IP0058T1: QPS and Contactless Chargeback Protection Amounts.....	113
Table IP0059T1: Timeliness Code.....	114
Table IP0060T1: Timeliness Holiday.....	116
Table IP0064T1: Transaction Function Group Code Table.....	118
Table IP0069T1: Global Currency.....	118
Table IP0070T1: Common Area	119
Table IP0071T1: Chip Liability Shift Country Exclusions.....	120
Table IP0072T1: Expanded Member ID Master.....	120
Table IP0074T1: IFC Gaming.....	125

Table IP0075T1: Acceptor Business Codes (MCCs).....	126
Table IP0076T1: Mastercard Assigned IDs.....	129
Table IP0087T1: Masked Business Services and Interchange Rate Designators.....	130
Table IP0088T1: Masked Business Services.....	131
Table IP0089T1: Business Service Switches.....	133
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	133
Table IP0092T1: Transaction Functions Requiring Business Service Processing.....	135
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	136
Table IP0093T1: Intracountry Business Service Override.....	137
Table IP0094T1: Geographic Restrictions for Card Program Identifier Business Service Arrangement, and IRD.....	138
Table IP0095T1: Acceptor Business Program Restrictions.....	140
Table IP0096T1: Card Program Identifier and Product Restrictions.....	141
Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement.....	142
Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement.....	143
Table IP0099T1: Transaction Currency Qualification.....	146
Table IP0105T1: New Product Code Mapping.....	147
Table IP0106T1: Issuer Participation Activation/Deactivation.....	148
Table IP0128T1: Tiered Debit U.S. and Territories.....	149
Table IP0132T1: Anonymous Prepaid Countries.....	149
Table IP0137T1: Brazil Flex Mapping.....	150
Table IP0138T1: Authentication Enforcement.....	151
Table IP0142T1: Business Service Selection Enforcement.....	153
Table IP0144T1: Processing Code and Transaction Type Indicator.....	154
Table IP0304T1: Transaction Type Identifier and AB Code.....	155
Tables IP1100T1: Mandatory and Not Allowed Field Edits.....	156
Table IP1102T1: Mandatory Field Edits for Elements Used in the Selection Process.....	157
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier.....	158
Tables IP7XXXT1 through IP9XXXT1: reserved tables.....	167

The IPM Mastercard Parameter Extract (MPE) contains all of the parameters that the Clearing Optimizer uses to edit the member's clearing files and run the IPM utilities.

If there is no data for a specific table, there will be no table entry. In the event that there are no changes to the IPM MPE for a given day, the file will still be sent to the members containing a 0000 table as well as the header and trailer.

IPM MPE definitions

A **MPE table** is a unit of the IPM MPE that provides data on a particular set of parameters, which affect the Clearing Optimizer and Clearing System programs. For example, the Merchant Category Codes (MCC) table provides data related to the Acceptor Business Codes (MCCs) that Mastercard supports. The IPM MPE contains many tables.

A **MPE record** is a unit of an IPM MPE table that provides data on a particular parameter. For example, within the Data Element Attributes table, each record provides data on a single data element.

Each MPE record represents a single **row** of the MPE table in the customer's Parameter Master File.

The **key** for each MPE record is a combination of Effective Timestamp, Active-Inactive Code, Copy Member (formerly known as "copybook"), and the fields uniquely identify the record data. (For example, within the Data Element Attributes Table, the Data Element Number is essential to identify a particular record.)

Using the CurrentParm.txt file

The CurrentParm.txt file is created during the optimization process. It contains only the currently active records from the IPM MPE File. This is a line sequential text file that can be easily displayed since it contains no binary or packed decimal data.

The table layouts in this chapter apply to both the CurrentParm.txt file located in the C:\Pre-edit 9999.9\InputFiles\OneDayFile folder for AutoEdit users (the version number 9999.9 refers to the current version number) and the file created in PRIP0350, STEP040, SYS211, for mainframe users. The IPM MPE file and the CurrentParm.txt file layouts are identical.

Annotation of data element attributes

Following is a listing of notation convention layouts used in the IPM MPE.

The following notation conventions describe the attributes of data elements:

Table 3: Data representation attributes

Notation	Description
a	alphabetic characters A-Z and a-z (Note that Country and Country Subdivision must be capitalized)
an	alphabetic (A-Z and a-z) and numeric (digits 0-9) characters
ans	alphabetic (A-Z and a-z), numeric (digits 0-9) and special characters (including spaces)
as	alphabetic (A-Z and a-z) and special characters (including spaces)
b	binary All binary data elements are constructed of bit-strings that have lengths that are an integral number of eight-bit bytes. No binary data element has a length of less than eight bits (one byte). b-8 indicates a fixed-length binary field of eight characters (eight bytes, 64 bits)
n	numeric digits 0-9
ns	numeric digits 0-9 and special characters (including spaces)
s	special characters Special characters are any non-numeric or non-alphabetic characters (for example, @, #, &, and \$), including spaces.

The following notations describe date and time data element subfields:

Table 4: Date and time attributes

Notation	Description
MM	month (two digits; 01-12)
DD	day (two digits; 01-31)
YY	year (last two digits of calendar year; 00-99)
YYYY	year (four digits of calendar year: 1900-1999; 2000-2099)
hh	hour (two digits; 00-23)
mm	minute (two digits; 00-59)

Notation	Description
ss	second (two digits; 00-59))

The following notations describe the data length attributes:

Table 5: Data length attributes

Notation	Description
-digit(s)	Fixed length in number of positions. Example: n-3 indicates a three-position numeric data element. Example: an-10 indicates a 10-position alphanumeric data element.
...digit(s)	Variable length, with maximum number of positions specified. Example: n...1 indicates a variable-length numeric data element of 1–11 digits. Example: an...25 indicates a variable-length alphanumeric data element of 1–25 positions.

Applying the IPM MPE updates

The Clearing Optimizer software provides an automated mechanism for applying table updates from the IPM MPE file. However, customers may choose to create their own internal software for applying updates. The following examples will help customers understand how to apply the IPM MPE table updates.

NOTE: An IPM MPE update record containing an "inactive" code must be applied only if its key exactly matches the key of an existing IPM MPE record starting at position 12.

Applying an inactive IPM MPE update record

Each IPM MPE table has a unique key that consists of several contiguous fields. The keys for all of the tables are defined in table IP0000T1 Keys, which is the first table in the IPM MPE file. Customers must ensure that they only apply an "inactive" record if they have an existing record with an identical key starting at position 12. Since positions 1-11 contain the effective date/time and the active/inactive code, these positions will not match an existing entry and can be disregarded. Following are some examples:

Example 1: The IPM MPE update file contains an "inactive" record for table IP0072T1 Expanded Member ID Master.

Determine the key for table IP0072T1 by locating the Subject Table ID field in table IP0000T1 Keys for table IP0072T1. This field indicates that the Subject Table Key Start is position 1, and the Subject Table Key Length is 30. This means that the key to table IP0072T1 is in positions 1-30. Disregard positions 1-11 of the key since they represent the effective date/time and the active/inactive indicator. The IPM MPE update record for table IP0072T1 must exactly match positions 12-30 of an existing IPM MPE record before it can be applied.

IPM MPE update record:

2005020514**IP0072T100000001234**NN100 1...

Existing IPM MPE record:

2001070114**AIP0072T100000001234**NN100 1...

In this example, there is an exact match starting at position 12 in the key of the update record when compared with the key of the existing record, as shown in the bolded characters. As a result, the table IP0072T1 record for this member ID is now inactive.

Example 2: The IPM MPE update file contains an "inactive" record for table IP0040T1 Account Range.

Determine the key for table IP0072T1 by locating the Subject Table ID field in table IP0000T1 Keys for table IP0040T1. This field indicates that the Subject Table Key Start is position 1, and the Subject Table Key Length is 41. This means that the key to table IP0040T1 is in positions 1-41. Disregard positions 1-11 of the key since they represent the effective date/time and the active/inactive indicator. The IPM MPE update record for table IP0040T1 must exactly match positions 12-41 of an existing MPE record before it can be applied.

IPM MPE update record:

2005052814**IP0040T13540080000000000000MSI**35400899999999999999MSI01

Existing IPM MPE records:

2005050514AIP0040T13540080000000000000CIR35400899999999999999CIR02

2005050514**AIP0040T13540080000000000000MSI**35400899999999999999MSI01

In this example, there is an exact match from positions 12-41 in the key of the update record compared with the key of the existing record, as shown in the bolded characters. As a result, the table IP0040T1 record for this combination of Issuer Account Range: Low and GCMS Product ID is now inactive.

This example shows two entries that were active for this combination of Issuer Account Range: Low and GCMS Product ID. One for the CIR GCMS Product ID, and the other for the MSI GCMS Product ID. The IPM MPE update record containing an "inactive" status applies **ONLY** to the entry with the MSI GCMS Product ID. This means only the MSI GCMS Product ID is inactive. The Issuer Account Range is active for the CIR GCMS Product ID, because there was an exact match.

If an MPE update record contains an "inactive" code, and there is **NO** existing IPM MPE record with a key that matches the key of the update record starting at position 12, then disregard the IPM MPE update record. This condition may occur infrequently, but it is possible.

Example: The IPM MPE update file contains an "inactive" record for table IP0040T1 Account Range.

Determine the key for table IP0040T1 by locating the Subject Table ID field in table IP0000T1 Keys for table IP0040T1. This field indicates that the Subject Table Key Start is in position 1, and the Subject Table Key Length is 41. This means that the key to table IP0040T1 is in positions 1-41. Disregard positions 1-11 of the key, since they represent the effective date/time and the active/inactive indicator. The IPM MPE update record for table IP0040T1 must exactly match positions 12-41 of an existing IPM MPE record before it can be applied.

IPM MPE update record:

2005052814**IP0040T16666080000000000000MSI**66660899999999999999MSI01

Existing IPM MPE record:

2005050514**AIP0040T16666080000000000000CIR**66660899999999999999CIR02

There is **NOT** an exact match starting at position 12 in the key of the update record compared with the key of the existing record. Although the issuer Account Range: Low matches the existing record, the GCMS Product ID does not. In this example the update record for the MSI GCMS Product ID, and the existing record for the CIR GCMS Product ID are different as shown in the bolded characters. In other words, this IPM MPE update record should be ignored since it does not match any existing IPM MPE record.

Applying an active IPM MPE update record

If an IPM MPE update record contains an "active" code, and its key exactly matches the key of an existing IPM MPE record starting at position 12, then the IPM MPE update record replaces the existing IPM MPE record since it contains the most current effective date/time.

Example: The IPM MPE update file contains an "active" record for table IP0072T1 Expanded Member ID Master.

Determine the key for table IP0072T1 by locating the Subject Table ID field in table IP0000T1 Keys for table IP0072T1. This field indicates that the Subject Table Key Start is position 1, and the Subject Table Key Length is 30. This means that the key for table IP0072T1 is in positions 1-30. Disregard positions 1-11 of the key since they represent the effective date/time and the active/inactive indicator. The IPM MPE update record for table IP0072T1 must exactly match positions 12-30 of an existing IPM MPE record before it can be applied.

IPM MPE update record:

2005072514**AIP0072T100000001111**NN101...

Existing IPM MPE record:

2005072014**AIP0072T100000001111**NY101...

In this example, there is an exact match starting at position 12 in the key of the update record compared with the key of an existing record as shown in the bolded characters. So the IPM MPE

update record becomes the correct record to use for member ID 1111 since it has the most recent effective date/time.

If an IPM MPE update record contains an "active" code, and there is **NO** existing IPM MPE record whose key matches the key of the update record starting at position 12, then the IPM MPE update record represents a new piece of information, and is added as an active record.

Example: The IPM MPE update file contains an "active" record for table IP0040T1 Account Range.

Determine the key for table IP0040T1 by locating the Subject Table ID field in table IP0000T1 Keys for table IP0040T1. This field indicates that the Subject Table Key Start is position 1, and the Subject Table Key Length is 41. This means that the key to table IP0040T1 is in positions 1-41. Disregard positions 1-11 of the key, since they represent the effective date/time and the active/inactive indicator. In other words, the IPM MPE update record for table IP0040T1 must exactly match positions 12-41 of an existing IPM MPE record before it can be applied.

IPM MPE update record:

2005052814A**IP0040T15412340000000000000**CIR54123499999999999999CIR02

Existing IPM MPE record:

2005050514A**IP0040T15412340000000000000**MCG54123499999999999999MCC01

In this example, there is **NOT** an exact match starting at position 12 in the key of the update record compared with the key of an existing record. Although the issuer Account Range: Low matches the existing record, the GCMS Product ID does not. In this example the update record for the CIR GCMS Product ID, and the existing record for the MCG GCMS Product ID are different as shown in the bolded characters. In other words, the IPM MPE update record is new, and should be added.

Header and trailer records for the IPM MPE update file

Each IPM MPE Daily Update file begins with a File Header record. It is followed by applicable table update records. At the end of each group of updates for a particular table, an Intermediate Trailer record is presented that indicates the total number of preceding update records for the specified table. At the end of the file, is a File Trailer record. The File Header, Intermediate File Trailer, and File Trailer record layouts are documented below

Following is the record layout for the first record in each IPM MPE Daily Update file.

Table 6: File header record for IPM MPE daily update

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-15	an-15	Constant value: "UPDATE FILE" followed by four spaces.

Field Name	Positions	Attribute	Comments and Values
Date created	16-23	n-8	Date the IPM MPE Daily Update file was generated. Format: YYYYMMDD.
Time created	24-27	n-4	Time the IPM MPE Daily Update file was generated. Format: HHMM.
Filler	28-30	an-3	Spaces.

Following is the record layout for the Intermediate Trailer Record. One of these records appears in the IPM MPE Daily Update File following the update records for each table.

For example, if the IPM MPE Daily Update file contains 10 update records for table IP1234T1 and 4 update records for table IP5678T1, this Intermediate Trailer record would appear as follows:

- After the 10 update records for table IP1234T1, containing "IP1234T1" in the **Table ID** field and a value of 00000010 in the **Number of Records** field.
- After the 4 update records for table IP5678T1, containing "IP5678T1" in the **Table ID** field and a value of 00000004 in the **Number of Records** field.

Table 7: Intermediate trailer record layout

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-15	an-15	Constant value: "TRAILER RECORD" followed by one space.
Table ID	16-23	an-8	The table number to which the preceding IPM MPE update records refer.
Filler	24-25	an-2	Space.
Number of records	26-33	n-8	The number of preceding update records for the specified Table ID, right-justified, with leading zeros.
Filler	34-80	an-47	Spaces.

Following is the record layout for the last record in each IPM MPE Daily Update file.

Table 8: File trailer record for IPM MPE daily update

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-15	an-15	Constant value: "TRAILER RECORD" followed by one space.
Table ID	16-24	an-9	Constant value: "TABLEZZZZ".
Filler	25	an-1	Space.
Number of records	26-33	n-8	The total number of records in this IPM MPE Daily Update file, right-justified, with leading zeros. This count includes the File Header record, all of the table update records, all of the Intermediate Trailer records, and this File Trailer record.
Filler	34-80	an-47	Spaces.

Header and trailer records for the IPM MPE full file replacement

Each IPM MPE full file replacement file begins with a file header record. It is followed by detail entries for each table. At the end of each group of table entries, an intermediate trailer record is presented that indicates the total number of preceding table entries for the specified table. At the end of the file is a file trailer record. The file header, intermediate file trailer, and file trailer record layouts are documented below.

Following is the record layout for the first record in each IPM MPE full file replacement file.

Table 9: File header record for IPM MPE full file replacement

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-17	an-17	Constant value: "REPLACEMENT FILE" followed by one space.
Module Identifier	18-31	an-14	Module that generated the IPM MPE.
Filler	32-45	an-14	Constant value: "CURRENT-DATE=" followed by one space.

About IPM Mastercard Parameter Extract
Header and trailer records for the IPM MPE full file replacement

Field Name	Positions	Attribute	Comments and Values
Date created	46-54	an-9	Date the IPM MPE Full File Replacement was generated. Format: MM/DD/YY followed by one space.
Filler	55-61	an-7	Constant value: "TIME =" followed by one space.
Time created	62-69	an-8	Time the IPM MPE Full File Replacement was generated. Format: HH:MM:SS
Filler	70-80	an-11	Spaces.

Following is the record layout for the intermediate trailer record. One of these records appears in the IPM MPE full file replacement file following the detail table records for each table.

For example, if the IPM MPE full file replacement file contains 200 table records for table IP1234T1 and 50 table records for table IP5678T1, this intermediate trailer record would appear as follows:

- After the 200 table records for table IP1234T1, containing "IP1234T1" in the **Table ID** field and a value of 00000200 in the **Number of Records** field
- After the 50 table records for table IP5678T1, containing "IP5678T1" in the **Table ID** field and a value of 00000050 in the **Number of Records** field.

Table 10: Intermediate trailer record for IPM MPE full file replacement

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-15	an-15	Constant value: "TRAILER RECORD" followed by one spaces.
Table ID	16-23	an-8	The table number to which the preceding IPM MPE table records refer.
Filler	24-25	an-2	Spaces.
Number of records	26-33	n-8	The number of preceding table records for the specified Table ID, right-justified, with leading zeros.
Filler	34-80	an-47	Spaces.

Following is the record layout for the last record in each IPM MPE Full File Replacement file.

Table 11: File trailer record for IPM MPE full file replacement

Field Name	Positions	Attribute	Comments and Values
IPM MPE File Identifier	1-15	an-15	Constant value: "TRAILER RECORD" followed by one space.
Table ID	16-24	an-9	Constant value: "TABLEZZZZ".
Filler	25	an-1	Space.
Number of records	26-33	n-8	The total number of records in this IPM MPE Full File Replacement file, right-justified, with leading zeros. This count includes the File Header record, all of the table update records, all of the Intermediate Trailer records, and this File Trailer record.
Filler	34-80	an-47	Spaces.

Mastercard reserved tables

In preparation for future use, Mastercard has reserved all IPM MPE tables beginning with IP7XXXT1 through IP9XXXT1. This series of tables will be used in the future as needed for enhancements to the GCMS system.

Empty table processing

If there is no data available for a given table, the table will not be included in the IPM MPE. There also will not be an entry shown in the IP0000T: Keys, for this empty table.

Expanding the IPM MPE file

Within the Clearing Optimizer and Utilities software, the following process expands the IPM MPE tables that are delivered in a compressed format.

Convert date and table ID

Convert and expand the **Effective Timestamp** field for all tables except table IP0000T1. The compressed format is Julian format (YYDDD). The expanded format is the Gregorian format (YYYYMMDD).

In addition, expand the **Table ID** field for all tables except table IP0000T1. The compressed format is a three-digit code. Compare the three-digit **Table ID** of the compressed table to the **Table Sub Indicator** field in IP0000T1. Replace the compressed table ID with the corresponding value from the **Subject Table ID** field in the relevant table IP0000T1 record.

Expand table IP0040T1 records

Mastercard compresses table IP0040T1 records by removing the 'Filler' (Central Site use only) field at the end of each record in order to reduce the IPM MPE size.

To expand the table IP0040T1 records, zero-fill the 'Filler' (Central Site use only) field at the end of each record. As a result, the expanded IP0040T1 records will match the table maximum record length as defined for IP0040T1 in table IP0000T1.

Refer to the section titled "Compressed table layouts" for more information on the compressed format for table IP0040T1.

When expanding an IPM MPE full file replacement, complete this process **before** building the table IP0090T1 and IP0091T1 default agreements.

Expand table IP0041T1 records

Mastercard only compresses the effective timestamp and table ID for table IP0041T1 as we currently do for all tables. As a result, the expanded IP0041T1 records will have the length of the table maximum record length as defined for IP0041T1 in table IP0000T1.

Build table IP0090T1 default agreements

Perform this task **only** when table IP0036T1 is present in an IPM MPE full file replacement file.

Table IP0090T1 of the compressed IPM MPE full file replacement file does not contain interregional and intraregional business service participation records for default business service agreements. Whenever table IP0036T1 is present in an IPM MPE full file Replacement file, the table IP0090T1 records for the default interregional and intraregional business service participation must be generated for each relevant issuer account range, as described in the following steps.

Step 1: For each table IP0040T1 record in the IPM MPE full file replacement file, search for a matching record in table IP0036T1. To match, compare the table IP0040T1 Region and Card Program Identifier fields to the table IP0036T1 To Region (for interregional business services), Region (for intraregional business services), and Card Program Identifier fields:

- If the Region field and Card Program Identifier field in IP0040T1 match the To Region and Card Program Identifier fields in IP0036T1, generate an interregional agreement (Business Service Arrangement Type Code = 1) record for table IP0090T1.
- If the Region field and Card Program Identifier field in IP0040T1 match the Region and Card Program Identifier fields in IP0036T1, generate an intraregional agreement (Business Service Arrangement Type Code = 2) record for table IP0090T1.

Step 2: When a match is found in table IP0036T1, write an IP0090T1 record using a combination of fields from tables IP0040T1 and IP0036T1.

Step 3: Repeat steps 1 and 2 to build table IP0090T1 default agreements for the account ranges in table IP9000T1 (if present). For this step, use table IP9000T1 in place of table IP0040T1.

Note: Table IP9000T1 is for use by the Clearing Optimizer and Utilities software to process transactions that were authorized by MDS before the issuer account range was converted from the Cirrus network to Visa's PLUS network. The issuer account ranges in table IP9000T1 are not present in table IP0040T1 to help acquirers understand that new authorization requests for these issuer account ranges must no longer be sent to MDS. The IPM MPE table layout for table IP9000T1 is identical to the table layout for IP0040T1.

Upon completion of this process, the IP0090T1 records (for Business Service Arrangement Types 1 and 2 created from tables IP0036T1 and IP0040T1) must be merged with the existing IP0090T1 records (for Business Service Arrangement Types 3, 4, and 8) included in the IPM MPE full file replacement file. The sort order should be ascending on Table ID, ascending on IP0090T1 key (defined in IP0000T1), and descending by Effective Timestamp.

Build table IP0091T1 default agreements

Perform this task **only** when table IP0036T1 is present, which occurs only in an IPM MPE full file replacement file.

Table IP0091T1 of the compressed IPM MPE full file replacement file does not contain interregional and intraregional business service participation records for default business service agreements. Whenever table IP0036T1 is present in an IPM MPE full file replacement file, the table IP0091T1 records for the default interregional and intraregional business service participation must be generated for each relevant acquiring BIN, as described in this section.

For each table IP0041T1 record in the IPM MPE full file replacement file, search for a matching record in table IP0036T1. To match, compare the table IP0041T1 Region and Card Program Identifier fields to the table IP0036T1 From Region (for interregional business services), Region (for intraregional business services), and Card Program Identifier fields:

- If the Region field and Card Program Identifier field in IP0041T1 match the From Region and Card Program Identifier fields in IP0036T1, generate an interregional agreement (Business Service Arrangement Type Code = 1) record for table IP0091T1.
- If the Region field and Card Program Identifier field in IP0041T1 matches Region and Card Program Identifier fields in IP0036T1, generate an intraregional agreement (Business Service Arrangement Type Code = 2) record for table IP0091T1.

When a match is found in table IP0036T1, write an IP0091T1 record using a combination of fields from tables IP0041T1 and IP0036T1.

Upon completion of this process, the IP0091T1 records (for Business Service Arrangement Types 1 and 2 created from tables IP0036T1 and IP0041T1) must be merged with the existing IP0091T1 records (for Business Service Arrangement Types 3, 4, and 8) included in the IPM MPE full file replacement file. The sort order should be ascending on Table ID, ascending on IP0091T1 key (defined in IP0000T1), and descending by Effective Timestamp.

IPM MPE compressed table layouts

The following provides a layout of some of the compressed tables. Customers that do not use the Clearing Optimizer and Utilities software to process their IPM MPE files should expand these compressed tables so that they match the table layouts described in the IPM MPE Table Layouts section of this chapter.

Table IP0036T1: Default Business Service

This table identifies the acceptance brand, business service arrangement type and business service arrangement ID for default business service arrangements.

It is present only when Mastercard sends an IPM MPE full file replacement. When it is present, customers that do not use the Clearing Optimizer and Utilities software to process their IPM MPE files should use the information in this table to add the necessary entries to tables IP0090T1 and IP0091T1 to accurately reflect customer participation in the default business services. Refer to the sections Build Table IP0090T1 Default Agreements and Build Table IP0091T1 Default Agreements for procedures describing how to handle the information in this table.

Table 12: Table IP0036T1: Default Business Service

Table Key: The key positions for this compressed table layout are 1-26.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-7	n-7	Date and time that the information in this record becomes effective or was last updated. Format: YYDDH

Field Name	Positions	Attribute	Comments and Values
Active-Inactive Code	8	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	9-11	an-3	Unique identifier of this IPM table. Valid value: Value of TBL-SUB-ID field of IP0000T1 for IP0036T1 table.
Region	12	an-1	The region associated to the acceptance brand, business service arrangement type, and business service arrangement ID.
From Region	13	an-1	"From" acquiring region associated to the acceptance brand, business service arrangement type, and business service arrangement ID.
To Region	14	an-1	"To" issuing region associated to the acceptance brand, business service arrangement type, and business service arrangement ID.
Acceptance Brand	15-17	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type Priority Code	18-19	n-2	The priority of the business service arrangement type.
Business Service Arrangement Type	20	an-1	The business service arrangement type.
Business Service ID Code	21-26	an-6	The business service arrangement ID code.
Business Service Arrangement Life Cycle Indicator	27	an-1	The business service life cycle indicator. Valid values are: A = All transactions may be submitted for this business service arrangement. L = Life cycle: Only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.

Field Name	Positions	Attribute	Comments and Values
Business Service Selection Enforcement Indicator	28	an-1	The business service arrangement enforcement indicator. Valid values are: Space = Default value. Not a mandatory business service arrangement. A = This is a mandatory business service arrangement. The mandate applies to all valid message types. F = This is a mandatory business service arrangement. The mandate applies only to First Presentments.

Table IP0040T1: Issuer Account Range

This table contains all issuing account ranges and associated card program identifier information. Any unique combination of issuing account range (low) and GCMS product ID generates a separate record of this type.

Table 13: Table IP0040T1: Issuer Account Range

Table Key: The key positions for this compressed table layout are 1-33.

Field name	Positions	Attribute	Comments and values
Effective Timestamp	1-7	n-7	Date and time that the information in this record becomes effective or was last updated. Format: YYDDH
Active-Inactive Code	8	an-1	Code that controls the updating of the member's Parameter Master File. A= Add this record to Parameter Master File I = This is an inactive parameter
Table ID	9-11	an-3	Unique identifier of this IPM table. Valid value: Value in TBL-SUB-ID field of IP0000T1 for IP0040T1 table.
Issuer account range: Low	12-30	an-19	The account number at the low end of the account range.

Field name	Positions	Attribute	Comments and values
GCMS product ID	31-33	an-3	This is the Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Licensed Product ID associated with the issuer account range and card program identifier combination.
Issuer Account Range: High	34-52	an-19	The account number at the high end of the account range.
Card program identifier	53-55	an-3	The card program identifier associated to the account range. Mastercard or other proprietary service mark.
Issuer card program identifier priority code	56-57	n-2	The priority code assigned to the card program identifier by the issuer, for the associated account range. Priority codes begin with a low-value number for the highest priority and continue in ascending sequence. For example, an issuing account range that shows the CIR identifier as priority 01 and the MCC identifier as priority 02 indicates that the CIR identifier has a higher priority and that GCMS will consider it first. Also important to note is that priority code values are not always present in unbroken ascending sequence. For example, an issuing account range might consist of a single entry showing the CIR identifier as priority 02 (with no entry for priority 01). In another example, an issuing account range might consist of one entry showing priority 01 and another entry showing priority 03 (with no entry for priority 02). GCMS looks for the highest priority code value (lowest numerical value), and then the next highest priority, and so on. Member systems should not expect every account range to contain an entry with priority 01, or the priority codes to appear in an unbroken sequence.
Member ID	58-68	n-11	The member ID associated with the account range.

Field name	Positions	Attribute	Comments and values
Product type ID	69	n-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Endpoint	70-76	n-7	The seven-digit routing endpoint associated with the account range.
Country code: alpha	77-79	an-3	The alphabetic country code associated with the account range.
Country code: numeric	80-82	n-3	The ISO-defined numeric country code associated with the account range.
Region	83	an-1	The region of the associated country code. 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Product class	84-86	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Transaction routing indicator	87	ans-1	Used in intra-European interchange processing. Valid values: Space = Normal routing P = Processing Code

Field name	Positions	Attribute	Comments and values
First presentment reassignment switch	88	an-1	Product reassignment switch for first presentment transactions. Valid values: Y = Product reassigned N = Product not reassigned
Product reassignment switch	89	an-1	Product reassignment switch for life cycle transactions. Valid values: Y = Product reassigned N = Product not reassigned
PWCB opt-in switch	90	an-1	The account range is a participant in purchase with cash back transactions.
Licensed product ID	91-93	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Field name	Positions	Attribute	Comments and values
Mapping service indicator	94	ans-1	The Mapping Service Indicator identifies issuing account ranges that require a Mapping Service. Valid values: Space = The issuer account range does not participate in a Mapping Service. 1 = Active Contactless Issuer Participation (Full) 2 = Active Contactless Issuer Participation (Partial) 3 = Active Contactless Issuer Participation (Mastercard-assigned range) 4 = Passive Contactless Issuer Participation 5 = Passive Contactless Issuer Participation (Merchant Sponsor) 6 = Passive Contactless Issuer Participation (Mastercard Sponsor) 7 = Service-eligible Contactless Account Range 8 = Service-eligible In Control Account Range 9 = Service-eligible Electronic Commerce Account Range A-B = Mastercard use C = Mastercard Digital Enablement Service Account Range D-H = Mastercard use I = Token Service Provider Token Range J-O = Mastercard use P = Service-eligible Pay with Rewards Q-Z = Mastercard use

Field name	Positions	Attribute	Comments and values
Account Level Management participation indicator	95	an-1	The account level management participation indicator. Valid values: N = No cardholder accounts within range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program. Y = Some cardholder accounts within range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program.
Account Level Management activation date	96-101	n-6	The account level management activation date Format: YYMMDD.
Cardholder billing currency default	102-104	n-3	Cardholder Billing Currency default.
Cardholder billing currency exponent default	105	n-1	Cardholder Billing Currency exponent default.
Cardholder billing additional currency (occurs from 0 to 4 times)	106-133	n-28	Cardholder Billing Currency (occurs 4 times).
Cardholder Billing Additional Transaction Currency		n-3	Cardholder Billing Additional Transaction Currency.
Cardholder billing additional currency		n-3	Cardholder Billing Additional Currency.
Cardholder billing additional currency exponent		n-1	Cardholder Billing Additional Currency exponent.

Field name	Positions	Attribute	Comments and values
Chip to magnetic conversion service indicator	134	an-1	The Chip to Magnetic Conversion Service Indicator. Valid values: Y = Chip to Magnetic Conversion Service applied and issuer has opted to receive the Chip to Magnetic Stripe Conversion Service results. Space = Chip to Magnetic Conversion Service not applied. S = Chip to Magnetic Conversion Service applied and issuer has opted not to receive the Chip to Magnetic Stripe Conversion Service results.
Floor expiration date	135-140	n-6	The Floor Expiration Date Format: YYYYMM
Co-brand participation switch	141	a-1	Co-Brand participation switch. Valid values: N = The account range does not participate in Co-Brand Processing Y = The account range participates in Co-Brand Processing
Spend control switch	142	a-1	Spend Control Switch Valid values: N = The account range does not participate in Spend Control Processing. Y = The account range participates in Spend Control processing.

Field name	Positions	Attribute	Comments and values
Merchant cleansing service participation	143-145	ans-3	Merchant Cleansing Service Participation. Valid values: 077 = Merchant Data Cleansing 078 = Merchant Data Cleansing Plus 079 = Merchant Data Advance 080 = Merchant Data Cleansing + Merchant Data Advance 081 = Merchant Data Cleansing Plus + Merchant Data Advance Spaces = Merchant Cleansing Service not applied
Merchant cleansing activation date	146-151	n-6	Merchant Cleansing Activation Date Format: YYMMDD
Contactless enabled indicator	152	a-1	Contactless Enabled Indicator. Valid values: N = Not Contactless Enabled Y = Contactless Enabled M = Mobile Contactless Enabled
Regulated rate type indicator	153	an-1	Regulated Rate Type Indicator. Valid values: B = Base regulated 1 = Regulated with Fraud Protected N = Not regulated
PSN route indicator	154	an-1	PSN Route Indicator. Valid values: Y = Route based on PAN Sequence Number N = Do Not Route based on PAN Sequence Number
Cash back without purchase indicator	155	an-1	Cash Back Without Purchase Indicator Valid values: Y = Account Range participates in Cash Back Without Purchase service. N = Account Range does not participate in Cash Back Without Purchase service.

Field name	Positions	Attribute	Comments and values
Filler	156	ans-1	Reserved for future use.
RePower reload participation indicator	157	an-1	RePower Reload Participation Indicator. Valid values: N = rePower reload capability R = RePower reload capability X =Non Mastercard rePower exclusive reload capability
MoneySend indicator	158	an-1	MoneySend Indicator Valid values: Y = BINS are MoneySend enabled, Domestic and Cross Border Domestic and Cross Border D = BINS are MoneySend enabled Domestic only N = BINS are not MoneySend enabled U =MoneySend unknown for BIN
Durbin regulated rate indicator	159	ans-1	Durbin Regulated Rate Indicator Valid values: Y = Regulated switch N = Non-regulated switch
Cash access only participating indicator	160	ans-1	Cash Access Only Participating Indicator Valid values: Y = Cash Access Only Participating Account Range N = Not a Cash Access Only Participating Account Range
Authentication indicator	161	n-1	Authentication Indicator Valid values: 0 = Account Range not registered for Authentication Indicator 1 = Transaction qualified for Type 1 Person Present 2 = Transaction qualified for Type 2 Person Present
Filler	162	ans-1	Reserved for future use.

Field name	Positions	Attribute	Comments and values
Issuer target market participation indicator	163	ans-1	Indicator identifies account ranges participating in the Target Market Program. Valid values: Y = Account Ranges participating in the Target Market Program. N = Account Ranges not participating in the Target Market Program.
Post date service indicator	164	ans-1	Identifies if the Account Range allows for a one-time Post Date Installment per purchase. Y = Account Range allows Post Dated Payments N = Account Range does not allow Post Dated Payments
Meal voucher indicator	165	ans-1	Indicator for Meal Voucher Program Y = Qualified for Meal Voucher program N = Not qualified for Meal Voucher program
Non-reloadable prepaid switch	166-167	ans-2	Identifies if the Account Range is a non-reloadable prepaid card 01 = Non-reloadable prepaid program Spaces = Reloadable prepaid program or nonprepaid program 99 = The account range or BIN represents a non-Mastercard product
Faster funds indicator	168	ans-1	Identifies whether Faster Funds is supported Valid values: N = Faster Funds is not supported D = Faster Funds is supported for Domestic but not Cross Border Y = Faster Funds is supported for Domestic and Cross Border
Anonymous prepaid indicator	169	ans-1	Identifies whether Anonymous Prepaid is supported Valid values: A = Anonymous prepaid program and not AMLD5 compliant

Field name	Positions	Attribute	Comments and values
			E = Anonymous prepaid program and AMLD5 compliant
			N = Not prepaid or non-anonymous prepaid program/default
			U = Unknown
Cardholder currency indicator	170	ans-1	Cardholder Currency Indicator support Valid values: C = Do not provide POI currency conversion (or DCC) -corporate client optout D = POI currency conversion (or DCC) is permissible for account range per Mastercard Rules T = Do not provide POI currency conversion (or DCC) per Mastercard Rules- travel cards or multi-currency accounts U = Not a Mastercard-branded account range
Pay by account indicator	171	an-1	Account range PbA participation indicator Valid values: Y = PbA participation N = Non PbA participation
Issuer account range gaming participation indicator	172	ans-1	Issuer account range Game participation indicator Valid values: N = Issuer not qualified for Gaming Participation Y = Issuer Gaming Participation
Embedded flex interchange indicator	173	an-1	Indicates Embedded Flex Interchange participation. Valid values: Y = Issuer Embedded Flex Interchange Participant N = Not Issuer Embedded Flex Interchange Participant

About IPM Mastercard Parameter Extract
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service
Arrangement Participation

Field name	Positions	Attribute	Comments and values
Digital first indicator	174	an-1	Indicates Digital First participation. Valid values: Y = Issuer is a Digital First Participant N = Issuer is not a Digital First Participant
Gaming and Gambling Payments Program Fast Posting Indicator	175	ans-1	Y = Issuer supports fast posting with immediate funds availability N = Issuer does not support fast posting with immediate funds availability
Name Validation Service	176	an-1	Name Validation Service Participation Flag Valid Values: Y= Issuer is participating N= Issuer not participating
Mastercard One Credential Participation Indicator	177	an-1	Indicates Mastercard One Credential Participation Valid values: - Y = Issuer is participating in Mastercard One Credential - N = Issuer is not participating in Mastercard One Credential
Filler	178-194	ans-17	Reserved for future use.

Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation

This table identifies the card program identifier and business service arrangements associated with an issuer account range. Each unique issuer account range, business service arrangement type, business service ID code, and card program identifier combination generates a separate record of this type.

Table Key: The key positions for this compressed table layout are 1-40.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-7	n-7	Date and time that the information in this record becomes effective or was last updated. Format: YYDDH

About IPM Mastercard Parameter Extract
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service
Arrangement Participation

Field Name	Positions	Attributes	Comments and Values
Active-Inactive Code	8	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	9-11	an-3	Unique identifier of this IPM table. Valid value: Value in TBL-SUB-ID field of IP0000T1 for IP0090T1 table.
Issuer Account Range: Low	12-30	an-19	The account number at the low end of the issuing account range associated to the card program identifier and business service arrangement combination.
Business Service Arrangement Type	31	an-1	The business service arrangement type.
Business Service ID Code	32-37	an-6	The business service arrangement ID code.
Card Program Identifier	38-40	an-3	Mastercard or other proprietary service mark.
Issuer Account Range: High	41-59	an-19	The account number at the high end of the issuing account range associated to the card program identifier and business service arrangement combination.
Business Service Arrangement Type Priority Code	60-61	n-2	The priority of the business service arrangement type.
Issuer Card Program Identifier Priority Code	62-63	n-2	The priority of the issuer card program identifier in relation to its use with the account range and business service arrangement combination.
Business Service Arrangement Life Cycle Indicator	64	an-1	The business service life cycle indicator. Valid values: A = All transactions may be submitted for this business service arrangement. L = Life Cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.

About IPM Mastercard Parameter Extract
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

Field Name	Positions	Attributes	Comments and Values
Business Service Selection Enforcement Indicator	65	an-1	The business service arrangement enforcement indicator. Valid values: Space = No business service arrangement enforcement. A = Business service arrangement enforcement for all transactions. F = Business service arrangement enforcement for First Presentments only.
Filler	66-72	ans-7	Reserved for future use.

Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

This table identifies the card program identifier and business service arrangements associated with an acquiring BIN. Each unique acquiring BIN, card program identifier, business service arrangement type, and business service ID code combination generates a separate record of this type.

Table Key: The key positions for this compressed table layout are 1-27.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-7	n-7	Date and time that the information in this record becomes effective or was last updated. Format: YYDDH
Active-Inactive Code	8	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	9-11	an-3	Unique identifier of this IPM table. Valid value: Value in TBL-SUB-ID field of IP0000T1 for IP0091T1 table.
Acquiring BIN	12-17	n-6	The six-position acquiring BIN associated with the card program identifier and business service arrangement information.

Field Name	Positions	Attributes	Comments and Values
Business Service Arrangement Type	18	an-1	The business service arrangement type.
Business Service ID Code	19-24	an-6	The business service arrangement ID code.
Card Program Identifier	25-27	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type Priority	28-29	n-2	The priority of the business service arrangement type.
Business Service Arrangement Life Cycle Indicator	30	an-1	The business service life cycle indicator. Valid values are: A = All transactions may be submitted for this business service arrangement. L = Life Cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Filler	31-51	ans-21	Reserved for future use.

IPM MPE non-compressed table layouts

The following provides the non-compressed table layouts in the IPM MPE file. The Clearing Optimizer software automatically expands the compressed tables into these table layouts. Customers who do not use the Clearing Optimizer software to process IPM MPE files should expand the compressed tables into these table layouts.

Table IP0000T1: keys

This table provides an index to all of the other MPE tables, including the version number, the starting position, and the length of the key of each table.

Table Key: The key for this table is positions 1-27.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attribute	Comments and Values
Active: Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0000T1
Subject Table ID	20-27	an-8	Identifies the table that is the subject of this Keys Table record. Must be a valid IPM Table ID.
Filler (reserved for internal use)	28	an-1	Space-filled.
Subject Table Name	29-55	an-27	Identifies by name the table that is the subject of this Keys Table record.
Subject Table Key Length	56-60	n-5	Length of the key that uniquely identifies each record in the table that is the subject of this Keys Table record.
Subject Table Key Start	61-64	n-4	Starting position of the key that uniquely identifies each record in the table that is the subject of this Keys Table record.
Subject Table Record Length—Minimum	65-69	n-5	Indicates the minimum length of each record in the table that is the subject of this Keys Table record.
Subject Table Record Length: Maximum	70-74	n-5	Indicates the maximum length of each record in the table that is the subject of this Keys Table record.
Version Number	75-82	n-8	The version of the table, generated by Mastercard. - This field on the first row of table IP0000T1 has the file version number and increases by one for each new daily update file. - All other tables have an incremented Version Number only when updates have been applied to the table. Format: NNNNNNNN

Field Name	Positions	Attribute	Comments and Values
Central Update	83-94	n-12	The last date and time that Mastercard updated this table at Central Site in St. Louis, Missouri, USA. Format: YYYYMMDDHHMM
Member Update	95-106	n-12	The last date and time that the member system updated this table at the member site. Format: YYYYMMDDHHMM
Table Row Count	107-114	n-8	Filler (Central Site use only)
Filler	115-224	an-110	Filler (Central Site use only)
Full Table Build Indicator	225	ans-1	Code indicates the type of data contained in a particular table. R = Full table replace. Indicates that a particular table data is being replaced in full. U or D = Regular updates.
Filler	226-243	ans-18	Filler (Central Site use only)
Table Sub Indicator	244-246	ans-3	Table ID converted three-position sub ID.
Filler	247-259	an-13	Filler (Central Site use only)

Table IP0001T1: Run Control Options

This table provides the parameters that are established as the defaults for running the Clearing Optimizer software and for updating the customer's Parameter Master File with a particular IPM MPE table.

Table Key: The key for this table is positions 1-24.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0001T1
Run Option Group ID	20	an-1	Valid values: 0 = Run Option 1 = Report Option 2 = Threshold Option
Run Option ID	21-24	an-4	The sequence number within a Run Option Group.
Run Option Description	25-59	an-35	The name of the option described in this record.
Run Option value for three-position Run Options	60-62	an-3	The default value if this Run Option is a three-position value. (All Group 2 options and the "Maximum Number of Cycles" Group 0 option contain three-position values.)
Run Option value for one-position Run Options			
Run Option	60	an-1	The default value if this Run Option is a one-position value. (All Group 1 options and most Group 0 options contain one-position values.
Filler (reserved for internal use)	61-62	an-2	Space filled
Run Option Error Number 1	63-67	an-5	Applicable error number when validating run options.
Run Option Error Number 2	68-72	an-5	Applicable error number when validating run options.

Table IP0002T1: Valid Run Option Overrides

This table provides the parameters that are established as the valid values for the customer to use when overriding the default values established for the run control process (the values in table IP0001T1).

Table 14: Table IP0002T1: Valid Run Option Overrides

Table Key: The key for this table is positions 1-25.

Field Name		Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0002T1
Run Option Group ID	20	an-1	Valid values: 0 = Run Option 1 = Report Option 2 = Threshold Option
Run Option ID	21-24	an-4	The sequence number within a Run Option Group.
Run Option Default	25	an-1	Valid values for this particular option.
Run Option Description	26-78	an-53	The name of the option described in this record.

Table IP0003T1: Run Control Errors

This table shows the error number and error message that applies to the Run Control error.

Table Key: The key for this table is positions 1-24.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0003T1
Run Control Error Number	20-23	an-4	The four-digit IPM error message number.
Run Control Error Line	24	an-1	Identifies when additional records are required to contain the error message text.
Run Control Abend Code	25-28	an-4	The abend code displayed when the program terminates.
Run Control Error Message	29-92	an-64	The actual error message text associated with the error number.

Table IP0006T1: Data Element Attributes

This table contains the number, name, format requirements, length requirements, and number of subfields within each data element.

Table 15: Table IP0006T1: Data Element Attributes

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0006T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.

Field Name	Positions	Attribute	Comments and Values
Data Element Number	23-25	n-3	Data element number defined in this record. Valid values: A valid DE as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Name	26-82	an-57	Name of the data element defined in this record. Valid values: The data element name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Format	83-85	an-3	Attribute convention describing the format of the data element defined in this record. Valid values: a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and space character ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
Data Element Minimum Length	86-88	n-3	The minimum length of the data element.
Data Element Mastercard Maximum Length	89-91	n-3	Maximum length of this data element, as defined by Mastercard.
Data Element ISO Maximum Length	92-94	n-3	Maximum length of this data element, as defined by the International Organization for Standardization (ISO).
DE-LLL-Size	95	n-1	Value that describes the data element length field size. Valid values: 0, 2, 3
Data Element-Subfields	96-97	n-2	Total count of subfields within the data element or PDS.

Table IP0007T1: Data Element Subfield Attributes

This table contains the number, name, format requirements, and length requirements for each data element subfield.

Table 16: Table IP0007T1: Data Element Subfield Attributes

Table Key: The key for this table is positions 1-24.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0007T1
Data Element Number	20-22	n-3	Data element number related to the subfield in this record. Valid values: A valid data element as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Subfield Number	23-24	n-2	Number of the subfield defined in this record. Valid values: A valid subfield associated with the data element, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Subfield Name	25-81	an-57	Name of the subfield defined in this record. Valid values: The subfield name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
Data Element Subfield Format	82-84	an-3	Attribute convention describing the format of the subfield defined in this record. Valid values: a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
Data Element Subfield Start	85-87	n-3	Starting position of the first occurrence of this subfield within the data element. A value of "000" indicates that a preceding subfield within DE 48 is variable; thus, the starting position of the subfield is unknown.
Data Element Subfield Minimum Length	88-90	n-3	Minimum length of the subfield.
Data Element Subfield Maximum Length	91-93	n-3	Maximum length of the subfield.

Table IP0008T1: PDS Attributes

This table contains the number, name, format requirements for the overall PDS, length requirements, and number of subfields within each PDS.

Table 17: Table IP0008T1: PDS Attributes

Table Key: The key for this table is positions 1-23.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attribute	Comments and Values
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0008T1
PDS Number	20-23	n-4	PDS number defined in this record. Valid values: A valid PDS as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Name	24-80	an-57	Name of the PDS defined in this record. Valid values: A valid PDS as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Format	81-83	an-3	Attribute convention describing the format of the PDS defined in this record. Valid values: a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
PDS Minimum Length	84-86	n-3	Minimum length of the PDS.
PDS Maximum Length	87-89	n-3	Maximum length of the PDS.
PDS Number of Subfields	90-91	n-2	The number of subfields contained within this PDS, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Table IP0009T1: PDS Subfield Attributes

This table contains the number, name, format requirements, and length requirements for each PDS subfield. Entries in this table will only exist for PDSs that have subfields.

Table 18: Table IP0009T1: PDS Subfield Attributes

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0009T1
PDS Number	20-23	n-4	PDS number related to the subfield in this record. Valid values: A valid PDS as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Subfield Number	24-25	n-2	Number of the subfield defined in this record. Valid values: A valid subfield associated with the PDS, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Subfield Name	26-82	an-57	Name of the subfield defined in this record. Valid values: The subfield name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
PDS Subfield Format	83-85	an-3	Attribute convention describing the format of the subfield defined in this record. Valid values: a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
PDS Subfield Minimum Length	86-88	n-3	Minimum length of the subfield
PDS Subfield Maximum Length	89-91	n-3	Maximum length of the subfield
PDS Subfield Start	92-94	n-3	Starting position of this subfield within the PDS.

Table IP0011T1: Expanded MTI/Function/Reason Code

This table provides switches indicating whether there is impact to settlement and fee processing.

Table Key: The key for this table is positions 1-33.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to the Parameter Master File I = This is an inactive parameter

About IPM Mastercard Parameter Extract
Table IP0011T1: Expanded MTI/Function/Reason Code

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0011T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Message Type Identifier (MTI)	23-26	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	27-29	n-3	The three-digit Function Code that indicates the message's specific purpose.
Message Reason Code (DE 25)	30-33	n-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.
Mnemonic	34-36	n-3	This identifies whether the Fee Collection 1740 message is a Retrieval Fee Billing message or a non-Retrieval Fee Billing message. Valid values: 018 = Fee Collection Retrieval Fee Billing 020 = Fee Collection Other (When the Function Code is equal to 700, 780, 781, 782, or 783) 790 = Funds Transfer Fee Collection (When the Function Code is equal to 700, 780, 781, 782, or 783) 791 = Funds Transfer Fee Collection Backout (When the Function Code is equal to 791) For all other message types, the mnemonic will be the same value as the Function Code.
Settlement Impact Switch	37	an-1	Valid values: Y = Settlement impact N = No Settlement impact
Retrieval Fee Switch	38	an-1	Valid values: Y = Retrieval fee is applicable N = Retrieval fee is not applicable
Filler (reserved for internal use)	39	an-1	Space filled.
Filler (reserved for internal use)	40-41	n-2	Zero filled.

Field Name	Positions	Attribute	Comments and Values
Filler (reserved for internal use)	42	an-1	Space filled.
Message Originator	43	an-1	Valid values: A = Acquirer I = Issuer
Fee Collection Indicator	44	an-1	This applies to Fee Collection/1740 messages. Valid values: Y = The Message Type Identifier (MTI) is fee collection N = The Message Type Identifier (MTI) is not fee collection

Table IP0012T1: Life Cycle Time Frame

This table contains the minimum and maximum time frames for which the clearing system will edit based on a particular card program identifier, business service arrangement type, business service ID code, transaction function (combination of MTI and Function Code) or Message Reason Code.

The minimum and maximum time frames are associated with various combinations of the dates in the transaction life cycle. For example, there could be a minimum time frame associated with the transaction between first chargeback and second presentment.

Table Key: The key for this table is positions 1-44.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0012T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type (Business Service Level)	23	an-1	The business service arrangement type (business service level).
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Message Type Identifier (MTI)	30-33	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	34-36	n-3	The three-digit Function Code that indicates the message's specific purpose.
Message Reason Code (DE 25)	37-40	n-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.
Begin Date Code	41-42	n-2	The first of the combination of dates with which this minimum or maximum amount is associated. Based on the stage in the life cycle, the Begin Date can represent the date of: 01 = First presentment 02 = Retrieval request 03 = Retrieval fulfillment 04 = First chargeback 05 = Second presentment 06 = Arbitration chargeback
End Date Code	43-44	n-2	The second of the combination of dates with which this minimum or maximum amount is associated. Based on the stage in the life cycle, the End Date can represent the date of: 01 = First presentment 02 = Retrieval request 03 = Retrieval fulfillment 04 = First chargeback 05 = Second presentment 06 = Arbitration chargeback

Field Name	Positions	Attribute	Comments and Values
Minimum Time Frame	45-47	an-3	The minimum time frame allowed for members to submit transactions for clearing for the particular combination of card program identifier, business service arrangement, transaction function, and message reason code.
Maximum Time Frame	48-50	an-3	The maximum time frame allowed for members to submit transactions for clearing for the particular combination of card program identifier, business service arrangement, transaction function, and message reason code.
Minimum Error Code	51-54	an-4	The four-digit error code associated with the minimum timeframe requirement.
Minimum Error Message	55-58	an-4	The error message associated with the minimum error code.
Maximum Error Code	59-62	an-4	The four-digit error code associated with the maximum timeframe requirement.
Maximum Error Message	63-66	an-4	The error message associated with the maximum error code.

Table IP0015T1: IPM Error Messages

This table contains the internal IPM error codes and the corresponding message texts for each IPM error code.

Table Key: The key for this table is positions 1–23.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File. I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0015T1

Field Name	Positions	Attribute	Comments and Values
IPM Error Message Number	20-23	n-4	The four-digit internal IPM error message text number. This is a unique number assigned by GCMS.
IPM Error Message Text	24-278	an-255	The error message text for each corresponding internal IPM error text message number.

Table IP0016T1: Brand Product

This table contains the valid licensed product ID and masked product ID combinations.

Table 19: Table IP0016T1: Brand Product

Table Key: The key for this table is positions 1-22.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File. I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0016T1
Licensed Product ID	20-22	an-3	The actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
GCMS Product ID	23-25	an-3	The Product ID recognized by the GCMS issuer account range and card program ID combination. It may be different from the licensed Product ID associated with the issuer account card program identifier combination.
Card Program Identifier	26-28	an-3	The card program identifier associated with the account range. Mastercard or other proprietary service mark.

Field Name	Positions	Attribute	Comments and Values
Product Class	29-31	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Product Type ID	32	an-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Product Category	33	an-1	Identifies the intended business functionality of cards issued under the associated licensed product ID. Cards function in-market as Mastercard credit, debit or prepaid products, or as non-Mastercard products (such as private label cards), as indicated by the Product Category value. This value does not control Mastercard interchange or systemic processing, nor does it replace the use of the Card Program Identifier associated with an issuer account range for those purposes. D = Debit P = Prepaid C = Credit N= Non-Mastercard (For non-Mastercard product codes)
Europe Product Category Code	34	ans-1	Europe Product Category Code Valid values: D = Europe Debit Product C = Europe Credit Product P = Europe Prepaid Product O = Europe Commercial Product N = Not applicable

Field Name	Positions	Attribute	Comments and Values
Commercial Product Indicator	35	ans-1	Identifies the product category Valid values: 0 = No participant 1 = Small business participant 2 = Large market participant 3 = Business debit participant 4 = Business prepaid participant
Filler	36-41	ans-6	Reserved for future use.

Table IP0017T1: Currency Codes

This table contains the Mastercard supported ISO currency codes and their associated currency exponents.

Table Key: The key for this table is positions 1-22.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File. I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0017T1
ISO Code	20-22	n-3	Must be a valid ISO currency code.
Alpha Currency Code	23-25	an-3	Must be a valid ISO alpha currency code.
Currency Exponent Code	26	n-1	One-position value representing the real currency exponent for the five ISO currencies. Valid ISO currency code exponent.
Filler	27-42	ans-16	Reserved for future use.

Table IP0018T1: Mastercard Product Graduation Parameters

This table contains the valid account category/licensed product ID/IRD combinations.

Table 20: Table IP0018T1: Mastercard Product Graduation Parameters

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0018T1
Account Category Code	20	an-1	The Account Category Code Valid values: M = Domestic-Enhanced Value and Product Graduation P = Mastercard Product Graduation or Co-Brand Proprietary Card Program. T = U.S. Domestic-High Value and Product Graduation Y = Spend Shortfall and Product Graduation D = Level 1 + Product Graduation F = Level 2 + Product Graduation H = Level 3 + Product Graduation K = Level 4 + Product Graduation R = Level 5 + Product Graduation
Licensed Product ID	21-23	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Interchange Rate Designator (IRD)	24-25	an-2	The interchange rate designator. This field will contain spaces.

About IPM Mastercard Parameter Extract
Table IP0018T1: Mastercard Product Graduation Parameters

Field Name	Positions	Attribute	Comments and Values
GCMS Product ID	26-28	an-3	This is the Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Licensed Product ID associated with the issuer account range and card program identifier combination.
Product Class	29-31	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Product Type ID	32	n-1	The product type of the associated issuing account range. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Account Type Category Code	33-35	an-3	The account type category code. Valid value: 002 = Mastercard Product Graduation or Co-brand Proprietary Card Program 003 = Mastercard Enhanced Value Platform/High Value/Spend Shortfall/Small Business and Mastercard Product Graduation
Account Category Code Life Cycle Date	36-43	ns-8	The Account Category Code Life cycle date. Format: CCYYMMDD
Product Code Life Cycle Date	44-51	ns-8	The Product Code Life Cycle Date. Format: CCYYMMDD
Filler	52-60	ans-9	Reserved for future use.

Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

This table identifies Account Level Management participation based on Card Program Identifier and Business Service Arrangement Type and Business Service ID code combination. It also provides information related to the Business As Usual and Enhanced Value Platform account categories.

Table Key: The key for this table is positions 1-35.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0019T1
Acceptance Brand	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator. Note: A Null IRD setup with an Account Category Code value represents Account Level Management participation for the Acceptance Brand/Business Service Arrangement Type/Business Service ID Code.
Licensed Product ID	32-34	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

Field Name	Positions	Attribute	Comments and Values
Account Category Code	35	an-1	The Account Category Code An account category code setup for the Business Service and Acceptance Brand where the IRD, shown as spaces, indicates the Account Level Management programs that the Business Service supports. If the Business Service participates in Account Level Management and there is no unique IRDs setup with the Account Category Code, then incentive interchange is determined by rate type 20 on the transaction. Account Level Management participation valid values: B = Domestic-Enhanced Value; Canada-High Spend P = Product Graduation S = U.S. Domestic-High Value; Canada-Premium High Spend W = Spend Shortfall C = Level 1 E = Level 2 G = Level 3 J = Level 4 Q = Level 5 R = Level 5 + Product Graduation

About IPM Mastercard Parameter Extract
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

Field Name	Positions	Attribute	Comments and Values
			An Account Category Code setup for a Business Service and Acceptance Brand where an IRD has a value (not space) indicates that the IRD is valid for transactions qualified as Account Level Management under the Business Service. Valid values: B = U.S. Domestic-Enhanced Value; Canada-High Spend M = U.S. Domestic-Enhanced Value and Product Graduation S = U.S. Domestic-High Value; Canada-Premium High Spend T = U.S. Domestic-High Value and Product Graduation W = Spend Shortfall Y = Spend Shortfall and Production Graduation Z = Mastercard provided default value indicating that the specific cardholder account found in the DE 2 (Primary Account Number [PAN]) of the transaction does not participate in Account Level Management processing for Mastercard Enhanced Value Platform or Mastercard Product Graduation. C = Level 1 D = Level 1 + Product Graduation E = Level 2 F = Level 2+ Product Graduation G = Level 3 H = Level 3+ Product Graduation J = Level 4 K = Level 4+ Product Graduation

Field Name	Positions	Attribute	Comments and Values
Account Type Category Code	36-38	an-3	The account type category code. Valid values: 000 = Business As Usual 001 = Mastercard Enhanced Value Platform/ Small Business 002 = Mastercard Product Graduation or Cobrand Proprietary Card Program 003 = Mastercard Enhanced Value Platform/ High Value/Spend Shortfall/Small Business and Mastercard Product Graduation 004 = Spend Shortfall
Account Category Code Life Cycle Date	39-46	ns-8	The Account Category Code life cycle date. Format: CCYYMMDD
Filler	47-50	ans-4	Mastercard use only.

Table IP0020T1: PAN Mapping Product Code Pairs

This table contains valid Primary Account Number (PAN) mapping point-of-sale (POS) licensed product code and funding licensed product code pairs.

Table 21: Table IP0020T1: PAN Mapping Product Code Pairs

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0020T1

About IPM Mastercard Parameter Extract
Table IP0020T1: PAN Mapping Product Code Pairs

Field Name	Positions	Attribute	Comments and Values
POS Licensed Product ID	20-22	an-3	This is the actual Point-of-Sale product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Funding Licensed Product ID	23-25	an-3	This is the actual Funding product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Funding GCMS Product ID	26-28	an-3	This is the Funding Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Funding Licensed Product ID associated with the issuer account range and card program identifier combination.
Funding Product Class	29-31	an-3	The product class associated to the funding account range. Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Funding Product Type ID	32	an-1	The product type associated to the funding account range. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Funding Card Program Identifier	33-35	an-3	The card program identifier associated with the account range. Mastercard or other proprietary service mark.
In Control Future Use Switch	36	an-1	In Control future use switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for an anticipated future In Control program. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for an anticipated future In Control program.

Field Name	Positions	Attribute	Comments and Values
In Control Service F Switch	37	an-1	In Control Service F Switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for In Control Service F. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for In Control Service F.
In Control Service E Switch	38	an-1	In Control Service E Switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for In Control Service E. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for In Control Service E.
Filler	39-48	ans-10	Reserved for future use.

Table IP0023T1: MDS Routing Member ID

This table contains the processor ID for the Single Message System in Europe. This table is used for specific transactions submitted by the Single Message System.

Table Key: The key for this table is positions 1-30.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0023T1

Field Name	Positions	Attribute	Comments and Values
MDSE Member ID	20-30	an-11	Processor ID

Table IP0025T1: Message Reason Codes

This table is only used for Reason Codes on Fee Collection Messages.

Table 22: Table IP0025T1: Message Reason Codes

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0025T1
Message Reason Code (DE 25)	20-23	n-4	Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Message Reason Code (DE 25) Debit/Credit Indicator	24-25	n-2	Valid values: 19 = Credit to Originator 29 = Debit to Originator

Table IP0026T1: Parameter Print Controls

This table contains control information to print data on a report for all IPM parameter tables. The parameters include specifics regarding the orientation of the report, placement of the header and column lines, and positioning of data on the report.

Table Key: The key for this table is positions 1-29.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0026T1
Subject Table ID	20-23	an-4	Identifies the table that is the subject of this Keys Table record. Must be a valid IPM MPE Table ID.
Line Indicator	24	an-1	Valid values: 1 = Header Line 2 = Detail Line
Line Number	25-26	n-2	The applicable line number.
Column Number	27-29	n-3	The applicable column number.
Header Line Information			
Text	30-99	an-70	Present only for Header Lines: Indicates the header text that will go in the Line/Column position.
Detail Line Information			Present only for Detail Lines: redefines the Header Line.
Field Length	30-33	n-4	The length of the Detail Line.
Field Type	34	an-1	Valid values: X = Alphanumeric N = Zoned decimal P = Packed decimal B = Binary L = Label
Non-Label Information			
Position in Row	35-38	n-4	The position within the applicable row.

Field Name	Positions	Attribute	Comments and Values
Decimal Places	39	n-1	The number of decimal places.
Filler (reserved for internal use)	40-99	an-60	Space filled.
Label Information			Redefines the Non-Label information.
Label Text	35-99	an-65	The label text.

Table IP0027T1: Run Control Default Override Values

This table contains all lines required for creation of the run control file that the user updates when overriding the default values established for the run control process (the values in table IP0001T1).

Table Key: The key for this table is positions 1-21.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0027T1
Sequence Number	20-21	n-2	Valid values: 0099
Line Type	22	an-1	Valid values: Space = Blank on label line 1 = Header line 0 = UTC offset P = Processing Date T = Processing Time D= Details with user edited run options

Field Name	Positions	Attribute	Comments and Values
Filler (reserved for internal use)	23-24	an-2	Space filled.
Data	25-104	an-80	Run Control Parameter file details.

Table IP0028T1: Country Codes

This table contains the numeric and alphanumeric country codes. It also contains state/province codes for countries that require the presence of state/province codes.

Table 23: Table IP0028T1: Country Codes

Table Key: The key for this table is positions 1-25.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active, Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0028T1
Country Code: Alpha	20-22	an-3	The alphanumeric country code established by Mastercard.
State-Province Code: Alpha	23-25	an-3	The alphanumeric state/province code established by Mastercard.
Country Code Edit ID	26	an-1	Valid values: Y = the edit to validate the state/province code is applicable N = the edit to validate the state/province code is not applicable
Region	27	an-1	The region in which the country is located.
Country Code: Numeric	28-30	n-3	The numeric country code established by the International Organization for Standardization (ISO).

Field Name	Positions	Attribute	Comments and Values
National Currency Code: Numeric	31-33	n-3	The numeric currency code associated with the country code established by ISO.
Country Name	34-63	a-30	The country name
Life Cycle Indicator	64	an-1	State/Province Code Life Cycle Indicator. Valid values: A = All transactions L = Life cycle transactions only.
Diners Interchange Indicator	65	n-1	Indicator identifies Caribbean or U.S. Territories Valid values: 0 = Not Applicable 1 = Caribbean or U.S. Territory for Diners Interchange.
Filler	66	an-1	Filler (Central Site use only)
Euro Zone Indicator	67	an-1	Reserved for Mastercard use
Additional National Currency Codes (occurs 4 times)	68-79		The numeric currency codes associated with the country code established by ISO.
Additional National Currency Code		n-3	Additional Currency Code
VAT Indicator	80	an-1	The VAT indicator: Valid values: N = Not a Participating VAT Country Y = Participating VAT Country
Filler	81-83	an-3	Reserved for Mastercard use.
EEA Regulated Indicator	84	ans-1	EEA Regulated Indicator Valid values: Y = Country Qualifies for EEA Regulated Interchange N = Country does not qualify for EEA Regulated Interchange

Field Name	Positions	Attribute	Comments and Values
EEA Domestic Rate Qualification Indicator	85	ans-1	EEA Domestic Rate Qualification Indicator Valid values: Y = EEA Domestic Rate qualified N = Not EEA Domestic Rate qualified
CCCR Participation Country	86	ans-1	Customer Currency Conversion Rate (CCCR) participation country. Valid values: Y = Country CCCR participant N = Not a CCCR participant
SEPA Participation Indicator	87	ans-1	SEPA Participation Indicator. Valid values: S = SEPA participant T = Non-SEPA participant N = Not applicable
EEA Territory Indicator	88	ans-1	EEA Territory Indicator Valid Values: Y = Territory qualifies for EEA regulated interchange N = Territory does not qualify for EEA regulated interchange.
EEA Regulated Extension Country Indicator	89	ans-1	EEA Regulated Extension Country Indicator Valid values: Y = Country is not EEA but qualifies for EEA regulated interchange. N = Country is not EEA and does not qualify for EEA regulated interchange.
Mastercard Transaction Calculator Indicator	90	ans-1	Mastercard Transaction Calculator Indicator Valid values: - Y = Mastercard Transaction Calculator service is available in this country - N = Mastercard Transaction Calculator service is not available in this country
Filler	91-140	ans-50	Reserved for future use.

Table IP0029T1: Edit Override Table

This table contains the GCMS Internal Edit Number for which GCMS applies date based life cycle processing.

Table Key: The key for this table is positions 1-26.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0029T1
GCMS Internal Edit Number	20-23	n-4	Field edit number.
Environment	24-26	an-3	Environment.
Edit Implementation Date	27-34	an-8	Edit implementation date in CCYYMMDD format.
Override Value List	35-42	an-8	Table override value

Table IP0030T1: Interchange Amount Restriction

This table contains the amount ranges for large ticket interchange programs that are restricted based on the transaction amount.

Table Key: The key for this table is positions 1-31.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attribute	Comments and Values
ActiveInactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0030T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator.
Currency Codenumeric	32-34	n-3	The ISO defined numeric currency code associated with minimum and maximum transaction amounts.
Exponent	35	n-1	Currency exponent
Minimum Transaction Amount	36-47	n-12	The minimum amount applicable to a minimum transaction amount range limit.
Maximum Transaction Amount	48-59	n-12	The maximum amount applicable to a maximum transaction amount range limit.
Filler	60-66	ans-7	Reserved for future use.

Table IP0031T1: Addendum Data

This table contains the mandatory elements for addendum messages (PDS 0500 and greater).

Table Key: The key for this table is positions 133.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attribute	Comments and Values
ActiveInactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0031T1
Addendum Edit Number	20-23	n-4	The specific addendum message four-digit edit number.
Contents of PDS 0501 Transaction Description, subfield 1 (Usage Code)	24-25	an-2	Valid values: 01 = Passenger Transport Detail 05 = Vehicle Rental Detail 06 = Lodging Detail 07 = Temporary Services 08 = Shipping/Courier Services 09 = Electronic Invoice: Transaction Data/ Party Information 10 = Payment Transaction 11 = Telephony Billing: Detail/Summary 12 = Travel Agency 13 = Lodged Account 14 = Private Label 15 = Healthcare 98 = Corporate Detail 99 = Generic Detail

Field Name	Positions	Attribute	Comments and Values
Contents of PDS 0501 Transaction Description, subfield 2 (Industry Record Number)	26-28	an-3	The Usage Code and Industry Record are used in conjunction to uniquely identify the addendum data format. Valid values: 001 = Passenger Transport Detail: General Ticket Information 002 = Passenger Transport Detail: Trip Leg Data 000 = Passenger Transport Detail: Rail Data 000 = Vehicle Rental Detail 000 = Lodging Detail 000 = Temporary Services 000 = Shipping/Courier Services 000 = Electronic Invoice: Transaction Data 001 = Electronic Invoice: Party Information 000 = Payment Transaction Detail 000 = Telephony Billing Summary 001 = Telephony Billing: Party Information 000 = Corporate Detail: Corporate Card Common Data Requirements 000 = Travel Agency 000 = Lodged Account 002 = Corporate Detail: Corporate Fleet Transaction Information 950 = Corporate Detail: Corporate Card Line Item Detail 000 = Generic Detail 000 = Private Label: Common Data 001 = Private Label: Line Item Detail 000 = Healthcare
Data Element/PDS Indicator	29	an-1	Valid values: 2 = Data element 3 = PDS

Field Name	Positions	Attribute	Comments and Values
Field Number	30-33	n-4	The addendum message field number to be edited.
Filler	34-37	ans-4	Reserved for future use.

Table IP0033T1: IPM Module Names and Version Numbers

This table includes all of the names and version numbers of the modules that GCMS and the Clearing Optimizer software include.

Table Key: The key for this table is positions 1-43.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0033T1
Module ID	20-27	an-8	Unique identifier of the GCMS or Clearing Optimizer module.
Source Date and Time	28-41	n-14	Source Date and Time of the GCMS or Clearing Optimizer module. Unique identifier of the module. Format: YYYYMMDDHHMMSS This field is applicable only if the Type field is a value of PR.
Type	42-43	an-2	Indicator of the type of module. Valid values: PR = Program CP = Copybook JC = JCL PC = Proc

Field Name	Positions	Attribute	Comments and Values
Location ID	44	an-1	Indication whether the distributed Clearing Optimizer software, the Central Site clearing system, or both use this module. Valid values: P = Module used by the Clearing Optimizer software C = Module used by Central Site (GCMS) B = Module used by both the Clearing Optimizer software, and the Central Site clearing system.
Description	45-69	an-25	Description of the GCMS or Clearing Optimizer module.

Table IP0034T1: Processing Code Group

This table is used in settlement service selection processing. It provides the group code for each processing code recognized in the IPM format.

Table Key: The key for this table is positions 1-22.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File. I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0034T1
Processing Code	20-22	n-3	Processing Code
Processing Code Group	23-25	an-3	Code that defines a grouping of processing codes that can be used across various clearing and settlement systems.

Table IP0035T1: Settlement Service Selection BIN Data

This table contains BIN settlement service criteria.

Processing guidelines for the input source ID field name

The optimize process that runs at Central Site and customer sites will use card PCIP3102 to determine if Input Source ID 1 settlement data or Input Source ID 9 settlement data should be loaded into the one-day file.

The Russian customers (those customers that send IPM inbound files to Mastercard using bulk ID RCA1) should identify 0000000009 as the Input Source ID in card PCIP3102. Russian customers must manually update card PCIP3102 to contain the value in positions 1-10.

Those customers that send IPM inbound files to Mastercard using bulk ID R111 should identify 0000000001 as the Input Source ID in card PCIP3102. The card will contain the correct value and will not need to be modified.

Table Key: The key for this table is positions 1-48

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0035T1
Selection Criteria ID	20-30	n-11	Unique identifier relating to the criteria record.
Acquiring BIN	31-37	an-7	The six digit acquiring BIN containing a preceding leading zero. When this position is populated with an asterisk, it indicates that there is no Acquiring BIN set up for this criterion.
Input Source ID	38-48	n-11	Identifies the system where the record is valid. Valid values: 00000000001 = GCMS 00000000009 = LCMS

Field Name	Positions	Attribute	Comments and Values
Effective Date Number	49-59	n-11	Latest Effective Date/Time Stamp in integer format.
Filler	60-71	ans-12	Mastercard use only.

Table IP0036T1: Default Business Service

This table identifies the acceptance brand, business service arrangement type and business service arrangement ID for default business service arrangements.

Table Key: The key for this table is positions 1-34.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0036T1
Region	20	an-1	The region associated to the acceptance brand, business service arrangement type and business service arrangement ID.
From Region	21	an-1	"From" acquiring region associated to the acceptance brand, business service arrangement type and business service arrangement ID.
To Region	22	an-1	"To" issuing region associated to the acceptance brand, business service arrangement type and business service arrangement ID.
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type Priority	26-27	an-2	The priority of the business service arrangement type.

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	28	an-1	The business service arrangement type.
Business Service ID Code	29-34	an-6	The business service arrangement ID code.
Business Service Arrangement Life Cycle Indicator	35	an-1	The business service life cycle indicator. Valid values: A = All transactions may be submitted for this business service arrangement. L = Life cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Business Service Selection Enforcement Indicator	36	an-1	The business service arrangement enforcement indicator. Valid values: Space = Default value. Not a mandatory business service arrangement. A = This is a mandatory business service arrangement. The mandate applies to all valid message types. F = This is a mandatory business service arrangement. The mandate applies only to First Presentments.

Table IP0037T1: Selection Criteria Data

This table identifies settlement service criteria data.

Processing guidelines for the input source ID field name

The optimize process that runs at Central Site and the Customer Sites will use card PCIP3102 to determine if Input Source ID 1 settlement data or Input Source ID 9 settlement data should be loaded into the one-day file.

The Russian customers (those customers that send IPM inbound files to Mastercard using bulk ID RCA1) should identify 0000000009 as the Input Source ID in card PCIP3102. Russian customers must manually update card PCIP3102 to contain the value in positions 1-10.

Those customers that send IPM inbound files to Mastercard using bulk ID R111 should identify 0000000001 as the Input Source ID in card PCIP3102. The card will contain the correct value and will not need to be modified.

Table Key: The key for this table is positions 1-59.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0037T1
Selection Criteria ID	20-30	n-11	Unique identifier relating to the criteria record.
Sequence Number	31-32	n-2	Sequence number
Input Source ID	33-43	n-11	Identifies the system where the record is valid. Valid values: 000000000001 = GCMS 000000000009 = LCMS
Filler	44-55	ans-12	Mastercard use only
Number of Selection Criteria Occurrences	56-59	n-4	Specifies the number of Selection Criteria Data occurrences.
Selection Criteria Data	60-95		There will be one occurrence.
	Effective Date Number	n-11	Effective date and time, in integer format, applied to the specific selection criteria for each settlement service and TAA combination.
	Card Program ID	an-3	The Card Program Identifier value associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Card Program ID set up for this criteria.

Field Name	Positions	Attributes	Comments and Values
	Transaction Function Group	an-2	The Transaction Function Group associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Transaction Function Group set up for this criteria.
	Transaction Currency	an-3	The Transaction Currency associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Transaction Currency set up for this criteria.
	Business Service Arrangement Type	an-1	The Business Service Type associated with the settlement service ID for the member. This applies to intra-European transactions only. When this position is populated with an asterisk, it indicates that there is no Business Service Arrangement Type set up for this criteria.
	Licensed Product ID	an-3	This is the actual product assigned by Mastercard when licensing the combination of issuer account range and card program identifier. When this position is populated with an asterisk, it indicates that there is no Licensed Product ID set for this criteria.
	Processing Code Group	an-3	Code that defines a grouping of processing codes that can be used across various clearing and settlement systems. When this position is populated with an asterisk, it indicates that there is no Processing Code Group set up for this criteria.
Filler		an-3	Mastercard use only.
Acceptor Business Code		n-4	Acceptor Business Code classifies the type of business applicable to the acceptor.
Installment Type Code		an-3	Type of Installment Valid Values: 403: with interest 407: without interest 410: Installment by Issuer 488: IATA

Table IP0039T1: Selection Criteria Account Range

This table contains account range settlement service criteria.

Processing guidelines for the input source ID field name

The optimize process that runs at Central Site and the Customer Sites will use card PCIP3102 to determine if Input Source ID 1 settlement data or Input Source ID 9 settlement data should be loaded into the one-day file.

The Russian customers (those customers that send IPM inbound files to Mastercard using bulk ID RCA1) should identify 0000000009 as the Input Source ID in card PCIP3102. Russian customers must manually update card PCIP3102 to contain the value in positions 1-10.

Those customers that send IPM inbound files to Mastercard using bulk ID R111 should identify 0000000001 as the Input Source ID in card PCIP3102. The card will contain the correct value and will not need to be modified.

Table Key: The key for this table is positions 1-79.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0039T1
Selection Criteria ID	20-30	n-11	Unique identifier relating to the criteria record.
Issuer Account Range: Low	31-49	an-19	The account number at the low end of the issuing account range.
Issuer Account Range: High	50-68	an-19	The account number at the high end of the issuing account range.
Input Source ID	69-79	n-11	Identifies the system where the record is valid. Valid values: 00000000001 = GCMS 00000000009 = LCMS

Field Name	Positions	Attributes	Comments and Values
Effective Date Number	80-90	n-11	Effective date and time, in integer format, applied to the specific select criteria for each settlement service and TAA combination.
Filler	91-102	ans-12	Mastercard use only.

Table IP0040T1: Issuer Account Range

This table contains all issuing account ranges and associated card program identifier information. Any unique combination of issuing account range (low) and GCMS product ID generates a separate record of this type.

NOTE: The filler in position 185-307 is not present before it is applied to the Parameter Master File when a full IPM MPE replacement file is received.

Table 24: Table IP0040T1: Issuer Account Range

Table Key: The key for this table is positions 1-41.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0040T1
Issuer Account Range - Low	20-38	an-19	The account number at the low end of the account range.
GCMS Product ID	39-41	an-3	This is the Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Licensed Product ID associated with the issuer account range and card program identifier combination.

Field Name	Positions	Attribute	Comments and Values
Issuer Account Range - High	42-60	an-19	The account number at the high end of the account range.
Card Program Identifier	61-63	an-3	The card program identifier associated to the account range. Mastercard or other proprietary service mark.
Issuer Card Program Identifier Priority Code	64-65	n-2	The priority code assigned to the card program identifier by the issuer, for the associated account range. Priority codes begin with a low-value number for the highest priority and continue in ascending sequence. For example, an issuing account range that shows the CIR identifier as priority 01 and the MCC identifier as priority 02 indicates that the CIR identifier has a higher priority and that GCMS will consider it first. Also important to note is that priority code values are not always present in unbroken ascending sequence. For example, an issuing account range might consist of a single entry showing the CIR identifier as priority 02 (with no entry for priority 01). In another example, an issuing account range might consist of one entry showing priority 01 and another entry showing priority 03 (with no entry for priority 02). GCMS looks for the highest priority code value (lowest numerical value), and then the next highest priority, and so on. Customer systems should not expect every account range to contain an entry with priority 01, or the priority codes to appear in an unbroken sequence.
Member ID	66-76	n-11	The member ID associated with the account range.
Product Type ID	77	n-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other

Field Name	Positions	Attribute	Comments and Values
Endpoint	78-84	n-7	The seven-digit routing endpoint associated with the account range.
Country Code-Alpha	85-87	an-3	The alphabetic country code associated with the account range.
Country Code-Numeric	88-90	n-3	The ISO-defined numeric country code associated with the account range.
Region	91	an-1	The region of the associated country code. 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Product Class	92-94	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Transaction Routing Indicator	95	ans-1	Used in intra-European interchange processing. Valid values: Space = Normal routing P = Processing Code
First Presentment Reassignment Switch	96	an-1	Product reassignment switch for first presentment transactions. Valid values: Y = Product reassigned N = Product not reassigned

Field Name	Positions	Attribute	Comments and Values
Product Reassignment Switch	97	an-1	Product reassignment switch for life cycle transaction. Valid values: Y = Product Reassigned N = Product Not Reassigned
PWCB Opt-In Switch	98	an-1	The account range is a participant in purchase with cash back transactions. Valid values: Y = Opt-In (will apply to all issuer account ranges as of GCMS Release 06.2)
Licensed Product ID	99-101	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Field Name	Positions	Attribute	Comments and Values
Mapping Service Indicator	102	ans-1	The Mapping Service Indicator identifies issuing account ranges that require a Mapping Service. Valid values: Space = The issuer account range does not participate in a Mapping Service 1 = Active Contactless Issuer Participation (full) 2 = Active Contactless Issuer Participation (partial) 3 = Active Contactless Issuer Participation (Mastercard assigned range) 4 = Passive Contactless Issuer Participation 5 = Passive Contactless Issuer Participation (Merchant Sponsor) 6 = Passive Contactless Issuer Participation (Mastercard Sponsor) 7 = Service-eligible Contactless Account Range 8 = Service-eligible In Control Account Range 9 = Service-eligible Electronic Commerce Account Range A-B = Mastercard use C = Mastercard Digital Enablement Service Account Range D-H = Mastercard use I = Token Service Provider Token Range J-O = Mastercard use P = Service-eligible Pay with Rewards Q-Z = Mastercard use

Field Name	Positions	Attribute	Comments and Values
Account Level Management Participation Indicator	103	an-1	The account level management participation indicator. Valid values: N = No cardholder accounts within range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program Y = Some cardholder accounts within range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program
Account Level Management Activation Date	104-109	n-6	The account level management activation date Format: YYMMDD
Cardholder Billing Currency Default	110-112	n-3	Cardholder Billing Currency default.
Cardholder Billing Currency Exponent Default	113	n-1	Cardholder Billing Currency exponent default.
Cardholder Billing Additional Currency (occurs from 0 to 4 times)	114-141 (varying length)	n-28	Cardholder Billing Currency (occurs 4 times).
Cardholder Billing Additional Transaction Currency		n-3	Cardholder Billing Additional Transaction Currency
Cardholder Billing Additional Currency		n-3	Cardholder Billing Additional Currency
Cardholder Billing Additional Currency Exponent		n-1	Cardholder Billing Additional Currency exponent

Field Name	Positions	Attribute	Comments and Values
Chip to Magnetic Conversion Service Indicator	142	an-1	The Chip to Magnetic Conversion Service Indicator. Valid values: Y = Chip to Magnetic Conversion Service applied and issuer opted to receive the Chip to Magnetic Stripe Conversion Service results. Space = Chip to Magnetic Conversion Service not applied. S = Chip to Magnetic Conversion Service applied and issuer has opted to not receive the Chip to Magnetic Stripe Conversion Service results.
Floor Expiration Date	143-148	n-6	The Floor Expiration Date. Format: YYYYMM
Co-Brand Participation Switch	149	a-1	Co-Brand participation switch. Valid values: N = The account range does not participate in Co-Brand Processing Y = The account range participates in Co-Brand Processing
Spend Control Switch	150	a-1	Spend Control Switch Valid values: N = The account range does not participate in Spend Control Processing Y = The account range participates in Spend Control Processing
Filler	151-153	ans-3	Reserved for future use.
Filler	154-159	n-6	Reserved for future use.
Contactless Enabled Indicator	160	a-1	Contactless Enabled Indicator. Valid values: N = Not Contactless Enabled Y = Contactless Enabled M = Mobile Contactless Enabled

Field Name	Positions	Attribute	Comments and Values
Regulated Rate Type Indicator	161	an-1	Regulated Rate Type Indicator. Valid values: B = Base regulated 1 = Regulated with Fraud Protected N = Not regulated
PSN Route Indicator	162	an-1	PSN Route Indicator. Valid values: Y = Route based on PAN Sequence Number N = Do Not Route based on PAN Sequence Number
Cash Back Without Purchase Indicator	163	an-1	Cash Back Without Purchase Indicator Valid values: Y = Account Range participates in Cash Back Without Purchase service. N = Account Range does not participate in Cash Back Without Purchase service.
Filler	164	ans-1	Reserved for future use.
RePower Reload Participation Indicator	165	an-1	RePower Reload Participation Indicator. Valid values: N = No rePower reload capability R = RePower reload capability X = Non Mastercard rePower exclusive reload capability
MoneySend Indicator	166	an-1	MoneySend Indicator Valid values: Y = BINS are MoneySend enabled; Domestic and Cross Border D = BINS are MoneySend enabled Domestic only N = BINS are not MoneySend enabled U = MoneySend unknown for BIN
Durbin Regulated Rate Indicator	167	ans-1	Durbin Regulated Rate Indicator Valid values: Y = Regulated switch N = Non-regulated switch

Field Name	Positions	Attribute	Comments and Values
Cash Access Only Participating Indicator	168	ans-1	Cash Access Only Participating Indicator Valid values: Y = Cash Access Only Participating Account Range N = Not a Cash Access Only Participating Account Range
Authentication Indicator	169	n-1	Authentication Indicator Valid values: 0 = Account Range not registered for Authentication Indicator 1 = Transaction qualified for Type 1 Person Present 2 = Transaction qualified for Type 2 Person Present
Filler	170	ans-1	Reserved for future use.
Issuer Target Market Participation Indicator	171	ans-1	Indicator identifies account ranges participating in the Target Market Program. Valid Values: Y = Account Ranges participating in the Target Market Program. N = Account Ranges not participating in the Target Market Program.
Post Date Service Indicator	172	ans-1	Identifies if the Account Range allows for a one-time Post Date Installment per purchase. Y = Account Range allows Post Dated Payments N = Account Range does not allow Post Dated Payments
Meal Voucher Indicator	173	ans-1	Indicator for Meal Voucher Program Y = Qualified for Meal Voucher program N = Not qualified for Meal Voucher program

Field Name	Positions	Attribute	Comments and Values
Non-Reloadable Prepaid Switch	174-175	ans-2	Identifies if the Account Range is a non-reloadable prepaid card 01 = Non-reloadable prepaid program Spaces = Reloadable prepaid program or nonprepaid program 99 = The account range or BIN represents a non-Mastercard product
Faster Funds Indicator	176	ans-1	Identifies whether Faster Funds is supported Valid values: N = Faster Funds is not supported D = Faster Funds is supported for Domestic but not Cross Border Y = Faster Funds is supported for Domestic and Cross Border
Anonymous Prepaid Indicator	177	ans-1	Identifies whether Anonymous Prepaid is supported Valid values: A = Anonymous prepaid program and not AMLD5 compliant E = Anonymous prepaid program and AMLD5 compliant N = Not prepaid or non-anonymous prepaid program/default U = Unknown
Cardholder Currency Indicator	178	ans-1	Cardholder Currency Indicator support Valid values: C = Do not provide POI currency conversion (or DCC) -corporate client optout D = POI currency conversion (or DCC) is permissible for account range per Mastercard Rules T = Do not provide POI currency conversion (or DCC) per Mastercard Rules- travel cards or multi-currency accounts U = Not a Mastercard-branded account range

Field Name	Positions	Attribute	Comments and Values
Pay by Account Indicator	179	an-1	Account range PbA participation indicator Valid values: Y = PbA participation N = Non PbA participation
Issuer Account Range Gaming Participation Indicator	180	ans-1	Issuer account range Game participation indicator Valid values: N = Issuer not qualified for Gaming Participation Y = Issuer Gaming Participation
Embedded Flex Interchange Indicator	181	an-1	Indicates Embedded Flex Interchange participation. Valid values: Y = Issuer Embedded Flex Interchange Participant N = Not Issuer Embedded Flex Interchange Participant
Digital First Indicator	182	an-1	Indicates Digital First participation. Valid values: Y = Issuer is a Digital First Participant N = Issuer is not a Digital First Participant
Gaming and Gambling Payments Program Fast Posting Indicator	183	ans-1	Y = Issuer supports fast posting with immediate funds availability N = Issuer does not support fast posting with immediate funds availability
Name Validation Service	184	an-1	Name Validation Service Participation Flag Valid Values: Y= Issuer is participating N= Issuer not participating

Field Name	Positions	Attribute	Comments and Values
Mastercard One Credential Participation Indicator	185	an-1	Indicates Mastercard One Credential Participation Valid values: - Y = Issuer is participating in Mastercard One Credential - N = Issuer is not participating in Mastercard One Credential
Filler	186-307	ans-122	Reserved for future use.

Table IP0041T1: Acquirer Reference ID

This table contains all of the acquiring BINs for a particular acquirer and associated card program identifier information. Each unique acquirer BIN and card program identifier combination generates a separate record of this type.

NOTE: Mastercard only compresses the Effective Timestamp and Table ID for this table. Refer to Expanding the IPM MPE File for additional information.

Table Key: The key for this table is positions 1–28.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0041T1
Acquiring BIN	20-25	n-6	The six digit acquiring BIN.
Card Program Identifier	26-28	an-3	The card program identifier associated to the acquiring BIN ID. Mastercard or other proprietary service mark.
Member ID	29-39	n-11	The customer ID associated with the acquiring BIN ID.
Filler	40	an-1	Space filled.

Field Name	Positions	Attribute	Comments and Values
Endpoint	41-47	n-7	The seven-digit endpoint associated with the acquiring BIN ID.
POS EMV Compliance Indicator	48	an-1	Used in intra-European interchange processing to indicate whether the acquirer has one or more POS terminals that are EMV compliant and therefore qualifies for various Chip tiers. Valid values: Y = Yes N = No
ATM EMV Compliance Indicator	49	an-1	Used in intra-European interchange processing to indicate whether the acquirer has one or more ATM terminals that are EMV compliant and therefore qualifies for various Chip tiers. Valid values: Y = Yes N = No
Merchant UCAF Indicator	50	an-1	Used in intra-European interchange processing to qualify for the merchant UCAF rate. Valid values: Y = Yes N = No
Region (occurs 6 times)	51-56	an-1	The region associated to the acquiring BIN ID (occurs 6 times).
Country-Alpha (occurs 20 times)	57-116	an-3	The alphabetic country code associated with the acquiring BIN ID (occurs 20 times) and card program identifier.
Filler	117-160	ans-44	Reserved for future use.

Table IP0045T1: Cash Disbursement Fee

This table is used during the interchange calculation process for interregional and intraregional domestic cash disbursements. This table contains a pointer to Table IP0053T1 (Interchange Fee Type) to obtain domestic (that is, both customers are located in the same country) cash disbursement fees.

NOTE: Non-domestic cash disbursement fees are obtained using Table IP0052T1 (Interchange Fee Group) and Table IP0053T1 (Interchange Fee Type).

Table Key: The key for this table is positions 1-34.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0045T1
Control Name	20-23	an-4	Valid values: CAPR = Cash Disbursement Presentment CACB = Cash Disbursement Chargeback
Control Pointer	24-34	n-11	This is the pointer to Table IP0053T1 (Interchange Fee Type Table) that identifies the record for cash disbursements.

Table IP0048T1: Settlement Service

This table contains the settlement service ID, settlement transfer agent, and related information for bilateral and intracurrency settlement service agreements.

Processing guidelines for the input source ID field name

The optimize process that runs at Central Site and the Customer Sites will use card PCIP3102 to determine if Input Source ID 1 settlement data or Input Source ID 9 settlement data should be loaded into the one-day file.

The Russian customers (those customers that send IPM inbound files to Mastercard using bulk ID RCA1) should identify 0000000009 as the Input Source ID in card PCIP3102. Russian customers must manually update card PCIP3102 to contain the value in positions 1-10.

Those customers that send IPM inbound files to Mastercard using bulk ID R111 should identify 0000000001 as the Input Source ID in card PCIP3102. The card will contain the correct value and will not need to be modified.

Table Key: The key for this table is positions 1-60.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the Member's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0048T1
Member ID	20-30	n-11	The customer ID.
Settlement Service ID	31-40	ans-10	The settlement service ID in which the customer participates.
Account Reference Code	41-49	an-9	Sequence number identifying the settlement service/transfer agent assignments.
Input Source ID	50-60	n-11	Identifies the system where the record is valid. Valid values: 00000000001 = GCMS 00000000009 = LCMS
Settlement Service Level Priority	61	n-1	The priority used in the selection process.
Settlement Service Level Code	62	an-1	The code that identifies the settlement level of the settlement service. Valid values: 3 = Intracurrency 5 = Bilateral
Settlement Transfer Agent	63-73	an-11	The settlement transfer agent associated with the settlement service.
Filler	74-92	ans-19	Spaces.
Settlement Currency Code	93-95	n-3	The numeric currency code of the settlement service.
Exponent	96	n-1	The exponent for the currency of the service.

Field Name	Positions	Attributes	Comments and Values
Filler	97-108	ans-12	Mastercard use only.

Table IP0050T1: Settlement Service Selection Criteria

This table contains the settlement service ID, and selection criteria for the settlement service agreements specified.

Processing guidelines for the input source ID field name

The optimize process that runs at Central Site and the Customer Sites will use card PCIP3102 to determine if Input Source ID 1 settlement data or Input Source ID 9 settlement data should be loaded into the one-day file.

The Russian customers (those customers that send IPM inbound files to Mastercard using bulk ID RCA1) should identify 0000000009 as the Input Source ID in card PCIP3102. Russian customers must manually update card PCIP3102 to contain the value in positions 1-10.

Those customers that send IPM inbound files to Mastercard using bulk ID R111 should identify 0000000001 as the Input Source ID in card PCIP3102. The card will contain the correct value and will not need to be modified.

Table Key: The key for this table is positions 1-71.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0050T1
Member ID	20-30	n-11	The customer ID.
Settlement Service ID	31-40	an-10	The settlement service ID in which the customer participates.
Account Reference Code	41-49	an-9	Sequence number identifying the settlement service/transfer agent assignments.

Field Name	Positions	Attributes	Comments and Values
Selection Criteria ID	50-60	n-11	Unique identifier relating to the criteria record.
Input Source ID	61-71	n-11	Identifies the system where the record is valid. Valid values: 000000000001 = GCMS 000000000009 = LCMS
Settlement Service Level Priority	72	n-1	The priority used in the selection process.
Settlement Service Level Code	73	an-1	The code that identifies the settlement level of the settlement service. Valid values: 3 = Intracurrency 5 = Bilateral
Acquirer, Issuer, Both Switch	74	an-1	Code indicating the activity allowed by the settlement service. A = Acquirer I = Issuer Both= Both
Effective Date Number	75-85	n-11	Effective date and time, in integer format, applied to the specific select criteria for each settlement service and TAA combination.
Filler	86-97	ans-12	Mastercard use only.

Table IP0052T1: Interchange Fee Group

This table identifies interchange fee groups and contains the data necessary to establish fees for each of the groups.

Table Key: The key for this table is positions 1-44.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attribute	Comments and Values
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0052T1
Card Program Identifier	20-22	an-3	The card program identifier value pertaining to the interchange fee group. Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	n-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator.
Message Type Identifier (MTI)	32-35	n-4	The four-digit descriptor of each IPM message class and function.
Function Code (DE 24)	36-38	n-3	The three-digit Function Code that indicates the message's specific purpose.

Field Name	Positions	Attribute	Comments and Values
Processing Code - Cardholder Transaction Type (DE 3, subfield 1)	39-40	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 =ATM Cash Withdrawal 09 = Purchase with Case Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Processing Code: Cardholder "From" Type (DE 3, subfield 2)	41-42	n-2	The cardholder "From" type field contains the "masked" value for DE 3, subfield 2 as provided in table IP2054T1. Valid values: 00 = Default Account
Processing Code: Cardholder "To" Type (DE 3, subfield 3)	43-44	n-2	The cardholder "To" type. Valid value: 00 = Default Account
Reversal Allowed	45	an-1	Determines whether reversals are permitted for the combination of card program identifier, business service, IRD, MTI, function code, and processing code. B = Both Reversal and non-Reversals R = Reversals only N = non-reversals only

Field Name	Positions	Attribute	Comments and Values
Interchange Compliance Switch	46	an-1	Indicates whether Interchange Compliance processing applies to the card program identifier, business service arrangement, IRD, MTI, function code, and processing code combination. Valid values: N = Not valid for Interchange compliance 1 = Valid for Interchange compliance, U.S. Acquired, U.S. Issued 2 = Valid for Interchange compliance, U.S. Acquired, non U.S. Issued
Fee Code Pointer	47-57	n-11	Pointer to Table IP0053T1 (Interchange Fee Type).
Product Type ID	58	n-1	The product type associated with the interchange fee group. Valid values: 1 = Consumer 2 = Commercial 3 = Both 4 = Other
Timeliness Authorization Code Pointer	59-69	n-11	Pointer to Table IP0059T1 (Timeliness and Authorization Code table).
Product Class: Acceptor Override Pointer	70-80	n-11	Pointer to Table IP0057T1 (Interchange Fee Group Override Parameters Table).
Mastercard Assigned ID Mandatory Indicator	81	an-1	Identifies if Mastercard Assigned ID is mandatory. Valid values: Y = Mastercard assigned ID mandatory N = Mastercard assigned ID not mandatory

Field Name	Positions	Attribute	Comments and Values
Valid Mastercard Assigned ID	82	an-1	Identifies at the acceptance brand, business service arrangement type, Business Service ID Code, Interchange Rate designator combination that the Mastercard Assigned ID should be validated. Valid values: Y = Mastercard Assigned ID will be validated N = Mastercard Assigned ID will not be validated.
Contactless Indicator	83	an-1	Contactless Indicator Valid values: M = Mobile Contactless Enabled N = Not Contactless Enabled or Mobile Contactless Enabled Y = Contactless Enabled Space = Not applicable for editing
Filler	84-100	ans-17	Reserved for future use.

Table IP0053T1: Interchange Fee Type

This table identifies interchange rates, unit fees, and limits for various interchange programs.

Table Key: The key for this table is positions 1-36.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0053T1
Fee Code Pointer	20-30	n-11	The value associated with Table IP0052T1 and IP0057T1

Field Name	Positions	Attribute	Comments and Values
Rate Type	31-33	an-3	The rate type value. Valid values: 000 = Cash Advance Fee (applies to manual cash disbursement transactions) 001 = Interchange Fee 006 = MPP Interchange Fee 007 = National Payment Gateway Switch Fee 010 = VA on interchange fee (specific to Mexico processing) 013 = Late Presentment Fee 014 = First-level Corporate incentive discount 015 = Purchase with Cash Back 017 = Second-level Corporate Incentive discount 018 = New UK Summary VAT Incentive Interchange 020 = Europe Enhanced Value Incentive Rate 021 = MasterPass-Enabled Merchant Incentive Interchange 023 = EC Credit Cross Border Regulated Rate 024 = EC Debit Cross Border Regulated Rate 028 = Digital First Adjustment 030 = Digital Wallet Interchange Rate 031 = Reserved for future use
Payment Party	34-36	an-3	Valid values: ACQ = Acquirer ISS = Issuer INT = Internal
Currency Code-numeric	37-39	n-3	The ISO defined numeric currency code associated with the fee.
Exponent	40	n-1	The currency code exponent associated with the fee currency minimum, and maximum fee limits.
Filler	41-51	an-11	Space filled.
Program Type	52-55	an-4	The program associated with the interchange fee type.

Field Name	Positions	Attribute	Comments and Values
Fee Type Code	56-57	an-2	The code associated with the interchange fee type. Valid value: 00 = Transaction Interchange Fee
No of Fee Segments	58-59	n-2	Number of Fee Segments
Interchange Fee Segment	60 (Varying from 142 to 889)		The following segment of table data occurs 1 to 10 times depending on 'No of Fee Segments'.
Transaction Amount Range Low		n(12) v n(6)	Transaction Amount Range - Low
Interchange Rate		n(5) v n(6)	The interchange rate, as a percentage of the transaction.
Rate Direction		an-2	The direction in which the interchange rate is applied to the specified payment party.
Unit Fee		n(6) v n(6)	If applicable, the unit fee applied to the transaction.
Fee Direction		an-2	The direction in which the interchange unit fees are applied to the specified payment party.
Minimum Fee Limit		an-18	If applicable, the minimum interchange fee amount applied to the transaction. The fee amount will be in the format of n(12) v n(6). Can be space filled if a minimum fee limit does not apply.
Maximum Fee Limit		an-18	If applicable, the maximum interchange fee amount applied to the transaction. The fee amount will be in the format of n(12) v n(6). Can be space filled if a maximum fee limit does not apply.
Minimum-maximum Direction		an-2	The direction in which the minimum and/or maximum interchange fees are applied to the specified payment party.

Table IP0054T1: Retrieval Fee

This table identifies retrieval fee by card program identifier, document type, and currency.

Table Key: The key for this table is positions 1-23.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0054T1
Card Program Identifier	20-22	an-3	The card program identifier associated with the retrieval fee.
Documentation Type	23	n-1	The documentation type associated with the retrieval fee. Valid value: 1 = Hard copy original document
Currency - numeric	24-26	n-3	The ISO defined numeric currency code associated with the retrieval fee.
Currency Exponent	27	n-1	The currency code exponent associated with the currency code of the retrieval fee.
Default Fee	28-38	n(6) v n(5)	

Table IP0056T1: Member Business Service Arrangements

This table identifies the valid card program identifier and business service arrangement participation information for a member. This information is a compilation of the card program identifier and business service arrangement participation maintained at the issuer account range and acquiring BIN levels for each customer ID.

Table Key: The key for this table is positions 1-44.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

About IPM Mastercard Parameter Extract
Table IP0056T1: Member Business Service Arrangements

Field Name	Positions	Attribute	Comments and Values
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0056T1
Member ID	20-30	n-11	The member ID associated with the member business agreement.
Member Business Service Arrangement Priority Code	31-32	n-2	The priority of the business service arrangement.
Business Service Arrangement Type	33	n-1	The business service arrangement type.
Business Service Arrangement ID Code	34-39	an-6	The business service arrangement ID code.
Card Program Identifier Priority Code	40-41	n-2	The priority of the card program identifier in relation to its use with the member ID and business service arrangement combination.
Card Program Identifier	42-44	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Life Cycle Indicator	45	an-1	The business service life cycle indicator. Valid values:
Business Service Arrangement Life Cycle Indicator	45	an-1	The business service life cycle indicator. Valid values: A = All transactions may be submitted for this business service arrangement. L = Life cycle; only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Filler	46-52	ans-7	Reserved for future use.

Table IP0057T1: Interchange Override Fee Group

This table identifies interchange fees which vary by product class, acceptor business code (MCC), acceptor business code (MCC) type, and Mastercard assigned ID overrides.

Table 25: Table IP0057T1: Interchange Override Fee Group

Table Key: The key for this table is positions 1-41.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A =Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0057T1
Product Class - Acceptor Override Pointer	20-30	n-11	The value associated with Table IP0052T1.
Override Item ID	31-41	n-11	Item ID associated to override items
Product Class	42-44	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Acceptor Business Code (MCC)	45-48	an-4	Valid values are listed in the <i>Mastercard Quick Reference Booklet</i> .

About IPM Mastercard Parameter Extract
Table IP0057T1: Interchange Override Fee Group

Field Name	Positions	Attribute	Comments and Values
Acceptor Business Code (MCC) Type Redefines Acceptor Business Code (MCC)	45	an-1	Valid values: A = Passenger Transport: Airline B = Cruise Line/Steamship C = Cash Disbursement D = Payment Transaction F = Restaurant H = Lodging M = Mail Order/Telephone Order P = Beauty Salons R = Passenger Transport: Railway S = Supermarket T = Telephone U = Unique V = Automobile/Vehicle Rental W = Warehouse Club Z = ATM 1 = All others (The Acceptor Business Codes [MCCs] on the record do not belong to a particular clearing Group Code.)
	46-48	ans-3	Filler
Mastercard Assigned ID	49-54	an-6	The Mastercard Assigned ID
Override Priority Code	55-56	n-2	If a transaction qualifies for more than one override, the clearing system will check for combinations of overrides and apply the override based on the override priority code.
Fee Code Pointer	57-67	n-11	Pointer to table IP0053T1 (Interchange Fee Type)
Filler	68-78	ans-11	Reserved for future use.

Table IP0058T1: QPS and Contactless Chargeback Protection Amounts

This table contains the list of QPS and Contactless chargeback protection amounts.

Table Key: The key for this table is positions 1-41.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File. I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0058T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Chargeback Protection Type	23	an-1	Chargeback Protection Type Valid values: A = Post-Authorized Aggregated Contactless Transit P = Contactless Q = QPS
Acceptor Business Code (MCC)	24-28	n-5	Valid values are listed in the Mastercard <i>Quick Reference Booklet</i> . When this field is populated with zeros, it represents any MCC.

Field Name	Positions	Attribute	Comments and Values
Region	29	n-1	Region of the associated country. Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa Space = Represents any region
Country Code— Numeric	30-32	n-3	The numeric country code established by the International Organization for Standardization (ISO). When this field is populated with zeros, it represents any country code.
Country Code: Alpha	33-35	an-3	The alphanumeric country code established by Mastercard. When this field is populated with spaces, it represents any country code.
Currency Code: Numeric	36-38	n-3	The numeric currency code associated with the country code established by ISO.
Currency Code: Alpha	39-41	an-3	The alpha currency code associated with the country code.
Currency Exponent	42	n-1	Currency Exponent
Chargeback Protection Amount	43-54	n-12	Chargeback Protection Amount

Table IP0059T1: Timeliness Code

This table identifies the codes for timeliness and authorization.

Table Key: The key for this table is positions 1-31.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0059T1
Authorization Timeliness Code Pointer	20-30	n-11	This value is from Table IP0052T1 (Interchange Fee Group), and indicates the applicable timeliness and authorization code criteria.
System Application	31	an-1	Valid values: 1 = Global Clearing Management System and Clearing Optimizer application 2 = Interchange Compliance System
Timeliness Data - Two Occurrences	32-51		The remaining entries occur twice. The first occurrence is for non-airline and the second is for airline.
Airline Indicator		an-1	Valid values: Y = Yes: Record is for airline transactions N = No: Record is for non-airline transactions
Submission Time Frame		n-4	Valid values: 0000 = No submission timeframe required 0001-9999 = Valid values for submission timeframes
Exclude Non-Processing Days Switch		an-1	If the exclude non-processing days switch is "Y" GCMS will query the individual day exclusion switches to determine which days to exclude. If this switch is "N," GCMS will not query the individual day exclusion switches, and will not perform this exclusion. Valid values: Y = Exclude non-processing days N = Do not exclude non-processing days

Field Name	Positions	Attribute	Comments and Values
Holiday Exclusion		an-1	Exclude Holiday in calculation. Valid values: Y = Exclude Holiday N = Include Holiday
Transaction Date Exclusion		an-1	Exclude Transaction Date in calculation. Valid values: Y = Exclude Transaction Date N = Include Transaction Date
Header Processing Date Exclusion		an-1	Exclude Header Processing Date in calculation. Valid values: Y = Exclude Header Processing Date N = Include Header Processing Date
Authorization Indicator		an-1	Valid values: Y = Standard authorization code edits will be applied to transactions submitted with the interchange rate indicator specified in the record. N = Standard authorization code edits will not be applied.

Table IP0060T1: Timeliness Holiday

This table identifies the timeliness holiday parameters.

Table Key: The key for this table is positions 1-26.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0060T1

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	20	an-1	The business service arrangement type.
Business Service ID Code	21-26	an-6	The business service arrangement ID code.
Sunday Exclusion	27	an-1	Exclude Sunday in calculation. Valid values: Y = Exclude Sunday N = Include Sunday
Monday Exclusion	28	an-1	Exclude Monday in calculation. Valid values: Y = Exclude Monday N = Include Monday
Tuesday Exclusion	29	an-1	Exclude Tuesday in calculation. Valid values: Y = Exclude Tuesday N = Include Tuesday
Wednesday Exclusion	30	an-1	Exclude Wednesday in calculation. Valid values: Y = Exclude Wednesday N = Include Wednesday
Thursday Exclusion	31	an-1	Exclude Thursday in calculation. Valid values: Y = Exclude Thursday N = Include Thursday
Friday Exclusion	32	an-1	Exclude Friday in calculation. Valid values: Y = Exclude Friday N = Include Friday
Saturday Exclusion	33	an-1	Exclude Saturday in calculation. Valid values: Y = Exclude Saturday N = Include Saturday
Holidays	34-183	n-5	30 Occurrences Format is YYDDD, where YY is positions three and four of the four-position year, and DDD is the Julian date.

Table IP0064T1: Transaction Function Group Code Table

This table contains the Transaction Function Group Codes for each MTI/Function Code combination. This table can be used to determine the Transaction Function group Code for a given MTI/Function Code combination. The Transaction Function Group Code is optionally used in Settlement Service Selection Criteria (refer to table IP0050T1).

Table Key: The key for this table is positions 1-26.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	ans-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	ans-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	ans-8	Unique identifier of this IPM table. Valid value: IP0064T1
Message Type Identifier (MTI)	20-23	n-4	The MTI of the specified Transaction Function Group Code.
Function Code	24-26	n-3	The function code (DE 24) of the specified Transaction Function Group Code.
Transaction Function Group Code	27-28	ans-2	The Transaction Function Group Code. Valid values are: FP = First Presentment SP = Second Presentment FC = First Chargeback AC = Arbitration Chargeback FE = Fee Collections NF = Non-Financials

Table IP0069T1: Global Currency

This table contains the numeric currency code and the currency code exponent for the currency designated for system balancing.

Table Key: The key for this table is positions 1-22.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0069T1
Global Currency Code - numeric	20-22	n-3	The ISO defined numeric currency code designating the Global Currency.
Global Currency Exponent	23	n-1	The currency code exponent for the Global Currency code.

Table IP0070T1: Common Area

This table defines a common area used in GCMS programs. This table contains a row for each internally used data field present in this common area.

Table Key: The key for this table is positions 1-24.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0070T1
Field Number	20-24	n-5	The field number of the specific data field.
Field Creator	25-36	an-12	A description of the creator of the field; for informational purposes only.
Field Description	37-96	an-60	A description of the specific data field.

Field Name	Positions	Attribute	Comments and Values
Field Length	97-100	n-4	The length of the specific data field.

Table IP0071T1: Chip Liability Shift Country Exclusions

This table contains the business service arrangement/country combinations that are excluded from the Chip Liability Shift Program.

Table Key: The key for this table is positions 1-29.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0071T1
Business Service Arrangement Type	20	an-1	The business service arrangement type.
Business Service ID Code	21-26	an-6	The business service arrangement ID code.
Country Code: Numeric	27-29	n-3	The numeric country code established by the International Organization for Standardization (ISO).
Country Code: Alpha	30-32	an-3	The alphanumeric country code established by Mastercard.

Table IP0072T1: Expanded Member ID Master

This table provides the layout of the expanded member parameter master file, containing fields that support both GCMS and Clearing Optimizer processing.

Table Key: The key for this table is positions 1-30.

About IPM Mastercard Parameter Extract
Table IP0072T1: Expanded Member ID Master

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0072T1
Member ID	20-30	n-11	The member ID pertaining to the customer profile described.
Filler	31	an-1	Space filled. (Mastercard use only)
Filler	32	an-1	Space filled. (Mastercard use only)
Interchange Region	33	an-1	Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
International Electronic Interchange (IEI) Qualifier	34-35	an-2	Valid values: 00 = Not Qualified for IEI 01 = IEI Qualified
Internal Member ID Indicator	36	an-1	Valid values: Space = Not Internal Use (This is a Member ICA) B = Cannot be debited or credited C = Cannot be credited D = Cannot be debited

Field Name	Positions	Attribute	Comments and Values
Acquirer Switch	37	an-1	Valid values: A = Acquirer Only I = Issuer Only Space = Both Issuer and Acquirer
ATM Indicator	38	an-1	Valid values: Space = ATM non-participant 1 = The MDS outside of Europe 2 = Non-MDS customer outside of Europe 3 = Not currently in use 4 = The MDS in Europe 5 = Non-MDS customer in Europe
RCL Region	39	an-1	The Mastercard-defined region for restricted or negative card accounts. Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Endpoint	40-46	n-7	This is the default routing endpoint at the member ID level.
World Member ID Chargeback Switch	47	an-1	Valid values: Y = Applies to World Card chargeback limits N = Does not apply to World Card chargeback limits

Field Name	Positions	Attribute	Comments and Values
World Card Acceptor Business Code (MCC) Group CD1	48	an-1	Valid values: A = Passenger Transport: Airline B = Cruise Line/Steamship C = Cash Disbursement D = Payment Transaction F = Restaurant H = Lodging M = Mail Order/Telephone Order P = Beauty Salons R = Passenger Transport: Railway S = Supermarket T = Telephone U = Unique V = Automobile/Vehicle Rental W = Warehouse Club Z = ATM 1 = All others Space = not applicable to World Card
World Card Acceptor Business Code (MCC) Group CD2	49	an-1	Same as Group CD 1
World Card Acceptor Business Code (MCC) Group CD3	50	an-1	Same as Group CD 1
World Card Acceptor Business Code (MCC) Group CD4	51	an-1	Same as Group CD 1

Field Name	Positions	Attribute	Comments and Values
World Card Acceptor Business Code (MCC) Group CD5	52	an-1	Same as Group CD 1
Filler	53	an-1	Space filled. (Mastercard use only)
Member Name	54-83	an-30	The customer name.
Country Code	84-86	an-3	Alphabetic country code established by Mastercard.
Country Code ISO	87-89	n-3	Numeric country code established by ISO.
Filler (reserved for internal use)	90	an-1	Space filled.
Filler (reserved for internal use)	91-96	n-6	Zero filled.
Filler (reserved for internal use)	97-98	an-2	Space filled.
Filler (reserved for internal use)	99-110	n-12	Zero filled.
Outbound Format Indicator	111	an-1	Indicates the message format that the customer receives from Mastercard. Valid values: 2 = IPM Format 4 = RAW data to XML 5 = RAW data file 6 = Japan Domestic Format 8 = Credit and Installment data
Mastercard Electronic Card Indicator	112	an-1	Valid values: C = Acquirer and its merchants do not participate E = Acquirer and its merchants participate U = Unidentified acquirer

Field Name	Positions	Attribute	Comments and Values
EEA Acquirer Country Service ICA	113	ans-1	EEA Acquirer Country Service ICA Valid values: Y = EEA Acquirer Country Participant N = Not an EEA Acquirer Country Participant
Filler	114	an-1	Reserved for future use.
National Payment Gateway Processor Switch	115	an-1	National Payment Gateway Processor ICA Valid values: Y = ICA is a National Payment Gateway Processor N = ICA is not a National Payment Gateway Processor
Limited License Payment Transfer Activity Participation Indicator	116	an-1	Indicates Limited License Payment Transfer Activity Participation Valid values: Y = Limited License Payment Transfer Activity participant N = Not a Limited License Payment Transfer Activity participant
Embedded Flex Interchange Indicator	117	an-1	Indicates Embedded Flex Interchange participation. Valid values: Y = Issuer Embedded Flex Interchange Participant N = Not Issuer Embedded Flex Interchange Participant
Filler	118-209	ans-92	Reserved for future use.

Table IP0074T1: IFC Gaming

This table contains the amount limits for clearing transactions that involve In-flight Commerce (IFC) gaming amounts.

Table Key: The key for this table is positions 1-28.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0074T1
Point-of-Interaction Terminal Type	20-22	an-3	Valid value: CT4 = CAT Level 4 (In-Flight Commerce Terminal)
Acceptor Business Code (MCC)	23-26	n-4	Valid value: 7995 = Gaming Transactions
Processing Code (DE 3)	27-28	n-2	Valid values: 18 = Unique 20 = Credit
Amount	29-40	n-12	The amount limit for transactions with the combination of parameters shown in this table.
Currency Code-numeric	41-43	n-3	The ISO defined numeric currency code associated with the amount.
Currency Exponent	44	n-1	The currency code exponent for the currency code associated with the amount.

Table IP0075T1: Acceptor Business Codes (MCCs)

Customers use this table to identify all acceptor business codes (MCCs) that Mastercard supports; both current and obsolete. GCMS rejects any transaction with a acceptor business code (MCC) value that is not in this table.

Table Key: The key for this table is positions 1-28.

About IPM Mastercard Parameter Extract
Table IP0075T1: Acceptor Business Codes (MCCs)

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0075T1
Acceptor Business Code (MCC)	20-24	n-5	Valid values are listed in the Mastercard <i>Quick Reference Booklet</i> .
Acceptor Business (AB) Program	25-28	an-4	The four-digit MCC program associated to the MCC value.
Acceptor Business (AB) Program Life Cycle Indicator	29	an-1	Acceptor Program Life Cycle Indicator. Valid values: A = All transactions may be submitted with this AB program. L = Life Cycle: only transactions designated as "life cycle" transactions may be submitted with this AB program.

About IPM Mastercard Parameter Extract
Table IP0075T1: Acceptor Business Codes (MCCs)

Field Name	Positions	Attribute	Comments and Values
Acceptor Business (AB) Type	30	an-1	Valid values: A = Passenger Transport Airline B = Cruise Line/Steamship C = Cash Disbursement D = Payment Transaction F = Restaurant H = Lodging M = Non-Face-to-Face P = Beauty Salons R = Passenger Transport: Railway S = Supermarket T = Telephone U = Unique V = Automobile/Vehicle Rental W = Warehouse Club Z = ATM 1 = All other 2 = Spain Domestic Local Processing 2 3 = Portugal Large Merchants 4 = Portugal Unique Ab Codes 5 = Spain Unique Ab Codes 6 = Mexico Unique Ab Codes 7 = Mastercard proprietary use 8 = Mastercard proprietary use 9 = MoneySend
Acceptor Business (AB) Life Cycle Indicator	31	an-1	Valid values: A = Active L = Obsolete
Filler	32-51	an-20	Reserved for future use.

Table IP0076T1: Mastercard Assigned IDs

This table will contain the Mastercard Assigned IDs.

Table 26: Table IP0076T1: Mastercard Assigned IDs

Table Key: The key for this table is positions 1-25

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0076T1
Mastercard Assigned ID	20-25	an-6	Mastercard Assigned ID.
Life cycle Indicator	26	an-1	The Life Cycle indicator. Valid values: A = Valid for all messages L = Valid for life cycle messages only
Filler	27	an-1	Space filled. (Mastercard use only)
IIAS Participation Switch	28	an-1	IIAS Participation Indicator. Valid values: N = The Mastercard Assigned ID is not an IIAS participant. Y = The Mastercard Assigned ID is an IIAS participant.
PVL Participation Switch	29	an-1	Private Label (PVL) Participation Indicator . Valid values: N = The Mastercard Assigned ID is not an PVL participant. Y = The Mastercard Assigned ID is an PVL participant.
Filler	30-46	an-17	Space filled

Field Name	Positions	Attribute	Comments and Values
Merchant MARP Full UCAF Participation Switch	47	an-1	Merchant Maestro Advanced Registration Program Full UCAF Participation Switch. Valid values: Y = Merchant does participate in MARP Full UCAF N = Merchant does not participate in MARP Full UCAF
Filler	48-54	ans-7	Central Site Use Only

Table IP0087T1: Masked Business Services and Interchange Rate Designators

This table contains the masked business service arrangements and interchange rate designators.

GCMS finds the combination of Card Program Identifier, Business Service Arrangement Type, Business Service ID, and Interchange Designator in table IP0087T1 to see if it is masked to another business service arrangement and interchange rate designator.

- If there is no entry in table IP0087T1 that matches all of these values, then the business service arrangement is not masked and GCMS performs all table finds using the actual card program identifier and business service arrangement values.
- If there is an entry in table IP0087T1 that matches all of these values, then GCMS obtains the related "Masked Card Program Identifier," "Masked Business Service Arrangement Type," "Masked Business Service ID," and "Masked Interchange Designator" and performs table IP0095T1 and IP0096T1 finds using these masked values instead of the actual card program identifier, business service arrangement, and interchange designator values.

Table Key: The key for this table is positions 1-31.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0087T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator.
Masked Card Program Identifier	32-34	an-3	Card program identifier which is masked to card program identifier.
Masked Business Service Arrangement Type	35	an-1	Business Service Arrangement Type masked to Business Service Arrangement Type
Masked Business Service ID	36-41	an-6	Business Service ID masked to Business Service ID
Masked IRD	42-43	an-2	Interchange rate designator masked to interchange rate designator.

Table IP0088T1: Masked Business Services

This table contains the masked business service arrangements.

GCMS finds the combination of Card Program Identifier, Business Service Arrangement Type, and Business Service ID in table IP0088T1 to see if it is masked to another business service arrangement.

- If there is no entry in table IP0088T1 that matches all of these values, then the business service arrangement is not masked and GCMS performs all table finds using the actual card program identifier and business service arrangement values.
- If there is an entry in table IP0088T1 that matches all of these values, then GCMS obtains the related "Masked Card Program Identifier," "Masked Business Service Arrangement Type," and "Masked Business Service ID" and performs table IP0098T1 and IP0097T1 finds using these masked values instead of the actual card program identifier and business service arrangement values.

Table Key: The key for this table is positions 1-30.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0088T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Masked Type	30	an-1	Type of mask. Valid value: R = Restrictions
Masked Card Program Identifier	31-33	an-3	Card Program Identifier which is masked to Card Program Identifier
Masked Business Service Arrangement Type	34	an-1	Business Service Arrangement Type masked to Business Service Arrangement Type
Masked Business Service ID	35-40	an-6	Business Service ID masked to Business Service ID

Table IP0089T1: Business Service Switches

This table contains business service switches information.

Table Key: The key for this table is positions 1-26.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the Member's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0089T1
Business Service Arrangement Type	20	an-1	The business service arrangement type.
Business Service ID Code	21-26	an-6	The business service arrangement ID code.
Filler	27-30	ans-4	Spaces
Central Acquired Switch	31	an-1	Indicates if Central Acquiring logic should apply. Valid values: Y = Apply Central Acquiring logic. The Member-to-Member business service arrangement cannot be applied to a centrally acquired transaction. N = Do not apply Central Acquiring logic. The Member-to-Member business service arrangement can be applied to a centrally acquired transaction.

Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation

This table identifies the card program identifier and business service arrangements associated with an issuer account range. Each unique issuer account range, business service arrangement

About IPM Mastercard Parameter Extract
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service
Arrangement Participation

type, business service ID code, and card program identifier combination generates a separate record of this type.

Table Key: The key for this table is positions 1-48.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0090T1
Issuer Account Range-Low	20-38	an-19	The account number at the low end of the issuing account range associated to the card program identifier and business service arrangement combination.
Business Service Arrangement Type	39	an-1	The business service arrangement type.
Business Service ID Code	40-45	an-6	The business service arrangement ID code.
Card Program Identifier	46-48	an-3	Mastercard or other proprietary service mark.
Issuer Account Range-High	49-67	an-19	The account number at the high end of the issuing account range associated to the card program identifier and business service arrangement combination.
Business Service Arrangement Type Priority	68-69	n-2	The priority of the business service arrangement type.
Issuer Card Program Identifier Priority Code	70-71	n-2	The priority of the issuer card program identifier in relation to its use with the account range and business service arrangement combination.

About IPM Mastercard Parameter Extract
Table IP0092T1: Transaction Functions Requiring Business Service Processing

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Life Cycle Indicator	72	an-1	The business service life cycle indicator. Valid values: A = All transactions may be submitted for this business service arrangement. L = Life Cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Business Service Selection Enforcement Indicator	73	an-1	The business service arrangement enforcement indicator. Valid values: Space = Default value. Not a mandatory business service arrangement. A = This is a mandatory business service arrangement. The mandate applies to all valid message types F = This is a mandatory business service arrangement. The mandate applies only to First Presentments.
Filler	74-80	ans-7	Reserved for future use.

Table IP0092T1: Transaction Functions Requiring Business Service Processing

This table identifies the transaction functions (MTI/Function Code [DE24] combinations) that require business service processing.

Table Key: The key for this table is positions 1-26.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter

About IPM Mastercard Parameter Extract
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0092T1
Message Type Identifier (MTI)	20-23	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	24-26	n-3	The three-digit Function Code that indicates the message's specific purpose.
Requires Business Service Processing Switch	27	an-1	Identifies whether the transaction function (combination of MTI and Function Code) is subject to business service processing. Y = Business service processing applies to this transaction function. N = Business service processing does not apply to this transaction function.

Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

This table identifies the card program identifier and business service arrangements associated with an acquiring BIN. Each unique acquiring BIN, card program identifier, business service arrangement type, and business service ID code combination generates a separate record of this type.

Table Key: The key for this table is positions 1-35.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0091T1

Field Name	Positions	Attribute	Comments and Values
Acquiring BIN	20-25	n-6	The six-position acquiring BIN associated with the card program identifier and business service arrangement information.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Card Program Identifier	33-35	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type Priority	36-37	n-2	The priority of the business service arrangement type.
Business Service Arrangement Life Cycle Indicator	38	an-1	The business service life cycle indicator. Valid values are: A = All transactions may be submitted for this business service arrangement. L = Life Cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Filler	39-59	ans-21	Reserved for future use.

Table IP0093T1: Intracountry Business Service Override

This table contains issuer account ranges and related business service arrangements in which the merchant country code must equal the country code of the acquiring BIN and issuing account range in order to qualify for the country's intracountry business service arrangement.

Table Key: The key for this table is positions 1-45.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

About IPM Mastercard Parameter Extract

Table IP0094T1: Geographic Restrictions for Card Program Identifier Business Service Arrangement, and IRD

Field Name	Positions	Attribute	Comments and Values
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0093T1
Issuer Account Range: Low	20-38	an-19	The account number at the low end of the issuing account range associated to the business service arrangement.
Business Service Arrangement Type	39	an-1	The business service arrangement type
Business Service ID Code	40-45	an-6	The business service arrangement ID code
Issuer Account Range: High	46-64	an-19	The account number at the high end of the issuing account range associated to the business service arrangement.

Table IP0094T1: Geographic Restrictions for Card Program Identifier Business Service Arrangement, and IRD

Customers use this table to validate selection criteria. It lists the valid country codes and regions for a card program identifier and business service arrangement combination. Each country and region associated to a business service arrangement combination will have a unique entry in this table.

Table Key: The key for this table is positions 1-33.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File A = Add this record to Parameter Master File I = This is an inactive parameter

About IPM Mastercard Parameter Extract

Table IP0094T1: Geographic Restrictions for Card Program Identifier Business Service Arrangement, and IRD

Field Name	Positions	Attribute	Comments and Values
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0094T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Country	30-32	an-3	The alphanumeric country code of the country associated to the card program identifier, business service arrangement type, business service ID and IRD.
Region	33	an-1	The region associated to the card program identifier, business service arrangement type, business service ID and IRD.
Country Life Cycle Indicator	34	an-1	Country Life Cycle Indicator. Valid values: A = All transactions L = Life Cycle transactions only Space = Not applicable to country Life Cycle Indicator
Region Life Cycle Indicator	35	an-1	Region Life Cycle Indicator. Valid values: A = All transactions L = Life Cycle transactions only Space = Not applicable to region Life Cycle Indicator

Table IP0095T1: Acceptor Business Program Restrictions

This table is used to validate selection criteria. It identifies the valid acceptor business (AB) programs for the combination of Card Program Identifier, business service arrangement, and IRD.

Table Key: The key for this table is positions 1-35.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0095T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator
Acceptor Business (AB) Program	32-35	an-4	The four-position acceptor business program valid for the card program identifier, business service arrangement type, business service ID and IRD.
Life Cycle Indicator	36	an-1	The Life Cycle Indicator for the card program identifier, business service arrangement type, business service ID, IRD and AB program. Valid values: A = All transactions L = Life Cycle transactions only

Table IP0096T1: Card Program Identifier and Product Restrictions

This table is used to validate selection criteria. It identifies the valid GCMS Product Codes for a Card Program Identifier, business service arrangement, and IRD combination.

Table Key: The key for this table is positions 1-34.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0096T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	30-31	an-2	The interchange rate designator.
GCMS Product ID	32-34	an-3	The three-position GCMS Product IDs that are valid for the card program identifier, business service arrangement type, business service ID code, and IRD.
Life Cycle Indicator	35	an-1	The Life Cycle Indicator for the card program identifier, business service arrangement type, business service ID, IRD, and GCMS Product Code. Valid values: A = All transactions L = Life Cycle transactions only

Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement

This table is used to validate selection criteria. It indicates the valid Message Reason Codes for a Card Program Identifier, business service arrangement and transaction function/reversal indicator combination.

Table Key: The key for this table is positions 1-40.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0097T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark. Field will contain the "masked" value for the business service arrangement if the arrangement is listed in Table IP0088T1.
Business Service Arrangement Type	23	an-1	The business service arrangement type. Field will contain the "masked" value for the business service arrangement if the arrangement is listed in Table IP0088T1.
Business Service ID Code	24-29	an-6	The business service arrangement ID code. Field will contain the "masked" value for the business service arrangement if the arrangement is listed in Table IP0088T1.
Message Type Identifier (MTI)	30-33	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	34-36	n-3	The three-digit Function Code that indicates the message's specific purpose.
Message Reason Code (DE 25)	37-40	an-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.

About IPM Mastercard Parameter Extract

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attributes	Comments and Values
Reversal Indicator	41	an-1	The reversal indicator value associated to the card program identifier, business service arrangement type, MTI, function code, and message reason code combination. Valid values: B = Both Reversal and non-Reversals are permitted R = Reversals only are permitted N = Non-reversals only are permitted
Chargeback Support Documentation Requirement	42	an-1	Valid values: A = Documentation is always required. O = Documentation is sometimes required. N = Documentation is never required.
Fee Processing Impact Switch.	43	an-1	Valid values: Y = Interchange fee applies. N = Interchange fee does not apply.
Fee Collection Maximum Amount	44-55	n-12	Only used for Fee Collection 1740 messages. For any messages other than Fee Collections, this is zero filled.
Fee Collection Maximum Amount Currency	56-58	n-3	A valid ISO defined numeric currency code, representing the currency defined in the Fee Collection Maximum Amount.
Fee Collection Maximum Amount Currency Exponent	59	n-1	A valid ISO defined currency exponent for the corresponding currency code.

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

This table is used to validate selection criteria. It lists the valid Processing Code/Reversal Indicator values for a Card Program Identifier, business service arrangement, and transaction function combination. It also indicates the transaction function/processing code combinations that require interchange rate designator validation for a given card program identifier and business service arrangement combination.

Table Key: The key for this table is positions 1-42.

About IPM Mastercard Parameter Extract

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0098T1
Card Program Identifier	20-22	an-3	Mastercard or other proprietary service mark. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.
Business Service Arrangement Type	23	an-1	The business service arrangement type. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.
Business Service ID Code	24-29	an-6	The business service arrangement ID code. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.
Message Type Identifier (MTI)	30-33	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	34-36	n-3	The three-digit Function Code that indicates the message's specific purpose.

About IPM Mastercard Parameter Extract

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attributes	Comments and Values
Processing Code (DE 3, subfield 1)	37-38	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 = ATM Cash Withdrawal 09 = Purchase with Cash Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Processing Code —Cardholder "From" Type (DE 3, subfield 2)	39-40	n-2	The Cardholder "From" Type field contains the "masked" value for DE 3, subfield 2 as provided in Table IP2054T1. Valid value: 00 = Default Account
Processing Code —Cardholder "To" Type (DE 3, subfield 3)	41-42	n-2	The Cardholder "To" Type. Valid value: 00 = Default Account
Reversal Indicator	43	an-1	The reversal indicator value associated to the card program identifier, business service arrangement type, MTI, Function Code and Processing Code combination. Valid values: B = Both Reversals and non-Reversals are permitted R = Reversals only are permitted N = Non-reversals only are permitted
Requires IRD Validation Switch	44	an-1	Requires IRD Validation switch associated to the card program identifier, business service arrangement type, MTI, Function Code and Processing Code combination. Valid values: Y = Requires IRD validation N = Does not require IRD validation

Field Name	Positions	Attributes	Comments and Values
Extended Decimal Interchange Indicator	45	an-1	Extended Decimal Interchange Indicator. Valid values: Space = Do not apply Extended Decimal precision 6 = Apply Extended Decimal Precision
Exception Rate Override Switch	46	an-1	Exception Rate Override Switch identifies whether the commercial refund transaction interchange fee will be calculated based on the original purchase interchange rates and unit fees. Valid values: Y = Exception Rate Override applies N = Exception Rate Override does not apply

Table IP0099T1: Transaction Currency Qualification

For business service arrangements existing in this table, the transaction currency of the message must equal the transaction currency of the business service arrangement for the transaction to qualify for that specific arrangement. This table applies to intra-European transactions only.

Table Key: The key for this table is positions 1-29.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0099T1
Numeric Country Code	20-22	an-3	The card program identifier associated to the account range. Mastercard or other proprietary service mark.

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	23	an-1	The business service arrangement type
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Transaction Currency Code	30-32	n-3	The transaction currency code associated to the business service arrangement.

Table IP0105T1: New Product Code Mapping

The new Product Code Mapping table maps an existing Brand Product code to a new Brand Product code associated to a Country or Region.

Table Key: The key for this table is positions 1-29.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0105T1
Region	20	n-1	The region of the associated country code. 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Country Code	21-23	an-3	The alphanumeric country code established by Mastercard.

Field Name	Positions	Attribute	Comments and Values
Existing Licensed Product Code	24-26	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
New Licensed Product Code	27-29	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Table IP0106T1: Issuer Participation Activation/Deactivation

Customers use this table to identify the active/inactive status for a new product.

Table Key: The key for this table is positions 1-57.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0106T1
Issuer Account Range—Low	20-38	an-19	The account number at the low end of the issuing account range.
Issuer Account Range—High	39-57	an-19	The account number at the high end of the issuing account range.
Effective Date (occurs 5 times)	58-117	n-60	The date(s) when a new product is in effect.
Starting Effective Date		n-6	Starting effective date of new product.
Ending Effective Date		n-6	Ending effective date of new product.

Table IP0128T1: Tiered Debit U.S. and Territories

This table identifies the countries (U.S. and territories) that must adhere to the Durbin (Tiered Debit) regulation.

Table Key: The key for this table is positions 1-22.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0128T1
Numeric Country Code	20-22	n-3	Numeric Country Code

Table IP0132T1: Anonymous Prepaid Countries

This table contains the countries that will determine anonymous prepaid program transactions that are to be blocked.

Table Key: The key for this table is positions 1-21.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0132T1

Field Name	Positions	Attribute	Comments and Values
Service Code	20-21	an-2	Service Code
Number of Entries	22-23	n-2	Number of country code entries
Country Code (occurs from 1 to 50 times)	24-173		Country Code (occurs up to 50 times)
Country Code		an-3	Country Code

Table IP0137T1: Brazil Flex Mapping

This table consists of account range product code mapping to a debit product code.

Table Key: The key for this table is positions 1-58.

Field name	Positions	Attribute	Comments and values
Effective Date and Time	01-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	ans-8	Unique identifier of this IPM table. Valid value: IP0137T1
Issuer Account Range - Low	20-38	an-19	The account number at the low end of the account range.
Issuer Account Range - High	39-57	an-19	The account number at the high end of the account range.

Field name	Positions	Attribute	Comments and values
Product Type ID	58	an-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Existing Product ID	59-61	an-3	Product ID attached with Issuer PAN range
New Product ID (Debit/Prepaid)	62-64	an-3	Flex Debit and Prepaid Product ID

Table IP0138T1: Authentication Enforcement

This table consists of categories based on unique combination values of Electronic Commerce Security Level Indicator (PDS 0052) and/or Accountholder Authentication Value (PDS 0185).

Table 27: Table IP0138T1: Authentication Enforcement

Table Key: The key for this table is positions 1-25.

Field name	Positions	Attribute	Comments and values
Effective Date and Time	01-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0138T1

About IPM Mastercard Parameter Extract
Table IP0138T1: Authentication Enforcement

Field name	Positions	Attribute	Comments and values
Category	20	n-1	Category field Valid values: 1=Authenticated Frictionless 2=Authenticated but not Frictionless 3=Sent to 3DS Frictionless but not Authenticated 4=Not Sent to 3DS
Electronic Commerce SLI	21-23	ans-3	This field will contain values as described in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> for PDS 0052 (Electronic Commerce Security Level Indicator), subfield 1 (Security Protocol), subfield 2 (Cardholder Authentication), and subfield 3 (UCAF Collection Indicator). Not present is a valid value.
AAV	24-25	ans-2	This field will contain values as described in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> for PDS 0185 (Accountholder Authentication Value). Not present is a valid value.

Table IP0142T1: Business Service Selection Enforcement

This table contains the valid IRD's associated to each Card Program Identifier/Business Service Arrangement Type/Business Service ID Code, MTI, Function Code/Processing Code combination, where there is a mandatory business service arrangement.

Table 28: Table IP0142T1: Business Service Selection Enforcement

Table Key: The key for this table is positions 1-38.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0142T1
Card Program Identifier	20-22	an-3	The card program identifier value pertaining to the interchange fee group. Mastercard or other proprietary service mark.
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Message Type Identifier (MTI)	30-33	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	34-36	n-3	The three-digit Function Code that indicates the message's specific purpose.

Field Name	Positions	Attribute	Comments and Values
Processing Code - Cardholder Transaction Type (DE 3, subfield 1)	37-38	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 = ATM Cash Withdrawal 09 = Purchase with Cash Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Interchange Rate Designator (IRD)	39-40	an-2	The interchange rate designator.

Table IP0144T1: Processing Code and Transaction Type Indicator

This table consists of interchange rate designator, the mapping processing code, and the transaction type indicator (TTI).

Table 29: Table IP0144T1: Processing Code and Transaction Type Indicator

Field name	Positions	Attribute	Comments and values
Effective date and time	01-10	n-10	Date and time that the information in this record becomes effective or was last updated Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File A = Add this record to Parameter Master File I = This is an inactive parameter

Field name	Positions	Attribute	Comments and values
Table ID	12-19	an-8	Unique identifier of this IPM table Valid value: IP0144T1
Interchange Rate Designator (IRD)	20-21	an-2	The interchange rate designator
Processing code	22-23	n-2	Processing code
Transaction type identifier	24-26	an-3	The three-digit MoneySend Transaction Type ID
Filler	27-34	ans-8	Reserved for future use

Table IP0304T1: Transaction Type Identifier and AB Code

Customers use this table to identify all acceptor business codes (MCCs) and Transaction Type ID combinations that Mastercard supports; both current and obsolete.

Table 30: Table IP0304T1: Transaction Type Identifier and AB Code

Table Key: The key for this table is positions 1-29.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated.Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP0304T1
Acceptor Business Code (MCC)	20-24	n-5	Valid values are listed in the Mastercard Quick Reference Booklet.
Transaction Type Identifier	25-27	an-3	The three-digit MoneySend Transaction Type ID
Processing Code	28-29	n-2	The cardholder transaction type

Field Name	Positions	Attribute	Comments and Values
Include/Exclude	30	an-1	Include/Exclude indicator for the Acceptor Business Codes that are valid for payment or funding MoneySend Transaction Type ID Valid values: I = Include - Acceptor Business Code (MCC) is valid for MoneySend Transaction Type ID and Processing Code. E = Exclude - Acceptor Business Code (MCC) is not valid for MoneySend Transaction Type ID and Processing Code. All other Acceptor Business Codes (MCC) not listed are considered valid.

Tables IP1100T1: Mandatory and Not Allowed Field Edits

This table contains the mandatory field edits (both data element and private data subelement) by MTI and Function Code (DE 24) combination, for the originator of the message.

Table Key: The key for this table is positions 1-45.

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP1100T1
Message Type Identifier (MTI)	20-23	an-4	The four-digit descriptor of each IPM message class and function.
Function Code (DE 24)	24-26	an-3	The three digit Function Code that indicates the message's specific purpose.

Field Name	Positions	Attribute	Comments and Values
Card Program Identifier	27-29	an-3	The card program identifier applicable to data element or private data subelement.
Business Service Arrangement Type and ID Code			The business service arrangement type and ID code.
Business Service Arrangement Type	30	an-1	The business service arrangement type.
Business Service ID Code	31-36	an-6	The business service arrangement ID code.
Field Type	37	n-1	Valid values: 2 = Data Element 3 = Private Data Subelement (PDS)
Field Number	38-41	n-4	The field number (data element or PDS) of the applicable field.
Subfield Number	42-45	n-4	If applicable, the subfield number for the corresponding field number.
Mandatory/Not Allowed Indicator	46	an-1	Valid values: M = Mandatory N = Not allowed

Table IP1102T1: Mandatory Field Edits for Elements Used in the Selection Process

This table contains the mandatory field edits for elements used in the selection process.

Table Key: The key for this table is positions 1-35.

Field Name	Positions	Attributes	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH

Field Name	Positions	Attributes	Comments and Values
Active-Inactive Code	11	an-1	Code that controls the updating of the member's Parameter Master File. Valid values are: A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP1102T1
Message Type Identifier (MTI)	20-23	an-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	24-26	an-3	The three-digit function code that indicates the message's specific purpose.
Field Type	27	n-1	Valid values: 2 = Data Element 3 = Private Data Subelement (PDS)
Field Number	28-31	n-4	The field number (data element or PDS) of the applicable field.
Subfield Number	32-35	n-4	If applicable, the subfield number for the corresponding field number.
Mandatory/Optional Indicator	36	an-1	Valid value: M = Mandatory

Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

This table contains value lists. Each table within this range contains a list of valid values that any number of data elements and private data subelements (PDSs) may use given a particular card program identifier. GCMS and the Clearing Optimizer and Utilities software use these lists when checking the validity of the values contained in the data elements and PDSs.

Table 31: Tables IP2nnnT1 and IP3nnnT1 Keys

Table Key: The key for this table is positions 1-54.

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Field Name	Positions	Attribute	Comments and Values
Effective Timestamp	1-10	n-10	Date and time that the information in this record becomes effective or was last updated. Format: YYYYMMDDHH
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File. A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table. Valid value: IP2nnnT1 or IP3nnnT1
Card Program Identifier	20-22	an-3	The card program identifier applicable to the values listed in the table data element or private data subelement. When the valid values are not influenced by card program identifier and business service arrangement, this field is filled with spaces.
Business Service Arrangement Type and Business Service ID Code	23-29	an-7	The business service arrangement type and ID code applicable to the values listed. When the valid values are not influenced by card program identifier and business service arrangement, this field is zero filled.
Item Length	30-33	n-4	Provides the length of data defined in the item text field.
Item Text	34-54	an-21	Provides one of the valid values; for example 01 is one of the valid values for table IP2048T1.
Item Type	55	an-1	Indicates if valid value type is list or range. L = List R = Range

The following are valid value tables.

Table 32: Tables IP2nnnT1 and IP3nnnT1: Valid Values

Table ID	Value Description
IP2001T1	PDS 0146 Transaction Fee Amounts, subfield 3 Fee Settlement Indicator
IP2002T1	Time Parameter Table
IP2003T1	DE 22 Point of Service Data Code, subfield 11 Terminal Data Output Capability
IP2004T1	DE 22 Point of Service Data Code, subfield 4 Terminal Operating Environment
IP2005T1	DE 22 Point of Service Data Code, subfield 7 Card Data Input Mode
IP2006T1	DE 22 Point of Service Data Code, subfield 1 Terminal Data-Card Data Input Capability
IP2007T1	DE 22 Point of Service Data Code, subfield 10 Card Data Output Capability
IP2008T1	DE 22 Point of Service Data Code, subfield 12 PIN Capture Capability
IP2009T1	DE 22 Point of Service Data Code, subfield 9 Cardholder Authentication Entity
IP2010T1	DE 22 Point of Service Data Code, subfield 5 Cardholder Present Data
IP2011T1	DE 22 Point of Service Data Code, subfield 2 Terminal Data-Cardholder Authentication Capability
IP2012T1	DE 22 Point of Service Data Code, subfield 6 Card Present Data
IP2013T1	DE 22 Point of Service Data Code, subfield 8 Cardholder Authentication Method
IP2014T1	DE 22 Point of Service Data Code, subfield 3 Terminal Data-Card Capture Capability
IP2015T1	PDS 0682 Tax Amount 1, subfield 6 Tax Type Identifier 1 PDS 0683 Tax Amount 2, subfield 6 Tax Type Identifier 2 PDS 0684 Tax Amount 3, subfield 6 Tax Type Identifier 3 PDS 0751 Tax Amount 4, subfield 6 Tax Type Identifier 4 PDS 0752 Tax Amount 5, subfield 6 Tax Type Identifier 5 PDS 0753 Tax Amount 6, subfield 6 Tax Type Identifier 6
IP2016T1	PDS 0230 Fulfillment Document Code
IP2017T1	PDS 0262 Documentation Indicator
IP2018T1	PDS 0558 Miles/Kilometers Indicator

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2020T1	PDS 0654 Debit or Credit Indicator
IP2021T1	PDS 0598 Tax Collected Indicator
IP2022T1	PDS 0158, subfield 1 Card Program Identifier ID Code
IP2023T1	PDS 0622 Motor Fuel Service Type
IP2024T1	PDS 0553 Rental Rate, subfield 1 Rental Rate Indicator
IP2025T1	PDS 0747 Shipping Party Descriptor, subfield 1 Shipping Party Descriptor
IP2026T1	DE 4 Transaction Amounts for U.S. Region Large Ticket Interchange
IP2027T1	PDS 0559 Vehicle Insurance, subfield 1 Vehicle Insurance Indicator
IP2028T1	PDS 0561 Adjusted Amount, subfield 1 Adjusted Amount Indicator
IP2029T1	PDS 0578 Billing Adjustment, subfield 1 Billing Adjustment Indicator
IP2030T1	PDS 0648 Item Discount, subfield 1 Item Discount Indicator
IP2031T1	PDS 0165 Settlement Method Indicator, subfield 1 Settlement Indicator
IP2032T1	PDS 0754 Delivery Party Contact, subfield 1 Delivery Party Descriptor
IP2033T1	PDS 0682 Detail Tax Amount 1, subfield 1 Detail Tax Amount Indicator 1 PDS 0683 Detail Tax Amount 2, subfield 1 Detail Tax Amount Indicator 2 PDS 0684 Detail Tax Amount 3, subfield 1 Detail Tax Amount Indicator 3 PDS 0751 Detail Tax Amount 4, subfield 1 Detail Tax Amount Indicator 4 PDS 0752 Detail Tax Amount 5, subfield 1 Detail Tax Amount Indicator 5 PDS 0753 Detail Tax Amount 6, subfield 1 Detail Tax Amount Indicator 6
IP2034T1	PDS 0641 Product Code
IP2035T1	PDS 0617 Medical Services Price Adjustment
IP2036T1	PDS 0618 Medical Service Product Number Qualifier
IP2037T1	PDS 0023 Terminal Type
IP2038T1	PDS 0590 Party Identification
IP2039T1	PDS 0594 Party Contact, subfield 1 Party Contact Descriptor
IP2040T1	PDS 0601 Party Nature of Filing
IP2041T1	PDS 0686 Tax Exempt Indicator
IP2042T1	PDS 0690 No Show Indicator
IP2043T1	PDS 0713 Restricted Ticket Indicator
IP2044T1	PDS 0711 Fire Safety Act Indicator
IP2045T1	PDS 0685 Type of Supply

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2046T1	PDS 0105 File ID, subfield 1 File Type
IP2047T1	PDS 0110 Transmission ID, subfield 1 Transmission Type
IP2048T1	DE 3 Processing Code, subfield 1 Cardholder Transaction Type
IP2049T1	PDS 0026 File Reversal Indicator, subfield 1 File Reversal Indicator
IP2050T1	PDS 0191 Originating Message Format
IP2052T1	PDS 0501 Transaction Description, subfield 1 Usage Code
IP2053T1	PDS 0146 Transaction Fee Amounts, subfield 2 Fee Processing Code
IP2054T1	DE 3 Processing Code, subfield 2 Cardholder From Account Type Code and Masked Value
IP2055T1	DE 3 Processing Code, subfield 3 Cardholder To Account Type Code
IP2056T1	PDS 0732, subfield 3 Debit/Credit Sign, Value of D or C
IP2057T1	PDS 0519 Additional Fuel Location Information, subfields 1-14, Y, N Indicator
IP2058T1	DE 63 Transaction Life Cycle ID, subfield 1 Life Cycle Support Indicator
IP2059T1	PDS 0025 Message Reversal Indicator, subfield 1 Message Reversal Indicator
IP2060T1	PDS 0171 Alternate Merchant Description, subfield 1 Character Set Indicator
IP2061T1	PDS 0189 Point of Interaction Phone Data, subfield 1 Format Indicator
IP2062T1	PDS 0228 Retrieval Document Code
IP2063T1	PDS 0264 Original Reason for Retrieval Request
IP2064T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability (for specific interchange programs)
IP2065T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability (for specific interchange programs)
IP2068T1	DE 40 Extended Service Code
IP2069T1	DE 40 Extended Service Code
IP2070T1	PDS 0638 Call To Information, subfield 5 Call To Type
IP2071T1	PDS 0640 Call Time Period
IP2072T1	PDS 0597, subfield 2 Exponent, Value of 0-5
IP2073T1	DE 22 Point of Service Data Code, subfield 4 Terminal Operating Environment (for specific interchange programs)
IP2074T1	DE 22 Point of Service Data Code, subfield 7 Card Data Input Mode (for specific interchange programs)

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2075T1	DE 22 Point of Service Data Code, subfield 5 Cardholder Present Data (for specific interchange programs)
IP2076T1	DE 22 Point of Service Data Code, subfield 6 Card Present Data (for specific interchange programs)
IP2077T1	PDS 0632 Product Type Code
IP2079T1	PDS 0595 Acceptor Type, subfield 5 Business Type Provided Code
IP2079T1	PDS 0595 Acceptor Type, subfield 6 Business Owner Type Provided Code
IP2079T1	PDS 0595 Acceptor Type, subfield 7 Business Certification Type Provided Code
IP2079T1	PDS 0595 Acceptor Type, subfield 8 Business Racial/Ethnic Type Provided Code
IP2079T1	PDS 0596 Acceptor Tax ID, subfield 2 Acceptor Tax ID Provided Code
IP2080T1	PDS 0623 Motor Fuel Information, subfield 3 Motor Fuel Unit of Measure
IP2081T1	PDS 0623 Motor Fuel Information, subfield 1 Motor Fuel Product Code
IP2082T1	PDS 0146 Transaction Fee Amounts, subfield 1 Fee Type Code
IP2084T1	PDS 0623 Motor Fuel Information, subfield 5 Motor Fuel Quantity Exponent
IP2085T1	PDS 0648 Item Discount, subfield 4 Item Discount Rate Exponent
IP2086T1	PDS 0596 Acceptor Tax ID, subfield 1 Acceptor Tax ID
IP2087T1	PDS 0260 Edit Exclusion Indicator, subfield 1 Exclusion Request Code

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2088T1	PDS 0643 Item Quantity, subfield 2 Item Quantity Exponent PDS 0646 Unit Price, subfield 2 Unit Price Exponent PDS 0751 Detail Tax Amount 4, subfield 4 Detail Tax Rate Exponent 4 PDS 0752 Detail Tax Amount 5, subfield 4 Detail Tax Amount Exponent 5 PDS 0753 Detail Tax Amount 6, subfield 4 Detail Tax Amount Exponent 6 PDS 0723 Regular Hours Worked, subfield 2 Regular Hours Worked Exponent PDS 0724 Regular Hours Rate, subfield 2 Regular Hours Rate Exponent PDS 0725 Overtime Hours Worked, subfield 2 Overtime Hours Worked Exponent PDS 0726 Overtime Hours Rate, subfield 2 Overtime Hours Rate Exponent PDS 0505 Travel Agency Fee, subfield 2 Travel Agency Fee Amount Exponent PDS 0653 Service Amount, subfield 2 Service Amount Exponent PDS 0656 Full VAT Amounts, subfield 2 Full VAT Gross Amount Exponent PDS 0656 Full VAT Amounts, subfield 5 Full VAT Tax Amount Exponent PDS 0657 Half VAT Amounts, subfield 2 Half VAT Gross Amount Exponent PDS 0657 Half VAT Amounts, subfield 5 Half VAT Tax Amount Exponent PDS 0682 Detail Tax Amount 1, subfield 4 Detail Tax Rate Exponent 1 PDS 0683 Detail Tax Amount 2, subfield 4 Detail Tax Rate Exponent 2 PDS 0684 Detail Tax Amount 3, subfield 4 Detail Tax Rate Exponent 3 PDS 0712 Net Fuel Price, subfield 2 Net Fuel Price Exponent
IP2090T1	DE 23 Card Sequence Number
IP2093T1	DE 54 Amounts, Additional, subfield 4 Additional Amount, Amount Sign (for U. K. Domestic Maestro use only)
IP2094T1	PDS 0165 Settlement Indicator, subfield 1 Settlement Indicator (for U. K. Domestic Maestro use only)
IP2099T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF Collection
IP2100T1	DE 43 Acceptor Name/Location, subfield 5 Acceptor State/Province Code
IP2104T1	DE 43 Acceptor Name/Location, subfield 4 Acceptor Postal (Zip) Code
IP2105T1	PDS 0502 Custom Identifier, subfield 1 Custom Identifier Type

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2106T1	PDS 660 Customer Reference, subfield 1 Customer Reference ID
IP2108T1	PDS 0762 Data Source
IP2113T1	PDS 0620 Oil Company Brand Name
IP2115T1	PDS 0057 Transaction Category Indicator
IP2116T1	CEM Response Codes
IP2118T1	DE 22 Point of Service Data Code, subfield 7 Card Data: Input Mode
IP2119T1	PDS 0595 Acceptor Type, subfield 1 Business Type
IP2126T1	Life Cycle Transactions
IP2128T1	PDS 0195 Installment Data, subfield 2 Payment Option Code
IP2129T1	PDS 0195 Installment Data, subfield 3 Installment Number
IP2130T1	PDS 0195 Installment Data, subfield 4 Bonus Code
IP2131T1	PDS 0195 Installment Data, subfield 6 Number Bonus Payments Per Year
IP2133T1	PDS 0179 Long Running Transaction Indicator
IP2134T1	Payment Methods
IP2135T1	Alternate Custom Identifier Types
IP2144T1	PDS 0194 Remote Payments Program Data
IP2146T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF
IP2147T1	PDS 0181 Installment Data, subfield 1 Type of Installment
IP2148T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2149T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2150T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2151T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2152T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2153T1	DE 40 Service Code Valid Ranges
IP2154T1	Acceptor Business Code Exclusions
IP2155T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability for Contactless Enabled
IP2158T1	PDS0042 Merchant Capability Valid Values
IP2167T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF
IP2170T1	Single Message System Endpoints
IP2171T1	Logic Control Using ID and Date

About IPM Mastercard Parameter Extract
Tables IP2nnnT1 and IP3nnnT1: Valid Values Influenced by Card Program Identifier

Table ID	Value Description
IP2172T1	DE022 Point of Service Data Code, Subfield 4 Point of Sale Terminal Operating Environment
IP2190T1	PDS 0052 Electronic Commerce Security Level Indicator
IP2196T1	PDS0715 Ancillary Service Charges, subfield 1 Ancillary Fee Code
IP2201T1	PDS 0021 MCHIP QR
IP2203T1	DE22 Cardless ATM, Subfield 7
IP2211T1	DE 43 Acceptor Name/Location, Subfield 4 Acceptor Postal (ZIP) Code
IP2219T1	PDS 0176 MAID and IRD
IP2222T1	PDS 0052 (Electronic Commerce Security Level Indicator) and PDS 0185 (Accountholder Authentication Value) Combinations
IP2225T1	MDS Processing code and Overlayed IRD
IP2226T1	IntraRegional Participant Regions for MDS IRD Overlay logic
IP2230T1	CIT/MIT Category Indicator
IP2233T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2234T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2235T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2236T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2239T1	PDS0790 Fleet Addendum Prompt Codes PDS0791 Fleet Addendum Prompt Codes PDS0792 Fleet Addendum Prompt Codes PDS0793 Fleet Addendum Prompt Codes PDS0794 Fleet Addendum Prompt Codes
IP2240T1	PDS0782s1 Fleet Fuel Products
IP2241T1	PDS0783 Fleet Addendum Non-Fuel Product Codes
IP2244T1	PDS 0052 (Electronic Commerce Security Level Indicator) and PDS 0185 (Accountholder Authentication Value) Combinations
IP2245T1	Country Specific Micro-Merchant Algorithms, Sequence 01 through 07
IP2246T1	Country Specific Micro-Merchant Algorithms, Sequence 08 through 14
IP2247T1	Country Specific Micro-Merchant Algorithms, Sequence 15 through 21
IP2248T1	Country Specific Micro-Merchant Algorithm, Alpha to Numeric Result
IP3001T1	Payment Transaction Type Codes
IP3002T1	Transaction Type Identifier and Registration type Codes

Table ID	Value Description
IP3004T1	Transaction Type Identifier and MCC Code Combination

Tables IP7XXXT1 through IP9XXXT1: reserved tables

These tables are Mastercard reserved tables. Customers' local applications must disregard these tables. The IP7XXXT1 through IP9XXXT1 table IDs are in positions 12 to 19 (XXX = 000 to 999).

Chapter 2 About optimized current parameter file layouts

This section provides the layout of the parameters used in the IPM Optimized Current Parameters File.

File structure comparison.....	171
Annotation of data element attributes.....	176
IPM optimized current parameters file layouts.....	177
Table IP0000T1: keys.....	177
Table IP0001T1: Run Control Options.....	179
Table IP0002T1: Valid Run Option Overrides.....	181
Table IP0003T1: Run Control Errors.....	182
Table IP0005T1: KSDS Optimized Keys.....	183
Table IP0006T1: Data Element Attributes.....	183
Table IP0006T2: Data Element Attribute Overrides.....	185
Table IP0007T1: Data Element Subfield Attributes.....	187
Table IP0008T1: PDS Attributes.....	189
Table IP0009T1: PDS Subfield Attributes.....	191
Table IP0010T1: RRDS Optimized Keys	192
Table IP0011T1: Expanded MTI/Function/Reason Code.....	193
Table IP0012T1: Life Cycle Time Frame.....	195
Table IP0015T1: IPM Error Messages.....	198
Table IP0016T1: Brand Product.....	199
Table IP0017T1: Currency Codes.....	202
Table IP0018T1: Mastercard Product Graduation Parameters.....	202
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters.....	204
Table IP0020T1: PAN Mapping Product Code Pairs.....	208
Table IP0023T1: MDS Routing Member ID.....	211
Table IP0025T1: Message Reason Codes.....	211
Table IP0026T1: Parameter Print Controls.....	212
Table IP0027T1: Run Control Default Override Values.....	214
Table IP0028T1: Country Codes.....	215
Table IP0029T1: Edit Override Table.....	218
Table IP0030T1: Interchange Amount Restriction	219
Table IP0031T1: Addendum Data.....	220
Table IP0033T1: IPM Module Names and Version Numbers.....	223
Table IP0034T1: Processing Code Group	225

Table IP0035T1: Settlement Service Selection BIN Data.....	225
Table IP0037T1: Selection Criteria Data.....	226
Table IP0039T1: Selection Criteria Account Range	228
Table IP0040T1: Issuer Account Range	229
Table IP0041T1: Acquirer Reference ID.....	242
Table IP0045T1: Cash Disbursement.....	243
Table IP0048T1: Settlement Service	244
Table IP0050T1: Settlement Service Selection Criteria.....	246
Table IP0052T1: Interchange Fee Group	247
Table IP0053T1: Interchange Fee Type.....	250
Table IP0054T1: Retrieval Fee	255
Table IP0056T1: Member Business Service Arrangements	256
Table IP0057T1: Interchange Override Fee Group.....	257
Table IP0058T1: QPS and Contactless Chargeback Protection Amounts.....	259
Table IP0059T1: Timeliness Code	260
Table IP0060T1: Timeliness Holiday	262
Table IP0064T1: Transaction Function Group Codes.....	264
Table IP0069T1: Global Currency.....	265
Table IP0070T1: Common Area.....	266
Table IP0071T1: Chip Liability Shift Country Exclusions.....	267
Table IP0072T1: Expanded Member ID Master.....	268
Table IP0074T1: IFC Gaming	273
Table IP0075T1: Acceptor Business Codes (MCCs).....	274
Table IP0076T1: Mastercard Assigned IDs.....	277
Table IP0087T1: Masked Business Services and Interchange Rate Designators.....	278
Table IP0088T1: Masked Business Services.....	280
Table IP0089T1: Business Service Switches.....	281
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation.....	282
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation.....	284
Table IP0092T1: Transaction Functions Requiring Business Service Processing.....	285
Table IP0093T1: Intracountry Business Service Override.....	286
Table IP0094T1: Geographic Restrictions for Card Program Identifier and Business Service Arrangement/IRD.....	287
Table IP0095T1: Acceptor Business Program Restrictions for Card Program Identifier and Business Service Arrangement, and IRD.....	289
Table IP0096T1: Product Restrictions for Card Program Identifier and Business Service Arrangement, and IRD.....	290

Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement.....	291
Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement.....	293
Table IP0099T1: Transaction Currency Qualification.....	295
Table IP0105T1: New Product Code Mapping.....	296
Table IP0106T1: Issuer Participation Activation/Deactivation.....	297
Table IP0128T1: Tiered Debit U.S. and Territories.....	298
Table IP0132T1: Anonymous Prepaid Countries.....	299
Table IP0137T1: Brazil Flex Mapping.....	300
Table IP0138T1: Authentication Enforcement.....	301
Table IP0142T1: Business Service Selection Enforcement.....	303
Table IP0144T1: Processing Code and Transaction Type Indicator.....	304
Table IP0304T1: Transaction Type Identifier and AB Code.....	305
Table IP0970T1: key for IP0097T1 (Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement).....	306
Tables IP1100T1 and IP1100T2: mandatory field edits.....	307
Table IP2000T1 and IP2000T2: valid values/ranges	309
Table IP4090T1: Account Range ID.....	318
Table IP4191T1: BIN Pointer.....	322
Table IP5200T1: key for IP0052T1 (Interchange Fee Group).....	323
Table IP5300T1: key for IP0053T1 (Interchange Fee Type).....	324
Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements).....	325
Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group).....	326

The IPM Optimized Current Parameters File is generated during the Clearing Optimizer editing process. The Clearing Optimizer software takes the processing date and time entered by the customer in the Run Control File and selects the parameters that are in effect for that date and time. It then restructures the parameters so that they are used more efficiently and ultimately allows for faster processing.

NOTE: This section is intended for Mainframe Clearing Optimizer customers only. The Workstation Plus Optimized Current Parameters File contains embedded code that is proprietary to MicroFocus COBOL and cannot be documented by Mastercard. Workstation Plus members should refer to the CurrentParm.txt file which contains a text version of the Optimized Current Parameters File layout. Mainframe members are also encouraged to use the file created in PRIP0350, STEP040, SYS211, that may be easier to display for information purposes. Refer to Using the CurrentParm.txt File section for additional information regarding the CurrentParm.txt file.

File structure comparison

The Optimized Current Parameters File is included as part of the IPM MPE Update Options.

This process uses three major parameter files:

IPM Member Parameter Extract (IPM MPE): Sent from Mastercard to customers each day, this file contains daily parameter updates, each with an effective date and time. On occasion, based on a customer's request, this file can contain a full replacement file of all parameter values.

IPM Parameter Master File: This file resides at the customer's location, and contains all parameters, whether effective in the past, present, or future. The IPM MPE updates this file each day, and old parameters automatically purge seven days after they are replaced.

Optimized Current Parameter Files: There are actually two Optimized Current Parameter files. These files also reside at the customer's location. These files contain only those parameter values that are effective for the customer-specified processing date and time.

- RRDS file: This file contains IPM parameter tables: IP0000T1, IP0040T1, IP0041T1, IP0052T1, IP0056T1, IP0057T1, IP0090T1, IP0091T1, IP0093T1, IP0097T1 and Dynamically Created Tables: IP0010T1, IP0970T1, IP4090T1, IP4191T1, IP5200T1, IP5300T1, IP5600T1, IP5700T1.
- KSDS file: This file contains all other IPM parameter tables.

These two Optimized Current Parameter files are the source of parameter values for the Clearing Optimizer and each of the Utilities.

NOTE: In the initial release of the Clearing Optimizer software, the Optimized Current Parameters File consisted of a single file structured as a sequential file. With the second release of the Clearing Optimizer software, there are two Optimized Current Parameter files structured as VSAM files. While the Mastercard Clearing Optimizer software accommodates these changes, members must modify any proprietary applications that they developed that access the Optimized Current Parameter Files to accommodate these changes.

The output from the optimize process creates the Parameter Master File with the entries of a single table in a format that is easily accessed by the Clearing Optimizer software. Since each table has different characteristics, the optimization of the table can occur in one of five ways. This section outlines the differences in the way each table is optimized, and which tables fall into each category.

Unless otherwise noted, the tables in the optimized file begin with a 22-position table identifier. This identifier consists of the Table ID, Effective Date and Time, and Sequence Number. The data that follows the table identifier is multiple occurrences of the data for that table.

The record layout is different between the IPM MPE, Parameter Master File, and the Optimized Current Parameter File. The following table provides the layout of one record for each of these files.

IPM MPE Record	IPM Parameter Master Record	Optimized Current Parameters Record
Effective date and time	Effective date and time	Table ID
Active-inactive code	Record Status Code	Effective date and time
Table ID	Table ID	Sequence number
Contents of one table entry	Contents of one table entry	Concatenated contents of all entries in a table, to a maximum record length of 32k bytes.

If the concatenated individual entries for a table exceed 32k bytes, a second Optimized Current Parameter record is created with the same Table ID, Effective Date, and Time, an incremented Sequence Number, and contains additional concatenated individual entries for that table, up to 32k bytes. This is repeated as often as needed to present all of the concatenated individual entries for a table.

The contents of the each table are concatenated based on one of five types of concatenation. The tables can be built in one of the following ways.

Generic: All entries for the table that follows the key are combined one after the other. The Parameter Master File table contents has the same positioning as the Optimized Current Parameters File. The maximum allowable entries for each row are concatenated.

Field Reformatting: All entries for the table that follows the key are combined and may be compressed, based on the copybook layouts. The Parameter Master records that are presented as numeric data in the Parameter Master File are converted to either packed or binary data in the Optimized Current Parameter Files.

Table Reformatting: In addition to having fields that may be compressed, these entries could also have fields added to aid addressability. For example, in Table IP0008T1, PDS Attributes the PDS number is eliminated, and the positional reference is used to identify the PDS. Therefore, position 25 would be PDS0025.

Table Re-structuring: The entry detail table is grouped in a parent child relationship by reducing the number of key entries, and by grouping similar entries with multiple occurrences of detail. For example, in Table IP0012T1, Life Cycle Time Frame and the combination of Card Program Identifier -MTI-DE 24-DE 25 has one occurrence with up to 15 time frame occurrence entries.

Dynamically Created Tables: These tables are built as part of the optimized process for internal use by the Clearing Optimizer software. The tables built for internal use are IP0005T1 and IP0010T1.

Following is an example that illustrates the difference between the IPM MPE, Parameter Master, and the Optimized Current Parameters records.

Assume that Mastercard has defined table IP1234T1, which provides the months of the year and the number of days in each month. At the beginning of a leap year, Mastercard must update the entry for February to indicate 29 days instead of 28. The following describes the representation of this information in each of the three parameter files:

IPM MPE: Mastercard would send one update record structured as follows:

Field Name	Position	Attribute	Value
Effective Date and Time	1-10	n-10 (format YYYYMMDDHH)	2000010100 (indicates that this table change is effective 1 January, 2000, at midnight)
Active/Inactive Code	11	an-1	A (add this to Parameter Master)
Table-ID	12-19	an-8	IP1234T1
Month number	20-21	n-2	02 (February)
Number of days	22-23	n-2	29

The data for the above IPM MPE record would look like the following:

2000010100AIP1234T10229

IPM Parameter Master: After the IPM MPE Update process applies the above IPM MPE update record, for table IP1234T1 the Parameter Master file would have thirteen records (one for each of the twelve months, plus the new record for February). Each record would be structured as follows:

Field Name	Position	Attribute	Value
Effective Date and Time	1-10	n-10 (format YYYYMMDDHH)	For the original 12 entries, this value would be 1999010100. For the new entry for February, this value is 2000010100 as indicated in the IPM MPE update record.
Record Status	11	an-1	For last year's February entry, the value would be I (inactive). For all other months, plus the new February entry, the value is A (active).
Table-ID	12-19	an-8	IP1234T1
Month number	20-21	n-2	01, 02, through 12
Number of days	22-23	n-2	As appropriate

The data for the 13 Parameter Master records described above would look like the following:

1999010100AIP1234T10131
1999010100AIP1234T10228
2000010100AIP1234T10229
1999010100AIP1234T10331
1999010100AIP1234T10430
1999010100AIP1234T10531
1999010100AIP1234T10630
1999010100AIP1234T10731
1999010100AIP1234T10831
1999010100AIP1234T10930
1999010100AIP1234T11031
1999010100AIP1234T11130
1999010100AIP1234T11231

Optimized Current Parameter record: After running the Clearing Optimizer software with an effective date of 2 January, 2000 and an effective time of midnight, the Optimized Current Parameter file would contain one record for table IP1234T1, structured as follows:

Field Name	Position	Attribute	Comments and Values
Table ID	1-8	an-8	IP1234T1
Effective Date and Time	9-18	n-10	2000010100
Sequence Number	19-22	b-4	Binary value of 1
Month number 1	23-24	n-2	01
Number of days 1	25-26	n-2	31
Month number 2	27-28	n-2	02
Number of days 2	29-30	n-2	29

Up to:

Month number 12	67-68	n-2	12
Number of days 12	69-70	n-2	31

The data for the single Optimized Current Parameter record described above would appear as follows:

IP1234T12000010100 013102290331043005310630073108310930 103111301231
--

Chapter 1 of this publication describes the detailed record layouts of the IPM MPE file. The record layouts of the corresponding tables in the IPM Parameter Master File are identical to those in the IPM MPE layouts with the exception that the IPM Parameter Master File has a Record Status in position 11 of each record instead of an Active/Inactive Code.

The remainder of this chapter describes the detailed record layouts of the Optimized Current Parameters file.

Annotation of data element attributes

The following notation conventions describe the attributes of data elements:

Table 33: Data representation attributes

Notation	Description
a	alphabetic characters A-Z and a-z
b	binary
n	numeric digits 0-9
an	alphabetic and numeric characters
as	alphabetic characters A-Z and a-z, and space character
ns	numeric digits 0-9 and special characters (including space)
ans	alphabetic, numeric, and special characters (including space)
p	packed
ps	packed-signed

The following notations describe date and time data element subfields:

Table 34: Date and time attributes

Notation	Description
MM	month (two digits; 01-12)
DD	day (two digits; 01-31)
YY	year (last two digits of calendar year; 00-99)
YYYY	year (four digits of calendar year: 1900-1999; 2000-2099)
hh	hour (two digits; 00-23)
mm	minute (two digits; 00-59)
ss	second (two digits; 00-59))

The following notations describe the data length attributes:

Table 35: Data length attributes

Notation	Description
-digit(s)	Fixed length in number of positions. Example: "n-3" indicates a three-position numeric data element. Example: "an-10" indicates a 10-position alphanumeric data element.
...digit(s)	Variable length, with maximum number of positions specified. Example: "n...11" indicates a variable-length numeric data element of 1-11 digits. Example: "an...25" indicates a variable-length alphanumeric data element of 1-25 positions.

NOTE: The following optimized table layouts are a proprietary subset of the Parameter Master File produced from Micro Focus COBOL routines used by Mastercard.

IPM optimized current parameters file layouts

The following provides the optimized table layouts in the IPM file.

Table IP0000T1: keys

This table provides an index to all of the other MPE tables, including the version number, the starting position, and length of the key of each table.

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

NOTE:

In the two Optimized Current Parameter files:

KSDS: Includes all Table 0 entries for all tables on the IPM MPE.

RRDS: Has only one Table 0 entry (for Table IP0000T1), and is used to validate the version number of the IPM Optimized Current Parameters (RRDS) file. Customers who use the IPM Optimized Current Parameters (RRDS) File within their own system processing should ignore this Table IP0000T1 record.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	VSAM Key
Effective Date and Time	9-18	n-10	VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Subject Table ID	23-30	an-8	Identifies the table that is the subject of this Keys Table record. Must be a valid IPM Table ID.
Filler (reserved for internal use)	31	an-1	Space filled.
Subject Table Name	32-58	an-27	Identifies by name the table that is the subject of this Keys Table record.
Subject Table Key Length	59-63	n-5	Length of the key that uniquely identifies each record in the table that is the subject of this Keys Table record.
Subject Table Key Start	64-67	n-4	Starting position of the key that uniquely identifies each record in the table that is the subject of this Keys Table record.
Subject Table Record Length: Minimum	68-72	n-5	Indicates the minimum length of each record in the table that is the subject of this Keys Table record.
Subject Table Record Length: Maximum	73-77	n-5	Indicates the maximum length of each record in the table that is the subject of this Keys Table record.

Field Name	Positions	Attribute	Comments and Values
Version Number	78-85	n-8	The version of the table, generated by Mastercard. - This field on the first row of table IP0000T1 has the file version number and increases by one for each daily update file. - All other tables have an incremented Version Number only when updates have been applied to the table. Format: NNNNNNNN
Central Update	86-97	n-12	The last date and time that Mastercard updated this table at Central Site in St. Louis, Missouri, USA. Format: YYYYMMDDHHMM
Member Update	98-109	n-12	The last date and time that the member system updated this table at the member site. Format: YYYYMMDDHHMM
Table Row Count	110-117	n-8	Filler (Central Site use only)
Filler	118-227	an-110	Filler (Central Site use only)
Full Table Build Indicator	228	ans-1	Code indicates the type of data contained in a particular table. R = Full table replace. Indicates that a particular table data is being replaced in full. U or D = Regular updates.
Filler	229-246	ans-18	Filler (Central Site use only)
Table Sub Indicator	247-249	ans-3	Table ID converted three-position sub ID.
Filler	250-262	an-13	Filler (Central Site use only)

Table IP0001T1: Run Control Options

This table provides the parameters that are established as the defaults for running the Clearing Optimizer software and for updating the customer's Parameter Master File with a particular IPM MPE table.

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Run Option Group ID	23	an-1	Valid values: 0 = Run Option 1 = Report Option 2 = Threshold Option
Run Option ID	24-27	an-4	The sequence number within a Run Option Group.
Run Option Description	28-62	an-35	The name of the option described in this record.
Run Option value for three-position Run Options	63-65	an-3	The default value if this Run Option is a three-position value. (All Group 2 options and the "Maximum Number of Cycles" Group 0 option contain three-position values.)
Run Option value for one-position Run Options			
Run Option	63	an-1	The default value if this Run Option is a one-position value. (All Group 1 options and most Group 0 options contain one-position values.)
Filler (reserved for internal use)	64-65	an-2	Space filled.
Run Option Error Number 1	66-70	n-5	Applicable error number when validating run options.

Field Name	Positions	Attribute	Comments and Values
Run Option Error Number 2	71-75	n-5	Applicable error number when validating run options.

Table IP0002T1: Valid Run Option Overrides

This table provides the parameters that are established as the valid values for the member to use when overriding the default values established for the run control process (the values in table IP0001T1).

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Run Option Group ID	23	an-1	Valid values: 0 = Run Option 1 = Report Option 2 = Threshold Option
Run Option ID	24-27	an-4	The sequence number within a Run Option Group.
Run Option Default	28	an-1	Valid values for this particular option

Field Name	Positions	Attribute	Comments and Values
Run Option Description	29-81	an-53	The name of the option described in this record.

Table IP0003T1: Run Control Errors

This table shows the error number and error message that applies to the Run Control error.

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Run Control Error Number	23-26	an-4	The four-digit IPM error message number.
Run Control Error Line	27	an-1	Identifies when additional records are required to contain the error message text.
Run Control Abend Code	28-31	an-4	The abend code displayed when the program terminates.
Run Control Error Message	32-95	an-64	The actual error message text associated with the error number.

Table IP0005T1: KSDS Optimized Keys

This table contains all the KSDS optimized table keys for unique Table ID - Effective Date and Time combinations.

This table is used to position the read to the first record of a Table ID for applicable Effective Date and Time.

Optimized Structure: Dynamically Created Tables: These tables are built as part of the optimized process for internal use by the Clearing Optimizer software. The tables built for internal use are IP0005T1 and IP0010T1.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Key Table ID	23-30	an-8	The table ID of key table.
Key Sequence Number	31-34	b-4	Sequence number of first record of key table
Reload date and time	35-44	n-10	Effective Date and Time of key table

Table IP0006T1: Data Element Attributes

This table contains the number, name, format requirements, length requirements, and number of subfields within each data element.

Optimized Structure: Field reformatting-The entries in this table are compressed from the layout in the Parameter Master File.

Table 36: Table IP0006T1: Data Element Attributes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Override Index	23-26	b-4	The table IP0006T1 index that points to the Table IP0006T2 record that contains the overrides for the data element attributes.
Card Program Identifier	27-29	n-3	Mastercard or other proprietary service mark.
Data Element Number	30-32	n-3	Data element number defined in this record. Valid values: A valid data element as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Name	33-89	an-57	Name of the data element defined in this record. Valid values: The data element name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
Data Element Format	90-92	an-3	a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
Data Element Minimum Length	93-94	b-2	The minimum length of the data element.
Data Element Mastercard Maximum Length	95-96	b-2	Maximum length of this data element, as defined by Mastercard.
Data Element ISO Maximum Length	97-98	b-2	Maximum length of this data element, as defined by the International Organization for Standardization (ISO).
DE-LLL-Size	99-100	b-2	Value that describes the data element length field size. Valid values: 0, 2, 3
Data Element: Subfields	101-102	b-2	Total count of subfields within the data element or PDS.
Data Element: Subfields: Index	103-106	b-4	

Table IP0006T2: Data Element Attribute Overrides

This table contains the number, name, format requirements, length requirements, and number of subfields within each data element for non-default Card Program Identifiers.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 37: Table IP0006T2: Data Element Attribute Overrides

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	n-3	Mastercard or other proprietary service mark.
Data Element Number	26-28	n-3	Data element number defined in this record. Valid values: A valid data element as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i>.
Data Element Name	29-85	an-57	Name of the data element defined in this record. Valid values: The data element name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i>.

Field Name	Positions	Attribute	Comments and Values
Data Element Format	86-88	an-3	a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
Data Element Minimum Length	89-90	b-2	The minimum length of the data element.
Data Element Mastercard Maximum Length	91-92	b-2	Maximum length of this data element, as defined by Mastercard.
Data Element ISO Maximum Length	93-94	b-2	Maximum length of this data element, as defined by the International Organization for Standardization (ISO).
DE-LLL-Size	95-96	b-2	Value that describes the data element length field size. Valid values: 0, 2, 3
Data Element—Subfields	97-98	b-2	Total count of subfields within the data element or PDS.
Data Element—Subfields—Index	99-102	b-4	

Table IP0007T1: Data Element Subfield Attributes

This table contains the number, name, format requirements, and length requirements for each data element subfield.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 38: Table IP0007T1: Data Element Subfield Attributes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Data Element Number	23-24	b-2	Data element number related to the subfield in this record. Valid values: A valid data element as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Subfield Number	25-26	b-2	Number of the subfield defined in this record. Valid values: A valid subfield associated with the data element, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Data Element Subfield Name	27-83	an-57	Name of the subfield defined in this record. Valid values: The subfield name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
Data Element Subfield Format	84-86	an-3	Attribute convention describing the format of the subfield defined in this record. Valid values: a = alphabetic characters A-Z and a-z n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
Data Element Subfield Start	87-88	b-2	Starting position of the first occurrence of this subfield within the data element. A value of "000" indicates that a preceding subfield within DE 48 is variable; thus, the starting position of the subfield is unknown.
Data Element Subfield Minimum Length	89-90	b-2	Minimum length of the subfield.
Data Element Subfield Maximum Length	91-92	b-2	Maximum length of the subfield.

Table IP0008T1: PDS Attributes

This table contains the number, name, format requirements for the overall PDS, length requirements, and number of subfields within each PDS.

Optimized Structure: Table reformatting: In addition to field compression, the PDS number field is removed from this table layout. The PDS number is determined by the number of subsequent occurrences within the table. The first occurrence would be PDS0001, the second PDS0002, and continuing until there are no more occurrences.

Table 39: Table IP0008T1: PDS Attributes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
PDS Name	23-79	an-57	Name of the PDS defined in this record. Valid values: The PDS name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i>.
PDS Format	80-82	an-3	Attribute convention describing the format of the PDS defined in this record. Valid values: a = alphabetic characters A-Z and a-z n = numeric digits 0-9 as = alphabetic characters A-Z and a-z, and special characters (including space) an = alphabetic and numeric characters ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
PDS Minimum Length	83-84	b-2	Minimum length of the PDS.
PDS Maximum Length	85-86	b-2	Maximum length of the PDS.
PDS Number of Subfields	87-88	b-2	The number of subfields contained within this PDS, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
PDS First Subfield	89-92	n-4	Index pointing to the first subfield of the element.

Table IP0009T1: PDS Subfield Attributes

This table contains the number, name, format requirements, and length requirements for each PDS subfield. Entries in this table will only exist for PDSs that have subfields.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 40: Table IP0009T1: PDS Subfield Attributes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
PDS Number	23-24	b-2	PDS number related to the subfield in this record.Valid values: A valid PDS as documented in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Subfield Number	25-26	b-2	Number of the subfield defined in this record.Valid values: A valid subfield associated with the PDS, as defined in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .

Field Name	Positions	Attribute	Comments and Values
PDS Subfield Name	27-83	an-57	Name of the subfield defined in this record. Valid values: The subfield name shown in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
PDS Subfield Format	84-86	an-3	Attribute convention describing the format of the PDS defined in this record. Valid values: a = alphabetic characters A-Z and a-z b = binary n = numeric digits 0-9 an = alphabetic and numeric characters as = alphabetic characters A-Z and a-z, and special characters (including space) ns = numeric digits 0-9 and special characters (including space) ans = alphabetic, numeric, and special characters (including space)
PDS Subfield Start	87-88	b-2	Starting position of this subfield within the PDS
PDS Subfield Minimum Length	89-90	b-2	Minimum length of the subfield.
PDS Subfield Maximum Length	91-92	b-2	Maximum length of the subfield.

Table IP0010T1: RRDS Optimized Keys

This table contains all the RRDS optimized table keys for unique Table ID - Effective Date and Time combinations.

This table is used to position the read to the first record of a Table ID for applicable Effective Date and Time.

Optimized Structure: Dynamically Created Tables: These tables are built as part of the optimized process for internal use by the Clearing Optimizer software. The tables built for internal use are IP0005T1 and IP0010T1.

Table 41: Table IP0010T1: RRDS Optimized Keys

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Key Table ID	23-30	an-8	The table ID of key table.
Effective Date and Time	31-40	n-10	Effective Date and Time of key table
Relative record number	41-48	n-8	Relative record number of first record of key table.
Record count	49-56	n-8	Number of Relative records for this Key table.

Table IP0011T1: Expanded MTI/Function/Reason Code

This table provides switches indicating whether there is impact to settlement and fee processing.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key

About optimized current parameter file layouts
Table IP0011T1: Expanded MTI/Function/Reason Code

Field Name	Positions	Attribute	Comments and Values
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Message Type Identifier (MTI)	26-29	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	30-32	n-3	The three-digit Function Code that indicates the message's specific purpose.
Message Reason Code (DE 25)	33-36	n-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.
Mnemonic	37-39	n-3	This identifies whether the Fee Collection 1740 message is a Retrieval Fee Billing message or a non-Retrieval Fee Billing message. Valid values: 018 = Fee Collection Retrieval Fee Billing 020 = Fee Collection Other (When the Function Code is equal to 700, 780, 781, 782, or 783) 790 = Funds Transfer Fee Collection (When the Function Code is equal to 700, 780, 781, 782, or 783) 791 = Funds Transfer Fee Collection Backout (When the Function Code is equal to 791)
			For all other message types, the mnemonic will be the same value as the Function Code.
Settlement Impact Switch	40	an-1	Valid values: Y = Settlement impact N = No settlement impact

Field Name	Positions	Attribute	Comments and Values
Retrieval Fee Switch	41	an-1	Valid values: Y = Retrieval fee is applicable N = Retrieval fee is not applicable
Filler (reserved for internal use)	42	an-1	Space filled.
Filler (reserved for internal use)	43-44	n-2	Zero filled.
Filler (reserved for internal use)	45	an-1	Space filled.
Message Originator	46	an-1	Valid values: A = Acquirer I = Issuer
Fee Collection Indicator	47	an-1	This applies to Fee Collection/1740 messages. Valid values: Y = The Message Type Identifier (MTI) is fee collection N = The Message Type Identifier (MTI) is not fee collection

Table IP0012T1: Life Cycle Time Frame

This table contains the minimum and maximum timeframes for which the clearing system will edit based on member specification and the presence of a particular card program identifier, transaction function, or Message Reason Code (DE 25). (A transaction function is the combination of MTI and Function Code [DE 24].)

The minimum and maximum timeframes are associated with various combinations of the dates in the transaction life cycle. For example, there could be a minimum timeframe associated with the transaction between first chargeback and second presentment.

Optimized Structure: Table restructuring: For each occurrence of Card Program Identifier, MTI, Function Code, and Reason Code, up to 15 timeframe entries can occur. For example, MCC-1442-450-4801 will have two occurrences of the timeliness data.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the key to the time frame entries and will occur once for each unique combination of these fields.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
MTI	26-29	n-4	The four-digit descriptor of each IPM message class and function.
Function Code (DE 24)	30-32	n-3	The three-digit Function Code that indicates the message's specific purpose.
Message Reason Code (DE 25)	33-36	n-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.
Number of Test	37-40	n-4	Number of Card Program identifier /MTI/ Function Code/Message Code segments in sequence.

The following segment of table data represents the first 15 occurrences of this data.

Field Name	Positions	Attribute	Comments and Values
Begin Date Code	41-42	n-2	The first of the combination of dates with which this minimum or maximum amount is associated. Based on the stage in the life cycle, the Begin Date can represent the date of the: 01 = First presentment 02 = Retrieval request 03 = Retrieval fulfillment 04 = First chargeback 05 = Second presentment 06 = Arbitration chargeback
Ending Date Code	43-44	n-2	The second of the combination of dates with which this minimum or maximum amount is associated. Based on the stage in the life cycle, the Begin Date can represent the date of the: 01 = First presentment 02 = Retrieval request 03 = Retrieval fulfillment 04 = First chargeback 05 = Second presentment 06 = Arbitration chargeback
Minimum Time Frame	45-47	an-3	The minimum time frame allowed for members to submit transactions for clearing for the particular combination of card program identifier, transaction function, and reason code.
Maximum Time Frame	48-50	an-3	The maximum time frame allowed for members to submit transactions for clearing for the particular combination of card program identifier, transaction function, and reason code.
Minimum Error Code	51-54	an-4	The four-digit error code associated with the minimum time frame requirement.
Minimum Error Message	55-58	an-4	The error message associated with the minimum error code.

Field Name	Positions	Attribute	Comments and Values
Maximum Error Code	59-62	an-4	The four-digit error code associated with the maximum time frame requirement.
Maximum Error Message	63-66	an-4	The error message associated with the maximum error code.

Table IP0015T1: IPM Error Messages

This table contains the internal IPM error codes and the corresponding message texts for each IPM error code.

Optimized Structure: This table is reformatted by adding a text string to the front of the record to easily access the error code. The table begins with a key for the first number of error codes in the row up to 300 error codes. Each key is 13 positions, and consists of the error message key, message start, message length, and number of error message variable fields. After the key entries is the actual error text followed by the starting position and length of the error message variable field in the text string.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of data occurs once to identify the number of error records in the row.			
IPM Error Entries	23-25	n-3	The number of keys for the subsequent error messages.

Field Name	Positions	Attribute	Comments and Values
The following segment of data represents the key to the error text. This group of fields occurs 300 times. If there is no valid data, the occurrences will be space filled.			
IPM Error Message Number	26-29	n-4	The four-digit internal IPM error message text number. This is a unique number assigned by GCMS.
IPM Error Message Start	30-34	n-5	The start position of the error message.
IPM Error Message Length	35-37	n-3	The length of the error message.
Number IPM Error Message Variable Fields	38	n-1	The number of variable fields in the IPM error message.

The following segment of data occurs once for each error message row.

Field Name	Positions	Attribute	Comments and Values
IPM Error Message Text	3,926-29,962	n-26,037	The error message text for each corresponding internal IPM error text message number.

Table IP0016T1: Brand Product

This table contains the valid licensed product ID and masked product ID combinations.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 42: Table IP0016T1: Brand Product

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Licensed Product ID	23-25	an-3	The actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
GCMS Product ID	26-28	an-3	The Product ID recognized by the GCMS issuer account range and card program ID combination. It may be different from the licensed Product ID associated with the issuer account card program identifier combination.
Card Program Identifier	29-31	an-3	The card program identifier associated with the account range. Mastercard or other proprietary service mark.
Product Class	32-34	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.

Field Name	Positions	Attribute	Comments and Values
Product Type ID	35	an-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Product Category	36	an-1	Identifies the product category of the Mastercard product code. Valid values: D = Debit P = Prepaid C = Credit N = None (For non-Mastercard Product Codes)
Europe Product Category Code	37	ans-1	Europe Product Category Code Valid values: D = Europe Debit Product C = Europe Credit Product P = Europe Prepaid Product O = Europe Commercial Product N = Not applicable
Commercial Product Indicator	38	ans-1	Identifies the product category Valid values: 0 = No participant 1 = Small business participant 2 = Large market participant 3 = Business debit participant 4 = Business prepaid participant
Filler	39-44	ans-6	Reserved for future use.

Table IP0017T1: Currency Codes

This table contains the Mastercard supported ISO currency codes and their associated currency exponents.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
ISO Code 1	23-25	n-3	Must be a valid ISO currency code.
Alpha Currency Code	26-28	an-3	Must be a valid ISO alpha currency code.
Currency Exponent Code	29	n-1	Valid ISO currency code exponent.
Filler	30-45	ans-16	Reserved for future use.

Table IP0018T1: Mastercard Product Graduation Parameters

This table contains the valid account category/licensed product ID/IRD combinations.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 43: Table IP0018T1: Mastercard Product Graduation Parameters

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the key to the time frame entries and will occur once for each unique combination of these fields.			
Account Category Code	23	an-1	The Account Category Code Valid values: M = Domestic-Enhanced Value and Product Graduation P = Mastercard Product Graduation or Co-Brand Proprietary Card Program. T = U.S. Domestic-High Value and Product Graduation Y = Spend Shortfall and Product Graduation D = Level 1 + Product Graduation F = Level 2 + Product Graduation H = Level 3 + Product Graduation K = Level 4 + Product Graduation R = Level 5 + Product Graduation
Licensed Product ID	24-26	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Interchange Rate Designator (IRD)	27-28	an-2	The interchange rate designator. This field will contain spaces.

About optimized current parameter file layouts
Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

Field Name	Positions	Attribute	Comments and Values
GCMS Product ID	29-31	an-3	This is the Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Licensed Product ID associated with the issuer account range and card program identifier combination.
Product Class	32-34	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values
Product Type ID	35	n-1	The product type of the associated issuing account range. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Account Type Category Code	36-38	an-3	003 = Mastercard Enhanced Value Platform/ High Value/Spend Shortfall/Small Business and Mastercard Product Graduation
Account Category Code Life Cycle Date	39-46	ns-8	The Account Category Code Life cycle date. Format: CCYYMMDD
Product Code Life Cycle Date	47-54	ns-8	The Product Code Life Cycle Date. Format: CCYYMMDD
Filler	55-63	ans-9	Reserved for future use.

Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

This table identifies Account Level Management participation based on Card Program Identifier, Business Service Arrangement Type, and Business Service ID code combination. It will also

provide information related to the Business As Usual and Enhanced Value Platform account categories.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Acceptance Brand	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	33-34	an-2	The interchange rate designator. NOTE: A Null IRD setup with an Account Category Code value represents Account Level Management participation for the Acceptance Brand/Business Service Arrangement Type/Business Service ID Code.
Licensed Product ID	35-37	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

Field Name	Positions	Attribute	Comments and Values
Account Category Code	38	an-1	The Account Category Code An account category code setup for the Business Service and Acceptance Brand where the IRD, shown as spaces, indicates the Account Level Management programs that the Business Service supports. If the Business Service participates in Account Level Management and there is no unique IRDs setup with the Account Category Code, then incentive interchange is determined by rate type 20 on the transaction. Account Level Management Participation valid values: B = Domestic-Enhanced Value Canada-High Spend P = Product Graduation S = U.S. Domestic-High Value Canada-Premium High Spend W = Spend Shortfall C = Level 1 E = Level 2 G = Level 3 J = Level 4 Q = Level 5 R = Level 5 + Product Graduation

Table IP0019T1: Account Level Management Participation and Enhanced Value Parameters

Field Name	Positions	Attribute	Comments and Values
			An Account Category Code setup for a Business Service and Acceptance Brand where an IRD has a value (not space) indicates that the IRD is valid for transactions qualified as Account Level Management under the Business Service. B = U.S. Domestic-Enhanced Value Canada-High Spend M = U.S. Domestic-Enhanced Value and Product Graduation S = Domestic-High Value Canada-Premium High Spend T = U.S. Domestic-High Value and Product Graduation W = Spend Shortfall Y = Spend Shortfall and Product Graduation Z = Mastercard provided default value indicating that the specific cardholder account found in the DE 2 (Primary Account Number [PAN]) of the transaction does not participate in Account Level Management processing for Mastercard Enhanced Value Platform or Mastercard Product Graduation. C = Level 1 D = Level 1 + Product Graduation E = Level 2 F = Level 2+ Product Graduation G = Level 3 H = Level 3 + Product Graduation J = Level 4 K = Level 4 + Product Graduation

Field Name	Positions	Attribute	Comments and Values
Account Type Category Code	39-41	an-3	The account type category code. Valid values: 000 = Business As Usual 001 = Mastercard Enhanced Value Platform/ Small Business 002 = Mastercard Product Graduation or Cobrand Proprietary Card Program 003 = Mastercard Enhanced Value Platform/ High Value/Spend Shortfall/Small Business and Mastercard Product Graduation 004 = Spend Shortfall
Account Category Code Life Cycle Date	42-49	ns-8	The Account Category Code life cycle date. Format: CCYYMMDD
Filler	50-53	ans-4	Mastercard use only.

Table IP0020T1: PAN Mapping Product Code Pairs

Contains valid Primary Account Number (PAN) mapping POS licensed product code and funding licensed product code pairs.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 44: Table IP0020T1: PAN Mapping Product Code Pairs

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
POS Licensed Product ID	23-25	an-3	This is the actual Point-of-Sale product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Funding Licensed Product ID	26-28	an-3	This is the actual Funding product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
Funding GCMS Product ID	29-31	an-3	This is the Funding Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Funding Licensed Product ID associated with the issuer account range and card program identifier combination.
Funding Product Class	32-34	an-3	The product class associated to the funding account range. Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i>, Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Funding Product Type ID	35	an-1	The product type associated to the funding account range. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other

Field Name	Positions	Attribute	Comments and Values
Funding Card Program Identifier	36-38	an-3	The card program identifier associated with the account range. Mastercard or other proprietary service mark.
In Control Future Use Switch	39	an-1	In Control future use switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for an anticipated future In Control program. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for an anticipated future In Control program.
In Control Service F Switch	40	an-1	In Control Service F Switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for In Control Service F. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for In Control Service F.
In Control Service E Switch	41	an-1	In Control Service E Switch. Valid values: Y = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is valid for In Control Service E. N = The Product ID pair (POS Licensed Product ID and Funding Licensed Product ID) is NOT valid for In Control Service E.
Filler	42-51	ans-10	Reserved for future use.

Table IP0023T1: MDS Routing Member ID

This table contains the processor ID for the Mastercard Debit Switch (MDS) in Europe. This table is used for specific transactions submitted to the MDS.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
MDSE Member ID	23-33	an-11	Processor ID

Table IP0025T1: Message Reason Codes

This table is only used for Reason Codes on Fee Collection Messages.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 45: Table IP0025T1: Message Reason Codes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Message Reason Code (DE 25)	23-26	n-4	Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> .
Message Reason Code (DE 25) Debit/Credit Indicator	27-28	n-2	Valid values: 19 = Credit to Originator 29 = Debit to Originator

Table IP0026T1: Parameter Print Controls

This table contains control information to print data on a report for all IPM parameter tables. The parameters include specifics regarding the orientation of the report, placement of the header and column lines, and positioning of data on the report.

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Subject Table ID	23-26	an-4	Identifies the table that is the subject of this Keys Table record. Must be a valid IPM MPE Table ID.
Line Indicator	27	an-1	Valid values: 1 = Header Line 2 = Detail Line
Line Number	28-29	n-2	The applicable line number.
Column Number	30-32	n-3	The applicable column number.
Header Line Information			
Text	33-102	an-70	Present only for Header Lines: Indicates the header text that will go in the Line/Column position.
Detail Line Information—Label			Present only for Detail Label Lines. Redefines the Header Line Text.
Field Length	33-36	n-4	Present only for Detail Label Lines. The length of the Detail Line.
Field Type	37	an-1	Present only for Detail Label Lines. Valid values: X = Alphanumeric N = Zoned decimal P = Packed decimal B = Binary L = Label
Label Text	38-102	an-65	Present only for Detail Label Lines. The label text.

Field Name	Positions	Attribute	Comments and Values
Detail Line Information: Non-Label			Present only for Detail Non-Label Lines. Redefines the Header Line Text.
Field Length	33-36	n-4	Present only for Detail Non-Label Lines. The length of the Detail Line.
Field Type	37	an-1	Present only for Detail Non-Label Lines. Valid values: X = Alphanumeric N = Zoned decimal P = Packed decimal B = Binary L = Label
Non-Label Information			Present only for Detail Non-Label lines.
Position in Row	38-41	n-4	The position within the applicable row.
Decimal Places	42	n-1	The number of decimal places.
Filler (reserved for internal use)	43-102	an-60	Space filled.

Table IP0027T1: Run Control Default Override Values

This table contains all lines required for creation of the run control file that the user updates when overriding the default values established for the run control process (the values in table IP0001T1).

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.

Line Type	23	an-1	Valid values: Space = Blank on label line 1 = Header line 0 = UTC Offset P = Processing Date T = Processing Time D = Details with user edited run options
Filler (reserved for internal use)	24-25	an-2	Space filled.
Data	26-105	an-80	Run Control Parameter file details.

Table IP0028T1: Country Codes

This table contains the numeric and alphanumeric country codes. It also contains state/province codes for countries that require the presence of state/province codes.

Optimized Structure: Generic, All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 46: Table IP0028T1: Country Codes

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Timestamp	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Country Code: Alpha	23-25	an-3	The alphanumeric country code established by Mastercard.
State-Province Code: Alpha	26-28	an-3	The alphanumeric state/province code established by Mastercard.
Country Code Edit ID	29	an-1	Valid values: Y = the edit to validate the state/province code is applicable N = the edit to validate the state/province code is not applicable
Region	30	an-1	The region in which the country is located.
Country Code: Numeric	31-33	n-3	The numeric country code established by the International Organization for Standardization (ISO).
National Currency Code: Numeric	34-36	n-3	The numeric currency code associated with the country code established by ISO.
Country Name	37-66	a-30	The country name
Life Cycle Indicator	67	an-1	State/Province Code Life Cycle Indicator. Valid values: A = All transactions L = Life cycle transactions only.
Diners Interchange Indicator	68	n-1	Indicator identifies Caribbean or U.S. Territories Valid values: 0 = Not Applicable 1 = Caribbean or U.S. Territory for Diners Interchange.

Field Name	Positions	Attribute	Comments and Values
Filler	69	an-1	Filler (Central Site use only)
Euro Zone Indicator	70	an-1	Reserved for Mastercard use
Additional National Currency Codes (occurs 4 times)	71-82		The numeric currency codes associated with the country code established by ISO.
Additional National Currency Code		n-3	Additional Currency Code
VAT Indicator	83	an-1	The VAT indicator: Valid values: N = Not a Participating VAT Country Y = Participating VAT Country
Filler	84-86	an-3	Reserved for Mastercard use.
EEA Regulated Indicator	87	ans-1	EEA Regulated Indicator Valid values: Y = Country Qualifies for EEA Regulated Interchange N = Country does not qualify for EEA Regulated Interchange
EEA Domestic Rate Qualification Indicator	88	ans-1	EEA Domestic Rate Qualification Indicator Valid values: Y = EEA Domestic Rate qualified N = Not EEA Domestic Rate qualified
CCCR Participation Country	89	ans-1	Customer Currency Conversion Rate (CCCR) participation country. Valid values: Y = Country CCCR participant N = Not a CCCR participant

Field Name	Positions	Attribute	Comments and Values
SEPA Participation Indicator	90	ans-1	SEPA Participation Indicator. Valid values: S = SEPA participant T = Non-SEPA participant N = Not applicable
EEA Territory Indicator	91	ans-1	EEA Territory Indicator Valid Values: Y = Territory qualifies for EEA regulated interchange N = Territory does not qualify for EEA regulated interchange.
EEA Regulated Extension Country Indicator	92	ans-1	EEA Regulated Extension Country Indicator Valid values: Y = Country is not EEA but qualifies for EEA regulated interchange. N = Country is not EEA and does not qualify for EEA regulated interchange.
Mastercard Transaction Calculator Indicator	93	ans-1	Mastercard Transaction Calculator Indicator Valid values: - Y = Mastercard Transaction Calculator service is available in this country - N = Mastercard Transaction Calculator service is not available in this country
Filler	94-143	ans-50	Reserved for future use.

Table IP0029T1: Edit Override Table

This table contains the GCMS Internal Edit Number for which GCMS applies date based life cycle processing.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
GCMS Internal Edit Number	23-26	n-4	Field edit number.
Environment	27-29	an-3	Environment.
Edit Implementation Date	30-37	an-8	Edit implementation date in CCYYMMDD format.
Override Value List	38-45	an-8	Table override value

Table IP0030T1: Interchange Amount Restriction

This table contains the amount ranges for large ticket interchange programs that are restricted based on the transaction amount.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the key to the time frame entries and will occur once for each unique combination of these fields.			
Card Program Indicator	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	33-34	an-2	The interchange rate designator.
Currency Code-numeric	35-37	n-3	The ISO defined numeric currency code associated with minimum and maximum transaction amounts.
Exponent	38	n-1	Currency exponent
Minimum Transaction Amount	39-50	n-12	The minimum amount applicable to a minimum transaction amount range limit.
Maximum Transaction Amount	51-62	n-12	The minimum amount applicable to a maximum transaction amount range limit.
Filler	63-69	ans-7	Reserved for future use.

Table IP0031T1: Addendum Data

This table contains the mandatory elements for addendum messages (PDS 0500 and greater).

Optimized Structure: Table Restructuring: This table is setup to identify a single edit number PDS 0501 subfield 1 and subfield 2, and the number of entries to occur once per unique

occurrence. It then concatenates the valid Data Element/PDS Indicator and PDS number in occurrences.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the key to the time frame entries and will occur once for each unique combination of these fields.			
Addendum Edit Number	23-26	n-4	The specific addendum message four-digit edit number.
Contents of PDS 0501 (Transaction Description), subfield 1 (Usage Code)	27-28	an-2	Valid values: 01 = Passenger Transport Detail 05 = Vehicle Rental Detail 06 = Lodging Detail 07 = Temporary Services 08 = Shipping/Courier Services 09 = Electronic Invoice: Transaction Data/ Party Information 10 = Payment Transaction 11 = Telephony Billing: Detail/Summary 12 = Travel Agency 13 = Lodged Account 14 = Private Label 15 = Healthcare 98 = Corporate Detail 99 = Generic Detail

Field Name	Positions	Attribute	Comments and Values
Contents of PDS 0501 (Transaction Description), subfield 2 (Industry Record Number)	29-31	an-3	NOTE: The Usage Code and Industry Record are used in conjunction to uniquely identify the addendum data format. Valid values: 000 = Passenger Transport Detail: General Ticket Information 001 = Passenger Transport Detail: Trip Leg Data 002 = Passenger Transport Detail: Rail Data 000 = Vehicle Rental Detail 000 = Lodging Detail 000 = Temporary Services 000 = Shipping/Courier Services 000 = Electronic Invoice: Transaction Data 001 = Electronic Invoice: Party Information 000 = Payment Transaction Detail 000 = Telephony Billing Summary 001 = Telephony Billing: Party Information 000 = Corporate Detail: Corporate Card Common Data Requirements 000 = Travel Agency 000 = Lodged Account 002 = Corporate Detail: Corporate Fleet Transaction Information 950 = Corporate Detail: Corporate Card Line Item Detail 000 = Generic Detail 000 = Private Label: Common Data 001 = Private Label: Line Item Detail 000 = Healthcare
No of Entries	32-35	n-4	Value

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the key to the time frame entries and will occur once for each unique combination of these fields.			
Data Element/PDS Indicator	36	n-1	Valid values: 2 = Data element 3 = PDS
Field Number	37-40	n-4	The addendum message field number to be edited.
Filler	41-44	ans-4	Reserved for future use.

Table IP0033T1: IPM Module Names and Version Numbers

This table includes all of the names and version numbers of the modules that GCMS and the Clearing Optimizer software include.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum possible entries per record are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

About optimized current parameter file layouts
Table IP0033T1: IPM Module Names and Version Numbers

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Module ID	23-30	an-8	Unique identifier of the GCMS or Clearing Optimizer module.
Source Date and Time	31-44	an-14	Source Date and Time of the GCMS or Clearing Optimizer module. Unique identifier of the module. Format: YYYYMMDDHHMMSS This field is applicable only if the Type field is a value of PR.
Type	45-46	an-2	Indicator of the type of module. Valid values: PR = Program CP = Copybook JC = JCL PC = Proc
Location ID	47	an-1	Indication whether the distributed Clearing Optimizer software, the Central Site clearing system, or both use this module. Valid values: P = Module used by the Clearing Optimizer software C = Module used by Central Site (GCMS) B = Module used by both the Clearing Optimizer software and the Central Site clearing system
Description	48-72	an-25	Description of the GCMS or Clearing Optimizer module.

Table IP0034T1: Processing Code Group

This table is used in settlement service selection processing. It provides the group code for each processing code recognized in the IPM format.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Processing Code	23-25	n-3	Processing Code
Processing Code Group	26-28	an-3	Code that defines a grouping of processing codes that can be used across various clearing and settlement systems.

Table IP0035T1: Settlement Service Selection BIN Data

This table contains BIN settlement service criteria.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Selection Criteria ID	23-33	n-11	Unique identifier relating to the criteria record.
Acquiring BIN	34-40	an-7	The six digit acquiring BIN containing a preceding leading zero. When this position is populated with an asterisk, it indicates that there is no Acquiring BIN set up for this criterion.
Effective Date Number	41-51	n-11	Latest Effective Date/Time Stamp in integer format.

Table IP0037T1: Selection Criteria Data

This table contains settlement service criteria data.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

NOTE: When positions 45-69 of this table are populated with an asterisk, it indicates that there is no <field name> set up for this criteria.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Selection Criteria ID	23-33	n-11	Unique identifier relating to the criteria record.
Effective Date Number	34-44	n-11	Effective date and time, in integer format, applied to the specific selection criteria for each settlement service and TAA combination.
Card Program ID	45-47	an-3	The Card Program Identifier value associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Card Program ID set up for this criteria.
Transaction Function Group	48-49	an-2	The Transaction Function Group associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Transaction Function Group set up for this criteria.
Transaction Currency	50-52	an-3	The Transaction Currency associated with the settlement service ID for the member. When this position is populated with an asterisk, it indicates that there is no Transaction Currency set up for this criteria.
Business Service Arrangement Type	53	an-1	The Business Service Type associated with the settlement service ID for the member. This applies to intra-European transactions only. When this position is populated with an asterisk, it indicates that there is no Business Service Arrangement Type set up for this criteria.

Field Name	Positions	Attribute	Comments and Values
Licensed Product ID	54-56	an-3	This is the actual product assigned by Mastercard when licensing the combination of issuer account range and card program identifier. When this position is populated with an asterisk, it indicates that there is no Licensed Product ID set for this criteria.
Processing Code Group	57-59	an-3	Code that defines a grouping of processing codes that can be used across various clearing and settlement systems. When this position is populated with an asterisk, it indicates that there is no Processing Code Group set up for this criteria.
Filler	60-62	an-3	Mastercard use only.
Acceptor Business Code	63-66	n-4	Acceptor Business Code classifies the type of business applicable to the acceptor.
Installment Type Code	67-69	an-3	Type of Installment Valid Values: 403: with interest 407: without interest 410: Installment by Issuer 488: IATA

Table IP0039T1: Selection Criteria Account Range

This table contains account range settlement service criteria.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Selection Criteria ID	23-33	n-11	Unique identifier relating to the criteria record.
Issuer Account Range—Low	34-52	an-19	The account number at the low end of the issuing account range.
Issuer Account Range—High	53-71	an-19	The account number at the high end of the issuing account range.
Effective Date Number	72-82	n-11	Effective date and time, in integer format, applied to the specific select criteria for each settlement service and TAA combination.

Table IP0040T1: Issuer Account Range

This table contains all issuing account ranges and associated card program identifier information. Any unique combination of issuing account range (low) and GCMS product ID generates a separate record of this type.

The following is an example of how to obtain information, such as ICA, for a specific PAN from the new optimized table IP0040T1. This example is not intended to represent a module that is supported by Mastercard. It is intended to identify COBOL code that can be incorporated into another application. The COBOL copybooks and called sub-modules, are available as part of the Clearing Optimizer Mainframe version software code distribution.

```
* YOU NEED SYS007A IN THE JCL ASSIGNED TO RRD
* ONEDAY FILE TO RUN THIS PROGRAM.

* COPYBOOK FOR TABLE 40 - ACCOUNT RANGE TABLE.

01 IP00404-TABLE EXTERNAL.
05 IP00404-ENTRIES-FOUND-COUNT PIC S9(08) COMP.
05 IP00404-AR-RANGE-GRP.
    10 IP00404-TBL-40-AR-H PIC X(19).
    10 IP00404-TBL-40-AR-L PIC X(19).
05 IP00404-ENTRY OCCURS 99 TIMES
INDEXED BY IP00404-ACCT-RNG-INDEX.
COPY IP004004 REPLACING ==:T:== BY ==IP00404==.

* COPYBOOK TO PASS EFFECTIVE DATE AND TIME.
```

```

COPY IP500005 REPLACING ==:T:== BY ==IP500005==.

PROCEDURE DIVISION.

* IN THIS SAMPLE CODE 2004040214 IS THE PROCESS DATE AND TIME
* PROCESS DATE OR RUN CONTROL DATE MUST BE USED HERE.
  MOVE '2004040214'
    TO IP500005-CLEARING-DT-TM
* IN BELOW EXAMPLE 5404030123456789 IS THE ACCOUNT NUMBER
  MOVE ZEROES TO IP00404-TBL-40-AR-H
  MOVE '5404030123456789'
    TO IP00404-TBL-40-AR-H(1:16)

* IP00404-TBL-40-AR-H SHOULD HAVE THE ACCOUNT NUMBER WHICH IS
* LEFT JUSTIFIED WITH TRAILING ZEROES. IN ABOVE CASE IT WILL BE
* 5404030123456789000
  CALL 'IP280010'
  IF IP00404-ENTRIES-FOUND-COUNT IS GREATER THAN ZERO
    DISPLAY 'ACCOUNT NUMBER FOUND'
    DISPLAY 'ICA = ' IP00404-PRFX-ICA(1)
  ELSE
    DISPLAY 'ACCOUNT NUMBER NOT FOUND'

END-IF

```

Optimized Structure: Field Reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 47: Table IP0040T1: Issuer Account Range

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Account Range ID	23-28	n-6	A unique identifier representing the Account Range.

Field Name	Positions	Attribute	Comments and Values
Card Program Identifier	29-31	an-3	The card program identifier associated to the issuer account range. Mastercard or other proprietary service mark.
Issuer Card Program Identifier Priority Code	32-33	n-2	The priority code assigned to the Card program identifier by the issuer, for the associated issuing account range. Priority codes begin with a low-value number for the highest priority and continue in ascending sequence. For example, an issuing account range that shows the CIR identifier as priority 01 and the MCC identifier as priority 02 indicates that the CIR identifier has a higher priority and that GCMS will consider it first. Also important to note is that priority code values are not always present in unbroken ascending sequence. For example, an issuing account range might consist of a single entry showing the CIR identifier as priority 02 (with no entry for priority 01). In another example, an issuing account range might consist of one entry showing priority 01 and another entry showing priority 03 (with no entry for priority 02). GCMS looks for the highest priority code value (lowest numerical value), and then the next highest priority, and so on. Member systems should not expect every account range to contain an entry with priority 01, or the priority codes to appear in an unbroken sequence.
Member ID	34-44	n-11	The Member ID associated with the issuing account range.
GCMS Product ID	45-47	an-3	This is the Product ID recognized by GCMS for the issuer account range and card program identifier combination. It may be different from the Licensed Product ID associated with the issuer account range and card program identifier combination.

Field Name	Positions	Attribute	Comments and Values
Product Type ID	48	n-1	The product type of the associated issuing account range. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Endpoint	49-55	n-7	The seven-digit routing endpoint associated with the issuing account range.
Country Code—Alpha	56-58	an-3	The alphabetic country code associated with the issuing account range.
Country Code—Numeric	59-61	n-3	The ISO defined numeric country code associated with the issuing account range.
Region	62	an-1	The region of the associated country code.
Product Class	63-65	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> , Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Transaction Routing Indicator	66	ans-1	Used in intra-European interchange processing. Valid values: Space = Normal routing P = Processing Code
First Presentment Reassignment Switch	67	an-1	Product reassignment switch for first presentment transactions. Valid values: Y = Product reassigned N = Product not reassigned

Field Name	Positions	Attribute	Comments and Values
Product Reassignment Switch	68	an-1	Product reassignment switch for life cycle transaction. Valid values: Y = Product Reassigned N = Product Not Reassigned
PWCB Opt-In Switch	69	an-1	The account range is a participant in purchase with cash back transactions. Valid values: Y = Opt-In (applies to all issuer account ranges)
Licensed Product ID	70-72	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Field Name	Positions	Attribute	Comments and Values
Mapping Service Indicator	73	ans-1	The Mapping Service Indicator identifies issuing account ranges that require a Mapping Service. Valid values: Space = The issuer account range does not participate in a Mapping Service 1 = Active Contactless Issuer Participation (Full) 2 = Active Contactless Issuer Participation (Partial) 3 = Active Contactless Issuer Participation (Mastercard-assigned range) 4 = Passive Contactless Issuer Participation 5 = Passive Contactless Issuer Participation (Merchant Sponsor) 6 = Passive Contactless Issuer Participation (Mastercard Sponsor) 7 = Service-eligible Contactless Account Range 8 = Service-eligible In Control Account Range 9 = Service-eligible Electronic Commerce Account Rang A-B = Mastercard use C = Mastercard Digital Enablement Service Account Range D-H = Mastercard use I = Token Service Provider Token Range J-O = Mastercard use P = Service-eligible Pay with Rewards Q-Z = Mastercard use

Field Name	Positions	Attribute	Comments and Values
Account Level Management Participation Indicator	74	an-1	The account level management participation indicator. Valid values: N = No cardholder accounts within range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program. Y = Some cardholder accounts with range are participants in Account Level Management Processing or Co-Brand Proprietary Card Program.
Account Level Management Activation Date	75-80	n-6	The account level management activation date (yyymmdd).
Cardholder Billing Currency Default	81-83	n-3	Cardholder Billing Currency default
Cardholder Billing Currency Exponent Default	84	n-1	Cardholder Billing Currency exponent default
Cardholder Billing Additional Currency (occurs 4 times)	85-112	n-28	Cardholder Billing Currency (occurs 4 times)
Cardholder Billing Additional Transaction Currency		n-3	Cardholder Billing Additional Transaction Currency
Cardholder Billing Additional Currency		n-3	Cardholder Billing Additional Currency
Cardholder Billing Additional Currency Exponent		n-1	Cardholder Billing Additional Currency exponent

Field Name	Positions	Attribute	Comments and Values
Chip to Magnetic Conversion Service Indicator	113	an-1	The Chip to Magnetic Conversion Service Indicator. Valid values: Y = Chip to Magnetic Conversion Service applied and issuer has opted to receive the Chip to Magnetic Stripe Conversion Service results. Space = Chip to Magnetic Conversion Service not applied. S = Chip to Magnetic Conversion Service applied and issuer has opted not to receive the Chip to Magnetic Stripe Conversion Service results
Floor Expiration Date	114-119	n-6	The Floor Expiration Date. Format: YYYYMM
Co-Brand Participation Switch	120	a-1	Co-Brand participation switch. Valid values: N = The account range does not participate in Co-Brand Processing Y = The account range participates in Co-Brand Processing
Spend Control Switch	121	a-1	Spend Control Switch Valid values: N = The account range does not participate in Spend Control processing. Y = The account range participates in Spend Control processing

Field Name	Positions	Attribute	Comments and Values
Merchant Cleansing Service Participation	122-124	ans-3	Merchant Cleansing Service Participation. Valid values: 077 = Merchant Data Cleansing 078 = Merchant Data Cleansing Plus 079 = Merchant Data Advance 080 = Merchant Data Cleansing + Merchant Data Advance 081 = Merchant Data Cleansing Plus + Merchant Data Advance Space = Merchant Cleansing Service not applied
Merchant Cleansing Activation Date	125-130	n-6	Merchant Cleansing Activation Date Format: YYMMDD
Contactless Enabled Indicator	131	a-1	Contactless Enabled Indicator. Valid values: N = Not Contactless Enabled Y = Contactless Enabled M = Mobile Contactless Enabled
Regulated Rate Type Indicator	132	an-1	Regulated Rate Type Indicator. Valid values: B = Base regulated 1 = Regulated with Fraud Protected N = Not regulated
PSN Route Indicator	133	an-1	PSN Route Indicator. Valid values: Y = Route based on PAN Sequence Number N = Do Not Route based on PAN Sequence Number

Field Name	Positions	Attribute	Comments and Values
Cash Back Without Purchase Indicator	134	an-1	Cash Back Without Purchase Indicator Valid values: Y = Account Range participates in Cash Back Without Purchase service. N = Account Range does not participate in Cash Back Without Purchase service
Filler	135	ans-1	Reserved for future use.
RePower Reload Participation Indicator	136	an-1	RePower Reload Participation Indicator. Valid values: N = No rePower reload capability R = RePower reload capability X = Non Mastercard rePower exclusive reload capability
MoneySend Indicator	137	an-1	MoneySend Indicator Valid values: Y = BINS are MoneySend enabled; Domestic and Cross Border D = BINS are MoneySend enabled Domestic only N = BINS are not MoneySend enabled U = MoneySend unknown for BIN
Durbin Regulated Rate Indicator	138	ans-1	Durbin Regulated Rate Indicator Valid values: Y = Regulated switch N = Non-regulated switch
Cash Access Only Participating Indicator	139	ans-1	Cash Access Only Participating Indicator Valid values: Y = Cash Access Only Participating Account Range N = Not a Cash Access Only Participating Account Range

Field Name	Positions	Attribute	Comments and Values
Authentication Indicator	140	n-1	Authentication Indicator Valid values: 0 = Account Range not registered for Authentication Indicator 1 = Transaction qualified for Type 1 Person Present 2 = Transaction qualified for Type 2 Person Present
Filler	141	ans-1	Reserved for future use.
Issuer Target Market Participation Indicator	142	ans-1	Indicator identifies account ranges participating in the Target Market Program. Valid Values: Y = Account Ranges participating in the Target Market Program. N = Account Ranges not participating in the Target Market Program.
Post Date Service Indicator	143	ans-1	Identifies if the Account Range allows for a one-time Post Date Installment per purchase. Y = Account Range allows Post Dated Payments N = Account Range does not allow Post Dated Payments
Meal Voucher Indicator	144	ans-1	Indicator for Meal Voucher Program Y = Qualified for Meal Voucher program N = Not qualified for Meal Voucher program
Non-Reloadable Prepaid Switch	145-146	ans-2	Identifies if the Account Range is a non-reloadable prepaid card 01 = Non-reloadable prepaid program Spaces = Reloadable prepaid program or nonprepaid program 99 = The account range or BIN represents a non-Mastercard product

Field Name	Positions	Attribute	Comments and Values
Faster Funds Indicator	147	ans-1	Identifies whether Faster Funds is supported Valid values: N = Faster Funds is not supported D = Faster Funds is supported for Domestic but not Cross Border Y = Faster Funds is supported for Domestic and Cross Border
Anonymous Prepaid Indicator	148	ans-1	Identifies whether Anonymous Prepaid is supported Valid values: A = Anonymous prepaid program and not AMLD5 compliant E = Anonymous prepaid program and AMLD5 compliant N = Not prepaid or non-anonymous prepaid program/default U = Unknown
Cardholder Currency Indicator	149	ans-1	Cardholder Currency Indicator support Valid values: C = Do not provide POI currency conversion D = POI currency conversion (or DCC) is permissible for account range per Mastercard Rules T = Do not provide POI currency conversion (or DCC) per Mastercard Rules- travel cards or multi-currency accounts U = Not a Mastercard-branded account range
Pay by Account Indicator	150	an-1	Account range PbA participation indicator Valid values: Y = PbA participation N = Non PbA participation

Field Name	Positions	Attribute	Comments and Values
Issuer Account Range Gaming Participation Indicator	151	ans-1	Issuer account range Game participation indicator Valid values: N = Issuer not qualified for Gaming Participation Y = Issuer Gaming Participation
Embedded Flex Interchange Indicator	152	an-1	Indicates Embedded Flex Interchange participation. Valid values: Y = Issuer Embedded Flex Interchange Participant N = Not Issuer Embedded Flex Interchange Participant
Digital First Indicator	153	an-1	Indicates Digital First participation. Valid values: Y = Issuer is a Digital First Participant N = Issuer is not a Digital First Participant
Gaming and Gambling Payments Program Fast Posting Indicator	154	ans-1	Y = Issuer supports fast posting with immediate funds availability N = Issuer does not support fast posting with immediate funds availability
Name Validation Service	155	an-1	Name Validation Service Participation Flag Valid Values: Y= Issuer is participating N= Issuer not participating
Mastercard One Credential Participation Indicator	156	an-1	Indicates Mastercard One Credential Participation Valid values: - Y = Issuer is participating in Mastercard One Credential - N = Issuer is not participating in Mastercard One Credential
Filler	157-278	ans-122	Reserved for future use.

Table IP0041T1: Acquirer Reference ID

This table contains the identifier from table IP4191T1 for each BIN range. Any unique acquirer BIN and card program identifier combination generates a separate record of this type.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Acquiring BIN	23-28	n-6	The unique identifier representing the acquiring BIN.
Card Program Identifier	29-31	an-3	The card program identifier associated with the acquiring BIN ID.
Member ID	32-42	n-11	The member ID associated with the acquiring BIN ID.
Filler	43	an-1	Space filled.
Endpoint	44-50	n-7	The seven-digit endpoint associated with the acquiring BIN ID. 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa

Field Name	Positions	Attribute	Comments and Values
POS EMV Compliance Indicator	51	an-1	Used in intra-European interchange processing to indicate whether the acquirer has one or more POS terminals that are EMV compliant and therefore qualifies for various Chip tiers. Valid values: Y = Yes N = No
ATM EMV Compliance Indicator	52	an-1	Used in intra-European interchange processing to indicate whether the acquirer has one or more ATM terminals that are EMV compliant and therefore qualifies for various Chip tiers. Valid values: Y = Yes N = No
Merchant UCAF Indicator	53	an-1	Used in intra-European interchange processing to qualify for the merchant UCAF rate. Valid values: Y = Yes N = No
Region (Occurs 6 times)	54-59	an-1	The region of the associated country code.
Country: Alpha (Occurs 20 times)	60-119	an-3	The alphabetic country code associated with the acquiring BIN ID.
Filler	120-163	ans-44	Reserved for future use.

Table IP0045T1: Cash Disbursement

This table is used during the interchange calculation process for interregional and intraregional domestic cash disbursements. This table contains a pointer to Table IP0053T1 (Interchange Fee Type) to obtain domestic (that is, both members are located in the same country) cash disbursement fees.

Optimized Structure: Field Reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

NOTE: Non-domestic cash disbursement fees are obtained using Table IP0052T1 (Interchange Fee Group) and Table IP0053T1 (Interchange Fee Type).

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Control Name	23-26	an-4	Valid values: CAPR = Cash Disbursement Presentment CACB = Cash Disbursement Chargeback
Control Pointer	27-37	n-11	This is the pointer to Table IP0053T1 (Interchange Fee Type Table) that identifies the record for cash disbursements.

Table IP0048T1: Settlement Service

This table contains the settlement service ID, settlement transfer agent, and related information for bilateral and intracurrency settlement service agreements.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Member ID	23-33	n-11	The customer ID.
Settlement Service Level Priority	34	n-1	The priority used in the selection process.
Settlement Service Level Code	35	an-1	The code that identifies the settlement level of the settlement service. Valid values: 1 = Regional 3 = Intracurrency 5 = Bilateral
Settlement Service ID	36-45	ans-10	The settlement service ID in which the member participates.
Account Reference Code	46-54	an-9	Sequence number identifying the settlement service/transfer agent assignments.
Settlement Transfer Agent	55-65	an-11	The settlement transfer agent associated with the settlement service.
Filler	66-84	ans-19	Spaces
Settlement Currency Code	85-87	n-3	The numeric currency code of the settlement service.
Settlement Currency Exponent	88	n-1	The exponent for the currency of the service.

Table IP0050T1: Settlement Service Selection Criteria

This table contains the settlement service ID, and selection criteria for the settlement service agreements specified.

Optimized Structure: Generic: All entries for the table that follows the key are combined one after the other. The Parameter Master File table contents has the same positioning as the Optimized Current Parameters File. The maximum allowable entries for each row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Member ID	23-33	n-11	The customer ID.
Settlement Service Level Priority	34	n-1	The priority used in the selection process.
Settlement Service Level Code	35	an-1	The code that identifies the settlement level of the settlement service. Valid values: 3 = Intracurrency 5 = Bilateral
Settlement Service ID	36-45	ans-10	The settlement service ID in which the member participates.
Account Reference Code	46-54	an-9	Sequence number identifying the settlement service/transfer agent assignments.
Selection Criteria ID	55-65	n-11	Unique identifier relating to the criteria record.

Field Name	Positions	Attribute	Comments and Values
Acquirer, Issuer, Both Switch	66	an-1	Code indicating the activity allowed by the settlement service. A = Acquirer I = Issuer B = Both
Effective Date Number	67-77	n-11	Effective date and time, in integer format, applied to the specific select criteria for each settlement service and TAA combination.

Table IP0052T1: Interchange Fee Group

This table identifies interchange fee groups and contains the data necessary to establish fees for each of the groups.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File. This table is accessed through table IP5200T1 which contains the data key (Card Program Identifier/Business Service/IRD) and pointer information for the fee group.

Table 48: Table IP0052T1: Interchange Fee Group

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Message Type Identifier (MTI)	23-24	b-2	The four-digit descriptor for each IPM message class and function.

Field Name	Positions	Attribute	Comments and Values
Function Code (DE 24)	25-26	b-2	The three-digit function code that indicates the message's specific purpose.
Process Code (DE 3, subfield 1)	27-28	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 = ATM Cash Withdrawal 09 = Purchase with Cash Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Processing Code - Cardholder "From" Type (DE 3, subfield 2)	29-30	n-2	The Cardholder "From" Type field contains the "masked" value for DE 3, subfield 2 as provided in table IP2054T1. 00 = Default
Processing Code - Cardholder "To" Type (DE 3, subfield 3)	31-32	n-2	The Cardholder "To" Type. Valid values: 00 = Default
Reversals Allowed	33	an-1	Determines whether reversals are permitted for the combination of card program identifier, business service, IRD, MTI, function code and processing code. Valid values: B = Both reversals and non-reversals R = Reversals only N = Non-reversals only

Field Name	Positions	Attribute	Comments and Values
Interchange Compliance Switch	34	an-1	Indicates whether Interchange Compliance processing applies to the card program identifier, business service, IRD, MTI, function code and processing code combination. N = Not valid for Interchange Compliance 1 = Valid for Interchange Compliance, U.S. Acquired, U.S. Issued 2 = Valid for Interchange Compliance, U.S. Acquired, non-U.S. Issued
Fee Code Pointer	35-40	ps-6	Pointer to Table IP0053T1 (Interchange Fee Type).
Product Type ID	41	n-1	The product type associated with the interchange fee group. Valid values: 1 = Consumer 2 = Commercial 3 = Both 4 = Other
Timeliness Authorization Code Pointer	42-47	ps-6	Pointer to Table IP0059T1 (Timeliness and Authorization Code Table).
Product Class: Acceptor Override Pointer	48-53	ps-6	Pointer to Table IP0057T1 (Interchange Fee Group Override Parameters Table).
Mastercard Assigned ID Mandatory Indicator	54	an-1	Identifies if Mastercard Assigned ID is mandatory. Valid values: Y = Mastercard assigned ID mandatory N = Mastercard assigned ID not mandatory

Field Name	Positions	Attribute	Comments and Values
Valid Mastercard Assigned ID	55	an-1	Identifies at the acceptance brand, business service arrangement type, Business Service ID Code, Interchange Rate designator combination that the Mastercard Assigned ID should be validated. Valid values: Y = Mastercard Assigned ID will be validated N = Mastercard Assigned ID will not be validated.
Contactless Indicator	56	an-1	Contactless Indicator Valid values: M = Mobile Contactless Enabled N = Not Contactless Enabled or Mobile Contactless Enabled Y =Contactless Enabled Space = Not applicable for editing
Filler	57-73	ans-17	Reserved for future use.

Table IP0053T1: Interchange Fee Type

This table contains the identifier from Table IP5300T1 for each fee code pointer. Any fee code pointer with unique rate type and payment party combination generates a separate record of this type.

The following is an example of how to obtain information such as rate type, and payment party, for a specific Fee Code Pointer from the new optimized table IP0053T1. This example is not intended to represent a module that is supported by Mastercard. It is intended to identify COBOL code that can be incorporate into another application. The COBOL copybooks and called sub-modules, are available as part of the Clearing Optimizer and Utilities—Mainframe version software code distribution.

```
* YOU NEED SYS007A IN THE JCL ASSIGNED TO RRD
* ONEDAY FILE TO RUN THIS PROGRAM.

* COPYBOOK FOR TABLE 53 - INTERCHANGE FEE TYPE

01 IP00534W-TABLE-DATA          EXTERNAL.
02 IP00534W-ENTRIES             PIC S9(08) COMP.
02 IP00534W-FEE-CODE-PTR       PIC 9(11) COMP-3.
02 IP00534W-TABLE.
03 IP00534W-ENTRY OCCURS 250 TIMES
    INDEXED BY IP00534W-IDX.
    COPY IP005304 REPLACING ==:T:== BY ==IP00534W==.
```

```
* LAYOUT TO PASS FEE CODE POINTER.

01 IP00534-TABLE          EXTERNAL.
05 IP00534-FEE-CODE-PTR  PIC 9(11) COMP-3.

* COPYBOOK TO PASS EFFECTIVE DATE AND TIME.

COPY IP500005 REPLACING ==:T:== BY ==IP50005==.

PROCEDURE DIVISION.

* IN THIS SAMPLE CODE 2014041414 IS THE PROCESS DATE AND TIME
* PROCESS DATE OR RUN CONTROL DATE MUST BE USED HERE.
  MOVE '2014041414'
    TO IP50005-CLEARING-DT-TM

* IN BELOW EXAMPLE 000000000001 IS THE FEE CODE POINTER
  MOVE 000000000001
    TO IP00534-FEE-CODE-PTR
  CALL 'IP785410'
  IF IP00534W-ENTRIES GREATER THAN ZERO
    PERFORM VARYING IP00534W-IDX FROM 1 BY 1
      UNTIL IP00534W-IDX GREATER THAN IP00534W-ENTRIES
      DISPLAY 'FEE CODE POINTER FOUND'
      DISPLAY 'IP00534W-RATE-TYPE'
      IP00534W-RATE-TYPE(IP00534W-IDX)

      DISPLAY 'IP00534W-PAYMENT-PARTY'
      IP00534W-PAYMENT-PARTY(IP00534W-IDX)

      DISPLAY 'IP00534W-CURR-CODE'
      IP00534W-CURR-CODE(IP00534W-IDX)

      DISPLAY 'IP00534W-CURR-EXP'
      IP00534W-CURR-EXP(IP00534W-IDX)

      DISPLAY 'IP00534W-PROGRAM-TYPE'
      IP00534W-PROGRAM-TYPE(IP00534W-IDX)

      DISPLAY 'IP00534W-FEE-TYPE'
      IP00534W-FEE-TYPE(IP00534W-IDX)

      DISPLAY 'IP00534W-NO-OF-SGMNTS'
      IP00534W-NO-OF-SGMNTS(IP00534W-IDX)

      PERFORM VARYING IP00534W-S FROM 1 BY 1
        UNTIL IP00534W-S GREATER THAN
          IP00534W-NO-OF-SGMNTS(IP00534W-IDX)
        DISPLAY 'IP00534W-TXN-LOW-AMOUNT'
        IP00534W-TXN-LOW-AMOUNT
        (IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-INTRCHG-RATE'
        IP00534W-INTRCHG-RATE
        (IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-RATE-FEE-DIRECTION'
        IP00534W-RATE-FEE-DIRECTION
        (IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-UNIT-FEE'
        IP00534W-UNIT-FEE
        (IP00534W-IDX, IP00534W-S)
```

```

        DISPLAY 'IP00534W-UNIT-FEE-DIRECTION      '
        IP00534W-UNIT-FEE-DIRECTION
        ( IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-MIN-FEE-LIMIT-X        '
        IP00534W-MIN-FEE-LIMIT-X
        ( IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-MAX-FEE-LIMIT-X        '
        IP00534W-MAX-FEE-LIMIT-X
        ( IP00534W-IDX, IP00534W-S)

        DISPLAY 'IP00534W-MIN-MAX-DIRECTION      '
        IP00534W-MIN-MAX-DIRECTION
        ( IP00534W-IDX, IP00534W-S)

        END-PERFORM
    END-PERFORM
ELSE
    DISPLAY 'FEE CODE POINTER NOT FOUND'
END-IF.

```

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			

Field Name	Positions	Attribute	Comments and Values
Rate Type	23-25	an-3	The rate type value. Valid values: 000 = Cash Advance Fee (applies to manual cash disbursement transactions) 001 = Interchange Fee 006 = MPP Interchange Fee 007 = National Payment Gateway Switch Fee 010 = IVA on interchange fee (specific to Mexico processing) 013 = Late Presentment Fee 014 = First-level Corporate incentive discount 015 = Purchase with Cash Back 017 = Second-level Corporate Incentive discount 018 = New UK Summary VAT Incentive Interchange 020 = Europe Enhanced Value Incentive Rate 021 = MasterPass-Enabled Merchant Incentive Interchange 023 = EC Credit Cross Border Regulated Rate 024 = EC Debit Cross Border Regulated Rate 028 = Digital First Adjustment 030 = Digital Wallet Interchange Rate 031 = Reserved for future use
Payment Party	26-28	an-3	Valid values: ACQ = Acquirer ISS = Issuer INT = Internal
Currency Code— Numeric	29-31	n-3	The ISO defined numeric currency code associated with the fee.
Exponent	32	n-1	The currency code exponent associated with the fee currency.
Filler	33-38	ps-6	Spaces
Program Type	39-42	an-4	The program associated with the interchange fee type.

Field Name	Positions	Attribute	Comments and Values
Fee Type Code	43-44	an-2	The code associated with the interchange fee type. Valid value: 00 = Transaction Interchange Fee
No of Fee Segments	45-46	n-2	Number of Fee Segments
Interchange Fee Segment	47 (Varying from 91 to 496)		The following segment of table data occurs 1 to 10 times depending on "No of Fee Segments".
Transaction Amount Range Low		b-8	Transaction Amount Range - Low
Interchange Rate		b-8	The interchange rate, as a percentage of the transaction.
Rate Direction		an-2	Indicates how interchange unit rate is applied to the specified payment party. CR = Credit DR = Debit
Unit Fee		ps-7	If applicable, the unit fee applied to the transaction.
Fee Direction		an-2	Indicates how interchange unit fees are applied. CR = Credit DR = Debit
Minimum Fee Limit		b-8	If applicable, the minimum interchange fee amount applied to the transaction. The fee amount will be in the format of n(12) v n(6). Can be space filled if a minimum fee limit does not apply.
Maximum Fee Limit		b-8	If applicable, the maximum interchange fee amount applied to the transaction. The fee amount will be in the format of n(12) v n(6). Can be space filled if a minimum fee limit does not apply.

Field Name	Positions	Attribute	Comments and Values
Minimum-maximum Direction		an-2	Indicates how the minimum, maximum, or both interchange fees are applied. CR = Credit DR = Debit

Table IP0054T1: Retrieval Fee

This table identifies retrieval fee by card program identifier, document type, and currency.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	The card program identifier associated with the retrieval fee.
Documentation Type	26	n-1	The documentation type associated with the retrieval fee. Valid value: 1 = Hard copy original document
Currency: numeric	27-29	n-3	The ISO defined numeric currency code associated with the retrieval fee.
Currency Exponent	30	n-1	The currency code exponent associated with the currency code of the retrieval fee.

Field Name	Positions	Attribute	Comments and Values
Default Fee	31-36	p-6	

Table IP0056T1: Member Business Service Arrangements

This table identifies the valid card program identifier and business service arrangement participation information for a member. This information is a compilation of the card program identifier and business service arrangement participation maintained at the issuer account range and acquiring BIN levels for each member ID.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. This table is accessed thru table IP5600T1, which contains the data key (Member ID) and pointer information for the member business service arrangements.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Business Service Priority	23-24	n-2	The priority of the business service arrangement type.

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	25	n-1	The business service arrangement type associated with the member business service arrangement. Valid values: 1 = Interregional 2 = Intraregional 3 = Intercountry 4 = Intracountry 8 = Member-to-Member
Business Service ID Code	26-31	an-6	The business service arrangement ID code associated with the member business service arrangement type.
Business Service/ Card Program Identifier Priority	32-33	n-2	The priority of the Business Service in relationship to the card program identifier for the member.
Card Program Identifier	34-36	an-3	Mastercard or other proprietary service mark.
Business Service/ Card Program Identifier Life Cycle Indicator	37	an-1	The life cycle indicator for the combination of business service/card program identifier. Valid values are: A = All transactions may be submitted for this business service arrangement/card program identifier combination L = Life cycle: Only transactions designated as "life cycle" transactions may be submitted for this business service arrangement/card program identifier combination.
Filler	38-44	ans-7	Reserved for future use.

Table IP0057T1: Interchange Override Fee Group

This table identifies interchange fees which vary by product class, acceptor business code (MCC), acceptor business code (MCC) type, and Mastercard assigned ID overrides.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File. This table is accessed through table IP5700T1, which contains the data key (Product Class: Acceptor Override Pointer) and pointer information for the override fee group.

Table 49: Table IP0057T1: Interchange Override Fee Group

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Product Class	23-25	ans-3	Used in interchange processing. Valid values: Refer to the <i>Mastercard Network Processing Dual Message Clearing System Guide</i>, Private Data, Subelement definitions for PDS 0158, Business Activity, Subfield 8, Product Class Override Indicator for the Product Class values.
Acceptor Business Code (MCC)	26	an-4	Valid Values are listed in the <i>Mastercard Quick Reference Booklet</i> .
	27-29	ans-3	FILLER
Mastercard Assigned ID	30-35	ans-6	The Mastercard Assigned ID
Override Priority Code	36-37	n-2	If a transaction qualifies for more than one override, the clearing system will check for combinations of overrides and apply the override based on the override priority code.
Fee Code Pointer	38-43	b-6	Pointer to Table IP0053T1 (Interchange Fee Type)

Table IP0058T1: QPS and Contactless Chargeback Protection Amounts

This table contains the list of QPS and Contactless chargeback protection amounts.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Chargeback Protection Type	26	an-1	Chargeback Protection Type Valid values: A = Post-Authorized Aggregated Contactless Transit P = Contactless Q = QPS
Acceptor Business Code (MCC)	27-31	n-5	Valid values are listed in the Mastercard <i>Quick Reference Booklet</i>. When this field is populated with zeros, it represents any MCC.

Field Name	Positions	Attribute	Comments and Values
Region	32	n-1	Region of the associated country. Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa Space = Represents any region
Country Code: Numeric	33-35	n-3	The numeric country code established by the International Organization for Standardization (ISO).When this field is populated with zeros, it represents any country code.
Country Code: Alpha	36-38	an-3	The alphanumeric country code established by Mastercard. When this field is populated with spaces, it represents any country code.
Currency Code: Numeric	39-41	n-3	The numeric currency code associated with the country code established by ISO.
Currency Code: Alpha	42-44	an-3	The alpha currency code associated with the country code.
Currency Exponent	45	n-1	Currency Exponent
Chargeback Protection Amount	46-57	n-12	Chargeback Protection Amount

Table IP0059T1: Timeliness Code

This table identifies the codes for timeliness and authorization.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes			
Authorization Timeliness Code Pointer	23-33	n-11	This value is from Table IP0052T1 (Interchange Fee Group), and indicates the applicable timeliness and authorization code criteria.
System Application	34	an-1	Valid values: 1 = Global Clearing Management System application 2 = Interchange Compliance System
Timeliness Date - Two Occurrences	35-54		Non-Airline transactions are the first occurrence.
	Airline Indicator	an-1	Valid values: Y = Yes record is for airline transactions N = No record is for non-airline transactions
	Submission Time Frame	n-4	Valid values: 0000 = No submission timeframe required 0001- 9999 = Valid values for submission timeframes

Field Name	Positions	Attribute	Comments and Values
	Exclude Non-Processing Days	a-1	If the exclude non-processing days switch is "Y," GCMS will query the individual day exclusion switches to determine which days to exclude. If this switch is "N," GCMS will not query the individual day exclusion switches, and will not perform this exclusion. Valid values: Y = Exclude non-processing days. N = Do not exclude non-processing days.
Holiday Exclusion		an-1	Exclude Holiday in calculation. Valid values: Y = Exclude Holiday N = Include Holiday
Transaction Date Exclusion		an-1	Exclude Transaction Date in calculation. Valid values: Y = Exclude Transaction Date N = Include Transaction Date
Header Process Date Exclusion		an-1	Exclude Header Processing Date in calculation. Valid values: Y = Exclude Header Process Date N = Include Header Process Date
Authorization Indicator		an-1	Valid values: Y = Standard authorization code edits will be applied to transactions submitted with the interchange rate indicator specified in the record N = Standard authorization code edits will not be applied

Table IP0060T1: Timeliness Holiday

This table identifies the timeliness holiday parameters.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Business Service Arrangement Type	23	an-1	The business service arrangement type associated with the member business service arrangement.
Business Service ID Code	24-29	an-6	The business service arrangement ID code associated with the member business service arrangement.
Sunday Exclusion	30	an-1	Valid values: Y = Exclude Sunday N = Include Sunday
Monday Exclusion	31	an-1	Valid values: Y = Exclude Monday N = Include Monday
Tuesday Exclusion	32	an-1	Valid values: Y = Exclude Tuesday N = Include Tuesday
Wednesday Exclusion	33	an-1	Valid values: Y = Exclude Wednesday N = Include Wednesday
Thursday Exclusion	34	an-1	Valid values: Y = Exclude Thursday N = Include Thursday

Field Name	Positions	Attribute	Comments and Values
Friday Exclusion	35	an-1	Valid values: Y = Exclude Friday N = Include Friday
Saturday Exclusion	36	an-1	Valid values: Y = Exclude Saturday N = Include Saturday
Holiday Data (Occurs 30 times)	37-186		
	Holidays	n-5	Format is YYDDD, where YY is positions three and four of the four-position year, and DDD is the Julian date.

Table IP0064T1: Transaction Function Group Codes

This table contains the Transaction Function Group Codes for each MTI/Function Code combination. This table can be used to determine the Transaction Function group Code for a given MTI/Function Code combination. The Transaction Function Group Code is optionally used in Settlement Service Selection Criteria (refer to table IP0050T1).

Optimized Structure: Generic: All entries for the table that follows the key are combined one after the other. The Parameter Master File table contents have the same positioning as the Optimized Current Parameters File. The maximum allowable entries for each row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Message Type Identifier (MTI)	23-26	n-4	The MTI of the specified transaction function group code.
Function Code	27-29	n-3	The function code (DE 24) of the specified transaction function group code.
Transaction Function Group Code	30-31	ans-2	The transaction function group code. Valid values: FP = First Presentment SP = Second Presentment FC = First Chargeback AC = Arbitration Chargeback FE = Fee Collection NF = Non-Financial

Table IP0069T1: Global Currency

This table contains the numeric currency code and the currency code exponent for the currency designated for system balancing.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Global Currency Code: numeric	23-25	n-3	The ISO defined numeric currency code designating the Global Currency.
Global Currency Exponent	26	n-1	The currency code exponent for the Global Currency code.

Table IP0070T1: Common Area

This table defines a common area used in GCMS programs. This table contains a row for each internally used data field present in this common area.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Field Start	23-26	n-4	The start position of the specific data field.
Field Length	27-30	n-4	The length of the specific data field.

Table IP0071T1: Chip Liability Shift Country Exclusions

This table contains the business service arrangement/country combinations that are excluded from the Chip Liability Shift Program.

Optimized Structure: Generic: All entries for the table that follows the key are combined one after the other. The Parameter Master File table contents has the same positioning as the Optimized Current Parameters File. The maximum allowable entries for each row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.
Country Code—Numeric	30-32	n-3	The numeric country code established by the International Organization for Standardization (ISO).
Country Code—Alpha	33-35	an-3	The alphanumeric country code established by Mastercard.

Table IP0072T1: Expanded Member ID Master

This table provides the layout of the expanded member parameter master file, containing fields that support both GCMS and Clearing Optimizer processing.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Member ID	23-33	an-11	The member ID pertaining to the member profile described.
Filler	34	an-1	Space filled. (Mastercard use only)

Field Name	Positions	Attribute	Comments and Values
Filler	35	an-1	Space filled. (Mastercard use only)
Interchange Region	36	an-1	Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
International Electronic Interchange (IEI) Qualifier	37-38	an-2	Valid values: 00 = Not Qualified for IEI 01 = IEI Qualified
Internal Member ID Indicator	39	an-1	Valid values: Space = Not Internal Use (This is a Member ICA) B = Cannot be debited or credited C = Cannot be credited D = Cannot be debited
Acquirer Switch	40	an-1	Valid values: A = Acquirer Only I = Issuer Only Space = Both acquirer and issuer
ATM Indicator	41	an-1	Valid values: Space = ATM non-participant 1 = The MDS outside of Europe 2 = Non-MDS member outside of Europe 3 = Not currently in use 4 = The MDS in Europe 5 = Non-MDS member in Europe

Field Name	Positions	Attribute	Comments and Values
RCL Region	42	an-1	The Mastercard-defined region for restricted or negative card accounts. Valid values: 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Endpoint	43-49	n-7	This is the default endpoint at the member ID level.
World Member ID Chargeback Switch	50	an-1	Valid values: Y = Applies to World Card chargeback limits N = Does not apply to World Card chargeback limits
World Card Acceptor Business Code (MCC) Group CD1	51	an-1	Valid values: A = Passenger Transport: Airline B = Cruise Line/Steamship C = Cash Disbursement D = Payment Transaction F = Restaurant H = Lodging M = Order/Telephone Order

Field Name	Positions	Attribute	Comments and Values
			P = Beauty Salons R = Passenger Transport: Railway S = Supermarket T = Telephone U = Unique V = Automobile/Vehicle Rental W = Warehouse Club Z = ATM 1 = All others Space = not applicable to World Card
World Card Acceptor Business Code (MCC) Group CD2	52	an-1	Same as Group CD 1
World Card Acceptor Business Code (MCC) Group CD3	53	an-1	Same as Group CD 1
World Card Acceptor Business Code (MCC) Group CD4	54	an-1	Same as Group CD 1
World Card Acceptor Business Code (MCC) Group CD5	55	an-1	Same as Group CD 1
Filler	56	an-1	Space filled. (Mastercard use only)
Member Name	57-86	an-30	The customer name.
Country Code	87-89	an-3	Alphabetic country code established by Mastercard.
Country Code ISO	90-92	n-3	Numeric country code established by ISO.
Filler (reserved for internal use)	93	an-1	

Field Name	Positions	Attribute	Comments and Values
Filler (reserved for internal use)	94-99	n-6	
Filler (reserved for internal use)	100	an-1	
Filler (reserved for internal use)	101	an-1	
Filler (reserved for internal use)	102-107	n-6	
Filler (reserved for internal use)	108-113	n-6	
Outbound Format Indicator	114	an-1	Indicates the message format that the customer receives from Mastercard. Valid values: 2 = IPM Format 4 = RAW data to XML 5 = RAW data file 6 = Japan Domestic Format 8 = Credit and Installment data
Mastercard Electronic Card Indicator	115	an-1	Valid values: C = Acquirer and its merchants do not participate E = Acquirer and its merchants participate U = Unidentified acquirer
EEA Acquirer Country Service ICA	116	ans-1	EEA Acquirer Country Service ICA Valid values: Y = EEA Acquirer Country Participant N = Not an EEA Acquirer Country Participant
Filler	117	an-1	Reserved for future use.
National Payment Gateway Processor Switch	118	an-1	National Payment Gateway Processor ICA Valid values: Y = ICA is a National Payment Gateway Processor N = ICA is not a National Payment Gateway Processor

Field Name	Positions	Attribute	Comments and Values
Limited License Payment Transfer Activity Participation Indicator	119	an-1	Indicates Limited License Payment Transfer Activity Participation Valid values: Y = Limited License Payment Transfer Activity participant N = Not a Limited License Payment Transfer Activity participant
Embedded Flex Interchange Indicator	120	an-1	Indicates Embedded Flex Interchange participation. Valid values: Y = Issuer Embedded Flex Interchange Participant N = Not Issuer Embedded Flex Interchange Participant
Filler	121-212	ans-92	Reserved for future use.

Table IP0074T1: IFC Gaming

This table contains the amount limits for clearing transactions that involve In-flight Commerce (IFC) gaming amounts.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Point-of-Interaction Terminal Type	23-25	an-3	Valid value: CT4 = CAT Level 4 (In-Flight Commerce Terminal)
Acceptor Business Code (MCC)	26-29	n-4	Valid value: 7995
Processing Code (DE 3)	30-31	n-2	Valid values: 18 = Unique 20 = Credit
Amount	32-39	b-8	The amount limit for transactions with the combination of parameters shown in this table.
Currency Code: numeric	40-42	n-3	The ISO defined numeric currency code associated with the amount.
Currency Exponent	43	n-1	The currency code exponent for the currency code associated with the amount.

Table IP0075T1: Acceptor Business Codes (MCCs)

Customers use this table to identify all Acceptor Business Codes (MCCs) that Mastercard supports; both current and obsolete. GCMS rejects any transaction with a Acceptor Business Code (MCC) value that is not in this table.

Optimized Structure: Field Reformatting: The entries in this table are compressed from the Parameter Master File layout. The MCC is reformatted from five characters to four characters.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Acceptor Business Code (MCC)	23-26	n-4	Valid values are listed in the Mastercard <i>Quick Reference Booklet</i> .
Acceptor Business Code (MCC) Type	27	an-1	Valid values: A = Passenger Transport: Airline B = Cruise Line/Steamship C = Cash Disbursement D = Payment Transaction F = Restaurant H = Lodging M = Mail Order/Telephone Order

About optimized current parameter file layouts
Table IP0075T1: Acceptor Business Codes (MCCs)

Field Name	Positions	Attribute	Comments and Values
			P = Beauty Salons R = Passenger Transport: Railway S = Supermarket T = Telephone U = Unique V = Automobile/Vehicle Rental W = Warehouse Club Z = ATM 1 = All others (The Acceptor Business Codes [MCCs] on the record do not belong to a particular clearing Group Code.) 2 = Spain Domestic Local Processing 2 3 = Portugal Large Merchants 4 = Portugal Unique Ab Codes 5 = Spain Unique Ab Codes 6 = Mexico Unique Ab Codes 7 = Mastercard proprietary use 8 = Mastercard proprietary use 9 = MoneySend
Acceptor Business Code (MCC) Life Cycle Indicator	28	an-1	Valid values: A = Active L = Life cycle
Acceptor Business Program (Occurs 160 times)	29-828		The AB program associated with the MCC value.
	Acceptor Business Program	an-4	The AB program associated to the MCC value.
	Acceptor Business (AB) Program Life Cycle Indicator	an-1	Acceptor Program life cycle indicator. Valid values: A = All transactions L = Life cycle only

Field Name	Positions	Attribute	Comments and Values
Filler	829-848	an-20	Reserved for future use.

Table IP0076T1: Mastercard Assigned IDs

This table will contain the Mastercard Assigned IDs.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Mastercard Assigned ID	23-28	an-6	Mastercard Assigned ID.
Life Cycle Indicator	29	an-1	The Life Cycle indicator Valid values: A = Valid for all messages L = Valid for life cycle messages only
Filler	30	an-1	Space filled. (Mastercard use only)

Field Name	Positions	Attribute	Comments and Values
IIAS Participation Switch	31	an-1	IIAS Participation Indicator Valid values: N = The Mastercard Assigned ID is not an IIAS participant. Y = The Mastercard Assigned ID is an IIAS participant.
PVL Participation Switch	32	an-1	Private Label (PVL) Participation Indicator Valid values: N = The Mastercard Assigned ID is not a PVL participant. Y = The Mastercard Assigned ID is a PVL participant.
Filler	33-49	an-17	Space filled
Merchant MARP Full UCAF Participation Switch	50	an-1	Merchant Maestro Advanced Registration Program Full UCAF Participation Switch. Valid values: Y = Merchant does participate in MARP Full UCAF N = Merchant does not participate in MARP Full UCAF
Filler	51-57	ans-7	Central Site Use Only

Table IP0087T1: Masked Business Services and Interchange Rate Designators

This table contains the masked business service arrangements and interchange rate designators.

GCMS finds the combination of Card Program Identifier, Business Service Arrangement Type, Business Service ID, and Interchange Designator in table IP0087T1 to see if it is masked to another business service arrangement and interchange rate designator.

- If there is no entry in table IP0087T1 that matches all of these values, then the business service arrangement is not masked and GCMS performs all table finds using the actual card program identifier and business service arrangement values.
- If there is an entry in table IP0087T1 that matches all of these values, then GCMS obtains the related "Masked Card Program Identifier," "Masked Business Service Arrangement Type," "Masked Business Service ID," and "Masked Interchange Designator" and performs table

IP0095T1 and IP0096T1 finds using these masked values instead of the actual card program identifier, business service arrangement, and interchange designator values.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.

Field Name	Positions	Attributes	Comments and Values
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	33-34	an-2	The interchange rate designator.
Masked Card Program Identifier	35-37	an-3	Card program identifier which is masked to card program identifier.
Masked Business Service Arrangement Type	38	an-1	Business Service Arrangement Type masked to Business Service Arrangement Type
Masked Business Service ID	39-44	an-6	Business Service ID masked to Business Service ID
Masked IRD	45-46	an-2	Interchange rate designator masked to interchange rate designator.

Table IP0088T1: Masked Business Services

This table contains the masked business service arrangements.

GCMS finds the combination of Card Program Identifier, Business Service Arrangement Type, and Business Service ID in table IP0088T1 to see if it is masked to another business service arrangement.

- If there is no entry in table IP0088T1 that matches all of these values, then the business service arrangement is not masked and GCMS performs all table finds using the actual card program identifier and business service arrangement values.
- If there is an entry in table IP0088T1 that matches all of these values, then GCMS obtains the related "Masked Card Program Identifier," "Masked Business Service Arrangement Type," and "Masked Business Service ID" and performs table IP0098T1 and IP0097T1 finds using these masked values instead of the actual card program identifier and business service arrangement values.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.

Field Name	Positions	Attributes	Comments and Values
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.

Field Name	Positions	Attributes	Comments and Values
Masked Type	33	an-1	Type of mask. Valid value: R = Restrictions
Masked Card Program Identifier	34-36	an-3	Card Program Identifier which is masked to Card Program Identifier
Masked Business Service Arrangement Type	37	an-1	Business Service Arrangement Type masked to Business Service Arrangement Type.
Masked Business Service ID	38-43	an-6	Business Service ID masked to Business Service ID

Table IP0089T1: Business Service Switches

This table contains business service switches information.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.

Field Name	Positions	Attributes	Comments and Values
Business Service Arrangement Type	23	an-1	The business service arrangement type.
Business Service ID Code	24-29	an-6	The business service arrangement ID code.

About optimized current parameter file layouts
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service
Arrangement Participation

Field Name	Positions	Attributes	Comments and Values
Filler	30-33	ans-4	Spaces
Central Acquired Switch	34	an-1	Indicates if Central Acquiring logic should apply. Valid values: Y = Apply Central Acquiring logic. The Member-to-Member business service arrangement cannot be applied to a centrally acquired transaction. N = Do not apply Central Acquiring logic. The Customer-to-Customer business service arrangement can be applied to a centrally acquired transaction.

Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service Arrangement Participation

Customers use this table to identify all card program identifier and business service arrangements associated with an issuer account range. Each unique issuer account range/business service arrangement/card program identifier combination generates a separate record of this type.

Optimized Structure: This table uses an Account Range ID instead of the Account Range as the key into the table.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

About optimized current parameter file layouts
Table IP0090T1: Issuer Account Range Card Program Identifier and Business Service
Arrangement Participation

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Account Range ID	23-28	n-6	A unique identifier representing the Account Range.
Business Service Arrangement Type Priority	29-30	n-2	The priority of the business service arrangement type.
Business Service Arrangement Type	31	an-1	The business service arrangement type.
Business Service ID Code	32-37	an-6	The business service arrangement ID code.
Card Program Identifier Priority Code	38-39	n-2	The priority of the card program identifier in relation to its use with the account range and business service arrangement combination.
Card Program Identifier	40-42	an-3	The card program identifier associated to the issuer account range. Mastercard or other proprietary service mark.
Business Service Arrangement Life Cycle Indicator	43	an-1	The business service life cycle indicator. Valid values are: A = All transactions may be submitted for this business service arrangement. L = Life cycle: only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.

About optimized current parameter file layouts
Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

Field Name	Positions	Attribute	Comments and Values
Business Service Selection Enforcement Indicator	44	an-1	The business service arrangement enforcement indicator. Space = No business service arrangement enforcement. A = Business service arrangement enforcement for all transactions. F = Business service arrangement enforcement for first presentments only.
Filler	45-51	ans-7	Reserved for future use.

Table IP0091T1: Acquiring BIN Card Program Identifier and Business Service Arrangement Participation

Customers use this table to identify all card program identifier and business service arrangements associated with an acquiring BIN. Each unique acquiring BIN/business service arrangement/card program identifier combination generates a separate record of this type.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Acquiring BIN	23-28	n-6	The six-position acquiring BIN associated with the card program identifier and business service arrangement information.

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type Priority	29-30	n-2	The priority of the business service arrangement type.
Business Service Arrangement Type	31	an-1	The business service arrangement type.
Business Service ID Code	32-37	an-6	The business service arrangement ID code.
Card Program Identifier	38-40	an-3	The card program identifier associated with the acquirer BIN. Mastercard or other proprietary service mark.
Business Service Arrangement Life Cycle Indicator	41	an-1	The business service life cycle indicator. Valid values: A = All transactions may be submitted for this business service arrangement. L = Life cycle: Only transactions designated as "life cycle" transactions may be submitted for this business service arrangement.
Filler	42-62	ans-21	Reserved for future use.

Table IP0092T1: Transaction Functions Requiring Business Service Processing

Customers use this table to identify the transaction functions (MTI/Function code [DE 24] combinations) that require business service processing.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Message Type Identifier (MTI)	23-26	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	27-29	n-3	The priority of the business service arrangement type.
Requires Business Service Processing Switch	30	an-1	Identifies whether the transaction function (combination of MTI and Function Code) is subject to business service processing. Y = Business service processing applies to this transaction function. N = Business Service processing does not apply to this transaction function.

Table IP0093T1: Intracountry Business Service Override

This table contains issuer account ranges and related business service arrangements in which the merchant country code must equal the country code of the acquiring BIN and issuing account range in order to qualify for the country's intracountry business service arrangement.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

About optimized current parameter file layouts
Table IP0094T1: Geographic Restrictions for Card Program Identifier and Business Service Arrangement/IRD

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Account Range ID	23-28	n-6	A unique identifier representing the account range
Business Service Arrangement Type	29	an-1	The business service arrangement type
Business Service ID Code	30-35	an-6	The business service arrangement ID code

Table IP0094T1: Geographic Restrictions for Card Program Identifier and Business Service Arrangement/IRD

Customers use this table to validate selection criteria. It lists the valid country codes and regions for a card program identifier and business service arrangement combination. Each country and region associated to a business service arrangement combination will have a unique entry in this table.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

About optimized current parameter file layouts
Table IP0094T1: Geographic Restrictions for Card Program Identifier and Business Service Arrangement/IRD

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Country Data (Occurs 99 times)	33-428		The alphabetic country code of the country associated to the card program identifier, business service arrangement, and IRD.
Country Code		an-3	The alphabetic country code of the country associated to the card program identifier, business service arrangement, and IRD.
Country Life Cycle Indicator		an-1	The country life cycle indicator. Valid values are: A = All transactions L = Life cycle transactions only Space = Not applicable to country Life Cycle Indicator
Region Data (Occurs 6 times)	429-440		
	Region	an-1	The region associated to the card program identifier, business service arrangement, and IRD.

About optimized current parameter file layouts
Table IP0095T1: Acceptor Business Program Restrictions for Card Program Identifier and Business Service Arrangement, and IRD

Field Name	Positions	Attribute	Comments and Values
	Region Life Cycle Indicator	an-1	The region life cycle indicator. Valid values: A = All transactions L = Life cycle transactions only Space = Not applicable to region Life Cycle Indicator

Table IP0095T1: Acceptor Business Program Restrictions for Card Program Identifier and Business Service Arrangement, and IRD

Customers use this table to validate selection criteria. It identifies the valid Acceptor Business (AB) Programs for the combination of card program identifier, business service arrangement, and interchange rate designator.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.

About optimized current parameter file layouts
Table IP0096T1: Product Restrictions for Card Program Identifier and Business Service Arrangement, and IRD

Field Name	Positions	Attribute	Comments and Values
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	33-34	an-2	The interchange rate designator.
Acceptor Program Data (occurs 80 times)	35-434		
Acceptor Business (AB) Program		an-4	The four-position acceptor business program valid for the card program identifier, business service and IRD.
Life Cycle Indicator		an-1	The life cycle indicator for the card program identifier, business service, IRD and AB Program combination. Valid values: A = All transactions L = Life cycle transactions only

Table IP0096T1: Product Restrictions for Card Program Identifier and Business Service Arrangement, and IRD

Customers use this table to validate selection criteria. It identifies the valid GCMS Product Codes for the combination of card program identifier, business service arrangement, and interchange rate designator.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

About optimized current parameter file layouts

Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	33-34	an-2	The interchange rate designator.
GCMS Product ID	35-37	an-3	The three-position GCMS Product IDs that are valid for the card program identifier, business service and IRD.
Life Cycle Indicator	38	an-1	The life cycle indicator for the card program identifier, business service IRD and GCMS Product Code combination. Valid values: A = All transactions L = Life cycle transactions only

Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement

Customers use this table to validate selection criteria. It identifies the valid Message Reason Codes for the combination of card program identifier, business service arrangement, and transaction function/reversal indicator combination.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File. This table is accessed through table IP0970T1, which contains the data key (Card Program Identifier/Business Service/MTI/Function Code) and pointer information for message reason code details.

About optimized current parameter file layouts
Table IP0097T1: Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Message Reason Code (DE 25)	23-26	an-4	The four-digit Message Reason Code, which provides the message receiver with the reason that the message was sent.
Reversal Indicator	27	an-1	Determines whether reversals are permitted for the combination of card program identifier, business service MTI, function code and message reason code. B = Both non-reversal and reversal transactions are permitted R = Only reversal transactions are permitted. N = Only non-reversal transactions are permitted.
Chargeback Support Documentation Requirement	28	an-1	Valid values: A = Documentation is always required O = Documentation is sometimes required N = Documentation is never required
Fee Processing Impact Switch	29	an-1	Valid values: Y = Interchange fee applies N = Interchange fee does not apply
Fee Collection Maximum Amount	30-37	b-8	Only used for Fee Collection 1740 message. For any message other than Fee Collections, this is zero filled.

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attribute	Comments and Values
Fee Collection Maximum Amount Currency	38-39	b-2	A valid ISO defined numeric currency code, representing the currency defined in the Fee collection Maximum Amount.
Fee Collection Maximum Amount Currency Exponent	40	n-1	A valid ISO defined currency exponent for the corresponding currency code.

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Customers use this table to validate selection criteria. It identifies the valid Processing Code/ Reversal Indicator values for a card program identifier, business service arrangement and transaction function combination. It also indicates the transaction function/processing code combinations that require interchange rate designator validation for a given card program identifier and business service arrangement combination.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	23-25	an-3	Mastercard or other proprietary service mark. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.

About optimized current parameter file layouts

Table IP0098T1: Processing Code Restrictions for Card Program Identifier and Business Service Arrangement

Field Name	Positions	Attribute	Comments and Values
Business Service Arrangement Type	26	an-1	The business service arrangement type. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.
Business Service ID Code	27-32	an-6	The business service arrangement ID code. Field will contain "masked" values for the business service arrangement if the arrangement is in Table IP0088T1.
Message Type Identifier (MTI)	33-36	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	37-39	n-3	The three-digit Function Code that indicates the message's specific purpose.
Processing Code: Cardholder Transaction Type (DE 3, subfield 1)	40-41	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 = ATM Cash Withdrawal 09 = purchase with Cash Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Processing Code: Cardholder "From" Account (DE 3, subfield 2)	42-43	n-2	The Cardholder "From" Account. Type field contains the "masked" value for DE 3, subfield 2 as provided in Table IP2054T1. Valid values: 00 = Default
Processing Code —Cardholder "To" Account (DE 3, subfield 3)	44-45	n-2	The Cardholder "To" Account. Valid values: 00 = Default Account

Field Name	Positions	Attribute	Comments and Values
Reversal Indicator	46	an-1	Determines whether reversals are permitted for the combination of card program identifier, business service MTI, function code and processing code. B = Both non-reversal and reversal transactions are permitted R = Only reversal transactions are permitted. N = Only non-reversal transactions are permitted.
Requires IRD Validation Switch	47	an-1	Determines whether the IRD validation is required for the card program identifier, business service, transaction function and processing code combination. Valid values: Y = Requires IRD validation N = Does not require IRD validation
Extended Decimal Interchange Indicator	48	an-1	Extended Decimal Interchange Indicator Valid values: Space = Do not apply Extended Decimal precision 6 = Apply Extended Decimal precision
Exception Rate Override Switch	49	an-1	Exception Rate Override Switch identifies whether the commercial refund transaction interchange fee will be calculated based on the original purchase interchange rates and unit fees. Valid values: Y = Exception Rate Override applies N = Exception Rate Override does not apply

Table IP0099T1: Transaction Currency Qualification

For business service arrangements existing in this table, the transaction currency of the message must equal the transaction currency of the business service arrangement for the

transaction to qualify for that specific arrangement. This table applies to intra-European transactions only.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.

Field Name	Positions	Attribute	Comments and Values
Card Program Identifier	23-25	an-3	The card program identifier associated to the account range. Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	an-1	The business service arrangement type
Business Service ID Code	27-32	an-6	The business service arrangement ID code
Transaction Currency Code	33-35	n-3	The transaction currency code associated to the business service arrangement

Table IP0105T1: New Product Code Mapping

The new Product Code Mapping table maps an existing Brand Product code to a new Brand Product code associated to a Country or Region.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Region	23	n-1	The region of the associated country code. 1 = United States A = Canada B = Latin America and the Caribbean C = Asia/Pacific D = Europe E = Middle East/Africa
Country Code	24-26	an-3	The alphanumeric country code established by Mastercard.
Existing Licensed Product Code	27-29	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.
New Licensed Product Code	30-32	an-3	This is the actual product code assigned by Mastercard when licensing the combination of issuer account range and card program identifier.

Table IP0106T1: Issuer Participation Activation/Deactivation

Customers use this table to identify the active/inactive status for a new product.

Optimized Structure: This table uses an Account Range ID instead of the Account Range as the key into the table.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Account Range ID	23-28	n-6	A unique identifier representing the Account Range
Effective Date (occurs 5 times)	29-88	n-60	The date(s) when a new product is in effect.
Starting Effective Date		n-6	Starting effective date of new product.
Ending Effective Date		n-6	Ending effective date of new product.

Table IP0128T1: Tiered Debit U.S. and Territories

This table identifies the countries (U.S. and territories) that must adhere to the Durbin (Tiered Debit) regulation.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Numeric Country Code	23-25	n-3	Numeric Country Code

Table IP0132T1: Anonymous Prepaid Countries

This table contains the countries that will determine anonymous prepaid program transactions that are to be blocked.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Service Code	23-24	an-2	Service Code

Field Name	Positions	Attribute	Comments and Values
Number of Entries	25-26	n-2	Number of country code entries
Country Code (occurs from 1 to 50 times)	27-176		Country Code (occurs up to 50 times)
Country Code		an-3	Country Code

Table IP0137T1: Brazil Flex Mapping

This table consists of account range product code mapping to a debit product code.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this Optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Issuer Account Range - Low	23-41	an-19	The account number at the low end of the account range.
Issuer Account Range - High	42-60	an-19	The account number at the high end of the account range.

Field Name	Positions	Attribute	Comments and Values
Product Type ID	61	an-1	The product type of the associated account range and card program identifier. Valid values: 1 = Consumer 2 = Commercial 3 = All 4 = Other
Existing Product ID	62-64	an-3	Product ID attached with Issuer PAN range
New Product ID (Debit/Prepaid)	65-67	an-3	Flex Debit and Prepaid Product ID

Table IP0138T1: Authentication Enforcement

This table consists of categories based on unique combination values of Electronic Commerce Security Level Indicator (PDS 0052) and/or Accountholder Authentication Value (PDS 0185).

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Table 50: Table IP0138T1: Authentication Enforcement

Field name	Positions	Attribute	Comments and values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			

Field name	Positions	Attribute	Comments and values
Category	23	n-1	Category field Valid values: 1=Authenticated Frictionless 2=Authenticated but not Frictionless 3=Sent to 3DS Frictionless but not Authenticated 4=Not Sent to 3DS
Electronic Commerce SLI	24-26	ans-3	This field will contain values as described in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> for PDS 0052 (Electronic Commerce Security Level Indicator), subfield 1 (Security Protocol), subfield 2 (Cardholder Authentication), and subfield 3 (UCAF Collection Indicator). Not present is a valid value.
AAV	27-28	ans-2	This field will contain values as described in the <i>Mastercard Network Processing Dual Message Clearing System Guide</i> for PDS 0185 (Accountholder Authentication Value). Not present is a valid value.

Table IP0142T1: Business Service Selection Enforcement

This table contains the valid IRD's associated to each Card Program Identifier/Business Service Arrangement Type/Business Service ID Code, MTI, Function Code/Processing Code combination, where there is a mandatory business service arrangement.

Optimized Structure: Field reformatting: Table ID, Effective Date and Time, and Sequence Number have been reformatted to the optimized format. Each record of this table is in its own row.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the key to the entries, and will occur once for each unique combination of these fields.

Field Name	Positions	Attribute	Comments and Values
Card Program Identifier	23-25	an-3	The card program identifier value pertaining to the interchange fee group. Mastercard or other proprietary service mark.
Business Service Arrangement Type	26	n-1	The business service arrangement type.
Business Service ID Code	27-32	an-6	The business service arrangement ID code.
Message Type Identifier (MTI)	33-36	n-4	The four-digit descriptor for each IPM message class and function.
Function Code (DE 24)	37-39	n-3	The three-digit Function Code that indicates the message's specific purpose.

Field Name	Positions	Attribute	Comments and Values
Processing Code - Cardholder Transaction Type (DE 3, subfield 1)	40-41	n-2	The cardholder transaction type. Valid values: 00 = Purchase 01 = ATM Cash Withdrawal 09 = Purchase with Cash Back 12 = Cash Disbursement 18 = Unique Transaction 19 = Fee Collection (Credit to Transaction Originator) 20 = Credit (Purchase Return) 28 = Payment Transaction 29 = Fee Collection (Debit to Transaction Originator) 30 = Balance Inquiry 91 = PIN Unblock 92 = PIN Change
Interchange Rate Designator (IRD) (occurs 150 times)	42-341		The interchange rate designator.
	Interchange Rate Designator (IRD)	an-2	The interchange rate designator.

Table IP0144T1: Processing Code and Transaction Type Indicator

This table consists of interchange rate designator, the mapping processing code, and the transaction type indicator (TTI).

Table 51: Table IP0144T1: Processing Code and Transaction Type Indicator

Field name	Positions	Attribute	Comments and values
Effective date and time	01-10	n-10	Date and time that the information in this record becomes effective or was last updated Format: YYYYMMDDHH

Field name	Positions	Attribute	Comments and values
Active-Inactive Code	11	an-1	Code that controls the updating of the customer's Parameter Master File A = Add this record to Parameter Master File I = This is an inactive parameter
Table ID	12-19	an-8	Unique identifier of this IPM table Valid value: IP0144T1
Interchange Rate Designator (IRD)	20-21	an-2	The interchange rate designator
Processing code	22-23	n-2	Processing code
Transaction type identifier	24-26	an-3	The three-digit MoneySend Transaction Type ID
Filler	27-34	ans-8	Reserved for future use

Table IP0304T1: Transaction Type Identifier and AB Code

Customers use this table to identify all acceptor business codes (MCCs) and Transaction Type ID combinations that Mastercard supports; both current and obsolete.

Optimized Structure: Generic: All entries for this table after the key are combined one after the other. The Parameter Master File table contents have the same positioning as this optimized file. The maximum allowable entries per row are concatenated.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			

About optimized current parameter file layouts
Table IP0970T1: key for IP0097T1 (Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement)

Field Name	Positions	Attribute	Comments and Values
Acceptor Business Code (MCC)	23-27	n-5	Valid values are listed in the Mastercard <i>Quick Reference Booklet</i> .
Transaction Type Identifier	28-30	an-3	The three-digit MoneySend Transaction Type ID
Processing Code	31-32	n-2	The cardholder transaction type
Include/Exclude	33	an-1	Include/Exclude indicator for the Acceptor Business Codes that are valid for payment or funding MoneySend Transaction Type ID Valid values: I = Include - Acceptor Business Code (MCC) is valid for MoneySend Transaction Type ID and Processing Code. E = Exclude - Acceptor Business Code (MCC) is not valid for MoneySend Transaction Type ID and Processing Code. All other Acceptor Business Codes (MCC) not listed are considered valid.

Table IP0970T1: key for IP0097T1 (Message Reason Code Restrictions for Card Program Identifier and Business Service Arrangement)

This table contains the table IP0097T1 data key (Card Program Identifier/Business Service/MTI/Function Code) and pointer information for the interchange fee group details.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

Field Name	Positions	Attribute	Comments and Values
Entry Count	23-26	b-4	Total number of records.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	27-29	an-3	The card program identifier value pertaining to the interchange fee group. Mastercard or other proprietary service mark.
Business Service Arrangement Type	30	n-1	The business service arrangement type.
Business Service ID Code	31-36	an-6	The business service arrangement ID code.
Message Type Identifier (MTI)	37-38	an-2	The four-digit descriptor for each IPM message class and function.
Function Code (DE24)	39-40	b-2	The three-digit Function Code that indicates the message's specific purpose.
Relative record number	41-42	b-2	Relative record number of table IP0097T1 record on which customer business service arrangements is located.
ICA entry start	43-46	b-4	Starting location of customer business service arrangements on the table IP0097T1 relative record.
ICA entry length	47-48	b-2	Length of member business service arrangements on the table IP0097T1 relative record.

Tables IP1100T1 and IP1100T2: mandatory field edits

These tables contain the mandatory field edits (both data element and private data subelement) and fields not allowed by MTI and Function Code (DE 24) combination, for the originator of the message.

Optimized Structure: For each Card Program Identifier, Business Service, MTI, and Function Code, the number of entries will represent the number of elements that will occur for each

unique subset. Table IP1100T2 is being added for the purpose of improving efficiency in the way the data is handled.

Table 52: Table IP1100T1

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of table data represents the key to the entries, and will occur once for each unique combination of these fields.

Field Name	Positions	Attribute	Comments and Values
MTI	23-24	b-2	The four-digit descriptor of each IPM message class and function.
Function Code (DE 24)	25-26	b-2	The three-digit function code that indicates the message's specific purpose.
Card Program Identifier	27-29	an-3	The card program identifier applicable to the data element or private data subelement.
Business Service Data Arrangement Type and ID Code			The business service arrangement type and ID code.
Business Service Arrangement Type	30	an-1	The business service arrangement type.
Business Service ID Code	31-36	an-6	The business service arrangement ID code.
Table IP1100T2 Start Position	37-40	b-4	This will point to the IP1100T2 table where the field list starts.
Number of Entries	41-42	n-2	The number of entries for each combination of card program identifier, business service, MTI, and function code.

Table 53: Table IP1100T

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.

The following segment of data will occur for each data element or PDS that is required for the message type as defined in the unique key above.

Field Name	Positions	Attribute	Comments and Values
Field Type	23	n-1	Valid values: 2 = Data Element 3 = Private Data Subelement (PDS)
Field Number	24-25	b-2	The field number (data element or PDS) of the applicable field.
Subfield Number	26-27	b-2	If applicable, the subfield number for the corresponding field number.
Mandatory/Not Allowed Indicator	28	an-1	Valid values: M = Mandatory Not allowed

Table IP2000T1 and IP2000T2: valid values/ranges

GCMS and the Clearing Optimizer and Utilities software use these lists to check the validity of the values contained in the data elements and PDSs.

Optimized Structure: The IP2nnnT1 tables that do not vary by card program identifier-business service are optimized into table IP2000T1. The IP2nnnT1 or IP3nnnT1 tables that do vary by card program identifier-business service are optimized into table IP2000T2.

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	KSDS VSAM Key

Field Name	Positions	Attribute	Comments and Values
Effective Date and Time	9-18	n-10	KSDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Table ID	23-30	an-8	KSDS VSAM Key
Effective Date and Time	31-40	n-10	KSDS VSAM Key
Card Program Identifier	41-43	an-3	The card program identifier applicable to data element or private data subelement. Default value of spaces is used in IP2000T1.
Business Service Arrangement Type	44	an-1	The business service arrangement type. Default value of zero is used in IP2000T1.
Business Service ID Code	45-50	an-6	The business service arrangement ID code. Default value of zero is used in IP2000T1
Item Count	51-52	b-2	Number of value list/range values.
Item Length	53-54	b-2	Length of value list/range value.
Item Type	55	an-1	Identifies the type of data. L = Value List R = Value Range
Items	56-480	ans-425	Value list/range items
Pointer to IP2000T2	481-482	b-2	Points to the same table on IP2000T2 with entries that vary by card program identifier-business service.

The following sub-tables comprise Table IP2nnnT1:

Table ID	Value Description
IP2001T1	PDS 0146 Transaction Fee Amounts, subfield 3 Fee Settlement Indicator
IP2002T1	Time Parameter Table
IP2003T1	DE 22 Point of Service Data Code, subfield 11 Terminal Data Output Capability
IP2004T1	DE 22 Point of Service Data Code, subfield 4 Terminal Operating Environment
IP2005T1	DE 22 Point of Service Data Code, subfield 7 Card Data Input Mode
IP2006T1	DE 22 Point of Service Data Code, subfield 1 Terminal Data-Card Data Input Capability
IP2007T1	DE 22 Point of Service Data Code, subfield 10 Card Data Output Capability
IP2008T1	DE 22 Point of Service Data Code, subfield 12 PIN Capture Capability
IP2009T1	DE 22 Point of Service Data Code, subfield 9 Cardholder Authentication Entity
IP2010T1	DE 22 Point of Service Data Code, subfield 5 Cardholder Present Data
IP2011T1	DE 22 Point of Service Data Code, subfield 2 Terminal Data-Cardholder Authentication Capability
IP2012T1	DE 22 Point of Service Data Code, subfield 6 Card Present Data
IP2013T1	DE 22 Point of Service Data Code, subfield 8 Cardholder Authentication Method
IP2014T1	DE 22 Point of Service Data Code, subfield 3 Terminal Data-Card Capture Capability
IP2015T1	PDS 0682 Detail Tax Amount 1, subfield 6 Detail Tax Type Identifier 1 PDS 0683 Detail Tax Amount 2, subfield 6 Detail Tax Type Identifier 2 PDS 0684 Detail Tax Amount 3, subfield 6 Detail Tax Type Identifier 3 PDS 0751 Detail Tax Amount 4, subfield 6 Detail Tax Type Identifier 4 PDS 0752 Detail Tax Amount 5, subfield 6 Detail Tax Type Identifier 5 PDS 0753 Detail Tax Amount 6, subfield 6 Detail Tax Type Identifier 6
IP2016T1	PDS 0230 Fulfillment Document Code
IP2017T1	PDS 0262 Documentation Indicator
IP2018T1	PDS 0558 Miles/Kilometers Indicator
IP2020T1	PDS 0654 Debit or Credit Indicator
IP2021T1	PDS 0598 Tax Collected Indicator

Table ID	Value Description
IP2022T1	PDS 0122 Processing Mode
IP2023T1	PDS 0622 Motor Fuel Service Type
IP2024T1	PDS 0553 Rental Rate, subfield 1 Rental Rate Indicator
IP2025T1	PDS 0747 Shipping Party Descriptor, subfield 1 Shipping Party Descriptor
IP2026T1	DE 4 Transaction Amounts for U.S. Region Large Ticket Interchange
IP2027T1	PDS 0559 Vehicle Insurance, subfield 1 Vehicle Insurance Indicator
IP2028T1	PDS 0561 Adjusted Amount, subfield 1 Adjusted Amount Indicator
IP2029T1	PDS 0578 Billing Adjustment, subfield 1 Billing Adjustment Indicator
IP2030T1	PDS 0648 Item Discount, subfield 1 Item Discount Indicator
IP2031T1	PDS 0165 Settlement Indicator, subfield 1 Settlement Indicator
IP2032T1	PDS 0754 Delivery Party Descriptor, subfield 1 Delivery Party Descriptor
IP2033T1	PDS 0682 Detail Tax Amount 1, subfield 1 Detail Tax Amount Indicator 1 PDS 0683 Detail Tax Amount 2, subfield 1 Detail Tax Amount Indicator 2 PDS 0684 Detail Tax Amount 3, subfield 1 Detail Tax Amount Indicator 3 PDS 0751 Detail Tax Amount 4, subfield 1 Detail Tax Amount Indicator 4 PDS 0752 Detail Tax Amount 5, subfield 1 Detail Tax Amount Indicator 5 PDS 0753 Detail Tax Amount 6, subfield 1 Detail Tax Amount Indicator 6
IP2034T1	PDS 0641 Product Code
IP2035T1	PDS 0617 Medical Services Price Adjustment
IP2036T1	PDS 0618 Medical Services Product Number Qualifier
IP2037T1	PDS 0023 Terminal Type
IP2038T1	PDS 0590 Party Identification
IP2039T1	PDS 0594 Party Contact, subfield 1 Party Contact Descriptor
IP2040T1	PDS 0601 Party Nature of Filing
IP2041T1	PDS 0686 Tax Exempt Indicator
IP2042T1	PDS 0690 No Show Indicator
IP2043T1	PDS 0713 Restricted Ticket Indicator
IP2044T1	PDS 0711 Fire Safety Act Indicator
IP2045T1	PDS 0685 Type of Supply
IP2046T1	PDS 0105 File ID, subfield 1 File Type
IP2047T1	PDS 0110 Transmission ID, subfield 1 Transmission Type

Table ID	Value Description
IP2048T1	DE 3 Processing Code, subfield 1 Cardholder Transaction Type
IP2049T1	PDS 0026 File Reversal Indicator, subfield 1 File Reversal Indicator
IP2050T1	PDS 0191 Originating Message Format
IP2052T1	PDS 0501 Transaction Description, subfield 1 Usage Code
IP2053T1	PDS 0146 Transaction Fee Amounts, subfield 2 Fee Processing Code
IP2054T1	DE 3 Processing Code, subfield 2 Cardholder From Account Type and Masked Value
IP2055T1	DE 3 Processing Code, subfield 3 Cardholder To Account Type Code
IP2056T1	PDS 0732, subfield 3 Debit/Credit Indicator
IP2057T1	PDS 0519 Additional Fuel Location Information, Subfields 1-14
IP2058T1	DE 63 Transaction Life Cycle ID, subfield 1 Life Cycle Support Indicator
IP2059T1	PDS 0025 Message Reversal Indicator, subfield 1 Message Reversal Indicator
IP2060T1	PDS 0171 Alternate Merchant Description, subfield 1 Character Set Indicator
IP2061T1	PDS 0189 Point of Interaction Phone Data, subfield 1 Format Indicator
IP2062T1	PDS 0228 Retrieval Document Code
IP2063T1	PDS 0264 Original Reason for Retrieval Request
IP2064T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability (for specific interchange programs)
IP2065T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability (for specific interchange programs)
IP2068T1	DE 40 Extended Service Code
IP2069T1	DE 40 Extended Service Code
IP2070T1	PDS 0638 Call To Information, subfield 5 Call To Type
IP2071T1	PDS 0640 Call Time Period
IP2072T1	PDS 0597, subfield 2 Exponent
IP2073T1	DE 22 Point of Service Data Code, subfield 4 Terminal Operating Environment (for specific interchange programs)
IP2074T1	DE 22 Point of Service Data Code, subfield 7 Card Data Input Mode (for specific interchange programs)
IP2075T1	DE 22 Point of Service Data Code, subfield 5 Cardholder Present Data (for specific interchange programs)

Table ID	Value Description
IP2076T1	DE 22 Point of Service Data Code, subfield 6 Card Present Data (for specific interchange programs)
IP2077T1	PDS 0632 Product Type Code
IP2079T1	PDS 0595 Acceptor Type, subfield 5 Business type Provided Code PDS 0595 Acceptor Type, subfield 6 Business Owner Type Provided Code PDS 0595 Acceptor Type, subfield 7 Business Certification Type Provided Code PDS 0595 Acceptor Type, subfield 8 Business Racial/Ethnic Type Provided Code PDS 0596 Acceptor Tax ID, subfield 2 Acceptor Tax ID Provided Code
IP2080T1	PDS 0623 Motor Fuel Information, subfield 3 Motor Fuel Unit of Measure
IP2081T1	PDS 0623 Motor Fuel Information, subfield 1 Motor Fuel Product Code
IP2082T1	PDS 0146 Transaction Fee Amounts, subfield 1 Fee Type Code
IP2084T1	PDS 0623 Motor Fuel Information, subfield 5 Motor Fuel Quantity Exponent
IP2085T1	PDS 0648 Item Discount, subfield 4 Item Discount Rate Exponent
IP2086T1	PDS 0596 Acceptor Tax ID, subfield 1 Acceptor Tax ID
IP2087T1	PDS 0260 Edit Exclusion Indicator, subfield 1 Exclusion Request Code

Table ID	Value Description
IP2088T1	PDS 0643 Item Quantity, subfield 2 Item Quantity Exponent PDS 0646 Unit Price, subfield 2 Unit Price Exponent PDS 0751 Detail Tax Amount 4, subfield 4 Detail Tax Rate Exponent 4 PDS 0752 Detail Tax Amount 5, subfield 4 Detail Tax Amount Exponent 5 PDS 0753 Detail Tax Amount 6, subfield 4 Detail Tax Amount Exponent 6 PDS 0723 Regular Hours Worked, subfield 2 Regular Hours Worked Exponent PDS 0724 Regular Hours Rate, subfield 2 Regular Hours Rate Exponent PDS 0725 Overtime Hours Worked, subfield 2 Overtime Hours Worked Exponent PDS 0726 Overtime Hours Rate, subfield 2 Overtime Hours Rate Exponent PDS 0505 Travel Agency Fee, subfield 2 Travel Agency Fee Amount Exponent PDS 0653 Service Amount, subfield 2 Service Amount Exponent PDS 0656 Full VAT Amounts, subfield 2 Full VAT Gross Amount Exponent PDS 0656 Full VAT Amounts, subfield 5 Full VAT Tax Amount Exponent PDS 0657 Half VAT Amounts, subfield 2 Half VAT Gross Amount Exponent PDS 0657 Half VAT Amounts, subfield 5 Half VAT Tax Amount Exponent PDS 0682 Detail Tax Amount 1, subfield 4 Detail Tax Rate Exponent 1 PDS 0683 Detail Tax Amount 2, subfield 4 Detail Tax Rate Exponent 2 PDS 0684 Detail Tax Amount 3, subfield 4 Detail Tax Rate Exponent 3 PDS 0712 Net Fuel Price, subfield 2 Net Fuel Price Exponent
IP2090T1	DE 23 Card Sequence Number
IP2093T1	DE 54 Amounts, Additional, subfield 4 Additional Amount, Amount Sign (for U.K. Domestic Maestro use only)
IP2094T1	PDS 0165 Settlement Indicator, subfield 1 Settlement Indicator (for U. K. Domestic Maestro use only)
IP2099T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF Collector Indicator
IP2100T1	DE 43 Acceptor Name/Location, subfield 5 Acceptor State/Province Code
IP2104T1	DE 43 Acceptor Name/Location, subfield 4 Acceptor Postal (Zip) Code
IP2105T1	PDS 0502 Custom Identifier, subfield 1 Custom Identifier Type

Table ID	Value Description
IP2106T1	PDS 660 Customer Reference, subfield 1 Customer Reference ID
IP2108T1	PDS 0762 Data Source
IP2113T1	PDS 0620 Oil Company Brand Name
IP2115T1	PDS 0057 Transaction Category Indicator
IP2116T1	CEM Response Codes
IP2118T1	DE 22 Point of Service Data Code, subfield 7 Card Data: Input Mode
IP2119T1	PDS 0595 Acceptor Type, subfield 1 Business Type
IP2126T1	Life Cycle Transactions
IP2128T1	PDS 0195 Installment Data, subfield 2 Payment Option Code
IP2129T1	PDS 0195 Installment Data, subfield 3 Installment Number
IP2130T1	PDS 0195 Installment Data, subfield 4 Bonus Code
IP2131T1	PDS 0195 Installment Data, subfield 6 Number Bonus Payments Per Year
IP2133T1	PDS 0179 Long Running Transaction Indicator
IP2134T1	Payment Methods
IP2135T1	Alternate Custom Identifier Types
IP2144T1	PDS 0194 Remote Payments Program Data
IP2146T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF
IP2147T1	PDS 0181 Installment Data, subfield 1 Type of Installment
IP2148T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2149T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2150T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2151T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2152T1	PDS 0181 Installment Data, subfield 2 Number of Installments
IP2153T1	DE 40 Service Code Valid Ranges
IP2154T1	Acceptor Business Code Exclusions
IP2155T1	DE 22 Point of Service Data Code, subfield 1 Card Data Input Capability for Contactless Enabled
IP2158T1	PDS0042 Merchant Capability Valid Values
IP2167T1	PDS 0052 Electronic Commerce Security Level Indicator, subfield 3 UCAF
IP2170T1	Single Message System Endpoints
IP2171T1	Logic Control Using ID and Date

Table ID	Value Description
IP2172T1	DE022 Point of Service Data Code, subfield 4 Point of Sale Terminal Operating Environment
IP2190T1	PDS 0052 Electronic Commerce Security Level Indicator
IP2196T1	PDS0715 Ancillary Service Charges, subfield 1 Ancillary Fee Code
IP2201T1	PDS 0021 MCHIP QR
IP2203T1	DE22 Cardless ATM, subfield 7
IP2211T1	DE 43 Acceptor Name/Location, subfield 4 Acceptor Postal (ZIP) Code
IP2219T1	PDS 0176 MAID and IRD
IP2222T1	PDS 0052 (Electronic Commerce Security Level Indicator) and PDS 0185 (Accountholder Authentication Value) Combinations
IP2225T1	MDS Processing code and Overlayed IRD
IP2226T1	IntraRegional Participant Regions for MDS IRD Overlay logic
IP2230T1	CIT/MIT Category Indicator
IP2233T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2234T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2235T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2236T1	PDS 1001 MEMBER-TO-MEMBER PROPRIETARY DATA
IP2239T1	PDS0790 Fleet Addendum Prompt Codes PDS0791 Fleet Addendum Prompt Codes PDS0792 Fleet Addendum Prompt Codes PDS0793 Fleet Addendum Prompt Codes PDS0794 Fleet Addendum Prompt Codes
IP2240T1	PDS0782s1 Fleet Fuel Products
IP2241T1	PDS0783 Fleet Addendum Non-Fuel Product Codes
IP2244T1	PDS 0052 (Electronic Commerce Security Level Indicator) and PDS 0185 (Accountholder Authentication Value) Combinations
IP2245T1	Country Specific Micro-Merchant Algorithms, Sequence 01 through 07
IP2246T1	Country Specific Micro-Merchant Algorithms, Sequence 08 through 14
IP2247T1	Country Specific Micro-Merchant Algorithms, Sequence 15 through 21
IP2248T1	Country Specific Micro-Merchant Algorithm, Alpha to Numeric Result
IP3001T1	Payment Transaction Type Codes
IP3002T1	Transaction Type Identifier and Registration type Codes

Table ID	Value Description
IP3004T1	Transaction Type Identifier and MCC Code Combination

Table IP4090T1: Account Range ID

This table contains issuing account ranges and pointer information to the tables that have account ranges on the RRDS optimized file.

The following is an example of how to obtain the Issuer Account Range: High and the Issuer Account Range: Low from the new optimized table IP4090T1, and its ICA from the changed optimized table IP0040T1. This example is not intended to represent a module that is supported by Mastercard. It is intended to identify COBOL code that can be incorporated into another application. The COBOL copybooks and called sub-modules are available as part of the Clearing Optimizer Mainframe version software code distribution.

Optimized Structure: Dynamically Created Tables: These tables are built as part of the optimized process for internal use by the Clearing Optimizer software. The tables built for internal use are IP0005T1 and IP0010T1.

```
WORKING-STORAGE SECTION. WORKING-STORAGE SECTION.

*TABLE 10 COPY BOOK.

01 IP00104-TABLE-ENTRY EXTERNAL.

COPY IP001004 REPLACING ==:T:== BY ==IP00104==.

*TABLE TO STORE ALL ACCOUNT RANGE RECORDS. ON ONE RRDS RECORD
*BASED ON IP409004 COPYBOOK LENGTH WE CAN FIT MAX 500 TABLE 4090
*ENTRIES.

01 IP4090T1-TABLE.
03 IP4090T1-TABLE-ENTRY OCCURS 500 TIMES
INDEXED BY IP4090T1-IDX.
COPY IP409004 REPLACING ==:T:== BY ==IP4090T1==.

*RECORD STRUCTURE FOR ONE-DAY-FILE/REFRESH FILE RECORD:

COPY IP500005 REPLACING ==:T:== BY ==IP50005==.

*COPYBOOK FOR TABLE 40- ACCOUNT RANGE TABLE.

01 IP00404-TABLE EXTERNAL.
05 IP00404-ENTRIES-FOUND-COUNT PIC S9(08) COMP.
05 IP00404-AR-RANGE-GRP.
10 IP00404-TBL-40-AR-H PIC X(19).
10 IP00404-TBL-40-AR-L PIC X(19).
05 IP00404-ENTRY OCCURS 99 TIMES
INDEXED BY IP00404-ACCT-RNG-INDEX.
COPY IP004004 REPLACING ==:T:== BY ==IP00404==.

*GENERAL PURPOSE VARIABLES:

01.
05 800-ENTRY-LENGTH PIC 9(08) COMP VALUE 0.
```

```
05 800-BLOCK-ENTRY-COUNT PIC 9(08) COMP VALUE 0.
05 800-BLOCK-ENTRY-COUNT-X REDEFINES
    800-BLOCK-ENTRY-COUNT PIC X(04).
05 800-BLOCK-ENTRY-LENGTH PIC 9(08) COMP VALUE 0.
05 800-TOTAL-4090-RECS PIC 9(04).
05 800-4090-RRN-START PIC 9(08) COMP.

PROCEDURE DIVISION.
* IN THIS SAMPLE CODE 2004040214 IS THE PROCESS DATE AND TIME
* PROCESS DATE OR RUN CONTROL DATE MUST BE USED HERE.

    MOVE '2004040214' TO IP50005-CLEARING-DT-TM

    MOVE LENGTH OF IP4090T1-TABLE-ENTRY(1)
      TO 800-ENTRY-LENGTH
    MOVE IP50005-CLEARING-DT-TM TO IP00104-TOC-EFF-DATE
    MOVE 'IP4090T1' TO IP00104-TOC-TABLE-ID
    CALL 'IP283010'
    *
    * IP283010 is a sub-module to determine the relative start
    * location of Table 4090 in the VSAM One-day RRDS file.
    *

    MOVE IP00104-TOC-REL-REC-NUM TO 800-4090-RRN-START
    MOVE IP00104-TOC-RECORD-COUNT TO 800-TOTAL-4090-RECS
    PERFORM 1000-GET-REC-FROM-RRDS-FILE
      800-TOTAL-4090-RECS TIMES.
    STOP RUN.

*1000-GET-REC-FROM-RRDS-FILE.
    MOVE 800-4090-RRN-START TO IP50005-SEQ
    CALL 'IP660010'

    * IP660010 is a sub-module that reads the VSAM One-day RRDS
    * physical record

    ADD 1 TO 800-4090-RRN-START
    MOVE IP50005-TABLE-DATA(1:4) TO 800-BLOCK-ENTRY-COUNT-X

    * IP50005-TABLE-DATA (1:4) contains the number of table 4090
    * entries in the RRDS physical record

    MULTIPLY 800-BLOCK-ENTRY-COUNT BY 800-ENTRY-LENGTH
    GIVING 800-BLOCK-ENTRY-LENGTH
    MOVE IP50005-TABLE-DATA(5:800-BLOCK-ENTRY-LENGTH)
      TO IP4090T1-TABLE(1:800-BLOCK-ENTRY-LENGTH)
    SET IP4090T1-IDX TO 1
    PERFORM 1100-DISPLAY-ICABIN 800-BLOCK-ENTRY-COUNT TIMES.

* 1100-DISPLAY-ICABIN.

    MOVE IP4090T1-ACCOUNT-RANGE-L(IP4090T1-IDX)
      TO IP00404-TBL-40-AR-H
    CALL 'IP280010'

    * IP280010 is the Table 40 sub-module

    SET IP4090T1-IDX UP BY 1

    IF IP00404-ENTRIES-FOUND-COUNT IS GREATER THAN ZERO
      DISPLAY 'ACCOUNT RANGE = '
        IP4090T1-ACCOUNT-RANGE-L(IP4090T1-IDX) ' - '
        IP4090T1-ACCOUNT-RANGE-H(IP4090T1-IDX) ' ICA= '
```

IP00404 - PRFX - ICA(1)
END - IF

This table is not in the Parameter Master File, it is built during the optimization process.

Table 54: Table IP4090T1: Account Range ID

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
Number of Ranges	23-26	b-4	Total number of account ranges on this relative record.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Account Range ID	27-32	n-6	A unique identifier representing the Account Range.
Issuer Account Range - Low	33-51	an-19	The account number at the low end of the issuing account range.
Issuer Account Range - High	52-70	an-19	The account number at the high end of the issuing account range.
Table IP0040T1 relative record number.	71-74	b-4	Relative record number of table IP0040T1 record on which account range information is located.
Table IP0040T1 data start	75-78	b-4	Starting location of the account range information on table IP0040T1 relative record number.
Table IP0040T1 data length	79-82	b-4	Length of the acceptance account range information on table IP0040T1 relative record number.

Field Name	Positions	Attribute	Comments and Values
Table IP0090T1 relative record number.	83-86	b-4	Relative record number of table IP0090T1 record on which card program identifier/ acceptance brand-business service arrangement information is located.
Table IP0090T1 data start	87-90	b-4	Starting location of the card program identifier/acceptance brand-business service arrangement information on table IP0090T1 relative record number.
Table IP0090T1 data length	91-94	b-4	Length of the card program identifier/ acceptance brand-business service arrangement information on table IP0090T1 relative record number.
Table IP0049T1 relative record number.	95-98	b-4	Relative record number of table IP0049T1 record on which information is located.
Table IP0049T1 data start	99-102	b-4	Starting location of the information on table IP0049T1 relative record number.
Table IP0049T1 data length	103-106	b-4	Length of the information on table IP0049T1 relative record number.
Table IP0051T1 relative record number.	107-110	b-4	Relative record number of table IP0051T1 record on which information is located.
Table IP0051T1 data start	111-114	b-4	Starting location of the information on table IP0051T1 relative record number.
Table IP0051T1 data length	115-118	b-4	Length of the information on table IP0051T1 relative record number.
Internal use	119-126	b-8	Internal use.
Table IP0093T1 relative record number	127-130	b-4	Relative record number of table IP0093T1 record on which information is located
Table IP0093T1 data start	131-134	b-4	Starting location of the information on table IP0093T1 relative record number
Table IP0093T1 data length	135-138	b-4	Length of the information on table IP0093T1 relative record number
Internal use	139-146	b-8	Internal use.
Internal use	147-154	b-8	Internal use.
Internal use	155-162	b-8	Internal use.

Table IP4191T1: BIN Pointer

This table contains acquirer BINs and pointer information to the tables that have BINs on the RRDS optimized file.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Dynamically Created Tables: These tables are built as part of the optimized process for internal use by the Clearing Optimizer software. The tables built for internal use are IP0005T1 and IP0010T1.

Table 55: Table IP4191T1: BIN Pointer

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
Number of BINs	23-26	b-4	Total number of BINs on this relative record.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
BIN	27-32	n-6	The six-digit acquiring BIN.
Table IP0041T1 relative record number.	33-36	b-4	Relative record number of table IP0041T1 record on which BIN information is located.
Table IP0041T1 data start	37-40	b-4	Starting location of the BIN information on table IP0041T1 relative record number.
Table IP0041T1 data length	41-44	b-4	Length of the acceptance BIN information on table IP0041T1 relative record number.
Table IP0091T1 relative record number.	45-48	b-4	Relative record number of table IP0091T1 record on which card program identifier - business service arrangement information is located.

Field Name	Positions	Attribute	Comments and Values
Table IP0091T1 data start	49-52	b-4	Starting location of the card program identifier-business service arrangement information on table IP0091T1 relative record number.
Table IP0091T1 data length	53-56	b-4	Length of the card program identifier-business service arrangement information on table IP0091T1 relative record number.
Table IP0043T1 relative record number.	57-60	b-4	Relative record number of table IP0043T1 record on which information is located.
Table IP0043T1 data start	61-64	b-4	Starting location of the information on table IP0043T1 relative record number.
Table IP0043T1 data length	65-68	b-4	Length of information on table IP0043T1 relative record number.

Table IP5200T1: key for IP0052T1 (Interchange Fee Group)

This table contains the table IP0052T1 data key (Card Program Identifier/Business Service/IRD) and pointer information for the interchange fee group details.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 56: Table IP5200T1: key for IP0052T1 (Interchange Fee Group)

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
Entry Count	23-26	b-4	Total number of records.

Field Name	Positions	Attribute	Comments and Values
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Card Program Identifier	27-29	an-3	The card program identifier value pertaining to the interchange fee group. Mastercard or other proprietary service mark.
Business Service Arrangement Type	30	n-1	The business service arrangement type.
Business Service ID Code	31-36	an-6	The business service arrangement ID code.
Interchange Rate Designator (IRD)	37-38	an-2	The interchange rate designator.
Relative record number	39-42	b-4	Relative record number of table IP0052T1 record on which member business service arrangements is located.
ICA entry start	43-46	b-4	Starting location of member business service arrangements on the table IP0052T1 relative record.
ICA entry length	47-50	b-4	Length of member business service arrangements on the table IP0052T1 relative record.

Table IP5300T1: key for IP0053T1 (Interchange Fee Type)

This table contains the table IP0053T1 data key (Fee Code Pointer) and pointer information for the interchange fee type.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 57: Table IP5300T1: key for IP0053T1 (Interchange Fee Type)

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
Entry Count	23-26	b-4	Total number of records.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Fee Code Pointer	27-32	ps-6	The value associated with Table IP0053T1
Relative record number start	33-36	b-4	Relative record number of Table IP0053T1 record from which the interchange fee type starts.
Relative record number end	37-40	b-4	Relative record number of Table IP0053T1 record from which the interchange fee type ends.
Override fee group entry start	41-44	b-4	Starting location of interchange fee type data within relative record.
Override fee group entry end	45-48	b-4	Ending location of interchange fee type data within relative record.

Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements)

This table contains the table IP0056T1 data key (Member ID) and pointer information for the member business service arrangements.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Generic: All entries for the table that follows the key are combined one after the other. The Parameter Master File table contents has the same positioning as the Optimized Current Parameters File. The maximum allowable entries for each row are concatenated.

Table 58: Table IP5600T1: key for IP0056T1 (Member Business Service Arrangements)

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Member ID	23-28	b-6	The customer ID
Relative record number	29-32	b-4	Relative record number of table IP0056T1 record on which member business service arrangements is located.
ICA entry start	33-36	b-4	Starting location of member business service arrangements on the table IP0056T1 relative record.
ICA entry length	37-40	b-4	Length of member business service arrangements on the table IP0056T1 relative record.

Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group)

This table contains the table IP0057T1 data key (Product Class: Acceptor Pointer Override) and pointer information for the override fee group.

This table is not in the Parameter Master File, it is built during the optimization process.

Optimized Structure: Field reformatting: The entries in this table are compressed from the layout in the Parameter Master File.

Table 59: Table IP5700T1: key for IP0057T1 (Interchange Override Fee Group)

Field Name	Positions	Attribute	Comments and Values
Table ID	1-8	an-8	RRDS VSAM Key
Effective Date and Time	9-18	n-10	RRDS VSAM Key
Sequence Number	19-22	b-4	The number that indicates the order of a multi-record table entry.
Entry Count	23-26	b-4	Total number of records.
The following segment of table data represents the first occurrence of this data. Subsequent occurrences repeat using the same attributes.			
Product Class - Acceptor Pointer Override	27-32	b-6	The value associated with table IP0052T1.
Relative record number start	33-36	b-4	Relative record number of table IP0057T1 record from which the override fee group starts.
Relative record number end	37-40	b-4	Relative record number of table IP0057T1 record at which the override fee group ends.
Override fee group entry start	41-44	b-4	Starting location of override fee group data within relative record.
Override fee group entry end	45-48	b-4	Ending location of override fee group data within relative record.

Notices

Following are policies pertaining to proprietary rights, trademarks, translations, and details about the availability of additional information online.

Proprietary Rights

The information contained in this document is proprietary and confidential to Mastercard International Incorporated, one or more of its affiliated entities (collectively "Mastercard"), or both.

This material may not be duplicated, published, or disclosed, in whole or in part, without the prior written permission of Mastercard.

Trademarks

Trademark notices and symbols used in this document reflect the registration status of Mastercard trademarks in the United States. Consult with the Global Customer Service team or the Mastercard Law Department for the registration status of particular product, program, or service names outside the United States.

All third-party product and service names are trademarks or registered trademarks of their respective owners.

EMV® is a registered trademark of EMVCo LLC in the United States and other countries. For more information, see <http://www.emvco.com>.

Disclaimer

Mastercard makes no representations or warranties of any kind, express or implied, with respect to the contents of this document. Without limitation, Mastercard specifically disclaims all representations and warranties with respect to this document and any intellectual property rights subsisting therein or any part thereof, including but not limited to any and all implied warranties of title, non-infringement, or suitability for any purpose (whether or not Mastercard has been advised, has reason to know, or is otherwise in fact aware of any information) or achievement of any particular result.

Translation

A translation of any Mastercard manual, bulletin, release, or other Mastercard document into a language other than English is intended solely as a convenience to Mastercard customers. Mastercard provides any translated document to its customers "AS IS" and makes no representations or warranties of any kind with respect to the translated document, including, but not limited to, its accuracy or reliability. In no event shall Mastercard be liable for any damages resulting from reliance on any translated document. The English version of any Mastercard document will take precedence over any translated version in any legal proceeding.

Information Available Online

Mastercard provides details about the standards used for this document, including times expressed, language use, and contact information, on the Technical Resource Center (TRC).