

Programming
Simplified [Home](#) » [C programming](#) » [C programming examples](#) » C program to read a file

C program to read a file



C program to read a file: This program reads a file entered by the user and displays its contents on the screen, fopen function is used to open a file it returns a pointer to structure FILE. FILE is a predefined structure in stdio.h . If the file is successfully opened then fopen returns a pointer to file and if it is unable to open a file then it returns NULL. fgetc function returns a character which is read from the file and fclose function closes the file. Opening a file means we bring file from disk to ram to perform operations on it. The file must be present in the directory in which the executable file of this code is present.

C program to open a file

C programming code to open a file and to print its contents on screen.

```
#include <stdio.h>
#include <stdlib.h>

int main()
{
    char ch, file_name[25];
    FILE *fp;

    printf("Enter the name of file you wish to see\n");
    gets(file_name);

    fp = fopen(file_name, "r"); // read mode

    if( fp == NULL )
    {
        perror("Error while opening the file.\n");
        exit(EXIT_FAILURE);
    }


    printf("The contents of %s file are :\n", file_name);

    while( ( ch = fgetc(fp) ) != EOF )
        printf("%c", ch);

    fclose(fp);
    return 0;
}
```

Download [Read file](#) program.

Output of program:



```
E:\programmingsimplified.com\c\read-file.exe
Enter the name of file you wish to see
computer-programming.txt
The contents of computer-programming.txt file are :
Computer programming is fun.

Process returned 0 (0x0) execution time : 8.697 s
Press any key to continue.
```

There are blank lines present at end of file. In our program we have opened only one file but you can open multiple files in a single program and in different modes as desired. File handling is very important when we wish to store data permanently on a storage device. All variables and data of program is lost when program exits so if that data is required later we need to use files.

