

Logic Programming – Laboratory 1

Prolog - Introduction

Isabela Drămnesc

1 Useful Links

- [Course material](#).
- [The laboratories](#).
- [The student guide](#).
- Use: [SWI-Prolog](#).
- SWI-Prolog – [Useful material](#).

2 Concepts

- Logic programming
- Predicates
- Clauses
- Facts
- Rules
- Goals
- Variables
- Conjunctions

3 Prolog

- Logic programming: programs = a set of axioms; execution = a constructive proof for a goal.
 - **PRO**gramming in **LOG**ic.
 - Declarative programming - we describe what we want to solve, not how we want to solve (imperative programming).
 - Deal with problems in terms of objects and relations between those objects.
 - Use logic (first order predicate logic)
 - ⇒ We show the relations between the objects using **predicates**.
 - Programming in Prolog = a conversation with the interpreter:

- declare the facts (about the objects and the relations between them), about the facts we know that they are true. If we declare `green(snow)`, the interpreter it will consider true either if it not corresponds to the real world.

Example:

```
mother(john,mary). /* john's mother is mary */

father(john,albert). /* john's father is albert */
```

Or we can **write**:

```
mother(mary,john). /* mary is the mather of john */
```

- define the rules (head and body)

Example:

```
children(john,mary,doru):-
    mother(john,mary),
    father(john,doru).
```

Or:

```
uncle(X,Y):-
    father(Y,X),
    brother(Y,Z),
    mother_in_law(X,Z).
/* X is the uncle of Y if:
the father of Y is X and
the brother of Y is Z and
the mother_in_law of X is Z. */
```

Or:

```
son_in_law(X,Y):-
    father(Z,Y),
    married(X,Z).

son_in_law(X,Y):-
    mother(Z,X),
    married(Y,Z).
```

- ask the interpreter

```
mother(X,mary). /* Who's mother is mary? */

son_in_law(X,X). /* Who is his own son-in-law? */

uncle(john,X). /* Who is the uncle of john? */
```

– $\underbrace{\text{Facts} + \text{Rules}}_{\text{Clauses}} = \text{Database}.$

By defining some facts and some rules we construct (build) a model.

Use:

- [Symbolic computation](#);
- [Artificial intelligence](#);
- [Natural language processing](#), etc.

3.1 Useful commands:

- Ctrl-D or **halt.** – exit the interpreter.
- **help(name-of-the-command).**
- **apropos(keyword).** – displays all the predicates, functions and sections in which exists the keyword.
- **consult(file-name).** or **[file-name].** – for loading the database from a file. Ex: `[problem1].` or `['problem1.pl']`. We can read more files in the same time: `[problem1, problem2, problem3].`
- **listing.** – displays the clauses from the database.
- **listing(predicate).** – displays all the clauses from the database which define the adequate predicate. Similar, but for more predicates in the same time: **listing([pred1, pred2, pred3]).**
- **;** – For obtaining more solutions (if there are more). (repeat the searching in order to obtain other valid solutions).
- **trace.** – Follow interactively each step of the execution.

3.2 Exercises:

1)

```
artist(emerese).  
artist(denis).  
austrian(emerese).
```

```
?-austrian(emerese).  
?-artist(denis).  
?-greek(emerese).
```

2)

```
eats(john, fish).  
eats(john, pizza).  
eats(mary, pie).  
eats(mary, sandwich).  
eats(john, sweets).  
eats(victor, soup).
```

```
?-eats(mary, pie).
?-eats(john, X).
?-eats(X, Y).
?-eats(victor, Z).
```

3) — introduce the database from ex2.

```
?-eats(john, fish), eats(fish, john).

?-eats(john, X), eats(mary, X).

?-eats(john, X), eats(mary, Y).
```

4)

```
male(albert).
male(edward).
female(alice).
female(victoria).
parents(edward, victoria, albert).
parents(alice, victoria, albert).
```

```
sister(X,Y):-
    female(X),
    parents(X,B,F),
    parents(Y,B,F).
```

```
?-sister(alice, edward).
?-sister(alice, X).
?-sister(X,X).
?-sister(X,Y).
```

Modify the database such that if we ask

```
?-sister(X,X).
```

we get 3 solutions: edward, alice, albert.

5)

```
likes(marian, beer).
likes(mariana, sweets).
likes(mariana, champagne).
likes(marian, X) :-
    likes(X, champagne).
likes(mariana, Y):-
    likes(Y, champagne).
```

```
?-likes(marian,mariana).  
?-likes(marian,X).  
?-likes(mariana,X).  
?-likes(X,X).
```

6)

Create a database such that you get solutions for the next questions:

- When has alex the logic-programming course?
- In which day ecaterina has the algorithms course?
- Who has the logic-programming laboratory on monday?
- What courses has alex on wednesday?

Write at least one rule such that you get an answer for:

- Which are the mutual courses of alex and ecaterina?

3.3 Homework: (Deadline: next lab.)

[Homework1](#)